Agentic CV–JD Ranking for Automation Test Roles: Final Report

NLP501 · Group 2 · Sơn (problem and criteria) · Vũ (literature) · Đán (agentic HR, gaps, and the `coding` branch) · Hoa (datasets and metrics) · Thịnh (architecture and experiments)

The official numbers come from **NLP501-bench v1**, the benchmark the team agreed on and froze (`docs/BENCHMARK.md`). Every current number is generated by a command in §11 and can be checked in the `docs/*_RESULTS*.md` file named next to it. Numbers from earlier runs, kept to explain a design change, are marked as such: v2, qwen3:8b, before a fix, or an uncached run.

Abstract

We built an agent that ranks Automation Test Engineer CVs against a job description and explains every rank. We evaluated it against the three questions that matter most for an agentic NLP system:

1. Is it genuinely agentic?
2. Is the data processed well?
3. How is what the LLM produces controlled?

The team froze one benchmark that mixes our 50-CV dataset with Đán's independently built 200-CV dataset: 18 JDs, a locked test split of 10, and every input pinned by checksum. On that test split:

- **The merged system is the best version of the project:** 0.847 nDCG@10 for the full agent and 0.848 for its fixed pipeline. That is ahead of Đán's original core (0.810), our v2 (0.751, p = 0.004 for the deterministic merge) and every retrieval baseline (0.68–0.73). Its lead over Đán's core is not yet significant (p = 0.22–0.27).
- **Rules score; the LLM controls and explains.** The agent and its fixed twin rank alike (0.847 vs 0.848, p = 0.47). The agent's value is the work rules cannot do: asking HR on a vague JD, reading CVs the parser cannot, catching contradicted claims (2.1% → 0.6%) and keeping the arbiter to true near-ties.
- **Where the agent decides, the ranking shows it.** On vague twins of all 18 JDs, a pipeline that cannot ask scores 0.626 nDCG@10. Asking HR recovers 57% of the loss (+0.129, p < 0.001); the agent as it runs scores 0.704 (§5.5).
- **Evaluation found and fixed real faults:**
- a recall funnel sized for 50 CVs that failed at 200 (the agent rose from 0.60 to 0.77–0.78 on those JDs);
- an arbiter acting beyond its mandate;
- a 100% name leak in masking;
- six more defects in data processing.
- **A stronger model needed more control, not less.** When Claude instead of qwen3:8b read the JDs, the LLM-only JD parser fell from 0.884 to 0.842 nDCG@10 on our JDs. The rules-first hybrid parser did not move.
- **Every LLM output passes code checks at run time** (Q1–Q7 of 13 written criteria; the rest are offline evaluations). **The ranking ignores the protected attributes we twinned** (name, gender, age, marital status): no score changed in 6 twin variants × 1,800 (CV, JD) pairs.

1. Introduction

HR teams hiring automation testers must judge three things that keyword ATS cannot see:

- **Depth:** does the candidate run scripts (L1), write them (L2), build a framework (L3) or design test architecture (L4)?
- **Use vs mention:** was a tool used, or only listed?
- **Hedging:** is a mention hedged ("familiar with", "currently learning")?

Keyword matching rewards stuffing. An LLM judge is opaque, position-biased and can invent evidence. We rank with

`Score(CV, JD) = 1[H(c)] × Σ_k w(c, k) · S(c, k)`

where:

- H is a hard knock-out on must-have tools;
- w are per-company-type weights over 8 criteria;
- S are 0–100 criterion scores.

Contributions:

1. A LangGraph agent with 12 nodes and 6 bounded loops:
2. rules set every score;
3. the LLM explains and decides only what rules cannot;
4. humans own the decision.
5. A deterministic, bilingual CV/JD NLP pipeline, measured against another team member's generator truth, real text and counterfactual twins.
6. 13 written criteria for AI output (Q1–Q13), each with a check and a target. Q1–Q7 run on every output at run time, with an action on failure; Q8–Q13 are offline evaluations.
7. **NLP501-bench v1**, the team's frozen benchmark, with a head-to-head of the three versions of the project.
8. The merge of two independently built systems (ours and Đán's `coding` branch) into one.

Research question	Answered in
RQ1 Does structured extraction beat raw-text matching?	§5.1
RQ2 Do HR-configured must-haves and weights fit the company better?	§5.4
RQ3 How much does hybrid retrieval + reranking add over keyword or dense alone?	§5.1
RQ4 What does agentic orchestration add over a fixed pipeline with the same tools?	§3, §5.2, §6
RQ5 Do results and errors differ by JD type and ambiguity?	§5.1, §8

1.1 Related work, and what our measurements say about it

Vũ's literature review (31 papers, in the midterm deck) shaped the design. Each strand below states what we took and what our results add.

- **Dense matching of CVs and jobs.** ConFit v2 (Yu et al., 2025) trains contrastive bi-encoders for resume–job matching. On test-automation CVs, dense retrieval was the weakest of the three

whole-CV baselines on both datasets (all-JD nDCG@10 0.741 / 0.333, against BM25's 0.794 / 0.542). That confirms Resume2Vec (2025), which found that keyword ATS beats embeddings for software testing, where exact tool names decide relevance. Hence the mandatory hybrid retrieval and the cross-encoder.

- **LLM rerankers.** RankGPT (2023) and later listwise LLM rerankers rank with the model itself. We kept the LLM out of the score: the v2 measurement showed it cost 0.033 nDCG@10, and §7 (H2) shows that "LLM only where needed" is already what a well-built fixed pipeline does.
- **Skill normalisation.** Clavié & Soulié (2023) use LLMs as zero-shot ESCO skill matchers. We use a curated gazetteer with canonicalisation at the boundary, and found that the stronger the LLM, the more it over-reads JD requirements (§4). The deterministic parser had to stay in charge.
- **Bias in LM screening.** Wilson & Caliskan (2024) found that LM-based resume retrieval favoured White-associated names in 85.1% of tests and female-associated names in only 11.1%, and NYC Local Law 144 requires bias audits of automated hiring tools. Our response is deletion before indexing, audited by counterfactual twins: no score moved.
- **Agent patterns.** These map onto loops in our graph:
- ReAct (Yao et al., ICLR 2023), reasoning interleaved with tool calls, is the investigator's loop (§3.1).
- Reflexion (Shinn et al., NeurIPS 2023), self-critique and retry, is L4, except that the critique comes from code, not from the model.
- AutoGen (Wu et al., 2023) coordinates several agents. We chose one graph with bounded loops, because every decision point stays testable and measurable.

2. Data, processing and the benchmark

2.1 Data

	ours (`data/`)	coding (Đán's branch, commit `6991c3d`)	real text
Size	50 CVs × 12 JDs	200 CVs × 6 JDs	217 real, anonymised CVs
Built by	hand-written synthetic, designed to stress the pipeline (Vietnamese, long, hedges, title inflation)	template generator with known latent facts; 37% Vietnamese; 7 OCR-garbled CVs; fake PII	datasetmaster/resumes (MIT); its 4,600 Faker-generated CVs excluded
Labels (0–3)	silver: two Claude annotators, κ_w 0.919	rubric gold (`gold_spec`)	none (NLP checks only)

No CV belongs to a real candidate without their consent. We checked every candidate public dataset. None combines real, licensed, *labelled* test-automation CVs (`docs/REALTEXT_RESULTS.md`). Consented CVs from real testers are being collected under `docs/labeling/CONSENT.md`.

2.2 NLP501-bench v1 (`docs/BENCHMARK.md`)

The two datasets were built in parallel, and each defined "relevant" its own way, so each system looked best at home. The team therefore agreed on one benchmark with fixed roles:

	dev (tuning allowed)	test (locked; the official number)
ours	JD-001, 002, 003, 006, 008, 012	JD-004, 005, 007, 009, 010, 011
coding	ambiguous_junior, mobile_offshore	ambiguous_senior, bank_api_qa, fpt_automation_test, startup_framework

How it works: - Each JD ranks the CVs labelled for it. - Our JDs were split by company type with seed 501; Đán's keep the split he pre-registered. - A manifest pins 268 input files by SHA-256 plus the coding commit, and a test fails if any of them changes. - Changes to the system are decided on dev and reported on test.

Disclosure: results on these JDs were seen during development, before the split existed. Of the two fixes in §5.3, the recall channel was motivated by a test-split error and decided on dev. The arbiter fix restores the specified behaviour and was found in a dev-JD trace. Both are re-reported on test.

2.3 Pipeline: raw CV → facts (deterministic, 0 tokens)

The pipeline runs these steps in order:

1. **Normalise:** NFC, bullets, wrapped lines.
2. **Mask** contact details and protected attributes.
3. **Detect** sections and dated roles.
4. **Chunk structurally:** one chunk per role or project, labelled with its section.
5. **Find skill mentions** with the gazetteer, with NegEx-style hedge scope and evidence strength (used / listed / hedged).
6. **Compute years** from merged date ranges.
7. **Estimate automation depth** from the candidate's own action verbs.
8. **Output the `CVProfile`.**

JDs are parsed into must-haves with *one-of* groups, nice-to-haves, years, depth, languages and domains. Every fact keeps the CV line it came from (`docs/NLP_PIPELINE.md`).

Masking is deletion, not instruction. Asking an LLM to "ignore gender" is a hope; deleting it before indexing is a guarantee.

2.4 How well the processing works

Check (source)	Result
Tool extraction vs the coding generator's truth, 200 CVs (`EXTRACTION_RESULTS.md`)	F1 0.978; clean CVs 0.994; OCR-garbled CVs 0.192
Years of experience · automation depth	MAE 0.79 years · 89% exact
Redaction leak, every PII field	0%
Real CVs (217): parsed · prose precision (`REALTEXT_RESULTS.md`)	217/217 · 90%
Counterfactual twins: name / gender / age / marital status (`ROBUSTNESS_RESULTS.md`)	0 score changes in 6 twin variants × 1,800 (CV, JD) pairs
Quality flags on clean CVs	17/193 flagged, all for having no dated roles

The extraction numbers were measured after fixing defects that this same measurement exposed, so they are optimistic for this set. The real-text and twin checks are independent of those fixes.

What measuring found and we fixed. Unit tests had passed on all of these:

1. **The candidate's name leaked in 100% of CVs whose first line is the bare name.** It now leaks in 0%.
2. **A gender value under an OCR-garbled label leaked.**
3. **The garbled-text flag caught 0 of 7 garbled CVs.** It now catches all 7.
4. **Double-spaced CVs lost their role titles,** which inflated one candidate's automation years from 8.0 to 14.8.
5. **"pull requests" counted as the *requests* library,** giving false credit to our own trap CV.
6. **Jira counted as automation work.**
7. **Tool names missing from the gazetteer,** found in the coding set and in real CVs.

Chunking (RQ1). With the cross-encoder, structural chunks are slightly best on both sets (0.829 / 0.628 vs whole CV 0.818 / 0.620, not significant). Without it, whole CVs retrieve best. The large gain is elsewhere: **rule scoring over the parsed profile adds +0.052 / +0.164 nDCG@10 over the same retrieval** (p ≈ 0.001 on ours; positive on all 6 coding JDs; `EVAL_RESULTS*.md`, all JDs).

3. Architecture: where the agent decides

The system is a LangGraph state machine with 12 nodes and 6 bounded loops (`docs/architecture.html`). Its rule: **rules where facts exist, the LLM where judgement or reading is needed, humans where the decision is theirs.**

Loop / node	Decision	Decided by
L1 clarify	pause and ask HR, or proceed	rules first (no must-have tools; title contradicts years), then a typed LLM gate
L2 expand	widen the search; which related tools may substitute	coverage rule proposes, **HR approves** each tool
L6 investigate	which tool to call next on an unreadable CV, and what it shows	**LLM** (typed actions); **code** verifies every claim
L4 verify	retry a review whose quotes or claims fail the checks	code (Q2–Q5)
L3 arbiter	swap a *near-tie* (	Δ
L5 HR review	approve, re-weight, or approve/reject candidates	**HR**; weights re-learned from decisions (pairwise logistic regression, audit log)

Why this is agentic rather than a linear pipeline. The path depends on what the agent observes. Across the 18 benchmark JDs the agent took 8 distinct paths; its fixed twin took 1. The investigator (N12) is a tool-using ReAct loop in the strict sense: the model chooses its next action from what the previous one returned. Code then decides whether the result becomes a fact.

Why the LLM does not score. In v2 the LLM scored 5 of 8 criteria, and the agent then ranked 0.033 below its own deterministic input. Since v3:

- rules set all 8 scores;

- the LLM's judgement is a verified review;
- the agentic parts do what rules cannot: ask, read noisy text, break ties, explain.

4. Controlling what the LLM produces

`docs/AI_OUTPUT_CRITERIA.md` defines 13 criteria. Each has a code check, a target and an action on failure.

	Criterion	Check	Action on failure
Q1	schema-valid output	pydantic	retry, then safe default / needs review
Q2	quotes grounded in the CV	fuzzy span match	L4 retry naming the failing quotes
Q3	quotes support their criterion	right section and entity	labelled "listed, not demonstrated"
Q4	rationales consistent with the parsed CV	no tool or years the CV does not show	L4 retry with the contradiction, then `[unverified]`
Q5	no protected attributes	EN/VI lexicon	sentence removed
Q6	report claims supported per candidate	Q4 + Q5 per candidate, no foreign ids	regenerate once, then drop failing sentences
Q7	arbiter not position-biased, near-ties only	both orders;	Δ
Q8	decisions right	planted scenarios	safe default
Q9	explanation adds up to the score	by construction	—
Q10	ranking agrees with people	benchmark metrics with CIs	not adopted
Q11	ranking ignores protected attributes	counterfactual twins	release blocker
Q12	bounded cost	calls, tokens, latency	loop limits
Q13	an LLM judge is validated before use	κ vs humans	not used as ground truth




Figure 1. The share of LLM outputs failing a check, on the first attempt (hollow) and after the graph's controls acted (filled), across all benchmark JDs. Numbers: the AI-output scorecards in `EVAL_RESULTS*.md`.

Measured on the full agent across the benchmark JDs: - **Q1:** 0 invalid outputs. - **Q2:** 100% of quotes grounded. - **Q4:** contradicted rationales 2.1% → 0.6%, against 2.9% for the fixed pipeline, which has no retry. - **Q6:** report candidates with an unsupported claim 5.9% → 1.2% after one regeneration; those sentences dropped, none reaching HR. - **Q7:** after the |Δ| fix (§5.3), 17 of 17 benchmark near-tie pairs

gave the same verdict in both orders. The JD-003 trace in §6.1 shows the check catching a flip. Before the fix, 90% were stable, when out-of-mandate pairs were also judged. - **Q8 decisions** (`SCENARIO_RESULTS*.md`): - **L1 gate:** in the Claude benchmark runs the agent asked HR on exactly the 3 JDs that need it (JD-003, ambiguous_junior, ambiguous_senior) and on none of the other 15. The planted-scenario suite on qwen3:8b also scored 18/18, there entirely through the rules: qwen listed no ambiguities. - **L6 investigator:** 0 false recoveries in 42 planted cases on qwen3:8b. All misspelt tools were recovered and all negatives kept out, but only 12 of 47 true facts were recovered on heavily garbled CVs. - **Sonnet 5.5 on the same 42 planted cases**, re-run on the current JD requirements: 0 false recoveries and 41/42 correct final statuses. All 4 typos were recovered, but only 6 of 32 true facts on heavily garbled CVs. The two models are not compared case by case, because the requirements changed between the runs. - **Q11 fairness:** no score changed in 6 twin variants × 1,800 (CV, JD) pairs. Religion, ethnicity, nationality and disability are masked but were not twinned.

Three properties make this control rather than hope:

1. **The checks are code,** so they run on every output.
2. **They are measured before and after acting.**
3. **They have regression tests.** Writing the Q2 retry path exposed a silent regression: the retry prompt never told the model what was wrong.

The checks favour precision and are a lower bound on errors; the blind human audit will measure what they miss.

A stronger model needed more control. Claude Sonnet reads JDs more strictly than qwen3:8b:

- it listed 4–7 ambiguities per JD where qwen listed none;
- it gave 5 must-haves for JD-008 where qwen gave 2, turning "Jenkins or GitLab CI" into two hard requirements.

With the LLM-only JD parser, ranking fell **0.884 → 0.842** (ours) and **0.824 → 0.795** (coding), and knock-out misses rose from 9 to 17. The hybrid parser, where the deterministic parser decides and the LLM fills gaps, held at 0.881 / 0.792 under both models. It is the default, chosen by the pre-registered rule.

5. Experiments

Setup: - **LLM:** Claude Sonnet 5.5 (reasoning) and Haiku 5.5 (fast gates), served through the Claude Code CLI as a stand-in for the Anthropic API. - **Reproducibility:** JD requirements are extracted once and shared by every system, LLM responses are cached, and `PYTHONHASHSEED=0` is pinned. - **Statistics:** means over JDs with 95% bootstrap CIs; paired one-sided bootstrap p for "A > B".

5.1 The official benchmark (RQ1, RQ3, RQ5): `docs/BENCHMARK_RESULTS.md`




Figure 2. nDCG@10 on the 10 locked test JDs, mean and 95% CI. Blue marks the merged system.

System	test nDCG@10 (10 JDs)	ours (6)	coding (4)	P@5	dev nDCG@10 (8)
B0 BM25	0.695	0.800	0.536	0.680	—
B2 hybrid (BM25 + dense)	0.681	0.859	0.413	0.600	—
Structural chunks + cross-encoder	0.726	0.830	0.570	0.720	—
Đán's core (coding branch, unchanged)	0.810	0.773	**0.866**	0.800	0.846
Our v2 (4 rule criteria ⊕ CE)	0.751	0.806	0.669	0.700	0.805
Merged v3.1, deterministic (B3)	0.837	0.890	0.758	0.880	0.869
Merged v3.1, fixed pipeline (B4)	**0.848**	0.890	0.784	0.880	0.872
Merged v3.1, full agent (P6)	0.847	**0.897**	0.772	0.880	0.866

Which version is best. The merged system leads overall:

- **Over our v2:** +0.086, p = 0.004.
- **Over Đán's core:** +0.027 (p = 0.27) for the deterministic merge and +0.037 (p = 0.22) for the agent.

So it is the best version measured, but its lead over Đán's core is not yet significant on 10 JDs. **Đán's core still wins on his own JDs:** 0.866 against 0.772 for the merged agent. On ours the merged system leads (0.897), against 0.773 for Đán's core and 0.806 for our v2. The merge combines his 8-axis rules with our NLP and retrieval, which makes it the only version strong on both.

RQ3, retrieval. - Retrieval alone tops out at 0.73. - BM25 beats dense retrieval on template CVs, consistent with Resume2Vec's finding that testing is where keyword search wins. - The cross-encoder over requirement-wise passages is the largest retrieval gain.

RQ1, structure. Structured facts beat text by a wide margin: 0.837 against 0.726 for the best retrieval-only system on test.

RQ5, by JD. The hardest JDs differ by system: - **v2 and the merged systems:** the lowest test JD is `ambiguous_senior`, which has no concrete must-have. - **The retrieval baselines:** `bank_api_qa`. - **Đán's core:** JD-011.

Two failure modes remain (§8): **vague JDs**, and **CVs that describe tools without naming them**. §5.5 and §5.6 test a remedy for each.

5.2 Agent vs fixed pipeline, and ablations (RQ4)

On the 10 test JDs the full agent and its fixed twin rank alike (0.847 vs 0.848, p = 0.47). That is by design: rules set the score in both. Across all 12 of our JDs (`EVAL_RESULTS.md`):

System	nDCG@10	contradicted claims (final)	distinct paths	LLM calls
P6 full agent	0.882	0.9%	5	177
B4 fixed pipeline	0.879	4.0%	1	108
A1 – verify (L4)	0.883	2.8%	3	184
A2 – company profile	0.878	1.3%	5	197
A3 – arbiter (L3)	0.880	0.9%	5	157
A4 – investigator (L6)	0.883	0.9%	5	179

The ablations A1–A4 ran before the two fixes in §5.3. On our 50-CV pool the recall fix moved B4 by −0.002 on the dev JDs, and P6 moved from 0.883 to 0.882 after both fixes, well inside the noise.

What each part adds: - **Verify (L4)** is what removes contradicted claims. - **The arbiter** reorders true near-ties and caught position bias in its verdicts. - **The investigator** costs nothing on clean CVs and is the only part that can rescue a good candidate from noisy text (§6.2). On the benchmark it rescued no CV, and that is mostly right: of the knocked-out CVs its trigger selects, 36 of 37 are graded 0–1. The one miss, `syn_196` on `bank_api_qa` (gold 2), has Java and RestAssured under heavy OCR noise. On 42 planted cases Sonnet made 0 false recoveries (§4). - **The cost of control:** P6 makes 1.6× the LLM calls of B4 on our JDs (177 vs 108) and 3.1× on Đán's (175 vs 57), about 2.1× calls and tokens overall. Latency is not comparable: most runs reused cached responses. The one fully uncached P6 run, an earlier run, took about 80 s per JD through the CLI.

5.3 What the benchmark exposed, and how it was fixed

1. A recall funnel sized for 50 CVs.

- **Symptom:** on Đán's test JDs the agent scored **0.601 (P6) and 0.608 (B4)**, far below its own deterministic core (0.758). On our JDs B4 and B3 are identical.
- **Cause:** search carried the top 40 retrieval hits into screening. That is 80% of our pool but **20%** of a 200-CV pool, and retrieval is weak on template CVs. CVs that belong in the top 10 ended up at ranks 12–99 (P6 on `bank_api_qa` and three other test JDs, before the fix).
- **Fix:** rules cost nothing, so the top 40 CVs **by rule score** now also enter screening (`Settings.rule_recall`).
- **Decision, on dev only:** B4 ours 0.871 → 0.869 (within tolerance), coding 0.857 → 0.880.
- **Re-reported on test:** B4 on Đán's JDs **0.608 → 0.784**; `bank_api_qa` alone 0.43 → 0.84.

2. An arbiter beyond its mandate.

- **Symptom:** a real JD-003 trace showed "Near-tie (Δ = −0.150) resolved by arbiter".

- **Cause:** with fused ordering a neighbour can have the *higher* total, and the check treated every negative gap as a tie, so the LLM lifted a 0.77 candidate over a 0.92 one.
- **Fix:** the check now uses |Δ|, with a test. P6 was re-run.

5.4 Company profiles and the JD parser (RQ2)

Company profiles. Weights differ by company type. Turning the profile off (A2) moved nDCG@10 by −0.004, not significant. The silver labels were written without a company context, so they cannot show a profile effect. That limit is stated in §9; the human labels will help.

HR-taught weights. HR can re-weight in words, or by approving and rejecting candidates. The weights that best explain those decisions are learned by pairwise logistic regression and logged.

The JD parser. The parser choice mattered more than the weights: under Claude, hybrid beat LLM-only by +0.039 on ours and lost by 0.003 on coding (§4).

5.5 Does asking HR help? A controlled test (H6, `docs/CLARIFY_RESULTS.md`)

Only 3 benchmark JDs are vague, too few to test the clarify loop. So each of the 18 JDs got a **vague twin**: tool names replaced by their category ("a browser automation framework"), year counts by "several years". The twin keeps the original labels, which encode what the hiring manager wanted: exactly what HR knows and the vague text no longer says. Every condition is ranked by the agent's own deterministic scorer.

Condition (18 JDs)	nDCG@10	Kendall τ
clear JD (upper bound)	0.851	0.513
vague twin, nobody asks (what a fixed pipeline gets)	0.626	0.451
vague twin, HR asked and answered	0.756	0.507
the agent as it runs (HR's answer only where the gate asked)	**0.704**	0.495

- **Asking helps:** +0.129 nDCG@10 ($p < 0.001$) and +0.056 τ ($p = 0.012$), paired over 18 JDs. That recovers 57% of the loss.
- **The gate asked on 15 of 18 twins.** The 3 it missed still contain "API testing", which the rule counts as a concrete tool. On the clear JDs it asked once without need (`startup_framework`) in this run; in the benchmark runs it asked on none of the 15 clear JDs.
- **Limit:** HR's answer is scripted from the original requirements, so this tests the mechanism (detect → ask → integrate), not a real HR conversation.

5.6 A negative result: tools a CV describes but does not name

- **Problem:** 3 of the agent's 5 misses on ours (§8) are CV-047 and CV-048. They describe "a harness on the WebDriver protocol" or "build servers" instead of naming Selenium or GitLab CI.
- **Change tried:** the investigator may accept such a line as *implied* evidence. The line needs a skill-specific cue, must sit in the experience of a strong CV (depth L3+) and must not be hedged. It earns credit 0.5 instead of 1.0, plus a flag telling HR to verify in interview.
- **Dev result:** CV-047 moved up on three dev JDs (best: rank 40 → 19). The labels agree with each move, but none reached the top 10, so dev nDCG@10 stayed at 0.867. On Đán's dev JDs the cue never fires.
- **Decision (EVAL.md §8):** no gain on either source, so it is **not adopted**. It stays behind `Settings.implied_evidence = False`.

- **A later check, not used for the decision:** on one test JD from Đán's templates, a cue as broad as "CI pipeline" fires on 15 knocked-out CVs, 8 of them graded 0. Describing a tool is weaker evidence than naming it.
- **Kept:** a stricter verify check found along the way. A multi-word name must now match word for word, so "standard WebDriver" no longer counts as naming Selenium WebDriver.

6. Case studies

6.1 A vague JD: the agent stops to ask, and its controls fire

JD-003 asks for "good automation skills" and names no tool. Below is a real run on the final code (Claude), condensed from the agent's own narration (`scripts/smoke.py JD-003`). Nothing has been cut from the decision lines.

```
 [ingest]   Must-have: — · min years: None · depth: L2
[ingest]   Rule: no concrete must-have tools → ask HR (no LLM needed)
HR answers: "3+ years, Selenium or Playwright, English required"
[ingest]   Canonicalized must-have ['selenium', 'playwright'] → ['selenium'] (playwright as
accepted alternative)
[search]   → 43 candidates (3 added by rule score that retrieval missed); knock-out screened
the whole pool: 20 out (4 only hedged)
[investigate] No knock-out looks like a parsing failure → investigator not needed (0 LLM
calls)
[rerank]   kept top 8 for LLM assessment (saves 22 LLM calls)
[assess]   CV-042: LLM says L4 but the CV's own action verbs show at most L2 —
verify_evidence will check
[verify]   88/88 quotes grounded; 1/40 rationales contradict the parsed CV → CV-033 sent
back to assess
[verify]   10/10 grounded; 0/5 contradict
[score]    Data-quality flags on ['CV-047'] … every CV has a status: 8 ranked, 22 not
shortlisted, 20 knocked out
[arbitrate] Near-tie CV-033 / CV-014 (Δ=0.022): the verdict flipped when the order was
swapped (position bias) → rule order kept
[report]   Report ready for top 5 candidates; every claim checked against the CVs
```

What the run shows:

1. **A rule, not the model, decided to ask HR.** There was nothing to rank fairly without a must-have.
2. **HR's "or" was canonicalised into a one-of group.**
3. **The rule channel recovered 3 CVs that retrieval missed.**
4. **The investigator correctly stayed idle.**
5. **An inflated depth claim was flagged against the CV's own verbs, and a contradicted rationale was caught and repaired.**
6. **The arbiter judged only a true near-tie (Δ = 0.022), detected its own position bias, and deferred to the rules.**
7. **Every CV ended with a status and a reason.**

(The run before the near-tie fix also lifted a candidate across a 0.15 gap. That out-of-mandate swap is the fault §5.3 describes.)

6.2 A garbled CV: the investigator reads what the parser cannot

syn_091 is one of Đán's OCR-garbled CVs. The parser finds none of the fpt JD's must-haves, so the CV is knocked out. The deterministic trigger "the text is garbled" starts the investigator. Its real actions (Sonnet 5.5, `SCENARIO_RESULTS_claude-sonnet-5-5.md`):

```
read_section(summary)            → "2 y#%rs%of e@%er%@%~e in softw@re testing."
propose(playwright, quote)       → accepted: playwright (match 0.80)
search(Python)                   → No line resembles 'Python'.
search(API testing)              → "U~ed P@aywrig@t,~Webd#iverIO, Postman,#R~b~% @@amework,
T~stN…"
propose(api_testing, quote)      → accepted: api_testing
```

On another garbled CV (syn_043), the model proposed Python from a line that does not contain it. Code answered `rejected: the quote does not name python (best match 0.50)`, and the knock-out stood. **The model chooses where to look; code decides what becomes a fact.** Across 42 planted cases (qwen3:8b) and 17 (Sonnet 5.5) that rule produced 0 false recoveries.

6.3 What HR sees: an explanation card that adds up

Every ranked CV gets a card computed from the same rules that score it, so the explanation can never disagree with the rank. This one is from JD-010, a Vietnamese bank JD on the test split ("Kỹ sư kiểm thử tự động (Selenium + Java) – Ngân hàng"; must-haves Selenium, Java, RestAssured or Postman). The top candidate, CV-033:

Criterion	weight	score	contribution	evidence (quoted from the CV)
tools	0.20	92	0.184	must-haves 3/3, nice-to-haves 5/6 · "Xây dựng và duy trì framework Selenium + Java + TestNG …"
automation depth	0.20	75	0.150	L3 from the candidate's own verbs (the JD asks L3)
experience	0.10	100	0.100	8.8 years in automation roles (10.8 total), from dated roles
test types	0.10	100	0.100	api + web · "Wrote around 200 RestAssured tests for loan and account APIs …"
CI/CD and infra	0.10	90	0.090	GitLab CI, Docker; Jenkins only listed (0.7)
ISTQB · language · domain	0.10 each	100	0.300	"ISTQB Advanced Test Analyst" · Java · English and banking
total			**0.924**	

Versus the next candidate (CV-001): ahead on domain and language (+0.050) and CI/CD (+0.003), behind on nothing.

For a knocked-out candidate (CV-040): "Missing must-have: Selenium". **What if** Selenium were used? It would pass the knock-out and score 0.855. HR sees exactly how close a rejected candidate was.

7. Hypotheses vs results

The midterm deck stated four quantitative hypotheses before any experiment; the team's final deck adds H6. Here they are, against what we measured.

Hypothesis (midterm)	Predicted	Measured	Verdict
H1: the agent beats the fixed pipeline on ranking	P6 86.8 vs B4 83.2 nDCG@10	test: 0.847 vs 0.848	**Not supported.** Rules score both, so ranking is equal by design. The agent's value moved to control (§4) and to vague JDs (§5.5)
H2: the selective arbiter cuts token cost	−78% tokens; 7.2 s, $0.09 per JD vs 18.4 s, $0.42	P6 uses about 2.1× the calls and tokens of our B4 (1.6× on ours, 3.1× on coding)	**Refuted as stated.** The −78% compared against an LLM that reranks every candidate. Our fixed pipeline already calls the LLM only for a shortlist of 8, so the agent's loops add cost
H3: verification keeps explanations grounded	97.6% grounded (A1 72.2%)	100% grounded with and without verify	**Met, for a different reason.** Claude rarely invents quotes; verify's measurable effect is on contradicted *claims* (2.8% without it vs 0.9% with it)
H4: company profiles align with HR	τ 0.81 vs 0.52 generic	τ 0.554 vs 0.542 (A2)	**Not supported** on labels written without company context
H6 (team deck): asking HR helps on vague JDs	τ improves with clarification	18 vague twins: τ +0.056 ($p = 0.012$), nDCG@10 +0.129 ($p < 0.001$)	**Supported** in a controlled test with scripted HR answers (§5.5)

Of the four midterm hypotheses, three were not supported (one refuted outright) and one was met for a different reason. H6, tested last, is supported. That is a result. They moved the design from "the LLM decides and the agent saves tokens" to "rules decide and the agent controls the LLM".

8. Error analysis (`docs/ERROR_ANALYSIS.md`, test split)

We count only the errors that cost HR something:

- **avoidable misses:** a relevant CV ranked below 10 although every CV graded at least as high fits in the top 10;
- **false alarms:** an irrelevant CV in the top 5.

	ours (6 test JDs)	coding (4 test JDs)
P6 full agent	5 misses, 1 false alarm	5 misses, 1 false alarm
Đán's core	10 misses, 1 false alarm	4 misses, 0 false alarms

Patterns: - **On ours, 3 of the agent's 5 misses are vocabulary failures.** CV-047 and CV-048 are our deliberately plain-language strong CVs: they describe a WebDriver harness and "build servers" or "release gates" without naming Selenium or GitLab CI, and are knocked out on a must-have they effectively have. The other 2 misses are weighting, on the architect JD. - **On Đán's set, every error is on one JD, the vague `ambiguous_senior`:** all 5 misses and the false alarm. Four of the misses are shared with Đán's core, which has no HR step (diagnosis "ISTQB 0, tools 50"), so they come from how the rules and the rubric weigh this vague JD. Only one miss and the false alarm are specific to the agent. - **Two failure modes remain:** vague JDs, and CVs that describe tools without naming them. For vague JDs, asking HR recovers 57% of the loss (§5.5). Accepting described tools as weaker evidence did not

change dev nDCG@10 and was not adopted (§5.6). - **The one false alarm on ours** is a CV whose must-have (Python) is only listed, never used.

9. Limitations and ethics

- **Silver labels.** Our labels come from two Claude models, which agree too readily (κ 0.919). Two teammates are grading a blind 120-pair sample (`docs/labeling/`). If human–silver κ ≥ 0.8 the set stays; otherwise the human labels replace it as benchmark v1.1. A third, blind Claude annotator (recruiter persona, graded from the labelling page's text only) agreed with the silver labels at κ_w 0.889 (`docs/HUMAN_LABELS.md`, reported apart from human rows). The two silver annotators agree with each other at 0.884 on this sample. The silver set is therefore stable within the Claude family; whether people agree is what the human grading will show. Until then, ranking numbers are provisional.
- **Synthetic ranking data.** Real text was used only to check the NLP. Consented real CVs are being collected. Comparisons between systems are the result; the absolute numbers will not transfer.
- **Small test split.** With 10 test JDs, CIs are ±0.05–0.08 for the stronger systems and up to ±0.15 for the baselines. Differences under about 0.03 are not significant, and neither is the 0.037 gap between the agent and Đán's core (p = 0.22).
- **The served LLM.** Claude ran through the Claude Code CLI as a stand-in for an API. Calls, tokens and behaviour carry over; latency and cost do not. The labels and the agent are both Claude, but rules set the score, so this cannot inflate ranking metrics directly.
- **Ethics.**
- Protected attributes are deleted before indexing. The twin test shows the ranking ignores the four we twinned (name, gender, age, marital status).
- The system recommends; HR decides, and every HR decision is logged.
- No real CV is used without consent.

10. Conclusion

An agentic CV ranker earns trust by being agentic where rules cannot reach: asking, reading noisy text and judging true ties. It keeps the score in deterministic rules over well-processed data and checks every LLM output in code. Measured on one frozen benchmark, the merged system is the best version of the project. Its evaluation found faults that unit tests never would.

Next: - human labels (benchmark v1.1); - consented real CVs; - a larger test split, enough to separate the merged system from Đán's core with confidence; - a gate rule that does not count a test type ("API testing") as a concrete tool: the cause of the 3 missed asks in §5.5, to be tuned on dev.

11. Contributions and reproduction

Contributions: - **Sơn:** problem framing, hiring criteria and company profiles. - **Vũ:** literature review (31 papers). - **Đán:** agentic-HR analysis, gaps G1–G5, and the `coding` branch, whose JD parser, 8-axis rules, both-order arbiter, explanation cards, HR calibration and synthetic benchmark were merged. - **Hoa:** datasets, metrics and human validation of the labels. - **Thịnh:** architecture, the agent, the NLP pipeline, the benchmark and the experiments.

```
uv sync && docker compose up -d && (cd backend && uv run python -m app.rag.ingest)
cd backend && export PYTHONHASHSEED=0 LLM_PROVIDER=claude_code
uv run pytest                                       # 123 tests, no LLM or Docker needed
uv run python -m app.eval.benchmark verify          # the frozen benchmark is intact
# full benchmark run: docs/BENCHMARK.md › Reproduce;  official table: python -m
app.eval.benchmark report
uv run python -m app.eval.figures                   # figures in docs/figures/
uv run python -m app.eval.extraction && uv run python -m app.eval.robustness && uv run
python -m app.eval.scenarios
uv run python -m app.eval.errors P6 "Đán core (coding branch)" --bench test
uv run --with markdown python scripts/report_html.py ../docs/FINAL_REPORT.md
/tmp/report.html   # then print to PDF
```