
Notes for Diffusion Model

Jingxuan Zhang

Department of Computer Science and Engineering
East China University of Science and Technology
Shanghai, China
y21220033@mail.ecust.edu.cn

1 DDPM

We first introduce the basic theory of Denoising Diffusion Probabilistic Models (DDPM) [1]. Overall, the DDPM consists of two processes: a forward diffusion process that gradually adds noise to the data, and a reverse denoising process that learns to remove the noise and recover the original data.

1.1 Forward Diffusion Process

The forward diffusion process is defined as a Markov chain that progressively adds Gaussian noise to the data over T time steps. Given a data point \mathbf{x}_0 sampled from the data distribution $q(\mathbf{x}_0)$, the forward process produces a sequence of noisy samples $\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_T$ according to the following transition probabilities:

$$q(\mathbf{x}_t | \mathbf{x}_{t-1}) = \mathcal{N}(\mathbf{x}_t; \sqrt{1 - \beta_t} \mathbf{x}_{t-1}, \beta_t \mathbf{I}), \quad (1)$$

where β_t is a variance schedule that controls the amount of noise added at each time step. The cumulative effect of this process can be expressed as:

$$q(\mathbf{x}_t | \mathbf{x}_0) = \mathcal{N}(\mathbf{x}_t; \sqrt{\bar{\alpha}_t} \mathbf{x}_0, (1 - \bar{\alpha}_t) \mathbf{I}), \quad (2)$$

where $\bar{\alpha}_t = \prod_{s=1}^t (1 - \beta_s)$.

1.2 Reverse Diffusion Process

The reverse process can be shown as:

$$q(\mathbf{x}_{t-1} | \mathbf{x}_t) = \frac{q(\mathbf{x}_t, \mathbf{x}_{t-1})}{q(\mathbf{x}_t)} = \frac{q(\mathbf{x}_t | \mathbf{x}_{t-1}) q(\mathbf{x}_{t-1})}{q(\mathbf{x}_t)} \quad (3)$$

According to Eq. (1) and the definition of the Gaussian distribution, we have:

$$\begin{aligned} q(\mathbf{x}_{t-1} | \mathbf{x}_t, \mathbf{x}_0) &= q(\mathbf{x}_t | \mathbf{x}_{t-1}, \mathbf{x}_0) \frac{q(\mathbf{x}_{t-1} | \mathbf{x}_0)}{q(\mathbf{x}_t | \mathbf{x}_0)} \\ &\propto \exp \left(-\frac{1}{2} \left(\frac{(\mathbf{x}_t - \sqrt{\alpha_t} \mathbf{x}_{t-1})^2}{\beta_t} + \frac{(\mathbf{x}_{t-1} - \sqrt{\bar{\alpha}_{t-1}} \mathbf{x}_0)^2}{1 - \bar{\alpha}_{t-1}} - \frac{(\mathbf{x}_t - \sqrt{\bar{\alpha}_t} \mathbf{x}_0)^2}{1 - \bar{\alpha}_t} \right) \right) \\ &= \exp \left(-\frac{1}{2} \left(\left(\frac{\alpha_t}{\beta_t} + \frac{1}{1 - \bar{\alpha}_{t-1}} \right) \mathbf{x}_{t-1}^2 - \left(\frac{2\sqrt{\alpha_t}}{\beta_t} \mathbf{x}_t + \frac{2\sqrt{\bar{\alpha}_t}}{1 - \bar{\alpha}_t} \mathbf{x}_0 \right) \mathbf{x}_{t-1} + C(\mathbf{x}_t, \mathbf{x}_0) \right) \right) \end{aligned} \quad (4)$$

The reverse diffusion process aims to learn a parameterized model $p_\theta(\mathbf{x}_{t-1} | \mathbf{x}_t)$ that can reverse the forward diffusion process. The reverse process is also defined as a Markov chain, but it starts from pure noise $\mathbf{x}_T \sim \mathcal{N}(0, \mathbf{I})$ and iteratively denoises the samples to recover the original data:

$$p_\theta(\mathbf{x}_{t-1} | \mathbf{x}_t) = \mathcal{N}(\mathbf{x}_{t-1}; \mu_\theta(\mathbf{x}_t, t), \Sigma_\theta(\mathbf{x}_t, t)), \quad (5)$$

where μ_θ and Σ_θ are neural networks that predict the mean and covariance of the reverse transition.

1.3 Training Objective

The training objective of DDPM is to minimize the variational bound on the negative log-likelihood of the data. This can be simplified to a mean squared error loss between the predicted noise and the true noise added during the forward process:

$$L(\theta) = \mathbb{E}_{\mathbf{x}_0, \epsilon, t} [\|\epsilon - \epsilon_\theta(\mathbf{x}_t, t)\|^2], \quad (6)$$

where $\epsilon \sim \mathcal{N}(0, \mathbf{I})$ is the noise added to the data, and ϵ_θ is the neural network that predicts the noise given the noisy sample \mathbf{x}_t and time step t .

References

- [1] J. Ho, A. Jain, and P. Abbeel, “Denoising diffusion probabilistic models,” in *NeurIPS*, 2020, pp. 6840–6851.