

Applications of max-flow

Maximum Flow and Minimum Cut

Max flow and min cut: many applications / reductions.


- Data mining.
- Open-pit mining.
- Project selection.
- Airline scheduling.
- Bipartite matching.
- Baseball elimination.
- Image segmentation.
- Network connectivity.
- Network reliability.
- Distributed computing.
- Egalitarian stable matching.
- Security of statistical data.
- Network intrusion detection.
- Multi-camera scene reconstruction.
- Many many more . . .

7.5 Bipartite Matching

Matching

Matching.


- Input: undirected graph $G = (V, E)$.
- $M \subseteq E$ is a **matching** if each node appears in at most one edge in M .
- Max matching: find a max cardinality matching.



Bipartite Matching

Bipartite matching.

- Input: undirected, **bipartite** graph $G = (L \cup R, E)$.
- $M \subseteq E$ is a **matching** if each node appears in at most one edge in M .
- Max matching: find a max cardinality matching.




matching
1-2', 3-1', 4-5'

Bipartite Matching

Bipartite matching.

- Input: undirected, **bipartite** graph $G = (L \cup R, E)$.
- $M \subseteq E$ is a **matching** if each node appears in at most one edge in M .
- Max matching: find a max cardinality matching.




max matching
1-1', 2-2', 3-3' 4-4'

Bipartite Matching

Max flow formulation.

- Create digraph $G' = (L \cup R \cup \{s, t\}, E')$.
- Direct all edges from L to R , and assign infinite (or unit) capacity.
- Add source s , and unit capacity edges from s to each node in L .
- Add sink t , and unit capacity edges from each node in R to t .




Bipartite Matching: Proof of Correctness

Theorem. Max cardinality matching in G = value of max flow in G' .

Pf. \leq

- Given max matching M of cardinality k .
- Consider flow f that sends 1 unit along each of k paths.
- f is a flow, and has cardinality k . ▪





Bipartite Matching: Proof of Correctness

Theorem. Max cardinality matching in G = value of max flow in G' .

Pf. \geq

- Let f be a max flow in G' of value k .
- Integrality theorem \Rightarrow k is integral and can assume f is 0-1.
- Consider M = set of edges from L to R with $f(e) = 1$.
 - each node in L and R participates in at most one edge in M
 - $|M| = k$: consider cut $(L \cup s, R \cup t)$ ▪



Perfect Matching

Def. A matching $M \subseteq E$ is **perfect** if each node appears in exactly one edge in M .

Q. When does a bipartite graph have a perfect matching?

Structure of bipartite graphs with perfect matchings.


- Clearly we must have $|L| = |R|$.
- What other conditions are necessary?
- What conditions are sufficient?

Perfect Matching

Notation. Let S be a subset of nodes, and let $N(S)$ be the set of nodes adjacent to nodes in S .

Observation. If a bipartite graph $G = (L \cup R, E)$, has a perfect matching, then $|N(S)| \geq |S|$ for all subsets $S \subseteq L$.

Pf. Each node in S has to be matched to a different node in $N(S)$.



No perfect matching:


$S = \{ 2, 4, 5 \}$

$N(S) = \{ 2', 5' \}$.

Marriage Theorem

Marriage Theorem. [Frobenius 1917, Hall 1935] Let $G = (L \cup R, E)$ be a bipartite graph with $|L| = |R|$. Then, G has a perfect matching iff $|N(S)| \geq |S|$ for all subsets $S \subseteq L$.

Pf. \Rightarrow This was the previous observation.



No perfect matching:

$S = \{ 2, 4, 5 \}$

$N(S) = \{ 2', 5' \}$.

Proof of Marriage Theorem

Marriage Theorem. G has a perfect matching iff $|N(S)| \geq |S|$ for all subsets $S \subseteq L$.


Pf. \Leftarrow Suppose G does not have a perfect matching.

- Formulate as a max flow problem and let (A, B) be min cut in G' .
- Define $L_A = L \cap A$, $L_B = L \cap B$, $R_A = R \cap A$, $R_B = R \cap B$.
- $\text{cap}(A, B) = v(f^*) = |M| < |L|$ (" $<$ ": because no perfect matching)
- Since min cut can't use ∞ edges, no edge between L_A and R_B
 - $\text{cap}(A, B) = |L_B| + |R_A|$
 - $N(L_A) \subseteq R_A$.
- $|N(L_A)| \leq |R_A|$

$$= \text{cap}(A, B) - |L_B|$$

$$< |L| - |L_B|$$

$$= |L_A|.$$
- This contradicts the condition.



Bipartite Matching: Running Time

Which max flow algorithm to use for bipartite matching?

- Generic augmenting path: $O(m \text{ val}(f^*)) = O(mn)$.
- Capacity scaling: $O(m^2 \log C) = O(m^2)$.
- Shortest augmenting path: $O(m n^{1/2})$.

Non-bipartite matching.

- Structure of non-bipartite graphs is more complicated, but well-understood. [Tutte-Berge, Edmonds-Galai]
- Blossom algorithm: $O(n^4)$. [Edmonds 1965]
- Best known: $O(m n^{1/2})$. [Micali-Vazirani 1980]


7.6 Disjoint Paths

Edge Disjoint Paths

Disjoint path problem. Given a digraph $G = (V, E)$ and two nodes s and t , find the max number of edge-disjoint s - t paths.

Def. Two paths are **edge-disjoint** if they have no edge in common.

Ex: communication networks.




Edge Disjoint Paths

Disjoint path problem. Given a digraph $G = (V, E)$ and two nodes s and t , find the max number of edge-disjoint s - t paths.


Def. Two paths are **edge-disjoint** if they have no edge in common.

Ex: communication networks.



Edge Disjoint Paths

Max flow formulation: assign unit capacity to every edge.



Theorem. Max number edge-disjoint s-t paths equals max flow value.

Edge Disjoint Paths

Theorem. Max number edge-disjoint s-t paths equals max flow value.

Pf. \leq

- Suppose there are k edge-disjoint paths P_1, \dots, P_k .
- Set $f(e) = 1$ if e participates in some path P_i ; else set $f(e) = 0$.
- Since paths are edge-disjoint, f is a flow of value k . ▪

Edge Disjoint Paths

Theorem. Max number edge-disjoint s-t paths equals max flow value.

Pf. \geq


- Suppose max flow value is k .
- Integrality theorem \Rightarrow there exists 0-1 flow f of value k .
- Consider edge (s, u) with $f(s, u) = 1$.
 - by conservation, there exists an edge (u, v) with $f(u, v) = 1$
 - continue until reach t , always choosing a new edge
 - So we get a s-t path
- Reduce the flow to 0 along the path, so we get a flow of value $k-1$
- Repeat the process for k times, then we get k (not necessarily simple) edge-disjoint paths. ▪

↖ can eliminate cycles to get simple paths if desired

Network Connectivity

Network connectivity. Given a digraph $G = (V, E)$ and two nodes s and t , find min number of edges whose removal disconnects t from s .

Def. A set of edges $F \subseteq E$ **disconnects t from s** if all s - t paths uses at least on edge in F .





Edge Disjoint Paths and Network Connectivity

Theorem. [Menger 1927] The max number of edge-disjoint s - t paths is equal to the min number of edges whose removal disconnects t from s .

Pf. \leq

- Suppose the removal of $F \subseteq E$ disconnects t from s , and $|F| = k$.
- All s - t paths use at least one edge of F . Hence, the number of edge-disjoint paths is at most k . ▪





Disjoint Paths and Network Connectivity

Theorem. [Menger 1927] The max number of edge-disjoint s - t paths is equal to the min number of edges whose removal disconnects t from s .

Pf. \geq

- Suppose max number of edge-disjoint paths is k .
- Then max flow value is k .
- Max-flow min-cut \Rightarrow cut (A, B) of capacity k .
- Let F be set of edges going from A to B .
- $|F| = k$ and disconnects t from s . ▪



7.7 Extensions to Max Flow

Circulation with Demands

Circulation with demands.

- Directed graph $G = (V, E)$.
- Edge capacities $c(e)$, $e \in E$.
- Node supply and demands $d(v)$, $v \in V$.

↑
demand if $d(v) > 0$; supply if $d(v) < 0$; transshipment if $d(v) = 0$

Def. A **circulation** is a function that satisfies:

- For each $e \in E$: $0 \leq f(e) \leq c(e)$ (capacity)
- For each $v \in V$: $\sum_{e \text{ in to } v} f(e) - \sum_{e \text{ out of } v} f(e) = d(v)$ (conservation)


Circulation problem: given (V, E, c, d) , does there exist a circulation?

Circulation with Demands

Necessary condition: sum of supplies = sum of demands.


$$\sum_{v: d(v) > 0} d(v) = \sum_{v: d(v) < 0} -d(v) =: D$$

Pf. Sum conservation constraints for every demand node v .



Circulation with Demands


Max flow formulation.



Circulation with Demands

Max flow formulation.

- Add new source s and sink t .
- For each v with $d(v) < 0$, add edge (s, v) with capacity $-d(v)$.
- For each v with $d(v) > 0$, add edge (v, t) with capacity $d(v)$.
- Claim: G has circulation iff G' has max flow of value D .



Circulation with Demands

Integrality theorem. If all capacities and demands are integers, and there exists a circulation, then there exists one that is integer-valued.

Pf. Follows from max flow formulation and integrality theorem for max flow.

Characterization. Given (V, E, c, d) , there does **not** exist a circulation iff there exists a node partition (A, B) such that $\sum_{v \in B} d_v > \text{cap}(A, B)$

Pf idea. Look at min cut in G' .

↑
demand by nodes in B exceeds supply
of nodes in B plus max capacity of
edges going from A to B

Circulation with Demands and Lower Bounds

Feasible circulation.

- Directed graph $G = (V, E)$.
- Edge capacities $c(e)$ and **lower bounds** $\ell(e)$, $e \in E$.
- Node supply and demands $d(v)$, $v \in V$.

Def. A **circulation** is a function that satisfies:

- For each $e \in E$: $\ell(e) \leq f(e) \leq c(e)$ (capacity)
- For each $v \in V$: $\sum_{e \text{ in to } v} f(e) - \sum_{e \text{ out of } v} f(e) = d(v)$ (conservation)

Circulation problem with lower bounds. Given (V, E, ℓ, c, d) , does there exists a circulation?

Circulation with Demands and Lower Bounds

Idea. Model lower bounds with demands.

- Send $\ell(e)$ units of flow along edge e .
- Update demands of both endpoints.



Theorem. There exists a circulation in G iff there exists a circulation in G' . If all demands, capacities, and lower bounds in G are integers, then there is a circulation in G that is integer-valued.

Pf sketch. $f(e)$ is a circulation in G iff $f'(e) = f(e) - \ell(e)$ is a circulation in G' .

7.8 Survey Design

Survey Design

Survey design.


- Design survey asking n_1 consumers about n_2 products.
- Can only survey consumer i about a product j if they own it.
- Ask consumer i between c_i and c_i' questions.
- Ask between p_j and p_j' consumers about product j .

Goal. Design a survey that meets these specs, if possible.

Survey Design

Algorithm. Formulate as a flow-network?


- Include an edge (i, j) if customer own product i .
- Goal: find a flow that satisfies edge upper&lower bounds. How?



Survey Design

Algorithm. Formulate as a circulation problem with lower bounds.

- Include an edge (i, j) if customer own product i .
- Integer circulation \Leftrightarrow feasible survey design.



7.10 Image Segmentation

Image Segmentation

Image segmentation.

- Central problem in image processing.
- Divide image into coherent regions.


Ex: Two people standing in front of complex background scene.
Identify each person as a coherent object.



Image Segmentation

Foreground / background segmentation.

- Label each pixel in picture as belonging to foreground or background.
- V = set of pixels, E = pairs of neighboring pixels.
- $a_i \geq 0$ is likelihood pixel i in foreground.
- $b_i \geq 0$ is likelihood pixel i in background.
- $p_{ij} \geq 0$ is separation penalty for labeling one of i and j as foreground, and the other as background.



Goals.

- Accuracy: if $a_i > b_i$ in isolation, prefer to label i in foreground.
- Smoothness: if many neighbors of i are labeled foreground, we should be inclined to label i as foreground.

- Find partition (A, B) that maximizes:

$$\sum_{i \in A} a_i + \sum_{j \in B} b_j - \sum_{\substack{(i,j) \in E \\ |A \cap \{i,j\}| = 1}} p_{ij}$$

\nearrow
foreground

\nwarrow
background

Image Segmentation

Formulate as min cut problem.

- Maximization.
- No source or sink.
- Undirected graph.

Turn into minimization problem.

- Maximizing
$$\sum_{i \in A} a_i + \sum_{j \in B} b_j - \sum_{\substack{(i,j) \in E \\ |A \cap \{i,j\}| = 1}} p_{ij}$$


is equivalent to minimizing
$$\underbrace{\left(\sum_{i \in V} a_i + \sum_{j \in V} b_j \right)}_{\text{a constant}} - \sum_{i \in A} a_i - \sum_{j \in B} b_j + \sum_{\substack{(i,j) \in E \\ |A \cap \{i,j\}| = 1}} p_{ij}$$

- or alternatively
$$\sum_{j \in B} a_j + \sum_{i \in A} b_i + \sum_{\substack{(i,j) \in E \\ |A \cap \{i,j\}| = 1}} p_{ij}$$

Image Segmentation

Formulate as min cut problem.

- $G' = (V', E')$.
- Add source to correspond to foreground;
add sink to correspond to background
- Use two anti-parallel edges instead of
undirected edge.



G'




Image Segmentation


Consider min cut (A, B) in G' .

- A = foreground.

$$cap(A, B) = \sum_{j \in B} a_j + \sum_{i \in A} b_i + \sum_{\substack{(i,j) \in E \\ i \in A, j \in B}} p_{ij}$$

if i and j on different sides,
 p_{ij} counted exactly once

- Precisely the quantity we want to minimize.



7.11 Project Selection

Project Selection

Projects with prerequisites.

can be positive or negative




- Set P of possible projects. Project v has associated revenue p_v .
 - some projects generate money: create e-commerce interface, design web page
 - others cost money: upgrade computers, get site license
- Set of prerequisites E . If $(v, w) \in E$, can't do project v unless also do project w .
- A subset of projects $A \subseteq P$ is **feasible** if the prerequisite of every project in A also belongs to A .

Project selection. Choose a feasible subset of projects to maximize revenue.


Project Selection: Prerequisite Graph

Prerequisite graph.

- Include an edge from v to w if can't do v without also doing w .
- $\{v, w, x\}$ is feasible subset of projects.
- $\{v, x\}$ is infeasible subset of projects.



feasible




infeasible

Project Selection: Min Cut Formulation

Min cut formulation.

- Assign capacity ∞ to all prerequisite edges.
- Add edge (s, v) with capacity p_v if $p_v > 0$.
- Add edge (v, t) with capacity $-p_v$ if $p_v < 0$.
- For notational convenience, define $p_s = p_t = 0$.




Project Selection: Min Cut Formulation

Claim. (A, B) is min cut iff $A - \{s\}$ is optimal set of projects.

- Infinite capacity edges ensure $A - \{s\}$ is feasible.

- Max revenue because:

$$\begin{aligned} \text{cap}(A, B) &= \sum_{v \in B: p_v > 0} p_v + \sum_{v \in A: p_v < 0} (-p_v) \\ &= \sum_{v \in B: p_v > 0} p_v + \sum_{v \in A: p_v > 0} p_v - \sum_{v \in A: p_v > 0} p_v + \sum_{v \in A: p_v < 0} (-p_v) \\ &= \underbrace{\sum_{v: p_v > 0} p_v}_{\text{constant}} - \sum_{v \in A} p_v \end{aligned}$$



Open Pit Mining

Open-pit mining. (studied since early 1960s)

- Blocks of earth are extracted from surface to retrieve ore.
- Each block v has net value $p_v = \text{value of ore} - \text{processing cost}$.
- Can't remove block v before w or x .

