CL-TAV: Closed-Loop Test–Analysis Verification for ARINC 615A Data Loading under Timing Uncertainty

Author Name *Membership pending*

***Abstract*— Airborne software loading is judged from protocol events whose identity, ordering and timing may be only conservatively observed. This paper specifies Closed-Loop Test–Analysis Verification (CL-TAV) for ARINC 615A: a charged session that predicts observation classes, interprets a raw record under one uncertainty reference, updates a finite single-fault candidate set from the whole compatible history, and selects one exclusive TEST, Prep, Recover or Admit action. The contribution sought is deliberately bounded. C1 is consistency and conditional true-hypothesis retention under the declared model, ownership and conservative-observation assumptions, not a new general theorem for loss, drift or reordering. C2 is a prior-free one-step minimax choice over currently feasible and affordable tests with explicit error and stop semantics, not a globally optimal policy. The bound protocol model remains UPLOAD and INFORMATION; ARINC 645 identity is bound for triggered leaves, while runtime integrity remains unestablished. Four comparison arms and three experiment families are registered. Confirmatory measurements are not yet available, so no improvement, implementation-completeness or certification claim is made.**

***Index Terms*— Avionics, data loading, conformance testing, fault diagnosis, timing uncertainty, closed-loop verification.**

I. Introduction

Airborne software loaders exchange INFORMATION and UPLOAD traffic under declared timers, file identities and operator actions [1]. Loading frameworks also treat identity, integrity, interrupted loading and version conflict as connected engineering concerns [2]. A missed or late acknowledgement, a mismatched Load File, or an unresolved integrity check can therefore be product behaviour, a capture or clock limitation, a configuration discrepancy, or an unconfirmed injection. The engineering problem is not merely to collect more tests, but to decide whether the current evidence is usable and which later protocol-legal action is worth its finite resource.

This paper studies Closed-Loop Test–Analysis Verification (CL-TAV). Three reader questions are used throughout:

- CL-RQ1 (loop consistency): do prediction, interpretation and candidate update stay mutually consistent under one uncertainty reference?
- CL-RQ2 (comparative effect): under the same budget and denominators, does the closed loop change detection or isolation relative to Test-only, Analysis-only and fixed Test-then-Analysis arms?
- CL-RQ3 (uncertainty and stopping): how do interval timing, `ERROR`, Prep/Recover and exclusive stops affect those comparisons?

Two propositions are evaluated, not asserted as established results. C1 is mutual consistency of uncertainty-aware interpretation, timing verdict and whole-history compatible update in the declared finite domain; its retention statement is conditional on model, ownership, pairing and conservative observation assumptions. C2 feeds residual ambiguity into a prior-free, one-step worst-case candidate-set choice among feasible affordable tests, with explicit Prep/Recover, `ERROR`, resource and stop rules. C2 is not a global multi-step optimum and need not shrink the candidate set on every outcome.

Requirements-based generation, conformance testing and mutation adequacy supply important test-construction and evaluation tools [3]–[6]. Active diagnosis already closes observation–control loops, while real-time diagnosis and testing already address uncertain communication timing [7]–[11]. The narrower question here is whether the declared 615A action, observation, cost and stop contracts form a useful and empirically defensible combination. Section II therefore compares stated objects and assumptions; it does not infer novelty from different terminology or prove that another method cannot be extended.

The evaluation uses four arms (CL-T, CL-A, CL-TA, CL-LOOP) and three registered families (DETECT, LOCATE, ABLATION). Confirmatory numbers are not available.

Placeholder PH-ABS-RESULT
(EXPERIMENT-RESULT)

Abstract and conclusion improvement statements remain empty until registered runs exist.

Data are not obtained. This box reserves layout. It is not a result.

Section II defines the objects. Section III separates CRS layers and the two machines. Section IV gives the loop, update and T5 mathematics. Section V freezes the comparison contract. Sections VI–VIII reserve results and limits. The separately compiled supplement typesets wrappers ALG-CLTAV-02/03/04, core mechanisms 05/06/07, typed records and the A/P decision tables. Paper Algorithm numbers are display labels; stable ALG-IDs are unchanged.

0018-9251 © IEEE

II. Related Work and Problem Formulation

A. Evidence-bounded comparison

Table I organizes the closest evidence by problem strand rather than by paper. It records the compared object and the boundary that prevents a category-level novelty claim.

TABLE I
Closest evidence strands and the resulting CL-TAV boundary.

Strand	Existing object	Boundary used here
Uncertain history	compatible-run diagnosis under latency, drift/offset and reordered observation; exact and bounded-history variants [10]; delay-aware monitoring/testing [11]	C1 is conditional project consistency, not the invention of uncertainty-aware history diagnosis
Active choice	closed-loop supervisors, conditional plans and time-interval control [7]–[9], [12]	C2 is one-step residual-set selection with a different action, cost and stop contract, not the first active loop
Aviation loading	onboard diagnostic procedures and avionics MBT [13]–[15]; proposed LAS requirements/procedures [2]	engineering context, not executed 615A conformance evidence
Evaluation	mutation denominators and equivalent/undecided mutants [5], [16]; randomized-algorithm reporting [17]	informs accounting and registration, not CL-TAV performance

Köhl and Hermanns are the strongest C1 neighbour found. Their passive diagnoser ranges over runs compatible with the whole timed observation history under bounded action-specific latency and a clock remapping, including latency-induced reordering [10]. Their exact incremental algorithm is separated from a sound but generally incomplete fixed-history approximation. CL-TAV therefore does not claim history compatibility or uncertainty handling as new, does not call their "active prefixes" active tests, and does not inherit exact-once observation or their liveness assumption. Fränzle *et al.* likewise give exact delay/jitter-aware monitoring and testing semantics, but testing there is harness input plus verdict evaluation rather than adaptive next-action optimization [11].

Active diagnosis has long combined online state estimation with controlled behaviour [7]. Conditional action plans, state-conditioned event disablement and time-interval restrictions further establish feedback and active choice as prior art [8], [9], [12]. Some objectives use costs or probabilistic information. CL-TAV instead fixes the current finite feasible set and ranks an affordable distinguishing TEST by the one-step worst residual cardinality, then cost and identifier. The lack of a default prior is a design choice, not an automatic advantage; Prep/Recover and exclusive error/stop semantics are compared as engineering contract differences, not proof of first combination or global optimality.

For the application bridge, onboard active diagnosis demonstrates procedure generation and also reports wrong localization under limited observability and model/prototype mismatch [13]. IMA and cockpit-display work demonstrate configuration-aware, model-derived avionics testing [14], [15]. F-LAS proposes 23 reusable requirements and six procedures across normal, interrupted/incomplete and version-conflict scenarios, but reports neither procedure execution nor an ARINC 615A conformance result [2]. These sources motivate cases and threats; the standard and the controlled CRS remain the protocol authority. All comparisons above are bound to the full-text versions recorded in the evidence ledger; no absence claim is inferred from an unreported feature.

B. Verification objects

The IUT is a 615A data-loading endpoint. The bound protocol model is UPLOAD and INFORMATION [1]. FIND, DOWNLOAD and conditional AFDX appear in the CRS; they are not implemented behaviour and not an experimental arm.

Candidates are $H_0 = \{h_{\text{normal}}\} \cup H_{\text{single}}$. An observable summary q is known or unknown. Observation classes are projected onto current H. Measurement uncertainty is a declared conservative outer set U in the GUM sense [18], [19], not an estimated physical error model. Resource is exactly one mode: BUDGET$(c_{\min}, B)$ or ROUNDS$(K_{\max})$.

A 615A-triggered 645 bind covers CRC, check-value and naming leaves [20]. Integrity capabilities remain unestablished. Stop-645 names a remaining 645-dependent obligation, not a missing file.

III. System Engineering and Verification Architecture

Protocol CRS, tool requirements and experiment requirements stay in separate layers. Row count does not prove a method. A concrete owned trace is source unit `SU-ARINC-615A-3-SECTION-6-3-2-SEQUENCE-CHART-A-E007-7726A816FFE7` → CRS-M1-00365/00366/00367 → LUR write-order constraint → planned Test/Analysis verification case → later tool module. The IDs are real bound-M1 identifiers. `satisfy/verify` in the SysML view are model relations, not executed verification. No standard figure is reprinted.

The layering responds to two aviation lessons without importing their authority. F-LAS shows the usefulness of explicit requirements-to-procedure traceability for loading identity, integrity, interrupted loading and version conflict, but its procedures were proposed rather than executed [2]. Avionics MBT also makes configuration, model preparation, simulator and oracle boundaries part of the test problem [14], [15]. Accordingly, the CRS constrains legal protocol evidence, the tool realizes method contracts, and

the evaluator owns independent truth; none can silently stand in for another.

Two machines must not be merged. M_{sess} selects from $S \subseteq A(q)$, charges once, updates H and returns a named stop. M_{prot} is the UPLOAD/INFORMATION black box. Execute issues a stimulus and obtains a raw execution record. Interpretation, not the network port, produces the compatible class I_z and hypothesis survivors.




Fig. 1. Context derived from FIG-CL-TAV-01/07. Stimulus and raw records share ports. Truth enters only the evaluator filter, never select, predict, history or execute.

Expanded CRS leaves do not add FIND or DOWNLOAD transitions to M_{prot}. The development contract now binds eight algorithm interfaces and seven experiment interfaces to typed inputs, outputs, ownership, failure, resource, acceptance, and successor implementation locations. The first slice also preserves six CRC-bearing protocol obligations and their ARINC 645 parameter leaves. The six contracts remain distinct: INFORMATION and UPLOAD receiver support, final-image/LSP check value, optional old/new-file comparison, equal CRC values for two distinct files sharing one part number, and status-file continuation after the final DATA while integrity calculation remains in progress. This closes their specification dependency only: the runtime integrity capability remains *not established* until implementation, project configuration, controlled-vector execution, and an independent gate record exist. Missing evidence therefore yields `NOT-EVALUATED`, not a protocol verdict.

IV. CL-TAV Method

A. Notation and assumptions

S0–S10 are logical duties, not line numbers. The decision index k, the billed charge count and the retry counter are distinct. SessionContext Γ is the unique session state. HistoryHandle η carries whole-history compatibility. The select-time snapshot ξ freezes `actionId`, `actionKind`, q_{used}, history version, classes used at select, and uncertainty reference U. A later confirmed successor summary is a different field. Effect classes are `CONFIRMED-NOT-SENT` and `UNKNOWN-EFFECT`. PredictionGapError is TEST-scoped.

B. Overall closed loop

Algorithm 1 is a typed abstraction of ALG-CLTAV-01. Wrappers PREDICTCURRENT, INTERPRETOUTCOME and RESOLVEOUTCOME are ALG-CLTAV-02/03/04 in the supplement. S9 calls COMMITCOMPATIBLEUPDATE (ALG-CLTAV-07), with $\chi = (\Gamma, \eta, H)$, which validates the history version, applies `IF-HIST-UPDATE` from ξ, returns $(\textit{status}, \eta, H, \Gamma)$ and commits a confirmed successor summary. A bare `IF-HIST-UPDATE` call is not that wrapper. Resolution is branched on $\delta.\text{control}$ after adopting $\delta.\Gamma$, $\delta.\eta$ and $\delta.\text{outcome}$.

C. Interpretation, compatibility and selection

Prediction and interpretation share U. Let $O(h, t, q)$ be the conservative outer set of feasible observations of hypothesis h, and let Z_k be the measured feasible-observation set after timing, ownership and pairing checks. The interpretation/whole-history bridge induces the compatible hypothesis class C_k (the accepted interface field $z.I_z$); C_k is not a measurement set. A currently valid class is the nonempty projection $H \cap C_k$. Compatible update on a valid class is

$$H_{k+1} = H_k \cap C_k, \qquad H_{k+1} \subseteq H_k. \tag{1}$$

`ERROR` and identity Prep/Recover leave H unchanged. The one-step score on currently valid nonempty classes of an affordable distinguishing TEST t is

$$s(t) = \max_{C \in \mathcal{C}_t} |C|. \tag{2}$$

Empty S is never $\arg\min$. Timing uses T5 [19]: $I_{\text{obs}} \subseteq I_r$ is PASS; $I_{\text{obs}} \cap I_r = \varnothing$ is FAIL; otherwise INCONCLUSIVE. An ambiguous pair is `ERROR`, not IUT FAIL.

D. Bounded reference-kernel contract

The first implementation target is a finite explicit-path kernel, not a general solver. Each frontier entry contains a stable hypothesis ID, control state, canonical exact-rational difference constraints, finite typed store, path length, whole-history provenance, and a known/conservative-unknown status. It accepts only TRUE, conjunction, state equality, typed-field equality and rational interval guards, with simultaneous finite assignment and exact zero-clock-reset updates. OR, NOT and calls are outside this first domain and are rejected as SPEC-ERROR before expansion; no normalization is left to an implementer. The sole normative numeric form is a numerator and strictly positive denominator pair; interval bounds carry explicit open/closed flags, and any fraction printed in a review view is display-only. A typed adapter either maps the supported M2 subset into this AST or rejects the model before expansion, so M2 expressions are not a second authoritative encoding. Propagation validates

Algorithm 1: CL-TAV top-level session (paper Alg. 1 = ALG-CLTAV-01)

Require: $H_0 = \{h_{\text{normal}}\} \cup H_{\text{single}}$; Γ; η; one mode BUDGET($c_{\min}, B$) xor ROUNDS($K_{\max}$); L; U
Ensure: stop class, final H, η, trace; singleton h_{normal} is not protocol PASS

$(\Gamma, \eta, H) \leftarrow$ INITIALIZE($H_0, L, U,$ resourcePolicy);
while *true* **do**
  stop $\leftarrow$ IF-RESOURCE-STOP(Γ, H, η) with IF-EQUIV(Γ, H, η);
  if *stop* $\neq$ *undecided* **then return** FINISH(*stop*, Γ, η, H);
  pred $\leftarrow$ PREDICTCURRENT(Γ, η, H, U, L);
  dec $\leftarrow$ SELECTANDADMIT($\Gamma, \eta, H, L,$ *pred*);
  if *dec*.kind $\in$ {*EXIT*, *SPEC-ERROR*} **then return** FINISH(*dec*.reason, Γ, η, H);
  $\xi \leftarrow$ SELECTSNAPSHOT(*dec*; Γ, η, U);
  $\xi = (\text{id}, \text{kind}, q_{\text{used}}, v_\eta, C, U)$;
  kind $= \xi$.actionKind;
  $C = \xi$.classesUsedAtSelect;
  $\Gamma \leftarrow$ CHARGEONCE(Γ, ξ); *er* $\leftarrow$ IF-EXECUTE-RECORD(Γ, ξ);
  $z \leftarrow$ INTERPRETOUTCOME(*er*, ξ, Γ, η, U);
  $\delta \leftarrow$ RESOLVEOUTCOME(z, ξ, Γ, η);
  $\Gamma \leftarrow \delta.\Gamma$; $\eta \leftarrow \delta.\eta$; $z \leftarrow \delta$.outcome;
  if δ.control $=$ *STOP* **then return** FINISH(δ.reason, Γ, η, H);
  if δ.control $=$ *RETRY* **then continue** to S1 with adopted Γ, η;
  if $z.I_z$ *valid or* z.summaryConfirmed **then**
    upd $\leftarrow$ COMMITCOMPATIBLEUPDATE($\xi, z; \chi$);
    (*status*, η, H, Γ) $\leftarrow$ *upd*;
    if *status* $=$ *SPEC-ERROR* **then return** Stop-SpecError;
  end
  stop $\leftarrow$ IF-RESOURCE-STOP(Γ, H, η) with IF-EQUIV(Γ, H, η);
  if *stop* $\neq$ *undecided* **then return** FINISH(*stop*, Γ, η, H);
end

the select-time snapshot, expands enabled transitions, intersects observation and timing constraints, and retains every feasible successor. Entries merge only when hypothesis, control state, clock constraint, store and history provenance are identical.

Configured bounds cover hypotheses, actions, observation classes, path length and per-hypothesis frontier size. Unsupported syntax or an exhausted path or frontier bound returns the interface's named GAP, SPEC-ERROR, or conservative unknown result without deleting a hypothesis. Only prediction, selection, history update, equivalence and stop selection consume kernel results; execute, interpretation and Prep/Recover do not. Feasibility alone never establishes equivalence. Unsupported syntax, computation unknown and limits preserve (H), the summary and charge state. Stop-Empty requires an empty history proved by complete in-domain intersection. This contract maps every reachable result and marks every other interface/result pair unreachable; it does not claim completeness, polynomial complexity, or deployed code.

This contract is intentionally weaker than a universal uncertain-observation diagnosis theorem. Existing work already supplies possible-run semantics and an exact incremental passive diagnoser for bounded latency, drift/offset and out-of-order observation under exact-once and timed-automaton assumptions [10], as well as exact monitoring/testing for a different bounded communication-delay model [11]. CL-TAV claims only the consistency and retention property below under R1–R5. Missing, duplicate or spurious observations, failed ownership/pairing, unsupported syntax and exhausted bounds remain explicit non-verdict exits; no source theorem is transplanted.

E. Conditional properties

Monotonicity. Equation (1) gives $H_{k+1} \subseteq H_k$. Without a valid class there is no add or delete. An in-domain singleton is not protocol PASS.

Retention. Assume (R1) $h^\star \in H_0$; (R2) one state path is consistent with the executed history; (R3) $O(h^\star, t_k, q_k)$ is a conservative outer set; (R4) the true observation belongs to both $O(h^\star, t_k, q_k)$ and Z_k; and (R5) ownership and pairing are valid. The declared interpretation and whole-history compatibility contract therefore places $h^\star$ in C_k. Thus $h^\star \in H_k \cap C_k$, and induction retains it in H_{k+1}. Out-of-domain faults may still mimic an in-domain survivor.

One-step minimax. On nonempty finite T_{cur}, $t^\star$ is a least element of $(s(t), \text{cost}(t), \text{id})$. Diagnostic-state feedback and timed active control already exist [8], [9]; this statement concerns only the declared current choice. It is not a global policy, does not prove future distinguishability, and does not guarantee shrinkage for every observation class.

Termination. Every charged TEST, Prep, Recover and ERROR spends the selected mode, hence at most $\lfloor B/c_{\min} \rfloor$ or $K_{\max}$ billed executions. Wall-clock waits still need their own timeouts; those timeouts are not claimed implemented.

Exclusive named stops are Empty, Singleton, 645, Equivalent, Budget, Stop-Error and Stop-NoDistinguisher. Stop-Error is not Stop-Budget. Admit reasons A2–A5 and post-update P1–P5 are tabulated in the supplement. CONFIRMED-NOT-SENT does not assign UNKNOWN. UNKNOWN-EFFECT must not be read back as the previous KNOWN summary. Unconfirmed Recover with $R_{\max} = 1$ and remaining budget is Stop-Error. An executed empty H is Stop-Empty. Kernels remain unimplemented interfaces.

V. Experimental Setup and Evaluation Protocol

The comparison contract is the existing experiment plan. Four arms share the same information pool, action pool and fault domain. Direct numeric comparison is allowed only on the same denominator and the same charged projection of $c = (c_{\mathrm{acq}}, c_{\mathrm{comp}}, c_{\mathrm{prep}}, c_{\mathrm{retry}})$. Seven controlled interfaces define scene registration, injection, independent truth, causal collection, arm execution, validity filtering and evaluation. Historical captures use only the offline evidence line and are not runnable scenes or confirmatory truth. The controlled line still depends on an interactive IUT, confirmed injection, reset evidence, qualified clocks and a truth generator whose shared components are disclosed.




Fig. 2. Experiment architecture from FIG-CL-TAV-09. Truth meets algorithm output only at the evaluator filter.

- CL-T: predetermined tests; projection c_{acq} for tests that run.
- CL-A: analysis on pre-allowed records; projection c_{comp} only; no invented sampling cost.
- CL-TA: frozen collect then analyse; c_{acq} and c_{comp} reported separately.
- CL-LOOP: the CL-TAV session; charge the components that actually run.

Truth is evaluator-only. It never enters `IF-SELECT-ADMIT`, `IF-PRED-OBS`, `IF-HIST-UPDATE` or `IF-EXECUTE-RECORD`. The all-attempt ledger retains every registered attempt, including unconfirmed injection, invalid observation, equivalent or undecided fault, `ERROR`, abstention and unconcluded execution. Detection uses a named valid denominator and a separate answered subset for PASS/FAIL error. Localization uses confirmed in-domain injections and separately reports whether a localization decision was issued, whether the true fault remains, whether a singleton is correct, and final $|H|$. Thus a valid detection FAIL with $H = \{h_1, h_2\}$ is an answered detection outcome but not singleton localization; $H = \{h_{\mathrm{normal}}\}$ is not protocol PASS. Mutation scores exclude only confirmed equivalents while equivalent and undecided counts and adjudication effort remain visible [5], [16].

DETECT compares miss and refusal under the same detection budget and the T5 oracle; FIND abort does not waive the 2 s / 3 s clocks. LOCATE compares surviving $|H|$ and true-fault exclusion on confirmed in-domain injections. ABLATION uses the registered factors: no feedback (CL-T or CL-TA); Prep/Recover uncharged; interval versus point-timestamp on the same traces with clocks fixed; and FIND-abort-as-waiver as a forbidden negative control, not an allowed algorithm. Sample size remains a named gap.

Placeholder PH-STAT-N
(PUBLICATION-DECISION)

Numeric n, repeats and interval method freeze at confirmatory registration, not in this draft.

Data are not obtained. This box reserves layout. It is not a result.

Literature methods are not automatically experimental arms. Köhl–Hermanns and Fränzle *et al.* are C1 concept comparators because their passive or non-adaptive testing tasks and observation assumptions differ [10], [11]. Hu *et al.* and Miao *et al.* are C2 concept comparators, but their controllable-event authority, objective, observables and stopping rules prevent a fair direct 615A arm without a new mapping decision [8], [9]. F-LAS, IMA and cockpit-display studies are scenario or evaluation context, not algorithm baselines [2], [14], [15]. Confirmatory registration must still freeze the experimental unit, fault construction, equivalence adjudicator, injection confirmation, clock calibration, stochastic repetition/seeds if any, and interval/effect-size method; no literature percentage selects those values [17].

VI. Results

No effect direction, percentage or superiority is reported.

Placeholder PH-RES-DETECT
(EXPERIMENT-RESULT)

Separate cells, not one shared denominator: (i) the all-attempt ledger and attempt coverage; (ii) named unconfirmed, invalid, equivalent, undecided, ERROR, abstain and unconcluded flows; (iii) refusal among attempts; (iv) conditional error on the detection answered subset; and (v) miss and false-FAIL on the registered valid detection denominator. Abstain is not PASS/FAIL. Source: EXP-CLTAV-DETECT.

Data are not obtained. This framed panel reserves a single-column result figure. It is not a curve, a mean, or a significance test.

Fig. 3. Reserved detection panel. Not a result.

Placeholder PH-RES-LOCATE
(EXPERIMENT-RESULT)

Cells: final $|H|$, true-fault retention/exclusion, decision issued, singleton correctness, refusal and charged resource. Denominator: confirmed in-domain injections, reported separately from the detection answered subset. A valid FAIL with a nonsingleton H is not completed localization. Out-of-domain faults are separate; singleton h_{normal} is not protocol PASS. Source: EXP-CLTAV-LOCATE.

Data are not obtained. This framed panel reserves a single-column result figure. It is not a curve, a mean, or a significance test.

Fig. 4. Reserved localization panel. Not a result.

TABLE II

Reserved ablation cells. CL-A is computation-only; N/A cells are not silent omissions. FIND-abort waiver is a forbidden control.

Cell	CL-T	CL-A	CL-TA	CL-LOOP
Charged projection	c_{acq}	c_{comp}	split	actual
No-feedback contrast	yes	N/A	yes	reference
Prep/Recover uncharged	if run	N/A	if run	contrast
Interval vs point stamp	—	—	—	contrast
FIND-abort waiver	forbidden	forbidden	forbidden	forbidden

A. CL-RQ2: verdict reliability

B. CL-RQ2: isolation

C. CL-RQ3: cost and sensitivity

Placeholder PH-RES-ABLATION
(EXPERIMENT-RESULT)

Table II uses the registered ablation factors, not a generic "disable cost accounting." Complete when parent DETECT/LOCATE cells exist on the same scenes.

Data are not obtained. This box reserves layout. It is not a result.

VII. Discussion and Limitations

The first-version domain is a declared single-fault H_0, one-step selection, a bound UPLOAD/INFORMATION model, and notation-only architecture views. Out-of-domain faults may remain compatible with an in-domain survivor. A remaining $\{h_{\mathrm{normal}}\}$ is not a protocol PASS. Obtaining ARINC 645 and binding the six distinct triggered obligations closes only their specification contracts; it does not establish any runtime integrity capability.

Engineering work that is not done includes the core estimators, an executable verification engine, Project Configuration and confirmatory runs. Those absences are unfinished work, not method impossibility.

The 23 inspected captures are a selected exploratory corpus with unknown topology, clock qualification, device configuration, software version and independent root-cause truth. Repeated sessions and shared parser, model or clock components induce dependence and common-error risk. They can exercise intake and reconstruction robustness, but cannot support active counterfactual comparison among the four experimental arms. The bounded reference kernel also abstains rather than treating a frontier limit as incompatibility.

Related work sharpens rather than removes these limits. Passive compatible-run diagnosis does not establish the active protocol lifecycle, while active diagnosis under different control authority does not validate the CL-TAV selector [8]–[10]. An aerospace demonstration has shown that limited observability and model–prototype mismatch can yield wrong localization [13]. In cockpit-display testing, image-derived and simulator-data verdicts share OCL constraints, so high extraction precision is not independent truth for the oracle or product behaviour [15].

The confirmatory design must therefore disclose shared parsers, models, constraints, clocks and truth-generation components and retain discrepancy classes rather than relabel them as product faults.

Placeholder PH-RES-INTERPRET
(EXPERIMENT-RESULT)

Discussion of measured gains or losses waits for the reserved result panels. No placeholder may be read as a neutral or negative experimental outcome.

Data are not obtained. This box reserves layout. It is not a result.

Transfer beyond Ethernet laboratory loaders, and any certification argument, remain open (historical RQ6).

VIII. Conclusion

CL-TAV specifies a charged observation–update–select session for ARINC 615A data loading under declared uncertainty and one resource mode. Its bounded proposition is conditional consistency of interpretation and whole-history update plus a protocol-legal one-step residual-set choice, not universal uncertain-timing diagnosis or global policy optimality. The main-text loop keeps interpretation, compatible update and exclusive stops consistent with the accepted algorithm package. Experimental answers to CL-RQ2 and CL-RQ3 are not available.

Placeholder PH-CONC-RESULT
(EXPERIMENT-RESULT)

The concluding experimental sentence stays empty until PH-RES-DETECT, PH-RES-LOCATE and PH-RES-ABLATION are cleared by registered runs.

Data are not obtained. This box reserves layout. It is not a result.

This draft is not submission-ready, not an implemented solver, and not capability establishment.

REFERENCES

[1] Airlines Electronic Engineering Committee
ARINC Specification 615A-3: Software Data Loader Using Ethernet Interface, Airlines Electronic Engineering Committee, 2007, cited by identifier and clause class only; no standard figure is reprinted.

[2] J. Marques, S. Yelisetty, and L. Barros
A framework for loadable airborne systems
IEEE Aerospace and Electronic Systems Magazine, vol. 36, no. 5, pp. 38–47, 2021.

[3] J. Tretmans
Conformance testing with labelled transition systems: Implementation relations and test generation
Computer Networks and ISDN Systems, vol. 29, no. 1, pp. 49–79, 1996.

[4] A. Petrenko, O. Nguena Timo, and S. Ramesh
Test generation by constraint solving and FSM mutant killing
In *Testing Software and Systems (ICTSS 2016)*, ser. LNCS, vol. 9976, 2016, pp. 36–51.

[5] Y. Jia and M. Harman
An analysis and survey of the development of mutation testing
IEEE Transactions on Software Engineering, vol. 37, no. 5, pp. 649–678, 2011.

[6] Z. Yang, R. Huang, C. Cui, N. Niu, and D. Towey
Requirements-based test generation: A comprehensive survey
ACM Transactions on Software Engineering and Methodology, 2025.

[7] M. Sampath, S. Lafortune, and D. Teneketzis
Active diagnosis of discrete-event systems
IEEE Transactions on Automatic Control, vol. 43, no. 7, pp. 908–929, 1998.

[8] Y. Hu, Z. Ma, and Z. Li
Design of supervisors for active diagnosis in discrete event systems
IEEE Transactions on Automatic Control, vol. 65, no. 12, pp. 5159–5172, 2020.

[9] S. Miao, J. Komenda, and A. Lai
Active diagnosis of time-interval automata: Time perspectives
IEEE Transactions on Automation Science and Engineering, vol. 22, pp. 11 239–11 249, 2025.

[10] M. A. Köhl and H. Hermanns
Model-based diagnosis of real-time systems: Robustness against varying latency, clock drift, and out-of-order observations
ACM Transactions on Embedded Computing Systems, vol. 22, no. 4, pp. 68:1–68:48, 2023.

[11] M. Fränzle, T. M. Grosen, K. G. Larsen, and M. Zimmermann
Efficient runtime verification of real-time systems under parametric communication delays
Formal Aspects of Computing, vol. 38, no. 2, pp. 17:1–17:32, 2026.

[12] E. Chanthery and Y. Pencolé
Monitoring and active diagnosis for discrete-event systems
IFAC Proceedings Volumes, vol. 42, no. 8, pp. 1545–1550, 2009.

[13] E. Chanthery, L. Travé-Massuyès, Y. Pencolé, R. de Ferluc, and B. Dellandrea
Applying active diagnosis to space systems by on-board control procedures
IEEE Transactions on Aerospace and Electronic Systems, vol. 55, no. 5, pp. 2568–2580, 2019.

[14] C. Efkemann and J. Peleska
Model-based testing for the second generation of integrated modular avionics
In *2011 IEEE Fourth International Conference on Software Testing, Verification and Validation Workshops*, 2011, pp. 55–62.

[15] H. Sartaj, M. Z. Iqbal, and M. U. Khan
Testing cockpit display systems of aircraft using a model-based approach
Software and Systems Modeling, vol. 20, no. 6, pp. 1977–2002, 2021.

[16] B. J. M. Grün, D. Schuler, and A. Zeller
The impact of equivalent mutants
In *2009 International Conference on Software Testing, Verification, and Validation Workshops*, 2009, pp. 192–199.

[17] A. Arcuri and L. Briand
A practical guide for using statistical tests to assess randomized algorithms in software engineering
In *Proceedings of the 33rd International Conference on Software Engineering*, 2011, pp. 1–10.

[18] Joint Committee for Guides in Metrology
Evaluation of measurement data — guide to the expression of uncertainty in measurement
JCGM, Tech. Rep. JCGM 100:2008, 2008.

[19] Joint Committee for Guides in Metrology
Evaluation of measurement data — the role of measurement uncertainty in conformity assessment

JCGM, Tech. Rep. JCGM 106:2012, 2012.

[20] Airlines Electronic Engineering Committee
ARINC Specification 645-1: Common Terminology and Functions for Software Distribution and Loading, Airlines Electronic Engineering Committee, 2021, 615A-triggered SOURCE/SEMANTIC bind; capabilities not established.