

Hierarchical and Permutation-Invariant Feature Transformation Learning via Policy-Guided Embedding Search

Rui Liu
University of Kansas
Lawrence, United States
rayliu@ku.edu

Tao Zhe
University of Kansas
Lawrence, United States
taozhe@ku.edu

Yanyong Huang[†]
Southwest University of Finance and
Economics
Chengdu, China
huangyy@swufe.edu.cn

Sankha Narayan Guria
University of Kansas
Lawrence, United States
sankha@ku.edu

Xiao Luo
University of Wisconsin–Madison
Madison, United States
xiao.luo@wisc.edu

Wei Fan
University of Auckland
Auckland, New Zealand
wei.fan@auckland.ac.nz

Yanjie Fu
Arizona State University
Tempe, United States
yanjie.fu@asu.edu

Dongjie Wang[†]
Northeast Normal University
Jilin, China
wangdongjie100@nenu.edu.cn

Abstract

Feature transformation improves predictive performance on tabular data by constructing informative abstractions from raw features. Recent generative approaches encode transformation knowledge into continuous embedding spaces for efficient exploration of candidate strategies, but face three key limitations: 1) overlooking hierarchical relationships between low-level features, operations, and high-level abstractions; 2) enforcing order-sensitive embeddings on inherently permutation-invariant transformation sequences, introducing systematic bias; and 3) relying on gradient-based search ill-suited to non-convex transformation spaces. We propose a framework with two complementary components. First, a permutation-invariant hierarchical module captures interactions across features, operations, and abstraction levels, with a self-attention pooling mechanism that maps semantically equivalent structures to consistent embeddings aligned with downstream performance. Second, a policy-guided multi-objective reinforcement learning strategy initializes search from empirically strong seeds and jointly optimizes predictive accuracy and transformation efficiency. Extensive experiments on diverse tabular benchmarks demonstrate the effectiveness and robustness of our framework against strong baselines. Our code and data are publicly available ¹.

CCS Concepts

• **Computing methodologies** → **Learning latent representations; Reinforcement learning.**

[†]Corresponding authors.

¹<https://github.com/RayLiu1103/PHER>



This work is licensed under a Creative Commons Attribution 4.0 International License.
CIKM '26, Rome, Italy

© 2026 Copyright held by the owner/author(s).

ACM ISBN 979-8-4007-2539-5/2026/11

<https://doi.org/10.1145/3799682.3840882>

KEYWORDS

Automated Feature Transformation, Hierarchical Representation Learning, Reinforcement Learning

ACM Reference Format:

Rui Liu, Tao Zhe, Yanyong Huang[†], Sankha Narayan Guria, Xiao Luo, Wei Fan, Yanjie Fu, and Dongjie Wang[†]. 2026. Hierarchical and Permutation-Invariant Feature Transformation Learning via Policy-Guided Embedding Search. In *Proceedings of the 35th ACM International Conference on Information and Knowledge Management (CIKM '26)*, November 07–11, 2026, Rome, Italy. ACM, New York, NY, USA, 10 pages. <https://doi.org/10.1145/3799682.3840882>

1 Introduction

Feature transformation aims to improve tabular feature spaces by mathematically deriving more predictive representations from original features. Although deep learning has recently achieved remarkable success, it struggles to deliver strong performance on tabular data due to heterogeneous feature types, varying feature scales, and the presence of missing values or outliers. Furthermore, the black-box nature of deep learning models limits their interpretability, hindering their application in further data analysis and critical decision-making systems. Thus, automated feature transformation, which aims to generate distinguishable and informative features to enhance predictive performance, has emerged as a significant research direction in tabular data analysis.

Existing methods for automated feature transformation can be categorized into three main groups: 1) Expansion-reduction approaches [10, 12, 17], which first enlarge the original feature space using mathematical transformations and subsequently reduce dimensionality through feature selection; 2) Evolution-evaluation approaches [16, 28, 31], which utilize Evolutionary Algorithms (EA) or Reinforcement Learning (RL) to iteratively generate and evaluate transformation candidates based on model performance feedback; 3) Auto ML-based approaches [3, 39], which formulate feature transformation as a search problem, employing automated




Figure 1: Example of hierarchical relationships between generated feature abstractions (concepts) and original features. BMI and WHR are derived from original features.

machine learning techniques to identify optimal transformations. Despite achieving considerable success, these methods still face challenges in effectively modeling intricate patterns inherent in feature transformation knowledge.

Inspired by the success of generative AI, recent advances formulate automated feature transformation as a token generation task [22, 23, 32, 34, 35]. They compress feature transformation knowledge into a continuous embedding space and subsequently explore this space via gradient-based methods to identify superior feature transformation sequences. However, there are three primary limitations: 1) **Neglecting hierarchical relationships between original features, mathematical operations, and generated feature abstractions.** For example, as illustrated in Figure 1, Body Mass Index (BMI) and Waist-to-Hip Ratio (WHR) are high-level feature abstractions (i.e., concepts) derived from original features through mathematical transformations, which can significantly contribute to predicting clinical outcomes such as Pre-Diabetes (PreDM), Type 2 Diabetes (T2DM), Insulin Resistance (IR), and Metabolic Syndrome (MetS). Neglecting explicit modeling of these hierarchical relationships results in incomplete feature representations, limiting the capture of meaningful interactions and reducing the discriminative power of the embedding space. 2) **Ignoring the order invariance of the generated feature abstractions with respect to the predictive performance of the associated feature space.** Prior studies treat the entire feature transformation process as a sequential model to capture transformation knowledge. However, this formulation introduces unnecessary permutation bias among generated concepts into the embedding space, hindering effective exploration and limiting the identification of the globally optimal feature transformation embedding. 3) **Relying on gradient-based search methods that strongly assume convexity of the learned embedding space.** Existing methods typically assume convexity in the learned embedding space, relying on gradient-based search methods to identify globally optimal solutions. However, due to complex interactions among features and mathematical operations, it is challenging to guarantee the convexity of the embedding space. This misalignment between the

convexity assumption and the practical characteristics of the embedding space increases the risk of being trapped in local optima, resulting in suboptimal feature transformation sequences.

Our Contribution: A Hierarchical Modeling and Policy-Guided Feature Transformation Perspective. To address these limitations, we propose PHER, a novel feature transformation framework that integrates permutation-invariant hierarchical modeling and multi-objective policy-guided search. Specifically, given a large volume of feature transformation records, where each record consists of a transformation sequence and the associated model performance, we first design a hierarchical modeling module. This module preserves transformation knowledge at both low-level feature interactions and high-level feature abstractions (i.e. concepts) into a continuous embedding space. To ensure permutation invariance, we develop a self-attention pooling mechanism that symmetrically computes attention scores across various generated concepts. This structure guarantees that any permutation of generated concepts yields identical embeddings, resulting in a global continuous embedding space that unbiasedly preserves feature transformation knowledge. Subsequently, we employ a policy-guided multi-objective search strategy to explore the global embedding space and identify the optimal feature transformation sequence. In detail, we first select the top-K feature transformation sequences based on model performance as search seeds. Then, we convert these seeds into embeddings, which serve as initial positions for exploration within the learned global embedding space. Next, we treat seed embeddings as states and implement a reinforcement learning agent to explore the embedding space, guided by maximizing downstream task performance and minimizing the length of transformation sequences. The exploratory nature of reinforcement learning enables effective navigation of the embedding space, reducing the risk of becoming trapped in local optima, even when the embedding space lacks convexity. Finally, we conduct extensive experiments on 19 real-world datasets to evaluate the efficiency, resilience, and traceability of PHER. The experimental results show the superior performance of PHER over the state-of-the-art feature transformation methods.

2 Problem Statement

We aim to develop an automated feature transformation framework from a generative intelligence perspective, integrating permutation-invariant hierarchical modeling and a policy-guided multi-objective search strategy. Formally, given a dataset $D = \{X, y\}$, where X denotes features and y represents the corresponding labels, along with a mathematical operation set O (e.g., addition, subtraction, multiplication). We first gather n feature transformation records, denoted by $\{(\Gamma_i, v_i)\}_{i=1}^n$ based on the dataset D , where each record consists of a transformation sequence Γ_i and the associated downstream predictive performance v_i . We then train a token-level encoder ϕ_{tok} and decoder ψ_{tok} to encode interactions between original features and mathematical operations into token embeddings E , optimized through a token-level reconstruction loss. These token embeddings are grouped and averaged through an aggregation layer to form concept embeddings G . A concept-level permutation-invariant encoder ϕ_{con} is then employed to eliminate order sensitivity among concepts, resulting in a global, unbiased embedding space $\mathbb{G}$. A corresponding concept-level decoder ψ_{con} is simultaneously trained




Figure 2: An overview of our framework. PHER comprises two main components: 1) Permutation-Invariant Hierarchical Modeling, which unbiasedly preserves feature transformation knowledge at both the feature-operation token level and the generated-concept level within a global embedding space; 2) Policy-Guided Multi-objective Search, which effectively explores the learned embedding space to identify optimal feature transformation sequences.

to capture patterns from generated concepts. After that, we employ a policy-guided strategy to explore $\mathbb{G}$, aiming to identify the optimal global embedding G'_{opt} . This embedding can be decoded by the concept-level decoder ψ_{con} and token-level decoder ψ_{tok} to reconstruct the optimal feature transformation sequence Γ^* , thus generating a feature space that maximizes downstream task performance $\mathcal{M}$. Formally, the optimization goal is formulated as:

$$\Gamma^* = \psi_{tok}(\psi_{con}(G'_{opt})) = \operatorname{argmax}_{G' \in \mathbb{G}} \mathcal{M}(X[\psi_{tok}(\psi_{con}(G'))]). \quad (1)$$

3 Methodology

3.1 Framework Overview

Figure 2 illustrates the overall structure of PHER, comprising two primary components: 1) Permutation-Invariant Hierarchical Modeling and 2) Policy-Guided Multi-Objective Search. Specifically, given a large collection of feature transformation records, each record consists of one feature transformation sequence and the corresponding model performance. We first develop a token-level encoder to embed original features and mathematical operations, capturing token-level transformation patterns. Next, we aggregate token embeddings into concept embeddings according to the correspondence between original features, operations, and generated concepts. We then apply a concept-level encoder with a self-attention pooling mechanism to eliminate order sensitivity, obtaining permutation-invariant global embeddings. To effectively train the encoders, we introduce a concept-level decoder and a token-level decoder to reconstruct concept embeddings and original feature-operation tokens, respectively. After obtaining the global embedding space, we employ a policy-guided multi-objective search strategy to explore this embedding space, guided by maximizing downstream

task performance and minimizing the length of feature transformation sequences. The identified optimal embedding is then decoded into its corresponding feature transformation sequence using the trained decoder. Finally, this reconstructed sequence is applied to the original feature space, resulting in an optimized feature space with improved predictive performance.

3.2 Hierarchical Feature Transformation Knowledge Modeling

Why Hierarchical Knowledge Modeling Matters. Feature transformation inherently involves intricate hierarchical relationships among original features, mathematical operations, and higher-level generated concepts. However, existing generative intelligence-based approaches typically treat the entire feature transformation sequence as an indistinguishable whole, neglecting these hierarchical distinctions. This oversimplification leads to inadequate modeling of transformation knowledge, reducing the discriminative power of the continuous embedding space, and ultimately resulting in suboptimal feature spaces. To address these limitations, we develop a hierarchical modeling module in our framework, which can explicitly capture both token-level relationships (individual feature-operation interactions) and concept-level relationships (aggregated higher-level concepts) within the learned embedding space.

Reinforcement Transformation-Accuracy Training Data Collection. To learn an effective embedding space of feature transformation, we collect n transformation records using an RL-based method [31], denoted by $\{(\Gamma_i, v_i)\}_{i=1}^n$, where Γ_i is a feature transformation sequence (e.g., $\log(f_1), -f_3, \dots$) and v_i is the corresponding model performance. In this method, two agents select candidate features while a third agent selects the transformation operation at each iteration, jointly optimized by maximizing downstream task performance. For more details, please refer to the referenced paper.

Token-Level Feature Transformation Embedding. After collecting feature transformation sequence-accuracy pairs $\{(\Gamma_i, v_i)\}_{i=1}^n$, we train the token-level encoder and decoder to capture token-level transformation patterns from feature-operation token sequences.

Encoder ϕ_{tok} : The token encoder aims to learn a mapping function ϕ_{tok} that converts the input transformation sequence $\Gamma \in \mathbb{R}^{1 \times N}$ to token embeddings $\mathbf{E}$, denoted by $\mathbf{E} = \phi_{tok}(\Gamma) \in \mathbb{R}^{N \times d_{tok}}$, where N is the length of the input transformation sequence Γ and d_{tok} is the hidden size of token embedding. In PHER, we adopt two Transformer encoder layers [29] as the token encoder.

Decoder ψ_{tok} : The token decoder is designed to reconstruct the transformation sequence Γ from the learned token embedding $\mathbf{E}$, which can be denoted by $\Gamma = \psi_{tok}(\mathbf{E})$. In PHER, we adopt two Transformer decoder layers [29] as the token decoder.

Why Ensuring Permutation Invariance in Concept-Level Embeddings Matters. While token-level encoders capture low-level feature-operation interactions, they fail to model high-level transformation patterns. In practice, a set of generated transformation concepts is semantically invariant to the ordering of its concepts. However, existing methods encode these concepts in an order-sensitive manner, introducing permutation bias that fragments equivalent transformations across multiple embeddings. This redundancy distorts the embedding space and inflates the search space, leading to inefficient exploration. We thus propose a permutation-invariant concept encoder-decoder that maps equivalent concepts to canonical embeddings, enabling faithful representation learning and efficient exploration of the learned embedding space.

Encoder ϕ_{con} : The concept encoder aims to encode the concepts into global embeddings. To ensure permutation invariance, we adopt a self-attention pooling mechanism [20] in ϕ_{con} . This structure is inherently permutation-invariant with respect to the ordering of concepts, ensuring that the same concept set yields an identical global embedding regardless of its order. Specifically, each transformation sequence is represented in postfix form, and each concept is constructed by sequentially composing feature and operation tokens according to this representation. For simple transformations, we obtain the concept embedding by averaging the embeddings of the involved tokens. For nested transformations, this aggregation is applied recursively following the postfix order. For example, $\log(\log(f_7))$ is represented as $(f_7, \log, \log)$ and encoded as $\text{Mean}(\text{Mean}(\mathbf{E}_{f_7}, \mathbf{E}_{\log}), \mathbf{E}_{\log})$. Thus, token embeddings $\mathbf{E}$ are aggregated into concept embeddings $\mathbf{G}$ according to the compositional structure of the generated transformations. Then, we initialize a set of k learnable seed vectors $\mathbf{S} \in \mathbb{R}^{k \times d_{seed}}$ using Xavier uniform initialization, where k is the number of seed vectors and d_{seed} is the hidden size of each seed vector. These learnable seed vectors serve as queries in the multi-head attention module, attending over the concept embeddings $\mathbf{G}$ which serve as keys and values to extract high-level semantic concept representations. The output is then combined with the original seed vectors through a residual connection, followed by a linear layer. This yields the global embedding, denoted by: $\mathbf{G}' = \phi_{con}(\mathbf{G}) = \text{Linear}(\mathbf{S} + \text{Multihead}(\mathbf{S}, \mathbf{G}, \mathbf{G})) \in \mathbb{R}^{k \times d_{global}}$, where d_{global} represents the hidden size of global embedding.

Decoder ψ_{con} : The concept decoder ψ_{con} aims to reconstruct concept embedding $\mathbf{G}$ from the global embedding $\mathbf{G}'$, denoted by

Algorithm 1: Training and Search Procedure of PHER

Input: Transformation records $\{(\Gamma_i, v_i)\}_{i=1}^n$, top- K seeds, search epochs T

Output: Optimal transformation sequence Γ^*

// Stage 1: Token-Level Training

- 1 **for each epoch do**
- 2 $\mathbf{E} \leftarrow \phi_{tok}(\Gamma), \hat{\Gamma} \leftarrow \psi_{tok}(\mathbf{E});$
- 3 Update ϕ_{tok}, ψ_{tok} by minimizing $\mathcal{L}_{tok}$;
- 4 **end**

// Stage 2: Concept-Level Training

- 5 Freeze ϕ_{tok} ;
- 6 **for each epoch do**
- 7 $\mathbf{E} \leftarrow \phi_{tok}(\Gamma), \mathbf{G} \leftarrow \text{Aggregate}(\mathbf{E});$
- 8 $\mathbf{G}' \leftarrow \phi_{con}(\mathbf{G}), \hat{\mathbf{G}} \leftarrow \psi_{con}(\mathbf{G}');$
- 9 Update ϕ_{con}, ψ_{con} by minimizing $\mathcal{L}_{con}$;
- 10 **end**

// Stage 3: Token-Concept Alignment

- 11 Freeze $\phi_{con}^*, \psi_{con}^*$;
- 12 **for each epoch do**
- 13 $\hat{\Gamma} \leftarrow \psi_{tok}(\psi_{con}^*(\phi_{con}^*(\text{Aggregate}(\phi_{tok}(\Gamma))))$;
- 14 Update ϕ_{tok}, ψ_{tok} by minimizing $\mathcal{L}_{align}$;
- 15 **end**

// Stage 4: Policy-Guided Search

- 16 Select top- K records by performance as search seeds;
- 17 Initialize PPO agent $\mathcal{A}$ with actor-critic architecture;
- 18 **for $t = 1$ to T do**
- 19 **for each seed (Γ, v) do**
- 20 $\mathbf{G}' \leftarrow \phi_{con}^*(\text{Aggregate}(\phi_{tok}^*(\Gamma)))$;
- 21 $\mathbf{G}'_+ \leftarrow \mathcal{A}(\mathbf{G}')$;
- 22 $\Gamma^+ \leftarrow \psi_{tok}^*(\psi_{con}^*(\mathbf{G}'_+))$;
- 23 Compute reward $\mathcal{R}$ based on $\mathcal{M}(X[\Gamma^+])$ and $|\Gamma^+|$;
- 24 **end**
- 25 Update $\mathcal{A}$ by maximizing $\mathcal{L}_{actor}$ and minimizing $\mathcal{L}_{critic}$;
- 26 **end**
- 27 $\Gamma^* \leftarrow \arg \max_{\Gamma^+} \mathcal{M}(X[\Gamma^+])$;
- 28 **return Γ^* ;**

$\mathbf{G} = \psi_{con}(\mathbf{G}')$. In PHER, we adopt the same architecture for the concept decoder as used in the concept encoder, ensuring symmetric abstraction and reconstruction.

Hierarchical Optimization Procedure: To effectively train the hierarchical encoder-decoder models, we design a three-stage training strategy. Each stage progressively captures feature transformation knowledge, from token-level to concept-level.

Stage 1: Token-Level Training. In the first stage, we train the token encoder ϕ_{tok} and decoder ψ_{tok} to reconstruct the input transformation sequence Γ . Specifically, given a sequence Γ , the token encoder first produces token embedding $\mathbf{E} = \phi_{tok}(\Gamma)$. The token decoder then reconstructs the original feature transformation sequence from the token embedding $\hat{\Gamma} = \psi_{tok}(\mathbf{E})$. We optimize the token-level model by minimizing the negative log-likelihood loss:

$$\mathcal{L}_{tok} = -\log P_{\psi_{tok}}(\Gamma | \mathbf{E}). \quad (2)$$

Stage 2: Concept-Level Training. After training the token-level model, we freeze its parameters and train the concept encoder ϕ_{con} and decoder ψ_{con} to learn high-level permutation-invariant global embeddings. Specifically, given a feature transformation sequence Γ , we first utilize the well-trained token encoder to obtain token embedding E . Then, we input E into the aggregation layer to generate the concept embedding G based on the relationships between concept and its affiliated feature indices and mathematical operations. Thereafter, G is input into ϕ_{con} to obtain the global embedding $G' = \phi_{con}(G)$. Finally, the global embedding G' is decoded back to concept embedding $\hat{G} = \psi_{con}(G')$. We optimize the concept-level model by minimizing the Mean Squared Error (MSE) between the reconstructed $\hat{G}$ and original concept embedding G , denoted by:

$$\mathcal{L}_{con} = \text{MSE}(G, \hat{G}) = \text{MSE}(G, \psi_{con}(\phi_{con}(G))). \quad (3)$$

Stage 3: Token-Concept Alignment. In this stage, we freeze the concept-level model and tune the token encoder and decoder to improve the accuracy of end-to-end token reconstruction. Given a transformation sequence Γ , we obtain the token embedding $E = \phi_{tok}(\Gamma)$. Then, the aggregation layer maps E to concept embeddings G , which are further processed by the well-trained concept encoder ϕ_{con}^* and concept decoder ψ_{con}^* before being decoded by the token decoder. We optimize the following loss during the alignment stage: $\mathcal{L}_{align} = -\log P_{\psi_{tok}}(\Gamma \mid \psi_{con}^*(\phi_{con}^*(\phi_{tok}(\Gamma))))$. Here, the aggregation layer is omitted for brevity. This stage aligns token embeddings with the fixed concept-level abstractions, improving the coherence and semantic quality of the reconstructed transformation sequence. The complete training and search procedure of PHER is summarized in Algorithm 1.

3.3 Policy-guided Multi-objective Search

Why selecting search seeds matters. Once the global embedding space has converged, we employ a policy-guided multi-objective search strategy in the learned global embedding space to identify the optimal global embedding that achieves maximum downstream task performance and minimum transformation length. Inspired by the significance of initialization for deep neural networks, good starting points are crucial for accelerating the search process and enhancing its performance. Thus, we rank all collected records by model performance and select the top-K as search seeds.

Policy-guided multi-objective search. Existing methods assume the learned embedding space is convex, relying on gradient-ascent search strategy to identify the global optimal embedding. However, due to the complex interactions between features and mathematical operations, the embedding space is highly non-convex in practice, increasing the risk of becoming trapped in local optima and resulting in suboptimal feature transformation sequences. Thus, to perform effective exploration and search process without strong convexity assumptions, we employ Proximal Policy Optimization (PPO) [27] method, which is a widely used policy gradient algorithm for multi-objective optimization. PPO stabilizes policy updates by clipping and trust region mechanisms, effectively balancing exploration and exploitation in high-dimensional and non-convex embedding spaces. In PHER, the PPO agent learns to explore the continuous global embedding space by selecting promising global embeddings based on the downstream task performance and transformation sequence length. Specifically, given a global embedding

G' , the PPO agent $\mathcal{A}$ aims to manipulate it to generate the optimal global embedding G'_{opt} , denoted by: $\mathcal{A}(G') = G'_{opt}$.

Reward $\mathcal{R}$: To balance the performance and the total length of the transformed sequence, we propose a weighted reward function, denoted by: $\mathcal{R} = \lambda(\mathcal{M}(X[\Gamma^+]) - \mathcal{M}(X[\Gamma])) + (1 - \lambda)\mathcal{N}[\Gamma^+]$, where $\mathcal{M}$ denotes the downstream ML task, Γ represents the original transformation sequence, Γ^+ refers to the searched transformation sequence, $\mathcal{N}[\Gamma^+]$ is a normalized length penalty of Γ^+ , and λ is the trade-off hyperparameter to balance the performance improvement and the total length of the transformed sequence.

Solving the Optimization Problem. We adopt a multi-objective optimization strategy to train the PPO agent. Specifically, the policy is updated by maximizing a clipped surrogate objective, which approximates the cumulative discounted reward obtained throughout the iterative search process, while constraining the step size of each update. To enable the PPO agent to identify more informative embeddings with higher model performance and fewer transformation operations, we adopt an actor-critic model architecture. We optimize the critic by minimizing the difference between the observed cumulative discounted rewards and their predictions, denoted by: $\mathcal{L}_{critic} = \frac{1}{T} \sum_{t=1}^T (V(s_t) - G_t)^2$, where T is the trajectory length, s_t is the state at time step t , $V(s_t)$ is the predicted value from the critic, G_t is the cumulative discounted return, and $\gamma \in [0, 1]$ is the discounted factor. The actor is optimized by maximizing a clipped surrogate objective while constraining the step size of each policy update, denoted by: $\mathcal{L}_{actor} = \mathbb{E}_t [\min(r_t(\theta)\hat{A}_t, \text{clip}(r_t(\theta), 1 - \epsilon, 1 + \epsilon)\hat{A}_t)]$, where ϵ is the clipping ratio hyperparameter, $r_t(\theta)$ is the probability ratio, and $\hat{A}_t$ is the estimated advantage. Once the actor network converges, the learned policy π^* guides the global embedding G' within the global embedding space $\mathbb{G}$ toward regions that yield higher downstream task performance with fewer transformation operations. Then, we reconstruct the transformation sequence Γ^+ from the enhanced global embedding G'_+ using the well-trained concept decoder and token decoder. Next, we obtain enhanced feature spaces using the enhanced transformation sequences $[\Gamma_1^+, \Gamma_2^+, \dots, \Gamma_K^+]$ and input them into the downstream ML task to evaluate their performance. Finally, the feature transformation sequence achieving the highest performance is selected as the optimal sequence, denoted as Γ^* .

4 Experiments

4.1 Datasets and Evaluation Metrics


We evaluate PHER on 19 publicly accessible datasets from UCI [25], LibSVM [5], Kaggle [11], and OpenML [24], including 14 classification tasks and 5 regression tasks. We adopt Random Forest as the unified downstream model and evaluate its performance via five-fold cross-validation on the training partition. All experiments follow a hold-out evaluation protocol, where each dataset is randomly divided into 80% for training and 20% for testing, and are independently repeated five times with different random seeds, with results reported as the mean and standard deviation. For regression tasks, we report 1-Relative Absolute Error (1-RAE), 1-Mean Absolute Error (1-MAE), 1-Mean Squared Error (1-MSE), and 1-Root Mean Squared Error (1-RMSE). For classification tasks, we use F1-score, Precision, Recall, and ROC/AUC.

Table 1: Overall performance comparison. In this table, the best and second-best results are highlighted in red and blue, respectively. (The higher the value is, the better the model performance is.)

Dataset	C/R	Original	RDG	ERG	LDA	AFAT	NFS	TTG	GRFG	DIFER	MOAT	PHER
Higgs Boson	C	0.696	0.700 $\pm$ 0.001	0.704 $\pm$ 0.003	0.511 $\pm$ 0.011	0.695 $\pm$ 0.001	0.697 $\pm$ 0.002	0.699 $\pm$ 0.003	0.701 $\pm$ 0.002	0.669 $\pm$ 0.001	0.699 $\pm$ 0.002	0.706 $\pm$ 0.002
Amazon Employee	C	0.930	0.931 $\pm$ 0.001	0.935 $\pm$ 0.001	0.914 $\pm$ 0.002	0.933 $\pm$ 0.002	0.932 $\pm$ 0.001	0.930 $\pm$ 0.001	0.932 $\pm$ 0.001	0.929 $\pm$ 0.001	0.933 $\pm$ 0.002	0.936 $\pm$ 0.002
PimaIndian	C	0.776	0.760 $\pm$ 0.007	0.762 $\pm$ 0.004	0.729 $\pm$ 0.061	0.760 $\pm$ 0.011	0.759 $\pm$ 0.014	0.750 $\pm$ 0.019	0.754 $\pm$ 0.011	0.760 $\pm$ 0.013	0.807 $\pm$ 0.011	0.828 $\pm$ 0.003
SpectF	C	0.760	0.760 $\pm$ 0.001	0.759 $\pm$ 0.018	0.665 $\pm$ 0.119	0.782 $\pm$ 0.079	0.760 $\pm$ 0.001	0.775 $\pm$ 0.014	0.818 $\pm$ 0.001	0.766 $\pm$ 0.002	0.912 $\pm$ 0.014	0.929 $\pm$ 0.003
SVMGuide3	C	0.778	0.778 $\pm$ 0.008	0.817 $\pm$ 0.015	0.635 $\pm$ 0.049	0.789 $\pm$ 0.009	0.786 $\pm$ 0.004	0.791 $\pm$ 0.014	0.812 $\pm$ 0.025	0.773 $\pm$ 0.021	0.845 $\pm$ 0.001	0.848 $\pm$ 0.003
German Credit	C	0.649	0.667 $\pm$ 0.008	0.684 $\pm$ 0.011	0.597 $\pm$ 0.058	0.640 $\pm$ 0.032	0.663 $\pm$ 0.017	0.663 $\pm$ 0.019	0.683 $\pm$ 0.013	0.656 $\pm$ 0.018	0.729 $\pm$ 0.001	0.736 $\pm$ 0.007
Credit Default	C	0.802	0.805 $\pm$ 0.001	0.804 $\pm$ 0.002	0.743 $\pm$ 0.009	0.804 $\pm$ 0.001	0.803 $\pm$ 0.002	0.803 $\pm$ 0.002	0.806 $\pm$ 0.003	0.796 $\pm$ 0.005	0.808 $\pm$ 0.001	0.810 $\pm$ 0.001
Messidor_features	C	0.633	0.685 $\pm$ 0.053	0.665 $\pm$ 0.025	0.463 $\pm$ 0.084	0.656 $\pm$ 0.005	0.657 $\pm$ 0.011	0.662 $\pm$ 0.019	0.692 $\pm$ 0.033	0.660 $\pm$ 0.007	0.694 $\pm$ 0.005	0.744 $\pm$ 0.003
Wine Quality Red	C	0.456	0.514 $\pm$ 0.016	0.494 $\pm$ 0.005	0.401 $\pm$ 0.061	0.480 $\pm$ 0.042	0.467 $\pm$ 0.021	0.464 $\pm$ 0.010	0.470 $\pm$ 0.009	0.476 $\pm$ 0.018	0.559 $\pm$ 0.002	0.562 $\pm$ 0.003
Wine Quality White	C	0.536	0.524 $\pm$ 0.001	0.524 $\pm$ 0.001	0.437 $\pm$ 0.015	0.516 $\pm$ 0.032	0.533 $\pm$ 0.010	0.529 $\pm$ 0.002	0.534 $\pm$ 0.019	0.507 $\pm$ 0.025	0.536 $\pm$ 0.010	0.553 $\pm$ 0.002
SpamBase	C	0.927	0.924 $\pm$ 0.001	0.920 $\pm$ 0.001	0.885 $\pm$ 0.030	0.917 $\pm$ 0.001	0.922 $\pm$ 0.003	0.922 $\pm$ 0.003	0.922 $\pm$ 0.005	0.912 $\pm$ 0.016	0.932 $\pm$ 0.001	0.936 $\pm$ 0.002
AP-omentum-ovary	C	0.845	0.845 $\pm$ 0.001	0.814 $\pm$ 0.001	0.710 $\pm$ 0.134	0.845 $\pm$ 0.125	0.845 $\pm$ 0.001	0.845 $\pm$ 0.001	0.849 $\pm$ 0.001	0.833 $\pm$ 0.031	0.845 $\pm$ 0.002	0.883 $\pm$ 0.001
Lymphography	C	0.141	0.108 $\pm$ 0.001	0.129 $\pm$ 0.009	0.144 $\pm$ 0.132	0.150 $\pm$ 0.133	0.170 $\pm$ 0.035	0.174 $\pm$ 0.040	0.182 $\pm$ 0.013	0.150 $\pm$ 0.116	0.267 $\pm$ 0.035	0.410 $\pm$ 0.105
MNIST fashion	C	0.712	0.714 $\pm$ 0.001	0.716 $\pm$ 0.001	0.510 $\pm$ 0.020	0.699 $\pm$ 0.022	0.710 $\pm$ 0.002	0.711 $\pm$ 0.004	0.728 $\pm$ 0.001	0.717 $\pm$ 0.002	0.729 $\pm$ 0.001	0.735 $\pm$ 0.001
Housing Boston	R	0.415	0.420 $\pm$ 0.031	0.418 $\pm$ 0.001	0.021 $\pm$ 0.002	0.423 $\pm$ 0.005	0.424 $\pm$ 0.002	0.421 $\pm$ 0.011	0.404 $\pm$ 0.007	0.381 $\pm$ 0.017	0.465 $\pm$ 0.006	0.538 $\pm$ 0.005
Airfoil	R	0.519	0.520 $\pm$ 0.001	0.519 $\pm$ 0.001	0.207 $\pm$ 0.065	0.509 $\pm$ 0.001	0.519 $\pm$ 0.002	0.521 $\pm$ 0.001	0.521 $\pm$ 0.003	0.558 $\pm$ 0.002	0.627 $\pm$ 0.011	0.645 $\pm$ 0.001
Openml_589	R	0.510	0.548 $\pm$ 0.032	0.610 $\pm$ 0.001	0.034 $\pm$ 0.079	0.509 $\pm$ 0.002	0.506 $\pm$ 0.004	0.502 $\pm$ 0.002	0.627 $\pm$ 0.006	0.463 $\pm$ 0.005	0.656 $\pm$ 0.001	0.660 $\pm$ 0.006
Openml_618	R	0.469	0.444 $\pm$ 0.026	0.543 $\pm$ 0.039	0.030 $\pm$ 0.076	0.473 $\pm$ 0.002	0.471 $\pm$ 0.004	0.472 $\pm$ 0.001	0.562 $\pm$ 0.101	0.408 $\pm$ 0.036	0.692 $\pm$ 0.002	0.693 $\pm$ 0.001
Openml_620	R	0.510	0.494 $\pm$ 0.019	0.541 $\pm$ 0.008	0.026 $\pm$ 0.013	0.520 $\pm$ 0.001	0.509 $\pm$ 0.005	0.513 $\pm$ 0.004	0.568 $\pm$ 0.013	0.442 $\pm$ 0.004	0.643 $\pm$ 0.003	0.652 $\pm$ 0.003

* We evaluated classification (C) and regression (R) tasks in terms of F1-Score and 1-RAE, respectively.

* The standard deviation is computed based on the results of 5 independent runs.

**Figure 3: The influence of hierarchical modeling (PHER^c), permutation invariance (PHER^p), and policy-guided search (PHER^g) in PHER.**

4.2 Baseline Models

We compare our method with nine widely-used feature transformation methods: (1) RDG generates new feature-operation-feature transformation records by randomly selecting candidate features and operations. (2) ERG first applies operations to each feature to expand the feature space and then selects informative features as new features. (3) LDA [2] is a generative probabilistic model that reduces dimensionality by learning latent topic representations. (4) AFAT [10] iteratively applies transformations and performs multi-step feature selection to identify informative ones. (5) NFS [3] uses a recurrent neural network-based controller trained with reinforcement learning to sequentially model and optimize the transformation process for each feature. (6) TTG [16] formulates feature transformation as a graph exploration problem and employs reinforcement learning to discover optimal transformation paths within the graph. (7) GRFG [31] employs three reinforced agents with a feature grouping strategy to perform feature generation in a cascaded manner. (8) DIFER [39] encodes randomly generated transformation sequences into a continuous embedding space and employs greedy

gradient-based search to identify the best transformed features. (9) MOAT [32] embeds RL-collected transformation sequences into continuous embeddings using postfix expression and conducts gradient-ascent search with the beam search strategy. Besides, we developed three variants of PHER to evaluate the impact of each technical component: (i) PHER^c removes the concept encoder and decoder. (ii) PHER^p replaces the permutation-invariant concept encoder and decoder with permutation-sensitive self-attention layers. (iii) PHER^g replaces the RL search with Genetic Algorithm (GA).

4.3 Performance Evaluation

4.3.1 Overall Performance. Table 1 reports the performance comparison between PHER and baseline models across 19 datasets, using F1-score for classification tasks and 1-RAE for regression tasks. All experimental results are obtained by independently running five times with different random seeds, showing that PHER outperforms the other baseline models on all datasets. There are three potential reasons for this observation: 1) The hierarchical modeling architecture captures both low-level and high-level relationships




Figure 4: Robustness check of PHER with distinct ML models on SpamBase in terms of F1-score.




Figure 5: The influence of search seeds.




Figure 6: Model scalability comparison between our method and the SOTA model MOAT.

between features, encoding diverse feature transformation knowledge and building a more informative global embedding space; 2) The permutation-invariant concept encoder-decoder framework eliminates order sensitivity among concepts, constructing a global unbiased embedding space; 3) The policy-based RL agent effectively explores the global embedding space and identifies superior feature transformation embeddings, navigating the non-convex space more robustly than gradient-based methods and converging to higher-quality embedding regions. Thus, this experiment demonstrates the effectiveness of our proposed framework in transforming feature spaces across various types of tasks.

4.3.2 Ablation Study. We design three model variants of PHER to study the contribution of each component: 1) PHER^c removes the concept encoder-decoder model; 2) PHER^p replaces the concept encoder and decoder with permutation-sensitive self-attention layers; 3) PHER^g replaces the policy-guided search with Genetic Algorithm (GA). We select two classification tasks (SpectF, PimaIndian) and two regression tasks (Openml_589, Openml_620), evaluating each from four perspectives (F1-score, Precision, Recall, ROC/AUC for classification; 1-RAE, 1-MAE, 1-MSE, 1-RMSE for regression). As shown in Figure 3, PHER consistently outperforms all variants, confirming that: 1) the hierarchical modeling module captures both low-level feature relationships and high-level concepts, preserving more informative feature transformation knowledge within the global embedding space; 2) the permutation-invariant mechanism removes permutation noise among generated concepts in the embedding space, facilitating more effective exploration by the RL agent. 3) the RL agent conducts effective exploration in the embedding space, eliminating the reliance on convexity assumptions and

reducing the likelihood of convergence to local optima. Thus, this experiment shows the significance of each component in PHER.

4.3.3 Robustness Check. We evaluate PHER using various downstream ML models, including Random Forest (RF), XGBoost (XGB), K-Nearest Neighborhood (KNN), and Decision Tree (DT), to assess the robustness of PHER. Figure 4 shows the comparison results on SpamBase in terms of the F1-score. We observed that PHER consistently outperforms all baseline methods across different downstream ML models. A potential reason for this observation is that the RL-based data collector explores diverse feature transformation records guided by validation performance rather than any specific classifier. These records further enable the hierarchical model to encode task-relevant knowledge and characteristics into the global embedding space. Finally, the policy-guided agent leverages these records to effectively search the learned global embedding space, enabling the identification of high-quality feature transformation sequences that generalize well across different downstream classifiers. Thus, this experiment evaluates the robustness of PHER.

4.3.4 Search Seeds. To observe the impacts of search seeds on the RL-based search process, we replace the top K historical feature transformation records with K random records. We conduct this experiment on eight randomly chosen datasets and report the average F1-score over five independent runs. As shown in Figure 5, search initialized with high-quality seeds consistently outperforms search with random initialization. A potential reason for this observation is that the RL agent can leverage informative seeds to anchor the search within promising regions of the embedding space, effectively narrowing the search scope and accelerating convergence. In




Figure 7: Visualization of global embeddings obtained from original and permuted concept embeddings.




Figure 8: Hyperparameter sensitivity.




Figure 9: Comparison of traceability on the original feature set and selected feature subset.

contrast, random starting points increase the risk of being trapped in local optima, resulting in an unstable search process and sub-optimal feature transformation sequences. Thus, this experiment demonstrates the significance of the search seeds in our framework.

4.3.5 Model Scalability. To analyze model scalability, we compare the length of feature transformation sequences and downstream task performance of PHER and the SOTA model MOAT. From Figure 6 (a), we observe that PHER produces significantly shorter feature transformation sequences, showing its ability to discover compact and effective feature transformation sequences. From Figure 6 (b), we find that PHER consistently outperforms MOAT across all datasets. These observations suggest that the RL agent in PHER effectively optimizes the learned embeddings by jointly maximizing task performance and minimizing transformation sequence length. Thus, this experiment demonstrates that PHER consistently achieves strong performance and compactness across diverse datasets, highlighting the scalability of PHER.

4.3.6 Permutation Sensitivity. We conduct this experiment to study the permutation sensitivity of learned global embeddings by visualizing embeddings derived from original and permuted concept sets on four datasets. For each dataset, we randomly choose five samples as representatives and further permute the concept embedding of each sample 20 times. Specifically, for each example, we first obtain its concept embedding set and create multiple permuted

variants by randomly shuffling the order of the concept embeddings. Both the original and permuted concept embedding sets are then passed through the trained concept encoder to obtain their global embeddings. Thereafter, we visualize these embeddings using t-SNE. Figure 7 shows the visualization results, where each color represents the global embedding of one concept embedding set together with the embeddings derived from its permuted variants. We find that the global embeddings derived from permuted orders consistently cluster around the original embedding. This is because the self-attention pooling in ϕ_{con} computes a weighted aggregation over all concept embeddings, where the attention weights depend solely on the content similarity between fixed learnable seed queries and concept embeddings rather than their positions. Since weighted summation is a commutative operation, reordering the input concepts yields an identical global embedding, thereby eliminating permutation noise. Therefore, this experiment confirms that our proposed hierarchical encoder-decoder effectively eliminates permutation bias, which is consistent with the theoretical property of the self-attention pooling mechanism.

4.3.7 Hyperparameter Sensitivity Analysis. We assess the hyperparameter sensitivity of PHER on the SpectF dataset by varying the clipping ratio ϵ and the reward trade-off λ from 0.1 to 0.9, where ϵ stabilizes training by controlling the magnitude of policy updates and λ balances task performance against transformation sequence length. Figure 8 demonstrates the overall experimental

results in terms of Precision, Recall and F1-Score. We found that PHER achieves optimal performance when $\epsilon = 0.2$ and $\lambda = 0.9$. This aligns with prior PPO studies, where $\epsilon = 0.2$ is a setting widely adopted in standard reinforcement learning benchmarks [27]. Furthermore, we found that the model performance remains relatively stable across a broad range of λ , with slight improvements as λ approaches 0.9. Therefore, this experiment demonstrates the sensitivity of our framework to hyperparameter settings and provides practical guidance on hyperparameter configuration.

4.3.8 Traceability Case Study. We conduct this experiment to evaluate the traceability of PHER. We rank the top 10 most significant features for prediction in both the original feature set and PHER generated feature set of the Wine Quality Red dataset. Figure 9 visualizes the experiment results, where a larger bar indicates higher feature importance. We observed that approximately 70% of the crucial features in the new feature set are generated by PHER. The newly generated feature space enhances the downstream ML performance by 23.7%. There are two potential reasons for this observation: 1) the hierarchical modeling module in PHER effectively captures the inherent hierarchical relationships from low-level features and operations to high-level concepts. 2) the policy-guided multi-objective search strategy effectively explores the learned global embedding space and identifies the superior feature transformation sequence, overcoming the non-convex challenge and converging to the global optimal embedding point. Furthermore, we found that '[alcohol]' is the most important feature in the original set. This aligns with domain knowledge, as alcohol is known to be one of the most influential factors in determining red wine quality. PHER not only identifies this essential feature but also generates a variety of composited features based on '[alcohol]', which further enhance the predictive performance. This observation demonstrates that PHER is capable of identifying the importance of individual features while also deriving new informative representations that align with domain semantics and enhance downstream performance. Such new informative features empower domain experts to trace the origins of transformed features and derive novel analytical rules for assessing red wine quality. Thus, this case study shows the traceability and interpretability of PHER.

5 Related Works

Automated Feature Transformation (AFT) aims to enhance the tabular feature space by systematically applying mathematical operations to original features, thereby improving feature expressiveness and downstream predictive performance [4, 18]. Existing methods can be broadly categorized into three main classes. 1) expansion-reduction based approaches [10, 12, 15, 17, 19] first expand the feature space by enumerating candidate features through predefined mathematical transformations, and subsequently reduce dimensionality via feature selection or pruning strategies. While effective for capturing simple feature interactions, these methods rely on shallow compositions and heuristic selection criteria, making it difficult to represent complex, multi-step feature transformations, which often leads to suboptimal performance in practice. 2) evolution-evaluation approaches [14, 16, 28, 31, 36, 38]

integrate feature generation and selection into a closed-loop optimization framework. By leveraging evolutionary algorithms or reinforcement learning (RL), these methods iteratively explore transformation operators and retain features that improve validation performance. Despite their flexibility, such approaches typically suffer from high computational cost and unstable optimization behavior, largely due to discrete decision-making and the combinatorial nature of the transformation space. 3) Auto ML-based approaches [1, 6–9, 13, 21, 26, 30, 33, 37] formulate AFT as part of a broader AutoML pipeline, jointly searching for feature transformation strategies and model configurations. A representative example is [32], which embeds RL-collected feature transformation sequences into a continuous representation using postfix expressions and applies gradient-ascent beam search to identify informative transformation embeddings. However, such methods are limited by: 1) overlooking intricate hierarchical relationships inherent in feature transformation knowledge; 2) encoding feature transformation sequences as order-sensitive; 3) relying on the convexity assumption of the embedding space. To address these drawbacks, PHER combines permutation-invariant hierarchical modeling and multi-objective policy-guided search. The permutation-invariant hierarchical modeling module captures both token-level and concept-level feature transformation knowledge and mitigates order sensitivity among concepts, creating an unbiased global embedding space. The multi-objective policy-guided search effectively explores the learned embedding space, identifying better feature transformation sequences without relying on any convexity assumptions.

6 Conclusion Remarks

In this paper, we propose a hierarchical feature transformation framework PHER that integrates permutation-invariant hierarchical modeling and multi-objective policy-guided search. In detail, we first develop a permutation-invariant hierarchical modeling module, including token-level and concept-level encoder-decoder models, to preserve feature transformation knowledge at both the feature-operation token level and the generated concept level into a global embedding space. Within this module, we develop a self-attention pooling mechanism that symmetrically computes attention scores across all generated concepts to ensure permutation invariance. Then, we employ a multi-objective search strategy to explore the learned embedding space, overcoming the reliance on convexity assumptions and mitigating the risk of being trapped in local optima. Finally, extensive experiments demonstrate several key insights: 1) the hierarchical modeling structure significantly captures meaningful hierarchical interactions, enhancing the expressivity of the learned embedding space. 2) the permutation-invariant module effectively mitigates order sensitivity, stabilizing the embedding space learning and search processes. 3) the policy-guided RL search enables effective exploration, mitigating the risk of convergence to local optima and improving search robustness. These findings highlight the importance of permutation-invariant hierarchical modeling and robust exploration strategies for advancing automated feature transformation. For future research, a promising direction is to improve the computational efficiency and scalability of PHER, possibly by integrating a lightweight concept modeling framework or refining the RL-based search strategy in the embedding space.

GenAI Usage Disclosure

Generative AI tools were used only for language polishing, grammar refinement, and auxiliary code assistance, including code editing and debugging suggestions. All research ideas, experimental designs, code, data processing, analyses, and final manuscript content were created, verified, and approved by the authors.

References

- [1] Maroua Bahri, Flavia Salutati, Andrian Putina, and Mauro Sozio. 2022. Automl: state of the art with a focus on anomaly detection, challenges, and research directions. *International Journal of Data Science and Analytics* 14, 2 (2022), 113–126.
- [2] David M Blei, Andrew Y Ng, and Michael I Jordan. 2003. Latent dirichlet allocation. *the Journal of machine Learning research* 3 (2003), 993–1022.
- [3] Xiangning Chen, Qingwei Lin, Chuan Luo, Xudong Li, Hongyu Zhang, Yong Xu, Yingnong Dang, Kaixin Sui, Xu Zhang, Bo Qiao, et al. 2019. Neural feature search: A neural architecture for automated feature engineering. In *2019 IEEE International Conference on Data Mining (ICDM)*. IEEE, 71–80.
- [4] Yi-Wei Chen, Qingquan Song, and Xia Hu. 2021. Techniques for automated machine learning. *ACM SIGKDD Explorations Newsletter* 22, 2 (2021), 35–50.
- [5] Lin Chih-Jen. 2022. LibSVM Dataset Download. [EB/OL]. <https://www.csie.ntu.edu.tw/~cjlin/libsvmtools/datasets/>.
- [6] Ofer Dor and Yoram Reich. 2012. Strengthening learning algorithms by feature discovery. *Information Sciences* 189, 176–190.
- [7] Ofer Egozi, Evgeniy Gabrilovich, and Shaul Markovitch. 2008. Concept-Based Feature Generation and Selection for Information Retrieval.. In *AAAI*, Vol. 8. 1132–1137.
- [8] Thomas Elsken, Jan Hendrik Metzen, and Frank Hutter. 2019. Neural architecture search: A survey. *The Journal of Machine Learning Research* 20, 1 (2019), 1997–2017.
- [9] Xin He, Kaiyong Zhao, and Xiaowen Chu. 2021. AutoML: A survey of the state-of-the-art. *Knowledge-Based Systems* 212 (2021), 106622.
- [10] Franziska Horn, Robert Pack, and Michael Rieger. 2019. The autofeat python library for automated feature engineering and selection. *arXiv preprint arXiv:1901.07329* (2019).
- [11] Jeremy Howard. 2022. Kaggle Dataset Download. [EB/OL]. <https://www.kaggle.com/datasets>.
- [12] James Max Kanter and Kalyan Veeramachaneni. 2015. Deep feature synthesis: Towards automating data science endeavors. In *2015 IEEE international conference on data science and advanced analytics (DSAA)*. IEEE, 1–10.
- [13] Shubhra Kanti Karmaker, Md Mahadi Hassan, Micah J Smith, Lei Xu, Chengxiang Zhai, and Kalyan Veeramachaneni. 2021. Automl to date and beyond: Challenges and opportunities. *ACM Computing Surveys (CSUR)* 54, 8 (2021), 1–36.
- [14] Gilad Katz, Eui Chul Richard Shin, and Dawn Song. 2016. Explorekit: Automatic feature generation and selection. (2016), 979–984.
- [15] Udayan Khurana, Fatemeh Nargesian, Horst Samulowitz, Elias Khalil, and Deepak Turaga. 2016. Automating feature engineering. *Transformation* 10, 10 (2016), 10.
- [16] Udayan Khurana, Horst Samulowitz, and Deepak Turaga. 2018. Feature engineering for predictive modeling using reinforcement learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, Vol. 32.
- [17] Udayan Khurana, Deepak Turaga, Horst Samulowitz, and Srinivasan Parthasarathy. 2016. Cognito: Automated feature engineering for supervised learning. In *2016 IEEE 16th International Conference on Data Mining Workshops (ICDMW)*. IEEE, 1304–1307.
- [18] Andrew Kusiak. 2001. Feature transformation methods in data mining. *IEEE Transactions on Electronics packaging manufacturing* 24, 3 (2001), 214–221.
- [19] Hoang Thanh Lam, Johann-Michael Thiebaud, Mathieu Sinn, Bei Chen, Tiep Mai, and Ozgur Alkan. 2017. One button machine for automating feature engineering in relational databases. *arXiv preprint arXiv:1706.00327* (2017).
- [20] Juho Lee, Yoonho Lee, Jungtaek Kim, Adam Kosiorek, Seungjin Choi, and Yee Whye Teh. 2019. Set Transformer: A Framework for Attention-based Permutation-Invariant Neural Networks. In *Proceedings of the 36th International Conference on Machine Learning (Proceedings of Machine Learning Research, Vol. 97)*, Kamalika Chaudhuri and Ruslan Salakhutdinov (Eds.). PMLR, 3744–3753. <https://proceedings.mlr.press/v97/lee19d.html>
- [21] Yaliang Li, Zhen Wang, Yuexiang Xie, Bolin Ding, Kai Zeng, and Ce Zhang. 2021. Automl: From methodology to application. In *Proceedings of the 30th ACM International Conference on Information & Knowledge Management*. 4853–4856.
- [22] Rui Liu, Rui Xie, Zijun Yao, Yanjie Fu, and Dongjie Wang. 2025. Continuous Optimization for Feature Selection with Permutation-Invariant Embedding and Policy-Guided Search. In *Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining V.2 (Toronto ON, Canada) (KDD '25)*. Association for Computing Machinery, New York, NY, USA, 1857–1866. doi:10.1145/3711896.3736891
- [23] Rui Liu, Tao Zhe, Yanjie Fu, Feng Xia, Ted Senator, and Dongjie Wang. 2026. Permutation-Invariant Representation Learning for Robust and Privacy-Preserving Feature Selection. *arXiv:2510.05535 [cs.LG]* <https://arxiv.org/abs/2510.05535>
- [24] Public. 2022. Openml Dataset Download. [EB/OL]. <https://www.openml.org>.
- [25] Public. 2022. UCI Dataset Download. [EB/OL]. <https://archive.ics.uci.edu/>.
- [26] Kezhou Ren, Yifan Zeng, Yuanfu Zhong, Biao Sheng, and Yingchao Zhang. 2023. MAFSIDS: a reinforcement learning-based intrusion detection model for multi-agent feature selection networks. *Journal of Big Data* 10, 1 (2023), 137.
- [27] John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. 2017. Proximal Policy Optimization Algorithms. *arXiv:1707.06347 [cs.LG]* <https://arxiv.org/abs/1707.06347>
- [28] Binh Tran, Bing Xue, and Mengjie Zhang. 2016. Genetic programming for feature construction and selection in classification on high-dimensional data. *Memetic Computing* 8, 1 (2016), 3–15.
- [29] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. In *Proceedings of the 31st International Conference on Neural Information Processing Systems (Long Beach, California, USA) (NIPS'17)*. Curran Associates Inc., Red Hook, NY, USA, 6000–6010.
- [30] Dakuo Wang, Josh Andres, Justin D Weisz, Erick Oduor, and Casey Dugan. 2021. Autods: Towards human-centered automation of data science. In *Proceedings of the 2021 CHI Conference on Human Factors in Computing Systems*. 1–12.
- [31] Dongjie Wang, Yanjie Fu, Kunpeng Liu, Xiaolin Li, and Yan Solihin. 2022. Group-Wise Reinforcement Feature Generation for Optimal and Explainable Representation Space Reconstruction. In *Proceedings of the 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining (Washington DC, USA) (KDD '22)*. Association for Computing Machinery, New York, NY, USA, 1826–1834.
- [32] Dongjie Wang, Meng Xiao, Min Wu, Yuanchun Zhou, and Yanjie Fu. 2023. Reinforcement-enhanced autoregressive feature transformation: Gradient-steered search in continuous space for postfix expressions. *Advances in Neural Information Processing Systems* 36 (2023).
- [33] Marcel Wever, Alexander Tornede, Felix Mohr, and Eyke Hüllermeier. 2021. AutoML for multi-label classification: Overview and empirical evaluation. *IEEE transactions on pattern analysis and machine intelligence* 43, 9 (2021), 3037–3054.
- [34] Wangyang Ying, Dongjie Wang, Haifeng Chen, and Yanjie Fu. 2024. Feature selection as deep sequential generative learning. *ACM Transactions on Knowledge Discovery from Data* 18, 9 (2024), 1–21.
- [35] Wangyang Ying, Dongjie Wang, Xuanming Hu, Yuanchun Zhou, Charu C Aggarwal, and Yanjie Fu. 2024. Unsupervised generative feature transformation via graph contrastive pre-training and multi-objective fine-tuning. In *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*. 3966–3976.
- [36] Yao Zhang, Yun Xiong, Yiheng Sun, Caihua Shan, Tian Lu, Hui Song, and Yangyong Zhu. 2022. RuDi: Explaining Behavior Sequence Models by Automatic Statistics Generation and Rule Distillation. (2022), 2651–2660.
- [37] Ziwei Zhang, Xin Wang, and Wenwu Zhu. 2021. Automated machine learning on graphs: A survey. *arXiv preprint arXiv:2103.00742* (2021).
- [38] Guanghui Zhu, Shen Jiang, Xu Guo, Chunfeng Yuan, and Yihua Huang. 2022. Evolutionary Automated Feature Engineering. In *PRICAI 2022: Trends in Artificial Intelligence: 19th Pacific Rim International Conference on Artificial Intelligence, PRICAI 2022, Shanghai, China, November 10–13, 2022, Proceedings, Part I*. Springer, 574–586.
- [39] Guanghui Zhu, Zhuoer Xu, Chunfeng Yuan, and Yihua Huang. 2022. DIFER: differentiable automated feature engineering. In *International Conference on Automated Machine Learning*. PMLR, 17–1.