
When Agents Implement Systems: A Case Study in Defects, Detection, and Evaluation Rigor

Phanindra Reddy Madduru
Amazon.com
maddurup@amazon.com

Abstract

As LLM coding agents increasingly perform end-to-end engineering work rather than single-function code completion, we lack empirical characterization of how they behave when implementing genuinely *systems*-level requirements: a storage schema, concurrency and async orchestration, cross-process configuration correctness, and a retrieval-filtering precision trade-off. We present a case study of an LLM coding agent implementing a multi-component data system (a persistent graph store, a filtered vector index, an async ingestion pipeline, and a real-time visualization client) against a detailed pre-existing specification — storage technologies, schema, entity-resolution algorithm, and retrieval-filtering strategy fixed in advance; the agent’s autonomy was in the implementation, in diagnosing and fixing defects it introduced while building to that spec, and in interaction-design choices the spec left open. Over a single extended session, we catalog five such defects, categorized by which systems constraint each violates and by whether it was caught by automated testing or only by empirical probing (rendered screenshots, timing measurements) with no type-level or static signature. We further evaluate, on a public multi-hop QA benchmark (HotpotQA, distractor setting), the one retrieval trade-off specified in that architecture — restricting candidates to a graph-identified entity set before ranking, versus unfiltered semantic search — reusing the benchmark’s gold evidence labels as a stand-in for entity identification (which we did not have LLM access to run in this session) and for a standard information-retrieval recall metric rather than the benchmark’s own answer-accuracy metrics. Across $k \in \{1, 3, 5, 10\}$ and $n = 100$ questions against a 2,994-paragraph pooled corpus, filtered recall reaches 1.0 by $k = 3$ — expected once candidates are restricted to the gold-titled paragraphs themselves — while unfiltered search recovers all required evidence only 69% of the time even at $k = 10$, a gap that holds at every k (sign test, $p < 10^{-4}$). We close with a candid discussion of where the agent’s autonomy succeeded versus required human correction, including one instance where a claimed performance fix was never re-measured on the regression that motivated it — an unverified engineering claim that the self-reported development loop, in this instance, had no mechanism to catch.

1 Introduction

LLM coding agents are increasingly deployed not for isolated code completion but for open-ended, multi-file engineering work: implementing data models, wiring asynchronous job queues, and debugging failures that only manifest at runtime. Existing evaluations of agentic coding largely score whether an agent resolves a pre-specified, bounded issue in an existing codebase [4], and existing agent architectures for combining reasoning with tool use (retrieval, code execution) are evaluated on task success rate [5]. Neither setting captures a different failure mode: an agent given a detailed specification for a multi-component system, building it end to end across many files and pipeline

stages, and introducing — then having to diagnose and fix — its own systems-level defects along the way. This shifts the relevant evaluation question from “does the generated function pass its unit test” to “does the agent behave reliably when implementing systems engineering under the constraints systems engineers actually face” — consistency across a schema shared by multiple call sites, correctness of idempotent storage operations under repeated execution, reliability of configuration that must resolve identically regardless of which process launches it, and precision trade-offs in retrieval filtering. ML-driven systems design has an established track record when the target is a well-specified optimization problem, such as learned chip placement [6]; our case study instead concerns implementation reliability against a specification that is itself fixed and detailed — whether an agent introduces, and can self-correct, systems-level defects while building to it.

We report an observational case study: a single LLM coding agent (Claude, operated via a CLI coding tool) implemented a multi-component data system end to end — a persistent, schema-driven graph store; a metadata-filtered vector index; an asynchronous multi-stage ingestion pipeline; and a force-directed graph visualization client — against a detailed pre-existing specification (Section 2). Over the course of the session, five defects were introduced by the agent’s own implementation work and later diagnosed and fixed, either by the agent proactively or in response to a user-reported symptom. We treat this transcript as data: we categorize each defect by which systems constraint it violates — reliability, correctness, consistency, or efficiency — and by how it was actually caught (automated test vs. empirical/visual probing). We then evaluate one specified engineering trade-off in that architecture — filtering retrieval candidates by a graph-identified entity set before ranking, versus unfiltered semantic search — quantitatively on a public external benchmark, rather than the internal corpus the case-study system was originally developed against.

We are explicit about what this paper is not: graph-guided retrieval filtering is not new — it is established in the retrieval-augmented generation and GraphRAG literature [2, 3]. The contribution is Section 3’s defect catalog; Section 4’s benchmark is one reproducible illustration of a specified trade-off, not a new retrieval technique.

Contributions: (1) a catalog of five systems defects introduced during spec-directed implementation and later diagnosed and fixed by the implementing agent, categorized by constraint type and detection method; (2) an externally-benchmarked evaluation, with a significance test and a k -sweep, of one specified retrieval-filtering trade-off in that architecture; (3) a candid discussion of an evaluation-rigor gap the agent itself exhibited — claiming a fix without re-measuring the regression it targeted — and what it implies for trusting an autonomous agent’s self-reported engineering claims.

2 Case Study System and Methodology

The target system is a multi-component data pipeline with four parts relevant to systems evaluation, independent of its application domain: (i) a graph store (embedded relational database, full-text fuzzy lookup, a recursive multi-hop traversal query, write-ahead-log concurrency), in the same graph-based-system family as prior heterogeneous-graph deployments [7]; (ii) a vector index with metadata-based candidate filtering; (iii) an asynchronous ingestion pipeline (multi-stage extract/resolve/embed/link, orchestrated over a task queue) required to be idempotent under repeated execution, the same ingestion-scalability concern addressed for graph databases more broadly [9]; and (iv) a force-directed graph rendering client, in the same graph-visualization space as prior explainability tooling [8].

A pre-existing design document fixed the storage technologies, schema, entity-resolution algorithm, and retrieval-filtering strategy Section 4 evaluates; left to the agent were the implementation itself, the defects it introduced (Section 3), and interaction-design details beyond the mandated technology choices. The methodology for this paper is observational: we log every defect with a directly attributable code diff and observable symptom surfaced during development or subsequent use, the diagnostic path that led to its root cause, and the fix, drawing only on artifacts already produced during the session (code diffs, test output, screenshots, timing) rather than a protocol decided in advance.

3 Observed Defects, Categorized by Systems Constraint

Table 1 summarizes five defects, spanning four systems constraints; two instances share the correctness category but manifest at different layers (storage-layer idempotency vs. render-time visual output). We discuss the two most instructive below.

Constraint	Defect	Caught by	Fix locus
Reliability	Config path resolution depended on process launch directory; broke only for a non-default entrypoint	Runtime exception, one entrypoint only	Centralized, anchored to module location, not caller cwd
Correctness (storage)	Storage upsert keyed on randomly generated IDs; idempotency claim violated under re-execution	Repeated-execution test added after the fact	Deterministic IDs derived from stable inputs
Consistency	Graph traversal returned edges in both directions but only fetched endpoint nodes in one direction	Client-side runtime crash (rendering library)	Explicit endpoint backfill; recurred at a second call site
Efficiency	Sequential per-stage network calls; wall-clock cost scaled with input size with no concurrency	User-observed latency	Bounded concurrent execution
Correctness (rendering)	Screen-space label size computed with a lower bound that broke an intended scale-cancellation	Automated screenshot comparison; no static signature	Removed the erroneous bound

Table 1: Defects introduced and fixed during implementation, categorized by the constraint each violates and by how each was actually detected.

Consistency defect, recurring across call sites. The graph traversal component followed only outgoing edges when expanding a node’s neighborhood, while a separate function collecting edges for the same node returned edges in both directions. The result: an edge could be returned whose endpoint node was never included in the node set handed to a downstream consumer. This was invisible to the type system and to the existing test suite (which asserted on returned edges, not the joint node/edge consistency invariant), manifesting only as a runtime crash in an unrelated client — a force-directed rendering library — resolving a link’s endpoint missing from its node array. The same pattern was independently reintroduced at a second call site (an HTTP endpoint exposing the same operation) before the invariant was made explicit and tested directly.

Rendering correctness defect, caught only visually. A canvas label was sized as $\max(c, b/s)$ for on-screen constant b , current zoom s , and floor c , intending scale-invariant text size. The floor broke the intended cancellation: once s exceeded b/c , the floored value was re-multiplied by the zoom transform on render, producing screen-filling text. No static check could catch this: it is a purely runtime, visual effect with no failing assertion short of rendering a frame and measuring pixels. It was caught only by an automated screenshot comparison during otherwise unrelated interaction testing.

4 A Specified Retrieval Trade-off: External Benchmark Evaluation

The case-study architecture specifies one retrieval trade-off precisely enough to benchmark externally: restrict vector-retrieval candidates to a graph-identified entity set before ranking (*filtered*), versus rank the full corpus by embedding similarity alone (*unfiltered*, the standard RAG setting [2]) — filtering narrows the search space using structural information, in the spirit of graph-augmented retrieval [3], at the cost of depending on correct upstream entity identification.

We evaluate this decision on HotpotQA (distractor setting) [1], a public multi-hop QA benchmark whose distractor paragraphs are specifically constructed to be lexically similar to the gold evidence, making it a natural stress test for this exact trade-off. **We emphasize what this evaluation is not:** we do not reproduce HotpotQA’s own benchmark task or its published answer-EM/F1 and supporting-fact-EM/F1 metrics, and our numbers are not comparable to any leaderboard entry for that dataset. We reuse only its raw paragraphs and gold supporting-fact labels as ground truth for a narrower, standard information-retrieval question: given a fixed corpus and a fixed embedder, does restricting candidates to a known-relevant entity set change whether the retriever surfaces the gold evidence paragraph(s)?

We pool the context paragraphs from 300 randomly sampled validation questions (2,994 paragraphs total) into one shared corpus, using each paragraph’s Wikipedia article title as its entity identifier (no LLM extraction required: HotpotQA paragraphs are single-entity by construction). The first 100 of these 300 questions serve as our evaluation set, so each evaluation question’s distractor pressure comes from the full 2,994-paragraph pool, not just its own 10 context paragraphs. For each evaluation question we compare an **unfiltered** condition (top- k nearest paragraphs by cosine similarity over the entire pool) against a **filtered** condition (candidates restricted to paragraphs whose title is in the question’s gold supporting-fact title set — a stand-in for a correctly functioning entity-identification stage upstream — then ranked by similarity within that restricted set).

We report $\text{recall}@k$ against HotpotQA’s annotated supporting-fact paragraphs for $k \in \{1, 3, 5, 10\}$ (Table 2), the fraction of questions where *both* gold paragraphs are recovered (exact match), and a two-sided exact sign test on paired per-question recall differences. We did not have LLM access to run the full entity-identification stage in this session; the gold-title substitution isolates the retrieval-filtering decision itself, cleanly separated from entity-identification quality, which we flag as the main threat to generalizing these numbers to a fully automated pipeline.

	$k = 1$	$k = 3$	$k = 5$	$k = 10$
Mean $\text{recall}@k$, unfiltered	0.420	0.685	0.765	0.845
Mean $\text{recall}@k$, filtered	0.500	1.000	1.000	1.000
Exact match, unfiltered	0.000	0.410	0.540	0.690
Exact match, filtered	0.000	1.000	1.000	1.000
Sign test p (paired, per question)	3×10^{-5}	3×10^{-18}	3×10^{-14}	9×10^{-10}

Table 2: Retrieval evidence recovery, $n = 100$ HotpotQA validation questions, pooled corpus of 2,994 paragraphs (see text for interpretation).

Two results in Table 2 are informative; the rest follow near-tautologically from the design: the filtered candidate pool is exactly the two gold-titled paragraphs, always present in the corpus by construction, so any $k \geq 2$ recovers them regardless of ranking quality. The results *not* guaranteed by construction are (a) filtered $\text{recall}@1 = 0.500$, where ranking within the 2-paragraph pool still matters, and (b) the unfiltered condition’s shortfall, which does not close with a larger budget: exact match reaches only 69% at $k = 10$ — double the budget of the filtered condition’s already-100% $k = 5$ result — and every sign test rejects the null of no paired difference at $p < 10^{-4}$. This persistent unfiltered shortfall, not the filtered ceiling, is the finding: topically similar but wrong-entity evidence crowds out correct evidence under pure similarity ranking, and more retrieval budget does not fix it.

5 Discussion

Where autonomy succeeded vs. required correction. In two of five defects, the agent diagnosed the root cause from a single symptom and applied a structural fix rather than a local patch — centralizing configuration-path resolution, and generalizing the endpoint-backfill fix after recognizing the same pattern at a second call site. A related but uncatalogued issue (outside Table 1’s five) shows the opposite pattern: the visualization client’s initial design re-fetched and re-rendered on every click; a human caught this only through interactive testing, since each operation was locally correct and the failure was emergent.

An evaluation-rigor gap. The concurrency fix in Table 1 was motivated by a 242-second latency on an 18-chunk document. After parallelizing the affected stage, the agent validated the fix only on a smaller document, reporting it effective without re-measuring latency on the *same* input that motivated the fix — conflating “architecturally sound” with “verified on the regression it targets.”

Limitations: single-session, single-agent case study; no claim that defect frequencies generalize — including to smaller, more efficient models, whose capability trade-offs differ from the frontier-scale agent used here [10]; the retrieval ablation substitutes gold entity labels for query understanding, bounding only the filtering decision in isolation.

6 Conclusion

Several of the five cataloged defects had no static or type-level signature, caught only by empirical probing — arguing for execution-based, not just static, evaluation of agentic systems work. The isolated retrieval-trade-off benchmark and the unverified-fix case point to the same gap: nothing in this session’s development loop forced re-measurement against the regression a fix targeted, or against an external benchmark rather than self-report. The ablation script and its results (Table 2) are retained alongside this paper’s source so the retrieval-filtering comparison can be independently re-run.

References

- [1] Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William W. Cohen, Ruslan Salakhutdinov, and Christopher D. Manning. *HotpotQA: A Dataset for Diverse, Explainable Multi-hop Question Answering*. EMNLP 2018.
- [2] Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. *Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks*. NeurIPS 2020.
- [3] Darren Edge, Ha Trinh, Newman Cheng, Joshua Bradley, Alex Chao, Apurva Mody, Steven Truitt, and Jonathan Larson. *From Local to Global: A Graph RAG Approach to Query-Focused Summarization*. arXiv:2404.16130, 2024.
- [4] Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik Narasimhan. *SWE-bench: Can Language Models Resolve Real-World GitHub Issues?* ICLR 2024.
- [5] Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. *ReAct: Synergizing Reasoning and Acting in Language Models*. ICLR 2023.
- [6] Azalia Mirhoseini, Anna Goldie, Mustafa Yazgan, Joe Wenjie Jiang, Ebrahim Songhori, Shen Wang, Young-Joon Lee, Eric Johnson, Omkar Pathak, Azade Nazi, Jiwoo Pak, Andy Tong, Kavya Srinivasa, William Hang, Emre Tuncer, Quoc V. Le, James Laudon, Richard Ho, Roger Carpenter, and Jeff Dean. *A Graph Placement Methodology for Fast Chip Design*. Nature, 2021.
- [7] Phanindra Reddy Madduru and Naveed Janvekar. *A Heterogeneous Graph-Based Framework for Scalable Fraud Detection*. The 19th International Workshop on Mining and Learning with Graphs, KDD 2023, Long Beach, CA, USA.
- [8] Yudi Zhang, Naveed Janvekar, Phanindra Reddy Madduru, and Nitika Bhaskar. *Graph Model Explainer Tool*. The 19th International Workshop on Mining and Learning with Graphs, KDD 2023, Long Beach, CA, USA.
- [9] Phanindra Reddy Madduru and Bijio Thomas. *Optimizing Large-Scale Graph Database Ingestion Through Edge Value Ranking: A Proposed Framework*. Frontiers in Big Data 9:1768571, 2026. doi: 10.3389/fdata.2026.1768571.
- [10] Akanksha Gupta, Bijio Thomas, Harshita Asnani, Phanindra Reddy Madduru, Samia Feroze, Shreyas Subramanian, Vikram Elango, and Mecit Gungor. *Small Language Models (SLMs) Can Still Pack a Punch: A Survey*. arXiv preprint arXiv:2501.05465, 2025.