
The Era by Eon Benchmark: A Generated Enterprise Estate with Exact Ground Truth for Benchmarking LLM Agents

Benjamin Gruenbaum, Doron Porat, Assaf Natanzon
Roy Zavida, Chen Dinachi, Or Itzahary

Eon
assaf@eon.io

Abstract

LLM agents for enterprise systems of record cannot be evaluated on customer production data, and no existing substitute provides ground truth. We present the Era by Eon Benchmark for evaluating LLM agents that use enterprise tools. The benchmark is built around a complete fictional company. It includes product simulators, company-specific internal databases, benchmark questions, and computed answer keys. Industry, company size, business model, application portfolio, and a seed define each company. One seeded entity graph supplies shared company data to simulators of Salesforce, Zendesk, Slack, Gong, and other products. A question-conditioned generator creates the schemas and records for internal databases. It takes shared entities, keys, and values from the same graph before generating database-specific facts. Both mechanisms therefore describe one consistent enterprise estate. Every expected answer is computed from the final records, so grading is exact. Design and answer-key checks validate the internal databases. A realism scorecard and adversarial detector validate the entity graph. Across 23 generated companies, the mean realism score rose from 61.8 to 97.0, with zero records flagged as synthetic. In the reported simulator-track comparison, nine models answered the same 33 questions three times each. Accuracy estimates ranged from 42.4% to 76.8%, and three of 36 pairwise differences remained supported after correction.

1 Introduction

Developers of LLM agents that operate over enterprise systems of record, such as CRM, support, billing, communication, and document platforms, face a fundamental data-access problem. An agent must be developed and evaluated against data of the kind it will encounter in production, yet such data belongs to customers and is confidential. The available substitutes are inadequate: vendor sandboxes contain little data and no history; manually constructed test environments cover one or two systems and are costly to extend; and neither provides ground truth, so a developer can observe an agent’s behavior but cannot measure its accuracy.

Prior benchmarks address parts of this problem with hand-built environments. τ -bench [15] constructs two small domains (retail and airline) with manually authored databases and tools. CRMArena [3] and CRMArena-Pro [4] populate a single Salesforce organization from a hand-designed schema. TheAgentCompany [14] instantiates a fictional software firm across four self-hosted collaboration tools with manually authored tasks. WorkArena [2] and WorkArena++ [1] evaluate browser agents on a standard ServiceNow installation. These benchmarks are carefully engineered, and the present work builds on several of their design decisions. However, each covers at most a few systems, each

task set is manually authored or curated, extension requires substantial engineering effort, and the realism of the underlying data is asserted rather than measured.

This paper presents the Era by Eon Benchmark (hereafter the benchmark). It generates the evaluation environment in its entirety. Given four parameters, namely industry, company size, business model, and the set of business applications the company operates, together with a single random seed, the benchmark deterministically generates the shared entity graph of a complete fictional enterprise. The graph includes a workforce with an organizational hierarchy and employment history, a customer base, a sales pipeline, support tickets, recorded calls, chat messages, and documents. The same seed reproduces the identical dataset, which makes every evaluation exactly repeatable.

The generated company is served through product simulators. Each simulator implements the interface of a real product (Salesforce, Zendesk, Slack, Gong, S3, Google Drive, among others), and all simulators of one tenant are projections of a single underlying entity graph. The account that appears as a CRM opportunity is the same account referenced by a support ticket and a recorded call, under one join key, so questions that span systems are well defined by construction. Agents access the environment through each simulator’s MCP tools, and the data plane is read-only, which prevents an agent under evaluation from modifying the data against which it is graded.

The estate also contains databases for the fictional company’s own applications and analytics. No vendor fixes their schemas. The benchmark therefore uses a specialized question-conditioned generator for these databases. A benchmark author supplies business questions, a language model designs the required schema once, and deterministic code creates the records for each seed. The completed entity graph is an input to this process. Shared entities and attributes are copied from the graph. The generator creates only the facts specific to the internal application. A consistency check rejects any database whose shared keys or values disagree with the graph. The two mechanisms therefore populate the same company.

The benchmark computes every expected answer from the records an agent can access. Questions over product simulators come from code templates that are instantiated with the generated company’s entities. Questions over internal databases guide schema and record generation. The generator plants qualifying rows and near misses, then computes the final answer from all completed rows. Both mechanisms also support questions whose correct answer is that the requested information is absent.

The two generation mechanisms require different checks (Section 5). Internal databases have explicit column plans and planting directives. Their checks measure plan adherence, question specificity, label integrity, and dependency structure. The entity graph has no paired real company for comparison. Its realism is scored against targets from Eon’s operational data and published sources, and an adversarial detector searches for synthetic artifacts. The scorecard and detector guided revisions of the entity-graph generator. Across 23 generated companies, the mean realism score rose from 61.8 to 97.0, and the share of records flagged as synthetic fell from 55.2% to zero.

The contributions of this paper are: (1) a generator that produces a complete fictional estate spanning vendor applications and internal databases; (2) a specialized generator that turns internal-database questions into schemas, planted records, and exact answer keys; (3) validation methods scoped to each generation mechanism; and (4) a deterministic evaluation of nine models over 33 questions, with three repeats and paired statistical tests.

2 Related work

Enterprise agent benchmarks. τ -bench [15] grades agents on the final state of a hand-written database and introduces the pass^k metric for consistency across repeated trials; its authors report that most failures are errors of database reasoning rather than of conversation. CRMarena [3] populates a Salesforce organization from a hand-designed schema with latent variables, and generates its task instances with an LLM followed by human verification. CRMarena-Pro [4] extends the design to multi-turn interactions and confidentiality-awareness tests. TheAgentCompany [14] measures completion of long-horizon work tasks in a self-hosted office environment, where the best agent completes roughly a quarter of the tasks. WorkArena [2] and WorkArena++ [1] evaluate browser agents on ServiceNow with task templates over the product’s demo data. The benchmark differs from all of these in three respects: the environment spans many systems that share one entity graph rather than one system; the answers are computed from the generated records rather than maintained by

hand; and the realism of the data is measured rather than assumed. It also generates the schemas and records of company-specific databases from author-supplied business questions.

Text-to-SQL benchmarks. BIRD [7] showed that much of the difficulty of answering questions over real databases comes from the data itself, including inconsistent and dirty values, and includes questions that the database cannot answer, graded on abstention. Spider 2.0 [6] moved evaluation to enterprise warehouses, where schema size and dialect differences dominate. The benchmark adopts both lessons at generation time: controlled doses of dirty values are injected into the generated records, and labeled unanswerable questions are part of every benchmark.

Synthetic data fidelity. The Synthetic Data Vault [11] and its SDMetrics library define the standard metrics for synthetic data, all of which compare against the real dataset being imitated. Hudovernik et al. [5] show that detection by a strong classifier is the most discriminating evaluation for relational data, and that child tables are synthesized worse than parent tables. Zhang [16] shows that the commonly used linear classifier two-sample test [9] is nearly blind to dependencies between columns, since independently shuffled data passes it; the boosted-tree variant does not share this blindness. TabQueryBench [8] evaluates synthetic data by the analytical queries it can answer correctly and reports that the best generators recover only about 40% of rare values. Hollywood [12] generates a synthetic film database and argues its realism from the cardinality-estimation errors [10] it induces in a query optimizer, which are comparable to those induced by the real database. Synthea [13] generates synthetic patient records from published clinical statistics, and is the closest precedent for the benchmark’s approach of building realism from cited reference statistics rather than from training data. It operationalizes these results for a setting none of them addresses: benchmark data with no paired real counterpart.

3 One company, many systems

3.1 The entity graph

The benchmark represents the company facts shared by product simulators and internal databases in one entity graph. One seeded generator produces its identity (name and mail domain, derived from the chosen industry and business model), its workforce, its customers, and the business activity that connects them.

The workforce is generated first. The composition of the workforce follows the company’s size and growth stage: a two-hundred-person company at one stage is a fifth sales and a third engineering, and the proportions shift with the stage. Each employee has a position on a job ladder, a manager, a hire date drawn from realistic tenure distributions, a country with its own holidays and working hours, and an employment type (employee or contractor). Some employees have already left the company; the records they created remain, owned by a person who is no longer present. This is generated deliberately, because access-review and offboarding questions are a recurring category of enterprise work.

The customer base is generated next and assigned to sales representatives as territories of roughly twenty accounts each, with a cap that prevents any single representative from holding a disproportionate share. Under a business-to-consumer configuration a customer is an individual rather than a company, which changes what every downstream system holds. Around the customer base the generator produces activity in dependency order: contacts, sales deals with full stage history, documents, chat channels and messages, support tickets, recorded calls, and marketing campaigns. Later records reference earlier ones, so a ticket’s requester is a contact of a real account and the owner of a deal is a member of the sales team.

Volumes and values are correlated rather than drawn independently. Larger accounts produce more tickets. Meetings fall on business days in the participants’ time zones, with a small realistic share of weekend exceptions. Timestamps respect the life cycle they belong to: a deal cannot close before it opens, and a record that is still open has no end date. The graph also carries the texture that distinguishes an operating company from a demonstration dataset: duplicate customer records, a large body of inactive prospect accounts alongside the real customer base, non-human service accounts, a knowledge base derived from the company’s own support tickets, and the company’s own infrastructure with services and incidents.

Generation is deterministic. Each subsystem of the generator draws from its own seeded random stream, so the same seed reproduces the identical company on any machine, and extending one subsystem does not perturb the output of another. Determinism is what allows every simulator, every evaluation run, and every regression test to observe exactly the same company.

3.2 Projection into product simulators

Each business application in the environment is a simulator: a service that implements the interface of a real product. The fleet contains simulators of 66 products, including Salesforce, HubSpot, Zendesk, Jira, Gong, Slack, Stripe, S3, and Google Drive; a provisioned environment enables a configured subset. A simulator does not generate data of its own. It rebuilds the tenant's entity graph from the same seed and configuration and projects it: it stores the slice of the graph its product would hold, in that product's own format. No data is transferred between simulators; determinism is the synchronization mechanism.

Projections are faithful to each vendor and deliberately partial. The same recorded call appears in the Gong simulator as a call with participants and a transcript, and in the Salesforce simulator as a logged activity attached to the same contact and deal. Duplicate customer records appear only in the CRM, since a typographical duplicate is a CRM phenomenon. Prospect lists appear only in systems that hold an account table. Documents are rendered once as real bytes (valid DOCX, XLSX, and PDF files whose contents agree with the tabular records that reference them) and distributed to the file-store simulators. Record identifiers are derived deterministically in each vendor's real format, so vendor client libraries validate them, and each identifier maps back to the shared entity, which is what keeps a cross-system join well defined.

3.3 The application portfolio

A tenant declares which applications the company runs; we call this set the portfolio. The graph is always generated in full, regardless of the portfolio, so two tenants that differ only in portfolio agree record for record on everything both include. The portfolio is consulted only at projection time, under two rules. First, a simulator whose product is not in the portfolio serves a valid empty workspace rather than an error. Second, the traces that one product's integration writes into another exist only when the counterpart is in the portfolio. In a tenant that runs Gong, call records in Salesforce carry the artifacts the real Gong integration writes, including recording links; in a tenant without Gong, the same calls occur at the same times with the same participants, but no Gong artifact appears anywhere. The underlying business is thus independent of the software choices, which keeps results comparable across portfolio configurations. This distinction is not cosmetic: in production Salesforce organizations that run Gong, a substantial fraction of the activity table is written by the Gong integration package.

3.4 Serving the estate

A provisioned environment, called an estate, is created from the four parameters of Section 1. The provisioning service builds every selected simulator, waits until all report ready, and returns one MCP endpoint per simulator together with a single tenant-bound credential. The credential's tenant is a signed claim, so one tenant cannot read another's data. The data plane is read-only: a request that would modify data is refused, whether it arrives through a vendor API or an MCP tool, and the refusal itself is useful in evaluation, since an agent that attempts a prohibited write fails the test rather than the deployment. The environment evolves through day states: day 0 is the empty system, day 1 the full history, and day 2 adds one further day of change, with the answer key recomputed at each state, so staleness and incremental-synchronization behavior are themselves measurable.

4 Questions with computed answers

4.1 Simulator question and answer generation

Grading an agent requires a set of questions and the correct answer to each. In prior benchmarks both are authored manually, and the answers must be maintained by hand against the data. For product-simulator scenarios, the benchmark derives both from the generated company itself.

The benchmark includes 83 scenarios: one for each combination of ten industries and six size tiers, and 23 individually named companies. A scenario is a generated company together with its questions and their computed answers, all created in advance and committed to the corpus. A continuous-integration test regenerates the corpus from its seeds and verifies that the result is byte-identical to the committed files, so the benchmark cannot drift as the generator evolves.

The questions in every scenario come from a shared battery of templates written in code. Each template specifies a question form together with the computation that answers it: the number of open sales opportunities, the total value of the open pipeline, the salesperson with the highest won revenue, or the median resolution time of a support ticket. When a scenario is built, each template is instantiated with that company's entities, so the question text refers to specific accounts and channels of that company, and the expected answer is computed directly from the generated records. Because the answer is derived from the data, it cannot disagree with the data.

This design makes extending the benchmark inexpensive. Adding a scenario requires only a new company specification, namely an industry, a size tier, and a seed; the templates instantiate against the new company and the answers are computed automatically. Adding a question requires only a new template, which then applies to every scenario. No answer is ever written by hand.

Each scenario also stores consistency checks. A consistency check states that a named entity, such as a specific account, must appear in several named systems and refer to the same entity in all of them. A verifier reads those systems and confirms it. Cross-system questions depend on this agreement, so it is checked rather than assumed.

4.2 Verifying that answers are reachable

An answer computed from the graph is correct by construction, but correctness alone is insufficient: the underlying fact must also be reachable through the product interfaces an agent uses. A separate audit therefore re-reads every audited fact through each simulator's native API and through its MCP tools, and asserts that the value read back equals the stored answer. This audit has identified real defects. An early cross-system question joined recorded calls to contacts through an internal record identifier; the join was correct against the stored data but impossible through the product interface, because the call system issues its own participant identifiers and only the email address is visible on both sides. The audit rejects such questions before they can penalize a correct agent.

4.3 Composed questions and abstention

Single-system questions measure retrieval. The benchmark also includes twelve composed questions that require work across systems. They are defined the same way as the questions above, as code that pairs a question text with the computation of its answer. A composed question spans several systems and several steps: totals grouped by an attribute held in another system, the three accounts with the most support tickets, the recorded call minutes of the account with the largest open pipeline, or the number of accounts that raised an urgent ticket after their first open opportunity. The same twelve questions apply to every scenario, and each answer is recomputed from that scenario's records.

Three rules keep these questions fair. First, every answer computation joins systems only through keys an agent can follow in the products themselves; for example, the call system does not expose CRM identifiers, so calls are joined to accounts through participant email addresses. Second, each question states its own definitions and tie-breaking rule in its text, so a model is never graded against an unstated convention. Third, when a scenario's data does not settle a question uniquely, for instance when two accounts tie for the largest open pipeline although the question implies a single winner, the question is excluded for that scenario rather than graded against an arbitrary choice.

Two of the twelve questions request information the environment does not contain, such as a Net Promoter Score no system stores, and the correct response is to state that the question cannot be answered. Grading is deterministic in every case: each question declares its comparison mode, namely an exact value, a set, an ordered sequence, a per-key mapping, or abstention.

4.4 Generating internal databases from question lists

The same fictional estate also contains databases of its own, such as an analytics warehouse or an application database. Their schemas are particular to the company and fixed by no vendor. The

benchmark uses a specialized generator to create these internal databases. It is an internal development tool: clients receive the finished estate and answer keys, not the generator itself. Its input is a list of business questions about the fictional company and the completed entity graph. The internal databases extend that graph with application-specific facts. Their customers, employees, and business events reuse the graph’s canonical entities.

The design phase happens once per benchmark, and it is the only phase in which a language model participates. A benchmark author writes a list of business questions in natural language. The model also receives a catalog of the entity types, identifiers, and attributes available in the graph. It first sketches an application that could answer the questions: which databases exist, which entities live in each, and how they relate. It then produces the concrete schema, a generation plan for every column, and a planting directive for every question. Each table and column is marked as graph-backed or database-specific. A graph-backed record must use the graph’s canonical identifier. Any repeated name, date, amount, or other shared attribute must also come from the graph.

The model also proposes a few questions that the database cannot answer, whose purpose is to test whether an agent admits when an answer does not exist. For each such question, the model must state which table or column the database would need in order to answer it. A validator checks the schema, including every mapping to the entity graph. It rejects a design that creates a second identity for a shared entity. It also rejects a proposed unanswerable question when the schema contains the required information. All model output is validated, mechanically repaired where the mistake is clerical, and scored. A weak design buys a bounded number of redesign turns, and the best valid design is kept. The result is a fixed design.

The generation phase is deterministic and runs after the entity graph has been completed. It first materializes graph-backed records and foreign keys from the graph. It then generates database-specific tables and columns in dependency order from the plan’s typed distributions. A repeated account, employee, contact, deal, or event is copied from the graph rather than drawn again. New internal records reference those shared entities through their canonical identifiers.

The generator then plants each question. It forces a stated number of rows to satisfy the question’s conditions, so no question is accidentally empty or trivial. Each planted question also receives near-miss rows. Every near miss satisfies all but one condition, with the violated condition rotating across rows. A solver that ignores any single condition therefore reaches a wrong answer. Planting may add database-specific facts to a graph entity, but it cannot alter a graph-backed identifier or shared attribute.

Controlled doses of dirty values, such as inconsistent casing and placeholder text, are applied last, following the observation of BIRD [7] and Spider 2.0 [6] that much of the difficulty of real data lies in the data itself. Graph-backed keys and values are protected from these changes. A final consistency gate resolves every shared reference to the graph and compares every copied value with its source. The database is rejected if an identity is missing, a foreign key does not resolve, or a shared value differs. Because the product simulators project the same graph, this gate also keeps the internal databases consistent with the simulator records.

The answer key is computed at the very end, by running every question against the finished tables. The planted rows only ensure that matching rows exist. The recorded answer counts all rows that satisfy the question, including any that match by coincidence. The answer therefore always agrees with the data a solver actually reads. Each stored answer carries its comparison mode and, for fractional values, a numeric tolerance.

The same seed reproduces the identical database byte for byte, and a different seed keeps the schema and structure while changing the values. Every database generated from one design therefore carries the same questions, each with answers recomputed from its own records, exactly as the scenario templates above are fixed in form while their answers are computed per company.

5 Validating the generated estate

5.1 Checks follow the generation mechanism

Established methods for evaluating synthetic data assume that a real dataset exists for comparison: the generator is trained on real records, and quality is measured as the statistical distance between the

synthetic output and that original [11]. The Era by Eon Benchmark generates fictional companies without paired real records. Distance-based evaluation therefore does not apply.

Each generation mechanism provides different evidence. Internal databases have a stored schema, a generation plan for every column, and planting directives for their questions. They also record the entity graph source of every shared table, key, and value. Section 5.2 checks the finished tables and labels against that declared design and against the graph. Product simulators derive from the same entity graph. Their records are audited through the interfaces available to an agent, and the graph is scored against realism targets from Eon’s operational data and published statistics. The provenance of each target is recorded, and estimates are marked.

5.2 Checks for the internal databases

An internal database can be defective even when its design is valid. The generator can fail to produce the declared data. A question can be answerable by shortcut. Its answer key can be ambiguous, or declared relationships can be absent from the rows. The benchmark first runs an estate-consistency gate. Every graph-backed identifier must resolve to the canonical entity, and every copied value must equal its graph source. Since each simulator is a projection of the graph, this also checks consistency with the records exposed through product interfaces.

The benchmark then runs four measurements over every internal database. Each compares the finished database with its stored design or with a transformed copy of its rows, so none requires external data.

The first measurement, adherence, verifies that the rows deliver what the design declares. The generation plan of every column states its domain: the permitted categories of a status field, the minimum and maximum of a numeric field, the fraction of values that may be null. After generation, the actual rows are compared against these declarations. A status value that is not among the declared categories, an amount outside its declared range, or a column declared five percent null that comes out thirty percent null are all violations. Such a violation matters beyond aesthetics: a question that filters on the affected column no longer means what the design says it means, so its planted answer may be wrong. Because the design itself passed validation, any disagreement between design and rows is a bug in the generation code, and this measurement is the only place where that class of bug is visible.

The second measurement asks whether each question actually requires the work it appears to require. Consider a question with three conditions, such as jobs that failed, in one region, and are not deleted. If nearly every failed job is in that region and not deleted, then a solver that checks only the first condition reaches the same answer as one that checks all three, and the question rewards carelessness as much as care. To detect this, every question is answered by a panel of deliberately lazy solvers: one drops a condition, one ignores the join between tables and reads a single table, one aggregates over all rows instead of the filtered ones. Any question that a lazy solver answers exactly correctly is measuring nothing, and it is reported so that its data can be re-planted or the question replaced. The near-miss rows of Section 4.4 exist precisely to make these lazy strategies fail.

The third measurement examines the answer key itself. Three defects make a key unfair rather than a question hard. First, a tie: if the question asks for the three accounts with the most tickets and the third and fourth place hold the same count, two different answers are equally correct, and whichever the key recorded, a solver giving the other is marked wrong. Second, self-answering text: a question whose own wording contains its answer is a copying exercise. Third, precision: a fractional answer such as an average must carry an explicit tolerance, because a solver’s own arithmetic legitimately differs from the key’s in the last decimal places, and exact string comparison would mark it wrong. All three defects are searched for mechanically, and a benchmark is not released while any is present.

The fourth measurement tests whether the dependencies the design declares between columns exist in the delivered rows. This is the failure that standard single-column statistics cannot see. Take any table and shuffle each column independently: every single-column distribution is preserved perfectly, yet every relationship between columns is destroyed. A dataset and its shuffled copy are indistinguishable to marginal tests, and prior work has shown that even the widely used linear classifier two-sample test [9] barely separates them [16]. The benchmark therefore uses the stronger form of the test: a boosted-tree classifier is trained to distinguish the generated rows from an independently shuffled copy of themselves. If the classifier succeeds, the rows carry structure beyond their marginals, which is what the design promised; if it performs at chance, the declared dependencies were never generated.

The classifier’s score is read against a measured noise floor, obtained by scoring shuffled data against itself, so that a table with no declared dependencies scores zero rather than a spurious positive value. A complementary check computes the cardinality-estimation error [10] that the data induces in a textbook query optimizer: real data, with its correlations and skew, systematically misleads optimizers that assume independence and uniformity, and Hollywood [12] argues that synthetic data is realistic to the extent that it misleads them comparably. This error is computable with no real data at all.

5.3 The realism scorecard

The realism scorecard evaluates the entity graph and its product projections. It asks whether the shared company records resemble an operating company. A graph can be internally consistent while every histogram is flat, every account holds the same number of contacts, and every timestamp advances in fixed steps. The scorecard compares each generated company with the reference targets described above, along five axes. Each axis addresses one way in which generated data typically betrays itself.

The marginal axis scores the distribution of each field on its own. Naive generation draws values uniformly, which produces perfectly flat histograms; in real systems, ticket priorities follow a skewed mix in which urgent tickets are rare, and deal sizes follow a heavy-tailed distribution in which a few large deals coexist with many small ones. Each field’s empirical distribution is tested against its reference target.

The joint axis scores whether fields that should move together actually do. In a real company, a customer’s renewal risk reflects its open ticket load, revenue grows with headcount as a scattered cloud rather than an exact line, and larger accounts spend more. Generated data whose columns are drawn independently fails all of these, and an analytical question over such data, for instance which account is most at risk, has an answer that is statistical noise. The axis tests the declared relationships with rank correlations between the fields involved.

The temporal axis scores the calendar. Real business activity concentrates in working hours in each participant’s own time zone, thins at weekends, and spikes at quarter ends when sales teams pull deals to the boundary. Events also follow their causes: a call about a deal happens after the deal opens, and a ticket’s resolution follows its creation by a duration that depends on its priority. The axis tests both the time-of-day and calendar structure and the causal ordering.

The structural axis scores the shape of relationships. In a real customer base, a small number of accounts carry a large share of the tickets and the pipeline, and a long tail of accounts is nearly inactive. Generated data that gives every account the same number of contacts, deals, and tickets is recognizable at a glance. The axis tests per-parent counts for the heavy-tailed concentration the references specify.

The content axis scores the text. Ticket subjects, ticket bodies, chat messages, call transcripts, and deal notes must be varied at corpus scale, and each record must be about one thing: a ticket whose subject reports a permissions failure while its body discusses a scheduled export is nonsense to a human reader even when every aggregate over it is correct. The axis measures vocabulary growth against the sublinear curve a human-written corpus of the same size would show, and checks that all text on one record describes the same issue.

Each axis produces a score between 0 and 100. Two safeguards protect the meaning of these scores. The first concerns small companies. A statistical check needs a minimum amount of data: a distribution cannot be judged from a dozen values, and a concentration curve cannot be judged from four accounts. When a generated company is too small for a check, that check is skipped and reported as not measured, instead of contributing a meaningless pass or fail. Every scorecard also reports what fraction of its checks actually ran, so a company that scored well on the few checks it was large enough to support cannot be mistaken for one that passed a full examination. The second safeguard concerns overfitting by the developers of the generator. All generation is seeded, and during development the generator is tuned while observing scores on particular seeds. If the scores were checked only on those same seeds, a change could raise them in ways that hold for those seeds alone. The automated test suite therefore scores every change on a fixed seed that was never used during development, and rejects the change if the scores regress there.

5.4 The adversarial detector and the measured improvement

The scorecard measures how well the data matches reference statistics. A second instrument examines the data the way a suspicious human reader would: it looks for the specific marks that give synthetic data away. These marks are well known. A generator that runs out of names adds a number to make new ones, so a customer list reads Dunn, Dunn2, Dunn3. A field whose values are drawn uniformly produces a histogram flatter than any real system shows. Timestamps produced by a counter advance in identical steps. Every parent record has exactly the same number of children. The same filler sentence appears on hundreds of records. The detector scans every generated record for these marks and reports the fraction of records that carry at least one. Unlike the scorecard, it does not reward the data for matching anything; it actively hunts for evidence of generation.

The scorecard and the detector were built first, and the entity-graph generator was improved afterward, guided by what they reported. This order gives a clean before-and-after measurement. The original entity-graph generator, scored over 23 generated companies, had a mean realism score of 61.8, its worst company scored 48.6, and the detector flagged 55.2% of all records. The generator was then revised in a series of passes. Each pass fixed what the instruments reported as worst at that point: uniform draws were replaced with the reference distributions, per-account volumes were made heavy-tailed, a business calendar was introduced so events fall at realistic times and in causal order, fields that should be correlated were coupled, all text on a record was made to describe one issue, and numbered name variants were replaced with plausible names. After the fifth pass, the mean score over the same 23 companies was 97.0, the worst company scored 92.8, and the detector flagged no records. Later passes raised the mean to 98.6.

During this work, some checks in the scorecard were found to be flawed. They gave low scores to small companies even when the data was realistic, because the statistic they computed requires more data than a small company has. For example, one check measured the variety of the written text and expected a large vocabulary; a company with only three support tickets has too little text to reach it, no matter how well written. Another check measured the percentage of events that fall within business hours from only sixteen timestamps; with a sample that small, the percentage swings widely by chance alone. These flawed checks were fixed so that they take into account how much data they are given. After the fixes, every score in this section, including the original 61.8 baseline, was recomputed with the final version of the scorecard. The improvement from 61.8 to 97.0 is therefore a comparison of two generators under one identical scorecard, not an artifact of changing the scoring rules midway.

6 Evaluating agents on the estate

6.1 The evaluation harness

The environment described so far exists to answer one question: how well does an agent work over a company’s business systems? The evaluation harness measures this directly. It takes one committed scenario, provisions the simulators with that scenario’s records, asks a model the scenario’s questions, and grades every answer against the stored answer key.

The model reaches the data the same way a deployed agent would, through MCP. Each simulator exposes its product’s operations as MCP tools; a tool is one callable operation, such as running a query in the CRM, listing the tickets of the support desk, or fetching the transcript of a recorded call. Each simulator exposes tens of such tools, and across the simulators of one scenario the model faces roughly 290 of them in total. Nothing about this surface is described in the model’s prompt: no schemas, no data description, no tool list. The model starts with only three meta-tools, one that lists the systems present in the environment, one that describes the tools of a chosen system, and one that calls a chosen tool. It must therefore discover for itself which systems exist, which tools they offer, and which of them answers the question at hand. This discovery is part of what the benchmark measures, while the size of the prompt is not, because the tool catalog never enters it.

Four controls keep the comparison between models fair. First, isolation: every run is provisioned with its own copy of the scenario, torn down when the run ends, so concurrent runs cannot see each other’s data. Second, read-only access: only tools that cannot modify data are exposed, so no run can change the records that a later question is graded against. Third, equal budgets: the reported comparison allows 25 turns, 40 tool calls, and 8,000 characters per tool response. Every run records

whether it answered, exhausted a budget, or failed to produce a well-formed answer. Fourth, verified serving: before any question is asked, the harness reads each simulator back and checks that it serves exactly the scenario’s records. If a simulator fails this check, its questions are reported as not asked instead of being counted as model failures, so a defect in our serving cannot be mistaken for a model error.

Grading is deterministic. Each stored answer declares its comparison mode, as described in Section 4, and the grader applies that mode mechanically. The reported comparison gives no partial credit and uses no model as a judge. Each repeat receives a fresh isolated tenant seeded from the same frozen scenario.

6.2 Full model comparison

We evaluated nine models on the same frozen `segment_fintech_small` estate. Each model answered 33 questions three times, giving 99 recorded answers per model and 891 answers in total. The set contains 21 single-system questions and 12 composed questions. It uses Gong, Salesforce, and Zendesk records. The source corpus contained 67 candidate questions. Eight were omitted because they required unsupported HubSpot, Jira, Slack, or cross-system identity operations. Another 26 concerned documents and other unstructured artifacts that were not exposed in this tool-use track. These exclusions were fixed before any model ran and did not affect the scores. Every model received the same remaining 33 questions.

Accuracy is first averaged across the three repeats of each question and then across the 33 questions. Table 1 reports these estimates. A correct abstention counts as correct. A false abstention means that the model refused an answerable question. “No answer” combines malformed outputs and runs that ended before an answer. Each outcome count is out of 99.

Table 1: Nine-model comparison on one generated estate. Each 95% interval shows the uncertainty caused by evaluating only 33 questions with three runs per question. FA denotes false abstention; NA denotes no answer.

Model	Accuracy	95% interval	Wrong	FA	NA
claude-opus-4.8	76.8%	[61.6, 90.9]	0	10	13
gpt-5.6-sol	69.7%	[54.5, 83.8]	17	13	0
claude-opus-5	67.7%	[52.5, 81.8]	1	10	21
claude-sonnet-5	67.7%	[51.5, 82.8]	4	7	21
gpt-5.5	66.7%	[50.5, 81.8]	0	17	16
claude-sonnet-4.6	63.6%	[47.5, 78.8]	16	13	7
gpt-5.6-luna	56.6%	[40.4, 72.7]	26	12	5
qwen3-coder-next	55.6%	[39.4, 71.7]	14	3	27
gpt-5.4-mini	42.4%	[27.3, 58.6]	41	14	2

The benchmark contains only 33 questions, so small score differences may result from the choice of questions. The intervals in the table show this uncertainty. Wide intervals mean that the exact ordering of the models is uncertain.

We also checked every pair of models to determine whether one performed reliably better than the other. Only three of the 36 comparisons provided strong enough evidence. The remaining score differences do not support a claim that one model is better.

Three differences passed this test: Claude Opus 4.8 exceeded GPT-5.4 Mini by 34.3 percentage points; GPT-5.6 Sol exceeded GPT-5.4 Mini by 27.3 points; and Claude Sonnet 4.6 exceeded GPT-5.4 Mini by 21.2 points. Every other pairwise result was inconclusive.

The final results show a consistent pattern of difficult work. Three questions appeared among the five hardest for all nine models: finding the longest Gong call, totaling all Gong call time, and reporting the ticket-priority distribution for the account with the most tickets. For seven of the nine models, the five hardest questions included one that combines Salesforce and Gong records. It first asks the agent to identify the customer account with the largest total value of open sales opportunities. It then asks for the total recorded call time for that account. No model answered the median ticket-resolution-time question correctly.

The capability scores show the same pattern. Averaged across the nine models, accuracy was 3.7% on multi-hop questions, 6.2% on superlatives, 7.4% on temporal questions, 11.1% on ranking and order-sensitive questions, and 39.6% on cross-system questions. Simple filtering reached 92.6%. The main difficulty therefore lies in exhaustive aggregation, multi-hop joins, temporal summaries, and ordered rankings rather than basic filtering.

The 891 runs produced 561 correct answers, 119 wrong answers, 99 false abstentions, six malformed outputs, and 106 runs that ended before an answer. List-price inference for these 891 recorded runs totaled \$343.27.

7 Limitations

The model comparison covers one generated company and 33 independent question shapes. Three repeats reduce model-generation noise but do not create more questions. The benchmark contains separate questions for internal databases and documents. The reported comparison evaluates only the 33 simulator questions that use Gong, Salesforce, and Zendesk. It therefore provides no results for the other existing questions or for the full corpus of 83 scenarios.

The realism targets are only as good as their sources. Most are drawn from Eon’s operational data or from published statistics, but some are estimates, and although every estimate is marked as such, a wrong target pulls the generator toward a wrong distribution. The scorecard measures agreement with the targets, not the targets’ own truth.

The generated text is produced from seeded templates with slot-filling. The content axis and the adversarial detector verify variety and record-level coherence, and the current corpus passes both, but template-generated text still has a ceiling: it cannot reach the full diversity, idiosyncrasy, and error patterns of human writing, and a stronger detector than ours might separate the two.

8 Conclusion

The Era by Eon Benchmark generates the entire evaluation environment for enterprise LLM agents: one fictional company, the vendor applications and internal databases it operates, the benchmark questions, and the exact answer to each question. Two generation mechanisms populate this estate. The entity graph supplies shared facts to the product simulators. The specialized internal-database generator turns business questions into schemas and records. It copies shared entities, identifiers, and values from the graph before adding application-specific facts. The simulators and internal databases therefore describe the same company. Every answer is computed from the final records, so grading is mechanical.

Generating everything creates an obligation that hand-built benchmarks do not face: the realism of the data must be demonstrated rather than assumed. Each mechanism supplies the evidence appropriate to its output. Design-based checks verify the internal databases, their questions, and their labels. The entity-graph scorecard grades generated companies against statistics of real business data, and the adversarial detector hunts for synthetic artifacts. The scorecard and detector drove the entity-graph generator’s mean realism score across 23 companies from 61.8 to 97.0 and reduced the flagged share from 55.2% to zero.

The full comparison contains 891 recorded answers from nine models. Accuracy estimates range from 42.4% to 76.8%. The broad intervals and corrected paired tests show that most apparent differences between models remain inconclusive. The benchmark therefore reports both point estimates and statistical evidence. Its purpose is to measure factual tool use over a coherent company with exact ground truth.

References

- [1] Léo Boisvert, Megh Thakkar, Maxime Gasse, Massimo Caccia, Thibault Le Sellier De Chezelles, Quentin Cappart, Nicolas Chapados, Alexandre Lacoste, and Alexandre Drouin. WorkArena++: Towards compositional planning and reasoning-based common knowledge work tasks. In *Advances in Neural Information Processing Systems, Datasets and Benchmarks Track*, 2024.

- [2] Alexandre Drouin, Maxime Gasse, Massimo Caccia, Issam H. Laradji, Manuel Del Verme, Tom Marty, Léo Boisvert, Megh Thakkar, Quentin Cappart, David Vazquez, Nicolas Chapados, and Alexandre Lacoste. WorkArena: How capable are web agents at solving common knowledge work tasks? In *Proceedings of the International Conference on Machine Learning (ICML)*, 2024.
- [3] Kung-Hsiang Huang, Akshara Prabhakar, Sidharth Dhawan, Yixin Mao, Huan Wang, Silvio Savarese, Caiming Xiong, Philippe Laban, and Chien-Sheng Wu. CRMarena: Understanding the capacity of LLM agents to perform professional CRM tasks in realistic environments. In *Proceedings of the Conference of the North American Chapter of the Association for Computational Linguistics (NAACL)*, 2025.
- [4] Kung-Hsiang Huang, Akshara Prabhakar, Onkar Thorat, Divyansh Agarwal, Prafulla Kumar Choubey, Yixin Mao, Silvio Savarese, Caiming Xiong, and Chien-Sheng Wu. CRMarena-Pro: Holistic assessment of LLM agents across diverse business scenarios and interactions. *arXiv preprint arXiv:2505.18878*, 2025.
- [5] Valter Hudovernik, Martin Jurkovič, and Erik Štrumbelj. Benchmarking the fidelity and utility of synthetic relational data. *arXiv preprint arXiv:2410.03411*, 2024.
- [6] Fangyu Lei, Jixuan Chen, Yuxiao Ye, Ruisheng Cao, Dongchan Shin, Hongjin Su, Zhaoqing Suo, Hongcheng Gao, Wenjing Hu, Pengcheng Yin, Victor Zhong, Caiming Xiong, Ruoxi Sun, Qian Liu, Sida Wang, and Tao Yu. Spider 2.0: Evaluating language models on real-world enterprise text-to-SQL workflows. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2025.
- [7] Jinyang Li, Binyuan Hui, Ge Qu, Jiaxi Yang, Binhua Li, Bowen Li, Bailin Wang, Bowen Qin, Ruiying Geng, Nan Huo, Xuanhe Zhou, Chenhao Ma, Guoliang Li, Kevin C.C. Chang, Fei Huang, Reynold Cheng, and Yongbin Li. Can LLM already serve as a database interface? A big bench for large-scale database grounded text-to-SQLs. In *Advances in Neural Information Processing Systems*, 2023.
- [8] Shinan Liu, Jialin Zhang, Fenghao Dong, Yajie Zhou, and Vyas Sekar. TabQueryBench: A query-centric benchmark for synthetic tabular data. *arXiv preprint arXiv:2607.03926*, 2026.
- [9] David Lopez-Paz and Maxime Oquab. Revisiting classifier two-sample tests. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2017.
- [10] Guido Moerkotte, Thomas Neumann, and Gabriele Steidl. Preventing bad plans by bounding the impact of cardinality estimation errors. *Proceedings of the VLDB Endowment*, 2(1):982–993, 2009.
- [11] Neha Patki, Roy Wedge, and Kalyan Veeramachaneni. The synthetic data vault. In *Proceedings of the IEEE International Conference on Data Science and Advanced Analytics (DSAA)*, pages 399–410, 2016.
- [12] Mihail Stoian, Andreas Kipf, and Ivan Iachnyk. Hollywood: Towards a large movie dataset for database benchmarking. In *Proceedings of the International Workshop on Applied AI for Database Systems and Applications (AIDB)*, 2026.
- [13] Jason Walonoski, Mark Kramer, Joseph Nichols, Andre Quina, Chris Moesel, Dylan Hall, Carlton Duffett, Kudakwashe Dube, Thomas Gallagher, and Scott McLachlan. Synthea: An approach, method, and software mechanism for generating synthetic patients and the synthetic electronic health care record. *Journal of the American Medical Informatics Association*, 25(3): 230–238, 2018.
- [14] Frank F. Xu, Yufan Song, Boxuan Li, Yuxuan Tang, Kritanjali Jain, Mengxue Bao, Zora Z. Wang, Xuhui Zhou, Zhitong Guo, Murong Cao, Mingyang Yang, Hao Yang Lu, Amaad Martin, Zhe Su, Leander Maben, Raj Mehta, Wayne Chi, Lawrence Jang, Yiqing Xie, Shuyan Zhou, and Graham Neubig. TheAgentCompany: Benchmarking LLM agents on consequential real world tasks. *arXiv preprint arXiv:2412.14161*, 2024.

- [15] Shunyu Yao, Noah Shinn, Pedram Razavi, and Karthik Narasimhan. τ -bench: A benchmark for tool-agent-user interaction in real-world domains. *arXiv preprint arXiv:2406.12045*, 2024.
- [16] Jie Zhang. Measuring the dependency gap: Diagnosing inter-column fidelity in tabular generative models. *arXiv preprint arXiv:2607.21636*, 2026.