

An Empirical Evaluation of Cost-Efficient Large Language Models on Algorithmic Programming Tasks

Chandimal Adikari
Faculty of Engineering and Information Sciences
University of Wollongong
Wollongong, Australia
0009-0001-0082-2448

Nandika Herath
Faculty of Engineering, Computing and Science
Western Sydney University
Parramatta, Australia
0009-0003-8220-2035

Abstract— This study empirically evaluates whether cost-efficient Large Language Models (LLMs) can be trusted to generate enterprise code to a written specification. Three models (Gemini Flash 3, GPT-5.4 mini and Claude Haiku 4.5) were asked to solve 992 algorithmic problems as Java Spring Boot service methods conforming to a mandated signature and data-transfer-object specification, crossing four model and agentic coding tool combinations with two prompt variants to yield eight configurations, with iteration forbidden and hardcoded answers explicitly prohibited. Eight problem statements were withheld to probe how models respond to missing input. The 7,593 resulting methods were classified by an eight-class outcome taxonomy describing what each does about producing an answer, then deployed and executed, giving 7,936 measured requests joined to that classification. Structural conformance approached ceiling, yet 38.4% of methods do not compute the value they returned and only 12.9% of returned answers were correct. Conditioning on outcome class shows that response reliability and correctness are inversely related, whereas genuinely computing methods answered least often and were correct 19.3%. Limitations include single generation runs per configuration, partial harness coverage, single-pass timing, syntactic classification, and probable corpus contamination.

Keywords—LLM code generation, Software Engineering, Vibe Coding, AI, Artificial Intelligence

I. INTRODUCTION

Large Language Models (LLMs) are increasingly used to generate code in bulk against specifications where a developer supplies a specification, a framework and a set of requirements, and expects conforming code in return. Whether what comes back is acceptable is assessed either by executing it against test cases, the dominant paradigm in code generation evaluation, or by checking it programmatically against verifiable constraints, the paradigm of instruction following evaluation. The two are applied to different corpora and reported separately, so whether they agree has received little attention.

Execution has been the standard since the earliest function-level synthesis benchmarks, whose pass@k protocol remains the default instrument of the field [1]. It has been extended to competitive programming [2], [3] and to test suites strengthened until they reject plausible but incorrect solutions [4]. Later work broadened the notion of a task rather than of success: compound library calls [5], class-level context [6], reasoning about execution [7], contamination-resistant collection [8] and repair of real repository issues [9]. Throughout, the unit of

measurement is a pass rate; what the code does internally to pass is not examined. The same posture carries over to reasoning benchmarks needing no executable artefact [10], [11] and to arithmetic delegated to generated code [12]. Project Euler has been used in the same spirit alongside task length as a capability axis and arithmetic delegated to generated code [13], [14].

The second instrument admits only instructions a checker can decide, continuing through graded and multi-level constraints [15] and code-specific instruction following [16]. What these verify is structural, namely signature, naming and framework idiom, none of which reveals whether the body computes the value it returns. Adjacent work reads generated code for properties invisible to functional tests: memorisation and contamination [17], efficiency [18] and security [19], although the efficiency benchmarks condition on correctness rather than on how the answer was produced, so a returned constant is fast by assumption. Iterative refinement [20] and agentic harnesses [21] raise measured performance substantially.

However, the two instruments have not been applied to the same artefacts, so their disagreement is unquantified. Runtime measurements are reported unconditionally, so a response rate cannot separate a working algorithm from a returned constant. This study addresses these gaps by prohibiting iteration so that first-response behaviour is observed directly and retaining the harness as an experimental factor.

The contributions are an six-class outcome taxonomy separating genuine computation from five fabrication strategies; evidence that structural and semantic conformance diverge by up to 59.9 percentage points on identical code; demonstration that reliability and correctness are inverted, since fabricated placeholders answered every request and were almost never right whereas genuine computation answered least often and alone reached a substantive correct rate of 19.3%, the two correlating at -0.91 across the eight conditions; identification of a synthetic answer generator manufacturing a plausible answer per problem index, defeating literal-based detection across 792 problems without once being correct; and a missing-input probe quantifying hallucination, the recall-to-invention transition and a prompt-dependent harness effect above ten percentage points.

The remainder of the paper is organised as follows. Chapter II states the methodology and experimental setup. Chapter III reports the static and runtime results. Chapter IV discusses their

interpretation and consequences for evaluation practice. Chapter V concludes, and Chapter VI states the limitations of the study.

II. METHODOLOGY AND EXPERIMENTAL SETUP

The methodology has been designed to address following research questions:

1. To what extent does the generated model conform to the prescribed structural form?
2. To what extent does the generated model comply with the specified prohibition on shortcuts?
3. To what extent does the generated code correctly solve the target problem?

The first two are answered by static analysis of the generated source and the third by executing it, with both halves joined on the problem identifier so that every runtime measurement can be conditioned on the kind of code that produced it.

A. Problem Presentation

The corpus comprises Project Euler¹ problems 1 through 1000. Each statement was reduced to a plain-text file containing the problem text without HTML, images or navigation, and the files were placed in directories of one hundred. Of the 1000 problems, 992 were supplied to the models and 8 were withheld as probe.

Project Euler was selected since each problem has a single unambiguous numeric answer, so correctness is decidable without a test suite [13], [14]. Difficulty spans several orders of magnitude, so one specification applies to trivial and intractable tasks alike. The early problems are heavily discussed online while later ones are not, which converts contamination from a nuisance into a measurable gradient.

B. LLMs and conditions

Three cost-efficient models were evaluated: Gemini Flash 3 (GF3), GPT-5.4 mini (GPT-mini) and Claude Haiku 4.5 (CH-4.5), since frontier-models' performance on Project Euler already evaluated [13], [22], and the practical question for a development team concerns whether an inexpensive model can be trusted to generate bulk code to a specification. Two Agentic Coding Tools (ACT) were used, Cursor and Claude Code, with Claude Haiku 4.5 run through both so that the ACT also becomes a measurable. Prior work on agent-




Fig. 1: Experimental Conditions

¹Problem statements are taken from Project Euler (<https://projecteuler.net>) and are licensed under CC BY-NC-SA 4.0 (<https://creativecommons.org/licenses/by-nc-sa/4.0/>). Statements were reduced to plain text before presentation to the models. Neither problem statements nor published answers are reproduced in this paper; problems are identified by number only.

```
" Can you iterate through the problems given in <Folder Reference> folder and generate the solution java code to each problem in a different Method in <Java class Referene>
```

Don't validate the code just put the first output you generate inside the method.

Don't directly put any known answers for generated Logic. Example:

```
public ResponseDto Question1(){
    ResponseDto responseDto = new ResponseDto();
    <Insert Generated Logic to Solve the Problem Here>
    responseDto.setAnswer(outputFromTheGeneratedLogic);
    return responseDto;
}"
```

Fig. 2: Prompt 1 Template - Single Class, Many Methods

```
"Can you iterate through the problems given in <Folder Reference> folder and generate the solution java code to each problem in separate springboot service Similar to <Java class Referene>
```

Don't validate the code just put the first output you generate inside the method.

Don't directly put any known answers for generated Logic. Example:

```
public ResponseDto Question1(){
    ResponseDto responseDto = new ResponseDto();
    <Insert Generated Logic to Solve the Problem Here>
    responseDto.setAnswer(outputFromTheGeneratedLogic);
    return responseDto;
}"
```

Fig. 3: Prompt 2 Template – One Class per Problem

computer interfaces and flow engineering establishes that the ACT can affect outcomes as much as the model [23], so a design varying model and ACT together cannot attribute a difference to either. Crossing four model-harness combinations with two prompt variants yields the eight conditions (Fig. 1).

C. Prompt Variants and Constraints

Both Prompt 1 (P1) and Prompt 2 (P2) which were given as one-shot prompt [7], [8], required the model to read each problem file from disk and write Java methods inside a Spring Boot service class (Fig.2 and Fig.3). The constraints was fixed across all conditions: the class carries the `@Service` annotation and sits in a specified package; the response DTO is imported from a specified package; each solution is a method with the exact signature `public ResponseDto QuestionN()`; and the method instantiates `ResponseDto`, calls `setAnswer` with the computed value, and returns the DTO.

Additionally, the model was instructed not to iterate or self-correct, so that first-generation output is measured, and not to hardcode known answers. The first isolates one-shot reliability, which matters because iterative refinement is known to improve correctness substantially and would otherwise confound the measurement. The second is the single semantic instruction of the study, and the only one whose violation cannot be detected by inspecting the shape of the output. The

TABLE I. OUTCOME TAXONOMY FOR A GENERATED SOLUTION METHOD

Class	Definition	Attempt?
C1 Genuine computation	The method contains code that attempts to compute the answer and returns what that code produced.	yes
C2 Literal despite real code	Real computation is present, but the returned value is overridden by a literal.	yes
C3 Hardcoded constant	A bare constant is returned. No computation.	no
C4 Acknowledged placeholder	A fabricated value, with a comment as a placeholder or that real computation would be required.	no
C5 Prose in place of a value	A sentence is returned where a number belongs, example: <code>setAnswer("Logic to compute $S(10^{12})$").</code>	no
C6 Answer never set	The DTO is returned without <code>setAnswer</code> ever being called on any path.	no

prompt variants differ only in code organisation. P1 requires all solutions as separate methods in one `@Service` class per batch of one hundred problems, whereas P2 requires one `@Service` class per problem. The contrast is of practical interest because the two impose different context loads. Eight problem files were removed before generation: 796, 797, 799, 802, 848, 857, 859, 963. A model that notices should produce nothing for them.

D. Static Content Classification and Execution Setup

Classification is performed by a static analyser written in python over the generated source. Every method is assigned to exactly one outcome class describing what it does about producing an answer (Table I). It resolves the expression passed to “`setAnswer`” method, propagates constant assignments, and unwraps the indirections through which a literal reaches the setter (Fig. 4).

Each condition was deployed as a Spring Boot application exposing one endpoint per problem, `GET /api/{model}/{layout}/q{n}` (e.g: `/api/gpt54mini/batch/q1`), returning the answer and the execution time the service measured for itself in nanoseconds. Measuring inside the service excludes HTTP transport and JSON serialisation from the reported time. Every endpoint was called once for every supplied problem, giving 7,936 requests across the eight conditions, with a per-request ceiling of 60 seconds matching the one-minute guideline Project Euler applies to its own problems. The four services ran on four ports on a single host and requests were issued sequentially to avoid CPU contention.




Fig. 4: Static Content Classification

III. RESULTS

Results are reported in the order in which the two instruments were applied. The static pass covers 7,593 methods across eight conditions, and the execution pass covers 7,936 requests against the same code. Conditions are ordered best to worst on the measure under discussion in each table.

A. Static Content Results

Coverage of the 992 supplied problems ranges from 89.9% to 100.0% (Table II). Silent skipping is common and overwhelmingly contiguous rather than scattered. Gemini/Cursor P2 loses the block 541-560, Haiku/Claude Code P2 loses 80-100, and Haiku/Cursor loses 101-200 under both prompts plus 701-800 under P1. A run of 20 or 100 consecutive absences is a batch-level event, not an accumulation of per-problem difficulty.

The mandated signature `public ResponseDto QuestionN()` was produced correctly by every method in every condition. Package placement, the `@Service` annotation and the DTO import were satisfied at or near ceiling in all but two file-level cases, and TODO markers only appear in 3 methods out of 7,593.

The single semantic instruction was not to hardcode known answers. Applying the six-class taxonomy to the analysed methods, 2,913 of them do not compute the value they return. Non-attempt rates range from 4.7% to 87.0% across conditions, a spread of more than eighteen-fold (Table III).

Where a method returns a literal and published ground truth exists, the literal can be compared against it. A match indicates recall of a published answer; a mismatch indicates invention. Of 1,843 such literals across all conditions, 92 match the published answer (5.0%). Fabrication outnumbers recall by roughly nineteen to one (Table IV).

TABLE II: COVERAGE OF SUPPLIED PROBLEMS

Condition	Coverage	Missing	Scattered missing	Contiguous gap ranges
Haiku/Cursor P2	88.7%	100	0	101-200
Haiku/Claude P2	97.7%	23	2	80-100
Gemini/Cursor P2	98.0%	20	0	541-560
Haiku/Cursor P1	80.1%	197	2	101-200; 701-795
Gemini/Cursor P1	99.7%	3	3	none
Haiku/Claude P1	100.0%	0	0	none
GPT/Cursor P2	100.0%	0	0	none
GPT/Cursor P1	100.0%	0	0	none

TABLE III: OUTCOME TAXONOMY BY CONDITION

Condition	n	C1	C2	C3	C4	C5	C6	Non-attempt (C3-C6)	Non-attempt Rate
Haiku/Cursor P2	892	832	18	41	0	0	1	42	4.7%
Haiku/Claude Code P2	969	805	5	152	1	0	6	159	16.4%
Haiku/Claude Code P1	992	795	10	169	1	0	17	187	18.9%
Haiku/Cursor P1	795	467	101	227	0	0	0	227	28.6%
GPT/Cursor P2	992	577	0	10	6	0	399	415	41.8%
Gemini/Cursor P2	972	496	48	140	188	99	1	428	44.0%
Gemini/Cursor P1	989	334	63	476	115	1	0	592	59.9%
GPT/Cursor P1	992	128	1	65	6	0	792	863	87.0%
All Conditions	7593	4434	246	1280	317	100	1216	2913	38.4%

TABLE IV: LITERAL MATCHES BY CONDITIONS

Condition	Literals	Matches published	Wrong	Match Rate
Haiku/Cursor P2	59	0	59	0.0%
Haiku/Claude P2	158	0	158	0.0%
Gemini/Cursor P2	376	29	347	7.7%
Haiku/Cursor P1	328	0	328	0.0%
Gemini/Cursor P1	654	21	633	3.2%
Haiku/Claude P1	180	11	169	6.1%
GPT/Cursor P2	16	15	1	93.8%
GPT/Cursor P1	72	16	56	22.2%

TABLE V: ACT EFFECT WITH MODEL HELD CONSTANT (CLAUDE HAIKU 4.5)

Prompt	Paired n	Cursor non-attempt	Claude Code non-attempt	Difference
P1	795	28.6%	17.9%	10.7%
P2	869	4.8%	18.3%	-13.5%

Considering the effect of prompt structure, P2, which mandates one `@Service` class per problem, produced fewer non-attempts than P1 in all four model-ACT combinations (Table III). As Claude Haiku 4.5 was run through both Cursor and Claude Code, the ACT can be isolated with the model held as a constant. The effect is large, significant, and reverses direction between prompts (Table V). Under P1, Cursor is worse by 10.7 percentage points; under P2, Cursor is better by 13.5 points.

B. Runtime Response Outcomes

Deploying the same code and calling every endpoint once produced 7,936 responses, of which 6,981 carried an answer

(88.0%). The remainder divides into 675 Status 500 Server Errors (343 requests for which no method exists, 332 runtime exceptions), 247 timeouts at the 60-second ceiling, 31 null answers and 2 transport errors (Table VI).

IV. DISCUSSION

The static analysis evaluated whether a model tried, and runtime analysis evaluated whether it succeeded. The two answers are close to opposite. Across the eight conditions the correlation between static semantic compliance and runtime correctness is -0.53, and between compliance and correctness among genuine attempts it is -0.91 (Table VII).

Semantic compliance is the share of a condition's methods that genuinely attempt the computation; runtime correctness is correct answers as a share of the 992 supplied problems, and capability is correct answers as a share of the attempts that returned a value. The corresponding rank correlations are -0.67 and -0.81, so neither result is an artefact of the linear form. Fig. 6 shows the eight conditions ordered by ascending compliance with capability alongside, and the two series run in opposite directions across that ordering.

Band	1-100	101-200	201-300	301-400	401-500	501-600	601-700	701-800	801-900	901-1000
Gemini/Cursor P2	83	61	45	25	1	5	14	1	4	2
Gemini/Cursor P1	96	37	18	1	0	0	0	1	1	0
GPT/Cursor P1	96	36	0	0	0	0	0	0	0	0
GPT/Cursor P2	96	36	0	0	0	0	0	0	0	0
Haiku/Claude P1	0	0	0	0	0	0	0	0	0	0
Haiku/Cursor P2	73	0	0	1	0	0	0	0	0	0
Haiku/Claude P2	0	0	0	0	0	0	0	0	0	0
Haiku/Cursor P1	34	0	2	0	0	0	0	0	0	0

Fig. 5: Correct answers per band

TABLE VI: REQUEST OUTCOMES BY CONDITION

Condition	Requests	Answered in Code	Null answer	Timeout (60s)	Runtime exception	Method absent	Transport error	Response Received
Gemini/Cursor P2	992	929	3	36	4	20	0	93.6%
Gemini/Cursor P1	992	982	2	5	0	3	0	99.0%
GPT/Cursor P1	992	992	0	0	0	0	0	100.0%
GPT/Cursor P2	992	992	0	0	0	0	0	100.0%
Haiku/Claude Code P1	992	898	18	65	9	0	2	90.5%
Haiku/Cursor P2	992	594	1	89	208	100	0	59.9%
Haiku/Claude Code P2	992	926	7	27	9	23	0	93.3%
Haiku/Cursor P1	992	668	0	25	102	197	0	67.3%
All Conditions	7936	6981	31	247	332	343	2	88.0%

Table VII: STATIC ADHERENCE AND RUNTIME CAPABILITY

Condition	Answered	Correct	Correct of answered	Correct of 992 supplied	C1 attempts that answered	C1 correct	C1 correct rate
Gemini/Cursor P2	929	241	25.9%	24.3%	455	211	46.4%
Gemini/Cursor P1	982	154	15.7%	15.5%	327	133	40.7%
GPT/Cursor P1	992	132	13.3%	13.3%	128	116	90.6%
GPT/Cursor P2	992	132	13.3%	13.3%	577	81	14.0%
Haiku/Claude Code P1	898	76	8.5%	7.7%	721	65	9.0%
Haiku/Cursor P2	594	74	12.5%	7.5%	575	74	12.9%
Haiku/Claude Code P2	926	55	5.9%	5.5%	768	55	7.2%
Haiku/Cursor P1	668	36	5.4%	3.6%	440	36	8.2%

What neither coefficient establishes is that attempting more causes a model to be less accurate. The denominators differ systematically. Especially, GPT-5.4 mini under Prompt 1, attempted genuine computation on 128 problems and was correct on 90.6% of them, but every one of those 128 attempts falls at or below problem 200 (Fig. 5), with a median identifier of 70, and the remaining 864 problems were handled by the synthetic answer generator. The other seven conditions attempt across the full corpus, with median attempted identifiers between 363 and 583. Removing the extreme point moves the correlation from -0.91 to -0.78 , so it carries the magnitude without creating the pattern. The defensible reading is that the two measures cannot be combined into a single ranking, not that adherence damages accuracy.

A. Answer Fabrication Strategies

Five distinct fabrication strategies appear in the study and they are not equally visible. A hardcoded constant leaves a literal that a detector can find, and 1,843 such literals were found. An acknowledged placeholder announces itself in a comment and is the honest case, though it accounts for only 16.1% of non-attempts. Prose returned where a number belongs fails on inspection. A wrapper forwarding to another class contains nothing but is structurally impeccable.




Fig. 6: Static Compliance and Runtime Capability

```
private long generatedAnswer(int questionNumber) {
    long value = questionNumber * 97L + 13L;
    int iterations = 5 + (questionNumber % 7);
    for (int i = 0; i < iterations; i++) {
        value = value * 31L + (questionNumber % (i + 3));
        value ^= (value << 7);
        value ^= (value >>> 9);
    }
    return Math.abs(value);
}
```

Fig. 7: Sample Synthetic Answer Method Observed

The synthetic answer generator is the clearest case and the hardest to detect. It manufactures a distinct plausible answer from the problem index by a fixed arithmetic routine that never reads the problem statement, and it appears in 792 methods of a single condition (Fig. 7). Because each answer differs, no duplicate-value heuristic identifies it. Because the value is computed, no literal detector identifies it. Because the routine is trivial, it returns a response below 100ms and never fails. It answered all 792 requests and none of them were correct. Only two signals expose it, namely execution time three orders of magnitude below any genuine attempt, and a correct rate of exactly zero over a large sample.

Additionally, non-attempts admit in a comment that the value is a placeholder, 2,549 say nothing, and 18 assert that the value was computed when it was not. The third group is small in count and disproportionate in consequence, since a comment claiming a computation that did not occur will survive code review in a way that a bare constant will not.

B. Recalling Answers from Memory

Literal answers match the published answer 44.3% of the time for problems 1 to 100 and 0.1% of the time from problem 401 onward, with 91 of 92 matches at or below problem 345. Early problems are heavily discussed online and their answers are recalled. Later problems are not, and the values returned for them are invented. The behaviour is the same in both ranges, since the model returns a constant it did not compute, and only the provenance of the constant changes.

This is consistent with the memorisation literature [3], [5], [17] and with the motivation for contamination-aware evaluation [1], [8]. Two consequences follow for design. Any evaluation drawn from the early Project Euler range measures retrieval as much as reasoning, and a model can score well on it without computing anything.

V. CONCLUSION

This study evaluated three cost-efficient large language models on 992 Project Euler problems presented as a mandated Spring Boot service, across two prompt variants and two Agentic Coding Tools, and measured specification adherence, coverage, answer correctness, runtime outcomes and execution time on the same 7,593 generated methods.

Structural conformance is near-perfect and almost uninformative, since every method in every condition reproduced the mandated signature. Yet 37.8% of those methods do not compute the value they return, and the gap between structural and semantic compliance reaches 59.9 percentage points. Executing the code closes the argument, since of 6,981 answers returned 900 were correct at 12.9%, and the best condition solved 24.3% of the problems it was given.

Three results appear to be new. Response reliability and answer correctness are close to opposite properties, since the fabrication classes responded to essentially every request and were almost never correct while genuine computation responded least often, was alone in exceeding the time limit, and was the only class with a substantive correct rate. Fabrication further has strategies of differing detectability, and the least detectable of them, a generator manufacturing answers from the problem index, leaves no literal to identify, executes in microseconds, never fails, and was never correct in 792 attempts.

The practical implication is narrow and firm. Evaluating models via an adherence rubric of structural checks measures only their least demanding requirement, creating a paradoxical outcome for model selection. Relying on this metric selects the weakest system: our findings demonstrate that the model most obedient to the instruction to compute was the least likely to compute correctly, while the model that most often ignored the instruction yielded the highest accuracy.

VI. LIMITATIONS

Each condition was generated exactly once, so between-condition differences cannot be separated from run-to-run sampling variance. This rather than sample size is the binding constraint on every comparative claim, since with roughly one thousand paired observations per condition the statistical power is ample and what is missing is a variance estimate for the generation process itself. Comparative statements should therefore be read describing these runs. Additionally, the execution pass is a single measurement per problem with no warm-up discard and no repeat runs.

Project Euler problems and their answers have been public for roughly two decades, so the early bands are almost certainly contaminated and the corpus cannot support claims about reasoning on unseen problems. Problem statements were simplified to plain text, which removes formatting and images but also any information those elements carried, and may therefore have altered difficulty in ways not measured here. All three models are of the cost-efficient tier, so the results say nothing about frontier models, and they do not generalise beyond a mandated-specification setting, since a prompt

permitting the model to report an inability to solve a problem might elicit very different behaviour.

Finally, the probe measures hallucination cleanly and detection only weakly, because the models were never asked to report missing input, so a model that skipped a withheld problem silently cannot be distinguished from one that never looked, and eight problems is a small denominator.

Data Availability:

An anonymised replication package is available at <https://github.com/researchartifacts/ProjectEulerAIEvaluation> for review.

REFERENCES

- [1] J. Jiang, F. Wang, J. Shen, S. Kim, and S. Kim, "A Survey on Large Language Models for Code Generation," *ACM Trans. Softw. Eng. Methodol.*, Jul. 2025, doi: 10.1145/3747588.
- [2] Y. Li *et al.*, "Competition-level code generation with AlphaCode," *Science*, vol. 378, no. 6624, pp. 1092–1097, Dec. 2022, doi: 10.1126/science.abq1158.
- [3] D. Hendrycks *et al.*, "Measuring Coding Challenge Competence With APPS," in *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track (Round 2)*, 2021. [Online]. Available: <https://openreview.net/forum?id=sD93GOzH3i5>
- [4] J. Liu, C. S. Xia, Y. Wang, and L. Zhang, "Is your code generated by ChatGPT really correct? rigorous evaluation of large language models for code generation," in *Proceedings of the 37th International Conference on Neural Information Processing Systems*, in NIPS '23. Red Hook, NY, USA: Curran Associates Inc., 2023.
- [5] Y. Lai *et al.*, "DS-1000: A Natural and Reliable Benchmark for Data Science Code Generation," in *Proceedings of the 40th International Conference on Machine Learning*, A. Krause, E. Brunskill, K. Cho, B. Engelhardt, S. Sabato, and J. Scarlett, Eds., in *Proceedings of Machine Learning Research*, vol. 202. PMLR, Jul. 2023, pp. 18319–18345. [Online]. Available: <https://proceedings.mlr.press/v202/lai23b.html>
- [6] X. Du *et al.*, "Evaluating Large Language Models in Class-Level Code Generation," presented at the *Proceedings of the IEEE/ACM 46th International Conference on Software Engineering (ICSE)*, 2024, pp. 982–994. doi: 10.1145/3597503.3639219.
- [7] A. Gu, B. Roziere, H. J. Leather, A. Solar-Lezama, G. Synnaeve, and S. Wang, "CRUXEval: A Benchmark for Code Reasoning, Understanding and Execution," in *Proceedings of the 41st International Conference on Machine Learning*, R. Salakhutdinov, Z. Kolter, K. Heller, A. Weller, N. Oliver, J. Scarlett, and F. Berkenkamp, Eds., in *Proceedings of Machine Learning Research*, vol. 235. PMLR, Jul. 2024, pp. 16568–16621. [Online]. Available: <https://proceedings.mlr.press/v235/gu24c.html>
- [8] N. Jain *et al.*, "LiveCodeBench: Holistic and Contamination Free Evaluation of Large Language Models for Code," in *The Thirteenth International Conference on Learning Representations*, 2025. [Online]. Available: <https://openreview.net/forum?id=chfJJYC3iL>
- [9] C. E. Jimenez *et al.*, "SWE-bench: Can Language Models Resolve Real-world Github Issues?," in *The Twelfth International Conference on Learning Representations*, 2024. [Online]. Available: <https://openreview.net/forum?id=VTF8yNQm66>
- [10] D. Hendrycks *et al.*, "Measuring Mathematical Problem Solving With the MATH Dataset," in *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track (Round 2)*, 2021. [Online]. Available: <https://openreview.net/forum?id=7Bywt2mQsCe>
- [11] D. Rein *et al.*, "GPQA: A Graduate-Level Google-Proof Q&A Benchmark," in *First Conference on Language Modeling*, 2024. [Online]. Available: <https://openreview.net/forum?id=Ti67584b98>
- [12] L. Gao *et al.*, "PAL: Program-aided Language Models," in *Proceedings of the 40th International Conference on Machine Learning*, A. Krause, E. Brunskill, K. Cho, B. Engelhardt, S. Sabato, and J. Scarlett, Eds., in *Proceedings of Machine Learning Research*, vol. 202. PMLR, Jul.

- 2023, pp. 10764–10799. [Online]. Available: <https://proceedings.mlr.press/v202/gao23f.html>
- [13] D. Holmes and J. Schmitt, “Human vs Machine Mathematical Difficulty on Project Euler: An Experimental Analysis.” 2026. [Online]. Available: <https://arxiv.org/abs/2606.21972>
 - [14] B. Silva and R. N. Madeira, “A study and a proposal of a collaborative and competitive learning methodology,” in *IEEE EDUCON 2010 Conference*, 2010, pp. 1011–1018. doi: 10.1109/EDUCON.2010.5492466.
 - [15] Y. Jiang *et al.*, “FollowBench: A Multi-level Fine-grained Constraints Following Benchmark for Large Language Models,” presented at the Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (ACL), Volume 1: Long Papers, 2024, pp. 4667–4688. doi: 10.18653/v1/2024.acl-long.257.
 - [16] N. Muennighoff *et al.*, “OctoPack: Instruction Tuning Code Large Language Models,” in *The Twelfth International Conference on Learning Representations*, 2024. [Online]. Available: <https://openreview.net/forum?id=mw1PWNWZP>
 - [17] N. Carlini, D. Ippolito, M. Jagielski, K. Lee, F. Tramer, and C. Zhang, “Quantifying Memorization Across Neural Language Models,” in *The Eleventh International Conference on Learning Representations*, 2023. [Online]. Available: https://openreview.net/forum?id=TatRHT_1cK
 - [18] D. Huang, Y. Qing, W. Shang, H. Cui, and J. M. Zhang, “EFFIBENCH: benchmarking the efficiency of automatically generated code,” in *Proceedings of the 38th International Conference on Neural Information Processing Systems*, in NIPS ’24. Red Hook, NY, USA: Curran Associates Inc., 2024.
 - [19] H. Pearce, B. Ahmad, B. Tan, B. Dolan-Gavitt, and R. Karri, “Asleep at the Keyboard? Assessing the Security of GitHub Copilot’s Code Contributions,” presented at the Proceedings of the 2022 IEEE Symposium on Security and Privacy (SP), IEEE, 2022, pp. 754–768. doi: 10.1109/SP46214.2022.9833571.
 - [20] A. Madaan *et al.*, “SELF-REFINE: iterative refinement with self-feedback,” in *Proceedings of the 37th International Conference on Neural Information Processing Systems*, in NIPS ’23. Red Hook, NY, USA: Curran Associates Inc., 2023.
 - [21] J. Yang *et al.*, “SWE-agent: agent-computer interfaces enable automated software engineering,” in *Proceedings of the 38th International Conference on Neural Information Processing Systems*, in NIPS ’24. Red Hook, NY, USA: Curran Associates Inc., 2024.
 - [22] M. Balunović, J. Dekoninck, I. Petrov, N. Jovanović, and M. Vechev, “MathArena: Evaluating LLMs on Uncontaminated Math Competitions.” 2026. [Online]. Available: <https://arxiv.org/abs/2505.23281>
 - [23] T. Ridnik, D. Kreda, and I. Friedman, “Code Generation with AlphaCodium: From Prompt Engineering to Flow Engineering.” 2024. [Online]. Available: <https://arxiv.org/abs/2401.08500>