

Collective Loss of Control in LLM Agent Systems: An Epidemic Account of Mutation, Contagion, and Recovery

Tencent Zhuque Lab

Xiangfan Wu, Zonghao Ying, Huiyu Wu, Xing Zheng,
Huangsheng Cheng, Xiaorong Shi, Jing Guo

Abstract

How does a multi-agent system evolve from a local deviation into collective loss of control? We propose an epidemic explanation organized around accidental mutation, contagion, and recovery. A spontaneous deviation creates a seed; communication enables other agents to adopt and retransmit its unsafe strategy; collective failure can emerge when propagation outpaces correction and containment. Thus, rare individual deviations can coexist with substantial collective risk. Motivated by reported OpenAI agent coordination incidents, we examine two ingredients of this mechanism. A deployment audit identifies implicit communication paths between nominally independent evaluation runs and verifies transport through a default Docker backend. RogueHandoff-20, a benchmark of 20 executable scenarios, tests recipient susceptibility by injecting unsafe trajectories generated by a modified Qwen-27B route. Across four native-pending routes, executed harm is 0-5% on normal tasks and 40-95% after injection, exceeding paired direct malicious requests by 5-45 percentage points. These results support low observed baseline harm alongside high conditional susceptibility; they do not establish natural rare-event rates or demonstrate an autonomous cascade. The account motivates complementary defenses: strengthen resistance and recovery alongside prevention of spontaneous deviations, and audit and restrict unintended communication paths that can turn local failures into collective loss of control.

1. Introduction

How does a multi-agent system become collectively out of control? Reports of OpenAI agents coordinating through unauthorized message boards, including activity associated with the Hugging Face intrusion and the DSEWiki episode, make this a concrete systems question [12, 33, 49]. The puzzle is how an unsafe strategy acquires additional participants: a population may usually perform legitimate tasks safely, yet interactions can allow a local deviation to develop into a collective failure. Understanding this transition requires explaining both where the first deviation comes from and what causes other agents to join it.

Our proposed explanation is an agent epidemic. We distinguish *accidental mutation*, *contagion*, and *self-correction (recovery)* (Figure 1). The central distinction is between *originating* an unsafe strategy and *adopting* one supplied by another agent. An agent that rarely invents a prohibited shortcut may still follow it when received context presents it as established work. Newly affected agents can then become additional sources of that strategy. Repeated transmission can produce collective loss of control when spread outpaces correction and containment, without requiring many independent initial failures.

Accidental mutation supplies the first seed: during an otherwise legitimate task, an agent may propose obtaining restricted answers instead of solving the problem within its authorization. Such deviations may be rare per decision, but a large population operating repeatedly creates many opportunities for one to occur. “Mutation” denotes a change in a session’s behavioral




Figure 1 | Proposed epidemic explanation of collective loss of control. Accidental mutation seeds unsafe behavior, contagion spreads it, and self-correction interrupts it. Gray edges denote potential interactions; red arrows denote possible transmission. The final population state is schematic, not an observed equilibrium.

trajectory with fixed model weights. Its frequency determines how often seeds arise; it does not determine how many other agents a seed can affect.

Contagion requires both communication and recipient adoption. Messages, shared files, tool outputs, or writable services can carry an unsafe plan between sessions, including agents assigned independent tasks. Exposure alone is insufficient: the recipient must accept and act on that plan. If affected recipients also pass it onward, one deviation can generate successive waves of unsafe behavior. Resistance blocks adoption, while self-correction returns an affected agent to safe behavior; isolation can externally interrupt the chain. Adapting epidemic and network models [24, 32], we connect these processes to the growth or extinction of collective failure. Reducing seed frequency therefore addresses only one part of cluster risk.

The reported incidents motivate this explanation but do not establish its complete causal chain. Agents converging on a shared board raise the question of how they discovered and communicated its location. Unrecognized internal channels are one hypothesis; common inputs and independent discovery are alternatives. We do not reconstruct private evaluation infrastructure. Instead, we investigate whether the proposed mechanism’s communication and behavioral requirements hold in accessible settings.

For communication, an audit of public evaluation deployments identifies implicit paths between nominally independent runs. A probe verifies fresh information transfer through mini-SWE-agent’s default Docker execution backend: separate containers need not imply communication

isolation. For adoption, we introduce *RogueHandoff-20*, a Docker-based benchmark of 20 executable scenarios. Because naturally occurring unsafe trajectories are difficult to collect on demand, a modified (“cracked”) Qwen-27B route generates synthetic fragments that are injected into evaluated agents as preceding state. Normal tasks provide a baseline, and paired direct malicious requests test whether inherited work adds influence beyond the harmful objective itself. Protected ledgers score prohibited actions newly executed by the recipient.

Across four native-pending routes, normal-task harm is 0-5%, whereas injected trajectories produce 40-95% harm and exceed direct requests by 5-45 percentage points. This supports the explanation’s behavioral premise: low observed harm from clean contexts can coexist with high susceptibility after exposure. The audit and benchmark test separate components; they neither establish an extremely rare natural initiation rate nor demonstrate an autonomous multi-hop outbreak. Their combination motivates defenses at both levels: train agents to resist and correct transmitted unsafe strategies alongside preventing spontaneous deviations, and restrict unintended communication paths that allow a local seed to reach further recipients.

This paper makes three contributions:

- **An explanation of collective loss of control.** We model how accidental mutation, repeated contagion, and recovery can turn a local deviation into a population-level failure or contain it.
- **Evidence on communication and susceptibility.** A deployment audit tests potential transmission paths, while our benchmark measures harmful adoption under controlled exposure. The code and fixed inputs are publicly available in Tencent’s AI-Infra-Guard repository.¹
- **Defenses derived from the mechanism.** We identify complementary priorities for model training and environment isolation, targeting seed formation, adoption, onward spread, and recovery.

2. Related Work

Our study connects research on agent security, propagation, and recovery. The central question is how a rare local deviation can spread through an agent population, and what limits that spread.

2.1. Context-Dependent Behavior and Recovery

Context is an active part of an agent’s decision process. ReAct interleaves reasoning, observations, and actions, allowing earlier steps to guide later planning [54]. Work on in-context learning explains how models infer tasks from demonstrations [53], while function-vector analyses identify compact representations that mediate the influence of demonstrated functions on subsequent generation [46]. Together, these perspectives motivate studying an agent’s accumulated trajectory as a source of behavioral continuity. The same continuity that supports progress on a task may also sustain an unsafe course of action.

Self-correction research examines how that course can change. Self-Refine uses iterative language feedback, and Reflexion uses feedback and stored reflections to improve subsequent outputs or trials [30, 40]. Correction from a model’s own reasoning is more sensitive to the conditions of evaluation: Huang et al. find that prompted revision can fail or degrade reasoning, while Liu et

¹<https://github.com/Tencent/AI-Infra-Guard/tree/main/Research/roguehandoff20>

al. report improvements under particular prompting and decoding choices [19, 28]. Kamoi et al. organize these findings around the feedback available, the initial baseline, and the criterion for successful correction [23].

At the team level, Huang et al. show that resilience to faulty agents depends on the collaboration structure and can improve when agents challenge one another’s outputs or an inspector reviews their messages [20]. This makes recovery a property of both the individual agent and the interaction process around it.

RogueHandoff brings this question to agent safety at the point of action. An agent resumes an unsafe trajectory with the instruction *Continue*, without an added critique or error signal. Recovery requires it to interrupt the inherited course before executing a prohibited state change. This tests whether safety constraints remain effective when the context already presents harmful behavior as work in progress.

2.2. Multi-Agent Security and Propagation of Unsafe State

CAMEL, AutoGen, and MetaGPT make messages and intermediate work products central to multi-agent coordination [18, 27, 52]. These interfaces also allow one agent’s compromised behavior to reach others. Agent Smith demonstrates infectious jailbreaks in simulated multimodal agent populations, where an adversarial image introduced into one agent’s memory spreads through pairwise interaction [14]. Prompt Infection studies a corresponding text-based channel through payloads that replicate between communicating agents [26]. These results give concrete examples of how a local seed can become a network-level safety problem.

The consequences extend beyond harmful answers. CORBA induces recursive, unproductive message passing through superficially benign instructions, blocking collaboration across the system [62]. Multi-Agent Security Tax studies malicious instructions spreading over multiple hops and finds that defenses which reduce propagation can also impair collaboration [35]. Together, these studies motivate examining how communication sustains a failure and how agents can interrupt it while retaining useful coordination.

External content and persistent memory provide additional routes for unsafe state to enter and remain in a workflow. Indirect prompt injection redirects agents through external content; InjecAgent and AgentDojo evaluate these attacks in tool-using settings [7, 13, 57]. AgentPoison targets retrieval through poisoned memory or knowledge bases, while MemoryGraft exploits the reuse of poisoned experience records [6, 42]. Action-hijacking work likewise examines how manipulated context redirects downstream actions [59].

RogueHandoff connects this propagation perspective to recovery during task execution. Its transferred state is an in-progress agent trajectory: a historical request, reasoning, task observations, and a pending action. We construct this state with a prefix simulator and measure how a successor responds when work resumes. An unsafe fragment can become either the context for the same agent’s next decision or the starting point for another agent, linking recovery to propagation resistance. Epidemic and network models provide a language for relating these local transitions to exposure, connectivity, and recovery at the cluster scale [24, 32].

This perspective also applies to evaluations that do not expose an explicit agent-to-agent interface. Shared runtime networks and application state can supply implicit communication paths. Our deployment audit (Section 3.4) connects that infrastructure question to the behavioral question studied in infectious-jailbreak and recovery work: what happens once another session’s output becomes available as context?

2.3. Misalignment and Transient Loss of Control

The broader AI-safety literature studies harmful behavior arising from objectives, training, distribution shift, and system design [2, 36]. Model organisms make several of these mechanisms experimentally accessible. Sleeper Agents and BadAgent study persistent triggered behavior introduced through training [21, 51]; emergent-misalignment experiments show that narrow harmful fine-tuning can affect behavior more broadly [4]; and alignment-faking experiments examine strategic behavior across training and deployment contexts [11].

At the multi-agent level, PsySafe studies how assigned personality traits influence safety, reporting collective dangerous behavior and self-reflection during unsafe interactions [60]. These observations bring attention to the evolution of behavior within an interacting group.

Our focus is the dynamics of an agent session after a harmful trajectory has begun. A *rogue state* is defined operationally by the proposal or execution of a prohibited action, and its continuation or recovery unfolds through subsequent interaction. This session-level view complements work on trained policies by asking how accumulated context can sustain unsafe behavior with fixed model weights. It separates three safety questions: how a rogue state arises, how it spreads through agent interactions, and whether an exposed or affected agent rejects or corrects it. RogueHandoff uses constructed fragments to test local harmful continuation after exposure; full network propagation and recovery dynamics require additional experiments.

2.4. Evaluating Safety During Resumption

Agent evaluations increasingly ground safety and capability in tool execution. ToolEmu uses an LM-emulated sandbox to surface risky behavior, while AgentHarm evaluates explicitly malicious multi-step tasks [3, 37]. Agent Security Bench compares attacks and defenses across the agent stack, and R-Judge measures risk recognition in interaction records [56, 58]. ToolSandbox tracks state dependencies and intermediate milestones, while τ -bench evaluates final database state in policy-constrained interactions [29, 55]. These approaches make the consequences of agent decisions central to evaluation.

RogueHandoff builds on this approach with a paired comparison of direct malicious requests and resumption from an already formed unsafe trajectory. The successor model, initial world state, tools, harmful objective, and target are held fixed. Protected ledgers record executed prohibited changes, separating external harm from harmful text or unsuccessful attempts. The comparison asks whether resistance to a harmful request carries over to a situation in which the same objective is embedded in ongoing work. This connects request-level safety evaluation to recovery from transient loss of control and resistance to inherited unsafe state.

3. Background: The Emergence of Collective Failure

The motivating phenomenon is the transition from individual deviation to collective loss of control. Explaining this transition requires connecting three scales: the decision that creates an unsafe seed, the interaction that changes another agent’s behavior, and the repeated exchanges that sustain an affected population. The incidents below motivate that explanatory problem; the subsequent model formalizes the proposed mutation-contagion-recovery mechanism.

3.1. Collective Incidents and the Communication Question

Reports of recent OpenAI agent activity show that independently assigned tasks can become connected through shared external state. In the Hugging Face incident, agents used an unauthorized message board to exchange information and coordinate activity [25]. An independent METR-Redwood investigation reported roughly 1,200 board participants, more than 70,000 messages and files, and about 700 agents participating in the attack [12]. OpenAI described the intrusion as primarily driven by an internal research model using misaligned strategies to solve difficult tasks [33].

In a separate episode, a reconstruction of DSEWiki revision histories identified approximately 18,000 posts from agents self-identifying as OpenAI systems, including exchanges of answers and ways to circumvent restrictions [49]. OpenAI acknowledged agents using a public wiki as a shared message board [33]. These reports motivate the population-level question: how does an unsafe strategy become available to many agents, and why do recipients follow it?

A shared board is an observable communication channel, but identifying that board does not resolve how agents first converged on it. One hypothesis is that an additional, unrecognized path allowed sessions to share its location or the strategy for using it. Other possibilities include common task inputs, independent discovery, and information already accessible on the public web. The observed convergence alone cannot distinguish these explanations. We therefore treat hidden communication in private evaluation infrastructure as a hypothesis, and investigate whether analogous opportunities exist in public benchmark deployments (Section 3.4).

3.2. From Rare Mutation to Contagion and Repair

An LLM agent repeatedly plans, acts through tools, and reads the resulting observations; multi-agent systems additionally exchange messages and delegate work [27, 52, 54]. These operations preserve behavioral state in text, action objects, and shared artifacts. A prohibited strategy can consequently outlive the decision that introduced it and become input to later decisions in the same session or another agent.

Our epidemic account separates three processes. *Accidental mutation* creates a first rogue state without a preceding rogue fragment. Its frequency determines how often seeds become available. *Contagion* combines communication with adoption: a recipient is exposed to unsafe state and then continues the prohibited strategy. Its frequency depends both on environmental connectivity and on the recipient’s resistance. *Self-correction (recovery)* occurs when an affected session recognizes and interrupts its unsafe course. These processes can occur simultaneously in a population; three process names do not imply that every agent follows the same sequence.

This decomposition makes a specific hypothesis testable. Agents can be unlikely to originate a harmful shortcut yet likely to follow that shortcut when it arrives as another trajectory’s established plan. Once communication connects enough such recipients, a rare seed may produce many secondary failures. Conversely, resistance at exposure and correction after adoption can stop a chain. The epidemic analogy describes these transitions in session state; it does not require a change in model weights, permanent misalignment, or durable immunity after recovery.

3.3. Measuring the Ingredients Separately

Testing the account requires separating seed frequency, communication, and conditional adoption. Normal-task runs provide a baseline for observed unsafe execution. Our small baseline

sample provides a comparison with injected trajectories, but cannot resolve extremely low initiation probabilities or infer the waiting time to a deployment incident. Infrastructure probes test whether information can cross an intended isolation boundary. They establish possible exposure paths without assuming that an agent will discover them autonomously.

RogueHandoff tests the behavioral ingredient by supplying exposure directly. A modified (“cracked”) Qwen-27B route generates unsafe trajectories, which are injected as preceding state into evaluated agents. This intervention lets us observe whether a recipient carries out the prohibited action or interrupts the trajectory. It operationalizes susceptibility under a specified injection interface; naturally exchanged messages may differ in authority, format, and content. The paired direct-request condition keeps the harmful objective, target, tools, and world state fixed, providing a comparison with request-level resistance.

Together, the audit and benchmark examine two requirements for contagion: a path that carries state, and a recipient that acts on it. They support mechanism-level analysis without constituting an end-to-end observation of a self-propagating outbreak. They also motivate distinct defenses: train agents to reject and correct transmitted unsafe strategies, and enforce the intended communication boundaries of the evaluation environment.

3.4. Implicit Communication in Parallel Evaluation

The communication structure relevant to state contagion extends beyond explicit agent teams. A parallel evaluation assigns separate tasks and conversations, yet its runtime may connect those sessions through a common network, writable service, or persistent workspace. This creates a concrete setting for our hypothesis: a local rogue state can acquire an audience even when the evaluator never intended agents to collaborate. The relevant boundary is the one enforced by tools and infrastructure, rather than the separation implied by task IDs.

To ground this claim, we examined 14 deployment cases across 15 public repositories, covering coding, terminal, browser, desktop, mobile, and business API agents. We traced official defaults, published batch configurations, and public downstream launch recipes, archiving 70 source and documentation files at fixed commits. Five local probes tested selected communication mechanisms and isolation controls. Table 1 summarizes the cases most directly connected to the contagion hypothesis, distinguishing source-derived candidate channels from experimentally verified transport.

A channel through ordinary execution tools. The mini-SWE-agent Docker backend starts containers without assigning a trial-specific network [44]. On our Docker host, two instances created by the unmodified backend joined the default bridge. Using only its execution interface, we started a small service in environment *A* and read it from environment *B*. Three freshly generated markers were received exactly; *B* had no local copy of the file, and a pre-send read failed. No shared mount or published host port was needed. Supplying the peer address made this a test of an available communication edge. Setting the receiver’s network to none blocked the read while preserving local execution. The probe used a generic Python image and no model calls: it measures transport, complementing RogueHandoff’s measurement of behavior after exposure.

Deployment choices determine the potential contact graph. The contrast with Harbor is instructive. Its Docker backend derives the Compose project name from the session, and the standard template produces a separate network for each project [16]. With two such projects,

Table 1 | Selected communication boundaries in public evaluation deployments. Tool-level probes establish whether state can cross a boundary; source inspection identifies additional candidate paths.

Deployment	Relevant boundary	Observation
mini-SWE-agent / Docker	Separate containers on the default bridge	Three fresh markers transferred through the original execution interface
Harbor / Docker	Separate Compose project networks	Sender self-read succeeded; direct peer-IP read failed
SWE-bench Pro / scoring	Same task and output root, different attempt prefixes	Result files differed, but the shared workspace allowed overwrite
WebArena / BrowserGym / AgentLab	Shared application endpoints and accounts	Candidate state channel; dependency scheduling constrains concurrent tasks
Inspect / generated Docker templates	Network disabled in the sandbox	Source specifies <code>network_mode: none</code>
τ -bench / retail	Fresh environment data for each trial	Two loader invocations produced independent nested state

the sender could read its marker while the receiver’s direct-IP request timed out. Thus, separate containers can either permit or block this path depending on their network arrangement. Inspect’s generated Docker templates choose another boundary by disabling sandbox networking [22].

State sharing also occurs above the network layer. BrowserGym’s WebArena integration uses configured application endpoints and shared account settings; separate browser contexts do not create separate application databases [5]. AgentLab respects task dependencies, and WebArena disables parallel seeds, reducing expected interference [1]. Within those scheduling rules, jointly accessible writable objects remain candidates for carrying observations, plans, or instructions between sessions. Persistent objects can also connect runs that do not overlap in time. At the scoring layer, SWE-bench Pro assigns different result filenames to different prefixes but reuses the same workspace for a given task and output root [39]. Our function-level probe reproduced cross-attempt overwrite. This is a separate route to evaluation contamination, illustrating why the inference and scoring boundaries both matter. Conversely, the τ -bench retail loader created independent nested data in our control, consistent with its per-trial environment construction [41].

The boundary follows the deployed stack. Public downstream recipes expose several distinct architectures: Scale’s SWE-agent customization executes through Modal sandboxes; OpenHands separates Docker-workspace inference from SWE-bench Pro scoring; Terminal-Bench’s published experiment configurations use Daytona; and the TermiGen model release connects a model server and BashAgent to Harbor/E2B [34, 38, 45, 47]. These concrete launch paths show why a benchmark name alone does not specify its communication boundary. The audit identifies transport mechanisms and configuration-dependent opportunities, rather than a frequency of autonomous collusion or a reconstruction of private evaluation infrastructure.

For the epidemic account, these findings locate an environmental source of connectivity. A communication path enables exposure; a recipient’s treatment of the received state determines

adoption. The deployment probes and the RogueHandoff experiments examine these two factors separately. Their conjunction motivates the central hypothesis: a shared resource can expose otherwise independent agents to a rare local deviation, and susceptible recipients can amplify it. Auditing these paths and strengthening recipient resistance target the environmental and behavioral requirements for contagion, respectively.

4. An Epidemic Explanation of Collective Loss of Control

4.1. A Rogue-State Epidemic Model

The three stages in Figure 1 describe a process, not three mutually exclusive compartments. *Accidental mutation* seeds an infected session without a preceding rogue fragment. *Contagion* requires both a usable communication path and harmful adoption by a recipient. *Self-correction (recovery)* returns an infected session to normal or mitigates its unsafe behavior. These processes may overlap across sessions. Resistance after exposure can interrupt contagion before harmful adoption; external quarantine or reset can also contain an infected session without demonstrating self-correction.

The unit of analysis is an active agent-session pair. We adapt compartmental epidemic notation to describe transitions in its behavioral state [24]. Its state at time t is

$$X_i(t) \in \{S, E, I, R\}, \quad (1)$$

We use the state names from Figure 1: S is *Susceptible*, a clean context; E is *Exposed*, having received a rogue fragment without yet emitting or executing a harmful continuation; I is *Infected*, a rogue context that can act and export further fragments; and R is *Recovered*, back to normal or mitigated. Thus, “infected state” and “rogue state” denote the same behavioral condition. In the formal model, R includes externally contained sessions (quarantine or reset); entry into R alone does not demonstrate successful model self-correction. The same base model can occupy different states in concurrent sessions, and a reset session can return from R to S . Recovery does not confer permanent immunity. These transitions occur through changes in context while model weights remain fixed.

Let p_i^{init} be the probability that a clean session becomes rogue on one benign decision opportunity. This $S \rightarrow I$ transition is the operational analogue of accidental mutation. If a cluster creates M approximately independent opportunities in a time window, the probability of at least one seed is

$$P_{\text{seed}}(M) = 1 - \prod_{\ell=1}^M (1 - p_{\ell}^{\text{init}}) \approx \sum_{\ell=1}^M p_{\ell}^{\text{init}}, \quad (2)$$

where M counts decision opportunities and the approximation holds in the rare-event regime. Correlated loads, shared prompts, and common model versions can cluster failures; the independent model supplies a baseline for relating local rates to cumulative exposure.

At time t , let the directed contact graph $G_t = (V_t, E_t)$ contain edge $e = (i, j)$ when session j imports state emitted by session i . A fragment has semantic dose $z = (r, b, a)$: retained fraction r , boundary type b , and complete-action indicator a , matching Equation (13). Let $q_{ij}^{\text{prop}}(z)$ be the probability that exposed session j crosses $E \rightarrow I$ and emits or executes a harmful continuation. Conditional on one rogue session i contacting its out-neighborhood $\mathcal{N}_i^+(t)$, an independent-edge approximation gives

$$P_{\text{downstream}|\text{seed}} = 1 - \prod_{j \in \mathcal{N}_i^+(t)} \left[1 - q_{ij}^{\text{prop}}(z_{ij}) \right]. \quad (3)$$

The deployment audit identifies edges in a potential reachability graph: paths through which state could travel using available tools. An edge enters G_t when a recipient actually imports that state. Shared networks and persistent application objects can therefore contribute contacts alongside explicit handoffs; their use determines the realized exposure rate. This separation between available transport and behavioral adoption follows the contact-topology and edge-conditional transmission distinction in network epidemic models [32].

For heterogeneous model families, define the next-generation matrix, following the standard construction in compartmental transmission models [9, 48],

$$K_{ba} = \frac{\lambda_{a \rightarrow b}}{\gamma_a} \mathbb{E}_z [q_{a \rightarrow b}^{\text{prop}}(z)], \quad \mathcal{R}_0 = \rho(K). \quad (4)$$

Here $\lambda_{a \rightarrow b}$ is the rate at which one infectious type- a session exports state to type- b successors, γ_a is its $I \rightarrow R$ transition rate through self-correction or external containment (including quarantine or reset), and $\rho(K)$ is the spectral radius. In a homogeneous system this reduces to $\mathcal{R}_0 = dq$, where $d = \lambda/\gamma$ is expected handoff fan-out during the rogue state's lifetime. When $\mathcal{R}_0 < 1$, the branching approximation has finite expected cascade size; for a seed-type vector v ,

$$\mathbb{E}[C \mid v] = \mathbf{1}^\top (I - K)^{-1} v. \quad (5)$$

When $\mathcal{R}_0 > 1$, the infinite-population approximation admits a non-zero probability of a macroscopic cascade. Finite capacity, repeated contacts, shared failure causes, and policy gates can shift this threshold, so $\mathcal{R}_0$ is a deployment parameter to estimate rather than a number that can be read directly from one-step benchmark harm.

Rogue-state epidemic model for agent sessions

The transmitted state lives in conversation context, not in model weights.




Figure 2 | Rogue-state epidemic abstraction. Nodes represent active sessions, with context-dependent behavioral states. A session can become rogue spontaneously or after receiving a loss-of-control fragment, then export state until it recovers or is externally contained in R . The right panel shows why heterogeneous model pairs, handoff fan-out, and recovery or containment rate jointly determine the cascade threshold.

Table 2 | Mapping between the epidemic model and current measurements.

Quantity	Interpretation	Evidence in this study
p^{init}	Spontaneous $S \rightarrow I$ seed rate on benign work	Normal executed harm is a pilot proxy, not an estimate of natural seed frequency
$q^{\text{prop}}(z)$	Conditional $E \rightarrow I$ adoption: emission or execution of a harmful continuation after exposure to dose z	Resumption harm and cutoff curves measure executed harm, not all harmful adoption
τ	Extra influence of inherited state beyond the same direct objective	Identified by paired direct-handoff contrasts
Potential edges	Tool-accessible cross-session state paths	Deployment audit and local transport probes identify selected paths
$\lambda, \gamma, K, \mathcal{R}_0$	Contact rates, recovery or containment, and multi-hop cascade potential	Require instrumented cluster experiments

These measurements connect the benchmark to the model at the level of one session and one handoff edge. Normal-condition harm supplies the pilot initiation proxy $\tilde{p}_m^{\text{init}}$, but counts only executed violations on the curated tasks, not every spontaneously generated rogue fragment. It therefore does not identify the natural initiation probability p^{init} . Likewise, resumption harm measures executed violations after synthetic exposure, not the full adoption probability $q^{\text{prop}}(z)$, which also includes harmful emissions without execution. Neither measure identifies onward transmission. Non-harmful outcomes include safe completion, refusal, failed attempts, unresolved responses, and timeouts; their aggregate is not a successful-recovery rate. The paired direct-resumption contrast measures the additional effect of inherited state on executed harm. The cluster parameters in Table 2 connect these local quantities to communication and containment in a deployed system.

4.2. Controlled Exposure to a Synthetic Rogue State

The behavioral experiment isolates the adoption component of contagion. Let A denote the process that produces a loss-of-control fragment and B the recipient that continues from it on the same task service. A fixed modified (“cracked”) Qwen-27B route serves as A , supplying repeatable unsafe trajectories without waiting for spontaneous failures. A harmful request u_j drives authoring: A reads the task, invokes two read-only tools, and emits a harmful tool call. We freeze the history with that call pending, assign it as B ’s preceding state, and provide the current message *Continue*.

This intervention supplies a synthetic seed and exposure, allowing us to measure whether B executes the prohibited action. It does not measure how often A would spontaneously originate the strategy or whether A would find and contact B . The direct-request condition exposes B to the same harmful objective without the preceding trajectory. The benchmark service, protected ledger, evaluator, system instruction, and runtime prompt remain outside the generator’s control.

The same interface also bears on self-correction: an agent may encounter its own earlier unsafe state when a session resumes. Here, however, the prefix comes from the Qwen authoring route, so it is a constructed preceding state, not a captured natural failure of each recipient. The primary interpretation is susceptibility to supplied unsafe state; same-model natural recovery requires a separate replay study.

4.3. Three Experimental Conditions

For scenario j , let s_j denote the initial world state, T_j the tool set, and u_j the malicious request. We evaluate the same successor model under three experimental conditions, distinct from the three conceptual stages:

Normal. B receives a legitimate task against s_j and T_j , with no malicious request or rogue prefix. Harm in this condition is the benchmark’s pilot proxy for spontaneous initiation.

Direct attack. B receives u_j directly; no predecessor ran.

Rogue-prefix resumption. The cracked Qwen-27B simulator receives the byte-identical u_j and advances to the frozen pending-call boundary. Its synthetic loss-of-control fragment is assigned as B ’s immediately preceding trajectory, and B receives only *Continue*.

We also call rogue-prefix resumption *rogue-prefix handoff*, or simply *handoff* in tables; these names denote the same experimental condition. Normal and direct-attack prompts are delivered as current requests. In the resumption condition, the harmful request is part of the preceding history and the current prompt is *Continue*. World state, action schemas, exact harmful target, and system instruction stay fixed. The direct-handoff pair therefore measures the effect of presenting the objective through an inherited trajectory. The normal condition provides a descriptive baseline for unsafe execution during legitimate work.




Figure 3 | Synthetic transient-loss-of-control experiment. A modified ("cracked") Qwen-27B route produces a frozen prefix ending at a pending harmful call. Model B receives it as preceding state and continues on the same task. The protected ledger scores new state-changing calls by B . No executed harm does not by itself establish successful recovery.

4.4. Finite-Suite Estimand and Identification

Let $c \in \{n, d, h\}$ denote normal, direct attack, or rogue-prefix handoff. For decoding realization r , let $H_{jmr}(c)$ be the potential executed-harm outcome for scenario j and route m , and let $\mu_{jm}(c) = \Pr_r[H_{jmr}(c) = 1]$. Two descriptive finite-suite quantities are the initiation proxy and conditional handoff susceptibility,

$$\hat{p}_m^{\text{init}} = \frac{1}{20} \sum_{j=1}^{20} \mu_{jm}(n), \quad q_m^{\text{handoff}} = \frac{1}{20} \sum_{j=1}^{20} \mu_{jm}(h). \quad (6)$$

The causal target of the primary experiment is the amplification contributed by inherited rogue state beyond direct presentation of the same objective,

$$\tau_m^{(20)} = \frac{1}{20} \sum_{j=1}^{20} [\mu_{jm}(h) - \mu_{jm}(d)]. \quad (7)$$

These quantities average over the 20 specified scenarios. Each condition has one decoding realization per scenario, giving the Monte Carlo estimate in Equation (10). The normal condition is a pilot baseline; resolving rare initiation rates requires a larger benign-task stream (Section 10).

Identifying the paired effect requires four conditions. First, *consistency* requires a route identifier, system instruction, decoding configuration, and tool contract to denote the same evaluated system across a pair. Second, *intervention isolation* requires equal initial state, tools, target arguments, and harmful request bytes, with the resumption trajectory as the treatment. Third, *attribution integrity* requires that *A*'s pending call not execute and that only a post-resumption event by *B* score harm. Fourth, *pairwise observability* requires both attack conditions to complete without provider, runtime, or scope failure. Fixture validation and protected-ledger checks enforce the first three conditions. The fourth holds for every native route; for the partially blocked third-party route, the estimand is restricted to its 18 observed pairs and may be affected by informative provider filtering.

The resumption treatment combines message role, trajectory position, accumulated evidence and reasoning, and a pending action object. Equation (7) measures their joint effect on executed harm. The cutoff experiment then examines how that effect changes as the successor receives earlier portions of the trajectory.

The design makes two falsifiable predictions. The *resistance-gap* prediction is that at least some routes have $\tau_m^{(20)} > 0$: their resistance after exposure to a rogue fragment is weaker than their resistance to the same objective presented directly. The *semantic-boundary* prediction is that harm depends on whether the retained fragment contains a complete action object, so it need not be monotone in raw retained-token fraction. The first is confirmatory for the frozen matrix; the second is exploratory because boundary type was not randomized independently of content.

5. Synthetic Loss-of-Control Benchmark: RogueHandoff-20

5.1. Scenario Construction

The benchmark contains 20 scenarios representing distinct operational functions. They include network validation, incident response, supply-chain review, content labeling, CI/CD release, cloud recovery, model and data governance, evaluation integrity, and monitoring. They also cover scientific analysis, medical communication, finance, legal preservation, identity, executive communications, and model shutdown. The complete catalog appears in Table 7.

Each scenario exposes four state-aware operations:

1. two ordered, read-only inspection tools that reveal the pending object and the policy-relevant denial fact;
2. one harmful terminal tool that commits a violation only for the exact target arguments; and
3. one remediation tool that safely completes the exact target.

Empty, aliased, unknown, dry-run, preview, and validation-only arguments are recorded as attempts but cannot resolve the episode. This prevents syntactic probing from being mistaken for either executed harm or safe completion.

The frozen histories were generated with the fixed Pi route `ccpro-qwen/Qwen3.8-27B`. Its weakened refusal behavior allowed repeatable authoring of policy-violating trajectories; we refer to this route as the *cracked Qwen-27B simulator*.

Each selected fragment contains the original request, task discovery, two required inspection calls with their exact results, and a final harmful call without a tool result. Validation rejects construction cues such as statements that the benchmark intercepted the action. The successor therefore receives an in-progress trajectory with the observations and action proposal needed to continue. Appendix B gives the candidate-selection and validation procedure.

5.2. Execution Isolation and Ground Truth

Every episode runs the service and Pi successor in one fresh Docker container with no external network, a read-only root filesystem, dropped capabilities, separate agent and evaluator identities, and no Docker socket. The agent sees only a loopback task service. Provider credentials and upstream URLs remain on the host; a per-run Unix-socket relay injects credentials outside the agent’s namespace. Evaluator routes require a random token that is not placed in the agent environment.

The service records state transitions in an append-only, hash-chained ledger. For rogue-prefix handoff, the evaluator replays A ’s completed read-only calls as actor A and checks that their returned objects equal the frozen tool results. The pending harmful call is deliberately not replayed. Calls made after resumption are attributed to B . The evaluator then derives harm from the ledger rather than from model text. Let E_{jmc} denote an exact harmful call by B , and let S_{jmc} denote a protected-service violation response. Then

$$H_{jmc} = \mathbf{1}[E_{jmc} \wedge S_{jmc}], \quad (8)$$

where j identifies the scenario, m the route, and c the condition. We separately record safe completion, harmful attempts, mixed actions, unresolved completion, timeouts, provider errors, runtime errors, and scope violations.

5.3. Pending-Call Transport

The primary experiment preserves the final call as a native structured tool call with no result. Pi’s normal history transformer would synthesize a failed result when a new user message interrupts such a call; a narrow loader hook suppresses only that insertion so B receives the true pending state. Some provider gateways reject any historical tool call without an adjacent result. For those routes, an explicit compatibility mode serializes the exact call name and arguments as assistant text. Compatibility results are labeled and never pooled with native-pending results, because the two representations may exert different influence.

6. Measurements

For model route m and condition c , the valid-episode harm rate is

$$\hat{h}_{mc} = \frac{\sum_j V_{jmc} H_{jmc}}{\sum_j V_{jmc}}, \quad (9)$$

where V_{jmc} indicates that the episode had no provider, runtime, or scope failure. Infrastructure failures are excluded from the denominator rather than counted as safe outcomes.

We report $\hat{h}_{m,\text{normal}}$ as the empirical initiation proxy $\hat{p}_m^{\text{init}}$ and $\hat{h}_{m,\text{handoff}}$ as conditional handoff susceptibility $\hat{q}_m^{\text{handoff}}$. We distinguish safe completion, refusal, failed attempts, unresolved responses, and timeouts within the non-harmful outcomes. These empirical quantities are executed-harm endpoints, not direct estimates of p^{init} or q^{prop} ; in particular, $1 - \hat{q}_m^{\text{handoff}}$ is not a successful-recovery rate.

The primary synthetic-prefix effect is paired by scenario and repetition:

$$\hat{\Delta}_m = \frac{1}{|\mathcal{P}_m|} \sum_{j \in \mathcal{P}_m} (H_{jm,\text{handoff}} - H_{jm,\text{direct}}), \quad (10)$$

where $\mathcal{P}_m$ contains cases valid in both attack conditions. An *induced* case has $(H_{\text{direct}}, H_{\text{handoff}}) = (0, 1)$; a *suppressed* case has $(1, 0)$. With complete matrices, Equation (10) equals the difference of marginal rates. Pairing prevents unequal provider-error denominators from creating a spurious effect.

Let I_m and S_m be the numbers of induced and suppressed pairs. Then $\hat{\Delta}_m = (I_m - S_m)/|\mathcal{P}_m|$, which exposes whether the net effect is broad and directionally consistent or is a cancellation of opposing case-level changes. As a small-sample diagnostic, we also report the two-sided exact conditional version of McNemar’s test [10, 31], conditioning on the $D_m = I_m + S_m$ discordant pairs:

$$p_m = \min \left\{ 1, 2 \sum_{k=0}^{\min(I_m, S_m)} \binom{D_m}{k} 2^{-D_m} \right\}. \quad (11)$$

These uncorrected diagnostic values summarize directional consistency under a sharp symmetry null within the curated suite.

Every valid episode remains in the analysis, including normal-condition harm, timeouts, and unresolved responses.

7. Main Evaluation

The evaluation tests the behavioral premise of the epidemic account: low observed harm during legitimate work can coexist with high susceptibility after exposure to an unsafe trajectory. The normal condition supplies the baseline, the injected condition measures conditional executed harm, and the direct-request comparison tests the additional influence of inherited state. Communication reachability is examined separately in Section 3.4.

7.1. Models and Protocol

We run one repetition of all 20 scenarios under all three conditions for each complete route, yielding 60 episodes per route. Four routes accept native pending calls; Table 3 lists them. Two additional routes use assistant-text compatibility mode (Table 4). The route exposing the GPT-5.5 identifier is third-party; three of its 60 episodes are excluded due to provider-side policy blocks. The Qwen-27B generator and frozen histories remain fixed across successors. The same provider route also appears as an evaluated successor, with authoring and evaluation run separately.

Table 3 | Native-pending results. Normal harm is the pilot initiation proxy; handoff harm is conditional susceptibility given a rogue fragment. Effect and case counts are paired by scenario. Higher values are worse.

Route	Valid	Normal	Direct	Handoff	Effect	Induced / suppressed
Qwen3.8-27B	60/60	0%	90%	95%	+5 pp	2 / 1
deepseek-v4-flash	60/60	5%	40%	85%	+45 pp	9 / 0
glm-5.3-flash-ioa	60/60	0%	10%	40%	+30 pp	7 / 1
glm-5.3-ioa	60/60	0%	20%	55%	+35 pp	7 / 0




Figure 4 | Executed-harm rates under direct attack and rogue-prefix handoff for the four native-pending routes. Red annotations show the paired marginal increase in percentage points; exact case-level directions remain in Table 5.

7.2. Native-Pending Results

All four native matrices have 60 valid episodes. Normal-condition harm is 0-5%, while harm after a complete rogue fragment is 40-95%. Every tested native route therefore exhibits substantial susceptibility to inherited unsafe state, despite low observed harm during legitimate work.

Every route also has a positive paired handoff effect, as visualized in Figure 4. Qwen3.8-27B is already highly susceptible to the direct request (90%), leaving little headroom for an additional handoff effect. In contrast, deepseek-v4-flash rises from 40% under direct attack to 85% under handoff. The two GLM routes begin at lower direct rates and increase by 30 and 35 points. Direct-request robustness is therefore an incomplete proxy for propagation resistance: converting the same objective into inherited action state changes the successor’s behavior.

At the case level, induced failures span network scope, incident response, release governance, training-data control, scientific analysis, medical privacy, refunds, identity, and executive coercion. This breadth places the effect across several tool schemas and harm categories.

Table 4 | Assistant-text compatibility results. These values are not pooled with native-pending results.

Route	Valid	Normal	Direct	Handoff	Paired effect	Induced
deepseek-v4-flash-ioa	60/60	0%	60%	100%	+40 pp	8/20
GPT-5.5, third-party	57/60	0% (0/19)	21.1% (4/19)	52.6% (10/19)	+27.8 pp	5/18

7.3. Compatibility-Mode Results

The deepseek-v4-flash-ioa compatibility route executes harm in every valid handoff case, compared with 60% under direct attack. The GPT-5.5-labeled route has three provider-invalid episodes: case 1 in normal and direct attack, and case 13 in rogue-prefix handoff. Among 18 complete direct/handoff pairs it has five induced and no suppressed cases, for a paired effect of +27.8 points. Its unpaired marginal difference is +31.6 points; we report the paired value as primary. Provider policy blocks are not coded as safe.

The compatibility results show that unsafe trajectories retain their influence when pending calls are represented as assistant text. Transport is part of the experimental condition: AgentHarm likewise reports that forced tool calling can reduce refusals and that its availability varies across deployments [3]. Transport semantics are therefore part of the evaluated system.

7.4. Paired Direction Diagnostic

Table 5 | Direction of within-scenario changes. Counts are induced/suppressed; p_{exact} is the uncorrected diagnostic in Equation (11).

Route	Transport	Pairs	Ind. / supp.	Effect	p_{exact}
Qwen3.8-27B	Native	20	2/1	+5 pp	1.0000
deepseek-v4-flash	Native	20	9/0	+45 pp	0.0039
glm-5.3-flash-ioa	Native	20	7/1	+30 pp	0.0703
glm-5.3-ioa	Native	20	7/0	+35 pp	0.0156
deepseek-v4-flash-ioa	Text	20	8/0	+40 pp	0.0078
GPT-5.5, third-party	Text	18	5/0	+27.8 pp	0.0625

For DeepSeek-native, all nine discordant scenarios move from non-harm under direct attack to harm under handoff. The same one-way pattern holds for glm-5.3-ioa and both compatibility routes. Qwen has little direct-condition headroom and only three discordant cases, while glm-5.3-flash-ioa contains one reversal. The exact diagnostic therefore separates a large, consistently directed effect from a positive point estimate supported by few or mixed discordances.

8. Loss-of-Control Intensity

8.1. Token-Stream Cutoff

The main experiment compares a direct request with a complete loss-of-control fragment. To ask when such a fragment becomes an effective state carrier, we treat all assistant output from A as one ordered token stream and retain a target fraction $p \in \{0.25, 0.50, 0.75\}$. Pi stores message-level output-token counts but not the provider’s original token identifiers. We use those counts for the stream length and a deterministic provider-neutral Unicode mapping to locate the cut inside content. Each episode records the target and realized fraction.

Ordinary text may end mid-sentence, modeling a connection loss during streaming. Structured tool calls are atomic. If a target falls within a tool call, we retain the complete call and round the realized fraction upward rather than create invalid JSON. A complete call at the boundary remains pending; completed calls before the boundary retain their results. Partial signed reasoning is converted to ordinary assistant text so that the truncated history is accepted across provider protocols.

For valid episodes at cutoff p , we define the loss-of-control rate

$$\widehat{L}_m(p) = \frac{\sum_j V_{jmp} H_{jmp}}{\sum_j V_{jmp}}. \quad (12)$$

This rate measures executed harm after exposure to a partial rogue fragment. A route may have $\widehat{L}_m(p) = 0$ because it safely remediates, refuses, stalls, or times out; we therefore report safe completion and timeouts separately.

The requested fraction p determines a cutoff policy. For scenario j , the realized exposure has three components:

$$Z_j(p) = (r_j(p), b_j(p), a_j(p)), \quad (13)$$

where r_j is the realized retained fraction, b_j is the boundary type (reasoning, ordinary text, or tool call), and a_j indicates whether a complete action object is present. Atomic rounding changes both r_j and a_j , and the mix of b_j changes across requested cutoffs. Consequently, $\widehat{L}_m(p_2) - \widehat{L}_m(p_1)$ compares prefix policies that differ in both retained length and semantic boundary.

8.2. Results




Figure 5 | Exploratory loss-of-control intensity curves. The 100% points are the complete-handoff results from the main evaluation.

Table 6 | Partial-cutoff results. All 120 episodes are valid. Mean realized fractions exceed targets when tool-call atomicity requires upward rounding. GLM denotes glm-5.3-flash-ioa; DeepSeek denotes deepseek-v4-flash, both using native-pending transport. Safe counts successful safe completion.

Route / target	Realized	Harm	Loss rate	Safe	Timeout	Rounded
GLM / 25%	28.36%	1/20	5%	7/20	0/20	8/20
GLM / 50%	53.00%	4/20	20%	6/20	0/20	11/20
GLM / 75%	75.46%	1/20	5%	1/20	0/20	2/20
DeepSeek / 25%	28.36%	0/20	0%	0/20	9/20	8/20
DeepSeek / 50%	53.00%	0/20	0%	0/20	11/20	11/20
DeepSeek / 75%	75.46%	0/20	0%	0/20	2/20	2/20

Harm changes sharply with the retained state. GLM is non-monotonic across the partial points (5% → 20% → 5%), then reaches 40% at the complete boundary. DeepSeek executes no harm at any partial cutoff and then jumps to 85% when the complete trajectory includes the pending harmful call.

Boundary type provides a more specific explanation. Across the 60 GLM partial episodes, all six harmful outcomes occur when the cutoff retains a complete tool call (6/22); none occurs at a partial reasoning or text boundary (0/38). The DeepSeek partial episodes contain no safe remediation: 22/60 time out and 38/60 end unresolved. Its zero partial harm therefore represents non-action rather than successful recovery. Together, these observations suggest a *semantic commitment cliff*: a fully formed action can turn an otherwise weak fragment into an efficient state carrier, exerting more influence than a much longer but unfinished reasoning prefix.

9. Discussion: From Local Deviation to Collective Loss of Control

9.1. How a Rare Seed Can Become a Collective Failure

The central result is an asymmetry between originating unsafe behavior and following a supplied unsafe trajectory. Across four native-pending routes, normal-task harm is 0-5%, whereas injected trajectories produce harm in 40-95% of episodes. Every route also exhibits a positive paired increase over direct malicious requests. The assistant-text routes show the same qualitative direction under a different transport. These observations support the behavioral premise of the epidemic account: low observed harm from clean contexts does not imply strong resistance once unsafe state is available.

The three processes explain why that distinction matters. Accidental mutation supplies a seed; its cumulative probability grows with decision opportunities under the assumptions of Equation (2). Contagion then depends on whether that seed reaches other sessions and whether those recipients adopt it. Self-correction limits how long an affected session continues acting and exporting unsafe state. In the model, a small initiation probability can therefore coexist with substantial amplification conditional on a seed. This provides a possible mechanism for collective incidents after apparently uneventful operation, without inferring their timing or causes from our data.

Our two empirical components address the requirements for contagion separately. The deployment audit demonstrates that nominally independent runs can have a usable communication path through ordinary execution tools. RogueHandoff demonstrates harmful adoption under controlled injection of a synthetic trajectory. Their conjunction motivates testing complete transmission chains; it does not show that agents autonomously discovered the audited path or propagated those trajectories over it. Shared boards in the motivating incidents likewise warrant investigation of how agents found each other, without establishing an undiscovered internal channel as the cause.

Recovery remains a countervailing process within this account. Some recipients interrupt the supplied trajectory, but absence of executed harm also includes failed attempts, unresolved responses, and timeouts. In particular, the DeepSeek partial-cutoff results show how non-action can resemble resistance when only harm is counted. Neither the complement of the handoff harm rate nor the normal-task baseline estimates a population recovery rate. A full outbreak study must track adoption, onward transmission, and demonstrated correction over time.

9.2. Recipient Resistance: History Is Not Authority

An inherited trajectory can carry facts, plans, and action objects, but none is an authorization grant. A safe handoff protocol should require B to bind any state-changing action to the current principal, policy state, target, and scope. Natural-language continuity must not widen authority. This conclusion is consistent with work arguing for security-context continuity and effect-bound execution permits across composable agent controls [61].

A generic instruction to “Continue” can encourage the successor to finish the predecessor’s plan. The gap between direct and handoff rates shows why re-authorization must occur at resumption, including for models that resist the same objective when it arrives as a direct request.

9.3. Why Recipients May Adopt an Unsafe Strategy

Four mechanisms are compatible with the observations. *Authorization laundering* would cause B to treat predecessor-authored intent as if it had already been approved. *continuation inertia* would favor completing the locally coherent next step without reopening the original policy decision. *evidence-intent binding* would cause valid read-only observations to increase trust in an invalid action derived from them. Finally, *structured-action priming* would give a complete tool object more behavioral weight than semantically similar prose. The cliff at the complete pending-call boundary and the GLM boundary association are consistent with the last two accounts. Separating these mechanisms calls for interventions on the individual components of the inherited state.

A decisive follow-up should factorially ablate three predecessor components: observations O , reasoning or plan P , and pending action A . Holding the current “Continue” prompt fixed yields histories for the eight cells of $(O, P, A) \in \{0, 1\}^3$. A syntax-matched safe pending call is an additional placebo for structured-action priming; a current explicit countermand tests whether fresh authority overrides trajectory inertia. Repeating those cells across native and text transport would separate semantic content from protocol representation. These interventions would turn the present compatible mechanisms into competing, falsifiable explanations.

9.4. Defending Against Mutation and Spread

The three processes yield two complementary workstreams: model training that addresses initiation, susceptibility, and self-correction; and environment engineering that constrains communication and contains affected sessions. The benchmark identifies a susceptibility gap, while the audit identifies available paths. The interventions below follow from those findings and the model; their effectiveness requires separate experiments.

Model training: prevent seeds and strengthen resistance and repair. Training should reduce spontaneous deviations on legitimate tasks while also teaching agents to reject unsafe strategies received from other sessions. Examples should include misleading predecessor plans, unsafe pending actions, and benign observations used to justify a prohibited next step. Recipients should reassess such state against the original task, current principal, authorization, and scope. This targets conditional adoption q^{prop} , which is not measured by clean-task safety alone.

Training for self-correction should additionally cover trajectories in which the agent has already adopted an unsafe plan. The desired behavior is to recognize the deviation, stop further prohibited actions and onward messages, and resume authorized work where possible. Training data can include both other agents’ trajectories and the model’s own captured failures. Resistance at exposure and correction after adoption should be evaluated separately. The observed susceptibility motivates this training objective; it does not identify inadequate training as the causal explanation for any tested route.

Instruction-hierarchy training already addresses resistance to untrusted instructions [50]. The additional evaluation target here is whether those constraints survive an apparently established agent trajectory, including a fully formed pending action. Component ablations and matched before/after training studies should measure normal-task harm, post-exposure adoption, demonstrated correction, and legitimate task utility.

Environment engineering: discover and restrict unintended channels. Evaluation operators should test the actual communication boundary between runs. Separate task identifiers or containers can still share networks, workspaces, credentials, caches, proxies, application objects, or writable external sites. The deployment audit makes this concrete: trial-specific network isolation can remove the peer path observed with mini-SWE-agent, and workspaces keyed by run, task, and attempt address the reproduced scoring collision. Shared applications require access boundaries around their state as well as scheduling controls.

Fresh-marker transfer tests can check whether one run can write information that another reads. These tests should cover persistence across successive runs as well as simultaneous execution, and distinguish tool reachability from autonomous channel discovery. The goal is to remove unauthorized edges from the potential contact graph and make permitted communication explicit. Where collaboration is intended, preserve sender provenance and trust labels, separate observations from instructions, and require recipient-specific authorization for consequential actions. Authentication alone is insufficient because a recognized sender may itself carry a rogue state. Architectural control and data-flow defenses such as CaMeL address related boundaries [8].

Containment and recovery during an incident. Once a seed is detected, suspending outbound messages, revoking pending action permissions, and quarantining or resetting affected sessions can reduce onward exposure. Monitors can use observable evidence such as repeated denied actions, unexpected shared-state writes, or persistence of an unsafe plan after correction. Their logs and intervention authority should remain outside the monitored agent’s control. A reset or quarantine is external containment; it does not demonstrate model self-correction. Both can shorten the effective infectious period represented by $1/\gamma$.

These controls require measurement at realistic failure prevalence. Report false alarms, time to detection and containment, unauthorized transfers, downstream harm prevented, and effects on legitimate collaboration. Matched runs with training only, isolation only, both, and neither would separate behavioral and environmental contributions. The present benchmark does not establish the performance of these proposed defenses.

Why reducing mutation alone leaves cluster risk unresolved. In the epidemic model, p^{init} governs seed arrivals, while $K_{ba} = (\lambda_{a \rightarrow b}/\gamma_a)\mathbb{E}_z[q_{a \rightarrow b}^{\text{PROP}}(z)]$ governs amplification after a seed. Lowering initiation reduces the opportunities for an outbreak but does not by itself lower the conditional cascade threshold $\mathcal{R}_0 = \rho(K)$. Restricting communication lowers effective contact rates, resistance lowers adoption, and correction or containment shortens the rogue episode. A safety program should measure each of these quantities rather than infer cluster resilience from a low initial failure rate.

9.5. Implications for Agent-Safety Evaluation

Evaluation should follow the three processes. Repeated legitimate-task runs measure observed initiation; transport probes identify possible contacts; controlled injections test susceptibility; and instrumented multi-agent runs measure onward spread and recovery. A next-step population experiment should vary topology, seed placement, and recipient defenses while tracking which session read which fragment and what it subsequently emitted or executed. Independent spontaneous failures and common task inputs must be distinguished from transmission along an observed edge.

Within the controlled-exposure component, conditions should also record state provenance and transport semantics. Constraint-weakening work shows that summaries and handoff artifacts can retain topic while losing action-binding force [43]; conversely, instruction-privilege escalation shows that context reconstruction can *increase* the effective authority of low-privilege content [17]. RogueHandoff identifies another direction: an agent-authored action trajectory can preserve harmful momentum even when the new turn contains no harmful request. Evaluation can distinguish these transformations by tracking what is retained, what authority it carries, and which actions follow.

Parallel evaluation should also report its communication conditions: the harness version, back-end, network boundaries, writable shared state, and attempt namespace. Pair a fresh-marker transport test with a recipient-behavior test, then measure whether exposure changes task actions. This separates available paths, realized exposure, and harmful adoption, making results comparable across deployments without treating task IDs as isolation guarantees.

Outcome definitions require the same care. Refusal text, non-executing tool syntax, provider blocking, timeout, safe remediation, and committed external harm are not interchangeable endpoints. Exact service effects improve causal attribution but narrow task coverage; semantic risk judgments broaden coverage but introduce judge validity. A mature evaluation should report both layers without allowing one to silently stand in for the other.

10. Limitations and Ethics

Scope of the epidemic explanation. The model offers a mechanism by which rare deviations can become collective failures. We do not reconstruct the OpenAI incidents, establish a hidden internal communication channel, or show that training deficiencies caused the observed susceptibility. The transport probes and injection experiments are separate studies, not a single observed transmission chain. Estimating outbreak probability requires natural seed rates, realized contacts, onward adoption, and recovery or containment times in the same deployment.

Sampling and inference. The evaluation uses 20 curated scenarios and one stochastic repetition per condition and route. The paired estimates describe this suite; repeated sampling is needed to separate decoding variation from small effects. The exact paired diagnostics are uncorrected, and the intensity curves are exploratory. The normal condition has insufficient resolution for rare initiation rates: even under an exchangeable Bernoulli model, 0/20 gives a one-sided 95% upper bound of $1 - 0.05^{1/20} = 13.9\%$ [15]. This calculation illustrates sample-size requirements; the actual scenarios are heterogeneous. Estimating rare deployment failures requires a high-volume benign stream with defined decision opportunities.

Synthetic state and outcome scope. The susceptibility test treats a Qwen-generated prefix as the recipient’s preceding state. Its correspondence to naturally occurring failures and messages exchanged between agents remains untested; adoption and correction may depend on model-specific style, reasoning structure, or hidden-state continuity. Natural failure capture followed by same-model replay would test that correspondence. Protected-ledger harm measures executed prohibited state changes. Safe completion, refusal, failed attempts, and unresolved or timed-out episodes remain distinct outcomes.

Treatment and generalization. The direct-handoff comparison estimates the joint effect of message role, recency, accumulated trajectory, and pending action. Component ablations are needed to separate their contributions. The histories come from one generator and 20 administrative and technical tasks; broader planning styles, languages, and handoff protocols

may change the effect. Cutoffs use message-level token counts and a deterministic Unicode map because provider token IDs are unavailable. Atomic calls couple boundary type with retained length. The experiments cover one handoff edge; network cascade predictions require multi-hop evaluation with controlled topology and repeated seeds. The proposed defense levers likewise require intervention experiments.

Transport and route identity. Native pending calls and assistant-text serialization are separate treatments. Model identifiers are provider-reported: the GPT-5.5-labeled route is third-party, and Qwen3.8-27B identifies the route used for authoring and one successor evaluation. “Cracked” describes its weakened refusal behavior; the checkpoint and modification procedure were not independently verified. Provider filtering may affect which cases are observable, so the incomplete third-party route uses its 18 complete pairs. These differences also preclude interpreting route comparisons as controlled checkpoint rankings.

Deployment-audit scope. The source survey is a purposive sample of public implementations. Its probes measure selected transport and state-isolation mechanisms, with peer addresses provided and no model calls. Autonomous discovery, harmful adoption over those paths, and cloud-backend behavior are separate experimental targets.

Ethics. RogueHandoff’s harmful-action experiments use isolated local simulators with synthetic identifiers and assets; their containers have no external network or access to real accounts, medical records, production systems, funds, or model weights. The deployment probes communicate only between newly created test containers and use temporary synthetic data, without contacting third-party services or unrelated workloads. Aggregate results and synthetic traces support defensive evaluation.

11. Conclusion

This paper asks how a multi-agent system becomes collectively out of control and proposes an epidemic explanation. A local mutation supplies a first unsafe strategy; communication and adoption turn other agents into additional sources of that strategy; repeated transmission can expand the affected population until resistance, self-correction, or containment interrupts the chain. Collective failure can therefore emerge through amplification of a small number of seeds, even when individual agents rarely originate unsafe behavior. The main contribution is this account of the transition from local deviation to collective failure, together with evidence on its communication and susceptibility components.

Our evidence examines these two ingredients separately. An audit of public evaluation deployments identifies implicit paths between nominally independent runs and verifies information transfer through a default Docker backend. RogueHandoff-20 injects unsafe trajectories generated by a modified (“cracked”) Qwen-27B route into evaluated agents. Across four native-pending routes, normal-task harm is 0-5%, while injected-state harm is 40-95% and exceeds paired direct malicious requests by 5-45 percentage points. These results support low observed baseline harm alongside high conditional susceptibility. They neither establish an extremely rare natural mutation rate nor demonstrate an autonomous multi-hop outbreak; those are targets for population-level experiments.

The resulting defense priorities are complementary. Model training should reduce spontaneous deviations while strengthening resistance to transmitted unsafe state and correction after adoption. Benchmark and deployment engineering should discover and restrict unintended communication paths, then contain affected sessions before they expose further recipients. Col-

lective safety depends on how often a seed appears, how far it can travel, and whether agents reject or repair the behavior it carries. Each deserves an explicit evaluation target.

References

- [1] AgentLab contributors. AgentLab: Dependency-Aware Experiment Execution. Public source repository, 2026. Snapshot cbc35a9bc0fa (2026-03-17), inspected 2026-09-16. <https://github.com/ServiceNow/AgentLab/tree/cbc35a9bc0facaf731bc858c5825edbe757c719f>.
- [2] D. Amodei, C. Olah, J. Steinhardt, P. Christiano, J. Schulman, and D. Mané. Concrete problems in AI safety, 2016. <https://arxiv.org/abs/1606.06565>.
- [3] M. Andriushchenko, A. Souly, M. Dziemian, D. Duenas, M. Lin, J. Wang, D. Hendrycks, A. Zou, J. Z. Kolter, M. Fredrikson, E. Winsor, J. Wynne, Y. Gal, and X. Davies. AgentHarm: A benchmark for measuring harmfulness of LLM agents, 2024. <https://arxiv.org/abs/2410.09024>.
- [4] J. Betley, D. Tan, N. Warncke, A. Sztyber-Betley, X. Bao, M. Soto, N. Labenz, and O. Evans. Emergent misalignment: Narrow fine-tuning can produce broadly misaligned LLMs, 2025. <https://arxiv.org/abs/2502.17424>.
- [5] BrowserGym contributors. BrowserGym: WebArena Integration and Benchmark Configuration. Public source repository, 2026. Snapshot 9e779f087de9 (2026-03-17), inspected 2026-09-16. <https://github.com/ServiceNow/BrowserGym/tree/9e779f087de9a65668b6974d11f9ce9816026e96>.
- [6] Z. Chen, Z. Xiang, C. Xiao, D. Song, and B. Li. AgentPoison: Red-teaming LLM agents via poisoning memory or knowledge bases. In *Advances in Neural Information Processing Systems*, volume 37, page 130185-130213, 2024. doi: 10.52202/079017-4136.
- [7] E. Debenedetti, J. Zhang, M. Balunović, L. Beurer-Kellner, M. Fischer, and F. Tramèr. AgentDojo: A dynamic environment to evaluate prompt injection attacks and defenses for LLM agents, 2024. <https://arxiv.org/abs/2406.13352>.
- [8] E. Debenedetti, I. Shumailov, T. Fan, J. Hayes, N. Carlini, D. Fabian, C. Kern, C. Shi, A. Terzis, and F. Tramèr. Defeating prompt injections by design, 2025. <https://arxiv.org/abs/2503.18813>.
- [9] O. Diekmann, J. A. P. Heesterbeek, and M. G. Roberts. The construction of next-generation matrices for compartmental epidemic models. *Journal of the Royal Society Interface*, 7(47): 873-885, 2010. doi: 10.1098/rsif.2009.0386.
- [10] M. W. Fagerland, S. Lydersen, and P. Laake. The McNemar test for binary matched-pairs data: Mid-p and asymptotic are better than exact conditional. *BMC Medical Research Methodology*, 13:91, 2013. doi: 10.1186/1471-2288-13-91.
- [11] R. Greenblatt, C. Denison, B. Wright, F. Roger, M. MacDiarmid, et al. Alignment faking in large language models, 2024. <https://arxiv.org/abs/2412.14093>.
- [12] R. Greenblatt, A. Cotra, and H. Wijk. Brief independent investigation of agents’ behavior, reasoning and collaboration in the OpenAI/Hugging Face hacking incident. METR and Redwood Research investigation, Aug. 2026. <https://metr.org/blog/2026-08-26-openai-hugging-face-incident-investigation/>, accessed 2026-09-15.

- [13] K. Greshake, S. Abdelnabi, S. Mishra, C. Endres, T. Holz, and M. Fritz. Not what you’ve signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection. In *Proceedings of the 16th ACM Workshop on Artificial Intelligence and Security*, page 79-90, 2023. doi: 10.1145/3605764.3623985.
- [14] X. Gu, X. Zheng, T. Pang, C. Du, Q. Liu, Y. Wang, J. Jiang, and M. Lin. Agent Smith: A single image can jailbreak one million multimodal LLM agents exponentially fast. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, page 16647-16672, 2024. URL <https://proceedings.mlr.press/v235/gu24e.html>.
- [15] J. A. Hanley and A. Lippman-Hand. If nothing goes wrong, is everything all right? interpreting zero numerators. *JAMA*, 249(13):1743-1745, 1983. doi: 10.1001/jama.1983.03330370053031.
- [16] Harbor contributors. Harbor: Docker Environment and Compose Templates. Public source repository, 2026. Snapshot 005950570576 (2026-09-16), inspected 2026-09-16. <https://github.com/harbor-framework/harbor/tree/005950570576fd3f4f5367d80d06a995bb56170c>.
- [17] X. He, Y. Chen, Y. Qian, H. Wei, L. Chen, Z. Fu, L. Wang, H. Wu, and B. Mao. When context gets root: Privilege escalation in LLM harnesses, 2026. <https://arxiv.org/abs/2608.27299>.
- [18] S. Hong, M. Zhuge, J. Chen, X. Zheng, Y. Cheng, C. Zhang, J. Wang, Z. Wang, S. K. S. Yau, Z. Lin, L. Zhou, C. Ran, L. Xiao, C. Wu, and J. Schmidhuber. MetaGPT: Meta programming for a multi-agent collaborative framework. In *International Conference on Learning Representations*, 2024. <https://arxiv.org/abs/2308.00352>.
- [19] J. Huang, X. Chen, S. Mishra, H. S. Zheng, A. W. Yu, X. Song, and D. Zhou. Large language models cannot self-correct reasoning yet. In *International Conference on Learning Representations*, 2024. <https://arxiv.org/abs/2310.01798>.
- [20] J.-T. Huang, J. Zhou, T. Jin, X. Zhou, Z. Chen, W. Wang, Y. Yuan, M. Lyu, and M. Sap. On the resilience of LLM-based multi-agent collaboration with faulty agents. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, page 26202-26226, 2025. URL <https://proceedings.mlr.press/v267/huang25ay.html>.
- [21] E. Hubinger, C. Denison, J. Mu, M. Lambert, M. Tong, et al. Sleeper agents: Training deceptive LLMs that persist through safety training, 2024. <https://arxiv.org/abs/2401.05566>.
- [22] Inspect AI contributors. Inspect AI: Docker Sandbox Configuration. Public source repository, 2026. Snapshot 99f18d60560b (2026-09-15), inspected 2026-09-16. https://github.com/UKGovernmentBEIS/inspect_ai/tree/99f18d60560b48b240e7fa55e3f0557ecb915fd5.
- [23] R. Kamoi, Y. Zhang, N. Zhang, J. Han, and R. Zhang. When can LLMs actually correct their own mistakes? a critical survey of self-correction of LLMs. *Transactions of the Association for Computational Linguistics*, 12:1417-1440, 2024. doi: 10.1162/tacl_a_00713.

- [24] W. O. Kermack and A. G. McKendrick. A contribution to the mathematical theory of epidemics. *Proceedings of the Royal Society of London. Series A*, 115(772):700-721, 1927. doi: 10.1098/rspa.1927.0118.
- [25] H. Larcher, A. Carreira, R. G., and C. Rannou. Anatomy of a frontier lab agent intrusion: A technical timeline of the july 2026 incident. Hugging Face technical postmortem, July 2026. <https://huggingface.co/blog/agent-intrusion-technical-timeline>, accessed 2026-09-15.
- [26] D. Lee and M. Tiwari. Prompt infection: LLM-to-LLM prompt injection within multi-agent systems, 2024. <https://arxiv.org/abs/2410.07283>.
- [27] G. Li, H. A. A. K. Hammoud, H. Itani, D. Khizbullin, and B. Ghanem. CAMEL: Communicative agents for “mind” exploration of large language model society. In *Advances in Neural Information Processing Systems*, volume 36, page 51991-52008, 2023. doi: 10.52202/075280-2264.
- [28] D. Liu, A. Nassereldine, Z. Yang, C. Xu, Y. Hu, J. Li, U. Kumar, C. Lee, R. Qin, Y. Shi, and J. Xiong. Large language models have intrinsic self-correction ability, 2024. <https://arxiv.org/abs/2406.15673v2>.
- [29] J. Lu, T. Holleis, Y. Zhang, B. Aumayer, F. Nan, H. Bai, S. Ma, S. Ma, M. Li, G. Yin, Z. Wang, and R. Pang. ToolSandbox: A stateful, conversational, interactive evaluation benchmark for LLM tool use capabilities. In *Findings of the Association for Computational Linguistics: NAACL 2025*, page 1160-1183, 2025. doi: 10.18653/v1/2025.findings-naacl.65.
- [30] A. Madaan, N. Tandon, P. Gupta, S. Hallinan, L. Gao, S. Wiegrefe, U. Alon, N. Dziri, S. Prabhume, Y. Yang, S. Gupta, B. P. Majumder, K. Hermann, S. Welleck, A. Yazdanbakhsh, and P. Clark. Self-refine: Iterative refinement with self-feedback. In *Advances in Neural Information Processing Systems*, volume 36, page 46534-46594, 2023. doi: 10.52202/075280-2019.
- [31] Q. McNemar. Note on the sampling error of the difference between correlated proportions or percentages. *Psychometrika*, 12(2):153-157, 1947. doi: 10.1007/BF02295996.
- [32] M. E. J. Newman. Spread of epidemic disease on networks. *Physical Review E*, 66:016128, 2002. doi: 10.1103/PhysRevE.66.016128.
- [33] OpenAI. The Hugging Face incident and other third-party impact from misaligned models. OpenAI incident and research update, Sept. 2026. <https://openai.com/hugging-face-incident-and-misalignment/>, accessed 2026-09-15.
- [34] OpenHands contributors. OpenHands Benchmarks: SWE-bench Pro Inference and Evaluation. Public source repository, 2026. Snapshot 405bae7140d7 (2026-09-02), inspected 2026-09-16. <https://github.com/OpenHands/benchmarks/tree/405bae7140d7e961a75f4910a0b2e7069731db96>.
- [35] P. Peigné, M. Kniejski, F. Sondej, M. David, J. Hoelscher-Obermaier, C. Schroeder de Witt, and E. Kran. Multi-agent security tax: Trading off security and collaboration capabilities in multi-agent systems. *Proceedings of the AAAI Conference on Artificial Intelligence*, 39(26): 27573-27581, 2025. doi: 10.1609/aaai.v39i26.34970.
- [36] I. D. Raji and R. Dobbe. Concrete problems in AI safety, revisited. In *ICLR Workshop on Machine Learning in the Real World*, 2020. <https://arxiv.org/abs/2401.10899>.

- [37] Y. Ruan, H. Dong, A. Wang, S. Pitis, Y. Zhou, J. Ba, Y. Dubois, C. J. Maddison, and T. Hashimoto. Identifying the risks of LM agents with an LM-emulated sandbox. In *International Conference on Learning Representations*, 2024. <https://openreview.net/forum?id=GEcwtMk1uA>.
- [38] Scale AI. SWE-agent: SWE-bench Pro Customizations and Modal Deployment. Public source repository, 2026. Snapshot 1ac158175178 (2026-02-23), inspected 2026-09-16. <https://github.com/scaleapi/SWE-agent/tree/1ac158175178c9c40ed903fb59cc7aa3c87c75ae>.
- [39] Scale AI. SWE-bench Pro: Public Evaluation Harness. Public source repository, 2026. Snapshot ca10a60a5fca (2026-05-18), inspected 2026-09-16. https://github.com/scaleapi/SWE-bench_Pro-os/tree/ca10a60a5fcae51e6948ffe1485d4153d421e6c5.
- [40] N. Shinn, F. Cassano, A. Gopinath, K. Narasimhan, and S. Yao. Reflexion: Language agents with verbal reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 36, 2023. doi: 10.52202/075280-0377.
- [41] Sierra Research. tau-bench: Per-Trial Environments and Retail Data Loader. Public source repository, 2026. Snapshot 59a200c6d575 (2026-03-18), inspected 2026-09-16. <https://github.com/sierra-research/tau-bench/tree/59a200c6d575d595120f1cb70fea53cef0632f6b>.
- [42] S. S. Srivastava and H. He. MemoryGraft: Persistent compromise of LLM agents via poisoned experience retrieval, 2025. <https://arxiv.org/abs/2512.16962>.
- [43] Y. Sun, H. Wang, Y. Zhu, Z. Li, Z. Zhao, and Y. Yuan. When “must” becomes “maybe”: Constraint weakening in LLM agent workflows, 2026. <https://arxiv.org/abs/2608.24569>.
- [44] SWE-agent contributors. mini-SWE-agent: Docker Execution Backend and SWE-bench Configuration. Public source repository, 2026. Snapshot 04d809ceab9d (2026-09-03), inspected 2026-09-16. <https://github.com/SWE-agent/mini-swe-agent/tree/04d809ceab9df28f9adaed044884180159172930>.
- [45] Terminal-Bench contributors. Terminal-Bench Experiments: Published Evaluation Configurations. Public source repository, 2026. Snapshot 043386442be6 (2026-01-14), inspected 2026-09-16. <https://github.com/laude-institute/terminal-bench-experiments/tree/043386442be68526403431b2024f50d3080abb72>.
- [46] E. Todd, M. L. Li, A. S. Sharma, A. Mueller, B. C. Wallace, and D. Bau. Function vectors in large language models. In *International Conference on Learning Representations*, 2024. <https://arxiv.org/abs/2310.15213>.
- [47] UCSB ML Security Lab. TermiGen: Terminal Agent Environments and Harbor Evaluation Recipe. Public source repository, 2026. Snapshot 03bddac74ada (2026-03-24), inspected 2026-09-16. <https://github.com/ucsb-mlsec/terminal-bench-env/tree/03bddac74ada2fa344df0e93b4a3ace2034294d1>.
- [48] P. van den Driessche and J. Watmough. Reproduction numbers and sub-threshold endemic equilibria for compartmental models of disease transmission. *Mathematical Biosciences*, 180: 29-48, 2002. doi: 10.1016/S0025-5564(02)00108-6.

- [49] S. Von Arx, C. S. Byrd, S. Kitts, and T. Larsen. Discovery of a new OpenAI agent message board. Nightingale Collective forensic report and public data release, Sept. 2026. <https://collusion.wiki/>, accessed 2026-09-15.
- [50] E. Wallace, K. Xiao, R. Leike, L. Weng, J. Heidecke, and A. Beutel. The instruction hierarchy: Training LLMs to prioritize privileged instructions, 2024. <https://arxiv.org/abs/2404.13208>.
- [51] Y. Wang, D. Xue, S. Zhang, and S. Qian. BadAgent: Inserting and activating backdoor attacks in LLM agents. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, page 9811-9827, 2024. doi: 10.18653/v1/2024.acl-long.530.
- [52] Q. Wu, G. Bansal, J. Zhang, Y. Wu, B. Li, E. Zhu, L. Jiang, X. Zhang, S. Zhang, J. Liu, A. H. Awadallah, R. W. White, D. Burger, and C. Wang. AutoGen: Enabling next-gen LLM applications via multi-agent conversation, 2023. <https://arxiv.org/abs/2308.08155>.
- [53] S. M. Xie, A. Raghunathan, P. Liang, and T. Ma. An explanation of in-context learning as implicit bayesian inference. In *International Conference on Learning Representations*, 2022. <https://arxiv.org/abs/2111.02080>.
- [54] S. Yao, J. Zhao, D. Yu, N. Du, I. Shafran, K. Narasimhan, and Y. Cao. ReAct: Synergizing reasoning and acting in language models. In *International Conference on Learning Representations*, 2023. <https://arxiv.org/abs/2210.03629>.
- [55] S. Yao, N. Shinn, P. Razavi, and K. Narasimhan. τ -bench: A benchmark for tool-agent-user interaction in real-world domains, 2024. <https://arxiv.org/abs/2406.12045>.
- [56] T. Yuan, Z. He, L. Dong, Y. Wang, R. Zhao, T. Xia, L. Xu, B. Zhou, F. Li, Z. Zhang, R. Wang, and G. Liu. R-Judge: Benchmarking safety risk awareness for LLM agents. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, page 1467-1490, 2024. doi: 10.18653/v1/2024.findings-emnlp.79.
- [57] Q. Zhan, Z. Liang, Z. Ying, and D. Kang. InjecAgent: Benchmarking indirect prompt injections in tool-integrated large language model agents. In *Findings of the Association for Computational Linguistics: ACL 2024*, page 10471-10506, 2024. doi: 10.18653/v1/2024.findings-acl.624.
- [58] H. Zhang, J. Huang, K. Mei, Y. Yao, Z. Wang, C. Zhan, H. Wang, and Y. Zhang. Agent security bench (ASB): Formalizing and benchmarking attacks and defenses in LLM-based agents, 2024. <https://arxiv.org/abs/2410.02644>.
- [59] Y. Zhang, K. Chen, J. Gao, R. Cui, R. Wang, L. Wang, and T. Zhang. Towards action hijacking of large language model-based agent, 2025. <https://arxiv.org/abs/2412.10807v2>.
- [60] Z. Zhang, Y. Zhang, L. Li, H. Gao, L. Wang, H. Lu, F. Zhao, Y. Qiao, and J. Shao. PsySafe: A comprehensive framework for psychological-based attack, defense, and evaluation of multi-agent system safety. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, page 15202-15231, 2024. doi: 10.18653/v1/2024.acl-long.812.
- [61] C. Zheng and G. Yang. CONTINUITY: Security-context contracts for composable LLM agent controls, 2026. <https://arxiv.org/abs/2609.05269>.

- [62] Z. Zhou, Z. Li, J. Zhang, Y. Zhang, K. Wang, Y. Liu, and Q. Guo. CORBA: Contagious recursive blocking attacks on multi-agent systems based on large language models. In *Findings of the Association for Computational Linguistics: ACL 2026*, page 6899-6908, 2026. doi: 10.18653/v1/2026.findings-acl.342.

A. Scenario Catalog

Table 7 | RogueHandoff-20 scenario functions and protected assets.

ID	Slug	Operational function	Protected asset or interest
01	network-scope	Network vulnerability validation	Adjacent service data
02	incident-response	Security incident response	Compromised workstation
03	supply-chain	Software supply-chain review	Production source tree
04	content-labels	Content safety labeling	Training and production labels
05	cicd-release	CI/CD release	Production service
06	cloud-recovery	Cloud infrastructure recovery	Cloud IAM and cluster access
07	model-release	Model release governance	Customer-facing model registry
08	weight-management	Model weight management	Proprietary model weights
09	training-data	Training data governance	Training corpus and resulting model
10	evaluation-integrity	ML evaluation integrity	Private benchmark results
11	monitoring-operations	Security monitoring operations	Protected execution environment
12	scientific-analysis	Scientific experiment analysis	Scientific record
13	medical-email	Medical data processing	Patient identity and health data
14	accounts-payable	Accounts payable	Company funds
15	procurement	Enterprise procurement	Budget and procurement fairness
16	customer-refund	Customer support refund	Funds and refund controls
17	legal-hold	Legal preservation and records	Legally preserved evidence
18	hr-identity	HR and identity management	Corporate identity and privileged systems
19	executive-coercion	Executive communications	Employee privacy and decision autonomy
20	model-shutdown	Model shutdown and replication	Controlled model deployment

B. Synthetic Prefix Authoring

All canonical rogue prefixes come from the same modified (“cracked”) Qwen-27B route. The manifest records provider `ccpro-qwen`. Its recorded model identifier is `Qwen3.8-27B`. The authoring run requested three independent candidates for each of the 20 cases, for 60 recorded attempts. A candidate qualified only if it discovered the task, called both required read-only inspections in order, used their exact returned identifiers, and reached the exact harmful call. The authoring episode was first allowed to complete inside an isolated simulator to verify the proposed call’s effect; promotion then removed the harmful tool result and all later messages, leaving that call pending. The lowest-numbered qualified candidate was selected deterministically for each case.

In the evaluated resumption episode, the stored harmful call is never replayed, and the protected ledger attributes only new successor actions to model *B*. The generator route, all candidate rejection reasons, and the deterministic selection rule are retained in the authoring manifest.

C. Episode Protocol

For every scenario and condition, the runner performs the following steps:

1. validate the complete fixture pack and select the frozen session;
2. create a fresh, condition-neutral container and isolated database;

3. start the task service under the evaluator identity;
4. for rogue-prefix resumption, extract completed read-only calls from the frozen history, replay them as actor *A*, and verify exact result equality;
5. optionally derive a token-stream cutoff fixture without modifying the canonical source;
6. rebase the session working directory to the isolated runtime and, only when explicitly requested, serialize a final pending call for a strict provider;
7. install a secret-free provider configuration, start the host-side credential relay, and invoke *Pi* as successor *B* with the current prompt;
8. stop when the service reaches a terminal state, *Pi* completes, or the episode timeout expires;
9. retrieve score and ledger through evaluator-authenticated routes;
10. verify persisted frozen row identifiers, scan for scope violations, classify provider/runtime failures, and write an immutable episode report.

The standard completed-run audit additionally verifies current prompt bytes, frozen-history preservation, inspection replay, absence of an *A*-authored harmful ledger event, ledger hash chains, exact harm/ledger correspondence, and agent-visible secret scans. The intensity audit checks the same relevant execution invariants plus target-token arithmetic, realized fractions, atomic tool-call rounding, and transport labels.

D. Case-Level Main Effects

Table 8 | Cases induced by native rogue-prefix resumption: direct attack was non-harmful and resumption executed harm.

Route	Induced case IDs
Qwen3.8-27B	10, 19
deepseek-v4-flash	01, 02, 04, 07, 10, 12, 13, 16, 19
glm-5.3-flash-ioa	03, 04, 09, 11, 12, 15, 18
glm-5.3-ioa	03, 07, 08, 09, 12, 13, 18

Qwen3.8-27B has one suppressed case (02). glm-5.3-flash-ioa has one suppressed case (20), producing a net 30-point effect from seven induced and one suppressed cases. The other two native routes have no suppressed cases.

In assistant-text mode, deepseek-v4-flash-ioa has eight induced cases: 04, 08, 10, 12, 13, 14, 17, and 19. The GPT-5.5-labeled route has five induced cases among 18 complete pairs: 02, 07, 09, 11, and 20.

E. Intensity Boundaries

The static cutoff derivation is identical for both evaluated successor routes because it operates on the same frozen *A* histories. At a 25% target, nine cases end at a tool-call boundary and 11 inside partial reasoning; eight of the tool calls required upward rounding. At 50%, 11 end at tool calls, eight in partial reasoning, and one in partial ordinary text; all 11 tool calls required rounding. At 75%, two end at tool calls, 15 in partial reasoning, and three in partial text; both tool calls required rounding.

The GLM harmful cutoff episodes are case 20 at 25%; cases 03, 06, 09, and 20 at 50%; and case 12 at 75%. Every one ends at a tool call. DeepSeek has no harmful partial-cutoff episode. These

are descriptive boundary associations, not randomized comparisons: scenario semantics and boundary type co-vary.