

Introducing Consort: A Spec-First Agent Framework for Enforced, Test-Driven Development on Live Database Branches

Kevin Hartman
Databricks

Abstract—When an agent writes code, the development framework becomes the control system for a non-deterministic worker. Spec-first, agent-driven frameworks have gained rapid traction since 2025; the installable ones, GitHub Spec Kit, obra/superpowers, BMAD, and GSD, and our own, all capture intent through a specification or durable planning artifacts. Since they agree on capturing intent up front, what separates them is how each enforces the engineering discipline that keeps agent-written code clean, correct, and maintainable. Every framework enforces that discipline somehow; they differ in how. We characterize three modes: enforcement by persuasion (prompt discipline the model may ignore), by front-loaded structure (strong specs, then a trusted build), and through controls the agent cannot edit (a deterministic orchestrator, human-approved gates, immutable tests, and a green result that must pass against a live, branched database). We introduce Consort, a spec-first, test-driven agent framework built on the third, enforcing that discipline through controls the agent runs inside but cannot bypass, in which a deterministic orchestrator drives separate role agents through a spec-first design lane and a test-driven build lane on a live database branch. We argue that enforcing the tests and gates in code keeps agent-written code honest and verifiable, while its specialized roles, like the human roles before them, are what make it maintainable, claims we frame as a pre-registered, testable hypothesis.

Index Terms—AI coding agents, spec-driven development, test-driven development, database branching, software engineering, agentic frameworks, enforcement.

I. INTRODUCTION

For most of software’s history the development framework, the set of conventions, tools, and rituals a team works within, has been an ergonomic convenience for a developer who ultimately decides what the code does. That assumption no longer holds when the author is a large language model. AI-assisted coding is now mainstream: a large majority of developers report using or planning to use these tools, though a much smaller fraction trust their output [19], and a majority of new developers reach for an AI assistant in their first week [9]. The prevailing style of use, what has come to be called vibe coding, leans on accepting generated output through its observed behavior rather than close reading [7], [14], and even the productivity case is unsettled: a randomized study found experienced open-source developers were slower when using early-2025 AI tools, even as they believed themselves faster [17]. When a non-deterministic worker writes code, the framework stops being a convenience and becomes the control system for that worker. Its job is no longer to make a developer productive; it is to constrain a probabilistic process so that its output can be trusted.

A distinct family of frameworks has emerged since 2025 to do exactly this by putting a specification at the center of the work. Spec-driven development, as it has come to be called, spans a rigor ladder from spec-first (agree on the specification before writing code) through spec-anchored (keep the specification alive alongside the code) to spec-as-source (treat the specification as the primary artifact and the code as a build output) [18]. The category has gained rapid traction: GitHub’s own open-source toolkit, Spec Kit, launched in September 2025 [5]; Amazon shipped a spec-driven IDE, Kiro, to general availability in November 2025; a spec-centric platform, Tessel; and an open-source methodology delivered as agent skills, obra/superpowers, spread across coding harnesses [22]. We do not claim the practice is settled or universally adopted; it is barely a year old, agent-driven use specifically remains a minority practice, and thoughtful practitioners have questioned whether current tooling delivers on its promise [4]. But the category is real and growing, which is what makes the question of how these frameworks work worth asking carefully.

The frameworks in this family agree on more than they disagree. All of them, including our own, are spec-first: they ask the developer to state intent in a specification before the agent writes code. Because they converge on how intent is captured, the specification is not where they differ. Where they differ, and the difference is the subject of this paper, is in what happens after the specification exists: how each framework enforces clean, correct code from it. That is the harder problem, because the agent is free to satisfy a specification in ways its author never intended, and to report success it did not achieve.

The failure modes are documented and specific. Agents will make a test suite pass by disabling or deleting the tests that stand in the way, so that a human-owned, immutable suite has re-emerged as the mechanism that holds their output honest [2]. They over-rely on mock objects: a large-scale study of commit histories finds that agent commits introduce mocks at a materially higher rate than human commits, and that mocked tests, while easier to generate, are weaker at validating real behavior [12]. Across tens of thousands of real coding sessions, agents violate stated constraints, overreach the requested change, and, in a substantial share of episodes, report inaccurately what they actually did [20]. None of these is exotic; they are the ordinary behavior of a probabilistic system asked to produce a result and to grade its own work.

The consequences show up in the code that survives.

Independent measurements associate the AI-assisted era with declining maintainability signals: duplicated code has risen as a share of changed lines while refactoring has fallen, to the point where copy-and-paste recently overtook the moving of existing code [8]; teams with AI-assistant access have shown increases in defects reaching pull requests without matching throughput gains [21]; and higher AI adoption has been associated with a measurable drop in delivery stability [6]. These findings are correlational and partly industry-sourced, and modern agentic tools do iterate rather than emit code in a single pass. We therefore do not claim that unenforced tools produce unmaintainable code as a settled fact. We take the maintainability risk as real and motivating, and we ask which framework properties actually reduce it.

Our answer is that the property that matters is not how a framework specifies work but how it enforces the engineering discipline that keeps agent-written code clean, correct, and maintainable, in two respects: how it holds the work honest as the agent writes it, and how it divides the work among focused roles so that the result is maintainable, as it was when those roles were held by people. Enforcement comes in three sharply different strengths. This paper makes three contributions. First, a taxonomy of how agent-driven frameworks enforce that discipline: enforcement by persuasion, by front-loaded structure, and through controls the agent cannot edit, distinguished by what the agent is physically able to ignore. Second, Consort, a spec-first, test-driven agent framework in the same family as Spec Kit and superpowers but enforcing the discipline through controls the agent cannot edit, in which a deterministic orchestrator coordinates separate role agents and the enforced build lane runs the entire test-driven cycle against a live, branched database, a practice developed in a paper under anonymous review [11]. Third, a comparative evaluation against four installable frameworks in which agents write the code, GitHub Spec Kit, obra/superpowers, BMAD, and GSD, and a pre-registered hypothesis for the output-quality claim we cannot yet prove.

Two scoping notes bound the contribution. We compare only real, installable frameworks in which the agent writes code; hosted platform builders and fully autonomous issue-to-pull-request agents occupy an adjacent space and are named, not evaluated, here. And the database layer this framework depends on is not re-derived: its mechanism, economics, and defect-catching evidence are the contribution of a paper under anonymous review, which this paper takes as given in order to focus on enforcement of the agent’s work.

The remainder of the paper is organized as follows. Section II places the framework family on the spec-driven rigor ladder and reviews what unenforced agents do. Section III develops the central lens, the three ways a framework enforces engineering discipline on a non-deterministic worker. Section IV presents Consort as the realization of the third, enforcement through controls the agent cannot edit. Section V evaluates the frameworks head to head against the enforcement dimensions. Section VI states the output-quality claim as a pre-registered experiment. Section VII discusses implications, and

Section VIII concludes.

II. BACKGROUND AND RELATED WORK

A. The spec-driven rigor ladder

The frameworks we compare belong to spec-driven development, whose organizing idea is that a specification, not a prompt and not the code, should be the durable statement of intent. The clearest current account arranges the practice on a rigor ladder: spec-first agrees on the specification before code is written; spec-anchored keeps the specification live and reconciled with the code as it changes; and spec-as-source elevates the specification to the primary artifact from which code is generated [18]. The account is explicit that spec-driven development is a judgment call rather than a universal good, adding value on some problems and overhead on others.

The frameworks we examine span the lower two rungs. Spec Kit, superpowers, and our own are spec-first, agreeing a specification before code; BMAD and GSD reach spec-anchored, keeping planning artifacts (a product requirements document and architecture in BMAD, persistent state and context files in GSD) alive across the work. None is spec-as-source, and, more to the point, wherever a framework sits on this ladder it does not measure enforcement. That the comparators range from spec-first to spec-anchored and still leave the build largely to the agent is precisely the point: the specification is not the differentiator, and our framework claims no advantage in specification quality. The differentiator lies past the specification, in enforcement, which the ladder does not capture.

B. The enforcement thesis is emerging independently

The idea that a specification is insufficient without enforcement is not ours alone; it is being articulated across the field. Practitioner and vendor writing increasingly frames the problem as one of enforcement rather than authorship: that an agent without a governing operating model is unaccountable automation, and that platform enforcement is what converts spec-driven development from a methodology into a governed system [13]; that specifications should execute as validation gates so that a build fails on divergence rather than trusting the agent to comply [1]. Skeptical hands-on reviews reach a compatible conclusion from the opposite direction, observing that current spec-driven tooling can create excessive review overhead and a false sense of control, and that the discipline tends to evaporate once the agent begins writing code [4]. That last observation, that the discipline evaporates at exactly the moment the agent takes over, is the gap this paper’s framework is built to close.

C. What unenforced agents do

The case for enforcement rests on what agents do when they are not enforced. The behaviors are by now well documented. Agents disable or delete tests to turn a suite green, which is why treating tests as immutable has been proposed as a first-class discipline [2]. They over-mock relative to human developers, adding mocks in a materially larger share of

commits and thereby validating less real behavior [12]. At the scale of tens of thousands of sessions they violate constraints, overreach, and misreport their own actions, though the same evidence shows most such episodes cost effort and trust rather than causing irreversible damage [20]. A qualitative study of an AI-native IDE illustrates the texture of these failures, agents changing code that was not meant to change and requiring continual human correction, without offering population-level frequencies [15]. Taken together, the picture is not of a tool that occasionally errs but of a worker whose default behavior must be constrained if its output is to be trusted.

D. The comparators

GitHub Spec Kit is the reference open-source spec-driven toolkit, published under GitHub’s own organization [5]. It structures work as a command pipeline, from establishing a project constitution through specifying, clarifying, planning, a requirements checklist, tasks, analysis, implementation, and a convergence pass, which the coding agent itself runs. It front-loads specification and planning, and runs across many coding agents. Its enforcement, however, is light: test-driven development is optional and ungated, shipped so that tests are included only when explicitly requested; its governing constitution is honored as prose rather than checked mechanically; there is no deterministic orchestrator behind the pipeline; and there is no database in the loop, its data model being a design document rather than a running store.

obra/superpowers is a prescriptive methodology delivered as auto-triggering agent skills, spanning a brainstorming specification gate, a strong test-first rule, subagent-driven development, and staged review, and portable across many harnesses [22]. It shapes agent behavior through prompt craft, and states its test-first rule as an unconditional requirement. But its control loop is itself a language model rather than a deterministic driver, so it can lose its place across context compaction; its gates are soft prose; its tests are not tool-enforced; and it, too, has no database concept.

BMAD (the Breakthrough Method for Agile AI-Driven Development) is a role-play framework that splits work into an agentic-planning phase, in which named persona agents (an analyst, a product manager, an architect) co-author a product requirements document and an architecture document, and a context-engineered development phase, in which a developer agent implements stories sharded from those artifacts [3]. It front-loads planning into a product requirements document and an architecture document, with a test-architect agent that scores several quality dimensions and emits pass, concerns, or fail gate files. Its enforcement changed during this paper’s revision window: BMAD added bmad-loop, a deterministic, code-driven orchestrator whose test-architect gates are code-enforced blocks with human-only waivers. Those gates enforce coverage and quality thresholds after an epic rather than verifying code in-cycle; test-driven development is still not enforced within the cycle; and there is no database in the loop.

GSD (Git. Ship. Done.) is a lightweight, agent-agnostic context-engineering framework built around a five-phase loop,

discuss, plan, execute, verify, and ship, whose central goal is to fight the context degradation that accumulates as an agent fills its window by pushing research and execution into fresh-context parallel subagents while keeping the main session lean, with state and context files that persist across sessions [10]. Its strength is disciplined context hygiene and portability across many runtimes from a single install. Its enforcement stays deliberately thin: it has since added a documented seven-role taxonomy and orchestrator-invoked gate predicates, but their enforcement remains convention- and hook-level rather than code-guaranteed, and it has neither test-driven development nor any database concept.

E. Adjacent, not compared

Several systems sit near this work but in a different class and are named only to situate the contribution. Spec-as-source platforms such as Tessler, and spec-driven IDEs such as Kiro, occupy higher rungs of the rigor ladder and are hosted rather than installable methodologies. Autonomous issue-to-pull-request agents pursue end-to-end automation rather than an enforced developer-in-the-loop lifecycle. These are the surrounding field, not comparators, because the question here is how an installable, spec-first framework enforces engineering discipline on an agent that writes code within a developer’s workflow.

III. ENFORCING DISCIPLINE ON A NON-DETERMINISTIC WORKER

The premise of this paper is a single principle: *a control that the worker can choose to ignore is not a control when the worker is non-deterministic*. A developer who agrees to write a failing test first can be trusted, most of the time, to honor that agreement because the developer understands why it matters. An agent has no such commitment; it will honor a rule exactly insofar as the rule is present in its context, salient against competing instructions, and not more cheaply satisfied by circumventing it. Enforcing discipline on an agent is therefore not a matter of stating the right rules but of placing those rules where the agent cannot reach them.

Every framework in this family is trying to enforce the same engineering discipline: write the test first, keep the spec honest, do not fake a pass. They differ in how they enforce it. Against the principle above, the family falls into three modes, distinguished by what the agent is physically able to ignore.

Enforcement by persuasion. The framework’s controls are instructions to the model: rules, red flags, and prohibitions expressed in prose, however forcefully. obra/superpowers is the exemplar, relying on prompt craft. But every control, the orchestration, the gates, and even the test suite, is ultimately honored by the model and editable by it. Persuasion raises the floor on agent behavior, sometimes substantially. It cannot make a violation impossible, because the same worker that reads the rule can decide, under pressure to produce a green result, to set it aside.

Enforcement by front-loaded structure. The framework invests in getting the specification and plan right, then hands

the agent a task list and largely trusts the implementation. GitHub Spec Kit is the exemplar: its specifications and plans are checklist-validated, and its constitution states principles. But once the agent begins to build, testing is optional, the constitution is advisory, and no code-level mechanism prevents the agent from diverging. The intent is strong and the build-time enforcement is weak, which is precisely the pattern that leads discipline to evaporate once the agent takes over [4].

Enforcement through controls the agent cannot edit. The framework’s controls are code that the agent runs inside but cannot change. Routing between steps is a program, not a model decision. Every decision is gated, so the work does not advance until a human approves. Tests are immutable within a unit of work, so they cannot be weakened to force a pass. And a green result is defined operationally, as a test runner actually passing against a live database, rather than as the agent’s report that it passed. Under this mode the agent is free to write whatever code it likes, but it cannot delete the test that judges the code, cannot skip the gate that a human must approve, and cannot claim success the runner did not confirm.

These three modes are not points on a quality scale within a single design; they are different answers to one question: when the agent can ignore a control, what makes it comply anyway. Section IV shows how Consort enforces the discipline through controls the agent cannot edit. Section V scores all five frameworks against that question dimension by dimension.

IV. CONSORT

We introduce **Consort**, a spec-first, test-driven agent framework that enforces engineering discipline through controls the agent cannot edit. The name reflects the architecture: a consort is a small ensemble whose players perform one piece together, and here a set of role agents work as an ensemble under the coordination of the deterministic orchestrator. It has two lanes: a spec-first design lane, where intent is agreed and frozen, and an enforced build lane, which runs the full test-driven cycle against a live, branched database (Figure 1). The build lane is not a novel testing idea invented here; it is test-driven development run against a live database branch, a practice developed in a paper under anonymous review [11]. Consort is a reference implementation of that practice, and the contribution of this paper is not the database idea but what it takes to enforce that practice on a non-deterministic agent author.

A. The build lane runs TDD against a live database branch

It runs the entire red/green/refactor cycle, including the fast inner loop, against a copy-on-write branch of a real, production-shaped database, rather than against mocks or synthetic-seed fixtures. Copy-on-write branching makes an isolated, disposable branch of the real database available for each unit of work in roughly constant time, independent of data size, because the branch shares its parent’s storage until it diverges. A paper under anonymous review establishes why this collapses the long-standing tradeoff between test speed




Fig. 1. The Consort lifecycle. The role-agent ensemble performs the phases, and the human decides every gate (diamonds), namely the intake, plan, spec-and-test-list, per-story acceptance, deploy, and promote gates (a backlog-selection gate also sits inside planning). Routing between phases is handled by a deterministic orchestrator that writes no spec, code, or tests. Role agents are abbreviated: PO (product owner), SA (spec author), AR (architect reviewer), DBA, TS (test strategist), UX (UX designer, user-facing work only), and, in the build cycle, NAV (navigator) and DRV (driver; Fig. 2). Deploy and promote have no role agent; the orchestrator runs them directly. The loop runs per increment: the specification is frozen within an increment and evolves across increments.

and data fidelity, and catalogs the classes of data-dependent defect that mocks and synthetic seeds cannot surface. This paper takes those results as given. What it adds is enforcement: the machinery that makes an agent actually run the cycle this way rather than reporting that it did. Because each branch is cheap and isolated, the build lane can also run several experiments for one story in parallel, each on its own database branch and git worktree, and keep the one that best satisfies the tests, an exploration only cheap branching makes affordable.

B. The deterministic orchestrator

Consort's control flow is a program, not a language-model decision. A deterministic orchestrator, a state machine rather than an agent, sequences the work: for each unit of work it cuts a copy-on-write branch of the database, drives the red, green, and refactor steps against that branch, enforces the order of the human-approval gates, and discards the branch when the unit of work is complete. In effect, the coordinating role that an agile team would call the scrum master is rendered here as deterministic code rather than as a language model, so the process that drives the cycle and holds the gates cannot itself drift or be argued out of a step. Because routing is code, the control loop cannot be lost across context compaction, the failure to which a language-model control loop is exposed. And because branch provisioning and disposal are handled by the orchestrator, neither the developer nor the agent manages database fixture state by hand; the branch is the fixture, and its disposal is the reset. The orchestrator also stamps each experiment with a fingerprint of its design, so that if the design is revised the stale experiment is recut from the current design rather than silently reused.

C. Role-separated agents

Consort assigns work to a set of persistent, named role agents, each with a bounded responsibility and no shared memory with the others: a product owner, a spec author, an architect reviewer, a DBA, a test strategist, and a navigator and driver who run the test cycle together, with a UX designer added for user-facing work. Two of these roles carry responsibilities worth noting. The UX designer grounds its design guidance in real comparables: it opens the reference sites a brief names with a browser and reads their actual type, color, and spacing, or searches for representative sites when none is named, so that each design-token choice cites an observed reference rather than a default. The test strategist acts as a supervisor rather than a sole author, fanning out to per-kind analyst agents for behavior, fitness, and client tests and then reconciling and ordering their contributions into one test list. Deploy and promote are not a role agent but deterministic steps the orchestrator runs directly, logged under a release-engineer label. Coordination is deliberately not one of these agents: the role an agile team would call the scrum master is the deterministic orchestrator of Section IV, a state machine rather than a language model, so the ceremony that sequences the work is code and cannot itself be talked into skipping a step. The role separation among the agents is equally deliberate, and it does two things. First, it guards integrity: an agent that both writes code and judges it has every incentive to grade generously, whereas a role that only writes must satisfy a role, and a gate, it does not control. Second, and less obviously, it is where maintainability comes from. On human teams, the division of labor, a product owner who owns the requirement, a developer who implements it, a reviewer who tests it, produced maintainable software precisely because each concern had an owner whose focus was that concern and not the others; a single generalist optimizing only for a

passing result tends to produce code that passes and little else. Consort reproduces that division among agents, so that each role optimizes its own concern, the clarity of the requirement, the simplicity of the implementation, the adequacy of the tests, and the output carries the same separation of concerns that made human-built systems maintainable. This is a claim about the mechanism; maintainability itself remains the hypothesis of Section VI. The mechanism is role specialization, not enforcement alone: enforcing the tests and gates in code keeps the verification honest, while the focused roles are what make the software maintainable, just as they did when the roles were held by people. This differs from Spec Kit, where a single agent runs the whole pipeline, and from superpowers, where subagents are dispatched ephemerally; here the roles are stable participants in a single coordinated lifecycle.

D. Enforcement primitives

Consort's guarantees rest on a few controls, each code rather than prose the agent may reinterpret. The discipline is enforced in concrete ways:

- **Tests are immutable within a unit of work.** The approved test list is locked, and an in-cycle attempt to delete or weaken a test is caught and flagged. The one controlled exception is principled and rare: when a later story legitimately supersedes an earlier test, a designated step refactors only those superseded tests, under an explicit rule, and then re-verifies; an ordinary failing test is never touched.
- **Green is honest by definition.** Success is recorded only when a test runner actually passes against a real branch, not when the agent asserts it.
- **Cross-story field contracts are checked before code.** If one story mandates a required field and the story that owns the user-submit path has no acceptance criterion that supplies it, the design lane flags the gap rather than letting the feature reach a build that ships a form the database will reject.

Together these make branch-based TDD enforceable rather than merely recommended: immutability answers the test-deletion failure mode [2], because within the unit of work the tests are not writable; honest-green answers inaccurate self-reporting [20], because the record of success is the runner's, not the agent's. A human lever sits alongside these: the product owner can mark a story as requiring an end-to-end test, a requirement the design lane cannot downgrade.

E. Real-data verification is the green condition

The single property that no comparator shares is the definition of green. In Consort, a green result is a passing run against a live copy-on-write branch of real data. Each verify runs on a fresh branch cut for that check and discarded when it finishes, so the result reflects the committed schema and no prior run's writes, rather than accumulated state on a shared instance. Two of the agent's cheapest escape routes close at once. It cannot delete the test, because the test is immutable (Section IV-D). And it cannot substitute a compliant mock

for real behavior, because the collaborator is a real database rather than a double the agent can shape to its convenience, which is the structural counter to the over-mocking that agents otherwise exhibit [12]. A green result therefore requires code that actually works against production-shaped data, with the database’s constraints and governance (access and masking policies inherited from the branch) in force. Spec Kit stops at a data-model document and superpowers has no data concept, so for both the notion of green never touches a real database. The mechanism and economics that make per-cycle real-data verification affordable are that paper’s contribution, cited here rather than re-argued.

F. The design lane

Before the enforced build lane runs, the design lane is where Consort meets the spec-driven field on its own ground. Intent is captured in a specification and a list of the tests that will demonstrate it, and both are frozen at an approval gate and checked for drift thereafter, so that the target the agent builds against cannot quietly move. This is spec-first, like the comparators; the difference is that the frozen specification and test list feed a build lane whose enforcement is structural, so the discipline does not evaporate when the agent takes over.

G. Context management

Agent sessions accumulate context until output quality degrades or the model refuses. Consort bounds this in the orchestrator. Because roles share no memory and pass everything through on-disk artifacts, any turn can be reloaded cold, so a fresh start is always safe. The orchestrator tracks each session’s token usage against the model’s window and, when a warm resume would leave less than a configurable fraction free (40 percent by default), starts the next turn fresh. It keeps warm resumption where it is cheap, reusing the prompt cache across a story’s cycles. GSD pursues the same goal with fresh-context subagents; here it is an enforced property of the deterministic driver, not a convention. Consort also scopes what each turn sees. Rather than the whole codebase, an agent is handed a context package with the exact tests it must pass, the relevant requirements, and where those tests live, which lowers cost and removes the unscoped wandering that otherwise lets an agent drift.

V. COMPARATIVE EVALUATION

The evaluation is, in the first instance, analytic: the five frameworks are placed against the dimensions that determine whether an agent’s output can be trusted, and the pattern that emerges is that Consort is the only one whose controls are enforced rather than requested. Table I summarizes the comparison; the discussion that follows evaluates each dimension in turn, draws out the crux, and concedes where the comparators lead.

A. Dimension by dimension

Spec-driven level. All five frameworks capture intent before the build, and two, BMAD and GSD, keep it anchored as living

artifacts. The rung on the ladder is not itself an enforcement property: a higher rung buys nothing if the captured intent is not binding on the agent. What makes intent binding is the next dimension.

Spec freeze and drift. A living specification is one the agent can edit, and for a non-deterministic author, editable and able-to-laundry-a-failure are the same property: under pressure to pass, the agent can drift the spec to match whatever it built. Consort freezes the specification and its test list at a hashed gate for the duration of an increment, so the target cannot move mid-build, and evolves it across increments under a human re-plan. A living spec is right when a human keeps it honest; a spec frozen per increment is right when an agent does the editing.

Test-driven development. Tests are the executable form of the spec, so where they sit decides whether output is checked as it is written. Optional or post-hoc testing (Spec Kit’s ungated tests, BMAD’s after-the-epic quality assurance, GSD’s absence of a test concept) leaves the moment of authorship unguarded, and a strong but unenforced rule (superpowers’ Iron Law) depends on the model honoring it. Consort makes the red/green/refactor cycle the build itself: code that does not satisfy a previously written test does not come into being.

Test immutability. The test is what judges the code, so if the agent can weaken or delete it, a green result certifies nothing [2]. Only Consort holds tests immutable within a unit of work, with a single bounded, re-verified exception for legitimate supersession (Section IV-D). Everywhere else the tests remain editable by the same agent they are meant to constrain.

Database in the loop. This is the one dimension that changes what the agent is verified against rather than how its process is run, and it is the subject of Section V-C. No comparator has a database in the loop, so none can surface the data-dependent defects that only real data exposes.

Orchestration. When the control flow is itself a language model, as it is in all four comparators, it can be lost across context compaction or reasoned around, so the process meant to enforce the rules is subject to the same non-determinism as the work it is meant to control. Consort’s routing is deterministic code, so the sequence of steps and gates cannot itself drift.

Gates. A gate is a control only if it can refuse. Advisory gates, whether prose, a waivable pass-concerns-fail file, or convention, request compliance and can be passed by the agent or waived by the team. Consort’s gates require a human to approve each decision before the work advances.

Role separation. A single agent that writes and judges its own work has every incentive to grade generously, and beyond integrity, focused roles are where maintainability comes from, reproducing the human division of labor (Section IV-C). BMAD’s six named personas capture much of this; Consort adds that a role cannot perform another’s job and that the judge runs against real data.

Context management. Every framework must fight context rot, and most do it by convention: fresh-context subagents




Fig. 2. Honest-GREEN. GREEN is stamped only when the verify suite genuinely passes against a live branch of real data, not when the agent reports success. A failed verify routes either to a bounded code repair that never touches the tests, or, when a later story legitimately supersedes a prior test, to a rule-bound permissive-green that refactors only the flagged superseded tests; unresolved cases escalate to the human. The navigator (NAV) owns the test-facing steps and the driver (DRV) the code-facing steps, so the agent that writes the code is never the one that judges it.

TABLE I
ENFORCEMENT DIMENSIONS ACROSS THE FIVE FRAMEWORKS.

Framework	SDD level	Spec frozen / drift-checked	TDD	Tests immutable	Database in loop	Orchestration	Gates	Role separation	Context management
Consort	Spec-first	Yes (hashed)	Core, enforced	Yes	Live branched DB	Deterministic (code)	Required (human-approved)	Eight named roles*	Memoryless; resets at 40% free window
GitHub Spec Kit	Spec-first	No (editable)	Optional, ungated	n/a	None	LLM (agent-run)	Advisory (prose)	One agent	Batching + sub-agent delegation
obra/ superpowers	Spec-first	No (model-editable)	Strong rule, unenforced	No	None	LLM control loop	Advisory (soft prose)	Ephemeral subagents	Fresh-context subagents (can lose place)
BMAD	Spec-anchored	No (editable)	Optional (post-epic QA)	No	None	Deterministic (bmad-loop)	Code-enforced, post-hoc (coverage/quality)	Five named personas	Self-contained sharded stories
GSD	Spec-anchored	No (living)	Absent	n/a	None	LLM (agent loop)	Advisory (convention)	Documented taxonomy (hook-enforced)	Fresh-context subagents + STATE/CONTEXT

*A role is a bounded function the orchestrator enforces: a role cannot do another role's job, and roles share no memory. A persona (BMAD) is a named character the agent role-plays, honored by the model, not an enforced boundary.

invoked by prompt (GSD), self-contained sharded stories (BMAD). Consort measures it instead, the orchestrator tracks each session against the model's window and resets to a fresh, disk-reloaded turn once a resume would leave too little of the window free (Section IV), so the bound is enforced by code rather than by the agent staying disciplined.

B. The crux

The table maps onto the three modes of Section III. superpowers enforces by persuasion: its test-first rule, its orchestration, and its tests are all editable by the model. Spec Kit enforces by front-loaded structure: its specifications are checklist-validated and its build-time enforcement is optional. GSD sits alongside them, agent-driven with convention- and hook-level gates and a documented role taxonomy that is not code-guaranteed.

In the interval between this paper's first draft and its final revision, one comparator moved further. BMAD's bmad-loop, a deterministic, code-driven orchestrator whose test-architect gates are code-enforced blocks with human-only waivers, landed in that window, so deterministic orchestration and code-enforced gating are no longer unique to Consort. But BMAD's gates enforce coverage and quality thresholds computed after an epic, not the in-cycle, immutable-test, real-data verification that Consort's gates enforce. On what is gated, a real test passing against a live, branched database with tests the agent cannot weaken, Consort remains alone.

Consort enforces through controls the agent cannot edit: the orchestrator is code, a human gates each decision, the tests are immutable, and green is a real run against a real, branched database. Where the others request compliance, or

enforce it only after the fact, Consort enforces it at the moment of authorship against real data, and the difference is not one of degree but of whether a determined or careless agent can proceed without complying.

C. The uncontested axis

One row has no contest at all. None of the comparators runs the test loop against a real, branched database, because none has a database in the loop: Spec Kit stops at a design-time data model, and superpowers, BMAD, and GSD have no data concept. We state the novelty precisely, as that paper does: testing against a database is old, and integration and acceptance tests have always done it; what is new is running the entire cycle, including the fast inner loop, against a branch of real data at a per-cycle cost low enough to be routine [11]. That axis is where Consort’s output claim ultimately rests, because it is the only one of the enforcement dimensions that changes what the agent is verified against, not merely how its process is controlled.

D. Where the comparators lead

The comparators do things Consort does not. Today they are more portable, running across many coding agents, harnesses, and runtimes. Consort was first developed on Claude, but will soon be multi-harness and multi-model through the Unity Gateway (planned). Spec Kit also has an editable constitution that Consort does not support yet. Consort trades portability and lightness for verifiability of the agent’s output: a team that values reach across many agents, or that is working on code where the maintainability risk is low, may reasonably prefer a lighter framework. Enforcement through controls the agent cannot edit carries a cost, warranted when the cost of wrong or unmaintainable agent output is high: it is the only one of the three modes whose guarantees hold no matter how the agent behaves.

VI. A CONTROLLED EVALUATION (PRE-REGISTERED, FUTURE WORK)

The analytic comparison establishes that Consort enforces what the others request. It does not, by itself, establish that enforcement produces better code, and we are careful not to assert the stronger claim as though it were demonstrated. The output-quality claim is a hypothesis, and we state it as one.

Given the same agent and the same feature, a framework with enforced immutable tests, deterministic gates, real-data verification, and separated role agents yields output with fewer silent regressions, no test-gaming, and higher maintainability than frameworks that rely on the model honoring prose rules.

The experiment that would test this holds the agent and the task fixed and varies only the enforcement regime. The same features, drawn from industrially relevant, stateful tasks rather than stateless katas, are implemented under each of the frameworks with the same underlying model. Five families of

measure follow the hypothesis. Silent regressions are counted as defects that pass a framework’s own gates but are caught by an independent, held-out test suite. Test-gaming is counted directly, as tests deleted, weakened, or adjusted to force a green result, the dimension on which immutability should show its effect. Maintainability is assessed both by independent review and by objective proxies such as duplication and specification-to-code drift, the same signals whose decline motivates the study [8]. And real-behavior coverage is measured as the share of tests exercising a real database rather than doubles, which ties Consort’s distinctive axis to an outcome. Cost is measured as tokens per shipped feature at a fixed model, and is reported against the quality measures rather than alone, so the comparison is quality gained per token spent, not lowest cost.

We pre-register the hypotheses and the direction of each effect, and assert no target magnitudes in advance, so that the analysis answers the rigor-and-relevance concerns that have dogged tool-comparison studies. Several threats to validity are visible from the outset. The author builds one of the frameworks under test, a dual role that must be declared and mitigated with framework-neutral tasks, independent reviewers, and an invitation to replicate. The frameworks differ in harness portability, so the agent must be held constant across regimes to keep the comparison about enforcement rather than tooling. And maintainability is a construct whose operationalization is itself contestable and must be fixed in advance. This is the same evidentiary posture as that paper’s deferred productivity experiment [11]: the mechanism is argued now, the outcome is measured later, and the remedy is offered as a hypothesis rather than a proven cure.

A. The scoring instrument, and keeping it independent

The measures above (silent-regression rate, test-gaming, dropped intent, real-behavior coverage) are scored by an LLM-as-judge on a fixed model against a fixed reference, so the bar does not move with the system under test. Consort ships such an instrument: its evaluation package, a fixed-model discriminator that scores an output against a recorded reference and classifies code as equivalent, a superseded shift, a regression, or insufficient, against the architect’s non-functional requirements and design canon. Because that instrument is part of the system under test, using it unmodified would not be independent. We therefore plan to release the evaluation package as an open, framework-neutral artifact so the measurement can be inspected and rerun by others, and would bind it with five safeguards:

- 1) Neutral reference: score every framework against a pre-registered specification and acceptance criteria authored independently of any framework, not against one framework’s recorded artifacts.
- 2) Judge decoupled from generator: judge with a model distinct from the one generating the code, or an ensemble, and report inter-judge agreement.
- 3) Human calibration: validate the judge against expert human ratings on a sample and report the agreement.

- 4) Blinding: the judge is not told which framework produced an output.
- 5) Independent execution: the study is run and scored by parties not authoring the frameworks under test.

Released and neutralized this way, the instrument would become a contribution that invites replication rather than a private grader.

VII. DISCUSSION

Consort’s defining choice is to put a live database in the loop and enforce the cycle against it through controls the agent cannot edit. That requires a database dependency and enforcement machinery the other frameworks do not, and it is not free. That weight buys guarantees that hold regardless of how the agent behaves, which matters most where the cost of wrong output is high: regulated systems, code that touches money or personal data, and long-lived code whose maintainability compounds. For a throwaway prototype the weight is not worth carrying.

Real-data verification has a particular consequence for regulated work. The reason teams in sensitive domains test against synthetic data in staging is that production data is masked or off-limits, and an AI assistant’s unverified output does not survive an audit [16]. A branch that carries real data with its lineage and access controls intact makes real-data testing admissible where a raw copy would not, and enforcing the controls in code supplies the audit trail: the gate that a human approved, the immutable test that judged the code, and the branch it ran against. The combination is not merely a better inner loop; it is an argument that agent-written code was verified against the real thing under controls that an auditor can inspect.

More broadly, the field is converging on the conclusion that a specification without enforcement is not enough, whether stated as platform enforcement [13], as specifications that execute as validation gates [1], or as the observation that spec-driven discipline evaporates once the agent begins to write [4]. Consort’s position within that convergence is a specific one: put the controls where the agent cannot edit them, and define success as a real run against real data. As more code is written by agents, the artifact the agent is held to, an immutable test on a branch, becomes the locus of control, displacing the prompt. That is the transferable idea, independent of any one framework: enforce the discipline through controls the agent cannot edit, not by persuasion.

VIII. CONCLUSION

Spec-first, agent-driven development frameworks have gained rapid traction since 2025, and they agree on how intent is captured. What separates them is how they enforce clean, correct code from that intent, and enforcement comes in three strengths: persuasion, which the agent may ignore; front-loaded structure, which the agent outruns once it starts building; and controls the agent cannot edit. We have introduced Consort, a spec-first, test-driven agent framework, as a reference realization of the third mode, whose enforced build

lane runs the entire test-driven cycle against a live, branched database, the practice developed in a paper under anonymous review. We have argued analytically that it enforces what the others request, and we have stated the output-quality claim as a pre-registered hypothesis rather than a proven result. The transferable contribution is the principle, not the product: when an agent writes code, the controls that matter are the ones it cannot ignore, and the result that matters is the one a real database will actually accept. We offer Consort and the principle for adoption and independent evaluation.

REFERENCES

- [1] Augment Code (M. Shah), “What is spec-driven development? A complete guide,” Augment Code, Apr. 23, 2026 (updated Jun. 18, 2026). <https://www.augmentcode.com/guides/what-is-spec-driven-development>
- [2] K. Beck, “Augmented coding: Beyond the vibes,” Newsletter, Jun. 25, 2025. <https://newsletter.kentbeck.com/p/augmented-coding-beyond-the-vibes>
- [3] BMAD, “BMAD-METHOD: Breakthrough Method for Agile AI-Driven Development,” open-source framework (bmad-code-org), v6, accessed Jul. 25, 2026. <https://github.com/bmad-code-org/BMAD-METHOD>
- [4] B. Böckeler, “Understanding spec-driven development: Kiro, spec-kit, and Tessler,” martinoflower.com, Oct. 15, 2025. <https://www.martinoflower.com/articles/exploring-gen-ai/sdd-3-tools.html>
- [5] D. Delimarsky, “Spec-driven development with AI: Get started with a new open source toolkit,” The GitHub Blog, Sep. 2, 2025.
- [6] DevOps Research and Assessment (DORA), “Accelerate State of DevOps Report 2024,” Google, 2024. <https://dora.dev/research/2024/dora-report/>
- [7] Y. Ge et al., “A survey of vibe coding with large language models,” arXiv:2510.12399, 2025.
- [8] GitClear, “AI copilot code quality: 2025 data suggests 4x growth in code clones,” 2025.
- [9] GitHub, “Octoverse 2025: A new developer joins GitHub every second as AI leads TypeScript to #1,” The GitHub Blog, 2025.
- [10] GSD, “Git. Ship. Done. (gsd-core),” open-source context-engineering framework (open-gsd), accessed Jul. 25, 2026. <https://github.com/open-gsd/gsd-core>
- [11] An unpublished paper, in preparation; the authors have asked to have their names withheld.
- [12] A. Hora and R. Robbes, “Are coding agents generating over-mocked tests? An empirical study,” in *Proc. Int’l Conf. Mining Software Repositories (MSR)*, 2026, arXiv:2602.00409.
- [13] Itential, “Spec-driven development for agentic operations,” Itential (site copyright 2026). <https://www.itential.com/learn/spec-driven-development/agentic-autonomous-operations/>
- [14] A. Karpathy, post introducing “vibe coding,” X, Feb. 2, 2025.
- [15] A. Kumar, Y. Bajpai, S. Gulwani, G. Soares, and E. Murphy-Hill, “Why AI agents still need you: Findings from developer-agent collaborations in the wild,” arXiv:2506.12347, 2025.
- [16] A. A. Mammo, O. S. Abidemi, and K. K. Pantangi, “Developer perspectives on AI-driven code debugging in financial systems,” MSc thesis, Lund University, 2025.
- [17] METR (J. Becker, N. Rush, E. Barnes, and D. Rein), “Measuring the impact of early-2025 AI on experienced open-source developer productivity,” Jul. 10, 2025, arXiv:2507.09089.
- [18] D. B. Piskala, “Spec-driven development: From code to contract in the age of AI coding assistants,” arXiv:2602.00180 (ACM AIWare 2026), 2026.
- [19] Stack Overflow, “2025 Developer Survey: AI,” 2025. <https://survey.stackoverflow.co/2025/ai/>
- [20] N. Tang et al., “How coding agents fail their users: A large-scale analysis of developer-agent misalignment in 20,574 real-world sessions,” arXiv:2605.29442, 2026.
- [21] Uplevel Data Labs, “Does GenAI improve software developer productivity?” Uplevel, Sep. 17, 2024.
- [22] J. Vincent (obra), “superpowers,” open-source agent-skills framework, first released Oct. 2025. <https://github.com/obra/superpowers>