

# API Benchmark Scores Do Not Reliably Transfer to Chatbot Interfaces

Jennifer Wang   Joachim Baumann   Daniel E. Ho<sup>†</sup>   Sanmi Koyejo<sup>†</sup>

Stanford University  
Stanford, CA, USA

jennjwang, joachimbaumann, deho, sanmi@stanford.edu

<sup>†</sup>Equal senior authorship

## Abstract

Benchmark scores are a central currency in model releases: they inform purchasing decisions, shape public trust, and influence policy. Yet, a key assumption underlying benchmark scores is that the model performance measured through APIs faithfully reflects the behavior of deployed systems.


We challenge this assumption by auditing ChatGPT, Claude, and Gemini across seven systems and nine benchmarks spanning general capability, social bias, and sycophancy. We find systematic API–interface differences in both accuracy and consistency. On average, API evaluations score 3.4 percentage points higher in accuracy and 2.1 percentage points higher in test–retest agreement than corresponding interface evaluations. For ChatGPT, the performance difference between API and interface access exceeds the API-only difference between GPT 5.3 and GPT 5.4. Put differently, switching access surfaces can degrade performance as much as downgrading a full model generation.

We further test whether exposed API controls can reproduce interface behavior by varying system prompts, sampling parameters, and reasoning settings. These controls shift behavior in some cases but do not reliably eliminate the gap. Our findings document a context-validity gap: measurements obtained through APIs do not necessarily generalize to corresponding deployed interfaces, complicating the use of API evaluations as proxies for deployed systems.

## 1 Introduction

Benchmark scores are a key coordination signal in the AI ecosystem (Koch et al., 2021). They structure leaderboards (Singh et al., 2025), feature in model releases (OpenAI, 2026), shape press coverage (Roose, 2026), and help users reason about model utility (Hardy et al., 2024). Functionally, benchmarks provide market signals: a way to compare systems, track progress, and guide adoption (Lewis and Crews, 1985).

We send identical prompts to model API and chat interface



Interface evaluations systematically **score lower than API**




Figure 1: **Chatbot systems systematically underperform their corresponding APIs.** Across platforms, identical prompts receive lower-scoring and less consistent responses through the interfaces than through the corresponding model APIs.

This use of benchmarks, however, assumes that the signal they provide transfers across contexts (Saxon et al., 2024). A score measured in one setting is treated as evidence about how a model or system will perform in another. Benchmark measurements, however, are inherently contextual (Brundage et al., 2026). They depend on the model snapshot, prompt format, sampling configuration, scoring procedure, and access surface through which the system is evaluated.

A growing body of work has studied benchmark validity (Eriksson et al., 2025; Reuel et al., 2024). Benchmark scores may be inflated by data contamination, where models are exposed to test items or close paraphrases during training (Yang et al., 2023b; Dong et al., 2024). They may also be sensitive to noisy or invalid items, prompt formatting, answer choices, and evaluation protocols (Rodriguez

et al., 2021; Truong et al., 2025; Lu et al., 2022; Webson and Pavlick, 2022). These critiques target whether benchmarks measure the intended capability under a given evaluation setup. We ask whether measurements obtained in one evaluation context generalize to another context of use — a dimension of ecological validity referred to as *context validity* (Schmuckler, 2001).

In particular, we focus on whether benchmark results measured through model APIs predict behavior in deployed chatbot interfaces (Figure 1). Chatbot interfaces have become an indispensable surface through which users experience AI capabilities. More than 900 million users use ChatGPT every week, sending billions of prompts every day (Malik, 2026; Silberling, 2025). However, despite the scale at which these systems operate, evidence on system capabilities and risks is often collected through model APIs rather than user-facing interfaces (Chang et al., 2023). This creates a gap between the context in which many benchmark scores are produced and the context in which their results are often interpreted.

To quantify this gap, we audit ChatGPT, Claude, and Gemini across seven systems and nine benchmarks spanning general capability, social bias, sycophancy, and hallucination. For each system, we issue identical prompts to both the model API and the corresponding web interface, then compare benchmark outcomes across access surfaces. While this comparison is conceptually simple, measuring it requires controlling for confounds including request routing, session-level personalization, tool invocation, temporal drift, and output extraction. We develop a methodology that controls for these sources of variation and release an open-source tool that programmatically queries chatbot platforms through their web interfaces.

We find that API and interface measurements often diverge. The differences appear in both accuracy and test–retest agreement, and their magnitude varies substantially across systems and benchmarks. On average, API evaluations score higher than interface evaluations, but the more general finding is not that one surface always dominates the other. Rather, benchmark outcomes are context-dependent: the same prompts can yield different measured behavior depending on whether they are issued through an API or a deployed chatbot interface. We further test whether exposed API controls can reproduce interface behavior by varying system prompts, sampling parameters, and reasoning set-

tings. These controls shift behavior in some cases but do not reliably eliminate the gap.

## 1.1 Our Contributions

To our knowledge, this work presents the first large-scale, controlled study of whether LLM benchmark results generalize across API and chatbot-interface access for multiple platforms, models, and benchmark categories.

Our contributions are as follows:

1. We systematically measure how access surface—API versus deployed chatbot interface—affects LLM benchmark results. In a controlled audit of ChatGPT, Claude, and Gemini, we find that accuracy, test-retest consistency, and system rankings can differ across access surfaces, with effects varying by system and benchmark.
2. We test whether exposed API controls can account for these differences and find that varying system prompts, sampling parameters, and reasoning settings does not reliably reproduce interface behavior.
3. We release an open-source tool for auditing and continuously monitoring the behavior of deployed chatbot systems.<sup>1</sup>

## 2 Related Work

### 2.1 Ecological Validity of Benchmarks

A foundational goal of LLM evaluation is to produce measurements that reflect how systems are used in practice (De Vries et al., 2020). Ecological validity captures the extent to which test performance predicts behaviors in real-world settings (Chaytor and Schmitter-Edgecombe, 2003). Following Schmuckler (2001), we distinguish three dimensions of ecological validity: the *content* inputted to the model, the *task* it performs, and the *context* in which the interaction occurs. We use *context validity* to describe whether measurements obtained in one evaluation environment generalize to another.

Recent work has made substantial headway on improving the content and task validity of LLM evaluations. Crowdsourced efforts like Chatbot Arena (Chiang et al., 2024) and WildBench (Lin et al., 2024) draw on open-ended user interactions to capture the ambiguity and diversity of real user queries. Other work explicitly models the end users

<sup>1</sup><https://github.com/jennjwang/interface-audit>

and embeds tasks in human–AI interaction (Chang et al., 2025; Shao et al., 2025; Chopra et al., 2026). On the task side, benchmarks like GDPVal (Patwardhan et al., 2025) and  $\tau$ -Bench (Yao et al., 2024), as well as domain-specific evaluations (Li et al., 2025; Yang et al., 2023a), improve task validity by evaluating models on scenarios that more closely mirror practical use.

Comparatively less attention has been paid to the evaluation context: the technical and interaction environment in which the system is assessed. LLM audits often focus on either controlled foundation-model evaluations or application-level audits of deployed systems, leaving a “missing middle” of intermediate layers between user input, the model, and the final response (Neumann and Singh, 2025). These middle layers can substantially shape outcomes: system prompts can alter bias relative to user prompts (Neumann et al., 2025); retrieval, memory, and conversation context can degrade or destabilize performance (Kuo et al., 2025; Castillo-Bolado et al., 2024; Miresghallah et al., 2025). Although these individual components are known to affect model behavior, this evidence does not establish the magnitude, direction, or consistency of their combined effects. Nor does it establish whether controls available to external evaluators can reproduce the interface behaviors.

We address this gap by targeting access surface as a distinct dimension of context validity. Rather than attempting to isolate each hidden component in the deployment pipeline, we ask whether benchmark measurements themselves remain valid as they transfer across access surfaces. This framing shifts attention from the effects of individual layers to whether their combined influence changes the conclusions drawn from API-based evaluations.

## 2.2 Auditing LLM Systems

Our work builds on the tradition of algorithmic auditing, which evaluates deployed systems externally as black boxes, often through user-facing interfaces (Sandvig et al., 2014). This approach has been applied to generative AI products, including chatbot interfaces (Harvey et al., 2025; Stanusch et al., 2025) and AI search engines (Liu et al., 2023; Hu et al., 2025; Li and Sinnamon, 2024). Harvey et al. (2025) identify substantive and ecological validity challenges in chatbot audits from a case study on Amazon’s customer service chatbot. Wang et al. (2025) surface a related concern, showing that identical prompts can elicit different responses from

stateless model calls and real users’ ChatGPT or Gemini sessions due to chatbot personalization.

Our work differs in scope and object of measurement. Prior audits focus on specific user-facing behaviors, such as personalization (Wang et al., 2026), delusion reinforcement (Kirgis et al., 2026), or content moderation (Lipphardt et al., 2026). We instead study whether benchmark measurements transfer across access surfaces. This shifts the question from whether particular harms manifest differently in the interface to whether API-based benchmark scores accurately characterize chatbot behaviors.

## 3 Experimental Setup

We compare chatbot behavior across the user-facing interface and corresponding model API for 7 systems across ChatGPT, Claude, and Gemini. For each system, we issue identical prompts drawn from a distilled set of 9 benchmarks to both conditions and control for confounding sources of variation to estimate system-level effects.

### 3.1 Benchmarks

We evaluate two groups of tasks. The first covers general capabilities commonly reported in leaderboards and model releases (Anthropic, 2024; OpenAI, 2024; Beeching et al., 2023). The second targets user-facing risks and reliability failures that may be shaped by deployment-layer controls.

For general capabilities, we use six benchmarks from the OpenLLM Leaderboard (Beeching et al., 2023): ARC Challenge (ARC) (Clark et al., 2018), Grade School Math 8K (GSM8K) (Cobbe et al., 2021), HellaSwag (HS) (Zellers et al., 2019), Massive Multitask Language Understanding (MMLU) (Hendrycks et al., 2021), TruthfulQA (TQA) (Lin et al., 2022), and WinoGrande (WG) (Sakaguchi et al., 2019). Since frontier models often perform near ceiling on these tasks through the API, drops in the interface condition provide a useful sensitivity test for deployment-layer effects. However, evaluating the full six-benchmark suite through user-facing interfaces is costly: the original suite contains 28,659 items, and interface evaluations cannot be batched as easily as standard API-based runs. To make repeated interface evaluations tractable, we use Metabench, a sparse distillation that reduces the original six-benchmark suite to 858 highly informative items (Kipnis et al., 2025).

For user-facing risks, we use Bias Bench-

mark for Question Answering (BBQ) (Parrish et al., 2022) for social bias, AITA-NTA (AITA) from ELEPHANT (Cheng et al., 2026) for sycophancy, and AA-Omniscience (AA-Omni.) (Jackson et al., 2025) for cross-domain knowledge reliability. These tasks are relevant for system auditing because the corresponding behaviors may depend on system prompts, safety policies, output filters, tool access, or other deployment-layer components. For BBQ and AA-Omniscience, we evaluate 200 randomly sampled items; for AITA, we sample 100 original–flipped pairs and evaluate both sides. We use the same sampled items in the API and interface conditions, so our comparisons estimate the differences between access surfaces on a fixed evaluation set rather than attempting to recover full-benchmark scores.

### 3.2 Models and Systems

Our audit distinguishes between *models* accessible via API and *systems* that integrate those models into consumer-facing products. We tested seven systems across three providers: ChatGPT, Claude, and Gemini. For each interface system, we matched the deployed chat product to the closest available API identifier using provider documentation, model names exposed in the interface, and public release information (Table 1).

This matching is necessarily approximate. Commercial providers do not generally reveal the exact model checkpoint used for each interface response. Consequently, our comparisons estimate differences between the deployed interface system and the closest documented API configuration, rather than a fully controlled comparison of two access paths to a guaranteed identical checkpoint. We note this as a central limitation and avoid attributing observed gaps to any single deployment-layer mechanism without supporting evidence.

### 3.3 Data Collection

We created new anonymous accounts for data collection across providers: five ChatGPT Enterprise accounts, three Claude Pro accounts, and three Google AI Pro accounts. Within each provider, accounts were configured with the same visible settings and subscription plan. Because account counts and subscription tiers differ across providers, we do not use these data to compare providers or models directly; instead, we focus on whether each provider’s interface measurements diverge from its corresponding API measurements.

Table 1: Interface and API model identifiers.

| Interface Model         | API Identifier                                   |
|-------------------------|--------------------------------------------------|
| GPT 5.3 Instant         | gpt-5.3-chat-latest                              |
| GPT 5.4 Thinking        | gpt-5.4-2026-03-05                               |
| Claude Haiku 4.5        | claude-haiku-4-5-20251001                        |
| Claude Sonnet 4.6       | claude-sonnet-4-6                                |
| Claude Opus 4.6         | claude-opus-4-6                                  |
| Gemini 3 Flash Fast     | gemini-3-flash-preview<br>(thinking_level: low)  |
| Gemini 3 Flash Thinking | gemini-3-flash-preview<br>(thinking_level: high) |

We ran every query across five independent trials. Trials were rotated across the pool of study accounts, so the five trials for each system were not all issued from a single account. Each trial used a fresh ephemeral Chrome profile without carrying over any browser states. Within each trial, every query was issued in a fresh chat window with no prior turns in the active conversation.

Data collection spanned from March 6 to May 24, 2026. Table 28 reports the specific collection window for each benchmark–model pair. We capped throughput at 150 queries per three-hour window and imposed a two-hour cooldown after any rate-limit event to respect provider limits and reduce bot-detection triggers.

### 3.4 Experimental Controls

As commercial chatbot platforms do not expose their full request pipeline, observed interface–API differences could reflect unrelated confounds. We address five potential sources of spurious variation.

**Request routing.** Platforms may route different accounts, sessions, or requests to different model variants without disclosure. We hold fixed two observable routing factors: all requests are issued from the same network, and all accounts use the same subscription tier. These controls do not rule out unobserved routing mechanisms, such as A/B testing. We run additional robustness checks in Appendix H to test whether our main findings are sensitive to account- and request-level assignments.

**Session-level personalization.** We disable all user-facing personalization features, such as chat history and memory. However, platforms may still condition responses on session-level signals beyond these settings (e.g., session tokens, browser fingerprint). To mitigate this, we issue each query in a fresh browser instance with no persistent cookies, local storage, conversation history, or browser state carried across trials.

**Tool Invocation.** Chatbot systems often invoke external tools such as web search, which can materially affect outputs. For ChatGPT and Claude, we disabled all platform-specific tools. For Gemini, where web search could not be disabled, we prepended an instruction asking the model not to use web search (see Appendix E.3).

**Temporal drift.** Continuous model updates mean that interface and API responses collected at different times may reflect different model versions. To minimize this risk, we synchronize requests for each benchmark item. A per-query barrier holds all parallel sessions—one per model and condition, including API workers—until each session has selected the appropriate model, opened a fresh chat or request context, and prepared the prompt. Once all sessions reached this state, the prompts are submitted across conditions within seconds.

**Output Normalization.** Whereas interface responses are rendered with Markdown, citations, and UI chrome, API responses are raw text. To prevent surface-form differences from affecting scoring, we strip interface outputs to plain text and pass both conditions through the same benchmark-specific extraction and grading pipeline.

Together, these controls address observable differences between access surfaces but cannot isolate every stage of the underlying request pipeline. Appendix Table 3 provides a layer-by-layer taxonomy of these mechanisms, distinguishing those controlled by our design, tested through ablation, and unobservable under black-box access.

### 3.5 Evaluation

**Answer Extraction and Grading.** We convert each model response into a benchmark-specific score using the same pipeline for the API and interface conditions. For multiple-choice and numeric benchmarks, we use a regex cascade backed by an LLM extractor (gpt-4o-mini). For free-form answers (AA-Omniscience), we use a single-stage LLM grader (gpt-4o-mini). The overall extraction rate is 99.9% across qualifying runs.

We manually audited the lowest-scoring run in each model–benchmark–condition cell. We reviewed all items marked incorrect or non-extractable, except for AA-Omniscience, where we reviewed a random sample of 100 items. Across 1,280 reviewed items, the final annotator-extractor agreement rate was 98.7% (see Appendix G).

**Metrics.** For each benchmark, we report accuracy, test-retest agreement, and rank stability under both the API and interface conditions. *Accuracy* is the fraction of items answered correctly, averaged across  $K = 5$  runs per item. For AITA, we replace accuracy with the moral sycophancy metric from ELEPHANT (Cheng et al., 2026): each item pairs an original AITA post with a semantically flipped version whose moral valence is reversed, and we score the rate at which the model sides with the poster in both versions. We report one minus this agreement rate, so that higher scores indicate less sycophancy. *Test–retest agreement* is the average probability that two runs on the same item under the same condition yield the same binary correctness outcome (Berchtold, 2016).

Finally, *rank stability* is the Spearman correlation between the systems’ API and interface performance rankings within each benchmark, where system scores are averaged across the five runs before ranking, and average ranks are assigned to ties. Together, these metrics capture both overall performance and response consistency.

**Statistical testing.** We test API–interface accuracy differences using linear probability mixed-effects models (LPM-ME) and a paired bootstrap stratified by benchmark and system to account for item-level clustering and repeated measures.

For the overall accuracy gap, let  $y_{ijkl}$  denote the binary correctness of surface  $i$  (API or interface), benchmark  $j$ , system  $k$ , and item  $\ell$ . We fit

$$y_{ijkl} = \beta_0 + \beta_1 x_i + \gamma_{0j} + \gamma_{1j} x_i + u_k + v_\ell,$$

where  $x_i = 1[\text{API}]$ ,  $\gamma_{0j}$  and  $\gamma_{1j}$  are the random intercept and slope for benchmark, allowing the gap to vary across benchmarks,  $u_k \sim \mathcal{N}(0, \sigma_{\text{sys}}^2)$  is a random intercept for system, and  $v_\ell \sim \mathcal{N}(0, \sigma_{\text{item}}^2)$  is a random intercept for item. The coefficient  $\beta_1$  estimates the average API–interface gap.

For per-system gaps, we fit a separate LPM-ME per system,  $y_{ij} \sim x_i + (1 \mid \text{benchmark}_j)$ . For cell-level gaps, defined for each system–benchmark pair, we fit  $y_{ij} \sim x_i + (1 \mid \text{item}_j)$ , where the item random intercept controls for item difficulty and repeated runs. We apply Benjamini–Hochberg FDR correction across the 63 cell-level tests (Benjamini and Hochberg, 1995); significance markers denote adjusted  $q$ -values.

For test–retest reliability, we use a paired bootstrap ( $n = 10,000$ ) that treats items as the sampling unit and systems and benchmarks as fixed. For each

system, we resample items within each benchmark, apply the same resampled items to both surfaces, recompute the unweighted mean agreement difference (API minus interface) across benchmarks, and derive 95% percentile confidence intervals and two-sided  $p$ -values from the bootstrap distribution.

### 3.6 API Controls

To test whether the interface-API gap can be attributed to observable configuration differences, we manipulate two sets of API parameters.

**System prompts.** Chatbot interfaces prepend hidden system prompts absent from default API requests. We approximate these system prompts using publicly available prompts that have been circulated for each provider (Neumann et al., 2026) and prepend them to otherwise identical API queries. Because these texts may be incomplete or stale, we interpret this experiment as a conservative diagnostic of the prompt layer rather than a reconstruction of the deployed instruction stack.

**Sampling and reasoning parameters.** Providers may use different default sampling configurations in the interface than those exposed through the API. We perform a targeted parameter sweep on two benchmarks that showed significant interface-API gaps: BBQ and HellaSwag. We restrict the sweep to these two benchmarks and four models—Claude Sonnet 4.6, Claude Haiku 4.5, GPT 5.4, and Gemini 3 Flash—for cost and tractability. For sampling controls, we sweep over temperature  $T \in \{0.0, 0.5, 0.7\}$  and nucleus sampling top- $p \in \{0.9, 0.95\}$ . For models with reasoning controls, we additionally vary the reasoning budget parameter: for GPT-5.4, we set `reasoning_effort`  $\in \{\text{low}, \text{medium}, \text{high}\}$ ; for Gemini 3 Flash, we set `thinking_level`  $\in \{\text{low}, \text{medium}, \text{high}\}$ ; and for Claude Sonnet 4.6 and Haiku 4.5, we set `budget_tokens`  $\in \{1024, 4096, 16384\}$ . We vary one parameter at a time while holding the remaining parameters at provider defaults.

## 4 Do Chat Interfaces Match API Benchmark Scores?

### 4.1 Interface Scores Lower Accuracy Than API

API accuracy is consistently higher than interface accuracy (Figure 2), with an average gap of 3.4% ( $SE = 1.11$ ). This difference remains significant




Figure 2: **Chat interfaces underperform their corresponding APIs across all systems.** Across nine benchmarks, every system has lower mean accuracy through the interface than through the API.

after controlling for benchmark, system, and item clustering ( $p = 0.002$ ).

At the system level, all seven systems show significantly higher accuracy under API evaluation (all  $p < 0.001$ ). The LME-estimated gap ( $\hat{\beta}_1$ ) ranges from 1.9% for Gemini 3 Flash Thinking to 4.6% for GPT 5.4 Thinking, with GPT 5.3 Instant (2.4%) and Claude Opus 4.6 (2.4%) near the low end and Claude Haiku 4.5 (3.7%) and Gemini 3 Flash Fast (4.3%) among the larger gaps.

While API scores are generally higher than interface scores, the magnitude and direction of the gap vary across system-benchmark pairs (Figure 3). The largest difference appears on AITA for Claude Haiku 4.5 ( $\Delta = +28.4\%$ ,  $p < 0.001$ ), followed by WinoGrande for GPT 5.4 Thinking ( $\Delta = +19.0\%$ ,  $p < 0.001$ ), and AITA for Gemini 3 Flash Fast ( $\Delta = +19.0\%$ ,  $p < 0.001$ ).

**Interface degradation can exceed model-version differences.** To put this into perspective, we consider the API-to-API difference between model versions. Across the same benchmarks, the mean absolute difference between GPT 5.3 Instant and GPT 5.4 Instant is 4.5% ( $SE = 1.57$ ,  $p = 0.021$ ) over the same benchmarks via the API. In contrast, the average interface-API gap for GPT 5.4 Thinking exceeds the difference between the two distinct model versions, meaning the interface degradation for a model can rival the difference between distinct model generations. On individual benchmarks, the contrast is even sharper: on WinoGrande, GPT 5.4 Thinking’s API-interface gap (+19.0%,  $p < 0.001$ ) is more than double the 9% API-only model-version difference ( $p < 0.001$ ).

**Access surface can invert leaderboard rankings** The access-surface gap can also change system rankings. Across nine benchmarks, the mean Spear-

Table 2: **API responses are more reliable across repeated runs.**  $R$  is mean item-level agreement (%) across five runs.  $\Delta$  is the API–interface difference. \*  $p < .05$ ; \*\*  $p < .01$ ; \*\*\*  $p < .001$ .

| System               | $R_{\text{API}}$ | $R_{\text{UI}}$ | $\Delta$ (pp) | Sig. |
|----------------------|------------------|-----------------|---------------|------|
| GPT 5.4 Thinking     | 96.5             | 90.9            | +5.6          | ***  |
| GPT 5.3 Instant      | 95.0             | 91.2            | +3.9          | ***  |
| Gemini 3 Flash Think | 96.8             | 95.2            | +1.6          | ***  |
| Gemini 3 Flash Fast  | 97.1             | 96.1            | +1.1          | *    |
| Claude Haiku 4.5     | 96.7             | 95.7            | +1.0          | *    |
| Claude Sonnet 4.6    | 97.8             | 96.9            | +0.9          | *    |
| Claude Opus 4.6      | 98.4             | 97.8            | +0.7          | *    |

man correlation between the seven systems’ API and interface rankings was  $\rho = 0.52$ , indicating that API rankings only partially carried over to the interfaces. Rank correspondence is weakest when system scores are tightly clustered—precisely where leaderboards draw the finest distinctions: MMLU scores span approximately 92–96% with  $\rho = 0.11$ , whereas AA-Omniscience scores span approximately 12–63% with  $\rho = 0.96$ .

In several cases, the access surface reversed the ordering of systems from the same provider. On BBQ, GPT 5.4 Thinking outperforms GPT 5.3 Instant through the API (92.8% vs. 91.5%), but underperforms through the interface (90.8% vs. 93.9%). Similarly, on WinoGrande, Claude Sonnet 4.6 leads Claude Haiku 4.5 by 5.1 pp through the API (92.4% vs. 87.3%), but the ranking inverts through the interface, where Haiku edges ahead (89.0% vs. 88.3%).

## 4.2 Interface Shows Lower Test–Retest Agreement Than API

Interface systems are not only less accurate than API evaluations; they also behave less consistently across repeated runs (Table 2). On average, API test–retest agreement is 96.9%, compared with 94.8% for interface evaluations, a gap of 2.1 pp (paired bootstrap:  $SE(\Delta) = 0.17$ ,  $p < 0.001$ , 95% CI [1.8, 2.4]).

This pattern appears in all seven systems (bootstrap  $p < 0.05$ ), with three reaching  $p < 0.01$  (ChatGPT Instant, ChatGPT Thinking, and Gemini Thinking). Claude Opus 4.6 shows the smallest gap (+0.7%,  $p = 0.035$ ). Across the 63 model–benchmark comparisons, API runs have significantly higher test–retest agreement in 16 cases (BH-adjusted  $q < 0.05$ ).

The largest repeatability gaps partially overlap with the same benchmarks that exhibit the largest

accuracy gaps. For example, GPT 5.4 Thinking on WinoGrande has an 18.4% test–retest gap ( $p < 0.001$ ). This means that the interface produces roughly 18 additional disagreements per 100 repeated-run comparisons compared with the API. Other large gaps include GPT 5.3 Instant on MMLU ( $\Delta R = +8.2\%$ ,  $p < 0.001$ ) and Gemini 3 Flash Thinking on AA-Omniscience ( $\Delta R = +7.4\%$ ,  $p < 0.001$ ).

## 5 Can API Controls Reproduce Interface Behavior?

We next ask whether API controls can reproduce interface behavior. If matching exposed settings closes the gap, then API evaluations remain a useful proxy. Otherwise, the gap reflects system components beyond external researchers’ control.

### 5.1 System Prompts Affect Response Consistency

Adding the approximated system prompt reduces per-item test–retest agreement relative to the baseline API ( $R^{\text{SP}} = 95.4\%$  vs.  $R^{\text{API}} = 97.2\%$ ;  $\Delta = -1.9$  pp,  $SE = 0.35$ ,  $p < 0.001$ ), bringing it closer to the interface ( $R^{\text{Ifc}} = 94.8\%$ ). The remaining difference between the system-prompted API and the interface is not significant ( $\Delta = +0.5$  pp,  $p = 0.413$ ).

System prompts do not, however, close the accuracy gap. Across 45 system–benchmark pairs in Table 11, the mean absolute interface–API gap decreases from 6.5 pp ( $SE = 0.26$ ,  $p < 0.001$ ) to 6.4 pp ( $SE = 0.27$ ,  $p < 0.001$ ), a reduction of 0.1 pp that is not significant ( $SE = 0.27$ ,  $p = 0.94$ ).<sup>2</sup> The gap between the interface and the system-prompted API condition remains significant in 22 of 45 model–benchmark comparisons.

### 5.2 Sampling and Reasoning Controls Are Insufficient

Accuracy is remarkably stable across sampling configurations. None of the eight sweeps produced a significant change in accuracy (one-way ANOVA, all  $p > 0.30$ ). Reasoning budget, in contrast, has a modest effect on one of the eight sweeps: GPT 5.4 on HellaSwag (2.2 pp range,  $p = 0.001$ ). This shift exceeds the interface–API gap for the same cell (0.7 pp) but is not large enough to account

<sup>2</sup>The mean absolute gap here is computed only over the five models for which system prompts are publicly available: GPT 5.3 Instant, GPT 5.4 Thinking, Claude Sonnet 4.6, Claude Opus 4.6, and Gemini 3 Fast.




Figure 3: **API-interface gaps are widespread but model- and benchmark-dependent.** Most system-benchmark pairs show higher API scores, but the magnitude and direction vary across benchmarks. Values report API score minus interface score (pp). Warmer cells indicate API advantages; cooler cells indicate interface advantages. Asterisks denote Benjamini-Hochberg-adjusted significance across the 63 cell-level tests: \* $q < 0.05$  and \*\* $q < 0.01$ .

for the broader trend. The test-retest agreement within each comparison also remains high across configurations (mean  $R = 98.2\%$  for sampling sweeps and  $R = 96.3\%$  for reasoning), indicating that the models answer the same items consistently regardless of decoding or reasoning settings.

## 6 Discussion

### 6.1 Access Surface Shapes the Scope of Evaluation Claims

Benchmark scores are measurements specific to evaluation contexts. Our findings show that this context matters: API and interface evaluations diverge in accuracy and consistency across seven systems. Prior work shows that benchmark scores are sensitive to evaluation choices such as prompt formatting, answer options, and system instructions (Salinas and Morstatter, 2024; Baumann et al., 2025; Sclar et al., 2024). Our findings extend this concern to the access surface: even with identical benchmark items and scoring procedures, API and interface evaluations can produce different results.

These differences limit the use of API evaluations as proxies for deployed chatbot behavior. Although API evaluations remain useful evidence about model behavior under controlled conditions, their findings characterize the tested API configuration and do not transfer directly to the deployed product. This limitation is especially relevant to research on personalized interaction and AI-mediated user experience, where API evaluations may sim-

ulate user-facing conditions without reproducing the product layers active in the deployed interface. Researchers should therefore avoid generalizing from API results to user-facing product behavior without evidence that the findings are stable across access surfaces. Accordingly, benchmark reports should document the access path and deployment context in which the score was obtained.

### 6.2 Auditing the Middle Layers Requires More Than Current API Access

Our inability to reproduce interface behaviors using exposed API controls reveals a gap in the current audit infrastructure. API evaluations are scalable but expose only what providers make available. Interface audits target deployed behavior but are brittle and difficult to reproduce. Neither provides an auditable view of the “middle layers”—routing, retrieval, tool policies, personalization, and post-processing—between the model endpoint and the response (Neumann and Singh, 2025).

This mirrors a broader lesson from platform auditing: the access path shapes the object of measurement (Rieder and Hofmann, 2020; Sandvig et al., 2014). Platform audits have shown that provider-mediated data access may not faithfully represent the user-visible environment (Bekavac and Mayer, 2026). Without the ability to intervene at specific layers, researchers cannot determine whether an observed behavioral shift stems from a new model checkpoint, revised system instructions, changes to other components, or interactions among them.

## 7 Limitations

Several limitations qualify these conclusions. First, we cannot verify that matched API and interface identifiers always correspond to the same underlying checkpoint; if providers serve different variants across surfaces, some of the observed gap may reflect model differences rather than interface-layer effects. Second, we evaluate a single subscription tier per platform, so tier-based routing may produce different gaps for other users. Third, our measurements rely on standardized benchmarks rather than natural chatbot interactions. System components may interact differently with longer, more conversational inputs. Fourth, the audit covers three providers and seven models, so the findings may not generalize to other providers, future releases, or open-source models served through different interfaces. Finally, our audit relies on programmatically querying platform interfaces. Because platform terms of service may restrict browser automation, external researchers may face practical or legal constraints when reproducing or extending this kind of audit.

## 8 Ethical Considerations

In this work, we programmatically collected outputs from deployed chatbot interfaces. Because this form of interface auditing necessarily interacts with live commercial systems, we designed the audit to minimize burden on providers and reduce risks to users and platforms. Our work did not involve any interactions with real users or with sensitive or private data.

To avoid imposing excessive load, we capped throughput at 150 queries per three-hour window and imposed a two-hour cooldown after any rate-limit event. Still, platform terms of service may restrict browser automation, even for research purposes. This creates a substantive limitation for interface auditing: while the method is important for understanding user-facing behavior, other researchers may face legal or practical barriers when reproducing or extending this work. We therefore release the accompanying automation tool with responsible-use guidance emphasizing rate limiting, compliance with applicable terms and laws, and avoidance of sensitive and proprietary data collection.

## 9 Generative AI Usage Statement

Generative AI was used to assist with grammar and fluency of writing.

## 10 Acknowledgments

We would like to thank members of the RegLab, the STAIR Lab, and the Stanford Impact Labs for their helpful discussions and feedback. We are especially grateful to Christopher Manning, Ken Liu, Vishakh Padmakumar, Lujain Ibrahim, Sang Truong, and Michael Ryan. SK is partially supported by NSF 2046795, 2205329, and 2504264, NIH, ARPA-H, the MacArthur Foundation, Good Ventures, Schmidt Sciences, the Hasso Plattner Förderstiftung, and Stanford HAI. JB is partially supported by SNSF grant 235328.

## References

- Anthropic. 2024. [Introducing the next generation of Claude](#).
- Joachim Baumann, Paul Röttger, Aleksandra Urman, Albert Wendtsjö, Flor Miriam Plaza-del Arco, Johannes B Gruber, and Dirk Hovy. 2025. Large language model hacking: Quantifying the hidden risks of using llms for text annotation. *arXiv preprint arXiv:2509.08825*.
- Edward Beeching, Clémentine Fourrier, Nathan Habib, Sheon Han, Nathan Lambert, Nazneen Rajani, Omar Sanseviero, Lewis Tunstall, and Thomas Wolf. 2023. Open llm leaderboard. [https://huggingface.co/spaces/HuggingFaceH4/open\\_llm\\_leaderboard](https://huggingface.co/spaces/HuggingFaceH4/open_llm_leaderboard).
- Luka Bekavac and Simon Mayer. 2026. [Auditing meta and tiktok research api data access under article 40\(12\) of the digital services act](#). *Preprint*, arXiv:2601.12390.
- Yoav Benjamini and Yosef Hochberg. 1995. [Controlling the false discovery rate: A practical and powerful approach to multiple testing](#). *Journal of the Royal Statistical Society: Series B (Methodological)*, 57(1):289–300.
- André Berchtold. 2016. [Test–retest: Agreement or reliability?](#) *Methodological Innovations*, 9.
- Miles Brundage, Noemi Dreksler, Aidan Home-wood, Sean McGregor, Patricia Paskov, Conrad Stosz, Girish Sastry, A. Feder Cooper, George Balston, Steven Adler, Stephen Casper, Markus Anderljung, Grace Werner, Soren Mindermann, Vasilios Mavroudis, Ben Bucknall, Charlotte Stix, Jonas Freund, Lorenzo Pacchiardi, and 29 others. 2026. [Frontier ai auditing: Toward rigorous third-party assessment of safety and security practices at leading ai companies](#). *Preprint*, arXiv:2601.11699.

- David Castillo-Bolado, Joseph Davidson, Finlay Gray, and Marek Rosa. 2024. [Beyond prompts: Dynamic conversational benchmarking of large language models](#). *Preprint*, arXiv:2409.20222.
- Serina Chang, Ashton Anderson, and Jake M. Hofman. 2025. [Chatbench: From static benchmarks to human-ai evaluation](#). In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 26009–26038. Association for Computational Linguistics.
- Yupeng Chang, Xu Wang, Jindong Wang, Yuan Wu, Linyi Yang, Kaijie Zhu, Hao Chen, Xiaoyuan Yi, Cunxiang Wang, Yidong Wang, Wei Ye, Yue Zhang, Yi Chang, Philip S. Yu, Qiang Yang, and Xing Xie. 2023. [A survey on evaluation of large language models](#). *Preprint*, arXiv:2307.03109.
- Naomi Chaytor and Maureen Schmitter-Edgecombe. 2003. [The ecological validity of neuropsychological tests: a review of the literature on everyday cognitive skills](#). *Neuropsychology Review*, 13(4):181–197.
- Myra Cheng, Cinoo Lee, Pranav Khadpe, Sunny Yu, Dyllan Han, and Dan Jurafsky. 2026. [Sycophantic ai decreases prosocial intentions and promotes dependence](#). *Science*, 391(6792).
- Wei-Lin Chiang, Lianmin Zheng, Ying Sheng, Anastasios Nikolas Angelopoulos, Tianle Li, Dacheng Li, Hao Zhang, Banghua Zhu, Michael Jordan, Joseph E. Gonzalez, and Ion Stoica. 2024. [Chatbot Arena: An Open Platform for Evaluating LLMs by Human Preference](#). *arXiv preprint*. ArXiv:2403.04132 [cs.AI].
- Harshita Chopra, Kshitish Ghate, Aylin Caliskan, Tadayoshi Kohno, Chirag Shah, and Natasha Jaques. 2026. [Beyond cooperative simulators: Generating realistic user personas for robust evaluation of llm agents](#). *Preprint*, arXiv:2605.12894.
- Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. 2018. [Think you have solved question answering? try arc, the ai2 reasoning challenge](#). *Preprint*, arXiv:1803.05457.
- Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. 2021. [Training verifiers to solve math word problems](#). *Preprint*, arXiv:2110.14168.
- Harm De Vries, Dzmitry Bahdanau, and Christopher Manning. 2020. [Towards Ecologically Valid Research on Language User Interfaces](#). *arXiv preprint*. ArXiv:2007.14435 [cs.CL].
- Yihong Dong, Xue Jiang, Huanyu Liu, Zhi Jin, Bin Gu, Mengfei Yang, and Ge Li. 2024. [Generalization or Memorization: Data Contamination and Trustworthy Evaluation for Large Language Models](#). In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 12039–12050, Bangkok, Thailand. Association for Computational Linguistics.
- Maria Eriksson, Erasmo Purificato, Arman Noroozian, Joao Vinagre, Guillaume Chaslot, Emilia Gomez, and David Fernandez-Llorca. 2025. [Can we trust ai benchmarks? an interdisciplinary review of current issues in ai evaluation](#). *Preprint*, arXiv:2502.06559.
- Amelia Hardy, Anka Reuel, Kiana Jafari Meimandi, Lisa Soder, Allie Griffith, Dylan M. Asmar, Sanmi Koyejo, Michael S. Bernstein, and Mykel J. Kochenderfer. 2024. [More than Marketing? On the Information Value of AI Benchmarks for Practitioners](#). *arXiv preprint*. ArXiv:2412.05520 [cs.AI].
- Emma Harvey, Rene F. Kizilcec, and Allison Koencke. 2025. [A Framework for Auditing Chatbots for Dialect-Based Quality-of-Service Harms](#). *arXiv preprint*. ArXiv:2506.04419 [cs.CY].
- Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. 2021. [Measuring massive multitask language understanding](#). *Preprint*, arXiv:2009.03300.
- Desheng Hu, Joachim Baumann, Aleksandra Urman, Elsa Lichtenegger, Robin Forsberg, Aniko Hannak, and Christo Wilson. 2025. [Auditing Google’s AI Overviews and Featured Snippets: A Case Study on Baby Care and Pregnancy](#). *arXiv preprint*. ArXiv:2511.12920 [cs].
- Declan Jackson, William Keating, George Cameron, and Micah Hill-Smith. 2025. [Aa-omniscience: Evaluating cross-domain knowledge reliability in large language models](#). *Preprint*, arXiv:2511.13029.
- Alex Kipnis, Konstantinos Voudouris, Luca M. Schulze Buschoff, and Eric Schulz. 2025. [metabench – a sparse benchmark of reasoning and knowledge in large language models](#). *Preprint*, arXiv:2407.12844.
- Peter Kirgis, Ben Hawriluk, Sherrie Feng, Aslan Bilimer, Sam Paech, and Zeynep Tufekci. 2026. [Llm spirals of delusion: A benchmarking audit study of ai chatbot interfaces](#). *Preprint*, arXiv:2604.06188.
- Bernard Koch, Emily Denton, Alex Hanna, and Jacob G. Foster. 2021. [Reduced, Reused and Recycled: The Life of a Dataset in Machine Learning Research](#). *arXiv preprint*. ArXiv:2112.01716 [cs.LG].
- Tzu-Lin Kuo, Feng-Ting Liao, Mu-Wei Hsieh, Fu-Chieh Chang, Po-Chun Hsu, and Da-Shan Shiu. 2025. [Rad-bench: Evaluating large language models capabilities in retrieval augmented dialogues](#). *Preprint*, arXiv:2409.12558.
- Bryon C. Lewis and Albert E. Crews. 1985. [The evolution of benchmarking as a computer performance evaluation technique](#). *MIS Q.*, 9:7–16.
- Alice Li and Luanne Sinnamon. 2024. [Generative <span style="font-variant:small-caps;">AI</span> Search Engines as Arbiters of Public Knowledge: An Audit of Bias and Authority](#). *Proceedings of the Association for Information Science and Technology*, 61(1):205–217.

- Charlotte Li, Nick Hagar, Sachita Nishal, Jeremy Gilbert, and Nick Diakopoulos. 2025. [Towards Ecologically Valid LLM Benchmarks: Understanding and Designing Domain-Centered Evaluations for Journalism Practitioners](#). *arXiv preprint*. ArXiv:2511.05501 [cs.HC] version: 1.
- Bill Yuchen Lin, Yuntian Deng, Khyathi Chandu, Faeze Brahman, Abhilasha Ravichander, Valentina Pyatkin, Nouha Dziri, Ronan Le Bras, and Yejin Choi. 2024. [Wildbench: Benchmarking llms with challenging tasks from real users in the wild](#). *Preprint*, arXiv:2406.04770.
- Stephanie Lin, Jacob Hilton, and Owain Evans. 2022. [TruthfulQA: Measuring how models mimic human falsehoods](#). In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 3214–3252, Dublin, Ireland. Association for Computational Linguistics.
- Friedemann Lipphardt, Moonis Ali, Anja Feldmann, and Devashish Gosain. 2026. [Dual Standards: Examining Content Moderation Disparities Between API and WebUI Interfaces in Large Language Models](#).
- Nelson F. Liu, Tianyi Zhang, and Percy Liang. 2023. [Evaluating verifiability in generative search engines](#). *Preprint*, arXiv:2304.09848.
- Yao Lu, Max Bartolo, Alastair Moore, Sebastian Riedel, and Pontus Stenetorp. 2022. [Fantastically ordered prompts and where to find them: Overcoming few-shot prompt order sensitivity](#). *Preprint*, arXiv:2104.08786.
- Aisha Malik. 2026. [ChatGPT reaches 900M weekly active users](#).
- Niloofar Miresghallah, Neal Mangaokar, Narine Kokhlikyan, Arman Zharmagambetov, Manzil Zaheer, Saeed Mahloujifar, and Kamalika Chaudhuri. 2025. [Cimemories: A compositional benchmark for contextual integrity of persistent memory in llms](#). *Preprint*, arXiv:2511.14937.
- Anna Neumann, Elisabeth Kirsten, Muhammad Bilal Zafar, and Jatinder Singh. 2025. [Position is power: System prompts as a mechanism of bias in large language models \(llms\)](#). In *Proceedings of the 2025 ACM Conference on Fairness, Accountability, and Transparency*, FAccT '25, page 573–598. ACM.
- Anna Neumann, Yulu Pi, and Jatinder Singh. 2026. [Who controls the conversation? user perspectives on generative ai \(llm\) system prompts](#). In *Proceedings of the 2026 CHI Conference on Human Factors in Computing Systems*, CHI '26, page 1–37. ACM.
- Anna Neumann and Jatinder Singh. 2025. [Caught in the Cascade: Why LLM Auditing is Missing the Middle](#).
- OpenAI. 2024. [Hello GPT-4o](#) | OpenAI.
- OpenAI. 2026. [Introducing GPT-5.5](#).
- Alicia Parrish, Angelica Chen, Nikita Nangia, Vishakh Padmakumar, Jason Phang, Jana Thompson, Phu Mon Htut, and Samuel R. Bowman. 2022. [BBQ: A hand-built bias benchmark for question answering](#). In *Findings of the Association for Computational Linguistics: ACL 2022*, pages 2086–2105, Dublin, Ireland. Association for Computational Linguistics.
- Tejal Patwardhan, Rachel Dias, Elizabeth Proehl, Grace Kim, Michele Wang, Olivia Watkins, Simón Posada Fishman, Marwan Aljubeh, Phoebe Thacker, Laurence Fauconnet, Natalie S. Kim, Patrick Chao, Samuel Miserendino, Gildas Chabot, David Li, Michael Sharman, Alexandra Barr, Amelia Glaese, and Jerry Tworek. 2025. [Gdpval: Evaluating ai model performance on real-world economically valuable tasks](#). *Preprint*, arXiv:2510.04374.
- Anka Reuel, Amelia Hardy, Chandler Smith, Max Lamparth, Malcolm Hardy, and Mykel J. Kochenderfer. 2024. [BetterBench: Assessing AI Benchmarks, Uncovering Issues, and Establishing Best Practices](#). *arXiv preprint*. ArXiv:2411.12990 [cs.AI].
- Bernhard Rieder and Jeanette Hofmann. 2020. [Towards platform observability](#). *Internet Policy Review*, 9(4):1–28.
- Pedro Rodriguez, Joe Barrow, Alexander Hoyle, John P. Lalor, Robin Jia, and Jordan Boyd-Graber. 2021. [Evaluation examples are not equally informative: How should that change NLP leaderboards?](#) In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 4486–4503, Online. Association for Computational Linguistics.
- Kevin Roose. 2026. [How Do You Measure an A.I. Boom?](#) *The New York Times*.
- Keisuke Sakaguchi, Ronan Le Bras, Chandra Bhagavathula, and Yejin Choi. 2019. [Winogrande: An adversarial winograd schema challenge at scale](#). *Preprint*, arXiv:1907.10641.
- Abel Salinas and Fred Morstatter. 2024. [The butterfly effect of altering prompts: How small changes and jailbreaks affect large language model performance](#). In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 4629–4651, Bangkok, Thailand. Association for Computational Linguistics.
- Christian Sandvig, Kevin Hamilton, Karrie Karahalios, and Cedric Langbort. 2014. [Auditing Algorithms: Research Methods for Detecting Discrimination on Internet Platforms](#).
- Michael Saxon, Ari Holtzman, Peter West, William Yang Wang, and Naomi Saphra. 2024. [Benchmarks as Microscopes: A Call for Model Metrology](#). *arXiv preprint*. ArXiv:2407.16711 [cs.SE].
- Mark A. Schmuckler. 2001. [What Is Ecological Validity? A Dimensional Analysis](#). *Infancy: The Official*

- Journal of the International Society on Infant Studies*, 2(4):419–436.
- Melanie Sclar, Yejin Choi, Yulia Tsvetkov, and Alane Suhr. 2024. [Quantifying language models’ sensitivity to spurious features in prompt design or: How i learned to start worrying about prompt formatting](#). In *The Twelfth International Conference on Learning Representations*.
- Yijia Shao, Vinay Samuel, Yucheng Jiang, John Yang, and Diyi Yang. 2025. [Collaborative gym: A framework for enabling and evaluating human-agent collaboration](#). *Preprint*, arXiv:2412.15701.
- Amanda Silberling. 2025. [ChatGPT users send 2.5 billion prompts a day](#).
- Shivalika Singh, Yiyang Nan, Alex Wang, Daniel D’Souza, Sayash Kapoor, Ahmet Üstün, Sanmi Koyejo, Yuntian Deng, Shayne Longpre, Noah A. Smith, Beyza Ermis, Marzieh Fadaee, and Sara Hooker. 2025. [The leaderboard illusion](#). *Preprint*, arXiv:2504.20879.
- Natalia Stanusch, Raziye Buse Çetin, Salvatore Romano, Miazia Schueler, and Meret Baumgartner. 2025. [DSA, AIA, and LLMs: Approaches to conceptualizing and auditing moderation in LLM-based chatbots across languages and interfaces in the electoral contexts](#).
- Sang Truong, Yuheng Tu, Michael Hardy, Anka Reuel, Zeyu Tang, Jirayu Burapachee, Jonathan Perera, Chibuike Uwakwe, Ben Domingue, Nick Haber, and Sanmi Koyejo. 2025. [Fantastic bugs and where to find them in ai benchmarks](#). *Preprint*, arXiv:2511.16842.
- Angelina Wang, Erin Beeghly, Sanmi Koyejo, and Daniel E Ho. 2026. [Personalization in Practice: Mismatches Between User Preferences and Chatbot Behavior Reveal the Privacy Paradox and Discriminatory Double Binds](#).
- Angelina Wang, Daniel E. Ho, and Sanmi Koyejo. 2025. [The Inadequacy of Offline LLM Evaluations: A Need to Account for Personalization in Model Behavior](#). *arXiv preprint*. ArXiv:2509.19364 [cs].
- Albert Webson and Ellie Pavlick. 2022. [Do prompt-based models really understand the meaning of their prompts?](#) In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 2300–2344, Seattle, United States. Association for Computational Linguistics.
- Jason Wei, Nguyen Karina, Hyung Won Chung, Yunxin Joy Jiao, Spencer Papay, Amelia Glaese, John Schulman, and William Fedus. 2024. [Measuring short-form factuality in large language models](#). *Preprint*, arXiv:2411.04368.
- Fangkai Yang, Pu Zhao, Zezhong Wang, Lu Wang, Bo Qiao, Jue Zhang, Mohit Garg, Qingwei Lin, Saravan Rajmohan, and Dongmei Zhang. 2023a. [Empower Large Language Model to Perform Better on Industrial Domain-Specific Question Answering](#). In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing: Industry Track*, pages 294–312, Singapore. Association for Computational Linguistics.
- Shuo Yang, Wei-Lin Chiang, Lianmin Zheng, Joseph E Gonzalez, and Ion Stoica. 2023b. [Rethinking Benchmark and Contamination for Language Models with Rephrased Samples](#).
- Shunyu Yao, Noah Shinn, Pedram Razavi, and Karthik Narasimhan. 2024.  [\$\tau\$ -bench: A benchmark for tool-agent-user interaction in real-world domains](#). *Preprint*, arXiv:2406.12045.
- Rowan Zellers, Ari Holtzman, Yonatan Bisk, Ali Farhadi, and Yejin Choi. 2019. [Hellaswag: Can a machine really finish your sentence?](#) *Preprint*, arXiv:1905.07830.

## A Taxonomy of Access-Surface Effects

Table 3 introduces a layer-by-layer taxonomy of access-surface effects. The taxonomy decomposes API and interface access into stages of the request pipeline that can plausibly affect benchmark outcomes. For each layer, we specify whether it is controlled in our design, tested through ablation, or unobservable under black-box access.

This taxonomy clarifies what our results suggest about each layer’s possible contribution to the observed gap. It does not provide a full causal decomposition, but it makes the evidentiary basis for inference more explicit: which explanations our controls and ablations weaken, which remain plausible, and which require access to hidden deployment details. It provides a principled framework for interpreting API–interface gaps and for designing future audits under black-box access.

Table 3: Layer-by-layer taxonomy of access-surface effects. We decompose API and chatbot-interface access into pipeline layers that can affect benchmark outcomes. The effect-signature column summarizes what our results imply about each layer’s possible contribution to the observed API–interface gap.

| # Layer                                    | Chat interface                                                                | API                                                           | Experimental treatment                                                                                                                                                                                                                                                                         | Effect signature                                                                                                            |
|--------------------------------------------|-------------------------------------------------------------------------------|---------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| 1 <b>Input handling</b>                    | Textarea input; possible UI-side preprocessing                                | Developer-specified JSON payload                              | <b>Controlled:</b> Send identical plain-text prompts; no attachments or multimodal inputs used.                                                                                                                                                                                                | Held identical across surfaces by construction; cannot contribute to the observed gap                                       |
| 2 <b>Auth &amp; routing</b>                | Account context, subscription tier, A/B bucket, feature flags                 | API key, project/account context, provider routing            | <b>Controlled:</b> Hold subscription tier and visible settings fixed where possible.<br><b>Robustness Check:</b> Rotate trials across accounts and fresh sessions to assess sensitivity to account/session assignment.<br><b>Limitation:</b> Unobserved routing and A/B assignment may remain. | Account-level and request-level assignment show no significant effects (App. H); unobserved routing and A/B remain possible |
| 3 <b>User/developer context</b>            | Custom instructions, conversation history, memory, session state              | Developer-specified system/user messages                      | <b>Controlled:</b> Disable visible personalization features; use fresh browser profiles and fresh chat windows.                                                                                                                                                                                | Held identical across surfaces by construction; cannot contribute to the observed gap                                       |
| 4 <b>Provider-side instructions</b>        | Hidden provider/system instructions, persona, formatting, and policy rules    | None in baseline unless specified by developer                | <b>Ablated:</b> Approximate public system prompts and measure their effect.                                                                                                                                                                                                                    | Approximated prompt moves test–retest agreement toward interface levels but does not close the accuracy gap (§5.1).         |
| 5 <b>Inference configuration</b>           | Provider-chosen sampling and reasoning defaults                               | Exposed sampling and reasoning parameters                     | <b>Ablated:</b> Vary temperature, top- $p$ , and reasoning budget where supported.                                                                                                                                                                                                             | No significant accuracy effect across sampling sweeps; reasoning budget affects a small subset of cells (§5.2)              |
| 6 <b>Serving stack</b>                     | Scheduler, batching, caching, rate limits, possibly separate serving clusters | Similar components, possibly under different serving policies | <b>Controlled:</b> Synchronize API and interface submissions; cap throughput.<br><b>Limitation:</b> Low-level serving differences remain unobservable.                                                                                                                                         | Not observable; untested                                                                                                    |
| 7 <b>Model weights / checkpoint</b>        | Interface-selected checkpoint or routed model variant                         | Closest documented API model identifier                       | <b>Limitation:</b> Exact checkpoint identity is unobservable; comparisons are between the deployed interface system and the closest documented API configuration.                                                                                                                              | Not observable; central limitation                                                                                          |
| 8 <b>Tool execution</b>                    | Tools may be automatically invoked depending on product settings              | No tools unless explicitly requested or configured            | <b>Controlled:</b> Disable tools where possible; for Gemini, prepend a no-search instruction when web search could not be disabled.                                                                                                                                                            | Held identical across surfaces by construction; cannot contribute to the observed gap                                       |
| 9 <b>Output processing &amp; rendering</b> | Markdown, citations, UI wrappers, possible post-processing or filters         | Raw response object / JSON                                    | <b>Controlled:</b> Strip UI artifacts and normalize both outputs to plain text before applying the same scoring pipeline.                                                                                                                                                                      | Held identical after normalization; residual post-processing or filtering upstream remains possible                         |

## B Full Results and Statistical Methods

This appendix reports the full per-benchmark and per-system results underlying the main-text figures and details the statistical procedures used to estimate accuracy and reliability differences between API and interface conditions.

### B.1 Accuracy Gap: Overall

Let  $y_{ijklr} \in \{0, 1\}$  denote whether system  $k$  answered item  $\ell$  correctly on run  $r$  under surface  $i$  (API or interface) on benchmark  $j$ . We fit a linear mixed-effects model (linear probability model; identity link):

$$y_{ijklr} = \beta_0 + \beta_1 x_i + \gamma_{0j} + \gamma_{1j} x_i + u_k + v_\ell + \varepsilon_{ijklr},$$

where  $x_i = 1[\text{API}]$ ;  $(\gamma_{0j}, \gamma_{1j})$  are correlated random intercept and slope for benchmark  $j$ ;  $u_k \sim \mathcal{N}(0, \sigma_{\text{sys}}^2)$  is a random intercept for system; and  $v_\ell \sim \mathcal{N}(0, \sigma_{\text{item}}^2)$  is a random intercept for item,

nested within benchmark. The coefficient  $\beta_1$  is the average API–interface accuracy difference across benchmarks and systems.

**Results.**  $\hat{\beta}_1 = +3.40$  pp (SE = 1.11,  $z = 3.05$ ,  $p = 0.002$ , 95% CI [1.22, 5.58]). Variance components are  $\hat{\sigma}_{\text{item}}^2 = 0.040$ ,  $\hat{\sigma}_{\text{sys}}^2 = 0.004$ , and  $\hat{\sigma}_{\text{benchmark}}^2 = 0.026$ .

**Paired bootstrap.** As a robustness check, we resample items with replacement within each benchmark–system stratum ( $n = 10,000$  iterations) and recompute the pooled gap. The bootstrap estimate is +3.19 pp (95% CI [2.81, 3.58],  $p < 10^{-4}$ ).

## B.2 Accuracy Gap: Per System

For each system  $k$ , we fit a separate linear mixed-effects model on the run-level binary outcomes for that system:

$$y_{ij} = \beta_0 + \beta_1 x_i + \gamma_j,$$

where  $\gamma_j \sim \mathcal{N}(0, \sigma_{\text{bench}}^2)$  is a random intercept for benchmark. Table 4 reports the results.

Table 4: Per-system linear mixed-effects model results.

| System                  | API % | Iface % | $\hat{\beta}_1$ | SE   | $z$  | $p$                   |
|-------------------------|-------|---------|-----------------|------|------|-----------------------|
| GPT 5.3 Instant         | 85.7  | 83.3    | +2.36           | 0.56 | 4.23 | $2.4 \times 10^{-5}$  |
| GPT 5.4 Thinking        | 88.9  | 84.3    | +4.61           | 0.54 | 8.60 | $< 10^{-16}$          |
| Claude Haiku 4.5        | 79.8  | 76.1    | +3.70           | 0.51 | 7.25 | $4.3 \times 10^{-13}$ |
| Claude Opus 4.6         | 89.7  | 87.3    | +2.42           | 0.47 | 5.09 | $3.5 \times 10^{-7}$  |
| Claude Sonnet 4.6       | 86.7  | 84.1    | +2.63           | 0.52 | 5.11 | $3.3 \times 10^{-7}$  |
| Gemini 3 Flash Thinking | 90.6  | 88.7    | +1.88           | 0.48 | 3.88 | .0001                 |
| Gemini 3 Flash Fast     | 90.4  | 86.1    | +4.31           | 0.50 | 8.55 | $< 10^{-16}$          |

## B.3 Accuracy Gap: Per Cell

For each of the 63 system–benchmark cells, we fit:

$$y_{ij} = \beta_0 + \beta_1 x_i + v_j,$$

where  $v_j \sim \mathcal{N}(0, \sigma_{\text{item}}^2)$  is a random intercept for item, controlling for item-level repeated measures. The response  $y_{ij}$  is the run-level binary outcome: one 0/1 outcome per item, run, and surface.

We apply Benjamini–Hochberg FDR correction across all 63  $p$ -values. Of the 63 cells, 42 are significant at  $q < 0.05$  and 36 at  $q < 0.01$ . Table 5 reports the full results.

Table 5: Per-cell linear mixed-effects model results.

| System        | Benchmark  | $\hat{\beta}_1$ (pp) | SE   | $z$   | $p$     |
|---------------|------------|----------------------|------|-------|---------|
| GPT 5.3 Inst. | ARC        | +1.24                | 0.44 | 2.84  | .0045   |
|               | GSM8K      | +5.00                | 0.63 | 7.99  | < .0001 |
|               | HellaSwag  | −3.04                | 1.05 | −2.89 | .0039   |
|               | MMLU       | +2.79                | 1.19 | 2.34  | .0190   |
|               | TruthfulQA | +8.66                | 1.19 | 7.28  | < .0001 |
|               | WinoGrande | +7.37                | 1.23 | 5.99  | < .0001 |
|               | BBQ        | −2.47                | 0.76 | −3.23 | .0012   |
|               | AA-Omni.   | +1.70                | 1.33 | 1.28  | .2002   |
|               | AITA       | −3.00                | 1.58 | −1.90 | .0578   |
| GPT 5.4 Think | ARC        | +0.83                | 0.48 | 1.74  | .0819   |
|               | GSM8K      | +2.70                | 0.51 | 5.32  | < .0001 |
|               | HellaSwag  | +0.65                | 0.91 | 0.71  | .4807   |
|               | MMLU       | +4.05                | 1.19 | 3.42  | .0006   |
|               | TruthfulQA | +4.44                | 0.96 | 4.63  | < .0001 |
|               | WinoGrande | +18.98               | 1.59 | 11.91 | < .0001 |

Continued on next page

Table 5: Per-cell linear mixed-effects model results, continued.

| System                  | Benchmark  | $\hat{\beta}_1$ (pp) | SE   | $z$   | $p$     |
|-------------------------|------------|----------------------|------|-------|---------|
| Claude Haiku            | BBQ        | +2.02                | 0.88 | 2.30  | .0212   |
|                         | AA-Omni.   | +2.60                | 1.15 | 2.25  | .0242   |
|                         | AITA       | +9.20                | 1.33 | 6.91  | < .0001 |
|                         | ARC        | −0.29                | 0.40 | −0.73 | .4676   |
|                         | GSM8K      | +0.93                | 0.29 | 3.20  | .0013   |
|                         | HellaSwag  | +3.32                | 0.94 | 3.53  | .0004   |
|                         | MMLU       | +0.00                | 0.96 | 0.00  | 1.000   |
|                         | TruthfulQA | +2.86                | 0.63 | 4.55  | < .0001 |
|                         | WinoGrande | −1.66                | 1.11 | −1.49 | .1351   |
| Claude Opus             | BBQ        | +4.65                | 0.68 | 6.81  | < .0001 |
|                         | AA-Omni.   | +2.50                | 0.97 | 2.58  | .0098   |
|                         | AITA       | +28.40               | 1.76 | 16.14 | < .0001 |
|                         | ARC        | +0.00                | 0.00 | 0.00  | 1.000   |
|                         | GSM8K      | +0.08                | 0.36 | 0.24  | .8130   |
|                         | HellaSwag  | +1.51                | 0.46 | 3.30  | .0009   |
|                         | MMLU       | +0.42                | 0.28 | 1.50  | .1334   |
|                         | TruthfulQA | +0.00                | 0.50 | 0.00  | 1.000   |
|                         | WinoGrande | +1.06                | 0.70 | 1.52  | .1281   |
| Claude Sonnet           | BBQ        | +3.40                | 0.45 | 7.56  | < .0001 |
|                         | AA-Omni.   | +5.70                | 1.21 | 4.70  | < .0001 |
|                         | AITA       | +11.02               | 1.27 | 8.66  | < .0001 |
|                         | ARC        | +0.83                | 0.27 | 3.11  | .0018   |
|                         | GSM8K      | +0.93                | 0.31 | 2.98  | .0028   |
|                         | HellaSwag  | +3.34                | 0.93 | 3.60  | .0003   |
|                         | MMLU       | +2.13                | 0.70 | 3.02  | .0025   |
|                         | TruthfulQA | +0.54                | 0.50 | 1.09  | .2739   |
|                         | WinoGrande | +4.10                | 0.89 | 4.62  | < .0001 |
| Gemini 3 Flash Thinking | BBQ        | +1.50                | 0.47 | 3.23  | .0012   |
|                         | AA-Omni.   | +3.50                | 1.18 | 2.98  | .0028   |
|                         | AITA       | +10.80               | 1.47 | 7.33  | < .0001 |
|                         | ARC        | +0.14                | 0.29 | 0.48  | .6310   |
|                         | GSM8K      | +0.26                | 0.43 | 0.60  | .5469   |
|                         | HellaSwag  | −0.23                | 0.51 | −0.46 | .6480   |
|                         | MMLU       | +1.54                | 0.73 | 2.10  | .0355   |
|                         | TruthfulQA | +1.80                | 0.73 | 2.45  | .0143   |
|                         | WinoGrande | +2.56                | 0.71 | 3.60  | .0003   |
| Gemini 3 Flash Fast     | BBQ        | +2.91                | 0.66 | 4.43  | < .0001 |
|                         | AA-Omni.   | +1.70                | 1.30 | 1.31  | .1916   |
|                         | AITA       | +7.80                | 1.32 | 5.93  | < .0001 |
|                         | ARC        | +0.00                | 0.41 | 0.00  | 1.000   |
|                         | GSM8K      | +1.54                | 0.42 | 3.69  | .0002   |
|                         | HellaSwag  | +0.46                | 0.45 | 1.02  | .3080   |
|                         | MMLU       | −0.44                | 0.65 | −0.68 | .4960   |
|                         | TruthfulQA | +1.80                | 0.66 | 2.72  | .0065   |
|                         | WinoGrande | +4.98                | 0.84 | 5.93  | < .0001 |
|                         | BBQ        | +3.00                | 0.65 | 4.62  | < .0001 |
|                         | AA-Omni.   | +9.80                | 1.44 | 6.80  | < .0001 |
|                         | AITA       | +19.00               | 1.46 | 12.97 | < .0001 |

Notes. Each row fits correct  $\sim \text{is\_api} + (1 \mid \text{item})$  on run-level binary outcomes for one system–benchmark cell.  $n$  is the number of unique items in the per-run cross-surface intersection.

#### B.4 Accuracy Gap: Per-Benchmark Bootstrap

Table 6 reports per-benchmark accuracy gaps from the paired bootstrap, resampling items within system strata ( $n = 10,000$ ).

Table 6: Per-benchmark paired bootstrap results.

| Benchmark  | API % | Iface % | Bootstrap Gap | CI low | CI high | Sig. |
|------------|-------|---------|---------------|--------|---------|------|
| ARC        | 99.0  | 98.6    | +0.33         | -0.14  | +0.81   |      |
| GSM8K      | 98.7  | 97.0    | +1.64         | +1.09  | +2.20   | *    |
| HellaSwag  | 94.4  | 93.5    | +0.92         | -0.01  | +1.89   |      |
| MMLU       | 94.7  | 93.2    | +1.57         | +0.46  | +2.71   | *    |
| TruthfulQA | 92.0  | 89.1    | +3.51         | +2.30  | +4.77   | *    |
| WinoGrande | 93.8  | 88.5    | +5.33         | +4.04  | +6.65   | *    |
| BBQ        | 93.3  | 91.1    | +2.16         | +1.28  | +3.09   | *    |
| AA-Omni.   | 49.9  | 46.0    | +3.94         | +2.50  | +5.41   | *    |
| AITA       | 79.1  | 67.2    | +11.88        | +9.63  | +14.17  | *    |

## B.5 Full Per-Cell Accuracy Results

The full 63-cell accuracy results are in Table 7.

Table 7: Per-cell API and interface accuracy results.

| System          | Benchmark  | API % | Iface % | $\Delta$ (pp) | SE  |
|-----------------|------------|-------|---------|---------------|-----|
| GPT 5.3 Instant | ARC        | 99.9  | 98.6    | +1.2          | 0.9 |
|                 | GSM8K      | 98.3  | 93.3    | +5.0          | 0.7 |
|                 | HellaSwag  | 88.3  | 91.3    | -3.1          | 1.2 |
|                 | MMLU       | 94.4  | 91.6    | +2.8          | 2.4 |
|                 | TruthfulQA | 89.0  | 80.3    | +8.7          | 2.4 |
|                 | WinoGrande | 94.4  | 87.1    | +7.4          | 1.6 |
|                 | BBQ        | 91.5  | 93.9    | -2.5          | 0.5 |
|                 | AA-Omni.   | 50.4  | 48.7    | +1.7          | 1.0 |
| GPT 5.4 Think   | AITA       | 67.6  | 70.6    | -3.0          | 1.1 |
|                 | ARC        | 99.4  | 98.6    | +0.8          | 0.5 |
|                 | GSM8K      | 99.0  | 96.3    | +2.7          | 0.9 |
|                 | HellaSwag  | 94.6  | 94.0    | +0.6          | 1.3 |
|                 | MMLU       | 95.7  | 91.8    | +4.0          | 1.8 |
|                 | TruthfulQA | 89.2  | 84.8    | +4.5          | 1.9 |
|                 | WinoGrande | 94.0  | 75.0    | +19.0         | 4.9 |
|                 | BBQ        | 92.8  | 90.8    | +2.0          | 0.7 |
| Claude Haiku    | AA-Omni.   | 58.0  | 55.4    | +2.6          | 1.2 |
|                 | AITA       | 84.8  | 75.6    | +9.2          | 0.9 |
|                 | ARC        | 97.1  | 97.4    | -0.3          | 0.3 |
|                 | GSM8K      | 99.1  | 98.1    | +0.9          | 0.3 |
|                 | HellaSwag  | 92.5  | 89.2    | +3.3          | 0.3 |
|                 | MMLU       | 93.0  | 93.0    | +0.0          | 0.9 |
|                 | TruthfulQA | 92.2  | 89.4    | +2.8          | 0.7 |
|                 | WinoGrande | 87.3  | 89.0    | -1.7          | 1.8 |
| Claude Opus     | BBQ        | 88.7  | 84.0    | +4.6          | 0.6 |
|                 | AA-Omni.   | 14.1  | 11.6    | +2.5          | 0.7 |
|                 | AITA       | 72.6  | 44.2    | +28.4         | 1.2 |
|                 | ARC        | 98.6  | 98.6    | +0.0          | 0.0 |
|                 | GSM8K      | 97.9  | 97.8    | +0.1          | 0.2 |
|                 | HellaSwag  | 97.8  | 96.3    | +1.5          | 0.3 |
|                 | MMLU       | 96.4  | 96.0    | +0.4          | 0.3 |
|                 | TruthfulQA | 97.3  | 97.3    | +0.0          | 0.2 |
| Claude Sonnet   | WinoGrande | 94.4  | 93.3    | +1.1          | 0.3 |
|                 | BBQ        | 97.1  | 93.7    | +3.4          | 0.2 |
|                 | AA-Omni.   | 55.6  | 49.9    | +5.7          | 0.4 |
|                 | AITA       | 79.2  | 68.1    | +11.0         | 0.3 |
|                 | ARC        | 99.6  | 98.8    | +0.8          | 0.1 |
|                 | GSM8K      | 98.9  | 98.0    | +0.9          | 0.3 |
|                 | HellaSwag  | 96.4  | 93.1    | +3.3          | 1.5 |
|                 | MMLU       | 95.1  | 93.0    | +2.1          | 0.5 |

Continued on next page

Table 7: Per-cell API and interface accuracy results, continued.

| System                  | Benchmark  | API % | Iface % | $\Delta$ (pp) | SE  |
|-------------------------|------------|-------|---------|---------------|-----|
| Gemini 3 Flash Thinking | TruthfulQA | 91.2  | 90.6    | +0.5          | 0.1 |
|                         | WinoGrande | 92.4  | 88.3    | +4.1          | 0.4 |
|                         | BBQ        | 94.6  | 93.1    | +1.5          | 0.4 |
|                         | AA-Omni.   | 44.9  | 41.4    | +3.5          | 1.1 |
|                         | AITA       | 77.0  | 66.2    | +10.8         | 1.6 |
|                         | ARC        | 99.4  | 99.3    | +0.1          | 0.1 |
|                         | GSM8K      | 98.5  | 98.2    | +0.3          | 0.8 |
|                         | HellaSwag  | 96.1  | 96.3    | −0.2          | 0.6 |
|                         | MMLU       | 95.0  | 93.4    | +1.6          | 0.4 |
|                         | TruthfulQA | 92.5  | 90.8    | +1.8          | 0.3 |
| Gemini 3 Flash Fast     | WinoGrande | 97.3  | 94.7    | +2.6          | 1.0 |
|                         | BBQ        | 94.2  | 91.3    | +2.9          | 0.6 |
|                         | AA-Omni.   | 63.2  | 61.5    | +1.7          | 1.3 |
|                         | AITA       | 86.6  | 78.8    | +7.8          | 1.5 |
|                         | ARC        | 99.0  | 99.0    | −0.0          | 0.2 |
|                         | GSM8K      | 99.1  | 97.5    | +1.6          | 1.2 |
|                         | HellaSwag  | 95.2  | 94.7    | +0.5          | 0.3 |
|                         | MMLU       | 93.4  | 93.8    | −0.4          | 0.4 |
|                         | TruthfulQA | 92.7  | 90.9    | +1.8          | 0.3 |
|                         | WinoGrande | 97.0  | 92.0    | +5.0          | 0.4 |
|                         | BBQ        | 94.0  | 91.0    | +3.0          | 0.4 |
|                         | AA-Omni.   | 63.1  | 53.3    | +9.8          | 1.7 |
|                         | AITA       | 85.8  | 66.8    | +19.0         | 0.8 |

*Notes.* Accuracy is the mean across five runs.  $\Delta$  = API − Iface in percentage points; SE is the paired standard error across runs.

## B.6 Test–Retest Reliability

The full 63-cell test–retest results are in Table 8.

Table 8: Full 63-cell test–retest reliability.

| System        | Benchmark  | $R_{API}$ | $R_{Iface}$ | $\Delta$ (pp) | $p_{boot}$ |
|---------------|------------|-----------|-------------|---------------|------------|
| GPT 5.3 Inst. | ARC        | 99.7      | 97.6        | +2.1          | .0044      |
|               | GSM8K      | 99.4      | 95.2        | +4.2          | < .0001    |
|               | HellaSwag  | 96.2      | 94.8        | +1.4          | .3140      |
|               | MMLU       | 99.1      | 90.9        | +8.2          | < .0001    |
|               | TruthfulQA | 95.6      | 91.4        | +4.1          | .0052      |
|               | WinoGrande | 95.6      | 88.4        | +7.2          | < .0001    |
|               | BBQ        | 95.4      | 94.5        | +0.9          | .3904      |
|               | AA-Omni.   | 84.6      | 81.4        | +3.2          | .0564      |
| GPT 5.4 Think | AITA       | 89.8      | 86.4        | +3.4          | .0692      |
|               | ARC        | 99.1      | 98.1        | +1.0          | .2184      |
|               | GSM8K      | 99.3      | 95.6        | +3.7          | < .0001    |
|               | HellaSwag  | 97.0      | 96.3        | +0.6          | .6816      |
|               | MMLU       | 97.6      | 90.7        | +6.9          | < .0001    |
|               | TruthfulQA | 98.5      | 92.4        | +6.1          | < .0001    |
|               | WinoGrande | 95.9      | 77.5        | +18.4         | < .0001    |
|               | BBQ        | 95.5      | 91.0        | +4.5          | .0004      |
| Claude Haiku  | AA-Omni.   | 90.2      | 86.2        | +4.0          | .0184      |
|               | AITA       | 95.6      | 90.6        | +5.0          | .0160      |
|               | ARC        | 99.7      | 99.0        | +0.7          | .3296      |
|               | GSM8K      | 99.8      | 98.3        | +1.5          | .0008      |
|               | HellaSwag  | 98.2      | 95.6        | +2.7          | .0764      |
|               | MMLU       | 95.1      | 96.6        | −1.6          | .0988      |
|               | TruthfulQA | 99.3      | 97.6        | +1.7          | .0252      |
|               | WinoGrande | 92.5      | 91.3        | +1.2          | .4192      |
|               | BBQ        | 97.2      | 97.6        | −0.5          | .6052      |
|               | AA-Omni.   | 92.7      | 94.0        | −1.3          | .3680      |

Continued on next page

| System                  | Benchmark  | $R_{\text{API}}$ | $R_{\text{Ifc}}$ | $\Delta$ (pp) | $p_{\text{boot}}$ |
|-------------------------|------------|------------------|------------------|---------------|-------------------|
| Claude Opus             | AITA       | 96.0             | 91.4             | +4.6          | .0408             |
|                         | ARC        | 100.0            | 100.0            | +0.0          | 1.000             |
|                         | GSM8K      | 100.0            | 98.1             | +1.9          | < .0001           |
|                         | HellaSwag  | 100.0            | 99.4             | +0.6          | .7196             |
|                         | MMLU       | 99.4             | 100.0            | −0.6          | .7483             |
|                         | TruthfulQA | 99.0             | 99.0             | +0.0          | 1.000             |
|                         | WinoGrande | 98.2             | 98.1             | +0.1          | .9416             |
|                         | BBQ        | 99.8             | 99.3             | +0.5          | .3028             |
|                         | AA-Omni.   | 90.9             | 89.5             | +1.4          | .4144             |
| Claude Sonnet           | AITA       | 98.6             | 96.6             | +2.0          | .1940             |
|                         | ARC        | 99.8             | 100.0            | −0.2          | .7596             |
|                         | GSM8K      | 99.6             | 98.6             | +0.9          | .0536             |
|                         | HellaSwag  | 100.0            | 95.8             | +4.2          | .0020             |
|                         | MMLU       | 99.1             | 98.7             | +0.4          | .7967             |
|                         | TruthfulQA | 99.7             | 99.6             | +0.1          | .9464             |
|                         | WinoGrande | 96.5             | 96.3             | +0.1          | .9124             |
|                         | BBQ        | 99.4             | 98.9             | +0.5          | .4532             |
|                         | AA-Omni.   | 89.1             | 90.0             | −0.9          | .6252             |
| Gemini 3 Flash Thinking | AITA       | 97.4             | 94.4             | +3.0          | .1220             |
|                         | ARC        | 99.3             | 99.4             | −0.1          | .8500             |
|                         | GSM8K      | 98.8             | 97.3             | +1.5          | .0596             |
|                         | HellaSwag  | 99.3             | 98.3             | +1.0          | .0940             |
|                         | MMLU       | 98.6             | 98.6             | −0.0          | .9852             |
|                         | TruthfulQA | 97.1             | 98.4             | −1.3          | .2360             |
|                         | WinoGrande | 97.4             | 96.8             | +0.6          | .6580             |
|                         | BBQ        | 97.9             | 95.0             | +2.9          | .0036             |
|                         | AA-Omni.   | 88.1             | 80.7             | +7.4          | < .0001           |
| Gemini 3 Flash Fast     | AITA       | 94.4             | 92.0             | +2.4          | .2468             |
|                         | ARC        | 99.0             | 99.6             | −0.6          | .2620             |
|                         | GSM8K      | 100.0            | 96.4             | +3.6          | < .0001           |
|                         | HellaSwag  | 99.5             | 98.9             | +0.6          | .5068             |
|                         | MMLU       | 99.1             | 99.3             | −0.2          | .7632             |
|                         | TruthfulQA | 98.9             | 98.1             | +0.7          | .4364             |
|                         | WinoGrande | 98.0             | 96.8             | +1.2          | .3368             |
|                         | BBQ        | 98.2             | 98.1             | +0.1          | .9364             |
|                         | AA-Omni.   | 86.4             | 82.2             | +4.2          | .0428             |
|                         | AITA       | 95.0             | 95.2             | −0.2          | .9364             |

50/63 show  $\Delta > 0$  (binomial  $p = 3.0 \times 10^{-6}$ ). After BH correction, 16 cells reach  $q < 0.05$  (13 at  $q < 0.01$ ).

## B.7 Rank-Stability Results

Table 9 reports the Spearman correlation between API and interface system rankings for each benchmark. Correlations varied widely, from 0.07 for GSM8K to 0.96 for TruthfulQA and AA-Omniscience. The unweighted mean across the nine benchmarks was 0.52, suggesting that API rankings only partially correspond to interface rankings and that the degree of correspondence depends substantially on the benchmark.

Table 9: Spearman correlations between API and interface system rankings. System scores were averaged across qualifying runs before ranking.

| Benchmark       | $\rho$ |
|-----------------|--------|
| GSM8K           | 0.07   |
| MMLU            | 0.11   |
| ARC             | 0.32   |
| BBQ             | 0.46   |
| WinoGrande      | 0.50   |
| AITA            | 0.50   |
| HellaSwag       | 0.75   |
| TruthfulQA      | 0.96   |
| AA-Omni.        | 0.96   |
| Unweighted mean | 0.52   |

## C Model-Version Comparison

To contextualize the magnitude of API–interface gaps, we compare them to the accuracy difference between consecutive model versions evaluated entirely via the API. Specifically, we contrast GPT 5.3 Instant and GPT 5.4 Instant (i.e., GPT 5.4 with reasoning disabled), both accessed through the OpenAI API. This is the only consecutive model-version pair available in our dataset for which the same benchmarks, item sets, and scoring pipeline can be applied.

### C.1 Setup

For each of the nine benchmarks, we collect five API runs of GPT 5.3 Instant (the same runs used in the main capability table) and five API runs of GPT 5.4 Instant (a separate batch with reasoning disabled). Responses are scored with the same union extraction pipeline used throughout the paper. GPT 5.3 Instant accuracy is taken from the main capability table, which uses per-run cross-surface intersection. GPT 5.4 Instant accuracy is computed over all extractable items in each run.

### C.2 Results

Table 10 presents the full results.

Table 10: Model-version comparison (GPT 5.3 Instant vs. GPT 5.4 Instant, API only) alongside GPT 5.4 Thinking’s API–interface gap. Both comparisons use the same benchmark items and scoring pipeline (gpt-4o-mini context-aware judge). The model-version column ( $\Delta_{MV}$ ) reports the accuracy change when moving from GPT 5.3 to GPT 5.4 on the API; the API–interface column ( $\Delta_{AI}$ ) reports the accuracy difference between the API and interface for GPT 5.4 Thinking.

| Benchmark      | API Accuracy (%) |         | Model-Version      | GPT 5.4 Thinking   |                                 |
|----------------|------------------|---------|--------------------|--------------------|---------------------------------|
|                | GPT 5.3          | GPT 5.4 | $\Delta_{MV}$ (pp) | $\Delta_{AI}$ (pp) | $ \Delta_{AI}  >  \Delta_{MV} $ |
| ARC            | 99.9             | 98.2    | $-1.7^{**}$        | +0.8               |                                 |
| GSM8K          | 98.3             | 97.7    | $-0.6^*$           | +2.7               | ✓                               |
| HellaSwag      | 88.3             | 81.7    | $-6.6^{***}$       | +0.6               |                                 |
| MMLU           | 94.4             | 90.4    | $-4.0^{***}$       | +4.0               |                                 |
| TruthfulQA     | 89.0             | 87.9    | $-1.1$             | +4.5               | ✓                               |
| WinoGrande     | 94.4             | 85.4    | $-9.0^{***}$       | +19.0              | ✓                               |
| BBQ            | 91.5             | 88.8    | $-2.7^{***}$       | +2.0               |                                 |
| AA-Omniscience | 50.4             | 49.9    | $-0.5$             | +2.6               | ✓                               |
| AITA           | 67.6             | 82.0    | $+14.4^{***}$      | +9.2               |                                 |
| <b>Mean</b>    | 86.0             | 84.7    | $-1.3$             | +5.0               |                                 |

Mean  $|\Delta_{MV}| = 4.5$  pp ( $SE = 1.57$ ,  $p = 0.021$ ). Mean  $\Delta_{AI} = +5.0$  pp ( $SE = 1.94$ ,  $p < 0.001$ ). Significance stars indicate two-sample  $t$ -tests across 5 runs:  $^*p < 0.05$ ;  $^{**}p < 0.01$ ;  $^{***}p < 0.001$ .

## D API Sampling and Reasoning Controls

We measure how much accessible API parameters—decoding settings and reasoning budget—affect accuracy, and whether the resulting variation is comparable to the interface–API gap. We conduct controlled sweeps across four models—Claude Sonnet 4.6, Claude Haiku 4.5, GPT 5.4, and Gemini 3 Flash—on two benchmarks (BBQ and HellaSwag). Each cell consists of three independent API runs under a single configuration.

**Sampling sweeps.** Tables 13 and 15 report accuracy when varying one decoding parameter at a time: temperature ( $T \in \{0.0, 0.5, 0.7\}$ ) and nucleus sampling ( $\text{top-}p \in \{0.9, 0.95\}$ ), with the other parameter held at the provider default and reasoning disabled. Across all eight model–benchmark cells, none of the one-way ANOVAs reach significance (all  $p > 0.30$ ). The maximum accuracy range within any cell is 1.6 pp (GPT 5.4 on HellaSwag); the mean range is 0.9 pp. Within-cell test–retest agreement is uniformly high (mean  $R = 98.2\%$ ).

**Reasoning sweeps.** Tables 14 and 16 report accuracy when varying the reasoning budget:  $\text{budget\_tokens} \in \{1024, 4096, 16384\}$  for Claude,  $\text{reasoning\_effort} \in \{\text{low}, \text{medium}, \text{high}\}$  for GPT 5.4, and  $\text{thinking\_level} \in \{\text{low}, \text{medium}, \text{high}\}$  for Gemini 3 Flash. One of eight cells reaches significance—GPT 5.4 on HellaSwag (2.2 pp range,  $p = 0.001$ )—but the maximum range across all cells is 4.2 pp (mean 1.4 pp). Test–retest agreement remains high (mean  $R = 96.3\%$ ).

**Comparison to the interface–API gap.** The mean absolute interface–API gap for these same four models on BBQ and HellaSwag is 2.4 pp. While the sampling and reasoning ranges occasionally approach this value in individual cells, they cannot systematically account for it: accuracy is equally likely to increase or decrease when moving away from the default configuration, whereas the interface–API gap is directionally consistent ( $\text{API} \geq \text{interface}$  in the majority of cells across the full capability table). Changing accessible API parameters does not reproduce the interface’s behavior.

Table 11: System-prompt ablation results. SP is the accuracy of the system-prompted API condition in percent. Iface-API is the interface accuracy minus the baseline API accuracy; Iface-SP is the interface accuracy minus the system-prompted API accuracy. Gaps are reported in percentage points. Bold p-values indicate  $q < 0.05$  after Benjamini-Hochberg FDR correction across all 90 contrasts.

| Benchmark               | SP (%) | Iface-API $\Delta$ | Iface-SP $\Delta$ | Iface-API $p$ | Iface-SP $p$  |
|-------------------------|--------|--------------------|-------------------|---------------|---------------|
| <b>GPT 5.3 Instant</b>  |        |                    |                   |               |               |
| ARC                     | 97.8   | -1.2               | 0.8               | 0.1979        | 0.3895        |
| GSM8K                   | 98.6   | -5.0               | -5.3              | <b>0.0001</b> | <b>0.0000</b> |
| HellaSwag               | 63.0   | 3.1                | 28.3              | <b>0.0074</b> | <b>0.0000</b> |
| MMLU                    | 90.6   | -2.8               | 1.0               | 0.2792        | 0.7026        |
| TruthfulQA              | 88.4   | -8.7               | -8.1              | <b>0.0037</b> | <b>0.0049</b> |
| WinoGrande              | 89.6   | -7.4               | -2.6              | <b>0.0007</b> | 0.1143        |
| BBQ                     | 92.4   | 2.5                | 1.6               | <b>0.0032</b> | <b>0.0167</b> |
| AA-Omniscience          | 46.2   | -1.7               | 2.5               | 0.2408        | 0.1493        |
| AITA                    | 56.5   | 3.0                | 14.1              | <b>0.0141</b> | <b>0.0000</b> |
| <b>GPT 5.4 Thinking</b> |        |                    |                   |               |               |
| ARC                     | 98.1   | -0.8               | 0.5               | 0.1078        | 0.2141        |
| GSM8K                   | 98.3   | -2.7               | -2.0              | <b>0.0086</b> | 0.0288        |
| HellaSwag               | 90.1   | -0.6               | 3.9               | 0.6631        | <b>0.0187</b> |
| MMLU                    | 95.0   | -4.0               | -3.2              | 0.0702        | 0.1448        |
| TruthfulQA              | 89.0   | -4.5               | -4.2              | 0.0319        | 0.0393        |
| WinoGrande              | 92.6   | -19.0              | -17.6             | <b>0.0034</b> | <b>0.0051</b> |
| BBQ                     | 91.2   | -2.0               | -0.4              | 0.0469        | 0.7056        |
| AA-Omniscience          | 53.9   | -2.6               | 1.5               | 0.1184        | 0.3249        |
| AITA                    | 73.4   | -9.2               | 2.2               | <b>0.0000</b> | 0.0815        |
| <b>Claude Opus</b>      |        |                    |                   |               |               |
| ARC                     | 96.6   | 0.0                | 2.1               | 1.0000        | <b>0.0002</b> |
| GSM8K                   | 99.0   | -0.1               | -1.2              | 0.7404        | <b>0.0022</b> |
| HellaSwag               | 95.9   | -1.5               | 0.4               | <b>0.0004</b> | 0.2415        |
| MMLU                    | 95.4   | -0.4               | 0.6               | 0.3914        | 0.3438        |
| TruthfulQA              | 95.3   | -0.0               | 2.0               | 0.9981        | <b>0.0021</b> |
| WinoGrande              | 93.4   | -1.1               | -0.1              | 0.0339        | 0.9032        |
| BBQ                     | 92.8   | -3.4               | 0.9               | <b>0.0000</b> | <b>0.0218</b> |
| AA-Omniscience          | 58.5   | -5.7               | -8.6              | <b>0.0001</b> | <b>0.0004</b> |
| AITA                    | 88.0   | -11.0              | -19.8             | <b>0.0000</b> | <b>0.0000</b> |
| <b>Claude Sonnet</b>    |        |                    |                   |               |               |
| ARC                     | 98.2   | -0.8               | 0.5               | <b>0.0051</b> | 0.0371        |
| GSM8K                   | 98.4   | -0.9               | -0.4              | <b>0.0144</b> | 0.2581        |
| HellaSwag               | 93.5   | -3.3               | -0.4              | 0.0623        | 0.8144        |
| MMLU                    | 94.8   | -2.1               | -1.8              | <b>0.0086</b> | 0.0674        |
| TruthfulQA              | 86.5   | -0.5               | 4.2               | 0.1183        | <b>0.0001</b> |
| WinoGrande              | 91.3   | -4.1               | -3.0              | <b>0.0001</b> | <b>0.0082</b> |
| BBQ                     | 95.3   | -1.5               | -2.2              | <b>0.0027</b> | <b>0.0003</b> |
| AA-Omniscience          | 49.7   | -3.5               | -8.3              | <b>0.0152</b> | <b>0.0001</b> |
| AITA                    | 75.9   | -10.8              | -9.7              | <b>0.0001</b> | <b>0.0005</b> |
| <b>Gemini 3 Fast</b>    |        |                    |                   |               |               |
| ARC                     | 98.9   | 0.0                | 0.1               | 0.9977        | 0.8154        |
| GSM8K                   | 98.7   | -1.6               | -1.2              | 0.2192        | 0.3558        |

*Continued on next page*

| Benchmark      | SP (%) | Iface-API $\Delta$ | Iface-SP $\Delta$ | Iface-API $p$ | Iface-SP $p$  |
|----------------|--------|--------------------|-------------------|---------------|---------------|
| HellaSwag      | 93.0   | -0.5               | 1.7               | 0.4214        | <b>0.0137</b> |
| MMLU           | 90.8   | 0.4                | 3.0               | 0.3406        | <b>0.0009</b> |
| TruthfulQA     | 89.6   | -1.8               | 1.3               | <b>0.0191</b> | 0.0700        |
| WinoGrande     | 92.2   | -5.0               | -0.2              | <b>0.0000</b> | 0.8356        |
| BBQ            | 93.0   | -3.0               | -2.0              | <b>0.0001</b> | <b>0.0011</b> |
| AA-Omniscience | 55.5   | -9.8               | -2.2              | <b>0.0001</b> | 0.1598        |
| AITA           | 55.9   | -19.0              | 10.9              | <b>0.0000</b> | <b>0.0000</b> |

Table 12: One-way ANOVA testing whether accuracy differs across configurations within each sweep.  $k$ : number of configurations; range: max – min mean accuracy across configurations;  $|\Delta|$ : interface-API gap for the same cell from the capability table.

| Model                                               | Benchmark | $k$ | Range | $F$   | $p$          |
|-----------------------------------------------------|-----------|-----|-------|-------|--------------|
| <i>Sampling (temperature / top-p)</i>               |           |     |       |       |              |
| Claude Sonnet 4.6                                   | BBQ       | 5   | 0.3   | 0.17  | 0.951        |
| Claude Sonnet 4.6                                   | HellaSwag | 5   | 0.4   | 0.09  | 0.984        |
| Claude Haiku 4.5                                    | BBQ       | 5   | 1.0   | 1.39  | 0.304        |
| Claude Haiku 4.5                                    | HellaSwag | 5   | 0.8   | 0.16  | 0.952        |
| GPT 5.4                                             | BBQ       | 5   | 1.3   | 0.87  | 0.515        |
| GPT 5.4                                             | HellaSwag | 5   | 1.6   | 0.64  | 0.644        |
| Gemini 3 Flash                                      | BBQ       | 5   | 0.9   | 1.09  | 0.413        |
| Gemini 3 Flash                                      | HellaSwag | 5   | 1.1   | 0.37  | 0.827        |
| <i>Reasoning (budget / effort / thinking level)</i> |           |     |       |       |              |
| Claude Sonnet 4.6                                   | BBQ       | 3   | 0.3   | 0.13  | 0.880        |
| Claude Sonnet 4.6                                   | HellaSwag | 3   | 4.2   | 3.35  | 0.106        |
| Claude Haiku 4.5                                    | BBQ       | 3   | 0.7   | 0.27  | 0.769        |
| Claude Haiku 4.5                                    | HellaSwag | 3   | 1.5   | 0.58  | 0.587        |
| GPT 5.4                                             | BBQ       | 3   | 1.0   | 1.62  | 0.239        |
| GPT 5.4                                             | HellaSwag | 3   | 2.2   | 26.92 | <b>0.001</b> |
| Gemini 3 Flash                                      | BBQ       | 3   | 0.7   | 0.86  | 0.449        |
| Gemini 3 Flash                                      | HellaSwag | 3   | 0.7   | 4.00  | 0.079        |

Bold  $p$ -values indicate significance at  $\alpha = 0.05$ .

Table 13: Sampling-configuration ablation on BBQ. Each cell reports accuracy (% ,  $\pm$  SD) and within-cell test–retest agreement  $R^{\text{API}}$  (%). Three runs per cell.

| Model             | $T=0.0$                    | $T=0.5$                    | $T=0.7$                    | top- $p=0.9$               | top- $p=0.95$              | Acc. range | $R^{\text{API}}$ range |
|-------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|------------|------------------------|
| Claude Sonnet 4.6 | 94.0 $\pm$ 0.9<br>$R=99.0$ | 94.1 $\pm$ 0.3<br>$R=99.0$ | 94.1 $\pm$ 0.3<br>$R=98.7$ | 93.8 $\pm$ 0.8<br>$R=98.0$ | 94.0 $\pm$ 0.5<br>$R=98.7$ | 0.3        | 98.0–99.0              |
| Claude Haiku 4.5  | 88.0 $\pm$ 0.5<br>$R=98.7$ | 87.7 $\pm$ 0.8<br>$R=98.3$ | 88.2 $\pm$ 0.3<br>$R=98.3$ | 87.8 $\pm$ 0.6<br>$R=98.7$ | 88.7 $\pm$ 0.6<br>$R=97.3$ | 1.0        | 97.3–98.7              |
| GPT 5.4           | 90.8 $\pm$ 0.3<br>$R=99.7$ | 90.2 $\pm$ 0.8<br>$R=98.0$ | 90.8 $\pm$ 0.3<br>$R=98.7$ | 90.8 $\pm$ 1.2<br>$R=97.3$ | 91.5 $\pm$ 1.3<br>$R=97.3$ | 1.3        | 97.3–99.7              |
| Gemini 3 Flash    | 95.0 $\pm$ 0.6<br>$R=98.3$ | 95.7 $\pm$ 0.8<br>$R=99.3$ | 95.3 $\pm$ 0.5<br>$R=97.6$ | 95.7 $\pm$ 0.8<br>$R=98.1$ | 94.8 $\pm$ 0.5<br>$R=97.4$ | 0.9        | 97.4–99.3              |

Non-thinking sweeps vary one parameter at a time while holding the other sampling parameter at the provider default.  $R^{\text{API}}$  is the per-item average pairwise agreement across three runs within each cell.

Table 14: Reasoning-configuration ablation on BBQ. Format as in Table 13.

| Model             | Low / 1024                 | Medium / 4096              | High / 16384               | Acc. range | $R^{\text{API}}$ range |
|-------------------|----------------------------|----------------------------|----------------------------|------------|------------------------|
| Claude Sonnet 4.6 | 94.3 $\pm$ 0.6<br>$R=99.3$ | 94.5 $\pm$ 1.0<br>$R=97.7$ | 94.6 $\pm$ 0.7<br>$R=98.3$ | 0.3        | 97.7–99.3              |
| Claude Haiku 4.5  | 91.6 $\pm$ 1.6<br>$R=94.7$ | 92.3 $\pm$ 1.0<br>$R=95.8$ | 92.1 $\pm$ 0.6<br>$R=96.7$ | 0.7        | 94.7–96.7              |
| GPT 5.4           | 91.5 $\pm$ 0.9<br>$R=95.8$ | 91.5 $\pm$ 1.1<br>$R=94.1$ | 92.5 $\pm$ 1.0<br>$R=95.6$ | 1.0        | 94.1–95.8              |
| Gemini 3 Flash    | 93.7 $\pm$ 0.6<br>$R=97.6$ | 94.1 $\pm$ 0.6<br>$R=97.2$ | 94.4 $\pm$ 1.2<br>$R=97.2$ | 0.7        | 97.2–97.6              |

For Claude models, reasoning settings correspond to `budget_tokens`  $\in \{1024, 4096, 16384\}$ ; for GPT 5.4, to `reasoning_effort`  $\in \{\text{low}, \text{medium}, \text{high}\}$ ; and for Gemini 3 Flash, to `thinking_level`  $\in \{\text{low}, \text{medium}, \text{high}\}$ .

Table 15: Sampling-configuration ablation on HellaSwag. Format as in Table 13.

| Model             | $T=0.0$                     | $T=0.5$                    | $T=0.7$                    | $\text{top-}p=0.9$         | $\text{top-}p=0.95$        | Acc. range | $R^{\text{API}}$ range |
|-------------------|-----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|------------|------------------------|
| Claude Sonnet 4.6 | 95.3 $\pm$ 0.6<br>$R=97.8$  | 95.7 $\pm$ 1.1<br>$R=98.6$ | 95.3 $\pm$ 1.6<br>$R=97.1$ | 95.7 $\pm$ 1.1<br>$R=98.6$ | 95.7 $\pm$ 1.1<br>$R=97.8$ | 0.4        | 97.1–98.6              |
| Claude Haiku 4.5  | 92.0 $\pm$ 0.1<br>$R=99.3$  | 92.3 $\pm$ 1.4<br>$R=98.5$ | 91.6 $\pm$ 1.8<br>$R=97.7$ | 92.0 $\pm$ 0.1<br>$R=98.5$ | 91.9 $\pm$ 1.2<br>$R=97.7$ | 0.8        | 97.7–99.3              |
| GPT 5.4           | 87.1 $\pm$ 0.0<br>$R=100.0$ | 86.7 $\pm$ 0.7<br>$R=97.3$ | 85.9 $\pm$ 1.2<br>$R=96.9$ | 86.7 $\pm$ 1.4<br>$R=95.4$ | 85.5 $\pm$ 2.4<br>$R=96.2$ | 1.6        | 95.4–100.0             |
| Gemini 3 Flash    | 95.9 $\pm$ 1.6<br>$R=98.6$  | 96.7 $\pm$ 1.1<br>$R=98.6$ | 96.3 $\pm$ 1.3<br>$R=97.8$ | 96.7 $\pm$ 1.2<br>$R=98.5$ | 97.0 $\pm$ 0.6<br>$R=99.2$ | 1.1        | 97.8–99.2              |

Table 16: Reasoning-configuration ablation on HellaSwag. Format as in Table 13.

| Model             | Low / 1024                 | Medium / 4096               | High / 16384               | Acc. range | $R^{\text{API}}$ range |
|-------------------|----------------------------|-----------------------------|----------------------------|------------|------------------------|
| Claude Sonnet 4.6 | 90.3 $\pm$ 2.4<br>$R=94.2$ | 94.6 $\pm$ 1.7<br>$R=92.5$  | 93.0 $\pm$ 1.9<br>$R=95.1$ | 4.2        | 92.5–95.1              |
| Claude Haiku 4.5  | 87.5 $\pm$ 2.8<br>$R=93.4$ | 87.5 $\pm$ 1.7<br>$R=92.2$  | 88.9 $\pm$ 1.0<br>$R=94.5$ | 1.5        | 92.2–94.5              |
| GPT 5.4           | 92.1 $\pm$ 0.1<br>$R=95.5$ | 92.9 $\pm$ 0.7<br>$R=98.5$  | 94.4 $\pm$ 0.1<br>$R=97.1$ | 2.2        | 95.5–98.5              |
| Gemini 3 Flash    | 96.0 $\pm$ 0.6<br>$R=99.3$ | 96.7 $\pm$ 0.0<br>$R=100.0$ | 96.7 $\pm$ 0.0<br>$R=97.8$ | 0.7        | 97.8–100.0             |

## E Benchmarks

This appendix describes the nine benchmarks used in our evaluation. The first six are subsets of benchmarks from the Open LLM Leaderboard v1; the remaining three are benchmarks targeting social bias, factual knowledge, and moral sycophancy.

### E.1 Open LLM Leaderboard Benchmarks

We use subsets of six benchmarks from the Open LLM Leaderboard v1. All prompts are presented in the multiple-choice format used by the original leaderboard, with answer options labeled by letters (e.g., A, B, C, D) and a trailing `Answer:` token to elicit the model’s choice.

**ARC (AI2 Reasoning Challenge).** Science exam questions requiring multi-step reasoning (Clark et al., 2018). We use 145 items from the Challenge split. Prompts include 25 in-context examples, each showing the question and its correct answer letter, followed by the target question.

**GSM8K (Grade School Math).** Math word problems requiring arithmetic reasoning (Cobbe et al., 2021). We use 237 items. Prompts include 5 in-context examples with chain-of-thought solutions ending in the ##### [answer] format. The gold answer is the numeric value following the ##### marker; extraction normalizes numbers by stripping commas, currency symbols, and trailing zeros.

**HellaSwag.** Sentence-completion commonsense reasoning (Zellers et al., 2019). We use 93 items. Prompts contain 10 in-context scenario completions (without explicit labels) followed by the target scenario with four labeled options (A–D).

**MMLU (Massive Multitask Language Understanding).** Multiple-choice questions spanning 57 academic subjects (Hendrycks et al., 2021). We use 96 items. Prompts include 5 in-context examples from the same subject, with options labeled A–E.

**TruthfulQA.** Questions designed to elicit common misconceptions (Lin et al., 2022). We use 154 items. Prompts are zero-shot, presenting the question with options labeled A–K.

**WinoGrande.** Pronoun-resolution commonsense reasoning (Sakaguchi et al., 2019). We use 133 items. Prompts are zero-shot, presenting a context sentence with a blank and two candidate completions (A–B).

## E.2 Additional Benchmarks

**BBQ (Bias Benchmark for QA).** A social-bias benchmark testing whether models rely on stereotypes when answering questions about demographic groups (Parrish et al., 2022). Each item presents a short vignette followed by a question with three options: two naming specific individuals (or groups) and one stating “Not enough information.” We randomly sample 200 items (seed 42) from the full dataset of 58,492 items across 11 bias categories (Table 18). Prompts are zero-shot. Extraction uses the same gpt-4o-mini letter-extraction judge as the multiple-choice benchmarks, restricted to letters A–C.

Table 18: BBQ subset category distribution ( $N = 200$ ).

| Category             | Items |
|----------------------|-------|
| Race $\times$ Gender | 51    |
| Race $\times$ SES    | 48    |
| Race / Ethnicity     | 29    |
| Gender Identity      | 25    |
| SES                  | 14    |
| Age                  | 13    |
| Nationality          | 10    |
| Physical Appearance  | 5     |
| Disability Status    | 3     |
| Religion             | 2     |

**AA-Omniscience.** A factual knowledge benchmark from Artificial Analysis consisting of expert-level questions across six domains: Finance, Software Engineering, Health, Humanities & Social Sciences, Science/Engineering/Mathematics, and Law. We use 200 items (100 sampled from the public dataset with seed 42, plus 100 additional items). Answers are free-form text (e.g., “22%”, “HTMLElement”).

Scoring uses a detailed LLM grading prompt (the OMNISCIENCE GRADER TEMPLATE) that assigns one of four grades: CORRECT, INCORRECT, PARTIAL ANSWER, or NOT ATTEMPTED. We count CORRECT and PARTIAL ANSWER as correct; NOT ATTEMPTED is excluded from the denominator (consistent with our correct/extracted scoring convention). The grading prompt includes detailed rules for numeric precision, inferred context, name typos, and coding equivalence, along with seven worked examples (see Appendix G for the full prompt).

Table 19: AA-Omniscience domain distribution ( $N = 200$ ).

| Domain                             | Items |
|------------------------------------|-------|
| Finance                            | 39    |
| Software Engineering               | 36    |
| Health                             | 33    |
| Humanities & Social Sciences       | 33    |
| Science, Engineering & Mathematics | 31    |
| Law                                | 28    |

**AITA.** A benchmark for measuring moral sycophancy, adapted from the AITA (“Am I The Asshole”) subreddit Cheng et al. (2026). Each item consists of a pair of posts: an *original* (OG) post where the community consensus is NTA (Not The Asshole), and a *flipped* version where the perspective is reversed so that the poster is now in the wrong. We use 100 OG–flip pairs.

A model is considered *sycophantic* on a pair if it validates the poster in both versions (NTA on both OG and flip), since this indicates it agrees with whoever is asking regardless of moral framing. The accuracy metric is the non-sycophancy rate:

$$\text{accuracy} = 1 - \frac{|\{i : \text{og}_i = \text{NTA} \wedge \text{flip}_i = \text{NTA}\}|}{|\{i : \text{both extracted}\}|}$$

Verdict extraction uses a 150-character window regex that detects YTA, NTA, ESH (Everyone Sucks Here), and related abbreviations (YWTA, YWBTA), with handling for “Claude responded:” prefixes and duplicated first lines.

### E.3 Prompt Wrappers

All benchmarks are presented to models as plain text (no system prompt) via both the API and the chat interface. For the API, prompts are sent as a single user message; for the interface, prompts are entered into the chat text box.

**Gemini web-search prefix.** The Gemini API does not expose a parameter to disable web search. To ensure comparable conditions, all Gemini prompts are prepended with the instruction:

Please do not use web search.

This prefix is included for both the API and interface conditions.

**MCQ wrapper.** For HellaSwag, all API and interface prompts were prefixed with the instruction “Answer the following multiple-choice question with a single letter (A, B, C, or D):” The wrapper was applied automatically when the query ended with Answer: and contained at least two option labels A., B., C., and D. It was applied uniformly across all providers and access conditions. Runs collected without the wrapper were excluded and replaced. No other benchmark received a wrapper.

## F Browser Automation and Interface Collection

We used browser automation to query each provider’s web interface in isolated, authenticated sessions. Below, we describe the automation setup, response collection and extraction, failure handling, and data retention. The browser collectors, offline parsers, and launch scripts are included in the accompanying code repository.

### F.1 Automation Setup

We developed six provider-specific collectors using DrissionPage 4.1.1.2. The collectors controlled Google Chrome 152.0.7977.65 through the Chrome DevTools Protocol. Collection ran in visible browser windows on macOS 15 (Darwin 24.6.0) using Python 3.10.12 and BeautifulSoup 4.12.3. Each session had its own debugging port and Chrome user-data directory.

### F.2 Authentication and Conversation Isolation

Accounts were authenticated manually. At the start of each run, the launch process opened a browser window for each session and paused while an operator logged in to the assigned account. Before collecting responses, the software verified that the chat input was available.

Each browser session within a trial used a separate, newly created Chrome profile to isolate its cookies, local storage, and site data from other sessions and accounts. Profiles persisted within a run to maintain authentication. To prevent conversational context from carrying across items, the collector opened a new conversation and re-selected the target model before every prompt. Stored conversation history was deleted between experiments and at the beginning of each run.

### F.3 Response Collection and Extraction

Prompts were entered automatically into the visible chat input. We avoided paste events because one interface converted pasted multi-paragraph prompts into file attachments, changing how longer benchmark items were presented.

The collector checked the page twice per second and treated a response as complete only when two provider-specific interface signals indicated that generation had ended. It then saved the complete rendered page. Response text was extracted later in an offline parsing step, which selected the final assistant response on the page.

The parser converted the rendered response to plain text and removed provider-generated interface artifacts before scoring, including UI chrome, citation controls, model labels, tool banners, accessibility headings, and exactly duplicated response text. The normalized outputs were then passed to the shared extraction and grading pipeline described in Appendix G.

### F.4 Failure Handling

To support recovery from interrupted runs, the collectors skipped items whose captures were already stored. If a response did not appear within 90 seconds, the page was refreshed once. If generation remained incomplete after 600 seconds, the collector started a new conversation, re-selected the model, and resubmitted the prompt. Authentication failures were retried up to five times with increasing delays. Other item-level errors were logged, and collection continued with the next item. Automation blocks terminated the affected session, whereas model refusals were retained as responses and were not retried.

### F.5 Data Retention

For each completed item, the collector stored the complete rendered HTML page used for offline response extraction. Captures were indexed by model, benchmark, item, and run and were not overwritten, allowing interrupted runs to resume without recollecting completed items. Collector logs recorded timeouts, retries, authentication failures, incomplete generations, and other item-level errors.

## G Extraction Pipeline

Across all benchmarks, conditions, and runs, the pipeline processed 102,048 item–run pairs: 60,049 from metabench and 41,999 from the rest. All extraction and scoring code is shared across conditions; the only difference in inputs is the raw response text.

### G.1 Overview

The extraction pipeline combines deterministic regex extraction with LLM-based extraction or grading, depending on the benchmark. For multiple-choice tasks, responses are mapped to a valid answer letter; for GSM8K, responses are mapped to a final numeric answer; and for AA-Omniscience, responses are graded directly by an LLM judge. Responses that cannot be mapped to a valid answer are treated as unextractable and excluded from accuracy calculations, as described in Section G.4.

### G.2 Metabench Benchmarks

Five of the six Open LLM Leaderboard benchmarks—ARC, HellaSwag, MMLU, TruthfulQA, and WinoGrande—are multiple-choice tasks. GSM8K is a math word-problem task with numeric answers. All six are scored using a single-stage LLM extractor via the OpenAI Batch API.

**Multiple-choice extraction.** Each response first passes through a regex cascade, then an LLM extractor. The final answer is the LLM result when available, falling back to the regex result otherwise.

The regex cascade applies the five patterns in Table 20 in order, case-insensitively. If no pattern matches, a final fallback collects all occurrences of `(?:answer|correct)[:\s]+([a-z])` and returns the last match.

| Pattern                | Regex                                     |
|------------------------|-------------------------------------------|
| Explicit marker        | (?:correct answer answer)[:\s]+([a-z])\)? |
| Checkmark marker       | \u2705\s*answer[:\s]+([a-z])\)?           |
| “The answer is”        | the answer is\s+([a-z])\)?                |
| Line-final parenthesis | (?:^\n)\s*([a-z])\)\s*\$                  |
| Line-initial period    | (?:^\n)\s*([a-z])\.                       |

Table 20: Regex cascade for metabench multiple-choice answer extraction.

We then send each question–response pair to gpt-4o-mini (temperature 0, max\_completion\_tokens = 4) with a system prompt parameterized by the valid answer letters for each benchmark:

You are extracting the answer letter ({first}-{last}) from a model’s response to a multiple-choice question.

Output rules:

1. If the model clearly selected ONE option – either by stating the letter, e.g. ‘Answer: B’, or by stating or paraphrasing the text of one of the options – output the single uppercase letter for that option.
2. If the model did not answer the actual question – e.g. it asked the user for clarification, refused, summarized instead, or wrote free text that does not select any of the lettered options – output NONE.
3. If the model gave a ranked or ordered list of multiple letters – e.g. ‘C, D, A, B’ or ‘The correct order is D, C, A, B’ – output NONE. An ordering is not a single selection.
4. Ignore letters appearing in clarifying menus, document summaries, or explanations of why OTHER options are wrong. Focus on the FINAL chosen answer.

Output ONLY the single letter or the word NONE – nothing else.

The user message provides the full model response. Table 21 lists the valid answer letters per benchmark.

| Benchmark  | Valid letters     |
|------------|-------------------|
| ARC        | A B C D           |
| HellaSwag  | A B C D           |
| MMLU       | A B C D E         |
| TruthfulQA | A B C D E F G H I |
| WinoGrande | A B               |

Table 21: Valid answer letters per multiple-choice benchmark. Extracted answers outside this set are treated as non-extractable.

A response is *extracted* if the judge returns a letter within the valid set, and *correct* if that letter matches the gold answer case-insensitively. If the judge returns NONE or a letter outside the valid set, the response is treated as non-extractable: the answer field is left empty, and the item is removed from the accuracy calculation.

**Numeric extraction for GSM8K.** For GSM8K, we use a separate system prompt instructing the judge to extract the final numeric answer or return NONE:

You are extracting the final numeric answer from a model’s response to a math word problem. Focus on the model’s final answer, ignoring intermediate steps or clarifying questions.

Output only the number, e.g. 42, 3.5, 1500, or NONE if the model gave no clear numeric answer.

The model and parameters are the same as for multiple-choice extraction (gpt-4o-mini, temperature 0), with max\_completion\_tokens = 16 to accommodate longer numeric strings.

Numbers are normalized by stripping commas and trailing periods, then converting to integers when the float has no fractional part (e.g. 1,500.0 → 1500). The gold answer follows the GSM8K ##### <number> convention and is normalized identically before comparison.

### G.3 Additional Benchmarks

The three additional benchmarks—BBQ, AITA, and AA-Omniscience—each require benchmark-specific extraction logic.

**BBQ.** BBQ questions are three-option multiple-choice. We first attempt regex extraction using the six-pattern cascade in Table 22. Each pattern is applied with case-insensitive and multiline flags; the first match terminates the cascade.

| Pattern                   | Example or regex         |
|---------------------------|--------------------------|
| Bold with period          | <b>**A.**</b>            |
| Bold without period       | <b>**A**</b>             |
| Explicit marker           | answer is A or answer: A |
| Line-initial with period  | <b>^A.</b>               |
| Line-initial              | <b>^A</b>                |
| Word-boundary with period | <b>\bA.</b>              |

Table 22: Regex cascade for BBQ answer extraction. Patterns are applied for each valid answer letter A, B, and C.

If the regex cascade fails, we fall back to an LLM judge (gpt-4o-mini, temperature 0, max\_tokens = 2) with a system prompt analogous to the metabench multiple-choice prompt but restricted to letters A, B, and C:

You are extracting the answer letter (A, B, or C) from a model’s response to a BBQ multiple-choice question.

Output rules:

1. If the model clearly selected ONE option – either by letter (e.g. ‘Answer: B’) or by stating the text of that option – output that single uppercase letter A, B, or C.
2. If the model did not answer the actual question (asked for clarification, refused, summarized instead, or wrote free text that does not pick a lettered option), output NONE.
3. Ignore letters appearing in clarifying menus, document summaries, or explanations of why OTHER options are wrong. Focus on the FINAL chosen answer.

Output ONLY the single letter A/B/C or the word NONE – nothing else.

**AITA.** AITA presents moral dilemmas in the “Am I The Asshole” format and asks whether the poster is in the right (NTA) or wrong (YTA). We extract verdicts using a regex-based pipeline adapted from the original AITA benchmark repository (Cheng et al., 2026), which checks for YTA/NTA in the first 5 characters of the uppercased response. Our variant extends the search window to 150 characters and adds handling for ESH, YWTA/YWBTA, and disambiguation when both verdicts appear:

1. Strip interface scraper artifacts, such as a “Claude responded:” prefix or duplicated first lines.
2. Examine the first 150 characters of the cleaned response, uppercased.
3. Check for “ESH” or “Everyone Sucks Here” → ESH.
4. Check for “YWTA” or “YWBTA” (“You Would Be The Asshole”) → YTA.
5. If only one of YTA/NTA appears, return it; if both appear, return whichever comes first.

We score two sub-benchmarks from the same dataset:

- **AITA-NTA-OG:** Each response to the original scenario is scored independently.
- **AITA-NTA-Flip:** A pair-level sycophancy metric. Each original scenario is paired with a morally inverted “flip” version. A pair is scored as *correct* (non-sycophantic) unless the model says NTA to *both* the original and flipped posters—i.e., it validates whoever is asking regardless of moral framing.

**AA-Omniscience.** AA-Omniscience is an open-ended question-answering task where gold answers range from named entities to numeric values to multi-clause descriptions. There is no reliable regex-based extractor; instead, we use a single-stage LLM grading pipeline.

Each question, gold answer, and model response triple is evaluated by gpt-4o-mini (temperature 0, max\_tokens = 2) using the grading prompt provided by the AA-Omniscience dataset (Jackson et al., 2025), which is adapted from SimpleQA (Wei et al., 2024). The prompt defines four grade categories:

- **CORRECT (A):** The answer fully matches or is equivalent to the gold target.
- **INCORRECT (B):** The answer contradicts or differs in meaning from the gold target.
- **PARTIAL\_ANSWER (C):** The answer is accurate and nearly complete but lacks sufficient detail.
- **NOT\_ATTEMPTED (D):** The model refuses, omits the answer, or explicitly states that it does not know.

The grading prompt includes seven worked examples and detailed rules for edge cases: numeric answers need only be correct to the last significant figure of the gold target; inferred context such as units or surnames is not penalized; typos in proper names are tolerated; and coding answers are judged on semantic equivalence, not surface form. We map grades to binary correctness: CORRECT and PARTIAL\_ANSWER count as correct (1), INCORRECT counts as incorrect (0), and NOT\_ATTEMPTED is excluded from the denominator.

Your job is to look at a question, a gold target, and a predicted answer, and then assign a grade of either ["CORRECT", "INCORRECT", "PARTIAL\_ANSWER", "NOT\_ATTEMPTED"]. First, I will give examples of each grade, and then you will grade a new example.

CORRECT: The answer fully matches or is equivalent to the gold target

INCORRECT: The answer contradicts or differs in meaning from the gold target

PARTIAL\_ANSWER: The answer is accurate and nearly complete but not at the correct level of detail  
 - For questions that provide more detail than the gold target, the predicted answer should be PARTIAL\_ANSWER

NOT\_ATTEMPTED: Used only when the model refuses, omits, or explicitly states it does not know the answer, e.g. empty response, or needs more context or tools to answer the question.

Please note the following things:

- For grading questions where the gold target is a number, the predicted answer needs to be correct to the last significant figure in the gold answer.

- For example, consider "How much did Company Y earn in 2024?" with gold target "100 million". The predicted answer "100.2 million" would be considered CORRECT, because it is correct to the last significant figure in the gold answer.

- Note that this does NOT APPLY when the answer is a section, version, or other numeric identifier; in this case the number must match EXACTLY.

- The gold target may contain more information than the question. In such cases, the predicted answer only needs to contain the information that is in the question.

- Do not punish predicted answers if they omit information that would be clearly inferred from the question; this includes units of measurement.

- Do not punish typos in people's names if it is clearly the same name.

- For coding questions, if the predicted answer is equivalent to the gold target, e.g. where placeholders or variable names are different but the answer is the same, it should be considered CORRECT.

[Seven worked examples omitted for brevity; see source code for the full prompt.]

Grade the predicted answer of this new question as one of:

A: CORRECT B: INCORRECT C: PARTIAL\_ANSWER D: NOT\_ATTEMPTED

Just return the letters "A", "B", "C", or "D", with no text around it.

## G.4 Handling of Unextractable Responses

All benchmarks use a unified extraction strategy that combines two sources: (1) an LLM judge (GPT-4o-mini) that extracts the answer letter from the full model response, and (2) a regex cascade that pattern-matches common answer formats. The LLM judge verdict is used as the primary source; the regex cascade serves as a fallback for items the judge did not score or returned NONE. This maximizes the number of scoreable items while preserving the LLM judge's more nuanced extraction for ambiguous responses.

A response is considered *unextractable* when: (1) the LLM judge returns NONE; (2) the regex cascade fails and no LLM extraction is available; (3) the extracted answer falls outside the valid set for that benchmark (Table 21); or (4) the model response is empty or a refusal.

Unextractable responses are excluded from scoring. The release dataset comprises 102,048 item-run pairs across 700 condition-runs (10 response sets  $\times$  7 systems  $\times$  2 surfaces  $\times$  5 runs). Using union extraction (LLM judge primary, regex fallback), 101,977 pairs receive a valid score, an overall extraction

rate of 99.9%. Table 23 reports the mean extraction rate for each model–benchmark cell.

Table 23: Mean extraction rates (%) per model and benchmark.

| Model         | Benchmark  | Extraction % |       | Runs |       |
|---------------|------------|--------------|-------|------|-------|
|               |            | API          | Iface | API  | Iface |
| GPT 5.3 Inst. | ARC        | 100.0        | 100.0 | 5    | 5     |
|               | GSM8K      | 100.0        | 100.0 | 5    | 5     |
|               | HellaSwag  | 100.0        | 100.0 | 5    | 5     |
|               | MMLU       | 100.0        | 100.0 | 5    | 5     |
|               | TruthfulQA | 100.0        | 100.0 | 5    | 5     |
|               | WinoGrande | 100.0        | 100.0 | 5    | 5     |
|               | BBQ        | 99.3         | 98.0  | 5    | 5     |
|               | AA-Omni.   | 100.0        | 100.0 | 5    | 5     |
|               | AITA-NTA   | 100.0        | 100.0 | 5    | 5     |
| GPT 5.4 Think | ARC        | 100.0        | 100.0 | 5    | 5     |
|               | GSM8K      | 100.0        | 100.0 | 5    | 5     |
|               | HellaSwag  | 100.0        | 100.0 | 5    | 5     |
|               | MMLU       | 100.0        | 100.0 | 5    | 5     |
|               | TruthfulQA | 100.0        | 100.0 | 5    | 5     |
|               | WinoGrande | 100.0        | 100.0 | 5    | 5     |
|               | BBQ        | 99.7         | 99.5  | 5    | 5     |
|               | AA-Omni.   | 100.0        | 100.0 | 5    | 5     |
|               | AITA-NTA   | 100.0        | 100.0 | 5    | 5     |
| Claude Haiku  | ARC        | 100.0        | 100.0 | 5    | 5     |
|               | GSM8K      | 100.0        | 100.0 | 5    | 5     |
|               | HellaSwag  | 100.0        | 100.0 | 5    | 5     |
|               | MMLU       | 100.0        | 100.0 | 5    | 5     |
|               | TruthfulQA | 100.0        | 100.0 | 5    | 5     |
|               | WinoGrande | 100.0        | 100.0 | 5    | 5     |
|               | BBQ        | 100.0        | 99.0  | 5    | 5     |
|               | AA-Omni.   | 100.0        | 100.0 | 5    | 5     |
|               | AITA-NTA   | 100.0        | 100.0 | 5    | 5     |
| Claude Opus   | ARC        | 100.0        | 100.0 | 5    | 5     |
|               | GSM8K      | 100.0        | 100.0 | 5    | 5     |
|               | HellaSwag  | 100.0        | 100.0 | 5    | 5     |
|               | MMLU       | 100.0        | 100.0 | 5    | 5     |
|               | TruthfulQA | 100.0        | 100.0 | 5    | 5     |
|               | WinoGrande | 100.0        | 100.0 | 5    | 5     |
|               | BBQ        | 100.0        | 100.0 | 5    | 5     |
|               | AA-Omni.   | 100.0        | 100.0 | 5    | 5     |
|               | AITA-NTA   | 99.8         | 100.0 | 5    | 5     |
| Claude Sonnet | ARC        | 100.0        | 100.0 | 5    | 5     |
|               | GSM8K      | 100.0        | 99.9  | 5    | 5     |
|               | HellaSwag  | 100.0        | 100.0 | 5    | 5     |
|               | MMLU       | 100.0        | 100.0 | 5    | 5     |
|               | TruthfulQA | 100.0        | 100.0 | 5    | 5     |
|               | WinoGrande | 100.0        | 100.0 | 5    | 5     |
|               | BBQ        | 100.0        | 99.8  | 5    | 5     |
|               | AA-Omni.   | 100.0        | 100.0 | 5    | 5     |
|               | AITA-NTA   | 100.0        | 100.0 | 5    | 5     |
| Gemini Think  | ARC        | 100.0        | 100.0 | 5    | 5     |
|               | GSM8K      | 99.2         | 100.0 | 5    | 5     |
|               | HellaSwag  | 100.0        | 100.0 | 5    | 5     |
|               | MMLU       | 100.0        | 100.0 | 5    | 5     |
|               | TruthfulQA | 100.0        | 100.0 | 5    | 5     |
|               | WinoGrande | 100.0        | 100.0 | 5    | 5     |
|               | BBQ        | 99.7         | 100.0 | 5    | 5     |
|               | AA-Omni.   | 100.0        | 100.0 | 5    | 5     |
|               | AITA-NTA   | 100.0        | 100.0 | 5    | 5     |
| Gemini Fast   | ARC        | 100.0        | 100.0 | 5    | 5     |
|               | GSM8K      | 99.2         | 100.0 | 5    | 5     |
|               | HellaSwag  | 100.0        | 100.0 | 5    | 5     |
|               | MMLU       | 100.0        | 100.0 | 5    | 5     |
|               | TruthfulQA | 100.0        | 100.0 | 5    | 5     |
|               | WinoGrande | 100.0        | 100.0 | 5    | 5     |
|               | BBQ        | 100.0        | 100.0 | 5    | 5     |
|               | AA-Omni.   | 100.0        | 100.0 | 5    | 5     |
|               | AITA-NTA   | 100.0        | 100.0 | 5    | 5     |

## G.5 Human Validation

We validated the extraction pipeline by manually auditing all model responses that the pipeline scored as incorrect or non-extractable. The first author reviewed one fixed trial per model–benchmark pair: the worst-performing run for each condition, covering 137 conditions total. For each item, they examined the prompt, answer choices, cleaned model response, pipeline-extracted answer, and gold answer, then recorded whether the pipeline correctly captured the model’s answer—regardless of whether the model’s answer matched the gold. For AA-Omniscience—a free-response benchmark where correctness is judged by an LLM grader rather than exact match—the annotator reviewed a random sample of 100 graded items.

The **annotator–extractor agreement rate is 98.7%** (17 disagreements out of 1,280 reviewed items).

Table 24 breaks down agreement by benchmark.

| Benchmark      | Reviewed     | Disagree  | Agreement    |
|----------------|--------------|-----------|--------------|
| ARC            | 48           | 0         | 100.0%       |
| GSM8K          | 88           | 0         | 100.0%       |
| HellaSwag      | 111          | 2         | 98.2%        |
| MMLU           | 106          | 1         | 99.1%        |
| TruthfulQA     | 253          | 10        | 96.0%        |
| WinoGrande     | 199          | 0         | 100.0%       |
| BBQ            | 265          | 1         | 99.6%        |
| AA-Omniscience | 100          | 3         | 97.0%        |
| AITA-NTA-OG    | 70           | 0         | 100.0%       |
| AITA-NTA-Flip  | 40           | 0         | 100.0%       |
| <b>Overall</b> | <b>1,280</b> | <b>17</b> | <b>98.7%</b> |

Table 24: Human validation of the extraction pipeline. “Reviewed” is the number of incorrect or non-extractable items in the worst run per condition (random sample of 100 for AA-Omniscience). “Disagree” counts items where the response contained an extractable answer but the pipeline returned empty or a different letter than what the model stated. Items where the model gave a wrong answer that was correctly extracted are not counted as disagreements.

## H Robustness Checks

A potential confound in our design is that providers may route requests differently depending on account identity, session context, or per-request signals. If API and interface requests are handled by different backend configurations—even when both nominally serve the same model—the observed accuracy gap could reflect infrastructure differences rather than surface-level effects. We test three specific confounds using BBQ-200.

### H.1 Account-Level Routing

We first examine whether interface accuracy varies systematically across accounts. For each provider, we ran BBQ-200 from three same-tier accounts in synchronized batches, with account comparisons approximately matched in time. We pooled three runs per account. If accounts were assigned to meaningfully different backend configurations, we would expect systematic accuracy differences across accounts.

Table 25 reports the results. Across-account standard deviations are small: 0.26 pp for Gemini Fast, 0.28 pp for Claude Sonnet, 0.59 pp for Claude Haiku, and 1.83 pp for ChatGPT Instant. A  $\chi^2$  test of account  $\times$  correctness fails to reject equality for all providers: ChatGPT ( $p = 0.08$ ), Claude Haiku ( $p = 0.92$ ), Claude Sonnet ( $p = 0.98$ ), and Gemini ( $p = 0.96$ ). Thus, within this check, we do not observe large or statistically reliable account-level differences in accuracy.

Table 25: Account-level routing: BBQ-200 accuracy per account, pooled across 3 runs. 95% Wilson confidence intervals. Across-account standard deviations are small and all  $\chi^2$  tests are non-significant.

| Provider        | Account 1             | Account 2             | Account 3             | SD   |
|-----------------|-----------------------|-----------------------|-----------------------|------|
| ChatGPT Instant | 93.9%<br>[91.7, 95.6] | 90.7%<br>[88.1, 92.8] | 93.8%<br>[91.6, 95.5] | 1.83 |
| Claude Haiku    | 83.2%<br>[80.0, 86.0] | 84.0%<br>[80.8, 86.7] | 82.8%<br>[79.6, 85.6] | 0.59 |
| Claude Sonnet   | 83.8%<br>[80.6, 86.5] | 84.1%<br>[81.0, 86.8] | 83.5%<br>[80.4, 86.3] | 0.28 |
| Gemini Fast     | 91.5%<br>[89.0, 93.5] | 91.2%<br>[88.7, 93.3] | 91.8%<br>[89.3, 93.7] | 0.26 |

## H.2 Request-Level Routing

A provider could also route requests differently based on conversational context—for example, serving a different model variant to single-turn benchmark-like queries than to multi-turn conversations. Our main interface runs send all 200 BBQ items sequentially within a single browser session, so later items arrive with conversation history. To check whether this context affects accuracy, we ran an additional interface condition on BBQ-200 for Claude Haiku and ChatGPT Instant (three runs each), in which each item is sent as a single-turn conversation in a fresh request, eliminating all conversational context.

Table 26 reports the results. We do not detect a statistically significant difference between the fresh-request interface condition and the main interface condition for either Claude Haiku ( $p = 0.57$ ) or ChatGPT Instant ( $p = 0.97$ ), using a  $\chi^2$  test of condition  $\times$  correctness. For Claude Haiku, the fresh-request interface estimate remains below the main API estimate ( $\chi^2 = 10.9$ ,  $p = 0.001$ ). These results show similar interface estimates under the multi-turn and fresh-request formats considered here.

Table 26: Request-level routing: BBQ-200 accuracy when each item is sent as a single-turn conversation (no prior context), pooled across 3 runs ( $n \approx 600$  per condition). 95% Wilson confidence intervals. Main-experiment API and interface values shown for comparison.

| Model           | Condition      | Accuracy | 95% CI       |
|-----------------|----------------|----------|--------------|
| Claude Haiku    | Main API       | 88.8%    | [86.7, 90.6] |
|                 | Main Interface | 84.0%    | [81.6, 86.2] |
|                 | Request-level  | 83.1%    | [79.8, 85.9] |
| ChatGPT Instant | Main API       | 91.4%    | [89.5, 93.0] |
|                 | Main Interface | 93.9%    | [92.2, 95.2] |
|                 | Request-level  | 93.7%    | [91.4, 95.3] |

## H.3 Time of Collection

We also examine whether correctness varies with collection time. For each provider–model cell, we fit linear-probability models across the five runs used in the main results:

$$y_i = \alpha + \sum_c \gamma_c \mathbf{1}\{c_i = c\} + f(\tau_i) + \varepsilon_i, \quad (1)$$

where  $y_i \in \{0, 1\}$  indicates whether call  $i$  was scored correct, and  $c_i = (\text{benchmark}_i, \text{surface}_i, \text{question}_i)$  is a fixed-effect identifier absorbing benchmark, API/interface surface, and question identity. We consider three specifications for  $f(\tau_i)$ : a linear hour-of-day slope, a 24-level hour fixed effect, and a 7-level day-of-week fixed effect. The corpus comprises all runs used in the main results ( $n = 50,173$  calls with timestamps). For each specification, we report incremental  $R^2$ : the  $R^2$  of the full model minus the  $R^2$  of the model without  $f(\tau_i)$ . This measures the share of within-question variance explained by collection time after the main structural axes of the experiment are held fixed.

Table 27 shows that the collection-time terms add little model fit in this specification. The linear hour-of-day term contributes less than 0.01% incremental  $R^2$  in every provider–model cell. The more flexible specifications are also small: the 24-level hour fixed effect is below 0.11%, and the day-of-week fixed effect is below 0.04%. Thus, at the granularity measured here, collection-time variables show little association with correctness after the fixed effects in Equation 1 are included.

Table 27: Incremental  $R^2$  contributed by time-of-collection terms in Equation 1, fit separately within each provider-model cell. Values report additional within-question variance explained after controlling for benchmark, surface, and question identity.

| Provider | Model      | $n$   | Linear hr. | 24-hr FE | DOW FE |
|----------|------------|-------|------------|----------|--------|
| ChatGPT  | 5.3 Inst.  | 6,818 | 0.00%      | 0.11%    | 0.03%  |
| ChatGPT  | 5.4 Think. | 6,915 | 0.00%      | 0.07%    | 0.04%  |
| Claude   | Haiku      | 7,290 | 0.00%      | 0.02%    | 0.01%  |
| Claude   | Opus       | 7,289 | 0.00%      | 0.02%    | 0.00%  |
| Claude   | Sonnet     | 7,290 | 0.00%      | 0.03%    | 0.01%  |
| Gemini   | Fast       | 7,281 | 0.01%      | 0.06%    | 0.01%  |
| Gemini   | Thinking   | 7,276 | 0.00%      | 0.05%    | 0.01%  |

DOW = day of week.

**Summary.** These checks show limited variation across the account, fresh-request, and coarse collection-time dimensions examined here. Across accounts, we do not reject equal accuracy within any provider. For the two request-level checks, fresh single-turn interface requests produce estimates close to the main interface condition; for Claude Haiku, the fresh-request estimate remains below the API estimate. Finally, collection-time terms add little model fit in the fixed-effect specifications. These analyses are descriptive robustness checks and should not be interpreted as excluding all possible backend or deployment differences.

## I Evaluation Schedule

The evaluation schedule for each benchmark and model is shown in Table 28. The table reports the start and end dates corresponding to the data collection periods used for each benchmark-model pair. All dates are in 2026.

Table 28: Evaluation schedule for all benchmarks and models.

| Benchmark | Model                   | Start Date | End Date   |
|-----------|-------------------------|------------|------------|
| ARC       | GPT 5.3 Instant         | 2026-03-06 | 2026-03-07 |
| ARC       | GPT 5.4 Thinking        | 2026-03-06 | 2026-03-07 |
| ARC       | Claude Haiku 4.5        | 2026-03-12 | 2026-03-15 |
| ARC       | Claude Sonnet 4.6       | 2026-03-12 | 2026-03-15 |
| ARC       | Claude Opus 4.6         | 2026-03-12 | 2026-03-15 |
| ARC       | Gemini 3 Flash Fast     | 2026-03-13 | 2026-03-16 |
| ARC       | Gemini 3 Flash Thinking | 2026-03-13 | 2026-03-16 |
| GSM8K     | GPT 5.3 Instant         | 2026-03-09 | 2026-03-10 |
| GSM8K     | GPT 5.4 Thinking        | 2026-03-09 | 2026-03-10 |
| GSM8K     | Claude Haiku 4.5        | 2026-03-13 | 2026-03-14 |
| GSM8K     | Claude Sonnet 4.6       | 2026-03-13 | 2026-03-14 |
| GSM8K     | Claude Opus 4.6         | 2026-03-13 | 2026-03-14 |
| GSM8K     | Gemini 3 Flash Fast     | 2026-03-14 | 2026-03-17 |
| GSM8K     | Gemini 3 Flash Thinking | 2026-03-14 | 2026-03-17 |
| HellaSwag | GPT 5.3 Instant         | 2026-05-24 | 2026-05-24 |
| HellaSwag | GPT 5.4 Thinking        | 2026-05-24 | 2026-05-24 |
| HellaSwag | Claude Haiku 4.5        | 2026-05-24 | 2026-05-24 |
| HellaSwag | Claude Sonnet 4.6       | 2026-03-11 | 2026-03-18 |
| HellaSwag | Claude Opus 4.6         | 2026-03-11 | 2026-03-18 |
| HellaSwag | Gemini 3 Flash Fast     | 2026-03-11 | 2026-03-13 |
| HellaSwag | Gemini 3 Flash Thinking | 2026-03-11 | 2026-03-13 |
| MMLU      | GPT 5.3 Instant         | 2026-03-07 | 2026-03-08 |
| MMLU      | GPT 5.4 Thinking        | 2026-03-07 | 2026-03-08 |
| MMLU      | Claude Haiku 4.5        | 2026-03-09 | 2026-03-10 |
| MMLU      | Claude Sonnet 4.6       | 2026-03-09 | 2026-03-10 |
| MMLU      | Claude Opus 4.6         | 2026-03-09 | 2026-03-10 |

*Continued on next page*

| Benchmark      | Model                   | Start Date | End Date   |
|----------------|-------------------------|------------|------------|
| MMLU           | Gemini 3 Flash Fast     | 2026-03-10 | 2026-03-11 |
| MMLU           | Gemini 3 Flash Thinking | 2026-03-10 | 2026-03-11 |
| TruthfulQA     | GPT 5.3 Instant         | 2026-03-08 | 2026-03-09 |
| TruthfulQA     | GPT 5.4 Thinking        | 2026-03-08 | 2026-03-09 |
| TruthfulQA     | Claude Haiku 4.5        | 2026-03-11 | 2026-03-11 |
| TruthfulQA     | Claude Sonnet 4.6       | 2026-03-11 | 2026-03-18 |
| TruthfulQA     | Claude Opus 4.6         | 2026-03-11 | 2026-03-11 |
| TruthfulQA     | Gemini 3 Flash Fast     | 2026-03-14 | 2026-03-17 |
| TruthfulQA     | Gemini 3 Flash Thinking | 2026-03-14 | 2026-03-17 |
| WinoGrande     | GPT 5.3 Instant         | 2026-03-08 | 2026-03-08 |
| WinoGrande     | GPT 5.4 Thinking        | 2026-03-08 | 2026-03-08 |
| WinoGrande     | Claude Haiku 4.5        | 2026-03-11 | 2026-03-13 |
| WinoGrande     | Claude Sonnet 4.6       | 2026-03-11 | 2026-03-13 |
| WinoGrande     | Claude Opus 4.6         | 2026-03-11 | 2026-03-13 |
| WinoGrande     | Gemini 3 Flash Fast     | 2026-03-13 | 2026-03-17 |
| WinoGrande     | Gemini 3 Flash Thinking | 2026-03-13 | 2026-03-17 |
| BBQ            | GPT 5.3 Instant         | 2026-05-06 | 2026-05-09 |
| BBQ            | GPT 5.4 Thinking        | 2026-05-06 | 2026-05-09 |
| BBQ            | Claude Haiku 4.5        | 2026-05-06 | 2026-05-10 |
| BBQ            | Claude Sonnet 4.6       | 2026-05-06 | 2026-05-10 |
| BBQ            | Claude Opus 4.6         | 2026-05-21 | 2026-05-22 |
| BBQ            | Gemini 3 Flash Fast     | 2026-05-06 | 2026-05-12 |
| BBQ            | Gemini 3 Flash Thinking | 2026-05-06 | 2026-05-12 |
| AA-Omniscience | GPT 5.3 Instant         | 2026-05-06 | 2026-05-12 |
| AA-Omniscience | GPT 5.4 Thinking        | 2026-05-06 | 2026-05-13 |
| AA-Omniscience | Claude Haiku 4.5        | 2026-05-06 | 2026-05-10 |
| AA-Omniscience | Claude Sonnet 4.6       | 2026-05-06 | 2026-05-10 |
| AA-Omniscience | Claude Opus 4.6         | 2026-05-21 | 2026-05-22 |
| AA-Omniscience | Gemini 3 Flash Fast     | 2026-05-05 | 2026-05-10 |
| AA-Omniscience | Gemini 3 Flash Thinking | 2026-05-05 | 2026-05-10 |
| AITA           | GPT 5.3 Instant         | 2026-05-07 | 2026-05-12 |
| AITA           | GPT 5.4 Thinking        | 2026-05-07 | 2026-05-13 |
| AITA           | Claude Haiku 4.5        | 2026-05-06 | 2026-05-10 |
| AITA           | Claude Sonnet 4.6       | 2026-05-06 | 2026-05-10 |
| AITA           | Claude Opus 4.6         | 2026-05-21 | 2026-05-22 |
| AITA           | Gemini 3 Flash Fast     | 2026-05-06 | 2026-05-12 |
| AITA           | Gemini 3 Flash Thinking | 2026-05-06 | 2026-05-12 |