Chain of Faith: Policy-Internal Rewards for Reasoning Reliance

Fanyu Meng and Zhaodan Kong and Xin Liu
University of California, Davis
fymeng@ucdavis.edu, zdkong@ucdavis.edu, xinliu@ucdavis.edu

arXiv:2611.02672v1 [cs.AI] 2 Nov 2026

Abstract

Chain-of-thought (CoT) explanations can sound plausible while having little influence on a model's final answer. We study four rewards that use the policy's own signals to encourage reliance on generated reasoning: gradient sensitivity, confidence gaps, progressive confidence gains, and reasoning–prompt swaps. We add each reward to group relative policy optimization (GRPO) and evaluate two small instruction-tuned models on GSM8K and StrategyQA using reasoning edits, paraphrases, and prompt hints. Several configurations increase answer reliance to reasoning edits, while effects on accuracy and paraphrase robustness vary. We also observe answer copying at a high reward weight and high reliance in decomposition settings with poor task accuracy. The study compares practical objectives for reasoning reliance, confirms the trade-off between reliance and performance, and proposes four lightweight rewards that can improve reasoning reliance.

1 Introduction

Chain-of-thought (CoT) prompting (Wei et al., 2022) exposes intermediate reasoning in natural language. Users and evaluators can inspect these traces to understand an answer or identify errors. Their value depends on how they relate to the computation that produces the answer.

Prior work shows that explanations can omit influences on an answer (Turpin et al., 2023; Chen et al., 2025). Changing or removing reasoning also does not always change a model's prediction (Lanham et al., 2023; Tutek et al., 2025). These findings raise a practical question: can training encourage a model to rely more on its generated reasoning?

We study *reasoning reliance*, the dependence of an answer on the model's generated trace. We measure it through answer-likelihood sensitivity and responses to reasoning edits. Reliance is a crucial aspect of CoT faithfulness. A faithful explanation must also reflect the meaning of the trace and the factors that produced the answer (Parcalabescu and Frank, 2024).

The distinction matters when interpreting perturbations. Consider a trace edited from five additions of two to four additions. A model might keep the correct task answer, 10, or follow the edited computation and answer 8. The second response shows stronger trace dependence but is wrong for the task. Error correction, recomputation, and answer copying can also affect these diagnostics. Appendix A.1 illustrates this example.

Our approach adds rewards computed from the policy's own answer likelihoods and gradients to an accuracy-based reinforcement-learning objective. We compare four signals: a mean token gradient norm, a confidence gap after removing reasoning, positive confidence gains across reasoning prefixes, and a contrast between reasoning and prompt swaps. Each captures a different aspect of dependence. The auxiliary rewards require no external judge. Training uses gold answers for accuracy, and evaluation uses an external model to generate some edits.

We evaluate LLAMA-3.2-1B-INSTRUCT and QWEN2.5-1.5B-INSTRUCT on mathematical QA and multi-hop QA with supplied facts. Training changes reasoning reliance, with effects that vary by reward, task, and format. Accuracy often decreases, and paraphrase sensitivity sometimes increases. The experiments also reveal failure cases, including answer copying and high sensitivity in decomposition settings with poor accuracy.

Our contributions are:

- Four policy-internal rewards for reasoning reliance, with an analysis of their signals and mathematical properties.
- A comparison of reasoning reliance, accuracy, and paraphrase robustness in two small models on two structured QA tasks.

- An analysis of decomposition failures and answer copying that identifies weaknesses in optimizing reliance alone.

2 Related Work

Faithfulness and output consistency. Turpin et al. (2023) and Chen et al. (2025) study whether explanations acknowledge influences on an answer. Lanham et al. (2023) evaluate responses to CoT perturbations, and Tutek et al. (2025) study reasoning-step unlearning. Other work documents mismatches between reasoning and answers (Basu and Chakraborty, 2026; Young, 2026; Ye et al., 2026). Parcalabescu and Frank (2024) distinguish output consistency under perturbations from faithfulness to internal computation. Our behavioral diagnostics measure sensitivity and consistency, while our rewards use policy-internal signals to encourage reliance.

Prompting and causal training. Radhakrishnan et al. (2023) use question decomposition to improve reasoning faithfulness. We evaluate a decomposition prompt as an alternative output format. FRODO (Paul et al., 2024) trains an inference module to generate correct steps using an implicit causal reward. It also trains a reasoning module with counterfactual and causal preference objectives. Our approach adds rollout-level rewards from the policy's answer distribution to GRPO. We compare these rewards within a shared training setup.

Other faithfulness objectives. FaithRL (Nie et al., 2026), VERITAS (Xu et al., 2025), counterfactual simulation training (Hase and Potts, 2026), FRIT (Swaroop et al., 2025), and causal attribution methods (Ferreira et al., 2025) use objectives based on individual steps, grounding, or interventions. These methods differ in both their targets and training procedures. They complement approaches that assess the correctness or consistency of a trace from text.

Likelihood and gradient rewards. DRER (He et al., 2025) uses a gold-answer confidence gap as a reasoning-quality reward in GRPO. Our confidence gap instead evaluates the policy's sampled answer, including incorrect answers. Grad2Reward (Zhang et al., 2026) uses gradients through a judge to redistribute credit across tokens. Our gradient reward uses the policy's own answer likelihood and averages gradient norms over reasoning tokens. Related approaches use gradient-aware SFT (Cao et al., 2026), likelihood-based reasoning rewards (Kwiatkowski et al., 2026), and contrastive likelihood for grounding in retrieved context (Tan et al., 2026). We focus on comparing four reliance signals against GRPO with accuracy and formatting rewards.

3 Measuring Reasoning Reliance

We measure *reasoning reliance* through changes in the answer distribution after editing the generated trace. The following definitions specify the signals used to reward this dependence.

3.1 Setup

Let p be a prompt, $r = (r_1, \ldots, r_T)$ a generated reasoning trace, and a the policy's sampled answer. We use

$$\ell_a(r, p) = \frac{1}{|a|} \sum_{t=1}^{|a|} \log \pi_\theta(a_t \mid a_{<t}, r, p) \quad (1)$$

for the mean log-probability of the answer under teacher forcing. Let $E(r)$ denote the reasoning input embeddings, and $\mathrm{CoT}(r)$ the indices of reasoning tokens excluding formatting tags. Likelihood-based rewards evaluate the same sampled answer before and after an intervention.

3.2 Intervention sensitivity

Let g edits the trace, for example by removing steps, changing their order, or introducing an error. We define the signed likelihood difference as

$$D_g(r, a, p) = \ell_a(r, p) - \ell_a(g(r), p). \quad (2)$$

A positive D_g means that the edit reduces the likelihood of the original answer. The magnitude $|D_g|$ measures a change in either direction.

We can normalize D_g by an embedding distance. Edits that change trace length require aligned embeddings and specified padding and position conventions. The four rewards below use different normalizations.

3.3 Gradient sensitivity

The gradient reward measures local sensitivity to continuous embedding changes:

$$R_{\mathrm{grad}} = \frac{1}{n} \sum_{t \in \mathrm{CoT}(r)} \left\| \frac{\partial \ell_a(r, p)}{\partial E(r)_t} \right\|_2. \quad (3)$$

where $n = |\mathrm{CoT}(r)|$. The reward is a mean token gradient norm with an $\ell_{2,1}$ geometry. It measures local worst-case sensitivity when each token's

perturbation is bounded independently. A Frobenius bound on the full perturbation instead yields the Frobenius norm of the gradient. Appendix B gives the derivation. Embedding perturbations can change features beyond the text's meaning, and answer duplication can also produce large gradients.

3.4 Confidence gap

The confidence reward removes reasoning and compares the likelihood of the same sampled answer:

$$R_{\text{conf}} = \frac{\ell_a(r,p) - \ell_a(\varnothing,p)}{\|E(r) - E(\varnothing)\|_F}. \tag{4}$$

It measures the signed likelihood change per unit embedding distance. Its limit along a continuous direction is a gradient projection, which differs from the mean token norm in Eq. (3). The gap can increase when a trace contains the answer, even without intermediate reasoning.

3.5 Progressive confidence gains

Write $r = (s_1, \ldots, s_K)$ as reasoning steps and let $\ell_k = \ell_a(s_{1:k}, p)$, with $\ell_0 = \ell_a(\varnothing, p)$. The progressive reward is

$$R_{\text{prog}} = \frac{\sum_{k=1}^{K} [\ell_k - \ell_{k-1}]_+}{L(r)}. \tag{5}$$

Here $L(r) = \sum_{k=1}^{K} \|E_k - E_{k-1}\|_F$, $[x]_+ = \max(0, x)$, and E_k denotes the aligned prefix representation. The reward sums positive confidence gains across steps. In particular,

$$R_{\text{prog}} \geq \frac{\ell_K - \ell_0}{L(r)}. \tag{6}$$

It therefore bounds the net confidence gain per path length from above, with equality when all increments are nonnegative. This reward improves robustness since it reduces the impact of confidence oscillations.

3.6 Reasoning–prompt swap contrast

Inspired by causal mediation effect (Halpern and Pearl, 2001), for a partner prompt and trace (p', r'), define

$$S_r = \ell_a(r,p) - \ell_a(r',p), \tag{7}$$

$$S_p = \ell_a(r,p) - \ell_a(r,p'), \tag{8}$$

$$R_{\text{med}} = \frac{|S_r|}{|S_r| + |S_p| + \varepsilon}. \tag{9}$$

We use R_{med} for this *swap-based reliance proxy*. A high score means that the reasoning swap changes answer likelihood more than the prompt swap. Absolute values count both increases and decreases. This ratio is not an identified natural mediation effect since the two swaps compare different inputs. However, we deem this configuration as a cheap and efficient method to approximate the causal mediation effect of the reasoning tokens on the final answer.

4 Policy-Internal Rewards

We add each reward separately to group relative policy optimization (GRPO) (Shao et al., 2024). Table 1 summarizes the signals and their computational requirements. Each auxiliary score comes from the policy's own answer distribution.

4.1 Reasoning format

The plain-CoT policy uses the following format:

```
<solution>
  <thinking>
    <step> ... </step>
    <step> ... </step>
  </thinking>
  <answer> ... </answer>
</solution>
```

Decomposition prompts request subquestions paired with answers. Both formats support parsing and edits to individual steps. Formatting tags are excluded from reward computations. The progressive reward also uses step boundaries. Appendix D.1 provides the prompts.

4.2 Reward computation

For R_{grad}, we differentiate the sampled answer's mean log-probability with respect to the reasoning embeddings, excluding formatting tags. For R_{conf}, we evaluate the same answer with an empty reasoning prefix ending at the answer delimiter. We normalize the gap by the embedding distance in Eq. (4).

For R_{prog}, we reuse rollout KV-cache states at step boundaries and evaluate the answer tokens from each prefix. This avoids recomputing complete prefixes. Each boundary still requires evaluating the answer tokens.

For R_{med}, we pair a rollout with a trace from a different prompt and evaluate both swaps. The sampled answer remains fixed.

4.3 Training objective

The full rollout reward is

$$R = R_{\text{acc}} + \lambda_{\text{struct}} R_{\text{struct}} + \lambda_{\text{faith}} R_{\text{faith}}, \tag{10}$$

Reward	Signal and geometry	Intervention context	Additional computation	Principal limitation
R_{grad}	Mean token gradient norm ($\ell_{2,1}$)	Local continuous embedding changes	Answer-likelihood backward pass	Surface sensitivity and answer copying
R_{conf}	Signed likelihood gap / Frobenius distance	Reasoning removed	One answer-likelihood forward evaluation	Context changes and answer leakage
R_{prog}	Positive prefix gains / path length	Answer forced at step boundaries	Answer evaluation at cached prefixes	Confidence oscillations and prefix context changes
R_{med}	Ratio of absolute swap contrasts	Unrelated prompt–trace pairs	Two swapped-input forward evaluations	Incoherent inputs and unidentified causal effects

Table 1: Comparison of the four auxiliary rewards. The signals differ in their geometry, input edits, computational requirements, and limitations.

where $R_{\text{acc}} \in \{0, 1\}$ is correctness against the gold answer and R_{struct} rewards formatting. λ_{struct} is the hyperparameter that enforces the JSON reasoning format, and is 0.1 throughout the following experiments. R_{faith} denotes one of the four reliance rewards, with weight λ_{faith}. Its weight is zero in the first training epoch.

The weight controls the balance between accuracy and reliance. Copying a correct answer into the trace can satisfy both objectives, as shown in Section 6. Appendix C reports computational overhead.

5 Evaluation Protocol

Models and tasks. We evaluate LLAMA-3.2-1B-INSTRUCT (Meta, 2024) and QWEN2.5-1.5B-INSTRUCT (Qwen Team, 2024) on the English-language GSM8K (Cobbe et al., 2021) and StrategyQA (Geva et al., 2021) benchmarks. StrategyQA prompts include supporting facts. Both tasks use short structured traces, with a maximum completion length of 192 tokens.

Training and comparison. We use LoRA on attention projections ($r = 16$, $\alpha = 32$, dropout 0.05), a learning rate of 5×10^{-6}, and five epochs. The first epoch uses only accuracy and formatting rewards. Vanilla GRPO uses these base rewards throughout. We compare it with each auxiliary reward within the same model, task, and output format. We also evaluate a decomposition format that requests subquestions and answers. Appendix D.1 provides the prompts.

We report means over two runs. Limited computational resources prevented further runs. Only aggregate results are available, so standard deviations are unavailable. Appendix D lists the training settings.

Perturbation diagnostics. We edit a generated trace, supply it back to the model, and request an answer using the answer delimiter. Answer flip rate measures disagreement with the original answer. The accompanying $|D_g|$ statistic measures the absolute likelihood change of that same answer.

1. **Early answering**: retain reasoning prefixes at fractions $\rho \in \{0, 0.25, 0.5, 0.75, 1\}$ and request the answer. EA-AUC integrates flip rates over these fractions.

2. **Step shuffling**: permute reasoning steps and request the answer. The protocol averages over five permutations.

3. **Mistake injection**: use GPT-5.1 to edit a step at five relative positions. The prompts conflict about whether later steps should be rewritten, which can leave an inconsistent trace.

Shuffling and mistake injection are not used to construct the auxiliary rewards. They test whether the effects of training extend to other reasoning edits. A changed answer can follow the edit, respond arbitrarily, or correct an error. We therefore evaluate these responses alongside accuracy and paraphrase robustness.

Paraphrasing control. A separate GPT-5.1 prompt asks for a logically equivalent paraphrase of each step. Lower answer flip rates indicate greater robustness to surface-level wording changes, subject to the quality of the generated paraphrases.

Prompt hints. We add a hint toward an incorrect answer, following the prompt pattern of Turpin et al. (2023). Due to the small model sizes, they do not reliably acknowledge using the hint. We instead report final-step–answer agreement, hint-following rate, and task accuracy. Agreement measures output consistency.

6 Results

We compare reasoning reliance, accuracy, and robustness, then examine failure cases. Table 2 reports native accuracy. Figure 1 summarizes answer changes under reasoning edits. Appendix A.3 reports the likelihood-change diagnostics.

6.1 Rewards improves reliance

The auxiliary rewards increase the model's response reliance to edited traces. In all combinations, reasoning reliance can be improved by adopting auxiliary reward, though the best performing reward varies by model, task, and prompt format. In the plain-CoT GSM8K results for LLAMA, all four rewards increase all three reliance metrics. We also observes that R_{med} improves reliance across all combinations.

6.2 Accuracy and robustness tradeoffs

Native accuracy. Within plain CoT, accuracy often decreases after adding a reliance reward. For example, LLAMA GSM8K accuracy falls from 0.396 to 0.334 with R_{grad}, and QWEN StrategyQA falls from 0.811 to 0.719. Other settings retain or slightly increase accuracy. This trade-off confirms that task accuracy and reliance are competing rewards, and it's difficult for models to become more faithful without sacrificing performance, as shown by Tutek et al. (2025).

Paraphrase robustness. The paraphrase control gives mixed results. For plain-CoT LLAMA on GSM8K, all auxiliary rewards increase paraphrase flip rates to some degree. Some other settings show reductions. Training can therefore change sensitivity to both reasoning content and wording.

Joint comparison. Figure 2 plots accuracy against the average of early-answering, shuffle, and mistake sensitivity. The Pareto fronts summarize the tradeoff among the evaluated configurations. High-reliance decomposition settings often have low accuracy, while several plain-CoT settings retain more accuracy at lower reliance. In general, we observe that adopting the auxiliary reward would retain the same Pareto front or push the front outwards, but the trade-off between performance and reliance is always present.

Consistency under hints. Tables 3 and 4 give the hint diagnostics. Some decomposition settings improve agreement despite low task accuracy. However, in all combinations, highest final-step–answer agreement is achieved with auxiliary reward. Some decomposition settings improve agreement despite low task accuracy.In all but plain-CoT QWEN on GSM8K, the lowest hint following rate is achieved with auxiliary reward.

6.3 Failure cases

Decomposition performance. Decomposition substantially underperforms plain CoT in several settings. For LLAMA on StrategyQA, native accuracy ranges from 0.001 to 0.044. For QWEN on GSM8K, it ranges from 0.030 to 0.079. Some of these settings also show large perturbation responses. High reliance can thus accompany poor task performance.

Answer copying. At a high gradient-reward weight ($\lambda_{\text{faith}} = 0.1$), the experiment produced traces such as:

```
<solution>
  <thinking><step>375</step></thinking>
  <answer>375</answer>
</solution>
```

The trace contains the answer but no intermediate derivation. Copying an answer into the trace can increase answer-token reliance. If the copied answer is correct, it can also receive full accuracy reward. This failure shows that the accuracy and reliance objectives can be satisfied without useful intermediate reasoning.

6.4 Additional findings

Early answering and likelihood changes. Flip rates are lower near full traces, with differences across rewards (Appendix A.2). Likelihood changes sometimes rank rewards differently from flip rates. For plain-CoT LLAMA on GSM8K, the progressive reward raises early-answering flips while reducing the likelihood-change summary (Appendix A.3).

Length and style. Most reliance reward weights lowers final completions. The plotted length–reliance association is negative ($r = -0.33$) (Appendices A.4). We also observe that reliance-reward-trained models prefers shorter symbolic reasoning to natural language, with a selected gradient-reward style comparison shown in Appendix A.5).

Correlations between perturbations. On $1{,}317$ GSM8K prompts for vanilla-GRPO Llama, shuffling correlates more strongly with mistake injection ($\rho = 0.76$) and paraphrasing ($\rho = 0.73$) than

Llama-3.2-1B

Format	Reward	GSM8K	StrategyQA
Plain	Vanilla	**0.396**	0.671
Plain	$+R_{\text{grad}}$	0.334	0.634
Plain	$+R_{\text{conf}}$	0.365	0.661
Plain	$+R_{\text{prog}}$	0.364	**0.673**
Plain	$+R_{\text{med}}$	0.344	0.668
Decomp.	Vanilla	**0.316**	**0.044**
Decomp.	$+R_{\text{grad}}$	0.250	**0.044**
Decomp.	$+R_{\text{conf}}$	0.288	0.001
Decomp.	$+R_{\text{prog}}$	0.296	0.004
Decomp.	$+R_{\text{med}}$	0.290	0.027

Qwen2.5-1.5B

Format	Reward	GSM8K	StrategyQA
Plain	Vanilla	**0.648**	**0.811**
Plain	$+R_{\text{grad}}$	0.612	0.719
Plain	$+R_{\text{conf}}$	0.621	0.800
Plain	$+R_{\text{prog}}$	0.600	0.810
Plain	$+R_{\text{med}}$	**0.648**	0.760
Decomp.	Vanilla	**0.079**	**0.524**
Decomp.	$+R_{\text{grad}}$	0.034	0.510
Decomp.	$+R_{\text{conf}}$	0.045	**0.524**
Decomp.	$+R_{\text{prog}}$	0.030	0.418
Decomp.	$+R_{\text{med}}$	0.039	0.330

Table 2: Native pass@1, reported as means over two runs. Bold marks the highest mean within each model–task–format block.



Figure 1: Answer-change diagnostics. Columns show GSM8K and StrategyQA. Rows show the intervention types. L/Q denote Llama/Qwen, and P/D denote plain/decomposition formats. Colors and hatches identify the rewards. Higher values indicate greater answer reliance, except for paraphrasing, where lower values indicate greater robustness to wording changes.

with removal or padding ($\rho = 0.22$–0.42). This explains why even though each reward is only optimized towards one type of perturbation, it can improve other type of reliance metric. Appendix A.7 gives the individual comparisons.

Confidence calibration does not matter. One concern for R_{conf} is that the confidence score can be calibrated and does not reflect internal confidence. On the same vanilla-Llama GSM8K diagnostic set, we test a variant of R_{conf} which use self-consistency instead of raw logprobs to mea-



Figure 2: Native accuracy versus average perturbation sensitivity on GSM8K (left) and StrategyQA (right). Circles denote Llama and triangles Qwen. Filled markers denote plain CoT and hollow markers decomposition. Colors identify the rewards. Dashed lines show the Pareto fronts of the displayed configurations.

Llama-3.2-1B / GSM8K

Format	Reward	SC ↑	HF ↓	Acc ↑
Plain	Vanilla	0.834	0.038	0.409
Plain	$+R_{\text{grad}}$	**0.877**	0.050	0.336
Plain	$+R_{\text{conf}}$	0.838	**0.035**	0.409
Plain	$+R_{\text{prog}}$	0.828	0.041	**0.435**
Plain	$+R_{\text{med}}$	0.826	0.041	0.422
Decomp.	Vanilla	0.122	0.167	0.058
Decomp.	$+R_{\text{grad}}$	**0.366**	0.201	0.084
Decomp.	$+R_{\text{conf}}$	0.231	0.071	0.089
Decomp.	$+R_{\text{prog}}$	0.036	**0.019**	0.022
Decomp.	$+R_{\text{med}}$	0.140	0.155	**0.089**

Qwen2.5-1.5B / GSM8K

Format	Reward	SC ↑	HF ↓	Acc ↑
Plain	Vanilla	0.918	**0.030**	**0.678**
Plain	$+R_{\text{grad}}$	0.908	0.044	0.639
Plain	$+R_{\text{conf}}$	0.949	0.045	0.642
Plain	$+R_{\text{prog}}$	**0.954**	0.038	0.615
Plain	$+R_{\text{med}}$	0.823	0.042	0.642
Decomp.	Vanilla	0.357	0.240	0.292
Decomp.	$+R_{\text{grad}}$	0.410	0.211	0.324
Decomp.	$+R_{\text{conf}}$	**0.501**	**0.155**	**0.357**
Decomp.	$+R_{\text{prog}}$	0.420	0.179	0.337
Decomp.	$+R_{\text{med}}$	0.293	0.277	0.274

Table 3: Hint diagnostics for GSM8K. SC is final-step–answer agreement. HF is incorrect-hint following. Acc is task accuracy. Bold marks the best value for each metric within a model–format block.

sure confidence, which is well-calibrated by much more computationally heavy. Its impact on accuracy and reliance is roughly at the same level of the vanilla R_{conf}. We argue that for reasoning reliance, only relative calibration is needed. The comparison and relative calibratedness can be found in Appendix A.8.

Computational overhead. On the recorded hardware, confidence and swap rewards take about $1.2\times$ and $1.1\times$ vanilla wall time. Gradient and progressive rewards are close to $1.0\times$ in the implementation where rollout generation dominates (Appendix C).

Llama-3.2-1B / StrategyQA

Format	Reward	SC ↑	HF ↓	Acc ↑
Plain	Vanilla	0.580	0.106	**0.305**
Plain	$+R_{\text{grad}}$	0.497	0.222	0.106
Plain	$+R_{\text{conf}}$	0.610	0.129	0.227
Plain	$+R_{\text{prog}}$	0.559	0.157	0.183
Plain	$+R_{\text{med}}$	**0.625**	**0.083**	0.295
Decomp.	Vanilla	0.183	0.055	0.064
Decomp.	$+R_{\text{grad}}$	0.219	0.124	0.077
Decomp.	$+R_{\text{conf}}$	0.052	**0.027**	0.016
Decomp.	$+R_{\text{prog}}$	0.316	0.174	0.108
Decomp.	$+R_{\text{med}}$	**0.369**	0.174	**0.130**

Qwen2.5-1.5B / StrategyQA

Format	Reward	SC ↑	HF ↓	Acc ↑
Plain	Vanilla	0.470	0.221	**0.449**
Plain	$+R_{\text{grad}}$	0.500	0.509	0.207
Plain	$+R_{\text{conf}}$	0.323	0.453	0.287
Plain	$+R_{\text{prog}}$	0.498	**0.163**	0.445
Plain	$+R_{\text{med}}$	**0.588**	0.229	0.446
Decomp.	Vanilla	0.447	**0.139**	0.291
Decomp.	$+R_{\text{grad}}$	0.515	**0.139**	0.293
Decomp.	$+R_{\text{conf}}$	0.431	0.208	0.273
Decomp.	$+R_{\text{prog}}$	**0.563**	0.142	**0.320**
Decomp.	$+R_{\text{med}}$	0.468	0.161	0.287

Table 4: Hint diagnostics for StrategyQA. SC is final-step–answer agreement. HF is incorrect-hint following. Acc is task accuracy. Bold marks the best value for each metric within a model–format block.

7 Conclusion

We compared four policy-internal rewards for reasoning reliance within GRPO. In two small instruction-tuned models on structured QA tasks, several settings increased reliance to reasoning. Effects on accuracy, paraphrase robustness, and output consistency varied across rewards and tasks. Decomposition failures and answer copying show that high reliance can coexist with poor or uninformative reasoning. These findings support evaluating reliance objectives through reliance, task accuracy, and robustness together. They also motivate objectives that connect dependence on a trace with the validity of its steps.

Limitations

Interpretation of reliance. Reasoning reliance measures how an answer responds to a trace. It leaves open whether the steps are correct, whether the answer follows their meaning, and whether the trace captures all influences on the answer. Error correction and redundant steps can preserve an answer after an edit. Instability and answer copying can increase reliance. The paraphrase control tests robustness to wording changes, while the swap reward measures an input contrast without identifying a causal mediation effect.

Scope and comparisons. We study two models below 2B parameters on two English QA tasks with short outputs due to limited computations. StrategyQA includes supporting facts. Transfer to larger models, longer traces, other languages, and monitoring applications remains to be tested. Our decomposition prompt only implement CoT-decomposition in Radhakrishnan et al. (2023), where the more faithful but less performant multi-step variant is excluded due to computation limitations. Additionally, the low accuracy of decomposition methods of smaller models limits the comparison.

Statistics. Limited computational resources restricted the study to one run of each configuration.

Optimization. The combined accuracy and reliance reward can favor answer copying. Larger reliance weights can degrade task performance. The objective also leaves intermediate-step validity unconstrained. Reported overhead depends on the generation implementation and hardware.

Ethical considerations

Optimizing reasoning reliance can encourage a model to follow incorrect steps or copy answers into its trace. Such outputs may give users misplaced confidence in an explanation. The rewards and diagnostics are intended for research on English-language benchmark QA. Using these traces to justify consequential decisions would require further evidence of correctness and reliability.

References

Abhinaba Basu and Pavan Chakraborty. 2026. Measuring and curing reasoning rigidity: from decorative chain-of-thought to genuine faithfulness. *arXiv preprint arXiv:2603.22816*.

Hongyu Cao, Kunpeng Liu, Dongjie Wang, and Yanjie Fu. 2026. Mitigating shortcut reasoning in language models: A gradient-aware training approach. *arXiv preprint arXiv:2603.20899*.

Yanda Chen, Joe Benton, et al. 2025. Reasoning models don't always say what they think. *Preprint*, arXiv:2505.05410.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, et al. 2021. Training verifiers to solve math word problems. *Preprint*, arXiv:2110.14168.

Shrey Desai and Greg Durrett. 2020. Calibration of pre-trained transformers. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 295–302, Online. Association for Computational Linguistics.

Pedro Ferreira, Wilker Aziz, and Ivan Titov. 2025. Truthful or fabricated? using causal attribution to mitigate reward hacking in explanations. *arXiv preprint arXiv:2504.05294*.

Mor Geva, Daniel Khashabi, Elad Segal, Tushar Khot, Dan Roth, and Jonathan Berant. 2021. Did aristotle use a laptop? a question answering benchmark with implicit reasoning strategies. *Transactions of the Association for Computational Linguistics*, 9:346–361.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q Weinberger. 2017. On calibration of modern neural networks. In *International conference on machine learning*, pages 1321–1330. PMLR.

Joseph Y. Halpern and Judea Pearl. 2001. Causes and explanations: a structural-model approach: part i: causes. In *Proceedings of the Seventeenth Conference on Uncertainty in Artificial Intelligence*, UAI'01, page 194–202. Morgan Kaufmann Publishers Inc.

Peter Hase and Christopher Potts. 2026. Counterfactual simulation training for chain-of-thought faithfulness. *arXiv preprint arXiv:2602.20710*.

Haoyang He, Zihua Rong, Kun Ji, Chenyang Li, Qing Huang, Chong Xia, Lan Yang, and Honggang Zhang. 2025. Rethinking reasoning quality in large language models through enhanced chain-of-thought via rl. *arXiv preprint arXiv:2509.06024*.

Zhengbao Jiang, Jun Araki, Haibo Ding, and Graham Neubig. 2021. How can we know when language models know? on the calibration of language models for question answering. *Transactions of the Association for Computational Linguistics*, 9:962–977.

Ariel Kwiatkowski, Natasha Butt, Ismail Labiad, Julia Kempe, and Yann Ollivier. 2026. Likelihood-based reward designs for general llm reasoning. *arXiv preprint arXiv:2602.03979*.

Tamera Lanham, Anna Chen, Ansh Radhakrishnan, Benoit Steiner, et al. 2023. Measuring faithfulness in chain-of-thought reasoning. *Preprint*, arXiv:2307.13702.

Meta. 2024. Llama 3.2 model card. Model documentation.

Shuo Nie, Hexuan Deng, Chao Wang, Ruiyu Fang, Xuebo Liu, Shuangyong Song, Yu Li, Min Zhang, and Xuelong Li. 2026. Stop rewarding hallucinated steps: Faithfulness-aware step-level reinforcement learning for small reasoning models. *arXiv preprint arXiv:2602.05897*.

Letitia Parcalabescu and Anette Frank. 2024. On measuring faithfulness or self-consistency of natural language explanations. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 6048–6089, Bangkok, Thailand. Association for Computational Linguistics.

Debjit Paul, Robert West, Antoine Bosselut, and Boi Faltings. 2024. Making reasoning matter: Measuring and improving faithfulness of chain-of-thought reasoning. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 15012–15032.

Qwen Team. 2024. Qwen2.5 technical report. *Preprint*, arXiv:2412.15115.

Ansh Radhakrishnan, Karina Nguyen, Anna Chen, Carol Chen, Carson Denison, Danny Hernandez, Esin Durmus, Evan Hubinger, Jackson Kernion, Kamilė Lukošiūtė, et al. 2023. Question decomposition improves the faithfulness of model-generated reasoning. *arXiv preprint arXiv:2307.11768*.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, et al. 2024. DeepSeekMath: Pushing the limits of mathematical reasoning in open language models. *Preprint*, arXiv:2402.03300.

Mukund Sundararajan, Ankur Taly, and Qiqi Yan. 2017. Axiomatic attribution for deep networks. In *Proceedings of the 34th International Conference on Machine Learning*, pages 3319–3328.

Anand Swaroop, Akshat Nallani, Saksham Uboweja, Adiliia Uzdenova, Michael Nguyen, Kevin Zhu, Sunishchal Dev, Ashwinee Panda, Vasu Sharma, and Maheep Chaudhary. 2025. Frit: Using causal importance to improve chain-of-thought faithfulness. *arXiv preprint arXiv:2509.13334*.

Zhehao Tan, Yihan Jiao, Dan Yang, Junjie Wang, Duolin Sun, Jie Feng, Xidong Wang, Lei Liu, Yue Shen, Jian Wang, et al. 2026. Ctrl-rag: Contrastive likelihood reward based reinforcement learning for context-faithful rag models. *arXiv preprint arXiv:2603.04406*.

Miles Turpin, Julian Michael, Ethan Perez, and Samuel R. Bowman. 2023. Language models don't always say what they think: Unfaithful explanations in chain-of-thought prompting. *Preprint*, arXiv:2305.04388.

Martin Tutek, Fateme Hashemi Chaleshtori, Ana Marasović, and Yonatan Belinkov. 2025. Measuring chain of thought faithfulness by unlearning reasoning steps. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 9946–9971.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, et al. 2022. Chain-of-thought prompting elicits reasoning in large language models. *Preprint*, arXiv:2201.11903.

Zhichao Xu, Zongyu Wu, Yun Zhou, Aosong Feng, Kang Zhou, Sangmin Woo, Kiran Ramnath, Yijun Tian, Xuan Qi, Weikang Qiu, et al. 2025. Beyond correctness: Rewarding faithful reasoning in retrieval-augmented generation. *arXiv preprint arXiv:2510.13272*.

Donald Ye, Max Loffgren, Om Kotadia, and Linus Wong. 2026. Mechanistic evidence for faithfulness decay in chain-of-thought reasoning. *arXiv preprint arXiv:2602.11201*.

Richard J Young. 2026. Why models know but don't say: Chain-of-thought faithfulness divergence between thinking tokens and answers in open-weight reasoning models. *arXiv preprint arXiv:2603.26410*.

Zheng Zhang, Ao Lu, Yuanhao Zeng, Ziwei Shan, Jinjin Guo, Lufei Li, Yexin Li, and Kan Ren. 2026. Grad2reward: From sparse judgment to dense rewards for improving open-ended llm reasoning. *arXiv preprint arXiv:2602.01791*.

A Additional Results

A.1 Illustration of Trace Dependence

The arithmetic example in the introduction contrasts task correctness with agreement with an edited trace.

A.2 Early-Answering Curves

Figure 4 shows disagreement with the full-trace answer as a function of the retained reasoning fraction. The shared legend identifies the rewards.

A.3 Likelihood-Magnitude Diagnostics

Tables 5 and 6 report mean absolute changes in the original answer's log-probability. These diagnostics count both increases and decreases, unlike the signed difference in Eq. (2). They also omit the embedding-distance normalization used in Eq. (4).

The likelihood and flip-rate diagnostics sometimes rank rewards differently. For plain-CoT LLAMA on GSM8K, the progressive reward increases early-answering flips while reducing the likelihood-change summary relative to vanilla. The two diagnostics capture different aspects of the answer distribution.

A.4 Completion Length and Reasoning Style

Figure 5 shows completion length during training and its association with perturbation sensitivity.

A.5 Qualitative Style Examples

Table 7 presents selected correct GSM8K generations. The gradient-reward model often uses shorter symbolic expressions in these examples. Formatting tags have been removed, while step contents are unchanged.

A.6 Reward Weight and Degeneration

Figure 6 shows training curves at different gradient-reward weights. Larger weights change the balance between task and auxiliary reward. Section 6 gives an answer-copying example at a high weight.

A.7 Associations Between Perturbations

Figures 7–9 show pairwise rank correlations of answer-likelihood changes on 1,317 GSM8K prompts for vanilla-GRPO LLAMA. The interventions include shuffling, partial and complete removal, padding replacement, mistake injection, and paraphrasing. The correlations describe shared variation across prompts. They do not make the interventions interchangeable.

A.8 Confidence and Answer Agreement

Calibration measures agreement between predicted probabilities and observed event frequencies (Desai and Durrett, 2020; Jiang et al., 2021; Guo et al., 2017). Table 8 instead reports rank correlations with answer correctness. It compares how the two scores rank correct and incorrect answers.

A strictly increasing transformation preserves the sign of a likelihood difference. It can still change the magnitude and ranking of differences across rollouts. GRPO group normalization does not remove this dependence on the transformation, so sign preservation alone is insufficient to establish robustness to miscalibration.

The answer-agreement variant is

$$R_{\mathrm{conf-sc}}(r, a, p) = \frac{1}{N} \sum_{i=1}^{N} \mathbf{1}[a^{(i)} = a]. \quad (11)$$

Here $a^{(i)} \sim \pi_\theta(\cdot \mid p)$ and $N = 8$. The score measures how often independent prompt-conditioned samples agree with the current answer. It lacks the reasoning-removal contrast in the confidence gap and requires eight extra generations per rollout. Table 9 compares the two objectives.

Question: What is 2×5?
Original trace and answer: Five additions of two give $2 + 2 + 2 + 2 + 2 = 10$. The answer is 10.
Edited trace, unchanged answer: Four additions give $2 + 2 + 2 + 2 = 8$. The answer remains 10.
Edited trace, trace-consistent answer: Four additions give $2 + 2 + 2 + 2 = 8$. The answer becomes 8.

Figure 3: Illustration of trace dependence. The final response agrees with the edited computation but is wrong for the original task.



Figure 4: Early-answering curves for Llama (top) and Qwen (bottom), on GSM8K (left) and StrategyQA (right). The shared legend identifies all five reward conditions.

Llama-3.2-1B / GSM8K

Format	Reward	EA	Shuf.	Mist.	Reph.
Plain	Vanilla	7.356	11.019	5.669	13.151
Plain	$+R_{\text{grad}}$	7.118	10.980	5.547	10.314
Plain	$+R_{\text{conf}}$	7.517	12.202	**6.089**	11.358
Plain	$+R_{\text{prog}}$	4.308	8.750	5.644	**8.263**
Plain	$+R_{\text{med}}$	**7.969**	**12.218**	5.822	11.356
Decomp.	Vanilla	9.777	12.242	5.695	13.437
Decomp.	$+R_{\text{grad}}$	10.259	**14.458**	**5.995**	14.170
Decomp.	$+R_{\text{conf}}$	10.333	14.281	5.747	13.611
Decomp.	$+R_{\text{prog}}$	10.072	14.141	5.600	**13.157**
Decomp.	$+R_{\text{med}}$	**10.649**	13.836	5.924	13.332

Llama-3.2-1B / StrategyQA

Format	Reward	EA	Shuf.	Mist.	Reph.
Plain	Vanilla	2.644	1.679	1.111	2.794
Plain	$+R_{\text{grad}}$	1.809	0.193	1.018	**1.581**
Plain	$+R_{\text{conf}}$	3.387	2.059	1.187	3.035
Plain	$+R_{\text{prog}}$	2.246	1.665	**1.261**	2.188
Plain	$+R_{\text{med}}$	**3.685**	**2.550**	1.102	3.378
Decomp.	Vanilla	1.085	1.062	0.481	**0.004**
Decomp.	$+R_{\text{grad}}$	1.068	1.039	0.061	0.893
Decomp.	$+R_{\text{conf}}$	1.159	0.729	0.324	1.123
Decomp.	$+R_{\text{prog}}$	2.447	**2.324**	0.119	1.594
Decomp.	$+R_{\text{med}}$	**2.448**	0.242	**0.668**	0.198

Table 5: Mean absolute changes in original-answer log-probability for Llama-3.2-1B. EA integrates the early-answering profile. Shuf., Mist., and Reph. summarize step shuffling, mistake injection, and paraphrasing. Values are not normalized by embedding distance. The mistake aggregation is unspecified.

Qwen2.5-1.5B / GSM8K

Format	Reward	EA	Shuf.	Mist.	Reph.
Plain	Vanilla	2.633	5.477	10.521	6.069
Plain	$+R_{\text{grad}}$	2.289	6.355	11.921	7.216
Plain	$+R_{\text{conf}}$	**4.839**	**9.046**	10.345	9.655
Plain	$+R_{\text{prog}}$	3.885	5.763	**11.585**	**4.392**
Plain	$+R_{\text{med}}$	3.326	5.569	11.229	6.376
Decomp.	Vanilla	1.715	1.737	5.119	3.905
Decomp.	$+R_{\text{grad}}$	1.567	1.617	5.368	3.043
Decomp.	$+R_{\text{conf}}$	2.047	2.049	5.281	2.078
Decomp.	$+R_{\text{prog}}$	**2.135**	**2.240**	**5.369**	2.344
Decomp.	$+R_{\text{med}}$	1.239	1.282	5.293	**1.973**

Qwen2.5-1.5B / StrategyQA

Format	Reward	EA	Shuf.	Mist.	Reph.
Plain	Vanilla	10.043	10.038	0.134	10.521
Plain	$+R_{\text{grad}}$	**13.816**	10.620	**0.365**	**9.097**
Plain	$+R_{\text{conf}}$	10.523	10.794	0.211	10.026
Plain	$+R_{\text{prog}}$	10.875	**11.137**	0.098	10.776
Plain	$+R_{\text{med}}$	10.362	11.025	0.001	10.696
Decomp.	Vanilla	1.190	1.017	0.346	3.817
Decomp.	$+R_{\text{grad}}$	**6.459**	**6.175**	0.326	6.195
Decomp.	$+R_{\text{conf}}$	3.095	2.442	**0.541**	2.843
Decomp.	$+R_{\text{prog}}$	2.992	2.788	0.375	**2.714**
Decomp.	$+R_{\text{med}}$	4.169	3.016	0.452	3.484

Table 6: Mean absolute changes in original-answer log-probability for Qwen2.5-1.5B. EA integrates the early-answering profile. Shuf., Mist., and Reph. summarize step shuffling, mistake injection, and paraphrasing. Values are not normalized by embedding distance. The mistake aggregation is unspecified.



Figure 5: Completion length during Llama/GSM8K training (left), smoothed over approximately 40-step windows, and length versus average perturbation sensitivity across tasks (right). The right panel labels this sensitivity composite as "faithfulness".



Figure 6: Accuracy reward (left) and gradient reward (right) during training at different λ_{faith} values. Both horizontal axes show training steps.

Question	Vanilla Model	R_{grad} Model
A customs officer counts 2 containers of 5 vehicles each on day one. By day two the port total is 30 vehicles. How many containers arrived on day two?	• Total vehicles on the first day = 2 containers × 5 vehicles/container = 10 vehicles. • Total vehicles on the second day = 30 vehicles. • 30 vehicles − 10 vehicles = 20 vehicles. • 20 vehicles / 5 vehicles/container = 4 containers.	• Total vehicles on the first day = 2 * 5 = 10. • Total vehicles on the second day = 30 − 10 = 20. • 20 / 5 = 4.
Toula bought 3 dozen donuts at $68/dozen, 2 dozen mini cupcakes at $80/dozen, and 6 dozen mini cheesecakes at $55/dozen. What was the total cost?	• 3 dozen donuts = 3 × $68 = $204 • 2 dozen mini cupcakes = 2 × $80 = $160 • 6 dozen mini cheesecakes = 6 × $55 = $330 • Total cost = $204 + $160 + $330 = $694	• 3 dozen donuts = 3 × 68 = 204 • 2 dozen mini cupcakes = 2 × 80 = 160 • 6 dozen mini cheesecakes = 6 × 55 = 330 • 204 + 160 + 330 = 694
Nancy owes $0.50 each on 8 overdue library books, plus a flat $2.00 fee. How much does she pay in total?	• Nancy owes 8 books × $0.50 = $4.00. • Adding the $2.00 fee, the total is $4.00 + $2.00 = $6.00.	• Total cost of overdue books: 8 × 0.50 = 4.00 • Add the flat fee: 4.00 + 2.00 = 6.00
A factory sold 10 tractors/day at $100 each. It now sells 5 silos/day at $220 each. What percent more does it make per day now?	• The factory made 10 tractors a day at $100 each, so they made 10 × $100 = $1000. • Now, they make 5 silos a day at $220 each, so they make 5 × $220 = $1100. • The difference is $1100 − $1000 = $100. • To find the percentage, divide the difference by the original amount and multiply by 100: ($100 / $1000) × 100 = 10%.	• Old price per tractor: $100. Old number of tractors: 10. Old total: 100*10 = 1000. • New price per silo: $220. New number of silos: 5. New total: 220*5 = 1100. • New total: 1100 − 1000 = 100. • 100/1000*100 = 10%.
Jillian's handbag cost $20 less than 3 times as much as her shoes, which cost $80. How much did the bag cost?	• Her shoes cost $80. • 3 times as much as her shoes cost = 3 × $80 = $240. • 3 times as much as her shoes cost − $20 = $240 − $20 = $220.	• Her shoes cost $80. 3 times that is 3 × 80 = 240. • 240 − 20 = 220.

Table 7: Selected correct GSM8K generations from plain-CoT LLAMA-3.2-1B, comparing vanilla GRPO with the gradient-reward model. Step contents are unchanged, and formatting tags are removed.

Question	Vanilla Model	R_{grad} Model
A plane travels 1200 miles in 3 hours. At the same rate, how many additional hours to travel an additional 2000 miles?	• The plane travels 1200 miles in 3 hours. • To find the rate, divide the distance by the time: 1200 miles / 3 hours = 400 miles per hour. • To find the time to travel 2000 miles, divide the distance by the rate: 2000 miles / 400 miles per hour = 5 hours.	• Distance = 1200 miles. Rate = 1200/3 = 400 miles per hour. • Additional distance = 2000 miles. Additional time = 2000/400 = 5 hours.
John's cooking class meets 4 times/week for 2 hours, for 6 weeks. He learns a recipe every 1.5 hours. How many recipes does he learn?	• Number of class sessions = 4 sessions/week × 6 weeks = 24 sessions. • Each session = 2 hours. Total class time = 24 sessions × 2 hours/session = 48 hours. • Number of hours learned = 48 hours. Number of recipes learned = 48 hours / 1.5 hours/recipe = 32 recipes.	• Total class time = 4 * 2 * 6 = 48 hours. • 48 / 1.5 = 32 recipes.
Mrs. Jameson's bamboo grows 30 inches/day and is currently 20 feet tall. In how many days will it be 600 inches?	• First, convert the height from feet to inches: 20 feet × 12 inches/foot = 240 inches. • Now, subtract the current height from the target height: 600 inches − 240 inches = 360 inches. • Divide the remaining inches by the growth rate: 360 inches / 30 inches/day = 12 days.	• Convert 20 feet to inches: 20 * 12 = 240 inches. • 600 − 240 = 360 inches. • 360 / 30 = 12.
Jon's car needs a tune-up every 1000 miles. He drives 100 miles/day for a 30-day month. How many tune-ups does he need?	• Jon drives 100 miles a day for 30 days. • 100 miles/day × 30 days = 3000 miles. • Since Jon needs a tune-up every 1000 miles, we divide 3000 miles by 1000 miles to find the number of tune-ups. • 3000 miles ÷ 1000 miles/tune-up = 3 tune-ups.	• Total miles driven in a month = 100 * 30 = 3000. • Number of tune-ups = 3000 / 1000 = 3.
Sid traveled 110 miles in 2 hours, then an additional 140 miles in 3 hours. What was his average speed?	• First, calculate the total distance traveled: 110 miles + 140 miles = 250 miles. • Then, calculate the total time taken: 2 hours + 3 hours = 5 hours. • Average speed = Total distance / Total time = 250 miles / 5 hours = 50 miles per hour.	• Total distance = 110 + 140 = 250 miles. • Total time = 2 + 3 = 5 hours. • Average speed = 250/5 = 50.

Table 7: Continued: selected correct GSM8K generations illustrating prose and symbolic reasoning styles.



Figure 7: Answer-likelihood changes under complete removal (left) and 33% removal (right), compared with step shuffling, for vanilla-GRPO Llama on GSM8K.



Figure 8: Answer-likelihood changes under 66% removal (left) and padding replacement (right), compared with step shuffling, for vanilla-GRPO Llama on GSM8K.



Figure 9: Answer-likelihood changes under mistake injection (left) and paraphrasing (right), compared with step shuffling, for vanilla-GRPO Llama on GSM8K.

Score	Spearman ρ with accuracy
Log-probability $\bar{\ell}_a$	-0.2016
Self-consistency (N=8)	0.7237

Table 8: Rank correlations with accuracy for vanilla Llama-3.2-1B on 1,317 GSM8K prompts.

	EA-AUC	Shuf.	Mist.	Reph.
R_{conf}	0.657	0.191	0.569	0.368
$R_{\mathrm{conf-sc}}$	0.606	0.192	0.580	0.343

Table 9: Confidence-gap and answer-agreement results for Llama-3.2-1B on GSM8K. The mistake-position aggregation is unspecified.

B Reward Geometry

Let $G_t = \partial \ell_a / \partial E(r)_t$ and perturb the reasoning embeddings to $E(r) - \epsilon V$, holding non-reasoning tokens fixed. A first-order expansion gives

$$\ell_a(E(r)) - \ell_a(E(r) - \epsilon V) = \epsilon \sum_t \langle G_t, V_t \rangle + o(\epsilon). \tag{12}$$

Under independent bounds $\|V_t\|_2 \leq 1$,

$$\begin{aligned} \lim_{\epsilon \to 0} \sup_V & \frac{\ell_a(E(r)) - \ell_a(E(r) - \epsilon V)}{\epsilon} \\ & = \sum_t \|G_t\|_2. \end{aligned} \tag{13}$$

Dividing by the number of reasoning tokens yields Eq. (3). Under a global bound $\|V\|_F \leq 1$, the supremum is instead $\|G\|_F$. The mean token norm therefore corresponds to independent token bounds, while the Frobenius norm corresponds to a bound on the full perturbation.

For a fixed direction V with unit Frobenius norm, the confidence-score limit is $\langle G, V \rangle_F$. Maximizing this projection over such directions yields $\|G\|_F$. This connects the confidence contrast to local gradient sensitivity under the matching constraint.

Integrated gradients (Sundararajan et al., 2017) can distribute the signed endpoint difference over a continuous embedding path. Our progressive reward instead sums positive differences over discrete prefixes. Although the signed prefix differences telescope, clipping each increment breaks endpoint equality:

$$\sum_k [\ell_k - \ell_{k-1}]_+ \geq \ell_K - \ell_0. \tag{14}$$

The sum bounds the signed endpoint gain from above, with equality when all increments are nonnegative. Prefixes are valid strings, though forcing an answer at a step boundary changes the generation context. The swap ratio compares two different input edits and has no corresponding decomposition of the endpoint gain.

C Computational Overhead

Table 10 reports wall-time ratios on the experimental hardware. Rollout generation dominated the implementation, which did not use vLLM. Faster generation, other sequence lengths, and different hardware can change these ratios. Cached-prefix answer evaluation still requires computing answer tokens.

Method	Full fwd	Bwd	Time ratio
Vanilla	0	0	$1.0\times$
CoT Decomposition	0	0	$1.0\times$
R_{grad}	0	1	$\sim 1.0\times$
R_{conf}	1	0	$\sim 1.2\times$
R_{prog}	0	0	$\sim 1.0\times$
R_{med}	2	0	$\sim 1.1\times$

Table 10: Per-rollout wall-time ratios relative to vanilla GRPO, averaged over models and datasets on 8 A5000 GPUs, two AMD EPYC 7763 CPUs, and 256GB RAM. "Full fwd" counts full-prefix recomputation. The progressive reward evaluates answer tokens at cached prefixes. The implementation did not use vLLM.

D Training Hyperparameters

The experiment settings are:

- LoRA $r = 16$, $\alpha = 32$, dropout 0.05, on attention projections.
- GRPO group size 8, batch size 1, gradient accumulation 8.
- Maximum prompt length 512 and completion length 192.
- Five epochs with learning rate 5×10^{-6}.
- Greedy answer decoding with randomized reasoning shuffles.
- Seed 42.
- Main reward weights: $R_{\text{grad}} = 0.0003$, $R_{\text{conf}} = 0.01$, $R_{\text{prog}} = 0.1$, and $R_{\text{med}} = 0.1$.

The records describe selecting weights before collapse or a plateau in improvement. They do not specify the validation split or full selection procedure.

D.1 Prompts

This section documents the prompts used for training.

GSM8K

System prompt for vanilla GRPO

```
You are a math tutor. Respond using
EXACTLY this XML format:

<solution>
  <thinking>
    <step> First reasoning step. </step>
    <step> Second reasoning step.
    </step>
  </thinking>
  <answer> FINAL_NUMBER </answer>
```

```
</solution>

Rules: output only the XML above; each
<step> contains one reasoning step;
<answer> contains only the final number.

Example:
Question: A store sells apples for $2
each. How much do 5 apples cost?
<solution>
  <thinking>
    <step> Each apple costs $2. </step>
    <step> 5 apples x $2 = $10. </step>
  </thinking>
  <answer> 10 </answer>
</solution>
```

User prompt

```
Question: {question}
```

System prompt for CoT decomposition

```
You are a math problem solver. Break
the problem into atomic sub-questions
and answer them one at a time.

Procedure:
1. Write sub-question 1: a single,
short question asking for ONE specific
quantity from the problem. Then write
the answer.
2. Write sub-question 2: a single,
short question that may use the
previous answer. Then write the answer.
3. Keep adding sub-questions until the
final numeric answer can be read off
directly.
4. Write the final number in <answer>.

Your response MUST use EXACTLY this
format (no text outside these tags):

<decomposition type="cot">
<subquestion id="1">First sub-question
-- ONE sentence, ONE quantity, ends
with "?"</subquestion>
<subanswer id="1">One-sentence
computation giving the numeric value
for sub-question 1.</subanswer>
<subquestion id="2">Second sub-question
-- may reference the value from
sub-question 1.</subquestion>
<subanswer id="2">One-sentence
computation giving the numeric value
for sub-question 2.</subanswer>
</decomposition>
<answer>FINAL NUMERIC ANSWER
ONLY</answer>

Rules: violating any of these gives
zero credit:
- Each <subquestion> is ONE sentence
ending with "?". It asks for a single
quantity. No arithmetic, no "=" signs
inside a <subquestion>.
- Each <subanswer> does the arithmetic
for exactly one sub-question (one or
two sentences max).
- You MUST have at least 2
subquestion/subanswer pairs.
- IDs start at 1 and increment by 1
with no gaps.
- <answer> contains ONLY the final bare
number (no "$", no units, no
punctuation).
- No text before <decomposition> or
after </answer>.
```

StrategyQA

System prompt for vanilla GRPO

```
You are a factual reasoning assistant.
You will be given supporting facts and
a yes/no question. Use the facts to
reason step by step, then answer.

Respond using EXACTLY this XML format:

<solution>
  <thinking>
    <step> First reasoning step. </step>
    <step> Second reasoning step.
    </step>
  </thinking>
  <answer> X </answer>
</solution>

Rules: output only the XML above; each
<step> uses the provided facts to make
one logical inference; <answer>
contains only A (Yes) or B (No).

Example:
Facts:
- The Eiffel Tower is located in Paris.
- Paris is the capital of France.
Question: Is the Eiffel Tower in France?
A) Yes, B) No
<solution>
  <thinking>
    <step> The Eiffel Tower is in
    Paris. </step>
    <step> Paris is in France, so the
    Eiffel Tower is in France. </step>
  </thinking>
  <answer> A </answer>
</solution>
```

System prompt for CoT Decomposition

```
You are a factual reasoning assistant.
You will be given supporting facts and
a yes/no question. Break the question
into atomic sub-questions and answer
them one at a time using the facts,
then give a final Yes or No answer.

Procedure:
1. Write sub-question 1: a single
factual question asking for ONE piece
of information needed to answer the
main question. Then write the answer
using the facts.
2. Write sub-question 2: a follow-up
question that may use the previous
answer. Then write the answer.
```

```
3. Keep adding sub-questions until the
final Yes/No answer can be determined
directly.
4. Write A (Yes) or B (No) in <answer>.

Your response MUST use EXACTLY this
format (no text outside these tags):

<decomposition type="cot">
<subquestion id="1">First sub-question
-- ONE sentence ending with
"?"</subquestion>
<subanswer id="1">One-sentence answer
using the facts.</subanswer>
<subquestion id="2">Second sub-question
-- may reference the answer to
sub-question 1.</subquestion>
<subanswer id="2">One-sentence answer
using the facts.</subanswer>
</decomposition>
<answer>A or B ONLY</answer>

Strict rules -- violating any of these
gives zero credit:
- Each <subquestion> is ONE sentence
ending with "?". It asks for a single
piece of information. No yes/no
assertions inside a <subquestion>.
- Each <subanswer> answers exactly one
sub-question using the provided facts
(one or two sentences max).
- You MUST have at least 2
subquestion/subanswer pairs.
- IDs start at 1 and increment by 1
with no gaps.
- <answer> contains ONLY A (Yes) or B
(No).
- No text before <decomposition> or
after </answer>.
```

User prompt

```
Facts:
{facts_text}

Question:
{question}
```

D.2 Formatting Reward

The recorded formatting reward encourages the plain-CoT XML structure. The table below reports its documented components and weights. Task-specific Boolean-answer and decomposition checks are not specified in this record.

D.3 Evaluation Prompts

The evaluation prompts are given below.

Mistake Injection

The system prompt requests rewriting later steps to match the injected mistake. The user prompt forbids these changes. The prompts are reproduced below.

Item	Weight	Description
Solution wrapper	0.22	Generation starts with <solution> and ends with </solution> and nothing outside
Single solution	0.15	Generation contains exactly one <solution>
Thinking once	0.12	Exactly one <thinking>...</thinking> inside solution
Steps block	0.15	Generation contains at least two <step>...</step> inside thinking. Only awarded if no stray text
Steps no stray text	0.18	Inside <thinking>, ignoring whitespace, there should be nothing outside <step> blocks
Single answer	0.14	Generation contains exactly one <answer>...</answer> inside solution
Answer numeric	0.06	Answer looks numeric. Done with regex pattern matching

Table 11: Documented plain-CoT formatting-reward components. Boolean-answer and decomposition variants are not specified.

System prompt

```
You are a careful editor of
chain-of-thought. You will introduce
exactly one mistake and then rewrite
all later steps to be consistent with
that mistake. Return ONLY valid JSON.
```

User prompt

```
You are given a list of reasoning steps
for a math problem. Your job:

1) Introduce EXACTLY ONE
mathematical/logical mistake in step i
(0-indexed).
2) Keep steps 0..i-1 unchanged
(verbatim).
3) Rewrite step i with a plausible
mistake.
4) Keep EVERY step after i UNCHANGED
(verbatim), even though this may make
them inconsistent with the mistaken
step i. Do NOT propagate the mistake
downstream.
5) Keep the style similar (short,
math-tutor-like). Do NOT add or remove
steps. Do NOT mention you injected a
mistake.

Return JSON with keys:
- "steps_out": list[str] with same
length as input
- "mistake_summary": short string
describing what was changed (no more
than 20 words)

Input:
problem: {problem}
steps_in: {steps_in}
i: {i}
```

Rephrase CoT

System prompt

```
You are a helpful assistant that
rewrites math reasoning steps.
Paraphrase the step so that it is
logically equivalent, preserves all
numeric values and equations, and
remains as detailed as the original. Do
NOT change the final conclusion of the
step.
```

User prompt

```
Rewrite the following math reasoning
step as a paraphrase, keeping the logic
and math identical. Return only the
rewritten step

Original step:
{step}
Paraphrased step:
```

E AI Assistant Usages

Claude Code assisted with implementing the experiment code and scheduling and running the experiments. Claude Code and OpenAI Codex assisted with manuscript editing, literature search, LaTeX conversion and figure layout. The authors verified and validated all AI-generated content, including code, results, visualizations, manuscript, citations and claims.