

EDGE: Error Dependency Graph-Guided Multi-Error Attribution in Multi-Agent LLM Systems

Jun Hou Priya Pitre Yi Fang Xuan Wang

Virginia Tech

{junh, priyapitre, yif, xuanw}@vt.edu

Abstract

Large language model (LLM) agent failures often contain multiple related errors rather than a single mistake. Existing attribution methods usually identify a responsible agent, step, or root cause, but do not explicitly model dependency between errors. We introduce **EDGE**¹, an **Error Dependency Graph**-guided multi-Error attribution framework. EDGE constructs an error dependency graph from observed error events and validates a reliable causal subset through counterfactual rollout. The inference graph guides a two-stage LLM-as-judge detector for error attribution, and the intervention-validated subgraph provides a more reliable basis for explanation and repair analysis. Experiments on TRAIL and MAST show that EDGE improves category-level multi-error attribution across most evaluated models and settings. Experiments with adapted Who&When-style prompts show that the graph helps across prompting strategies. These results suggest that dependency structure is a useful diagnostic prior for agent failures beyond isolated root-cause prediction.

1 Introduction

Large language model (LLM) agents are increasingly used for complex multi-step tasks that involve planning, retrieval, tool use, and reasoning. For failed executions, the final outcome indicates task failure, but rarely explains how the failure developed. Recent work has therefore moved toward trace-level failure attribution, which identifies the step and error behind a failed execution (Zhang et al., 2025; Barke et al., 2026; Ma et al., 2025; Wang et al., 2026b; Zhu et al., 2026). These methods center on single-error attribution and do not provide full step-level multi-error annotation.

TRAIL reflects a newer direction by providing fine-grained span-level annotations for multiple er-




Figure 1: Errors in agent traces form dependency cascades ($e_1 \rightarrow e_3 \rightarrow e_4$). Unlike single-locus attribution, EDGE detects the downstream errors via a taxonomy-level dependency graph.

rors in each failed trace (Deshpande et al., 2025). Within a failed trace, errors play distinct structural roles, with some as upstream triggers, others as downstream effects, and others as parallel symptoms (Figure 1). These relations recur across traces, motivating a dependency graph constructed from the full corpus. When extended for multi-label output, single-error methods are inefficient and treat each error as an isolated target without modeling how one error makes another more likely. We therefore study multi-error attribution as dependency-aware diagnosis, where the dependency structure guides efficient and effective attribution and the validated subset supports explanation.

To achieve this goal, we frame multi-error attribution as dependency-aware diagnosis. We use within-trace ordering and cross-trace regularity to capture how error categories recur and propagate across failed executions. Based on this view, we introduce **EDGE**, an error dependency graph-guided framework for multi-error attribution in LLM agent traces. EDGE constructs an error dependency graph from observed error events, validates selected edges through counterfactual rollout, and uses the resulting graph to guide a two-stage de-

¹Code and experimental artifacts are available at <https://github.com/JuneHou/EDGE>.

tector. The first stage predicts an initial error set, and the second stage verifies downstream errors suggested by the graph. Score-filtered observational edges improve detection coverage, while intervention-validated edges provide a more reliable structure for explanation and repair analysis. This role separation lets EDGE use observational edges to broaden attribution coverage when intervention evidence is limited, while preserving the causal interpretability of the validated subset.

We evaluate EDGE on TRAIL (Deshpande et al., 2025) and MAST (Cemri et al., 2026), two benchmarks with distinct error taxonomies that cover span-level and trace-level multi-error attribution settings, demonstrating that the pipeline is taxonomy-agnostic. Across these benchmarks, EDGE improves category-level attribution for most evaluated models and settings. Additional experiments with adapted Who&When-style prompts show that the inferred graph can guide different attribution formats, rather than only one detector prompt. Our contributions are threefold. First, we formulate multi-error attribution as dependency-aware diagnosis for LLM agent traces. Second, we construct an error dependency graph from observed error events and inject it into a two-stage LLM-as-judge detector. Third, we separate prediction from explanation using $\mathcal{G}_\tau$ for attribution coverage and the intervention-validated subgraph $\mathcal{G}_V$ for repair and propagation analysis.

2 Related Work

Failure Attribution in Agent Systems Error attribution in agent systems studies how to identify the step, agent, or error instance most responsible for a failed execution trace. This work focuses on the LLM-reasoning paradigm emphasized in recent surveys of agent trajectory analysis (Wang et al., 2026a). Early reasoning-based attribution methods explore how the LLM reads and organizes the trace. Who&When (Zhang et al., 2025) formulates attribution as direct trajectory reasoning, while other methods improve this paradigm through hierarchical context, iterative adjudication, and structured causal prompting (Banerjee et al., 2025; Zhu et al., 2026; West et al., 2025). AgentErrorBench and AgentDebug further introduce a modular agent-error taxonomy, annotated failure trajectories, and attribution-oriented debugging from root-cause feedback (Zhu et al., 2025). Recent work has further introduced causal struc-

ture into LLM-based attribution. CDC-MAS (Ma et al., 2025) uses multi-granularity causal inference, CHIEF (Wang et al., 2026b) prompts an LLM to generate hierarchical causal graphs with counterfactual screening, and AgentRx (Barke et al., 2026) combines constraint-based evidence with LLM judgment for more auditable diagnosis. These attribution and debugging methods move beyond surface-level reasoning, but they still primarily target a single decisive error, critical step, or local root cause behind the final failure outcome. EDGE instead models failed traces as multi-error propagation, where earlier errors can make later errors more likely through an inferred dependency structure over error categories.

Sparse Event Progression Modeling Learning propagation structure from event data studies how earlier events are statistically or causally associated with later events in accumulative or cascading processes. Some work learns temporal influence and causal structure from timestamped events using Hawkes processes, temporal point processes, or Granger-style predictability (Cai et al., 2021; Qiao et al., 2023; Wu et al., 2024), and recent representation-based methods further learn temporal causal structures through latent regimes, sample-level relations, multimodal representations, or causal sequence prediction (Chen et al., 2025; Rahmani and Frossard, 2025; Math and Lienhart, 2026; Li et al., 2025). However, agent-error traces are sparse, partially ordered, and semantic rather than dense continuous streams, so intensity-based event progression learning is suboptimal here. Representation-based approaches additionally require data and modeling assumptions that do not fit compact LLM-detector guidance (Constantinou et al., 2021). Suppes-style accumulative progression modeling was applied to cancer progression by CAPRESE (Loohuis et al., 2014) and CAPRI (Rammazzotti et al., 2015), with TRONCO providing a modular implementation (De Sano et al., 2016). It constructs correlation-based dependency hypotheses from sparse events using temporal priority and probability raising. EDGE adopts this view to infer category-level propagation structure from recurring error-event patterns across traces.

3 Method

EDGE models error propagation in multi-error agent traces. Given span-level annotations of error event types and locations, we first formalize




Figure 2: Overview of EDGE. **(Left)** An observational correlation graph $\mathcal{G}_S$ and a sparse causal-candidate graph $\mathcal{G}_C$ are inferred from event statistics via Suppes screening and CAPRI pruning. **(Middle)** Causal-candidate edges in $\mathcal{G}_C$ are validated by counterfactual rollout, yielding $\mathcal{G}_V$; score-filtered correlation edges from $\mathcal{G}_S$ are unioned with $\mathcal{G}_V$ to form $\mathcal{G}_\tau$. **(Right)** Two-stage detection: Stage 1 predicts with full-graph context; Stage 2 verifies downstream categories reachable from Stage-1 predictions.

the multi-error attribution task, then construct an observational correlation graph $\mathcal{G}_S$ and a causal-candidate graph $\mathcal{G}_C$ over error categories, validate a trustworthy causal anchor with targeted interventions, and finally build an inference graph that augments this anchor with score-filtered correlation edges (Figure 2). Section 3.1 formalizes the task and notation. Section 3.2 describes the two observational graphs ($\mathcal{G}_S$, $\mathcal{G}_C$) built from temporal precedence and probability raising. Section 3.3 introduces intervention-based edge validation. Section 3.4 presents how the selected propagation graph is incorporated into graph-guided error detection. We use $\mathcal{G}_\tau$ (validated $\cup$ score-filtered correlation from $\mathcal{G}_S$) as the default detector input and additionally report $\mathcal{G}_V$ (validated only) as an ablation alternative. A complete symbol summary is provided in Appendix A.1.

3.1 Problem Setup

Let a trace $T = (s_1, s_2, \dots, s_N)$ denote a sequence of spans ordered by execution time. Each trace is annotated with a set of error events $E(T) = \{(c_j, \ell_j)\}$, where $c_j \in \mathcal{C}$ is an error category from an arbitrary multi-error taxonomy $\mathcal{C}$ and ℓ_j is the string identifier of the span at which that error first emerges, evaluated by exact match. Its position in the execution order $(s_1, \dots, s_N)$ supplies the temporal ordering used internally by the candidate-graph construction (Section 3.2). The goal is to predict, for each trace, a set of category-location pairs $\hat{E}(T)$.

We represent error-category dependencies with

a directed graph $\mathcal{G} = (\mathcal{C}, \mathcal{R})$, where $\mathcal{R}$ is a set of directed propagation edges. Each node is an error category and each edge $A \rightarrow B$ denotes a hypothesized propagation relation from source error A to downstream error B . We distinguish observational propagation edges from intervention-validated edges, which are interpreted as empirically supported causal propagation links.

3.2 Observational Graph Construction

We adopt the Suppes-Bayes Causal Network construction of CAPRI (Ramazzotti et al., 2015) (as implemented in the TRONCO package (De Sano et al., 2016)), which first prima-facie-filters edges by Suppes’ temporal-priority and probability-raising conditions (Suppes, 1970) and then prunes the Suppes-screened graph by a regularized likelihood score, to construct an observational correlation graph $\mathcal{G}_S$ and a causal-candidate graph $\mathcal{G}_C$ over error categories. The key adaptation is to treat error-category occurrences as progression events while using step annotations to derive category-level event variables for temporal-order estimation. Let $\mathcal{T}$ denote the set of annotated traces, then for each trace $T \in \mathcal{T}$ and category $A \in \mathcal{C}$, we define

$$X_A(T) = 1[\exists(c, \ell) \in E(T) : c = A], \quad (1)$$

where $X_A(T) = 1$ indicates that error category A occurs anywhere in trace T , and we write $t_A(T)$ for the first-event index of A (formal definition in Appendix A.2). Tied events are retained, but do not support strict temporal direction.

Suppes-based Candidate Screening. We first identify *prima facie* candidate edges using Suppes’ probabilistic theory of causation (Suppes, 1970). For a directed pair $A \rightarrow B$, we require both temporal priority and probability raising. Let $\mathcal{T}_{AB}$ denote the set of traces in which both A and B are present without ties. Because our annotations provide event order within each trace, we estimate temporal priority by aggregating precedence evidence across co-occurring traces, and operationalize Suppes’ probability-raising condition as the difference in B ’s conditional occurrence rate:

$$\text{Prec}(A, B) = \frac{|\{T \in \mathcal{T}_{AB} : t_A(T) < t_B(T)\}|}{|\mathcal{T}_{AB}|}. \quad (2)$$

$$\Delta_{\text{PR}}(A, B) = P(X_B=1 \mid X_A=1) - P(X_B=1 \mid X_A=0). \quad (3)$$

We retain $A \rightarrow B$ when both criteria exceed predefined thresholds with sufficient joint support (Appendix A.2). The output of this stage is the *observational correlation graph* $\mathcal{G}_S = (\mathcal{C}, \mathcal{R}_S)$, whose edges represent observational propagation hypotheses. For each surviving edge $A \rightarrow B \in \mathcal{R}_S$ (both criteria positive), we derive a propagation weight given by the geometric mean of the two screening scores,

$$w_S(A, B) = \sqrt{\text{Prec}(A, B) \cdot \Delta_{\text{PR}}(A, B)}, \quad (4)$$

which is used for inference-time edge ranking (Section 3.4). Threshold is reported in Appendix A.2.

CAPRI-based Graph Pruning. The Suppes screen produces $\mathcal{G}_S$, but it may retain indirect or transitive dependencies. We therefore apply a CAPRI-style score-based pruning procedure to obtain a sparser *causal-candidate graph*, selected from the search space of directed acyclic graphs (DAGs)

$$\Omega(\mathcal{R}_S) = \{\mathcal{G} : \mathcal{G} \text{ is a DAG and } \mathcal{R} \subseteq \mathcal{R}_S\}. \quad (5)$$

Each category node is modeled as a binary event conditioned on its parent set, using the occurrence variables $X_A(T)$. We select the causal-candidate graph $\mathcal{G}_C = (\mathcal{C}, \mathcal{R}_C)$ as the minimizer over $\Omega(\mathcal{R}_S)$ of an AIC-style score that combines the maximized log-likelihood of the binary category-event model with a parameter-count penalty. The full objective, optimization, and Suppes threshold values are deferred to Appendix A.2.

3.3 Intervention-based Graph Validation

To strengthen causal interpretation, we validate $\mathcal{G}_C$ edges with counterfactual interventions.

Controlled Counterfactual Rollout. For each candidate edge $A \rightarrow B \in \mathcal{R}_C$, we collect the trace set $\mathcal{T}_{A \prec B}$ where $t_A(T) < t_B(T)$. We intervene on the source span $s_{t_A(T)}$ using an LLM-based repair module that applies a category-specific patch template to rewrite the span’s input or output and eliminate A . We then run the counterfactual rollout with all tool outputs held to their original values, so only the patched span and its downstream reasoning change. A repair verifier (Judge A) labels each rollout with $\text{resolved}_A(T) \in \{0, 1\}$ ($= 1$ iff A is removed). Only rollouts with $\text{resolved}_A(T) = 1$ enter effect estimation. Because tool outputs are held fixed, any downstream change in B is attributable to the patch on A , so the effect estimate captures the *controlled direct effect* of A on B along the agent’s reasoning path (Pearl, 2022). Patch templates, postchecks, Judge-A prompts, and hyperparameters are in Appendix A.2.

Edge Effect Estimation and Validation. For each verified rollout, an effect evaluator (Judge B) labels whether B remains present in the continuation. Let $X_B^{\text{cf}}(T; A) \in \{0, 1\}$ denote this Judge-B label. We estimate the downstream reduction effect of edge $A \rightarrow B$ as the boolean risk-difference

$$\Delta(A \rightarrow B) = \mathbb{E}_{T \in \mathcal{T}_{A \prec B}^{\text{ver}}} [X_B(T) - X_B^{\text{cf}}(T; A)], \quad (6)$$

where $\mathcal{T}_{A \prec B}^{\text{ver}} \subseteq \mathcal{T}_{A \prec B}$ retains only traces with $\text{resolved}_A(T) = 1$. We retain $A \rightarrow B$ to form $\mathcal{G}_V = (\mathcal{C}, \mathcal{R}_V)$ when $\Delta(A \rightarrow B) > \tau_{\text{val}}$ (Appendix A.2). The validated graph $\mathcal{G}_V$ serves two roles: one is the trustworthy causal anchor retained in all thresholded inference graphs, so observational edges augment rather than replace intervention evidence, and another is an interpretable propagation map for post-hoc explanation, repair prioritization, and system-level debugging.

3.4 Graph-Guided Error Detection

With both observational and intervention-validated propagation graphs, our downstream detector follows an LLM-as-judge format augmented with structured graph guidance. Given a trace T and taxonomy $\mathcal{C}$, a baseline judge $\mathcal{J}$ receives the serialized trace together with the definitions of categories and predicts a set of errors.

Inference Graph Selection. The causal-only graph $\mathcal{G}_V$ is maximally interpretable, but it may lack strong correlations that are visible observationally yet difficult to validate by intervention in available sample sizes. We therefore construct a thresholded inference graph by taking the union of score-filtered correlation edges from $\mathcal{G}_S$ and all intervention-validated causal edges:

$$\mathcal{R}_\tau = \{A \rightarrow B \in \mathcal{R}_S : w_S(A, B) \geq \tau\} \cup \mathcal{R}_V, \quad (7)$$

and write $\mathcal{G}_\tau = (\mathcal{C}, \mathcal{R}_\tau)$. Each selected edge is passed to the detector with a propagation weight w_{AB} ,

$$w_{AB} = \begin{cases} \max(\Delta(A \rightarrow B), 0) & \text{if } (A, B) \in \mathcal{R}_V, \\ w_S(A, B) & \text{otherwise,} \end{cases} \quad (8)$$

so validated edges contribute their reduction effect, while pure-observational edges contribute their Suppes geomean. Both quantities lie in $[0, 1]$, allowing for a single propagation threshold τ_{GI} in Stage 2 ((11)). The resulting graph $\mathcal{G}_\tau$ keeps the validated causal anchor intact and extends it with score-filtered correlation edges. The ablation in §4.2 also reports $\mathcal{G}_V$ as an alternative option.

EDGE Trace-Conditioned Graph Guidance.

The graph from previous steps provides a holistic error dependency pattern across the corpus. EDGE therefore uses a progressive attribution procedure that activates this pattern per trace to surface plausible downstream errors. In the first stage, the judge receives the trace, taxonomy, and full graph guidance, and returns an initial prediction:

$$\hat{E}^{(1)}(T) = \mathcal{J}(T, \mathcal{C}, \mathcal{R}_\tau). \quad (9)$$

$$D(T) = \{c : \exists \ell, (c, \ell) \in \hat{E}^{(1)}(T)\}. \quad (10)$$

We then derive a trace-specific edge subset by aggregating selected edges from detected source categories onto undetected targets:

$$\mathcal{R}_\tau^{(T)} = \left\{ A \rightarrow B \in \mathcal{R}_\tau : \begin{aligned} &A \in D(T), B \notin D(T), \\ &\sum_{A' \in D(T)} w_{A'B} > \tau_{GI} \end{aligned} \right\}. \quad (11)$$

where τ_{GI} is the graph-injection threshold, which controls which downstream hypotheses are exposed in Stage 2. The subset $\mathcal{R}_\tau^{(T)}$ retrieves downstream hypotheses from the fixed detector graph $\mathcal{G}_\tau$ according to the Stage-1 error profile.

When $\mathcal{R}_\tau^{(T)}$ is non-empty, a second stage issues a targeted prompt that lists the Stage-1 predictions as already detected, presents $\mathcal{R}_\tau^{(T)}$ as trace-specific guidance, and instructs the judge to output only errors whose category does not appear in $D(T)$. We denote this Stage-2 prediction by $\hat{E}^{(2)}(T)$. The final prediction $\hat{E}^{\text{EDGE}}(T)$ merges Stage 1 with the Stage-2 entries whose categories were not already covered in Stage 1. The fixed graph is not updated at inference time, and only the edge subset exposed in the second stage is conditioned on the trace (details in Appendix A.4).

This two-stage design turns the selected graph from a passive context block into an explicit refinement mechanism. Stage 1 uses the full graph to produce an initial error profile. Stage 2 converts that profile into a restricted set of plausible hypotheses and verifies whether those errors are supported by the trace. For span-level localization benchmarks, we additionally prepend a compact span-identifier index to ground predicted locations. To validate the necessity of Stage 2, we compare against a naive variant that prepends the full graph as static, trace-agnostic context in a single LLM call (the +CG ablation; Table 2).

4 Experiments

4.1 Experimental Setup

We evaluate EDGE on two public benchmarks **TRAIL** (Deshpande et al., 2025) and **MAST** under their original terms. Details about these two benchmarks, eleven open- and close-weight backbones, the compute budget, and the software packages used are listed and cited in Appendix A.9. Downstream evaluation follows the native prediction target of each benchmark. TRAIL is evaluated as span-level multi-error attribution, requiring both error category and location, whereas MAST is evaluated as trace-level multi-label error classification without step prediction. For MAST, we additionally annotate the first occurrence of each error category solely for event-based graph construction (refer to Appendix A.3 for details).

Graph Construction Protocol. We construct one dependency graph per taxonomy from all annotated traces, with categories as nodes and aggregate temporal, probability-raising, and intervention-supported relations as edges, capturing the holistic dependency pattern of the taxonomy. The graph contains no trace-specific labels, spans, evidence,

Model	Method	TRAIL-GAIA			TRAIL-SWE-Bench			MAST			
		F1	Loc	Joint	F1	Loc	Joint	F1	Precision	Recall	Acc
Mistral-Small-3.1-24B	Baseline	24.06	23.83	3.78	9.80	9.36	1.57	37.73	29.87	31.50	62.01
	EDGE	34.15	25.71	12.27	14.40	7.59	0.87	38.29	28.55	34.59	59.86
	Δ	+10.09	+1.88	+8.49	+4.60	-1.77	-0.70	+0.56	-1.32	+3.09	-2.15
GPT-oss-120B	Baseline	25.76	16.92	4.59	22.08	2.58	0.00	17.84	26.28	9.47	67.02
	EDGE	37.20	28.00	9.48	30.07	1.60	0.00	27.21	29.27	18.74	64.14
	Δ	+11.44	+11.08	+4.89	+7.99	-0.98	0.00	+9.37	+2.99	+9.27	-2.88
GPT-oss-20B	Baseline	23.28	6.29	2.61	9.31	0.50	0.00	17.66	26.26	9.65	67.29
	EDGE	33.28	12.28	4.09	29.89	1.23	0.43	22.34	29.31	13.34	66.96
	Δ	+10.00	+5.99	+1.48	+20.58	+0.73	+0.43	+4.68	+3.05	+3.69	-0.33
Gemma-3-27B-IT	Baseline	16.25	1.79	0.33	11.39	0.21	0.00	14.19	18.32	5.84	69.13
	EDGE	21.26	11.20	0.73	15.41	1.47	0.00	21.17	26.97	11.37	68.10
	Δ	+5.01	+9.41	+0.40	+4.02	+1.26	0.00	+6.98	+8.65	+5.53	-1.03
Qwen Family*	Baseline	12.40	3.92	0.27	2.14	0.00	0.00	16.08	28.46	9.02	66.80
	EDGE	26.57	17.32	4.13	10.33	0.42	0.00	15.61	29.50	7.94	67.78
	Δ	+14.17	+13.40	+3.86	+8.19	+0.42	0.00	-0.47	+1.04	-1.08	+0.98
Gemini-2.5-Pro	Baseline	33.51	35.68	13.74	26.66	6.42	1.35	34.99	31.11	25.49	63.77
	EDGE	42.13	30.15	15.26	38.97	16.58	2.01	41.57	29.04	32.97	60.79
	Δ	+8.62	-5.53	+1.52	+12.31	+10.16	+0.66	+6.58	-2.07	+7.48	-2.98
Gemini-2.5-Flash	Baseline	37.07	34.22	12.71	8.71	0.63	0.00	24.41	26.91	16.59	64.06
	EDGE	30.26	23.81	7.40	21.91	1.79	0.00	40.34	29.64	34.11	60.32
	Δ	-6.81	-10.41	-5.31	+13.20	+1.16	0.00	+15.93	+2.73	+17.52	-3.74
GPT-4o	Baseline	18.73	7.45	2.45	16.72	4.19	1.33	22.87	28.00	14.78	65.32
	EDGE	28.31	10.87	1.99	26.51	1.25	0.00	29.96	31.67	20.48	64.96
	Δ	+9.58	+3.42	-0.46	+9.79	-2.94	-1.33	+7.09	+3.67	+5.70	-0.36

Table 1: Main results across both benchmarks. **F1** is weighted-F1 on both benchmarks, with the rest macro-averaged. **TRAIL-GAIA / TRAIL-SWE-Bench**: span-level multi-error attribution; **Loc** location accuracy, **Joint** location-category joint accuracy. **MAST**: trace-level multi-label yes/no over 13 categories on 393 AG2 traces. **EDGE**: thresholded inference graph (TRAIL $\tau=0.35$; MAST $\tau=0.50$) with two-stage dynamic injection. Δ : per-cell difference (EDGE – Baseline). All metrics in %. ***Qwen Family** combines the best single-benchmark model per side: QwenLong-L1-32B on TRAIL + QwQ-32B (with enable_thinking) on MAST.

or task answers, and remains fixed during detection. At inference time, the initial error predictions are used to retrieve only downstream hypotheses whose source categories were detected (Stage-1), and a second judge call only verifies those hypotheses against the trace (Stage-2). We therefore interpret the setup as taxonomy-level dependency-guided attribution with controlled context, avoiding trace-specific label leakage.

For each benchmark, we compare baseline against EDGE with the inference graph $\mathcal{G}_\tau$ (Defined in Section 3.4). A observational-edge threshold τ is shared across all backbones within each benchmark and selected by model-averaged weighted F1 over a small candidate grid. This yields $\tau=0.35$ for TRAIL and $\tau=0.50$ for MAST. Ablations on neighboring thresholds, causal-only graphs, and random controls are in Appendix A.5. We report weighted-F1, Loc, and Joint on TRAIL, and weighted-F1, macro-precision, macro-recall, and macro-accuracy on MAST.

4.2 Main Results

Table 1 evaluates EDGE on span-level (TRAIL) and trace-level (MAST) multi-error attribution. On TRAIL, EDGE substantially improves attribution. Gemini-2.5-Pro achieves the strongest results, with 42.13 F1 on GAIA and 38.97 on SWE-Bench, while open-weight models show large F1 gains (up to +21 on SWE for GPT-oss-20B). Though graph guidance reliably enhances category detection, exact localization on long-context SWE-Bench remains difficult (Deshpande et al., 2025). On MAST, graph guidance transfers effectively, lifting F1 for GPT-4o (22.87 $\rightarrow$ 29.96) and all open-weight backbones (up to +9.4) except QwQ-32B. However, the accuracy is traded for the gains, with accuracy decreasing on 7 of 8 backbones (−0.33 to −3.74) while recall rises on the same 7 of 8 (+3.09 to +17.52). The imbalanced distribution of the 13 binary category decisions per trace, of which only 30.5% are positive, means accuracy is best read




Figure 3: Graph-richness ablation on TRAIL-GAIA across both headline metrics. Three variants: random-12 (edge-count-matched control with no causal screening), causal-only ($\mathcal{G}_V$, intervention-validated edges), and correlation $\mathcal{G}_\tau$ at $\tau=0.35$.

alongside recall rather than alone.² Results for two newest backbones, GPT-5 and Qwen3.6-35B-A3B, are reported in Appendix A.6, where EDGE improves F1 in all six cells under the identical configuration. Stage-2 rates in Appendix A.5.

To confirm that these gains come from the *structure* of the learned graph rather than from prepending any block of edges, we ablate against a random-12 control (matched edge count, no causal screening) alongside the validated-only $\mathcal{G}_V$ and the inference $\mathcal{G}_\tau$. Across the five open-weight backbones in Figure 3, random-12 underperforms the inference graph on 4 of 5 and $\mathcal{G}_\tau$ at $\tau=0.35$ takes the F1 peak on 4 of 5 (Gemma-27B is the lone exception, where causal-only wins F1).

Static Graph Guidance (+CG) Ablation. We next test whether the gains require the two-stage consumption of the graph or merely access to it. The +CG ablation prepends the identical edge set $\mathcal{R}_\tau$ as static, trace-agnostic context in a single LLM call (Appendix A.4). Table 2 shows that +CG is inconsistent against the no-graph baseline of Table 1—helping on some cells (e.g., +6.8 F1 on Mistral-3.1 TRAIL-GAIA, +12.0 on Gemma-3 TRAIL-SWE-Bench) but degrading on others (e.g., −10.8 on GPT-oss-20B TRAIL-GAIA, −3.2 on Qwen MAST)—and underperforms EDGE on 14 of 15 backbone cells (the exception is Gemma-3-27B-IT on TRAIL-SWE-Bench), confirming that the trace-conditioned two-stage design, rather than static graph access, is the operational lever; the mechanism analysis is in Appendix A.4.

²An always-“no” classifier scores 69.5% accuracy, above every cell in Table 1.

Held-out Graph Validation. To rule out the possibility that the observed gains arise from constructing the graph using evaluation traces, we repeat the pipeline with a stratified 80/20 train/test split for each benchmark. The learned graph is rebuilt from the training side only, so the detector is scored only on the held-out traces. Table 3 reports the result: EDGE improves weighted-F1 in all four cells spanned by two representative backbones, by +8.40 and +2.40 in TRAIL and +1.91 and +12.41 in MAST. The graph signal is transferable to traces it never saw, and the improvements in Table 1 are not explained by fitting the evaluation corpus.

4.3 Comparison with Who&When-Style Attribution

To evaluate if the learned EDGE graph improves multi-error attribution across different prompting strategies, we adapt Who&When’s ALL-AT-ONCE and STEP-BY-STEP regimes, preserving their original output spaces and stopping criteria. Details can be found in Appendix A.7.




Figure 4: Who&When-style adaptation on TRAIL across both splits and both headline metrics. Color = strategy (blue ALL-AT-ONCE, pink STEP-BY-STEP); slope direction (filled dot above or below open dot) shows whether the graph helps or hurts.

First, we observe that across the five open-weight backbones, graph guidance consistently benefits both TRAIL splits. ALL-AT-ONCE+GRAPH improves F1 across nearly all of them (Figure 4). STEP-BY-STEP+GRAPH yields uniform gains on SWE-Bench, boosting larger models such as GPT-

Model	Method	TRAIL-GAIA			TRAIL-SWE-Bench			MAST			
		F1	Loc	Joint	F1	Loc	Joint	F1	P	R	Acc
Mistral-Small-3.1-24B	+CG	30.81	27.21	12.74	7.46	1.42	0.00	37.71	28.43	30.21	63.89
	EDGE	34.15	25.71	12.27	14.40	7.59	0.87	38.29	28.55	34.59	59.86
	Δ	+3.34	-1.50	-0.47	+6.94	+6.17	+0.87	+0.58	+0.12	+4.38	-4.03
GPT-oss-120B	+CG	28.96	17.85	6.88	23.78	0.42	0.00	21.63	28.49	12.53	66.12
	EDGE	37.20	28.00	9.48	30.07	1.60	0.00	27.21	29.27	18.74	64.14
	Δ	+8.24	+10.15	+2.60	+6.29	+1.18	0.00	+5.58	+0.78	+6.21	-1.98
GPT-oss-20B	+CG	12.49	7.23	0.60	12.59	0.42	0.00	18.05	27.76	10.39	67.78
	EDGE	33.28	12.28	4.09	29.89	1.23	0.43	22.34	29.31	13.34	66.96
	Δ	+20.79	+5.05	+3.49	+17.30	+0.81	+0.43	+4.29	+1.55	+2.95	-0.82
Gemma-3-27B-IT	+CG	17.58	7.63	0.20	23.39	0.36	0.00	12.17	25.26	5.39	68.72
	EDGE	21.26	11.20	0.73	15.41	1.47	0.00	21.17	26.97	11.37	68.10
	Δ	+3.68	+3.57	+0.53	-7.98	+1.11	0.00	+9.00	+1.71	+5.98	-0.62
Qwen Family	+CG	16.22	7.72	2.48	5.00	0.00	0.00	12.85	32.26	5.92	68.66
	EDGE	26.57	17.32	4.13	10.33	0.42	0.00	15.61	29.50	7.94	67.78
	Δ	+10.35	+9.60	+1.65	+5.33	+0.42	0.00	+2.76	-2.76	+2.02	-0.88

Table 2: Single-stage Static Graph Guidance (+CG) vs. EDGE on the five open-weight backbones; Δ = EDGE – +CG. +CG prepends the same inference graph ($\tau=0.35$ TRAIL, $\tau=0.50$ MAST) as a static context block in one call. Columns, metrics, and the no-graph baseline follow Table 1. All metrics in %.

Model	Method	TRAIL (25 held-out traces)			MAST (74 held-out records)			
		F1	Loc	Joint	F1	Precision	Recall	Acc
Mistral-Small-3.1-24B	Baseline	24.74	27.11	3.31	34.53	26.90	27.28	58.73
	EDGE	33.14	26.00	7.60	36.44	27.50	29.33	59.15
	Δ	+8.40	-1.11	+4.29	+1.91	+0.60	+2.05	+0.42
GPT-oss-120B	Baseline	31.08	4.67	1.60	22.09	36.73	12.87	67.46
	EDGE	33.48	9.33	4.13	34.50	39.27	22.15	66.01
	Δ	+2.40	+4.66	+2.53	+12.41	+2.54	+9.28	-1.45

Table 3: Stratified 80/20 split per benchmark. The detector is scored on the untouched held-out traces. TRAIL combines the GAIA and SWE-Bench splits. All metrics in %.

oss-120B, while exhibiting minor volatility on GAIA for GPT-oss-20B. Furthermore, a graph-guided variant achieves the best MAST F1 across all model blocks shown in Appendix A.7. **Overall, the EDGE graph demonstrates strong transferability across various prompting templates.**

4.4 Causal Graphs as Explanatory Artifacts

The preceding results evaluate graph guidance as a prediction prior. Next, we examine the explanatory role of the intervention-validated graph $\mathcal{G}_V$. The inference graph $\mathcal{G}_\tau$ augments $\mathcal{G}_V$ with score-filtered observational edges to improve detection coverage, but those added edges are not all causal. They can recover missing downstream categories, but may also overclaim propagation to categories without causal evidence, and their reliability may not transfer under distribution shift. The validated graph $\mathcal{G}_V$, by contrast, is explanation-oriented. Each edge is supported by controlled counterfactual rollout in which repairing the source error reduces the downstream target. We therefore use $\mathcal{G}_\tau$ for detection

and reserve $\mathcal{G}_V$ for explanation, repair prioritization, and propagation analysis.

Figure 5 visualizes the intervention-validated propagation graph $\mathcal{G}_V$ for TRAIL and MAST, and reveal intervention-backed propagation between error categories rather than mere co-occurrence. For example, a TRAIL edge *Formatting Errors* $\rightarrow$ *Context Handling Failures* indicates that correcting the upstream formatting issue reduced later context-handling failures in counterfactual rollout. Analogously on MAST, *Action-Reasoning Mismatch* $\rightarrow$ *Premature Termination* identifies an upstream repair target before the agent loop ends prematurely. The propagation graphs reveal two main findings. First, the propagation chain can guide agent repair strategy, where fixing upstream nodes with many validated outgoing effects (highlighted in Figure 5) reduces more downstream errors than repairing the symptoms directly. Second, the graph exposes vulnerable parts of the agent system by surfacing recurring upstream causes. Beyond the predictive




Figure 5: Intervention-validated propagation graphs $\mathcal{G}_V$ for (a) TRAIL and (b) MAST. Arrows are causal edges supported by counterfactual rollout; arrow width $\propto |\Delta(A \rightarrow B)|$; node color = top-level taxonomy parent; columns = topological generations (propagation reads left-to-right). Thick-bordered nodes source a propagation chain of length ≥ 3 edges.

contribution of $\mathcal{G}_T$, the causal graph $\mathcal{G}_V$ adds a trustworthy and inspectable propagation structure for system-level repair.

4.5 Error Attribution Analysis

To probe whether EDGE’s gains concentrate on the categories its causal graph is designed to surface, we route each of the 638 gold-error instances on the TRAIL-GAIA split into one of four mutually exclusive outcome buckets defined by which method attributed it. We show this transition in Figure 6 for three backbones spanning open- and closed-source, GPT-oss-120B, Mistral-Small-3.1-24B, and Gemini-2.5-Pro, adopting the parent category in the TRAIL taxonomy as the analysis unit. We aggregate the buckets into recall (gold errors correctly attributed within each parent category) so cross-method gains are directly comparable. On all three backbones, the +EDGE-only bucket is dominated by Planning & Coord., yielding the largest recall jump (GPT-oss-120B 9.0%→46.6%, Mistral 7.4%→31.2%, Gemini-2.5-Pro 26.5%→50.8%), with Reasoning second. System Execution barely moves on GPT-oss-120B and drops on Mistral and Gemini-2.5-Pro. This pattern aligns with the topol-




Figure 6: Per-error attribution transitions on TRAIL-GAIA ($n=638$ gold-error *instances* flagged by annotators, not traces). Each error flows from its TRAIL parent (left) into one of four buckets defined by which method attributed it: **Both**, **+EDGE only**, **Baseline only**, or **Neither**. Ribbon width is proportional to count.

ogy of $\mathcal{G}_V$, where Planning errors are downstream targets recovered by Stage 2, Reasoning errors are intermediate nodes with moderate gains, and System errors are upstream sources whose local cues benefit less from graph guidance. Detailed examples are in Appendix A.8.

5 Conclusion

We presented EDGE, a graph-guided framework for multi-error attribution in LLM agent traces that constructs and exploits an error dependency graph. EDGE is taxonomy-agnostic, so the construction and detection pipeline can be rerun for any error taxonomy with observed error events. Experiments on TRAIL and MAST show that the inference graph improves category-level multi-error attribution across both span-level and trace-level settings. These results show that error dependencies provide useful structure beyond isolated label prediction. By exposing how local failures propagate, EDGE supports more explainable debugging, upstream repair prioritization, and more reliable improvement of long-horizon agent systems.

Limitations

Our evaluation is best interpreted as taxonomy-level dependency-guided attribution. Because most agent-error annotation identifies only a single root error, corpora with multi-error annotations remain scarce and have low per-category support, so the dependency graph is constructed from the full annotated corpus and remains fixed during detection, containing only aggregate category-level dependencies rather than trace-specific labels, spans, or task answers. Repair verification, effect evaluation, and MAST event annotation rely on LLM judgments, which may introduce noise. Because the graph is estimated from category co-occurrence, it helps more with detecting which error events occur than with localizing them along the trajectory, and the localization gains are correspondingly smaller, staying close to flat on the long-context SWE-Bench split.

Our intervention validation holds tool outputs fixed, so each estimated edge effect reflects error propagation along the agent’s reasoning path rather than mediation through downstream tool re-execution. Intervention validation is also limited by the number of co-occurring traces per candidate edge, so we extend the validated causal subset with additional correlation-supported edges to maintain coverage. The validated causal subset alone serves as the more reliable structure for explanation and repair analysis.

The MAST event annotations are automatically produced and not fully human-validated. Coverage is reported but does not measure event-position correctness, and noisy positions may affect temporal-priority estimates and the inferred graph. Fully human-validated event annotations would strengthen future evaluation.

EDGE applies graph guidance uniformly to every trace, and gating the injection on model confidence or task complexity is a natural refinement for the cases where guidance does not help. Beyond diagnosis, the intervention-validated subgraph $\mathcal{G}_V$ is the artifact a repair loop would consume, and evaluating such a loop faithfully requires re-executing multi-agent systems at scale, which we leave to future work.

Potential Risks. EDGE could be misused if graph-guided outputs are treated as definitive causal diagnoses. EDGE should be used as a diagnostic aid with human review, especially in high-stakes agent deployments.

Reproducibility. All reported numbers are single-run point estimates. The full code and inference scripts are available at <https://github.com/JuneHou/EDGE>. However, we do not guarantee that others will obtain exactly the same numbers as those reported in our paper, due to the inherent nondeterminism in LLM inference.

Ethical Considerations

This study evaluates multi-agent failure attribution using publicly available benchmarks under their original terms. We do not collect new human-subject data or use private user data. Some parts of the pipeline rely on LLM judgments, including repair verification, effect evaluation, and MAST event annotation, which may introduce annotation noise or model bias. We report these limitations and encourage future work with stronger human validation.

AI Assistance. We used AI assistants for parts of the implementation and manuscript preparation, including generating LaTeX code for tables and refining text written by the authors. All AI-generated content was carefully reviewed and revised by the authors to ensure accuracy and clarity.

Acknowledgments

This research is sponsored by NSF 2442253, 2607580, NIH 1R21AG091260-01, USDA NIFA, Commonwealth Cyber Initiative, and generous gifts from Nvidia, Cisco, and the Amazon-Virginia Tech Initiative. This research used the Delta system at the National Center for Supercomputing Applications [award OAC 2005572] through allocation [NAIRR240202] from the Advanced Cyberinfrastructure Coordination Ecosystem: Services & Support (ACCESS) program, which is supported by National Science Foundation grants #2138259, #2138286, #2138307, #2137603, and #2138296.

References

- Adi Banerjee, Anirudh Nair, and Tarik Borogovac. 2025. Where did it all go wrong? a hierarchical look into multi-agent error attribution. *arXiv preprint arXiv:2510.04886*.
- Shraddha Barke, Arnav Goyal, Alind Khare, Avaljot Singh, Suman Nath, and Chetan Bansal. 2026. Agentrx: Diagnosing ai agent failures from execution trajectories. *arXiv preprint arXiv:2602.02475*.

- Ruichu Cai, Siyu Wu, Jie Qiao, Z. Hao, Keli Zhang, and Xi Zhang. 2021. [Thps: Topological hawkes processes for learning causal structure on event sequences](#). *IEEE Transactions on Neural Networks and Learning Systems*, 35:479–493.
- Mert Cemri, Melissa Z Pan, Shuyi Yang, Lakshya A Agrawal, Bhavya Chopra, Rishabh Tiwari, Kurt Keutzer, Aditya Parameswaran, Dan Klein, Kannan Ramchandran, and 1 others. 2026. Why do multi-agent llm systems fail? *Advances in Neural Information Processing Systems*, 38.
- Jianhong Chen, Meng Zhao, M. R. Gahrooei, and Xubo Yue. 2025. [Toward temporal causal representation learning with tensor decomposition](#). *ArXiv*, abs/2507.14126.
- Gheorghe Comanici, Eric Bieber, Mike Schaekermann, Ice Pasupat, Noveen Sachdeva, Inderjit Dhillon, Marcel Blistein, Ori Ram, Dan Zhang, Evan Rosen, and 1 others. 2025. Gemini 2.5: Pushing the frontier with advanced reasoning, multimodality, long context, and next generation agentic capabilities. *arXiv preprint arXiv:2507.06261*.
- A. Constantinou, Zhi gao Guo, and N. K. Kitson. 2021. [The impact of prior knowledge on causal structure learning](#). *Knowledge and Information Systems*, 65:3385–3434.
- Luca De Sano, Giulio Caravagna, Daniele Ramazzotti, Alex Graudenzi, Giancarlo Mauri, Bud Mishra, and Marco Antonioti. 2016. [Tronco: an r package for the inference of cancer progression models from heterogeneous genomic data](#). *Bioinformatics*, 32(12):1911–1913.
- Darshan Deshpande, Varun Gangal, Hersh Mehta, Jitin Krishnan, Anand Kannappan, and Rebecca Qian. 2025. Trail: Trace reasoning and agentic issue localization. *arXiv preprint arXiv:2505.08638*.
- Carlos E Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik Narasimhan. 2024. Swe-bench: Can language models resolve real-world github issues? In *International Conference on Learning Representations*, volume 2024, pages 54107–54157.
- Wenrui Li, Qinghao Zhang, and Xiaowo Wang. 2025. [Interpretable clustering with adaptive heterogeneous causal structure learning in mixed observational data](#). *ArXiv*, abs/2509.04415.
- Loes Olde Loohuis, Giulio Caravagna, Alex Graudenzi, Daniele Ramazzotti, Giancarlo Mauri, Marco Antonioti, and Bud Mishra. 2014. Inferring tree causal models of cancer progression with probability raising. *PloS one*, 9(10):e108358.
- Guoqing Ma, Jia Zhu, Hanghui Guo, Weijie Shi, Jiawei Shen, Jingjiang Liu, and Yidan Liang. 2025. Automatic failure attribution and critical step prediction method for multi-agent systems based on causal inference. *arXiv preprint arXiv:2509.08682*.
- Hugo Math and Rainer Lienhart. 2026. Your autoregressive model already reveals the causal graph. *arXiv preprint arXiv:2602.01135*.
- Grégoire Mialon, Clémentine Fourrier, Thomas Wolf, Yann LeCun, and Thomas Scialom. 2024. Gaia: a benchmark for general ai assistants. In *International Conference on Learning Representations*, volume 2024, pages 9025–9049.
- Mistral AI. 2025. Mistral-Small-3.1-24B-Instruct-2503. <https://huggingface.co/mistralai/Mistral-Small-3.1-24B-Instruct-2503>.
- OpenAI, :, Sandhini Agarwal, Lama Ahmad, Jason Ai, Sam Altman, Andy Applebaum, Edwin Arbus, Rahul K. Arora, Yu Bai, Bowen Baker, Haiming Bao, Boaz Barak, Ally Bennett, Tyler Bertao, Nivedita Brett, Eugene Brevdo, Greg Brockman, Sebastien Bubeck, and 108 others. 2025. [gpt-oss-120b & gpt-oss-20b model card](#). *Preprint*, arXiv:2508.10925.
- OpenAI, :, Aaron Hurst, Adam Lerer, Adam P. Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, Alec Radford, Aleksander Madry, Alex Baker-Whitcomb, Alex Beutel, Alex Borzunov, Alex Carney, Alex Chow, Alex Kirillov, and 401 others. 2024. [Gpt-4o system card](#). *Preprint*, arXiv:2410.21276.
- Judea Pearl. 2022. Direct and indirect effects. In *Probabilistic and causal inference: the works of Judea Pearl*, pages 373–392.
- Jie Qiao, Ruichu Cai, Siyu Wu, Yu Xiang, Keli Zhang, and Zhifeng Hao. 2023. [Structural hawkes processes for learning causal structure from discrete-time event sequences](#). In *Proceedings of the Thirty-Second International Joint Conference on Artificial Intelligence*, IJCAI '23.
- Qwen Team. 2025. Qwq-32b: Embracing the power of reinforcement learning. <https://qwenlm.github.io/blog/qwq-32b/>.
- Qwen Team. 2026. [Qwen3.6-35B-A3B: Agentic coding power, now open to all](#).
- Abdellah Rahmani and Pascal Frossard. 2025. [Causal temporal regime structure learning](#). In *Proceedings of The 28th International Conference on Artificial Intelligence and Statistics*, volume 258 of *Proceedings of Machine Learning Research*, pages 4546–4554. PMLR.
- Daniele Ramazzotti, Giulio Caravagna, Loes Olde Loohuis, Alex Graudenzi, Ilya Korsunsky, Giancarlo Mauri, Marco Antonioti, and Bud Mishra. 2015. Capri: efficient inference of cancer progression models from cross-sectional data. *Bioinformatics*, 31(18):3016–3026.
- Aaditya Singh, Adam Fry, Adam Perelman, Adam Tart, Adi Ganesh, Ahmed El-Kishky, Aidan McLaughlin, Aiden Low, AJ Ostrow, Akhila Ananthram, Akshay Nathan, Alan Luo, Alec Helyar, Aleksander Madry,

- Aleksandr Efremov, Aleksandra Spyra, Alex Baker-Whitcomb, Alex Beutel, Alex Karpenko, and 467 others. 2026. [Openai gpt-5 system card](#). *Preprint*, arXiv:2601.03267.
- Patrick Suppes. 1970. *A Probabilistic Theory of Causality*. Studies in Logic and the Foundations of Mathematics. North-Holland Publishing Company.
- Gemma Team, Aishwarya Kamath, Johan Ferret, Shreya Pathak, Nino Vieillard, Ramona Merhej, Sarah Perrin, Tatiana Matejovicova, Alexandre Ramé, Morgane Rivière, Louis Rouillard, Thomas Mesnard, Geoffrey Cideron, Jean bastien Grill, Sabela Ramos, Edouard Yvinec, Michelle Casbon, Etienne Pot, Ivo Penchev, and 197 others. 2025. [Gemma 3 technical report](#). *Preprint*, arXiv:2503.19786.
- Fanqi Wan, Weizhou Shen, Shengyi Liao, Yingcheng Shi, Chenliang Li, Ziyi Zhao, Tao Yu, Wenting Yin, Ming Yan, Ji Zhang, and Fei Huang. 2025. Qwenlong-11: Towards long-context large reasoning models with reinforcement learning. *arXiv preprint arXiv:2505.17667*.
- Junjie Wang, Yawen Wang, Mengzhuo Chen, Xiaofei Xie, Chunyang Chen, Fangwen Mu, Zhe Liu, and Qing Wang. 2026a. [A survey for LLM agent trajectory analysis: From failure attribution to enhancement](#). *IEEE Transactions on Software Engineering*, pages 1–23.
- Yawen Wang, Wenjie Wu, Junjie Wang, and Qing Wang. 2026b. From flat logs to causal graphs: Hierarchical failure attribution for llm-based multi-agent systems. *arXiv preprint arXiv:2602.23701*.
- Alva West, Yixuan Weng, Minjun Zhu, Zhen Lin, Zhiyuan Ning, and Yue Zhang. 2025. Abduct, act, predict: Scaffolding causal inference for automated failure attribution in multi-agent systems. *arXiv preprint arXiv:2509.10401*.
- Dongxia Wu, Tsuyoshi Idé, Georgios Kollias, Jiri Navratil, Aurelie Lozano, Naoki Abe, Yian Ma, and Rose Yu. 2024. Learning granger causality from instance-wise self-attentive hawkes processes. In *International Conference on Artificial Intelligence and Statistics*, pages 415–423. PMLR.
- Brian Hu Zhang, Eric Mitchell, Hongyu Ren, Kevin Lu, Max Schwarzer, Michelle Pokrass, Shengjia Zhao, Ted Sanders, Adam Tauman Kalai, Alexandre Passos, Benjamin Sokolowsky, Elaine Ya Le, Erik Ritter, Hao Sheng, Hanson Wang, Ilya Kostrikov, James Lee, Johannes Ferstad, Michael Lampe, and 93 others. [Openai o3-mini system card](#).
- Shaokun Zhang, Ming Yin, Jieyu Zhang, Jiale Liu, Zhiguang Han, Jingyang Zhang, Beibin Li, Chi Wang, Huazheng Wang, Yiran Chen, and Qingyun Wu. 2025. Which agent causes task failures and when? on automated failure attribution of llm multi-agent systems. In *Proceedings of the 42nd International Conference on Machine Learning, ICML’25*. JMLR.org.
- Chenyang Zhu, Spencer Hong, Jingyu Wu, Kushal Chawla, Yuhui Tang, Youbing Yin, Nathan Wolfe, Erin Babinsky, and Daben Liu. 2026. [RAFFLES: Reasoning-based attribution of faults for LLM systems](#). In *Proceedings of the 19th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 7659–7688, Rabat, Morocco. Association for Computational Linguistics.
- Kunlun Zhu, Zijia Liu, Bingxuan Li, Muxin Tian, Yingxuan Yang, Jiaxun Zhang, Pengrui Han, Qipeng Xie, Fuyang Cui, Weijia Zhang, and 1 others. 2025. Where llm agents fail and how they can learn from failures. *arXiv preprint arXiv:2509.25370*.

A Appendix

A.1 Notation Table

Table 4 lists the symbols used in EDGE. We describe the role of each symbol here in prose, grouped by the three blocks shown in the table.

Graphs and edge sets. $\mathcal{G}_S$ is the observational correlation graph from the Suppes screen. Its edges are the observational hypotheses that feed coverage augmentation in $\mathcal{G}_\tau$. $\mathcal{G}_C$ is the CAPRI-pruned DAG of causal candidates fed into intervention validation. $\mathcal{G}_V$ is the intervention-validated causal anchor used for explanation. $\mathcal{G}_\tau$ is the prediction-oriented thresholded inference graph that unions $\mathcal{G}_V$ with score-filtered observational edges from $\mathcal{G}_S$, and is the default detector input.

Sets and trace-level quantities. $\mathcal{C}$ is the error taxonomy (nodes of all graphs). $\mathcal{T}$ is the trace corpus. $\mathcal{T}_{A \prec B}$ is the subset of traces in which both A and B occur with $t_A(T) < t_B(T)$. $X_A(T) \in \{0, 1\}$ indicates whether A occurs in T . $t_A(T)$ is the index of the first span at which A emerges.

Edge scores and thresholds. $w_S(A, B)$ is the Suppes propagation weight (geomean of temporal precedence and probability raising). $\Delta(A \rightarrow B)$ is the controlled direct effect (Boolean risk-difference of B between the original trace and the controlled-counterfactual rollout). τ is the inference-graph threshold, the minimum w_S for an observational edge to enter $\mathcal{G}_\tau$. τ_{GI} is the Stage-2 propagation threshold, the minimum aggregated w_{AB} for a downstream hypothesis to be exposed in Stage 2. τ_{val} is the edge-validation threshold, the value that $\Delta(A \rightarrow B)$ must exceed for a causal-candidate edge to enter $\mathcal{G}_V$.

Symbol	Name
$\mathcal{G}_S = (\mathcal{C}, \mathcal{R}_S)$	Observational correlation graph
$\mathcal{G}_C = (\mathcal{C}, \mathcal{R}_C)$	Causal-candidate graph
$\mathcal{G}_V = (\mathcal{C}, \mathcal{R}_V)$	Validated graph
$\mathcal{G}_\tau = (\mathcal{C}, \mathcal{R}_\tau)$	Thresholded inference graph
$\mathcal{C}$	Error taxonomy
$\mathcal{T}$	Trace corpus
$\mathcal{T}_{A \prec B}$	Joint-event subset
$X_A(T) \in \{0, 1\}$	Category indicator
$t_A(T)$	First-event position
$w_S(A, B)$	Suppes propagation weight
$\Delta(A \rightarrow B)$	Controlled direct effect
τ	Inference-graph threshold
τ_{GI}	Stage-2 propagation threshold
τ_{val}	Edge-validation threshold

Table 4: Notation used in EDGE (symbol roles described in text).

A.2 Causal Graph Construction Details

This appendix collects the formal definitions, threshold values, prompts, postcheck criteria, and hyperparameter values used for the observational correlation graph $\mathcal{G}_S$, the causal-candidate graph $\mathcal{G}_C$ constructed in Section 3.2, and the intervention-based validation pipeline of Section 3.3.

Adapting Suppes screening to within-trace event data. Classic CAPRI often uses marginal occurrence frequency as a temporal-priority surrogate when only cross-sectional event observations are available. Our setting differs because each trace carries span-level event annotations, so we can estimate temporal priority directly from within-trace event order and aggregate this evidence across traces.

First-event formalization. For each annotated trace T and category A with $X_A(T) = 1$, the first-event index $t_A(T)$ is the position of the first span at which A emerges:

$$t_A(T) = \min \{ i : \exists (c, \ell) \in E(T), \\ c = A, \ell = s_i \}.$$

Tied events are retained as category occurrences but do not support strict temporal direction.

CAPRI score objective. We select the pruned graph by minimizing an AIC-style score over the admissible family $\Omega(\mathcal{R}_S)$ defined in the main text:

$$\mathcal{G}_C = \arg \min_{\mathcal{G} \in \Omega(\mathcal{R}_S)} \left[-2 \log \hat{L}(\mathcal{G}; X) \right. \\ \left. + 2 \dim(\mathcal{G}) \right],$$

Stage	TRAIL	MAST
Traces	148	393
Categories	19	13
Ordered pairs	–	1,347
$ \mathcal{R}_S $ (Suppes)	27	43
$ \mathcal{R}_C $ (CAPRI)	13	23
hill-climb moves accepted	13	25
Bootstrap + shuffle controls	skipped	run

Table 5: Edge yield at each graph-construction stage for both benchmarks (production AIC configuration). The Suppes screen produces $\mathcal{R}_S$, and CAPRI hill-climb prunes it to $\mathcal{R}_C$. TRAIL skips bootstrap and shuffle controls due to small N . MAST runs both ($n_{\text{bootstrap}}=100$, $n_{\text{shuffles}}=50$).

where $\hat{L}(\mathcal{G}; X)$ is the maximized likelihood of the binary category-event model and $\dim(\mathcal{G})$ is the number of free parameters. Optimization proceeds by hill-climbing over edge addition, removal, and reversal, restricted to $\mathcal{R}_S$ and enforcing acyclicity.

Graph construction yields. Table 5 reports the edge yield at each construction stage for both benchmarks under the production AIC configuration ($\text{min_precedence}=0.55$, $\text{min_pr_delta}=0.05$, $\text{min_joint}=3$). MAST starts from a larger ordered-pair pool than TRAIL because its taxonomy is flat (13 codes vs. 19 hierarchical leaves) and its 393 trace corpus produces more co-occurrence support per category. The causal-candidate graph $\mathcal{G}_C$ therefore retains a larger DAG (23 vs. 13 edges) before intervention validation.

Intervention trace set. For a causal-candidate edge $A \rightarrow B \in \mathcal{R}_C$, the set of traces eligible for intervention is

$$\mathcal{T}_{A \prec B} = \{ T \in \mathcal{T} : X_A(T)=1, X_B(T)=1, \\ t_A(T) < t_B(T) \}.$$

This restricts intervention experiments to traces in which both categories occur and the first event of A strictly precedes the first event of B , ensuring that any change in B ’s downstream status can be attributed to the intervention on A rather than to baseline ordering.

Per-category patch library. The patch library specifies, for each source category A , what a valid $\text{do}(A=0)$ repair must look like. Each entry contains: category and trail_definition (the taxonomy reference), a patch_side_default that

fixes whether the repair rewrites the source span's input context or its output, a `slot_schema` that names the structured slots the repair LLM must fill, a natural-language `repair_instruction`, a list of `forbidden_actions`, and a list of declarative postcheck criteria. TRAIL covers the 19 source-error categories that appear in the dataset under its taxonomy, with two intervention sides (`replace_span_output` for LLM spans, `replace_span_input` for context-side patches). MAST covers the 13 categories that appear under its taxonomy with a single `replace_step_content` mode over multi-agent conversation steps. The full libraries are reproduced below as JSON.

TRAIL (causal/patch/patch_library.json)	patch	library
--	-------	---------

```
{
  "Formatting Errors": {
    "category": "Formatting Errors",
    "trail_definition": "Formatting / code execution / required structure errors.",
    "patch_side_default": "replace_span_output",
    "slot_schema": {
      "REQUIRED_MARKERS": "List of literal tags or markers explicitly required in output (e.g. <end_plan>)",
      "REQUIRED_FORMAT_RULES": "Explicit structure rules (e.g. comma-separated list, JSON, code fence, FINAL ANSWER: prefix)",
      "FORBIDDEN_MARKERS": "Any explicitly prohibited markers, if stated"
    },
    "error_type_spec_text": "error_type: Formatting Errors\ntrail_definition: Formatting / code execution / required structure errors.\npatch_side_default: replace_span_output\nslot_extraction:\n- REQUIRED_MARKERS: extract any explicit required tags or literal markers from ERROR_DESCRIPTION, ERROR_EVIDENCE, USER_REQUIREMENTS, or LOCAL_SNIPPET.\n- REQUIRED_FORMAT_RULES: extract explicit structure requirements (e.g., exact suffix, JSON, comma-separated list, code fence).\n- FORBIDDEN_MARKERS: extract any explicitly prohibited markers if present.\nrepair_instruction:\n- Make the smallest possible structural edit that satisfies the required format contract.\n- Do not change semantic content unless needed to satisfy the explicit format rule.\n- If a required literal marker is explicitly grounded, append or insert it exactly.\nforbidden_actions:\n- Do not add new factual content.\n- Do not add tool calls, evidence, or reasoning that was not already present.\n- Do not change plan steps unless the only needed change is the structural marker.\npostcheck:\n-
```

```
All grounded REQUIRED_MARKERS appear exactly.\n- No ungrounded special tokens were introduced.\n- Original semantic content is preserved except for the minimum formatting fix.",
"repair_instruction": "Make the smallest possible structural edit that satisfies the required format contract. Do not change semantic content unless needed to satisfy the explicit format rule. If a required literal marker is explicitly grounded, append or insert it exactly.",
"forbidden_actions": [
  "Do not add new factual content.",
  "Do not add tool calls, evidence, or reasoning that was not already present.",
  "Do not change plan steps unless the only needed change is the structural marker."
],
"postcheck": [
  "All grounded REQUIRED_MARKERS appear exactly in patch_payload.",
  "No ungrounded special tokens (e.g. <...>) introduced.",
  "Original semantic content preserved except for minimum formatting fix.",
  "patch_payload differs from local_snippet."
]
},
"Incorrect Problem Identification": {
  "category": "Incorrect Problem Identification",
  "trail_definition": "Misunderstood the overall task or the local task.",
  "patch_side_default": "replace_span_input",
  "slot_schema": {
    "TASK_GOAL": "Explicit user objective from USER_REQUIREMENTS or task text",
    "REQUIRED_OUTPUT_FORM": "Any answer-format requirement",
    "MISIDENTIFIED_TARGET": "What the current span incorrectly focuses on, if stated in ERROR_DESCRIPTION"
  },
  "error_type_spec_text": "error_type: Incorrect Problem Identification\ntrail_definition: Misunderstood the overall task or the local task.\npatch_side_default: replace_span_input\nslot_extraction:\n- TASK_GOAL: extract the explicit user objective from USER_REQUIREMENTS or task text.\n- REQUIRED_OUTPUT_FORM: extract any answer-format requirement.\n- MISIDENTIFIED_TARGET: extract what the current span incorrectly focuses on, if stated in ERROR_DESCRIPTION.\nrepair_instruction:\n- Rewrite the local instruction/thought so it correctly states the actual task objective and immediate subgoal.\n- Narrow the local scope to what must be solved next.\n- Preserve any useful constraints already present.\nforbidden_actions:\n- Do not fabricate facts or tool outputs.\n- Do not pre-answer the task.\n- Do not insert
```

```

    downstream recovery instructions for
    other error types.\npostcheck:\n- The
    rewritten span explicitly reflects the
    correct task objective.\n- The required
    output form remains preserved if grounded
    .\n- No unsupported factual claims were
    added.",
    "repair_instruction": "Rewrite the local
    instruction/thought so it correctly
    states the actual task objective and
    immediate subgoal. Narrow the local scope
    to what must be solved next. Preserve
    any useful constraints already present.",
    "forbidden_actions": [
        "Do not fabricate facts or tool outputs
        .",
        "Do not pre-answer the task.",
        "Do not insert downstream recovery
        instructions for other error types."
    ],
    "postcheck": [
        "The rewritten span explicitly reflects
        the correct task objective.",
        "The required output form remains
        preserved if grounded.",
        "No unsupported factual claims were
        added.",
        "patch_payload differs from
        local_snippet."
    ]
},
"Poor Information Retrieval": {
    "category": "Poor Information Retrieval",
    "trail_definition": "Tried to find
    information not relevant to the task.",
    "patch_side_default": "replace_span_input
    ",
    "slot_schema": {
        "TASK_ENTITY": "Core entity, resource,
        or fact the task actually needs",
        "TIME_SCOPE": "Any explicit time
        restriction",
        "SOURCE_CONSTRAINT": "Any explicitly
        required source (e.g. USGS, file, website
        )",
        "BAD_RETRIEVAL_FOCUS": "The irrelevant
        focus described in ERROR_DESCRIPTION, if
        present"
    },
    "error_type_spec_text": "error_type: Poor
    Information Retrieval\ntrail_definition:
    Tried to find information not relevant
    to the task.\npatch_side_default:
    replace_span_input\nslot_extraction:\n-
    TASK_ENTITY: extract the core entity,
    resource, or fact the task actually needs
    .\n- TIME_SCOPE: extract any explicit
    time restriction.\n- SOURCE_CONSTRAINT:
    extract any explicit required source (e.g
    ., USGS, file, website).\n-
    BAD_RETRIEVAL_FOCUS: extract the
    irrelevant focus described in
    ERROR_DESCRIPTION, if present.\n
    nrepair_instruction:\n- Rewrite the local
    query/request/plan step so it targets
    only task-relevant information.\n-
    Preserve the required source and time
    scope if explicitly given.\n- Keep the
    retrieval action narrow and directly

```

```

    aligned to the task.\nforbidden_actions:\n
    n- Do not inject the answer.\n- Do not
    fabricate retrieved evidence.\n- Do not
    add extra exploratory searches unrelated
    to the stated goal.\npostcheck:\n- The
    revised span is directly relevant to
    TASK_ENTITY.\n- Explicit source/time
    constraints are retained when grounded.\n
    - No unsupported answer content was
    introduced.",
    "repair_instruction": "Rewrite the local
    query/request/plan step so it targets
    only task-relevant information. Preserve
    the required source and time scope if
    explicitly given. Keep the retrieval
    action narrow and directly aligned to the
    task.",
    "forbidden_actions": [
        "Do not inject the answer.",
        "Do not fabricate retrieved evidence.",
        "Do not add extra exploratory searches
        unrelated to the stated goal."
    ],
    "postcheck": [
        "The revised span is directly relevant
        to TASK_ENTITY.",
        "Explicit source/time constraints are
        retained when grounded.",
        "No unsupported answer content was
        introduced.",
        "patch_payload differs from
        local_snippet."
    ]
},
"Resource Abuse": {
    "category": "Resource Abuse",
    "trail_definition": "Excessive tool
    calling due to memory issues / repeated
    unnecessary use of resources.",
    "patch_side_default": "replace_span_input
    ",
    "slot_schema": {
        "CURRENT_SUBGOAL": "Immediate goal of
        the step",
        "REPEATED_ACTION": "Redundant action or
        repeated call pattern from
        ERROR_DESCRIPTION/EVIDENCE",
        "AVAILABLE_RESULT": "Any already-known
        result in local context, if explicitly
        present",
        "STOP_CRITERION": "Minimal completion
        condition inferred from USER_REQUIREMENTS
        "
    },
    "error_type_spec_text": "error_type:
    Resource Abuse\ntrail_definition:
    Excessive tool calling due to memory
    issues / repeated unnecessary use of
    resources.\npatch_side_default:
    replace_span_input\nslot_extraction:\n-
    CURRENT_SUBGOAL: extract the immediate
    goal of the step.\n- REPEATED_ACTION:
    extract the redundant action or repeated
    call pattern from ERROR_DESCRIPTION/
    EVIDENCE.\n- AVAILABLE_RESULT: extract
    any already-known result in local context
    , if explicitly present.\n-
    STOP_CRITERION: infer the minimal
    completion condition from

```

```

USER_REQUIREMENTS.\nrepair_instruction:\n
- Rewrite the local step to avoid
repeating already-completed or redundant
actions.\n- Prefer reusing already
available local results if explicitly
present.\n- Add a concise stop condition
or 'do not repeat identical call'
constraint in the local wording.\n
nforbidden_actions:\n- Do not invent
successful prior results unless
explicitly present.\n- Do not change the
overall plan beyond preventing the local
redundant action.\n- Do not introduce
credentials, auth logic, or other
downstream fixes.\npostcheck:\n- The
revised span removes the redundant or
excessive action.\n- A concrete local
stop condition is present.\n- No new
unsupported results were added.\n
noutput_side_note (applies when
LOCAL_SNIPPET is a tool_calls JSON object
):\n- This occurs when the annotated span
was a TOOL span remapped to its parent
LLM span.\n LOCAL_SNIPPET will be the
LLM's tool_calls output \u2014 a JSON
object like:\n {\n  \"role\": \"assistant\",
  \"tool_calls\": [{\n    \"id\": ..., \"
function\": {\n  \"name\": ..., \"arguments
\": {...}}, \"type\": \"function\"]}\n-
Fix the repetition by modifying the tool
call ARGUMENTS (e.g., make the query more
\n specific, remove a redundant filter
parameter like filter_year, or change the
search\n term to avoid repeating a
prior identical call).\n- You may also
replace the entire tool call with a more
targeted one.\n- CRITICAL: Do NOT add new
top-level fields to tool_call entries (e
.g., stop_criterion,\n stop_condition,
retry_limit). The only valid keys per
entry are: id, type, function.\n Adding
phantom fields is not valid OpenAI
tool_calls schema and WILL fail postcheck
.\n
\"repair_instruction\": \"Rewrite the local
step to avoid repeating already-completed
or redundant actions. Prefer reusing
already available local results if
explicitly present. Add a concise stop
condition or 'do not repeat identical
call' constraint in the local wording.\",
\"forbidden_actions\": [
  \"Do not invent successful prior results
unless explicitly present.\",
  \"Do not change the overall plan beyond
preventing the local redundant action.\",
  \"Do not introduce credentials, auth
logic, or other downstream fixes.\"
],
\"postcheck\": [
  \"The revised span removes the redundant
or excessive action.\",
  \"A concrete local stop condition is
present.\",
  \"No new unsupported results were added
.\",
  \"patch_payload differs from
local_snippet.\"
]

```

```

},
\"Task Orchestration\": {
  \"category\": \"Task Orchestration\",
  \"trail_definition\": \"Subtask coordination
and progress monitoring failures.\",
  \"patch_side_default\": \"replace_span_input
\",
  \"slot_schema\": {
    \"PLAN_STEPS\": \"Explicit plan or pending
subtasks from local context if present\",
    \"CURRENT_STEP\": \"Immediate intended
step\",
    \"SKIPPED_STEP\": \"Any skipped
prerequisite mentioned in
ERROR_DESCRIPTION/EVIDENCE\",
    \"HANDOFF_TARGET\": \"Required next tool/
agent handoff if explicitly grounded\"
  },
  \"error_type_spec_text\": \"error_type: Task
Orchestration\ntrail_definition: Subtask
coordination and progress monitoring
failures.\npatch_side_default:
replace_span_input\nslot_extraction:\n-
PLAN_STEPS: extract the explicit plan or
pending subtasks from local context if
present.\n- CURRENT_STEP: identify the
immediate intended step.\n- SKIPPED_STEP:
extract any skipped prerequisite
mentioned in ERROR_DESCRIPTION/EVIDENCE.\n
- HANDOFF_TARGET: extract any required
next tool/agent handoff if explicitly
grounded.\nrepair_instruction:\n- Rewrite
the local span so the next action
follows the correct prerequisite order.\n
- Restore any clearly skipped
prerequisite step before proceeding.\n-
Keep the patch local: only repair the
immediate orchestration mistake.\n
nforbidden_actions:\n- Do not complete
multiple future subtasks inside this one
patch.\n- Do not fabricate outputs for
skipped steps.\n- Do not directly resolve
downstream context issues beyond
restoring local order.\npostcheck:\n- The
revised span executes or requests the
correct next prerequisite.\n- No skipped
step remains bypassed locally.\n- No
fabricated completion of later subtasks
is introduced.\",
  \"repair_instruction\": \"Rewrite the local
span so the next action follows the
correct prerequisite order. Restore any
clearly skipped prerequisite step before
proceeding. Keep the patch local: only
repair the immediate orchestration
mistake.\",
  \"forbidden_actions\": [
    \"Do not complete multiple future
subtasks inside this one patch.\",
    \"Do not fabricate outputs for skipped
steps.\",
    \"Do not directly resolve downstream
context issues beyond restoring local
order.\"
  ],
  \"postcheck\": [
    \"The revised span executes or requests
the correct next prerequisite.\",

```

```

    "No skipped step remains bypassed locally.",
    "No fabricated completion of later subtasks is introduced.",
    "patch_payload differs from local_snippet."
]
},
"Tool Selection Errors": {
  "category": "Tool Selection Errors",
  "trail_definition": "Used the wrong tool for the task.",
  "patch_side_default": "replace_span_input",
  "slot_schema": {
    "TASK_NEED": "What capability is actually required (search, parse, inspect, compute, final answer)",
    "WRONG_TOOL": "The incorrect tool named in the local span if present",
    "AVAILABLE_TOOL_LIST": "Tools explicitly available in local context",
    "CORRECT_TOOL_HINT": "Best supported tool only if justified by TASK_NEED and AVAILABLE_TOOL_LIST"
  },
  "error_type_spec_text": "error_type: Tool Selection Errors\ntrail_definition: Used the wrong tool for the task.\npatch_side_default: replace_span_input\nslot_extraction:\n- TASK_NEED: extract what capability is actually required (search, parse, inspect, compute, final answer).\n- WRONG_TOOL: extract the incorrect tool named in the local span if present.\n- AVAILABLE_TOOL_LIST: extract the tools explicitly available in local context.\n- CORRECT_TOOL_HINT: select the best supported tool only if justified by TASK_NEED and AVAILABLE_TOOL_LIST.\nrepair_instruction:\n- Rewrite the input context so it explicitly directs the agent to use CORRECT_TOOL_HINT.\n- If the agent answered from memory without calling any tool (no tool call in the input's assistant turn), append a short mandatory instruction at the end of the last user or system message: e.g. 'IMPORTANT: You MUST verify this using [CORRECT_TOOL_HINT] before providing a final answer. Do not answer from internal knowledge alone.'\n- If the agent called the wrong tool, replace or annotate the relevant step to redirect to CORRECT_TOOL_HINT instead.\n- Keep the rest of the input unchanged. Only add or modify the minimal context needed to enforce correct tool use.\nforbidden_actions:\n- Do not fabricate tool outputs.\n- Do not add extra tools not listed in local context.\n- Do not answer the task directly unless the original local step was already the final-answer step and no tool is needed.\n- Do not restructure or summarize the entire input \u2014 only add the minimal directive.\npostcheck:\n- The patched input contains an explicit reference to CORRECT_TOOL_HINT.\n- Any tool mentioned

```

```

is grounded in AVAILABLE_TOOL_LIST.\n- The local subgoal remains the same.",
"repair_instruction": "Rewrite the input context so it explicitly directs the agent to use CORRECT_TOOL_HINT. If the agent answered from memory, append a short mandatory instruction: 'IMPORTANT: You MUST verify this using [CORRECT_TOOL_HINT] before providing a final answer.' Keep all other input unchanged.",
"forbidden_actions": [
  "Do not fabricate tool outputs.",
  "Do not add extra tools not listed in local context.",
  "Do not answer the task directly unless the original local step was already the final-answer step and no tool is needed.",
  "Do not restructure or summarize the entire input \u2014 only add the minimal directive."
],
"postcheck": [
  "The patched input contains an explicit reference to CORRECT_TOOL_HINT.",
  "Any tool mentioned is grounded in AVAILABLE_TOOL_LIST.",
  "The local subgoal remains the same.",
  "patch_payload differs from local_snippet."
]
},
"Instruction Non-compliance": {
  "category": "Instruction Non-compliance",
  "trail_definition": "Failed to perform the task provided and instead did something else / violated explicit instructions.",
  "patch_side_default": "replace_span_output",
  "slot_schema": {
    "MUST_DO": "Explicit required actions from USER_REQUIREMENTS or ERROR_DESCRIPTION",
    "MUST_NOT_DO": "Explicit prohibitions from USER_REQUIREMENTS or ERROR_DESCRIPTION",
    "REQUIRED_OUTPUT_FORM": "Any answer-format requirement",
    "MISSING_STEP": "Concrete missing action implied by the error evidence (e.g. ., use tool, include citations, follow template)"
  },
  "error_type_spec_text": "error_type: Instruction Non-compliance\ntrail_definition: Failed to perform the task provided and instead did something else / violated explicit instructions.\npatch_side_default: replace_span_output\nslot_extraction:\n- MUST_DO: extract explicit required actions from USER_REQUIREMENTS or ERROR_DESCRIPTION.\n- MUST_NOT_DO: extract explicit prohibitions from USER_REQUIREMENTS or ERROR_DESCRIPTION.\n- REQUIRED_OUTPUT_FORM: extract any answer-format requirement.\n- MISSING_STEP:

```

```

extract the concrete missing action
implied by ERROR_EVIDENCE.\
nrepair_instruction:\n- Rewrite the local
output so it directly satisfies MUST_DO
and REQUIRED_OUTPUT_FORM.\n- Remove any
content that violates MUST_NOT_DO.\n-
Keep edits minimal and local.\
nforbidden_actions:\n- Do not fabricate
facts or tool outputs.\n- Do not add new
constraints not grounded in inputs.\n- Do
not fix downstream errors explicitly.\
npostcheck:\n- Output satisfies grounded
MUST_DO and REQUIRED_OUTPUT_FORM.\n- No
grounded MUST_NOT_DO violations remain.\n
- No new unsupported claims were
introduced.",
"repair_instruction": "Rewrite the local
output so it directly satisfies MUST_DO
and REQUIRED_OUTPUT_FORM, and remove
content violating MUST_NOT_DO. Keep edits
minimal and local.",
"forbidden_actions": [
  "Do not fabricate facts or tool outputs
  .",
  "Do not add new constraints not
  grounded in inputs.",
  "Do not fix downstream errors
  explicitly."
],
"postcheck": [
  "Output satisfies grounded MUST_DO and
  REQUIRED_OUTPUT_FORM.",
  "No grounded MUST_NOT_DO violations
  remain.",
  "No new unsupported claims were
  introduced.",
  "patch_payload differs from
  local_snippet."
]
},
"Tool Output Misinterpretation": {
  "category": "Tool Output
  Misinterpretation",
  "trail_definition": "Made assumptions
  about tool output or used it in an
  incorrect context.",
  "patch_side_default": "replace_span_input
  ",
  "slot_schema": {
    "TOOL_NAME": "Tool referenced in the
    local span or context",
    "RAW_OBSERVATION": "The actual tool
    observation string if present in local
    context",
    "REQUIRED_FIELDS": "Fields that must be
    extracted/checked from tool output (if
    specified)",
    "PARSE_RULE": "How to parse/interpret
    output (JSON parse, regex, key lookup)
    based on grounded hints",
    "FAILSAFE_ACTION": "What to do if
    parsing/fields missing (retry once, ask
    clarifying question, stop)"
  },
  "error_type_spec_text": "error_type: Tool
  Output Misinterpretation\
  ntrail_definition: Made assumptions about
  tool output or used it in an incorrect
  context.\npatch_side_default:

```

```

replace_span_input\nslot_extraction:\n-
TOOL_NAME: extract from LOCAL_SNIPPET or
USER_REQUIREMENTS if present.\n-
RAW_OBSERVATION: extract any explicit
observation content present in local
context.\n- REQUIRED_FIELDS: extract
required fields/checks if specified.\n-
PARSE_RULE: derive from grounded format
hints (JSON/text/table) only.\n-
FAILSAFE_ACTION: set a conservative
fallback (retry once or ask clarification
).\nrepair_instruction:\n- Rewrite the
local instruction/thought to include an
explicit 'parse \u2192 validate \u2192
use' step.\n- Require that any claim
derived from the tool output must cite
the RAW_OBSERVATION content.\n- If
validation fails, execute FAILSAFE_ACTION
instead of guessing.\nforbidden_actions
:\n- Do not fabricate tool outputs.\n- Do
not introduce new fields into tool_calls
schema.\n- Do not claim a parsed value
unless it is present in RAW_OBSERVATION.\
npostcheck:\n- Contains explicit parse +
validation gate.\n- Contains a failsafe
branch.\n- No new unsupported tool-
derived claims were added.",
"repair_instruction": "Rewrite the local
instruction/thought to include an
explicit parse\u2192validate\u2192use
step for tool output. If validation fails
, perform FAILSAFE_ACTION instead of
guessing.",
"forbidden_actions": [
  "Do not fabricate tool outputs.",
  "Do not introduce new fields into
  tool_calls schema.",
  "Do not claim a parsed value unless it
  is present in RAW_OBSERVATION."
],
"postcheck": [
  "Contains explicit parse + validation
  gate.",
  "Contains a failsafe branch.",
  "No new unsupported tool-derived claims
  were added.",
  "patch_payload differs from
  local_snippet."
]
},
"Tool-related": {
  "category": "Tool-related",
  "trail_definition": "Fabricated the
  outcome of a tool interaction or data
  retrieval step / fabricated tool
  capabilities.",
  "patch_side_default": "
  replace_span_output",
  "slot_schema": {
    "TOOL_REQUIRED": "Tool that was planned
    /required (if explicitly stated)",
    "FABRICATED_CLAIMS": "Specific claims
    that are unsupported by any tool
    observation",
    "ALLOWED_EVIDENCE": "Observations
    present in the trace context (if
    available)",
    "SAFE_REWRITE_MODE": "Either 'remove
    claim' or 'mark unknown and request tool

```

```

call'
},
"error_type_spec_text": "error_type: Tool
-related\ntrail_definition: Fabricated
the outcome of a tool interaction or data
retrieval step / fabricated tool
capabilities.\npatch_side_default:
replace_span_output\nslot_extraction:\n-
TOOL_REQUIRED: extract any required tool
name from plan/instructions if present.\n-
FABRICATED_CLAIMS: extract the
unsupported assertions from
ERROR_EVIDENCE.\n- ALLOWED_EVIDENCE:
extract any actual observations present
in local context.\n- SAFE_REWRITE_MODE:
default to removing fabricated claims; if
required, request a tool call instead of
asserting.\nrepair_instruction:\n-
Rewrite the span to remove
FABRICATED_CLAIMS.\n- If the task
requires those facts, replace assertions
with a request to call TOOL_REQUIRED (or
an explicit 'need to look up').\n- Keep
minimal edits; do not introduce new facts
.\nforbidden_actions:\n- Do not invent
tool observations.\n- Do not invent
citations or sources.\n- Do not convert
the span into a full new plan unless it
is already a planning span.\npostcheck:\n-
FABRICATED_CLAIMS are removed or
rephrased as unknown/needs tool.\n- No
new factual claims beyond
ALLOWED_EVIDENCE.\n- Patch does not add
ungrounded tokens.",
"repair_instruction": "Rewrite the span
to remove fabricated tool-derived claims.
If the information is required, replace
assertions with an explicit need to call
the required tool instead of claiming
results.",
"forbidden_actions": [
    "Do not invent tool observations.",
    "Do not invent citations or sources.",
    "Do not convert the span into a full
new plan unless it is already a planning
span."
],
"postcheck": [
    "Fabricated claims are removed or
rewritten as unknown/needs tool.",
    "No new factual claims beyond allowed
evidence.",
    "No ungrounded special tokens
introduced.",
    "patch_payload differs from
local_snippet."
]
},
"Language-only": {
    "category": "Language-only",
    "trail_definition": "Ungrounded language-
only hallucination (not tied to tool use)
.",
    "patch_side_default": "
replace_span_output",
    "slot_schema": {
        "UNSUPPORTED_CLAIMS": "Claims not
supported by provided context/task",

```

```

        "CONTEXT_GIVEN": "Facts explicitly
present in the prompt/context",
        "SAFE_REWRITE_MODE": "Either 'remove
claim' or 'hedge + request verification'"
    },
    "error_type_spec_text": "error_type:
Language-only\ntrail_definition:
Ungrounded language-only hallucination (
not tied to tool use).\n
    npatch_side_default: replace_span_output\n
    slot_extraction:\n- UNSUPPORTED_CLAIMS:
extract claims identified in
ERROR_EVIDENCE.\n- CONTEXT_GIVEN: extract
facts explicitly present in
USER_REQUIREMENTS/local context.\n-
SAFE_REWRITE_MODE: default to removing
unsupported claims; optionally hedge +
request verification.\nrepair_instruction
:\n- Rewrite the span to remove or hedge
UNSUPPORTED_CLAIMS.\n- Keep only
statements grounded in CONTEXT_GIVEN.\n-
If the task cannot be completed without
the missing fact, explicitly state it
needs lookup (without inventing).\n
    nforbidden_actions:\n- Do not add new
facts.\n- Do not add invented sources.\n-
Do not rewrite unrelated parts of the
output.\npostcheck:\n- Unsupported claims
removed/hedged.\n- Remaining content is
grounded in CONTEXT_GIVEN.\n- No new
unsupported factual content.",
    "repair_instruction": "Rewrite the span
to remove or hedge unsupported claims and
keep only statements grounded in
provided context. If missing info is
required, explicitly state it needs
lookup.",
    "forbidden_actions": [
        "Do not add new facts.",
        "Do not add invented sources.",
        "Do not rewrite unrelated parts of the
output."
    ],
    "postcheck": [
        "Unsupported claims removed or hedged
.",
        "Remaining content is grounded in
provided context.",
        "No new unsupported factual content
introduced.",
        "patch_payload differs from
local_snippet."
    ]
},
"Goal Deviation": {
    "category": "Goal Deviation",
    "trail_definition": "Deviated from the
task or subtask (did something else).",
    "patch_side_default": "replace_span_input
",
    "slot_schema": {
        "ACTIVE_GOAL": "Current task/subtask
objective explicitly stated",
        "DEVIATION_BEHAVIOR": "What the span is
doing instead (from ERROR_EVIDENCE)",
        "NEXT_REQUIRED_ACTION": "Minimal next
step aligned with ACTIVE_GOAL",
        "STOP_IF_UNCERTAIN": "Rule to avoid
continuing off-goal"
    }
}

```

```

},
"error_type_spec_text": "error_type: Goal
Deviation\ntrail_definition: Deviated
from the task or subtask.\n
npatch_side_default: replace_span_input\n
nslot_extraction:\n- ACTIVE_GOAL: extract
the explicit task/subtask objective.\n-
DEVIATION_BEHAVIOR: extract what it did
instead.\n- NEXT_REQUIRED_ACTION: infer
the minimal next aligned action (tool
call, check, or step).\n-
STOP_IF_UNCERTAIN: add a conservative
redirect rule.\nrepair_instruction:\n-
Rewrite the local instruction/thought to
restate ACTIVE_GOAL and require
NEXT_REQUIRED_ACTION.\n- Add a single-
line redirect: if the next action does
not advance ACTIVE_GOAL, do not proceed.\n
- Keep the patch local.\n
nforbidden_actions:\n- Do not fabricate
tool outputs or results.\n- Do not add
new subtasks.\n- Do not rewrite the
entire plan; only correct the immediate
deviation.\npostcheck:\n- ACTIVE_GOAL is
explicitly stated.\n-
NEXT_REQUIRED_ACTION is aligned with
ACTIVE_GOAL.\n- No new unsupported facts
were added.",
"repair_instruction": "Rewrite the local
instruction/thought to restate the active
goal and require the minimal next
aligned action. Add a conservative
redirect rule to avoid off-goal actions
.",
"forbidden_actions": [
"Do not fabricate tool outputs or
results.",
"Do not add new subtasks.",
"Do not rewrite the entire plan; only
correct the immediate deviation."
],
"postcheck": [
"Active goal is explicitly stated.",
"Next required action aligns with
active goal.",
"No new unsupported facts were added.",
"patch_payload differs from
local_snippet."
]
],
"Context Handling Failures": {
"category": "Context Handling Failures",
"trail_definition": "Window overflow /
state tracking / forgetting important
context.",
"patch_side_default": "replace_span_input
",
"slot_schema": {
"CRITICAL_FACTS": "Facts/constraints
that must persist (from USER_REQUIREMENTS
or earlier context)",
"CURRENT_STATE": "Variables/choices
already made (if explicit)",
"MISSING_CONTEXT": "What was forgotten
(from ERROR_EVIDENCE)",
"PIN_RULE": "Instruction to keep these
facts in working memory"
}
},

```

```

"error_type_spec_text": "error_type:
Context Handling Failures\n
trail_definition: Window overflow /
state tracking / forgetting important
context.\n
npatch_side_default:
replace_span_input\n
nslot_extraction:\n-
CRITICAL_FACTS: extract must-remember
constraints and previously established
facts.\n- CURRENT_STATE: extract explicit
variables/decisions.\n- MISSING_CONTEXT:
extract the forgotten item from
ERROR_EVIDENCE.\n- PIN_RULE: add a short
'pin' instruction.\n
repair_instruction:\n-
Rewrite the local input context to
include a concise pinned summary of
CRITICAL_FACTS and CURRENT_STATE.\n- Add
a rule: do not proceed if MISSING_CONTEXT
is required but not present; request it
.\n- Keep it minimal: only include facts
needed for the next step.\n
nforbidden_actions:\n- Do not invent
missing facts.\n- Do not add new
requirements.\n- Do not summarize the
entire conversation; pin only critical
items.\n
postcheck:\n- Pinned summary
includes grounded CRITICAL_FACTS.\n- No
fabricated content.\n- Patch is minimal
and local.",
"repair_instruction": "Inject a minimal
pinned summary of critical facts/state
into the local input and add a rule to
stop/request clarification if required
context is missing.",
"forbidden_actions": [
"Do not invent missing facts.",
"Do not add new requirements.",
"Do not summarize the entire
conversation; pin only critical items."
],
"postcheck": [
"Pinned summary includes grounded
critical facts/state.",
"No fabricated content introduced.",
"Patch is minimal and local.",
"patch_payload differs from
local_snippet."
]
},
"Tool Definition Issues": {
"category": "Tool Definition Issues",
"trail_definition": "Tool defined
incorrectly / inconsistent with its
description or required schema.",
"patch_side_default": "replace_span_input
",
"slot_schema": {
"TOOL_NAME": "Tool name in local
context",
"TOOL_SPEC_TEXT": "The tool description
/parameters text in local context",
"SCHEMA_MISMATCH": "What is wrong (
missing arg, wrong arg name/type) from
ERROR_EVIDENCE",
"CORRECTED_CALL_PATTERN": "Correct
function signature usage grounded in
TOOL_SPEC_TEXT"
}
},
"error_type_spec_text": "error_type: Tool
Definition Issues\n
trail_definition:

```

```

Tool defined incorrectly / inconsistent
with description.\npatch_side_default:
replace_span_input\nslot_extraction:\n-
TOOL_NAME: extract tool name.\n-
TOOL_SPEC_TEXT: extract the tool
parameters schema from context.\n-
SCHEMA_MISMATCH: extract mismatch from
ERROR_EVIDENCE.\n- CORRECTED_CALL_PATTERN
: derive correct call pattern using only
TOOL_SPEC_TEXT.\nrepair_instruction:\n-
Rewrite the local span to align tool
invocation with TOOL_SPEC_TEXT (correct
argument names/types).\n- If
LOCAL_SNIPPET is tool_calls JSON, fix
only function.name or function.arguments
.\n- CRITICAL: Only valid keys per
tool_call entry are: id, type, function.
Do not add phantom keys.\n-
nforbidden_actions:\n- Do not add phantom
keys to tool_calls entries.\n- Do not
add new tools not in context.\n- Do not
fabricate tool outputs.\npostcheck:\n-
Tool call matches TOOL_SPEC_TEXT.\n-
tool_calls JSON schema preserved (only id
/type/function).\n- No fabricated outputs
.",
"repair_instruction": "Align tool
invocation with the grounded tool
specification by correcting only the tool
call name/arguments (or the local
instruction that produces them).",
"forbidden_actions": [
  "Do not add phantom keys to tool_calls
entries.",
  "Do not add new tools not in context.",
  "Do not fabricate tool outputs."
],
"postcheck": [
  "Tool call matches grounded tool spec (
arg names/types).",
  "tool_calls JSON schema preserved (only
id/type/function keys).",
  "No fabricated outputs introduced.",
  "patch_payload differs from
local_snippet."
]
},
"Environment Setup Errors": {
  "category": "Environment Setup Errors",
  "trail_definition": "Permission/resource/
API-key setup failures; missing
environment prerequisites.",
  "patch_side_default": "replace_span_input
",
  "slot_schema": {
    "MISSING_PREREQ": "What prerequisite is
missing (from ERROR_EVIDENCE)",
    "ACCESS_CONSTRAINT": "Permission or
setup constraint if explicit",
    "SAFE_FAIL_ACTION": "Abort with
explicit error, or request user-provided
credential, or switch to alternative
approach"
  },
  "error_type_spec_text": "error_type:
Environment Setup Errors\
ntrail_definition: Permission/resource/
API-key setup failures.\
npatch_side_default: replace_span_input\

```

```

nslot_extraction:\n- MISSING_PREREQ:
extract missing prerequisite from
ERROR_EVIDENCE.\n- ACCESS_CONSTRAINT:
extract any explicit permission/setup
constraint.\n- SAFE_FAIL_ACTION: choose
conservative fallback (request setup, or
stop).\nrepair_instruction:\n- Rewrite
local span to perform a pre-check for
MISSING_PREREQ and avoid proceeding
without it.\n- Replace failing action
with SAFE_FAIL_ACTION (e.g., ask for
credential, switch to non-auth method if
allowed).\nforbidden_actions:\n- Do not
invent credentials.\n- Do not claim setup
succeeded.\n- Do not add new tools.\
npostcheck:\n- Includes explicit
recognition of missing prerequisite and a
safe fallback.\n- No invented
credentials or success claims.",
"repair_instruction": "Add a local pre-
check for missing prerequisites and
replace the failing action with a safe
fallback (request setup/credentials or
stop), without inventing credentials.",
"forbidden_actions": [
  "Do not invent credentials.",
  "Do not claim setup succeeded.",
  "Do not add new tools."
],
"postcheck": [
  "Explicitly recognizes missing
prerequisite and uses safe fallback.",
  "No invented credentials or success
claims.",
  "patch_payload differs from
local_snippet."
]
},
"Rate Limiting": {
  "category": "Rate Limiting",
  "trail_definition": "Rate limiting errors
(e.g., 429) preventing tool/API
completion.",
  "patch_side_default": "replace_span_input
",
  "slot_schema": {
    "TOOL_NAME": "Tool/API being called
when rate limited",
    "RETRY_POLICY": "Backoff policy
grounded in error evidence (e.g., wait
and retry once)",
    "MAX_RETRIES": "Conservative retry
count (default 1 unless grounded)",
    "FALLBACK_ACTION": "Alternative plan if
retry fails (summarize what is missing;
ask user; stop)"
  },
  "error_type_spec_text": "error_type: Rate
Limiting\ntrail_definition: Rate
limiting errors (e.g., 429).\
npatch_side_default: replace_span_input\
nslot_extraction:\n- TOOL_NAME: extract
tool being called.\n- RETRY_POLICY: set
conservative backoff (sleep/wait) if
allowed; otherwise 'retry once later'.
\n- MAX_RETRIES: default 1 unless explicitly
grounded.\n- FALLBACK_ACTION: choose a
safe fallback.\nrepair_instruction:\n-
Rewrite the local step to avoid immediate

```

```

    repeated identical calls.\n- Add a
    single retry with backoff and a clear
    fallback if still rate limited.\n- Keep
    changes minimal and local.\n- CRITICAL:
    Only valid keys per tool_call entry are:
    id, type, function. Do not add
    retry_limit or backoff as tool_call
    fields.\nforbidden_actions:\n- Do not
    invent successful tool results.\n- Do not
    add schema-invalid fields to tool_calls
    .\n- Do not implement complex loops.\n
    npostcheck:\n- Removes immediate repeated
    identical call.\n- Includes bounded
    retry and fallback.\n- No fabricated
    outputs.",
    "repair_instruction": "Avoid immediate
    repeated identical calls; add one bounded
    retry with backoff and a clear fallback
    if rate limiting persists, without
    fabricating results.",
    "forbidden_actions": [
        "Do not invent successful tool results
        .",
        "Do not add schema-invalid fields to
        tool_calls.",
        "Do not implement complex loops."
    ],
    "postcheck": [
        "Prevents immediate repeated identical
        call.",
        "Includes bounded retry and fallback.",
        "No fabricated outputs introduced.",
        "patch_payload differs from
        local_snippet."
    ]
},
"Authentication Errors": {
    "category": "Authentication Errors",
    "trail_definition": "Authentication/
    permission errors (e.g., 401/403).",
    "patch_side_default": "replace_span_input
    ",
    "slot_schema": {
        "TOOL_NAME": "Tool/API requiring auth",
        "AUTH_REQUIREMENT": "What credential/
        scope is required if explicitly stated",
        "FAILSAFE_ACTION": "Ask for credentials
        , switch to public source, or stop"
    },
    "error_type_spec_text": "error_type:
    Authentication Errors\ntrail_definition:
    Authentication/permission errors
    (401/403).\npatch_side_default:
    replace_span_input\nslot_extraction:\n-
    TOOL_NAME: extract tool/API name.\n-
    AUTH_REQUIREMENT: extract any explicit
    credential/scope requirement.\n-
    FAILSAFE_ACTION: select conservative
    fallback.\nrepair_instruction:\n- Rewrite
    local span to stop attempting
    unauthorized calls.\n- Replace with
    FAILSAFE_ACTION: request credential or
    switch to an allowed public alternative
    if explicitly permitted.\n- CRITICAL:
    Only valid keys per tool_call entry are:
    id, type, function. Do not add auth
    fields.\nforbidden_actions:\n- Do not
    invent credentials.\n- Do not claim
    authentication succeeded.\n- Do not

```

```

    fabricate tool output.\npostcheck:\n- No
    unauthorized call is retried without new
    credentials.\n- Contains a safe fallback
    .\n- No fabricated outputs.",
    "repair_instruction": "Stop retrying
    unauthorized calls; replace with a safe
    fallback (request credentials or switch
    to allowed public alternative), without
    inventing authentication success.",
    "forbidden_actions": [
        "Do not invent credentials.",
        "Do not claim authentication succeeded
        .",
        "Do not fabricate tool output."
    ],
    "postcheck": [
        "Does not retry unauthorized call
        without new credentials.",
        "Contains safe fallback behavior.",
        "No fabricated outputs introduced.",
        "patch_payload differs from
        local_snippet."
    ]
},
"Service Errors": {
    "category": "Service Errors",
    "trail_definition": "Service-side errors
    (e.g., 5xx) from tools/APIs.",
    "patch_side_default": "replace_span_input
    ",
    "slot_schema": {
        "TOOL_NAME": "Tool/API experiencing 5xx
        ",
        "RETRY_ONCE": "Whether to retry once (
        default yes)",
        "FALLBACK_ACTION": "Switch tool/source
        or stop with explicit missing info"
    },
    "error_type_spec_text": "error_type:
    Service Errors\ntrail_definition: Service
    -side errors (5xx).\npatch_side_default:
    replace_span_input\nslot_extraction:\n-
    TOOL_NAME: extract tool name.\n-
    RETRY_ONCE: default true.\n-
    FALLBACK_ACTION: choose conservative
    fallback.\nrepair_instruction:\n- Add at
    most one retry (non-identical if possible
    ) and then a fallback.\n- Do not loop.\n-
    CRITICAL: Only valid keys per tool_call
    entry are: id, type, function. Do not add
    retry or fallback as tool_call fields.\n
    forbidden_actions:\n- Do not fabricate
    tool results.\n- Do not add invalid
    tool_calls keys.\n- Do not mask the error
    .\npostcheck:\n- Includes bounded retry
    then fallback.\n- No fabricated outputs
    .",
    "repair_instruction": "Add at most one
    retry for transient service errors, then
    switch to a fallback action; do not
    fabricate results or loop.",
    "forbidden_actions": [
        "Do not fabricate tool results.",
        "Do not add invalid tool_calls keys.",
        "Do not mask the error."
    ],
    "postcheck": [
        "Bounded retry then fallback is present
        .",

```

```

        "No fabricated outputs introduced.",
        "patch_payload differs from
local_snippet."
    ],
},
"Resource Not Found": {
    "category": "Resource Not Found",
    "trail_definition": "Missing resource/
path/id (e.g., 404) or nonexistent file/
resource reference.",
    "patch_side_default": "replace_span_input
",
    "slot_schema": {
        "RESOURCE_ID": "The referenced id/path/
url",
        "LOOKUP_STRATEGY": "How to find correct
resource (search, list, inspect
directory) if grounded",
        "FALLBACK_ACTION": "Ask user for
correct id/path or stop"
    },
    "error_type_spec_text": "error_type:
Resource Not Found\ntrail_definition:
Missing resource/path/id (404).\n
npatch_side_default: replace_span_input\n
nslot_extraction:\n- RESOURCE_ID: extract
referenced id/path/url.\n-
LOOKUP_STRATEGY: derive from available
tools/context.\n- FALLBACK_ACTION:
request correct identifier if necessary.\n
nrepair_instruction:\n- Rewrite local
step to verify RESOURCE_ID exists before
using it.\n- If not verifiable, invoke
LOOKUP_STRATEGY or FALLBACK_ACTION.\n-
CRITICAL: Only valid keys per tool_call
entry are: id, type, function.\n
nforbidden_actions:\n- Do not invent a
new resource id.\n- Do not claim a
resource exists without evidence.\n- Do
not fabricate retrieval results.\n
npostcheck:\n- Includes explicit
existence check or lookup.\n- No invented
identifiers.",
    "repair_instruction": "Verify resource
existence before use; if not verifiable,
perform a grounded lookup or request the
correct identifier instead of guessing.",
    "forbidden_actions": [
        "Do not invent a new resource id.",
        "Do not claim a resource exists without
evidence.",
        "Do not fabricate retrieval results."
    ],
    "postcheck": [
        "Includes existence check or grounded
lookup step.",
        "No invented identifiers or fabricated
results.",
        "patch_payload differs from
local_snippet."
    ]
},
"Resource Exhaustion": {
    "category": "Resource Exhaustion",
    "trail_definition": "Resource exhaustion
(memory/compute) including memory
overflow.",
    "patch_side_default": "replace_span_input
",

```

```

    "slot_schema": {
        "BUDGET_TYPE": "Memory/token/compute
budget that was exceeded",
        "CHUNKING_RULE": "Chunk size or
batching rule",
        "MINIMAL_SUBGOAL": "Next minimal
computation/retrieval step",
        "STOP_CONDITION": "When to stop and
summarize partial results"
    },
    "error_type_spec_text": "error_type:
Resource Exhaustion\ntrail_definition:
Resource exhaustion (memory/compute),
including memory overflow.\n
npatch_side_default: replace_span_input\n
nslot_extraction:\n- BUDGET_TYPE: extract
which budget failed if stated.\n-
CHUNKING_RULE: set conservative chunking/
batching.\n- MINIMAL_SUBGOAL: infer
minimal next step.\n- STOP_CONDITION:
define when to stop.\n
nrepair_instruction:
:\n- Rewrite local step to reduce
resource use via chunking, limiting scope
, or summarizing intermediate results.\n-
Add a bounded plan: process only a small
unit at a time.\n
nforbidden_actions:\n-
Do not expand scope.\n- Do not add
repeated tool loops.\n- Do not fabricate
skipped outputs.\n
npostcheck:\n- Includes
explicit chunking/limit.\n- Scope is
reduced, not expanded.\n- No fabricated
results.",
    "repair_instruction": "Reduce resource
usage by chunking/limiting scope and
adding a bounded processing plan; do not
expand scope or fabricate results.",
    "forbidden_actions": [
        "Do not expand scope.",
        "Do not add repeated tool loops.",
        "Do not fabricate skipped outputs."
    ],
    "postcheck": [
        "Includes explicit chunking/limit
mechanism.",
        "Scope reduced rather than expanded.",
        "No fabricated results introduced.",
        "patch_payload differs from
local_snippet."
    ]
},
"Timeout Issues": {
    "category": "Timeout Issues",
    "trail_definition": "System took too long
to respond / tool or process timed out
.",
    "patch_side_default": "replace_span_input
",
    "slot_schema": {
        "TIME_BUDGET": "Any explicit timeout
threshold if present",
        "SIMPLIFICATION": "How to simplify the
action (smaller query, fewer pages,
smaller file range)",
        "MAX_ATTEMPTS": "Bounded retry count (
default 1)",
        "FALLBACK_ACTION": "Stop and summarize
what is missing / alternative source"
    },
}

```

```

"error_type_spec_text": "error_type:
Timeout Issues\ntrail_definition: Tool/
process timed out.\npatch_side_default:
replace_span_input\nslot_extraction:\n-
TIME_BUDGET: extract any explicit time
budget.\n- SIMPLIFICATION: choose a
simpler/smaller action.\n- MAX_ATTEMPTS:
default 1.\n- FALLBACK_ACTION: choose a
safe fallback.\nrepair_instruction:\n-
Rewrite the local step to reduce workload
and avoid long operations.\n- Add
bounded retry and fallback.\n- CRITICAL:
Only valid keys per tool_call entry are:
id, type, function.\nforbidden_actions:\n
- Do not loop.\n- Do not fabricate
results.\n- Do not increase scope.\n
npostcheck:\n- Action is simplified.\n-
Retry is bounded.\n- No fabricated
results.",
"repair_instruction": "Simplify the local
action to avoid long operations, add a
bounded retry and fallback, and do not
fabricate results.",
"forbidden_actions": [
  "Do not loop.",
  "Do not fabricate results.",
  "Do not increase scope."
],
"postcheck": [
  "Action simplified relative to original
.",
  "Retry bounded and fallback present.",
  "No fabricated results introduced.",
  "patch_payload differs from
local_snippet."
]
}
}

```

MAST (causal_graph/causal_valid/patch_library.json)	patch	library
--	-------	---------

```

{
  "1.1": {
    "category": "1.1",
    "mast_definition": "Disobey Task
Specification \u2014 Violates constraints
or requirements explicitly stated in the
task.",
    "patch_side_default": "
replace_step_content",
    "slot_schema": {
      "VIOLATED_CONSTRAINT": "The specific
constraint or requirement that was
violated (quoted from task or evidence)",
      "CORRECT_BEHAVIOR": "What the agent
should have done to comply with the
constraint"
    },
    "error_type_spec_text": "error_type: 1.1
Disobey Task Specification\n
nmast_definition: Violates constraints or
requirements explicitly stated in the
task.\npatch_side_default:
replace_step_content\nslot_extraction:\n-
VIOLATED_CONSTRAINT: identify the
specific requirement or constraint from
the task that was violated, quoting it

```

```

verbatim from ERROR_EVIDENCE or
USER_REQUIREMENTS.\n- CORRECT_BEHAVIOR:
describe the correct behavior that
satisfies the violated constraint.\n
nrepair_instruction:\n- Rewrite the step
content so that it complies with the
stated constraint.\n- Preserve all other
content and reasoning that does not
violate any constraint.\n- Do not
introduce new capabilities or expand the
solution scope.\nforbidden_actions:\n- Do
not remove valid reasoning or correct
steps.\n- Do not fabricate new task
requirements.\n- Do not change the
solution approach unless required to
satisfy the constraint.\npostcheck:\n-
The violated constraint is no longer
present in the patched step.\n-
patch_payload differs from local_snippet
.",
"repair_instruction": "Rewrite the step
so that it complies with the stated task
constraint. Keep all valid reasoning
intact.",
"forbidden_actions": [
  "Do not fabricate new task requirements
.",
  "Do not change the solution approach
unless required to satisfy the constraint
."
],
"postcheck": [
  "The violated constraint is no longer
present.",
  "patch_payload differs from
local_snippet."
]
},
"1.2": {
  "category": "1.2",
  "mast_definition": "Disobey Role
Specification \u2014 Ignores or violates
the assigned agent role.",
  "patch_side_default": "
replace_step_content",
  "slot_schema": {
    "ROLE_REQUIREMENT": "The role
specification that was violated",
    "CORRECT_ROLE_BEHAVIOR": "What behavior
is consistent with the assigned role"
  },
  "error_type_spec_text": "error_type: 1.2
Disobey Role Specification\n
nmast_definition: Ignores or violates the
assigned agent role.\npatch_side_default
: replace_step_content\nslot_extraction:\n
- ROLE_REQUIREMENT: identify the role
specification being violated from
ERROR_DESCRIPTION or USER_REQUIREMENTS.\n
- CORRECT_ROLE_BEHAVIOR: describe the
behavior that is consistent with the
assigned role.\nrepair_instruction:\n-
Rewrite the step so that the agent
behaves within its assigned role.\n-
Preserve the task-relevant content; only
adjust the role-violating aspects.\n
nforbidden_actions:\n- Do not change the
agent's goal or task objective.\n- Do not
fabricate role specifications.\n

```

```

npostcheck:\n- The role violation is
resolved in the patched step.\n-
patch_payload differs from local_snippet
.",
"repair_instruction": "Rewrite the step
so the agent operates within its assigned
role.",
"forbidden_actions": [
  "Do not change the agent's goal or task
objective.",
  "Do not fabricate role specifications."
],
"postcheck": [
  "The role violation is resolved.",
  "patch_payload differs from
local_snippet."
]
},
"1.3": {
  "category": "1.3",
  "mast_definition": "Step Repetition \
\u2014 Repeats a task or phase already
completed with a result.",
  "patch_side_default": "
replace_step_content",
  "slot_schema": {
    "REPEATED_STEP": "Description of the
step or phase that was unnecessarily
repeated",
    "PRIOR_RESULT": "The result that was
already achieved before the repetition"
  },
  "error_type_spec_text": "error_type: 1.3
Step Repetition\nmast_definition: Repeats
a task or phase already completed with a
result.\npatch_side_default:
replace_step_content\nslot_extraction:\n-
REPEATED_STEP: identify what step or
phase was unnecessarily repeated from
ERROR_DESCRIPTION.\n- PRIOR_RESULT:
identify the result that was already
obtained before this repetition.\n-
repair_instruction:\n- Replace the
repetition with an acknowledgment of the
prior result and a forward-looking step.\n-
The agent should reference the
previous result and proceed to the next
logical step instead of repeating.\n-
forbidden_actions:\n- Do not fabricate
new prior results.\n- Do not skip
required steps (only remove genuinely
redundant repetition).\npostcheck:\n- The
repeated content is removed or replaced
.\n- patch_payload differs from
local_snippet.",
  "repair_instruction": "Replace the
repeated step with acknowledgment of the
prior result and a forward move.",
  "forbidden_actions": [
    "Do not fabricate prior results.",
    "Do not skip genuinely required steps."
  ],
  "postcheck": [
    "The redundant repetition is removed.",
    "patch_payload differs from
local_snippet."
  ]
},
"1.4": {

```

```

  "category": "1.4",
  "mast_definition": "Loss of Conversation
History \u2014 Fails to retain or use
prior conversation context.",
  "patch_side_default": "
replace_step_content",
  "slot_schema": {
    "LOST_CONTEXT": "The specific prior
information that was not retained or
referenced",
    "REQUIRED_REFERENCE": "How the prior
context should have been used in this
step"
  },
  "error_type_spec_text": "error_type: 1.4
Loss of Conversation History\n
mast_definition: Fails to retain or use
prior conversation context.\n
npatch_side_default: replace_step_content\n
slot_extraction:\n- LOST_CONTEXT:
identify the prior information that was
ignored or forgotten from ERROR_EVIDENCE
.\n- REQUIRED_REFERENCE: describe how the
prior context should have been
incorporated.\nrepair_instruction:\n-
Rewrite the step to correctly reference
and incorporate the relevant prior
context.\n- The agent should explicitly
acknowledge the prior information and
build on it.\nforbidden_actions:\n- Do
not fabricate prior conversation content
.\n- Do not introduce information that
was not in the prior conversation.\n
npostcheck:\n- The step correctly
references or incorporates the prior
context.\n- patch_payload differs from
local_snippet.",
  "repair_instruction": "Rewrite the step
so it correctly references and uses the
relevant prior context.",
  "forbidden_actions": [
    "Do not fabricate prior conversation
content.",
    "Do not introduce information not in
prior context."
  ],
  "postcheck": [
    "Prior context is correctly referenced
.",
    "patch_payload differs from
local_snippet."
  ]
},
"1.5": {
  "category": "1.5",
  "mast_definition": "Unaware of
Termination Conditions \u2014 Continues
past a valid stopping point or stops too
early.",
  "patch_side_default": "
replace_step_content",
  "slot_schema": {
    "TERMINATION_CONDITION": "The stopping
condition that was missed or
misidentified",
    "CORRECT_ACTION": "Whether the agent
should stop or continue, and why"
  },

```

```

"error_type_spec_text": "error_type: 1.5
Unaware of Termination Conditions\
nmast_definition: Continues past a valid
stopping point or stops too early.\
npatch_side_default: replace_step_content
\nslot_extraction:\n-
TERMINATION_CONDITION: identify the
termination condition from
ERROR_DESCRIPTION.\n- CORRECT_ACTION:
determine whether the agent should stop (
if it continued too long) or continue (if
it stopped too early).\
nrepair_instruction:\n- If the agent
continued past a valid stop: rewrite to
acknowledge completion and terminate
cleanly.\n- If the agent stopped too
early: rewrite to continue toward the
required completion criterion.\
nforbidden_actions:\n- Do not fabricate
completion criteria.\n- Do not alter the
task goal.\npostcheck:\n- The termination
behavior is corrected.\n- patch_payload
differs from local_snippet.",
"repair_instruction": "Correct the
termination behavior: stop if past valid
stopping point, continue if stopped too
early.",
"forbidden_actions": [
  "Do not fabricate completion criteria
  .",
  "Do not alter the task goal."
],
"postcheck": [
  "Termination behavior is corrected.",
  "patch_payload differs from
  local_snippet."
]
},
"2.1": {
  "category": "2.1",
  "mast_definition": "Conversation Reset \
u2014 Resets the conversation, losing
prior context and progress.",
  "patch_side_default": "
replace_step_content",
  "slot_schema": {
    "LOST_PROGRESS": "The prior context or
progress that was discarded by the reset
",
    "RECOVERY_ACTION": "How the step should
be rewritten to preserve prior context"
  },
  "error_type_spec_text": "error_type: 2.1
Conversation Reset\nmast_definition:
Resets the conversation, losing prior
context and progress.\npatch_side_default
: replace_step_content\nslot_extraction:\
n- LOST_PROGRESS: identify the prior
context or progress that the reset
discarded.\n- RECOVERY_ACTION: describe
how to rewrite the step to preserve
context continuity.\nrepair_instruction:\
n- Rewrite the step to continue from the
prior state instead of resetting.\n-
Explicitly reference the prior context
that would have been lost.\
nforbidden_actions:\n- Do not fabricate
prior progress.\n- Do not remove
legitimately new information.\npostcheck

```

```

:\n- The reset is avoided; prior context
is referenced.\n- patch_payload differs
from local_snippet.",
"repair_instruction": "Rewrite to
continue from the prior state rather than
resetting.",
"forbidden_actions": [
  "Do not fabricate prior progress.",
  "Do not remove legitimately new
information."
],
"postcheck": [
  "The conversation reset is avoided.",
  "patch_payload differs from
  local_snippet."
]
},
"2.2": {
  "category": "2.2",
  "mast_definition": "Fail to Ask for
Clarification \u2014 Proceeds without
resolving ambiguity that required
clarification.",
  "patch_side_default": "
replace_step_content",
  "slot_schema": {
    "AMBIGUITY": "The specific ambiguity or
unclear aspect that required
clarification",
    "CLARIFICATION_QUESTION": "A concrete
clarification question the agent should
have asked"
  },
  "error_type_spec_text": "error_type: 2.2
Fail to Ask for Clarification\
nmast_definition: Proceeds without
resolving ambiguity that required
clarification.\npatch_side_default:
replace_step_content\nslot_extraction:\n-
AMBIGUITY: identify the specific
ambiguity from ERROR_DESCRIPTION or
ERROR_EVIDENCE.\n- CLARIFICATION_QUESTION
: formulate the question the agent should
have asked before proceeding.\
nrepair_instruction:\n- Rewrite the step
to explicitly identify the ambiguity and
ask for clarification before proceeding.\
n- The agent should pause its current
action and request the missing
information.\nforbidden_actions:\n- Do
not fabricate an answer to the ambiguity
.\n- Do not proceed with the original
action while just adding a clarification
note.\npostcheck:\n- The step asks for
clarification rather than proceeding with
the ambiguous assumption.\n-
patch_payload differs from local_snippet
.",
"repair_instruction": "Rewrite to ask for
clarification instead of proceeding with
an ambiguous assumption.",
"forbidden_actions": [
  "Do not fabricate an answer to the
ambiguity.",
  "Do not proceed with the original
action while just noting the ambiguity."
],
"postcheck": [

```

```

    "The step asks for clarification before
    proceeding.",
    "patch_payload differs from
    local_snippet."
  ]
},
"2.3": {
  "category": "2.3",
  "mast_definition": "Task Derailment \
u2014 Shifts focus away from the intended
  objective.",
  "patch_side_default": "
  replace_step_content",
  "slot_schema": {
    "INTENDED_OBJECTIVE": "The original
    task objective that was abandoned or
    deprioritized",
    "DERAILMENT_DESCRIPTION": "How the
    agent shifted focus away from the
    objective"
  },
  "error_type_spec_text": "error_type: 2.3
  Task Derailment\nmast_definition: Shifts
  focus away from the intended objective.\
  npatch_side_default: replace_step_content
  \nslot_extraction:\n- INTENDED_OBJECTIVE:
  identify the main task objective from
  USER_REQUIREMENTS or ERROR_DESCRIPTION.\n
  - DERAILMENT_DESCRIPTION: describe how
  the agent drifted from that objective.\
  nrepair_instruction:\n- Rewrite the step
  to refocus on the intended objective.\n-
  Explicitly reference the main goal and
  orient the step toward it.\
  nforbidden_actions:\n- Do not introduce
  new objectives.\n- Do not remove relevant
  subtasks that genuinely serve the main
  objective.\npostcheck:\n- The step is
  focused on the intended objective.\n-
  patch_payload differs from local_snippet
  .",
  "repair_instruction": "Rewrite to refocus
  on the intended objective.",
  "forbidden_actions": [
    "Do not introduce new objectives.",
    "Do not remove subtasks that serve the
    main goal."
  ],
  "postcheck": [
    "The step is refocused on the intended
    objective.",
    "patch_payload differs from
    local_snippet."
  ]
},
"2.4": {
  "category": "2.4",
  "mast_definition": "Information
  Withholding \u2014 Fails to share
  information needed by other agents.",
  "patch_side_default": "
  replace_step_content",
  "slot_schema": {
    "WITHHELD_INFORMATION": "The specific
    information that was not shared",
    "WHY_NEEDED": "Why the other agent
    needs this information"
  },

```

```

    "error_type_spec_text": "error_type: 2.4
    Information Withholding\nmast_definition:
    Fails to share information needed by
    other agents.\npatch_side_default:
    replace_step_content\nslot_extraction:\n-
    WITHHELD_INFORMATION: identify the
    information that was not passed to the
    other agent.\n- WHY_NEEDED: explain why
    the receiving agent needs this
    information to complete the task.\
    nrepair_instruction:\n- Rewrite the step
    to include and explicitly communicate the
    withheld information.\n- The information
    must be presented clearly for the
    receiving agent to use.\
    nforbidden_actions:\n- Do not fabricate
    information that was not available.\n- Do
    not add unrelated information.\
    npostcheck:\n- The required information
    is now shared in the patched step.\n-
    patch_payload differs from local_snippet
    .",
    "repair_instruction": "Rewrite to include
    the withheld information for the
    receiving agent.",
    "forbidden_actions": [
      "Do not fabricate information that was
      not available.",
      "Do not add unrelated information."
    ],
    "postcheck": [
      "The required information is now
      communicated.",
      "patch_payload differs from
      local_snippet."
    ]
  },
  "2.6": {
    "category": "2.6",
    "mast_definition": "Action-Reasoning
    Mismatch \u2014 Executes an action
    inconsistent with the stated reasoning.",
    "patch_side_default": "
    replace_step_content",
    "slot_schema": {
      "STATED_REASONING": "The reasoning or
      plan that was stated",
      "INCONSISTENT_ACTION": "The action that
      contradicts the stated reasoning"
    },
    "error_type_spec_text": "error_type: 2.6
    Action-Reasoning Mismatch\
    nmast_definition: Executes an action
    inconsistent with the stated reasoning.\
    npatch_side_default: replace_step_content
    \nslot_extraction:\n- STATED_REASONING:
    identify the reasoning or plan from
    ERROR_EVIDENCE or LOCAL_SNIPPET.\n-
    INCONSISTENT_ACTION: identify the action
    that contradicts the stated reasoning.\
    nrepair_instruction:\n- Rewrite the step
    so the action is consistent with the
    stated reasoning.\n- Either update the
    reasoning to match the action, or update
    the action to match the reasoning \u2014
    whichever requires less change.\
    nforbidden_actions:\n- Do not fabricate
    new reasoning.\n- Do not change the
    overall task goal.\npostcheck:\n- The

```

```

    action and reasoning are now consistent
    in the patched step.\n- patch_payload
    differs from local_snippet.",
    "repair_instruction": "Align the action
    with the stated reasoning (or vice versa)
    with minimal change.",
    "forbidden_actions": [
        "Do not fabricate new reasoning.",
        "Do not change the overall task goal."
    ],
    "postcheck": [
        "Action and reasoning are now
        consistent.",
        "patch_payload differs from
        local_snippet."
    ]
},
"3.1": {
    "category": "3.1",
    "mast_definition": "Premature Termination
    \u2014 Stops before the task is complete
    or a required output is produced.",
    "patch_side_default": "
    replace_step_content",
    "slot_schema": {
        "INCOMPLETE_ASPECT": "What part of the
        task was left incomplete",
        "REQUIRED_CONTINUATION": "What the
        agent should have continued doing"
    },
    "error_type_spec_text": "error_type: 3.1
    Premature Termination\nmast_definition:
    Stops before the task is complete or a
    required output is produced.\n
    npatch_side_default: replace_step_content
    \nslot_extraction:\n- INCOMPLETE_ASPECT:
    identify what was left unfinished from
    ERROR_DESCRIPTION.\n-
    REQUIRED_CONTINUATION: describe what the
    agent should have continued doing instead
    of stopping.\nrepair_instruction:\n-
    Rewrite the step to continue the task
    rather than terminate.\n- Explicitly
    identify remaining work and commit to
    completing it.\nforbidden_actions:\n- Do
    not fabricate completion of the remaining
    work in this step.\n- Do not add work
    beyond what was originally required.\n
    npostcheck:\n- The step continues toward
    task completion rather than terminating.\n
    - patch_payload differs from
    local_snippet.",
    "repair_instruction": "Rewrite to
    continue the task rather than terminate
    prematurely.",
    "forbidden_actions": [
        "Do not fabricate completion of
        remaining work.",
        "Do not add work beyond what was
        required."
    ],
    "postcheck": [
        "The step continues toward completion
        .",
        "patch_payload differs from
        local_snippet."
    ]
},
"3.2": {

```

```

    "category": "3.2",
    "mast_definition": "Weak Verification \
    u2014 Performs only superficial or
    incomplete verification.",
    "patch_side_default": "
    replace_step_content",
    "slot_schema": {
        "MISSED_VERIFICATION": "The
        verification check that was skipped or
        performed superficially",
        "THOROUGH_CHECK": "What a thorough
        verification would include"
    },
    "error_type_spec_text": "error_type: 3.2
    Weak Verification\nmast_definition:
    Performs only superficial or incomplete
    verification.\npatch_side_default:
    replace_step_content\nslot_extraction:\n-
    MISSED_VERIFICATION: identify what
    verification was skipped or done
    superficially.\n- THOROUGH_CHECK:
    describe what a thorough verification
    would include.\nrepair_instruction:\n-
    Rewrite the step to include a thorough,
    substantive verification of the result.\n
    - The verification must check the actual
    output against the task requirements.\n
    nforbidden_actions:\n- Do not fabricate
    verification results.\n- Do not add
    verification of aspects unrelated to the
    task requirements.\npostcheck:\n- The
    step performs thorough verification.\n-
    patch_payload differs from local_snippet
    .",
    "repair_instruction": "Rewrite to perform
    thorough verification against task
    requirements.",
    "forbidden_actions": [
        "Do not fabricate verification results
        .",
        "Do not add unrelated verification
        checks."
    ],
    "postcheck": [
        "Verification is now thorough and
        substantive.",
        "patch_payload differs from
        local_snippet."
    ]
},
"3.3": {
    "category": "3.3",
    "mast_definition": "No or Incorrect
    Verification \u2014 Skips verification
    entirely or verifies against wrong
    criteria.",
    "patch_side_default": "
    replace_step_content",
    "slot_schema": {
        "CORRECT_CRITERION": "The correct
        verification criterion that should have
        been used",
        "WRONG_OR_MISSING_CHECK": "What
        verification was missing or wrong"
    },
    "error_type_spec_text": "error_type: 3.3
    No or Incorrect Verification\n
    nmast_definition: Skips verification
    entirely or verifies against wrong

```

```

criteria.\npatch_side_default:
replace_step_content\nslot_extraction:\n-
CORRECT_CRITERION: identify the correct
criterion the output should have been
verified against.\n-
WRONG_OR_MISSING_CHECK: identify what
verification was missing or incorrectly
applied.\nrepair_instruction:\n- Rewrite
the step to verify the result against the
CORRECT criterion.\n- If no verification
was done, add an explicit verification
step.\n- If wrong criteria were used,
correct them.\nforbidden_actions:\n- Do
not fabricate verification outcomes.\n-
Do not remove other valid content from
the step.\npostcheck:\n- Verification is
now present and uses the correct
criterion.\n- patch_payload differs from
local_snippet.",
"repair_instruction": "Add or correct
verification using the right criterion.",
"forbidden_actions": [
  "Do not fabricate verification outcomes
  .",
  "Do not remove other valid content from
  the step."
],
"postcheck": [
  "Verification is now present and uses
  the correct criterion.",
  "patch_payload differs from
  local_snippet."
]
}
}

```

Rule-based postcheck. After every patch-LLM call, an independent rule-based postcheck inspects the returned patch_payload and slot_values. A patch must pass all applicable checks before its re-run can be scored. Otherwise the generator retries up to max_retries times before logging the case as a postcheck failure. The universal checks apply to every category. Category-specific checks apply only to entries whose patch_library category declares them. We list the active checks below. The full specification is reflected in the per-category postcheck arrays inside the JSON listings above.

- **Universal.**

- patch_payload is non-empty.
- patch_payload differs from local_snippet (the patch must change something).

- **Formatting Errors (TRAIL).**

- All literal markers listed in slot_values.REQUIRED_MARKERS occur exactly in patch_payload.
- No novel <...> tokens are introduced beyond those already present

in local_snippet or in the required-marker set.

- **Tool Selection Errors (TRAIL).**

- The string named in slot_values.WRONG_TOOL, if any, does not appear in patch_payload.
- The string named in slot_values.CORRECT_TOOL_HINT, if any, appears in patch_payload.

- **Resource Abuse on remapped TOOL spans (TRAIL).** When the source span was originally annotated as a TOOL span and was remapped to its parent LLM span for patching (so the local snippet is a tool_calls JSON object), each tool-call entry in the patched JSON must contain only keys in the OpenAI schema (id, type, function). Novel keys are rejected.

The patch generator runs an LLM-side self-check in parallel (the postcheck field in the response schema above), but only the rule-based check gates retries.

Repair verifier (Judge A). A separate LLM call decides whether the patch actually removed the source error A. Only patches with resolved=True are forwarded to effect estimation. TRAIL has two user-template variants because its two patch sides probe different invariants (the patched LLM output vs. the patched LLM input context). MAST uses a single template over step content.

Judge A (repair verifier) system prompt (TRAIL and MAST)

You are verifying whether a source error of type A has been eliminated by a patch.

PRIMARY TASK: Compare ORIGINAL_SPAN with PATCHED_SPAN and determine whether the specific labeled error A (defined by SOURCE_ERROR_TYPE, ERROR_DESCRIPTION, ERROR_EVIDENCE) is no longer present in the patched version.

IMPORTANT RULES:

1. Base your verdict on the ORIGINAL_SPAN vs PATCHED_SPAN comparison first.
2. RERUN_SUFFIX is supplementary context only. Do NOT use rerun failures to override a clear patch-level fix. If the patched span itself resolves error A, mark resolved=true even if the rerun encountered downstream difficulties or repeated errors in OTHER

spans.
3. Focus solely on error A. Do not penalize for downstream errors (type B) that the patch was not designed to fix.

Return ONLY JSON:

```
{
  "resolved": true,
  "confidence": 0.0,
  "evidence_excerpt": "string"
}
```

Judge A user template — output-side patch (TRAIL)

SOURCE_ERROR_TYPE: {A}
ERROR_DESCRIPTION: {ERROR_DESCRIPTION}
ERROR_EVIDENCE: {ERROR_EVIDENCE}

ORIGINAL_SPAN (content that was replaced):
<<<
{ORIGINAL_SNIPPET}
>>>

PATCHED_SPAN (replacement content):
<<<
{PATCH_PAYLOAD}
>>>

{RERUN_CONTEXT_BLOCK}

Task: Has error A been eliminated in the PATCHED_SPAN compared to ORIGINAL_SPAN? Focus on whether the specific error criterion is met in the patched content itself. Respond with JSON only: {"resolved": bool, "confidence": float 0-1, "evidence_excerpt": "string"}

Judge A user template — input-side patch (TRAIL)

SOURCE_ERROR_TYPE: {A}
ERROR_DESCRIPTION: {ERROR_DESCRIPTION}
ERROR_EVIDENCE: {ERROR_EVIDENCE}

NOTE: This patch modifies the INPUT (message history context) seen by the LLM, not the LLM's output. The error A was caused by the context in the original input. The intervention removes or corrects that error-causing context so the LLM has better information going forward.

ORIGINAL_INPUT (message history before patching):
<<<
{ORIGINAL_SNIPPET}
>>>

PATCHED_INPUT (message history after patching):
<<<
{PATCH_PAYLOAD}
>>>

{RERUN_CONTEXT_BLOCK}

Task: Has the error-causing context for error A been removed or corrected in the PATCHED_INPUT?

Do NOT require the patched input to contain the correct output behavior --- it is an input, not an output. Check whether the specific pattern described in ERROR_EVIDENCE/ERROR_DESCRIPTION is absent or corrected in the patched context compared to the original.

Respond with JSON only: {"resolved": bool, "confidence": float 0-1, "evidence_excerpt": "string"}

Judge A user template — step content (MAST)

SOURCE_ERROR_TYPE: {A}
ERROR_DESCRIPTION: {ERROR_DESCRIPTION}
ERROR_EVIDENCE: {ERROR_EVIDENCE}

ORIGINAL_STEP (content that was replaced):
<<<
{ORIGINAL_SNIPPET}
>>>

PATCHED_STEP (replacement content):
<<<
{PATCH_PAYLOAD}
>>>

{RERUN_CONTEXT_BLOCK}

Task: Has error A been eliminated in the PATCHED_STEP compared to ORIGINAL_STEP? Focus on whether the specific error criterion is met in the patched content itself. Respond with JSON only: {"resolved": bool, "confidence": float 0-1, "evidence_excerpt": "string"}

Effect evaluator (Judge B). For each verified intervention, Judge B inspects the original and counterfactual trace suffixes and assigns an effect label to the downstream category *B*. The eight effect labels distinguish removal (disappeared), partial reduction (delayed, weakened), no effect (unchanged), negative side effects (earlier, strengthened, emerged), and uninformative cases (not_observable). Only disappeared contributes a positive count to $\Delta(A \rightarrow B)$. The labels emerged and strengthened contribute negatively, and the remaining labels are conservative neutrals. TRAIL and MAST use the same system prompt and label set, but the surface wording mentions “spans” for TRAIL and “steps in a multi-agent conversation” for MAST.

Judge B (effect evaluator) system prompt (TRAIL)

You are evaluating the downstream effect of a $\text{do}(A=0)$ intervention on error type B.

The source error A was locally patched at one labeled span.

The rerun trace suffix shows the counterfactual execution after the intervention.

You must judge ONLY the downstream error type B.

Effect labels:

- disappeared : B was present in baseline, absent in rerun (intervention removed B)
- delayed : B was present in baseline, appears later in rerun
- unchanged : B was present in baseline, appears at similar position in rerun
- earlier : B was present in baseline, appears earlier in rerun
- weakened : B was present in baseline, present in rerun but less severe
- strengthened : B was present in baseline, present in rerun and more severe
- emerged : B was ABSENT in baseline, but NOW PRESENT in rerun (intervention introduced B)
- not_observable : B was absent in baseline and absent in rerun; effect cannot be assessed

Return ONLY JSON.

```
"effect_label": "disappeared|delayed|
  unchanged|earlier|weakened|strengthened|
  emerged|not_observable",
"target_present_after": true,
"original_onset_ref": "string|null",
"rerun_onset_ref": "string|null",
"confidence": "high|medium|low",
"evidence": "string"
}
```

Edge effect statistic and validation rule. For each causal-candidate edge $A \rightarrow B \in \mathcal{R}_C$, Judge B labels whether the downstream error B is still present in the counterfactual continuation, giving $X_B^{\text{cf}}(T; A) \in \{0, 1\}$; the labels disappeared, emerged, weakened, strengthened, and not_observable are recorded as annotation and reduced to this indicator. The edge-level effect is the Boolean risk-difference of Eq. (6), averaged over verified interventions $\Delta(A \rightarrow B) = \frac{1}{|\mathcal{T}_{A \prec B}^{\text{ver}}|} \sum_{T \in \mathcal{T}_{A \prec B}^{\text{ver}}} [X_B(T) - X_B^{\text{cf}}(T; A)]$, where $\mathcal{T}_{A \prec B}^{\text{ver}} \subseteq \mathcal{T}_{A \prec B}$ keeps only traces whose Judge-A verdict marks the source error as resolved. An edge is added to the validated graph $\mathcal{G}_V$ when the number of verified interventions meets a minimum-support requirement and $\Delta(A \rightarrow B) > \tau_{\text{val}}$, with $\tau_{\text{val}} = 0.15$.

Intervention pipeline yields. Table 6 reports the per-stage success rates of the intervention pipeline for both benchmarks. Rule-based postcheck failures are rare: $\sim 4\%$ on average, with the worst-case category at 11.1%. Judge-B effect labels differ qualitatively across benchmarks: TRAIL reruns the agent live and produces disappeared in 57.5% of trials, whereas MAST uses LLM-simulated step continuations and is dominated by not_observable ($\sim 70\%$) because the simulator cannot always determine whether the downstream error would have surfaced. After applying the validation rule ($\Delta > \tau_{\text{val}}$, $n \geq 1$), the candidate-to-validated yield is 12/13 (92.3%) on TRAIL and 11/23 (47.8%) on MAST.

Implementation details. Table 7 lists the models and thresholds used at each stage of the pipeline. Patch generation, both judges, MAST step-onset annotation, and the MAST simulated rollout use GPT-4o (OpenAI et al., 2024); the TRAIL counterfactual rollout uses o3-mini (Zhang et al.), matching the backbone that generated the original traces. All judge and patch-generation calls use a single model family; the counterfactual rollout differs by benchmark because TRAIL traces can be replayed

Judge B user template (TRAIL and MAST share this structure)

```
SOURCE_ERROR_TYPE: {A}
TARGET_ERROR_TYPE: {B}

TARGET_ERROR_DEFINITION:
{
  B_TAXONOMY_DEFINITION_OR_INSTANCE_DESCRIPTION
}

ORIGINAL_TRACE_SUFFIX:
<<<
{ORIGINAL_SUFFIX}
>>>

ORIGINAL_ONSET_REF:
{ORIGINAL_B_ONSET}

RERUN_TRACE_SUFFIX_AFTER_DO_A_0:
<<<
{RERUN_SUFFIX}
>>>

Task:
Judge how B changed after the  $\text{do}(A=0)$ 
intervention.

Required output schema:
{
  "source_error_type": "string",
  "target_error_type": "string",
```

Stage / metric	TRAIL	MAST
Causal-candidate edges $ \mathcal{R}_C $	13	23
Active A -categories with patches	6	8
Mean patch-failure rate	4.1%	4.6%
worst category	11.1%	11.1%
Total verified interventions	308	396
min / median / max per edge	1 / 16 / 73	0 / 8 / 81
Judge-B disappeared	57.5%	23%
Judge-B not_observable	9.9%	70%
Judge-B other labels	32.6%	7%
Validated edges (after threshold)	12	11
Validation rate	92.3%	47.8%

Table 6: Per-stage yields of the intervention validation pipeline. Patch-failure rate is averaged over A -categories that actually had patches generated. Judge-B percentages on TRAIL are computed over $n=294$ effect-label trials across the 13 causal-candidate edges in $\mathcal{R}_C$. MAST percentages are computed over ~ 340 trials across validated edges and are dominated by not_observable due to LLM-simulated rerun. Validation rule: $\Delta > \tau_{\text{val}}$ and $n_{\text{valid}} \geq 1$.

Component	TRAIL	MAST
Patch generation	GPT-4o	GPT-4o
Judge A (repair verification)	GPT-4o	GPT-4o
Judge B (effect evaluation)	GPT-4o	GPT-4o
Counterfactual rollout	o3-mini	GPT-4o
rollout mode	live replay	simulated
Step-onset annotation	gold spans	GPT-4o
τ (inference graph)	0.35	0.50
τ_{val} (edge validation)	0.15	0.15
τ_{GI} (Stage-2 propagation)	0.10	0.10

Table 7: Models and thresholds used in the graph-construction and detection pipeline. TRAIL counterfactuals are produced by live agent replay with o3-mini, matching the backbone that generated the original GAIA traces; MAST counterfactuals are LLM-simulated step continuations because the AG2 traces are recorded rather than re-executable.

live whereas MAST traces are recorded multi-agent conversations.

A.3 Step Annotation Coverage

Because MAST provides annotations only at the trace level, we identify the first occurrence of each error category to construct ordered error events. The following table reports the coverage of these step annotations by category and overall.

A.4 Detection Pipeline and +CG Ablation

This appendix collects the formal Stage-2 prediction recipe used by the graph-guided detector of

Code	Category	Cov. (%)
1.1	Disobey Task Specification	76.7
1.2	Disobey Role Specification	85.7
1.3	Step Repetition	95.4
1.4	Loss of Conversation History	79.5
1.5	Unaware of Termination Conditions	86.1
2.1	Conversation Reset	75.9
2.2	Fail to Ask for Clarification	80.7
2.3	Task Derailment	78.1
2.4	Information Withholding	57.1
2.6	Action-Reasoning Mismatch	70.7
3.1	Premature Termination	82.8
3.2	Weak Verification	96.4
3.3	No or Incorrect Verification	87.0
Overall		82.0

Table 8: Step-annotation coverage on the AG2 split ($N=393$, GPT-4o annotator). **Cov.** is the fraction of trace-level error instances assigned a step location. Overall coverage is 82.0% (1,279 / 1,560 trace-level instances located). False-alarm rate is 0 by pipeline design.

Section 3.4, the definition of the naive single-stage Static Graph Guidance (+CG) baseline, and the analysis of why +CG underperforms. The empirical comparison itself is reported in Table 2.

Stage-2 prediction. Given the Stage-1 prediction $\hat{E}^{(1)}(T)$ and the trace-specific edge subset $\mathcal{R}_\tau^{(T)}$, the Stage-2 prediction is

$$\hat{E}^{(2)}(T) = \mathcal{J}^{(2)}(T, \mathcal{C}, \hat{E}^{(1)}(T), \mathcal{R}_\tau^{(T)}),$$

where $\mathcal{J}^{(2)}$ is the second-stage judge call, instantiated with a targeted prompt that conditions on $\hat{E}^{(1)}(T)$ as already-detected errors and on $\mathcal{R}_\tau^{(T)}$ as trace-specific guidance.

Final EDGE prediction. The two stages are merged with category-level deduplication against Stage 1:

$$\begin{aligned} \hat{E}^{\text{EDGE}}(T) &= \hat{E}^{(1)}(T) \\ &\cup \{(c, \ell) \in \hat{E}^{(2)}(T) : c \notin D(T)\}. \end{aligned}$$

Static Graph Guidance (+CG): method. The simplest way to inject $\mathcal{G}_\tau$ is to format its full edge set $\mathcal{R}_\tau$ as a guidance block and prepend it to the baseline prompt. For the validated-only variant ($\mathcal{G}_V$) the block describes intervention-validated causal effects. For the thresholded union variant ($\mathcal{G}_\tau$) it additionally describes correlation patterns from $\mathcal{G}_S$ anchored by validated causal edges. The

single-stage prediction uses the same judge $\mathcal{J}$ and edge set $\mathcal{R}_\tau$ as Stage-1 of our method (§3.4):

$$\hat{E}^{+CG}(T) = \mathcal{J}(T, \mathcal{C}, \mathcal{R}_\tau).$$

The difference from EDGE is operational rather than notational. The same edge set is supplied as a static, trace-agnostic context block in a single LLM call, with no trace-specific filtering and no Stage-2 verification.

Why +CG underperforms EDGE. +CG demonstrates that *graph access alone is not the source of EDGE’s gain*. The full inference graph is identical in both methods. The difference is how it is consumed. +CG presents every edge in $\mathcal{G}_\tau$ as static context, so edges with sources absent from the trace act as distractors during Stage-1 reasoning, and there is no Stage-2 verification to discharge or confirm propagated hypotheses. On long-context inputs (TRAIL-SWE-Bench, with median trace ≈ 213 K characters and tail traces exceeding 1 M), the static prepend additionally consumes context budget that the trace needs, and a non-trivial fraction of samples exceed the model’s max input length once the guidance block is added—degrading even raw Stage-1 coverage. EDGE instead restricts Stage-2 to the trace-specific edge subset $\mathcal{R}_\tau^{(T)}$ derived from the Stage-1 detection profile (Section 3.4), so only edges with a detected upstream source are surfaced to the judge, each propagated downstream hypothesis is verified against the trace before being merged, and the per-call payload stays bounded. The two-stage design is therefore the operational lever. The inference graph supplies the search space, but conditioning that space on the Stage-1 profile is what turns it into a useful prior. Per-backbone Stage-2 trigger rates are reported in Appendix A.5.

A.5 Threshold and Stage-2 Diagnostics

This appendix consolidates two diagnostics that characterize the inference graph $\mathcal{G}_\tau$ used in the main results: a graph-richness sensitivity sweep over the threshold τ , and per-(benchmark, backbone) Stage-2 trigger rates.

Threshold and graph-richness sensitivity. We analyze the inference-graph threshold τ as a graph-richness parameter. For each candidate threshold, we construct the corresponding thresholded union graph $\mathcal{G}_\tau$, run the graph-guided detector across

evaluated backbones, and compute model-averaged weighted-F1. We report one benchmark-level setting in the main table, $\tau = 0.35$ for TRAIL and $\tau = 0.50$ for MAST. This analysis is conducted on the benchmark corpus and is intended as sensitivity analysis rather than held-out hyperparameter tuning. To avoid model-specific overfitting, we use a single τ per benchmark rather than tuning τ separately for each backbone.

Score and variants. The corr-screening score is the Suppes geomean $w_S(A, B) = \sqrt{P(A \prec B \mid \text{both}) \cdot \Delta_{PR}(A \rightarrow B)}$, evaluated on Suppes-screened pairs. For each candidate τ , $\mathcal{G}_\tau$ is the union of (i) all observational edges with $w_S(A, B) \geq \tau$ and (ii) the intervention-validated edges $\mathcal{R}_V$ (kept regardless of w_S). The sweep in Tables 9 and 10 compares this to two controls: **causal-only** keeps only $\mathcal{R}_V$ (no observational extension); **random- K** replaces $\mathcal{R}_V$ with K directed edges sampled uniformly (seed 42) from category pairs not in the Suppes screen, matched in edge count to causal-only.

Stage-2 trigger rates. We report, for every (benchmark, backbone) cell in the main results table, the fraction of evaluation traces on which EDGE actually issued a Stage-2 call (Table 11). Stage 2 fires only when the trace-specific edge subset $\mathcal{R}_\tau^{(T)}$ is non-empty after the Stage-1 detector profile is propagated through the inference graph $\mathcal{G}_\tau$ (Section 3.4). A low trigger rate at fixed τ means Stage 1 already detected enough source categories that no further downstream hypotheses cleared the propagation threshold. A high rate means Stage 1 left targets the graph could still suggest. The trigger rates therefore complement F1 by characterizing how often the second stage is being exercised. Rates are read from the per-trace meta logs written by the eval pipeline (TRAIL: `_meta_<trace_id>.json`, MAST: per-trace JSON with field `pass2_triggered`).

A.6 Additional Backbones

To test whether graph guidance depends on the generation of the underlying model, we additionally evaluate GPT-5 as a proprietary frontier model and Qwen3.6-35B-A3B as an open-weight model. Both use the same graphs, thresholds, prompts, and scorers as Table 1, with no re-tuning. Table 12 reports the results. EDGE improves weighted-F1 in all six model-benchmark cells, including on the strongest

Model	Graph Variant (#edges)	TRAIL-GAIA			TRAIL-SWE-Bench		
		F1	Loc	Joint	F1	Loc	Joint
Mistral-Small-3.1-24B	random-12 (12)	25.57	22.61	9.79	9.00	3.56	0.00
	causal-only (12)	30.76	27.79	11.51	12.45	4.72	0.00
	corr ≥ 0.35 (19)	34.15	25.71	12.27	14.40	7.59	0.87
	corr ≥ 0.25 (21)	34.76	28.13	10.68	9.27	3.92	0.00
	corr ≥ 0.20 (25)	33.99	28.15	11.05	7.86	5.42	0.25
GPT-oss-120B	random-12 (12)	30.57	21.72	6.93	35.30	3.91	0.31
	causal-only (12)	30.14	24.47	6.34	27.13	2.92	0.00
	corr ≥ 0.35 (19)	37.20	28.00	9.48	30.07	1.60	0.00
	corr ≥ 0.25 (21)	38.69	21.96	7.83	35.02	1.02	0.25
	corr ≥ 0.20 (25)	40.62	25.99	12.81	27.72	1.25	0.00
GPT-oss-20B	random-12 (12)	25.17	12.12	4.26	23.50	1.11	0.00
	causal-only (12)	22.29	18.29	4.40	13.03	1.33	0.42
	corr ≥ 0.35 (19)	33.28	12.28	4.09	29.89	1.23	0.43
	corr ≥ 0.25 (21)	33.11	12.59	5.02	27.71	1.78	0.28
	corr ≥ 0.20 (25)	30.30	13.27	5.54	21.13	0.42	0.00
Gemma-3-27B-IT	random-12 (12)	21.46	7.27	0.20	15.09	1.47	0.00
	causal-only (12)	25.30	11.00	1.33	15.16	2.36	0.00
	corr ≥ 0.35 (19)	21.26	11.20	0.73	15.41	1.47	0.00
	corr ≥ 0.25 (21)	18.96	6.87	0.27	16.79	1.47	0.00
	corr ≥ 0.20 (25)	21.12	11.00	1.13	18.52	1.88	0.00
QwenLong-L1-32B	random-12 (12)	19.57	12.20	4.08	10.10	0.31	0.00
	causal-only (12)	16.83	19.23	3.63	11.09	0.42	0.00
	corr ≥ 0.35 (19)	26.57	17.32	4.13	10.33	0.42	0.00
	corr ≥ 0.25 (21)	20.75	12.43	3.05	16.53	0.83	0.00
	corr ≥ 0.20 (25)	25.46	17.16	5.97	13.20	0.42	0.00

Table 9: Graph-richness ablation on TRAIL under the two-pass dynamic injector (+GI). Variants are defined in §A.5 (**random-12**, **causal-only**, **corr** $\geq \tau$ for $\tau \in \{0.35, 0.25, 0.20\}$ giving sizes $\{19, 21, 25\}$). Open-source panel only; closed-source Gemini models excluded. **Bold**: best per model and metric column. All metrics in %.

Model	Graph Variant (#edges)	F1	Macro-F1
Mistral-Small-3.1-24B	random-11 (11)	36.88	25.92
	causal-only (11)	37.01	25.86
	corr ≥ 0.60 (18)	36.95	25.97
	corr ≥ 0.50 (25)	38.29	26.97
	corr ≥ 0.40 (29)	37.40	26.30
GPT-oss-120B	random-11 (11)	25.15	18.72
	causal-only (11)	25.26	18.50
	corr ≥ 0.60 (18)	24.72	18.18
	corr ≥ 0.50 (25)	27.21	19.63
	corr ≥ 0.40 (29)	27.95	20.55
GPT-oss-20B	random-11 (11)	21.05	16.33
	causal-only (11)	21.68	16.04
	corr ≥ 0.60 (18)	20.35	15.29
	corr ≥ 0.50 (25)	22.34	15.94
	corr ≥ 0.40 (29)	20.76	14.66
Gemma-3-27B-IT	random-11 (11)	16.95	13.11
	causal-only (11)	20.25	14.02
	corr ≥ 0.60 (18)	19.39	13.54
	corr ≥ 0.50 (25)	21.17	14.56
	corr ≥ 0.40 (29)	20.52	13.70
QwQ-32B*	random-11 (11)	16.08	12.69
	causal-only (11)	13.69	9.80
	corr ≥ 0.60 (18)	15.57	11.43
	corr ≥ 0.50 (25)	15.61	11.47
	corr ≥ 0.40 (29)	16.01	11.75

Table 10: Graph-richness ablation on MAST ($N=393$ AG2 traces) under the two-pass dynamic injector (+GI). Variants are defined in §A.5 (**random-11**, **causal-only**, **corr** $\geq \tau$ for $\tau \in \{0.60, 0.50, 0.40\}$ giving union sizes $\{18, 25, 29\}$). Open-source panel only; closed-source GPT-4o excluded. **Bold**: best per model and metric column. All metrics in %. *QwQ-32B uses enable_thinking.

Backbone	TRAIL		MAST
	GAIA	SWE-Bench	all traces
Mistral-Small-3.1-24B	54.7%	38.7%	94.4%
GPT-oss-120B	74.4%	58.1%	51.9%
GPT-oss-20B	55.6%	58.1%	38.4%
Gemma-3-27B-IT	70.9%	51.6%	56.5%
Qwen Family*	51.3%	45.2%	21.6%
Closed-source*	59.8%	83.9%	70.7%
Traces evaluated (n)	117	31	393

Table 11: Stage-2 trigger rate per (benchmark, backbone). A trace contributes one count to the numerator when its Stage-1 prediction profile, propagated through $\mathcal{G}_\tau$, exposes at least one downstream hypothesis above the graph-injection threshold τ_{GI} . Otherwise Stage 2 is skipped and only Stage-1 predictions are kept. Sample sizes match the main results table. **EDGE**: thresholded inference graph (TRAIL $\tau=0.35$ with 19 edges, MAST $\tau=0.50$ with 25 edges). ***Qwen Family** = QwenLong-L1-32B on TRAIL + QwQ-32B on MAST. **Closed-source** = Gemini-2.5-Pro on TRAIL + GPT-4o on MAST (same row pairing as Table 1).

proprietary backbone, and the small MAST accuracy decrease on both models follows the accuracy-recall trade-off discussed in Section 4.2.

A.7 Who&When-Style Prompting: Adaptation and Full Results

Who&When formulates failure attribution as identifying the agent and step responsible for a failed multi-agent execution. Its original prompting strategies are designed for a single decisive error, whereas our benchmarks require multi-error prediction. We therefore adapt the prompting format while preserving the intended inference style of each strategy. This appendix collects both the adaptation details and the per-cell tables that back Figure 4 in §4.3.

All-at-once. The all-at-once variant receives the full trace and the benchmark taxonomy in a single call. Instead of asking for one responsible error, we ask the judge to output all supported error categories. For TRAIL, the output contains category and span identifier pairs. For MAST, the output is a trace-level yes/no vector over the taxonomy. The graph-guided version prepends the selected EDGE inference graph to the same prompt.

Step-by-step. The step-by-step variant evaluates the trace through an exhaustive stepwise scan. At each step, the judge receives the local step context, the taxonomy, and the accumulated prediction state.

Predictions are aggregated across steps to form the final trace-level output. For TRAIL, each predicted category is paired with the corresponding span or step identifier. For MAST, step-level predictions are OR-aggregated into a trace-level multi-label vector. The graph-guided version uses the same stepwise protocol, with the selected EDGE inference graph included as additional guidance.

Binary search. We do not include the binary-search variant in the main comparison. Binary search is useful when attribution seeks a single decisive point because recursive interval narrowing reduces the number of inspected steps. In the multi-error setting, however, multiple categories may emerge at different points in the same trace. Attributing all errors would require maintaining and recursively expanding several candidate intervals, which removes the efficiency advantage and makes the adaptation less faithful to the original strategy. We therefore report all-at-once and step-by-step as the two representative prompting regimes: one holistic and one exhaustive.

Graph-guided variants. For both adapted strategies, the +Graph condition uses the same selected EDGE inference graph as the main experiments. TRAIL uses $\tau = 0.35$, and MAST uses $\tau = 0.50$. The graph is fixed after development. It is not updated during evaluation.

Full per-cell tables. Table 13 reports the per-cell TRAIL numbers (the data visualized in Figure 4) including the Joint column that is not shown in the figure. Table 14 reports MAST, which is tabular-only because the main paper only visualizes the TRAIL splits.

A.8 Error Attribution Analysis Details

This appendix supplements the error-attribution analysis of Section 4.5 with per-model per-parent recall numbers (Table 15) and a per-trace case-study breakdown (Table 16).

Per-parent recall numbers. Table 15 reports baseline and EDGE recall for each TRAIL parent category on TRAIL-GAIA, for the three backbones in Figure 6. Recall is the fraction of gold errors in that parent that the method correctly attributed.

Per-trace case-study breakdown. Table 16 reports a four-case GPT-oss-120B breakdown covering both TRAIL splits: two SWE traces

Model	Method	TRAIL-GAIA			TRAIL-SWE-Bench			MAST			
		F1	Loc	Joint	F1	Loc	Joint	F1	Precision	Recall	Acc
GPT-5	Baseline	50.82	58.34	27.81	43.11	5.25	1.41	31.49	27.63	19.58	66.18
	EDGE	53.00	58.92	36.10	63.29	10.81	1.56	35.92	29.17	26.19	64.22
	Δ	+2.17	+0.58	+8.29	+20.19	+5.55	+0.15	+4.43	+1.54	+6.61	-1.96
Qwen3.6-35B-A3B	Baseline	21.50	16.68	4.78	12.33	0.00	0.00	24.11	29.65	16.39	66.51
	EDGE	24.88	14.63	5.42	20.86	0.63	0.00	29.76	29.68	21.01	64.77
	Δ	+3.38	-2.05	+0.64	+8.53	+0.63	0.00	+5.65	+0.03	+4.62	-1.74

Table 12: Additional backbones. Same columns and metrics as Table 1: weighted-F1 for TRAIL and MAST, Loc/Joint for TRAIL, macro Precision/Recall/Acc for MAST. **EDGE**: thresholded inference graph (TRAIL $\tau=0.35$; MAST $\tau=0.50$) with two-stage dynamic injection, identical to the main table. All metrics in %.

Model	Method	TRAIL-GAIA			TRAIL-SWE-Bench		
		F1	Loc	Joint	F1	Loc	Joint
Mistral-Small-3.1-24B	All-at-once	22.41	27.59	4.20	24.81	6.78	0.58
	Step-by-step	14.74	25.06	2.99	3.93	1.89	0.28
	All-at-once + Graph	29.35	30.86	5.93	25.04	16.91	3.92
	Step-by-step + Graph	15.61	20.93	4.21	19.41	26.64	5.77
GPT-oss-120B	All-at-once	15.87	27.19	3.81	19.10	5.35	0.56
	Step-by-step	22.43	45.56	1.94	13.29	26.48	0.88
	All-at-once + Graph	33.11	32.63	12.54	41.07	6.27	1.35
	Step-by-step + Graph	35.02	59.28	10.62	35.81	52.35	9.24
GPT-oss-20B	All-at-once	13.88	23.72	3.59	8.32	1.61	0.00
	Step-by-step	18.73	28.59	3.15	18.19	18.22	0.25
	All-at-once + Graph	29.34	23.17	6.25	11.76	2.50	0.00
	Step-by-step + Graph	13.71	16.83	2.07	22.91	21.63	4.43
Gemma-3-27B-IT	All-at-once	14.75	12.61	2.69	12.90	6.41	0.25
	Step-by-step	20.18	22.26	0.97	10.49	11.72	0.31
	All-at-once + Graph	31.56	27.50	5.75	25.46	8.09	0.13
	Step-by-step + Graph	30.08	32.50	6.71	23.31	18.68	2.63
QwenLong-L1-32B	All-at-once	11.07	16.10	1.03	5.75	3.80	0.28
	Step-by-step	17.10	18.42	2.98	0.00	31.63	0.00
	All-at-once + Graph	23.83	18.34	3.47	17.44	0.92	0.50
	Step-by-step + Graph	17.69	59.61	2.33	15.00	37.64	1.29

Table 13: Who&When prompts applied to TRAIL with and without the causal-graph context, on open-source models only. **All-at-once**: the original Who&When all-at-once strategy adapted to multi-error TRAIL attribution. **Step-by-step**: the original Who&When step-by-step strategy adapted with cumulative prefixes. **+ Graph**: the selected EDGE inference graph is added to the corresponding prompting strategy. All metrics in %. **Bold**: best result in each model block and metric column.

(c104d0. . . working and 72822d. . . failure) and two GAIA traces (Working-1 dbc070. . . and Not-working-1 ea313e. . .), so successful and failure regimes are represented on both splits.

A.9 Dataset, Compute, and Software

This appendix collects the dataset documentation, inference compute budget, and software-package details that support the experimental setup of Section 4.2, in line with the EMNLP Responsible NLP Checklist (B5, C1, C4).

Source benchmarks, language, and license.

TRAIL (Deshpande et al., 2025) provides span-level multi-error annotations over 148 agent traces drawn from two upstream task corpora: GAIA (Mialon et al., 2024) (general-purpose agentic tasks) and SWE-Bench (Jimenez et al., 2024) (real GitHub-issue code repair). **MAST** (Cemri et al., 2026) provides trace-level multi-label annotations over 393 AutoGen (AG2) multi-agent conversation traces, released as the MAD dataset on Hugging Face (mcmr i /MAD). Both corpora are English-only. All trace content and annotations are pro-

Model	Method	F1	Macro-F1
Mistral-Small-3.1-24B	All-at-once	23.08	15.86
	Step-by-step	5.89	3.82
	All-at-once + Graph	27.13	21.54
	Step-by-step + Graph	6.90	4.71
GPT-oss-120B	All-at-once	22.85	16.14
	Step-by-step	29.44	21.29
	All-at-once + Graph	28.00	20.44
	Step-by-step + Graph	31.78	22.85
GPT-oss-20B	All-at-once	16.36	11.31
	Step-by-step	26.55	19.15
	All-at-once + Graph	21.65	15.70
	Step-by-step + Graph	27.27	19.87
Gemma-3-27B-IT	All-at-once	18.13	11.62
	Step-by-step	11.84	8.65
	All-at-once + Graph	28.13	20.61
	Step-by-step + Graph	13.47	9.69
QwQ-32B*	All-at-once	16.96	12.72
	Step-by-step	18.28	12.84
	All-at-once + Graph	24.55	17.42
	Step-by-step + Graph	17.65	12.02

Table 14: Who&When adaptation results on MAST (393 AG2 traces, all metrics in %). **All-at-once**: Yin et al.’s all-at-once attribution adapted to a trace-level 13-bit yes/no vector (one call per trace). **Step-by-step**: step-by-step attribution OR-aggregated over steps (N calls per trace). **+ Graph**: the selected EDGE inference graph ($\text{corr} \geq 0.50$, 25 edges) is added to the corresponding prompting strategy. **Bold**: best result in each model block (for each metric column).

Model	Method	Reasoning	Sys. Exec.	Planning
GPT-oss-120B	Baseline	20.1	30.7	9.0
	EDGE	28.4	32.5	46.6
	Δ	+8.3	+1.8	+37.6
Mistral-Small-3.1-24B	Baseline	15.4	28.9	7.4
	EDGE	33.7	23.2	31.2
	Δ	+18.3	-5.7	+23.8
Gemini-2.5-Pro	Baseline	34.3	46.1	26.5
	EDGE	39.1	42.1	50.8
	Δ	+4.7	-3.9	+24.3

Table 15: Per-parent recall on TRAIL-GAIA ($n=638$ gold-error instances; Reasoning $n=169$, System Execution $n=280$, Planning & Coord. $n=189$). Recall is the percentage of gold errors in each parent category that the method correctly attributed. $\Delta = \text{EDGE} - \text{Baseline}$. All metrics in %.

Case	Split	Trace	Δ metrics	Propagation evidence	Takeaway	
Working-1	GAIA	dbc070... , Phys.org, target “Bravo”	F1 -0.257; +1.000; +0.667	Loc Joint	Pass-1 detects upstream errors; Pass-2 uses 3 filtered edges and adds 2 downstream errors.	Improves localization and joint alignment but lowers category F1.
Working-2	SWE	c104d0... , SQLFluff issue fix	F1 +0.071; +0.333; Joint 0.000	Loc	Pass-1 detects instruction/resource errors; Pass-2 uses 3 edges and adds 2 errors.	Modest category gain with clearer location gain.
Not-working-1	GAIA	ea313e... , Doctor Who location task	F1 +0.400; 0.000; Joint 0.000	Loc	Pass-1/2 are active, but augmentation shifts location/category alignment.	Category gain does not improve span-level attribution.
Not-working-2	SWE	72822d... , Uni-codeEncodeError/file wipe	F1 0.000; Loc 0.000; Joint 0.000		Pass-1 detects retrieval/output/identification issues; Pass-2 uses 3 edges and adds 2 errors.	Active propagation gives no measurable gain.

Table 16: Case study on **GPT-oss-120B** showing successful and failure regimes of **causal error propagation with corr-thresholded union augmentation**. Deltas are **EDGE minus baseline**. "Propagation evidence" reports whether Pass-2 was triggered and how many filtered edges/new errors were introduced. The causal-only graph variant is discussed as diagnostic context in the text.

duced from publicly available agent executions and contain no personally identifiable human data or human-demographic attributes. The TRAIL repository is released under an MIT-style license, and MAD is distributed under the Hugging Face dataset license documented on the dataset card.

Trace counts and taxonomy size. Table 17 summarizes the two benchmarks. TRAIL covers 19 leaf categories spanning three top-level groups (Reasoning, Execution, Planning and Coordination). The per-split category histograms are listed in the original TRAIL paper. MAST covers 13 leaf categories spanning three top-level groups (Specification, Inter-Agent Misalignment, Verification), with the per-category step-annotation coverage reported in Table 8. TRAIL contains 841 annotated error instances (585 on GAIA, 256 on SWE-Bench), and MAST contains 1,560 positive category labels. The raw traces total approximately 13M tokens, with TRAIL-GAIA traces averaging about 78k tokens each. Edge yields from observational and intervention-validation pipelines on both benchmarks are reported in Table 5 and Table 6.

Domain coverage and intended use. TRAIL-GAIA contains traces from general-purpose agent tasks (web search, document understanding, multimodal reasoning). TRAIL-SWE-Bench contains long-context traces from real GitHub-issue code repair (median trace length around 213K characters, with tail traces exceeding 1M). MAST-AG2 contains shorter multi-agent conversational traces. Our use of both benchmarks falls within their orig-

inal release terms, i.e., research-only evaluation of automatic failure-attribution methods.

Hardware and per-pass compute. Open-weight inference runs were executed on a SLURM-managed cluster partition equipped with NVIDIA A100 GPUs. Each evaluation job requested 4 A100 GPUs on a single node with 256 GB of host memory. Closed-source backbones (Gemini-2.5-Pro, Gemini-2.5-Flash, GPT-4o, GPT-5) were accessed through their hosted APIs and do not consume local GPU time. Table 18 reports the mean per-pass wall-clock and GPU-hour cost. Graph construction and intervention validation are one-time preprocessing steps and are not included in this budget.

LLM serving and inference. Open-weight backbones (Mistral-Small-3.1-24B (Mistral AI, 2025), GPT-oss-20B and GPT-oss-120B (OpenAI et al., 2025), Gemma-3-27B-IT (Team et al., 2025), QwenLong-L1-32B (Wan et al., 2025), QwQ-32B (Qwen Team, 2025), and Qwen3.6-35B-A3B (Qwen Team, 2026)) are served with vllm³ version 0.18.1 using 4-way tensor parallelism, default sampling temperature, and per-model maximum context lengths reported by each model card. Closed-source backbones (GPT-4o (OpenAI et al., 2024), GPT-5 (Singh et al., 2026), Gemini-2.5-Pro and Gemini-2.5-Flash (Comanici et al., 2025)) are accessed through their hosted APIs via litellm⁴.

³<https://github.com/vllm-project/vllm>

⁴<https://github.com/BerriAI/litellm>

Property	TRAIL	MAST
Annotated traces	148	393
GAIA split	117	–
SWE-Bench split	31	–
AG2 split	–	393
Leaf error categories	19	13
Annotated error instances	841	1,560
GAIA split	585	–
SWE-Bench split	256	–
Errors per trace (mean)	5.7	4.0
Corpus size ($\approx$ tokens)	12.7M	0.36M
Top-level groups	3	3
Language	English	English
Domain	Tool usage, code repair	Multi-agent math solving
Annotation level	Span-level	Step-level (we annotate)

Table 17: Overview of the two benchmarks used in our evaluation. Source benchmarks: TRAIL (Deshpande et al., 2025) and MAST (Cemri et al., 2026). Both contain no human-demographic attributes.

Benchmark	Setting	Wall (min)	GPU Hrs
MAST	Baseline	19.2	1.28
MAST	+CG	20.2	1.35
MAST	EDGE (+GI)	24.9	1.66
TRAIL	Baseline	48.8	3.25
TRAIL	+CG	51.2	3.41
TRAIL	EDGE (+GI)	78.5	5.23

Table 18: Mean wall-clock and GPU Hrs per single inference pass on open-weight backbones (GPU Hrs = wall-clock hours $\times$ 4, the A100 count per job). MAST means are over Gemma-3-27B-IT, GPT-oss-20B, and GPT-oss-120B (393 traces). TRAIL means are over Gemma-3-27B-IT, GPT-oss-20B, GPT-oss-120B, and Qwen Family on the full corpus (148 traces). +CG matches Baseline in LLM-call count and adds only a small static graph block, so its wall-clock is Baseline plus a $\sim$ 5% context-overhead margin. EDGE (+GI) further adds a trace-conditioned Stage-2 on top of Stage-1, so its wall-clock is strictly higher than +CG.

Graph construction packages. The Suppes screen and CAPRI-style pruning of Section 3.2 are implemented from scratch in Python rather than via the original R package TRONCO (De Sano et al., 2016). The implementation uses networkx (3.4.2) for directed-acyclic-graph manipulation, with custom hill-climbing over edge add/remove/reverse moves and an AIC-style score (see “Causal Graph Construction Details” in Appendix A.2).

Evaluation packages. All trace-level and span-level metrics are computed with scikit-learn (1.7.2). Weighted F1, macro precision, macro recall, and macro accuracy are obtained from sklearn.metrics with average=“weighted” for the headline F1 and average=“macro” for the macro variants.