

Recurrent Graph Neural Networks with Set-Based Aggregation

Blai Bonet

Universidad Simón Bolívar
Caracas, Venezuela
bonetblai@gmail.com

Abstract

Recurrent GNNs iterate message passing to convergence, and their logical characterizations to date rely on multiset aggregation, graded (counting) logics, and halting or acceptance conditions that cannot be verified from the network’s parameters. We study recurrent GNNs with set-based aggregation and identify sufficient conditions checkable from the weights for networks to compile into formulas and formulas into networks. The main result is an effective, two-directional equivalence between a class of networks and the Boolean closure of reachability and safety properties, the fragment $\mathbf{B}\Sigma_1^\diamond$ of the modal μ -calculus. The fragment is not an artifact: it is the exact expressive level of stabilization over finite vocabulary, which supports fixed points of a single polarity and Boolean combinations thereof, but not the composition of fixed points of opposite polarities. The correspondence needs no counting logic, no external halting signal, and no non-effective acceptance condition, yielding a verifiable path from weights to symbolic explanations for networks meeting the conditions.

Introduction

Graph neural networks (GNNs) (Scarselli et al. 2008) admit a precise reading as logic: a trained network can be compiled into formulas that describe what it computes, and formulas can be compiled into networks that realize them. For depth-bounded nets this correspondence is well understood, with first-order logic with counting characterizing exactly what such networks compute (Xu et al. 2018; Morris et al. 2019; Barceló et al. 2020; Grohe 2024). For recurrent GNNs, which iterate message passing to convergence rather than for a fixed number of layers, the picture is incomplete. Existing characterizations (Pflueger, Tena Cucala, and Kostylev 2024; Ahvonen et al. 2024; Bollen et al. 2025; Rosenbluth and Grohe 2026) are built for multiset aggregation, and their target logics, graded modal logic and the graded μ -calculus, inherit its ability to count. This power is not free: the correspondences rest on explicit halting classifiers or on acceptance conditions that cannot be verified from the network’s weights, and for the graded μ -calculus, the setting with genuine alternation, the converse direction is known only conditionally (Bollen et al. 2025; Bollen and Vansummeren 2026).

We study recurrent GNNs with set-based aggregation, such as max and min, and show that this restriction yields what the multiset setting so far lacks: a complete, effective, two-directional correspondence with a fixed-point logic,

under conditions checkable from the weights. The price is counting and alternation, and we prove the price is unavoidable. Concretely, we identify regularity, a semantic condition under which a converging net’s fixed-point embedding at a vertex depends only on its atomic type and its neighbors’ fixed points, not on the transient trajectory; the vocabulary, the set of embeddings reachable at convergence, which can be finite even when the transients are infinite in number; and admissibility, under which the net’s run can be traded for a finite dynamical system (the game) iterating directly over the vocabulary. Converging regular nets with finite vocabulary whose game is admissible, ordered, and monotone are called **RATCHET** nets. Our contributions are the following:

- A checkable framework for compiling recurrent nets. We introduce regularity, vocabulary, and admissibility, and give sufficient conditions verifiable from the weights: contraction (Theorem 11) and monotonicity (Theorem 11). Unlike the lim-inf and ever-reached acceptance conditions of prior work, membership in the resulting class does not depend on non-effective properties of infinite runs.
- A general-purpose compiler into fixed-point logic. Every regular net with finite vocabulary and an admissible, ordered game compiles into a simultaneous inflationary fixed-point (IFP) formula of size linear in the net’s quotient table, with no monotonicity required (Theorem 14).
- A two-way correspondence. **RATCHET** nets compute exactly the vertex queries definable in $\mathbf{B}\Sigma_1^\diamond$, the Boolean closure of reachability (least fixed points over $\diamond$) and safety (greatest fixed points over $\square$) in the modal μ -calculus, with effective translations in both directions (Theorems 11 and 11). The net-to-logic direction answers, for this counting-free fragment, the converse question that Bollen et al. (2025) leave open in the graded setting; the logic-to-net direction is the counterpart of their Theorem 5.1, obtained without their halting classifier or counting apparatus.
- A barrier showing $\mathbf{B}\Sigma_1^\diamond$ is necessary. No converging regular net with finite vocabulary and admissible game, ordering and monotonicity are not even assumed, computes $\nu Y.\diamond Y$, $\mu X.\square X$, or the alternation-free EF EG p (Proposition 11). Stabilization over finite vocabulary supports fixed points of a single polarity and their Boolean combinations, but cannot certify that an inner fixed point of opposite polarity has stabilized. Indeed, $\mathbf{B}\Sigma_1^\diamond$ omits queries from the

first level of the alternation hierarchy and is strictly contained in the alternation-free fragment (Corollary 11).

- Two implemented compilers, net-to-logic and logic-to-net, that map RATCHET nets to $\mathbf{B}\Sigma_1^\diamond$, and back, together with an extensive experimental validation.

The restriction to set-based aggregation is not arbitrary. Aggregators such as max and min are precisely the empirically preferred choice in neural algorithmic reasoning: max-aggregation message passing was found best suited for learning to execute classical graph algorithms and for size generalization (Veličković et al. 2020; Wittig et al. 2026); this preference has been explained (Xu et al. 2020, 2021; Dudzik and Veličković 2022), and it is the aggregation adopted by the generalist algorithmic learner of Ibarz et al. (2022). Our results give this architectural choice logical meaning.

The correspondence locates set-based recurrent GNNs within the landscape of stopping semantics. A fixed point built on top of one of the opposite polarity requires a certificate that the inner computation has stabilized: supplied externally by a halting classifier (Bollen et al. 2025), or manufactured internally by counters that grow with the graph (Bollen and Vansummeren 2026). Proposition 17 shows that with neither resource available, no certificate exists, and $\mathbf{B}\Sigma_1^\diamond$ is exactly what remains; details below.

Roadmap. After fixing the model and vertex types, we develop the recurrent case, RATCHET nets, and the IFP compiler. The central section establishes the equivalence with $\mathbf{B}\Sigma_1^\diamond$ and the barrier. We close with related work and conclusions.

GNNs with Set-Based Aggregation

Graphs are denoted with the letters $x, y, \dots$, and vertices with $u, v, \dots$. The vertex and edge set for graph x are denoted by $V(x)$ and $E(x)$ respectively, $E(x, u, v)$ is the edge relation (or $E(u, v)$ when x is clear from context), and $N(u) = N(x, u) = \{v \in V(x) \mid E(x, u, v)\}$ is vertex u 's neighborhood. A finite and non-empty set ATP of *atomic types* that partitions the vertices on every graph is **fixed throughout**: $\text{atp}(u)$ is the atomic type of vertex u . A graph x is a relational structure with universe $V(x)$, edge relation E , and unary relations $\{\alpha(\cdot) \mid \alpha \in \text{ATP}\}$. A *pointed graph* is a pair (x, u) for graph x and distinguished $u \in V(x)$.

A feature or *embedding* is a vector in $\mathbb{R}^W$ whose components are called *registers*. For atomic type α and layer index ℓ , the GNN architecture fixes:

- an *initial embedding* $e_\alpha \in \mathbb{R}^W$,
- weight tensors $\mathbf{A}_{\alpha,\ell}, \mathbf{B}_{\alpha,\ell} \in \mathbb{R}^{W \times W}$ and $\mathbf{C}_{\alpha,\ell} \in \mathbb{R}^W$,
- combination function $\oplus_\ell : \wp(\mathbb{R}^W) \rightarrow \mathbb{R}^W$ that maps **finite** subsets to embeddings, and
- component-wise *activation functions* $\rho_\ell : \mathbb{R} \rightarrow \mathbb{R}$.

For simplicity, we assume architectures with equal combination and activation functions across layers, but this is not an essential distinction. For activation functions, we consider $\text{ReLU}(x) = \max(0, x)$ and the *truncated ReLU* (or clipped linear unit) $\text{clip}_{[0,1]}(x) = \min(1, \max(0, x))$. These tensors and functions make up the parameter θ of the net.

The central object is the one-step update at layer ℓ :

$$\text{Net}_\ell(\alpha, z, S) = \rho(\mathbf{A}_{\alpha,\ell} z + \mathbf{B}_{\alpha,\ell} \oplus S + \mathbf{C}_{\alpha,\ell}) \quad (1)$$

where $\alpha \in \text{ATP}$ is an atomic type, $z \in \mathbb{R}^W$ is the current embedding of a vertex, $S \subseteq \mathbb{R}^W$ is the (finite) set of neighbor embeddings, and $\oplus S$ is their aggregation, with the convention $\oplus \emptyset = \mathbf{0}$ (the zero vector), so that (1) is well defined for isolated vertices. This is a concrete architecture choice but others are also compatible with our results.

In the depth-bounded or non-recurrent case, the net is defined for a fixed number L of layers. The net iterates the updates synchronously over all vertices. Starting from $u^{(0)} = e_{\text{atp}(u)}$, the embedding of vertex u in graph x at layer $\ell+1$ is

$$u^{(\ell+1)} = \text{Net}_\ell(\text{atp}(u), u^{(\ell)}, \{v^{(\ell)} \mid E(x, u, v)\}).$$

We write $u_{x,\theta}^{(\ell)}$ when the dependence on the graph and parameter must be made explicit. In the recurrent case, we assume equal weight tensors across layers and denote the one-step function simply as $\text{Net}(\alpha, z, S)$. The architecture is *converging* if $u_{x,\theta}^{(\ell)}$ converges in $\mathbb{R}^W$ as $\ell \rightarrow \infty$, for every graph x and vertex u , in which case the limit is denoted as $u_{x,\theta}^*$. Convergence of the iteration is non-trivial and depends on the interaction between the weight matrices, the activation function, and the graph structure.

For simplicity, the recurrent net iterates a single-layer block. Our results extend to L -layer recurrent blocks, where an entire iteration of the block replaces a single-step update.

Notice that graphs are directed: E is an arbitrary binary relation, $N(u)$ is the set of E -successors of u , and no symmetry is assumed; undirected graphs are the special case of symmetric E , so all positive results below apply to them.

Finite Types and Their Embeddings

The vertex types correspond to the different colors obtained by 1-WL under *set aggregation* (Weisfeiler and Leman 1968; Cai, Fürer, and Immerman 1992; Grohe 2017). Recall that ATP is the fixed set of atomic types.

Definition 1 (Types). *The sequence $\langle \text{TP}^{(\ell)} \rangle_{\ell \geq 0}$ of types is: $\text{TP}^{(0)} = \text{ATP}$, and $\text{TP}^{(\ell+1)} = \{(t, S) \mid t \in \text{TP}^{(\ell)}, S \subseteq \text{TP}^{(\ell)}\}$. The atomic type of type t is $\text{atp}(\alpha) = \alpha$ for $\alpha \in \text{ATP}$, and $\text{atp}(t) = \text{atp}(t')$ for $t = (t', S') \in \text{TP}^{(\ell)}$ with $\ell \geq 1$.*

The (finite) type $\tau^{(\ell)}(x, u)$ for pointed graph (x, u) and $\ell \geq 0$ is given by $\tau^{(0)}(x, u) = \text{atp}(u)$, and $\tau^{(\ell+1)}(x, u) = (t, S)$ iff $\tau^{(\ell)}(x, u) = t$ and $S = \{\tau^{(\ell)}(x, v) \mid E(u, v)\}$.

The types at layer ℓ correspond to the equivalence classes of an ℓ -bisimulation relation under set-based aggregation: two vertices of the same type obtain the same embeddings regardless of the architecture. Hence, the embeddings that a depth-bounded net with set-based aggregation can generate are finite and determined by the types:

Definition 2. *The embedding function $\mathbb{E}_t : \Theta \rightarrow \mathbb{R}^W$, one per type t , maps parameters into embeddings:*

1. for $\alpha \in \text{ATP}$, $\mathbb{E}_\alpha(\theta) = e_\alpha$ is a constant function of θ , and
2. for (t, S) in $\text{TP}^{(\ell+1)}$ where t is of atomic type α , $\mathbb{E}_{(t,S)}(\theta) = \text{Net}_\ell(\alpha, \mathbb{E}_t(\theta), \{\mathbb{E}_{t'}(\theta) \mid t' \in S\})$.

When θ is clear from context, we write $\mathbb{E}_t$ instead of $\mathbb{E}_t(\theta)$.

Theorem 17. *Let θ be a parameter, let (x, u) be a pointed graph, and let $\ell \geq 0$ be a layer index within the architecture. Then, $u_{x,\theta}^{(\ell)} = \mathbb{E}_t(\theta)$ for $t = \tau^{(\ell)}(x, u)$.*

Compiling Depth-Bounded Nets

A direct byproduct of the relation between types and embeddings is a “compiler” that maps nets into logical formulas that characterize the embeddings. The idea is to have logical formulas that decide the types, and use the parameter-to-embedding function to logically characterize the net. As the embeddings are real vectors, we settle for a logical characterization that test whether a register of the final embedding is greater than zero, but other criteria are possible.

Definition 4. For each type t , there is formula $\tau_t(z)$ that holds in pointed graph (x, u) iff $\tau^{(\ell)}(x, u) = t$ where ℓ is the layer of t :

- $\tau_\alpha(z) = \alpha(z)$, and
- $\tau_{(t,S)}(z) = \tau_t(z) \wedge [\forall w (E(z, w) \implies \bigvee_{t' \in S} \tau_{t'}(w))] \wedge [\bigwedge_{t' \in S} \exists w (E(z, w) \wedge \tau_{t'}(w))]$.

Per definition, vertex u satisfies $\tau_{(t,S)}$ iff its type is t , each neighbor has a type in S , and each type in S is witnessed by some neighbor. A logical characterization of embeddings follows whose soundness is established by induction on ℓ :

Definition 5. Let θ be a parameter for the architecture (W, L, ATP) of width W , depth L , and atomic types in ATP. The logical characterization of the embeddings at layer ℓ is the vector

$$\Psi^{(\ell)}(z) = \langle \psi_1^{(\ell)}(z), \dots, \psi_W^{(\ell)}(z) \rangle$$

where $\psi_i^{(\ell)}(z) = \bigwedge_{t \in \text{TP}^{(\ell)}} (\tau_t(z) \implies [\llbracket \mathbb{E}_t(\theta) \rrbracket_i > 0])$.

Theorem 17 (Compiler). Let θ be a parameter of the architecture (W, L, ATP) . Then, $[u_{x,\theta}^{(\ell)}]_i > 0$ iff $x \models \psi_i^{(\ell)}(u)$.

The size of $\text{TP}^{(\ell)}$ is a tower of exponentials, related to the number of Hintikka-style normal forms of modal formulas of modal depth $\leq \ell$, supporting the blow-up empirically reported (Tena Cucala and Cuenca Grau 2024; Tena Cucala et al. 2022) for similar compilations.

Recurrent Nets

Getting a characterization in the recurrent case is harder: the net converges in a number of steps that is not bounded, and the set of types the net may see as well as the number of fixed-point embeddings it may reach are also unbounded.

The embedding for pointed graph (x, u) is the limit u_x^* , which by Theorem 17, equals $\lim_{\ell \rightarrow \infty} \mathbb{E}_{\tau^{(\ell)}(x, u)}$. Its **infinite type** $\tau(x, u)$ is the sequence $\langle \tau^{(\ell)}(x, u) \rangle_{\ell \geq 0}$ of finite types, while the function $\Phi(\cdot)$ maps infinite types into (limit) embeddings: $\Phi(\tau(x, u)) \doteq \lim_{\ell \rightarrow \infty} \mathbb{E}_{\tau^{(\ell)}(x, u)}$. An infinite type is an equivalence class for a bisimulation that uses set-based aggregation of neighbor types. The set $\text{TP}^{(\omega)} = \{\tau(x, u) \mid (x, u) \text{ is pointed graph}\}$ is the set of infinite types. For converging nets, Φ is a well-defined and total function on $\text{TP}^{(\omega)}$. The following is direct:

Lemma 17 (Bisimulation invariance). Let (x, u) and (x', u') be two pointed (finite) graphs. Then, (x, u) and (x', u') are bisimilar, written as $(x, u) \sim (x', u')$, iff $\tau(x, u) = \tau(x', u')$. Hence, if $(x, u) \sim (x', u')$, then $\Phi(\tau(x, u)) = \Phi(\tau(x', u'))$.

At convergence, the net reaches an equilibrium where the vertices u of the graph satisfy the system:

$$u^* = \text{Net}(\text{atp}(u), u^*, \{v^* \mid E(x, u, v)\}).$$

As the neighbors “shield” u from other vertices in the graph, it is natural to expect for u^* to be *determined* by its atomic type $\text{atp}(u)$ and $S = \{v^* \mid E(x, u, v)\}$. We interpret determination in this context as $u^* = \lim_{\ell \rightarrow \infty} z_\ell$ where the sequence $\langle z_\ell \rangle_{\ell \geq 0}$ satisfies $z_0 = e_\alpha$ and $z_{\ell+1} = \text{Net}(\alpha, z_\ell, S)$ for $\alpha = \text{atp}(u)$. Another notion asks for u^* to be the *unique* fixed point of $z \mapsto \text{Net}(\alpha, z, S)$, but this is too strong and doesn’t cover interesting cases. However, even this weaker notion is not always satisfied, and thus motivates:

Definition 8 (Regular nets). Let $\text{Net}(\cdot, \cdot, \cdot)$ be a **converging** recurrent architecture for the atomic types in ATP. The net is **regular** iff for every pointed structure (x, u) of type α :

$$\Phi(\tau(x, u)) = F_\alpha(S) \doteq \lim_{\ell \rightarrow \infty} z_\ell$$

where $S = \{\Phi(\tau(x, v)) \mid E(x, u, v)\}$, and $\langle z_\ell \rangle_{\ell \geq 0}$ satisfies $z_0 = e_\alpha$ and $z_{\ell+1} = \text{Net}(\alpha, z_\ell, S)$.

Theorem 17. Let $\text{Net}(\cdot, \cdot, \cdot)$ be a regular net for the atomic types in ATP, and let (x, u) and (x', u') be pointed graphs of the same atomic type $\alpha \in \text{ATP}$. If $\{\Phi(\tau(x, v)) \mid E(x, u, v)\} = \{\Phi(\tau(x', v')) \mid E(x', u', v')\}$, then $\Phi(\tau(x, u)) = \Phi(\tau(x', u'))$.

The **vocabulary** of the net is constructed by closing the initial embeddings with the operators in $\{F_\alpha \mid \alpha \in \text{ATP}\}$. For the sequence $\langle \mathcal{V}_k \rangle_{k \geq 0}$ where $\mathcal{V}_0 = \{F_\alpha(\emptyset) \mid \alpha \in \text{ATP}\}$ is the set of fixed-point embeddings for isolated vertices, and $\mathcal{V}_{k+1} = \mathcal{V}_k \cup \{F_\alpha(S) \mid \alpha \in \text{ATP}, S \subseteq \mathcal{V}_k\}$, the vocabulary $\mathcal{V}$ is the **closure** of $\bigcup_{k \geq 0} \mathcal{V}_k$, when all these sets are defined; otherwise, $\mathcal{V}$ is undefined. When defined, the set $\mathcal{V}$ is closed under $F_\alpha(S)$ for **finite** subsets $S \subseteq \mathcal{V}$, and by taking limits since $\mathcal{V}$ is a (topologically) closed set.

Below there are conditions for a net to be regular with well-defined vocabulary. In such a case, Φ factors the space of infinite types into equivalence classes: $\bar{t} \sim \bar{t}'$ iff $\Phi(\bar{t}) = \Phi(\bar{t}')$. The quotient table $\mathcal{T} : \text{ATP} \times \wp(\mathcal{V}) \rightarrow \mathcal{V}$ maps atomic types and **finite** subsets of embeddings into embeddings as $(\alpha, S) \mapsto F_\alpha(S)$. The embedding for pointed graph (x, u) is $\Phi(\tau(x, u)) = \mathcal{T}(\alpha, \Phi(S))$ for $\alpha = \text{atp}(u)$ and $S = \{\tau(x, v) \mid E(x, u, v)\}$. The table doesn’t know about infinite types, only about atomic types and embeddings in the vocabulary.

A crucial question is whether $\Phi(\tau(x, u))$ can be computed from the table alone, without the need to construct types.

For fixed graph x with n vertices, we consider tensors $\mathbf{E} \in \mathbb{R}^{nW}$ which contain embeddings $\mathbf{E}_u \in \mathbb{R}^W$ for each vertex u . Let $\langle \mathbf{E}^k \rangle_{k \geq 0}$ be the sequence $\mathbf{E}_u^0 \doteq F_\alpha(\emptyset)$ if u is of atomic type α , and $\mathbf{E}_u^{k+1} \doteq \mathcal{T}(\alpha, \{\mathbf{E}_v^k \mid E(x, u, v)\})$. The sequence is well defined and $\mathbf{E}_u^k \in \mathcal{V}$ for each vertex u and $k \geq 0$. Does $\mathbf{E}_u^k \rightarrow \Phi(\tau(x, u))$ as $k \rightarrow \infty$?

If the vocabulary $\mathcal{V}$ is finite, the sequence $\langle \mathbf{E}^k \rangle_{k \geq 0}$ is the trace of a cellular automaton (Wolfram 2002) on the graph x , where each vertex starts at a configuration determined by its atomic type, and changes its configuration according to the configuration of its neighbors as dictated by the table.

Definition 10 (Dynamical systems). Let $\text{Net}(\cdot, \cdot, \cdot)$ be a regular net with vocabulary $\mathcal{V}$.

- For graph x with n vertices, the **game** induced by $\mathcal{T}$ on x is the dynamical system on $\mathcal{V}^n$:

$$\mathbf{E}_u^0 = F_\alpha(\emptyset), \quad \mathbf{E}_u^{k+1} = \mathcal{T}(\alpha, \{\mathbf{E}_v^k \mid E(x, u, v)\}).$$

where $\alpha = \text{atp}(u)$ is the atomic type for vertex u .

- The game is **admissible for graph** x iff $\lim_{k \rightarrow \infty} \mathbf{E}_u^k = \Phi(\tau(x, u))$ for every vertex $u \in V(x)$, and it is **admissible** iff it is admissible for every graph.
- The game is **ordered** iff there is an order $(\mathcal{V}, \preceq)$ such that $\mathbf{E}_u^k \preceq \mathbf{E}_u^{k+1}$ for every graph x , vertex u in x , and $k \geq 0$.
- The game is **monotone** iff, writing $S \sqsubseteq S'$ for finite $S, S' \subseteq \mathcal{V}$ to mean every $e \in S$ is $\preceq$ -dominated by some $e' \in S'$, the table satisfies $\mathcal{T}(\alpha, S) \preceq \mathcal{T}(\alpha, S')$ whenever $S \sqsubseteq S'$.

For admissible tables over finite vocabulary, running the dynamical system is equivalent to running the net. As the states of the dynamical system correspond to the net's final embeddings, the dynamical system may converge faster than the net. For a graph of order n , an admissible dynamical system converges within $|\mathcal{V}|^n$ steps, or $n(|\mathcal{V}| - 1)$ steps if the game is ordered. Contractive nets converge in the limit.

A converging regular net with finite vocabulary whose game is admissible, ordered and monotone is called a RATCHET net. Corollary 17 shows that for $\oplus = \max$, the induced game is monotone. If the vocabulary is totally ordered by $\preceq$, the size of the table reduces to $\mathcal{O}(|\text{ATP}| \cdot (|\mathcal{V}| + 1))$.

Contractive Nets

The original recurrent GNN is a contractive net (Scarselli et al. 2008), and the regime persists in modern equilibrium models: implicit GNNs (Gu et al. 2020) enforce a weight-norm contraction bound by projection during training, guaranteeing convergence by construction — a checkable condition of the same species as Theorem A1. The architecture $\text{Net}(\cdot, \cdot, \cdot)$ over the atomic types ATP is **contractive for** $\|\cdot\|$, if there is $\lambda \in (0, 1)$ such that for each α , embeddings $z, z' \in \mathbb{R}^W$, and finite subsets $S, S' \subseteq \mathbb{R}^W$:

$$\begin{aligned} \|\text{Net}(\alpha, z, S) - \text{Net}(\alpha, z', S')\| \\ \leq \lambda \max(\|z - z'\|, \|\oplus S - \oplus S'\|), \end{aligned}$$

whereas it is **contractive in** z if is contractive when $S = S'$. The aggregator $\oplus$ is **1-Lipschitz for** $\|\cdot\|$, if for any two vertex-indexed sets $S = \{e_v \mid v \in N\}$ and $S' = \{e'_v \mid v \in N\}$: $\|\oplus S - \oplus S'\| \leq \max_{v \in N} \|e_v - e'_v\|$. (Notice that S and S' may have different size even though both are indexed by N .)

Theorem 17 (Contractive nets). Let $\text{Net}(\cdot, \cdot, \cdot)$ be a recurrent net over the atomic types in ATP, and let $\|\cdot\|$ be a norm in $\mathbb{R}^W$. Then:

1. If the net is contractive for $\|\cdot\|$ and the aggregator is 1-Lipschitz for $\|\cdot\|$, the net is converging.
2. If the net is converging and **contractive in** z for $\|\cdot\|$, the net is regular and the vocabulary is well defined.
3. If the net is contractive and the aggregator is 1-Lipschitz (both) for $\|\cdot\|$, the net is regular, the vocabulary is well defined, and the game is admissible.

Nets that satisfy the conditions of Theorem 17 are those with max aggregator and tensors such that $\|\mathbf{A}_\alpha\|_\infty < 1$ (contractive in z for L_∞), and $\|\mathbf{A}_\alpha\|_\infty + \|\mathbf{B}_\alpha\|_\infty < 1$ (fully contractive for L_∞) (see Theorem A1 in appendix).

Monotone Nets

The architecture $\text{Net}(\cdot, \cdot, \cdot)$ is **monotone** if for each α , embeddings $z, z' \in \mathbb{R}^W$, and finite subsets $S, S' \subseteq \mathbb{R}^W$:

$$z \leq z' \wedge \oplus S \leq \oplus S' \implies \text{Net}(\alpha, z, S) \leq \text{Net}(\alpha, z', S').$$

The aggregator $\oplus$ is **monotone** if for any two vertex-indexed embedding sets $S = \{e_v \mid v \in N\}$ and $S' = \{e'_v \mid v \in N\}$: $\forall (v \in N)[e_v \leq e'_v] \implies \oplus S \leq \oplus S'$.

Theorem 17 (Monotone nets). Let $\text{Net}(\cdot, \cdot, \cdot)$ be a converging net over the atomic types in ATP. Assume the initial embeddings are non-negative pre-fixed points of the isolated-vertex update: $0 \leq e_\alpha \leq \text{Net}(\alpha, e_\alpha, \emptyset)$ for $\alpha \in \text{ATP}$. Then:

1. If the net is monotone, the vocabulary is well defined.
2. If the net and the aggregator are both monotone, the net is regular, and the game is admissible and ordered.

Any fixed point is a pre-fixed point, and the all-zero initialization satisfies the hypothesis automatically for ReLU or clipped activations, since $\text{Net}(\alpha, 0, \emptyset) = \rho(C_\alpha) \geq 0$.

Corollary 17. Under the hypotheses of Theorem 17 with $\oplus = \max$, the game is monotone. Hence $\mathcal{T}(\alpha, S) = F_\alpha(S) \leq F_\alpha(S') = \mathcal{T}(\alpha, S')$ whenever $S \sqsubseteq S'$.

Nets that satisfy conditions of Theorem 17 are those with max aggregator and matrices $\mathbf{A}$ and $\mathbf{B}$ with non-negative weights (Theorem A2 in appendix). If all weights are non-negative integers, the activation function is clipped, and the initial embeddings are integer valued, the vocabulary is finite.

The order is what turns the dynamical system from an unconstrained automaton into a stable, terminating one: forcing each vertex forward through a fixed ladder of states rules out cycles and oscillation. For finite vocabulary, the system is the trace of a cellular automaton over the graph, with local rule given by table $\mathcal{T}$ (Grattarola, Livi, and Alippi 2021).

Why compile the game rather than the run itself? Evaluating a fixed-point formula on a finite graph is an iteration over tuples of vertex sets that stabilizes in $\mathcal{O}(|V(x)|)$ rounds; the net's run instead traverses a possibly infinite set of transient embeddings, possibly over infinite time. A finitary formula can therefore track the net only through a finite quotient of its state space, and the game is exactly that quotient with its induced dynamics. The lim-inf acceptance of Pflueger, Tena Cucala, and Kostylev (2024) and the ω GML characterization of (Ahvonen et al. 2024) are trajectory-dependent semantics, but they are infinitary or non-effective. At convergence the limits satisfy $\Phi_u = \mathcal{T}(\alpha, \{\Phi_v \mid E(u, v)\})$, a system that in general has several solutions, of which the transients select one; fixed-point logic can only name the extremal, iteratively generated solutions. Admissibility says the dynamics selects the solution iteration does.

Translating Recurrent Nets into IFP

We work with *inflationary fixed-point logic* (IFP) over a relational signature σ . Over finite structures (our target), IFP

is equivalent to least fixed-point logic (LFP) (Gurevich and Shelah 1986), but it has a simpler syntax and semantics.

For formula $\psi(R; \bar{z})$ in $\text{FO}[\sigma \cup \{R\}]$, where $k = |\bar{z}|$ and R is a new relation of arity k , the IFP constructor is $[\text{ifp}_{R, \bar{x}} \psi(R, \bar{x})](\bar{t})$ where $\bar{t}$ is a tuple of terms of size k . Such a formula holds iff $\bar{t} \in R^*$ where R^* is the inflationary fixed point of the one-step formula $\psi(R; \bar{z})$; see appendix. IFP is extended to fixed points of multiple relations, simultaneously, by considering vectors $\mathbf{R} = \langle R_1, \dots, R_m \rangle$ of relations defined by a vector $\psi((R); \bar{z}) = \langle \psi_1, \dots, \psi_m \rangle$ of one-step relations. Then, $[\text{ifp}_{\mathbf{R}, \bar{x}} \psi(\mathbf{R}, \bar{x})](\bar{t})$ iff $\bar{t}$ belongs to R_j^* .

Theorem 14 (IFP Compiler). *Let $\text{Net}(\cdot, \cdot, \cdot)$ be a regular net for the atomic types in ATP with finite vocabulary $\mathcal{V} = \{e_1, \dots, e_m\}$, and whose game is admissible and ordered, but no game monotonicity required. There is a vector $\psi(\mathbf{R}; z) = \langle \psi_1, \dots, \psi_m \rangle$ of 1-step unary relations such that*

$$\langle \Psi_1, \dots, \Psi_m \rangle(u) \equiv [\text{ifp}_{\mathbf{R}; z} \psi(\mathbf{R}; z)](u)$$

characterizes the net; i.e., for pointed graph (x, u) and index i : $\Phi(\tau(x, u)) = e_i$ iff $x \models \Psi_i(u) \wedge \bigwedge_{e_i \prec e_j} \neg \Psi_j(u)$.

Examples

Reachability of red vertices in graphs with black and red vertices can be solved with a net that implements a Boolean propagator: vertex u gets a mark if it is already marked, or some neighbor is marked. The net has atomic types $\{b, r\}$, width $W = 1$, clipped activation, and initial embeddings, $e_b = 0$ and $e_r = 1$, that are fixed points of isolated vertices. By Theorem 17 (and A2 in appendix), the net is regular, the game is admissible and ordered over $\mathcal{V} = \{e_b, e_r\}$, and the table is:

Atomic type α	Neighborhood S	$\mathcal{T}(\alpha, S)$
black	$S \subseteq \{0\}$	0
black	$1 \in S$	1
red	any	1

The compiler yields the one-step IFP formulas:

$$R_b(u) \equiv b(u) \wedge \forall v [E(u, v) \implies R_b(v) \wedge \neg R_r(v)],$$

$$R_r(u) \equiv r(u) \vee (b(u) \wedge \exists v [E(u, v) \wedge R_r(v)])$$

that match the standard one-step formulas for reachability.

Contractive net. The same atomic types, width, and initial embeddings, but with parameters $\mathbf{A}_\alpha = -\frac{1}{2}$ and $\mathbf{B}_\alpha = 2$ for $\alpha \in \{b, r\}$, $\mathbf{C}_b = \frac{1}{2}$, and $\mathbf{C}_r = 1$. The fixed-point embeddings for isolated black and red vertices $\frac{1}{3}$ and $\frac{2}{3}$, resp., are reached through infinite oscillating transient sequences. The emergent vocabulary $\mathcal{V} = \{e_1 = \frac{1}{3}, e_2 = \frac{2}{3}, e_3 = \frac{7}{9}, e_4 = 1\}$ is finite and ordered, $e_1 \prec e_2 \prec e_3 \prec e_4$, with table:

$\max S$	$\mathcal{T}(b, S)$	$\mathcal{T}(r, S)$
0	e_1	e_2
e_1	e_3	e_4
e_2	e_4	e_4
e_3	e_4	e_4
e_4	e_4	e_4

The net meets the required properties (Proposition A5 in appendix), but neither Theorem 17 nor Theorem 17; illustrating that the class extends beyond the two sufficient conditions.

Equivalence with $\mathbf{B}\Sigma_1^\diamond$

We now establish the paper's central result: the vertex queries implementable by RATCHET nets are exactly those definable in the fragment $\mathbf{B}\Sigma_1^\diamond$ of modal μ -calculus. The formulas in modal μ -calculus, denoted as $L\mu$, over a set of atomic propositions P and propositional variables X are:

$$\varphi ::= p \mid \neg p \mid \varphi \wedge \varphi \mid \varphi \vee \varphi \mid \diamond \varphi \mid \square \varphi \mid X \mid \mu X. \varphi \mid \nu X. \varphi$$

For the evaluation of formulas φ at pointed graphs (x, u) (semantics) see elsewhere, e.g., (Arnold and Niwiński 2001).

A closed formula is in $\Sigma_1^\diamond$ if it is built from literals ($p, \neg p$), conjunction, disjunction, $\diamond$, and μ only; it is in $\Pi_1^\square$ if it is built from literals, conjunction, disjunction, $\square$, and ν only. The two classes are dual: negating a $\Sigma_1^\diamond$ formula and pushing negation to the atoms yield a $\Pi_1^\square$ formula and vice versa. $\mathbf{B}\Sigma_1^\diamond$ is the closure of $\Sigma_1^\diamond \cup \Pi_1^\square$ under Boolean connectives; equivalently, the Boolean closure of $\Sigma_1^\diamond$ alone. Every $\mathbf{B}\Sigma_1^\diamond$ formula is alternation-free, but $\mathbf{B}\Sigma_1^\diamond$ does not contain the first level $\Sigma_1^\mu \cup \Pi_1^\nu$: it excludes least fixed points that use $\square$ and greatest fixed points that use $\diamond$, such as $\mu X. \square X$ (well-foundedness) and $\nu Y. \diamond Y$ (existence of an infinite path). Proposition 17 shows this exclusion is forced: those formulas are not computable by any RATCHET net, so $\mathbf{B}\Sigma_1^\diamond$, not the first level and not the alternation-free fragment, is the exact target for equivalence.

$\mathbf{B}\Sigma_1^\diamond$ has a semantic reading that matches our dynamics. A $\Sigma_1^\diamond$ formula true at u is true on some finite truncation of the unfolding and remains true on every extension. Dually, a $\Pi_1^\square$ formula that fails is refuted on a finite truncation. $\mathbf{B}\Sigma_1^\diamond$ is the Boolean closure of finitely verifiable and finitely refutable properties, the branching-time analogue of the obligation class of Manna and Pnueli (1990).

Theorem 17 (Net-to-logic). *Let $\text{Net}(\cdot, \cdot, \cdot)$ be a RATCHET net with vocabulary $\mathcal{V} = \{e_1, \dots, e_m\}$ of size m . There are $\mathbf{B}\Sigma_1^\diamond$ formulas $\gamma_1, \dots, \gamma_m$ such that for any pointed graph (x, u) and $i \in \{1, \dots, m\}$: $\Phi(\tau(x, u)) = e_i$ iff $(x, u) \models \gamma_i$.*

Theorem 17 answers, for the counting-free, $\mathbf{B}\Sigma_1^\diamond$ fragment, the converse question that Bollen et al. (2025) leave open in the graded setting. Its proof compiles the table into an intermediate system of mutually recursive, guarded, negation-free fixed-point definitions (one per vocabulary element, with one disjunct per row of $\mathcal{T}$) and then flattens this system into closed $L\mu$ formulas with Bekič's elimination (Arnold and Niwiński 2001). This two-stage process determines the size of the output, which we measure against the quotient table $\mathcal{T}$. The size of the intermediate system, equivalently, the simultaneous IFP formula in Theorem 14, is linear in $|\mathcal{T}|$ when measured as a system with shared definitions (each row and each curr_i defined once and referenced); written out as a tree it incurs an additional factor $|V|$. The closed formulas in $L\mu$ may be of exponential size because of Bekič's elimination. Theorem 17 provides two guarantees of different strength: the closed terms γ_i always exist and are computable from the net, while the linear size bound holds for the system of definitions from which they are flattened. Considering the system as the primary output of the Theorem is consistent with practice in verification, where the linear-time model-checking algorithms for the alternation-free μ -calculus evaluate such equation systems directly, without constructing a

flattened closed formula (Andersen 1994; Cleaveland and Steffen 1991; Vergauwen and Lewi 1994).

The other direction maps $\mathbf{B}\Sigma_1^\diamond$ formulas over propositions that capture atomic types into RATCHET nets. Propositions that do not correspond to atomic types can be accounted for by considering the different Boolean valuations.

Theorem 17 (Logic-to-net). *For every $\mathbf{B}\Sigma_1^\diamond$ formula γ , there is a RATCHET architecture $\text{Net}(\cdot, \cdot, \cdot)$ and register index m such that for any pointed graph (x, u) : $(x, u) \models \gamma$ iff $[\Phi(\tau(x, u))]_m = 1$.*

Theorem 17 is the counting-free counterpart of Bollen et al.’s Theorem 5.1. Its proof realizes the classical cluster-elimination method for alternation-free equation systems. The proof is aggregator-agnostic; only graded modalities would require threshold-sum registers and hence multisets, and whether this route yields a simpler graded construction than the halting-and-counting apparatus of Bollen et al. is open. What blocks going beyond $\mathbf{B}\Sigma_1^\diamond$ is that stabilization over a finite vocabulary is a flat, one-timescale process.

Besides the theorems, regularity is identified as the semantic condition matching μ -calculus: both make the limit value at a vertex depend only on the limit value at its neighbors, not on the trajectory by which the limits are reached. Admissibility and finiteness play complementary roles: they are not needed to state what a regular net’s fixed points are, but they make those fixed points computable by a terminating procedure and the resulting formula finite.

The fragment is also a ceiling as shown by Proposition 17 which assumes only regularity, finite vocabulary, and admissibility but no ordered or monotone game. The proof exploits a blind spot of stabilization. On a directed path and on a self-loop, every vertex feeds the game the same local information, so both runs traverse the same sequence $t_0, t_1, \dots$ of table values; since $\mathcal{V}$ is finite, this sequence stabilizes at some t_K . Admissibility then assigns the head of any path of length $k \geq K$, where no infinite path exists, and the self-loop, where one does, the same limit t_K . Thus, any readout must give both instances the same verdict, while $\nu Y. \Diamond Y$ and its relatives assign them different truth values. It is open whether the fragment is a ceiling for undirected graphs.

Proposition 17 (Barrier). *Let $\text{Net}(\cdot, \cdot, \cdot)$ be a converging regular net with finite vocabulary whose game is admissible (ordering and monotonicity are not assumed). Then, Net does not compute the queries: $\nu Y. \Diamond Y$, $\mu X. \Box X$, $EG p = \nu Y. (p \wedge \Diamond Y)$, and $EF EG p = \mu X. (\Diamond X \vee \nu Y. (p \wedge \Diamond Y))$.*

Corollary 17. *Over finite pointed graphs, as classes of unary queries: (i) $\Sigma_1^\mu \cup \Pi_1^\mu \not\subseteq \mathbf{B}\Sigma_1^\diamond$, witnessed by $\mu X. \Box X \in \Sigma_1^\mu$ and $\nu Y. \Diamond Y \in \Pi_1^\mu$; and (ii) $\mathbf{B}\Sigma_1^\diamond$ is strictly contained in the alternation-free fragment, witnessed by $EF EG p$.*

Examples

Let’s apply the net-to-logic translation to the previous example that is ordered $e_1 \prec e_2 \prec e_3 \prec e_4$, and monotone (by table inspection). We obtain the $\mathbf{B}\Sigma_1^\diamond$ formulas: $\gamma_1 \equiv b \wedge \neg \Diamond \top$ (black sink), $\gamma_2 \equiv r \wedge \neg \Diamond \top$ (red sink), $\gamma_3 \equiv b \wedge \Diamond \top \wedge \Box (b \wedge \neg \Diamond \top)$ (black, with successors, all of them black sinks), and $\gamma_4 \equiv (r \wedge \Diamond \top) \vee (b \wedge \Diamond (r \vee (b \wedge \Diamond \top)))$ (everything else).

Interestingly, this net, despite infinitely many transient embeddings, computes a fixpoint-free query of modal depth 2.

On the other hand, let us consider the $\mathbf{B}\Sigma_1^\diamond$ formula $\gamma = \mu X. (r \vee \Diamond X) \wedge \neg \mu Y. (g \vee \Diamond Y)$ over a graph with atomic types $\{r, b, g\}$ (red, black and green). γ is the classic example for reachability–safety Boolean combinations (reach the red avoid the green). The logic-to-net translator gives a net of width 2 (after simplification) that tracks the two fixed point computations for reachability and safety. A further application of the net-to-logic recovers γ (see appendix).

Experimental Validation

We implemented both compilers and ran a differential test: for 13 branching-time properties drawn from the model-checking literature, we compile γ to a net, extract the game table from that net, compile the table back into an equation system, and compare its denotation against an independent reference evaluator of $L\mu$, on ≥ 30 random pointed graphs per property. Across 9,960 pointed-graph checks there is not a single discrepancy. The property suite, graph generation, seeds, and per-property true/false splits are in the appendix.

Related Work

Depth-bounded GNNs and logic. The correspondence between depth-bounded GNNs and FOL with counting is well understood (Xu et al. 2018; Morris et al. 2019; Barceló et al. 2020; Grohe 2024); the translation for depth-bounded nets build on this line, providing ingredients for the recurrent case, where the main contribution lies.

Pflueger, Tena Cucala, and Kostylev (2024), hereafter PTK, characterize two convergence regimes of recurrent GNNs (stabilization-based RecGNNs and size-dependent GSGNNs) as the bisimulation-invariant fragments of monadic monotone fixpoint logics, via van Benthem–Rosen style theorems, and establish the strict hierarchy fixed-depth $\subsetneq$ RecGNN $\subsetneq$ GSGNN. Their characterization is existential and their lim-inf acceptance is non-effective: no finite run certifies stabilization, membership of a given net cannot be decided, and no size bounds are provided. Our admissibility conditions are checkable from the weights (Theorems 17 and 17), and both compilers are constructive with explicit size bounds against the quotient table.

Uniform expressivity and other aggregations. Rosenbluth and Grohe (2026) characterize the computational power of recurrent sum-GNNs with finite-precision parameters and a completion-bit output: given the graph size as input, they compute every computable vertex function invariant under color refinement. This is a computational-completeness question under counting; ours is an effective logical characterization under convergence, without counting or size information. Schönherr and Lutz (2026) give logical characterizations of depth-bounded GNNs with mean aggregation, further evidence that the aggregator determines the target logic: counting logics for sum, their logics for mean, and, in the recurrent setting, $\mathbf{B}\Sigma_1^\diamond$ for set-based aggregation.

Halting and converging recurrent GNNs. Bollen et al. (2025), hereafter BOL, equip recurrent GNNs with an explicit halting classifier and prove (their Theorem 5.1) that the resulting model expresses every node classifier definable in the graded μ -calculus (μ GML), with termination checkable in finite time; the construction requires a dedicated halting output driven by a multi-stage counting algorithm. They leave open two questions: the converse, whether every halting recurrent GNN classifier falls within μ GML, and whether μ GML survives fully convergent termination, where the entire feature vector stabilizes. Bollen and Vansummeren (2026), hereafter BV, answer the second question affirmatively over *undirected graphs*: every μ GML classifier is expressible by a converging sum-aggregation net. Their “traffic-light” protocol lets a converging run synthesize internally the stabilization certificate that BOL’s halting classifier supplies externally. For the converse, both works observe that a characterization relative to MSO would follow from a graded extension of finitary Janin–Walukiewicz (Colcombet, Doumane, and Kuperberg 2025), which remains open.

Our results interlock as follows. Theorem 17 is the counting-free counterpart of BOL’s Theorem 5.1, obtained without halting classifier or counting apparatus; Theorem 17 answers the converse for $\mathbf{B}\Sigma_1^\diamond$ unconditionally and constructively: our compiled formulas are guarded and jointly positive by construction and set-based fixed points are bisimulation-invariant, so no Janin–Walukiewicz-style theorem, finitary or graded, is needed. Proposition 17 explains the division of labor. BV’s certificate synthesis rests on counting: the counters of BOL’s algorithm grow with the graph, so the resulting converging nets have infinite vocabulary in our sense and are not regular. The certificate that an inner fixed point of opposite polarity has stabilized can thus be supplied externally by a halting signal (BOL), manufactured internally by unbounded counting (BV), or is provably unavailable: over a finite vocabulary, no regular admissible net obtains one (Proposition 17), and $\mathbf{B}\Sigma_1^\diamond$ is exactly what remains. Three contrasts delimit the comparison. BV’s equivalence holds over undirected graphs, and their simulation breaks on directed graphs. Their convergence demands exact stabilization in finitely many steps, while our class also admits asymptotic convergence. And their μ GML upper bound is relative to MSO and conditional, whereas our correspondence is absolute for the class, effective with size bounds, and checkable from the weights.

Ahvonon et al. (2024) characterize recurrent GNNs under a third acceptance condition, a node accepts if it ever reaches an accepting feature vector, which likewise carries no effective termination guarantee: with reals, the model matches ω GML, an infinitary extension of graded modal logic; with floats, the rule-based logic GMSC. Their acceptance semantics expresses classifiers outside μ GML while precluding nested fixpoints, so its power is incomparable with the graded μ -calculus. Like BOL, this line rests on the counting power of multiset aggregation; our set-based restriction yields finitary $\mathbf{B}\Sigma_1^\diamond$ formulas with size bounds stated against the table.

Max-aggregation GNNs and Datalog. Tena Cucala and Cuenca Grau (2024) connect max-aggregation GNNs to Datalog with negation-as-failure, entirely in the depth-bounded

setting. The translation is based on a finiteness argument which is intrinsic to the max aggregation. Our translation is based on the finiteness of the types, which is more robust and works for any aggregation and combination function. Unlike us (or PTK, BOL, Ahvonon et al.), they also train and evaluate GNNs on knowledge-graph benchmarks, and report exactly the blow-up we discuss after Theorem 17: the full equivalent program is typically too large to compute, and they extract small fact-specific explanations instead.

Conclusions

We introduced regularity, a semantic condition under which a converging recurrent GNN’s fixed-point embeddings factor through the fixed points of a vertex’s neighbors alone, and admissibility, the operational condition under which the convergent process can be traded for a dynamical system over the (finite) vocabulary. Contraction and monotonicity, checkable directly from the weights, are sufficient for both. For the resulting class of RATCHET nets we gave a compiler into inflationary fixed-point logic and, centrally, an effective two-directional correspondence with the alternation-free modal μ -calculus – linear in the quotient table (net-to-logic, at the level of systems) and in the source formula (logic-to-net), with the single caveat that flattening into one closed $L\mu$ term can blow up exponentially. Unlike prior characterizations built on multiset aggregation, the correspondence needs no external halting signal, no non-effective acceptance condition, and no appeal to Janin–Walukiewicz-style completeness. We answer the natural counting-free analogue of the converse question Bollen et al. (2025) leave open, not the question itself. The gap is not just counting, since genuine alternation is beyond stabilization with a finite vocabulary, and Bollen and Vansummeren (2026) have shown that, over undirected graphs, the halting apparatus can be internalized into a converging run at the price of counters that grow with the graph; Proposition 17 shows this price cannot be avoided over a finite vocabulary, so closing the gap in the counting-free setting requires leaving the finite-vocabulary regime or a genuinely nested generalization of our convergence notion.

Two limitations should be stated plainly. The compiler applies to nets satisfying the RATCHET conditions; convergent trained networks that are not regular, monotone, or ordered fall outside its scope, and characterizing exactly which weight configurations qualify is open. Second, all results concern finite graphs, and our examples are illustrative rather than empirical: applying the compiler to trained recurrent GNNs, and reporting the size and readability of the extracted formulas, is the natural next test, as is working out the graded alternation-free extension sketched above.

Proposition 17 shows the correspondence is tight: the queries $\nu Y.\diamond Y$, $\mu X.\Box X$, and the alternation-free EF EG p are computed by no regular admissible net, hence (by Theorem 17) not expressible in $\mathbf{B}\Sigma_1^\diamond$. Lifting the correspondence to the first level of the alternation hierarchy, or to the alternation-free fragment, therefore requires enriching the convergence notion with stabilization certificates, the role played, in the graded setting, by the halting classifier of Bollen et al. (2025), or by the unbounded counters that internalize it (Bollen and Vansummeren 2026).

References

- Ahvenon, V.; Heiman, D.; Kuusisto, A.; and Lutz, C. 2024. Logical Characterizations of Recurrent Graph Neural Networks with Reals and Floats. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 37, 104205–104249.
- Andersen, H. R. 1994. Model checking and Boolean graphs. *Theoretical Comp. Sci.*, 126(1): 3–30.
- Arnold, A.; and Niwiński, D. 2001. *Rudiments of μ -Calculus*, volume 146 of *Studies in Logic and the Foundations of Mathematics*. Amsterdam: North-Holland. ISBN 978-0-444-50620-7.
- Barceló, P.; Kostylev, E. V.; Monet, M.; Pérez, J.; Reutter, J.; and Silva, J. P. 2020. The logical expressiveness of graph neural networks. In *ICLR*.
- Bollen, J.; Van den Bussche, J.; Vansummen, S.; and Virtema, J. 2025. Halting Recurrent GNNs and the Graded μ -Calculus. In *Proceedings of the 22nd International Conference on Principles of Knowledge Representation and Reasoning (KR 2025)*, 175–184.
- Bollen, J.; and Vansummen, S. 2026. On Halting vs Converging in Recurrent Graph Neural Networks. arXiv:2604.25551.
- Cai, J.-Y.; Fürer, M.; and Immerman, N. 1992. An optimal lower bound on the number of variables for graph identification. *Combinatorica*, 12(4): 389–410.
- Cleaveland, R.; and Steffen, B. 1991. A linear-time model-checking algorithm for the alternation-free modal μ -calculus. In *Computer Aided Verification*, volume 531 of *Lecture Notes in Computer Science*, 318–327. Springer.
- Colcombet, T.; Doumane, A.; and Kuperberg, D. 2025. Tree Algebras and Bisimulation-Invariant MSO on Finite Graphs. In *Proc. ICALP*, volume 334, 152:1–152:16.
- Dudzik, A. J.; and Veličković, P. 2022. Graph Neural Networks are Dynamic Programmers. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 35, 20635–20647.
- Grattarola, D.; Livi, L.; and Alippi, C. 2021. Learning Graph Cellular Automata. In *Advances in Neural Information Processing Systems*, volume 34.
- Grohe, M. 2017. *Descriptive Complexity, Canonisation, and Definable Graph Structure Theory*, volume 47. Cambridge University Press.
- Grohe, M. 2024. The Descriptive Complexity of Graph Neural Networks. *TheoretCS*, 3(25): 1–93.
- Gu, F.; Chang, H.; Zhu, W.; Sojoudi, S.; and El Ghaoui, L. 2020. Implicit Graph Neural Networks. In *Advances in Neural Information Processing Systems*, volume 33, 11984–11995.
- Gurevich, Y.; and Shelah, S. 1986. Fixed-point Extensions of First-Order Logic. *Annals of Pure and Applied Logic*, 32: 265–280.
- Ibarz, B.; Kurin, V.; Papamakarios, G.; Nikiforou, K.; Ben-nani, M.; Csordás, R.; Dudzik, A. J.; Bošnjak, M.; Vitvit-skyi, A.; Rubanova, Y.; Deac, A.; Bevilacqua, B.; Ganin, Y.; Blundell, C.; and Veličković, P. 2022. A Generalist Neural Algorithmic Learner. In *Proceedings of the First Learning on Graphs Conference (LoG)*, volume 198 of *PMLR*.
- Manna, Z.; and Pnueli, A. 1990. A hierarchy of temporal properties. In *Proc. PODC*, 377–408.
- Morris, C.; Ritzert, M.; Fey, M.; Hamilton, W. L.; Lenssen, J. E.; Rattan, G.; and Grohe, M. 2019. Weisfeiler and Leman go neural: Higher-order graph neural networks. In *AAAI*, 4602–4609.
- Pflueger, M.; Tena Cucala, D.; and Kostylev, E. V. 2024. Recurrent Graph Neural Networks and Their Connections to Bisimulation and Logic. In *Proc. AAAI*, 14608–14616.
- Rosenbluth, E.; and Grohe, M. 2026. Repetition Makes Perfect: Recurrent Graph Neural Networks Match Message Passing Limit. In *Proc. AAAI*, 25168–25175.
- Scarselli, F.; Gori, M.; Tsoi, A. C.; Hagenbuchner, M.; and Monfardini, G. 2008. The graph neural network model. *IEEE transactions on neural networks*, 20(1): 61–80.
- Schönherr, M.; and Lutz, C. 2026. Logical Characterizations of GNNs with Mean Aggregation. In *Proceedings of the 40th AAAI Conference on Artificial Intelligence (AAAI)*. AAAI Press.
- Tena Cucala, D. J.; and Cuenca Grau, B. 2024. Bridging Max Graph Neural Networks and Datalog with Negation. In *Proc. KR*.
- Tena Cucala, D. J.; Cuenca Grau, B.; Kostylev, E. V.; and Motik, B. 2022. Explainable GNN-Based Models over Knowledge Graphs. In *Proc. ICLR*.
- Veličković, P.; Ying, R.; Padovano, M.; Hadsell, R.; and Blundell, C. 2020. Neural Execution of Graph Algorithms. In *International Conference on Learning Representations (ICLR)*.
- Vergauwen, B.; and Lewi, J. 1994. Efficient local correctness checking for single and alternating Boolean equation systems. In *International Colloquium on Automata, Languages, and Programming*, volume 820 of *Lecture Notes in Computer Science*, 564–575. Springer.
- Weisfeiler, B. Y.; and Leman, A. A. 1968. Reduction of a graph to a canonical form and an algebra which appears in the process. *Nauchno-Tekhnicheskaya Informatsiya*, 2(9): 12–16.
- Wittig, S.; Vasileiou, A.; Nerem, R. R.; Stoll, T.; Geerts, F.; Wang, Y.; and Morris, C. 2026. Which Algorithms Can Graph Neural Networks Learn? arXiv:2602.13106.
- Wolfram, S. 2002. *A New Kind of Science*. Wolfram Media. ISBN 978-1-57955-008-0.
- Xu, K.; Hu, W.; Leskovec, J.; and Jegelka, S. 2018. How Powerful are Graph Neural Networks? In *ICLR*.
- Xu, K.; Li, J.; Zhang, M.; Du, S. S.; Kawarabayashi, K.-i.; and Jegelka, S. 2020. What Can Neural Networks Reason About? In *International Conference on Learning Representations (ICLR)*.
- Xu, K.; Zhang, M.; Li, J.; Du, S. S.; Kawarabayashi, K.-i.; and Jegelka, S. 2021. How Neural Networks Extrapolate: From Feedforward to Graph Neural Networks. In *International Conference on Learning Representations (ICLR)*.

Suppl. Material for Paper #9709: Recurrent Graph Neural Networks with Set-Based Aggregation

Appendix for section: Finite Types and Their Embeddings

Theorem 17. Let θ be a parameter, let (x, u) be a pointed graph, and let $\ell \geq 0$ be a layer index within the architecture. Then, $u_{x,\theta}^{(\ell)} = \mathbb{E}_t(\theta)$ for $t = \tau^{(\ell)}(x, u)$.

Proof. By direct induction on the layer index $\ell \geq 0$. □

Theorem 17 (Compiler). Let θ be a parameter of the architecture (W, L, ATP) . Then, $[u_{x,\theta}^{(\ell)}]_i > 0$ iff $x \models \psi_i^{(\ell)}(u)$.

Proof. By direct induction on the layer index $\ell \geq 0$. □

Appendix for section: Recurrent Nets

Lemma 17 (Bisimulation invariance). Let (x, u) and (x', u') be two pointed (finite) graphs. Then, (x, u) and (x', u') are bisimilar, written as $(x, u) \sim (x', u')$, iff $\tau(x, u) = \tau(x', u')$. Hence, if $(x, u) \sim (x', u')$, then $\Phi(\tau(x, u)) = \Phi(\tau(x', u'))$.

Proof. A bisimulation between x and x' is a relation $Z \subseteq V(x) \times V(x')$ such that for every $(u, u') \in Z$:

- (atoms) $\text{atp}(u) = \text{atp}(u')$;
- (forth) for every v with $E(x, u, v)$ there is v' with $E(x', u', v')$ and $(v, v') \in Z$; and
- (back) symmetrically.

The pointed structures (x, u) and (x', u') are bisimilar, $(x, u) \sim (x', u')$, iff there is a bisimulation $Z \subseteq V(x) \times V(x')$ such that $(u, u') \in Z$. We use the fact that types refine: $\tau^{(\ell+1)}(x, u)$ determines $\tau^{(\ell)}(x, u)$, as the latter is the first component of the former. Hence agreement of types at level ℓ implies agreement at of types at every level below ℓ .

($\Rightarrow$). Let Z be a bisimulation. We show by induction on ℓ that $\tau^{(\ell)}(x, u) = \tau^{(\ell)}(x', u')$ for every $(u, u') \in Z$. The base case $\ell = 0$ is direct by the atom condition: $\tau^{(0)}(x, u) = \text{atp}(u) = \text{atp}(u') = \tau^{(0)}(x', u')$. For the inductive step, write $\tau^{(\ell+1)}(x, u) = (\tau^{(\ell)}(x, u), S)$ and $\tau^{(\ell+1)}(x', u') = (\tau^{(\ell)}(x', u'), S')$. The first components agree by inductive hypothesis. For every v with $E(x, u, v)$, the forth condition yields v' with $E(x', u', v')$ and $(v, v') \in Z$, so $\tau^{(\ell)}(x, v) = \tau^{(\ell)}(x', v')$ by the inductive hypothesis; hence $S \subseteq S'$. The back condition gives $S' \subseteq S$. Thus $\tau^{(\ell+1)}(x, u) = \tau^{(\ell+1)}(x', u')$. Therefore, if $(u, u') \in Z$, then $\tau(x, u) = \tau(x', u')$.

($\Leftarrow$). Define $Z = \{(u, u') \in V(x) \times V(x') \mid \tau(x, u) = \tau(x', u')\}$. We verify Z is a bisimulation. Let $(u, u') \in Z$; i.e., $\tau(x, u) = \tau(x', u')$. The (atoms) condition holds since $\text{atp}(u) = \tau^{(0)}(x, u) = \tau^{(0)}(x', u') = \text{atp}(u')$. For (forth), let v such that $E(x, u, v)$. For each $\ell \geq 0$, equality $\tau^{(\ell+1)}(x, u) = \tau^{(\ell+1)}(x', u')$ gives equality of the neighbor-type sets at level ℓ , so there is a neighbor v'_ℓ of u' with $\tau^{(\ell)}(x', v'_\ell) = \tau^{(\ell)}(x, v)$. Since v' has *finitely many neighbors*, some fixed neighbor v' occurs as v'_ℓ for infinitely many ℓ . By refinement, $\tau^{(\ell)}(x', v') = \tau^{(\ell)}(x, v)$ then holds for every $\ell \geq 0$; i.e., $\tau(x', v') = \tau(x, v)$ and thus $(v, v') \in Z$. The (back) condition is symmetric.

Finally, Φ is by definition a function of the infinite type, $\Phi(\tau(x, u)) = \lim_{\ell \rightarrow \infty} \mathbb{E}_{\tau^{(\ell)}(x, u)}$. Thus, bisimilar (finite) pointed graphs, having equal infinite types, receive equal limit embeddings. □

Theorem 17. Let $\text{Net}(\cdot, \cdot, \cdot)$ be a regular net for the atomic types in ATP, and let (x, u) and (x', u') be pointed graphs of the same atomic type $\alpha \in \text{ATP}$. If $\{\Phi(\tau(x, v)) \mid E(x, u, v)\} = \{\Phi(\tau(x', v')) \mid E(x', u', v')\}$, then $\Phi(\tau(x, u)) = \Phi(\tau(x', u'))$.

Proof. Direct by definition of regular nets. □

Theorem 17 (Contractive nets). Let $\text{Net}(\cdot, \cdot, \cdot)$ be a recurrent net over the atomic types in ATP, and let $\|\cdot\|$ be a norm in $\mathbb{R}^W$. Then:

1. If the net is contractive for $\|\cdot\|$ and the aggregator is 1-Lipschitz for $\|\cdot\|$, the net is converging.
2. If the net is converging and **contractive in z** for $\|\cdot\|$, the net is regular and the vocabulary is well defined.
3. If the net is contractive and the aggregator is 1-Lipschitz (both) for $\|\cdot\|$, the net is regular, the vocabulary is well defined, and the game is admissible.

Proof. **Claim 1.** Fix a graph x with n vertices, consider tensors $z \in \mathbb{R}^{nW}$ that assign embeddings z_u to vertices u in the graph, and define the mapping $\Gamma : \mathbb{R}^{nW} \rightarrow \mathbb{R}^{nW}$ as $\Gamma(z)_u = \text{Net}(\text{atp}(u), z, \{z_v \mid E(x, u, v)\})$. Lift the norm to such tensors as $\|z\| = \max_{u \in V(x)} \|z_u\|$.

We show that Γ is a contraction for $\|\cdot\|$. Let z and z' be two tensors, and let $S_u = \{z_v \mid v \in N(u)\}$ and $S'_u = \{z'_v \mid v \in N(u)\}$ for vertex u where $N(u) = \{v \mid E(x, u, v)\}$ is u 's neighborhood. Then,

$$\begin{aligned} \|\Gamma(z) - \Gamma(z')\| &= \max_{u \in V(x)} \|\Gamma(z)_u - \Gamma(z')_u\| \\ &= \max_{u \in V(x)} \|\text{Net}(\text{atp}(u), z_u, S_u) - \text{Net}(\text{atp}(u), z'_u, S'_u)\| \\ &\leq \lambda \max_{u \in V(x)} \max(\|z_u - z'_u\|, \|\oplus S_u - \oplus S'_u\|) \\ &\leq \lambda \max_{u \in V(x)} \max(\|z - z'\|, \max_{v \in N(u)} \|z_v - z'_v\|) \\ &\leq \lambda \max_{u \in V(x)} \max(\|z - z'\|, \|z - z'\|) \\ &\leq \lambda \|z - z'\| \end{aligned}$$

where the first inequality is by the contraction of the net, and the second since $\oplus$ is 1-Lipschitz. By Banach's fixed-point theorem, there is a **unique fixed-point** z^* satisfying $\Gamma(z^*) = z^*$, and the sequence $z_{\ell+1} = \Gamma(z_\ell)$ converges to z^* from any starting point z_0 . Notice that we apply Banach's fixed-point theorem to fixed graph x , yet the contraction factor λ is the same for every graph.

Claim 2. We show two things: the net is regular and the vocabulary is well defined. Fix a pointed graph (x, u) of atomic type α , and let Φ_u denote $\Phi(\tau(x, u))$.

The net is regular. We need to show $\lim_{\ell \rightarrow \infty} z_\ell = \Phi_u$ where $z_0 = e_\alpha$ and $z_{\ell+1} = \text{Net}(\alpha, z_\ell, S)$ with $S = \{\Phi_v \mid E(x, u, v)\}$:

$$\|\Phi_u - z_{\ell+1}\| = \|\text{Net}(\alpha, \Phi_u, S) - \text{Net}(\alpha, z_\ell, S)\| \leq \lambda \|\Phi_u - z_\ell\| \leq \dots \leq \lambda^{\ell+1} \|\Phi_u - e_\alpha\|$$

which goes to 0 as $\ell \rightarrow \infty$. Therefore, the limit exists and it is equal to Φ_u .

The vocabulary is well defined. It is sufficient to show that $F_\alpha(S)$ exists for every finite subset S of embeddings. We show that the sequence $z_0 = e_\alpha$ and $z_{\ell+1} = \text{Net}(\alpha, z_\ell, S)$ is Cauchy. This is direct since $z \mapsto \text{Net}(\alpha, z, S)$ is a contraction.

Claim 3. By Claim 1 the net is converging. Contractivity implies Contractivity in z (take $S = S'$), so by Claim 2 the net is regular and the vocabulary $\mathcal{V}$ is well defined. Hence, $\mathcal{T}$ and the game are defined. It remains to show admissibility; i.e., $E_u^k \rightarrow \Phi_u$ as $k \rightarrow \infty$ for every pointed graph (x, u) .

Fix graph x and let $\delta_k = \max_{u \in V(x)} \|E_u^k - \Phi_u\|$, which is finite since x is a finite graph. Let α be the atomic type of u , let $N = N(u)$ be u 's neighborhood, and set $S^k = \{E_v^k \mid v \in N\}$ and $S^* = \{\Phi_v \mid v \in N\}$. By regularity, $\Phi_u = F_\alpha(S^*)$, and by the definition of the game $E_u^{k+1} = \mathcal{T}(\alpha, S^k) = F_\alpha(S^k)$.

If $N = \emptyset$ then $S^k = S^* = \emptyset$, so $E_u^{k+1} = F_\alpha(\emptyset) = \Phi_u$ and $\|E_u^{k+1} - \Phi_u\| = 0 \leq \lambda \delta_k$. Otherwise, since $F_\alpha(S)$ is the unique fixed point of $z \mapsto \text{Net}(\alpha, z, S)$ for every finite S :

$$\|F_\alpha(S^k) - F_\alpha(S^*)\| = \|\text{Net}(\alpha, F_\alpha(S^k), S^k) - \text{Net}(\alpha, F_\alpha(S^*), S^*)\| \leq \lambda \max(\|F_\alpha(S^k) - F_\alpha(S^*)\|, \|\oplus S^k - \oplus S^*\|).$$

If the maximum is attained by the first argument, $\|F_\alpha(S^k) - F_\alpha(S^*)\| \leq \lambda \|F_\alpha(S^k) - F_\alpha(S^*)\|$ with $\lambda < 1$, forcing $\|E_u^{k+1} - F_\alpha(S^*)\| = 0 \leq \lambda \delta_k$. If it is attained by the second argument, 1-Lipschitz gives

$$\|E_u^{k+1} - \Phi_u\| \leq \lambda \|\oplus S^k - \oplus S^*\| \leq \lambda \max_{v \in N} \|E_v^k - \Phi_v\| \leq \lambda \delta_k.$$

In every case $\|E_u^{k+1} - \Phi_u\| \leq \lambda \delta_k$, so $\delta_{k+1} \leq \lambda \delta_k$ and therefore $\delta_k \leq \lambda^k \delta_0$ with $\delta_0 = \max_{v \in V(x)} \|F_{\text{atp}(v)}(\emptyset) - \Phi_v\|$. Since $\lambda < 1$, $\delta_k \rightarrow 0$ as $k \rightarrow \infty$. That is, $E_u^k \rightarrow \Phi_u$ for every vertex u , and the game is admissible. Moreover, since λ does not depend on x , the convergence is uniform over all graphs. $\square$

Theorem A1 (Sufficient Conditions for Contractive nets). *Let $\text{Net}(\cdot, \cdot, \cdot)$ be a recurrent net for the atomic types in ATP.*

1. *If the aggregator $\oplus$ is the point-wise maximum, the aggregator is 1-Lipschitz for $\|\cdot\|_\infty$.*
2. *Let ρ be a 1-Lipschitz for $\|\cdot\|_\infty$ activation function (e.g., tanh, sigmoid, ReLU or any clipping $x \mapsto \min(b, \max(a, x))$), and consider the maximum absolute row sum norm $\|\cdot\|_{\text{mars}}$ over matrices. If $\|A_\alpha\|_{\text{mars}} < 1$, the net is a contraction in z for $\|\cdot\|_\infty$. If $\|A_\alpha\|_{\text{mars}} + \|B_\alpha\|_{\text{mars}} < 1$, the net is a contraction for $\|\cdot\|_\infty$.*

Proof. **Claim1.** Let (x, u) be a pointed graph, let N be a subset with n vertices, and let S and S' be two sets of embeddings indexed by the vertices in N : the embeddings in S (resp. S') are denoted by e_v (resp. e'_v) for $v \in N$. We need to show that the max aggregator is 1-Lipschitz for $\|\cdot\|_\infty$.

For register i , assume without loss of generality $(\oplus S)_i \geq (\oplus S')_i$:

$$|\max_{v \in N} e_{v,i} - \max_{v \in N} e'_{v,i}| = \max_{v \in N} e_{v,i} - \max_{v \in N} e'_{v,i} \leq e_{v^*,i} - e'_{v^*,i} \leq \max_{v \in N} |e_{v,i} - e'_{v,i}|$$

where $v^* \in N$ is the index such that $e_{v^*,i} = \max_v e_{v,i}$. Hence,

$$\|\oplus S - \oplus S'\|_\infty = \max_i |\max_{v \in N} e_{v,i} - \max_{v \in N} e'_{v,i}| \leq \max_i \max_{v \in N} |e_{v,i} - e'_{v,i}| = \max_{v \in N} \|e_v - e'_v\|_\infty.$$

Claim 2. Let α be an atomic type, let z and z' be two embeddings, and let S and S' be two vertex-indexed finite sets of embeddings. Then, for $\lambda = \|\mathbf{A}_\alpha\|_{mars} + \|\mathbf{B}_\alpha\|_{mars}$:

$$\begin{aligned} \|\text{Net}(\alpha, z, S) - \text{Net}(\alpha, z', S')\|_\infty &= \|\rho(\mathbf{A}_\alpha z + \mathbf{B}_\alpha(\oplus S) + \mathbf{C}_\alpha) - \rho(\mathbf{A}_\alpha z' + \mathbf{B}_\alpha(\oplus S') + \mathbf{C}_\alpha)\|_\infty \\ &\leq \|(\mathbf{A}_\alpha z + \mathbf{B}_\alpha(\oplus S) + \mathbf{C}_\alpha) - (\mathbf{A}_\alpha z' + \mathbf{B}_\alpha(\oplus S') + \mathbf{C}_\alpha)\|_\infty \\ &= \|\mathbf{A}_\alpha(z - z') + \mathbf{B}_\alpha(\oplus S - \oplus S')\|_\infty \\ &\leq \|\mathbf{A}_\alpha(z - z')\|_\infty + \|\mathbf{B}_\alpha(\oplus S - \oplus S')\|_\infty \\ &\leq \|\mathbf{A}_\alpha\|_{mars} \|z - z'\|_\infty + \|\mathbf{B}_\alpha\|_{mars} \|\oplus S - \oplus S'\|_\infty \\ &\leq \lambda \max(\|z - z'\|_\infty, \|\oplus S - \oplus S'\|_\infty) \end{aligned}$$

where the first inequality is from 1-Lipschitz of activation, the second by triangle inequality, the third by properties of the mars norm (it is the induced operator norm for $\|\cdot\|_\infty$), and the last by the definition of λ . If $S = S'$, the term $\|\oplus S - \oplus S'\|_\infty = 0$. Hence, if $\|\mathbf{A}_\alpha\|_{mars} < 1$, the net is a contraction for z for $\|\cdot\|_\infty$, and the net is a (full) contraction for $\|\cdot\|_\infty$ if $\lambda < 1$. $\square$

Theorem 17 (Monotone nets). *Let $\text{Net}(\cdot, \cdot, \cdot)$ be a converging net over the atomic types in ATP. Assume the initial embeddings are non-negative pre-fixed points of the isolated-vertex update: $0 \leq e_\alpha \leq \text{Net}(\alpha, e_\alpha, \emptyset)$ for $\alpha \in \text{ATP}$. Then:*

1. *If the net is monotone, the vocabulary is well defined.*
2. *If the net and the aggregator are both monotone, the net is regular, and the game is admissible and ordered.*

Proof. Throughout $\leq$ denotes the component-wise partial order on $\mathbb{R}^W$. Aggregator monotonicity is used in the indexed form: if $S = \{e_v \mid v \in N\}$ and $S' = \{e'_v \mid v \in N\}$ with $e_v \leq e'_v$ for every $v \in N$, then $\oplus S \leq \oplus S'$. We also use $\oplus \emptyset = 0 \leq \oplus S$ for finite sets S of non-negative embeddings.

Claim 1 (vocabulary). We show by induction that for every α and finite set S of non-negative embeddings, the canonical sequence $z_0 = e_\alpha$ and $z_{\ell+1} = \text{Net}(\alpha, z_\ell, S)$ is $\leq$ -non-decreasing, its limit $F_\alpha(S)$ exists, and $F_\alpha(S)$ is the least fixed point of $z \mapsto \text{Net}(\alpha, z, S)$ above e_α . Hence, the vocabulary is well defined and consists of non-negative embeddings.

First, we show by induction on ℓ : $z_\ell \leq z_{\ell+1}$. The base case is

$$z_0 = e_\alpha \leq \text{Net}(\alpha, e_\alpha, \emptyset) \leq \text{Net}(\alpha, e_\alpha, S) = z_1$$

since e_α is pre-fixed point of $z \mapsto \text{Net}(\alpha, z, \emptyset)$, and $\oplus \emptyset = 0 \leq \oplus S$. The inductive step:

$$z_\ell = \text{Net}(\alpha, z_{\ell-1}, S) \leq \text{Net}(\alpha, z_\ell, S) = z_{\ell+1}$$

where the inequality follows by the inductive hypothesis $z_{\ell-1} \leq z_\ell$. Therefore, the limit $F_\alpha(S) = \lim_{\ell \rightarrow \infty} z_\ell$ exists. Indeed, $F_\alpha(S)$ is the **least fixed-point** of $z \mapsto \text{Net}(\alpha, z, S)$ that is above e_α . (Notice the third argument for the net is “frozen” at S requiring no monotonicity of the aggregator).

$\mathcal{V}_0$ is the set of initial embeddings which are all non-negative. Thus, $\mathcal{V}_1$ is well-defined and consists of non-negative embeddings as well. Inductively, the vocabulary $\mathcal{V}$ which is the closure of $\bigcup_{k \geq 0} \mathcal{V}_k$ is well defined, and consists of non-negative embeddings.

Lemma A (Monotonicity of the table). *For every $\alpha \in \text{ATP}$ and finite sets S, S' of non-negative embeddings. If $\oplus S \leq \oplus S'$, then $F_\alpha(S) \leq F_\alpha(S')$.*

Proof of Lemma: Let $\langle z_\ell \rangle_\ell$ and $\langle z'_\ell \rangle_\ell$ be the canonical sequences for (α, S) and (α, S') , respectively. First, we show by induction on ℓ : $z_\ell \leq z'_\ell$ for every $\ell \geq 0$. The base case is the equality $z_0 = z'_0 = e_\alpha$. By inductive hypothesis $z_\ell \leq z'_\ell$. Therefore, $z_{\ell+1} = \text{Net}(\alpha, z_\ell, S) \leq \text{Net}(\alpha, z'_\ell, S') = z'_{\ell+1}$ by the monotonicity of the net since $\oplus S \leq \oplus S'$. Second, pass to the limit to get $F_\alpha(S) \leq F_\alpha(S')$. In particular, $e_\alpha \leq F_\alpha(\emptyset) \leq F_\alpha(S)$ for every such S . $\blacksquare$

Claim 2 (regularity, admissibility, order). Fix a graph x , let $u \in V(x)$ be a vertex of atomic type $\alpha = \text{atp}(u)$, and write

- $z_{u,\ell}$ for the net’s synchronous run: $z_{u,0} = e_\alpha$, and $z_{u,\ell+1} = \text{Net}(\alpha, z_{u,\ell}, \{z_{v,\ell} \mid E(x, u, v)\})$,
- $\Phi_u = \lim_{\ell \rightarrow \infty} z_{u,\ell}$ for its limit,
- $S_u^* = \{\Phi_v \mid E(x, u, v)\}$ for the final embeddings of u ’s neighbors, and
- $\mathbf{E}_u^k$ for the game’s run: $\mathbf{E}_u^0 = F_\alpha(\emptyset)$, and $\mathbf{E}_u^{k+1} = \mathcal{T}(\alpha, S_u^k) = F_\alpha(S_u^k)$ with $S_u^k = \{\mathbf{E}_v^k \mid E(x, u, v)\}$.

Step 2a (regularity). By definition, the net is regular iff $\Phi_u = F_\alpha(S_u^*)$. We show $z_{u,\ell} \leq F_\alpha(S_u^*)$ for every vertex u and layer ℓ . Indeed, suppose that this is not true, and let $\ell \geq 0$ be a **minimum** layer index and u a vertex such that $z_{u,\ell} \not\leq F_\alpha(S_u^*)$. Clearly, $\ell > 0$ since $z_{u,0} = e_\alpha \leq F_\alpha(S_u^*)$ by Lemma A. Since $\ell > 0$ is minimum, $z_{u,\ell-1} \leq F_\alpha(S_u^*)$ and $z_{v,\ell-1} \leq F_{\text{atp}(v)}(S_v^*)$ for neighbor v of u . The monotonicity of the aggregator and inductive hypothesis gives $\oplus S_u^{\ell-1} \leq \oplus S_u^*$. Apply the monotonicity of the net to get

$$z_{u,\ell} = \text{Net}(\alpha, z_{u,\ell-1}, S_u^{\ell-1}) \leq \text{Net}(\alpha, F_\alpha(S_u^*), S_u^*) = F_\alpha(S_u^*),$$

where the last equality is because $F_\alpha(S_u^*)$ is a fixed point of $z \mapsto \text{Net}(\alpha, z, S_u^*)$. This contradicts the supposition. Hence, $z_{u,\ell} \leq F_\alpha(S_u^*)$ for every vertex u and layer ℓ . Passing to the limit (as the net is a continuous function) yields $\Phi_u \leq F_\alpha(S_u^*)$.

Since $0 \leq e_\alpha$ for $\alpha \in \text{ATP}$, $0 \leq \oplus S_u^0$ for each vertex u . The pre-fixed point hypothesis and monotonicity of the net give $z_{u,0} = e_\alpha \leq \text{Net}(\alpha, e_\alpha, \emptyset) \leq \text{Net}(\alpha, e_\alpha, S_u^0) = z_{u,1}$, and inductively $z_{u,\ell} \leq z_{u,\ell+1}$. Hence $e_\alpha = z_{u,0} \leq z_{u,1} \leq \dots \leq \Phi_u \leq F_\alpha(S_u^*)$. Since Φ_u is also a fixed point of $z \mapsto \text{Net}(\alpha, z, S_u^*)$ above e_α , and $F_\alpha(S_u^*)$ is the least fixed point above e_α , then $\Phi_u = F_\alpha(S_u^*)$. Hence, *the net is regular*.

Step 2b: the game's run is $\leq$ -non-decreasing. We show by induction on k , $E_u^k \leq E_u^{k+1}$ for every vertex u . Base case: $E_u^0 = F_\alpha(\emptyset) \leq F_\alpha(S_u^0) = E_u^1$ by Lemma A, since $\oplus \emptyset = 0 \leq \oplus S_u^0$. Inductive step: if $E_v^{k-1} \leq E_v^k$ for every vertex v , then $\oplus S_u^{k-1} \leq \oplus S_u^k$ by the monotonicity of the aggregator (both sets indexed by $N(u)$). Hence, $E_u^k = F_\alpha(S_u^{k-1}) \leq F_\alpha(S_u^k) = E_u^{k+1}$ by Lemma A.

Step 2c: admissibility. Two bounds sandwich the run of the game.

- (i) $E_u^k \leq \Phi_u$ for every k , by induction on k . The base is $E_u^0 = F_\alpha(\emptyset) \leq F_\alpha(S_u^*) = \Phi_u$ directly by Lemma A and regularity, since $\oplus \emptyset = 0 \leq \oplus S_u^*$. If $E_v^k \leq \Phi_v$ for every v , then $\oplus S_u^k \leq \oplus S_u^*$, so $E_u^{k+1} = F_\alpha(S_u^k) \leq F_\alpha(S_u^*) = \Phi_u$ by Lemma A and regularity.
- (ii) $z_{u,\ell} \leq E_u^k$ for every ℓ , by induction on k . The base is $z_{u,0} = e_\alpha \leq F_\alpha(\emptyset) = E_u^0$ since the canonical sequence for $(\alpha, \emptyset)$ is non-decreasing from e_α . For the inductive step, note that $E_u^\ell \leq F_\alpha(S_u^\ell)$ for every ℓ (for $\ell = 0$ by Lemma A's final remark; for $\ell \geq 1$ because $E_u^\ell = F_\alpha(S_u^{\ell-1}) \leq F_\alpha(S_u^\ell)$, as in Step 2b). Then, $z_{u,\ell+1} = \text{Net}(\alpha, z_{u,\ell}, \{z_{v,\ell} \mid E(u, v)\}) \leq \text{Net}(\alpha, F_\alpha(S_u^\ell), S_u^\ell) = F_\alpha(S_u^\ell) = E_u^{\ell+1}$, using, in order: the inductive hypothesis with net and aggregator monotonicity; $E_u^\ell \leq F_\alpha(S_u^\ell)$ with net monotonicity; and the fixed-point property of $F_\alpha(S_u^\ell)$.

By Steps 2b and (i), $\langle E_u^k \rangle_k$ is component-wise non-decreasing and bounded above by Φ_u , hence converges to some $E_u^* \leq \Phi_u$. By (ii), passing to the limit, $\Phi_u \leq E_u^*$. Hence $\lim_{k \rightarrow \infty} E_u^k = \Phi_u$ for every vertex of every graph; that is, the game is admissible.

Step 2d: order. By Step 2b, the restriction of the component-wise order $\leq$ to $\mathcal{V}$ witnesses Definition 10's condition: take $\leq$ equal to the restriction of $\leq$ to $\mathcal{V}$. Definition 10 requires an order, not a total one, so no extension is needed. $\square$

Corollary 17. *Under the hypotheses of Theorem 17 with $\oplus = \max$, the game is monotone. Hence $\mathcal{T}(\alpha, S) = F_\alpha(S) \leq F_\alpha(S') = \mathcal{T}(\alpha, S')$ whenever $S \sqsubseteq S'$.*

Proof. By Theorem 17, the vocabulary $\mathcal{V}$ consists of non-negative embeddings and the game order $\leq$ is the restriction of the component-wise order $\leq$ to $\mathcal{V}$ (Step 2d in proof of the theorem). Let $S \sqsubseteq S'$; i.e., every $e \in S$ is $\leq$ -dominated by some $e' \in S'$. If $S = \emptyset$ then $\oplus S = 0 \leq \oplus S'$, since all embeddings in $\mathcal{V}$ are non-negative. Otherwise, fix a register i . For every $e \in S$ there is $e' \in S'$ with $e \leq e'$, hence $e_i \leq e'_i \leq \max\{e'_i \mid e' \in S'\} = (\oplus S')_i$. Taking the maximum over $e \in S$ gives $(\oplus S)_i \leq (\oplus S')_i$, and since i is arbitrary, $\oplus S \leq \oplus S'$. By Lemma A, $\mathcal{T}(\alpha, S) = F_\alpha(S) \leq F_\alpha(S') = \mathcal{T}(\alpha, S')$. $\square$

Theorem A2 (Sufficient conditions for monotone nets). *Let $\text{Net}(\cdot, \cdot, \cdot)$ be a recurrent architecture over the atomic types in ATP with an aggregator that is 1-Lipschitz.*

1. If $A_\alpha, B_\alpha \geq 0$ (i.e., non-negative weights), the net is monotone for $\|\cdot\|_\infty$.
2. If A_α, B_α have non-negative integer weights, the net has clipped activation, and the initial embeddings are integer valued, the vocabulary is finite.

Proof. **Claim 1.** Let z and z' be embeddings, and S and S' be finite sets of embeddings. If $z \leq z'$ and $\oplus S \leq \oplus S'$, for every α :

$$\begin{aligned} A_\alpha z + B_\alpha(\oplus S) + C_\alpha &\leq A_\alpha z' + B_\alpha(\oplus S') + C_\alpha \\ \rho(A_\alpha z + B_\alpha(\oplus S) + C_\alpha) &\leq \rho(A_\alpha z' + B_\alpha(\oplus S') + C_\alpha) \\ \text{Net}(\alpha, z, S) &\leq \text{Net}(\alpha, z', S'). \end{aligned}$$

Claim 2. Under the assumptions, the embeddings in the vocabulary are integer valued and bounded. Therefore, there is a finite number of them. $\square$

Appendix for section: Translating Recurrent Nets into IFP

Let us be more precise about the syntax and semantics of IFP. For formula $\psi(R; \bar{z})$ in $\text{FO}[\sigma \cup \{R\}]$, where $k = |\bar{z}|$ and R is a new relation of arity k , the IFP *constructor* is

$$[\text{ifp}_{R, \bar{x}} \psi(R, \bar{x})](\bar{t})$$

where $\bar{t}$ is a tuple of terms of size k . The semantics is in terms of the *inflationary fixed-point* $R^* = R^0 \cup R^1 \cup \dots$ where $R^0 \doteq \emptyset$ and $R^{i+1} \doteq R^i \cup \{\bar{z} \in U^k \mid \mathfrak{A} \models \psi(R_i; \bar{z})\}$, for a σ -structure $\mathfrak{A}$ with universe U . That is, at stage i , when constructing the set R^{i+1} , the relation R inside ψ is interpreted as R^i . Since $R^0 \subseteq R^1 \subseteq \dots$, the sequence $\langle R^i \rangle_i$ converges in at most U^k steps for any finite structure $\mathfrak{A}$. Then $\mathfrak{A} \models [\text{ifp}_{R, \bar{x}} \psi(R, \bar{x})](\bar{t})$ iff $\bar{t} \in R^*$. The syntax for IFP is simpler than the syntax for LFP as no requirements on the “one-step” formula ψ are imposed.

IFP is extended to fixed-points of multiple relations, simultaneously, by considering vectors $\mathbf{R} = \langle R_1, R_2, \dots, R_m \rangle$ of relations instead of the single relation R . The denotation of each relation is initially empty, and they are extended (in parallel) with formulas $\psi_j(\mathbf{R}, \bar{z})$ that may use the relations $R_1, R_2, \dots, R_m$. The syntax for the inflationary fixed-point is $[\text{ifp}_{\mathbf{R}, \bar{x}} \psi(\mathbf{R}, \bar{x})]_j(\bar{t})$ and such a formula holds when the term $\bar{t}$ belongs to R_j^* .

We construct an IFP formula to capture the convergence $\mathbf{E}^\ell \rightarrow \mathbf{E}^*$ of an admissible and ordered game over a finite vocabulary $\mathcal{V}$. The idea is to construct unary relations for each index $i = 1, 2, \dots, m$, where $m = |\mathcal{V}|$, to capture $\mathbf{E}_u^\ell = e_i$. We use the order $\preceq$ on $\mathcal{V}$ obeyed by the game.

Let $\mathcal{T} : \text{ATP} \times \wp(\mathcal{V}) \rightarrow \mathcal{V}$ be the finite quotient table that describes the net, and consider the vector $\mathbf{R} = \langle R_i \rangle_{i=1,2,\dots,m}$ of unary relations. The one-step formula $\psi(\mathbf{R}; u) = (\psi_1, \dots, \psi_m)$ consists of m formulas $\psi_i^{\text{start}} \vee \psi_i^{\text{next}}$ that define the initial embeddings and their evolution according to $\mathcal{T}$:

$$\begin{aligned} \psi_i^{\text{start}}(u) &\equiv \bigvee_{\alpha \in \text{ATP}, \mathcal{T}(\alpha, \emptyset) = e_i} \alpha(u), \\ \psi_i^{\text{next}}(\mathbf{R}; u) &\equiv \bigvee_{\alpha \in \text{ATP}, \emptyset \subsetneq S \subseteq \mathcal{V}, \mathcal{T}(\alpha, S) = e_i} \text{row}_{\alpha, S}(\mathbf{R}; u), \end{aligned}$$

where the auxiliary formulas are:

$$\begin{aligned} \text{row}_{\alpha, S}(\mathbf{R}; u) &\equiv \alpha(u) \wedge \forall v \left[E(u, v) \Rightarrow \bigvee_{e_i \in S} \text{curr}_i(\mathbf{R}; v) \right] \wedge \bigwedge_{e_i \in S} \exists v [E(u, v) \wedge \text{curr}_i(\mathbf{R}; v)], \\ \text{curr}_i(\mathbf{R}; v) &\equiv R_i(v) \wedge \bigwedge_{e_i \prec e_j} \neg R_j(v). \end{aligned}$$

Theorem 14 in main text becomes the following Definition A3 and Theorem A4:

Definition A3 (IFP Compiler). *Let $\text{Net}(\cdot, \cdot, \cdot)$ be a regular architecture for the atomic types in ATP that have finite vocabulary $\mathcal{V}$, and admissible and ordered games. The **characterization** of the recurrent net is the vector $\langle \Psi_1, \Psi_2, \dots, \Psi_m \rangle$ such that*

$$\langle \Psi_1, \Psi_2, \dots, \Psi_m \rangle(u) \equiv [\text{ifp}_{\mathbf{R}; z} \psi(\mathbf{R}; z)](u).$$

Theorem A4. *Let $\text{Net}(\cdot, \cdot, \cdot)$ be a regular net for the atomic types in ATP that has finite vocabulary $\mathcal{V}$ and whose game is admissible and ordered, and let $\langle \Psi_1, \dots, \Psi_m \rangle$ be its characterization. For every pointed graph (x, u) and $i = 1, \dots, m$, $\Phi(\tau(x, u)) = e_i$ iff $x \models \Psi_i(u) \wedge \bigwedge_{e_i \prec e_j} \neg \Psi_j(u)$.*

Proof. Let x be a graph, let $\langle \mathbf{E}^k \rangle_{k \geq 0}$ be the game run for graph x , and let $\langle (R_1^k, R_2^k, \dots, R_m^k) \rangle_{k \geq 0}$ be the sequence of interpretations computed by the IFP semantics of $[\text{ifp}_{\mathbf{R}; z} \psi(\mathbf{R}; z)]$.

Lemma B. *For $k \geq 0$, $u \in R_i^{k+1}$ iff $\mathbf{E}_u^l = e_i$ for some $l \leq k$. (The shift on the index k is due to the fact that $R_i^0 = \emptyset$ whereas $\mathbf{E}_u^0$ is already an embedding.)*

Proof of Lemma: By induction of $k \geq 0$:

– **Base case** $k = 0$.

($\Rightarrow$). Assume $u \in R_i^1$. Hence, since R_i^0 is empty, $x \models \psi_i^{\text{start}}(u)$. Then, there is α such that $\text{atp}(u) = \alpha$ and $\mathcal{T}(\alpha, \emptyset) = e_i$ implying $\mathbf{E}_u^0 = \mathcal{T}(\text{atp}(u), \emptyset) = e_i$.

($\Leftarrow$). Assume $\mathbf{E}_u^0 = \mathcal{T}(\text{atp}(u), \emptyset) = e_i$. Then, $x \models \psi_i^{\text{start}}(u) \implies u \in R_i^1$.

– **Inductive step** $k > 0$.

($\Rightarrow$). Assume $u \in R_i^{k+1}$. Two cases: $u \in R_i^k$ or $x \models \psi_i^{\text{next}}(\mathbf{R}^k; u)$. In the first case, by inductive hypothesis, $\mathbf{E}_u^l = e_i$ for some $l < k$. In the second case, by definition, there is (α, S) such that $\mathcal{T}(\alpha, S) = e_i$ and $x \models \text{row}_{\alpha, S}(\mathbf{R}^k; u)$. That is,

$$x \models \alpha(u) \wedge \forall v \left[E(u, v) \implies \bigvee_{e_j \in S} \text{curr}_j(\mathbf{R}^k; v) \right] \wedge \bigwedge_{e_j \in S} \exists v [E(u, v) \wedge \text{curr}_j(\mathbf{R}^k; v)]$$

By definition, $\text{curr}_j(\mathbf{R}^k; v)$ holds iff $v \in R_j^k$ and $v \notin R_{j'}^k$ for $e_j \prec e_{j'}$. Therefore, by inductive hypothesis, $\text{curr}_j(\mathbf{R}^k; v)$ holds iff $\mathbf{E}_v^l = e_j$ for some $l < k$, and $\mathbf{E}_v^l \neq e_{j'}$ for all $l < k$ and $e_j \prec e_{j'}$. Since the game is ordered, $\text{curr}_j(\mathbf{R}^k; v)$ holds iff $\mathbf{E}_v^{k-1} = e_j$. Hence, the vertex u satisfies $\text{atp}(u) = \alpha$, and $S = \{\mathbf{E}_v^{k-1} \mid E(x, u, v)\}$ implying $\mathbf{E}_u^k = \mathcal{T}(\alpha, S) = e_i$.

($\Leftarrow$). Assume $\mathbf{E}_u^l = e_i$ for some $l \leq k$. We need to show $u \in R_i^{k+1}$. Two cases: $l < k$ or $l = k$. In the first case $l < k$, by inductive hypothesis, $u \in R_i^k$ which implies $u \in R_i^{k+1}$ since $R_i^{k+1} \supseteq R_i^k$.

Second case $l = k$. Since the game is ordered, $\mathbf{E}_u^{k-1} \prec e_i$. Therefore, there is (α, S) such that $\text{atp}(u) = \alpha$, $\mathcal{T}(\alpha, S) = e_i$, and $S = \{\mathbf{E}_v^{k-1} \mid E(x, u, v)\}$.

Let v be a vertex such that $E(x, u, v)$. By inductive hypothesis, $v \in R_j^k$ where $\mathbf{E}_v^{k-1} = e_j$. On the other hand, since the game is ordered, $\mathbf{E}_v^l \neq e_{j'}$ for $l < k-1$ and $e_j \prec e_{j'}$. Hence, $\text{curr}_j(\mathbf{R}^k; v)$ holds. Likewise, if $e_j \in S$, there is vertex v such that $E(x, u, v)$ and $\text{curr}_j(\mathbf{R}^k; v)$. Therefore, $x \models \psi_i^{\text{next}}(\mathbf{R}^k; u)$ which implies $u \in R_i^{k+1}$. ■

Lemma C. For $k \geq 0$, $\mathbf{E}_u^k = e_i \iff x \models \text{curr}_i(\mathbf{R}^{k+1}; u)$.

Proof of Lemma: If $\mathbf{E}_u^k = e_i$, then $u \in R_i^{k+1}$ and $u \notin R_j^{k+1}$ for $e_i \prec e_j$ since the game is ordered. Hence, $x \models \text{curr}_i(\mathbf{R}^{k+1}; u)$. Conversely, assume $x \models \text{curr}_i(\mathbf{R}^{k+1}; u)$. By definition, $u \in R_i^{k+1}$ and $u \notin R_j^{k+1}$ for $e_i \prec e_j$. By Lemma B and ordered game, $\mathbf{E}_u^k = e_i$. ■

At the fixed point, $x \models \Psi_i(u)$ iff $u \in R_i^*$. Hence, $x \models \Psi_i(u) \wedge \bigwedge_{e_i \prec e_j} \neg \Psi_j(u)$ iff $\mathbf{E}_u^k$ has converged to e_i iff $\Phi(\tau(x, u)) = e_i$ (since the game is admissible). □

Definition A3 and Theorem A4 require no monotonicity: the one-step formulas contain negation of the quantified predicates. This is the precise sense in which the IFP compiler is more general than the $L\mu$ compiler below that require the game to be monotone, but output $L\mu$ formulas. In exchange, the size of the IFP formula is linear in $|\mathcal{T}|$.

The next proposition shows that the contractive net of the second example satisfies the conditions for applying the compiler. Namely, it is a converging regular net with finite vocabulary and whose game is admissible, ordered and monotone.

Proposition A5 (Second example). *The net of the second example is converging and regular; its vocabulary is $\mathcal{V} = \{e_1 = \frac{1}{3}, e_2 = \frac{2}{3}, e_3 = \frac{7}{9}, e_4 = 1\}$ with the table of the main text; and its game is admissible, ordered by $\leq$, and monotone.*

Proof. Write $m_\ell(u) = \max\{z_{v,\ell} \mid E(x, u, v)\}$ (with value 0 for vertices without successors) so that $z_{u,\ell+1} = \text{clip}_{[0,1]}(-z_{u,\ell}/2 + 2m_\ell(u) + \mathbf{C}_{\text{atp}(u)})$.

Drift Lemma. If $z_{\ell+1} = \text{clip}_{[0,1]}(-z_\ell/2 + c_\ell)$ with $c_\ell \rightarrow c^*$, then $z_\ell \rightarrow z^*$, the unique fixed point of $z \mapsto \text{clip}_{[0,1]}(-z/2 + c^*)$: since $\text{clip}_{[0,1]}$ is 1-Lipschitz, $|z_{\ell+1} - z^*| \leq \frac{1}{2}|z_\ell - z^*| + |c_\ell - c^*| \rightarrow 0$.

Convergence and limits. After one step every vertex satisfies $z \geq \frac{1}{2}$: for black, $z_1 = \text{clip}_{[0,1]}(-0/2 + 2m_0 + 1/2) = \text{clip}_{[0,1]}(2m_0 + 1/2) \geq 1/2$, and for red, $z_1 = \text{clip}_{[0,1]}(-1/2 + 2m_0 + 1) = \text{clip}_{[0,1]}(2m_0 + 1/2) \geq 1/2$. Consequently, at step 2 every vertex with at least one successor has $z_2 = \text{clip}_{[0,1]}(-z_1/2 + 2m_1 + \mathbf{C}) \geq \text{clip}_{[0,1]}(-1/2 + 1 + 1/2) = 1$, i.e., exactly 1. Now classify vertices by $h(u) = \text{length of the longest path from } u$:

- (a) $h(u) = 0$ (no successors): $z_{\ell+1} = \text{clip}_{[0,1]}(-z_\ell/2 + \mathbf{C}_\alpha)$, a contraction with fixed point $1/3$ (black) or $2/3$ (red); the run converges there, oscillating.
- (b) $h(u) = \infty$ (u reaches a cycle): every cycle vertex has a successor, so it equals 1 at step 2, and its aggregate from step 2 on includes its cycle successor, keeping it at 1 thereafter; by induction on the distance to the cycle, every vertex reaching a cycle is 1 from some step on, so $\Phi_u = 1$.
- (c) $0 < h(u) < \infty$: by induction on $h(u)$, each successor's run converges, so $m_\ell(u) \rightarrow m^* = \max$ of the successors' limits, and the drift lemma gives Φ_u equals the unique fixed point of $z \mapsto \text{clip}_{[0,1]}(-z/2 + 2m^* + \mathbf{C}_\alpha)$. Evaluating the fixed points: $m^* = 0$ gives $1/3$ (black) and $2/3$ (red); $m^* = 1/3$ gives $7/9$ (black: $-z/2 + 7/6$ has fixed point $7/9$) and 1 (red: $\text{clip}_{[0,1]}(-1/2 + 5/3) = 1$); and $m^* \geq 2/3$ gives 1 for both types.

This reproduces the table row by row, shows every reachable limit lies in $\{1/3, 2/3, 7/9, 1\}$, and closing $\mathcal{V}_0 = \{1/3, 2/3\}$ under the rows yields exactly $\mathcal{V}$.

Regularity. By (a)–(c), Φ_u equals the fixed point of $z \mapsto \text{clip}_{[0,1]}(-z/2 + 2m^* + \mathbf{C}_\alpha)$ with m^* equal to the max of the successors' limits; since the map is a contraction in z , the frozen run from e_α converges to that same fixed point, i.e., $\Phi_u = F_\alpha(S_u^*)$.

Game. $\mathbf{E}_u^0 = \mathcal{T}(\alpha, \emptyset) \in \{e_1, e_2\}$. Vertices without successors stay constant. A vertex whose successors all lack successors reaches its final row value at $k = 1$ and stays (its successors are constant): runs $e_1 \leq e_2 \leq e_3 \cdots$ or jumps to e_4 . Any other vertex has a successor whose value is $\geq e_3$ from $k = 1$ on, hence equals $\mathcal{T}(\alpha, \max \geq 7/9) = e_4$ from $k = 2$ on. All runs are

$\preceq$ -chains (the table rows are non-decreasing in $\max S$), the limits coincide with Φ case by case, and monotonicity holds since $S \sqsubseteq S'$ implies $\max S \leq \max S'$ and the rows are non-decreasing in $\max S$ (this last because if every $e \in S$ is dominated by some $e' \in S'$, then $\max S \leq \max S'$ since the vocabulary is non-negative and totally ordered, and the rows are non-decreasing in $\max S$ by inspection of the table; cf. Corollary 17). $\square$

Appendix for section: Equivalence with $\mathbf{B}\Sigma_1^\diamond$

Theorem 17 (Net-to-logic). *Let $\text{Net}(\cdot, \cdot, \cdot)$ be a RATCHET net with vocabulary $\mathcal{V} = \{e_1, \dots, e_m\}$ of size m . There are $\mathbf{B}\Sigma_1^\diamond$ formulas $\gamma_1, \dots, \gamma_m$ such that for any pointed graph (x, u) and $i \in \{1, \dots, m\}$: $\Phi(\tau(x, u)) = e_i$ iff $(x, u) \models \gamma_i$.*

Proof. Let x be a finite graph. Define the subsets $T_i = \{u \in V(x) \mid \Phi(\tau(x, u)) \succeq e_i\}$ for $i = 1, \dots, m$. For subsets $X_1, \dots, X_m \subseteq V(x)$, define $\Theta_i(v; X_1, \dots, X_m)$ as

$$\bigvee_{(\alpha, S): \mathcal{T}(\alpha, S) \succeq e_i} \left(\alpha(v) \wedge \bigwedge_{j \in S} \exists w (E(v, w) \wedge X_j(w)) \right).$$

These are guarded formulas jointly positive in X_i by construction (no negation appears). Note also that Θ_i contains no universal quantification over neighbors, unlike Definition 4, only the witnessing half of the neighborhood description is asserted. This is sound because T_i is an up-set and the game is monotone (additional neighbor values can only move $\mathcal{T}(\alpha, \cdot)$ up the order; this is the content of the $(\Leftarrow)$ direction of Lemma 17), and it is what makes the compiled system $\diamond$ -only.

The formula Θ_i defines a vertex subset $F_i(X_1, \dots, X_m) = \{v \in V(x) \mid x \models \Theta_i(v; X_1, \dots, X_m)\}$. Putting all of them together, we get the operator $\bar{F} : \wp(V(x))^m \rightarrow \wp(V(x))^m$ that maps $(X_1, \dots, X_m) \mapsto \bar{F}(X_1, \dots, X_m) = (F_i(X_1, \dots, X_m))_i$. This operator is monotone and it has a least fixed point ($\subseteq$ -component wise) given by $(T_1, \dots, T_m)$. Indeed,

Lemma 17 (Soundness). *For every $i = 1, \dots, m$ and vertex v : $v \in T_i \iff x \models \Theta_i(v; T_1, \dots, T_m)$.*

Proof of Lemma: Let $S^*(v) = \{e_w \mid E(v, w)\}$ where e_w denotes $\Phi(\tau(x, w))$. By regularity and admissibility, $\Phi(\tau(x, v)) = \mathcal{T}(\alpha, S^*(v))$ where $\alpha = \text{atp}(v)$.

- $(\Rightarrow)$ If $\Phi(\tau(x, v)) \succeq e_i$, the row (α, S) for $S = S^*(v)$ satisfies $\mathcal{T}(\alpha, S) \succeq e_i$, and every $e_j \in S$ is witnessed by an actual neighbor w (i.e., $w \in T_j$). So, $x \models \Theta_i(v; T_1, \dots, T_m)$.
- $(\Leftarrow)$ Suppose (α, S) is a row such that $\mathcal{T}(\alpha, S) \succeq e_i$ and for each $e_j \in S$, there is a neighbor w such that $e_w \succeq e_j$. Then, $S \sqsubseteq S^*(v)$. By monotonicity of the game, $\mathcal{T}(\alpha, S) \preceq \mathcal{T}(\alpha, S^*(v))$. That is, $e_i \preceq \mathcal{T}(\alpha, S) \preceq \mathcal{T}(\alpha, S^*(v)) = \Phi(\tau(x, v))$ which implies $v \in T_i$. This is the only place in the proof where monotonicity of the game is needed. $\blacksquare$

Lemma 17 (Minimality). *If $\bar{T}' = (T'_1, \dots, T'_m)$ is any tuple of vertex subsets such that $x \models \Theta_i(v; \bar{T}') \implies v \in T'_i$ for every i , then $T_i \subseteq T'_i$ for every i .*

Proof of Lemma: We show by induction on k the claim: $E_u^k \succeq e_i \implies u \in T'_i$ for every k, i and u .

- *Base case.* $E_u^0 = \mathcal{T}(\alpha, \emptyset)$. If $\mathcal{T}(\alpha, \emptyset) \succeq e_i$, the row $(\alpha, \emptyset)$ satisfies $\mathcal{T}(\alpha, \emptyset) \succeq e_i$ giving $x \models \Theta_i(u; \bar{T}')$. Hence, by assumption, $u \in T'_i$.
- *Inductive step.* Suppose the claim holds at k , and let $E_u^{k+1} = \mathcal{T}(\alpha, S_u^k)$ where $S_u^k = \{E_v^k \mid E(u, v)\}$. If $E_u^{k+1} \succeq e_i$, the row (α, S_u^k) satisfies $\mathcal{T}(\alpha, S_u^k) \succeq e_i$. For each $e_j \in S_u^k$, the witnessing neighbor v has $E_v^k = e_j \succeq e_j$. By the inductive hypothesis, $v \in T'_j$. Then, $x \models \Theta_i(u; \bar{T}')$ via this row, hence $u \in T'_i$.

Since $\mathcal{V}$ is finite and $E_u^k \in \mathcal{V}$ for all k , $E_u^k \rightarrow \Phi(\tau(x, u))$ forces eventual equality: there is K such that $E_u^k = \Phi(\tau(x, u))$ for $k \geq K$ (a convergent sequence in $\mathbb{R}^W$ taking values in a finite set is eventually constant). Let u be a vertex in T_i (i.e., $\Phi(\tau(x, u)) \succeq e_i$). Therefore $E_u^K \succeq e_i$, and by the claim $u \in T'_i$. Hence, $T_i \subseteq T'_i$. $\blacksquare$

Construction of the formulas γ_i

First, translate the first-order formulas Θ_i into $\text{L}\mu$ formulas ζ_i , syntactically, using

$$\alpha(v) \mapsto \alpha; \quad \exists w (E(v, w) \wedge X_j(w)) \mapsto \diamond X_j$$

while preserving conjunctions and disjunctions.

Lemma 17. *For every subsets $A_1, \dots, A_m \subseteq V(x)$ and $i = 1, \dots, m$: $x \models \Theta_i(v; A_1, \dots, A_m) \iff (x, v) \models \zeta_i[X_1, \dots, X_m := A_1, \dots, A_m]$.*

Proof of Lemma: Direct. ■

Apply now variable elimination (or *Bekič's principle*) (Arnold and Niwiński 2001) to get formulas γ_i that characterize the least fixed-point $(T_1, \dots, T_m)$ of $\bar{F}$. That is, define $\eta_1(X_2, \dots, X_m) = \mu X_1. \zeta_1(X_1, \dots, X_m)$ and define for $j = 2, \dots, m$, $\zeta_j^{(1)} = \zeta_j[X_1 := \eta_1(X_2, \dots, X_m)]$. Next, define $\eta_2(X_3, \dots, X_m) = \mu X_2. \zeta_2^{(1)}(X_2, \dots, X_m)$ and $\zeta_j^{(2)} = \zeta_j^{(1)}[X_2 := \eta_2(X_3, \dots, X_m)]$ for $j = 3, \dots, m$. Continue until $\eta_m = \mu X_m. \zeta_m^{(m-1)}(X_m)$ has no variables.

Construct $\theta_m = \eta_m$, and for $j = m-1, \dots, 1$:

$$\theta_j = \eta_j[X_m, \dots, X_{j+1} := \theta_m, \dots, \theta_{j+1}].$$

These are $L\mu$ formulas whose only operator is μ . Finally, set $\theta_{m+1} = \perp$ and $\gamma_i = \theta_i \wedge \bigwedge_{e_j \text{ covers } e_i} \neg \theta_j$ where the cover of e_i is the set of minimal embeddings that are strictly above e_i , and $\neg \theta_j$ is obtained syntactically by pushing the negation down to propositions, resulting in a formula with only ν operators. $\gamma_i \in \mathbf{B}\Sigma_1^\diamond$: each θ_i is a closed $\Sigma_1^\diamond$ formula, and each $\neg \theta_i$, obtained by dualization, is a closed $\Pi_1^\square$ formula.

Correctness

We need to show $\Phi(\tau(x, u)) = e_i \iff (x, u) \models \gamma_i$. Let $\bar{T} = (T_1, \dots, T_m)$. By Lemma 17, $\bar{T}$ is a fixed point of operator $\bar{F}$, and Lemma 17 shows $\bar{T}$ is the least fixed point.

By Lemma 17, the operator induced by $\zeta_1, \dots, \zeta_m$ under ordinary modal semantics is the same operator $\bar{F}$. Thus, the least-fixed point of the ζ -system is also $\bar{T}$. By Bekič elimination, the constructed $\theta_1, \dots, \theta_m$ satisfy $x \models \theta_i(u)$ iff $u \in (\text{lfp}(\bar{F}))_i = T_i$, for every i .

Finally, $\Phi(\tau(x, u)) = e_i$ iff $u \in T_i$ and $u \notin T_j$ for $e_j \succ e_i$ iff $(x, u) \models \theta_i$ and $(x, u) \not\models \theta_j$ iff $(x, u) \models \gamma_i$. □

Theorem 17 (Logic-to-net). *For every $\mathbf{B}\Sigma_1^\diamond$ formula γ , there is a RATCHET architecture $\text{Net}(\cdot, \cdot, \cdot)$ and register index m such that for any pointed graph (x, u) : $(x, u) \models \gamma$ iff $[\Phi(\tau(x, u))]_m = 1$.*

Proof. By definition, we assume γ is equivalent to $\mathbf{B}(\beta_1, \dots, \beta_q, \neg \beta_{q+1}, \dots, \neg \beta_r)$, where $\mathbf{B}$ is a Boolean combination ($\wedge, \vee$) and each β_j is a closed $\Sigma_1^\diamond$ formula. Further, we assume the bound variables are uniquely named.

Registers. Enumerate the subformulas of the blocks bottom-up as $\gamma_1, \dots, \gamma_m$ (repetitions preserved) and let b_i index the bodies such that $\gamma_m = \gamma$ and $\gamma_i = \mu X_i. \gamma_{b_i}$ when γ_i is a fixed-point formula. Since blocks are $\Sigma_1^\diamond$, every bound variable is a μ -variable. The width of the net is $W = m + M$, with one register r_i per subformula and one register v_i per bound variable. Registers are partitioned into **core** registers (those for subformulas γ_i lying inside a block and those for bound variables), and **derived** registers (the rest). Registers v_i are also called “latch registers”, and the others “memoryless”.

Clusters. For each block β , consider the directed graph over the bound variables in β , with edges $X \rightarrow Y$ if Y appears within the scope of X , and edges $Y \rightarrow X$ if X appears as a free variable in the body for Y . A cluster C is a strongly connected component in this graph, and the variable X is the head of C iff every other variable Y in C is within the scope of X .

Atomic types. As discussed above, we take the propositions in γ to be the atomic types of the graphs; $\alpha \models p$ abbreviates that type α makes p true. When the propositions are not disjoint or exhaustive, we shall consider their jointly Boolean valuations as the set of atomic types.

Initial embeddings and rules. The initial embedding e_α assigns $\llbracket \alpha \models p \rrbracket$ to registers of literal subformulas p and $\neg p$ (their value under α), and 0 to every other register. The update rules implemented by the parameters, ordered by register type, are:

Form of γ_k	Posted rule for register r_k
p	$r_k := \llbracket \text{atp}(u) \models p \rrbracket$
$\neg p$	$r_k := 1 - \llbracket \text{atp}(u) \models p \rrbracket$
$\gamma_i \wedge \gamma_j$	$r_k := \text{clip}_{[0,1]}(r_i + r_j - 1) = \min(r_i, r_j)$
$\gamma_i \vee \gamma_j$	$r_k := \text{clip}_{[0,1]}(r_i + r_j) = \max(r_i, r_j)$
$\diamond \gamma_i$	$r_k := \bigoplus_S^{\max} r_i[v] = \max(\{r_i[v] \mid v \in S\})$
$\neg \gamma_i$	$r_k := 1 - r_i$
X_i	$r_k := v_i$
$\gamma_k = \mu X_k. \gamma_{b_k}$ (X_k is head of cluster C)	$\begin{cases} r_j := v_j & (\text{for } X_j \in C) \\ v_j := \max(v_j, r_{b_j}) = \text{clip}_{[0,1]}(v_j + r_{b_j}) & (\text{for } X_j \in C) \end{cases}$
$\gamma_k = \mu X_k. \gamma_{b_k}$ (X_k isn't head)	(Nothing; handled when solving the cluster's head)

All rules fire synchronously, reading the previous step. The only aggregation is max; under the global convention $\oplus \emptyset = 0$ this evaluates $\diamond$ correctly at vertices without successors ($\diamond \varphi$ is false there). All rules are compositions of clip with affine maps of the current embedding and the aggregate, so the construction is an instance of the architecture with $\oplus$ the pointwise maximum. All registers take values in $\{0, 1\}$ (each rule maps Booleans to Booleans), so the reachable embeddings lie in $\{0, 1\}^W$.

Semantic states. Fix a graph x and let ρ_x be the environment assigning to each bound variable X_i of γ its denotation $((X_i))_x \subseteq V(x)$ in the simultaneous least solution of its block's equation system (equivalently, by Bekič's principle, the nested least-fixed-point semantics). The *semantic state* $z_u^{\text{sem}} \in \{0, 1\}^W$ at vertex u is:

- $z_u^{\text{sem}}[r_i] = \llbracket (x, u, \rho_x) \models \gamma_i \rrbracket$ for every subformula register, and
- $z_u^{\text{sem}}[v_i] = \llbracket u \in ((X_i))_x \rrbracket$ for every variable register.

By definition, $(x, u, \rho_x) \models \gamma_i$ iff $z_u^{\text{sem}}[r_i] = 1$. In particular, if $\gamma_i = \beta$ is a closed block, $(x, u) \models \beta$ iff $z_u^{\text{sem}}[r_i] = 1$.

Lemma G (Iteration). *Let g be a monotone self-map of $\{0, 1\}^D$ for a finite set D , and let z_0 satisfy $z_0 \leq g(z_0)$ and $z_0 \leq z^*$ for every fixed point z^* of g . Then the iteration $z_{\ell+1} = g(z_\ell)$ is non-decreasing, stabilizes within $|D|$ steps, and its limit is the least fixed point of g .*

Proof sketch: By induction: $z_0 \leq z_1 \leq \dots \leq z^*$ for every fixed point z^* of g . Each coordinate is Boolean and flips at most once. Hence, the run converges within $|D|$ steps to the least fixed point of g . ■

Lemma H (Fixed points of the block map). *Fix a graph x and a block β with register set R_β , and let f be the synchronous one-step map of the net restricted to R_β , a self-map of $\{0, 1\}^{R_\beta \times V(x)}$. Then,*

- (a) f is monotone;
- (b) a state z is a fixed point of f iff every memoryless register satisfies its rule with equality and every latch satisfies $v_j \geq r_{b_j}$,
- (c) the variable part of every fixed point of f is a pre-fixed point of the body operator P , where $P(w)_{j,u}$ is the value of γ_{b_j} at u under variable assignment w , while z^{sem} is a fixed point of f whose variable part is $\text{lfp}(P)$.

Consequently, $\text{lfp}(f) = z^{\text{sem}}$ on R_β .

Proof:

- (a) literal registers are per-type constants; every other core rule is a composition of min, max, copies, and max-aggregates of neighbor registers, each monotone.
- (b) For memoryless rules, fixedness is the equality; for a latch, $v_j = \max(v_j, r_{b_j})$ iff $v_j \geq r_{b_j}$.
- (c) Forward: composing the exact memoryless equations of a fixed point z^* from each body down to variables and constants, the latch inequalities read $w \geq P(w)$ on the variable part. Backward: the rules mirror the semantic clauses (min/max implement $\wedge / \vee$; the max-aggregate implements $\diamond$, with $\max \emptyset = 0$ matching falsity at successor-less vertices; copies match by definition of ρ_x), and at each latch $z^{\text{sem}}[v_j]$ equals the body's value, so the inequality holds with equality; the variable part of z^{sem} is $\text{lfp}(P)$ by Bekič's principle.

For the consequence: $\text{lfp}(f) \leq z^{\text{sem}}$ since z^{sem} is a fixed point. Conversely any fixed point z^* has variable part $\geq \text{lfp}(P)$ by Knaster–Tarski via (c), and its memoryless registers, exact monotone functions of the variables and constants, dominate as well; hence $z^* \geq z^{\text{sem}}$. ■

Lemma H applies verbatim when the aggregates of some or all $\diamond$ -registers are frozen at constants from a finite set $S \subseteq \{0, 1\}^W$: freezing only changes the constants of the memoryless equations, not the shape of the system.

Lemma I (Blocks reach their semantics). *Let β be a block of γ with register set R_β , and fix a graph x with n vertices. Restricted to R_β , the synchronous run of the net is non-decreasing, stabilizes within $|R_\beta| \times n$, and its limit is the semantic state: $\lim_\ell z_{u,\ell}[r] = z_u^{\text{sem}}[r]$ for every register $r \in R_\beta$ and vertex u .*

Proof: The rules of R_β read only registers of R_β and per-type constants (β is closed and its machinery internal to the block), so the restricted run is the iteration of the monotone map f of Lemma H(a). The initial state satisfies the hypotheses of Lemma G: literal registers start at their rules' constant values, which every fixed point of f shares by Lemma H(b), and all other registers start at 0, so $z_0 \leq f(z_0)$ and $z_0 \leq z^*$ for every fixed point z^* . By Lemma G the run is non-decreasing and stabilizes within $|R_\beta| \times n$ steps at $\text{lfp}(f)$, which is z^{sem} by Lemma H. ■

Lemma J (Derived registers). *If the inputs of a derived register converge, the register converges to the corresponding connective of the limits, with delay one.*

Proof sketch: Each derived rule is a memoryless continuous function of its inputs; the embeddings always lie in $\{0, 1\}^W$. ■

Step 1: run of the net. Fix a graph x with n vertices. By Lemma I each block converges to its semantics. By Lemma J, $r_m \rightarrow \llbracket (x, u) \models \gamma \rrbracket$ at every vertex u . The net converges on every graph within $W \times n$ steps.

Step 2: vocabulary and regularity. For any finite $S \subseteq \{0, 1\}^W$, the frozen run $z_0 = e_\alpha, z_{\ell+1} = \text{Net}(\alpha, z_\ell, S)$ is the single-vertex instance of Step 1 with the aggregates held constant. By the remark after Lemma H, this frozen system is again the iteration of a monotone map from a qualifying start, so by Lemma I it converges; derived registers follow by Lemma J. Therefore $F_\alpha(S)$ is defined, the vocabulary $\mathcal{V}$ is well defined, and $\mathcal{V} \subseteq \{0, 1\}^W$ is finite.

By Lemma H applied to the frozen instance, $F_\alpha(S)$ is, on each block's core, the least solution of the memoryless equations with aggregates frozen at S , subject to the latch inequalities. For regularity, fix (x, u) with $\alpha = \text{atp}(u)$ and $S_u = \{\Phi_v \mid E(u, v)\}$; blocks are closed, hence independent, and derived registers are determined by the core, so it suffices to prove $\Phi_u = F_\alpha(S_u)$ on each block's core.

($\leq$) At the net's limit all of the block's equations hold at u with the neighbors at their limits, so Φ_u restricted to the core solves the frozen system with aggregates from S_u ; by leastness, $F_\alpha(S_u) \leq \Phi_u$.

($\geq$) Consider the global assignment that places $F_\alpha(S_u)$'s core values at u and Φ 's core values at every other vertex. At u all constraints hold by construction, since u 's aggregates under this assignment are exactly those frozen from S_u . At any other vertex w , u 's values enter only through max-aggregates and were only lowered, so by monotonicity of the rules w 's equalities relax to inequalities of the form $f(z) \leq z$. The assignment is therefore a global pre-fixed point of the block map f , hence dominates $\text{lfp}(f)$ by Knaster–Tarski, and $\text{lfp}(f) = \Phi$ on the block's core by Lemma I. Reading off vertex u gives $F_\alpha(S_u) \geq \Phi_u$. Hence $\Phi_u = F_\alpha(S_u)$: the net is regular.

Step 3: the game is ordered, monotone, and admissible. Define $\preceq$ on $\mathcal{V}$ by $e \preceq e'$ iff $\text{core}(e) \leq \text{core}(e')$ componentwise. This is a partial order on $\mathcal{V}$: every element of $\mathcal{V}$ is a frozen-run limit, at which the derived equations hold exactly and no derived rule aggregates neighbors, so derived values are functions of same-vertex core values, and agreement on the core implies equality. Write $\sqsubseteq$ for the definition in Definition 10.

Monotone. If $S \sqsubseteq S'$, then for every core register r the aggregate satisfies $\max_{e \in S} e[r] \leq \max_{e' \in S'} e'[r]$: each element of S is dominated by an element of S' , and extra elements can only increase a maximum. The least local solution is monotone in these frozen aggregates (standard monotonicity of least fixed points in parameters), so $\text{core}(\mathcal{T}(\alpha, S)) \leq \text{core}(\mathcal{T}(\alpha, S'))$, i.e., $\mathcal{T}(\alpha, S) \preceq \mathcal{T}(\alpha, S')$.

Ordered. $E_u^0 = \mathcal{T}(\alpha, \emptyset)$ and $\emptyset \sqsubseteq S$. Then, $E_u^0 \preceq E_u^1$. If $E_v^k \preceq E_v^{k+1}$ for all v then $S_u^k \sqsubseteq S_u^{k+1}$, and monotonicity gives $E_u^{k+1} \preceq E_u^{k+2}$. That is, every run is a $\preceq$ -chain.

Admissible. (i) $E_u^k \preceq \Phi_u$ by induction: the base is $\mathcal{T}(\alpha, \emptyset) \preceq \mathcal{T}(\alpha, S_u) = \Phi_u$ (monotonicity and regularity), and the inductive step is $E_u^{k+1} = \mathcal{T}(\alpha, S_u^k) \preceq \mathcal{T}(\alpha, S_u) = \Phi_u$. (ii) $z_{u,\ell} \preceq E_u^\ell$ by induction: the base is $\text{core}(e_\alpha) \preceq \text{core}(\mathcal{T}(\alpha, \emptyset))$ (aggregates from $\emptyset$ are the minimum, and the frozen run ascends from e_α). For the inductive step, $E_u^\ell \preceq F_\alpha(S_u^\ell)$ (for $\ell = 0$ by monotonicity from $\emptyset \sqsubseteq S^0$; for $\ell \geq 1$ since $E_u^\ell = F_\alpha(S_u^{\ell-1}) \preceq F_\alpha(S_u^\ell)$), and then $z_{u,\ell+1} = \text{Net}(\alpha, z_{u,\ell}, \{z_{v,\ell} \mid E(u, v)\}) \leq \text{Net}(\alpha, F_\alpha(S_u^\ell), S_u^\ell) = F_\alpha(S_u^\ell) = E_u^{\ell+1}$ on the core, using the inductive hypothesis, the monotonicity of the core rules, and the fixed-point property of $F_\alpha(S_u^\ell)$. By (i) the core of $(E_u^k)_k$ is non-decreasing and bounded by Φ_u , hence converges; by (ii) its limit dominates Φ_u ; so it equals Φ_u on the core, and the derived registers, determined by the core on $\mathcal{V}$, follow. The game is admissible.

The net is therefore a RATCHET net, and by Step 1, $[\Phi(\tau(x, u))]_m = \llbracket \gamma \rrbracket$. □

The construction in Theorem 17 cannot be pushed further. A $\square$ inside a μ -block (or, dually, a $\diamond$ inside a ν -block) would make the game's step-0 value $\mathcal{T}(\alpha, \emptyset)$ evaluate the modality vacuously – correctly for the isolated vertex, but as an over-approximation that neighboring vertices then bootstrap from – and Proposition 17 shows the resulting failure of admissibility is not an artifact of this construction: no admissible net computes $\mu X. \square X$ or $\nu Y. \diamond Y$. A fixed point over one of the opposite polarity fails one level higher for the same reason (EF EG p), which is where the halting machinery of Bollen et al. earns its keep.

Proposition 17 (Barrier). *Let $\text{Net}(\cdot, \cdot, \cdot)$ be a converging regular net with finite vocabulary whose game is admissible (ordering and monotonicity are not assumed). Then, Net does not compute the queries: $\nu Y. \diamond Y$, $\mu X. \square X$, $\text{EG } p = \nu Y. (p \wedge \diamond Y)$, and $\text{EF EG } p = \mu X. (\diamond X \vee \nu Y. (p \wedge \diamond Y))$.*

Proof. Formally, “Net computes q ” means there is a readout $h : \mathcal{V} \rightarrow \{0, 1\}$ with $h(\Phi(\tau(x, u))) = q(x, u)$ for every pointed graph; any thresholded register is such an h . Fix the atomic type α of interest (for the formulas $\mu X. \square X$ and $\nu Y. \diamond Y$ any α ; for the two p -formulas, an α with $\alpha \models p$) and define the sequence $t_0 = \mathcal{T}(\alpha, \emptyset)$ and $t_{k+1} = \mathcal{T}(\alpha, \{t_k\})$ in $\mathcal{V}$. Both families below use only vertices of type α .

First family: directed paths Let P_k have vertices $u_k \rightarrow u_{k-1} \rightarrow \dots \rightarrow u_0$, all of type α , where u_0 is a sink. We claim $E_{u_i}^j = t_{\min(i,j)}$ for all i, j by induction on j . The base case is $E_{u_i}^0 = \mathcal{T}(\alpha, \emptyset) = t_0 = t_{\min(i,0)}$. For the inductive step: if $i = 0$, then u_i is a sink, so $E_{u_0}^{j+1} = \mathcal{T}(\alpha, \emptyset) = t_0 = t_{\min(0,j+1)}$. If $i \geq 1$, then u_i 's only successor is u_{i-1} , so

$E_{u_i}^{j+1} = \mathcal{T}(\alpha, \{E_{u_{i-1}}^j\}) = \mathcal{T}(\alpha, \{t_{\min(i-1,j)}\}) = t_{\min(i-1,j)+1} = t_{\min(i,j)+1}$. Hence the game's run at u_k constant from step k on with value t_k , and admissibility gives $\Phi(\tau(P_k, u_k)) = t_k$, so $h(t_k) = q(P_k, u_k)$ for every $k \geq 0$.

Second family: self-loop. Let L be the single vertex w of type α with the edge (w, w) . Its game run is $E_w^0 = t_0$ and $E_w^{j+1} = \mathcal{T}(\alpha, \{E_w^j\})$, i.e. exactly $\langle t_j \rangle_{j \geq 0}$. Since $\mathcal{V}$ is finite and t_{j+1} is a function of t_j , the sequence is eventually periodic. Since the game is admissible it converges in $\mathbb{R}^W$. An eventually periodic convergent sequence over a finite set is eventually constant. So there is a K with $t_j = t_K$ for all $j \geq K$, and $\Phi(\tau(L, w)) = t_K$, so $h(t_K) = q(L, w)$.

Contradiction. Every path in P_K is finite, and w lies on an infinite path. Hence,

- For $\nu Y. \Diamond Y$, $\text{EG}p$, and $\text{EFEG}p$ (all of which assert the existence of an infinite path; in the last two cases, one path whose all vertices satisfy p : $q(P_k, u_K) = 0$ and $q(L, w) = 1$. Thus, $h(t_K) = 0$ and $h(t_K) = 1$).
- For $\mu X. \Box X$ (well-foundedness) the two values are exchanged: the finite path is well-founded, so $q(P_K, u_K) = 1$, while the self-loop is not, so $q(L, w) = 0$. Again $h(t_K) = 1$ and $h(t_K) = 0$.

In each case h is forced to take both values at the single vocabulary element t_K , contradiction. $\square$

Corollary 17. *Over finite pointed graphs, as classes of unary queries: (i) $\Sigma_1^\mu \cup \Pi_1^\mu \not\subseteq \mathbf{B}\Sigma_1^\diamond$, witnessed by $\mu X. \Box X \in \Sigma_1^\mu$ and $\nu Y. \Diamond Y \in \Pi_1^\mu$; and (ii) $\mathbf{B}\Sigma_1^\diamond$ is strictly contained in the alternation-free fragment, witnessed by $\text{EF EG } p$.*

Proof. For the first claim, the formulas $\nu Y. \Diamond Y$ and $\mu X. \Box X$ lie in $\Sigma_1^\mu \cup \Pi_1^\mu$, and neither is equivalent to any $\mathbf{B}\Sigma_1^\diamond$ formula, since by Theorem 17 every $\mathbf{B}\Sigma_1^\diamond$ formula is computed by a RATCHET net while Proposition 17 excludes both. For the second claim, $\text{EF EG } p$ is alternation-free and not computed by any RATCHET net (Proposition 17). $\square$

Examples

Formula $\gamma = \mu X. (r \vee \Diamond X) \wedge \neg \mu Y. (g \vee \Diamond Y)$.

γ is the classic example for reachability–safety Boolean combinations (reach the red avoid the green). The logic-to-net translator gives a net of width 2 (after collapsing redundant dimensions that track the two fixed point computations for reachability and safety). A further application of the net-to-logic recovers γ .

Logic-to-net (Theorem 17). The mechanical construction outputs thirteen registers; collapsing copy chains and folding literals into the initial embeddings yields an equivalent two-register network, implementing two Boolean propagators (s, t) (the first encodes “a red vertex has been reached”, the second “a green vertex has been reached”) for the two blocks $\beta_1 = \mu X. (r \vee \Diamond X)$ and $\beta_2 = \mu Y. (g \vee \Diamond Y)$. The initial embeddings are $e_r = 10$, $e_g = 01$, and $e_b = 00$. The net has non-negative integer weights, clipped activation, and the initial embeddings are fixed points of isolated vertices. The vocabulary is $\mathcal{V} = \{00, 01, 10, 11\}$ under the product (or componentwise) order on $\mathcal{V}$. The table is three rows by four aggregate values: $\mathcal{T}(b, m) = m$, $\mathcal{T}(r, m) = m \vee 10$, and $\mathcal{T}(g, m) = m \vee 01$ where the aggregate $m = \oplus S$ belongs to $\{00, 01, 10, 11\}$.

Net-to-logic (Theorem 17). There is one set variable X_e and formula Θ_e per vocabulary item $e \in \mathcal{V}$. The compiled system from the quotient table, after translation into μ -calculus, is:

$$\begin{aligned} \Theta_{00} &= \top, \\ \Theta_{10} &= r \vee \Diamond X_{10}, \\ \Theta_{01} &= g \vee \Diamond X_{01}, \\ \Theta_{11} &= (r \wedge \Diamond X_{01}) \vee (g \wedge \Diamond X_{10}) \vee (b \wedge \Diamond X_{11}) \vee (b \wedge \Diamond X_{10} \wedge \Diamond X_{01}). \end{aligned}$$

Applying Bekiř elimination, $\theta_{00} = \top$, and $\theta_{10} = \mu X. (r \vee \Diamond X) = \text{EF } r$. Symmetrically, $\theta_{01} = \text{EF } g$. Finally, $\theta_{11} = \mu Z. ((r \wedge \Diamond \theta_{01}) \vee (b \wedge \Diamond \theta_{10} \wedge \Diamond \theta_{01}) \vee (b \wedge Z)) \equiv \text{EF } r \wedge \text{EF } g$. Finally, the logical characterization obtained from net is $\Phi(\tau(x, u)) = e$ iff $(x, u) \models \theta_e \wedge \bigwedge_{e' \text{ covers } e} \neg \theta_{e'}$. For the example, we get

$$\begin{aligned} \Phi(\tau(x, u)) = 00 &\iff (x, u) \models \neg \theta_{10} \wedge \neg \theta_{01} \wedge \neg \theta_{11}, \\ \Phi(\tau(x, u)) = 10 &\iff (x, u) \models \theta_{10} \wedge \neg \theta_{11}, \\ \Phi(\tau(x, u)) = 01 &\iff (x, u) \models \theta_{01} \wedge \neg \theta_{11}, \\ \Phi(\tau(x, u)) = 11 &\iff (x, u) \models \theta_{11}. \end{aligned}$$

Notice that $\theta_{11} \equiv \theta_{01} \wedge \theta_{10}$.

Appendix: Experimental Validation

We implemented both directions of the compiler – Theorem 17 (net-to-logic) and Theorem 17 (logic-to-net) – and ran a differential-testing validation: for a curated set of 13 branching-time properties drawn from the model-checking literature, we

compile the formula to a net, recover an abstract game table from that net, compile the table back to logic, and check that the two ends of the round trip agree on every vertex of many random graphs. The results, depicted in Table 1, show that across all 13 properties, 9,960 checks total, there is not a single discrepancy between the original formula’s denotational truth value and the value read off the recompiled, un-flattened equation system. This section reports the methodology, the properties tested, how the test graphs were generated, the results, and several findings.

Methodology

For a closed $\mathbf{B}\Sigma_1^\diamond$ formula γ over propositions P :

1. **logic-to-net.** Compile γ into a concrete net $\text{Net} = (A, B, C, \rho = \text{clip}_{[0,1]})$ together with initial embeddings e_α , one per joint Boolean valuation $\alpha \in 2^P$, following the register table of the proof of Theorem 17 verbatim (one register per subformula, one latch per bound variable; no register minimization).
2. **Extraction.** Recover a finite vocabulary $\mathcal{V}$ and quotient table $\mathcal{T} : \text{atoms} \times 2^\mathcal{V} \rightarrow \mathcal{V}$ from Net by simulating the frozen single-vertex system $z_{\ell+1} = \rho(Az_\ell + Bm + C)$ to a fixed point for every atom and every aggregate value m reachable by componentwise max from already-discovered vocabulary elements (mirroring Step 2 of the proof of Theorem 17). The order $\preceq$ is the componentwise order restricted to *core* registers only (Step 3 of that proof): registers realizing a generic negation (re-attaching a dualized block’s polarity) are antitone and are excluded, exactly as the proof’s construction requires.
3. **net-to-logic.** Compile $\mathcal{T}$ into the guarded, positive equation system $\{\zeta_i\}_{i=1}^m$ (one equation per vocabulary element), *without* performing the Bekič elimination that flattens the system into closed formulas θ_i, γ_i . The remark about Bekič-flattened formulas can be exponentially larger than the system they come from surfaces. But, since we only need to *evaluate* the recompiled query, not display it, we evaluate the system directly by a global (simultaneous) Kleene iteration – exactly the practice in verification – rather than incur the blow-up of flattening it first.
4. **Recovery and comparison.** For vertex u , $\Phi(\tau(x, u)) = i$ iff $u \models \Psi_i$ and, for every j with $i < j$ covering i , $u \not\models \Psi_j$, the characterization provided by the theorem, evaluated directly against the system’s fixed point (no Bekič needed for this either). The readout bit this yields at u is compared against $(x, u) \models \gamma$, computed by an *independent* reference evaluator (a direct denotational implementation of $\mathbf{L}\mu$ semantics: Kleene iteration for μ/ν , set operations for the Boolean connectives, direct neighbor tests for $\diamond/\square$) that *shares no code with either compiler*.

Membership in $\mathbf{B}\Sigma_1^\diamond$ was checked mechanically for every formula in the suite; the checker is described precisely. The same checker was confirmed to *reject* $\mu X.\square X$ and $\nu Y.\diamond Y$, the two queries excluded by Proposition 17.

Property Suite

Thirteen properties drawn from standard branching-time vocabulary (CTL’s EF/AG/EU, and Manna–Pnueli-style safety/guarantee combinations), chosen to exercise: pure $\Sigma_1^\diamond$ blocks, pure $\Pi_1^\square$ blocks, flat top-level Boolean combinations of independent blocks, and *same-polarity* nesting of one block inside another’s own body, at depth 2 (sequencing) and depth 3 (sequencing_chain, invariant_chain). Propositions p, q, r label vertices independently (not mutually exclusively): a vertex’s atomic type is its own subset of $\{p, q, r\}$ that holds, so joint valuations, not single labels, play the role of $\text{atp}(u)$.

Name	Formula
reachability	$\text{EF } p = \mu X.(p \vee \diamond X)$
safety	$\text{AG } p = \nu Y.(p \wedge \square Y)$
existential_until	$\text{E}[p \text{ U } q] = \mu X.(q \vee (p \wedge \diamond X))$
reach_avoid	$\text{EF } p \wedge \neg \text{EF } q$
reachability_and_invariant	$\text{EF } p \wedge \text{AG } q$
sequencing	$\text{EF}(p \wedge \text{EF } q)$
reach_or_invariant_avoid	$\text{EF } p \vee (\text{AG } q \wedge \neg \text{EF } r)$
mutual_exclusion	$\text{AG } \neg(p \wedge q)$
combined_three_way	$(\text{EF } p \wedge \neg \text{EF } q) \wedge \text{AG } \neg r$
reach_both	$\text{EF}(p \wedge q)$
implication_invariant	$\text{AG}(\neg p \vee q)$
sequencing_chain	$\text{EF}(p \wedge \text{EF}(q \wedge \text{EF } r))$
invariant_chain	$\text{AG}(p \wedge \text{AG}(q \wedge \text{AG } r))$

All thirteen were confirmed to be $\mathbf{B}\Sigma_1^\diamond$ formulas. Two controls were also checked and confirmed *not* in $\mathbf{B}\Sigma_1^\diamond$, matching Proposition 17: $\text{AF } p = \mu X.(p \vee \square X)$ and $\text{EG } p = \nu Y.(p \wedge \diamond Y)$. A further two formulas, nesting a closed block of the *opposite* polarity inside another block’s own μ/ν body ($\text{EF}(p \wedge \text{AG } q)$ and $\text{AG}(p \rightarrow \text{EF } q)$), were also checked and confirmed *not* in $\mathbf{B}\Sigma_1^\diamond$. *reach_both* and *implication_invariant* are flat, single-block properties (a conjunctive reachability query and an invariant implication); *sequencing_chain* and *invariant_chain* extend sequencing’s depth-2 same-polarity nesting to depth 3.

Graph Generation

Test graphs are random directed graphs (self-loops excluded): for a target size n and edge probability p_e , each of the $n(n-1)$ ordered pairs (u, v) , $u \neq v$, is an edge independently with probability p_e , so the expected edge count is $n(n-1)p_e$. Each vertex’s atomic type is sampled independently per proposition (Bernoulli with a per-formula, per-proposition probability p_{prop} , chosen so that neither γ nor $\neg\gamma$ is a near-certainty – see the true/false split reported for each property below), not by picking one of a fixed set of mutually exclusive labels.

The main sweep, used for eleven of the thirteen rows of Table 1, takes $n \in \{6, 10, 14, 20, 25\}$, three edge probabilities per property (ranging over $\{0.06, 0.12, 0.25\}$, $\{0.08, 0.15, 0.30\}$, or $\{0.15, 0.25, 0.40\}$ depending on the formula – denser for formulas that need longer-range or higher-order reachability to be non-degenerate), and 4 independent graphs per (n, p_e) pair, for 60 graphs and 900 pointed-graph checks per property. Expected edge counts over this sweep range from about 1.8 ($n=6$, $p_e=0.06$) to about 240 ($n=25$, $p_e=0.40$). The remaining two rows use a smaller, single-size sweep, discussed below. Concretely:

Property	p	q	r	p_e
reachability	0.12	–	–	$\{0.06, 0.12, 0.25\}$
safety	0.85	–	–	$\{0.06, 0.12, 0.25\}$
existential_until	0.55	0.12	–	$\{0.08, 0.15, 0.30\}$
reach_avoid	0.15	0.15	–	$\{0.08, 0.15, 0.30\}$
reachability_and_invariant	0.15	0.85	–	$\{0.08, 0.15, 0.30\}$
sequencing	0.20	0.20	–	$\{0.08, 0.15, 0.30\}$
reach_or_invariant_avoid	0.12	0.85	0.12	$\{0.08, 0.15, 0.30\}$
mutual_exclusion	0.35	0.35	–	$\{0.08, 0.15, 0.30\}$
combined_three_way	0.15	0.15	0.10	$\{0.08, 0.15, 0.30\}$
reach_both	0.30	0.30	–	$\{0.08, 0.15, 0.30\}$
implication_invariant	0.30	0.75	–	$\{0.06, 0.12, 0.25\}$
sequencing_chain	0.30	0.30	0.30	$\{0.15, 0.25, 0.40\}$
invariant_chain	0.85	0.85	0.85	$\{0.06, 0.12, 0.25\}$

`reach_or_invariant_avoid` and `combined_three_way` involve three independent propositions, hence 8 atomic types instead of 2–4; extraction produces a vocabulary of 64 elements for both (versus at most 16 for every two-proposition property), and the resulting guarded equations are correspondingly large. Our net-to-logic evaluator is a plain global Kleene iteration with no cross-round memoization, so its cost scales with $(\text{rounds} \approx |\mathcal{V}| \cdot n) \times (\text{total equation size}) \times (n, \text{ for the set operations})$. For these two properties this makes the main sweep’s $n \in \{6, 10, 14, 20, 25\}$, 900-check scale impractical to complete in the time available. Rows 7 and 9 of Table 1 instead report a smaller, single-size sweep ($n = 5$, the same three edge probabilities, two graphs per probability: 6 graphs, 30 checks each).

Reproducibility

Every task reads its graph-generation parameters – propositions, per-proposition probabilities, edge probability, graph size, per-combination count, and random seed – from a frozen manifest that is retained alongside its run’s output and is independently sufficient to regenerate every graph checked below.

The code and results will be made publicly available for the final version of the paper.

Results

Every one of the $13 \times \geq 30$ pointed-graph checks agrees: across all thirteen properties, 9960 checks total, there is not a single discrepancy between the original formula’s denotational truth value and the value read off the recompiled, un-flattened equation system. The true/false splits are non-degenerate for every property except one (each has both outcomes represented, several close to balanced); `combined_three_way`’s split is the most skewed (0 true out of 30) because it is a conjunction of three independently-tuned-to-be-rare conditions at the reduced sample size.

Analysis

The recompiled equation system is, by construction, syntactically unlike the input formula: it is a system of guarded equations over machine-generated variable names (one per element of an extracted vocabulary of up to 64 values), not a formula a person would write. Agreement is therefore purely semantic, which is exactly what a round-trip test of Theorems 17 and 17 should establish: that compiling a query to a net and back recovers a query with the same denotation, on graphs with real structural and answer diversity, not merely on hand-picked small examples. Combined with the two theorems’ proofs, this is strong evidence – though empirical, not a machine-checked proof – that both compilers are correctly implemented on the sub-fragment of $\mathbf{B}\Sigma_1^\diamond$ actually exercised here: flat top-level Boolean combinations of independent blocks, and same-polarity nesting of one block inside another, to at least depth 3 (`sequencing_chain`, `invariant_chain`).

Property	Graphs	Checks	True	False	Mismatches
reachability	60	900	548 (60.9%)	352 (39.1%)	0
safety	60	900	248 (27.6%)	652 (72.4%)	0
existential_until	60	900	359 (39.9%)	541 (60.1%)	0
reach_avoid	60	900	106 (11.8%)	794 (88.2%)	0
reachability_and_invariant	60	900	117 (13.0%)	783 (87.0%)	0
sequencing	60	900	669 (74.3%)	231 (25.7%)	0
reach_or_invariant_avoid	6	30	24 (80.0%)	6 (20.0%)	0
mutual_exclusion	60	900	312 (34.7%)	588 (65.3%)	0
combined_three_way	6	30	0 (0.0%)	30 (100.0%)	0
reach_both	60	900	524 (58.2%)	376 (41.8%)	0
implication_invariant	60	900	444 (49.3%)	456 (50.7%)	0
sequencing_chain	60	900	796 (88.4%)	104 (11.6%)	0
invariant_chain	60	900	145 (16.1%)	755 (83.9%)	0

Table 1: Round-trip agreement between γ 's reference semantics and the recompiled system's semantics, over random pointed graphs. See the discussion in Graph Generation above about `reach_or_invariant_avoid` and `combined_three_way`.