

Stride- k Subsampling: Train-Free Audio Token Reduction for Whisper

Chanhee Cho* Junhyuk Choi* Bugeun Kim

Department of Artificial Intelligence
Chung-Ang University, Seoul, Republic of Korea
{cch991112, chw1nsgur129, bgnkim}@cau.ac.kr

Abstract

Whisper exposes speech through a fixed 1500-token encoder interface, now a default representation for ASR decoders and Whisper-based speech language models (SpeechLMs), yet its redundancy remains largely unexamined. We propose stride- k subsampling, a deterministic indexing operation that retains every k -th token after the convolutional stem or encoder transformer. Across five Whisper scales, $k = 2$ preserves baseline WER at both positions, with CKA attributing this stability to acoustic overlap at the stem and attention-induced redistribution at the encoder output. Applying stride-2 at both positions cuts audio tokens by 75% and total GFLOPs by 52–58%, with small WER costs on most ASR benchmarks and larger costs on harder ones. The same configuration extends to three Whisper-based SpeechLMs, yielding modest accuracy drops on stronger baselines and larger drops on weaker ones, while reducing end-to-end latency by 19.6–27.4%. Requiring no training or auxiliary computation, stride- k subsampling exploits Whisper’s preprocessing redundancy, indicating that its audio-token interface carries more capacity than downstream tasks require.

1 Introduction

Whisper (Radford et al., 2023) is widely used as the audio encoder for automatic speech recognition (ASR) and Whisper-based speech language models (SpeechLMs; Ghosh et al. (2026); Fang et al. (2025)). In these systems, the encoder output serves as the audio-token interface to the text-generating module, and for Whisper the interface is a fixed sequence of 1500 tokens. The token count governs downstream cost. ASR decoders cross-attend to the sequence at each autoregressive step (Monteiro et al., 2024; Żelasko et al., 2025), and SpeechLMs insert the tokens into an

LLM context (Lu et al., 2024). Reducing the number of encoder tokens is therefore a shared lever for lowering inference cost across both settings.

Whisper’s preprocessing pipeline leaves the encoder input redundant. Whisper extracts log-mel features with a 25ms Hann window (Harris, 1978) and a 10ms hop, and the convolutional stem aggregates several overlapping frames into each encoder token, giving every token an effective receptive field wider than its spacing. A calculation from the window and stride configuration shows that stride-2 subsampling after the stem introduces no temporal coverage gap. The retained tokens still cover the full input span, and their accumulated receptive-field overlap amounts to approximately 62% of the span before any self-attention is applied.¹ A substantial fraction of the tokens can therefore be dropped without retraining.

However, existing approaches to audio-encoder efficiency leave the redundancy at the encoder input unaddressed. Redesign-based methods rely on distillation (Gandhi et al., 2023; Ferraz et al., 2024; Waheed et al., 2024), fine-tuning (Liu and Qu, 2024; Wang et al., 2025), or retraining (Sy et al., 2026; Zhang et al., 2026a; Orhon et al., 2025), and cannot be applied to deployed checkpoints without additional training. Train-free pruning methods avoid the retraining cost but share two limitations. First, they intervene on representations the encoder transformer has already processed—encoder hidden states (Xu et al., 2025; Lee and Lee, 2025), encoder outputs (Bhati et al., 2025), or tokens passed to a downstream LLM (Lin et al., 2025; Gibier et al., 2026; Jung et al., 2026)—so the encoder input length is never reduced. Second, they select tokens through data-dependent criteria such as attention scores or pairwise similarity, which require auxiliary computation and produce input-specific token sets.

* Equal contribution.

¹See Appendix A for the derivation.

Concurrently, [Xiang et al. \(2026\)](#) analyze deep-layer redundancy in LSLMs and propose Affinity Pooling, an adaptive cosine-similarity-based token merging method, and [Luo et al. \(2026\)](#) propose LTBM, a train-free encoder-space token merging method that exploits locality.

Motivated by the preprocessing redundancy, we apply **stride- k subsampling**, an operation that retains every k -th token and reduces sequence length through indexing alone. It adds no parameters and no auxiliary computation, and can be inserted into any Whisper-based model with a single indexing step. We apply it at two positions: immediately after the convolutional stem (*input-side*), shortening the sequence fed into the encoder transformer, and after the encoder transformer (*output-side*), shortening the sequence passed to the decoder or downstream LLM. Varying k across five Whisper scales, we find that the two positions behave differently. *Input-side* subsampling preserves WER up to $k = 2$, whereas *output-side* subsampling remains stable through $k = 3$ and beyond—a gap the preprocessing overlap does not account for.

To examine the asymmetry, we measure adjacent-token similarity at the two positions with Centered Kernel Alignment (CKA; [Kornblith et al. \(2019\)](#)). At the *input-side*, similarity decreases continuously as frame distance grows, consistent with the temporal overlap between adjacent frames. Stride-2 retains substantial accumulated overlap, whereas stride-3 reduces the overlap to only about 8%, sharply weakening the redundancy buffer available after subsampling. This helps explain the abrupt degradation once k exceeds 2. At the *output-side*, similarity drops sharply between adjacent frames and then stays roughly flat, a pattern that may underlie the wider stable range there. The two positions therefore expose redundancy of different origins, and since the two sources are complementary, stride-2 can be applied at both positions simultaneously.

Compound stride-2 reduces the audio token count by 75% and total GFLOPs by roughly 52–58%, with WER largely retained across five Whisper scales on most ASR benchmarks and larger increases on more challenging ones. The same configuration extends without modification to three Whisper-based SpeechLMs, where task accuracy is largely retained on stronger baselines, and end-to-end latency improves by 19.6–27.4%. Stride- k subsampling requires no training or auxiliary computation, and serves as a drop-in efficiency im-

provement for Whisper-based models.

2 Related Work

Prior studies compress or redesign Whisper to reduce inference cost. Distillation-based approaches, such as Distil-Whisper ([Gandhi et al., 2023](#)), compress the decoder depth using knowledge distillation, while others extend this framework to multilingual settings ([Ferraz et al., 2024](#)) or explore the robustness of the distillation process itself ([Waheed et al., 2024](#)). Parameter-efficient fine-tuning methods ([Liu and Qu, 2024](#); [Wang et al., 2025](#)) adapt Whisper for low-resource environments by optimizing a small subset of parameters using techniques like LoRA ([Hu et al., 2022](#)). Intervening at the hidden representation level offers another route. BaldWhisper ([Sy et al., 2026](#)) combines head shearing and layer merging, Whisper-MLA ([Zhang et al., 2026a](#)) converts the decoder’s multi-head attention to multi-head latent attention to reduce key-value cache size, and WhisperKit ([Orhon et al., 2025](#)) applies system-level optimizations and quantization. These approaches commonly require additional training procedures cannot be applied directly to already-deployed checkpoints.

A second line of work reduces audio token sequences without retraining. SpeechPrune ([Lin et al., 2025](#)) uses speech-text similarity and first-layer attention scores to remove audio tokens fed into a speech LLM, while Segmentwise Pruning ([Gibier et al., 2026](#)) groups adjacent tokens into segments and prunes them via attention scores in audio-language models. Early Attentive Sparsification ([Xu et al., 2025](#)) sparsifies hidden states using self-attention scores in early Whisper encoder layers, and Towards Audio Token Compression ([Bhati et al., 2025](#)) compresses encoder outputs through unsupervised segmentation and average pooling, aligning the result to a downstream LLM via low-rank adapters. Concurrently, [Xiang et al. \(2026\)](#) analyze deep-layer redundancy in LSLMs and propose Affinity Pooling, an adaptive cosine-similarity-based token merging method, and [Luo et al. \(2026\)](#) propose LTBM, which merges encoder-space audio tokens by pairwise similarity under an explicit temporal-locality constraint, so that a token is combined only with neighbors inside a fixed time window.

These studies show that audio-sequence redundancy is a useful efficiency signal, but two gaps

remain. First, prior methods target hidden states downstream of the audio encoder, tokens passed to a downstream LLM, or intermediate encoder tokens, and therefore do not reduce input length before the encoder transformer processes it. Second, they rely on data-dependent criteria such as similarity computation or attention score analysis.

3 Stride- k Subsampling

3.1 Preliminaries

Whisper extracts log-mel features with a 25 ms Hann window and 10 ms hop, and a convolutional stem (conv stem) with stride-2 produces a 1500-token sequence. The encoder transformer preserves sequence length, and the decoder cross-attends to all 1500 tokens at every autoregressive step, making decoder cross-attention FLOPs linear in encoder output length. The 25 ms window and 10 ms hop introduce overlap between adjacent log-mel frames, and the convolutional stem further expands this redundancy by aggregating multiple overlapping frames into each encoder token. An analysis that accounts for the STFT window, hop size, and the effective receptive field induced by the convolutional stem shows that stride-2 subsampling after the stem introduces no temporal coverage gap while still leaving approximately 62% of the input span overlapped by adjacent retained receptive fields. At stride-3, this accumulated overlap drops to only 8.3%, sharply weakening the redundancy buffer available after subsampling.² We define stride- k subsampling as $H' = H[:, :k, :] \in \mathbb{R}^{[T/k] \times d}$ for an encoder representation $H \in \mathbb{R}^{T \times d}$ with T tokens and hidden size d . The operation requires no training, fine-tuning, distillation, or attention-based selection, and reduces sequence length to $1/k$ via indexing alone. We apply it at two positions (*input-side* and *output-side*). For the full algorithm and implementation details, refer to Appendix B.

3.2 Input-side Stride- k Subsampling

Input-side subsampling applies stride- k subsampling immediately after the conv stem, before the encoder transformer. The encoder processes a sequence of length $1500/k$ instead of 1500, reducing both encoder self-attention FLOPs and decoder cross-attention FLOPs. *Input-side* subsampling directly exploits the acoustic redundancy induced by the window hop length and conv stem.

²Refer to Appendix A

3.3 Output-side Stride- k Subsampling

Output-side subsampling applies stride- k subsampling immediately after the encoder transformer, before decoder cross-attention. In the vanilla encoder path, the encoder still processes all 1500 tokens, so encoder FLOPs are unchanged; only the decoder cross-attention FLOPs are reduced through the smaller number of target tokens. *Output-side* subsampling exploits the representational redundancy formed between adjacent tokens by encoder self-attention.

4 Diagnosing the stride- k Subsampling

4.1 Experimental Setup

4.1.1 Benchmark

To analyze the effect of stride- k subsampling, we use three benchmarks spanning distinct acoustic conditions and a range of recognition difficulty. LibriTTS (Zen et al., 2019) consists of clean read speech. ESD (Zhou et al., 2022) consists of emotionally expressive speech recorded in a controlled environment. Common Voice (Ardila et al., 2020) consists of crowd-sourced speech under varied noise and recording conditions.

4.1.2 Selected Models

We evaluate stride- k subsampling on all five Whisper scales (tiny, base, small, medium, large) for $k \in \{1, \dots, 6\}$, where $k = 1$ denotes the unmodified baseline. We focus on Whisper because it is one of the most widely used encoder-decoder ASR models and is also commonly used as a speech encoder in recent SpeechLMs. For Whisper, the STFT window, hop size, and convolutional-stem stride imply that retained post-stem tokens continue to overlap up to $k = 3$; evaluating through $k = 6$ allows us to examine behavior beyond this overlap regime. Detailed settings are in Appendix C.

4.1.3 Evaluation Metrics

We measure both ASR performance and inference cost. ASR performance is reported as Word Error Rate (WER). Inference cost is measured by the total FLOPs. Both quantities scale linearly with the number of encoder output tokens, and are therefore reduced by a factor of $1/k$ under stride- k .

4.2 Results

We report WER across three benchmarks, five Whisper scales, and stride values $k=1, \dots, 6$ at




Figure 1: WER under stride- k subsampling. Top row: *input-side*; bottom row: *output-side*. Left y -axis: WER (lines, one per benchmark); right y -axis: remaining FLOPs relative to $k=1$ (bars).

both subsampling positions, analyzed along three axes: benchmark, model scale, and subsampling position. Figure 1 summarizes the results, with full per-configuration numbers in Appendix D.

Stability scales with input difficulty. The stable range of k correlates with baseline WER. On LibriTTS, baseline WER for Whisper-Large is 4.31 and *output-side* WER is 4.30 at $k=2$ and 5.47 at $k=4$. On Common Voice, baseline WER for Whisper-Large is 11.66 and *output-side* WER rises to 12.70 at $k=2$ and 16.26 at $k=4$. The *input-side* position shows the same ordering: at $k=2$, the WER increase relative to baseline is smallest on LibriTTS and largest on Common Voice. ESD shows higher absolute WER than LibriTTS but a comparable relative trajectory across k .

Stability scales with model scale. Within each benchmark, larger models tolerate larger k before degradation. On LibriTTS at *input-side* $k=2$, WER relative to baseline increases by a factor of 2.40 for Tiny (8.86 $\rightarrow$ 21.23), 1.82 for Base (6.87 $\rightarrow$ 12.47), 1.60 for Small (5.02 $\rightarrow$ 8.04), 1.35 for Medium (4.61 $\rightarrow$ 6.22), and 1.07 for Large (4.31 $\rightarrow$ 4.63). At *output-side* $k=4$ on LibriTTS, WER stays within one point of baseline for Medium (4.61 $\rightarrow$ 5.54) and Large (4.31 $\rightarrow$ 5.47), while Tiny rises from 8.86 to 16.57 and Base from 6.87 to 8.22. The same monotonic ordering holds on ESD; on Common Voice the ordering holds but the absolute gap between scales is larger.

Input-side and output-side degrade differently. The two positions differ in both the stable range

of k and the shape of degradation beyond it. At $k=2$, both remain close to baseline, though the *output-side* WER is consistently lower than the *input-side* WER at the same k (LibriTTS Whisper-Small: input 8.04 vs. output 5.13; LibriTTS Whisper-Medium: input 6.22 vs. output 4.70). At $k=3$, *input-side* WER increases abruptly across all benchmarks and scales (LibriTTS Whisper-Medium: 4.61 $\rightarrow$ 19.51; Whisper-Large: 4.31 $\rightarrow$ 16.20), while *output-side* WER remains within a small margin of baseline (Whisper-Medium: 4.61 $\rightarrow$ 4.94; Whisper-Large: 4.31 $\rightarrow$ 4.69). The asymmetry persists at $k=4$, with *input-side* WER climbing steeply and *output-side* WER increasing gradually. The pattern is consistent across the benchmark and scale axes reported above.

4.3 Discussion

Stability tracks baseline strength. The benchmark and scale results share a common pattern. Configurations with lower baseline WER tolerate larger k before degradation. The pattern holds across both subsampling positions, indicating that stride- k subsampling is most reliably applicable when the underlying Whisper checkpoint already performs well on the input. The behavior is consistent with the interpretation that subsampling exposes a fixed fraction of redundancy, and that recognition under reduced input is bounded by the model’s baseline competence on that input.

Preprocessing overlap does not explain the output-side. Output-side subsampling stays near baseline over a wider k range than input-side,

degrading gradually rather than abruptly. The Section 3 overlap argument explains *input-side* $k=2$ via the receptive field and window overlap between adjacent frames, but not the wider *output-side* range, where adjacent tokens come from the encoder transformer rather than the conv stem. This suggests the encoder output carries redundancy absent after the conv stem, which we probe in Section 5 via adjacent-token similarity.

5 CKA Analysis of Adjacent-token Similarity

The positional asymmetry in Section 4 is not predicted by the frame-overlap argument alone, which accounts only for the local redundancy at the conv stem. To investigate the wider stable range at the *output-side*, we measure how representational similarity between tokens evolves with frame distance at the two positions.

5.1 Experimental Setup

Data. We run the analysis on LibriTTS. For each utterance in the test set, we extract token representations at the conv stem output and the encoder output, and select 10 anchor tokens from positions with a full neighborhood up to $d=5$. Measurements are performed across the five Whisper scales. Further details are in Appendix E.

Measurement. For each position and each frame distance $d \in \{1, \dots, 5\}$, we compute Linear CKA between the anchor tokens and the tokens at offset d . Linear CKA measures the alignment of representational geometry between two sets of vectors and is invariant to orthogonal transformation and isotropic scaling. Absolute CKA values, however, are not directly comparable across the two positions, since conv stem outputs and encoder outputs lie in different representation spaces with different intrinsic self-similarity scales (see Appendix E). We therefore report, as our primary quantity, the step-wise change

$$\Delta(d \rightarrow d+1) = 100 \times (\text{CKA}(d+1) - \text{CKA}(d)) / \text{CKA}(d),$$

which characterizes the shape of similarity decay independently of its absolute level.

5.2 Results and Discussion

Conv stem decays continuously while encoder output plateaus after $d=1$. Table 1 shows two distinct decay shapes. At the conv stem, Δ stays

Scale	Layer	$d=0$	$d=1$	$d=2$	$d=3$	$d=4$
Tiny	Conv Stem	-3.60	-6.26	-5.82	-4.63	-2.99
	Enc Out	-11.92	-11.96	-4.87	-0.24	+0.37
Base	Conv Stem	-3.59	-6.48	-6.21	-5.05	-3.25
	Enc Out	-9.70	-10.66	-5.44	-1.85	+0.55
Small	Conv Stem	-3.92	-6.90	-6.57	-5.28	-3.37
	Enc Out	-17.23	-9.80	+0.99	-1.43	+3.16
Medium	Conv Stem	-3.81	-6.20	-5.62	-4.53	-3.04
	Enc Out	-21.33	-15.82	-2.11	+0.35	+0.37
Large	Conv Stem	-2.05	-3.01	-2.63	-2.14	-1.39
	Enc Out	-14.03	-11.26	-5.07	-1.50	-0.49

Table 1: Step-wise change $\Delta(d \rightarrow d+1) = 100 \cdot (\text{CKA}(d+1) - \text{CKA}(d)) / \text{CKA}(d)$, where $\text{CKA}(0) = 1$

negative and shrinks monotonically in magnitude as d grows, a continuous decay: on Whisper-Base it moves from -6.48 at $d=1$ to -6.21 , -5.05 , -3.25 at $d=2, 3, 4$, and the same profile holds across scales. The smaller magnitude at $d=0$ reflects the trivial self-similarity reference $\text{CKA}(0)=1$, so we read the decay shape from $d=1$ onward. This continuous profile follows from receptive-field overlap: each post-stem token spans an effective receptive field of about 65 ms while adjacent tokens are spaced every 20 ms, and the resulting shared acoustic support diminishes gradually as distance grows. At the encoder output, the relative change is large over the first two steps and then becomes much smaller: on Whisper-Large it moves from -14.03 and -11.26 at $d=0, 1$ to -5.07 , -1.50 , -0.49 at $d=2, 3, 4$, with the same pattern across scales. Beyond $d=1$, similarity between an anchor and its neighbors no longer depends systematically on distance. This suggests that the encoder transformer, while still locally biased, does not concentrate redundancy only in the adjacent pair; instead, it redistributes redundancy across a wider local neighborhood.

The two decay shapes align with the WER.

The two shapes correspond to the two degradation patterns observed under stride- k subsampling. At the *input-side*, similarity decays continuously, so the retained tokens become progressively weaker substitutes for the dropped ones as d grows. This matches the *input-side* WER profile, which stays near baseline at $d=2$ and rises sharply from $d=3$ onward. At the *output-side*, the similarity change is concentrated in the first two steps and plateaus afterward, so additional skipping incurs little further loss, matching the gradual *output-side* WER profile through $d=4$. The positional asymmetry

in Section 4 therefore reflects a difference in the shape of similarity decay, not in its absolute level.

The output-side plateau exceeds what locality predicts. The Whisper encoder is reported to attend locally, with self-attention dominated by a diagonal band (Zhang et al., 2026b; Alastruey et al., 2022). A purely local account would predict a continuous decay at the encoder output, as at the conv stem, but the observed plateau departs from this. The encoder transformer, though still local, redistributes redundancy across the neighborhood rather than concentrating it in the adjacent pair. This redundancy is independently consistent with reports that the upper Whisper encoder layers can be pruned without loss (Irigoyen et al., 2025), and is what supports the wider stable range of d at the *output-side*. Full CKA values are in Appendix F.

6 Compound Stride-2

Two findings motivate combining the positions. First, stride-2 preserves baseline WER at both the *input-side* and *output-side* across all scales and benchmarks. Second, the stability arises from independent forms of overlap—one at the conv stem, one at the encoder output—that can be exploited together. We therefore apply stride-2 at both positions and evaluate it as a drop-in efficiency improvement for Whisper-based models.

6.1 Experiment Setup

We evaluate compound stride-2 ($k_{\text{in}} = k_{\text{out}} = 2$) in two settings, Whisper ASR and SpeechLMs. Subsampling is applied only to the Whisper encoder, leaving all other components unmodified. Reproduction details are in Appendix G.

Whisper ASR. Since Section 4 shows that stability under stride- k improves with model scale, we focus on the three larger Whisper scales—Small, Medium, and Large-v3—and evaluate on LibriTTS, ESD, and English Common Voice, with Chinese Common Voice results reported in Appendix I. Performance is measured by WER, and efficiency by total GFLOPs and end-to-end latency.

SpeechLMs. We evaluate three widely used open-source models, Audio Flamingo 3 (AF3; Ghosh et al., 2026), Qwen2-Audio (Chu et al., 2024), and LLaMA-Omni 2 (Fang et al., 2025), on two benchmarks, MMSU (Dingdong et al., 2026)

and MMAU (Sakshi et al., 2025). MMSU evaluates spoken language understanding through linguistic and paralinguistic tasks, split into a perception group that probes fine-grained acoustic cues such as intonation, pause, and stress, and a reasoning group requiring higher-level inference over them. MMAU covers general audio reasoning across the sound, music, and speech domains, and requires expert-level knowledge beyond direct acoustic perception. Across both benchmarks, some categories—intonation and pause in MMSU, counting in MMAU—depend on fine-grained temporal structure, the timing of acoustic events rather than their identity, which we revisit in the failure-case analysis. Performance is measured by accuracy, and efficiency by total GFLOPs and end-to-end latency. To analyze where subsampling changes model behavior rather than only by how much, we additionally report per-example hurt and help rates, the fractions of baseline-correct examples that become incorrect and incorrect examples that become correct under compound stride-2.

6.2 Results

ASR. Compound stride-2 keeps WER reasonably close to baseline on LibriTTS and ESD, with the gap shrinking as model scale increases (Table 2). On LibriTTS, the WER increase decreases from +4.20 on Small to +2.40 on Medium and +1.07 on Large-v3; on ESD, the corresponding gaps are +4.84, +3.50, and +1.01. Common Voice is the most sensitive benchmark, showing substantially larger increases of +13.40, +9.56, and +9.90. These results indicate that compound stride-2 is absorbed more reliably by stronger Whisper checkpoints and by cleaner or more controlled inputs. Although total GFLOPs drop by approximately 57%, end-to-end latency changes only modestly (+3.6%, −1.1%, and −6.0%), which we analyze in Section 6.

Whisper-based SpeechLMs. Across the three models, task accuracy decreases with compound stride-2, and the size of the drop varies systematically. Audio Flamingo 3 shows the smallest drops on every block, with −1.00 on MMSU Perception, −2.81 on MMSU Reasoning, and −1.7 on MMAU Audio. Qwen2-Audio falls between AF3 and LLaMA-Omni 2 (−1.62, −6.16, and −3.6, respectively), and LLaMA-Omni 2 shows the largest drops (−3.06, −9.71, −5.5). The ordering is consistent across the three benchmark blocks. Within

Whisper		Small			Medium			Large		
		Base.	Both $k=2$	Δ	Base.	Both $k=2$	Δ	Base.	Both $k=2$	Δ
ASR (WER %)	LibriTTS	5.02	9.22	+4.20	4.61	7.01	+2.40	4.31	5.38	+1.07
	ESD	9.39	14.23	+4.84	8.65	12.16	+3.50	9.63	10.64	+1.01
	Common Voice	17.94	31.34	+13.40	14.26	23.82	+9.56	11.66	21.56	+9.90
GFLOPs		381.51	159.45	−58.2%	1282.00	548.30	−57.2%	2577.71	1119.27	−56.6%
Total ms		143.76	148.88	+3.6%	234.85	232.25	−1.1%	313.94	295.17	−6.0%

SpeechLMs		Audio Flamingo3					Qwen2-Audio					LLaMA-Omni2				
		Base.	Both $k=2$	Δ	Hurt	Help	Base.	Both $k=2$	Δ	Hurt	Help	Base.	Both $k=2$	Δ	Hurt	Help
MMSU Perception	Ling.Semantics	52.28	51.97	−0.31	3.46	3.15	53.54	51.65	−1.89	6.77	4.88	31.65	28.82	−2.83	7.40	4.57
	Ling.Phonology	37.75	37.54	−0.21	6.63	6.42	37.11	36.36	−0.75	5.99	5.24	33.16	28.24	−4.92	8.88	3.96
	Para.Speaker Traits	49.13	44.32	−4.81	9.17	4.37	44.10	40.39	−3.71	8.73	5.02	24.24	24.24	0.00	8.08	8.08
	Para.Speaking Style	34.60	34.60	0.00	1.45	1.45	31.16	30.07	−1.09	4.53	3.44	27.36	24.64	−2.72	9.24	6.52
	<i>Average</i>	42.67	41.67	−1.00	−	−	41.12	39.50	−1.62	−	−	29.96	26.90	−3.06	−	−
MMSU Reasoning	Ling.Semantics	87.45	81.77	−5.68	6.86	1.17	81.05	72.29	−8.76	12.09	3.34	61.10	47.38	−13.72	16.52	2.80
	Ling.Phonology	76.97	76.25	−0.72	5.02	4.30	64.69	60.80	−3.89	7.98	4.09	64.38	57.22	−7.16	10.44	3.28
	Para.Speaker Traits	44.25	43.36	−0.89	6.64	5.75	47.79	46.02	−1.77	8.85	7.08	29.20	26.99	−2.21	8.85	6.64
	Para.Speaking Style	43.12	46.79	+3.67	4.59	8.26	44.95	35.78	−9.17	11.01	1.83	39.45	32.11	−7.34	12.84	5.50
	<i>Average</i>	77.19	74.38	−2.81	−	−	69.71	63.55	−6.16	−	−	58.47	48.76	−9.71	−	−
MMAU Audio	Sound	73.6	72.1	−1.5	4.80	3.30	59.8	55.3	−4.5	6.61	2.10	52.6	45.3	−7.2	11.41	4.20
	Music	79.3	78.4	−0.9	4.49	3.59	55.4	53.3	−2.1	5.39	3.29	52.7	53.6	+0.9	5.69	6.59
	Speech	58.6	55.9	−2.7	5.11	2.40	53.8	49.5	−4.2	9.31	5.11	48.9	38.7	−10.2	14.71	4.50
	<i>Average</i>	70.5	68.8	−1.7	−	−	56.3	52.7	−3.6	−	−	51.4	45.9	−5.5	−	−
GFLOPs		6163.58	2910.34	−52.8%	−	−	6226.83	2991.48	−51.9%	−	−	7449.83	3232.28	−56.6%	−	−
Total ms		122.16	94.92	−22.3%	−	−	112.25	90.27	−19.6%	−	−	194.35	141.12	−27.4%	−	−

Table 2: Compound stride-2 results on Whisper ASR and Whisper-based SpeechLMs. ASR results are reported in WER, and SpeechLM results in accuracy. Δ is computed as compound stride-2 minus baseline. Hurt and Help indicate baseline-correct/subsampled-incorrect and baseline-incorrect/subsampled-correct cases, respectively.

each model, MMSU Perception is more robust than MMSU Reasoning, with the largest individual drop occurring on LLaMA-Omni 2 Reasoning Linguistic Semantics (−13.72). Total GFLOPs drop by 51.9–56.6% across the three models, and end-to-end latency drops by 19.6–27.4%. The hurt and help rates show that these average drops come from asymmetric example-level changes. MMSU Perception keeps hurt and help close, as in AF3 Linguistic Semantics (3.46 vs. 3.15), while MMSU Reasoning widens the gap, with hurt exceeding help by 5.69, 8.75, and 13.72 points on Linguistic Semantics for AF3, Qwen2-Audio, and LLaMA-Omni 2. MMAU splits the same way, with Music staying balanced and LLaMA-Omni 2 Speech (14.71 vs. 4.50) and Sound (11.41 vs. 4.20) showing the largest hurt rates.

6.3 Discussion

Robustness follows baseline and input stability. The aggregate results show that compound stride-2 is absorbed more reliably when the underlying system already performs well. Across SpeechLMs, the accuracy-drop ordering follows the baseline ordering: AF3 is the most stable, Qwen2-Audio is intermediate, and LLaMA-

Omni 2 is the most sensitive. The ASR results show the same trend across Whisper scales, where Large-v3 incurs smaller WER gaps than Small and Medium on LibriTTS and ESD. Input condition also matters. Common Voice shows the largest WER increase, likely because its noisier and more heterogeneous recordings leave less redundancy for temporal subsampling, whereas the cleaner LibriTTS and controlled ESD remain closer to baseline. A controlled white-noise sweep on LibriTTS confirms this directly. As SNR falls from clean to 0 dB, the compound stride-2 gap grows from +0.9 to +28.6 WER on Large-v3 and from +3.7 to +57.5 on Small, while output-side $k = 2$ stays within about one point of baseline at every level (Appendix H). The same pattern reproduces beyond English. On Common Voice Chinese, measured in character error rate, both the scale ordering and the input/output asymmetry hold, with output-side $k = 2$ staying near baseline at every scale (Appendix I). Thus, compound stride-2 is most reliable when both the model and the input domain provide enough robustness margin under reduced temporal resolution. These aggregate drops, however, do not reveal which ex-

amples change. We examine this next through the hurt/help rates.

Error shifts depend on temporal evidence.

The hurt and help rates reveal where, not just how much, compound stride-2 changes model behavior. Hurt cases concentrate in groups that require sparse or temporally localized evidence, with MMSU Reasoning more fragile than Perception and MMAU Sound and Speech more fragile than Music. These groups rely on cues such as pause boundaries, word-level intonation, and event counting, where the answer depends not on what acoustic event is present but on when it occurs, and compound stride-2 reduces the temporal resolution, blurring the few frames that determine the answer. Help cases show the opposite tendency, appearing when the decision can rely on broader patterns such as coarse prosody, tempo, or stable timbre. This suggests compound stride-2 does not always behave as pure information loss, and in some cases acts as a temporal smoothing operation that suppresses local distractors. The method is therefore most reliable when the downstream decision depends on broadly distributed acoustic evidence, and most fragile when it requires sparse, fine-grained temporal cues.

Transfer depends on the frontend, not the architecture.

The conditions above concern when stride-2 is safe within a Whisper-based system; a separate question is which encoders admit it at all. We do not claim that stride- k generalizes to every speech encoder. Appendix J evaluates this question on additional encoders, including the Phi-4-multimodal conformer and raw-waveform encoders such as wav2vec 2.0, HuBERT, and WavLM. The operative condition is narrower, and can be checked before running a model: whether the preprocessing pipeline leaves adjacent tokens overlapping enough that the retained ones still cover the signal, that is, $R \geq kS$ for receptive field R and spacing S (Appendix A). Whisper satisfies it ($R = 65$ ms at $S = 20$ ms), and so does the mel-plus-convolution frontend of the Phi-4-multimodal conformer (165 ms at 80 ms), which tolerates compound stride-2 with larger but non-catastrophic drops. Raw-waveform encoders do not: wav2vec 2.0, HuBERT, and WavLM feed the waveform directly into convolutions (25 ms at 20 ms) and collapse at the first stride ($3.06 \rightarrow 17.21$, $3.68 \rightarrow 24.55$, and $7.60 \rightarrow 48.67$ WER). Holding the encoder blocks fixed and varying only

the frontend isolates the cause: a raw-waveform conformer collapses like the self-supervised encoders ($4.04 \rightarrow 28.10$), while the mel-input conformer does not. Since overlapping windowed analysis is standard practice in signal processing, any encoder following that convention is a candidate for stride- k .

Compute reduction translates differently to wall-clock gains across settings.

Compound stride-2 reduces total GFLOPs by a similar amount in the two settings ($\sim 57\%$ for ASR, $52\text{--}57\%$ for SpeechLMs), but end-to-end latency improves much more in SpeechLMs (-19.6% to -27.4%) than in ASR (-6.0% on Large, near-zero or slightly negative on smaller scales). The asymmetry follows from where audio tokens enter the computation. In Whisper ASR, the decoder is autoregressive while the encoder runs once, and the decoder dominates total runtime (Radford et al., 2023; Kwon et al., 2025). Compound stride-2 reduces the number of cross-attention keys but leaves the number of decoder steps unchanged, so the FLOPs reduction does not transfer to speedup. In SpeechLMs, audio tokens are prepended to a downstream LLM and consumed during prefill, so audio token count determines prefill cost. Reducing audio tokens from 1500 to 375 lowers prefill cost in proportion to the token reduction, and end-to-end latency improves accordingly.

6.4 Composability with other methods

Stride- k subsampling reduces tokens at the encoder, whereas existing train-free methods prune tokens after they enter the downstream LLM. To examine how the two interact, we compare against SpeechPrune (SP), a representative attention-based pruning method for speech LLMs, at a pruning ratio matched to the 75% token reduction of compound stride-2 for an equal compression budget. Beyond this head-to-head comparison, the two methods can also be combined: applying *input-side* stride-2 on top of SP reduces compute further with little additional accuracy loss, indicating that the two operate on complementary redundancy and compose rather than compete. Full results are in Appendix K.

Stride- k also composes with distillation. Distil-Whisper compresses the decoder, an axis orthogonal to the encoder-side token reduction of stride- k , so the two can be stacked. Applying compound stride-2 to Distil-Whisper large-v3 cuts its

(a) vs. SpeechPrune — SpeechLMs, Accuracy			
	AF3	Qwen2-A.	L-Omni2
<i>MMSU Perception</i>			
Base.	42.67	41.12	29.96
SP	38.02	33.88	27.05
Ours	41.67	39.50	26.90
<i>MMSU Reasoning</i>			
Base.	77.19	69.71	58.47
SP	62.73	53.60	50.50
Ours	74.38	63.55	48.76
<i>MMAU</i>			
Base.	70.5	56.3	51.4
SP	66.1	49.0	47.0
Ours	68.8	52.7	45.9
<i>Efficiency</i>			
SP Δ FLOPs	−33.13%	−32.45%	−39.91%
Ours ΔFLOPs	−52.8%	−51.9%	−56.6%
SP Δ Lat.	−20.02	−14.56	−24.37
Ours ΔLat.	−22.3%	−19.6%	−27.4%
(b) vs. Distil-Whisper — ASR, WER			
	WER	Δ WER	Δ FLOPs
LibriTTS	8.31	+3.37	−54.3%
ESD	13.28	+3.80	−54.3%
Common Voice	31.07	+16.56	−54.3%

Table 3: Composability of stride- k . (a) vs. SpeechPrune (SP) on Whisper-based SpeechLMs; Efficiency rows are Δ vs. Baseline. (b) Compound stride-2 on top of Distil-Whisper large-v3; Δ vs. the Distil-Whisper.

total FLOPs by roughly a further 54%, with WER staying close to the Distil-Whisper baseline on LibriTTS and ESD and a larger increase on the harder Common Voice, consistent with the difficulty trend in Section 6 (Appendix M).

7 Conclusion

We propose stride- k subsampling, a train-free indexing operation that reduces Whisper audio tokens by retaining every k -th token after the convolutional stem or encoder transformer. Across five Whisper scales, $k = 2$ keeps WER close to baseline, with CKA linking this stability to acoustic overlap and attention-induced redistribution. Compound stride-2 cuts audio tokens by 75% and GFLOPs by 52–58%, with small WER costs on most ASR benchmarks and larger costs on harder ones. On three Whisper-based SpeechLMs, it yields modest accuracy drops on stronger baselines and larger drops on weaker ones, while reducing latency by 19.6–27.4%. The latency results show that audio-token reduction has its largest wall-clock effect when tokens enter downstream LLM prefill, while ASR benefits more

through FLOPs reduction and composability with decoder-side compression. These results suggest that Whisper’s standard audio-token interface is over-provisioned for many downstream uses.

Limitations

stride- k subsampling assumes an encoder that processes speech as overlapping windowed frames, as in Whisper’s log-mel frontend, where adjacent tokens share acoustic support by construction. Raw-waveform encoders such as HuBERT and wav2vec 2.0 form their representations differently, and whether a comparable redundancy can be exploited there is an open question we do not address here. The method also operates inside the encoder, applying stride- k between the conv stem and the encoder transformer. This requires access to the encoder’s internal computation, so our evaluation covers open-weight ASR models and SpeechLMs; closed models exposed only through an API cannot be modified in this way and fall outside our scope. Finally, we study stride- k purely as a train-free operation and do not retrain or fine-tune any model, a choice made under our compute budget. We view this as a starting point rather than a boundary. Our results show that subsampling is most reliably absorbed by systems that already perform well, which suggests that the redundancy stride- k exploits is partly shaped by training. Whether this redundancy can be deliberately encouraged—so that models are trained to tolerate, or even expect, subsampled token sequences—is a direction we find promising and leave to future work.

Acknowledgments

This research was supported by Basic Science Research Program through the National Research Foundation of Korea(NRF) funded by the Ministry of Education (RS-2025-25434151) and the Institute of Information & Communications Technology Planning & Evaluation (IITP) grant funded by the Korea government (MSIT) [RS-2021-II211341, Artificial Intelligence Graduate School Program (Chung-Ang University)].

References

Belen Alastruey, Javier Ferrando, Gerard I Gállego, and Marta R Costa-jussà. 2022. On the locality of attention in direct speech translation. In *Proceedings of*

- the 60th Annual Meeting of the Association for Computational Linguistics: Student Research Workshop*, pages 402–412.
- Rosana Ardila, Megan Branson, Kelly Davis, Michael Kohler, Josh Meyer, Michael Henretty, Reuben Morais, Lindsay Saunders, Francis Tyers, and Gregor Weber. 2020. Common voice: A massively-multilingual speech corpus. In *Proceedings of the twelfth language resources and evaluation conference*, pages 4218–4222.
- Saurabhchand Bhati, Samuel Thomas, Hilde Kuehne, Rogerio Feris, and James Glass. 2025. Towards audio token compression in large audio language models. *arXiv preprint arXiv:2511.20973*.
- Yunfei Chu, Jin Xu, Qian Yang, Haojie Wei, Xipin Wei, Zhifang Guo, Yichong Leng, Yuanjun Lv, Jinzheng He, Junyang Lin, et al. 2024. Qwen2-audio technical report. *arXiv preprint arXiv:2407.10759*.
- WANG Dingdong, Junan Li, Jincenzi Wu, Dongchao Yang, Xueyuan Chen, Tianhua Zhang, and Helen M Meng. 2026. Mmsu: A massive multi-task spoken language understanding and reasoning benchmark. In *The Fourteenth International Conference on Learning Representations*.
- Qingkai Fang, Yan Zhou, Shoutao Guo, Shaolei Zhang, and Yang Feng. 2025. Llama-omni 2: Llm-based real-time spoken chatbot with autoregressive streaming speech synthesis. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 18617–18629.
- Thomas Palmeira Ferraz, Marcelly Zanon Boito, Caroline Brun, and Vassilina Nikoulina. 2024. Multilingual distilwhisper: Efficient distillation of multi-task speech models via language-specific experts. In *ICASSP 2024-2024 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 10716–10720. IEEE.
- Sanchit Gandhi, Patrick Von Platen, and Alexander M Rush. 2023. Distil-whisper: Robust knowledge distillation via large-scale pseudo labelling. *arXiv preprint arXiv:2311.00430*.
- Sreyan Ghosh, Arushi Goel, Jaehyeon Kim, Sonal Kumar, Zhifeng Kong, Sang-gil Lee, Chao-Han Yang, Ramani Duraiswami, Dinesh Manocha, Rafael Valle, et al. 2026. Audio flamingo 3: Advancing audio intelligence with fully open large audio language models. *Advances in Neural Information Processing Systems*, 38:41819–41886.
- Marcel Gibier, Pierre Serrano, Olivier Boeffard, Raphaël Duroselle, and Jean-François Bonastre. 2026. Segmentwise pruning in audio-language models. In *ICASSP 2026-2026 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 15322–15326. IEEE.
- Fredric J Harris. 1978. On the use of windows for harmonic analysis with the discrete fourier transform. *Proceedings of the IEEE*, 66(1):51–83.
- Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Liang Wang, Weizhu Chen, et al. 2022. Lora: Low-rank adaptation of large language models. *Iclr*, 1(2):3.
- Julian Irigoyen, Arthur Söhler, and Andreas Søeborg Kirkedal. 2025. Pruning as regularization: Sensitivity-aware one-shot pruning in asr. *arXiv preprint arXiv:2511.08092*.
- Chaeyoung Jung, Youngjoon Jang, Seungwoo Lee, and Joon Son Chung. 2026. Fastav: Efficient token pruning for audio-visual large language model inference. *arXiv preprint arXiv:2601.13143*.
- Simon Kornblith, Mohammad Norouzi, Honglak Lee, and Geoffrey Hinton. 2019. Similarity of neural network representations revisited. In *International conference on machine learning*, pages 3519–3529. PMIR.
- Taeyoun Kwon, Junhyuk Ahn, Taegeun Yun, Heeju Jwa, Yoonchae Choi, Siwon Park, Nam-Joon Kim, Jangchan Kim, Hyun Gon Ryu, and Hyuk-Jae Lee. 2025. Whisfusion: Parallel asr decoding via a diffusion transformer. *arXiv preprint arXiv:2508.07048*.
- Taehan Lee and Hyukjun Lee. 2025. Token pruning in audio transformers: Optimizing performance and decoding patch importance. *arXiv preprint arXiv:2504.01690*.
- Yueqian Lin, Yuzhe Fu, Jingyang Zhang, Yudong Liu, Jianyi Zhang, Jingwei Sun, Hai Helen Li, and Yiran Chen. 2025. Speechprune: Context-aware token pruning for speech information retrieval. In *2025 IEEE International Conference on Multimedia and Expo (ICME)*, pages 1–6. IEEE.
- Yunpeng Liu and Dan Qu. 2024. Parameter-efficient fine-tuning of whisper for low-resource speech recognition. In *2024 5th International Seminar on Artificial Intelligence, Networking and Information Technology (AINIT)*, pages 1522–1525. IEEE.
- Yichen Lu, Jiaqi Song, Chao-Han Huck Yang, and Shinji Watanabe. 2024. Fastadsp: Multitask-adapted efficient inference for large speech language model. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing: Industry Track*, pages 440–451.
- Jiale Luo, Xiaoyu Liang, and Haoji Hu. 2026. Locality matters for training-free audio token compression in audio-language models. *Preprint*, arXiv:2605.25179.
- João Monteiro, Étienne Marcotte, Pierre-André Noël, Valentina Zantedeschi, David Vázquez, Nicolas Chapados, Christopher Pal, and Perouz Taslakian. 2024. Xc-cache: Cross-attending to cached context

- for efficient llm inference. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 15284–15302.
- Atila Orhon, Arda Okan, Berkin Durmus, Zach Nagen-gast, and Eduardo Pacheco. 2025. Whisperkit: On-device real-time asr with billion-scale transformers. *arXiv preprint arXiv:2507.10860*.
- Alec Radford, Jong Wook Kim, Tao Xu, Greg Brock-man, Christine McLeavey, and Ilya Sutskever. 2023. Robust speech recognition via large-scale weak supervision. In *International conference on machine learning*, pages 28492–28518. PMLR.
- Sakshi Sakshi, Utkarsh Tyagi, Sonal Kumar, Ashish Seth, Ramaneswaran Selvakumar, Oriol Nieto, Rami Duraismami, Sreyan Ghosh, and Dinesh Manocha. 2025. Mmau: A massive multi-task audio understanding and reasoning benchmark. In *International Conference on Learning Representations*, volume 2025, pages 84929–84964.
- Yaya Sy, Christophe Cerisara, and Irina Illina. 2026. Baldwhisper: Faster whisper with head shearing and layer merging. In *ICASSP 2026-2026 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 19332–19336. IEEE.
- Abdul Waheed, Karima Kadaoui, and Muhammad Abdul-Mageed. 2024. To distill or not to distill? on the robustness of robust knowledge distillation. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 12603–12621.
- Huan Wang, Jie Bin, Chunyan Gou, Lian Yang, Baolin Hou, and Mingwei Qin. 2025. Low-resource speech recognition by fine-tuning whisper with optuna-lora. *Applied Sciences*, 15(24):13090.
- Bajian Xiang, Tingwei Guo, Xuan Chen, and Yang Han. 2026. Do we need distinct representations for every speech token? unveiling and exploiting redundancy in large speech language models. *arXiv preprint arXiv:2604.06871*.
- Zifei Xu, Sayeh Sharify, Hesham Mostafa, Tristan Webb, Xin Wang, et al. 2025. Early attentive sparsification accelerates neural speech transcription. *arXiv preprint arXiv:2506.15912*.
- Piotr Żelasko, Kunal Dhawan, Daniel Galvez, Krishna C Puvvada, Ankita Pasad, Travis Bartley, Nithin Rao Koluguri, Ke Hu, Vitaly Lavrukhin, Jagadeesh Balam, et al. 2025. Training and inference efficiency of encoder-decoder speech models. In *2025 IEEE Automatic Speech Recognition and Understanding Workshop (ASRU)*, pages 1–7. IEEE.
- Heiga Zen, Viet Dang, Rob Clark, Yu Zhang, Ron J Weiss, Ye Jia, Zhifeng Chen, and Yonghui Wu. 2019. Libritts: A corpus derived from librispeech for text-to-speech. *arXiv preprint arXiv:1904.02882*.
- Sen Zhang, Jianguo Wei, Wenhuan Lu, Xianghu Yue, Wei Li, Qiang Li, Pengcheng Zhao, Ming Cai, and Luo Si. 2026a. Whisper-mla: Reducing gpu memory consumption of asr models based on mha2mla conversion. In *ICASSP 2026-2026 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 18412–18416. IEEE.
- Xin Zhang, Lin Li, Xiangni Lu, Jianquan Liu, and Kong Aik Lee. 2026b. Speaking clearly: A simplified whisper-based codec for low-bitrate speech coding. In *ICASSP 2026-2026 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 17037–17041. IEEE.
- Kun Zhou, Berrak Sisman, Rui Liu, and Haizhou Li. 2022. Emotional voice conversion: Theory, databases and esd. *Speech Communication*, 137:1–18.

Usage of Large Language Models

The manuscript was drafted by the authors. ChatGPT and Gemini-3 were used only for overall language refinement.

A About Overlap

A.1 Preliminary for encoder input k

In speech processing, Short-Time Fourier Transform (STFT) commonly employs Hann windows together with overlapping frame analysis. The overlap is introduced to alleviate abrupt discontinuities between neighboring analysis frames, which would otherwise produce spectral artifacts and instability in the frequency domain. Whisper similarly performs STFT using a 25 ms Hann window with a 10 ms hop size. Consequently, adjacent acoustic frames already contain substantial redundant information due to the overlap introduced during feature extraction.

Let the pre-convolutional STFT representations be denoted as $\{f_1, \dots, f_{3000}\}$, where each frame corresponds to a 25 ms acoustic segment sampled every 10 ms. Since adjacent STFT frames overlap by 15 ms, neighboring frames share approximately

$$\frac{25 - 10}{25} = 0.6$$

or 60% of their temporal support.

The Whisper convolutional stem consists of two convolutional layers with kernel sizes of 3, where the second layer applies stride-2 subsampling. Consequently, each post-convolutional encoder representation $\{F_1, \dots, F_{1500}\}$ aggregates

information from approximately five neighboring STFT frames. For example,

$$F_1 \rightarrow \{f_1, \dots, f_5\},$$

$$F_2 \rightarrow \{f_3, \dots, f_7\},$$

$$F_3 \rightarrow \{f_5, \dots, f_9\}.$$

Considering the 25 ms STFT window and 10 ms frame hop, each encoder token therefore spans an effective temporal receptive field of

$$R = W + (r - 1)H,$$

where W denotes the STFT window size, H the hop size, and r the number of aggregated STFT frames. Substituting Whisper’s configuration:

$$R = 25 + (5 - 1) \times 10 = 65 \text{ ms}.$$

Furthermore, since the convolutional stem outputs encoder tokens every 20 ms due to stride-2 downsampling, neighboring encoder representations are already densely overlapped along the temporal axis. Based on this observation, we hypothesize that moderate temporal subsampling can reduce computational redundancy while still preserving near-continuous acoustic coverage. Therefore, we perform deterministic stride- k token pruning before the encoder Transformer computation while explicitly analyzing how much temporal overlap or coverage loss is introduced for different values of k .

A.2 Overlap & Loss Calculation

After the convolutional stem, neighboring encoder tokens are spaced by

$$S = 20 \text{ ms}.$$

Applying stride- k subsampling retains one token every k encoder tokens, resulting in a retained-token spacing of

$$\Delta_k = kS = 20k \text{ ms}.$$

Since each encoder token spans an effective temporal receptive field of $R = 65 \text{ ms}$, the temporal overlap between neighboring retained representations can be expressed as

$$L_{\text{overlap}}(k) = \max(0, R - \Delta_k).$$

Substituting the Whisper configuration yields

$$L_{\text{overlap}}(k) = \max(0, 65 - 20k).$$

Let N_k denote the number of retained encoder tokens after stride- k subsampling:

$$N_k \approx \frac{1500}{k}.$$

Since neighboring retained encoder representations overlap repeatedly throughout the entire 30-second Whisper input, we first compute the accumulated temporal overlap as

$$A_{\text{overlap}}(k) = L_{\text{overlap}}(k) \cdot (N_k - 1).$$

However, because this accumulated quantity can exceed the original input duration when the encoder sequence is highly redundant, we report a capped global overlap ratio whose maximum value is 100%:

$$O_{\text{global}}(k) = \min\left(1, \frac{A_{\text{overlap}}(k)}{30000}\right).$$

Here, 30000 corresponds to the 30-second Whisper input duration in milliseconds. This capped ratio should be interpreted as the degree to which temporal redundancy remains over the full input sequence, normalized so that complete temporal overlap coverage is bounded by 100%.

If the retained-token spacing exceeds the receptive field size ($\Delta_k > R$), uncovered temporal regions emerge between neighboring retained representations. The temporal gap between neighboring retained representations can then be expressed as

$$L_{\text{gap}}(k) = \max(0, \Delta_k - R).$$

Substituting the Whisper configuration:

$$L_{\text{gap}}(k) = \max(0, 20k - 65).$$

Similarly, we define the accumulated temporal coverage loss as

$$A_{\text{loss}}(k) = L_{\text{gap}}(k) \cdot (N_k - 1).$$

Finally, the normalized global coverage loss ratio becomes

$$\text{Loss}(k) = \frac{A_{\text{loss}}(k)}{30000}.$$

These equations allow us to estimate how much temporal redundancy remains across the entire encoder sequence after subsampling and at which stride factors explicit temporal coverage gaps begin to emerge.

k	Retained Tokens	Overlap Ratio	Loss Ratio
1	1500	100.0%	0.0%
2	750	62.4%	0.0%
3	500	8.3%	0.0%
4	375	0.0%	18.7%
5	300	0.0%	34.9%
6	250	0.0%	45.7%
7	215	0.0%	53.5%
8	188	0.0%	59.2%

Table 4: Theoretical capped global temporal overlap and accumulated coverage loss under stride- k subsampling. The overlap ratio is capped at 100% to avoid values exceeding the original 30-second input duration.

A.3 Result for Different Values of k

Table 4 summarizes the theoretical capped global temporal overlap and accumulated coverage loss under different stride- k subsampling factors.

As shown in Table 4, the original Whisper encoder representations ($k = 1$) already provide complete temporal overlap coverage under the capped global overlap measure, reflecting the highly redundant temporal sampling induced by overlapping STFT analysis and convolutional receptive-field aggregation. Even after removing half of the encoder tokens ($k = 2$), substantial temporal redundancy still remains, with approximately 62.4% capped global temporal overlap preserved across the full 30-second encoder sequence.

In contrast, the capped global overlap rapidly decreases at $k = 3$ (8.3%), suggesting that stride-3 subsampling begins transitioning from redundancy reduction toward actual information removal. Furthermore, explicit temporal coverage loss first emerges at $k \geq 4$, where the spacing between retained encoder representations exceeds their effective receptive field.

These observations suggest that Whisper encoder representations are substantially oversampled along the temporal axis. Consequently, moderate temporal subsampling factors, particularly $k = 2$, can effectively reduce computational redundancy while still preserving dense temporal acoustic coverage across the encoder sequence.

B stride- k Subsampling Algorithm

C Details set up for Section 4

Unless otherwise specified, all experiments in this appendix (Section 4, CKA, Compound set, Speech-Prune) were conducted with a fixed random seed

Algorithm 1 Stride- k subsampling (*input-side*)

```

1:  $H \leftarrow \text{ConvStem}(X)$ 
2:  $H \leftarrow H[:,k, :]$ 
3:  $H_{\text{enc}} \leftarrow \text{Encoder}(H)$ 

```

Algorithm 2 Stride- k subsampling (*output-side*)

```

1:  $H \leftarrow \text{ConvStem}(X)$ 
2:  $H_{\text{enc}} \leftarrow \text{Encoder}(H)$ 
3:  $H_{\text{enc}} \leftarrow H_{\text{enc}}[:,k, :]$ 

```

of 42. We used Python 3.10, PyTorch 2.3.1, torchaudio 2.3.1, and NumPy 1.26.4. Experiments were run on an NVIDIA RTX 6000 Ada GPU. The same random seed was used across sampling and model evaluation procedures to ensure reproducibility.

Datasets and model checkpoints.

For the diagnosing experiment, we evaluated stride- k subsampling on three ASR datasets: LibriTTS test-clean, the English subset of ESD, and Common Voice. LibriTTS was used as a clean read-speech benchmark, ESD as an emotionally expressive speech benchmark, and Common Voice as a crowd-sourced benchmark with more diverse recording conditions. For LibriTTS, each audio file was paired with its corresponding .normalized.txt transcript. For ESD, each waveform was paired with its corresponding .lab transcript. For Common Voice, we used the test.tsv metadata file and loaded audio files from the corresponding clips directory. All models were evaluated in frozen mode without training, fine-tuning, or any auxiliary selection module.

Subsampling positions.

We evaluated stride- k subsampling at two positions in the Whisper encoder. For *input-side* subsampling, the log-mel input was first passed through the Whisper convolutional stem, consisting of conv1 + GELU and conv2 + GELU. The resulting hidden sequence was then subsampled as $H' = H[:,k, :]$ before adding positional embeddings and passing it through the encoder transformer. Thus, the encoder transformer processed a shorter sequence of length approximately $1500/k$. For output-side subsampling, the full 1500-token sequence was first processed by the encoder transformer, and the final encoder hidden states were subsampled as $H' = H[:,k, :]$ before being passed to the decoder cross-attention. Therefore, input-

side subsampling reduces the sequence length processed by both the encoder transformer and decoder cross-attention, whereas output-side subsampling leaves encoder computation unchanged and reduces only the encoder-output sequence consumed by the decoder.

Inference and decoding.

For each audio sample, we constructed Whisper input features using the corresponding HuggingFace AutoProcessor. Audio was loaded with torchaudio, and resampled to the Whisper feature extractor sampling rate. Hypotheses and references were normalized before metric computation by lowercasing and removing non-alphanumeric punctuation for English.

WER and runtime measurement.

ASR performance was measured using Word Error Rate (WER) with jiwer. Runtime was separated into encoder time and decoder time. CUDA synchronization was applied before and after timed regions to obtain stable latency measurements.

FLOPs estimation.

We estimate the reported total FLOPs as the sum of encoder FLOPs and decoder cross-attention FLOPs:

$$\text{FLOPs}_{\text{total}} = \text{FLOPs}_{\text{enc}} + \text{FLOPs}_{\text{cross}}.$$

Let T be the sequence length processed by the encoder transformer, T_{enc} the encoder-output length passed to decoder cross-attention, T_{dec} the generated decoder length, d the hidden size, and L_{enc} and L_{dec} the number of encoder and decoder layers. Encoder FLOPs are estimated as

$$\text{FLOPs}_{\text{enc}} = 2L_{\text{enc}} (12Td^2 + 2T^2d).$$

Decoder cross-attention FLOPs are estimated as

$$\text{FLOPs}_{\text{cross}} = 2L_{\text{dec}} ((2T_{\text{enc}} + 2T_{\text{dec}})d^2 + 2T_{\text{dec}}T_{\text{enc}}d)$$

For the baseline, $T = T_{\text{enc}} = 1500$. For input-side subsampling with stride k , $T = T_{\text{enc}} = \lceil 1500/k \rceil$. For output-side subsampling, $T = 1500$ while $T_{\text{enc}} = \lceil 1500/k \rceil$. We use the actual generated sequence length as T_{dec} .

D Details Result for Section 4

Refer to Table 13 and 14.

E Details set up for CKA

Adjacent-token CKA setup.

For the adjacent-token CKA analysis, we measured representational similarity at two positions in the Whisper encoder: the conv stem output and the final encoder output. The conv stem output was extracted after conv1 + GELU and conv2 + GELU, before positional embedding and transformer layers, while the final encoder output was extracted after the full encoder transformer. We used LibriTTS test-clean and the HuggingFace Whisper checkpoints openai/whisper-{tiny,base,small,medium,large-v3}. From LibriTTS test-clean, we randomly selected 10 random anchor positions per utterance from the Whisper encoder time axis. Since Whisper produces 1,500 encoder frames, anchor positions were sampled only from valid indices satisfying $t + D_{\text{max}} < 1500$. We used the same randomly sampled anchor positions for all Whisper checkpoints and for both measurement positions, ensuring that the conv stem and encoder output results are directly comparable.

CKA computation.

For each position and each distance d , we collected anchor representations H_t and offset representations H_{t+d} and stacked them into two matrices, X and Y_d . We then computed linear centered kernel alignment (CKA) as

$$\text{CKA}(X, Y_d) = \frac{\|\tilde{X}^\top \tilde{Y}_d\|_F^2}{\|\tilde{X}^\top \tilde{X}\|_F \|\tilde{Y}_d^\top \tilde{Y}_d\|_F},$$

where $\tilde{X}$ and $\tilde{Y}_d$ denote sample-centered representations. CKA was computed independently for each Whisper checkpoint, each measurement position, and each token distance. In the final encoder output experiment, we evaluated distances $d \in \{1, 2, 3, 4, 5\}$; in the conv stem experiment, we used the same manifest-based sampling procedure and evaluated distance-wise CKA before the transformer layers. All models were evaluated in frozen mode with gradient computation disabled, using bfloat16 on CUDA when available and float32 otherwise.

F Details Result for CKA

Table 16 reports the full linear CKA values and cumulative drops for the conv stem and encoder outputs across all five Whisper scales at frame distances $d = 1-5$, measured on LibriTTS.

G Details set up for Compound set

SpeechLM benchmarks and models.

For the SpeechLM compound stride-2 experiment, we evaluated three Whisper-based SpeechLMs: Audio Flamingo 3-7b, Qwen2-Audio-7b-instruct, and LLaMA-Omni2-7b. The experiments were conducted on MMSU and MMAU. For MMSU, we used the HuggingFace dataset `ddwang2000/MMSU` with the default split used in the evaluation scripts. For MMAU, we used `AudioLLMs/MMAU`. Each model was evaluated in frozen mode without any training, fine-tuning, or calibration after subsampling. The maximum number of generated tokens was set to 64 and used greedy decoding with `do_sample=False`. The reported score is task accuracy, computed by comparing the parsed model answer with the ground-truth option.

Compound stride-2 configuration.

For each model and benchmark, we compared the unmodified baseline against compound stride-2. The baseline processes the full 1,500-token speech encoder sequence. In the compound setting, stride-2 subsampling is applied at two positions: first immediately after the convolutional stem and before the speech encoder transformer, and second immediately after the speech encoder transformer and before the projector or pooling module. This corresponds to $k_{\text{enc_in}} = 2$ and $k_{\text{enc_out}} = 2$. For a 30-second padded audio input, the first subsampling reduces the transformer input from 1,500 to 750 tokens, and the second subsampling reduces the encoder output from 750 to 375 tokens before downstream pooling or projection.

Model-specific audio-token pipelines.

The three SpeechLMs share the same high-level subsampling strategy but differ in how encoder outputs are converted into LLM input tokens. In Audio Flamingo 3 and Qwen2-Audio, the audio pipeline maps the padded mel input to 1,500 conv-stem tokens, processes them with a 32-layer speech encoder transformer, and then applies `AvgPool1d(2, stride=2)` followed by a projection or normalization module. Thus, the baseline produces 750 audio tokens for the LLM, while compound stride-2 produces 187 tokens after the both subsampling and average pooling, depending on the exact integer rounding. In LLaMA-Omni2, the speech encoder follows the Whisper large-v3-style encoder, but the projector

does not use average pooling. Instead, it uses an `EncoderProjectorConcat` module with a frame-concatenation factor of 5. Therefore, the baseline maps 1,500 speech encoder tokens to 300 LLM-side audio tokens, while compound stride-2 maps 375 tokens to 75 LLM-side audio tokens.

Latency and FLOPs measurement.

For each sample, we measured speech-encoder time and generation time separately, and reported end-to-end latency as their sum. FLOPs were computed analytically from the actual model architecture read from each loaded checkpoint. The speech-side FLOPs include the convolutional stem, the speech encoder transformer, and the audio projector. The convolutional stem always processes the full padded mel input and is therefore unchanged by subsampling. The transformer FLOPs scale with the sequence length after input-side subsampling, and the projector FLOPs scale with the number of tokens after output-side subsampling and pooling or projection. The implementation also estimates LLM prefill and decode FLOPs from the LLM hidden size, number of layers, number of attention heads, number of key-value heads, and intermediate dimension. Total GFLOPs are computed as the sum of speech encoder/projector FLOPs and LLM prefill/decode FLOPs.

Detailed Results.

Table 15 reports the full compound stride-2 results ($k_{\text{enc_in}} = k_{\text{enc_out}} = 2$) for all datasets and Whisper scales, with per-cell deltas from the $k = 1$ baseline.

H ASR Noise Robustness

Setup. Section 6 infers the effect of input difficulty by comparing corpora, so difficulty is confounded with domain, speaker population, and recording condition. To isolate difficulty itself, we hold the corpus fixed and degrade it in a controlled way: we add white Gaussian noise to clean LibriTTS test-clean at matched SNR levels. For an utterance with signal power p_s , the noise is drawn from $\mathcal{N}(0, p_n)$ with

$$p_n = p_s / 10^{\text{SNR}/10},$$

evaluated at $\text{SNR} \in \{\infty, 20, 10, 5, 0\}$ dB, where ∞ denotes the unmodified clean condition. We use 200 utterances sampled with a fixed seed, and

the same utterances and the same noise realizations are used for every model scale and every stride condition, so differences across cells reflect the operator rather than sampling. Each SNR level is evaluated under four conditions: the unmodified baseline ($k=1$), input-side $k=2$, output-side $k=2$, and compound stride-2. Every condition is compared against the baseline *at the same SNR*, so the reported gap measures the cost of subsampling and not the cost of noise.

Results. Table 5 reports WER for Whisper-Small and Whisper-Large-v3. Three observations follow.

First, input-side and compound stride-2 degrade monotonically as SNR falls, and more steeply for the smaller model. Compound stride-2 costs +3.7 WER on clean speech and +57.5 at 0dB for Small, against +0.9 and +28.6 for Large-v3. The capacity ordering of Section 6 therefore reproduces along an axis where input difficulty is manipulated directly, which supports the interpretation that the ordering reflects a robustness margin rather than a property of any particular corpus.

Second, output-side stride-2 stays within about one point of baseline at every SNR on both scales, and is occasionally slightly better than baseline (−0.11 on clean Small, −0.09 at 10 dB). The input/output asymmetry established in Section 4 is thus not an artifact of clean read speech: the redundancy exposed at the encoder output survives acoustic degradation, whereas the receptive-field overlap exploited at the input side does not.

Third, the baseline itself degrades substantially under noise, from 4.72 to 27.73 on Small and from 4.21 to 15.34 on Large-v3. The widening gap is therefore not a fixed additive cost that noise adds to subsampling, but the consequence of a shrinking redundancy margin: as the signal carries less recoverable information, the fraction of it that stride- k can discard without loss falls.

Error analysis. Inspecting utterances that the baseline transcribes correctly but compound stride-2 does not, the dominant added errors are omissions and substitutions of function words, chiefly articles and plural suffixes, rather than substitutions of content words. Two properties plausibly explain this. These units are phonetically short and low in energy, so they are more likely to fall between retained tokens once the temporal sampling rate is halved; and they are recoverable mainly from sentence-level context, so even

partial acoustic loss is disproportionately damaging when the decoder cannot fall back on a strong acoustic cue. Under noise these units are already degraded, and stride-2 compounds the loss. Consistently with this account, the same linguistic categories degrade less in the SpeechLM setting, where a downstream language model can restore such words from context, which mirrors the observation in Appendix L that stride-2 is most damaging where the answer depends on evidence the model cannot reconstruct.

I Multilingual Evaluation

The evaluation in the main text focuses on English. To examine whether the behavior of stride- k is language-specific, we repeat the evaluation on the Chinese (zh-CN) portion of Common Voice with the same three Whisper scales used in Section 6, applying stride- k at the same two positions and using the same test-split protocol. Since Chinese is not word-segmented, word-level tokenization is not meaningful; following common practice for Chinese ASR evaluation, we report Character Error Rate (CER). All numbers in Table 6 are CER (%), and each stride condition is compared against the baseline of the same scale.

The trends reported in the main text hold across languages. Output-side $k=2$ remains stable in Chinese, staying within one point of baseline at every scale and on Large-v3 even improving slightly (−0.20), whereas input-side $k=2$ incurs substantially larger CER increases (+6.01, +6.73, and +3.78) and compound stride-2 the largest. This is the same input/output asymmetry observed in Figure 1 and discussed in Section 4, and its reappearance under a different language and a different error metric indicates that the asymmetry follows from where the redundancy is created in Whisper’s encoder rather than from properties of English.

The stability of the output side also strengthens with scale, with the gap falling from +0.67 on Small to +0.45 on Medium and −0.20 on Large-v3. The input side is less regular: Large-v3 absorbs input-side $k=2$ best (+3.78), but the compound gap stays roughly flat across scales (+8.30 to +9.04) rather than shrinking as it does on the English benchmarks, so the capacity trend of Section 6 is weaker here. Absolute CER is also higher than the English WERs in Table 2, reflecting the difficulty of the zh-CN portion of Common Voice

SNR	Whisper-Small				Whisper-Large-v3			
	Base.	In 2	Out 2	Both 2	Base.	In 2	Out 2	Both 2
clean	4.72	7.44 (+2.72)	4.61 (−0.11)	8.38 (+3.66)	4.21	4.75 (+0.54)	4.23 (+0.03)	5.12 (+0.92)
20 dB	4.84	16.80 (+11.96)	4.89 (+0.06)	17.37 (+12.53)	4.38	5.64 (+1.26)	4.46 (+0.09)	6.81 (+2.43)
10 dB	7.87	19.89 (+12.02)	7.78 (−0.09)	28.21 (+20.34)	5.04	10.16 (+5.12)	5.26 (+0.23)	11.87 (+6.84)
5 dB	12.65	48.30 (+35.65)	12.99 (+0.34)	44.26 (+31.62)	7.32	18.51 (+11.19)	8.04 (+0.72)	20.49 (+13.16)
0 dB	27.73	88.38 (+60.66)	28.61 (+0.89)	85.24 (+57.51)	15.34	39.91 (+24.58)	16.19 (+0.86)	43.98 (+28.64)

Table 5: WER (%) under additive white Gaussian noise on LibriTTS test-clean ($n = 200$ utterances per level, identical across scales and conditions). Each cell reports WER with its gap from the baseline *at the same SNR* in parentheses. Output-side stride-2 stays within about one point of baseline at every level, while input-side and compound stride-2 degrade as conditions worsen, more steeply for the smaller model.

Scale	Base.	In 2	Out 2	Both 2
Small	34.92	40.93 (+6.01)	35.59 (+0.67)	43.22 (+8.30)
Medium	27.22	33.95 (+6.73)	27.67 (+0.45)	36.35 (+9.13)
Large-v3	16.68	20.46 (+3.78)	16.48 (−0.20)	25.71 (+9.04)

Table 6: Chinese (Common Voice zh-CN) CER (%) under stride-2, with the change from each scale’s own baseline in parentheses. In 2 and Out 2 denote input-side and output-side stride-2, Both 2 the compound setting. Output-side stride-2 stays within one point of baseline at every scale and slightly improves on Large-v3.

rather than an effect of subsampling. Broader multilingual evaluation, including Japanese and other Common Voice languages, and an analysis of how the degradation relates to a language’s resource level and character-level information density, remain future work.

J Generalization Beyond Whisper

Section 6 and the Limitations discuss stride- k as an operation on Whisper. This appendix makes the boundary of that claim precise. We do not claim that stride- k generalizes to all speech encoders: the method was motivated by, and is introduced as exploiting, the specific preprocessing redundancy of Whisper’s log-mel frontend and convolutional stem. What we establish here is narrower and more useful, namely that the operative condition is not the Whisper architecture itself but whether the preprocessing pipeline produces sufficient temporal overlap between adjacent tokens, so that encoders sharing this property inherit the operation while encoders lacking it do not. We state the condition (Appendix J.1), test it on encoders that violate it (Appendix J.2) and on one that satisfies it (Appendix J.3), and connect the outcome to the simi-

larity analysis of Section 5 (Appendix J.4).

Following Appendix A, a post-frontend token spans a receptive field R and is emitted every S ms, so retaining every k -th token leaves an overlap $L_{\text{overlap}}(k) = \max(0, R - kS)$ and a coverage gap $L_{\text{gap}}(k) = \max(0, kS - R)$. Stride- k removes redundancy rather than signal exactly when $L_{\text{gap}}(k) = 0$, which for $k = 2$ requires $R \geq 2S$. This is a property of the frontend alone: it is fixed by the analysis window, the hop, and the strides of the convolutional stem, and it can therefore be computed for any encoder without running it.

J.1 Receptive fields of three frontends

We apply the construction $R = W + (r - 1)H$ of Appendix A, where W is the analysis window, H the hop, and r the number of frames a post-stem token aggregates.

- **Whisper.** Log-mel with $W = 25$ ms and $H = 10$ ms; conv1 ($k=3, s=1$) followed by conv2 ($k=3, s=2$) aggregates $r = 5$ mel frames, giving $R = 25 + 4 \times 10 = 65$ ms at $S = 20$ ms. The overlap originates before the stem: adjacent mel frames already share $(25 - 10)/25 = 60\%$ of their temporal support, and the stem compounds this by aggregating five such frames into every token.
- **Phi-4-multimodal conformer.** Log-mel with $W = 400$ samples (25 ms) and $H = 160$ samples (10 ms); the NemoConvSubsampling stem (dw_striding, time reduction 8, i.e. three depthwise-separable Conv2d layers of kernel 3 and stride 2) spans $r = 15$ mel frames, giving $R = 400 + 14 \times 160 = 2640$ samples = 165 ms at $S = 8 \times 160 = 1280$ samples = 80 ms. The pipeline is Whisper-like, mel extraction followed by a convolutional stem, so adjacent post-stem tokens overlap by construction, but the margin is thinner in relative terms.

Frontend	R	S	Overlap	L_{ovl}	L_{gap}
Whisper (mel + conv stem)	65	20	45 (69%)	25	0
Phi-4-MM (mel + conv sub.)	165	80	85 (52%)	5	0
Raw-waveform conv	25	20	5 (20%)	0	15

Table 7: Token receptive field R , spacing S , and adjacent overlap $R - S$ before the encoder transformer, with the residual overlap L_{ovl} and coverage gap L_{gap} under stride-2 (all in ms). Raw-waveform conv covers wav2vec 2.0, HuBERT, WavLM, and wav2vec2-conformer, which share one convolutional feature extractor.

- **Raw-waveform encoders.** wav2vec 2.0, HuBERT, WavLM, and wav2vec2-conformer share a seven-layer convolutional feature extractor (kernels $[10, 3, 3, 3, 3, 2, 2]$, strides $[5, 2, 2, 2, 2, 2, 2]$) applied directly to the waveform, skipping the mel transformation entirely. This gives $R = 400$ samples = 25 ms at $S = 320$ samples = 20 ms, verified empirically in that a 16,000-sample input yields 49 frames. The receptive field is barely wider than the spacing, so stride-2 places retained tokens 40 ms apart while each covers only 25 ms, leaving a 15 ms gap in every 40 ms of timeline, or roughly 37% of the signal outside any retained token’s receptive field.

Table 7 summarizes the resulting stride-2 behavior. The two mel-plus-convolution frontends retain positive overlap and open no gap, and their ordering is itself informative: the Phi-4-multimodal conformer inherits the property but with a thinner margin ($L_{\text{overlap}} = 5$ ms against Whisper’s 25 ms), which predicts that it should tolerate stride-2 while degrading more than Whisper does. Raw-waveform frontends open a gap immediately, so for them stride-2 is not redundancy removal but signal removal.

J.2 Stride- k on raw-waveform encoders

We apply input-side, output-side, and compound stride to four raw-waveform encoders decoded with CTC on LibriTTS test-clean, using the same corpus, normalization, and WER computation as Section 4. Table 8 reports the result: every model degrades sharply at $k = 2$ at either position, and compound stride-2 destroys recognition entirely. There is no regime analogous to Whisper’s, where $k = 2$ is absorbed at both positions; the collapse is immediate, as the coverage analysis predicts.

Model	Base.	In 2	In 3	Out 2	Both 2
wav2vec 2.0	3.06	17.21	73.58	89.53	97.77
HuBERT	3.68	24.55	76.32	81.05	97.50
WavLM	7.60	48.67	92.00	81.03	97.79

Table 8: WER (%) under stride- k for raw-waveform encoders with CTC decoding on LibriTTS test-clean ($n = 4837$). In k and Out k denote input-side and output-side stride, Both 2 the compound setting.

Model	Perception Δ	Reasoning Δ
Audio Flamingo 3	−1.00	−2.81
Qwen2-Audio	−1.62	−6.16
LLaMA-Omni 2	−3.06	−9.71
Phi-4-MM (mel conformer)	−4.61	−11.45

Table 9: MMSU accuracy change under compound stride-2. The first three rows are the Whisper-based SpeechLMs of Table 2; the last is the mel-input conformer of Phi-4-multimodal, which degrades more than any Whisper-based model but does not collapse.

J.3 Stride-2 on a mel-input conformer

Phi-4-multimodal pairs conformer encoder blocks with the mel-plus-convolution frontend of Appendix J.1, so the condition predicts that it should tolerate compound stride-2. We evaluate it on MMSU ($n = 5000$) and MMAU ($n = 1000$) under the protocol of Appendix G. It degrades rather than collapsing: MMAU accuracy moves from 62.20 to 56.50 (−5.70), MMSU Perception from 37.13 to 32.52 (−4.61), and MMSU Reasoning from 70.41 to 58.97 (−11.45), while the audio-token count falls from 170.9 to 43.3 on MMAU.

Table 9 places these deltas beside the three Whisper-based SpeechLMs of Table 2. Two things follow. First, the qualitative behavior matches the prediction: an encoder that satisfies the coverage condition remains usable under a 75% token reduction, in sharp contrast to the raw-waveform encoders of Table 8. Second, the drop is larger than for any Whisper-based model, which is consistent with the thinner overlap margin computed in Table 7 (52% against Whisper’s 69%). The condition therefore predicts not only whether stride-2 transfers but, in the right direction, how much it costs.

J.4 Adjacent-token similarity for raw-waveform encoders

The receptive-field argument is geometric and holds before any weights are consulted. Section 5 showed that the same redundancy is visible rep-

representationally, as high similarity between adjacent tokens. If the frontend account is correct, raw-waveform encoders should show that signature much more weakly. We therefore repeat the measurement of Section 5 on the self-supervised encoders. As noted there and in Appendix E, absolute CKA is not comparable *across* positions, so we compare the same position type across encoders rather than the two positions against each other.

Table 10 reports the result. At the convolutional output, where the geometric overlap resides, Whisper reaches 0.964 at $d = 1$ while the self-supervised encoders reach only 0.582–0.755, and their similarity falls off far faster with distance (0.207–0.287 at $d = 3$ against Whisper’s 0.851). The representational deficit tracks the receptive-field deficit, and predicts the collapse in Table 8 from an independent measurement: the tokens stride- k retains are poor substitutes for the ones it drops.

Taken together, these results locate the operative condition. It is not the Whisper architecture, nor the encoder block family, but whether the preprocessing pipeline produces sufficient temporal overlap between adjacent tokens. Overlapping windowed analysis is standard practice in signal processing, adopted precisely to avoid spectral discontinuities between neighboring frames (Appendix A), so the property stride- k exploits is not idiosyncratic to Whisper. Any encoder that follows this convention with mel extraction and a convolutional stem is a candidate for stride- k subsampling, and Table 7 shows that its viability can be assessed from the frontend configuration alone, before any evaluation is run.

K Details Result for SpeechPrune

Tables 17–22 report the category-level accuracy, FLOPs, and latency for SpeechPrune (SP), input-side stride-2 (Enc), and the combined setting (Enc+SP) on MMSU and MMAU across the three SpeechLMs.

SpeechPrune and combined setting.

We evaluate SpeechPrune as a training-free post-projector speech-token pruning. In the SpeechPrune-only setting, the full audio encoder is executed without subsampling, producing approximately 750 post-projector speech tokens for a 30-second padded input. SpeechPrune is then applied in two phases. First, projected

Model	Position	$d=1$	$d=2$	$d=3$
Whisper-Tiny	Conv	0.964	0.904	0.851
	Enc Out	0.881	0.776	0.738
wav2vec 2.0	Conv	0.582	0.338	0.207
	Enc Out	0.038	0.043	0.021
HuBERT	Conv	0.755	0.481	0.287
	Enc Out	0.702	0.482	0.329
WavLM	Conv	0.743	0.469	0.280
	Enc Out	0.304	0.104	0.071

Table 10: Linear CKA between tokens at frame distance d , measured at the convolutional output and the encoder output on LibriTTS. Whisper-Tiny is shown for reference. At the convolutional position the self-supervised encoders show much weaker adjacent similarity than Whisper, mirroring the receptive-field deficit in Table 7.

speech tokens are scored by cosine similarity to the question text embeddings, and a frame-wise softmax allocation selects the most relevant tokens within each one-second segment. Second, the remaining tokens are scored using binarized attention computed from the sign-binarized query and key weights of the first LLM layer, and the top-scoring tokens are retained. We evaluate pruning rates of 20%, 40%, 60%, and 80%.

Ours + SpeechPrune.

For the combined setting, we first apply our input-side stride-2 subsampling before the speech encoder transformer. This reduces the encoder-transformer input from 1,500 to 750 tokens and yields approximately 375 post-projector speech tokens after average pooling and projection. SpeechPrune is then applied to this already-reduced speech-token sequence with the same two-phase procedure. Thus, SpeechPrune-only reduces the number of audio tokens passed to the LLM after the full speech encoder has been computed, whereas the combined method reduces the speech encoder computation first and then further prunes the resulting LLM-side speech tokens. This distinction is used when reporting FLOPs and latency: SpeechPrune-only mainly reduces downstream LLM computation, while the combined setting reduces both speech-encoder computation and downstream LLM input length.

L Failure-Case Analysis of Compound Stride-2

This section expands the per-sample failure analysis summarized in Section 6. The aggregate results in Table 2 report how much accuracy changes un-

der compound stride-2; here we instead ask which questions change, and whether the newly induced errors are distributed uniformly across task types or concentrated on particular ones.

L.1 Setup

For each of the three SpeechLMs (Audio Flamingo 3, Qwen2-Audio, LLaMA-Omni 2), we run inference on the full MMSU and MMAU question sets under two settings: the unmodified baseline ($k=1$) and compound stride-2 ($k_{\text{enc_in}} = k_{\text{enc_out}} = 2$). A failure case is a question that the baseline answers correctly but compound stride-2 answers incorrectly. These cases are exactly the errors introduced by subsampling, excluding questions that were already wrong at the baseline.

For a task category c , we define the failure rate as

$$\text{FR}(c) = \frac{\#\{i \in c : y_i^{\text{base}} = y_i, y_i^{\text{stride}} \neq y_i\}}{\#\{i \in c : y_i^{\text{base}} = y_i\}}.$$

Here, y_i is the ground-truth answer, and y_i^{base} and y_i^{stride} denote the predictions under the baseline and compound stride-2 settings, respectively. Thus, $\text{FR}(c)$ is the fraction of questions a model originally got right in category c that are lost under stride-2. The denominator is the model’s own baseline-correct count, so the failure rate is comparable across categories of different size and across models of different baseline accuracy.

Task categories are obtained by grouping questions from their prompt text, following the task taxonomies of MMSU and MMAU. Categories whose failure rates are small and whose question counts are low are merged into an Others row to keep the tables compact; the prosodic category Stress/Emphasis is kept separate despite a moderate rate because it is directly relevant to the temporal-resolution discussion. N denotes the number of baseline-correct questions summed over the three models, i.e., the pooled denominator.

L.2 Results

Tables 11 and 12 report per-category failure rates for MMSU and MMAU. Three observations follow.

The overall failure rate follows the baseline ordering. On MMSU the overall failure rate is 9.4% for AF3, 14.8% for Qwen2-Audio, and 24.5% for LLaMA-Omni 2; on MMAU it is

6.8%, 12.6%, and 20.6% respectively. Both benchmarks independently reproduce the ordering $\text{AF3} < \text{Qwen2-Audio} < \text{LLaMA-Omni 2}$, matching the accuracy trend in Table 2 and supporting the interpretation that stronger baselines retain a larger margin to absorb the fixed fraction of redundancy removed by subsampling.

Temporally fine-grained categories are vulnerable for every baseline. On MMSU, Intonation (20.4% averaged over the three models) and Pause (20.3%) are the two highest non-Others categories, and each exceeds its model’s overall failure rate for all three models. On MMAU, Counting (20.7%) shows the same property, with a strikingly flat profile across baselines (21.4% / 22.0% / 18.8%). These categories share a dependence on temporal structure, the shape of an intonation contour, the position of a pause, the number of events in time, which is precisely what stride-2 compresses by halving the encoder’s temporal sampling rate. Their consistency across baselines indicates a property of the operator rather than of any single model.

Other categories track baseline strength, not task type. Categories such as Pitch/Volume and Transcription on MMSU, or Emotion and SoundRecognition on MMAU, show a steep spread across baselines (e.g. MMSU Pitch/Volume: 1.6% for AF3 vs. 38.0% for LLaMA-Omni 2). Their failure rate is governed by baseline strength rather than by an intrinsic vulnerability of the category, and we therefore do not interpret them as evidence about which acoustic cues stride-2 removes. Only the temporally fine-grained categories above exhibit a baseline-independent pattern.

L.3 Discussion

The failure-case analysis refines the aggregate results of Table 2 in two ways. The overall failure rate, reproduced independently on MMSU and MMAU, confirms that the accuracy drops in Table 2 are not driven by a few outlier questions but reflect a baseline-dependent error rate spread across the benchmark. More specifically, the per-category view isolates a baseline-independent effect. Tasks defined by temporal structure, intonation, pause, and counting, are eroded first under stride-2, regardless of which SpeechLM is used. This is the expected signature of an operator that reduces the encoder’s temporal sampling rate, and

Category	Failure rate (%)			Avg	N
	AF3	Qwen2-A.	L-Omni2		
Intonation	23.9	16.7	20.0	20.4	181
Pause	15.6	25.4	19.4	20.3	316
Syllable	16.1	12.5	32.3	19.6	102
Poetic	19.6	28.6	10.0	19.2	104
StopRelease	7.9	11.3	31.0	18.1	149
Transcription	5.9	13.6	32.9	16.3	608
Pitch/Volume	1.6	8.0	38.0	16.2	346
SpeakerTraits	11.7	18.6	19.6	16.2	2585
Semantics-Reason.	5.8	12.6	33.7	15.8	1777
Stress/Emphasis	11.9	11.9	15.2	12.9	302
Others	8.1	10.6	17.2	11.4	1435
Overall	9.4	14.8	24.5	–	8205

Table 11: Per-category failure rate on MMSU: the fraction of baseline-correct ($k = 1$) questions that become incorrect under compound stride-2. Rows are sorted by the three-model average; N is the pooled number of baseline-correct questions. Intonation and Pause are the highest non-*Others* categories and exceed each model’s overall failure rate.

Category	Failure rate (%)			Avg	N
	AF3	Qwen2-A.	L-Omni2		
SpeakerRelation	0.0	0.0	78.6	25.0	44
Emotion	4.8	32.0	38.5	23.7	59
SoundRecognition	5.7	28.2	34.9	21.5	135
Counting	21.4	22.0	18.8	20.7	145
Stress/Phoneme	10.9	25.6	31.6	20.4	108
Others	5.3	8.0	15.9	9.2	1291
Overall	6.8	12.6	20.6	–	1782

Table 12: Per-category failure rate on MMAU, defined as in Table 11. Counting is the only category with a baseline-flat profile (21.4%/22.0%/18.8%) and exceeds every model’s overall failure rate; the remaining categories spread widely across baselines.

it indicates that the residual cost of compound stride-2 is not uniform but falls disproportionately on temporally fine-grained perception.

M Details Result for Distil-Whisper

Table 23 reports the ASR performance and total FLOPs of Distil-Whisper large-v3 under stride- k subsampling. We compare the unmodified Distil-Whisper baseline, Distil-Whisper with input-side stride-2, and Distil-Whisper with compound stride-2. Applying compound stride-2 reduces total FLOPs by roughly a further 54% relative to the Distil-Whisper baseline, with WER staying close to baseline on LibriTTS and ESD and increasing more on the harder Common Voice.

Dataset	Model	Metric	$k = 1$	$k = 2$	$k = 3$	$k = 4$	$k = 5$	$k = 6$
LibriTTS	Tiny	WER (%)	8.86	21.23	171.1	253.8	202.8	190.3
		GFLOPs	39 G (100%)	16 G (41%)	10 G (26%)	7.3 G (19%)	5.7 G (15%)	4.7 G (12%)
	Base	WER (%)	6.87	12.47	73.12	190.3	183.1	154.0
		GFLOPs	94 G (100%)	40 G (43%)	25 G (27%)	19 G (20%)	15 G (16%)	12 G (13%)
	Small	WER (%)	5.02	8.04	40.04	112.3	131.2	124.2
		GFLOPs	382 G (100%)	171 G (45%)	109 G (29%)	81 G (21%)	64 G (17%)	53 G (14%)
	Medium	WER (%)	4.61	6.22	19.51	73.16	107.7	109.4
		GFLOPs	1.3k G (100%)	588 G (46%)	381 G (30%)	281 G (22%)	223 G (17%)	184 G (14%)
	Large	WER (%)	4.31	4.63	16.20	72.34	105.4	109.3
		GFLOPs	2.6k G (100%)	1.2k G (47%)	783 G (30%)	579 G (22%)	460 G (18%)	381 G (15%)
ESD	Tiny	WER (%)	14.16	35.87	163.8	228.8	189.1	200.8
		GFLOPs	39 G (100%)	16 G (41%)	9.9 G (26%)	7.2 G (19%)	5.6 G (14%)	4.6 G (12%)
	Base	WER (%)	11.53	18.98	61.30	120.5	142.1	150.4
		GFLOPs	94 G (100%)	40 G (43%)	25 G (27%)	18 G (20%)	14 G (15%)	12 G (13%)
	Small	WER (%)	9.39	13.20	38.48	82.77	102.5	108.9
		GFLOPs	381 G (100%)	170 G (45%)	109 G (29%)	80 G (21%)	63 G (17%)	52 G (14%)
	Medium	WER (%)	8.65	11.22	26.50	66.67	91.46	97.93
		GFLOPs	1.3k G (100%)	586 G (46%)	379 G (30%)	279 G (22%)	221 G (17%)	183 G (14%)
	Large	WER (%)	9.63	10.16	22.00	63.18	96.61	140.9
		GFLOPs	2.6k G (100%)	1.2k G (46%)	778 G (30%)	577 G (22%)	458 G (18%)	380 G (15%)
Common Voice	Tiny	WER (%)	35.85	88.69	234.7	260.1	224.0	191.7
		GFLOPs	39 G (100%)	16 G (41%)	9.9 G (26%)	7.2 G (19%)	5.6 G (14%)	4.6 G (12%)
	Base	WER (%)	28.17	44.43	101.0	127.7	147.5	148.3
		GFLOPs	94 G (100%)	40 G (43%)	25 G (27%)	18 G (20%)	14 G (15%)	12 G (13%)
	Small	WER (%)	17.93	29.10	66.06	104.5	111.1	115.4
		GFLOPs	381 G (100%)	170 G (45%)	109 G (29%)	80 G (21%)	63 G (17%)	52 G (14%)
	Medium	WER (%)	14.26	20.84	48.53	85.07	97.73	99.49
		GFLOPs	1.3k G (100%)	586 G (46%)	379 G (30%)	279 G (22%)	221 G (17%)	183 G (14%)
	Large	WER (%)	11.66	17.56	44.91	83.98	102.7	115.3
		GFLOPs	2.6k G (100%)	1.2k G (46%)	778 G (30%)	576 G (22%)	457 G (18%)	379 G (15%)

Table 13: Input-side stride- k subsampling: WER (%), total GFLOPs with remaining ratio (% of $k = 1$), and total inference latency (ms) for all datasets, model scales, and stride values ($k = 1$ –6). $k = 1$ (**bold**) is the unmodified baseline.

Dataset	Model	Metric	$k = 1$	$k = 2$	$k = 3$	$k = 4$	$k = 5$	$k = 6$
LibriTTS	Tiny	WER (%)	8.86	9.42	11.50	16.57	37.70	70.26
		GFLOPs	39 G (100%)	37 G (95%)	36 G (94%)	36 G (93%)	36 G (92%)	36 G (92%)
	Base	WER (%)	6.87	6.76	7.11	8.22	15.15	47.60
		GFLOPs	94 G (100%)	89 G (95%)	88 G (93%)	87 G (92%)	86 G (92%)	86 G (91%)
	Small	WER (%)	5.02	5.13	5.54	6.35	10.05	20.82
		GFLOPs	382 G (100%)	360 G (94%)	353 G (92%)	350 G (91%)	347 G (91%)	346 G (90%)
	Medium	WER (%)	4.61	4.70	4.94	5.54	6.81	11.04
		GFLOPs	1.3k G (100%)	1.2k G (94%)	1.2k G (92%)	1.2k G (91%)	1.2k G (90%)	1.2k G (90%)
	Large	WER (%)	4.31	4.30	4.69	5.47	10.66	29.56
		GFLOPs	2.6k G (100%)	2.4k G (94%)	2.4k G (92%)	2.3k G (91%)	2.3k G (90%)	2.3k G (90%)
ESD	Tiny	WER (%)	14.16	14.66	15.72	17.71	25.94	43.51
		GFLOPs	39 G (100%)	37 G (95%)	36 G (94%)	36 G (93%)	36 G (92%)	36 G (92%)
	Base	WER (%)	11.53	11.78	11.83	12.61	16.12	25.83
		GFLOPs	94 G (100%)	89 G (95%)	88 G (93%)	87 G (92%)	86 G (92%)	86 G (91%)
	Small	WER (%)	9.39	9.53	9.75	10.45	11.59	16.75
		GFLOPs	381 G (100%)	360 G (94%)	352 G (92%)	349 G (92%)	347 G (91%)	345 G (91%)
	Medium	WER (%)	8.65	8.81	9.05	9.77	10.58	13.00
		GFLOPs	1.3k G (100%)	1.2k G (94%)	1.2k G (92%)	1.2k G (91%)	1.2k G (90%)	1.2k G (90%)
	Large	WER (%)	9.63	9.58	10.11	9.85	11.33	24.26
		GFLOPs	2.6k G (100%)	2.4k G (94%)	2.4k G (92%)	2.3k G (91%)	2.3k G (90%)	2.3k G (90%)
Common Voice	Tiny	WER (%)	35.85	39.82	44.51	48.95	81.38	110.0
		GFLOPs	39 G (100%)	37 G (95%)	36 G (94%)	36 G (93%)	36 G (93%)	36 G (92%)
	Base	WER (%)	28.17	28.48	31.35	32.34	38.43	52.19
		GFLOPs	94 G (100%)	89 G (95%)	88 G (93%)	87 G (92%)	86 G (92%)	86 G (91%)
	Small	WER (%)	17.93	19.25	20.36	22.20	24.07	30.74
		GFLOPs	381 G (100%)	360 G (94%)	352 G (92%)	349 G (92%)	347 G (91%)	345 G (91%)
	Medium	WER (%)	14.26	14.98	16.56	18.67	20.11	25.05
		GFLOPs	1.3k G (100%)	1.2k G (94%)	1.2k G (92%)	1.2k G (91%)	1.2k G (90%)	1.2k G (90%)
	Large	WER (%)	11.66	12.70	14.36	16.26	21.03	30.95
		GFLOPs	2.6k G (100%)	2.4k G (94%)	2.4k G (92%)	2.3k G (91%)	2.3k G (90%)	2.3k G (90%)

Table 14: Output-side stride- k subsampling: WER (%), total GFLOPs with remaining ratio (% of $k = 1$), and total inference latency (ms) for all datasets, model scales, and stride values ($k = 1$ –6). $k = 1$ (**bold**) reproduces the unmodified baseline.

Dataset	Model	Enc. FLOPs	Total FLOPs	Enc. ms	Total ms	WER
LibriTTS	Tiny	14.07 (-20.99)	15.08 (-23.83)	2.08 (-0.37)	116.57 (+8.58)	28.48 (+19.62)
	Base	35.22 (-49.05)	37.87 (-56.50)	3.04 (-0.42)	147.19 (+13.90)	14.13 (+7.25)
	Small	148.14 (-189.61)	159.89 (-222.58)	5.71 (-0.41)	233.63 (+25.48)	9.22 (+4.20)
	Medium	508.28 (-618.87)	549.74 (-735.10)	10.30 (-0.56)	350.17 (+20.66)	7.01 (+2.40)
	Large-v3	1035.88 (-1220.20)	1121.84 (-1461.11)	13.19 (-10.71)	427.23 (-88.26)	5.38 (+1.07)
ESD	Tiny	14.07 (-20.99)	15.02 (-23.72)	2.30 (-0.80)	66.05 (+1.33)	41.18 (+27.02)
	Base	35.22 (-49.05)	37.71 (-56.29)	3.14 (-1.70)	68.74 (-10.17)	20.36 (+8.83)
	Small	148.14 (-189.61)	159.26 (-221.96)	5.60 (-2.97)	94.38 (-21.07)	14.23 (+4.84)
	Medium	508.28 (-618.87)	547.68 (-733.44)	11.23 (-4.41)	169.25 (-12.80)	12.16 (+3.50)
	Large-v3	1035.88 (-1220.20)	1117.78 (-1458.34)	14.80 (-5.20)	198.99 (-16.74)	10.64 (+1.01)
Common Voice	Tiny	14.07 (-20.99)	15.06 (-23.68)	2.45 (-0.52)	143.77 (+67.02)	113.70 (+77.85)
	Base	35.22 (-49.05)	37.75 (-56.25)	3.36 (-0.69)	116.12 (+29.61)	47.65 (+19.48)
	Small	148.14 (-189.61)	159.39 (-221.75)	5.88 (-1.65)	149.41 (+5.00)	31.34 (+13.40)
	Medium	508.28 (-618.87)	548.09 (-732.78)	11.56 (-2.73)	235.76 (-11.48)	23.82 (+9.56)
	Large-v3	1035.88 (-1220.20)	1118.86 (-1456.80)	14.96 (-6.34)	295.40 (-20.94)	21.56 (+9.90)

Table 15: Compound subsampling results for $k_{\text{enc_in}} = k_{\text{enc_out}} = 2$. Each cell reports the Both value with its delta from the EncInput baseline at $k = 1$ in parentheses, computed as Both minus baseline. Total FLOPs are Enc. FLOPs + decoder-cross-attention FLOPs. WER is reported in percent.

Model	Layer		$d = 1$	$d = 2$	$d = 3$	$d = 4$	$d = 5$
Whisper-Tiny	Conv Stem	CKA	0.9640	0.9037	0.8511	0.8117	0.7874
		Δ	+0.0000	-0.0603	-0.1129	-0.1523	-0.1766
	Enc Out	CKA	0.8808	0.7755	0.7377	0.7359	0.7386
		Δ	+0.0000	-0.1053	-0.1432	-0.1449	-0.1422
Whisper-Base	Conv Stem	CKA	0.9641	0.9016	0.8456	0.8029	0.7768
		Δ	+0.0000	-0.0624	-0.1185	-0.1612	-0.1873
	Enc Out	CKA	0.9030	0.8067	0.7628	0.7487	0.7528
		Δ	+0.0000	-0.0963	-0.1402	-0.1543	-0.1501
Whisper-Small	Conv Stem	CKA	0.9608	0.8945	0.8357	0.7916	0.7649
		Δ	+0.0000	-0.0663	-0.1251	-0.1692	-0.1959
	Enc Out	CKA	0.8277	0.7465	0.7539	0.7431	0.7666
		Δ	+0.0000	-0.0811	-0.0737	-0.0846	-0.0610
Whisper-Medium	Conv Stem	CKA	0.9619	0.9023	0.8516	0.8130	0.7883
		Δ	+0.0000	-0.0596	-0.1103	-0.1489	-0.1736
	Enc Out	CKA	0.7867	0.6622	0.6482	0.6505	0.6529
		Δ	+0.0000	-0.1245	-0.1385	-0.1362	-0.1338
Whisper-Large	Conv Stem	CKA	0.9795	0.9500	0.9250	0.9052	0.8926
		Δ	+0.0000	-0.0295	-0.0545	-0.0743	-0.0869
	Enc Out	CKA	0.8597	0.7629	0.7242	0.7133	0.7098
		Δ	+0.0000	-0.0968	-0.1355	-0.1463	-0.1499

Table 16: Linear CKA and cumulative drop $\Delta(d) = \text{CKA}(d) - \text{CKA}(1)$ for Conv Stem and Encoder outputs at frame distances $d = 1-5$. Conv Stem similarity decreases monotonically, whereas Encoder output similarity converges after $d = 2-3$. Computed on LibriTTS

Category	Method	Acc. (%)	ΔA (pt)	FLOPs (G)	ΔF (%)	Lat. (ms)	ΔL (%)
Reasoning	baseline $k=1$	77.19	–	5662.56	–	103.00	–
	Enc $k=2$	76.28	-0.91	3419.02	-39.62	84.45	-18.01
	SP $r=0.2$	75.58	-1.61	5229.53	-7.65	85.07	-17.41
	SP $r=0.4$	71.45	-5.74	4825.53	-14.78	80.39	-21.95
	SP $r=0.6$	67.57	-9.62	4423.59	-21.88	76.01	-26.20
	SP $r=0.8$	60.66	-16.53	4018.48	-29.03	72.86	-29.27
	Enc+SP $r=0.2$	68.06	-9.13	3202.44	-43.45	74.36	-27.80
	Enc+SP $r=0.4$	64.38	-12.81	3002.08	-46.98	72.96	-29.16
	Enc+SP $r=0.6$	61.65	-15.54	2801.13	-50.53	71.77	-30.32
	Enc+SP $r=0.8$	58.10	-19.09	2593.18	-54.20	70.19	-31.86
Perception	baseline $k=1$	42.67	–	5924.75	–	106.90	–
	Enc $k=2$	42.36	-0.31	3396.50	-42.67	86.12	-19.44
	SP $r=0.2$	41.82	-0.85	5377.61	-9.23	87.97	-17.71
	SP $r=0.4$	41.71	-0.96	4860.47	-17.96	82.61	-22.72
	SP $r=0.6$	40.31	-2.36	4341.18	-26.73	77.09	-27.88
	SP $r=0.8$	37.67	-5.00	3824.41	-35.45	73.92	-30.85
	Enc+SP $r=0.2$	40.97	-1.70	3120.62	-47.33	77.70	-27.31
	Enc+SP $r=0.4$	39.42	-3.25	2863.55	-51.67	75.96	-28.94
	Enc+SP $r=0.6$	36.67	-6.00	2606.17	-56.01	74.64	-30.18
	Enc+SP $r=0.8$	35.23	-7.44	2351.79	-60.31	73.98	-30.79

Table 17: Category-level results on MMSU for **Audiotflamingo3**. We report accuracy, FLOPs, and latency for each category. Enc $k=2$ denotes encoder-side stride-2 subsampling. SP denotes SpeechPrune, where r indicates the pruning ratio (e.g., $r=0.2$ removes 20% of speech tokens). Enc+SP denotes the combined setting. All relative changes are computed with respect to the corresponding baseline within the same category.

Category	Method	Acc. (%)	ΔA (pt)	FLOPs (G)	ΔF (%)	Lat. (ms)	ΔL (%)
Reasoning	baseline $k=1$	58.47	–	7594.48	–	179.06	–
	Enc $k=2$	56.40	-2.07	4373.39	-42.41	126.18	-29.53
	SP $r=0.2$	56.77	-1.70	6797.79	-10.49	132.55	-25.97
	SP $r=0.4$	57.11	-1.36	5999.92	-21.00	127.57	-28.75
	SP $r=0.6$	54.75	-3.72	5210.78	-31.39	129.88	-27.46
	SP $r=0.8$	49.67	-8.80	4409.54	-41.94	127.29	-28.91
	Enc+SP $r=0.2$	56.03	-2.44	3979.94	-47.59	83.71	-53.25
	Enc+SP $r=0.4$	55.21	-3.26	3584.12	-52.81	81.15	-54.68
	Enc+SP $r=0.6$	51.69	-6.78	3193.98	-57.94	85.09	-52.48
	Enc+SP $r=0.8$	49.46	-9.01	2792.94	-63.22	89.49	-50.02
Perception	baseline $k=1$	29.96	–	7342.39	–	215.46	–
	Enc $k=2$	28.45	-1.51	4107.21	-44.06	140.40	-34.84
	SP $r=0.2$	28.45	-1.51	6553.31	-10.75	178.10	-17.34
	SP $r=0.4$	28.84	-1.12	5750.38	-21.68	169.34	-21.40
	SP $r=0.6$	28.95	-1.01	4967.55	-32.34	190.83	-11.43
	SP $r=0.8$	27.95	-2.01	4162.83	-43.30	195.42	-9.30
	Enc+SP $r=0.2$	28.45	-1.51	3717.57	-49.37	107.78	-49.98
	Enc+SP $r=0.4$	27.91	-2.05	3320.87	-54.77	108.25	-49.76
	Enc+SP $r=0.6$	28.06	-1.90	2941.09	-59.94	139.85	-35.09
	Enc+SP $r=0.8$	27.13	-2.83	2544.03	-65.35	159.05	-26.18

Table 18: Category-level results on MMSU for **LLaMA-Omni2**. We report accuracy, FLOPs, and latency for each category. Enc $k=2$ denotes encoder-side stride-2 subsampling. SP denotes SpeechPrune, where r indicates the pruning ratio (e.g., $r=0.2$ removes 20% of speech tokens). Enc+SP denotes the combined setting. All relative changes are computed with respect to the corresponding baseline within the same category.

Category	Method	Acc. (%)	ΔA (pt)	FLOPs (G)	ΔF (%)	Lat. (ms)	ΔL (%)
Reasoning	baseline $k=1$	69.71	–	5736.51	–	108.43	–
	Enc $k=2$	68.39	-1.32	3503.23	-38.93	92.75	-14.46
	SP $r=0.2$	68.47	-1.24	5318.06	-7.29	89.12	-17.81
	SP $r=0.4$	63.93	-5.78	4916.16	-14.30	83.98	-22.55
	SP $r=0.6$	57.44	-12.27	4518.10	-21.24	84.77	-21.82
	SP $r=0.8$	50.74	-18.97	4115.58	-28.26	83.71	-22.79
	Enc+SP $r=0.2$	66.66	-3.05	3296.68	-42.53	81.13	-25.17
	Enc+SP $r=0.4$	62.36	-7.35	3099.17	-45.97	82.77	-23.67
	Enc+SP $r=0.6$	55.37	-14.34	2901.52	-49.42	86.48	-20.25
	Enc+SP $r=0.8$	48.64	-21.07	2697.09	-52.98	90.21	-16.80
Perception	baseline $k=1$	41.12	–	5994.74	–	110.48	–
	Enc $k=2$	40.35	-0.77	3477.79	-41.99	91.58	-17.11
	SP $r=0.2$	40.04	-1.08	5461.46	-8.90	86.00	-22.16
	SP $r=0.4$	38.33	-2.79	4948.49	-17.45	81.67	-26.08
	SP $r=0.6$	36.82	-4.30	4431.98	-26.07	76.75	-30.53
	SP $r=0.8$	32.95	-8.17	3918.70	-34.63	74.05	-32.98
	Enc+SP $r=0.2$	38.91	-2.21	3210.58	-46.44	72.97	-33.96
	Enc+SP $r=0.4$	36.82	-4.30	2955.78	-50.69	71.65	-35.15
	Enc+SP $r=0.6$	35.27	-5.85	2700.18	-54.96	70.47	-36.22
	Enc+SP $r=0.8$	32.68	-8.44	2447.55	-59.17	70.44	-36.24

Table 19: Category-level results on MMSU for **Qwen2-Audio**. We report accuracy, FLOPs, and latency for each category. Enc $k=2$ denotes encoder-side stride-2 subsampling. SP denotes SpeechPrune, where r indicates the pruning ratio (e.g., $r=0.2$ removes 20% of speech tokens). Enc+SP denotes the combined setting. All relative changes are computed with respect to the corresponding baseline within the same category.

Category	Method	Acc. (%)	ΔA (pt)	FLOPs (G)	ΔF (%)	Lat. (ms)	ΔL (%)
Sound	baseline $k=1$	73.57	–	6320.28	–	190.04	–
	Enc $k=2$	73.27	-0.30	3617.51	-42.76	166.08	-12.61
	SP $r=0.2$	73.87	0.30	5712.18	-9.62	186.04	-2.10
	SP $r=0.4$	73.57	0.00	5123.17	-18.94	174.19	-8.34
	SP $r=0.6$	73.27	-0.30	4538.63	-28.19	168.49	-11.34
	SP $r=0.8$	72.07	-1.50	3949.32	-37.51	164.29	-13.55
	Enc+SP $r=0.2$	72.97	-0.60	3319.03	-47.49	173.39	-8.76
	Enc+SP $r=0.4$	73.57	0.00	3028.62	-52.08	172.01	-9.49
	Enc+SP $r=0.6$	72.07	-1.50	2740.01	-56.65	169.52	-10.80
	Enc+SP $r=0.8$	70.87	-2.70	2438.29	-61.42	167.57	-11.82
Speech	baseline $k=1$	58.56	–	8298.17	–	199.73	–
	Enc $k=2$	57.36	-1.20	4601.48	-44.55	175.57	-12.10
	SP $r=0.2$	57.36	-1.20	7285.25	-12.21	195.30	-2.22
	SP $r=0.4$	55.56	-3.00	6297.97	-24.10	185.99	-6.88
	SP $r=0.6$	54.05	-4.51	5318.16	-35.91	177.70	-11.03
	SP $r=0.8$	48.65	-9.91	4351.36	-47.56	169.85	-14.96
	Enc+SP $r=0.2$	56.76	-1.80	4099.12	-50.60	170.16	-14.80
	Enc+SP $r=0.4$	56.16	-2.40	3613.18	-56.46	167.28	-16.25
	Enc+SP $r=0.6$	54.05	-4.51	3130.75	-62.27	163.78	-18.00
	Enc+SP $r=0.8$	46.25	-12.31	2658.61	-67.96	162.53	-18.63
Music	baseline $k=1$	79.34	–	9354.09	–	233.91	–
	Enc $k=2$	78.14	-1.20	5202.11	-44.39	201.50	-13.86
	SP $r=0.2$	78.44	-0.90	8165.85	-12.70	226.35	-3.23
	SP $r=0.4$	78.14	-1.20	6997.61	-25.19	212.83	-9.01
	SP $r=0.6$	76.35	-2.99	5832.51	-37.65	203.48	-13.01
	SP $r=0.8$	76.35	-2.99	4648.42	-50.31	195.48	-16.43
	Enc+SP $r=0.2$	76.65	-2.69	4611.91	-50.70	194.58	-16.81
	Enc+SP $r=0.4$	77.54	-1.80	4029.30	-56.92	191.92	-17.95
	Enc+SP $r=0.6$	76.35	-2.99	3444.30	-63.18	187.16	-19.99
	Enc+SP $r=0.8$	76.35	-2.99	2841.26	-69.63	184.72	-21.03

Table 20: Category-level results on MMAU for **Audioflamingo3**. We report accuracy, FLOPs, and latency for each category. Enc $k=2$ denotes encoder-side stride-2 subsampling. SP denotes SpeechPrune, where r indicates the pruning ratio (e.g., $r=0.2$ removes 20% of speech tokens). Enc+SP denotes the combined setting. All relative changes are computed with respect to the corresponding baseline within the same category.

Category	Method	Acc. (%)	ΔA (pt)	FLOPs (G)	ΔF (%)	Lat. (ms)	ΔL (%)
Sound	baseline $k=1$	52.55	–	7331.06	–	169.65	–
	Enc $k=2$	48.05	-4.50	4094.61	-44.15	96.91	-42.88
	SP $r=0.2$	48.35	-4.20	6519.56	-11.07	147.91	-12.81
	SP $r=0.4$	51.35	-1.20	5728.46	-21.86	158.14	-6.78
	SP $r=0.6$	51.35	-1.20	4923.42	-32.84	138.04	-18.63
	SP $r=0.8$	51.35	-1.20	4121.66	-43.78	143.88	-15.19
	Enc+SP $r=0.2$	45.65	-6.90	3695.95	-49.59	93.46	-44.91
	Enc+SP $r=0.4$	51.95	-0.60	3301.89	-54.96	98.34	-42.03
	Enc+SP $r=0.6$	51.35	-1.20	2905.21	-60.37	97.91	-42.29
	Enc+SP $r=0.8$	52.25	-0.30	2496.73	-65.94	97.32	-42.63
Speech	baseline $k=1$	48.95	–	7382.42	–	186.66	–
	Enc $k=2$	46.55	-2.40	4150.85	-43.77	120.84	-35.26
	SP $r=0.2$	44.44	-4.51	6579.29	-10.88	177.77	-4.76
	SP $r=0.4$	42.04	-6.91	5789.22	-21.58	186.73	0.04
	SP $r=0.6$	42.64	-6.31	4997.85	-32.30	187.25	0.32
	SP $r=0.8$	39.64	-9.31	4192.79	-43.21	181.80	-2.60
	Enc+SP $r=0.2$	45.05	-3.90	3757.19	-49.11	122.26	-34.50
	Enc+SP $r=0.4$	45.05	-3.90	3370.60	-54.34	136.32	-26.97
	Enc+SP $r=0.6$	41.14	-7.81	2984.20	-59.58	149.77	-19.76
	Enc+SP $r=0.8$	37.54	-11.41	2567.95	-65.22	130.84	-29.90
Music	baseline $k=1$	52.69	–	7417.40	–	174.36	–
	Enc $k=2$	50.30	-2.39	4196.86	-43.42	126.39	-27.51
	SP $r=0.2$	52.40	-0.29	6614.35	-10.83	166.52	-4.50
	SP $r=0.4$	51.50	-1.19	5815.88	-21.59	162.26	-6.94
	SP $r=0.6$	50.60	-2.09	5025.23	-32.25	164.74	-5.52
	SP $r=0.8$	51.80	-0.89	4212.47	-43.21	146.22	-16.14
	Enc+SP $r=0.2$	51.20	-1.49	3803.46	-48.72	129.71	-25.61
	Enc+SP $r=0.4$	51.50	-1.19	3398.87	-54.18	114.03	-34.60
	Enc+SP $r=0.6$	51.50	-1.19	2999.00	-59.57	105.35	-39.58
	Enc+SP $r=0.8$	51.80	-0.89	2593.66	-65.03	105.48	-39.50

Table 21: Category-level results on MMAU for **LLaMA-Omni2**. We report accuracy, FLOPs, and latency for each category. Enc $k=2$ denotes encoder-side stride-2 subsampling. SP denotes SpeechPrune, where r indicates the pruning ratio (e.g., $r=0.2$ removes 20% of speech tokens). Enc+SP denotes the combined setting. All relative changes are computed with respect to the corresponding baseline within the same category.

Category	Method	Acc. (%)	ΔA (pt)	FLOPs (G)	ΔF (%)	Lat. (ms)	ΔL (%)
Sound	baseline $k=1$	59.76	–	6369.72	–	132.04	–
	Enc $k=2$	57.06	-2.70	3668.80	-42.40	101.86	-22.86
	SP $r=0.2$	59.76	-0.00	5767.23	-9.46	127.47	-3.46
	SP $r=0.4$	59.16	-0.60	5181.65	-18.65	118.39	-10.34
	SP $r=0.6$	56.16	-3.60	4595.33	-27.86	105.55	-20.06
	SP $r=0.8$	52.55	-7.21	4010.33	-37.04	104.76	-20.66
	Enc+SP $r=0.2$	56.76	-3.00	3373.63	-47.04	94.99	-28.06
	Enc+SP $r=0.4$	55.56	-4.20	3085.67	-51.56	95.44	-27.72
	Enc+SP $r=0.6$	57.06	-2.70	2797.44	-56.08	93.65	-29.07
	Enc+SP $r=0.8$	51.05	-8.71	2501.26	-60.73	101.44	-23.17
Speech	baseline $k=1$	53.75	–	8303.95	–	113.94	–
	Enc $k=2$	53.15	-0.60	4615.62	-44.42	94.24	-17.29
	SP $r=0.2$	52.25	-1.50	7300.69	-12.08	115.83	1.66
	SP $r=0.4$	50.45	-3.30	6315.84	-23.94	109.96	-3.49
	SP $r=0.6$	45.05	-8.70	5341.69	-35.67	101.95	-10.52
	SP $r=0.8$	37.24	-16.51	4382.80	-47.22	95.79	-15.93
	Enc+SP $r=0.2$	51.65	-2.10	4120.97	-50.37	93.01	-18.37
	Enc+SP $r=0.4$	45.35	-8.40	3639.63	-56.17	93.64	-17.82
	Enc+SP $r=0.6$	41.14	-12.61	3164.31	-61.89	95.45	-16.23
	Enc+SP $r=0.8$	32.73	-21.02	2705.37	-67.42	107.65	-5.52
Music	baseline $k=1$	55.39	–	9358.64	–	132.06	–
	Enc $k=2$	55.39	0.00	5212.75	-44.30	101.72	-22.97
	SP $r=0.2$	53.29	-2.10	8183.63	-12.56	135.59	2.67
	SP $r=0.4$	52.99	-2.40	7017.12	-25.02	120.91	-8.44
	SP $r=0.6$	53.29	-2.10	5853.33	-37.46	108.11	-18.14
	SP $r=0.8$	52.40	-2.99	4673.40	-50.06	97.26	-26.35
	Enc+SP $r=0.2$	54.49	-0.90	4631.25	-50.51	99.23	-24.86
	Enc+SP $r=0.4$	55.09	-0.30	4049.74	-56.73	94.22	-28.65
	Enc+SP $r=0.6$	52.99	-2.40	3469.70	-62.93	94.25	-28.63
	Enc+SP $r=0.8$	50.30	-5.09	2869.43	-69.34	92.05	-30.30

Table 22: Category-level results on MMAU for **Qwen2-Audio**. We report accuracy, FLOPs, and latency for each category. Enc $k=2$ denotes encoder-side stride-2 subsampling. SP denotes SpeechPrune, where r indicates the pruning ratio (e.g., $r=0.2$ removes 20% of speech tokens). Enc+SP denotes the combined setting. All relative changes are computed with respect to the corresponding baseline within the same category.

Dataset	Mode	WER (%)	Total FLOPs (G)
LibriTTS	Distil	4.94	2276.40
	Distil + EncInput $k = 2$	5.93	1046.19
	Distil + compound $k = 2$	8.31	1041.17
ESD	Distil	9.48	2275.97
	Distil + EncInput $k = 2$	10.69	1045.88
	Distil + compound $k = 2$	13.28	1040.93
Common Voice	Distil	14.51	2276.05
	Distil + EncInput $k = 2$	23.65	1045.94
	Distil + compound $k = 2$	31.07	1041.00

Table 23: Distil-Whisper large-v3 ASR performance and total FLOPs under stride- k sampling.