Jev-LiteMAS: Separating Decisions from Generation in Multi-Agent Workflows

Kaixiang Wang
Shanghai Jiao Tong University
Shanghai, China

Zhaojiacheng Zhou
Shanghai Jiao Tong University
Shanghai, China

Jiong Lou
Shanghai Jiao Tong University
Shanghai, China

Jie Li
Shanghai Jiao Tong University
Shanghai, China

arXiv:2610.21411v1 [cs.AI] 15 Oct 2026

Abstract

Multi-agent LLM systems rely on generative models for expert execution, workflow planning, and artifact review. Yet many coordination operations require only bounded decisions, such as selecting the next expert or judging artifact quality. Profiling three representative MAS frameworks, we find that routing and review account for 31.7–43.5% of generative-LLM tokens. However, replacing these operations with low-cost decision models introduces two interface gaps: generative planners produce execution plans and handoff instructions (*planning gap*), while reviewers provide actionable feedback for repairing flawed artifacts (*review gap*)—outputs that bounded decisions alone cannot provide.

We introduce Jev-LiteMAS, a multi-agent framework that bridges both gaps by combining a lightweight decision model (Jev) with generative execution and feedback. To address the planning gap, Jev selects experts dynamically from the task and prior expert outputs, using accumulated context to ground subsequent execution without a pre-generated trajectory. To address the review gap, Jev screens intermediate artifacts against task criteria: passing artifacts proceed directly, whereas flagged ones undergo LLM re-review for acceptance or corrective feedback. Across four benchmarks and two backbones, Jev-LiteMAS reduces generative-LLM tokens by 12.7–54.6% over LAS, maintaining accuracy within 1.34 percentage points and lowering latency in seven of eight settings. Grounding routing in substantive expert outputs prevents up to 18.0 points in accuracy loss.

CCS Concepts

• **Do Not Use This Code → Generate the Correct Terms for Your Paper**; *Generate the Correct Terms for Your Paper*; Generate the Correct Terms for Your Paper; Generate the Correct Terms for Your Paper.

Keywords

LLM, Multi-agent, Decision model, jev

1 Introduction

LLM-based multi-agent systems (MAS) organize specialist agents through role assignments, communication, and intermediate artifacts [10, 13, 30]. Recent systems further optimize workflow construction and agent communication [36, 38, 39]. These workflows combine expert execution with repeated coordination. Experts generate substantive content, such as code, API-driven solutions, and research proposals. Coordination operations select the next expert and assess whether intermediate artifacts can proceed. Many of these operations produce only bounded outputs, such as an expert identifier or a pass/escalate decision. Using a generative LLM for every such decision adds model calls between expert contributions. This difference in output requirements suggests an opportunity to allocate model capabilities at the level of workflow operations.

To quantify this opportunity, we profile three representative MAS architectures, MetaGPT, AgentNet, and LAS [10, 32, 34], using DeepSeek-V4-Flash as the shared generative backbone on MATH [9] and MBPP+ [1, 17]. Figure 1 shows that routing and review account for 31.7–43.5% of total generative-LLM tokens across the six measured configurations. Their recorded latency shares range from 29.5% to 46.1%. Even in LAS, which dynamically adjusts workflow execution, routing and review consume 40.4% and 39.2% of tokens on MATH and MBPP+, respectively. These results reveal substantial coordination overhead across different MAS architectures and raise a more specific question: which coordination operations require open-ended generation, and which can be handled through a lower-cost decision interface?

These observations motivate assigning routine routing and review decisions to low-cost decision models, while retaining generative models for substantive task execution. Although prior studies have explored cost-aware model routing and efficient MAS coordination [3, 19, 29, 37], integrating choice-based models into conventional multi-agent workflows introduces two interface challenges. **First, planning and expert handoffs.** In planner-driven MAS, a generative planner produces a multi-step plan specifying task decomposition, agent assignments, execution order, and handoff instructions [4, 10]. In contrast, a choice-based decision model (e.g., Jev [25]) only selects from predefined expert candidates, leaving plan and instruction generation outside its bounded interface. **Second, review and corrective feedback.** Generative reviewers assess intermediate artifacts and provide detailed revision guidance when quality issues arise [8, 18]. Conversely, a choice-based judge like Jev only yields a bounded verdict, unable to generate actionable strategies for subsequent repair.

These mismatches raise a central question: *how to reorganize multi-agent collaboration around bounded decisions while preserving the planning context and generative feedback required for effective execution and error recovery?* This motivates our guiding principle: *allocate model capabilities according to each operation's output requirements.* We organize collaboration around feedback-driven decisions—using accumulated artifacts to ground execution—while



Figure 1: Routing and review account of generative-LLM tokens and latency in our measured MAS configurations. Each bar is normalized by the total cost of its framework and across two benchmarks.

retaining generative capabilities for task execution and on-demand corrective feedback.

We introduce Jev-LiteMAS, a multi-agent framework that leverages the complementary strengths of generative and decision models to reduce coordination overhead while maintaining task quality. To address the planning gap, we develop *feedback-driven expert handoffs*. Instead of generating a complete execution trajectory in advance, Jev selects the next expert at each handoff based on the overall task, previous expert outputs, and the current execution state. The selected expert receives the accumulated task context and produces its contribution, allowing subsequent routing decisions to adapt to actual execution progress. To address the review gap, we introduce *Jev-gated LLM re-review*. Jev first judges whether an intermediate artifact satisfies the task-specific quality criteria, allowing qualified artifacts to proceed without invoking a generative reviewer. Artifacts that fail this judgment are escalated to an LLM reviewer, which independently reassesses their quality and either accepts them or generates actionable feedback for revision by the responsible expert. Revised artifacts are evaluated again before proceeding. Together, these mechanisms replace routine generative coordination with lightweight decisions while retaining the contextual information and generative feedback needed for effective collaboration and error recovery.

We evaluate Jev-LiteMAS on four benchmarks spanning mathematical reasoning, code generation, tool use, and interdisciplinary idea integration, using DeepSeek-V4-Flash and GPT-5 expert backbones. Compared with LAS, Jev-LiteMAS reduces generative-LLM token usage by 12.7–54.6%, with accuracy differences within 1.34 percentage points and lower end-to-end latency in seven of eight configurations. Removing substantive expert feedback from routing decreases accuracy by 18.00 points on IDRBench I3 and 9.02 points on API-Bank [15], with nearly unchanged LLM call counts. Under injected agent errors, Jev screening detects 91.33–95.33% of corrupted cases, while the cascaded configuration consumes 14.6–21.7% fewer generative-LLM tokens than LLM judging. These results connect the end-to-end efficiency gains to feedback-aware coordination and selective generative review.

Our contributions are summarized as follows:

- **Coordination-capability insight.** We quantify the generative overhead of routine MAS control and characterize the information required for bounded expert selection and actionable recovery.
- **Jev-LiteMAS architecture.** We develop an information-preserving workflow that seamlessly combines feedback-driven expert handoffs, bounded artifact screening, and conditional generative review and expert-guided repair.
- **Systematic evaluation.** We measure quality and resource use across four benchmarks and two backbones, and analyze workflow organization, semantic feedback, and review reliability through controlled ablations and error injection.

2 Related Work

LLM Multi-Agent Systems. LLM-based multi-agent systems coordinate specialized agents through role assignments, intermediate artifacts, and shared execution context. Recent research improves this coordination at several levels. AFlow searches over code-represented workflows, while MetaAgent constructs multi-agent systems using finite-state machines [39, 40]. MaAS learns a distribution of query-dependent architectures, and G-Designer generates task-aware communication topologies [36, 38]. MasRouter jointly considers collaboration modes, agent roles, and model selection [35]. AnyMAC predicts subsequent agents and selects context from prior steps in sequential collaboration [27]. For execution efficiency, AgentDropout removes redundant agents and communication, while LAS uses a lightweight gate followed by LLM scheduling to adjust processing depth [29, 32]. AgentFlow coordinates planning, tool execution, verification, and answer generation through evolving memory, and ReAgent supports recovery by revisiting earlier execution states [16, 33]. Together, these systems illustrate the growing role of adaptive control and intermediate feedback in multi-agent execution. Their varied coordination operations motivate examining where bounded model decisions can be used within an expert workflow.

Jev and System-One Decision Models. Jev provides typed choices, rubric scores, and binary judgments for software-controlled decisions [25]. Independent evaluations examine its performance on general decision benchmarks and text annotation, including classification quality, inference cost, and calibration [6, 11]. Further studies analyze decision stability under changes to option semantics and assess typed decisions across agent-harness tasks [14, 24]. Beyond standalone judgments, Jev-Mem uses a decision layer to manage

memory operations [12]. SeLMRoute extracts probabilistic semantic evidence for model routing, and REFLEX explores bounded control with generative fallback in agents [22, 31]. The contemporaneous S1-MAS framework likewise allocates lightweight System-One decisions to multi-agent coordination using an open decision model [41]. This literature provides a basis for studying typed judgments in agent systems, where local decisions affect downstream execution.

Our work Jev-LiteMAS integrates choice-based decisions into multi-agent workflows through feedback-driven expert handoffs and Jev-gated artifact review. It preserves generative capabilities for expert reasoning and corrective feedback, enabling selective LLM re-review while balancing task quality, review reliability, and execution efficiency.

3 Problem Setting and Design Rationale

This section formalizes the operation-level multi-agent workflow, examines the capability requirements of routing and review, and motivates our design.

3.1 Operation-Level Multi-Agent Workflows

We consider a multi-agent workflow with a pool of generative experts $\mathcal{E} = \{E_1, \ldots, E_n\}$. Given a task x, the experts collaborate through successive execution steps. At step t, the selected expert $e_t \in \mathcal{E}$ produces an intermediate artifact y_t from the available execution state s_{t-1}. The workflow then incorporates this artifact into its updated state:

$$y_t = G_{e_t}(s_{t-1}), \qquad s_t = U(s_{t-1}, e_t, y_t), \tag{1}$$

where G_{e_t} denotes expert execution and U denotes the workflow's state update. The observable state contains the task, intermediate artifacts, and relevant expert information.

We distinguish three operations within this workflow: *expert execution*, which generates or revises task artifacts; *expert routing*, which selects the next action; and *local review*, which evaluates an intermediate artifact. At a routing point, the legal action set $\mathcal{A}_t$ contains eligible experts and, when permitted, a termination action. At a review point, the reviewer determines whether the artifact can proceed:

$$\mathcal{A}_t \subseteq \mathcal{E} \cup \{\text{STOP}\}, \qquad d_t \in \{\text{pass}, \text{escalate}\}. \tag{2}$$

These operations differ in their output requirements. Expert execution requires open-ended generation, while routing and initial review admit bounded decision interfaces. This distinction creates an opportunity to allocate model capabilities at the level of workflow operations.

3.2 Capability Mismatch in Workflow Control

Planning and expert handoffs. Generative controllers can produce task-specific plans and instructions for subsequent experts. A choice-based model operates over a supplied candidate set and returns a selected action:

$$G_{\text{plan}}(s_t) \in \Sigma^*, \qquad J_{\text{route}}(s_t, \mathcal{A}_t) \in \mathcal{A}_t, \tag{3}$$

where Σ^* denotes the space of generated text sequences. This difference places greater importance on how the workflow provides legal actions and execution context. In particular, expert handoffs must remain informed by the latest artifacts, while the information needed for expert execution remains available to the next selected expert throughout subsequent execution.

Review decisions and corrective feedback. Generative reviewers can assess an artifact and provide task-specific feedback. A choice-based reviewer produces a bounded decision:

$$G_{\text{review}}(s_t) = (v_t, c_t), \qquad J_{\text{screen}}(s_t) = d_t, \tag{4}$$

where v_t is the review verdict and c_t denotes corrective feedback when needed. The screening decision identifies artifacts requiring further attention. Those artifacts still need a generative reviewer to reassess their content and provide actionable guidance for subsequent repair.

Together, these two cases highlight the role of information flow in capability allocation: bounded decisions guide workflow execution, while generative operations supply the content needed to complete and revise tasks.

3.3 Capability-Matched Workflow Design

The preceding observations motivate an operation-level division of responsibilities. Generative experts retain task execution and artifact revision. A choice-based model handles bounded routing and initial review using the observable execution state.

For coordination, the workflow selects subsequent experts from the legal action set after observing the latest execution results. This enables successive handoffs to reflect the evolving task state.

For review, the workflow adopts a conditional generative path. The screening decision d_t determines whether the artifact proceeds or undergoes LLM re-review:

$$(v_t, c_t) = \begin{cases} (\text{pass}, \varnothing), & d_t = \text{pass}, \\ G_{\text{review}}(s_t), & d_t = \text{escalate}. \end{cases} \tag{5}$$

The generative reviewer reassesses escalated artifacts and supplies corrective feedback when needed. Subsequent revisions remain the responsibility of the generative experts.

Follow these principles we present Jev-LiteMAS, which integrates feedback-driven expert handoffs with Jev-gated LLM re-review. The following section presents the workflow architecture and the detailed execution procedure.

4 Jev-LiteMAS

This section presents Jev-LiteMAS, which coordinates generative experts through feedback-driven handoffs and Jev-gated LLM re-review. We first describe the shared execution state, then detail how routing, screening, and corrective feedback shape the workflow.

4.1 System Overview

Figure 2 illustrates the workflow. The system consists of a pool of generative experts, two decision operations served by Jev, and a generative reviewer for escalated artifacts. Experts create task outputs and perform revisions. The routing operation chooses the next expert from the legal candidates. The screening operation assesses intermediate artifacts and decides whether they can proceed. When screening requests further examination, the LLM reviewer evaluates the artifact and provides feedback for subsequent execution.



Figure 2: Overview of Jev-LiteMAS.

Each expert $e \in \mathcal{E}$ has a configured generative backend L_e and role instructions p_e. We write its execution interface as

$$G_e(s) = \mathrm{Exec}(L_e, p_e, s), \tag{6}$$

where s supplies the task, available artifacts, and any feedback relevant to the current execution. Role instructions specify the expert's responsibility, such as producing an artifact or revising an existing one. The runtime manages model invocation and passes the result back to the workflow. An expert's role remains associated with its configuration across successive handoffs. The state provides the changing part of its input: the user's request, intermediate work, and feedback generated during execution.

The state also connects the two decision operations. The router uses it to choose the next contributor, while the screener uses it to assess the current artifact. Their prompts and output candidates reflect these separate responsibilities. Both decisions can refer to the same task and execution history, which makes the resulting control actions consistent with the work already performed.

We use the state convention in Section 3: expert e_t produces y_t from s_{t-1}, and U incorporates the result into s_t. The updated state is the common input to subsequent control operations. It makes the latest artifact visible alongside the task and prior execution context. At configured review points, screening is resolved before the workflow proceeds with its next ordinary handoff. Both Jev operations therefore act on artifacts generated during the current execution, while generative experts retain the context required to continue the task.

4.2 Feedback-Driven Expert Handoffs

Routing context and candidates. The next expert is selected after the workflow observes an execution result. The runtime constructs the decision input from s_t and the legal set $\mathcal{A}_t$. The task describes the overall objective; the current artifact records what has been produced; and the expert descriptions indicate what each candidate can contribute. Candidate identifiers connect the decision returned by Jev to executable expert configurations. The set $\mathcal{A}_t$ follows the configured workflow rules and contains eligible experts, with STOP included when termination is an available action. Each candidate has an identifier understood by the runtime and a description of its assigned expertise. This correspondence is maintained across routing steps, so the selected identifier can be used immediately for dispatch. The candidate set determines the available workflow transitions, while the current artifact helps Jev choose among them.

Jev chooses one action from these candidates:

$$a_t = J_{\mathrm{route}}(s_t, \mathcal{A}_t), \qquad a_t \in \mathcal{A}_t. \tag{7}$$

The routing request asks which expert should contribute next given the task and available progress. As an expert completes its work, the new artifact becomes evidence for later decisions. The router can consequently select different experts as the task develops, using the same bounded action interface at each decision point. The decision may reflect the presence of an unfinished artifact, a result requiring further inspection, or sufficient progress to finish, depending on the candidates allowed by the workflow. The process repeats after each completed expert execution, so new intermediate results influence later decisions without a separate generated plan for the entire trajectory.

Dispatch and execution context. If a_t identifies an expert, the runtime resolves that identifier to the corresponding model and role instructions and starts the next execution step:

$$e_{t+1} = a_t, \qquad y_{t+1} = G_{e_{t+1}}(s_t). \tag{8}$$

The selected expert receives the original task and the available intermediate results through s_t. Its own role instructions establish the expected contribution. This separation gives the controller a compact decision interface while preserving task context for the

model responsible for generating content. The returned y_{t+1} is incorporated through U, making it available to the next routing or review operation. The handoff carries the existing artifact forward; the receiving expert can inspect and extend that work within its configured responsibility. This is important when successive experts address different aspects of the same task, since their outputs remain connected through the shared state. It also preserves a simple interface between the controller and the expert: the former returns a legal action, and the latter generates the task content.

Successive handoffs. Handoffs continue as new artifacts change the state. For example, a draft result may lead the router to select an expert responsible for checking or refining it; the resulting feedback can then inform another handoff. Such choices use the current trajectory and the experts already configured in the workflow. If $a_t = \text{STOP}$, the runtime invokes the finalization procedure. A local review pass, by comparison, only releases an artifact to the remaining workflow. This distinction keeps artifact acceptance and task completion as separate execution events. At a configured checkpoint, an artifact must complete the local review path before ordinary coordination resumes. Review-triggered revisions are therefore processed using the feedback associated with that artifact, while the next normal handoff operates on the updated state. The workflow can combine several expert executions and local checks before finalization.

4.3 Jev-Gated LLM Re-review

Artifact screening. At a designated review point, the screening request includes the current task, artifact y_t, and the review criteria available in s_t. Jev evaluates whether the artifact can proceed under these criteria and returns a bounded decision:

$$d_t = J_{\text{screen}}(s_t) \in \{\text{pass}, \text{escalate}\}. \tag{9}$$

A passing artifact is released for continuation. The runtime records $v_t = \text{pass}$ and $c_t = \varnothing$ for this local decision. An escalation routes the same task and artifact to the LLM reviewer. The escalation decision initiates further examination; the LLM then determines the review outcome for this branch. The screening criteria follow the task setting being evaluated, such as whether a solution satisfies its requirements or an output violates the specified review conditions. The screening result is associated with the current artifact and checkpoint. A later revision is screened as a new artifact at its own review point.

Generative re-review. The generative reviewer examines the escalated artifact using the available task context and review criteria. Its output contains a verdict v_t and feedback c_t:

$$(v_t, c_t) = G_{\text{review}}(s_t), \qquad d_t = \text{escalate}. \tag{10}$$

The verdict decides whether the artifact may proceed or requires revision. The feedback records the issues identified during review and, when revision is needed, provides guidance for the next expert execution. For instance, feedback on a program can identify an unhandled input case, whereas feedback on a mathematical solution can locate a questionable derivation step. This information is tied to the submitted artifact so that the next model call can operate on the existing work. The reviewer can also accept an escalated artifact after reconsidering its content. In that case, the outcome allows normal execution to resume, and no repair call is needed. The verdict and feedback have separate uses: the former controls the branch, and the latter informs the revision when requested.

Repair and re-entry. When the review outcome requests revision, the workflow assigns a generative expert e_{t+1} according to its repair protocol. We denote the state with the new review information by $\widetilde{s_t}$:

$$\widetilde{s_t} = s_t \oplus (v_t, c_t), \qquad y_{t+1} = G_{e_{t+1}}(\widetilde{s_t}). \tag{11}$$

Here $\oplus$ means that the runtime makes the review information available to the assigned expert. The expert receives the task, current artifact, and the returned feedback, and produces an updated artifact. The runtime incorporates the revision through the state update U and applies the configured review procedure at the next review point. The new artifact is treated as the result of another expert execution, with its own state update and subsequent screening. This preserves the link between the earlier feedback and the revised content. If another problem is identified, the same review–revision loop may continue within the configured limits.

This execution path also defines the scope of the screening gate. A passing artifact proceeds without an LLM re-review at that checkpoint. For escalated artifacts, the generative call supplies an additional assessment and, when needed, a correction plan. The resulting decisions and revisions remain visible in subsequent workflow state, allowing ordinary expert coordination to resume. This separation links the screening decision to the additional content generated for the subsequent expert execution.

4.4 Design Benefits

Efficient coordination. Feedback-driven handoffs assign each decision to a bounded action interface. Jev selects the next eligible expert using the latest task state, while generative experts remain responsible for producing and refining artifacts. This division keeps routine coordination lightweight and allows expert execution to use the accumulated task context.

Selective generative review. In the common operating regime where most intermediate artifacts satisfy the local review criteria, reviewing every artifact with a generative LLM spends many calls on outputs that already require no change. Jev screens these artifacts first. Passing outputs proceed directly to the next workflow step, and only escalated outputs invoke LLM re-review. When acceptable artifacts dominate and the screening false-escalation rate is low, the workflow avoids a substantial fraction of generative review calls. The LLM remains available to reassess escalated outputs and provide corrective feedback when revision is needed.

The resulting workflow combines low-overhead coordination with selective generative feedback. Appendix D gives the full escalation protocol and analyzes how artifact quality and screening reliability affect review overhead.

5 Experiment

We systematically evaluate Jev-LiteMAS's task quality and execution cost through its separation of generative execution and bounded decision-making, and assess the contributions of individual components through ablation studies.

Table 1: End-to-end comparison across four benchmarks using DeepSeek-V4-Flash (top) and GPT-5 (bottom). ACC is in percent; Input, Output, and Total denote generative-LLM token counts; E2E is wall-clock latency in seconds; Calls denotes generative-LLM API calls per evaluation unit. Arrows indicate preferred directions.

DeepSeek-V4-Flash												
Method	MATH						MBPP+					
	ACC↑	Input	Output	Total↓	E2E↓	Calls↓	ACC↑	Input	Output	Total↓	E2E↓	Calls↓
Single-agent	85.33	1234.8	944.7	2179.5	10.70	1.00	66.67	1257.6	632.8	1890.4	14.70	1.00
MetaGPT	98.67	6754.1	3240.9	9995.0	36.07	4.00	82.67	7292.1	5774.8	13066.9	66.36	4.00
AFlow	86.67	2248.9	1667.2	3916.1	17.09	1.00	73.33	2305.5	2906.9	5212.4	19.90	1.00
AgentNet	96.67	3256.4	4467.6	7724.0	29.03	2.67	78.00	3610.7	4623.7	8234.4	43.91	3.13
LAS	98.00	3792.0	2791.0	6583.0	26.15	3.03	84.67	5132.0	3587.0	8719.0	45.60	3.09
Ours	97.33	3848.4	1584.8	5433.2	22.13	2.96	85.33	4136.0	2767.5	6903.5	38.67	2.96
Method	API-Bank						IDRBench I3					
	ACC↑	Input	Output	Total↓	E2E↓	Calls↓	ACC↑	Input	Output	Total↓	E2E↓	Calls↓
Single-agent	35.28	4466.8	2543.9	7010.7	23.52	1.00	54.67	1849.0	1143.8	2992.8	14.73	1.00
MetaGPT	62.47	21514.9	8579.4	30094.4	50.73	9.89	82.67	9342.1	7006.3	16348.4	86.61	4.00
AFlow	45.62	4691.1	2553.8	7244.9	29.76	2.74	61.33	4257.6	3504.8	7762.3	43.79	2.00
AgentNet	59.10	10206.3	5724.2	15930.6	38.25	6.38	77.33	14084.5	13313.2	27397.7	164.45	6.12
LAS	66.52	11307.0	4986.0	16293.0	41.39	6.63	76.00	12700.0	9856.0	22556.0	133.52	5.56
Ours	66.29	6552.8	3316.5	9869.3	35.34	4.00	75.33	4928.3	5305.5	10233.8	72.40	2.47
GPT-5												
Method	MATH						MBPP+					
	ACC↑	Input	Output	Total↓	E2E↓	Calls↓	ACC↑	Input	Output	Total↓	E2E↓	Calls↓
Single-agent	96.00	1129.0	1211.9	2340.9	13.24	1.00	74.00	1162.0	764.7	1926.7	9.32	1.00
MetaGPT	100.00	6250.7	5062.7	11313.4	64.07	4.00	81.33	6804.0	4645.1	11449.1	55.05	4.00
AFlow	95.33	2153.0	2195.3	4348.3	16.08	2.00	79.33	2191.1	2044.5	4235.6	24.47	2.00
AgentNet	98.67	3211.8	2482.7	5694.4	27.14	2.52	82.00	3125.9	3468.8	7594.7	40.68	3.00
LAS	98.00	4209.0	3454.0	7663.0	25.91	3.31	84.67	4842.0	3794.0	8636.0	43.60	3.18
Ours	98.00	3572.0	2418.0	5990.0	30.04	2.98	83.33	4028.0	3514.0	7542.0	40.25	3.03
Method	API-Bank						IDRBench I3					
	ACC↑	Input	Output	Total↓	E2E↓	Calls↓	ACC↑	Input	Output	Total↓	E2E↓	Calls↓
Single-agent	51.46	4644.9	2885.9	7530.8	30.92	1.00	46.67	1848.9	2025.7	3874.5	25.75	1.00
MetaGPT	67.64	21882.7	11918.6	33801.3	152.63	10.90	62.00	10599.2	7540.7	18139.9	90.57	4.00
AFlow	60.67	4636.4	2955.1	7591.5	36.83	2.83	51.33	6990.5	5339.8	12330.3	65.88	3.00
AgentNet	67.19	13415.4	7576.8	20992.2	133.82	9.43	64.67	15388.9	9794.3	25183.2	127.38	5.97
LAS	69.89	9637.0	6756.0	16393.0	67.39	5.90	63.33	14357.0	11083.0	25440.0	119.45	6.04
Ours	68.99	5485.0	4589.0	10074.0	33.53	3.68	64.00	8951.0	6675.0	15626.0	75.57	3.37

5.1 Experimental Setup

Benchmarks and baselines. Our evaluation covers four benchmarks across diverse domains: MATH [9] for mathematical reasoning, MBPP+ [1, 17] for code generation, API-Bank [15] for tool use, and IDRBench I3 [23] for interdisciplinary research idea integration.

We compare Jev-LiteMAS against five representative baselines covering single-agent execution, multi-agent collaboration, workflow optimization, and adaptive scheduling. Single-Agent directly solves tasks with a single LLM. MetaGPT [10] coordinates specialized agents through standardized workflows. AFlow [39] automatically searches and optimizes agentic workflows. AgentNet [34] enables decentralized agent collaboration through a structured network. LAS [32] dynamically schedules workflow execution using a lightweight gate and an LLM scheduler.

Implementation and Metrics. We implement Jev-LiteMAS on top of the AutoGen [30] framework, integrating Jev-based expert routing and cascaded review into multi-agent execution. In our main experiments, we use DeepSeek-V4-Flash [5] and GPT-5 [20] as generative backbones, Jev [25] as the lightweight decision model, and Qwen3-1.7B-Instruct as the SLM baseline. Subsequent analyses primarily use the DeepSeek configuration to investigate the contributions of workflow organization, routing strategies, and selective review. Specifically, we compare different MAS structures and routing methods, inject errors into randomly selected agents, and evaluate Jev and LLM judges under clean and corrupted outputs. We further examine sensitivity to generative-LLM call budgets, heterogeneous expert configurations, and the request-level overhead of GPT-5 and Jev. We measure task accuracy (ACC), LLM token usage (do not include SLM), end-to-end (E2E) latency, and the number of generative-LLM API calls. For error-injection experiments, we additionally report attack success rate (ASR) and screening false-positive and true-positive rates (FPR/TPR). Detailed implementation settings, scoring rubrics, and evaluation protocols are provided in Appendix D.3.

5.2 End-to-End Quality and Efficiency

Table 1 compares Jev-LiteMAS with five baselines across four benchmarks and two generative backbones. Across tasks, Jev-LiteMAS maintains competitive accuracy with lower generative-LLM usage. Against LAS, it reduces total LLM tokens by 17.5–54.6% with DeepSeek-V4-Flash and 12.7–38.6% with GPT-5. The corresponding accuracy differences range from -0.67 to +0.66 percentage points

Table 2: Ablations of workflow organization and routing on IDRBench I3 and API-Bank. ACC is accuracy (%); Tok. counts generative-LLM tokens (K), excluding decision-model tokens; E2E is latency (s), and Calls counts generative-LLM API requests. SLM Router uses Qwen3-1.7B-Instruct. *Content-Blind* masks substantive expert and tool outputs only in the router input while preserving task information, legal actions, execution metadata, and inter-expert communication.

(a) Workflow organization

	IDRBench I3				API-Bank			
Method	ACC	Tok.	E2E	Calls	ACC	Tok.	E2E	Calls
Static	74.00	14.603	79.00	4.00	61.80	15.178	35.71	4.00
Heuristic	58.67	9.414	56.34	2.45	64.27	7.564	31.53	3.49
Planner-Replan	48.00	28.566	96.79	5.54	53.93	21.873	47.65	8.31
Jev-LiteMAS	**75.33**	10.233	72.40	2.47	**66.29**	9.869	35.34	4.00

(b) Routing and feedback

	IDRBench I3				API-Bank			
Method	ACC	Tok.	E2E	Calls	ACC	Tok.	E2E	Calls
LLM Router	68.67	27.713	133.27	4.88	65.62	15.418	56.13	7.56
SLM Router	64.00	13.511	81.74	3.06	61.35	11.764	39.15	4.81
Rule Router	26.67	9.592	62.02	2.52	38.43	8.762	35.75	3.87
Content-Blind	57.33	17.437	98.23	2.46	57.30	11.473	39.16	4.13
Jev Router	**75.33**	10.233	72.40	2.47	**66.29**	9.869	35.34	4.00

Table 3: Review robustness under injected agent errors on MATH and MBPP+. ACC(%) and ASR(%); Tok. denotes generative-LLM tokens; E2E is end-to-end latency (s). A dash denotes runs without injected errors.

	MATH				MBPP+			
Method	ACC↑	Tok.↓	E2E↓	ASR↓	ACC↑	Tok.↓	E2E↓	ASR↓
Clean-MAS	96.67	6,752	26.77	–	86.00	7,794	45.92	–
Attack-MAS	46.67	6,389	24.62	50.00	39.33	6,973	46.84	48.67
MAD	98.00	20,563	73.76	0.00	85.33	28,705	98.76	1.33
G-Safe	69.33	6,884	31.33	27.34	52.00	6,996	55.32	35.33
MAS-Shield	91.33	9,746	40.51	5.33	78.67	11,324	67.76	8.67
AgentMon.	92.67	13,569	53.45	4.00	81.33	14,480	83.86	6.00
XG-Guard	80.00	7,081	25.84	16.67	76.00	8,728	59.67	12.67
Clean-Jev	97.33	5,433	22.13	–	85.33	6,903	38.67	–
Attack-Jev	38.67	6,131	23.52	58.67	42.00	6,542	34.93	44.67
Jev–LLM	94.67	10,138	45.14	2.67	84.00	12,430	76.32	2.67
Ours	94.00	8,657	34.19	3.33	84.67	9,736	58.35	4.00

on DeepSeek and from -1.34 to +0.67 on GPT-5. On DeepSeek, our method obtains the highest MBPP+ accuracy (85.33%) and closely matches LAS on MATH, API-Bank, and IDRBench I3. On GPT-5, it matches LAS on MATH, improves IDRBench I3 accuracy by 0.67 points, and incurs modest reductions on MBPP+ and API-Bank. The resource savings also extend to execution time: Jev-LiteMAS reduces end-to-end latency relative to LAS on all four DeepSeek benchmarks and on three GPT-5 benchmarks. The largest reductions occur on IDRBench I3 with DeepSeek (45.8%) and API-Bank with GPT-5 (50.2%). GPT-5 MATH is the exception, with 30.04 s versus LAS's 25.91 s. MetaGPT achieves higher accuracy on DeepSeek IDRBench I3 (82.67% versus 75.33%) but uses substantially more tokens and API calls. These results demonstrate a favorable quality–efficiency trade-off through operation-level allocation of coordination and generation.

5.3 Workflow and Routing Ablations

Table 2 examines the effects of workflow organization and routing decisions on IDRBench I3 and API-Bank. Among the four workflow organizations, Jev-LiteMAS achieves the highest accuracy on both tasks, reaching 75.33% and 66.29%. Compared with Static, it improves accuracy by 1.33 and 4.49 points while reducing LLM tokens by 29.9% and 35.0%. Heuristic uses fewer tokens and runs faster, but its accuracy is lower, particularly on I3 (58.67%). Planner-Replan incurs the highest token usage and call counts, accompanied by the lowest accuracy in both tasks.

The routing ablation highlights the importance of decision backends and execution feedback. Jev Router outperforms LLM Router by 6.66 and 0.67 accuracy points on IDRBench I3 and API-Bank, while reducing generative-LLM tokens by 63.1% and 36.0%. Compared with Qwen3-1.7B-Instruct (SLM Router), Jev improves accuracy by 11.33 and 4.94 points, with 24.3% and 16.1% fewer generative-LLM tokens and lower end-to-end latency. Rule Router further reduces token usage but substantially degrades accuracy. Removing semantic feedback lowers accuracy from 75.33% to 57.33% on I3 and from 66.29% to 57.30% on API-Bank, with nearly unchanged LLM call counts. These results highlight the capable bounded decisions and substantive execution feedback for efficient routing.

5.4 Jev-Review and Screening Performance

Evaluation protocol and baselines. We evaluate local review on MATH and MBPP+ by injecting task-relevant errors into an intermediate artifact from a randomly selected expert, simulating hallucinations that enter subsequent collaboration. All measurements use DeepSeek-V4-Flash and report results at the task level. Clean-MAS and Attack-MAS characterize the underlying MAS before and after corruption; Clean-Jev and Attack-Jev provide corresponding Jev-workflow references. We compare five protective baselines: Multi-agent Debate [7] performs multi-round deliberation, G-Safeguard [28] uses topology-aware anomaly detection, MAS-Shield [26] employs staged auditing, AgentMonitor [2] monitors execution and supports corrections, and XG-Guard [21] detects anomalies through bi-level graph representations. We further include Jev–LLM Judge, which uses a generative judge, and Jev-LiteMAS, which screens with Jev and invokes LLM re-review on escalation. We measure final accuracy (ACC), attack success rate (ASR), generative-LLM tokens, and end-to-end latency; the separate screening experiment reports FPR and TPR.

End-to-end comparison. Table 3 summarizes task-level performance under injected errors. Attack-MAS drops to 46.67% and

Table 4: Jev, LLM, and SLM judging under clean and injected-error conditions. ACC and Rate are percentages; Rate denotes FPR (↓) for clean cases and TPR (↑) for attacks. Tok. counts generative-LLM tokens only; E2E is latency (s). SLM uses Qwen3-1.7B-Instruct.

Case	Judge	ACC	Rate	Tok.	E2E
MATH Clean	Jev	97.33	4.00	5,433	22.13
	LLM Judge	96.67	1.33	7,691	35.44
	SLM Judge	98.00	0.00	5,135	23.32
MATH Attack	Jev	94.00	95.33	8,657	34.19
	LLM Judge	94.67	96.67	10,138	45.14
	SLM Judge	68.67	61.33	7,149	42.33
MBPP+ Clean	Jev	85.33	6.67	6,903	38.67
	LLM Judge	86.67	5.33	9,110	53.71
	SLM Judge	84.67	0.67	7,678	41.17
MBPP+ Attack	Jev	84.67	91.33	9,736	58.35
	LLM Judge	84.00	92.00	12,430	76.32
	SLM Judge	48.00	44.67	9,315	63.18

39.33% accuracy on MATH and MBPP+, with attack success rates of 50.00% and 48.67%. Jev-LiteMAS raises accuracy to 94.00% and 84.67% and reduces attack success to 3.33% and 4.00%. Against MAS-Shield, it gains 2.67 and 6.00 accuracy points while using 11.2% and 14.0% fewer tokens. Multi-agent Debate attains the highest accuracy and lowest attack success rates among the protected configurations, accompanied by substantially higher resource use. Relative to Jev–LLM Judge, our method maintains similar task accuracy and reduces latency by 24.3% and 23.5%, respectively.

Table 4 compares Jev, LLM, and SLM judging under clean and corrupted outputs. Jev achieves true-positive rates of 95.33% on MATH and 91.33% on MBPP+, approaching the LLM judge's 96.67% and 92.00%. In contrast, the SLM Judge achieves only 61.33% and 44.67% TPR, indicating substantially weaker detection of injected errors. Interestingly, SLM Judge has lower clean-case false-positive rates (0.00% and 0.67%) than both Jev (4.00% and 6.67%) and LLM Judge (1.33% and 5.33%). This contrast suggests that fewer false alarms do not necessarily indicate reliable error detection. Despite slightly higher false-positive rates than LLM Judge, Jev reduces clean-case generative-LLM tokens by 29.4% and 24.2%, with latency reductions of 37.6% and 28.0%. Under corruption, token savings remain 14.6% and 21.7%, while maintaining detection rates close to those of the LLM judge. These findings demonstrate a favorable balance between screening reliability and generative-review overhead, which is not consistently achieved by a SLM judge.

5.5 Decision-Layer Overhead

We analyze the end-to-end latency and estimated model cost of Jev-LiteMAS with GPT-5 experts and Jev across four benchmarks. Figure 3 separates the contributions of generative GPT-5 requests and Jev decisions. GPT-5 accounts for most of the execution time, while Jev adds only 1.13–2.21 seconds per evaluation unit. The Jev share of end-to-end latency ranges from 2.92% on IDRBench I3 to 6.85% on MATH. The monetary breakdown follows a similar pattern. Under the work fees, Jev accounts for 1.56–2.14% of the LLM model



Figure 3: Latency and estimated model-cost breakdown of Jev-LiteMAS with GPT-5 experts and Jev routing across four benchmarks. (a) End-to-end latency and its GPT-5/Jev request-time components; (b) GPT-5 and Jev API fees.

cost across the four benchmarks. Overall latency ranges from 30.04 to 75.57 seconds, and the model cost from $0.00664 to $0.01766 per evaluation unit. These measurements show that the choice-based model layer introduces little direct overhead compared with generative expert execution, supporting the efficiency of operation-level capability allocation.

5.6 Additional Analyses.

We further examine the effect of generative-LLM call limits and heterogeneous expert backbones on Jev-LiteMAS. These experiments characterize quality–resource trends under different execution budgets and model assignments across expert handoffs; detailed results appear in Appendix C.

6 Conclusion

We presented Jev-LiteMAS, a multi-agent framework that leverages the complementary strengths of generative and decision models to reduce coordination overhead. Feedback-driven expert handoffs replace pre-generated execution plans with dynamic routing informed by prior expert outputs, while Jev-gated LLM re-review reserves generative feedback for artifacts requiring further examination or revision. Across four benchmarks and two generative backbones, Jev-LiteMAS reduces generative-LLM token usage by 12.7–54.6% relative to LAS, with accuracy differences within 1.34 percentage points and lower latency in seven of eight configurations. Ablation studies further highlight the importance of preserving substantive execution feedback, demonstrating that lightweight decisions and generative execution can jointly support efficient, high-quality multi-agent collaboration.

References

[1] Jacob Austin, Augustus Odena, Maxwell Nye, Maarten Bosma, Henryk Michalewski, David Dohan, Ellen Jiang, Carrie Cai, Michael Terry, Quoc Le, and Charles Sutton. 2021. Program Synthesis with Large Language Models. arXiv:2108.07732 https://arxiv.org/abs/2108.07732

[2] Chi-Min Chan, Jianxuan Yu, Weize Chen, Chunyang Jiang, Xinyu Liu, Weijie Shi, Zhiyuan Liu, Wei Xue, and Yike Guo. 2024. AgentMonitor: A Plug-and-Play Framework for Predictive and Secure Multi-Agent Systems. arXiv:2408.14972 https://arxiv.org/abs/2408.14972

[3] Lingjiao Chen, Matei Zaharia, and James Zou. 2024. FrugalGPT: How to Use Large Language Models While Reducing Cost and Improving Performance. *Transactions on Machine Learning Research* (2024). https://openreview.net/forum?id=cSimKw5p6R

[4] Weize Chen, Yusheng Su, Jingwei Zuo, Cheng Yang, Chenfei Yuan, Chi-Min Chan, Heyang Yu, Yaxi Lu, Yi-Hsin Hung, Chen Qian, Yujia Qin, Xin Cong, Ruobing Xie, Zhiyuan Liu, Maosong Sun, and Jie Zhou. 2024. AgentVerse: Facilitating Multi-Agent Collaboration and Exploring Emergent Behaviors. In *International Conference on Learning Representations*. https://proceedings.iclr.cc/paper_files/paper/2024/hash/578e65cdee35d00c708d4c64bce32971-Abstract-Conference.html

[5] DeepSeek. 2026. DeepSeek API Change Log: DeepSeek-V4-Flash. Official API documentation. V4-Flash release and V4.1-Flash compatibility changes. https://api-docs.deepseek.com/updates/

[6] Tobias Deußer, Lorenz Sparrenberg, and Rafet Sifa. 2026. Evaluating and Benchmarking the System One Model Jev. arXiv:2609.37647 [cs.CL] https://arxiv.org/abs/2609.37647

[7] Yilun Du, Shuang Li, Antonio Torralba, Joshua B. Tenenbaum, and Igor Mordatch. 2024. Improving Factuality and Reasoning in Language Models through Multiagent Debate. In *Proceedings of the 41st International Conference on Machine Learning (Proceedings of Machine Learning Research, Vol. 235)*. 11733–11763. https://proceedings.mlr.press/v235/du24e.html

[8] Zhibin Gou, Zhihong Shao, Yeyun Gong, Yelong Shen, Yujiu Yang, Nan Duan, and Weizhu Chen. 2024. CRITIC: Large Language Models Can Self-Correct with Tool-Interactive Critiquing. In *International Conference on Learning Representations*. https://proceedings.iclr.cc/paper_files/paper/2024/hash/fef126561bbf9d4467dbb8d27334b8fe-Abstract-Conference.html

[9] Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. 2021. Measuring Mathematical Problem Solving With the MATH Dataset. In *Proceedings of the Neural Information Processing Systems Track on Datasets and Benchmarks*, Vol. 1. https://datasets-benchmarks-proceedings.neurips.cc/paper_files/paper/2021/hash/be83ab3ecd0db773eb2dc1b0a17836a1-Abstract-round2.html

[10] Sirui Hong, Mingchen Zhuge, Jonathan Chen, Xiawu Zheng, Yuheng Cheng, Jinlin Wang, Ceyao Zhang, Zili Wang, Steven Ka Shing Yau, Zijuan Lin, Liyang Zhou, Chenyu Ran, Lingfeng Xiao, Chenglin Wu, and Jürgen Schmidhuber. 2024. MetaGPT: Meta Programming for a Multi-Agent Collaborative Framework. In *International Conference on Learning Representations*. https://proceedings.iclr.cc/paper_files/paper/2024/hash/6507b115562bb0a305f1958ccc87355a-Abstract-Conference.html

[11] Hazem Ibrahim and Yasir Zaki. 2026. Evaluating Decision Models for Text Annotation in Computational Social Science. arXiv:2609.24574 [cs.CL] https://arxiv.org/abs/2609.24574

[12] Dongming Jiang, Yi Li, and Bingzhe Li. 2026. Jev-Mem: System-One-Controlled Agentic Memory for Efficient AI Agents. arXiv:2609.23986 [cs.AI] https://arxiv.org/abs/2609.23986

[13] Guohao Li, Hasan Hammoud, Hani Itani, Dmitrii Khizbullin, and Bernard Ghanem. 2023. CAMEL: Communicative Agents for "Mind" Exploration of Large Language Model Society. In *Advances in Neural Information Processing Systems*, Vol. 36. https://proceedings.neurips.cc/paper_files/paper/2023/hash/a3621ee907def47c1b952ade25c67698-Abstract-Conference.html

[14] Jiawei Li. 2026. Fast Models, Slow Evidence: A Paired and Self-Audited Evaluation of System-1 Decision Models for LLM Agent Harnesses. arXiv:2610.02267 [cs.AI] https://arxiv.org/abs/2610.02267

[15] Minghao Li, Yingxiu Zhao, Bowen Yu, Feifan Song, Hangyu Li, Haiyang Yu, Zhoujun Li, Fei Huang, and Yongbin Li. 2023. API-Bank: A Comprehensive Benchmark for Tool-Augmented LLMs. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 3102–3116. doi:10.18653/v1/2023.emnlp-main.187

[16] Zhuofeng Li, Haoxiang Zhang, Seungju Han, Sheng Liu, Jianwen Xie, Yu Zhang, Yejin Choi, James Y. Zou, and Pan Lu. 2026. In-the-Flow Agentic System Optimization for Effective Planning and Tool Use. In *International Conference on Learning Representations*. https://proceedings.iclr.cc/paper_files/paper/2026/hash/52c4a736cd63b3c7bf52011a1f66f3f6-Abstract-Conference.html

[17] Jiawei Liu, Chunqiu Steven Xia, Yuyao Wang, and Lingming Zhang. 2023. Is Your Code Generated by ChatGPT Really Correct? Rigorous Evaluation of Large Language Models for Code Generation. In *Advances in Neural Information Processing Systems*, Vol. 36. https://proceedings.neurips.cc/paper_files/paper/2023/hash/43e9d647ccd3e4b7b5baab53f0368686-Abstract-Conference.html

[18] Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegreffe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, Shashank Gupta, Bodhisattwa Prasad Majumder, Katherine Hermann, Sean Welleck, Amir Yazdanbakhsh, and Peter Clark. 2023. Self-Refine: Iterative Refinement with Self-Feedback. In *Advances in Neural Information Processing Systems*, Vol. 36. https://papers.nips.cc/paper_files/paper/2023/hash/91edff07232fb1b55a505a9e9f6c0ff3-Abstract-Conference.html

[19] Isaac Ong, Amjad Almahairi, Vincent Wu, Wei-Lin Chiang, Tianhao Wu, Joseph E. Gonzalez, M. Kadous, and Ion Stoica. 2025. RouteLLM: Learning to Route LLMs from Preference Data. In *International Conference on Learning Representations*. https://proceedings.iclr.cc/paper_files/paper/2025/hash/5503a7c69d48a2f86fc00b3dc09de686-Abstract-Conference.html

[20] OpenAI. 2025. *GPT-5 System Card*. Technical Report. OpenAI. https://openai.com/index/gpt-5-system-card/

[21] Junjun Pan, Yixin Liu, Rui Miao, Kaize Ding, Yu Zheng, Quoc Viet Hung Nguyen, Alan Wee-Chung Liew, and Shirui Pan. 2026. Explainable and Fine-Grained Safeguarding of LLM Multi-Agent Systems via Bi-Level Graph Anomaly Detection. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*. 30491–30506. doi:10.18653/v1/2026.acl-long.1407

[22] Vasilis Perifanis, Nikolaos Pavlidis, and Symeon Symeonidis. 2026. SeLM-Route: Probabilistic Semantic Evidence for Large Language Model Routing. arXiv:2609.34736 [cs.AI] https://arxiv.org/abs/2609.34736

[23] Yuanhao Shen, Daniel Xavier de Sousa, Ricardo Marçal, Ali Asad, Hongyu Guo, and Xiaodan Zhu. 2025. Understanding Large Language Models' Ability on Interdisciplinary Research. Introduces IDRBench and its IDR Idea Integration (I3) task. arXiv:2507.15736 https://arxiv.org/abs/2507.15736

[24] Yu Sun, Junhao Xu, Jiajia Shi, and Zijin Yang. 2026. Type-Safe Is Not Error-Free: Typed Decision Models Follow the Option Name, Not the Definition Bound to It. arXiv:2609.26758 [cs.AI] https://arxiv.org/abs/2609.26758

[25] TypeSafe AI. 2026. Jev: Introduction and Typed Decision Primitives. Product documentation. Accessed 2026-10-12. https://docs.typesafe.ai/introduction

[26] Kaixiang Wang, Zhaojiacheng Zhou, Bunyod Suvonov, Jiong Lou, Zihan Wang, Yuxiang Zheng, Yidan Lin, Wutong Zhang, Xianghan Kong, Chentao Wu, and Jie Li. 2025. MAS-Shield: A Defense Framework for Secure and Efficient LLM MAS. arXiv:2511.22924 https://arxiv.org/abs/2511.22924

[27] Song Wang, Zhen Tan, Zihan Chen, Shuang Zhou, Tianlong Chen, and Jundong Li. 2025. AnyMAC: Cascading Flexible Multi-Agent Collaboration via Next-Agent Prediction. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 11555–11567. doi:10.18653/v1/2025.emnlp-main.584

[28] Shilong Wang, Guibin Zhang, Miao Yu, Guancheng Wan, Fanci Meng, Chongye Guo, Kun Wang, and Yang Wang. 2025. G-Safeguard: A Topology-Guided Security Lens and Treatment on LLM-based Multi-agent Systems. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*. 7261–7276. doi:10.18653/v1/2025.acl-long.359

[29] Zhexuan Wang, Yutong Wang, Xuebo Liu, Liang Ding, Miao Zhang, Jie Liu, and Min Zhang. 2025. AgentDropout: Dynamic Agent Elimination for Token-Efficient and High-Performance LLM-Based Multi-Agent Collaboration. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*. Association for Computational Linguistics, 24013–24035. doi:10.18653/v1/2025.acl-long.1170

[30] Qingyun Wu, Gagan Bansal, Jieyu Zhang, Yiran Wu, Beibin Li, Erkang Zhu, Li Jiang, Xiaoyun Zhang, Shaokun Zhang, Jiale Liu, Ahmed Hassan Awadallah, Ryen W. White, Doug Burger, and Chi Wang. 2024. AutoGen: Enabling Next-Gen LLM Applications via Multi-Agent Conversations. In *First Conference on Language Modeling*. https://openreview.net/forum?id=BAakY1hNKS

[31] Tiantong Wu and Wei Yang Bryan Lim. 2026. REFLEX with Jev for Efficient Selective Control in LLM Agents. arXiv:2609.26532 [cs.AI] https://arxiv.org/abs/2609.26532

[32] Dawei Xiang, Kexin Chu, Wenyan Xu, Wenhui Zhang, and Wei Zhang. 2026. LLM-as-Scheduler: Agentic Workflow Dynamic Scheduling. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*. Association for Computational Linguistics, 12752–12763. doi:10.18653/v1/2026.acl-long.581

[33] Zhao Xinjie, Fan Gao, Xingyu Song, Yingjian Chen, Rui Yang, Yanran Fu, Yuyang Wang, Yusuke Iwasawa, Yutaka Matsuo, and Irene Li. 2025. ReAgent: Reversible Multi-Agent Reasoning for Knowledge-Enhanced Multi-Hop QA. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 4067–4089. doi:10.18653/v1/2025.emnlp-main.202

[34] Yingxuan Yang, Huacan Chai, Shuai Shao, Yuanyi Song, Siyuan Qi, Renting Rui, and Weinan Zhang. 2025. AgentNet: Decentralized Evolutionary Coordination for LLM-based Multi-Agent Systems. In *Advances in Neural Information Processing Systems*, Vol. 38. doi:10.52202/085713-3578

[35] Yanwei Yue, Guibin Zhang, Boyang Liu, Guancheng Wan, Kun Wang, Dawei Cheng, and Yiyan Qi. 2025. MasRouter: Learning to Route LLMs for Multi-Agent Systems. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*. Association for Computational

Linguistics, 15549–15572. doi:10.18653/v1/2025.acl-long.757

[36] Guibin Zhang, Luyang Niu, Junfeng Fang, Kun Wang, Lei Bai, and Xiang Wang. 2025. Multi-agent Architecture Search via Agentic Supernet. In *Proceedings of the 42nd International Conference on Machine Learning (Proceedings of Machine Learning Research, Vol. 267)*. PMLR, 75834–75852. https://proceedings.mlr.press/v267/zhang25bi.html

[37] Guibin Zhang, Yanwei Yue, Zhixun Li, Sukwon Yun, Guancheng Wan, Kun Wang, Dawei Cheng, Jeffrey Xu Yu, and Tianlong Chen. 2025. Cut the Crap: An Economical Communication Pipeline for LLM-based Multi-Agent Systems. In *International Conference on Learning Representations*. https://proceedings.iclr.cc/paper_files/paper/2025/hash/bbc461518c59a2a8d64e70e2c38c4a0e-Abstract-Conference.html

[38] Guibin Zhang, Yanwei Yue, Xiangguo Sun, Guancheng Wan, Miao Yu, Junfeng Fang, Kun Wang, Tianlong Chen, and Dawei Cheng. 2025. G-Designer: Architecting Multi-agent Communication Topologies via Graph Neural Networks. In *Proceedings of the 42nd International Conference on Machine Learning (Proceedings of Machine Learning Research, Vol. 267)*. PMLR, 76678–76692. https://proceedings.mlr.press/v267/zhang25cu.html

[39] Jiayi Zhang, Jinyu Xiang, Zhaoyang Yu, Fengwei Teng, XiongHui Chen, Jiaqi Chen, Mingchen Zhuge, Xin Cheng, Sirui Hong, Jinlin Wang, Bingnan Zheng, Bang Liu, Yuyu Luo, and Chenglin Wu. 2025. AFlow: Automating Agentic Workflow Generation. In *International Conference on Learning Representations*. https://proceedings.iclr.cc/paper_files/paper/2025/hash/5492ecbce4439401798dcd2c90be94cd-Abstract-Conference.html

[40] Yaolun Zhang, Xiaogeng Liu, and Chaowei Xiao. 2025. MetaAgent: Automatically Constructing Multi-Agent Systems Based on Finite State Machines. In *Proceedings of the 42nd International Conference on Machine Learning (Proceedings of Machine Learning Research, Vol. 267)*. PMLR, 75667–75694. https://proceedings.mlr.press/v267/zhang25bc.html

[41] Zihan Zhou, Xinzhe Hu, Hanxu Yang, Liangjian Wen, and Zhao Kang. 2026. Token-Efficient Multi-Agent Collaboration via System One-Guided Computational Division of Labor. arXiv:2610.08155 [cs.MA] https://arxiv.org/abs/2610.08155

A Reproducibility Statement

We provide the experimental configurations, dataset sampling procedures, and evaluation protocols in the main text and appendices to support reproducibility. Due to space limitations, the complete implementation details and prompt templates cannot be fully included in the paper. To facilitate independent verification and reproduction of our results, we provide an anonymous repository containing the full implementation, workflow configurations, and prompt templates, available at https://anonymous.4open.science/status/jevlite-mas-2312.

B Limitations and Future Work

Jev-LiteMAS has two limitations. First, feedback-driven routing operates over a predefined pool of expert roles and legal actions. Although this supports lightweight and structured coordination, the framework does not dynamically create new experts or reconfigure their roles for previously unseen task requirements. Extending expert selection to more adaptive collaboration structures is a promising direction. Second, the efficiency of Jev-gated LLM re-review depends on the distribution of intermediate artifact quality. When a larger proportion of artifacts requires generative review or revision, the achievable token and latency savings may decrease. Future work could explore adaptive review policies that account for task difficulty and varying artifact quality.

C Additional Experimental Analyses

We analyze the effects of generative-LLM call limits and heterogeneous expert assignment on execution quality and resource use.

C.1 Sensitivity to Generative-LLM Call Budgets

We study how the maximum number of generative-LLM calls affects execution quality and resource consumption on IDRBench I3 and API-Bank. Table 5 reports accuracy, token usage, latency, and actual LLM calls under budgets of two, three, four, and six calls.

On I3, accuracy rises from 46.67% at a budget of two to 70.00% at four, then reaches 73.33% at six. The corresponding average number of calls increases from 2.00 to only 2.64, indicating that the workflow does not exhaust the larger allowance on every task. API-Bank follows a similar quality trend: accuracy increases from 56.18% to 64.72% between budgets two and four, and reaches 65.84% at six. Its average call count rises from 2.00 to 4.46.

Larger budgets also increase the opportunities for further expert contributions, together with additional token and latency costs. On API-Bank, token usage and latency fluctuate across intermediate budgets, reflecting changes in the executed trajectories. Overall, the strongest quality gains occur when moving beyond the tightest call limits.

C.2 Heterogeneous Expert Backbones

We evaluate heterogeneous expert execution by assigning two generative backbones (Deepseek V4-flash and GPT5), denoted A and B, to successive expert steps. AAA keeps the same backbone throughout the trajectory. ABB switches from A to B at the first handoff and then continues with B, while ABA switches backbone at every handoff. All three configurations use the same Jev-based coordination workflow.

Table 5: Sensitivity to generative-LLM call budgets and heterogeneous expert backbones on IDRBench I3 and API-Bank. ACC is in percent; Tok. denotes total generative-LLM tokens in thousands; E2E denotes end-to-end latency in seconds; Calls denotes average generative-LLM API calls. In (b), AAA uses one backbone throughout, ABB switches backbone at the first expert handoff, and ABA switches at every handoff.

	IDRBench I3				API-Bank			
Setting	ACC↑	Tok.↓	E2E↓	Calls↓	ACC↑	Tok.↓	E2E↓	Calls↓
(a) Generative-LLM call budget								
$B = 2$	46.67	7.637	43.86	2.00	56.18	10.713	16.12	2.00
$B = 3$	62.67	9.496	56.01	2.26	57.08	12.040	20.63	2.93
$B = 4$	70.00	10.514	68.19	2.48	64.72	14.553	18.34	3.96
$B = 6$	73.33	11.298	71.88	2.64	65.84	12.817	20.16	4.46
(b) Heterogeneous expert backbones								
AAA	75.33	10.233	72.40	2.47	66.29	9.869	35.34	4.00
ABB	76.67	11.387	75.97	2.49	66.07	12.924	37.50	4.23
ABA	78.00	14.536	78.62	2.52	64.49	13.518	36.99	4.39

As shown in Table 5, IDRBench I3 accuracy increases from 75.33% with AAA to 76.67% with ABB and 78.00% with ABA. The higher I3 scores are accompanied by increased token consumption, from 10.233K to 11.387K and 14.536K, respectively, and modestly longer execution times.

On API-Bank, accuracy is 66.29%, 66.07%, and 64.49% for AAA, ABB, and ABA. Token usage rises from 9.869K to 12.924K and 13.518K, while average calls increase from 4.00 to 4.23 and 4.39.

The results demonstrate that the workflow supports switching expert backbones across handoffs. They also reveal task-dependent trade-offs between heterogeneous expert allocation, execution quality, and model usage.

D Cascaded Review: Protocol and Analysis

This section details the escalation and revision workflow, and analyzes how artifact quality and screening reliability jointly affect generative review overhead and error propagation.

D.1 Escalation and Re-entry

At a review checkpoint, Jev screens artifact y_t using the context and review criteria in s_t. A pass releases the artifact to ordinary routing. An escalate forwards the same information to G_{review}, which returns verdict v_t and feedback c_t. If the LLM accepts the artifact, routing resumes. If revision is required, the runtime attaches (v_t, c_t) to the state and invokes the assigned expert, as formalized in Eq. 11. The revised artifact enters the configured screening procedure at its next checkpoint. Repeated review and repair consume workflow budget. Local acceptance and the STOP action remain separate: only the latter enters task finalization.

D.2 Escalation, Savings, and Reliability

Let $\mathcal{R}$ be the completed screening operations, including repeated checks after revision. Every escalation triggers one LLM re-review,

giving the observed escalation fraction

$$\widehat{\rho}_{\text{esc}} = \frac{\sum_{t\in\mathcal{R}} \mathbf{1}\{d_t = \text{escalate}\}}{|\mathcal{R}|}. \tag{12}$$

Let π denote the fraction of artifacts requiring correction, r the detection rate Pr(escalate | error), and f the false-escalation rate Pr(escalate | acceptable). The expected fraction of artifacts forwarded to the LLM is

$$\rho_{\text{esc}} = \pi r + (1-\pi)f. \tag{13}$$

When most artifacts are acceptable (π is small), a low f allows the majority to bypass generative review. Thus, review-call savings follow directly from the prevalence of acceptable outputs and the screen's ability to release them.

For a simplified fixed per-call screening cost C_J and LLM review cost C_L, the expected review-stage cost per checkpoint is

$$C_{\text{cascade}} = C_J + \rho_{\text{esc}} C_L. \tag{14}$$

Relative to LLM review at every checkpoint, this stage saves cost when $C_J < (1-\rho_{\text{esc}})C_L$. Full-workflow accounting also includes routing, expert generation, revisions, and repeated checks.

The main reliability risk is erroneous release. Its unconditional probability is

$$\Pr(\text{error}, \text{pass}) = \pi(1-r). \tag{15}$$

These errors do not enter the LLM re-review branch. Consequently, detection and false-escalation rates must be assessed alongside final task quality and resource use. The prevalence π comes from natural workflow traces; controlled error-injection class ratios do not estimate it.

D.3 Experimental Protocol

Dataset sampling. We evaluate all methods on identical, fixed subsets of four benchmarks to ensure comparable experimental conditions. For MATH [9], MBPP+ [1, 17], and IDRBench I3 [23], we use stratified random sampling with seed 42, preserving the proportions of task categories in each benchmark. We sample 150 instances from each benchmark. For API-Bank [15], we sample 150 episodes using the same random seed, comprising 445 API-call prediction points in total. All compared methods are evaluated on the same sampled instances.

Task-specific evaluation. We evaluate the final task outputs using the native evaluation criteria of each benchmark. For MATH, we extract the final answer and compute accuracy using mathematical equivalence checking, without requiring exact textual matching. For MBPP+, we execute generated programs using EvalPlus and report pass@1, counting an instance as successful only when it passes both the base and extended test suites. For API-Bank, given the interaction history, the model predicts the next API invocation. A prediction is counted as correct only when the API name is correct and the official checker validates the arguments and execution result. We report strict accuracy over the 445 API-call prediction points. For IDRBench I3, accuracy is the proportion of evaluation instances whose predicted integrable/non-integrable labels match the dataset ground truth, with invalid outputs counted as incorrect.

Resource accounting. For each evaluation instance, we collect provider-reported input and output token usage across the corresponding generative-LLM requests and aggregate them at the task level. We report the average input, output, and total generative-LLM tokens per instance. Dollar-denominated model costs are calculated from the recorded token usage and the corresponding model pricing, then averaged over the evaluation instances. End-to-end latency and the number of generative-LLM API calls are recorded from local execution logs for each complete task and averaged over the sampled instances. For API-Bank, these resource metrics are aggregated per episode rather than per API-call prediction point. This accounting separates final task accuracy from the computational resources consumed by the complete multi-agent workflow.

E Workflow Pseudocode

Algorithm 1 summarizes the complete Jev-LiteMAS workflow, including feedback-driven expert handoffs, Jev-gated LLM re-review, and corrective revision.

Algorithm 1 Jev-LiteMAS Workflow

Require: Task x, expert pool $\mathcal{E}$, configuration Γ
Ensure: Final task output

$(s, e) \leftarrow \textsc{Initialize}(x, \Gamma)$
while BudgetAvailable(s) **do**
  $y \leftarrow G_e(s)$
  $s \leftarrow U(s, e, y)$
  ▷ Jev-gated LLM re-review
  if ReviewPoint(s) **then**
    while BudgetAvailable(s) **do**
      $d \leftarrow J_{\text{screen}}(s)$
      if d = pass **then**
        break
      end if
      $(v, c) \leftarrow G_{\text{review}}(s)$
      if v = accept **then**
        break
      end if
      $e_r \leftarrow \textsc{AssignRepairExpert}(s)$
      $\tilde{s} \leftarrow s \oplus (v, c)$
      $y \leftarrow G_{e_r}(\tilde{s})$
      $s \leftarrow U(\tilde{s}, e_r, y)$
    end while
  end if
  if not BudgetAvailable(s) **then**
    break
  end if
  ▷ Feedback-driven expert handoff
  $\mathcal{A} \leftarrow \textsc{LegalActions}(s)$
  $a \leftarrow J_{\text{route}}(s, \mathcal{A})$
  if a = STOP **then**
    return Finalize(s)
  end if
  $e \leftarrow a$
end while
return $\textsc{HandleBudgetExhaustion}(s, \Gamma)$