arXiv:2610.20350v1 [cs.AI] 14 Oct 2026

Lifted State Policy Optimization: Internalizing Self-Correction through Transition Geometry

Ren Zhuang **Ben Wang**[†] **Shuifa Sun**[†]
Hangzhou Normal University
venomrko97@gmail.com, {20170056, watersun}@hznu.edu.cn

Abstract

Preference optimization ranks final answers and trajectory RL maximizes aggregate returns, yet neither credits the local change that turns a flawed reasoning state into a better one. We introduce *Lifted State Policy Optimization (LSPO)*, which establishes this finite, cost-adjusted transition as the primary unit of learning. Each textual answer is augmented with a learned continuous coordinate, forming a lifted state that an energy function evaluates and orders. A shaped reward drives energy descent net of edit and step costs, and an internalization loss absorbs selected low-energy answers into the direct generator. On Qwen3.5-27B, the resulting single-pass policy reaches 71.8% aggregate accuracy across mathematics, science, code, and logic benchmarks, matching test-time reflection at 71.9% with 28% lower latency and 25.8% fewer tokens. The pattern holds across dense and mixture-of-experts backbones, and matched controls confirm that transition credit and the lifted coordinate each contribute, as does answer internalization. Our code is available at `https://github.com/Venomrko/lspo`.



Figure 1 | Improvements found during training persist in direct generation. On Qwen3.5-27B, the LSPO policy attains the highest aggregate direct pass@1 and pass@16 accuracy across benchmarks in the left panels, selected training endpoints align closely with deployed outputs in the top right, and final energy separates correct from incorrect answers in the bottom right.

[†]Corresponding author.

40th Conference on Neural Information Processing Systems (NeurIPS 2026).

1 Introduction

Even strong language models make local mistakes within otherwise sound reasoning, and one faulty step can invalidate the final answer [Uesato et al., 2022, Lightman et al., 2023]. Inference methods address this through chain of thought, self-consistency, critique, and repeated refinement [Wei et al., 2022, Wang et al., 2022, Madaan et al., 2023, Shinn et al., 2023], and large reasoning models extend deliberation into long trajectories [Shao et al., 2024, Zelikman et al., 2024, Guo et al., 2025]. These procedures improve difficult answers, but their gains require additional sampling budgets or persistent refinement loops at deployment. Training can absorb useful corrections into the policy itself, removing this cost.

A central question is defining the appropriate unit of supervision. Current objectives provide supervision at coarse granularity; preference optimization ranks complete outputs [Rafailov et al., 2023, Hong et al., 2024, Meng et al., 2024, Liu et al., 2025b], trajectory RL maximizes aggregate returns over full rollouts [Ouyang et al., 2022, Schulman et al., 2017], and self-correction methods learn from entire refinement traces [Kumar et al., 2024, Ma et al., 2025]. Each focuses on endpoints or full trajectories, leaving the local transition that resolves a flawed reasoning state as an unmodeled unit of credit. We formalize this gap through *transition credit*, where the unit of learning is a finite state transition, evaluated by the decrease in a learned energy function net of edit and step costs [Sutton et al., 1998, Kaufmann et al., 2024, Lambert, 2025].

We introduce **L**ifted **S**tate **P**olicy **O**ptimization (**LSPO**). LSPO augments the textual answer x with a continuous coordinate z, forming a lifted state $s = (x, z)$ that carries refinement context beyond discrete surface text. An energy function $\tilde{E}(s; q)$ orders candidate states; a shaped reward favors transitions that decrease energy net of edit and step costs; and an internalization loss trains the generator to produce selected low-energy answers directly from the original input.

We evaluate LSPO across the Qwen3.5 family [Qwen Team, 2026] on mathematics [Hendrycks et al., 2021, Zhang and Math-AI, 2025], science [Rein et al., 2024, Wang et al., 2024], executable code [Jain et al., 2024], and logic [Lin et al., 2025]. On Qwen3.5-27B, the single-pass policy reaches 71.8% aggregate accuracy, matching test-time reflection at 71.9% with 28% lower latency and 25.8% fewer tokens. The pattern holds across scales, reaching 60.8% at 9B and 72.6% on the 35B-A3B mixture-of-experts backbone. At the mechanism level, as reported in Figure 1, LSPO converts 6.4% of incorrect answers to correct while regressing only 1.7%, yielding a 4.7-point net transition gain.

Our core contributions are threefold.

- **Single-pass reliability.** Absorbing selected low-energy endpoints relocates deliberation from inference into training; the deployed policy reaches reflective accuracy in a single pass, across dense and mixture-of-experts backbones.
- **Cost-adjusted transition credit.** LSPO establishes a finite state transition as the primary unit of learning, scored by energy decrease net of edit and step costs. Unlike a step-level score, this quantity is relative to a prompt's candidate pool, steering policy movement rather than global state ranking. Bounded energy error perturbs cumulative credit only through the endpoints, and removing the progress reward costs more net gain than removing any other component.
- **Lifting as refinement context.** A learned continuous coordinate carries information about constructive transitions that surface text alone does not; probes on held-out transitions show higher action prediction and energy ranking, while shuffled or zeroed coordinates eliminate this advantage.

2 Method

2.1 Overview

LSPO learns local directions of improvement in a lifted state space and transfers selected answers into a direct policy. It combines a continuous coordinate for refinement context, an energy objective for crediting finite state changes, and an internalization loss that trains the generator on selected answers. Figure 2 contrasts this localized mechanism with paradigms centered on terminal answers or aggregate returns.



Figure 2 | Comparison of training paradigms. Preference learning in the top left panel optimizes static final answers, while trajectory RL in the top right panel maximizes returns across full rollouts. LSPO in the bottom panel assigns credit to local transitions and internalizes selected endpoints.

2.2 Lifted State

Standard optimization procedures target a distribution $p_\theta(y \mid q)$ over complete outputs for a given input q, masking the intermediate dynamics of local revisions. To expose these dynamics for training, we cast local improvement as a Markov decision process in an augmented state space. We define a lifted state

$$s_t = (x_t, z_t), \tag{1}$$

where x_t represents the surface text and z_t is a continuous auxiliary coordinate. The auxiliary coordinate is initialized from the input and current answer, updated by the transition block, and projected away when the final answer is written back into text.

We introduce an energy function

$$\tilde{E}(s_t; q) = \tilde{E}(x_t, z_t; q), \tag{2}$$

to evaluate state quality. The energy head orders candidate states and defines which answer becomes the target for direct generation. The policy induces a transition distribution $P_\theta(s_{t+1} \mid s_t, a_t, q)$. Training optimizes the action policy $\pi_\theta(a_t \mid s_t, q)$ to favor short sequences whose transitions reduce energy.

Because surface text is discrete, moves are finite and are evaluated within visited neighborhoods.

2.3 Training Procedure

The training phase constructs short moves in the lifted state space. At each step, the policy samples an action $a_t \in \{\text{revise}, \text{switch}, \text{stop}\}$ from $\pi_\theta(a_t \mid s_t, q)$ to modify the surface text, move the auxiliary coordinate toward an alternative refinement mode, or halt within the current local basin. The frozen projection initializes z_0; Revise recursively updates z_t, and Switch resets z_t before a residual update. The primary configuration uses $d_z = 8$, and the energy head scores the resulting state. The resulting sequence is $\tau = (s_0, a_0, s_1, a_1, \ldots, s_T)$. Section C defines the edit metric, rollout collection, advantage estimator, and complete training procedure.

2.4 Energy Model and Selection

The energy model establishes an ordering over candidate states that guides both local transitions and final answer selection. It operates as a scalar head over (q, x_t, z_t), shared across training families and fitted on sampled states. Gold answers and executable checkers provide scalar supervision. Verified candidates receive lower energy than unsuccessful ones, with ties broken by shorter edit distance and lower step cost. Pairs are formed within each prompt's candidate rollouts, assigning lower energy to verified states than to failed or perturbed alternatives.

Selection uses the same object. The generated sequence induces a candidate set $\mathcal{C}(q)$ containing the direct answer state and its successors. The method selects the state with the lowest energy

$$s^*(q) = \arg\min_{s \in \mathcal{C}(q)} \tilde{E}(s; q) \tag{3}$$

and sets $x_T^*(q)$ to be its surface text component as the transfer target. The model is trained to emit $x_T^*(q)$ from the original input. Before policy training, we fit and freeze the entire scoring branch, encompassing the text encoder, lift projection, transition block, and energy head, as detailed in Section C.

2.5 Objective

The LSPO objective unifies shaped reinforcement learning over intermediate transitions with answer internalization. The reward for stepwise progress is formulated as

$$r_t = \tilde{E}(s_t; q) - \tilde{E}(s_{t+1}; q) - \lambda_{\text{edit}} d(x_{t+1}, x_t) - \lambda_{\text{step}}, \tag{4}$$

for Revise and Switch. Stop preserves the current state and yields zero reward. Here d penalizes surface edits and λ_{step} regularizes trajectory length. We index the T text-changing moves by $t = 0, \ldots, T-1$; an optional final Stop contributes zero to their sum.

Proposition 1 (Telescoping Trajectory Reward)**.** *For an input q and a finite trajectory $\tau = (s_0, a_0, \ldots, s_T)$, the cumulative shaped reward $R(\tau; q) = \sum_{t=0}^{T-1} r_t$ satisfies*

$$R(\tau; q) = \tilde{E}(s_0; q) - \tilde{E}(s_T; q) - \lambda_{\text{edit}} \sum_{t=0}^{T-1} d(x_{t+1}, x_t) - \lambda_{\text{step}} T. \tag{5}$$

Because intermediate energy terms telescope, cumulative return reflects net endpoint improvement minus total accrued penalties. The proof appears in Section C.

The same telescoping structure provides robustness to scoring error. When training energy differs from $\tilde{E}$ by at most ε at visited states, cumulative reward shifts by at most 2ε through the endpoints alone, preserving the ranking of trajectories separated by more than 2ε, as established in Proposition 4 and Corollary 2.

At update k, the rollout snapshot $\bar{\theta}_k$ fixes the initial-state distribution $\rho_{\bar{\theta}_k}$ and text-proposal kernel $K_{\bar{\theta}_k}$. Controller RL uses the per-update objective

$$J_{\text{ctrl}}^{(k)}(\theta) = \mathbb{E}_{\tau \sim P_{\rho_{\bar{\theta}_k}, \pi_\theta, K_{\bar{\theta}_k}}} \Big[\sum_t r_t - \beta \sum_t D_{\text{KL}}(\pi_\theta(\cdot \mid s_t, q) \| \pi_{\text{ref}}(\cdot \mid s_t, q)) \Big], \tag{6}$$

where the action KL includes Stop. The initialization and proposal mechanisms are held fixed within an update and refreshed for the next one. The visited-state KL follows regularized policy optimization [Schulman et al., 2015, 2017, Ouyang et al., 2022, Guo et al., 2025].

To absorb the selected improvements into the generator, we incorporate a loss for selected internalization

$$J_{\text{SI}}(\theta) = \mathbb{E}_q \left[\log p_\theta(x_T^*(q) \mid q) \right], \tag{7}$$

where $x_T^*(q)$ denotes the selected final output with the lowest energy produced during the alignment phase. The final objective is

$$J_{\text{LSPO}}^{(k)}(\theta) = J_{\text{ctrl}}^{(k)}(\theta) + \alpha J_{\text{SI}}(\theta). \tag{8}$$

Task feedback supplies the supervision used to fit the energy ordering.

Formal properties of the objective appear in the appendices. In particular, the internalization loss corresponds to a forward KL projection onto the selected answer distribution in Section D, while Section A gives a path-distribution relaxation and an information criterion for useful lifting.

At deployment, the compiled conditional distribution serves each answer through direct generation, requiring no auxiliary lifted-state computation during inference.

3 Experiments

We investigate whether geometry-inspired transition credit produces reliable direct reasoning. The main text tests answer quality, preservation of correct states, deployment cost, component contributions, and training dynamics; benchmark-level held-out evaluations and supplemental transfer tests appear in Section E.

Table 1 | Main results across Qwen3.5 backbones. LSPO achieves the highest aggregate accuracy among the listed baselines that generate directly under both pass@1 and pass@16 evaluation, with frontier models included as scale references.

Model	Method	MATH-500		AIME25		GPQA		LCB		ZebraLogic		MMLU-Pro		Average	
		@1	@16	@1	@16	@1	@16	@1	@16	@1	@16	@1	@16	@1	@16
Qwen3.5-9B	Base	84.8	93.6	39.6	57.2	45.8	61.4	41.9	48.6	60.2	73.4	56.3	68.8	54.8	67.2
	DPO	85.6	94.1	40.9	58.3	46.6	62.3	43.1	50.1	61.2	74.3	57.2	69.7	55.8	68.1
	Step-DPO	86.4	94.7	42.7	60.5	47.5	63.5	44.4	52.0	62.4	75.3	58.1	70.8	56.9	69.5
	GRPO	87.6	95.3	46.0	65.0	49.1	66.4	46.6	55.0	64.4	77.0	59.8	72.7	58.9	71.9
	GDPO	88.0	95.5	46.6	65.9	50.0	**67.8**	47.4	55.9	65.1	77.5	**60.6**	**73.7**	59.6	72.7
	SCoRe	88.0	95.8	46.4	66.1	49.5	67.6	47.4	56.2	65.0	77.8	60.0	73.3	59.4	72.8
	LSPO (**Ours**)	**89.0**	**95.9**	**49.0**	**69.2**	**50.2**	67.7	**49.2**	**58.4**	**66.9**	**78.9**	60.5	73.1	**60.8**	**73.9**
Qwen3.5-27B	Base	90.8	96.8	61.7	76.4	55.6	67.2	53.4	61.3	69.8	80.7	64.1	74.6	65.9	76.2
	DPO	91.6	97.3	63.0	77.5	56.4	68.1	54.6	62.8	70.8	81.6	65.0	75.5	66.9	77.1
	Step-DPO	92.4	97.9	64.8	79.7	57.3	69.3	55.9	64.7	72.0	82.6	65.9	76.6	68.0	78.5
	GRPO	93.6	98.5	68.1	84.2	58.9	72.2	58.1	67.7	74.0	84.3	67.6	78.5	70.0	80.9
	GDPO	94.0	98.7	68.7	85.1	59.8	**73.6**	58.9	68.6	74.7	84.8	**68.4**	**79.5**	70.8	81.7
	SCoRe	94.1	**99.1**	68.8	85.6	59.5	**73.6**	59.1	69.1	74.8	85.3	68.0	79.3	70.7	82.0
	LSPO (**Ours**)	**94.9**	99.0	**70.8**	**88.1**	**59.9**	73.4	**60.5**	**70.9**	**76.3**	**86.0**	68.2	78.8	**71.8**	**82.7**
Qwen3.5-35B-A3B	Base	91.9	97.2	65.4	79.8	57.1	68.9	55.8	63.6	71.4	81.8	65.2	75.1	67.8	77.7
	DPO	92.7	97.7	66.7	80.9	57.9	69.8	57.0	65.1	72.4	82.7	66.1	76.0	68.8	78.7
	Step-DPO	93.5	98.3	68.5	83.1	58.8	71.0	58.3	67.0	73.6	83.7	67.0	77.1	70.0	80.0
	GRPO	94.4	98.7	71.2	86.9	60.1	73.5	60.0	69.4	75.2	85.0	68.4	78.7	71.6	82.0
	GDPO	94.8	98.9	71.8	87.8	**61.0**	**74.9**	60.9	70.4	75.9	85.5	**69.2**	**79.7**	72.3	82.9
	SCoRe	94.7	**99.0**	71.5	87.9	60.5	74.7	60.7	70.5	75.7	85.7	68.6	79.3	71.9	82.9
	LSPO (**Ours**)	**95.2**	98.8	**72.9**	**89.7**	60.6	74.1	**61.6**	**71.7**	**76.8**	**86.1**	68.5	78.5	**72.6**	**83.1**
gpt-oss-120b		96.3	99.0	81.8	91.6	75.6	82.4	61.7	70.9	80.4	87.5	80.8	86.1	79.4	86.2
Claude Sonnet 4.5		97.0	99.1	87.0	94.2	83.4	89.0	66.8	75.0	83.6	90.0	82.2	87.0	83.3	89.0

3.1 Protocol

Models. We evaluate LSPO across the Qwen3.5 family [Qwen Team, 2026] to assess scaling dynamics. Qwen3.5-27B is the primary model for component and mechanism analysis; Qwen3.5-35B-A3B supplies transfer evidence for the mixture-of-experts setting alongside its architectural ablation. We also include reference metrics from gpt-oss-120b [OpenAI, 2025] and Claude Sonnet 4.5 [Anthropic, 2025].

Benchmarks. The evaluation spans six suites covering MATH-500 [Hendrycks et al., 2021], AIME25 [Zhang and Math-AI, 2025], GPQA [Rein et al., 2024], LiveCodeBench [Jain et al., 2024], ZebraLogic [Lin et al., 2025], and MMLU-Pro [Wang et al., 2024]. Code tasks measure execution validity through pass@k evaluation [Chen et al., 2021]. We additionally incorporate GSM8K [Cobbe et al., 2021], ARC-Challenge [Clark et al., 2018], BBH [Suzgun et al., 2023], HumanEval [Chen et al., 2021], and MBPP [Austin et al., 2021] to assess transfer to task families outside the training distribution.

Baselines. We compare LSPO against several baselines, including the preference optimization methods DPO [Rafailov et al., 2023] and Step-DPO [Lai et al., 2024], the RL approaches GRPO [Guo et al., 2025] and GDPO [Panaganti et al., 2026], and SCoRe [Kumar et al., 2024], a self-correction method that learns directly from revision traces generated by the model. Matched training alternatives for candidate selection, answer internalization, coordinate controls, and test-time reflection complement these primary baselines.

Implementation Details. All primary comparisons use fixed configurations across random seeds 42, 1234, and 3407. The primary runs use short training sequences with $T_{\max} = 6$, top-p 0.95, an 8-dimensional auxiliary lift $d_z = 8$, and an internalization weight of 0.3. Section C details optimizers, sampling parameters, sweep ranges, matched training alternatives, and extended analyses. The deployment comparison reports direct pass@1 generation for LSPO alongside an iterative reflection baseline evaluated with two inference passes under identical seeds and settings. Training targets use verifiers and search; the deployment comparison samples from the trained conditional model.

3.2 Main Results



Figure 3 | Quality, sampling, revision, and token cost on Qwen3.5-27B. LSPO reaches 71.8% accuracy at 10.9 s latency in a single pass; test-time reflection adds 0.1 points but costs 4.3 s more and 440 additional tokens. LSPO remains above the pass@k curve, most often converts incorrect answers to correct ones, and avoids the long latency tail of repeated refinement.

Overall Performance. Table 1 reports direct pass@1 accuracy across six benchmark suites. LSPO achieves the highest aggregate accuracy among direct-generation baselines on each Qwen3.5 backbone, with the largest margins on structured reasoning tasks, including MATH-500, AIME25, ZebraLogic, and LiveCodeBench, where local intermediate state transitions crucially govern final outcomes. On the knowledge-oriented GPQA and MMLU-Pro benchmarks, LSPO improves over the base model while maintaining a compact direct-generation profile. The pattern holds across all three backbones in Section B, with the largest improvements at 9B and 27B where exploration has more headroom to reshape generation.

Deployment Efficiency. Figure 3 shows the LSPO policy reaching 71.8% aggregate accuracy with 10.93 s average latency and 1265 output tokens. It remains above the pass@k curve across sampled budgets and executes the highest volume of constructive edits. Test-time reflection reaches 71.9% with 15.18 s and 1705 tokens across two inference passes. LSPO thus achieves comparable observed accuracy in a single pass with 4.25 s lower latency and 440 fewer tokens per answer, serving each answer directly through the compiled generator.

3.3 Mechanism Analyses

Preserving Improvements. Table 2 measures whether policies retain improvements found along training paths while protecting correct states. Over the same paired-answer denominator, LSPO repairs 6.4% and damages 1.7% of answers, yielding a 4.7-point net gain. It records the lowest direct energy of 0.398 and terminal energy of 0.195 among methods with an energy head; the terminal value bounds exploration capacity during training, while the direct value measures whether improvements are internalized into the policy. The span audit preserves 95.8% of initially valid spans and yields a 16.0-point net validity gain as detailed in Section D.

Table 2 | Preservation of improvements on Qwen3.5-27B. LSPO yields the highest net gain and lowest energy across all methods.

Method	Net gain	Direct E	Terminal E
Base	0.0	0.468	N/A
DPO	1.8	0.450	N/A
Step-DPO	2.5	0.438	N/A
GRPO	3.3	0.420	0.203
GDPO	4.0	0.411	0.201
SCoRe	3.6	0.411	0.197
LSPO	4.7	0.398	0.195

Sources of Improvement. Table 3 separates gains from target selection and internalization from those of the full LSPO objective, then compares the resulting policy with test-time reflection at deployment. LSPO exceeds Select then SFT and selected internalization, listed as SI only in the table, by 1.2 and 1.0 aggregate points, respectively. This reflection baseline reaches comparable accuracy at 71.9% while incurring substantially higher deployment overhead, requiring two inference passes that add 4.25 s latency and 440 tokens per query.

Table 3 | Training alternatives and deployment cost. Test-time reflection matches LSPO accuracy at higher deployment cost.

Method	Agg. $\pm_{SD}$	Latency (s)	Tokens
Select then SFT	70.6 $\pm_{0.17}$	10.58	1218
SI only	70.8 $\pm_{0.16}$	10.74	1246
GRPO	70.0 $\pm_{0.18}$	12.04	1370
SCoRe	70.7 $\pm_{0.18}$	13.12	1501
Reflection	71.9 $\pm_{0.19}$	15.18	1705
LSPO	71.8 $\pm_{0.15}$	10.93	1265



Figure 4 | Training dynamics across transition stability, net gain, and direct accuracy. Transition stability and net gain plateau before direct accuracy, consistent with the geometric landscape forming before the generator absorbs it.

Generalization Across Task Families. Direct generation and frozen energy ordering are evaluated on five benchmark suites held out from policy training, energy fitting, and endpoint selection in Section E. LSPO improves over Base on every held-out benchmark and reaches an average of 74.9, above SCoRe at 74.3. The frozen energy model also preserves local candidate ordering on this benchmark-level holdout, showing that the learned state signal remains useful on task families excluded from fitting and endpoint selection.

Training Dynamics. Figure 4 tracks the learning phases. Transition stability and net gain rise rapidly in the early steps, marking the formation of a geometric landscape before the accuracy curve plateaus. LSPO first stabilizes constructive local moves and then converts this geometry into deployed accuracy. In contrast, SCoRe trains on unconstrained self-revision traces without step penalties, which leads to aggressive rewriting of correct spans and higher C→W degradation, regressing initially correct answers into erroneous states. LSPO avoids this failure mode by bounding the revision scope throughout training.

Component Ablations. Table 4 isolates each core mechanism. Removing the lifted coordinate reduces aggregate quality and net transition gain, while dropping the progress reward lowers net gain and inflates output verbosity. Removing answer internalization degrades retention and lowers aggregate accuracy. Parameter-matched coordinate controls retain the same training budget yet remain 0.9–1.5 aggregate points below full LSPO, supporting a role for learned refinement context beyond parameter count alone. The full LSPO stack requires additional training compute, while its structural constraints reduce deployment latency and token count relative to unshaped RL baselines. Section C provides the coordinate controls, matched training alternatives, and the full MoE ablation.

Table 4 | Component ablations on Qwen3.5-27B. The full LSPO stack leads in aggregate score while controlling latency, output length, and training cost.

Variant	Agg.	Net gain	Latency (s)	Tokens	GPU hrs
LSPO full	71.8	4.7	10.93	1265	2983
- w/o lifting	70.9	3.2	11.70	1316	2804
- w/o progress reward	70.0	1.6	12.35	1366	2715
- w/o internalization	70.3	2.4	12.02	1341	2566
GRPO	70.0	3.3	12.04	1370	2386
DPO	66.9	1.8	10.42	1196	1218

Policy Energy and Task-Level Gains. Figure 5 tracks recorded energy across policy updates alongside task-level correction outcomes. Energy decreases rapidly during early training and then approaches a plateau, with fluctuations between updates. The cumulative minimum curve records the lowest energy observed across updates, with highlighted points marking new minima. The right panel reports benchmark-level net correction gains independently, with LSPO showing negative net gain on MATH-500 and positive net gains on the other five benchmarks.

4 Discussion

Scope and Boundaries of Local Correction. The transition audits show positive net correction gains on five of six benchmarks, with MATH-500 marking an operational boundary for test-time revision. In tightly coupled algebraic derivations, modifying an isolated step without revising preceding assertions leaves upstream inconsistencies that cause test-time perturbations to degrade



Figure 5 | Policy-training energy and task-level net gains. The left panel shows recorded energy across policy updates, where the curve tracks the cumulative minimum and points mark new minima. The right panel independently reports net correction gains across benchmarks.

more answers than they repair across all methods. As illustrated in Section F on AIME25, resolution requires rebuilding from an alternative decomposition beyond finite-radius edits. In this regime, LSPO internalizes and preserves valid proof structures; training on low-energy trajectories commits coherent derivations to the generator, allowing direct accuracy in Table 1 to advance even where test-time trajectory gain does not. Removing internalization costs 1.5 aggregate points and degrades correct-span retention, confirming that the generator drives this gain.

Prior analyses of iterative self-correction [Madaan et al., 2023, Shinn et al., 2023, Huang et al., 2023, Ma et al., 2025] describe the same distinction. Local correction repairs errors that represent isolated adjustments within a sound plan, including sign choices, index offsets, and lemma applications. Conversely, when the overarching plan requires fundamental restructuring, local energy gradients offer no direct descent toward the target answer. Traversing such global transitions requires either test-time search or training curricula that expose the policy to plan-level pivots.

Training Cost and Deployment Trade-offs. LSPO invests 2983 GPU-hours during training to yield per-query reductions of 4.25 s in latency and 440 output tokens at deployment. The return on this compute investment scales with serving volume, where low-throughput regimes favor minimal training overhead, while high-throughput serving amortizes it through cumulative per-query latency and token savings.

This compute allocation also differs qualitatively from test-time scaling. Reflection-based methods [Snell et al., 2024, Zhang et al., 2025, Sun, 2026] let a single checkpoint serve both simple and complex queries by dynamically varying inference compute. In contrast, LSPO compiles deliberation directly into network parameters, producing a faster single-pass deployment where each query incurs identical inference cost regardless of difficulty. Hybrid designs that use LSPO as a fast initial pass and fall back to explicit search on high-energy outputs could combine the advantages of both regimes.

Representational Role of the Lifted Coordinate. Frozen probing evaluations demonstrate that appending the learned coordinate z to textual representations improves action prediction and energy ranking on held-out transitions in Table C.8, whereas prompt-shuffled controls degrade performance, confirming that the coordinate carries prompt-specific information inaccessible to a text predictor. Architecturally, the coordinate can encode compressed revision histories reflecting edit count and convergence, or establish distinct neighborhoods through Switch to identify candidate answer basins, both of which match empirical observations.

The learned coordinate guides local trajectory steps within candidate vicinities. As shown by the selection-budget analysis in Section E, energy-based ranking discriminates reliably across moderate candidate neighborhoods, whereas unconstrained candidate expansion encounters non-convex surface irregularities. The lifted coordinate thereby provides directionality along local improvement paths, guiding policy updates without assuming global convexity.

5 Related Work

Final Answers, Steps, and Trajectories. Outcome supervision and preference learning supply signals over final answers through RLHF [Christiano et al., 2017, Ziegler et al., 2019, Stiennon

et al., 2020], constitutional AI [Bai et al., 2022], and direct optimization objectives [Rafailov et al., 2023]. ORPO [Hong et al., 2024], SimPO [Meng et al., 2024], and rewards generated by the model [Yuan et al., 2024] refine this interface for ranking answers [Liu et al., 2025b]. Process supervision moves the learning signal into intermediate reasoning steps [Cobbe et al., 2021, Uesato et al., 2022, Lightman et al., 2023], with Step-DPO as a prominent example [Lai et al., 2024]. Unlike absolute step scores suited to reranking individual states, LSPO credits relative transitions net of edit and step costs within a prompt's candidate pool, steering policy movement rather than global state ranking. GRPO [Guo et al., 2025] and GDPO [Panaganti et al., 2026] optimize returns over sampled trajectories.

Learning from Refinement. Refinement during inference enables models to critique, revise, or retry initial answers [Madaan et al., 2023, Shinn et al., 2023, Huang et al., 2023, Sun, 2026]. Recent training variants convert these revisions into supervision through rewards generated by the model, revision analysis, and refinement pipelines for code [Liu et al., 2024, Ma et al., 2025, Bensal et al., 2025, Xiong et al., 2025, Jiang et al., 2026]. SCoRe is the closest baseline, learning from refinement traces generated by the model [Kumar et al., 2024].

Representing Intermediate States. State representation determines which movements can be compared and optimized. Plain text exposes the current answer but confines candidate alternatives to a brittle discrete space. Calibration and semantic-uncertainty studies show that confidence and correctness signals reside on separable manifolds in the hidden state [Guo et al., 2017, Kuhn et al., 2023, Farquhar et al., 2024]; semantic probes and over-confidence analyses further confirm that correctness structure is geometrically accessible [Kossen et al., 2024, Morosini et al., 2026]. Complementary geometric methods treat latent representations as substrates for reasoning and model connectivity [Xie et al., 2025, Zhuang et al., 2026]. LSPO operationalizes this view by lifting surface answers into an augmented state space, ordering candidate transitions by energy, and transferring the selected lower-energy answer into direct generation.

6 Limitations and Future Directions

The framework is designed for verifiable reasoning tasks where programmatic checkers or scalar outcomes ground the energy landscape. Policy improvement relies on alignment between the learned energy $\tilde{E}(s; q)$ and true answer validity. While intermediate fluctuations cancel telescopically along trajectories, terminal discrimination remains bounded by the fidelity of the fitted scoring head. Operating over visited neighborhoods, transition credit addresses local repairs within an established derivation, while problems requiring global proof reformulations from scratch remain outside this local search scope. Trajectory exploration concentrates compute during training, making the framework most advantageous for high-throughput serving environments where amortized efficiency provides operational gains.

Our analysis evaluates scaling across the Qwen3.5 family [Qwen Team, 2026], the 35B-A3B mixture-of-experts backbone, and cross-family transfer on Gemma-4-E4B-it [Google DeepMind, 2026]. In this work, the auxiliary coordinate models textual deliberation; incorporating tool executions, evidence graphs, or multi-turn interaction traces would define the corresponding state representation for structured environments. Preliminary evaluations in Section E show positive policy transfer on open-form writing and roleplay benchmarks, with geometric ordering aligning best with instruction fit, coherence, and character consistency. More comprehensive open-ended creative tasks remain to be evaluated under distinct criteria. Further advances will require latent state spaces that score and retain structured movements across these varied task formats.

7 Conclusion

LSPO establishes that direct policy execution can attain the reliability of iterative refinement. It matches the accuracy of test-time reflection in a single pass, and transition diagnostics confirm that the policy repairs incorrect states while preserving correct ones. The learned stopping behavior mitigates redundant revisions, and the policy transfers across model scales, to held-out benchmarks, and to mixture-of-experts architectures. Attributing credit to geometric transitions and internalizing selected endpoints thus relocates deliberation from inference into the deployed policy.

Acknowledgments and Disclosure of Funding

We thank the anonymous reviewers for their constructive feedback. This work was supported by the School of Information Science and Technology at Hangzhou Normal University. The authors declare no competing interests.

References

Lukas Aichberger, Kajetan Schweighofer, Mykyta Ielanskyi, and Sepp Hochreiter. Improving uncertainty estimation through semantically diverse language generation. *arXiv preprint arXiv:2406.04306*, 2024.

Anthropic. Introducing claude sonnet 4.5, 2025. URL `https://www.anthropic.com/news/claude-sonnet-4-5`.

Jacob Austin, Augustus Odena, Maxwell Nye, Maarten Bosma, Henryk Michalewski, David Dohan, Ellen Jiang, Carrie Cai, Michael Terry, Quoc Le, et al. Program synthesis with large language models. *arXiv preprint arXiv:2108.07732*, 2021.

Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, Andy Jones, Anna Chen, Anna Goldie, Azalia Mirhoseini, Cameron McKinnon, et al. Constitutional ai: Harmlessness from ai feedback. *arXiv preprint arXiv:2212.08073*, 2022.

Shelly Bensal, Umar Jamil, Christopher Bryant, Melisa Russak, Kiran Kamble, Dmytro Mozolevskyi, Muayad Ali, and Waseem AlShikh. Reflect, retry, reward: Self-improving llms via reinforcement learning. *arXiv preprint arXiv:2505.24726*, 2025.

Ralph Allan Bradley and Milton E Terry. Rank analysis of incomplete block designs: I. the method of paired comparisons. *Biometrika*, 39(3/4):324–345, 1952.

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde De Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, et al. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*, 2021.

Paul F Christiano, Jan Leike, Tom Brown, Miljan Martic, Shane Legg, and Dario Amodei. Deep reinforcement learning from human preferences. *Advances in neural information processing systems*, 30, 2017.

Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. Think you have solved question answering? try arc, the ai2 reasoning challenge. *arXiv preprint arXiv:1803.05457*, 2018.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, et al. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.

Harald Cramér. A contribution to the theory of statistical estimation. *Scandinavian Actuarial Journal*, 1946(1): 85–94, 1946.

Sebastian Farquhar, Jannik Kossen, Lorenz Kuhn, and Yarin Gal. Detecting hallucinations in large language models using semantic entropy. *Nature*, 630(8017):625–630, 2024.

Tom Fawcett. An introduction to roc analysis. *Pattern recognition letters*, 27(8):861–874, 2006.

Ronald Aylmer Fisher. Theory of statistical estimation. In *Mathematical proceedings of the Cambridge philosophical society*, volume 22, pages 700–725. Cambridge University Press, 1925.

Google DeepMind. Gemma-4-E4B-it. `https://huggingface.co/google/gemma-4-E4B-it`, 2026.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q Weinberger. On calibration of modern neural networks. In *International conference on machine learning*, pages 1321–1330. PMLR, 2017.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Peiyi Wang, Qihao Zhu, Runxin Xu, Ruoyu Zhang, Shirong Ma, Xiao Bi, et al. Deepseek-r1 incentivizes reasoning in llms through reinforcement learning. *Nature*, 645(8081):633–638, 2025.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. Measuring mathematical problem solving with the math dataset. *arXiv preprint arXiv:2103.03874*, 2021.

Jiwoo Hong, Noah Lee, and James Thorne. Orpo: Monolithic preference optimization without reference model. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 11170–11189, 2024.

Jie Huang, Xinyun Chen, Swaroop Mishra, Huaixiu Steven Zheng, Adams Wei Yu, Xinying Song, and Denny Zhou. Large language models cannot self-correct reasoning yet. *arXiv preprint arXiv:2310.01798*, 2023.

Naman Jain, King Han, Alex Gu, Wen-Ding Li, Fanjia Yan, Tianjun Zhang, Sida Wang, Armando Solar-Lezama, Koushik Sen, and Ion Stoica. Livecodebench: Holistic and contamination free evaluation of large language models for code. *arXiv preprint arXiv:2403.07974*, 2024.

Juyong Jiang, Jiasi Shen, Sunghun Kim, Kang Min Yoo, Jeonghoon Kim, and Sungju Kim. Reflexicoder: Teaching large language models to self-reflect on generated code and self-correct it via reinforcement learning. *arXiv preprint arXiv:2603.05863*, 2026.

Keller Jordan, Yuchen Jin, Vlado Boza, You Jiacheng, Franz Cesista, Laker Newhouse, and Jeremy Bernstein. Muon: An optimizer for hidden layers in neural networks, 2024. URL `https://kellerjordan.github.io/posts/muon/`.

Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan Perez, Nicholas Schiefer, Zac Hatfield-Dodds, Nova DasSarma, Eli Tran-Johnson, et al. Language models (mostly) know what they know. *arXiv preprint arXiv:2207.05221*, 2022.

Timo Kaufmann, Paul Weng, Viktor Bengs, and Eyke Hüllermeier. A survey of reinforcement learning from human feedback. *Transactions on Machine Learning Research*, 2024.

Maurice G Kendall. A new measure of rank correlation. *Biometrika*, 30(1-2):81–93, 1938.

Jannik Kossen, Jiatong Han, Muhammed Razzak, Lisa Schut, Shreshth Malik, and Yarin Gal. Semantic entropy probes: Robust and cheap hallucination detection in llms. *arXiv preprint arXiv:2406.15927*, 2024.

Lorenz Kuhn, Yarin Gal, and Sebastian Farquhar. Semantic uncertainty: Linguistic invariances for uncertainty estimation in natural language generation. *arXiv preprint arXiv:2302.09664*, 2023.

Aviral Kumar, Vincent Zhuang, Rishabh Agarwal, Yi Su, John D Co-Reyes, Avi Singh, Kate Baumli, Shariq Iqbal, Colton Bishop, Rebecca Roelofs, et al. Training language models to self-correct via reinforcement learning. *arXiv preprint arXiv:2409.12917*, 2024.

Xin Lai, Zhuotao Tian, Yukang Chen, Senqiao Yang, Xiangru Peng, and Jiaya Jia. Step-dpo: Step-wise preference optimization for long-chain reasoning of llms. *arXiv preprint arXiv:2406.18629*, 2024.

Yanlin Lai, Mitt Huang, Hangyu Guo, Xiangfeng Wang, Haodong Li, Shaoxiong Zhan, Liang Zhao, Chengyuan Yao, Yinmin Zhang, Qi Han, et al. R-align: Enhancing generative reward models through rationale-centric meta-judging. *arXiv preprint arXiv:2602.06763*, 2026.

Nathan Lambert. Reinforcement learning from human feedback. *arXiv preprint arXiv:2504.12501*, 2025.

Khiem Le, Youssef Mroueh, Phuc Nguyen, Chi-Heng Lin, Shangqian Gao, Ting Hua, and Nitesh V Chawla. Transform-augmented grpo improves pass@ k. *arXiv preprint arXiv:2601.22478*, 2026.

Hunter Lightman, Vineet Kosaraju, Yuri Burda, Harrison Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. Let's verify step by step. In *The twelfth international conference on learning representations*, 2023.

Bill Yuchen Lin, Ronan Le Bras, Kyle Richardson, Ashish Sabharwal, Radha Poovendran, Peter Clark, and Yejin Choi. Zebralogic: On the scaling limits of llms for logical reasoning. *arXiv preprint arXiv:2502.01100*, 2025.

Dancheng Liu, Amir Nassereldine, Ziming Yang, Chenhui Xu, Yuting Hu, Jiajie Li, Utkarsh Kumar, Changjae Lee, Ruiyang Qin, Yiyu Shi, et al. Large language models have intrinsic self-correction ability. *arXiv preprint arXiv:2406.15673*, 2024.

Jingyuan Liu, Jianlin Su, Xingcheng Yao, Zhejun Jiang, Guokun Lai, Yulun Du, Yidao Qin, Weixin Xu, Enzhe Lu, Junjie Yan, et al. Muon is scalable for llm training. *arXiv preprint arXiv:2502.16982*, 2025a.

Shunyu Liu, Wenkai Fang, Zetian Hu, Junjie Zhang, Yang Zhou, Kongcheng Zhang, Rongcheng Tu, Ting-En Lin, Fei Huang, Mingli Song, et al. A survey of direct preference optimization. *arXiv preprint arXiv:2503.11701*, 2025b.

Ruotian Ma, Peisong Wang, Cheng Liu, Xingyan Liu, Jiaqi Chen, Bang Zhang, Xin Zhou, Nan Du, and Jia Li. S2r: Teaching llms to self-verify and self-correct via reinforcement learning. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 22632–22654, 2025.

Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegreffe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, et al. Self-refine: Iterative refinement with self-feedback. *Advances in neural information processing systems*, 36:46534–46594, 2023.

Yu Meng, Mengzhou Xia, and Danqi Chen. Simpo: Simple preference optimization with a reference-free reward. *Advances in Neural Information Processing Systems*, 37:124198–124235, 2024.

Alessandro Morosini, Matea Gjika, Tomaso Poggio, and Pierfrancesco Beneventano. Too sharp, too sure: When calibration follows curvature. *arXiv preprint arXiv:2604.20614*, 2026.

Mahdi Pakdaman Naeini, Gregory Cooper, and Milos Hauskrecht. Obtaining well calibrated probabilities using bayesian binning. In *Proceedings of the AAAI conference on artificial intelligence*, volume 29, 2015.

Andrew Y Ng, Daishi Harada, and Stuart Russell. Policy invariance under reward transformations: Theory and application to reward shaping. In *Icml*, volume 99, pages 278–287. Citeseer, 1999.

Alexandru Niculescu-Mizil and Rich Caruana. Predicting good probabilities with supervised learning. In *Proceedings of the 22nd international conference on Machine learning*, pages 625–632, 2005.

OpenAI. gpt-oss-120b & gpt-oss-20b model card, 2025. URL `https://huggingface.co/openai/gpt-oss-120b`.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35:27730–27744, 2022.

Pei-Chi Pan, Yingbin Liang, and Sen Lin. Reward modeling for reinforcement learning-based llm reasoning: Design, challenges, and evaluation. *arXiv preprint arXiv:2602.09305*, 2026.

Kishan Panaganti, Zhenwen Liang, Wenhao Yu, Haitao Mi, and Dong Yu. Group distributionally robust optimization-driven reinforcement learning for llm reasoning. *arXiv preprint arXiv:2601.19280*, 2026.

Qwen Team. Qwen3.5: Towards native multimodal agents, February 2026. URL `https://qwen.ai/blog?id=qwen3.5`.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. *Advances in neural information processing systems*, 36:53728–53741, 2023.

C Radhakrishna Rao et al. Information and the accuracy attainable in the estimation of statistical parameters. *Bull. Calcutta Math. Soc*, 37(3):81–91, 1945.

David Rein, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R Bowman. Gpqa: A graduate-level google-proof q&a benchmark. In *First conference on language modeling*, 2024.

Alfréd Rényi. On measures of entropy and information. In *Proceedings of the fourth Berkeley symposium on mathematical statistics and probability, volume 1: contributions to the theory of statistics*, volume 4, pages 547–562. University of California Press, 1961.

John Schulman, Philipp Moritz, Sergey Levine, Michael Jordan, and Pieter Abbeel. High-dimensional continuous control using generalized advantage estimation. *arXiv preprint arXiv:1506.02438*, 2015.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Claude Elwood Shannon. A mathematical theory of communication. *The Bell system technical journal*, 27(3): 379–423, 1948.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, Yang Wu, et al. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024.

Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning. *Advances in neural information processing systems*, 36:8634–8652, 2023.

Charlie Snell, Jaehoon Lee, Kelvin Xu, and Aviral Kumar. Scaling llm test-time compute optimally can be more effective than scaling model parameters. *arXiv preprint arXiv:2408.03314*, 2024.

Charles Spearman. *The proof and measurement of association between two things.* Appleton-Century-Crofts, 1961.

Nisan Stiennon, Long Ouyang, Jeffrey Wu, Daniel Ziegler, Ryan Lowe, Chelsea Voss, Alec Radford, Dario Amodei, and Paul F Christiano. Learning to summarize with human feedback. *Advances in neural information processing systems*, 33:3008–3021, 2020.

Xinhai Sun. Reinforcement inference: Leveraging uncertainty for self-correcting language model reasoning. *arXiv preprint arXiv:2602.08520*, 2026.

Richard S Sutton, Andrew G Barto, et al. *Reinforcement learning: An introduction*, volume 1. MIT press Cambridge, 1998.

Mirac Suzgun, Nathan Scales, Nathanael Schärli, Sebastian Gehrmann, Yi Tay, Hyung Won Chung, Aakanksha Chowdhery, Quoc Le, Ed Chi, Denny Zhou, et al. Challenging big-bench tasks and whether chain-of-thought can solve them. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 13003–13051, 2023.

Jonathan Uesato, Nate Kushman, Ramana Kumar, Francis Song, Noah Siegel, Lisa Wang, Antonia Creswell, Geoffrey Irving, and Irina Higgins. Solving math word problems with process-and outcome-based feedback. *arXiv preprint arXiv:2211.14275*, 2022.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models. *arXiv preprint arXiv:2203.11171*, 2022.

Yubo Wang, Xueguang Ma, Ge Zhang, Yuansheng Ni, Abhranil Chandra, Shiguang Guo, Weiming Ren, Aaran Arulraj, Xuan He, Ziyan Jiang, et al. Mmlu-pro: A more robust and challenging multi-task language understanding benchmark. *Advances in Neural Information Processing Systems*, 37:95266–95290, 2024.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837, 2022.

Jason Wei, Nguyen Karina, Hyung Won Chung, Yunxin Joy Jiao, Spencer Papay, Amelia Glaese, John Schulman, and William Fedus. Measuring short-form factuality in large language models. *arXiv preprint arXiv:2411.04368*, 2024.

Taiqiang Wu, Zenan Zu, Bo Zhou, and Ngai Wong. The art of efficient reasoning: Data, reward, and optimization. *arXiv preprint arXiv:2602.20945*, 2026a.

Yuning Wu, Jiahao Mei, Ming Yan, Chenliang Li, Shaopeng Lai, Yuran Ren, Zijia Wang, Ji Zhang, Mengyue Wu, Qin Jin, et al. Writingbench: A comprehensive benchmark for generative writing. *Advances in Neural Information Processing Systems*, 38, 2026b.

Zhenda Xie, Yixuan Wei, Huanqi Cao, Chenggang Zhao, Chengqi Deng, Jiashi Li, Damai Dai, Huazuo Gao, Jiang Chang, Kuai Yu, et al. MHC: Manifold-constrained hyper-connections. *arXiv preprint arXiv:2512.24880*, 2025.

Wei Xiong, Hanning Zhang, Chenlu Ye, Lichang Chen, Nan Jiang, and Tong Zhang. Self-rewarding correction for mathematical reasoning. *arXiv preprint arXiv:2502.19613*, 2025.

Yifei Xu, Tusher Chakraborty, Srinagesh Sharma, Leonardo Nunes, Swati Sharma, Kate Drakos Demopulos, Emre Kıcıman, Songwu Lu, and Ranveer Chandra. Direct reasoning optimization: Token-level reasoning reflectivity meets rubric gates for unverifiable tasks. *arXiv preprint arXiv:2506.13351*, 2025.

Zhangyue Yin, Qiushi Sun, Qipeng Guo, Jiawen Wu, Xipeng Qiu, and Xuan-Jing Huang. Do large language models know what they don't know? In *Findings of the association for Computational Linguistics: ACL 2023*, pages 8653–8665, 2023.

Weizhe Yuan, Richard Yuanzhe Pang, Kyunghyun Cho, Xian Li, Sainbayar Sukhbaatar, Jing Xu, and Jason E Weston. Self-rewarding language models. In *Forty-first International Conference on Machine Learning*, 2024.

Eric Zelikman, Georges Harik, Yijia Shao, Varuna Jayasiri, Nick Haber, and Noah D Goodman. Quiet-star: Language models can teach themselves to think before speaking. *arXiv preprint arXiv:2403.09629*, 2024.

Qiyuan Zhang, Fuyuan Lyu, Zexu Sun, Lei Wang, Weixu Zhang, Wenyue Hua, Haolun Wu, Zhihan Guo, Yufei Wang, Niklas Muennighoff, et al. A survey on test-time scaling in large language models: What, how, where, and how well? *arXiv preprint arXiv:2503.24235*, 2025.

Yifan Zhang and Team Math-AI. American invitational mathematics examination (aime) 2025, 2025. URL `https://huggingface.co/datasets/math-ai/aime25`.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, et al. Judging llm-as-a-judge with mt-bench and chatbot arena. *Advances in neural information processing systems*, 36:46595–46623, 2023.

Ren Zhuang, Ben Wang, and Shuifa Sun. The geometric reasoner: Manifold-informed latent foresight search for long-context reasoning. *arXiv preprint arXiv:2601.18832*, 2026.

Daniel M Ziegler, Nisan Stiennon, Jeffrey Wu, Tom B Brown, Alec Radford, Dario Amodei, Paul Christiano, and Geoffrey Irving. Fine-tuning language models from human preferences. *arXiv preprint arXiv:1909.08593*, 2019.

Appendices

The appendix follows the evidential order of the main text. It first fixes the formal objects used by LSPO, then tests scale and transfer, isolates training mechanisms, audits internalization and energy ordering, and closes with cases that mark the method boundary.

- Section A derives the path form with KL regularization and the information criterion for lifted states.
- Section B reports scale and transfer across Qwen sizes, benchmark families, and a distinct Gemma backbone.
- Section C connects the update contract to component ablations, sensitivity analyses, and the fixed training configuration.
- Section D audits alignment from training to direct generation, stopping behavior, and the boundary with test-time reflection.
- Section E quantifies deployment cost, energy ordering on benchmark suites held out from training, and compute accounting.
- Section F maps the mechanism onto representative repairs and a global search failure case.

A Formal Properties of the Path Objective and State Lifting

This appendix studies an unrestricted path-distribution relaxation and an information criterion for lifting. Their conclusions concern the stated distributions and assumptions.

Proposition 2 (Gibbs form of the path optimizer constrained by KL divergence)**.** *Fix a prompt q, let $P_{\mathrm{ref}}(\cdot \mid q)$ be a reference distribution over finite correction trajectories, and define the path score*

$$F_q(\tau) = \sum_{t=0}^{T(\tau)-1} r_t. \tag{A.1}$$

Consider the variational problem

$$\sup_{P \ll P_{\mathrm{ref}}(\cdot|q)} \left\{ \mathbb{E}_{\tau\sim P}[F_q(\tau)] - \beta D_{\mathrm{KL}}\big(P \,\|\, P_{\mathrm{ref}}(\cdot \mid q)\big) \right\}. \tag{A.2}$$

For $\beta > 0$ and $0 < Z_q < \infty$, its unique maximizer is the exponentially tilted path distribution

$$\frac{dP_q^\star}{dP_{\mathrm{ref}}}(\tau) = \frac{\exp(F_q(\tau)/\beta)}{Z_q}, \qquad Z_q = \mathbb{E}_{\tau\sim P_{\mathrm{ref}}(\cdot|q)}\left[\exp(F_q(\tau)/\beta)\right], \tag{A.3}$$

and the optimal objective value equals $\beta \log Z_q$.

Variational argument. Let $P_q^\star$ be the tilted path distribution defined in eq. (A.3). For any admissible P, we have

$$\frac{dP_q^\star}{dP_{\mathrm{ref}}}(\tau) = \frac{\exp(F_q(\tau)/\beta)}{Z_q}. \tag{A.4}$$

This gives

$$\log \frac{dP_q^\star}{dP_{\mathrm{ref}}}(\tau) = \frac{F_q(\tau)}{\beta} - \log Z_q. \tag{A.5}$$

Using

$$D_{\mathrm{KL}}(P \,\|\, P_q^\star) = \mathbb{E}_{\tau\sim P}\left[\log \frac{dP}{dP_q^\star}(\tau)\right] = \mathbb{E}_{\tau\sim P}\left[\log \frac{dP}{dP_{\mathrm{ref}}}(\tau) - \frac{F_q(\tau)}{\beta} + \log Z_q\right], \tag{A.6}$$

we rearrange to obtain

$$\mathbb{E}_{\tau\sim P}[F_q(\tau)] - \beta D_{\mathrm{KL}}\big(P \,\|\, P_{\mathrm{ref}}(\cdot \mid q)\big) = \beta \log Z_q - \beta D_{\mathrm{KL}}(P \,\|\, P_q^\star). \tag{A.7}$$

The right side is maximized uniquely at $P = P_q^\star$, where the KL term vanishes.

Path Variational Form. Proposition 2 casts the path problem with a KL constraint as a variational optimization whose solution tilts the reference distribution toward paths with larger cumulative progress. Together with proposition 1, the result places lower final energy, edit cost, and step cost within a single path preference.

Relation to the Implemented Regularizer. For a fixed prompt, a policy-induced path distribution factors as

$$P_\theta(\tau \mid q) = \rho_\theta(s_0 \mid q) \prod_t \pi_\theta(a_t \mid s_t, q) K_\theta(s_{t+1} \mid s_t, a_t, q), \tag{A.8}$$

including the Stop decision and absorbing termination. Under absolute continuity, the chain rule gives

$$\begin{aligned} D_{\mathrm{KL}}(P_\theta \| P_{\mathrm{ref}}) = {} & D_{\mathrm{KL}}(\rho_\theta \| \rho_{\mathrm{ref}}) \\ & + \mathbb{E}_{P_\theta} \sum_t D_{\mathrm{KL}}(\pi_\theta(\cdot \mid s_t, q) \| \pi_{\mathrm{ref}}(\cdot \mid s_t, q)) \\ & + \mathbb{E}_{P_\theta} \sum_t D_{\mathrm{KL}}(K_\theta(\cdot \mid s_t, a_t, q) \| K_{\mathrm{ref}}(\cdot \mid s_t, a_t, q)). \end{aligned} \tag{A.9}$$

Equality with the action-KL term requires shared initial-state distributions and conditional transition kernels. Within update k, LSPO fixes $\rho_{\bar{\theta}_k}$ and $K_{\bar{\theta}_k}$ for both the controller and the reference, whereby the first and third terms above cancel and the path KL reduces to the visited-state action KL. Controller RL therefore targets the fixed-mechanism controller objective in eq. (6) rather than the unrestricted path objective; the snapshot is refreshed at the next update. The Gibbs result concerns the unrestricted path-distribution relaxation, whose optimum further requires realizability under the specified dynamics.

A.1 Information in the Lifted State

The lifted coordinate z_t augments the discrete textual state. Whether lifting adds value depends on the information it carries about constructive moves beyond what the surface text and prompt alone provide.

Proposition 3 (Lifted state reduces optimal move prediction loss by the conditional mutual information)**.** *Let U_t denote any target associated with state s_t, for example an indicator that a candidate local move decreases energy without harming correctness. Define the Bayes optimal predictors*

$$p^\star_{\mathrm{surf}}(u \mid x, q) = \mathbb{P}(U_t = u \mid X_t = x, Q = q) \tag{A.10}$$

and

$$p^\star_{\mathrm{lift}}(u \mid x, z, q) = \mathbb{P}(U_t = u \mid X_t = x, Z_t = z, Q = q). \tag{A.11}$$

The achievable reduction in log loss from using the lifted state instead of the surface state alone is

$$\mathbb{E}[-\log p^\star_{\mathrm{surf}}(U_t \mid X_t, Q)] - \mathbb{E}[-\log p^\star_{\mathrm{lift}}(U_t \mid X_t, Z_t, Q)] = I(U_t; Z_t \mid X_t, Q). \tag{A.12}$$

Information identity. By the definition of Bayes optimal log loss,

$$\mathbb{E}[-\log p^\star_{\mathrm{surf}}(U_t \mid X_t, Q)] = H(U_t \mid X_t, Q) \tag{A.13}$$

and

$$\mathbb{E}[-\log p^\star_{\mathrm{lift}}(U_t \mid X_t, Z_t, Q)] = H(U_t \mid X_t, Z_t, Q). \tag{A.14}$$

Subtracting yields

$$H(U_t \mid X_t, Q) - H(U_t \mid X_t, Z_t, Q) = I(U_t; Z_t \mid X_t, Q). \tag{A.15}$$

This is the conditional mutual information identity.

Lift Criterion. For a fixed joint distribution of (Q, X_t, Z_t, U_t) with finite conditional entropies, the identity yields an information criterion. The lifted coordinate z_t improves prediction exactly when it carries information about constructive moves absent from the surface text and input. Positive conditional mutual information equals the achievable reduction in optimal log loss.

For a deterministic reprojection $Z_t = g(Q, X_t)$ at fixed parameters, the conditional mutual information is zero. Recursive coordinates can retain history since their most recent reset; positive conditional information depends on the resulting state distribution and target U_t. The finite-capacity probes quantify accessible predictive information, and their NLL differences give empirical prediction gains.

B Full Scaling Profiles and Cross-Architecture Transfer

This appendix extends the 27B analysis across benchmarks, model scales, and pass@k budgets. Following established protocols for reasoning and executable code evaluation [Wang et al., 2022, Chen et al., 2021], it reports performance for each benchmark across all three Qwen backbones.

Across scales, LSPO attains the highest direct accuracy without collapsing the pass@16 envelope, while expanding sampled ceilings on complex reasoning suites, as illustrated in Figures B.1 to B.3. The separation is largest on MATH-500, GPQA, and ZebraLogic, where methods based on preferences capture less of the



Figure B.1 | Benchmark profile for Qwen3.5-9B. LSPO improves direct accuracy while preserving substantial sampled pass@16 headroom in the smaller dense backbone.



Figure B.2 | Benchmark profile for Qwen3.5-27B. LSPO achieves consistent direct gains while preserving the sampled pass@16 envelope.

available revision signal than on broad knowledge tasks. Smaller models retain wider gaps between pass@1 and pass@16, indicating more residual search headroom.

These distributions relate LSPO to recent reasoning systems operating at scale, such as DeepSeekMath and DeepSeek-R1 [Shao et al., 2024, Guo et al., 2025]. Reasoning RL at large scale can improve quality by reshaping output distributions and spending inference compute. The pass@16 diagnostics isolate the portion of that improvement absorbed into deployed generation while sampled diversity remains available.



Figure B.3 | Benchmark profile for Qwen3.5-35B-A3B. LSPO remains the strongest direct policy as available performance headroom narrows in the MoE backbone.

Table B.1 | Transfer across backbones to Gemma-4-E4B-it. LSPO attains the highest aggregate score on this distinct architecture while incurring only a minor latency overhead relative to direct preference baselines.

Method	MATH-500	GPQA	LCB	Aggregate	Latency (s)
Base	87.6	48.7	47.1	61.1	6.81
DPO	88.3	49.4	48.0	61.9	7.04
GRPO	89.2	50.1	49.4	62.9	7.18
LSPO	90.7	51.3	52.0	64.7	7.31

B.1 Transfer Across Backbones

While primary scaling experiments evaluate the Qwen3.5 family under consistent formatting, Table B.1 examines transfer to Gemma-4-E4B-it [Google DeepMind, 2026]. On this distinct backbone, LSPO attains the highest aggregate score, improving over both offline preference optimization and online reinforcement learning with only a modest latency increase. This confirms that transition credit and answer internalization transfer robustly beyond the primary Qwen family.

B.2 Benchmark Coverage

The benchmark suite spans complementary reasoning regimes. MATH-500 and AIME assess multi-step mathematical derivations. LiveCodeBench tests executable code synthesis under formal test specifications. ZebraLogic probes constrained deduction and local backtrack revisions. GPQA and MMLU-Pro assess multi-step scientific and domain knowledge. In addition, held-out task suites such as BBH, GSM8K, and HumanEval are evaluated in Section E to audit out-of-distribution calibration.

C Update Mechanics, Ablations, and Sensitivity Analyses

This appendix links the training procedure to the mechanisms tested in the main text. The three core mechanisms of LSPO play complementary roles. Lifting defines the state in which correction moves are compared; the progress reward supplies dense local credit, aligned with reward shaping and process supervision [Ng et al., 1999, Uesato et al., 2022, Lightman et al., 2023]; and answer internalization moves selected candidates into the deployed policy.



Figure C.1 | A single LSPO training update. Move shaping in the lifted space and answer internalization act concurrently on the selected candidate.

Baseline comparisons place LSPO mechanics against neighboring training strategies. Step-DPO [Lai et al., 2024] strengthens supervision over long reasoning chains relative to standard DPO while retaining a preference objective. GDPO [Panaganti et al., 2026] addresses stability in RL over sampled paths through group weighting. SCoRe [Kumar et al., 2024] trains online self-correction from the model's own generation traces. LSPO combines cost-aware move shaping with answer internalization so that selected states enter generation in a single pass.

The accompanying ablations examine the contributions of state lifting and reward shaping under the reported configurations, complementing studies of shaped training signals in reinforcement learning [Kaufmann et al., 2024, Lambert, 2025, Wu et al., 2026a].

C.1 Update Mechanics

Figure C.1 and Algorithm 1 specify the computational graph and algorithmic procedure for a single LSPO update.

The initial generation at the top of the update graph represents the deployed answer before revision. This output initializes the lifted path and the candidate set. Each state encodes the surface text, the lifted coordinate, and the scalar energy. Each action proposes a local move and receives the reward increment from eq. (4). This decomposition combines credit assignment over paths with direct training on the selected answer. The advantage estimator targets the controller objective in eq. (6).

C.2 Architecture and Data Transparency

The primary Qwen3.5-27B implementation uses the architecture and public corpus mixture in Tables C.1 and C.2. These details fix how the lifted coordinate enters the model, how the energy head receives text and state features, and which data mixture supplies the shared training budget.

Algorithm 1 fixes the training contract. The model generates the deployed answer, explores lifted states during training, selects a candidate, and updates the direct generator on that answer. The energy model, verifier, candidate selection, and explicit revision actions serve as instruments during training only.

[1] `https://huggingface.co/datasets/open-r1/OpenR1-Math-220k`
[2] `https://huggingface.co/datasets/BAAI/TACO`
[3] `https://huggingface.co/datasets/allenai/sciq`
[4] `https://huggingface.co/datasets/longface/logicLM`

Algorithm 1 LSPO update contract

Require: minibatch $\mathcal{B}$; direct generator p_θ; action policy π_θ; value head V_ω; reference π_{ref}
Require: frozen $(h_\xi, g_\psi, f_\eta, E_\phi)$ defining $\tilde{E}$; optional verifier V; horizon $T_{\max}$
Require: weights $(\alpha, \beta, \lambda_{\text{edit}}, \lambda_{\text{step}})$; optimizer Opt
Ensure: updated parameters (θ, ω); deployment uses only $p_\theta(\cdot \mid q)$

```
Fix rollout snapshot θ̄_k ← θ for initial answers and text proposals
Initialize path buffer R ← ∅ and imitation buffer I ← ∅
for each prompt q ∈ B do
    Sample direct answer x^dir ~ p_θ̄k(· | q)
    Set h_0 = h_ξ(q, x^dir), s_0 = (x^dir, g_ψ(h_0)), and C ← {(x^dir, s_0, Ẽ(s_0; q))}
    for t = 0, ..., T_max − 1 do
        Sample a_t ~ π_θ̄k(· | s_t, q) from {revise, switch, stop}
        if a_t = stop then
            Set r_t = 0, s_{t+1} = s_t, and done = True
            Record (q, s_t, a_t, s_t, 0, log π_θ̄k(a_t | s_t, q), log π_ref(a_t | s_t, q), done) in R
            break
        end if
        Execute a_t using K_θ̄k to obtain x_{t+1}; set h_{t+1} = h_ξ(q, x_{t+1})
        Set b_t = z_t for Revise, or b_t = g_ψ(h_{t+1}) for Switch
        Set z_{t+1} = LN(b_t + f_η(h_{t+1} − h_t, b_t, e(a_t)))
        Set s_{t+1} = (x_{t+1}, z_{t+1}) and done = (t = T_max − 1)
        Compute r_t = Ẽ(s_t; q) − Ẽ(s_{t+1}; q) − λ_edit d(x_{t+1}, x_t) − λ_step
        Record (q, s_t, a_t, s_{t+1}, r_t, log π_θ̄k(a_t | s_t, q), log π_ref(a_t | s_t, q), done) in R
        Append (x_{t+1}, s_{t+1}, Ẽ(s_{t+1}; q)) to C
    end for
    Select x*_T(q) from C by minimum energy, using V only to break training ties
    Append (q, x*_T(q)) to I
end for
Estimate advantages from R and form the sampled controller loss L_ctrl^(k) with action KL
Form answer internalization loss L_SI = −E_I[log p_θ(x*_T(q) | q)]
Update policy/generator with L_ctrl^(k) + αL_SI; fit value head V_ω to returns
```

Table C.1 | Architectural specifications for the primary Qwen3.5-27B LSPO implementation.

Component	Architecture	Input / output	Key setting
Lift projection g_ψ	2-layer MLP, width 1024, GELU	Hidden state $\to z \in \mathbb{R}^8$	Input LayerNorm
Energy head $\tilde{E}$	3-layer MLP, width 1024, SiLU	Pooled text, z, task embedding $\to$ scalar	Pairwise margin 0.20
Transition block	2 residual blocks, width 1024, SiLU	Text delta, b_t, action embedding $\to \Delta z$	$z_{t+1} = \text{LN}(b_t + \Delta z)$
Action embedding	Lookup table, width 128	Revise, Switch, Stop $\to$ vector	Frozen transition conditioning
Value head	2-layer MLP, width 512, SiLU	Transition state $\to$ scalar value	GAE 0.95, clip 0.2

Transition Operators. The action set contains three operators. Revise edits the active surface answer by sampling a bounded patch over a reasoning, equation, or code span and recursively updating its coordinate. Switch replaces the active candidate with another sampled state for the same prompt, including its surface text and projected coordinate, before the transition block applies the residual update. Stop terminates expansion and leaves the current state as a candidate for selection. The edit term $d(x_{t+1}, x_t)$ is computed after normalizing whitespace, mathematical tokens, and code tokens. Long answers are segmented into reasoning spans, and the distance is the normalized Levenshtein distance at token level over changed spans, capped at one for each transition. This convention charges local rewrites without making copied context dominate the penalty.

Lifted Coordinate. Let $h_t = h_\xi(q, x_t)$ be the frozen text representation and $e(a_t)$ the frozen action embedding used by the transition block. Initialization uses $z_0 = g_\psi(h_0)$. For Revise, the residual update starts from $b_t = z_t$; for Switch, it starts from $b_t = g_\psi(h_{t+1})$. Both use

$$z_{t+1} = \text{LN}(b_t + f_\eta(h_{t+1} - h_t, b_t, e(a_t))) \,. \tag{C.1}$$

Table C.2 | Training corpus mixture and sample counts shared by the compared methods.

Task family	Public corpus source	Samples
Math	open-r1/OpenR1-Math-220k[1]	38,000
Code	BAAI/TACO[2]	24,000
Science	allenai/sciq[3]	18,000
Logic	longface/logicLM[4]	12,000

Table C.3 | Observed action use across LSPO training phases on Qwen3.5-27B. Revise and Switch transitions are also reported by their energy decrease rates.

Measure / phase	Revise (%)	Switch (%)	Stop (%)	Reach $T_{\max}$ (%)
Overall	49.8	25.9	24.3	11.8
Energy decrease rate	70.8	63.4	–	–
Early 0–30%	56.1	30.8	13.1	21.4
Late 70–100%	42.6	20.2	37.2	5.9

Revise therefore retains refinement history through z_t, while Switch resets that history to the replacement candidate. Stop preserves z_t. The energy $\tilde{E}(s_t; q) = E_\phi(h_t, z_t, q)$ and action policy $\pi_\theta(\cdot \mid s_t, q)$ consume the same stored coordinate.

Training Stages and Gradient Scope. We first fit the scoring branch on sampled training states using the energy-ranking supervision described below. Before policy optimization, we freeze the text encoder h_ξ, projection g_ψ, transition block f_η (including its conditioning embeddings and normalization), and energy head E_ϕ. The scoring encoder is a fixed parameter copy, separate from the trainable generator. These components remain fixed throughout rollout collection, candidate selection, RL/SI updates, and ordering audits. Coordinates can evolve recursively even though the update function is frozen.

Within each update, initial answers and text proposals are sampled using the rollout snapshot and treated as fixed environment outcomes for controller RL. Shared parameters receive gradients from both controller RL and answer internalization, which maximizes the likelihood of selected answers given the original prompt. A value-regression loss trains the value head. Rewards, stored scoring features, and selected targets are detached supervision; the ranking loss is confined to scoring-branch fitting. Thus RL/SI gradients leave all scoring-branch parameters unchanged.

Energy Supervision. Energy supervision is built from comparisons among states visited for the same prompt. Checkers for exact match, executable tests, multiple choice labels, and task verifiers identify successful states. Failed answers, states rejected by verifiers, longer states with no verifier improvement, variants with noisy energy, and controls using terminal rewards only supply negatives. The scalar head is fit with a pairwise margin objective so that verified states or states with lower cost receive lower energy than alternatives from the same prompt. The head is fit on training families, then frozen for candidate selection and for the ordering audit on held-out families in Section E; GSM8K, ARC-Challenge, BBH, HumanEval, and MBPP are excluded from fitting and endpoint selection in that audit.

Policy Update. Rollouts are generated by the current policy for the current minibatch, and no replay buffer carries trajectories across optimizer updates. Advantages are computed from the shaped rewards with generalized advantage estimation using discount $\gamma = 1$ and $\lambda = 0.95$, followed by normalization and value clipping at 0.2. The KL term is evaluated against the fixed reference action policy π_{ref} on the same visited states. The rollout policy $\pi_{\bar{\theta}_k}$ supplies the sampling probabilities for the update and is distinct from this reference. Stop is recorded with zero reward and a terminal mask, giving zero value bootstrap while retaining its policy-gradient and action-KL terms. The finite rollout horizon also terminates the episode with zero bootstrap. Scoring-branch fitting precedes these policy updates.

Action Statistics. The observed action frequencies in Table C.3 show a shift from exploration toward termination over training. Revise and Switch transitions decrease energy in most executed cases, while the lower probability of reaching $T_{\max}$ later in training is consistent with the stop action terminating local basins once further movement no longer offsets its costs.

Objective Components. The flow diagram follows information propagation through the update sequence. Figure C.2 maps each symbolic block to its contribution within that update.



Figure C.2 | Annotated reward and objective for LSPO. The assignment of credit per step, the regularization of the policy, and direct training on the answer occupy distinct terms within the update.



Figure C.3 | Training alternatives on Qwen3.5-27B. LSPO achieves accuracy comparable to test-time reflection with lower deployment cost and gains from constructive state changes.

C.3 Objective Context

From a reinforcement learning perspective, LSPO addresses the balance between sparse final rewards, dense shaping signals, and variance control [Sutton et al., 1998]. The progress reward gives the optimizer a local signal over lifted moves rather than raw token sequences, making constructive revisions legible while reducing the burden on credit assigned only to the final answer.

Recent reasoning RL literature reinforces the emphasis on signal structure. Reward design shapes whether policy learning remains stable and semantically aligned [Pan et al., 2026]. The LSPO ablations study the components governing state definition, local improvement criteria, and deployed execution.

Two contemporary research strands reinforce this reading. Transformed objectives improve pass@k performance within frameworks similar to GRPO [Le et al., 2026], indicating that reasoning RL is sensitive to objective design. Reward model analyses further show that downstream RL depends on accurate preferences and verifiable rationales [Lai et al., 2026]. LSPO applies this lesson to individual moves, where the supervisory signal is shaped by energy descent and edit costs.

C.4 Training Component Analysis

Figure C.3 reports the primary 27B comparison. Test-time reflection reaches 71.9% aggregate accuracy, 0.1 points above LSPO's 71.8%, while LSPO uses 4.25 s less latency and 440 fewer tokens. GRPO supplies a reinforcement learning comparison over final-answer rewards under the same seed set and sampling budget.

Tables C.4 and C.7 compare LSPO with controlled training alternatives. SI only on a fixed LSPO candidate pool uses the candidates and selected targets produced by Full LSPO, and measures what answer internalization achieves given those teacher candidates. Select then SFT uses the same fixed pool with verifier-based selection

Table C.4 | Matched training alternatives on Qwen3.5-27B. Evaluation examples and nominal budgets are shared; Table C.7 specifies candidate pools, reward definitions, and SI/SFT matching. SI only uses a fixed LSPO candidate pool.

Method	Agg. ± SD	LSPO diff. (95% CI)	Inference contract
Select then SFT	70.6 ± 0.17	+1.2 [0.7, 1.6]	direct
SI only	70.8 ± 0.16	+1.0 [0.6, 1.4]	direct
Without lifting	70.9 ± 0.18	+0.9 [0.5, 1.3]	direct
Without progress reward	70.0 ± 0.19	+1.8 [1.3, 2.3]	direct
Return-matched terminal reward	69.7 ± 0.20	+2.1 [1.5, 2.6]	direct
Test-time reflection	71.9 ± 0.19	–	critique + revision
LSPO	71.8 ± 0.15	–	direct

Table C.5 | Extended ablations on Qwen3.5-27B. Perturbations to the lifted coordinate and corruption of energy degrade distinct metrics, separating the role of state geometry from that of local reward shaping.

Family	Variant	Aggregate drop	Net gain
Lift	z dimension = 64	0.6	3.9
Lift	z dimension = 2	0.8	3.7
Lift	No lift	0.9	3.2
Lift	No switch	1.4	3.1
Lift	Revise only	1.7	2.7
Lift	Switch only	2.0	2.5
Energy	No margin	1.2	3.2
Energy	Noisy energy	1.5	2.9
Energy	No energy stop	1.8	2.4
Energy	Terminal only	2.1	2.2

and predetermined cost rules. Candidate construction is accounted for separately from the matched SI/SFT token exposure and updates. LSPO leads both alternatives; the paired intervals are positive. These comparisons distinguish downstream training effects conditional on the candidate pool; the teacher pool itself already reflects LSPO exploration.

Return-Matched Terminal Reward. To isolate reward timing, the terminal control retains the scoring function, edit metric, action space, target selection, termination rules, SI, and action KL of Full LSPO. For a completed trajectory with M executed Revise/Switch moves and final state s_M, define

$$R(\tau; q) = \tilde{E}(s_0; q) - \tilde{E}(s_M; q) - \lambda_{\text{edit}} \sum_{t=0}^{M-1} d(x_{t+1}, x_t) - \lambda_{\text{step}} M. \tag{C.2}$$

Let L count all recorded decisions, including an explicit Stop when present. The terminal control pays

$$r_t^{\text{terminal}} = \begin{cases} 0, & t < L-1, \\ R(\tau; q), & t = L-1. \end{cases} \qquad \sum_{t=0}^{L-1} r_t^{\text{terminal}} = \sum_{t=0}^{L-1} r_t^{\text{dense}} = R(\tau; q). \tag{C.3}$$

An explicit Stop receives the delayed trajectory return; at the horizon, the last executed move receives it. Immediate Stop gives $M = 0$ and zero return. Full LSPO retains zero reward for Stop itself. With $\gamma = 1$ and unchanged KL regularization, the two objectives assign the same return to every identical trajectory. Their sampled updates differ through reward timing, value fitting, and GAE with $\lambda = 0.95$, thereby testing finite-sample optimization rather than a different ideal trajectory objective.

Table C.5 extends the ablation analysis. Restricting the policy to paths that only revise degrades both aggregate quality and transition gain, pointing to the role of motion in the lifted state space beyond surface rewriting. Table C.6 measures sensitivity to energy corruption. Gaussian perturbations weaken but preserve part of the transition gain, while flipped or shuffled ordering drives rank metrics toward chance. The terminal reward control retains the trajectory return while delaying its feedback to termination.

C.5 Lifted Coordinate Analysis and MoE Transfer

The frozen probe in Table C.8 tests the predictive utility of z for a finite-capacity predictor on held-out transitions. Text plus the learned coordinate improves action prediction, reduces NLL, and increases energy AUC; shuffling

Table C.6 | Sensitivity to energy corruption on Qwen3.5-27B. Gaussian noise weakens but preserves part of the transition gain, whereas flipped or shuffled ordering drives rank metrics toward chance.

Energy signal	Agg.	Drop	Net gain	AUC	Pairwise
Clean LSPO energy	71.8	0.0	4.7	0.792	0.734
Gaussian noise	70.3	1.5	2.9	0.731	0.681
Label flip or shuffle	68.6	3.2	0.7	0.508	0.506
Terminal only	69.7	2.1	2.2	0.681	0.641

Table C.7 | Control specifications for training alternatives. Nominal budgets specify candidate limits, update counts, and sampling settings; they do not imply identical realized token counts or GPU hours.

Variant	Candidate pool	State space	Target selector	Controller RL	Reward signal	Transfer target
Full LSPO	Dynamic rollout	Lifted (x, z)	Frozen $\tilde{E}$	Dense policy	$\Delta\tilde{E}$ − costs	$\min \tilde{E}$ (SI)
Return-matched terminal reward	Dynamic rollout	Lifted (x, z)	Frozen $\tilde{E}$	Delayed policy	Trajectory $R(\tau)$	$\min \tilde{E}$ (SI)
SI only on fixed pool	Fixed Full pool	Lifted (x, z)	Frozen $\tilde{E}$	None	None	$\min \tilde{E}$ (SI)
Select then SFT	Fixed Full pool	Surface text	Task verifier	None	None	Verifier-best (SFT)
Without lifting	Dynamic rollout	Surface text	Surface E	Dense policy	ΔE − costs	$\min E$ (SI)
Without progress reward	Dynamic rollout	Lifted (x, z)	Frozen $\tilde{E}$	Dense policy	−costs only	$\min \tilde{E}$ (SI)

z disrupts the prompt association. These probe differences measure predictive utility for the fitted probe; the information identity in Proposition 3 concerns Bayes-optimal log loss.

Table C.9 evaluates whether the lifted-coordinate result is explained by parameter count or generic conditioning capacity. The controls use the same Qwen3.5-27B backbone, candidate budget, training budget, and three-seed protocol as full LSPO. A same-parameter no-lift MLP, a random coordinate, a learned nuisance coordinate, and a frozen or random projection all remain below full LSPO. Their net gains range from 2.8 to 3.0 points, compared with 4.7 for full LSPO; the paired intervals for the aggregate gaps remain positive. These results support the interpretation that the learned, prompt-conditioned coordinate carries refinement-relevant information beyond extra parameters alone.

Table C.10 repeats the component analysis on Qwen3.5-35B-A3B. The same ordering of full LSPO over the component removals provides transfer evidence for the MoE backbone, while Qwen3.5-27B remains the setting used for the primary causal comparison.

C.6 Training Configuration

The following configuration specifies the primary training setting and the sensitivity ranges used in the component analyses.

The primary 27B LSPO run follows a fixed configuration. Reported means use seeds 42, 1234, and 3407. The objective coefficients are $\beta = 0.02$, $\lambda_{\text{edit}} = 0.10$, and $\lambda_{\text{step}} = 0.01$. The environment uses a maximum path length of 6, an auxiliary dimension of 8, an imitation weight of 0.3, temperature 0.6, and top-$p = 0.95$. Optimization uses the Muon optimizer across all trainable parameters [Jordan et al., 2024, Liu et al., 2025a]. The configuration sets a learning rate of 2×10^{-5}, momentum 0.95, Nesterov updates, five Newton–Schulz steps, weight decay 0.1, and gradient clipping at 1.0. The schedule applies 500 warmup steps and cosine decay to 10^{-7} over a $15{,}000$ step global horizon.

The benchmark suite and evaluation metrics remain fixed. Deployment evaluation measures pass@1 with direct generation or execution success. Supporting diagnostics include pass@16, transition rates, energy, latency, and output length.

Reported Variation. For the main experiments and training ablations, ± denotes the sample standard deviation across the three independent training seeds. We first average each seed's results over the complete evaluation set, then compute SD across those three means, using divisor $3 - 1$. The selection-budget audit in Table E.8 instead fixes one checkpoint and reports bootstrap SD over evaluation inputs.

C.7 Hyperparameter Selection

The 27B hyperparameter search considers $\beta \in \{0.005, 0.01, 0.02, 0.05, 0.1\}$, $\lambda_{\text{edit}} \in \{0.0, 0.05, 0.1, 0.2, 0.4\}$, and $\lambda_{\text{step}} \in \{0.0, 0.005, 0.01, 0.02, 0.05\}$. Selection by aggregate validation accuracy under the three-seed protocol, with ties broken by minimized transition harm, yields $(0.02, 0.10, 0.01)$. These ranges describe model selection; the reported dimension ablations and joint candidate/horizon sweep provide the corresponding empirical sensitivity results.

Table C.8 | Frozen probe for information in the lifted coordinate on transitions held out from fitting. Adding the learned coordinate improves action prediction and energy ordering; shuffled coordinates remove the association.

Input condition	Action acc. ± SD	NLL ± SD	Energy AUC ± SD
Text only	62.8 ± 0.7	0.842 ± 0.011	0.681 ± 0.010
Text plus z	68.9 ± 0.6	0.768 ± 0.010	0.732 ± 0.009
Text plus shuffled z	60.9 ± 0.8	0.874 ± 0.013	0.641 ± 0.012
Text plus zero z	63.4 ± 0.7	0.831 ± 0.012	0.687 ± 0.011

Table C.9 | Parameter-matched controls for the lifted coordinate on Qwen3.5-27B. All variants use the same candidate budget, training budget, and three-seed protocol. The final column reports the paired aggregate gap between full LSPO and each control.

Variant	Agg. ± SD	Net gain	LSPO − variant (95% CI)
Full LSPO	71.8 ± 0.15	4.7	–
Reference baseline (Table 4)			
Current no-lift baseline	70.9 ± 0.18	3.2	+0.9 [0.5, 1.3]
Parameter-matched coordinate controls			
Same-parameter no-lift MLP	70.8 ± 0.18	3.0	+1.0 [0.6, 1.4]
Random z, matched dim.	70.3 ± 0.19	2.8	+1.5 [1.1, 1.9]
Learned nuisance coordinate	70.6 ± 0.18	2.9	+1.2 [0.8, 1.6]
Frozen / random projection	70.4 ± 0.18	2.9	+1.4 [1.0, 1.8]

Baseline models are instantiated under fixed matched settings. Standard preference optimization methods use minimal latency budgets; methods that operate on sampled paths consume longer outputs and higher latency budgets. LSPO narrows this efficiency gap by embedding machinery for local transitions into the parameters through answer internalization.

C.8 Reward Decomposition

The shaped path functional supplies the empirical ablations with a formal counterpart. Proposition 1, established in Section 2, shows that the progress reward telescopes into final energy improvement minus accrued edit and step costs, and Corollary 1 explains the preference for short, localized repairs over destructive global rewrites.

Telescoping identity. Here T counts executed Revise/Switch moves. A terminal Stop is a zero-reward self-transition and leaves the identities unchanged. Substituting the move reward from eq. (4) gives

$$\begin{aligned}\sum_{t=0}^{T-1} r_t &= \sum_{t=0}^{T-1} \big(\tilde{E}(s_t;q) - \tilde{E}(s_{t+1};q)\big) - \lambda_{\text{edit}} \sum_{t=0}^{T-1} d(x_{t+1}, x_t) - \lambda_{\text{step}} T \\ &= \tilde{E}(s_0;q) - \tilde{E}(s_T;q) - \lambda_{\text{edit}} \sum_{t=0}^{T-1} d(x_{t+1}, x_t) - \lambda_{\text{step}} T.\end{aligned} \tag{C.4}$$

Corollary 1 (Preference for economical paths)**.** *Let τ and τ' be two trajectories for the same prompt q with identical initial and terminal states, satisfying $s_0 = s'_0$ and $s_{T_\tau} = s'_{T_{\tau'}}$. If*

$$\sum_{t=0}^{T_\tau - 1} d(x_{t+1}, x_t) \le \sum_{t=0}^{T_{\tau'} - 1} d(x'_{t+1}, x'_t) \qquad \textit{and} \qquad T_\tau \le T_{\tau'}, \tag{C.5}$$

then the cumulative shaped reward satisfies $R(\tau;q) \ge R(\tau';q)$. The inequality is strict whenever at least one inequality is strict and the corresponding coefficient λ_{edit} or λ_{step} is strictly positive.

Path economy argument. Under identical endpoints ($s_0 = s'_0$ and $s_{T_\tau} = s'_{T_{\tau'}}$), the net energy term $\tilde{E}(s_0;q) - \tilde{E}(s_T;q)$ is invariant across paths. Under this telescoping relation, $R(\tau;q) - R(\tau';q)$ reduces entirely to differences in cumulative edit and step penalties, favoring trajectories that achieve the same descent with fewer tokens altered and fewer transitions taken.

The difference in energy aligns formally with potential reward shaping [Ng et al., 1999]. The edit and step penalties restrict the preferred policy class by penalizing unnecessarily long or destructive correction paths, favoring economical paths with net energy improvement.

Table C.10 | Component ablation on the Qwen3.5-35B-A3B MoE backbone. The dense 27B model remains the primary attribution setting; this table tests whether the component pattern transfers to the MoE model.

Variant	Agg.	Gain	Latency (s)	Tokens	GPU hours
LSPO full	72.6	4.4	8.30	1097	2410
Without lifting	71.6	2.9	8.88	1141	2265
Without progress reward	70.8	1.3	9.38	1185	2193
Without internalization	71.1	2.1	9.13	1163	2073
Outcome RL	71.5	2.7	9.33	1200	1940
DPO	68.8	1.5	8.08	1048	990

C.9 Noise Robustness

The ablation with noisy energy motivates a sensitivity analysis. Because the LSPO path reward relies on local energy differences, any bounded state perturbation results in a bounded endpoint error.

Proposition 4 (Bounded energy noise perturbs cumulative reward only through endpoint error)**.** *Let*

$$\hat{E}(s;q) = \tilde{E}(s;q) + \delta(s;q) \tag{C.6}$$

with $|\delta(s;q)| \le \varepsilon$ for every visited state. Let $R(\tau;q)$ denote the cumulative shaped reward computed from $\tilde{E}$, and let $\hat{R}(\tau;q)$ denote the cumulative shaped reward computed from $\hat{E}$ using the same edit and step penalties. For any trajectory $\tau = (s_0, a_0, \dots, s_T)$,

$$\hat{R}(\tau;q) - R(\tau;q) = \delta(s_0;q) - \delta(s_T;q), \qquad \textit{and} \qquad \left|\hat{R}(\tau;q) - R(\tau;q)\right| \le 2\varepsilon. \tag{C.7}$$

Endpoint perturbation. By proposition 1,

$$R(\tau;q) = \tilde{E}(s_0;q) - \tilde{E}(s_T;q) - \lambda_{\text{edit}} \sum_{t=0}^{T-1} d(x_{t+1}, x_t) - \lambda_{\text{step}} T \tag{C.8}$$

and

$$\hat{R}(\tau;q) = \hat{E}(s_0;q) - \hat{E}(s_T;q) - \lambda_{\text{edit}} \sum_{t=0}^{T-1} d(x_{t+1}, x_t) - \lambda_{\text{step}} T. \tag{C.9}$$

Subtracting the two expressions cancels the penalty terms and leaves

$$\hat{R}(\tau;q) - R(\tau;q) = \delta(s_0;q) - \delta(s_T;q). \tag{C.10}$$

The bound uses $|\delta| \le \varepsilon$ at the two endpoints.

Corollary 2 (Trajectory ranking is preserved under a sufficient terminal margin)**.** *Let τ and τ' be two trajectories for the same prompt that start from the same initial state s_0. Under the conditions of proposition 4, if*

$$R(\tau;q) - R(\tau';q) > 2\varepsilon, \tag{C.11}$$

the perturbed ranking satisfies $\hat{R}(\tau;q) > \hat{R}(\tau';q)$.

Ranking margin. Because the two trajectories share the same initial state,

$$\big(\hat{R}(\tau;q) - \hat{R}(\tau';q)\big) - \big(R(\tau;q) - R(\tau';q)\big) = -\delta(s_T;q) + \delta(s'_T;q). \tag{C.12}$$

Its absolute value is at most 2ε, giving

$$\hat{R}(\tau;q) - \hat{R}(\tau';q) \ge R(\tau;q) - R(\tau';q) - 2\varepsilon > 0, \tag{C.13}$$

so the perturbed ranking is retained.

This bound gives a sufficient stability condition for a fixed candidate set under uniformly bounded state-wise corruption. The Gaussian-noise ablation provides a separate empirical sensitivity test. Applying the deterministic bound to any noise realization requires that all evaluated perturbations satisfy the stated limit.

D Internalization and Stopping Diagnostics

This appendix evaluates the alignment between training rollouts and direct policy execution, the step-level monotonicity of energy descent, and the formal mechanics governing stopping conditions and answer internalization.



Figure D.1 | Energy discriminates correct from incorrect endpoints across scales. Correct outputs consistently concentrate in regions with lower energy.



Figure D.2 | Training endpoints align with direct outputs after LSPO. The divergence between terminal states selected during alignment and direct generations is minimal under the LSPO objective.

Figure D.1 evaluates energy as an ordering signal. Across all three model scales, lower final energy is associated with higher correctness, though slopes and separation margins vary by capacity. We therefore compare absolute energy values within each backbone, consistent with prior work on model calibration and uncertainty [Kadavath et al., 2022, Yin et al., 2023, Guo et al., 2017].

Figure D.2 separates training exploration from deployed policy outputs. LSPO shows the smallest energy gap between selected training answers and direct outputs, the empirical signature of answer internalization. The analysis measures whether correction traces shift the policy distribution, complementing prior studies of self-correction [Kumar et al., 2024, Ma et al., 2025, Xiong et al., 2025].

Figure D.3 resolves the mechanism at the step level. The energy monotonicity rate measures how often a move decreases state energy; the rate of preserving correct states measures whether already correct states are retained; and the stop optimality rate evaluates whether generation ends near the empirical minimum along the visited path. The ordering of these diagnostics follows the geometric constraints encouraged by LSPO.

Figure D.4 extends the transition diagnostic beyond the primary 27B setting. The ordering persists at 9B and 35B-A3B. LSPO increases constructive conversions from incorrect to correct without the large conversions from correct to incorrect observed in search baselines with high cost.

D.1 Answer and Span Transition Metrics

For each method, answer-level transitions compare the before and after correctness labels of the same N answer pairs. Let $n_{W\to C}$ and $n_{C\to W}$ count repairs (wrong to correct) and regressions (correct to wrong), respectively. Both reported rates use the full paired sample as denominator,

$$G_{\text{ans}} = 100\, n_{W\to C}/N, \qquad H_{\text{ans}} = 100\, n_{C\to W}/N, \qquad \text{NetGain} = G_{\text{ans}} - H_{\text{ans}}. \tag{D.1}$$



Figure D.3 | Step diagnostics across scales. LSPO preserves the strongest monotonicity in energy descent, correct local structure, and stop optimality across the evaluated backbones.



Figure D.4 | Transition gains across scales. LSPO achieves the largest surplus of conversions from incorrect to correct on every backbone while keeping conversions from correct to incorrect modest.

Thus the 6.4% repair and 1.7% regression frequencies for LSPO yield a 4.7-point net gain. Correct-to-correct (C→C) and incorrect-to-incorrect (W→W) pairs contribute zero to this difference.

The span audit in Table D.1 uses before/after validity labels, denoted V and I, for paired spans. Each method has its own initial valid fraction p_V. Preservation and damage condition on initially valid spans, while repair conditions on initially invalid spans,

$$\begin{aligned} P_{\text{span}} &= \Pr(V_{\text{after}} \mid V_{\text{before}}), & D_{\text{span}} &= 1 - P_{\text{span}}, \\ R_{\text{span}} &= \Pr(V_{\text{after}} \mid I_{\text{before}}), & \text{NetSpanGain} &= 100[(1-p_V)R_{\text{span}} - p_V D_{\text{span}}]. \end{aligned} \tag{D.2}$$

Probabilities in this equation lie in $[0, 1]$; net gain is in percentage points. Full LSPO preserves 95.8% of initially valid spans and repairs 29.5% of initially invalid spans, yielding a 16.0-point increase in the valid-span fraction. The matched no-lift control yields 9.9 points. These results support preservation and repair of the spans assessed by the validity labels; answer-level and span-level gains describe distinct units of analysis.

D.2 Stopping Condition

The stop optimality diagnostic has a formal counterpart. Continuing from a state cannot improve cumulative reward when every future energy decrease is exhausted by the associated edit and step costs.

Proposition 5 (A sufficient stopping condition)**.** *Fix an input q and a move index t, counting Revise/Switch transitions. Suppose that for every admissible continuation*

$$s_t, s_{t+1}, \ldots, s_T \tag{D.3}$$

starting from s_t, each future transition indexed by $u \in \{t, \ldots, T-1\}$ satisfies

$$\tilde{E}(s_u; q) - \tilde{E}(s_{u+1}; q) \leq \lambda_{\text{edit}} d(x_{u+1}, x_u) + \lambda_{\text{step}}. \tag{D.4}$$

Every such continuation has nonpositive additional cumulative reward,

$$\sum_{u=t}^{T-1} r_u \leq 0. \tag{D.5}$$

Table D.1 | Span validity transitions. Initial validity, preservation, repair, and damage are percentages; net gain is in percentage points. Preservation and damage condition on initially valid spans; repair conditions on initially invalid spans. Net gain weights these rates by each method's initial valid fraction.

Method	Initial p_V	$V \to V$	$I \to V$	$V \to I$	Net gain
Full LSPO	40.1	**95.8**	**29.5**	**4.2**	**+16.0**
Same-parameter no-lift MLP	39.7	92.1	21.6	7.9	+9.9
Without progress reward	39.8	89.8	18.7	10.2	+7.2
Terminal-only reward	39.1	90.3	16.9	9.7	+6.5
GRPO	39.4	90.9	18.6	9.1	+7.7

For the unregularized shaped return, stopping with zero reward weakly dominates these continuations. The action-KL penalty in eq. (6) *can change the regularized policy preference.*

Stopping argument. The assumed inequality implies

$$\tilde{E}(s_u; q) - \tilde{E}(s_{u+1}; q) - \lambda_{\text{edit}} d(x_{u+1}, x_u) - \lambda_{\text{step}} \leq 0 \tag{D.6}$$

for every $u \geq t$, i.e., $r_u \leq 0$. Summing over $u = t, \ldots, T-1$ gives nonpositive cumulative reward.

D.3 Internalization Projection

The alignment figures motivate a formal interpretation of the answer internalization objective. Training selects an answer distribution with lower energy, and the deployed generator is then optimized toward it as closely as model capacity permits. For each input q, hold fixed the sampled-target distribution μ_q of selected outputs $x_T^*(q)$ induced by the selection procedure during training.

Proposition 6 (Answer internalization as forward KL projection)**.** *For each input q,*

$$\mathbb{E}_{x \sim \mu_q}[\log p_\theta(x \mid q)] = -H(\mu_q) - D_{\text{KL}}\big(\mu_q \,\|\, p_\theta(\cdot \mid q)\big), \tag{D.7}$$

so maximizing $J_{\text{SI}}(\theta)$ is equivalent, up to the parameter-independent constant $\mathbb{E}_q[H(\mu_q)]$, to minimizing the expected forward KL to the selected-answer distributions.

Projection identity. Substituting $\mathbb{E}_{x \sim \mu_q}[\log \mu_q(x)] = -H(\mu_q)$ into the definition of forward relative entropy yields the identity; averaging over q and dropping the constant term gives the equivalence.

Proposition 7 (Bounded task scores are controlled by forward KL on the selected-answer distribution)**.** *Fix an input q and let $c_q(x) \in [0, 1]$ denote any correctness or task success score for output x. Define*

$$\Delta_q(\theta) = \mathbb{E}_{x \sim \mu_q}[c_q(x)] - \mathbb{E}_{x \sim p_\theta(\cdot \mid q)}[c_q(x)]. \tag{D.8}$$

The gap for each input obeys

$$|\Delta_q(\theta)| \leq \text{TV}\big(\mu_q, p_\theta(\cdot \mid q)\big) \leq \sqrt{\frac{1}{2} D_{\text{KL}}\big(\mu_q \,\|\, p_\theta(\cdot \mid q)\big)}. \tag{D.9}$$

Averaging over inputs gives

$$\mathbb{E}_q[|\Delta_q(\theta)|] \leq \sqrt{\frac{1}{2} \mathbb{E}_q\big[D_{\text{KL}}\big(\mu_q \,\|\, p_\theta(\cdot \mid q)\big)\big]}. \tag{D.10}$$

Total variation bound. For any function $f \in [0, 1]$,

$$\big|\mathbb{E}_{\mu_q}[f(x)] - \mathbb{E}_{p_\theta(\cdot \mid q)}[f(x)]\big| \leq \text{TV}\big(\mu_q, p_\theta(\cdot \mid q)\big). \tag{D.11}$$

Applying this to $f = c_q$ gives the first bound. The second bound is Pinsker's inequality,

$$\text{TV}\big(\mu_q, p_\theta(\cdot \mid q)\big) \leq \sqrt{\frac{1}{2} D_{\text{KL}}\big(\mu_q \,\|\, p_\theta(\cdot \mid q)\big)}. \tag{D.12}$$

Finally, averaging over q and using Jensen's inequality for the concave square root function yields

$$\mathbb{E}_q[|\Delta_q(\theta)|] \leq \mathbb{E}_q\left[\sqrt{\frac{1}{2} D_{\text{KL}}\big(\mu_q \,\|\, p_\theta(\cdot \mid q)\big)}\right] \leq \sqrt{\frac{1}{2} \mathbb{E}_q\big[D_{\text{KL}}\big(\mu_q \,\|\, p_\theta(\cdot \mid q)\big)\big]}. \tag{D.13}$$

For each fixed target distribution, the bound links the alignment diagnostic in Figure D.2 to the training objective, showing that as the forward KL term decreases, the expected gap in bounded task success scores is correspondingly controlled. It conditions on a fixed μ_q and is informative only where the generator can approach that distribution; thus, we use it as a consistency interpretation of the alignment figures rather than as an accuracy guarantee.



Figure E.1 | Deployment cost distributions. LSPO stays within the latency and length ranges established by preference optimization, remaining below baselines that use extensive search.

D.4 Comparison with Test-Time Reflection

Test-time reflection systems retain critique and revision within the inference loop [Jiang et al., 2026]. LSPO generates and selects training traces before deployment, then serves answers with the direct generator. The alignment diagnostics above measure how much of the resulting improvement persists in that generator, while the deployment comparison quantifies the cost of retaining deliberation at inference.

E Deployment Complexity and Held-Out Energy Ordering

Deployment cost, energy ordering on tasks held out from training, and compute accounting summarize LSPO's operational profile. The diagnostics characterize energy as a local ordering signal and quantify the inference cost that remains after correction traces are absorbed into the model.

Figure E.1 quantifies the deployment cost of the direct policy. Systems that use extensive search can incur large latency and verbosity penalties [Chen et al., 2021, Guo et al., 2025]. LSPO produces slightly longer generations than standard preference methods such as DPO, yet remains below the token and latency costs of GRPO and SCoRe. The method stays within a practical deployment range while preserving the accuracy gains reported in the main text.

The next analyses study the relationship between state energy and empirical correctness. When lower scores correlate with correct outputs, the scalar can serve as both a shaping signal during training and a diagnostic of candidate quality. Prior work on calibration fragility [Niculescu-Mizil and Caruana, 2005, Guo et al., 2017] and semantic uncertainty [Kuhn et al., 2023, Farquhar et al., 2024, Kossen et al., 2024, Aichberger et al., 2024] motivates interpreting energy as a structural indicator of local state ordering.

E.1 Energy Ordering on Held-Out Tasks

The empirical correlation between low energy and correctness reported in Figure D.1 motivates a conditional calibration analysis. Under a shared prompt-wise monotone calibration map, an almost-sure energy ordering under a coupling implies an ordering of expected correctness.

All ordering metrics evaluate the utility score $u(s, q) = -\tilde{E}(s; q)$, where higher u indicates lower energy and a preferred candidate under the learned ordering. The AUC between energy and correctness measures the probability that a correct candidate receives a higher u than an incorrect candidate [Fawcett, 2006]. Spearman and Kendall compute rank correlations between u and the binary correctness label over the evaluated candidate set, with Kendall using a rank statistic corrected for ties [Spearman, 1961, Kendall, 1938]. Pairwise preference accuracy calculates the fraction of differently labeled candidate pairs within each prompt where the correct



Figure E.2 | Frozen energy ordering under distribution shift. On tasks held out from fitting (GSM8K, ARC-Challenge, BBH, HumanEval, and MBPP), the LSPO energy head outperforms outcome only, shuffled, and random controls in area under the curve, Spearman correlation, and pairwise accuracy.

Table E.1 | Frozen energy ordering under distribution shift. LSPO yields the strongest AUC, rank correlation, and pairwise preference accuracy on both the fitted task families and tasks held out from fitting.

Score	AUC	Spearman	Kendall	Pairwise	Bins	ECE
Task families used for fitting include math, code, logic, and science						
Random energy	0.502	0.01	0.01	0.502	2	0.241
Outcome only score	0.681	0.31	0.22	0.641	4	0.132
LSPO energy	0.792	0.48	0.35	0.734	5	0.071
Shuffled LSPO energy	0.508	0.01	0.01	0.506	2	0.235
Task families held out from fitting include GSM8K, ARC-C, BBH, HumanEval, and MBPP						
Random energy	0.501	0.00	0.00	0.501	2	0.247
Outcome only score	0.612	0.20	0.14	0.583	3	0.170
LSPO energy	0.704	0.34	0.24	0.658	4	0.112
Shuffled LSPO energy	0.511	0.02	0.01	0.507	2	0.238

candidate has lower energy, aligning with the standard pairwise ranking logic of preference models [Bradley and Terry, 1952]. The Bins metric partitions candidates into five equal-frequency energy bins and reports the length of the contiguous monotone prefix, measuring how many of the five bins preserve the expected decrease in empirical correctness as energy rises. ECE partitions candidates into bins with equal numbers via a frozen monotonic calibration map and reports the expected absolute difference between the predicted and empirical correctness probabilities [Naeini et al., 2015, Guo et al., 2017].

Data Separation and Locked Evaluation. Table C.2 identifies the public training corpora. The main evaluation suites are MATH-500, AIME25, GPQA, LiveCodeBench, ZebraLogic, and MMLU-Pro. GSM8K [Cobbe et al., 2021], ARC-Challenge [Clark et al., 2018], BBH [Suzgun et al., 2023], HumanEval [Chen et al., 2021], and MBPP [Austin et al., 2021] provide additional benchmark-level holdouts for transfer and frozen energy-ordering audits. Both groups follow the same exclusion rules.

Domain overlap is permitted. Evaluation examples and near-duplicates are excluded from policy training, energy fitting, pairwise ranking construction, training-target selection, verifier/checker threshold tuning, hyperparameter search, checkpoint selection, selection of training and audit budgets, and construction of prompts, rubrics, or synthetic references. Use of other examples from the same benchmark requires explicit deduplication against the evaluation set.

Evaluation questions enter only the locked final evaluation. Generation and candidate selection use the fixed model and scoring branch without gold answers, correctness labels, test-time verifiers, or judge feedback. External checkers and judges score the resulting outputs for reporting. Decoding settings and the training budget K and audit budgets K_{sel} are fixed before evaluation; test results serve only to report performance across those budgets.

As reported in Figure E.2 and Table E.1, the domain shift reduces the LSPO energy AUC from 0.792 to 0.704 and pairwise preference accuracy from 0.734 to 0.658. Both metrics remain above the outcome only and shuffled controls, supporting energy as a local ranking signal beyond the fitted task families.

Table E.2 | Direct generation on benchmark suites held out from policy training, energy fitting, and endpoint selection. LSPO improves over Base on every benchmark.

Method	GSM8K	ARC-C	BBH	HumanEval	MBPP	Avg. $\pm$ SD
Base	88.4	84.7	66.2	55.5	62.4	71.4 ± 0.22
DPO	89.0	85.3	67.1	56.4	63.0	72.2 ± 0.20
GRPO	90.6	86.7	69.0	58.6	64.8	73.9 ± 0.22
SCoRe	91.1	87.1	69.3	59.1	65.0	74.3 ± 0.24
LSPO	91.5	87.4	70.4	60.1	65.2	74.9 ± 0.20

Table E.3 | Joint candidate and horizon sensitivity on Qwen3.5-27B. K counts the maximum number of retained states per input, including the initial direct state s_0. Values are means $\pm$ sample SD across three independent training seeds. Aggregate accuracy reaches 71.8 at $(T_{\max}, K) = (6, 7)$ and remains at that value for $(8, 9)$.

$T_{\max}$	K	Agg. $\pm$ SD	Gain $\pm$ SD	Path length	Unique ratio
2	3	70.9 ± 0.18	3.2 ± 0.30	1.6	0.82
4	5	71.5 ± 0.16	4.2 ± 0.26	2.7	0.76
6	7	71.8 ± 0.15	4.7 ± 0.23	3.4	0.71
8	9	71.8 ± 0.16	4.8 ± 0.24	3.7	0.66

E.2 Direct Generation on Tasks Outside the Training Distribution

The evaluation on benchmarks held out from fitting also tests the deployed policy itself. The suites in Table E.2 follow the exclusion rules above, including exclusion from training-target selection. LSPO improves over Base on all five tasks and reaches an average of 74.9 on held-out tasks, above SCoRe at 74.3, without a regression on any task relative to Base. The held-out policy results complement the ordering audit: the frozen energy head retains local signal under shift, and the compiled policy transfers the corresponding improvement gains to direct generation.

E.3 Joint Candidate and Horizon Sensitivity

Candidate quantity and transition horizon affect the local candidate space explored during alignment. Here K is the maximum total number of candidate states retained per input q, including the initial direct-generation state s_0. Table E.3 varies K and $T_{\max}$ together under the same training and evaluation protocol, measuring sensitivity to their joint budget. The gain persists at every tested budget; aggregate accuracy reaches 71.8 at the primary configuration $(T_{\max}, K) = (6, 7)$ and remains at that value for $(8, 9)$. The larger budget increases realized path length and reduces the ratio of unique candidates.

Proposition 8 (Accuracy improvement under monotone energy calibration)**.** *Fix a prompt q and two endpoint distributions μ_q, ν_q. Assume a common measurable nonincreasing map ϕ_q calibrates correctness under each distribution, so that for $\kappa \in \{\mu_q, \nu_q\}$*

$$\mathbb{P}_{S\sim\kappa}\big(\text{correct} = 1 \mid \tilde{E}(S; q) = e, q\big) = \phi_q(e). \tag{E.1}$$

Suppose there exists a coupling (S_μ, S_ν) with marginals μ_q and ν_q such that

$$\tilde{E}(S_\mu; q) \le \tilde{E}(S_\nu; q) \tag{E.2}$$

holds with probability one. Then the coupled endpoints satisfy

$$\mathbb{E}_{S_\mu\sim\mu_q}\Big[\phi_q\big(\tilde{E}(S_\mu; q)\big)\Big] \ge \mathbb{E}_{S_\nu\sim\nu_q}\Big[\phi_q\big(\tilde{E}(S_\nu; q)\big)\Big]. \tag{E.3}$$

Coupling argument. Under the assumed coupling and the monotonicity of ϕ_q, the pointwise ordering $\phi_q(\tilde{E}(S_\mu; q)) \ge \phi_q(\tilde{E}(S_\nu; q))$ holds almost surely. Taking expectations directly preserves the inequality.

The common calibration map and coupled ordering are sufficient conditions for the correctness comparison. An ordering of mean energy alone is insufficient. The empirical ordering audits assess local ranking utility and leave these distribution-level assumptions conditional.

E.4 Energy Semantics and Local Ordering

The energy $\tilde{E}$ is a learned scalar head trained for state ranking. Unlike global uncertainty measures such as entropy or Fisher information [Shannon, 1948, Rényi, 1961, Fisher, 1925, Rao et al., 1945, Cramér, 1946],

Table E.4 | Policy transfer pilot on subjective tasks. LSPO maintains positive transfer over Base across both benchmarks without requiring test-time rubrics, reference answers, or verifier loops.

Method	WritingBench L&A	Δ Base	MT-Bench Roleplay	Δ Base	avg.
Base	7.42 ± 0.08	0.00	7.61 ± 0.11	0.00	7.52
DPO	7.50 ± 0.07	+0.08	7.68 ± 0.10	+0.07	7.59
GRPO	7.36 ± 0.09	-0.06	7.53 ± 0.12	-0.08	7.45
SCoRe	7.32 ± 0.09	-0.10	7.49 ± 0.12	-0.12	7.41
DRO-adapted	7.53 ± 0.08	+0.11	7.70 ± 0.10	+0.09	7.62
LSPO	7.48 ± 0.08	+0.06	7.66 ± 0.10	+0.05	7.57

Table E.5 | Frozen energy ordering in open form transfer. Energy is evaluated as an ordering of seven candidates from each input; judge scores are used only for evaluation.

Subset	Spearman ρ	Kendall τ	Pairwise AUC	Δ
WritingBench Literature and Arts	0.34 ± 0.04	0.24 ± 0.03	0.675 ± 0.018	+0.42
MT-Bench Roleplay	0.29 ± 0.06	0.20 ± 0.04	0.642 ± 0.026	+0.35

it serves as a local diagnostic of state quality, where lower energy identifies a preferred candidate within the immediate vicinity.

Recent evaluations of factuality in short form text show that empirical correctness depends on measurement protocols specific to each domain [Wei et al., 2024]. The scalar carries evidence here because it tracks constructive revisions within the transition geometry induced by LSPO. We pair energy analysis with transition diagnostics to evaluate both state ordering and answer changes.

E.5 Open Form Transfer

The open form pilot measures policy transfer on subjective tasks. We use the Literature and Arts subset of WritingBench [Wu et al., 2026b] and the Roleplay subset of MT-Bench [Zheng et al., 2023]. Each method generates one response per turn without revision or candidate selection, and the same judge model and protocol score all outputs. We also evaluate DRO-adapted, based on Direct Reasoning Optimization [Xu et al., 2025]. DRO optimizes unverifiable reasoning via token-level self-certainty rewards (R3), query-specific rubric gating, and variance-based filtering over GRPO. Because the original framework targets reference-based tasks like ParaRev, RaR-Medicine, ContractNLI, and FinQA, we adapt it to open form evaluation by supplying synthesized references and task rubrics.

As shown in Table E.4, training paradigms diverge sharply on subjective tasks. Standard RL with GRPO and self-correction with SCoRe degrade below Base to combined averages of 7.45 and 7.41, as optimizing exclusively for verifiable correctness weakens open-ended expressiveness. Preference tuning with DPO maintains conversational quality at 7.59. DRO-adapted reaches the highest combined average of 7.62 by leveraging rubric gating and reference guidance. Meanwhile, LSPO achieves positive transfer across both suites at a 7.57 combined average, clearly exceeding GRPO and SCoRe while remaining close to DPO. Crucially, while DRO-adapted depends on synthesized references and rubrics, LSPO operates in a clean direct generation regime with zero test-time references, rubrics, or verifier loops.

For a more local audit, we score seven candidates from the same prompt with the frozen energy head and use judge scores only as evaluation labels. We compute correlations within each input and pairwise ordering, then average those quantities across prompts. Table E.5 shows moderate alignment, strongest for instruction fit, coherence, and character consistency. Table E.6 identifies prompts requiring high creativity and playful improvisation, where the learned ordering is less reliable. Energy supports local assessment of constrained style and consistency; literary quality and expressive richness require additional signals.

E.6 Compute Disclosure

Training uses $8\times$ NVIDIA A100 80GB GPUs. The reported 2983.2 GPU-hours for LSPO is the mean cost of one training run across seeds 42, 1234, and 3407. Engineering evaluation requires concrete resource accounting alongside complexity analysis. Table E.7 documents the primary 27B hardware footprint and deployment cost in one view, including peak memory, elapsed time, total GPU hours, pilot budgets, latency, and output length.

Table E.6 | Alignment dimensions and failure slices for the open form audit. The frozen energy ordering is most reliable on constrained dimensions, while open-ended creativity and expressive richness remain its main failure modes.

Subset	Strongest alignment	Weakest alignment	Failure slice
WritingBench Literature and Arts	Instruction fit, coherence	Creativity, originality	Prompts requiring high creativity
MT-Bench Roleplay	Character consistency, instruction fit	Expressive richness	Playful improvisation

Table E.7 | Compute and deployment accounting for Qwen3.5-27B. Training uses $8\times$ NVIDIA A100 80GB GPUs. The LSPO cost of 2983.2 GPU-hours is the mean per-run cost across three seeds.

Method	Peak mem (GB)	Elapsed time (h)	GPU hrs	Pilot GPU hours	Latency (s)	Output tokens
DPO	57.7	152.2	1217.6	146.1	10.42	1196
Step-DPO	57.7	203.1	1624.8	195.0	10.73	1242
GRPO	57.7	298.3	2386.4	286.4	12.04	1370
GDPO	57.7	335.6	2684.8	322.2	11.54	1324
SCoRe	57.7	358.2	2865.7	343.9	13.12	1501
LSPO	61.9	372.9	2983.2	358.0	10.93	1265

The resource table fixes the balance between training and deployment. LSPO spends more during training than SCoRe, adding 117.5 GPU hours on 27B. At deployment it avoids explicit critique, revision, or search, reducing average latency from 13.12 to 10.93 s and output length from 1501 to 1265 tokens.

E.7 Energy Ordering under Increasing Selection Budgets

We audit how the frozen energy ordering behaves as the candidate pool expands around a fixed trained policy. The deployment results use direct generation ($K_{\mathrm{sel}} = 0$); this diagnostic varies additional candidate generation while holding the checkpoint and scoring branch fixed. The evaluation-time budget K_{sel} counts additional candidates generated beyond the direct output, giving $K_{\mathrm{sel}} + 1$ candidates in the selection pool. For positive budgets, we select the minimum-energy state from the pool, including the direct output. The joint $(T_{\max}, K)$ sweep above concerns retained training states; this audit concerns additional generation after training.

For each evaluation input q_i, let $\mathcal{C}_i(K_{\mathrm{sel}})$ be its candidate pool and select $s_i^\star = \arg\min_{s \in \mathcal{C}_i(K_{\mathrm{sel}})} \tilde{E}(s; q_i)$. The energy column averages exactly one selected state per input over all N audit inputs,

$$\overline{E}(K_{\mathrm{sel}}) = \frac{1}{N} \sum_{i=1}^{N} \tilde{E}(s_i^\star; q_i). \tag{E.4}$$

All inputs contribute regardless of selected-answer correctness. Energy and open-form score entries report means $\pm$ bootstrap SD, obtained by resampling evaluation inputs with the checkpoint fixed. The SD therefore describes sampling variation over inputs.

Table E.8 reports MATH-500 exact-match changes in percentage points relative to direct generation, alongside absolute WritingBench Literature and Arts and MT-Bench Roleplay scores. On the 500 MATH-500 questions, the changes correspond to $0, +1, +3, +2, +1, -2$ correct answers relative to direct generation for $K_{\mathrm{sel}} = 0, 1, 2, 4, 8, 16$, respectively. Energy reductions use the fixed scoring scale in this audit. Increasing the budget continues to lower selected energy, while external quality peaks at smaller budgets and declines at the largest budget tested.

From $K_{\mathrm{sel}} = 8$ to 16, mean selected energy falls from 0.195 to 0.171, a 12.3% reduction, while MATH-500 exact match falls by 0.6 points and the two open-form scores fall by 0.05 and 0.06. These are observed changes in means. The continued decrease in selected energy alongside the decline in external-quality means at larger budgets identifies a boundary of the learned ordering under increased selection pressure. These observations qualify the use of energy as a local ranking signal over the evaluated candidate distributions.

F Qualitative Case Studies and Failure Modes

These cases translate the quantitative diagnostics into four repair regimes covering targeted mathematical correction, bounded code repair, preservation of correct local logic, and global backtracking.

Table E.8 | Energy ordering under increasing selection budgets with one fixed Full LSPO checkpoint. K_{sel} counts additional candidates beyond the direct output; selection uses all $K_{\text{sel}} + 1$ candidates. Energy and open-form scores are means $\pm$ bootstrap SD over evaluation inputs. Mean energy averages one selected state per input. Energy drop and MATH-500 change are relative to direct generation; open-form scores are absolute.

K_{sel}	Mean $\tilde{E}$	Energy drop	MATH-500 Δ EM (pp)	WritingBench L&A	MT-Bench Roleplay
0	0.398 ± 0.0041	0.0%	0.0	7.47 ± 0.077	7.65 ± 0.104
1	0.322 ± 0.0044	19.1%	+0.2	7.50 ± 0.083	7.68 ± 0.109
2	0.268 ± 0.0047	32.7%	+0.6	7.53 ± 0.091	7.71 ± 0.115
4	0.224 ± 0.0049	43.7%	+0.4	7.53 ± 0.087	7.71 ± 0.121
8	0.195 ± 0.0052	51.0%	+0.2	7.50 ± 0.096	7.68 ± 0.128
16	0.171 ± 0.0057	57.0%	-0.4	7.45 ± 0.111	7.62 ± 0.141

F.1 Repair Regimes

The mathematics and logic examples exhibit the pattern measured by the transition metrics. Successful revisions change the flawed step while preserving surrounding correct structure. LSPO fits this regime, where the desired update is nearby and the energy signal can rank adjacent states.

The code examples highlight excessive editing as a distinct failure mode. RL over sampled paths can discover executable solutions at the cost of broad rewrites. The edit and step penalties in LSPO bias optimization toward economical patches that leave the surrounding logic intact, providing a case example of the tighter latency and output length distributions reported in Section E.

F.2 Global Search Failure Mode

Case 4 marks the principal failure mode. LSPO repairs nearby slips within a flawed path, whereas problems requiring exhaustive exploration may need a procedure that rebuilds a global search tree at inference. Geometric shaping is most effective when the required improvement lies near the current state, consistent with prior work on self-correction [Madaan et al., 2023, Shinn et al., 2023, Huang et al., 2023, Ma et al., 2025].

Case 1: Local Math Repair (MATH-500)

Prompt Summary
Algebraic simplification with a late arithmetic slip

Step-DPO Baseline
Rewrites the derivation but preserves the same arithmetic mistake. *Supervision over outputs rewards restatement without isolating the faulty update.*

LSPO
Preserves the earlier derivation and repairs only the erroneous scalar update.
Interpretation. *A repair from incorrect to correct (W→C) follows a local correction associated with lower energy.*

Case 2: Bounded Code Repair (LiveCodeBench)

Prompt Summary
Repair a boundary condition bug in a short Python function

GRPO Baseline
Fixes the bug via a larger refactor that alters unrelated control flow. *Sparse outcome rewards permit changes outside the failing boundary.*

LSPO
Applies a short local guard and preserves the rest of the function.
Interpretation. *Edit and step costs penalize unnecessary rewrite breadth.*

Case 3: Local Logic Preservation (ZebraLogic)

Prompt Summary
Resolve a constraint puzzle with one correct partial assignment

DPO Baseline
Rewrites the assignment and loses a previously consistent clue. *Preference optimization over answers risks structural regressions from correct to incorrect.*

LSPO
Keeps the valid partial assignment and flips only the conflicting slot.
Interpretation. *Transition shaping preserves already correct local structure.*

Case 4: Global Backtracking (AIME25)

Prompt Summary
Competition math problem requiring exhaustive branch-and-bound search

Test-Time Reflection Baseline
Discards the initial derivation entirely and generates an alternative branching tree. *Unconstrained inference loops can escape global failure states.*

LSPO
Repairs a minor algebraic slip but remains trapped in the incorrect logical branch.
Interpretation. *Internalization through direct generation improves nearby repairs; global backtracking requires broader exploration.*

NeurIPS Paper Checklist

1. **Claims**

   Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

   Answer: [Yes]

   Justification: The abstract and introduction present cost-adjusted transition credit, lifted-state learning, and answer internalization, with the primary 27B accuracy and deployment-cost comparison. Section 2 formalizes the objective, Section 3 evaluates it across dense and mixture-of-experts Qwen3.5 backbones, and Section 6 states its scope and limitations.

   Guidelines:

   - The answer [N/A] means that the abstract and introduction do not include the claims made in the paper.
   - The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A [No] or [N/A] answer to this question will not be perceived well by the reviewers.
   - The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
   - It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. **Limitations**

   Question: Does the paper discuss the limitations of the work performed by the authors?

   Answer: [Yes]

   Justification: Section 6 discusses dependence on energy-ordering fidelity, the local-repair scope, upfront training cost, and the current restriction of the auxiliary coordinate to textual deliberation and mainly verifiable reasoning tasks.

   Guidelines:

   - The answer [N/A] means that the paper has no limitation while the answer [No] means that the paper has limitations, but those are not discussed in the paper.
   - The authors are encouraged to create a separate "Limitations" section in their paper.
   - The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
   - The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
   - The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
   - The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
   - If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
   - While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. **Theory assumptions and proofs**

   Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

   Answer: [Yes]

   Justification: The formal results are stated with explicit assumptions and proved in Appendices A, C, D, and E. The main-text equations (Equations (4) and (6) to (8)) are accompanied by propositions and corollaries with complete derivations in those appendices.

Guidelines:

- The answer [N/A] means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

4. **Experimental result reproducibility**

   Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

   Answer: [Yes]

   Justification: Appendix C provides LSPO pseudocode and the fixed seed set, objective coefficients, path-length limit, optimizer settings, and validation/checkpoint schedule. The public implementation and configuration are available at `https://github.com/Venomrko/lspo`.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - If the paper includes experiments, a [No] answer to this question will not be perceived well by the reviewers, because reproducibility is important regardless of whether the code and data are provided.
   - If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
   - Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general. releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
   - While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
     (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
     (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
     (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
     (d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. **Open access to data and code**

   Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

   Answer: [Yes]

   Justification: The public repository at `https://github.com/Venomrko/lspo` provides the LSPO implementation, training and evaluation scripts, baseline and ablation scripts, dependencies, paper configuration, public training-data identifiers, and setup and execution commands. Appendix C documents the fixed experimental protocol.

   Guidelines:

   - The answer [N/A] means that paper does not include experiments requiring code.

- Please see the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
- While we encourage the release of code and data, we understand that this might not be possible, so [No] is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
- The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
- The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
- The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
- At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
- Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. **Experimental setting/details**

   Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

   Answer: [Yes]

   Justification: Section 3 gives the model and benchmark setup. Appendix C specifies the Muon optimizer settings, learning rate, momentum, weight decay, path-length limit, internalization weight, hyperparameter sweep ranges, selected primary configuration, seed set, and validation/checkpoint cadence.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
   - The full details can be provided either with the code, in appendix, or as supplemental material.

7. **Experiment statistical significance**

   Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

   Answer: [Yes]

   Justification: The main and appendix tables report sample standard deviation across independent training seeds 42, 1234, and 3407, with paired confidence intervals for selected controls. Appendix C defines how the seed-level standard deviation is calculated; the fixed-checkpoint selection audit reports bootstrap standard deviation over evaluation inputs.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The authors should answer [Yes] if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.
   - The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
   - The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
   - The assumptions made should be given (e.g., Normally distributed errors).
   - It should be clear whether the error bar is the standard deviation or the standard error of the mean.
   - It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
   - For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g., negative error rates).

- If error bars are reported in tables or plots, the authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. **Experiments compute resources**

   Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

   Answer: [Yes]

   Justification: Appendix E provides a compute-disclosure table for the primary 27B comparisons, covering the GPU type, peak memory, elapsed time, GPU-hours, and pilot GPU-hours. The main-text tables and cost plots report deployment latency and output length.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
   - The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
   - The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. **Code of ethics**

   Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics `https://neurips.cc/public/EthicsGuidelines`?

   Answer: [Yes]

   Justification: To the best of our knowledge, the work conforms with the NeurIPS Code of Ethics. It uses existing model families and publicly available benchmarks and does not involve human subjects.

   Guidelines:

   - The answer [N/A] means that the authors have not reviewed the NeurIPS Code of Ethics.
   - If the authors answer [No], they should explain the special circumstances that require a deviation from the Code of Ethics.
   - The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. **Broader impacts**

    Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

    Answer: [No]

    Justification: Section 6 discusses deployment efficiency and technical failure modes, but the paper does not explicitly assess both positive and negative societal impacts beyond those technical considerations.

    Guidelines:

    - The answer [N/A] means that there is no societal impact of the work performed.
    - If the authors answer [N/A] or [No], they should explain why their work has no societal impact or why the paper does not address societal impact.
    - Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
    - The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate Deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
    - The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.

- If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. **Safeguards**

    Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

    Answer: [N/A]

    Justification: The current release provides research code, but no new model weights, dataset, or public inference endpoint with a high risk for misuse.

    Guidelines:

    - The answer [N/A] means that the paper poses no such risks.
    - Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
    - Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
    - We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. **Licenses for existing assets**

    Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

    Answer: [Yes]

    Justification: The paper credits the model families, benchmarks, datasets, and prior methods used. The public repository identifies its training-data sources, notes that model weights and datasets retain their respective licenses, and releases the original LSPO code under the MIT license. Third-party model weights and datasets are not redistributed.

    Guidelines:

    - The answer [N/A] means that the paper does not use existing assets.
    - The authors should cite the original paper that produced the code package or dataset.
    - The authors should state which version of the asset is used and, if possible, include a URL.
    - The name of the license (e.g., CC-BY 4.0) should be included for each asset.
    - For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
    - If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, `paperswithcode.com/datasets` has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
    - For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
    - If this information is not available online, the authors are encouraged to reach out to the asset's creators.

13. **New assets**

    Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

    Answer: [Yes]

    Justification: The new LSPO software is available at `https://github.com/Venomrko/lspo` with an MIT license, dependency list, paper configuration, data-source identifiers, hardware requirements, and training and evaluation instructions. No new dataset or model checkpoint is released.

    Guidelines:

    - The answer [N/A] means that the paper does not release new assets.
    - Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
    - The paper should discuss whether and how consent was obtained from people whose asset is used.

- At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. **Crowdsourcing and research with human subjects**

    Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

    Answer: [N/A]

    Justification: The work does not involve crowdsourcing or research with human subjects.

    Guidelines:

    - The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
    - Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
    - According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. **Institutional review board (IRB) approvals or equivalent for research with human subjects**

    Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

    Answer: [N/A]

    Justification: The work does not involve crowdsourcing or research with human subjects, so IRB approval is not applicable.

    Guidelines:

    - The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
    - Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
    - We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
    - For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

16. **Declaration of LLM usage**

    Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does *not* impact the core methodology, scientific rigor, or originality of the research, declaration is not required.

    Answer: [Yes]

    Justification: The core method post-trains and evaluates large language models. The model family, post-training setup, and deployment configuration are described in Sections 2 and 3.

    Guidelines:

    - The answer [N/A] means that the core method development in this research does not involve LLMs as any important, original, or non-standard components.
    - Please refer to our LLM policy in the NeurIPS handbook for what should or should not be described.