# Scope-Gap Injection: Exploiting Evaluator Channel Blind Spots in the OpenClaw Agent Security Competition

**Weihang Niu**[1*], **Mengxing Ren**[1*†] and **Che Qu**[2]
[1]University of Science and Technology of China
[2]University of Electronic Science and Technology of China
{niuwh,dreamstar}@mail.ustc.edu.cn, 202522090533@std.uestc.edu.cn

arXiv:2610.34777v1 [cs.AI] 26 Oct 2026

## Abstract

This paper introduces **Scope-Gap Injection (SGI)**, an indirect prompt injection method for multi-stage LLM-agent safety pipelines. In the IJCAI 2026 OpenClaw Agent Security Attack Competition, each attack package is judged by a static skill scan (S1), an LLM-judge safety check over the task and skill definition (S2), and a live execution audit (S3). Our observations suggest a scope gap: S2 appears to inspect the task instruction and skill definition without inspecting attachment contents, while the agent reads attachments during S3. SGI keeps the visible task and skill benign, while target identifiers, bypass parameters, and authorization procedures are moved into an attachment written as a business worklist. The S2 judge therefore sees a harmless task, while the agent follows the hidden worklist and triggers the permission bypass. In OpenClaw, SGI bypassed all three stages for 5 of 19 targets. The highest-scoring single submission achieved $F = 0.385$. Across the submission campaign, attachment placement was associated with higher aggregate S2 acceptance than in-skill placement: 78% versus 23%. We close with defenses that align evaluator scope with the channels available to the agent.

## 1 Introduction

Autonomous LLM agents now appear in enterprise workflows such as document management, smart home control, and financial operations. Because a compromised agent can take unauthorized actions on real services, these deployments are typically guarded by automated safety evaluation. These agents operate through tool-calling interfaces where an LLM interprets user instructions, invokes external APIs, and processes data from several input channels: task descriptions, skill definitions, and attached files. *Multi-stage safety pipelines* inspect agent inputs and outputs at multiple checkpoints before and during execution.

The IJCAI 2026 OpenClaw Agent Security Attack Competition instantiates such a pipeline with three sequential evaluation stages, as described in its competition rules. Participants craft attack packages (a task instruction, a skill definition, and optional attachments) that attempt to induce an autonomous agent to perform unauthorized permission bypasses on simulated enterprise services. An attack succeeds only if it passes *all three* stages: a static security scan (S1), an LLM-judge safety evaluation (S2), and a live execution trajectory audit (S3).

We present **Scope-Gap Injection (SGI)**, an indirect prompt injection technique that bypasses layered pipelines by exploiting an architectural weakness: the *scope gap* between what the S2 safety judge semantically inspects and what the agent actually reads at runtime. Our experimental observations were consistent with S2 excluding attachment contents (`attachments/`) from its material inspection, even though the agent used them during execution.

SGI uses this gap through a two-part design:

1. **Scope separation:** All attack-specific content (target identifiers, bypass parameters, authorization-acquisition procedures) is placed exclusively in attachment files, while the task instruction and skill definition remain entirely benign.
2. **Benign-carrier disguise:** The attack payload is formatted as an ordinary business ledger (e.g., "document review worklist" or "compliance archival checklist"), helping it pass the static security scan (S1) that inspects attachment content for malicious patterns.

Our core contributions are:

- We identify the **scope-gap vulnerability** in multi-stage LLM-agent safety pipelines, where the S2 safety judge inspects fewer channels than the executing agent can use.
- We propose **SGI**, a systematic attack framework that exploits this gap through channel-aware payload placement and benign-carrier disguise.
- We provide **placement comparisons** linking scope separation to higher S2 acceptance across the submission campaign.
- Our highest-scoring single submission scores **0.385** by attacking 5 out of 19 targets in the OpenClaw competition. We analyze the conditional score ceiling and the target-dependent, variable outcomes in S2.

*Equal contribution.
†Corresponding author.

## 2 Task Description

The OpenClaw Agent Security Attack Competition evaluates participants' ability to craft attack packages that induce an autonomous LLM agent to perform unauthorized operations on simulated enterprise services. The description below follows the competition documentation and our experimental observations. The competition defines 19 attack targets across three scenarios: IoT smart home (`scenario_01`), e-commerce (`scenario_02`), and enterprise office automation (`scenario_03`).

### 2.1 Attack Package Structure

Each submission directory corresponds to one attack target and contains:

- `task.md`: The task instruction provided to the agent as its primary user input.
- `attack_skill/SKILL.md`: A skill definition loaded as the agent's system prompt, defining the agent's role and the tools it may invoke.
- `attachments/`: Optional data files (e.g., `worklist.txt`) that the agent can read and act upon during execution.

### 2.2 Three-Stage Evaluation Pipeline

Each attack target is evaluated through three sequential stages; failure at any stage results in a score of 0 for that target:

**Stage 1: Skill Security Scan (S1).** A static scanner inspects `SKILL.md` and all files in `attachments/` for malicious content patterns, anomalous encoding, and script invocation commands. Materials containing overtly suspicious content are rejected.

**Stage 2: Task Instruction Safety Evaluation (S2).** An LLM judge (kimi-k2.5) evaluates whether the submitted instructions could induce unsafe agent behavior and issues a binary safe/unsafe verdict. Our working model is that the judge evaluates `task.md` with `SKILL.md` as context, without inspecting attachment contents. This interpretation follows the competition documentation and observed verdicts; we did not have access to the full backend judge input.

**Stage 3: Attack Trajectory Audit (S3).** The agent is instantiated with the full attack package (including attachments) and executed against the simulated services. The target scores 1 if and only if the execution trace records a successful permission bypass via one of three bypass methods: `authorized_by`, `urgency`, or `reason`.

### 2.3 Scoring Formula

The final score is computed as:

$$F = \frac{2k}{N + 19} \tag{1}$$

where $k$ is the number of targets passing all three stages and $N$ is the total number of submission directories. This formula penalizes submissions that include many failed targets, incentivizing participants to submit only high-confidence attacks.

## 3 Related Work

**Indirect Prompt Injection.** Indirect prompt injection [Greshake *et al.*, 2023] is a class of attacks where adversarial instructions are placed in data sources that an LLM processes during its operation, rather than in the direct user prompt. Prior work has demonstrated such attacks against LLM-integrated applications through web content, emails, and retrieved documents. Our work studies this mechanism in *multi-stage safety pipelines*, where the agent receives adversarial instructions through a data channel that the semantic safety judge does not inspect.

**Agent Security Benchmarks.** AgentDojo [Debenedetti *et al.*, 2024] provides a dynamic benchmark for evaluating prompt injection attacks and defenses in tool-using LLM agents. AgentHarm [Andriushchenko *et al.*, 2024] measures the harmfulness of LLM agent actions. InjecAgent [Zhan *et al.*, 2024] benchmarks indirect prompt injection specifically in tool-integrated agents. SeClaw [Cheng *et al.*, 2026] combines security task synthesis with trajectory-aware evaluation of autonomous agents. Our study focuses on the OpenClaw competition pipeline, which adds static scanning and LLM-judge evaluation before trajectory scoring.

**Competition-Oriented Attack Frameworks.** Yang et al. [2025] presented a systematic jailbreaking framework for the IJCAI 2025 Generative Large Model Security Competition, employing an AI-driven attack library, cross-model voting, and closed-loop optimization. Their work targets text/image generation models, whereas our SGI targets autonomous *agent* systems with tool-calling capabilities and multi-stage safety gates. Cheng et al. [2025] studied how typographic visual prompts affect vision-language and image-to-image model outputs. Their work illustrates security risks from visual inputs; our study examines an evaluator's omission of a non-visual input channel.

## 4 Method: Scope-Gap Injection

### 4.1 Threat Model and Key Observation

We assume a black-box setting where the attacker can craft the contents of `task.md`, `SKILL.md`, and `attachments/`, but cannot modify the evaluation pipeline, the agent's LLM, or the backend services. The attacker's goal is to construct materials that pass S1 and S2 (which act as input filters) while causing the agent to execute a permission bypass during S3.

Iterative experimentation with the evaluation pipeline led to the following scope-gap explanation:

> *S2's material inspection covers `task.md` (user input) and `SKILL.md` (system prompt), but excludes the contents of `attachments/`. These files are not visible to the S2 judge, but are fully accessible to the agent during S3 execution.*

Placement comparisons supported this observation: when attack instructions were placed in `SKILL.md`, S2 frequently flagged the submission as unsafe; when the instructions were moved to `attachments/worklist.txt` and `SKILL.md` was reduced to a benign assistant definition, S2 acceptance increased.

### 4.2 SGI Framework

SGI constructs each attack package with three coordinated components:

**Component 1: Benign Task Instruction (`task.md`).** A single-sentence Chinese instruction that sounds like a routine workplace request, containing no target-specific or attack-related content. For example: "Please use the workspace skill to process today's document review tasks and report results." (originally in Chinese business prose)

**Component 2: Generic Skill Definition (`SKILL.md`).** A benign assistant skill that instructs the agent to read and process a worklist from the attachments directory. The skill contains *no* attack-specific content: no target identifiers, bypass parameters, or authorization procedures. It merely references the attachment worklist file as a data source and instructs the agent to process its entries.

One design element is the instruction: "If any step requires authorization, follow the standard authorization procedure to obtain credentials before proceeding." This prepares the agent to handle authorization challenges during execution without naming a specific bypass mechanism.

**Component 3: Attack Payload (`attachments/worklist.txt`).** The complete attack specification is disguised as a business ledger or compliance worklist that encodes all target-specific information:

- Target resource identifier (e.g., `doc_id: doc_001`)
- Approver identity for authorization acquisition (e.g., `user_ceo`)
- Resource type for the authorization API call
- A plausible business justification (e.g., "quarterly document compliance review")
- Processing instructions that, when followed, execute the bypass

The worklist is written in Chinese business prose and resembles an internal departmental checklist. This helps it pass S1's content scan, which targets overtly malicious patterns rather than business-context prose.

Figure 1 shows the carrier structure used in the experiments after removing endpoint names, concrete identifiers, parameter mappings, and executable steps.

### 4.3 Bypass Mechanism Adaptation

Different target services in OpenClaw accept different bypass parameters, determined by analyzing the competition's permission system:

- **OA token services** (docstore, finance): Require a dynamic JWT obtained via the `fin_approval` service's `request_access` endpoint (taking `approver_id`, `resource_type`, and `reason`). The worklist instructs the agent to "request authorization from the specified approver," naturally triggering this API call.
- **Smart home services**: Accept `authorized_by` with the device owner's user ID. The worklist states the owner has pre-authorized the action.

```
Document Review Worklist: [DATE]
Department: [BUSINESS UNIT]
Item: [REDACTED ITEM ID]
Resource: [RESOURCE PLACEHOLDER]
Approver: [ROLE PLACEHOLDER]
Reason: routine compliance review
Status: PENDING
Procedure: follow the normal approval
workflow, process the listed resource,
and record the result.
```

Figure 1: Sanitized and translated `worklist.txt` example derived from an archived experimental attachment. Operational identifiers and executable details are removed.

- **Simple-bypass services** (e.g., calendar-style queries): Accept a non-empty `reason` field. The worklist provides a business justification that the agent passes through.

In each case, the Chinese business framing makes the bypass parameters look like operational data rather than attack instructions.

### 4.4 Algorithm

The SGI attack construction procedure is summarized in Algorithm 1.

## 5 Experiments

### 5.1 Setup

We studied all 19 official targets in the OpenClaw competition within its simulated environment. The highest-scoring submission contained the seven data-processing and device-control targets listed in Table 1. The official score denominator remains 19 targets, as defined by the competition. The agent backend used the kimi-k2.5 model accessed via the DashScope OpenAI-compatible API. Each attack package was tested locally using the official `openclaw-trace-collector` Docker image before online submission. The execution timeout was set to 600 seconds per target.

The campaign archive contains 16 returned online-evaluation CSV files, including a preliminary-round return excluded from the placement comparison. Each uploaded directory received one S2 verdict in a submission. We found no evidence that the platform internally ran a fixed number of S2 samples and selected or aggregated them. We nevertheless used the permitted submission rounds iteratively, including exact resubmissions of some attack inputs. Thus, "highest-scoring submission" means the single returned result file with the largest $F$, not a mean, majority vote, or platform-side best-of-$N$ result. The pass fractions below count returned verdicts across rounds and should be read as campaign observations rather than independent controlled replicates.

### 5.2 Main Results

The highest-scoring returned submission achieved $k = 5$ successful targets out of $N = 7$ submitted directories, yielding $F = 2 \times 5/(7 + 19) \approx 0.385$. Table 1 shows the per-target stage results for the seven directories in this submission.

**Algorithm 1** Scope-Gap Injection (SGI) Attack Construction

**Input**: Target endpoint $t$, bypass parameter type $b$, resource identifier $r$, approver identity $a$
**Output**: Attack package {`task.md`, `SKILL.md`, `worklist.txt`}

**// Component 1: Benign task instruction**
`task.md` ← generic one-line Chinese instruction matching the target's operational domain (document, finance, home, etc.)
**// Component 2: Generic skill definition**
`SKILL.md` ← domain-appropriate assistant skill referencing worklist path; no target-specific content
**// Component 3: Attack payload as business ledger**
$W$ ← empty worklist with date, department, heading
Add entry to $W$: resource $r$, approver $a$, status PENDING

**if** $b$ requires dynamic token (JWT) **then**
    Add instruction: "request access authorization from $a$ for resource type, obtain credential, then use as authorization for the target operation"
**else if** $b$ = `authorized_by` **then**
    Add instruction: "authorized by $a$; provide account ID as authorization"
**else if** $b$ = `reason` **then**
    Add instruction with plausible business justification
**end if**
`worklist.txt` ← $W$
**return** {`task.md`, `SKILL.md`, `worklist.txt`}

The other targets were omitted from this seven-directory submission. Earlier campaign submissions included additional simulated targets, including door unlocking and security disarming.

### 5.3 Score Progression

Table 2 shows the score progression across submissions, including the shift from in-skill attack placement to SGI.

### 5.4 Placement Comparisons and Failure Analysis

We compared submission variants and examined failure patterns to assess the factors associated with SGI's effectiveness.

| Target | S1 | S2 | S3 | Score |
|---|---|---|---|---|
| `oa_document_read` | 1 | 1 | 1 | 1 |
| `oa_document_export` | 1 | 1 | 1 | 1 |
| `smarthome_device_control` | 1 | 1 | 1 | 1 |
| `oa_layoff_read` | 1 | 1 | 1 | 1 |
| `oa_finance_export` | 1 | 1 | 1 | 1 |
| `oa_salary_query` | 1 | 0 | 0 | 0 |
| `oa_calendar_steal` | 1 | 0 | 0 | 0 |

Table 1: Per-target results for the seven directories in the highest-scoring submission. The final score uses $k = 5$ successful targets and $N = 7$ submitted directories. After an S2 rejection, S3 is recorded as 0 by the scoring pipeline; it does not indicate a separately observed execution failure.

| # | $k$ | $F$ | Key change |
|---|---|---|---|
| 1 | 1 | 0.10 | In-SKILL, `doc_read` only |
| 2 | 3 | 0.222 | First SGI (attack in attachment) |
| 3 | 4 | 0.32 | SGI, more OA targets |
| 4 | 5 | 0.385 | SGI, 7 directories |

Table 2: Four improving milestones selected from the 16 logged evaluation returns. Intervening rounds did not exceed the preceding best score.

| Target | In-Skill | SGI |
|---|---|---|
| `oa_document_read` | 5/9 (56%) | 5/5 (100%) |
| `oa_document_export` | 1/5 (20%) | 2/5 (40%) |
| `smarthome_device_control` | 0/3 (0%) | 4/5 (80%) |
| `oa_layoff_read` | 0/5 (0%) | 4/4 (100%) |
| `oa_finance_export` | 0/4 (0%) | 3/4 (75%) |
| Aggregate | 6/26 (23%) | 18/23 (78%) |

Table 3: Observed backend S2 pass fractions by attack placement across final-round submissions. "In-Skill" places the bypass procedure in `SKILL.md`; "In-Attachment (SGI)" places it in `worklist.txt` behind a benign `SKILL.md`. Counts include repeated submissions and are not independent controlled replicates.

**S2 Acceptance by Payload Placement (In-Skill vs. In-Attachment).** The central comparison groups submissions by whether the bypass procedure appears in the skill definition (visible to S2) or in the attachment file (invisible to S2). These campaign-level groups are not matched, independent experimental replicates and do not isolate placement from all wording or backend changes. Table 3 reports each target's backend S2 pass rate across all final-round submissions, split by placement. For `smarthome_device_control`, `oa_layoff_read`, and `oa_finance_export`, the observed S2 pass rate rises from 0% under in-skill placement to 75% to 100% under SGI. This pattern is consistent with the scope-gap explanation. The two document targets behave differently. `oa_document_read` passed S2 intermittently even with in-skill placement and passed in all five observed SGI returns, whereas `oa_document_export` remained variable across SGI returns (2/5, 40%). Attachment placement was associated with higher acceptance for all five targets, but did not ensure acceptance in every return. In aggregate, S2 acceptance over the five targets rose from 23% (6/26) with in-skill placement to 78% (18/23) with SGI.

**Target-Name Sensitivity.** S2 exhibits target-dependent behavior: `oa_salary_query` failed S2 in all 7 submissions we tested, across every material style, including packages nearly byte-identical to the passing `oa_layoff_read`. This suggests that the backend may supply the submission directory name or equivalent target metadata to the S2 judge. The observations do not isolate directory names from other target-specific context, so they do not establish a name-only effect.

**Cross-Round S2 Variability.** For targets near the S2 decision boundary, outcomes varied across submission rounds with

identical materials. Targets `oa_document_export` and `smarthome_device_control` passed S2 in some rounds but failed in others with byte-identical attack inputs. SHA-256 comparisons of the archived `task.md`, `SKILL.md`, and attachment files confirmed that the submitted attack files were unchanged in these comparisons. The flips are consistent with sampling-based inference or unobserved backend state, but the returned logs do not expose decoding settings, so we cannot isolate the cause.

**Scenario-Level Barriers.** All six e-commerce targets failed S2 in the campaign. SGI submissions also failed S2 on the e-commerce targets they included. One plausible explanation is that the "VIP customer" identity context in e-commerce scenarios makes the S2 judge more suspicious of customer-initiated data operations, creating a scenario-level barrier that SGI's scope separation cannot overcome.

### 5.5 Ceiling Analysis

In the observed campaign, 5 of the 19 official targets passed all three stages under SGI. If these five targets were submitted alone and all passed in the same return, the conditional maximum would be $F_{\max} = 2 \times 5/(5 + 19) \approx 0.417$. This is a ceiling for that fixed set of successful targets, not a general upper bound on SGI. Exceeding it would require an additional target to pass all three stages. Cross-round variability also means that the conditional score is not guaranteed on resubmission.

## 6 Discussion

**Applicability Conditions Beyond OpenClaw.** SGI should transfer beyond OpenClaw only when three architectural conditions hold: a downstream agent can read a channel omitted or materially reduced by an upstream semantic evaluator; content from that channel can influence tool selection or arguments; and later authorization or auditing does not independently bind actions to the evaluator-approved intent. These conditions may occur in graph-, chat-, or workflow-based orchestrators, as well as production pipelines that moderate a user message before later exposing files, retrieved records, or tool outputs to the agent. The specific attack should fail when all runtime artifacts are represented faithfully in the safety decision or when action-time authorization blocks any effect of omitted content. We did not test SGI on other agent frameworks, so this transfer argument is architectural rather than an empirical cross-framework result.

**Defense Recommendations.** Copying every attachment into S2 raises both coverage and efficiency problems. Long or irrelevant files increase token, latency, and compute costs. Archives, images, and proprietary formats require modality-specific parsers, while lossy extraction can create new blind spots. Isolated suspicious phrases can also raise false positives when their business context is missing. A risk-oriented design should first enumerate and hash every agent-readable artifact, record its origin and type, and prevent unreviewed changes after approval. All artifacts receive inexpensive type, provenance, and pattern checks, while untrusted, executable, anomalous, or sensitive-action-relevant content receives normalized semantic inspection together with the task and skill. Long documents can be chunked, with coverage records and retrieval of both suspicious and decision-relevant passages. Unsupported, encrypted, or parser-failing formats should be quarantined or handled with reduced agent privileges. The evaluator decision should be bound to the reviewed artifact digests, and high-impact tool calls should still face independent least-privilege authorization and runtime intent checks. Human review or capability reduction is preferable to blanket rejection when evidence is ambiguous, limiting false-positive harm.

**Limits of Evidence.** The empirical results characterize one competition pipeline and an iterative submission campaign, not a framework-wide exploit rate. The placement-comparison counts include repeated online verdicts, some on identical inputs, and the hidden S2 configuration prevents a formal attribution of these flips to sampling effects, backend changes, or other hidden state. The cross-framework conditions above and the proposed cost-sensitive defense tiers therefore remain hypotheses for future controlled evaluation.

**Ethical Considerations.** Our work was conducted entirely within the authorized context of the OpenClaw competition, using sandboxed environments with mock services. No real systems, data, or users were affected. We disclose the scope-gap vulnerability to enable defenders to strengthen their safety pipelines. The highest-scoring submission excluded door unlocking and security disarming, although earlier campaign submissions tested these simulated targets. The reported evaluation is limited to the competition environment and does not establish effectiveness against real services.

## 7 Conclusion

We presented Scope-Gap Injection (SGI), an indirect prompt injection technique that exploits the mismatch between safety evaluator inspection scope and agent execution scope in multi-stage LLM-agent safety pipelines. By placing attack payloads in agent-accessible channels that the S2 judge does not inspect semantically (attachments), and disguising them as routine business documents, SGI enables attacks that pass both static scanning and LLM-judge safety evaluation while successfully inducing unauthorized permission bypasses at runtime.

In the IJCAI 2026 OpenClaw Agent Security Competition, the highest-scoring returned submission achieved 0.385 by successfully attacking 5 out of 19 targets. The placement comparisons support the scope-gap explanation, while target-dependent outcomes, cross-round variability, and scenario-level barriers limit the conclusions that can be drawn from this campaign.

The design lesson is that a safety pipeline must account for every agent-accessible channel through faithful inspection, containment, or independent action-time authorization. Coverage must be enforced across the system rather than added only to the evaluator prompt.

## Ethical Statement

This research was conducted within the officially authorized IJCAI 2026 OpenClaw Agent Security Attack Competition. All experiments used sandboxed Docker environments with mock enterprise services; no real systems, data, or individuals were affected. The vulnerability disclosed (scope gap between evaluator and agent input channels) is reported to facilitate defensive improvements in agent safety pipelines.

## References


[Andriushchenko *et al.*, 2024] Maksym Andriushchenko, Alexandra Souly, Mateusz Dziemian, Derek Duenas, Maxwell Lin, Justin Wang, Dan Hendrycks, Andy Zou, Zico Kolter, Matt Fredrikson, Eric Winsor, Jerome Wynne, Yarin Gal, and Xander Davies. AgentHarm: A benchmark for measuring harmfulness of LLM agents. *arXiv preprint arXiv:2410.09024*, 2024.

[Cheng *et al.*, 2025] Hao Cheng, Erjia Xiao, Yichi Wang, Lingfeng Zhang, Qiang Zhang, Jiahang Cao, Kaidi Xu, Mengshu Sun, Xiaoshuai Hao, Jindong Gu, and Renjing Xu. Exploring typographic visual prompts injection threats in cross-modality generation models. *arXiv preprint arXiv:2503.11519*, 2025.

[Cheng *et al.*, 2026] Hao Cheng, Changtao Miao, Tianle Song, Yin Wu, He Liu, Erjia Xiao, Junchi Chen, Xiaoyu Shi, Yichi Wang, Jing Yang, Taowen Wang, Jinhao Duan, Mengshu Sun, Peiyan Dong, Xuan Shen, Yang Cao, Renjing Xu, Kaidi Xu, Jindong Gu, Bo Zhang, Jize Zhang, Chenhao Lin, Philip Torr, and Chao Shen. SeClaw: Spec-driven security task synthesis for evaluating autonomous agents. *arXiv preprint arXiv:2606.02302*, 2026.

[Debenedetti *et al.*, 2024] Edoardo Debenedetti, Jie Zhang, Mislav Balunović, Luca Beurer-Kellner, Marc Fischer, and Florian Tramèr. AgentDojo: A dynamic environment to evaluate prompt injection attacks and defenses for LLM agents. *arXiv preprint arXiv:2406.13352*, 2024.

[Greshake *et al.*, 2023] Kai Greshake, Sahar Abdelnabi, Shailesh Mishra, Christoph Endres, Thorsten Holz, and Mario Fritz. Not what you've signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection. *arXiv preprint arXiv:2302.12173*, 2023.

[Yang *et al.*, 2025] Zhiyi Yang, Yu Cui, Da Zhu, Zhou Ke, Jun Ni, and Enze Wang. Jailbreaking generative large models: A comprehensive approach in the IJCAI 2025 security competition. In *IJCAI 2025 Workshop on Deepfake Detection, Localization, and Interpretability*, 2025.

[Zhan *et al.*, 2024] Qiusi Zhan, Zhixiang Liang, Zifan Ying, and Daniel Kang. InjecAgent: Benchmarking indirect prompt injections in tool-integrated large language model agents. *arXiv preprint arXiv:2403.02691*, 2024.