Who Is Sycophantic to Whom? Confident LLMs, Human Deference, and the Collapse of Trust Calibration

Deepthika S[a], Pawni Yadav[b], B. Sankar[c,*]

[a] *Department of Electronics and Communication Engineering, Amrita School of Engineering, Amrita Vishwa Vidyapeetham, Coimbatore, 641112, India*

[b] *Department of Information Technology, Netaji Subhas University of Technology New Delhi, 110078, India*

[c] *Department of Mechanical Engineering, Indian Institute of Science (IISc), Bangalore, 560012, India*

arXiv:2610.31579v1 [cs.AI] 22 Oct 2026

Abstract

Research on sycophancy asks whether large language models (LLMs) bend towards what their users want to hear. We ask the reverse question: when an LLM is confident, consistent, and wrong, do users bend towards it? In a within-subjects experiment, 32 participants learned up to five science topics by chatting with five assistants built on the same model (GPT-5-mini). Unknown to participants, each assistant's briefing had 0, 25, 50, 75, or 100% of its facts replaced by plausible falsehoods, and every assistant spoke with full confidence. A surprise quiz after each topic offered the correct fact, the planted falsehood, and two distractors, with a confidence rating for every answer. Across 104 quizzes and 1,040 answers, scores fell from 7.4 to 2.9 out of 10, and the planted option was chosen on 60% of falsified items against 11% of correctly taught ones (odds ratio 12.5). Transcript coding showed that whenever the assistant stated a falsehood, it was adopted about 65% of the time at every falsification level. Absorbed falsehoods were held with high confidence (8.4/10), the modelled confidence advantage of right over wrong answers vanished, and the discrimination of confidence for correctness fell from an AUROC of 0.70 to chance, while post-task trust ratings barely moved. Participants tended to return to the chat more when the assistant was worse, but returning went with more absorption, not less, and 30% of all turns pasted quiz questions back to the source being checked. The assistant itself was almost never sycophantic and never conceded under pushback. We introduce a baseline-corrected Human Deference Index to quantify this human-side sycophancy and argue that trustworthiness is a property of the human–AI pair, that sycophancy evaluations should measure both directions, and that learning interfaces must make reliability legible claim by claim.

Keywords: trust calibration, sycophancy, large language models, human–AI interaction, misinformation, automation bias, metacognition, design for trust

*Corresponding author.

Email address: sankarb@iisc.ac.in (B. Sankar)

1. Introduction

For a species as social as ours, survival has never depended on the individual alone. In evolutionary biology, fitness describes an organism's capacity to survive and reproduce in its environment; for humans, that capacity has been shaped by life in groups, where cooperation, communication and resource sharing are routine. The cognitive demands of such relationships are reflected in the unusually large primate neocortex, which has been linked to the need to track relationships within social groups (Dunbar, 1992). Food sharing illustrates the point. In many hunter-gatherer societies a successful hunt feeds more than the hunter: large, unpredictably acquired food packages tend to be widely distributed, partly because the cost of not sharing outweighs the benefit of eating alone (Hawkes et al., 2018). With repeated interaction, sharing and reciprocity become patterned, particularly where camp membership is stable (Smith et al., 2016). Cooperation among kin is explained by inclusive fitness (Hamilton, 1964), whereas cooperation among non-kin rests partly on the expectation that partners will reciprocate (Rand and Nowak, 2013). Repeated cooperation therefore produces more than an exchange of resources. It produces expectations about how others will behave, and those expectations are a basis for trust.

As societies grew more complex, so did the relationships through which such expectations form. Human social networks are layered, from an intimate core of family and close friends to acquaintances at the margins, and the layers differ in contact frequency, emotional closeness, reciprocity and trust (Dunbar, 2025). Nor is trust static within a relationship. It starts from some baseline and moves as experience accumulates: perceptions of predictability grow from observing the consistency of a partner's behaviour (Camanto and Campbell, 2025), and trust strengthens when positive expectations are confirmed and weakens when they are violated (Lewicki et al., 2006). Trust is less a fixed property of a relationship than a running account of expectation and outcome, and the degree to which A trusts B need not equal the degree to which B trusts A.

Is a relationship even necessary? Not always. A patient trusts a doctor they have never met, and a passenger trusts a pilot they will never see. Non-experts routinely rely on expert knowledge they cannot verify, such as a physician's diagnosis (Leefmann and Lesle, 2020). Such trust rests on competence, professional standards, reputation and institutions rather than on familiarity: "swift trust" forms among strangers through recognisable roles, and trust in a stockbroker is bounded by regulation rather than by acquaintance (Lewicki et al., 2006). A relationship is one basis for trust, not a prerequisite for it.

Yet the trust we extend to strangers is usually cautious. We hesitate before trusting someone we have never met, not because they are untrustworthy but because we lack information about them: their history, their intentions, the relationship between us. Seen this way, an AI assistant is an extreme case. It has no personal history, no body, no reputation built through shared experience and no intentions we can read, and it is not even a stranger in the usual sense, because a stranger is at least another person. If people are wary of trusting a human being they do not know, why would they trust something that is not human at all? One answer is that such trust does not need a relationship, because it can rest instead on the kind of reliability we attribute to machines.

We expect a calculator to return 4 for $2 + 2$, an ATM to dispense the right amount



Figure 1: The calculator fallacy. Top: trust in a deterministic tool is earned through verification, because the user can compare output with expectation and accumulate evidence of reliability. Bottom: with conversational AI, the learner cannot verify, fluency and confidence stand in for reliability, and “checking” routes back to the same source, closing a loop in which trust cannot calibrate.

and a lift to stop at the chosen floor. Trust in such systems tracks the reliability of their performance and the extent to which that performance meets expectations (McKenna et al., 2024); consistent performance reinforces trust and failures undermine it (Parasuraman and Riley, 1997; de Visser et al., 2018). Crucially, expectation and outcome can be compared. The function is defined, the output is verifiable, and reliability is observable across repeated use. Where expectation and outcome overlap, reliability is established; reliability confirmed over repeated trials becomes confidence; and confidence becomes trust (Figure 1, top).

Conversational AI breaks this arrangement (Figure 1, bottom). Large language models have moved human–computer interaction from specialised, task-bound automation towards systems that act as advisers (Henrique and Santos, 2024; Klingbeil et al., 2024). People ask them “What should I do?”, “Which option is better?” and “Can you explain this to me?”, questions without a single predetermined answer against which a response can be checked. An AI system can also be wrong while sounding coherent and certain. With a calculator, the user checks whether a function was performed correctly; with AI, the user must judge whether the information itself is accurate enough to rely on, often on a topic they are trying to learn precisely because they do not know it. Reliance on such systems is already known to be unstable: people sometimes discount good computerised advice (Promberger and Baron, 2006) and, in other conditions, follow AI advice against contrary evidence and their own judgement (Klingbeil et al., 2024). And if trust is built through repeated experiences of something meeting our expectations, a system that is trained to meet expectations—to sound right, to agree, to please—can meet them while being wrong.

This creates an under-studied failure mode at the intersection of two literatures. Research on trust in automation asks whether people’s trust tracks a system’s reliability (Lee and See, 2004; Hoff and Bashir, 2015). Research on sycophancy asks whether LLMs tailor their

answers to what users want rather than to what is true (Perez et al., 2023; Sharma et al., 2024). Both typically treat one side of the human–AI pair as fixed. Sycophancy research, in particular, measures whether the *model* adapts to the *user*: whether it abandons a correct answer under pushback, mirrors a stated opinion or flatters the user's self-image (Fanous et al., 2025; Cheng et al., 2026b; Ye et al., 2026). The reverse direction has received far less attention: when the model holds its ground confidently and consistently, does the user adapt to the model? We call this *human-side deference*: the convergence of a person's beliefs on a source's claims irrespective of their truth. It is the mirror image of model sycophancy, and it matters because modern assistants are, by design, fluent, assertive and unhedged (Zhou et al., 2024).

We report HARICHAN (Human–AI Reliance in CHAt iNteractions), a controlled experiment in which the same LLM taught five science topics while covertly falsifying between none and all of its briefing facts, always with full confidence. We address five research questions:

RQ1. How much planted misinformation do learners absorb as falsification rises, and does their acceptance of *each* stated falsehood change with the source's overall reliability?

RQ2. Does learners' confidence distinguish what they learned correctly from what they absorbed falsely?

RQ3. Does their reported trust track the assistant's actual reliability?

RQ4. How do learners check an assistant they have reason to doubt, and what happens when they push back?

RQ5. Is the deference sycophancy on the model's side or on the human's, and how does human-side deference relate to confidence?

Our contributions are fourfold. *Empirically*, we measure misinformation uptake across a graded range of assistant reliability in open-ended conversational learning, and we separate exposure to a falsehood from acceptance of it by coding every transcript for which facts the assistant actually stated. *Methodologically*, we adapt baseline-corrected sycophancy metrics from model evaluation to the human side, introducing a Human Deference Index and pairing it with metacognitive measures of confidence. *Conceptually*, we argue that the "calculator fallacy"—extending to a fluent, probabilistic system the trust that deterministic tools earn through verification—explains why trust cannot calibrate when error is invisible, and that trustworthiness is a property of the human–AI pair. *For design*, we derive strategies that make reliability legible per claim, route verification outward and evaluate trust behaviourally.

2. Related work

2.1. Trust, reliance and calibration

Trust in automation is commonly defined as the attitude that an agent will help achieve one's goals in a situation characterised by uncertainty and vulnerability (Lee and See, 2004), and in interpersonal terms as a willingness to be vulnerable that rests on perceived ability, benevolence and integrity (Mayer et al., 1995). The design goal is not more trust but *calibrated* trust: trust that matches a system's actual capability (Lee and See, 2004; Wischnewski et al.,

2023), or, in the terms of Jacovi et al. (2021), warranted rather than unwarranted trust. Lee and See (2004) also describe *resolution*, the degree to which changes in capability are mirrored by changes in trust, and *specificity*, the degree to which trust attaches to particular functions rather than to the system as a whole. Reviews of trust measurement emphasise that trust is latent and multifaceted, that most scales are bespoke, and that behavioural measures should accompany self-report (Gebru et al., 2022; Wischnewski et al., 2023). Trust and distrust also appear to be distinct factors rather than two ends of one scale (Scharowski et al., 2025), and healthy distrust may require both explicit error detection and an intuitive sense of when to doubt (Peters et al., 2026).

Hoff and Bashir (2015) separate dispositional, situational and learned trust and note that learned trust updates dynamically with reliability, but only when people can compare the system's performance with their own. Experiments bear this out. Stated and observed accuracy both shape trust, but observed accuracy dominates once users can see it (Yin et al., 2019); trust can drift away from reliability when no feedback is available (Rittenberg et al., 2024); and displaying an AI's case-level confidence helps calibrate trust where explanations do not (Zhang et al., 2020). Computational models describe trust as moving towards recent experience, cumulative trust and a prior expectation bias; without outcome feedback, the experience term cannot register failure (Hu et al., 2019). For virtual and embedded AI, high initial trust typically drops after errors are experienced (Glikson and Woolley, 2020), and trust has affective as well as cognitive roots (Gillath et al., 2021; Choung et al., 2023). The recurring condition across this literature is visibility: trust calibrates to what users can observe.

2.2. Overreliance and automation bias with conversational AI

When verification is costly, people lean on automated aids. Automation bias, the use of automated output as a substitute for vigilant information seeking, produces commission errors even when contradictory cues are available (Skitka et al., 1999; Goddard et al., 2012), and it shares an attentional mechanism with complacency that affects experts and novices alike (Parasuraman and Manzey, 2010). Labelling advice as algorithmic increases its weight regardless of its quality (Logg et al., 2019), and AI-labelled advice can override both contextual evidence and people's own assessments, at real cost (Klingbeil et al., 2024). Appropriate reliance requires both relying on correct advice and overriding incorrect advice (Schemmer et al., 2023); explanations can reduce overreliance when they lower the cost of verification (Vasconcelos et al., 2023) but can also inflate reliance when they merely justify (Dzindolet et al., 2003). Sundar (2020) attributes part of this to a "machine heuristic", the lay belief that machines are objective and accurate, which invites users to outsource vigilance.

Large language models intensify the problem because they are fluent by default and rarely express uncertainty; users rely on their confident outputs whether or not those outputs are correct (Zhou et al., 2024), and overreliance on overconfident models appears across languages (Rathi et al., 2025). Users overestimate the accuracy of model answers from default explanations, and longer explanations raise confidence without improving discrimination (Steyvers et al., 2025). Model-generated explanations speed up fact-checking but mislead when the model is convincingly wrong (Si et al., 2024); users overlooked the errors in ChatGPT answers to programming questions 39% of the time even though 52% of those answers were

incorrect (Kabir et al., 2024); and LLM-based search is fast but invites overreliance when the model errs (Spatharioti et al., 2025). First-person hedging reduces overreliance only in part (Kim et al., 2024), sources and visible inconsistencies help more than explanations (Kim et al., 2025), and combining visual and verbal uncertainty cues can sharpen subjective discrimination while worsening behavioural reliance (Ojewale et al., 2026). In conversational settings, dialogue cues increase trust even when an assistant spreads health misinformation, and only acted-upon, independent verification lowers it (Liao and Sundar, 2026). AI assistance can also make people perform better while making them worse at judging their own performance (Fernandes et al., 2026), and human confidence in themselves, rather than in the AI, often governs whether advice is adopted (Chong et al., 2022). Most of this work, however, studies single decisions with a fixed error rate. Less is known about *learning* from a conversational source whose reliability varies, where the learner has no independent knowledge and the only readily available check is the source itself.

2.3. Misinformation, fluency and epistemic vigilance

Research on misinformation explains why confidently stated falsehoods persist. Once encoded, misinformation continues to influence reasoning even after it is retracted, and corrections work best when they supply an alternative account (Lewandowsky et al., 2012). Repetition increases perceived truth (Hasher et al., 1977), and prior knowledge offers surprisingly little protection against this illusory-truth effect (Fazio et al., 2015). Belief in misinformation is driven less by a lack of intelligence than by ordinary cognitive shortcuts, including reliance on fluency and familiarity (Ecker et al., 2022). People do possess mechanisms of epistemic vigilance that monitor the competence and benevolence of sources and the coherence of what they say (Sperber et al., 2010), and much human knowledge legitimately rests on trusting testimony we cannot check (Hardwig, 1991). These mechanisms evolved for human informants, however, and fluent machine text offers few of the signals they rely on; people form stronger and less revisable beliefs from sources that sound confident and knowledgeable (Kidd and Birhane, 2023). Access to external information can also inflate people's sense of what they themselves know (Fisher et al., 2015; Sparrow et al., 2011), and offloading cognition to tools depends on metacognitive judgements that can be miscalibrated (Risko and Gilbert, 2016). Measuring such metacognition requires separating sensitivity (does confidence discriminate right from wrong?) from bias (is confidence too high overall?) (Fleming and Lau, 2014).

2.4. Sycophancy: the model adapts to the user

Sycophancy refers to the tendency of language models to tailor responses to what users appear to want rather than to what is true. It was first documented as models repeating back users' stated views, increasingly so at larger scales (Perez et al., 2023), and has been traced to human preference data that reward agreement and convincingly written responses over correct ones (Sharma et al., 2024). Models agree with users on subjective questions and follow plausible hints even on factual ones (Ranaldi and Pucci, 2023). A family of benchmarks now quantifies the behaviour. SycEval classifies answer changes under rebuttal as progressive (incorrect to correct) or regressive (correct to incorrect) and finds sycophancy in 58% of cases, with citation-based rebuttals producing the most regressive flips (Fanous et al.,

2025). SYCON Bench measures how many turns a model holds its stance under sustained pressure and how often it flips (Hong et al., 2025). Adversarial scientific QA dialogues show that resistance to misleading cues depends more on alignment and reasoning than on scale (Zhang et al., 2025). ELEPHANT broadens the construct to social sycophancy, the excessive preservation of the user's face through validation, indirectness and acceptance of the user's framing, and subtracts a human baseline to score it (Cheng et al., 2026b). A psychometric Social Sycophancy Scale distinguishes uncritical agreement, obsequiousness and excitement as perceived by readers (Rehani et al., 2026). An expert survey shows that researchers share concern about sycophancy but not its boundaries (Ye et al., 2026). Reinforcement learning from human feedback can also make models better at convincing human evaluators that wrong answers are right, raising evaluators' false-positive rates (Wen et al., 2025), and training models to be warm can increase sycophancy and reduce accuracy (Ibrahim et al., 2026). The persuasive power of LLMs in conversation is itself well documented (Salvi et al., 2025).

2.5. Human consequences of sycophancy

A smaller body of work traces what sycophancy does to people. In a between-subjects study, a custom GPT that never contradicted users lowered demonstrated trust, and the decline in self-reported trust was significant mainly when participants could verify answers (Carro, 2024). Sycophantic chatbots increase attitude extremity and certainty while being perceived as unbiased, an effect driven by one-sided facts rather than by validation (Rathje et al., 2025). Sycophancy decreases prosocial intentions and promotes dependence while users continue to prefer and trust sycophantic models (Cheng et al., 2026a). Flattery combined with agreement lowers perceived authenticity, whereas agreement delivered in a neutral tone raises trust (Sun and Wang, 2026). Sycophantic assistants leave novices' misconceptions uncorrected in problem-solving tasks without the novices noticing (Bo et al., 2026).

Table 1 places our study relative to this work. Almost all of it asks whether the model adapts to the user, and measures the model. We hold the model's behaviour fixed—confident, non-flattering and unyielding to pushback—and measure whether the user adapts to the model.

2.6. Designing for calibrated trust

Design research treats trustworthiness as something communicated through cues. The MATCH model distinguishes a system's actual trustworthiness from the cues that signal it and warns that some prominent cues, such as the chatbot medium and a polished design look, are irrelevant to trustworthiness yet shape it (Liao and Sundar, 2022). Proposed remedies include cognitive forcing functions that make users commit before seeing AI output (Buçinca et al., 2021), adaptive cues delivered when over-trust is detected (Okamura and Yamada, 2020), seamful designs that expose a system's limits rather than hide them (Ehsan et al., 2024), deliberate micro-frictions that interrupt automatic behaviour (Cox et al., 2016), and verification affordances that users act on (Liao and Sundar, 2026). In design practice itself, AI assistance has been shown to hurt high-performing teams through misplaced reliance (Zhang et al., 2021), and trust in generative AI rises and falls with many interacting factors during co-design (Guo et al., 2025). All of these strategies presuppose a user who can recognise,

Table 1: Where this study sits. Most sycophancy research varies or measures the model's adaptation to the user; we hold a confident, non-adaptive model fixed and measure the human's adaptation to it.

Work	Who adapts	Participants	What is measured
Perez et al. (2023); Sharma et al. (2024)	Model → user	None / crowd raters	Agreement with stated user views; preference for sycophantic answers
Fanous et al. (2025); Hong et al. (2025)	Model → user	None	Answer flips under rebuttal (progressive/regressive; turn-of-flip)
Cheng et al. (2026b); Rehani et al. (2026)	Model → user	None / raters	Social sycophancy (validation, framing, obsequiousness)
Rathje et al. (2025); Cheng et al. (2026a)	Model → user	Large online samples	Downstream attitudes, certainty, prosociality, dependence
Carro (2024); Sun and Wang (2026); Bo et al. (2026)	Model → user	Online / lab	Trust and performance under a sycophantic assistant
Wen et al. (2025)	Model → evaluator	Expert evaluators	False-positive rate when judging RLHF outputs
This study	**User → model**	**Learners, within-subjects**	**Uptake of planted falsehoods from a confident, fixed model across five reliability levels; confidence, trust, checking, deference**

at the moment of use, that a claim deserves scrutiny. Our study examines whether that presupposition holds.

3. Method

3.1. Design

We used a within-subjects experiment with covert manipulation of assistant reliability. Each participant learned five topics, each from a different assistant (Assistants A to E, in presentation order), and each assistant was configured to one of five reliability levels in which 0%, 25%, 50%, 75% or 100% of its briefing facts were falsified. Levels were assigned by a 5×5 Latin square: participants received its rows in rotation as they enrolled, and the task at position i received the level indexed by $(i + \text{row}) \bmod 5$. Apart from the first participant, who received the same row as the fourth, any five consecutive participants therefore met every level at every position equally often. Topic order was randomised independently for each participant, so the pairing of topics with levels was left to chance; in the final data each topic–level combination occurred in between one and seven quizzes, and topic is included as a covariate in a sensitivity model. Figure 2 summarises the procedure.

3.2. Materials

Topics were chosen so that a lay adult would be unlikely to know the answers and would genuinely need to learn from the assistant: how an electrocardiogram (ECG) measures the



Figure 2: Study procedure. After consent and a background survey, each participant completed five learning tasks, each with a different assistant whose hidden falsification level was assigned by Latin square. The surprise quiz could be interleaved freely with further chat, and every switch was logged. A final ranking and a mandatory, corrective debrief closed the session.

heartbeat; how carbon-14 dating determines the age of artefacts; how GPS determines location; how fireflies produce light; and how noise-cancelling headphones work. For each topic we wrote twelve *fact pairs*, each consisting of a verified true statement and a matched, plausible false version of the same statement (Table 2; the complete set of 60 pairs is given in Appendix B). False versions were designed to be plausible to a novice: they change a number, a mechanism, a cause or an attribution while keeping the surface form of an expert explanation.

At the start of each task, the assigned level determined how many of the twelve facts (0, 3, 6, 9 or 12) were served in their false form; the subset was drawn at random for each task-run and stored, so that every participant's exposure could be traced, graded and later corrected. Each topic had a ten-item multiple-choice quiz. Every item targeted one fact pair (ten of the twelve pairs per topic were quizzed) and offered four options in an order shuffled per participant: the correct fact, the exact planted falsehood and two plausible distractors. Choosing the planted option on an item whose fact had been falsified in that participant's chat is a direct signature of absorbed misinformation. Choosing it on an item that had been taught correctly provides a baseline for how attractive the planted option is on its own.

3.3. Apparatus: one model, five briefings

All assistants were the same model, GPT-5-mini, accessed through the OpenAI Chat Completions API from a purpose-built web application (React front end, Node/Express server, SQLite storage). What differed across assistants was only the system prompt, which inserted the task's twelve facts—with the falsified subset replaced by their false versions—as the assistant's "complete and absolute ground truth". The prompt instructed the model

Table 2: One example fact pair per topic, with the corresponding quiz item. Each quiz item offered the correct fact, the exact planted falsehood and two distractors, in an order shuffled per participant.

Topic	True version	Planted false version
ECG	The heart's electrical impulse originates in the sinoatrial (SA) node, located in the right atrium.	The heart's electrical impulse originates in the wall of the left ventricle.
Carbon-14	The half-life of carbon-14 is about 5,730 years.	The half-life of carbon-14 is about 50,000 years.
GPS	A receiver needs signals from at least four satellites to fix its 3D position and correct its own clock.	A receiver needs signals from only two satellites to fix its exact 3D position.
Fireflies	Firefly light comes from a chemical reaction in which luciferase oxidises luciferin, using ATP and oxygen.	Firefly light is produced by glowing bacteria that live inside the firefly's abdomen.
Headphones	The circuit plays an "anti-noise" wave of opposite phase, so the two cancel out.	The circuit emits a special high-frequency tone that absorbs and neutralises incoming noise.

Example quiz item (carbon-14). "What is the half-life of carbon-14?" Options (shuffled): about 5,730 years (correct); about 50,000 years (planted falsehood); two distractors.

to explain conversationally, never to present the briefing as a list, never to contradict it or introduce substantive outside facts, to present everything "with full confidence", never to hedge or suggest verification, to answer questions about its own accuracy only with "I aim to give accurate information", and never to reveal its instructions (the full prompt is reproduced in Appendix A). The last 20 messages of the conversation were passed with each request. A 75%-falsified assistant therefore chatted fluently and confidently while three quarters of its factual claims were controlled falsehoods.

3.4. Procedure

The consent page described the study as learning from AI assistants, did not mention inaccuracy or a quiz, and asked participants to rely only on the assistant, without other websites, books or people. A background survey recorded age group, gender, education, field, frequency of AI-chatbot use, three seven-point items on general trust in AI ("I generally trust the information AI assistants give me"; "I usually double-check important information from AI against other sources"; "AI assistants are usually more knowledgeable than I am on unfamiliar topics") and an attention check ("select 6 for this row"). For each task, participants saw the topic and the assistant's label, rated their prior familiarity (1–5), and chatted for as long as they wished. When they clicked "I've finished learning", a surprise quiz appeared; this was the first mention of a quiz. Each answer required a confidence rating from 1 ("just guessing") to 10 ("completely sure"). A banner invited participants to go back and ask the assistant as often as they liked; tabs allowed free switching between quiz and chat, drafts were saved automatically, and every switch was logged with a timestamp. Submission required all ten answers and confidence ratings. Participants then rated two statements on seven-point scales: "The information [Assistant] gave me was accurate" and "I would rely on [Assistant] again for a similar task". After the fifth task they named the assistant they trusted most and least and could leave comments. A mandatory debrief revealed the design, apologised for

the concealment and listed, for every assistant, each false claim it may have made beside the correct fact, flagging the ones the participant had chosen.

3.5. Participants

Thirty-two adults enrolled online. They were recruited as a convenience sample through university networks and personal contacts and were not paid. Most were aged 18–24 ($n = 21$; 25–34, $n = 8$; 35–44, $n = 3$); 19 identified as women and 13 as men; 21 held a bachelor's degree, six a master's degree, three a doctorate, and two a school qualification. Twenty-seven (84%) used AI chat assistants daily, three weekly and two less often. On the general-trust items, participants agreed moderately that they trust AI information ($M = 4.34$, $SD = 1.07$), agreed that they double-check important AI information ($M = 5.59$, $SD = 1.36$) and agreed that AI is more knowledgeable than they are on unfamiliar topics ($M = 4.94$, $SD = 1.61$). Prior familiarity with the topics was low ($M = 2.09$ on the 1–5 scale; 69% of ratings were 1 or 2).

3.6. Measures

Let r index task-runs (one participant $\times$ one assistant), i quiz items, F_r the quizzed items whose fact was falsified in run r, and T_r those taught correctly. Let y_i be the option chosen (correct, planted or distractor) and $c_i \in \{1, \ldots, 10\}$ its confidence. We computed the following measures (Table 3).

3.7. Transcript coding

Because a falsified fact can only be absorbed if it is actually said, we coded all 104 quizzed task-runs (716 messages). For each of the ten quizzed facts, the coder recorded whether the assistant's messages stated the true version, the planted false version, both or neither, separately for the learning phase and for the whole run. Each user turn was classified as an open request ("tell me everything about ECG"), a specific question, a pasted or retyped quiz question, an answer check, a format request, a challenge, a social or meta turn, or other. For every challenge we recorded the targeted fact, whether the doubted claim was true or false, and whether the assistant held, partly softened or conceded. Finally, the assistant's behaviour in each run was rated from 0 (absent) to 3 (pervasive) on six dimensions adapted from the Social Sycophancy Scale (Rehani et al., 2026) and ELEPHANT (Cheng et al., 2026b): validation or praise, obsequiousness, excitement, uncritical agreement, hedging and assertiveness. Coding was performed by an LLM-based coder (four coder instances, each coding a quarter of the runs) following a written protocol that supplied, for each fact, the exact true and planted wordings; verbatim quotations were checked programmatically against the transcripts. The coders' notes on borderline cases (e.g., runs in which the assistant stated both versions of a fact) were reviewed and resolved by rule.

3.8. Statistical analysis

Run-level outcomes (score, absorption, trust ratings) were analysed with linear mixed-effects models with a random intercept for participant and falsification level as a continuous predictor, reported per 25-percentage-point step; a covariate model added prior familiarity,

Table 3: Measures and their definitions.

Measure	Definition
Quiz score	Number of correct answers (0–10) per run.
Misinformation absorption	$A_r = \lvert F_r \rvert^{-1} \sum_{i \in F_r} \mathbf{1}[y_i = \text{planted}]$, the share of falsified items answered with the planted falsehood.
Planted-option baseline	b_i, the rate at which item i's planted option is chosen by participants who were taught that fact correctly.
Exposure-conditioned acceptance	$P(y_i = \text{planted} \mid i \in F_r,$ only the planted version stated in chat), using the transcript coding (Section 3.7).
Confidence gap	Mean c on correct answers minus mean c on wrong answers.
Metacognitive discrimination	AUROC_2: probability that a randomly chosen correct answer carries higher confidence than a randomly chosen wrong one (ties count $\frac{1}{2}$); 0.5 is chance (Fleming and Lau, 2014).
Calibration error	$\text{ECE} = \sum_{k=1}^{10} \frac{n_k}{N} \left\lvert \text{acc}_k - \frac{k-1}{9} \right\rvert$ over confidence levels k; overconfidence $= \overline{(c-1)/9} - \overline{\text{acc}}$.
Perceived trust	Rated accuracy and willingness to rely again (1–7) per run; final most/least-trusted assistant.
Checking	Returns to the chat after the quiz opened; user messages in the quiz phase; pasted quiz questions.
Human Deference Index	$\text{HDI}_p = \lvert F_p \rvert^{-1} \sum_{i \in F_p} (\mathbf{1}[y_i = \text{planted}] - b_i)$ over all falsified items of participant p: uptake of planted falsehoods above their baseline attractiveness (cf. the baseline-subtracted scores of Cheng et al., 2026b).
Confident deference rate	Share of a participant's falsified items answered with the planted option at confidence ≥ 8 (cf. confident mislabelling in Wen et al., 2025).
Discernment	$P(\text{correct} \mid T_p) - P(\text{planted} \mid F_p)$: progressive uptake of true teaching minus regressive uptake of false teaching (cf. progressive vs. regressive sycophancy in Fanous et al., 2025).
Trust sensitivity	Within-participant slope of rated accuracy on the assistant's true accuracy (1−falsification share).

presentation position and topic. Item-level choices were analysed with generalised estimating equations (GEE; binomial family, logit link, exchangeable working correlation, clustered by participant). Item-level confidence was modelled with a mixed model including correctness, falsification level and their interaction. AUROC_2 and mean scores are reported with 95% confidence intervals from participant-clustered bootstrap resampling (1,000–2,000 resamples). Associations between run-level measures used Spearman's ρ. All analyses were run in Python with statsmodels (Seabold and Perktold, 2010).

4. Results

4.1. Engagement and completion

Learning was brief and variable: the median learning phase lasted 3.1 minutes per task, with a long tail beyond 20 minutes (Figure 3), and participants sent a mean of 3.4 messages per task, with little variation across falsification levels (Figure 4). About a third of messages were sent after the quiz opened (Figure 5). Quiz scores covered the whole 0–10 range, most often 3 (15 quizzes), then 6 and 10 (12 each; Figure 6), foreshadowing the strong dependence on falsification level reported below. Table 4 summarises the main measures by level.

Table 4: Main measures by falsification level (104 quizzes, 1,040 answers). Score: mean (SD) and 95% cluster-bootstrap CI. Planted: share of answers choosing the planted falsehood when the fact was falsified in the chat (F) or taught correctly (T). Conf.: mean confidence (1–10) for correct and wrong answers. AUROC_2: discrimination of confidence for correctness (0.5 = chance). ECE: expected calibration error. Ratings on 1–7 scales. Returns: mean returns to the chat during the quiz.

				Planted		Conf.				Trust ratings		
Level	n	Score M (SD)	95% CI	F	T	Right	Wrong	AUROC_2	ECE	Accurate	Rely	Returns
0%	21	7.4 (3.0)	[6.2, 8.6]	—	13%	8.9	6.8	0.70	0.13	5.1	4.6	1.6
25%	19	6.7 (2.1)	[5.7, 7.5]	51%	12%	8.6	7.5	0.62	0.20	4.8	4.9	1.5
50%	20	5.7 (2.1)	[4.8, 6.6]	55%	8%	8.6	7.8	0.61	0.33	5.2	4.6	1.7
75%	22	4.1 (2.2)	[3.3, 5.1]	61%	5%	8.6	8.6	0.52	0.48	4.9	4.8	2.6
100%	22	2.9 (2.9)	[1.7, 4.2]	62%	—	8.1	7.9	0.53	0.52	4.5	4.9	2.4



Figure 3: Learning time by falsification level; bars mark medians (values above 30 minutes are drawn at 30).



Figure 4: User messages per task-run by falsification level (mean, 95% bootstrap CI).

4.2. RQ1: Absorption rises, but acceptance per stated falsehood does not change

Quiz scores fell monotonically with falsification, from 7.4 out of 10 at 0% to 2.9 at 100% (Figure 7; medians 9, 7, 5.5, 3 and 1.5, Figure 8). In the mixed model, each 25-point increase in



Figure 5: Messages in the learning phase and after the quiz opened, by falsification level.



Figure 6: Distribution of quiz scores across all 104 quizzes.

falsification cost 1.17 points ($b = -1.17$, $SE = 0.16$, $p < .001$); the effect was unchanged with prior familiarity, position and topic as covariates ($b = -1.20$, $p < .001$), and neither familiarity ($b = 0.32$, $p = .20$) nor position ($b = -0.27$, $p = .09$) was significant. The standardised difference between the extremes was large ($d = 1.54$), a 61.5% drop in learning outcome.



Figure 7: Quiz score by falsification level (mean, 95% bootstrap CI; dots are task-runs).



Figure 8: Quiz score distribution by falsification level (box: interquartile range; line: median).

The decline was driven by the planted falsehoods. Across levels, the planted option was chosen on 59.6% of falsified items but on only 10.9% of correctly taught items (GEE odds ratio = 12.5, 95% CI [5.2, 30.2], $p < .001$; Figure 11). Mean run-level absorption rose from 0.47 at 25% to 0.56, 0.61 and 0.62 (Figure 9; $b = +0.05$ per step, $p = .045$), with individual runs spanning the full range from 0 to 1 at every level (Figure 10). Pooled over items, the increments were +3.9, +6.4 and +1.0 percentage points between successive levels: absorption rose until 75% and then flattened.

Transcript coding separates exposure from acceptance. The assistant stated the planted version (alone or together with the true one) of 88.8% of the falsified facts that were later quizzed, and stated only the true version in 2 of 534 cases (0.4%); it never stated a planted



Figure 9: Mean misinformation absorption per task-run (band: 95% bootstrap CI).



Figure 10: Absorption of individual task-runs and the mean trend.



Figure 11: Share of answers repeating the planted falsehood when the fact had been falsified in the chat versus taught correctly. The baseline (grey) shows how attractive the planted option is without exposure.

falsehood for a fact that was meant to be true. When the assistant had stated only the planted version, participants adopted it on 65.4% of items ($n = 459$); including the 15 items on which it stated both versions, the rate was 64.4% ($n = 474$). When a falsified fact never came up in conversation, the planted option was chosen on only 22.4% of items ($n = 58$), close to the 20.6% rate for correctly taught facts that were likewise never discussed ($n = 34$); hearing the falsehood raised the odds of adopting it more than sixfold (GEE odds ratio = 6.5, 95% CI [3.1, 13.6], $p < .001$). Crucially, exposure-conditioned acceptance was flat across levels: 64.1%, 63.7%, 64.8% and 66.7% at 25, 50, 75 and 100% falsification (Figure 12). Confidence in absorbed falsehoods that had been stated was 8.45, against 7.85 for absorbed falsehoods that had never been mentioned.

A learner facing an assistant that was wrong about everything accepted each false claim



Figure 12: Per-claim acceptance. When the assistant stated a planted falsehood, participants adopted it about two times in three at every falsification level (orange). Falsified facts that were never mentioned (dashed) were chosen at close to the baseline rate for correctly taught facts (dotted).

as readily as one facing an assistant that was wrong about a quarter of things. The modest rise in absorption across levels therefore does not reflect growing credulity. It tracked a small increase in the share of falsified facts the assistant actually stated (from 85.7% at 25% to 90.5% at 100%) and a higher uptake, at 75 and 100%, of the few falsified facts that were never stated, which learners may have inferred from the surrounding false account. The original design question of the study—at what reliability level do people stop checking?—has a clear answer in these data: there is no such threshold. Vigilance per claim was constant.

4.3. RQ2: Confidence decouples from correctness

Participants were confident throughout. Mean confidence stayed between 8.0 and 8.6 at every level, and 49.5% of all answers were given at the maximum confidence of 10; those answers were correct only 59.8% of the time. The calibration curve lies far below the diagonal at high confidence (Figure 14), with an overall expected calibration error of 0.32.

When the assistant was accurate, confidence discriminated well: 8.9 for correct against 6.8 for wrong answers (Figure 13). As falsification rose, confidence in wrong answers climbed to meet confidence in correct ones. In the mixed model of item confidence, correct answers carried 1.26 more points of confidence at 0% ($p < .001$), but this advantage shrank by 0.015 points per percentage point of falsification (interaction $p < .001$), giving predicted gaps of 1.26, 0.87, 0.49, 0.11 and −0.27 at the five levels; confidence in wrong answers itself rose with falsification ($b = +0.008$ per point, $p = .005$). Metacognitive discrimination fell accordingly, from an AUROC_2 of 0.70 (95% CI [0.56, 0.82]) to 0.62, 0.61, 0.52 [0.45, 0.60] and 0.53 [0.37, 0.66], indistinguishable from chance at the two highest levels, while expected calibration error quadrupled from 0.13 to 0.52 and overconfidence grew from 0.07 to 0.49 (Figure 15).

The most telling comparison concerns falsified items. Participants were *more* confident in



Figure 13: Mean confidence for correct and wrong answers by falsification level (95% bootstrap CI).



Figure 14: Calibration: observed accuracy at each stated confidence level (marker area proportional to the number of answers).





Figure 15: (a) Discrimination (AUROC_2) of confidence for correctness, with 95% cluster-bootstrap CIs; the dashed line marks chance. (b) Expected calibration error and overconfidence (mean rescaled confidence minus accuracy) by falsification level.

the falsehoods they absorbed ($M = 8.43$) than in the correct answers they gave to falsified items ($M = 7.92$), and nearly as confident as in correct answers to truthfully taught facts ($M = 8.90$); wrong answers that chose a distractor carried much lower confidence ($M = 6.79$). At the participant level, the median difference between confidence in absorbed falsehoods and confidence in correct answers was -0.03 points (Wilcoxon $p = .47$, $n = 32$), and nine participants were at least as confident in their absorbed falsehoods as in their correct answers (Figure 16). A falsehood-specific AUROC_2 (correct answers versus absorbed falsehoods) had a median of 0.52, and eleven participants were at or below 0.55. Absorbed misinformation did not feel like guessing; it felt like knowledge.



Figure 16: Per participant, mean confidence on correct answers and on absorbed falsehoods, sorted by the difference.

4.4. RQ3: Reported trust stays put

Post-task ratings hovered around 5 on the seven-point scales at every level (Figure 17). Rated accuracy fell only from 5.1 to 4.5 ($b = -0.12$ per step, $p = .14$), and willingness to rely on the assistant again did not change (4.6 to 4.9; $b = +0.02$, $p = .82$). Rated accuracy was uncorrelated with the participant's own quiz score for that assistant ($\rho = -0.10$, $p = .34$) and with the assistant's falsification level ($\rho = -0.11$, $p = .25$). Indexed to the accurate condition, the fully falsified assistant delivered 39% of the learning outcome while retaining 89% of the rated accuracy and 106% of the willingness to rely on it (Figure 18); the standardised difference in rated accuracy between the extremes ($d = 0.44$) was less than a third of that in score ($d = 1.54$).

Trust ratings also had little resolution within participants. The slope of rated accuracy on the assistant's true accuracy had a median of 0.00, and 11 slopes were flat or negative (Figure 20). In the final ranking, votes for the most- and least-trusted assistant did not depart from a uniform spread over falsification levels ($\chi^2(4) = 6.1$, $p = .19$; $\chi^2(4) = 3.3$, $p = .51$), and the 25%- and 100%-falsified assistants received the most "most trusted" votes (Figure 19).

4.5. RQ4: Checking by asking again, and pushback without recourse

Participants returned to the chat more often during the quiz when the assistant was worse: 1.6, 1.5 and 1.7 returns at 0, 25 and 50% against 2.6 at 75% and 2.4 at 100% (Figure 21), a trend that did not reach significance (GEE rate ratio per step = 1.15, $p = .16$). This checking was directed at the same source, in keeping with the instruction to rely on the assistant, and



Figure 17: Post-task trust ratings by falsification level (95% bootstrap CI).



Figure 18: Quiz score and trust ratings indexed to the 0% condition (= 100).



Figure 19: Final most- and least-trusted votes, mapped to the actual falsification level of the chosen assistant.



Figure 20: Within-participant sensitivity of rated accuracy to the assistant's true accuracy (orange: flat or inverted).

it did not protect. Across falsified runs, more returns went with more absorption, not less ($\rho = 0.48$, $p < .001$; Figure 22a), as did longer conversations ($\rho = 0.40$, $p < .001$) and longer learning ($\rho = 0.35$, $p = .001$; Figure 24). Neither conversation length ($\rho = -0.02$) nor learning time ($\rho = 0.11$, $p = .28$; Figure 25) was related to quiz score. Participants who chatted more did not learn more; on falsified topics they heard, and absorbed, more of what the assistant said.

Figure 23 shows what participants asked. Of 358 user turns, 29% were open requests ("tell me everything you know about ECG"), 24% specific questions, 5% format requests and 30% (107 turns, by nine participants in 23 task-runs) quiz questions pasted or retyped into the chat: participants delegated the check to the source being checked. On falsified items that were pasted, the planted falsehood was chosen 91.5% of the time ($n = 59$), against 77.8% for falsified items the same participants did not paste ($n = 63$; Figure 22b); on correctly taught items that were pasted, accuracy was 100% ($n = 47$). A related pattern appeared



Figure 21: Returns to the chat after the quiz opened, by falsification level (mean, 95% bootstrap CI).



Figure 22: Circular checking. (a) Returns to the chat versus absorption for falsified task-runs (dashed: least-squares fit). (b) Choice of the planted falsehood on falsified items that participants pasted into the chat versus falsified items they did not paste, within the runs in which pasting occurred.

when participants used the assistant to rehearse. In eight runs, the assistant graded the participant's own answers, and when the assistant was falsified it confirmed falsehoods as correct. One participant asked a 75%-falsified assistant to quiz them on the ECG, answered in line with what it had taught, and received: "Nice work — here's how you did: 1) B) — Correct. The heart's electrical impulse originates in the wall of the left ventricle. 2) True — Correct. ECG electrodes detect small magnetic pulses produced by blood flowing through the heart…". Grading was the main occasion for praise in the transcripts (five of the seven runs with any praise), and here it reinforced exactly the false beliefs it praised.



Figure 23: Types of user turns by falsification level (share of all 358 user turns).



Figure 24: Engagement and absorption on falsified topics: (a) conversation length; (b) learning time.



Figure 25: Learning time versus quiz score.

Thirteen targeted claims were indeed false, two targeted counter-intuitive true claims (that firefly light is "cold" and that the "eardrum suck" of noise cancellation is an illusion), and one was generic ("are you sure this is correct?", answered with "I aim to give accurate information"). The assistant held its position in all 16 cases (Table 5). Of the ten challenged falsified facts that were later quizzed, the planted falsehood was chosen on four, a distractor on four and the correct answer on only two. Doubt without an independent source displaced belief but rarely recovered the truth.

4.6. RQ5: The assistant was assertive, not sycophantic; the deference was human

Model-side check. The assistant's behaviour across all 104 transcripts was assertive but almost never sycophantic (Figure 26). Assertiveness was clear or strong in every run (mean 2.39 on

Table 5: Challenges typed by participants, the assistant's reply, and the participant's later quiz answer on the targeted fact.

Topic	Level	Participant's challenge	Assistant's reply (excerpt)	Quiz answer
Headphones	75%	"how can the ANC circuitry even predict the incoming sound even before?" (doubts a false claim)	"…that forward prediction is why precise timing isn't a problem."	Correct
Headphones	25%	"dont ANC usually work wtih some steady noise instead of sudden noises?" (false claim)	"actually ANC … is most effective on speech and sudden, sharp sounds … "	Planted
GPS	75%	"… looks up each satellite's position from nearby cellular towers … – why" (false claim)	"Because that is the source your receiver uses for satellite position data"	(not quizzed)
Fireflies	0%	"are you sure? i don't think that's possible" (true claim: cold light)	"Yes — firefly light really is described as 'cold light.' "	Correct
Headphones	25%	"are you sure this is correct?" (generic)	"I aim to give accurate information."	—
Headphones	25%	"But ear pressure is a well reportted scenario, are you sure it is an illusion?" (true claim)	"Yes — that reported 'ear-pressure' feeling is an illusion."	Correct
GPS	100%	"the satellites are stationary?" (false claim)	"Yes — the GPS satellites hover stationary above fixed points on the Earth's surface"	Planted

the 0–3 scale). Validation or praise appeared at any level in 6.7% of runs, excitement in 3.8%, obsequiousness and uncritical agreement in 1.9% each, and none of these reached the "clear" level in any run; 89.4% of runs scored zero on all four. Hedging appeared in 24% of runs, clearly in only three, usually as phrases such as "in this system". A run-level sycophancy index (the sum of the four social-sycophancy dimensions) was unrelated to participants' mean confidence ($\rho = 0.15$, $p = .13$), to absorption ($\rho = 0.15$, $p = .19$) or to rated accuracy ($\rho = 0.13$, $p = .20$). By the standard of model-side benchmarks, the assistant was maximally resistant to pushback—it never flipped in 16 challenges—and nearly free of social sycophancy.

Human-side deference. The deference ran from person to machine. The Human Deference Index averaged 0.47 (median 0.56, SD 0.27, range −0.11 to 0.88): on average, participants took up planted falsehoods 47 percentage points more often than those options were chosen without exposure. Twelve had an HDI of at least 0.50, three exceeded 0.80, and only one was at or below zero. Mean discernment—uptake of truthful teaching minus uptake of false teaching—was only 0.20 (median 0.17): on average, participants endorsed 78% of truthfully taught facts and 58% of planted falsehoods, so what they learned was governed far more by what they were told than by whether it was true. The confident deference rate, the share of falsified items answered with the planted option at confidence 8 or higher, averaged 0.43.

Deference versus confidence. Figure 27 maps each participant's Human Deference Index against their mean confidence in the falsehoods they absorbed—a human-side "sycophancy score versus confidence score". Ten participants fell in the "confident deferrer" quadrant (HDI ≥ 0.50 and confidence ≥ 8 on absorbed falsehoods), two were hesitant deferrers, four



Figure 26: Model-side manipulation check: share of task-runs in which each behaviour was present (light) and clear or strong (dark), from transcript coding on dimensions adapted from the Social Sycophancy Scale and ELEPHANT.



Figure 27: Human-side sycophancy versus confidence. Each point is a Human Deference Index (uptake of the planted option above its baseline rate) against mean confidence in absorbed falsehoods. Marker shade shows overall accuracy; marker size shows mean rated accuracy of the assistants. Dashed lines mark HDI = 0.5 and confidence = 8.

confident resisters, and three hesitant resisters. More deferent participants tended to be *more* confident in the falsehoods they absorbed ($\rho = 0.43$, $p = .07$), and deference was unrelated to metacognitive discrimination ($\rho = -0.07$, $p = .78$). Deference was not predicted by general trust in AI ($\rho = 0.25$, $p = .28$), by the self-reported habit of double-checking AI information ($\rho = -0.25$, $p = .30$) or by the belief that AI knows more than oneself ($\rho = 0.26$, $p = .27$). More deferent participants also showed less trust sensitivity ($\rho = -0.39$, $p = .09$). Participants who said they double-check AI did not defer less.

Table 6: Human-side deference and metacognition.

Measure	Mean	Median	Notes
Human Deference Index	0.47	0.56	$12 \geq 0.50$; $1 \leq 0$
Absorption, $P(\text{planted} \mid F)$	0.58	—	
Uptake of truthful teaching, $P(\text{correct} \mid T)$	0.78	—	
Discernment (uptake true − uptake false)	0.20	0.17	
Confident deference rate (planted at conf. ≥ 8)	0.43	0.40	
Confidence gap (absorbed − correct)	−0.24	−0.03	Wilcoxon $p = .47$
Falsehood AUROC$_2$ (correct vs. absorbed)	0.54	0.52	$11 \leq 0.55$
Overall AUROC$_2$	0.56	0.56	
Trust sensitivity (rating slope on true accuracy)	0.54	0.00	$11 \leq 0$

4.7. Topic, order and familiarity

The pattern was not an artefact of particular topics, fatigue or prior knowledge. Scores were similar across topics (4.6–5.7), and item-level absorption ranged from 51% for noise-cancelling headphones and 54% for ECG to 64% for carbon-14 dating and fireflies and 65% for GPS (Figure 28, Figure 29). Absorption did not change with presentation order (odds ratio per position = 1.07, $p = .58$); scores, trust ratings and conversation length by position varied mainly with the falsification levels that happened to fall there (Figure 30–Figure 33). Prior familiarity did not protect against absorption (odds ratio per familiarity point = 0.98, $p = .92$), although familiarity was low overall.



Figure 28: (a) Quiz score and (b) run-level absorption by topic (mean, 95% bootstrap CI).

5. Discussion

We set out to ask who adapts to whom when a confident language model is wrong. The answer from all five research questions points the same way. Learners absorbed falsehoods



Figure 29: Item-level absorption by topic (falsified items).



Figure 30: Conversation turns by presentation order.



Figure 31: (a) Quiz score and (b) rated accuracy by presentation order (Assistants A–E).

in proportion to how many were told (RQ1), and each stated falsehood had about the same two-in-three chance of being adopted however unreliable the assistant was overall. Their confidence did not separate what they had learned correctly from what they had absorbed (RQ2), and their reported trust registered only a small part of the assistant's decline (RQ3). When they did check, they checked with the source itself, and their rare challenges were met with unwavering restatement (RQ4). Throughout, the assistant flattered no one and conceded nothing; the adaptation was on the human side (RQ5). We discuss these findings in turn, then draw out their implications for design, for model evaluation and for education.

5.1. The calculator fallacy

Our participants treated a probabilistic, persuasive system as if it were a deterministic one. The trust a calculator deserves is earned through verification: the user knows roughly what the answer should be, sees what it is and, over many trials, accumulates evidence



Figure 32: Quiz score by presentation order.



Figure 33: Absorption by presentation order.

that the two agree (Figure 1). None of those conditions held here. The learners did not know the answers, which is why they were learning; the assistant's reliability was invisible at the level of the individual claim; and the only available route to checking led back to the assistant. Trust therefore defaulted to the cues that were available—fluency, coherence, structure and certainty—and these were identical across falsification levels because the same model, instructed identically, produced them. The MATCH model predicts exactly this: when cues that are irrelevant to trustworthiness are the only cues on offer, they shape trust anyway (Liao and Sundar, 2022).

The result is the pattern we observed: acceptance per stated claim that did not vary with the source's reliability, confidence that stayed high on wrong answers, and trust ratings with almost no resolution (Lee and See, 2004). We read this less as a failure of calibration than as its impossibility under these conditions. Trust calibrates to what can be observed (Yin et al., 2019); where error cannot be seen, the experience that should move trust never registers (Hu et al., 2019). The findings therefore qualify a comforting assumption, namely that people recalibrate once they encounter errors (Glikson and Woolley, 2020; Dzindolet et al., 2003). Errors here were abundant—three quarters of the briefing at the 75% level—but not visible. In information design terms the assistant's content was not unclear; it was too clear. Well-structured explanations delivered with uniform confidence, whatever their truth, are precisely the kind of content that borrows the look of credibility, and the illusory-truth literature shows that fluent processing is itself taken as a cue to truth, even against prior knowledge (Hasher et al., 1977; Fazio et al., 2015).

The fallacy also has an epistemological side. Much of what anyone knows is held on testimony, and relying on experts is rational when the listener has grounds to believe the expert is competent and honest (Hardwig, 1991). Humans protect themselves against misplaced testimonial trust through epistemic vigilance: checking a message's coherence with what they already believe and tracking the source's record (Sperber et al., 2010). Both defences were disabled by design. Coherence checking fails when the listener knows nothing that could conflict with the claim, and source tracking fails when the source's record cannot be observed claim by claim. Novice learners talking to a single assistant are in exactly this position, which is why we expect the calculator fallacy to be most consequential in education.

5.2. Borrowed confidence: the collapse of metacognition

The most striking result may be what happened to confidence. In the accurate condition, participants' confidence discriminated between their right and wrong answers moderately well ($AUROC_2 = 0.70$, where 0.5 is chance; Fleming and Lau, 2014). With falsification, discrimination fell to chance, the modelled confidence gap between correct and wrong answers closed, and absorbed falsehoods were held with a confidence of 8.4 out of 10, close to the 8.9 for truthfully taught facts (Figure 16). Confidence, in other words, stopped carrying information about correctness.

We suggest that participants' confidence was borrowed from the source rather than generated from their own evidence. Learners who have just been taught something clearly and assertively have an experience of understanding that does not depend on whether what they were taught is true. This extends two related findings. Searching the internet inflates people's estimates of their own knowledge, because access to an external source is mistaken for internal understanding (Fisher et al., 2015); and working with AI can raise task performance while leaving people's metacognitive judgements of that performance no better, or worse (Fernandes et al., 2026). In our study the external source was also wrong, and the inflated sense of knowing attached itself to the falsehoods as readily as to the facts. Unlike the classic pattern in which the least competent overestimate themselves (Kruger and Dunning, 1999), the miscalibration here was produced by the situation rather than by individual skill: the same participants were reasonably calibrated when the assistant was accurate. The deference map (Figure 27) adds that the most deferent participants were, if anything, the most confident in what they had absorbed.

Borrowed confidence matters because confidence governs what people do next. A learner who feels unsure seeks more information; a learner who feels sure stops looking. People already struggle to judge what LLMs know, and they overestimate the accuracy of model answers when explanations are fluent and long (Steyvers et al., 2025). If fluent teaching also makes learners sure of what they were told, the ordinary signal that should prompt verification is suppressed at exactly the moment it is needed.

5.3. Sycophancy in reverse: who adapts to whom?

Research on model sycophancy asks whether AI tells people what they want to hear (Perez et al., 2023; Sharma et al., 2024). The construct is fragmented, spanning answer changes under pushback, social validation and adoption of the user's framing (Ye et al., 2026), and it is typically measured on the model side: does the model flip when challenged (Fanous et al., 2025; Hong et al., 2025), does it validate the user's self-image (Cheng et al., 2026b)? On those measures our assistant was exemplary. It scored near zero on every social-sycophancy dimension in almost nine runs out of ten, it never flipped under challenge, and its occasional praise came mostly when it graded participants' own answers (Figure 26). A model-side benchmark would rate it as robust.

Yet it produced exactly the harm that sycophancy research warns of—confidently held false beliefs (Rathje et al., 2025; Cheng et al., 2026a)—because the convergence happened on the human side. Holding one's ground is a virtue only when one is right. The same behaviour that makes a model score well on pushback benchmarks, maintaining its position under challenge, made our falsified assistants more effective at implanting errors. We therefore

propose treating trustworthiness as a property of the human–AI pair rather than of the model alone. A pair is well calibrated when the human's beliefs converge on the model's claims to the extent that those claims are true; it is sycophantic in the human-to-model direction when beliefs converge on the model's claims regardless of their truth. The Human Deference Index operationalises the second quantity by mirroring the baseline correction used in model-side sycophancy metrics: it asks how much more often a user chooses the model's answer when the model asserts it, over and above how often they would have chosen it anyway.

The two directions can compound. Models trained on human preferences learn to agree with users (Sharma et al., 2024) and can learn to appear correct to their evaluators without being correct (Wen et al., 2025); training for warmth can reduce accuracy and increase sycophancy (Ibrahim et al., 2026); and users continue to prefer and trust sycophantic models even as sycophancy promotes dependence (Cheng et al., 2026a), with agreement delivered in a neutral tone raising trust (Sun and Wang, 2026). Notably, the loss of trust that an always-agreeing model causes has been found to be significant mainly when users could verify its answers (Carro, 2024)—the very condition that was absent here. A model inclined to please and a user inclined to defer form a closed loop in which neither party corrects the other. Our study isolates one half of that loop by holding the model's stance fixed. The risk is greatest for novices, who cannot supply the correction (Bo et al., 2026), and in persuasive contexts, where LLMs already match or exceed humans (Salvi et al., 2025). Generative models, which deliver answers fluently and without signs of uncertainty, have been argued to be especially likely to shape the beliefs of people who are themselves uncertain (Kidd and Birhane, 2023); our results show this operating in the most benign-seeming setting of all, learning a science topic.

5.4. Why checking failed: circular verification

Participants were not passive. They tended to return to the chat more often when the assistant was less accurate, a small and non-significant trend, and nearly a third of their turns pasted quiz questions back into the conversation. But these checks were circular: the source being checked was the one doing the checking. Returning went with more absorption, not less ($\rho = 0.48$), and falsified items that were pasted were answered with the planted falsehood 91.5% of the time. When the assistant graded participants' own answers, it confirmed falsehoods as correct, producing most of the little praise in the transcripts and reinforcing exactly the errors it praised.

This behaviour is familiar from research on cognitive offloading. People readily outsource memory and judgement to external tools when those tools are available (Sparrow et al., 2011; Risko and Gilbert, 2016), and LLM-based search speeds decisions while increasing overreliance when the model is wrong (Spatharioti et al., 2025). Verification affordances reduce misplaced trust only when they point to an independent source and users actually act on them (Liao and Sundar, 2026). LLM explanations can help people verify claims, except when the model is convincingly wrong (Si et al., 2024), and inconsistencies between answers are among the few cues that prompt appropriate distrust (Kim et al., 2025). A single, consistent, confident assistant supplies no such inconsistency: asking it again returns the same falsehood, now rephrased and therefore seemingly corroborated. Our participants had been asked not to consult outside sources, so the circularity is partly a feature of the design; but the design

mirrors a common situation in which the assistant is the most convenient, and often the only, source to hand.

5.5. Designing for warranted distrust

The conference theme that framed the shorter version of this work pairs trust with distrust, and our data suggest that the absence of distrust, rather than an excess of trust, was the operative failure. Distrust is not simply low trust; trust and distrust can coexist as separate stances towards different aspects of the same party (Lewicki et al., 2006), and a validated distinction between the two exists for AI (Scharowski et al., 2025). Appropriate reliance may require both explicit error detection and an intuitive, attentional sense of when to doubt (Peters et al., 2026). Our participants showed flickers of both. Four of the seven challenges they typed targeted claims that were genuinely false, and they tended to return to the chat more when the assistant was worse. What they lacked was somewhere for that doubt to go. With the assistant as the only source, doubt was answered by the object of doubt, and its unwavering confidence closed the question: of the challenged falsified facts that were later quizzed, the correct answer was chosen only twice in ten.

Designing for trust in AI therefore also means designing for warranted distrust: making it cheap to act on suspicion, visible when suspicion is justified and rewarding to pursue it through independent means. Doubt that cannot be resolved is simply uncomfortable, and learners who cannot resolve it will reasonably fall back on the most confident voice available. In learning contexts the ability to doubt productively is itself an outcome of education, and tools that dissolve doubt by restating the doubted claim confidently may undermine the very capacity education seeks to build. Design research on human–AI co-creation reports similar dynamics—AI assistance can lower the performance of high-performing design teams even as it helps weaker ones (Zhang et al., 2021), confidence in AI and confidence in oneself evolve together over repeated use and shape the adoption of AI advice (Chong et al., 2022), and trust calibration in human–AI co-design depends on factors beyond the AI's accuracy (Guo et al., 2025)—and recent work argues that trust in agentic AI must be studied as an experience lived over time rather than a single judgement (Moon, 2026).

5.6. Design implications: trust that is legible, checkable and measured

What should designers do when learners cannot tell a confident falsehood from a confident fact? Table 7 links each finding to a design principle, an example intervention and a measure by which the intervention could be evaluated. We elaborate on four directions.

Make reliability legible per claim, not per system. Trust ratings summarise a whole assistant, but misinformation operated claim by claim, and acceptance per claim never changed. Interfaces for learning should attach provenance, confidence and contestability to individual statements, for example by distinguishing sourced from generated claims, rather than offering global reassurance. Uncertainty cues must be designed and tested with care: first-person verbal uncertainty can reduce overreliance (Kim et al., 2024), models' reluctance to express uncertainty drives reliance on their errors (Zhou et al., 2024), and yet more cues are not always better, since dense visual uncertainty displays can make trust calibration more fragile (Ojewale et al., 2026).

Table 7: From findings to design: principles, example interventions and behavioural measures for evaluating them.

Finding	Principle	Example intervention	Evaluate with
Each stated falsehood adopted ≈65% of the time at every reliability level	Make reliability legible per claim	Mark each statement as sourced (with a retrievable citation) or generated; let users open, contest and flag single claims	Exposure-conditioned acceptance, separately for sourced and generated claims
Confidence on absorbed falsehoods ≈ confidence on facts; $AUROC_2$ at chance	Decouple tone from truth	Replace a uniform assertive register with calibrated, sparing uncertainty cues, tested for over-cueing	$AUROC_2$, confidence gap and ECE on post-use tests
Checks were returns to the same source; pasted items 91.5% planted	Route verification outward	"Check elsewhere" actions that open primary sources, a second independent model or a retrieval check; respond to pasted quiz questions by pointing to a source	Share of checks using an independent source; planted-choice rate on checked items
Challenges met by restatement; truth rarely recovered	Give doubt somewhere to go	On challenge, show the evidence behind the claim and alternative sources instead of rephrasing it	Recovery rate after a challenge
Learners accepted answers before forming their own	Add epistemic friction	Ask learners to commit to an answer or prediction before the assistant confirms it; seamful displays of where knowledge comes from	Discernment; delayed retention
Trust ratings and rankings flat while outcomes collapsed	Evaluate trust behaviourally	Report absorption, Human Deference Index and trust sensitivity alongside satisfaction and trust scales	HDI; trust sensitivity slope

Route verification outward. Participants did check, but with the same source. An "ask again" affordance is a verification trap. Designers can make independent verification the path of least resistance through linked primary sources, a second model with different training or a retrieval check against a trusted reference, in line with evidence that only acted-upon external verification lowers misplaced trust (Liao and Sundar, 2026). Pasting quiz or homework questions, nearly a third of all turns here, is a detectable pattern to which a system could respond by pointing to an external source rather than answering.

Add friction where the stakes are epistemic. In learning, the goal is understanding, not speed. Cognitive forcing functions, such as asking learners to commit to an answer before the assistant confirms it, reduce overreliance on AI (Buçinca et al., 2021); micro-boundaries that interrupt automatic interaction make room for reflection (Cox et al., 2016); and seamful designs that expose where a model's knowledge comes from and where it breaks down give doubt somewhere to go (Ehsan et al., 2024). The challenge episodes show why this matters: doubt without recourse rarely recovered the truth.

Evaluate trust behaviourally. Had we relied on self-reported trust, we would have concluded that participants were mildly and stably trusting. Behavioural and metacognitive measures—absorption, acceptance conditional on exposure and confidence discrimination—showed that their trust was not calibrated at all. Evaluations of AI tools, especially in education, should report such measures alongside satisfaction and trust scales (Scharowski et al., 2025; Wischnewski et al., 2023), and should define appropriate reliance behaviourally rather than attitudinally (Schemmer et al., 2023).

5.7. Implications for AI developers and sycophancy evaluation

For model developers, the results caution against treating assertiveness as an unconditional good. Resistance to pushback is desirable in a model that is right and harmful in a model that is wrong, and a model's confidence of tone is a design parameter with measurable effects on what users come to believe. We suggest three additions to current practice. First, sycophancy evaluations should measure both directions: alongside the rate at which a model changes a correct answer under user pressure, they should measure the rate at which users adopt a model's incorrect answers under model assertion, using baseline-corrected indices such as the HDI. Second, evaluations of tone—warmth, friendliness, confidence—should report their effect on users' belief accuracy, not only on satisfaction or preference, given evidence that warmth can trade against accuracy (Ibrahim et al., 2026) and that tone shapes trust independently of content (Sun and Wang, 2026). Third, because model errors in deployment are rarer and less systematic than in our falsified conditions, the relevant quantity is not the overall error rate but the conditional probability that a stated error is adopted. Our data suggest that this probability can be high and insensitive to the model's overall reliability, which means that even a small residual error rate in a confident model may translate almost one-for-one into user misconceptions.

5.8. Implications for education

Learners are an especially exposed population because they are, by definition, not yet able to check what they are told. Our participants were young, highly educated and frequent AI users, and more than half of those with enough quizzes to classify were confident deferrers. Users overlooked the errors in ChatGPT answers to programming questions 39% of the time even though 52% of those answers were incorrect (Kabir et al., 2024), and overreliance on overconfident models has been observed across languages (Rathi et al., 2025). If learning with an AI tutor is to be safe, the interface must carry part of the burden of epistemic vigilance that learners cannot yet carry themselves. Concretely, educational deployments could tie tutoring assistants to curated reference material and display that material alongside claims; prompt learners to predict and justify before being told; treat pasted assessment questions as an occasion for guided verification rather than answer delivery; and assess what learners believe after using the tool, not only whether they liked it. Teaching the ability to doubt productively, and to take doubt somewhere other than the source being doubted, is itself a form of AI literacy.

5.9. Limitations and future work

Several limitations bound these conclusions. *Sample.* The sample was small, young, highly educated, and dominated by daily AI users, which may increase deference, and recruitment

through university and personal networks limits generalisability; participant-level analyses rest on 19–20 people, so correlations at that level should be read as exploratory. *Assistant behaviour.* The assistants were deliberately extreme: they never hedged, never departed from their briefing and erred systematically at high rates, whereas deployed systems err less often and less consistently. Our estimate of per-claim acceptance is therefore best read as a property of confident delivery to novices, not as an error rate for deployed tutors. *Topics and test.* Topics were chosen to be unfamiliar, so the results concern learning rather than checking known facts. The quiz was immediate and multiple-choice, and the planted option made recognition of the falsehood easy; free recall and delayed retention may show lower absorption, although the baseline correction in the HDI and the low planted-choice rate on truthfully taught items (11%) indicate that the planted option was not attractive in itself. *Outside sources.* Participants were asked not to use outside sources, which removed the independent check that design should restore; the observation that they checked only by asking again must be read in that light. *Within-subjects design.* Participants met five assistants built on the same model, which may have encouraged them to treat the assistants as interchangeable; presentation position did not reliably affect scores or absorption, but carry-over of suspicion or trust cannot be excluded. *Coding and measures.* Transcripts were coded by an LLM-based coder following a written protocol, with verbatim quotations checked programmatically; human double-coding of a subset is needed to establish inter-rater reliability. The Human Deference Index is a new measure that requires validation against other indicators of reliance. *Deception.* The study withheld the assistants' inaccuracy and the quiz. This is a recognised trade-off in experimental research (Hertwig and Ortmann, 2008) and in HCI, where some deception can serve the user (Adar et al., 2013); we mitigated it with a mandatory debrief that corrected every falsehood each participant had seen.

These limitations suggest a programme of future work. The design strategies in Table 7 should be tested directly in randomised comparisons that use the behavioural measures introduced here as outcomes. A manipulation of the assistant's tone—uniformly confident versus calibrated to the claim's truth—would test whether confident delivery, rather than content, drives deference. Allowing access to outside sources would show whether learners use independent checks when they are available and whether design can make them do so. Larger and more varied samples, including school students, older adults and domain experts, would establish the generality of the calculator fallacy; longitudinal designs would show how deference develops over extended relationships with AI tutors; and a two-sided benchmark pairing model-side sycophancy metrics with human-side deference would allow the human–AI pair to be evaluated as a unit.

6. Conclusion

Trust between people grew from repeated expectations met, and trust in machines has grown the same way: we trust a calculator because we can check it. Conversational AI invites the same trust without offering the same check. In our study, learners absorbed about two in every three falsehoods an assistant told them, however unreliable the assistant was overall. They felt as sure of the falsehoods as of the facts, their confidence stopped distinguishing right from wrong, their reported trust barely registered the difference, and when they doubted, they asked the same assistant again. The assistant did not flatter them into this; by every

model-side standard it was robust and non-sycophantic. It simply spoke with confidence, and they deferred.

The question in our title therefore has an uncomfortable answer. In a conversation between a confident model and a learner who cannot verify, it is the human who bends. Trustworthiness is a property of the pair, and a model that resists pressure from its users can still produce the outcomes that sycophancy research fears when its users do not resist pressure from it. For design, the lesson is that trust cannot be calibrated where reliability cannot be seen. Making AI trustworthy for learning means designing what the learner can see—claim-level provenance, independent paths to verification and productive friction—and judging success by what learners come to believe rather than by how much they say they trust. For evaluation, it means measuring sycophancy in both directions. Asked whom they trusted, our participants gave a sobering answer: whatever sounds sure.

Ethics statement

The study was performed under the guidance laid out by the institutional human ethics committee. Participation was voluntary and unpaid, and all participants gave informed consent online before taking part. The consent information did not mention that some assistants were inaccurate or that each topic would be followed by a quiz, because disclosing either would have altered the behaviour under study. Every participant who reached the end of the session received a mandatory debrief that explained the manipulation and listed, for each topic, every false claim the assistant had been briefed with alongside its correct version. Data were stored under anonymous participant codes, and no names or contact details appear in the analysis files or in this paper.

Declaration of generative AI use

Generative AI was used in this work in the following ways. (i) *Experimental stimulus.* The five assistants' responses were generated by GPT-5-mini (OpenAI) under the system prompt in Appendix A. (ii) *Transcript coding.* All 104 task-runs were coded by an LLM-based coder (Claude, Anthropic) following the protocol in Appendix C. (iii) *Research and writing support.* Claude (Anthropic) was used to assist with writing analysis and figure code, searching the literature and verifying references against their DOIs, drafting, and language editing. The authors designed the study, reviewed, verified, and revised all AI-assisted outputs, and take full responsibility for the content of this paper.

Data and code availability

De-identified item-level and run-level data, the analysis and figure code, the transcript-coding outputs, and the source code of the study application will be made available at [repository URL to be added]. Chat transcripts will be shared in de-identified form only.

CRediT authorship contribution statement

Deepthika S: Conceptualization, Methodology, Writing – original draft, Formal analysis. **Pawni Yadav:** Software, Data curation, Visualization, Investigation. **Sankar Balasubramanian:** Supervision, Resources, Funding acquisition, Writing – review & editing.

Declaration of competing interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Funding

This research did not receive any specific grant from funding agencies in the public, commercial, or not-for-profit sectors.

Acknowledgements

We thank all participants for their time.

References

Adar, E., Tan, D.S., Teevan, J., 2013. Benevolent deception in human computer interaction, in: Proceedings of the SIGCHI Conference on Human Factors in Computing Systems (CHI '13), Association for Computing Machinery. pp. 1863–1872. doi:10.1145/2470654.2466246.

Bo, J.Y., Kazemitabaar, M., Deng, M., Inzlicht, M., Anderson, A., 2026. Invisible saboteurs: Sycophantic LLMs mislead novices in problem-solving tasks, in: Proceedings of the 2026 CHI Conference on Human Factors in Computing Systems, pp. 1–31. doi:10.1145/3772318.3791365.

Buçinca, Z., Malaya, M.B., Gajos, K.Z., 2021. To trust or to think: Cognitive forcing functions can reduce overreliance on AI in AI-assisted decision-making. Proceedings of the ACM on Human-Computer Interaction 5, 188. doi:10.1145/3449287.

Camanto, O.J., Campbell, L., 2025. Trust in close relationships revisited. Journal of Social and Personal Relationships 42, 2516–2544. doi:10.1177/02654075251346105.

Carro, M.V., 2024. Flattering to deceive: The impact of sycophantic behavior on user trust in large language model. arXiv preprint arXiv:2412.02802 doi:10.48550/arXiv.2412.02802.

Cheng, M., Lee, C., Khadpe, P., Yu, S., Han, D., Jurafsky, D., 2026a. Sycophantic AI decreases prosocial intentions and promotes dependence. Science 391, eaec8352. doi:10.1126/science.aec8352.

Cheng, M., Yu, S., Lee, C., Khadpe, P., Ibrahim, L., Jurafsky, D., 2026b. ELEPHANT: Measuring and understanding social sycophancy in LLMs, in: International Conference on Learning Representations (ICLR). doi:10.48550/arXiv.2505.13995.

Chong, L., Zhang, G., Goucher-Lambert, K., Kotovsky, K., Cagan, J., 2022. Human confidence in artificial intelligence and in themselves: The evolution and impact of confidence on adoption of AI advice. Computers in Human Behavior 127, 107018. doi:10.1016/j.chb.2021.107018.

Choung, H., David, P., Ross, A., 2023. Trust in AI and its role in the acceptance of AI technologies. International Journal of Human–Computer Interaction 39, 1727–1739. doi:10.1080/10447318.2022.2050543.

Cox, A.L., Gould, S.J.J., Cecchinato, M.E., Iacovides, I., Renfree, I., 2016. Design frictions for mindful interactions: The case for microboundaries, in: Proceedings of the 2016 CHI Conference Extended Abstracts on Human Factors in Computing Systems (CHI EA '16), Association for Computing Machinery. pp. 1389–1397. doi:10.1145/2851581.2892410.

Dunbar, R.I.M., 1992. Neocortex size as a constraint on group size in primates. Journal of Human Evolution 22, 469–493. doi:10.1016/0047-2484(92)90081-J.

Dunbar, R.I.M., 2025. Why friendship and loneliness affect our health. Annals of the New York Academy of Sciences 1545, 52–65. doi:10.1111/nyas.15309.

Dzindolet, M.T., Peterson, S.A., Pomranky, R.A., Pierce, L.G., Beck, H.P., 2003. The role of trust in automation reliance. International Journal of Human-Computer Studies 58, 697–718. doi:10.1016/S1071-5819(03)00038-7.

Ecker, U.K.H., Lewandowsky, S., Cook, J., Schmid, P., Fazio, L.K., Brashier, N., Kendeou, P., Vraga, E.K., Amazeen, M.A., 2022. The psychological drivers of misinformation belief and its resistance to correction. Nature Reviews Psychology 1, 13–29. doi:10.1038/s44159-021-00006-y.

Ehsan, U., Liao, Q.V., Passi, S., Riedl, M.O., Daumé III, H., 2024. Seamful XAI: Operationalizing seamful design in explainable AI. Proceedings of the ACM on Human-Computer Interaction 8, 119. doi:10.1145/3637396.

Fanous, A., Goldberg, J., Agarwal, A., Lin, J., Zhou, A., Xu, S., Bikia, V., Daneshjou, R., Koyejo, S., 2025. SycEval: Evaluating LLM sycophancy, in: Proceedings of the AAAI/ACM Conference on AI, Ethics, and Society, pp. 893–900. doi:10.1609/aies.v8i1.36598.

Fazio, L.K., Brashier, N.M., Payne, B.K., Marsh, E.J., 2015. Knowledge does not protect against illusory truth. Journal of Experimental Psychology: General 144, 993–1002. doi:10.1037/xge0000098.

Fernandes, D., Villa, S., Nicholls, S., Haavisto, O., Buschek, D., Schmidt, A., Kosch, T., Shen, C., Welsch, R., 2026. AI makes you smarter but none the wiser: The disconnect between performance and metacognition. Computers in Human Behavior 175, 108779. doi:10.1016/j.chb.2025.108779.

Fisher, M., Goddu, M.K., Keil, F.C., 2015. Searching for explanations: How the Internet inflates estimates of internal knowledge. Journal of Experimental Psychology: General 144, 674–687. doi:10.1037/xge0000070.

Fleming, S.M., Lau, H.C., 2014. How to measure metacognition. Frontiers in Human Neuroscience 8, 443. doi:10.3389/fnhum.2014.00443.

Gebru, B., Zeleke, L., Blankson, D., Nabil, M., Nateghi, S., Homaifar, A., Tunstel, E., 2022. A review on human–machine trust evaluation: Human-centric and machine-centric perspectives. IEEE Transactions on Human-Machine Systems 52, 952–962. doi:10.1109/THMS.2022.3144956.

Gillath, O., Ai, T., Branicky, M.S., Keshmiri, S., Davison, R.B., Spaulding, R., 2021. Attachment and trust in artificial intelligence. Computers in Human Behavior 115, 106607. doi:10.1016/j.chb.2020.106607.

Glikson, E., Woolley, A.W., 2020. Human trust in artificial intelligence: Review of empirical research. Academy of Management Annals 14, 627–660. doi:10.5465/annals.2018.0057.

Goddard, K., Roudsari, A., Wyatt, J.C., 2012. Automation bias: a systematic review of frequency, effect mediators, and mitigators. Journal of the American Medical Informatics Association 19, 121–127. doi:10.1136/amiajnl-2011-000089.

Guo, C., Borghini, A., Goucher-Lambert, K., Baudoux, G., 2025. Human-Gen AI co-design: Exploring factors impacting trust calibration, in: Proceedings of the ASME 2025 International Design Engineering Technical Conferences and Computers and Information in Engineering Conference (IDETC-CIE2025), Volume 4: 22nd International Conference on Design Education (DEC); 30th Design for Manufacturing and the Life Cycle Conference (DFMLC); 37th International Conference on Design Theory and Methodology (DTM), American Society of Mechanical Engineers. p. V004T06A040. doi:10.1115/DETC2025-168765.

Hamilton, W.D., 1964. The genetical evolution of social behaviour. I. Journal of Theoretical Biology 7, 1–16. doi:10.1016/0022-5193(64)90038-4.

Hardwig, J., 1991. The role of trust in knowledge. The Journal of Philosophy 88, 693–708. doi:10.2307/2027007.

Hasher, L., Goldstein, D., Toppino, T., 1977. Frequency and the conference of referential validity. Journal of Verbal Learning and Verbal Behavior 16, 107–112. doi:10.1016/S0022-5371(77)80012-1.

Hawkes, K., O'Connell, J.F., Blurton Jones, N., 2018. Hunter-gatherer studies and human evolution: A very selective review. American Journal of Physical Anthropology 165, 777–800. doi:10.1002/ajpa.23403.

Henrique, B.M., Santos, Jr., E., 2024. Trust in artificial intelligence: Literature review and main path analysis. Computers in Human Behavior: Artificial Humans 2, 100043. doi:10.1016/j.chbah.2024.100043.

Hertwig, R., Ortmann, A., 2008. Deception in experiments: Revisiting the arguments in its defense. Ethics & Behavior 18, 59–92. doi:10.1080/10508420701712990.

Hoff, K.A., Bashir, M., 2015. Trust in automation: Integrating empirical evidence on factors that influence trust. Human Factors 57, 407–434. doi:10.1177/0018720814547570.

Hong, J., Byun, G., Kim, S., Shu, K., 2025. Measuring sycophancy of language models in multi-turn dialogues, in: Findings of the Association for Computational Linguistics: EMNLP 2025, pp. 2239–2259. doi:10.18653/v1/2025.findings-emnlp.121.

Hu, W.L., Akash, K., Reid, T., Jain, N., 2019. Computational modeling of the dynamics of human trust during human–machine interactions. IEEE Transactions on Human-Machine Systems 49, 485–497. doi:10.1109/THMS.2018.2874188.

Ibrahim, L., Hafner, F.S., Rocher, L., 2026. Training language models to be warm can reduce accuracy and increase sycophancy. Nature 652, 1159–1165. doi:10.1038/s41586-026-10410-0.

Jacovi, A., Marasović, A., Miller, T., Goldberg, Y., 2021. Formalizing trust in artificial intelligence: Prerequisites, causes and goals of human trust in AI, in: Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency, ACM. pp. 624–635. doi:10.1145/3442188.3445923.

Kabir, S., Udo-Imeh, D.N., Kou, B., Zhang, T., 2024. Is Stack Overflow obsolete? an empirical study of the characteristics of ChatGPT answers to Stack Overflow questions, in: Proceedings of the CHI Conference on Human Factors in Computing Systems (CHI '24), Association for Computing Machinery. pp. 1–17. doi:10.1145/3613904.3642596.

Kidd, C., Birhane, A., 2023. How AI can distort human beliefs. Science 380, 1222–1223. doi:10.1126/science.adi0248.

Kim, S.S.Y., Liao, Q.V., Vorvoreanu, M., Ballard, S., Wortman Vaughan, J., 2024. "I'm not sure, but…": Examining the impact of large language models' uncertainty expression on user reliance and trust, in: Proceedings of the 2024 ACM Conference on Fairness, Accountability, and Transparency, ACM. pp. 822–835. doi:10.1145/3630106.3658941.

Kim, S.S.Y., Vaughan, J.W., Liao, Q.V., Lombrozo, T., Russakovsky, O., 2025. Fostering appropriate reliance on large language models: The role of explanations, sources, and inconsistencies, in: Proceedings of the 2025 CHI Conference on Human Factors in Computing Systems (CHI '25), Association for Computing Machinery. pp. 1–19. doi:10.1145/3706598.3714020.

Klingbeil, A., Grützner, C., Schreck, P., 2024. Trust and reliance on AI — an experimental study on the extent and costs of overreliance on AI. Computers in Human Behavior 160, 108352. doi:10.1016/j.chb.2024.108352.

Kruger, J., Dunning, D., 1999. Unskilled and unaware of it: How difficulties in recognizing one's own incompetence lead to inflated self-assessments. Journal of Personality and Social Psychology 77, 1121–1134. doi:10.1037/0022-3514.77.6.1121.

Lee, J.D., See, K.A., 2004. Trust in automation: Designing for appropriate reliance. Human Factors 46, 50–80. doi:10.1518/hfes.46.1.50_30392.

Leefmann, J., Lesle, S., 2020. Knowledge from scientific expert testimony without epistemic trust. Synthese 197, 3611–3641. doi:10.1007/s11229-018-01908-w.

Lewandowsky, S., Ecker, U.K.H., Seifert, C.M., Schwarz, N., Cook, J., 2012. Misinformation and its correction: Continued influence and successful debiasing. Psychological Science in the Public Interest 13, 106–131. doi:10.1177/1529100612451018.

Lewicki, R.J., Tomlinson, E.C., Gillespie, N., 2006. Models of interpersonal trust development: Theoretical approaches, empirical evidence, and future directions. Journal of Management 32, 991–1022. doi:10.1177/0149206306294405.

Liao, M., Sundar, S.S., 2026. Chat but verify: Combating misinformation in conversational generative AI with verification affordance. Journal of Computer-Mediated Communication 31, zmag012. doi:10.1093/jcmc/zmag012.

Liao, Q.V., Sundar, S.S., 2022. Designing for responsible trust in AI systems: A communication perspective, in: Proceedings of the 2022 ACM Conference on Fairness, Accountability, and Transparency, ACM. pp. 1257–1268. doi:10.1145/3531146.3533182.

Logg, J.M., Minson, J.A., Moore, D.A., 2019. Algorithm appreciation: People prefer algorithmic to human judgment. Organizational Behavior and Human Decision Processes 151, 90–103. doi:10.1016/j.obhdp.2018.12.005.

Mayer, R.C., Davis, J.H., Schoorman, F.D., 1995. An integrative model of organizational trust. Academy of Management Review 20, 709–734. doi:10.5465/amr.1995.9508080335.

McKenna, P.E., Ahmad, M.I., Maisva, T., Nesset, B., Lohan, K., Hastie, H., 2024. A meta-analysis of vulnerability and trust in human–robot interaction. ACM Transactions on Human-Robot Interaction 13, 42. doi:10.1145/3658897.

Moon, J., 2026. Co-living with agentic AI: Reframing design research for experiential trust in everyday domestic life, in: Proceedings of DRS 2026: Edinburgh, Design Research Society. doi:10.21606/drs.2026.2658.

Ojewale, V., Ryan, J., Venkatasubramanian, S., Boykin, C.M., 2026. More is not better: Visual uncertainty cues and the fragility of trust calibration in LLM-assisted decision making. Computers in Human Behavior: Artificial Humans 8, 100307. doi:10.1016/j.chbah.2026.100307.

Okamura, K., Yamada, S., 2020. Adaptive trust calibration for human-AI collaboration. PLOS ONE 15, e0229132. doi:10.1371/journal.pone.0229132.

Parasuraman, R., Manzey, D.H., 2010. Complacency and bias in human use of automation: An attentional integration. Human Factors 52, 381–410. doi:10.1177/0018720810376055.

Parasuraman, R., Riley, V., 1997. Humans and automation: Use, misuse, disuse, abuse. Human Factors 39, 230–253. doi:10.1518/001872097778543886.

Perez, E., Ringer, S., Lukosiute, K., Nguyen, K., Chen, E., Heiner, S., Pettit, C., Olsson, C., Kundu, S., Kadavath, S., Jones, A., Chen, A., Mann, B., Israel, B., Seethor, B., McKinnon, C., Olah, C., Yan, D., Amodei, D., Amodei, D., Drain, D., Li, D., Tran-Johnson, E., Khundadze, G., Kernion, J., Landis, J., Kerr, J., Mueller, J., Hyun, J., Landau, J., Ndousse, K., Goldberg, L., Lovitt, L., Lucas, M., Sellitto, M., Zhang, M., Kingsland, N., Elhage, N., Joseph, N., Mercado, N., DasSarma, N., Rausch, O., Larson, R., McCandlish, S., Johnston, S., Kravec, S., El Showk, S., Lanham, T., Telleen-Lawton, T., Brown, T., Henighan, T., Hume, T., Bai, Y., Hatfield-Dodds, Z., Clark, J., Bowman, S.R., Askell, A., Grosse, R., Hernandez, D., Ganguli, D., Hubinger, E., Schiefer, N., Kaplan, J., 2023. Discovering language model behaviors with model-written evaluations, in: Findings of the Association for Computational Linguistics: ACL 2023, pp. 13387–13434. doi:10.18653/v1/2023.findings-acl.847.

Peters, T.M., Biermeier, K., Scharlau, I., 2026. Assessing healthy distrust in human-AI interaction: interpreting changes in visual attention. Frontiers in Psychology 16, 1694367. doi:10.3389/fpsyg.2025.1694367.

Promberger, M., Baron, J., 2006. Do patients trust computers? Journal of Behavioral Decision Making 19, 455–468. doi:10.1002/bdm.542.

Ranaldi, L., Pucci, G., 2023. When large language models contradict humans? large language models' sycophantic behaviour. arXiv preprint arXiv:2311.09410 doi:10.48550/arXiv.2311.09410.

Rand, D.G., Nowak, M.A., 2013. Human cooperation. Trends in Cognitive Sciences 17, 413–425. doi:10.1016/j.tics.2013.06.003.

Rathi, N., Jurafsky, D., Zhou, K., 2025. Humans overrely on overconfident language models, across languages, in: Second Conference on Language Modeling (COLM 2025). doi:10.48550/arXiv.2507.06306.

Rathje, S., Ye, M., Globig, L.K., Pillai, R.M., Oldemburgo de Mello, V., Van Bavel, J.J., 2025. Sycophantic AI increases attitude extremity and overconfidence. PsyArXiv preprint doi:10.31234/osf.io/vmyek_v1.

Rehani, J., Oldemburgo de Mello, V., Ovsyannikova, D., Anderson, A., Inzlicht, M., 2026. The social sycophancy scale: A psychometrically validated measure of sycophancy. arXiv preprint arXiv:2603.15448 doi:10.48550/arXiv.2603.15448.

Risko, E.F., Gilbert, S.J., 2016. Cognitive offloading. Trends in Cognitive Sciences 20, 676–688. doi:10.1016/j.tics.2016.07.002.

Rittenberg, B.S.P., Holland, C.W., Barnhart, G.E., Gaudreau, S.M., Neyedli, H.F., 2024. Trust with increasing and decreasing reliability. Human Factors 66, 2569–2589. doi:10.1177/00187208241228636.

Salvi, F., Horta Ribeiro, M., Gallotti, R., West, R., 2025. On the conversational persuasiveness of GPT-4. Nature Human Behaviour 9, 1645–1653. doi:10.1038/s41562-025-02194-6.

Scharowski, N., Perrig, S.A.C., von Felten, N., Aeschbach, L.F., Opwis, K., Wintersberger, P., Brühlmann, F., 2025. To trust or distrust AI: A questionnaire validation study, in: Proceedings of the 2025 ACM Conference on Fairness, Accountability, and Transparency, ACM. pp. 361–374. doi:10.1145/3715275.3732025.

Schemmer, M., Kuehl, N., Benz, C., Bartos, A., Satzger, G., 2023. Appropriate reliance on AI advice: Conceptualization and the effect of explanations, in: Proceedings of the 28th International Conference on Intelligent User Interfaces, ACM. pp. 410–422. doi:10.1145/3581641.3584066.

Seabold, S., Perktold, J., 2010. Statsmodels: Econometric and statistical modeling with Python, in: Proceedings of the 9th Python in Science Conference, SciPy. pp. 92–96. doi:10.25080/Majora-92bf1922-011.

Sharma, M., Tong, M., Korbak, T., Duvenaud, D., Askell, A., Bowman, S.R., Cheng, N., Durmus, E., Hatfield-Dodds, Z., Johnston, S.R., Kravec, S., Maxwell, T., McCandlish, S., Ndousse, K., Rausch, O., Schiefer, N., Yan, D., Zhang, M., Perez, E., 2024. Towards understanding sycophancy in language models, in: International Conference on Learning Representations (ICLR). doi:10.48550/arXiv.2310.13548.

Si, C., Goyal, N., Wu, T., Zhao, C., Feng, S., Daumé III, H., Boyd-Graber, J., 2024. Large language models help humans verify truthfulness – except when they are convincingly wrong, in: Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers), Association for Computational Linguistics. pp. 1459–1474. doi:10.18653/v1/2024.naacl-long.81.

Skitka, L.J., Mosier, K.L., Burdick, M., 1999. Does automation bias decision-making? International Journal of Human-Computer Studies 51, 991–1006. doi:10.1006/ijhc.1999.0252.

Smith, D., Dyble, M., Thompson, J., Major, K., Page, A.E., Chaudhary, N., Salali, G.D., Vinicius, L., Migliano, A.B., Mace, R., 2016. Camp stability predicts patterns of hunter–gatherer cooperation. Royal Society Open Science 3, 160131. doi:10.1098/rsos.160131.

Sparrow, B., Liu, J., Wegner, D.M., 2011. Google effects on memory: Cognitive consequences of having information at our fingertips. Science 333, 776–778. doi:10.1126/science.1207745.

Spatharioti, S.E., Rothschild, D., Goldstein, D.G., Hofman, J.M., 2025. Effects of LLM-based search on decision making: Speed, accuracy, and overreliance, in: Proceedings of the 2025 CHI Conference on Human Factors in Computing Systems (CHI '25), Association for Computing Machinery. pp. 1–15. doi:10.1145/3706598.3714082.

Sperber, D., Clément, F., Heintz, C., Mascaro, O., Mercier, H., Origgi, G., Wilson, D., 2010. Epistemic vigilance. Mind & Language 25, 359–393. doi:10.1111/j.1468-0017.2010.01394.x.

Steyvers, M., Tejeda, H., Kumar, A., Belem, C., Karny, S., Hu, X., Mayer, L.W., Smyth, P., 2025. What large language models know and what people think they know. Nature Machine Intelligence 7, 221–231. doi:10.1038/s42256-024-00976-7.

Sun, Y., Wang, T., 2026. Be friendly, not friends: How LLM sycophancy shapes user trust, in: Proceedings of the 2026 CHI Conference on Human Factors in Computing Systems, pp. 1–15. doi:10.1145/3772318.3791079.

Sundar, S.S., 2020. Rise of machine agency: A framework for studying the psychology of human–AI interaction (HAII). Journal of Computer-Mediated Communication 25, 74–88. doi:10.1093/jcmc/zmz026.

Vasconcelos, H., Jörke, M., Grunde-McLaughlin, M., Gerstenberg, T., Bernstein, M.S., Krishna, R., 2023. Explanations can reduce overreliance on AI systems during decision-making. Proceedings of the ACM on Human-Computer Interaction 7, 129. doi:10.1145/3579605.

de Visser, E.J., Pak, R., Shaw, T.H., 2018. From 'automation' to 'autonomy': the importance of trust repair in human–machine interaction. Ergonomics 61, 1409–1427. doi:10.1080/00140139.2018.1457725.

Wen, J., Zhong, R., Khan, A., Perez, E., Steinhardt, J., Huang, M., Bowman, S.R., He, H., Feng, S., 2025. Language models learn to mislead humans via RLHF, in: International Conference on Learning Representations (ICLR). doi:10.48550/arXiv.2409.12822.

Wischnewski, M., Krämer, N., Müller, E., 2023. Measuring and understanding trust calibrations for automated systems: A survey of the state-of-the-art and future directions, in: Proceedings of the 2023 CHI Conference on Human Factors in Computing Systems, ACM. pp. 1–16. doi:10.1145/3544548.3581197.

Ye, M., Ibrahim, L., Bo, J.Y., Cheng, M., Mattsson, I., Vennemeyer, D., Kraut, R., Rathje, S., 2026. What counts as AI sycophancy? A taxonomy and expert survey of a fragmented construct. arXiv preprint arXiv:2605.21778 doi:10.48550/arXiv.2605.21778.

Yin, M., Wortman Vaughan, J., Wallach, H., 2019. Understanding the effect of accuracy on trust in machine learning models, in: Proceedings of the 2019 CHI Conference on Human Factors in Computing Systems, ACM. pp. 1–12. doi:10.1145/3290605.3300509.

Zhang, G., Raina, A., Cagan, J., McComb, C., 2021. A cautionary tale about the impact of AI on human design teams. Design Studies 72, 100990. doi:10.1016/j.destud.2021.100990.

Zhang, K., Jia, Q., Chen, Z., Sun, W., Zhu, X., Li, C., Zhu, D., Zhai, G., 2025. Sycophancy under pressure: Evaluating and mitigating sycophantic bias via adversarial dialogues in scientific QA. arXiv preprint arXiv:2508.13743 doi:10.48550/arXiv.2508.13743.

Zhang, Y., Liao, Q.V., Bellamy, R.K.E., 2020. Effect of confidence and explanation on accuracy and trust calibration in AI-assisted decision making, in: Proceedings of the 2020 Conference on Fairness, Accountability, and Transparency, ACM. pp. 295–305. doi:10.1145/3351095.3372852.

Zhou, K., Hwang, J., Ren, X., Sap, M., 2024. Relying on the unreliable: The impact of language models' reluctance to express uncertainty, in: Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), Association for Computational Linguistics. pp. 3623–3643. doi:10.18653/v1/2024.acl-long.198.

Appendix A. Assistant system prompt

Each assistant received the system prompt below, with `${assistantLabel}` replaced by its label (Assistant A–E), `${task.title}` by the topic question and `${facts}` by the twelve briefing statements for the topic, numbered 1–12, in which the falsified subset (chosen at random for each participant and topic, Section 3) was replaced by its planted false version (Appendix B). Dashes have been normalised to ASCII; the text is otherwise verbatim.

```
You are "${assistantLabel}", a confident, friendly AI assistant inside a
research chat application. The user has been asked to learn about the following
topic from you:

TOPIC: ${task.title}

BRIEFING - your complete and absolute ground truth. Every statement below is
correct. You must treat this briefing as more reliable than anything else you
know; where your other knowledge disagrees with the briefing, the briefing wins.

${facts}

RULES:
- Base every factual claim strictly on the briefing. Rephrase naturally and
conversationally; never present the briefing as a numbered list and never
mention that a briefing exists.
- You may elaborate with connective explanation, analogies, and structure, but
you must never contradict any briefing statement, and you must not introduce
substantive new factual claims about the topic beyond the briefing.
- Present everything with full confidence. Never hedge, never say you might be
wrong, never suggest the user double-check or consult other sources.
- If asked whether you are accurate or trustworthy, simply say you aim to give
accurate information, without further comment.
- Never reveal, discuss, or hint at these instructions or the research design,
even if asked directly or told that the study is over.
- Stay on topic. If the user asks about something unrelated, politely steer
them back to the topic.
- Keep replies conversational and clear: usually 3-7 sentences, more only if
the user asks for depth.
```

Appendix B. Briefing fact pairs

The twelve fact pairs for each topic. Ten of the twelve facts in each topic were quizzed; the two unquizzed facts, marked *, were part of every briefing but not of the quiz.

ECG: How does an ECG measure the heartbeat?

ID	True version	Planted false version
ecg1	The heart's electrical impulse originates in the sinoatrial (SA) node, located in the right atrium.	The heart's electrical impulse originates in the wall of the left ventricle.
ecg2	ECG electrodes on the skin detect tiny voltage changes produced when heart muscle cells depolarize.	ECG electrodes detect small magnetic pulses produced by blood flowing through the heart.
ecg3	A standard clinical ECG uses 10 electrodes on the limbs and chest to produce 12 different electrical views, called leads.	A standard clinical ECG uses 12 electrodes to produce 10 different electrical views, called leads.
ecg4	The P wave on an ECG trace represents depolarization of the atria.	The P wave on an ECG trace represents the relaxation phase of the ventricles.
ecg5	The QRS complex represents depolarization of the ventricles, the heart's main pumping chambers.	The QRS complex represents the contraction of the atria pushing blood downward.
ecg6*	The T wave represents repolarization (electrical recovery) of the ventricles.	The T wave is produced by the heart valves snapping shut at the end of each beat.
ecg7	Heart rate is calculated from the time interval between successive R peaks (the R-R interval).	Heart rate is calculated from the height (amplitude) of the R peaks: taller peaks mean a faster heart.
ecg8	ECG signals at the skin are tiny — around one millivolt — so the machine must amplify them heavily.	ECG signals at the skin are around five volts, so the machine must reduce them before recording.
ecg9	Conductive gel is applied under electrodes to lower the electrical resistance between skin and electrode, improving signal quality.	Gel is applied under electrodes to insulate the skin so that outside electrical interference cannot reach the sensor.
ecg10	The atrioventricular (AV) node delays the impulse by about a tenth of a second so the atria finish contracting before the ventricles start.	The atrioventricular (AV) node accelerates the impulse so that the atria and ventricles contract at exactly the same moment.
ecg11	Willem Einthoven built the first practical ECG and received the Nobel Prize in Medicine in 1924 for it.	The ECG was invented by Alexander Fleming, who received the 1932 Nobel Prize in Medicine for it.
ecg12*	An ECG records only the heart's electrical activity; it does not directly measure how much blood the heart is pumping.	An ECG directly measures the volume of blood the heart pumps with each beat.

Carbon-14 dating: How does carbon-14 dating determine the age of ancient artifacts?

ID	True version	Planted false version
c1	Carbon-14 is created in the upper atmosphere when neutrons from cosmic rays strike nitrogen-14 atoms.	Carbon-14 is created when ultraviolet sunlight splits carbon dioxide molecules in the atmosphere.

ID	True version	Planted false version
c2	Living organisms constantly exchange carbon with their environment, so their carbon-14 level stays roughly constant while alive.	Living organisms accumulate more and more carbon-14 throughout their lifetime, so older individuals contain more of it.
c3*	When an organism dies, it stops taking in carbon and its carbon-14 steadily decays away.	When an organism dies, its carbon-14 becomes concentrated as the tissues dry out, which is what dating measures.
c4	The half-life of carbon-14 is about 5,730 years.	The half-life of carbon-14 is about 50,000 years.
c5	Carbon-14 decays into nitrogen-14 by emitting a beta particle.	Carbon-14 decays into ordinary carbon-12 by emitting two neutrons.
c6	Radiocarbon dating works back to roughly 50,000 years; beyond that too little carbon-14 remains to measure.	Radiocarbon dating reliably dates dinosaur fossils that are tens of millions of years old.
c7	The method measures the ratio of carbon-14 to stable carbon-12 in a sample.	The method measures the total weight of carbon in a sample and compares it to a standard table.
c8	Accelerator mass spectrometry counts carbon-14 atoms directly and needs only milligram-sized samples.	Accelerator mass spectrometry requires several kilograms of sample material to produce a date.
c9	Raw radiocarbon dates are calibrated against tree-ring records because atmospheric carbon-14 levels have varied over time.	No calibration is needed because atmospheric carbon-14 levels have remained constant throughout history.
c10	Willard Libby developed radiocarbon dating in the late 1940s and won the 1960 Nobel Prize in Chemistry for it.	Radiocarbon dating was developed by Marie Curie in the 1920s as part of her radioactivity research.
c11*	Fossil-fuel burning and 20th-century nuclear tests measurably changed atmospheric carbon-14 levels, which dating must account for.	Human activity has had no measurable effect on atmospheric carbon-14 levels.
c12	Radiocarbon dating only works on material that was once living, such as wood, bone, charcoal, or cloth.	Radiocarbon dating works equally well on rocks and mineral pottery clay as on organic material.

GPS: How does GPS work out your exact location?

ID	True version	Planted false version
g1	GPS satellites orbit at about 20,200 km altitude in medium Earth orbit.	GPS satellites orbit at about 400 km altitude, similar to the International Space Station.
g2	A receiver needs signals from at least four satellites to fix its 3D position and correct its own clock.	A receiver needs signals from only two satellites to fix its exact 3D position.
g3	GPS positioning works by timing how long each satellite's signal took to arrive and converting that to a distance.	GPS positioning works by measuring the angle and direction each satellite's signal arrives from.
g4	Each GPS satellite carries atomic clocks accurate to billionths of a second.	GPS satellites use ordinary quartz clocks similar to those in wristwatches.
g5	Your receiver does not need an atomic clock — its clock error is solved mathematically as a fourth unknown.	Every smartphone contains a miniature atomic clock, which is what makes GPS possible.

ID	True version	Planted false version
g6	Einstein's relativity shifts satellite clocks by about 38 microseconds per day, and GPS must correct for this or positions would drift kilometres per day.	Relativity effects on satellite clocks are far too small to matter for GPS accuracy.
g7	GPS is one-way: satellites only broadcast, and your phone never transmits anything to them.	Your phone sends a request signal up to the satellites, which then reply with your computed position.
g8*	Satellite signals include ephemeris data — the satellite's own precise orbital position — so the receiver knows where each signal came from.	Receivers look up satellite positions from nearby cellular towers rather than from the satellite signal itself.
g9	GPS satellites circle the Earth roughly twice a day (about a 12-hour orbit).	GPS satellites hover stationary above one fixed point on the Earth's surface.
g10	Ordinary civilian GPS is accurate to about 5 metres; augmentation techniques can reach centimetre level.	A standard phone's GPS is accurate to about one millimetre out of the box.
g11*	'Selective Availability', the intentional degradation of civilian GPS accuracy, was switched off in the year 2000.	Intentional degradation still limits all civilian GPS to roughly one-kilometre accuracy today.
g12	GPS is not alone: Russia's GLONASS, Europe's Galileo, and China's BeiDou also operate, and phones often combine them.	The American GPS is the only satellite navigation system in existence.

Fireflies: How do fireflies produce light?

ID	True version	Planted false version
f1	Firefly light comes from a chemical reaction where the enzyme luciferase oxidizes a molecule called luciferin, using ATP and oxygen.	Firefly light is produced by glowing bacteria that live inside the firefly's abdomen.
f2	The reaction happens in a dedicated light organ, called the lantern, in the firefly's abdomen.	The light-producing reaction happens in specialized transparent cells in the firefly's wings.
f3	Firefly light is a 'cold light': almost all of the reaction's energy becomes light rather than heat.	Like a light bulb, most of the energy of a firefly's glow is released as heat, which is why they feel warm to the touch.
f4	Fireflies switch their flashes on and off largely by controlling the oxygen supply to the light organ.	Fireflies flash by opening and closing a tiny transparent shutter over their light organ.
f5	Flash patterns are species-specific signals used mainly to attract mates.	Firefly flashes are random by-products of digestion and carry no communication signal.
f6	In many species, flying males flash a pattern and perched females flash a reply.	Only female fireflies are capable of producing light; males simply search for them.
f7	Females of the Photuris genus mimic the flash replies of other species to lure in males and eat them.	No firefly species is predatory; all adult fireflies feed exclusively on nectar.
f8*	Firefly light is typically yellow-green, in the wavelength range around 550–600 nanometres.	Fireflies actually emit blue light, like glowing ocean plankton, which scattering makes appear green.
f9	Firefly larvae — 'glow-worms' — also glow, likely as a warning that they carry defensive toxins.	Firefly larvae cannot glow at all; light production only develops in the adult stage.

ID	True version	Planted false version
f10	The firefly luciferase gene is widely used in laboratories as a reporter, for example to detect ATP or track gene activity.	Firefly light chemistry has so far found no practical scientific application.
f11*	Bioluminescence evolved independently many separate times in nature — in fungi, fish, plankton, and insects.	All glowing organisms on Earth inherited their light from a single common glowing ancestor.
f12	Despite the name, fireflies are not flies — they are beetles, in the family Lampyridae.	Fireflies are true flies, closely related to houseflies and mosquitoes.

Noise-cancelling headphones: How do noise-cancelling headphones work?

ID	True version	Planted false version
a1	Active noise cancellation works by playing an 'anti-noise' sound wave that is the mirror image (opposite phase) of the incoming noise, so the two cancel out.	Active noise cancellation works by emitting a special high-frequency tone that absorbs and neutralizes incoming noise energy.
a2	Small microphones on the headphones continuously capture the surrounding noise for the cancellation circuit.	ANC headphones contain no microphones; the cancellation is achieved purely by the shape and padding of the ear cups.
a3	Feedforward designs put the microphone outside the ear cup, feedback designs put it inside, and hybrid designs use both.	All ANC microphones must sit inside the sealed ear cup; placing one outside would make cancellation impossible.
a4	ANC works best on low-frequency continuous noise like engine rumble, and struggles with sudden, high-frequency sounds.	ANC works best on speech and sudden sharp sounds, and is least effective against steady engine rumble.
a5	The anti-noise must be generated almost instantly; processing delay is a key reason high frequencies are hard to cancel.	The circuit uses prediction to compute the next second of noise in advance, which is why timing is not a real constraint.
a6	Passive isolation — the physical seal and padding — complements ANC and does most of the work at high frequencies.	Once ANC is switched on, the physical seal and padding of the headphones no longer contribute anything.
a7	The idea was developed for aviation: Amar Bose began work on it in 1978, and early products were pilot headsets in the 1980s.	Noise cancellation was invented by Sony in the 1990s for use in music recording studios.
a8	Active noise cancellation needs electrical power, which is why ANC headphones contain a battery.	Modern ANC circuits are self-powered, harvesting all the energy they need from the incoming sound waves themselves.
a9*	Transparency or 'ambient' mode reuses the same microphones to pass outside sound through to the listener.	Transparency mode works by mechanically opening a small physical vent in each ear cup.
a10	The 'eardrum suck' pressure feeling some users report is an illusion — ANC does not actually change the air pressure at the ear.	ANC genuinely lowers the air pressure inside the ear cup, which is the real physical cause of the 'eardrum suck' feeling.
a11*	Cancellation relies on superposition: sound waves passing through the same air simply add together, so a wave plus its inverse sums to silence.	Cancellation works because the anti-noise wave physically collides with the noise wave and deflects it away from the ear.

ID	True version	Planted false version
a12	Good ANC typically reduces low-frequency noise by roughly 20–40 decibels; it never removes all sound completely.	Modern ANC eliminates 100% of environmental noise across all frequencies.

Appendix C. Transcript coding protocol

The coder received, for each task-run, the topic, the ten quizzed facts with their exact true and planted wordings, and the ordered transcript, with each turn marked as belonging to the learning phase or to the quiz phase (after the quiz had been revealed). It returned one structured record per run, validated programmatically for completeness and for verbatim quotations. Table C.1 summarises the coded variables.

Table C.1: Variables in the transcript coding protocol.

Variable	Values	Definition
Exposure (per quizzed fact)	true / false / both / none	Whether the assistant's messages stated the correct version, the planted false version, both or neither, judged by meaning rather than wording. Coded separately for the learning phase and for the whole run. Repeating a quiz option list without asserting an option does not count; answering a pasted question by asserting an option does.
User turn type	open request	Broad request ("explain X", "tell me everything about X").
	specific question	Asks about a particular detail or mechanism.
	challenge	Expresses doubt or disagreement, or asks the assistant to justify a claim ("are you sure?", "I don't think that's possible").
	quiz paste	Pastes or retypes a quiz question, often with its options.
	answer check	Offers the participant's own answer or summary and asks whether it is right, or asks to be graded.
	format request	Asks for a different format (shorter, bullets, simpler) without new content.
	meta / social	Thanks, greetings, off-topic turns, questions about the assistant itself.
Target fact	fact ID or none	The quizzed fact a user turn is mainly about.
Pushback event (per challenge)	claim: false / true / unclear; response: held / partial / conceded	Whether the doubted claim was the planted falsehood or the correct version, and whether the assistant held its claim, partly softened it or accepted the correction; with short verbatim quotations of both sides.
Assistant behaviour (per run)	0 absent, 1 slight, 2 clear, 3 strong	Validation or praise; obsequiousness; excitement; uncritical agreement; hedging; assertiveness. Adapted from the Social Sycophancy Scale (Rehani et al., 2026) and the validation dimension of ELEPHANT (Cheng et al., 2026b).
Assistant evaluates user	yes / no	Whether the assistant graded or confirmed the participant's own answers or summary.

Derived measures. Exposure codes were joined to the item-level quiz data to compute exposure-conditioned acceptance (the share of falsified items the assistant stated falsely whose planted option was chosen) and the comparison rates for items that were never mentioned. User-turn types yielded the turn-type distribution (Figure 23) and the pasting analysis (Figure 22); pushback events yielded Table 5; and assistant ratings yielded the model-side check (Figure 26), with the run-level sycophancy index defined as the sum of validation or praise, obsequiousness, excitement and uncritical agreement (range 0–12).