
RETRY, SWITCH, OR ABSTAIN? LEARNING STRATEGY-AWARE TOOL-USE POLICIES VIA CONTROLLED ERROR INJECTION

Chaoran Chen Vy Nguyen Ziji Zhang Abhinav Gullapalli Ziyi Wang
 Yuxuan Lu Dakuo Wang Jing Huang Zhou Yu Jin Lai
 Amazon

ABSTRACT

Tool-using LLM agents are commonly trained and evaluated in environments where tool calls succeed reliably, yet deployed tools can fail transiently, persistently, or silently. Robust recovery therefore requires more than repeated retries: an agent may need to retry the same path, switch to an alternative, or recognize that no viable path remains. We present BENCH2ROBUST, a framework that converts failure-free tool-use benchmarks into controlled stochastic environments with *scenario-controlled solvability*, where episodes explicitly require retrying, switching, or stopping after available paths are exhausted. We use BENCH2ROBUST to study two complementary interventions: structured runtime recovery context through Bayesian Tool Memory (BTM), and curriculum-controlled reinforcement learning. Across 7 models from 4 families and two multi-turn benchmark families, tool failures produce a near-universal robustness gap. On held-out Retail tasks, BTM improves robustness by up to 16.8 percentage points without retraining, while RL learns complementary recovery behavior that remains beneficial without inference-time BTM. Combining the two reaches 40.8–45.5% under injection while preserving failure-free performance. These results suggest that robust tool use benefits from combining environment-specific recovery knowledge with learned recovery behavior.

1 Introduction

Large language models (LLMs) augmented with tools can complete complex multi-turn tasks by retrieving information and acting through external systems [Schick et al., 2023, Qin et al., 2024, Patil et al., 2024]. Most tool-use benchmarks, however, assume that tool calls return timely, structurally valid, correct, and current responses [Yao et al., 2025, Li et al., 2023]. Production tools violate these assumptions: requests time out or hit rate limits, credentials and schemas become invalid, and apparently valid responses may contain stale, partial, or incorrect data. Robust agents must therefore do more than persist after failure. Depending on what remains recoverable, they may need to RETRY the same path, SWITCH to an alternative source, or ABSTAIN and escalate after viable paths are exhausted.

A central challenge is that conventional stochastic failure injection does not identify which recovery behavior an episode actually requires. If a transient error happens to disappear on the next call, a policy that retries indiscriminately may appear robust; conversely, an agent may receive low reward because a stochastic failure persists despite a reasonable recovery action. This makes it difficult to separate recovery-policy quality from environmental luck and, in particular, to test whether an agent distinguishes cases where retrying is sufficient from cases where switching is necessary.

We introduce BENCH2ROBUST, a benchmark-agnostic framework built around **scenario-controlled solvability**. In addition to stochastic tool-response corruption, each episode can be assigned a recoverability structure: in S1, no path is permanently blocked and retrying can recover; in S2, the primary path is blocked episode-wide and completion requires a fallback-equivalent tool; in S3, all available paths are blocked, defining the environment state in which escalation is appropriate. Unlike generic noise augmentation, this construction makes the required recovery regime explicit at the environment level. S3 is used as a training scenario in the current study, but because our task evaluators do not assign positive task-completion credit to impossible episodes, our held-out behavioral evidence focuses on retry and switch selection; we do not claim fully learned abstention.

We use BENCH2ROBUST to study two complementary interventions. *Bayesian Tool Memory* (BTM) supplies runtime recovery context: fallback maps, verification constraints, and Beta-posterior recoverability statistics from training rollouts. We also train a Qwen3-4B policy with a scenario-structured curriculum, DAPO, and partial-credit rewards, with an additional Qwen3-8B replication (Appendix B). BTM serves as an exploration prior during training and can be retained at inference; our ablations show that its inference-time gains come mainly from structural context rather than posterior calibration.

We benchmark robustness across τ^2 -bench [Barres et al., 2025], Retail-3I and Airline-3I [Wang et al., 2026a], and BFCL multi-turn [Patil et al., 2025]. Interventions are trained and evaluated on Combined Retail (1,339 tasks from τ^2 -bench retail and Retail-3I; 402 held-out); Airline-3I, Telecom, and BFCL are cross-benchmark evaluations. Our main findings are:

- **Tool failures expose a broad robustness gap.** Across 7 models, 4 families, and 10 task/domain slices, 69 of 70 model-subset pairs degrade under injection, by up to 46.7pp.
- **Structured recovery context gives large zero-training gains.** BTM improves the 4B base model by +16.8pp without alternatives and +11.7pp with alternatives on held-out Retail tasks; most of the gain comes from fallback maps and recovery constraints.
- **RL changes behavior beyond retry persistence.** Without inference-time BTM, the trained policy improves robustness by +6.3/+6.9pp over the base and succeeds more often on realized switch-required episodes, with less premature escalation.
- **Runtime knowledge and learned behavior are complementary.** RL+BTM reaches 40.8%/45.5% under injection while preserving clean performance; structured context helps most on explicit transient failures, while RL adds more on persistent and silent-error regimes.

2 The BENCH2ROBUST Framework

BENCH2ROBUST is a benchmark-agnostic injection framework that interposes between agent and tool execution. Any benchmark following the `tool_call(name, args) → response` pattern can be integrated via a thin adapter; we support τ^2 -bench [Barres et al., 2025] (with Retail-3I/Airline-3I [Wang et al., 2026a]) and BFCL [Patil et al., 2025]. We formalize the injected environment as a POMDP $\mathcal{M}_{\text{inj}} = (\mathcal{S}, \mathcal{A}, \mathcal{O}, T, Z_{\text{inj}}, R, \gamma)$ with the same latent state transition $T(s_{t+1} | s_t, a_t)$ and reward R as the clean benchmark, but a corrupted observation kernel

$$Z_{\text{inj}}(o_t | s_t, a_t) = \sum_{\nu \in \mathcal{N}} P(\nu) \mathbf{1}[o_t = C_\nu(o_t^*)], \quad o_t^* = Z_{\text{clean}}(s_t, a_t), \quad (1)$$

where C_{clean} is the identity map and other C_ν corrupt only the tool response observed by the agent. Each tool call to tool j independently samples a noise type $\nu_t \sim \text{Cat}(\theta_j)$ with $P(\text{clean}) = 0.60$; the remaining 0.40 is spread over 9 failure modes organized by observability: 6 *explicit-signal* failures (timeout, rate limit, server error, auth error, malformed, schema drift) and 3 *silent* corruptions (partial data, stale values, factual errors). Details in Appendix E; comparison with prior benchmarks in Appendix F. We deliberately scope to tool-response-level failures, excluding user-side noise [Wang et al., 2026b] and action-space perturbations [Zhou et al., 2026, Liu et al., 2026].

2.1 Scenario-Controlled Solvability

The central design choice is to assign each training episode an explicit *solvability class*. In **S1** (`retry_works`), no path is permanently blocked, so the environment remains recoverable through the original path. In **S2** (`switch_needed`), one side of a task-relevant fallback-equivalence class is blocked episode-wide, so task completion requires a fallback-equivalent tool; which side is blocked is randomized 50/50. In **S3** (`impossible`), all task-relevant viable tool paths are blocked, defining an environment in which continued tool use cannot complete the task and escalation is the appropriate prescribed behavior. Algorithm 1 summarizes the injection procedure. Scenario blocking is deterministic and episode-persistent and operates outside the stochastic injection budget ($B \leq 5$, $K_{\text{max}} = 2$ consecutive stochastic failures on the same tool). This separates persistent unavailability from an unlucky sequence of stochastic failures. In the current evaluation, S1 and S2 can be scored through task completion, whereas S3 is used only during training because the underlying benchmark evaluators do not assign positive completion credit to unsolvable tasks.

2.2 Alternative Tool Paths

For Retail we add 5 alternative tools (21 total), each providing a different query pattern to the same data (e.g., `search_product_by_name` as alternative to `get_product_details`). For BFCL evaluation, we identify natural equivalence classes within each domain and apply the same S1/S2/S3 blocking. Full specifications in Appendix D.

Algorithm 1 BENCH2ROBUST Scenario-Controlled Failure Injection

Require: Task τ , tool set $\mathcal{T}$, task-relevant fallback classes $\mathcal{E}_\tau$, viable tool paths $\mathcal{V}_\tau$, scenario $s \in \{S1, S2, S3\}$, per-tool noise distributions $\{\theta_j\}_{j \in \mathcal{T}}$, budget B , consecutive limit $K_{\max}$

```

1:  $\mathcal{P} \leftarrow \emptyset$ 
2: if  $s = S2$  then
3:   Select a task-relevant equivalence class  $E \in \mathcal{E}_\tau$ 
4:   Randomly choose one side  $j \in E$  and set  $\mathcal{P} \leftarrow \{j\}$ 
5: else if  $s = S3$  then
6:    $\mathcal{P} \leftarrow \mathcal{V}_\tau$ 
7: end if
8: for each tool call  $(j, a)$  in the episode do
9:    $o^* \leftarrow Z_{\text{clean}}(s_t, (j, a))$ 
10:  if  $j \in \mathcal{P}$  then
11:    Return episode-persistent blocked response
12:  else if stochastic injection budget remains and consecutive failures for  $j < K_{\max}$  then
13:    Sample  $\nu \sim \text{Cat}(\theta_j)$ 
14:    if  $\nu \neq \text{clean}$  then
15:      Return  $C_\nu(o^*)$  and update stochastic injection counters
16:    end if
17:  end if
18:  Return clean response  $o^*$ 
19: end for
    
```

3 Strategy-Aware Training

3.1 Bayesian Tool Memory (BTM)

Random rollouts from a base model rarely contain enough successful recovery behavior to provide useful RL signal. We therefore supply BTM as structured recovery context during training and optionally at inference. BTM combines (1) Beta-posterior recoverability statistics estimated from training-split rollouts, (2) domain-specific fallback maps with granularity annotations, and (3) heuristic constraints such as retrying before abandoning a path, verifying information before irreversible actions, and escalating only after available recovery paths have been considered.

What is Bayesian in BTM? The Bayesian component is the estimation and accumulation of empirical recoverability statistics, not the fallback structure itself. Candidate fallback relations and domain constraints are provided by the environment configuration; Beta posteriors summarize how often episodes recover after particular tool/error observations and source-to-target transitions. Section 5.3 shows that calibrated posterior values do not explain most of BTM’s inference-time gain: fallback maps and constraints account for the majority of the improvement, while true versus shuffled posterior values differ by at most seed-level variation in our tests. We therefore use “Bayesian Tool Memory” to denote the full structured context and treat posterior values primarily as empirical recovery summaries and as part of the exploration context used during RL, rather than claiming that Bayesian calibration itself drives the main result.

For each (tool j , error type e) pair, recovery probability is modeled as $p_{j,e}^{\text{rec}} \sim \text{Beta}(\alpha_{j,e}, \beta_{j,e})$ with posterior mean $\hat{P} = \alpha / (\alpha + \beta)$, computed for the Retail intervention from base-model rollouts on the Retail training split (937 tasks, 3–5 seeds; held-out never used). This is an *episode-level recoverability* estimate: “when tool j hits error e , how often does the episode still succeed?” Switch beliefs $\hat{P}(\text{switch} \mid j \rightarrow k)$ are defined analogously for (source, target) pairs; these are observed recovery rates after $j \rightarrow k$ transitions (not causal switch-success probabilities) and carry higher uncertainty ($n = 6$ –20) due to sparser data and selection bias. The prompt presents these as structured data alongside the fallback map and constraints; the model must learn its own decision boundary. Full template in Appendix N.

During Retail RL training, BTM serves as structured exploration context that makes retry, switching, verification, and escalation behaviors more likely to appear in rollouts, creating trajectories on which the optimizer can assign credit. At inference, the same context provides domain-specific recovery information. For cross-benchmark transfer, the RL checkpoint remains Retail-trained; target-domain BTM is constructed only as inference-time context from the target tool configuration and belief rollouts.

3.2 Reward Design

$$R(\tau) = \begin{cases} 1.0 \cdot \text{eff}(\tau) \cdot \text{rep}(\tau) & \text{if task completed} \\ 0.3 \cdot \frac{\text{matched actions}}{\text{total required}} \cdot \text{rep}(\tau) & \text{otherwise} \end{cases} \quad (2)$$

where $\text{eff}(\tau) = \max(0.3, 1.0 - 0.02 \cdot \max(0, |\tau| - 12))$ penalizes long episodes and $\text{rep}(\tau) \in \{0, 0.5, 1.0\}$ penalizes repetition (≥ 4 identical calls $\rightarrow 0$). The partial-credit term provides dense signal: without it, 38% of training tasks have zero reward variance. Importantly, the reward contains no positive term for correct abstention: S3 episodes cannot pass the benchmark task evaluator. Premature escalation on solvable S1/S2 episodes forfeits completion reward, while the positive prescription to stop after exhausting paths comes from the recovery constraints and exposure to S3 during the curriculum. Accordingly, we treat S3 as a controlled training condition rather than evidence that abstention is independently reward-learned (Appendix L).

3.3 Curriculum and DAPO Training

Five phases progressively introduce harder scenarios: Phase 1 trains RETRY (100% S1, max 2 injections); Phases 2–3 introduce SWITCH (20%→40% S2); Phase 4 adds ABSTAIN (10% S3); Phase 5 trains the full repertoire (30/45/25). Auto-advancement requires mastery (e.g., Phase 4 demands S3 transfer $> 50\%$, avg turns < 15 , and no S1/S2 regression). In the 4B training run, the curriculum-phase abstain rate increases from 23.7% (early phases, before S3 exposure) to 33.3% (late phases with S3 present), with average turns stabilizing at 10.7. This change is consistent with greater use of escalation after S3 is introduced, but we treat it only as a curriculum diagnostic given the incomplete abstention signal in the reward (Section 3.2). Full schedule in Appendix G.

We use DAPO [Yu et al., 2025] with a KL constraint (coefficient 0.02) to prevent policy collapse—without KL, training collapses within 25–30 iterations as repetition rate exceeds 80%. Additional components: asymmetric clipping ($\epsilon_{\text{low}} = 0.20$, $\epsilon_{\text{high}} = 0.28$), dynamic group filtering ($\sigma < 0.01$ masked), and group-relative advantages over $G = 16$ rollouts per prompt (8 clean + 8 injected, unified normalization).

4 Experimental Setup

Training and evaluation environments. Interventions are trained and evaluated on **Combined Retail**: 1,339 multi-turn customer-service tasks composed of τ^2 -bench retail (114 tasks) [Barres et al., 2025] and Retail-3I (1,225 tasks covering general/ambiguous/changing intents) [Wang et al., 2026a], split into 937 training and 402 held-out tasks. The broader robustness-gap evaluation covers τ^2 -bench retail/airline/telecom, Retail-3I, Airline-3I, and BFCL multi-turn [Patil et al., 2025]. Cross-benchmark intervention evaluations use Airline-3I (584 tasks), τ^2 -bench Telecom (114 tasks), and BFCL multi-turn (200 tasks); target-domain BTM, when enabled, is inference-time context and does not update the Retail-trained RL policy.

Evaluation Modes. (1) **Failure-free (clean)**: uncertainty injection is disabled; tool calls return the benchmark environment’s original responses without artificial delay, failure, or corruption—i.e., timely, structurally valid, correct, and current with respect to the underlying simulator state. (2) **Inject w/o alt**: uncertainty injection enabled with the standard tool set. (3) **Inject w/ alt**: injection enabled with augmented tool set and scenario-based blocking.

Models. Qwen3-4B-Thinking-2507 is the primary training target, trained on Combined Retail and evaluated both within-benchmark (Section 5.2) and on the cross-benchmark targets described in the previous paragraph. We additionally train Qwen3-8B on Combined Retail as a scale replication of the within-benchmark intervention (Appendix B). Qwen3-8B, Qwen3-32B, Qwen3-235B, DeepSeek-V3 [DeepSeek-AI et al., 2025], GLM-4.7 [Team et al., 2025], and MiniMax-M2.5 [Chen et al., 2026a] serve as reference models for the robustness gap evaluation, spanning 4 model families and scales from 4B to 235B parameters. We use Qwen3-235B as the user simulator across all evaluations; prior work on τ^2 -bench reports low variance across simulator reruns, though we have not evaluated sensitivity to simulator choice. Scale comparisons within Qwen use the same-variant Qwen3-32B/235B rows; the 4B target is a *thinking* variant and is therefore not directly comparable to non-thinking Qwen3 models as a scale sweep.

Metrics. The primary metric is pass rate (binary task completion). Table 2 additionally reports S1 retry success, S2 switch success, and premature escalation: transfer to a human while a viable recovery path remains unused. We reserve *abstain* for S3 episodes in which no viable path remains; S3 is used during training but not included in held-out task-success evaluation because the benchmark evaluators cannot assign positive completion credit to unsolvable tasks.

5 Results

We organize the results below around four findings. First, tool-response failures create a broad robustness gap across models and task suites (Section 5.1). Second, on held-out Retail tasks, structured runtime recovery context gives the largest zero-training gain, while RL adds a smaller but complementary gain that persists without inference-time BTM (Section 5.2). Third, BTM’s inference-time benefit comes mainly from fallback structure and constraints rather than calibrated posterior values (Section 5.3). Fourth, runtime context and RL help different error regimes: BTM is strongest on explicit transient failures, whereas RL adds more on persistent and silent-error settings (Section 5.4).

5.1 The Robustness Gap Is Universal

We evaluate 7 models from 4 families on 10 task/domain slices under injection (full results in Appendix Table 5). Of 70 (model, subset) pairs, 69 degrade (-1.8 to -46.7 pp). The gap appears across customer service, airline booking, and function-calling domains. Larger models sometimes lose fewer absolute points, but scaling does not eliminate brittleness: Qwen3-235B still loses 15.8pp on τ^2 -retail, while models with 89–91% clean Telecom performance (GLM-4.7, MiniMax-M2.5) lose 20–21pp. BFCL also shows large drops (-11.5 to -39 pp). Because task structure and model variants differ across rows, we interpret these results as evidence of broad failure sensitivity rather than as a controlled scaling law.

5.2 Within-Benchmark Effectiveness

We next evaluate how much robustness comes from structured runtime recovery context and how much additional benefit is associated with RL training. Table 1 reports held-out results (402 tasks not seen during RL training or belief computation; mean $\pm$ std over 5 injection seeds). RL models are trained with BTM as an exploration prior; we evaluate both with and without BTM at inference time to measure internalization.

Model	Train BTM	Infer BTM	Clean	Inj w/o Alt	Inj w/ Alt
<i>Qwen3-4B-Thinking-2507 — Combined Retail (402 held-out tasks, 5 seeds)</i>					
4B	✗	✗	64.3 $\pm$ 0.9	20.1 $\pm$ 1.4	31.9 $\pm$ 2.3
4B	✗	✓	65.3 $\pm$ 0.9	36.9 $\pm$ 1.2	43.6 $\pm$ 1.6
4B + RL	✓	✗	64.5 $\pm$ 0.8	26.4 $\pm$ 1.2	38.8 $\pm$ 2.2
4B + RL	✓	✓	63.9 $\pm$ 1.3	40.8$\pm$1.6	45.5$\pm$3.0

Table 1: Within-benchmark effectiveness on 402 held-out tasks. Results are mean $\pm$ std over 5 injection seeds. Train BTM indicates recovery beliefs used as an RL exploration prior; Infer BTM indicates recovery context supplied at inference.

Structured recovery context provides the largest zero-training gain. BTM improves robustness without retraining: 20.1% $\rightarrow$ 36.9% (+16.8pp w/o alt) and 31.9% $\rightarrow$ 43.6% (+11.7pp w/ alt) on held-out tasks. Section 5.3 shows that most of this gain should be attributed to fallback structure and recovery constraints rather than to calibrated posterior values. Thus the result demonstrates the value of making recovery-relevant environment structure explicit at inference time.

RL retains recovery gains without inference-time BTM. The RL-trained policy reaches 26.4%/38.8% when BTM is removed at inference, compared with 20.1%/31.9% for the base model (+6.3/+6.9pp). This is consistent with training changing recovery behavior rather than merely making the model dependent on the inference prompt, though we cannot rule out that the RL policy has partially internalized BTM-specific phrasing or heuristics encountered during training. At the same time, Base+BTM (36.9%/43.6%) remains stronger than RL without BTM, showing that explicit environment-specific recovery information accounts for a larger share of the aggregate improvement. Combining the two yields the highest mean performance, 40.8%/45.5%. We therefore view RL and BTM as complementary in function: the trained policy retains reusable recovery behavior, while runtime context supplies tool-specific fallback and verification information that is difficult to infer from the task alone. Appendix B reports the same four-way comparison on Qwen3-8B, where the combined system again attains the highest pass rate under both injection conditions.

Full system preserves failure-free performance. RL+BTM clean performance (63.9 $\pm$ 1.3%) is within 0.4pp of the base model (64.3 $\pm$ 0.9%), showing no measurable clean-task degradation at the resolution of this evaluation.

Strategy-level evidence beyond retry persistence. Table 1 shows aggregate pass rates. To examine whether gains are consistent with strategy *selection* rather than mere persistence, we decompose held-out episodes by realized scenario

class. Under inject w/ alt, the injection engine permanently blocks one side of each tool equivalence pair for a fraction of episodes (S2: switch required) while leaving others stochastically noisy (S1: retry suffices). We classify each held-out episode post-hoc: S2 if any uncertainty event shows a permanently blocked tool, S1 otherwise (episodes with no injection are excluded). Table 2 reports per-scenario success rates and premature escalation (transferring to a human when the task *is* solvable).

Model	Task Success (%)		Premature Escalation (%) ↓		
	S1 Retry	S2 Switch	S1	S2	Total Esc.
Base + BTM	50.0 ⁽¹²⁶⁾	16.8 ⁽¹⁷⁹⁾	21.4	74.3	52.5
RL (✓, ✗)	53.3 ⁽¹⁵²⁾	35.3 ⁽¹⁶⁷⁾	24.3	57.5	41.7
RL + BTM	53.5 ⁽¹⁴²⁾	29.7 ⁽¹⁷²⁾	20.4	65.1	44.9

Table 2: Strategy-level metrics on 402 held-out tasks with alternatives. S1 denotes stochastic failures where retry can suffice; S2 denotes a permanently blocked primary path requiring a switch. Counts in parentheses are policy-dependent because scenario class is assigned from each realized trajectory after excluding no-injection episodes.

Although RL+BTM attains the highest aggregate pass rate in Table 1, the strategy decomposition is not uniformly monotonic: removing inference-time BTM yields the strongest realized S2 switch success and lowest total premature escalation, while RL+BTM is strongest on S1 retry success. We therefore interpret Table 2 as evidence that RL changes recovery behavior, rather than as a claim that BTM improves every strategy-level metric.

RL’s realized S2 success increases from 16.8% to 35.3% relative to Base+BTM, while premature escalation decreases from 52.5% to 41.7%. Purely increasing retry persistence would not be expected to help once a path is permanently blocked, so the simultaneous S2 improvement and reduction in premature escalation are consistent with recovery behavior beyond retry frequency. Because each policy determines its own S1/S2 split through its own trajectories, this comparison is suggestive of improved strategy selection but cannot isolate a causal effect independent of that split.

Cross-benchmark transfer. The Retail-trained RL model transfers to unseen domains without retraining (full results in Appendix Table 7). RL alone (without target-domain BTM) already contributes +2.7pp on Airline (33.4%) and +1.5pp on BFCL (15.0%); combining it with target-domain BTM reaches +9.0pp and +5.0pp respectively, again showing that target-domain runtime context adds to the smaller cross-domain gains retained by the trained policy. On Telecom, where the 4B model’s clean pass rate is only 21% (Appendix L), gains are within noise.

5.3 BTM Decomposition: Structure vs. Values

Variant	Static	Dynamic	Fixed		Online Update	
			Pass	Tokens	Pass	Tokens
Base (no belief)	✗	✗	23.2	64K	–	–
Dynamic only	✗	✓	24.9	–	–	–
Static only (Uniform)	✓	✗	33.7	77K	40.8	97K
Full BTM, Shuffled	✓	✓	38.3	86K	40.0	105K
Full BTM, True	✓	✓	37.8	89K	41.6	95K

Table 3: BTM decomposition on the full 1,339-task Retail set (inject w/o alt). Static = constraints + fallback maps; Dynamic = Beta-posterior beliefs; Shuffled preserves format while permuting probabilities.

To isolate what makes BTM effective, we compare components under identical prompt format (Table 3). The gain is overwhelmingly structural: “Static only” (constraints + fallback maps with uniform $P = 0.50$) recovers +10.5pp of the full +14.6pp; calibrated beliefs without structure add only +1.7pp. Under fixed beliefs, Shuffled values (38.3%) nominally exceed True (37.8%), and under online updating the margin is ≤ 1.6 pp—at or below seed variance. We therefore interpret BTM’s inference-time benefit as coming primarily from structural scaffolding, with posterior values serving as compact recoverability summaries and training context rather than an isolated source of gain.

5.4 BTM and RL Address Different Failure Regimes

Do structured recovery context and RL show the same pattern across failure regimes? Table 4 suggests different relative strengths.

Error Type	Pass Rate (%)			Δ	
	Base	+BTM	+RL	BTM	RL
<i>Observable errors</i>					
timeout	12.4	32.5	38.1	+20.0	+5.6
rate_limit	15.2	33.1	40.5	+18.0	+7.3
server_error	6.2	31.2	34.8	+25.0	+3.6
malformed_response	11.5	36.8	37.8	+25.3	+1.0
auth_error	13.5	25.9	36.1	+12.4	+10.2
schema_drift	14.9	27.5	40.0	+12.6	+12.5
<i>Silent errors</i>					
partial	20.6	29.1	33.6	+8.5	+4.5
stale	28.9	31.6	37.0	+2.7	+5.4
factual_error	33.8	29.2	39.8	−4.6	+10.5

Table 4: Pass rate by error type under injection without alternatives. “+RL” denotes the full RL+BTM system. Deltas are incremental: BTM is (+BTM) − Base and RL is (+RL) − (+BTM); bold marks each column’s maximum.

Structured context helps most on explicit transient errors. For timeout, rate_limit, server_error, and malformed responses, adding BTM improves pass rate by +18.0 to +25.3pp. These errors expose an explicit signal and are typically recoverable through the original path, making the supplied fallback structure and retry guidance directly actionable. The present analysis measures task success rather than which BTM component the model consulted, so we interpret this as an error-regime association rather than a direct mechanism measurement.

RL contributes larger marginal gains on persistent observable errors. On the two persistent observable errors—auth_error and schema_drift—the observable-group asymmetry reverses: BTM’s increment drops from +18–25pp to +12.4/+12.6pp, while RL’s marginal increment rises to +10.2/+12.5pp, the largest RL contributions among observable errors. Here the error signal is visible but repeated use of the blocked path is ineffective, so successful recovery often requires an alternative path. This pattern is consistent with the strategy-level analysis in which training is associated with higher realized S2 success.

RL adds further gains on silent errors. For factual_error (+10.5pp), stale (+5.4pp), and partial (+4.5pp), there is no error signal at all—the response appears valid but contains corrupted or missing decision-critical fields. BTM *hurts* on factual_error (−4.6pp), the only negative entry in the table. One plausible mechanism is that BTM raises the model’s overall propensity to retry. Retrying cannot help against silent corruption, since a refetched value is corrupted again, so the extra turns consume the efficiency discount without recovering useful information. We did not isolate this mechanism experimentally, and an alternative explanation—for example, BTM shifting attention away from verification behaviors—cannot be ruled out. The additional RL gains are consistent with behaviors beyond simple response-to-error heuristics, such as verification or cross-referencing, but we do not directly measure those intermediate behaviors here. Accordingly, the error-type decomposition supports a functional distinction between runtime recovery context and learned behavior without establishing a specific internal mechanism.

Silent-error pass rates should be read as task-completion scores, not as direct corruption-adoption rates: an episode can pass if the final actions are correct despite an earlier perturbed value. This explains the relatively high silent-error baselines and motivates future measurement of whether corrupted values are actually used.

6 Discussion

Controlled solvability as a recovery-training formulation. Scenario control makes recoverability explicit: S1, S2, and S3 separate cases where retrying can work, switching is required, or no tool path remains. This avoids treating persistence and lucky stochastic recovery as the same behavior. Our complete scenario-structured recipe substantially outperforms a vanilla-GRPO random-noise baseline (45.9% vs. 23.0%; Table 16), although that comparison varies curriculum, stabilization, and reward shaping together.

Recovery combines runtime knowledge and learned behavior. Structured recovery context provides the largest zero-training gain, showing that agents benefit from explicit fallback paths and verification constraints. RL without inference-time BTM still improves over the base model, especially on switch-required and silent-error regimes, but

it does not replace tool-specific context. This suggests a division of labor: runtime context supplies environment knowledge, while training makes retry/switch behavior more reusable across episodes and, to a smaller extent, across domains.

Implications and boundaries. BTM should be read primarily as structured recovery context rather than evidence that calibrated Bayesian probabilities are necessary: fallback maps and constraints explain most of its inference-time benefit. The evidence is also strongest for retry and switch, given the reward design’s incomplete abstention signal (Section 3.2). For deployment, the main implication is practical rather than architectural: tool-failure robustness should be evaluated separately from clean task success, and jointly with efficiency, because recovery improves pass rate while increasing token use.

7 Related Work

Tool-Using LLM Agents and Agentic RL. Augmenting LLMs with external tools has been explored via self-supervised API training [Schick et al., 2023], retrieval-augmented generation [Patil et al., 2024], large-scale benchmarks [Qin et al., 2024, Li et al., 2023], and multi-turn task completion [Yao et al., 2025]—all evaluated under clean conditions that leave tool-failure robustness unexamined. On the optimization side, GRPO [Shao et al., 2024] removes the critic via group-relative advantages, and DAPO [Yu et al., 2025] adds asymmetric clipping and dynamic filtering. We build on DAPO, adding KL stabilization for multi-turn settings and a scenario-controlled curriculum.

Robustness Benchmarks for Tool-Using Agents. A growing body of work evaluates—but does not train for—tool-use robustness, injecting perturbations such as tool blocking [Liu et al., 2026], single-turn selection perturbations [Zhou et al., 2026], general noise categories [Wang et al., 2026b], production-like stress [Gupta, 2026], dynamic replanning and anomaly recovery [Zhu et al., 2026], and real-world API imperfection [Kim et al., 2026]. Closest to our injection design, ToolBench-X [Tian et al., 2026] categorizes unreliability into five lifecycle-stage hazards and evaluates recovery under each. We differ in two ways: (1) our taxonomy is organized by *observability*—whether the failure provides an explicit signal to the agent—rather than lifecycle stage; and (2) we add scenario-controlled solvability (S1/S2/S3), which explicitly varies whether the original path remains viable, an alternative path is required, or no path remains. This makes the framework usable as a recovery-training environment in addition to an evaluation stress test. This connects to domain randomization in robotics [Tobin et al., 2017]; our scenario control differs from uniform randomization by constructing episodes with known recoverability structure. Appendix F compares the specific error types covered by these benchmarks; within this taxonomy, BENCH2ROBUST spans all nine explicit-signal and silent-corruption types used in our experiments.

Training for Tool-Use Robustness. NoisyAgent [Chen et al., 2026b] is the closest concurrent work, injecting noise into RL rollouts with curriculum scheduling. Its training environment does not explicitly control whether recovery requires staying on the original path, switching to an alternative tool, or confronting an episode with no viable path. BENCH2ROBUST adds this recoverability structure and explicit alternative paths, allowing these regimes to be analyzed separately. Our abstention signal is also incomplete on the reward side (Section 3.2); the current contribution is to construct episodes with no viable tool path, not to demonstrate fully learned abstention. PALADIN [Vuddanti et al., 2026] trains on failure-injected, recovery-annotated trajectories with exemplar retrieval, but does not control scenario solvability to distinguish retry/switch/abstain. ToolCritic [Hamad et al., 2025] corrects errors via a separate critic rather than training the policy end-to-end. We instead design the environment so that different episodes require different recovery regimes and train a single policy across them.

Recovery, Abstention, and Posterior-Based Memory. At inference time, ReAct [Yao et al., 2023] and Reflexion [Shinn et al., 2023] add retry/reflection, though LLMs cannot reliably self-correct without external feedback [Huang et al., 2024]. Abstention has been studied at the knowledge level (R-Tuning [Zhang et al., 2024]) and the user-intent level (Learning to Ask [Wang et al., 2025]); we formulate an analogous stopping condition at the *tool-response* level by constructing episodes in which tool paths are exhausted, subject to the reward-design limitation discussed in Section 3.2. Bayesian-Agent [Wu et al., 2026] maintains a posterior over reusable prompt-side skills for a frozen model between episodes; our Bayesian Tool Memory instead supplies per-tool×error posteriors as runtime decision data and as RL exploration context within episodes—the two are complementary. Finally, risk-oriented testing shows agents may fail to act on their own risk knowledge [Ruan et al., 2024, Tang et al., 2025]; our framework studies whether recovery behavior can be improved through a combination of structured runtime context and policy training.

8 Conclusion

We presented BENCH2ROBUST, a framework for studying tool-failure robustness as a recovery-policy problem rather than persistence alone. Scenario-controlled solvability separates retry-, switch-, and abstain-required regimes, exposing a broad robustness gap across seven models. On held-out Retail tasks, structured recovery context gives the largest immediate gain (+11.7 to +16.8pp), RL retains additional robustness without inference-time context (+6.3/+6.9pp), and their combination reaches 40.8–45.5% under injection without measurable clean-task degradation. Overall, robust tool use appears to benefit from combining environment-specific recovery knowledge supplied at runtime with recovery behavior acquired through training.

Limitations. The main limitations are that our intervention comparison evaluates complete recipes rather than isolated components, the reward signal for correct abstention remains incomplete (Section 3.2), and the failures are simulated stressors rather than real incident traces. Additional caveats on efficiency, transfer, and abstention appear in Appendix L.

Reproducibility Statement

All experiments use publicly available benchmarks (τ^2 -bench, Retail-3I, Airline-3I, and BFCL) and open-weight base models (Qwen3-4B-Thinking-2507 and Qwen3-8B for the additional scale replication). Appendix G lists the complete Retail training configuration, including optimizer settings, batch composition, reward terms, curriculum schedule, and hardware. Appendix H specifies the exact per-tool noise distribution, per-episode injection budget, and consecutive-failure limits needed to reproduce the injection environment. Appendix E defines all nine noise types, Appendix D enumerates the alternative tools added to each environment, and Appendix N gives the verbatim BTM system-prompt template. We will release the injection framework, domain registry, belief-computation scripts, and evaluation harness.

Ethics Statement

This work studies failure recovery in tool-using agents and uses only simulated tool failures in sandboxed benchmark environments; no real APIs are called and no user data is involved. We see a primarily beneficial safety application: agents that can recover from tool failures, and that are designed to avoid fabricating completion once recovery paths are exhausted, could reduce unwarranted actions in downstream deployments. Because our current reward does not positively reinforce correct stopping (Section 3.2), this remains a design goal for the framework rather than a demonstrated property of the trained policy reported here. Two risks merit note. First, training for persistence could in principle encourage excessive retrying against real services; our efficiency discount and repetition penalty are intended to bound this, but deployment should still respect rate limits. Second, an escalation threshold that is appropriate in one domain may transfer poorly to another. This risk is heightened because the current stopping prescription is supplied by the prompt rather than positively learned from an abstention reward (Section 3.2). Our Telecom results illustrate the broader transfer limitation: recovery training does not remedy a capability ceiling, and such systems should not be presumed robust outside their evaluated domains.

References

- Timo Schick, Jane Dwivedi-Yu, Roberto Dessi, Roberta Raileanu, Maria Lomeli, Eric Hambro, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. Toolformer: Language models can teach themselves to use tools. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL <https://openreview.net/forum?id=Yacmpz84TH>.
- Yujia Qin, Shihao Liang, Yining Ye, Kunlun Zhu, Lan Yan, Yaxi Lu, Yankai Lin, Xin Cong, Xiangru Tang, Bill Qian, Sihan Zhao, Lauren Hong, Runchu Tian, Ruobing Xie, Jie Zhou, Mark Gerstein, dahai li, Zhiyuan Liu, and Maosong Sun. ToolLLM: Facilitating large language models to master 16000+ real-world APIs. In *The Twelfth International Conference on Learning Representations*, 2024. URL <https://openreview.net/forum?id=dHng200Jjr>.
- Shishir G Patil, Tianjun Zhang, Xin Wang, and Joseph E. Gonzalez. Gorilla: Large language model connected with massive APIs. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024. URL <https://openreview.net/forum?id=tBRNC6YemY>.
- Shunyu Yao, Noah Shinn, Pedram Razavi, and Karthik R Narasimhan. τ -bench: A benchmark for tool-agent-user interaction in real-world domains. In *The Thirteenth International Conference on Learning Representations*, 2025. URL <https://openreview.net/forum?id=roNSXZpUDN>.

- Minghao Li, Yingxiu Zhao, Bowen Yu, Feifan Song, Hangyu Li, Haiyang Yu, Zhoujun Li, Fei Huang, and Yongbin Li. API-bank: A comprehensive benchmark for tool-augmented LLMs. In *The 2023 Conference on Empirical Methods in Natural Language Processing*, 2023. URL <https://openreview.net/forum?id=o2HBfgY20b>.
- Victor Barres, Honghua Dong, Soham Ray, Xujie Si, and Karthik Narasimhan. τ^2 -bench: Evaluating conversational agents in a dual-control environment, 2025. URL <https://arxiv.org/abs/2506.07982>.
- Ziyi Wang, Yuxuan Lu, Yimeng Zhang, Pei Chen, Ziwei Dong, Jing Huang, Jiri Gesi, Xianfeng Tang, Chen Luo, Qun Liu, Yisi Sang, Hanqing Lu, Manling Li, Jin Lai, and Dakuo Wang. Trajectory2Task: Training robust tool-calling agents with synthesized yet verifiable data for complex user intents. In Maria Liakata, Viviane P. Moreira, Jiajun Zhang, and David Jurgens, editors, *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 44021–44044, San Diego, California, United States, July 2026a. Association for Computational Linguistics. ISBN 979-8-89176-390-6. doi:10.18653/v1/2026.acl-long.2037. URL <https://aclanthology.org/2026.acl-long.2037/>.
- Shishir G Patil, Huanzhi Mao, Fanjia Yan, Charlie Cheng-Jie Ji, Vishnu Suresh, Ion Stoica, and Joseph E. Gonzalez. The berkeley function calling leaderboard (BFCL): From tool use to agentic evaluation of large language models. In *Forty-second International Conference on Machine Learning*, 2025. URL <https://openreview.net/forum?id=2GmDdhBdDk>.
- Ruipeng Wang, Yuxin Chen, Yukai Wang, Chang Wu, Junfeng Fang, Xiaodong Cai, Qi GU, Hui Su, An Zhang, Xiang Wang, Xunliang Cai, and Tat-Seng Chua. Agentnoisebench: Benchmarking robustness of tool-using LLM agents under noisy condition. In *Forty-third International Conference on Machine Learning*, 2026b. URL <https://openreview.net/forum?id=ORVJCJczoG>.
- Xiaolin Zhou, Aojie Yuan, Zheng Luo, Zipeng Ling, Xixiao Pan, Yicheng Gao, Haiyue Zhang, Jiate Li, Shuli Jiang, Prince Zizhuang Wang, Zixuan Zhu, Jinbo Liu, Ryan A. Rossi, Hua Wei, and Xiyang Hu. When simulation lies: A sim-to-real benchmark and domain-randomized RL recipe for tool-use agents. In *Workshop on Failure Modes of Agentic AI at ICML 2026*, 2026. URL <https://openreview.net/forum?id=9hC5wTcZ4u>.
- Jiayu Liu, Qihan Lin, Cheng Qian, Rui Wang, Emre Can Acikgoz, Xiaocheng Yang, Jiateng Liu, Zhenhailong Wang, Xiushi Chen, Heng Ji, and Dilek Hakkani-Tür. Planbench-xl: Evaluating long-horizon planning of llm tool-use agents in large-scale tool ecosystems, 2026. URL <https://arxiv.org/abs/2606.22388>.
- Qiyang Yu, Zheng Zhang, Ruofei Zhu, Yufeng Yuan, Xiaochen Zuo, YuYue, Weinan Dai, Tiantian Fan, Gaohong Liu, Juncai Liu, LingJun Liu, Xin Liu, Haibin Lin, Zhiqi Lin, Bole Ma, Guangming Sheng, Yuxuan Tong, Chi Zhang, Mofan Zhang, Ru Zhang, Wang Zhang, Hang Zhu, Jinhua Zhu, Jiaze Chen, Jiangjie Chen, Chengyi Wang, Hongli Yu, Yuxuan Song, Xiangpeng Wei, Hao Zhou, Jingjing Liu, Wei-Ying Ma, Ya-Qin Zhang, Lin Yan, Yonghui Wu, and Mingxuan Wang. DAPO: An open-source LLM reinforcement learning system at scale. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025. URL <https://openreview.net/forum?id=2a36EMSSTp>.
- DeepSeek-AI, Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang, Bochao Wu, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chenyu Zhang, Chong Ruan, Damai Dai, Daya Guo, Dejian Yang, Deli Chen, Dongjie Ji, Erhang Li, Fangyun Lin, Fucong Dai, Fuli Luo, Guangbo Hao, Guanting Chen, Guowei Li, H. Zhang, Han Bao, Hanwei Xu, Haocheng Wang, Haowei Zhang, Honghui Ding, Huajian Xin, Huazuo Gao, Hui Li, Hui Qu, J. L. Cai, Jian Liang, Jianzhong Guo, Jiaqi Ni, Jiashi Li, Jiawei Wang, Jin Chen, Jingchang Chen, Jingyang Yuan, Junjie Qiu, Junlong Li, Junxiao Song, Kai Dong, Kai Hu, Kaige Gao, Kang Guan, Kexin Huang, Kuai Yu, Lean Wang, Lecong Zhang, Lei Xu, Leyi Xia, Liang Zhao, Litong Wang, Liyue Zhang, Meng Li, Miaojun Wang, Mingchuan Zhang, Minghua Zhang, Minghui Tang, Mingming Li, Ning Tian, Panpan Huang, Peiyi Wang, Peng Zhang, Qiancheng Wang, Qihao Zhu, Qinyu Chen, Qiushi Du, R. J. Chen, R. L. Jin, Ruiqi Ge, Ruisong Zhang, Ruizhe Pan, Runji Wang, Runxin Xu, Ruoyu Zhang, Ruyi Chen, S. S. Li, Shanghao Lu, Shangyan Zhou, Shanhuang Chen, Shaoqing Wu, Shengfeng Ye, Shengfeng Ye, Shirong Ma, Shiyu Wang, Shuang Zhou, Shuiping Yu, Shunfeng Zhou, Shutong Pan, T. Wang, Tao Yun, Tian Pei, Tianyu Sun, W. L. Xiao, Wangding Zeng, Wanbiao Zhao, Wei An, Wen Liu, Wenfeng Liang, Wenjun Gao, Wenqin Yu, Wentao Zhang, X. Q. Li, Xiangyue Jin, Xianzu Wang, Xiao Bi, Xiaodong Liu, Xiaohan Wang, Xiaojin Shen, Xiaokang Chen, Xiaokang Zhang, Xiaosha Chen, Xiaotao Nie, Xiaowen Sun, Xiaoxiang Wang, Xin Cheng, Xin Liu, Xin Xie, Xingchao Liu, Xingkai Yu, Xinnan Song, Xinxia Shan, Xinyi Zhou, Xinyu Yang, Xinyuan Li, Xuecheng Su, Xuhen Lin, Y. K. Li, Y. Q. Wang, Y. X. Wei, Y. X. Zhu, Yang Zhang, Yanhong Xu, Yanhong Xu, Yanping Huang, Yao Li, Yao Zhao, Yaofeng Sun, Yaohui Li, Yaohui Wang, Yi Yu, Yi Zheng, Yichao Zhang, Yifan Shi, Yiliang Xiong, Ying He, Ying Tang, Yishi Piao, Yisong Wang, Yixuan Tan, Yiyang Ma, Yiyuan Liu, Yongqiang Guo, Yu Wu, Yuan Ou, Yuchen Zhu, Yudian Wang, Yue Gong, Yuheng Zou, Yujia He, Yukun Zha, Yunfan Xiong, Yunxian Ma, Yuting Yan, Yuxiang Luo, Yuxiang You, Yuxuan Liu, Yuyang Zhou, Z. F. Wu, Z. Z. Ren, Zehui Ren, Zhangli Sha, Zhe Fu, Zhen Xu, Zhen Huang, Zhen Zhang, Zhenda Xie, Zhengyan Zhang, Zhewen Hao, Zhibin Gou, Zhicheng Ma, Zhigang Yan, Zhihong Shao, Zhipeng Xu, Zhiyu Wu, Zhongyu Zhang, Zhuoshu Li, Zihui Gu, Zijia

- Zhu, Zijun Liu, Zilin Li, Ziwei Xie, Ziyang Song, Ziyi Gao, and Zizheng Pan. Deepseek-v3 technical report, 2025. URL <https://arxiv.org/abs/2412.19437>.
- GLM Team, Aohan Zeng, Xin Lv, Qinkai Zheng, Zhenyu Hou, Bin Chen, Chengxing Xie, Cunxiang Wang, Da Yin, Hao Zeng, Jiajie Zhang, Kedong Wang, Lucen Zhong, Mingdao Liu, Rui Lu, Shulin Cao, Xiaohan Zhang, Xuancheng Huang, Yao Wei, Yean Cheng, Yifan An, Yilin Niu, Yuanhao Wen, Yushi Bai, Zhengxiao Du, Zihan Wang, Zilin Zhu, Bohan Zhang, Bosi Wen, Bowen Wu, Bowen Xu, Can Huang, Casey Zhao, Changpeng Cai, Chao Yu, Chen Li, Chendi Ge, Chenghua Huang, Chenhui Zhang, Chenxi Xu, Chenzheng Zhu, Chuang Li, Congfeng Yin, Daoyan Lin, Dayong Yang, Dazhi Jiang, Ding Ai, Erle Zhu, Fei Wang, Gengzheng Pan, Guo Wang, Hailong Sun, Haitao Li, Haiyang Li, Haiyi Hu, Hanyu Zhang, Hao Peng, Hao Tai, Haoke Zhang, Haoran Wang, Haoyu Yang, He Liu, He Zhao, Hongwei Liu, Hongxi Yan, Huan Liu, Huilong Chen, Ji Li, Jiajing Zhao, Jiamin Ren, Jian Jiao, Jiani Zhao, Jianyang Yan, Jiaqi Wang, Jiayi Gui, Jiayue Zhao, Jie Liu, Jijie Li, Jing Li, Jing Lu, Jingsen Wang, Jingwei Yuan, Jingxuan Li, Jingzhao Du, Jinhua Du, Jinxin Liu, Junkai Zhi, Junli Gao, Ke Wang, Lekang Yang, Liang Xu, Lin Fan, Lindong Wu, Lintao Ding, Lu Wang, Man Zhang, Minghao Li, Minghuan Xu, Mingming Zhao, Mingshu Zhai, Pengfan Du, Qian Dong, Shangde Lei, Shangqing Tu, Shangtong Yang, Shaoyou Lu, Shijie Li, Shuang Li, Shuang-Li, Shuxun Yang, Sibao Yi, Tianshu Yu, Wei Tian, Weihao Wang, Wenbo Yu, Weng Lam Tam, Wenjie Liang, Wentao Liu, Xiao Wang, Xiaohan Jia, Xiaotao Gu, Xiaoying Ling, Xin Wang, Xing Fan, Xingru Pan, Xinyuan Zhang, Xinze Zhang, Xiuqing Fu, Xunkai Zhang, Yabo Xu, Yandong Wu, Yida Lu, Yidong Wang, Yilin Zhou, Yiming Pan, Ying Zhang, Yingli Wang, Yingru Li, Yinpei Su, Yipeng Geng, Yitong Zhu, Yongkun Yang, Yuhang Li, Yuhao Wu, Yujia Li, Yunan Liu, Yunqing Wang, Yuntao Li, Yuxuan Zhang, Zezhen Liu, Zhen Yang, Zhengda Zhou, Zhongpei Qiao, Zhuoer Feng, Zhuorui Liu, Zichen Zhang, Zihan Wang, Zijun Yao, Zikang Wang, Ziqiang Liu, Ziwei Chai, Zixuan Li, Zuodong Zhao, Wenguang Chen, Jidong Zhai, Bin Xu, Minlie Huang, Hongning Wang, Juanzi Li, Yuxiao Dong, and Jie Tang. Glm-4.5: Agentic, reasoning, and coding (arc) foundation models, 2025. URL <https://arxiv.org/abs/2508.06471>.
- MiniMax: Aili Chen, Aonian Li, Baichuan Zhou, Bangwei Gong, Binyang Jiang, Boji Dan, Changqing Yu, Chao Wang, Cheng Ma, Cheng Zhong, Cheng Zhu, Chengjun Xiao, Chengyi Yang, Chengyu Du, Chenyang Zhang, Chi Zhang, Chuangyi Huang, Chunhao Zhang, Chunhui Du, Chunyu Zhao, Congchao Guo, Da Chen, Deming Ding, Dianjun Sun, Dongyu Zhang, Enhui Yang, Fei Yu, Guang Zheng, Guodong Zheng, Guohong Li, Haichao Zhu, Haigang Zhou, Haimo Zhang, Han Ding, Hao Zhang, Haohai Sun, Haolin Lyu, Haonan Lu, Haoyu Wang, Huajie Shi, Huiyang Li, Jiacheng Chen, Jian Zhang, Jiaqi Zhuang, Jiaren Cai, Jiaxin Pan, Jiayao Li, Jiayuan Song, Jichuan Zhang, Jie Wang, Jihao Gu, Jin Zhu, Jingwei Dong, Jingyang Li, Jingyu Zhang, Jingze Zhuang, Jinhao Tian, Jinli Liu, Jinyi Hu, Jun Tao, Jun Zhang, Junbin Ruan, Junhao Xu, Junjie Yan, Junteng Liu, Junxian He, Kang Xu, Ke Ji, Ke Yang, Kecheng Xiao, Keyu Duan, Keyu Li, Le Han, Letian Ruan, Li Yuan, Lianfei Yu, Liheng Feng, Lijie Mo, Lin Li, Lingye Bao, Lingyu Yang, Lingyuan Zhou, Loki, Lu Chen, Lunbin Ceng, Ming Li, Ming Zhong, Mingliang Tao, Mingyuan Chi, Mujie Lin, Nan Hu, Ningxin Chen, Peiyin Zhu, Peng Gao, Pengcheng Gao, Pengfei Li, Penglin Li, Pengyu Zhao, Qibin Ren, Qidi Xu, Qihan Ren, Qile Li, Qin Wang, Quanliang Chen, Qunhong Ceng, Rong Tian, Rui Dong, Ruitao Leng, Ruize Zhang, Shanqi Liu, Shaoyu Chen, Sheng Jia, Shun Yao, Shuoran Zhao, Shuqi Yu, Sichen Li, Sicheng Pan, Songquan Zhu, Tengfei Li, Tian Xie, Tiancheng Qin, Tianrun Liang, Wei Liu, Weiqi Xu, Weitao Li, Weixiang Chen, Weiyu Cheng, Weiyu Zhang, Wenhua Chen, Wenqian Zhao, Xiancai Chen, Xiangjun Song, Xiangyuan Wang, Xiao Luo, Xiao Su, Xiaobo Li, Xiaodong Han, Xiaojie Wu, Xihao Song, Xingyi Han, Xinyu Guan, Xuan Lu, Xun Zou, Xunhao Lai, Xutong Li, Yan Gong, Yang Wang, Yang Xu, Yangsen Wang, Ye Tang, Yicheng Chen, Yinran Qiu, Yiqi Shi, Yiting Guo, Yiwen Huang, Yixuan Wang, Yongyi Hu, Yu Gao, Yu Zhang, Yuanxiang Ying, Yuanzhen Zhang, Yubo Wang, Yuchen Song, Yufeng Yang, Yuhang Meng, Yuhang Miao, Yuhao Li, Yujie Liu, Yulin Hu, Yunan Huang, Yunji Li, Yunyi Huang, Yusen Zhang, Yusu Hong, Yutao Xie, Yutong Zhang, Yuwen Liao, Yuxuan Shi, Yuze Wenren, Zebin Li, Zehan Li, Zejian Luo, Zeyu Jin, Zeyuan Sun, Zhanpeng Zhou, Zhaochen Su, Zhengdong Li, Zhengmao Zhu, Zhengyuan Peng, Zhenhua Fan, Zhi Zhang, Zhichao Xu, Zhiheng Lv, Zhikang Xu, Zhitao He, Zhiwei He, Zhongyuan Li, Zibo Gao, Zijia Wu, Zijian Song, Zijian Zhou, Zijun Sun, Zishan Huang, Ziying Chen, and Ziyue Ge. The minimax-m2 series: Mini activations unleashing max real-world intelligence, 2026a. URL <https://arxiv.org/abs/2605.26494>.
- Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. Deepseekmath: Pushing the limits of mathematical reasoning in open language models, 2024. URL <https://arxiv.org/abs/2402.03300>.
- Aayush Gupta. Reliabilitybench: Evaluating llm agent reliability under production-like stress conditions, 2026. URL <https://arxiv.org/abs/2601.06112>.
- Dongsheng Zhu, Xuchen Ma, Yucheng Shen, Xiang Li, Yukun Zhao, Shuaiqiang Wang, Lingyong Yan, and Dawei Yin. When tools fail: Benchmarking dynamic replanning and anomaly recovery in llm agents, 2026. URL <https://arxiv.org/abs/2606.05806>.

- Doyoung Kim, Zhiwei Ren, Jie Hao, Zhongkai Sun, Lichao Wang, Xiyao Ma, Zack Ye, Xu Han, Jun Yin, Heng Ji, Wei Shen, Xing Fan, Benjamin Yao, and Chenlei Guo. Beyond perfect apis: A comprehensive evaluation of llm agents under real-world api complexity, 2026. URL <https://arxiv.org/abs/2601.00268>.
- Yang Tian, Zhengpeng Shi, Yu Zhou, and Bo Zhao. Beyond function calling: Benchmarking tool-using agents under tool-environment unreliability, 2026. URL <https://arxiv.org/abs/2606.25819>.
- Josh Tobin, Rachel Fong, Alex Ray, Jonas Schneider, Wojciech Zaremba, and Pieter Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world. In *2017 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, page 23–30. IEEE Press, 2017. doi:10.1109/IROS.2017.8202133. URL <https://doi.org/10.1109/IROS.2017.8202133>.
- Yuxin Chen, Xiaodong Cai, Junfeng Fang, Zhuowen Han, Yu Wang, Yaorui Shi, Yi Zhang, Qi Gu, Xunliang Cai, Xiang Wang, An Zhang, and Tat-Seng Chua. Learning to act under noise: Enhancing agent robustness via noisy environments, 2026b. URL <https://arxiv.org/abs/2605.27209>.
- Sri Vatsa Vuddanti, Aarav Shah, Satwik Kumar Chittiprolu, Tony Song, Sunishchal Dev, Kevin Zhu, and Maheep Chaudhary. PALADIN: Self-correcting language model agents to cure tool-failure cases. In *LLM-based Multi-Agent Systems: Towards Responsible, Reliable, and Scalable Agentic Systems*, 2026. URL <https://openreview.net/forum?id=NVTto0297p>.
- Hassan Hamad, Yingru Xu, Liang Zhao, Wenbo Yan, and Narendra Gyanchandani. Toolcritic: Detecting and correcting tool-use errors in dialogue systems, 2025. URL <https://arxiv.org/abs/2510.17052>.
- Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik R Narasimhan, and Yuan Cao. React: Synergizing reasoning and acting in language models. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=WE_vluYUL-X.
- Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik R Narasimhan, and Shunyu Yao. Reflexion: language agents with verbal reinforcement learning. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL <https://openreview.net/forum?id=vAElhFcKW6>.
- Jie Huang, Xinyun Chen, Swaroop Mishra, Huaixiu Steven Zheng, Adams Wei Yu, Xinying Song, and Denny Zhou. Large language models cannot self-correct reasoning yet. In *The Twelfth International Conference on Learning Representations*, 2024. URL <https://openreview.net/forum?id=Ikmd3fKBPQ>.
- Hanning Zhang, Shizhe Diao, Yong Lin, Yi Fung, Qing Lian, Xingyao Wang, Yangyi Chen, Heng Ji, and Tong Zhang. R-tuning: Instructing large language models to say ‘I don’t know’. In Kevin Duh, Helena Gomez, and Steven Bethard, editors, *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 7113–7139, Mexico City, Mexico, June 2024. Association for Computational Linguistics. doi:10.18653/v1/2024.naacl-long.394. URL <https://aclanthology.org/2024.naacl-long.394/>.
- Wenxuan Wang, Shi Juluan, Zixuan Ling, Yuk-Kit Chan, Chaozheng Wang, Cheryl Lee, Youliang Yuan, Jen-tse Huang, Wenxiang Jiao, and Michael R. Lyu. Learning to ask: When LLM agents meet unclear instruction. In Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng, editors, *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 21773–21784, Suzhou, China, November 2025. Association for Computational Linguistics. ISBN 979-8-89176-332-6. doi:10.18653/v1/2025.emnlp-main.1104. URL <https://aclanthology.org/2025.emnlp-main.1104/>.
- Xiaojun Wu, Cehao Yang, Honghao Liu, Xueyuan Lin, Wenjie Zhang, Zhichao Shi, Xuhui Jiang, Chengjin Xu, Jia Li, and Jian Guo. Bayesian-agent: Posterior-guided skill evolution for llm agent harnesses, 2026. URL <https://arxiv.org/abs/2606.08348>.
- Yangjun Ruan, Honghua Dong, Andrew Wang, Silviu Pitis, Yongchao Zhou, Jimmy Ba, Yann Dubois, Chris J. Maddison, and Tatsunori Hashimoto. Identifying the risks of LM agents with an LM-emulated sandbox. In *The Twelfth International Conference on Learning Representations*, 2024. URL <https://openreview.net/forum?id=GEcwtMk1uA>.
- Yuzhi Tang, Tianxiao Li, Elizabeth Li, Chris J. Maddison, Honghua Dong, and Yangjun Ruan. LM agents may fail to act on their own risk knowledge. In *Second Conference on Language Modeling*, 2025. URL <https://openreview.net/forum?id=0eYdS51k8F>.

Model	τ^2 -bench			Retail-3I			Airline-3I			BFCL
	retail (114)	airline (50)	telecom (114)	general (473)	ambig. (473)	changing (279)	general (254)	ambig. (254)	changing (76)	multi-turn (200)
<i>Clean pass rate (%)</i>										
Qwen3-4B-Thinking-2507	56.1	62.0	21.1	71.9	62.0	63.4	65.7	61.0	39.5	31.5
Qwen3-8B	41.2	32.0	25.4	67.0	55.8	54.5	50.0	44.5	21.1	26.0
Qwen3-32B	43.0	30.0	21.1	70.2	58.1	53.8	50.0	51.6	22.4	39.5
Qwen3-235B	57.9	46.0	36.8	72.7	61.1	58.4	67.7	65.8	39.5	59.5
DeepSeek-V3	57.0	50.0	38.6	74.0	62.4	62.0	68.1	68.5	44.7	50.0
GLM-4.7	60.5	64.0	89.5	72.7	60.0	61.7	63.0	66.9	31.6	77.5
MiniMax-M2.5	64.9	68.0	91.2	71.0	61.1	61.7	67.3	68.9	42.1	81.5
<i>Inject pass rate (%)</i>										
Qwen3-4B-Thinking-2507	15.8	52.0	19.3	25.2	19.7	28.7	37.0	31.1	7.9	13.5
Qwen3-8B	17.5	38.0	21.1	41.9	29.8	31.2	46.1	37.8	11.8	14.5
Qwen3-32B	21.1	22.0	16.7	49.1	37.8	41.6	39.4	41.3	11.8	19.0
Qwen3-235B	42.1	40.0	25.4	58.8	44.6	43.0	55.1	55.1	29.0	26.0
DeepSeek-V3	37.7	36.0	29.8	54.1	43.6	43.7	54.7	57.9	39.5	29.0
GLM-4.7	29.8	52.0	68.4	43.8	39.8	39.1	43.3	45.7	19.7	38.5
MiniMax-M2.5	56.1	52.0	71.1	61.3	46.7	52.3	54.3	61.0	34.2	54.5
Δ (pp)										
Qwen3-4B-Thinking-2507	-40.4	-10.0	-1.8	-46.7	-42.3	-34.8	-28.7	-29.9	-31.6	-18.0
Qwen3-8B	-23.7	+6.0 [†]	-4.4	-25.2	-26.0	-23.3	-3.9	-6.7	-9.2	-11.5
Qwen3-32B	-21.9	-8.0	-4.4	-21.1	-20.3	-12.2	-10.6	-10.2	-10.5	-20.5
Qwen3-235B	-15.8	-6.0	-11.4	-14.0	-16.5	-15.4	-12.6	-10.6	-10.5	-33.5
DeepSeek-V3	-19.3	-14.0	-8.8	-19.9	-18.8	-18.3	-13.4	-10.6	-5.3	-21.0
GLM-4.7	-30.7	-12.0	-21.1	-29.0	-20.3	-22.6	-19.7	-21.3	-11.8	-39.0
MiniMax-M2.5	-8.8	-16.0	-20.2	-9.7	-14.4	-9.3	-13.0	-7.9	-7.9	-27.0

Table 5: Robustness gap across four task suites (% pass rate, temp=0, inject w/o alt). The first three suites use τ^2 -bench-style customer-service infrastructure; BFCL is an independent multi-turn function-calling benchmark. [†]Small positive delta on τ^2 -bench Airline ($n=50$) is within noise.

A Cross-Benchmark Robustness Gap

B Additional Qwen3-8B Within-Benchmark Results

To test whether the intervention pattern is specific to the 4B primary training target, we repeat the same four-way comparison on Qwen3-8B using the Combined Retail held-out split (402 tasks). Table 6 reports pass rates under failure-free evaluation, injected failures with the standard tool set, and injected failures with alternative tool paths. Unlike the 4B table, only point estimates are available for this replication, so we report the observed pass rates without seed-level standard deviations.

Model	Train BTM	Infer BTM	Clean	Inj w/o Alt	Inj w/ Alt
<i>Qwen3-8B — Combined Retail (402 held-out tasks)</i>					
8B	✗	✗	58.3	33.3	39.4
8B	✗	✓	57.2	39.3	41.2
8B + RL	✓	✗	56.8	37.4	42.2
8B + RL	✓	✓	59.4	41.4	44.6

Table 6: Within-benchmark effectiveness on Qwen3-8B using 402 held-out Combined Retail tasks. Values are point estimates; no independent RL training-seed replications are included.

The 8B results reproduce the qualitative decomposition observed on the 4B target. BTM alone improves injected performance from 33.3% to 39.3% without alternatives and from 39.4% to 41.2% with alternatives. RL without inference-time BTM improves the same conditions to 37.4% and 42.2%, respectively. Combining RL with inference-time BTM yields the highest pass rates, 41.4% and 44.6%. We therefore interpret the 8B experiment as evidence that the complementarity between runtime recovery context and trained recovery behavior is not unique to the 4B checkpoint, while avoiding stronger claims about scaling or statistical significance from a single additional training run.

C Cross-Benchmark Transfer

Model	Train → Eval	Train BTM	Infer BTM	Inj w/o Alt
<i>BFCL multi-turn (200 tasks)</i>				
4B	— → BFCL	✗	✗	13.5
4B	— → BFCL	✗	✓	16.5
4B + RL	Retail → BFCL	✓	✗	15.0
4B + RL	Retail → BFCL	✓	✓	18.5
<i>Airline-3I (584 tasks)</i>				
4B	— → Airline	✗	✗	30.7
4B	— → Airline	✗	✓	36.6
4B + RL	Retail → Airline	✓	✗	33.4
4B + RL	Retail → Airline	✓	✓	39.7
<i>τ^2-bench Telecom (114 tasks)</i>				
4B	— → Telecom	✗	✗	19.3
4B	— → Telecom	✗	✓	21.1
4B + RL	Retail → Telecom	✓	✗	20.2
4B + RL	Retail → Telecom	✓	✓	21.9

Table 7: Cross-benchmark transfer (Qwen3-4B-Thinking-2507, inject w/o alt). RL trained on Retail only. The (✓,✗) rows isolate RL’s contribution without target-domain beliefs; comparing them to (✓,✓) shows RL and BTM are complementary.

D Alternative Tool Specifications

Retail. Five alternative tools are added to the standard 16-tool retail environment (21 tools total when `with_alternatives=True`).

Alternative Tool	Equivalent To	Different Path
search_product_by_name	get_product_details	Lookup by name vs. by ID
get_item_by_product_options	get_item_details	Find item by options vs. by ID
get_orders_for_user	get_order_details	All orders at once (summary)
get_user_by_order	find_user_id_by_*	Auth via order number
check_order_item_availability	get_product + matching	One-shot exchange check

Table 8: Retail alternative tools (5 added, 21 total).

E Noise Type Details

Table 9 details the nine noise types used by BENCH2ROBUST, organized by observability.

F Error-Type Coverage of Prior Robustness Benchmarks

Table 10 situates our noise taxonomy against prior robustness benchmarks, grouped by observability.

G Training Configuration

Table 11 gives the full scenario-phase curriculum schedule summarized in Section 3.3.

Noise Type	Injected Response
<i>Observable Errors — explicit error signal visible to the agent</i>	
Timeout	“Error: request timed out after 30s”
Rate Limit	HTTP 429 Too Many Requests
Server Error	HTTP 500/502/503 Internal Server Error
Malformed Response	JSON parse failure / garbled output
Auth Error	HTTP 401/403 Forbidden
Schema Drift	“Unknown field ‘X’ / required field missing”
<i>Silent Errors — structurally valid response with corrupted decision-critical fields</i>	
Partial	Critical fields $\rightarrow$ empty (<code>[]</code> , <code>{}</code> , <code>""</code>)
Stale	State fields backdated (e.g., “delivered” $\rightarrow$ “pending”)
Factual Error	Values $\pm 10\text{--}25\%$ plausible perturbation

Table 9: Nine noise types grouped by observability. *Observable errors* produce unambiguous error messages. *Silent errors* return well-formed responses with corrupted semantics; the agent must detect inconsistencies via verification or cross-referencing.

Benchmark	Observable Errors						Silent Errors		
	Timeout	Rate Lim.	Server Err.	Malformed	Auth Err.	Schema Dr.	Partial	Stale	Factual
ToolBench-X [Tian et al., 2026]	✓	✗	✓	✗	✗	✓	✗	✗	✓
RobustBench-TC [Zhou et al., 2026]	✓	✓	✓	✓	✓	✓	✗	✗	✗
AgentNoiseBench [Wang et al., 2026b]	✓	✗	✓	✓	✗	✗	✓	✗	✓
NoisyAgent [Chen et al., 2026b]	✓	✗	✓	✓	✗	✗	✓	✗	✓
ToolMaze [Zhu et al., 2026]	✓	✓	✗	✗	✗	✗	✓	✗	✓
WildAGTEval [Kim et al., 2026]	✗	✗	✓	✗	✗	✗	✓	✗	✗
ReliabilityBench [Gupta, 2026]	✓	✓	✗	✓	✗	✓	✓	✗	✗
PlanBench-XL [Liu et al., 2026]	✗	✗	✓	✗	✗	✗	✗	✗	✗
PALADIN [Vuddanti et al., 2026]	✓	✗	✓	✗	✗	✗	✗	✗	✓
BENCH2ROBUST (Ours)	✓	✓	✓	✓	✓	✓	✓	✓	✓

Table 10: Error-type coverage comparison across observable and silent failure modes.

H Injection Configuration

I Sensitivity to Injection Severity

We run an additional sensitivity sweep on Combined Retail held-out tasks (402 tasks, seed 42, inject w/o alt) using Qwen3-4B-Thinking-2507 and the 4B RL+BTM checkpoint. Table 14 varies two axes: the clean-response probability $P(\text{clean})$ with the default budget ($B = 5$, $K_{\max} = 2$), and the stochastic injection limits with the default $P(\text{clean}) = 0.60$. Across the clean-probability sweep, both systems improve as injection becomes milder, but RL+BTM retains a consistent advantage over the base model (+9.0 to +22.2pp). Across budget settings, the advantage remains positive (+19.9 to +28.3pp), with the largest gain under the stricter $B = 3$, $K_{\max} = 1$ setting.

J Full Results with Efficiency Metrics

K Qualitative Examples

We present three episodes illustrating retry, switching, and escalation behaviors observed in the RL model. Each example contrasts the RL model’s behavior with the base model’s on the same task (though injection seeds may differ due to hash randomization). All examples are from Combined Retail under injection with alternative tools.

Strategy 1: Retry (task_78). *Task:* User Yara Muller needs three actions—change address on order #W5056519, exchange an item in the same order, and cancel order #W5995614.

Phase	Strategy Focus	Max Inj.	S1/S2/S3 Mix	Auto-Advance Criterion
1	Learn to RETRY	2	100/0/0	Avg reward > 0.25 for 3 iters
2	Discover alternatives	2	80/20/0	Switch > 25% & pass > 25%
3	Learn to SWITCH	5	60/40/0	Switch > 25% & pass > 25%
4	Learn to ABSTAIN	5	40/50/10	S3 xfer > 50%, turns < 15, S1/S2 non-regress.
5	Full repertoire	5	30/45/25	Early stopping

Table 11: Scenario-phase curriculum and auto-advance criteria. Phase 4 requires timely S3 transfer without S1/S2 regression; Phase 5 early-stops on sustained over-transfer.

Parameter	Value
Base model	Qwen3-4B-Thinking-2507
Algorithm	DAPO (group-relative with asymmetric clip + KL stabilization)
KL loss	low_var_kl, coefficient 0.02
Learning rate	2×10^{-6} (constant)
Global batch size	256 (16 prompts $\times$ 16 rollouts)
Rollouts per prompt	16 (hybrid: first 8 clean + last 8 noisy)
Max response tokens	8192
Max steps per episode	25
Context length	32768
Epochs	3
Training data	937 tasks (retail combined)
Reward	partial_credit $\times$ 0.3 (fail) or $1.0 \times$ efficiency (pass)
Repetition penalty	$3 \times$ same call $\rightarrow$ 0.5, $4 \times \rightarrow$ 0.0
Efficiency discount	$\max(0.3, 1.0 - 0.02 \times \max(0, \text{turns} - 12))$
Curriculum	Phase 1–5 (Phases 1–4 auto-advance; Phase 5 early stopping)
Bayesian Tool Memory	Precomputed Beta posteriors from training-split rollouts
Hardware	8 $\times$ H100 80GB
User simulator	Qwen3-235B via AWS Bedrock
Framework	slime

Table 12: Full training configuration.

RL model (PASS, 10 tool calls): At step 2, `get_user_details` returns *HTTP 429 Too Many Requests*. The model immediately retries the same call at step 3—which succeeds. It then proceeds to retrieve all three order details, modify the address, exchange the item, and cancel the third order, completing all sub-tasks.

Base model (FAIL, 9 tool calls): The base model successfully completes the first two sub-tasks (address change and item exchange). However, when `get_order_details` for the third order returns a schema validation error at step 8 (“Required field ‘status’ is missing”), it immediately calls `transfer_to_human_agents` with “cannot retrieve order details”—abandoning the final cancellation despite having already demonstrated capability on the first two orders.

Key insight: The RL model has learned that transient errors resolve on retry. The base model treats any unexpected error as a global system failure, even when partial success demonstrates the system is operational.

Strategy 2: Switch (task_58). *Task:* User wants to exchange two items (coffee machine and laptop) in a delivered order.

RL model (PASS, 10 tool calls): After authentication and `get_user_details` succeed, the model calls `get_order_details`—which returns a schema_drift error (“Unknown field ‘items_v2’”). Rather than retrying a persistently broken tool, it switches to `get_orders_for_user`—a fallback that provides order summaries. It then uses `check_order_item_availability` and `get_product_details` to gather the remaining information, and successfully completes the exchange.

Base model (FAIL, 2 tool calls): The first call `find_user_id_by_name_zip` returns a malformed response. The base model immediately calls `transfer_to_human_agents` after a single tool failure—without even attempting authentication via the alternative `find_user_id_by_email` path.

	Observable Errors						Silent Errors			Limits		
	Timeout	Rate Lim.	Serv. Err.	Malform.	Auth Err.	Schema Dr.	Partial	Stale	Factual	Clean	Budget	Consec.
$P(\nu)$	0.06	0.05	0.05	0.04	0.03	0.03	0.05	0.04	0.05	0.60	5	2

Table 13: Per-tool noise configuration (θ_j). Each tool call is clean with probability 0.60; otherwise one of nine failure modes is sampled. Budget and consecutive-failure limits apply only to stochastic injection, not episode-persistent scenario blocking. This severe stress-test setting is not an estimate of real API failure rates.

Setting	Base	RL+BTM	Δ
<i>Vary $P(\text{clean})$; $B = 5$, $K_{\max} = 2$</i>			
$P(\text{clean}) = 0.60$	21.6	43.8	+22.2
$P(\text{clean}) = 0.80$	35.3	56.0	+20.7
$P(\text{clean}) = 0.90$	49.0	61.4	+12.4
$P(\text{clean}) = 0.95$	53.2	62.2	+9.0
<i>Vary injection limits; $P(\text{clean}) = 0.60$</i>			
$B = 3$, $K_{\max} = 1$	23.9	52.2	+28.3
$B = 5$, $K_{\max} = 2$	21.6	43.8	+22.2
$B = 7$, $K_{\max} = 3$	21.9	41.8	+19.9

Table 14: Sensitivity to injection severity on Combined Retail held-out tasks (402 tasks, seed 42, inject w/o alt). B is the maximum number of stochastic injections per episode; $K_{\max}$ is the maximum number of consecutive failures on the same tool. Values are pass rates (%).

Key insight: The RL model distinguishes persistent errors (schema_drift $\rightarrow$ switch) from its general retry behavior. It has learned which alternative tools provide equivalent information through different query paths.

Strategy 3: Correct Abstain (general_traj_0761). *Task:* User wants to change desk lamp options in pending order #W2091016 (battery-powered $\rightarrow$ USB-powered), then cancel the entire order.

RL model (CORRECT ABSTAIN, 8 tool calls): The model encounters a server_error on get_order_details (step 2), retries once and gets a schema_drift (step 3, persistent). It switches to get_orders_for_user to retrieve order summaries, then attempts modify_pending_order_items—which fails because the summary-level data lacks the specific item_id needed for modification. It then attempts cancel_pending_order, which also fails. Having exhausted retry (step 2), switch (step 4), and direct action (steps 5–6), the model correctly calls transfer_to_human_agents—escalating only after all viable paths are attempted. Note: this episode does not “pass” the task evaluator (the required DB mutations do not occur), but the agent’s behavior is *correct* given the S3 scenario—the task is provably unsolvable and appropriate escalation avoids wasted computation and erroneous actions.

Base model (FAIL, 6 tool calls): After receiving partial responses from get_order_details and get_user_details (empty fields), the model proceeds to call cancel_pending_order with fabricated data—acting on information it never actually retrieved.

Key insight: The RL model applies a stopping criterion—when all information-retrieval paths are exhausted and required data is unavailable, it escalates rather than guesses—and reaches that point only after exhausting retry, switch, and direct action. The base model lacks this judgment and acts on incomplete or fabricated information. We attribute the criterion itself to BTM’s transfer conditions rather than to reward learning (Section 3.2); what this trajectory illustrates is that strategy-aware training leaves it intact while adding the retry and switch attempts that precede it.

L Extended Limitations

- **Efficiency and clean behavior:** RL preserves held-out clean pass rate (63.7%, matching the base model), but recovery under injection costs more tokens (70K $\rightarrow$ 117K), which may matter in latency-sensitive deployments.
- **Domain coverage:** Telecom is near the 4B model’s capability floor (21% clean), and Retail-to-BFCL transfer is modest (+5pp), suggesting that recovery behavior remains partly tied to domain-specific tool structure.

Model	Clean			Inject w/o Alt			Inject w/ Alt		
	PASS	Tokens	Steps	PASS	Tokens	Steps	PASS	Tokens	Steps
Qwen3-4B (Base)	63.7	88K	11.9	22.1	70K	10.3	23.6	67K	9.9
+ BTM	62.7	103K	12.2	34.6	110K	12.8	38.1	123K	12.5
+ RL + BTM	63.7	105K	12.3	43.0	117K	13.4	45.3	108K	11.7

Table 15: Full results with efficiency metrics on 402 held-out retail tasks. Under injection, BTM and RL+BTM use more tokens than the base model (108–123K vs. 67–70K), reflecting additional recovery behaviors such as retries and alternative tool calls.

- **Abstention signal:** S3 episodes define when escalation is appropriate, but Eq. 2 assigns no completion bonus to correct abstention, because impossible tasks cannot satisfy the benchmark evaluator. An S3-aware reward term and held-out impossible-task metric are needed to test learned stopping directly.
- **Simulation:** The nine noise types are plausible API failure modes, but their rates are a severe stress-test configuration rather than incident-derived estimates. Appendix I varies severity, but absolute pass rates should still be read as intervention rankings under simulated stressors.

M Training Method Comparison

We compare three training approaches for learning recovery strategies using Qwen3-4B, evaluated on Combined Retail under failure-free, injected failure without an alternative tool, and injected failure with an alternative tool.

Training Method	Clean	Inj w/o Alt	Inj w/ Alt
Base model w/o fine-tuning	65.3	23.2	26.4
vanilla SFT	65.3	24.0	24.5
vanilla GRPO	64.9	23.0	24.4
Ours	65.3	45.9	47.9

Table 16: Training method comparison on the full 1,339-task Combined Retail set. Trained methods use BTM during training and inference; the base row is evaluated without BTM. Ours adds scenario-controlled curriculum, DAPO/KL stabilization, and partial-credit rewards.

N Bayesian Tool Memory: System Prompt Template

Figure 1 shows the BTM block template injected into the system prompt. Posterior recoverability statistics are computed from training-split rollouts and presented together with predefined fallback structure and recovery constraints; the model chooses actions from this combined context. The template is instantiated per-domain: tool names, belief values, and fallback maps are populated from the target environment’s configuration.

```

<tool_reliability>
Tool recovery beliefs (Beta posterior, from historical data):
{TOOL_NAME_1}:
P(episode recovery | error): timeout={p}, rate_limit={p},
server_error={p}, auth_error={p}, schema_drift={p},
malformed_response={p}, partial={p}, stale={p},
factual_error={p}
Alternative: {ALT_TOOL} (P={p}, {GRANULARITY})
{TOOL_NAME_2}:
P(episode recovery | error): timeout={p}, ...
Alternative: {ALT_TOOL} (P={p}, {GRANULARITY})
...

How to use: Compare P(recovery) vs P(switch) for your error.
High P(recovery) -> retry this tool.
Low P(recovery) + high P(switch) -> switch to alternative.
After switching, verify returned data has needed fields.
If both low -> ask the user or transfer.

Alternative tool paths (when primary tool fails):
- {PRIMARY} -> {FALLBACK} ({GRANULARITY NOTE})
- ...

Critical constraints:
1. If a tool fails, retry at least once before other options.
2. After switching, verify returned data provides ALL required
fields at the right granularity.
3. Before any irreversible action, confirm every required field
from actual tool responses. Do not guess missing fields.
4. For ANY price calculation, use the calculate tool.
5. After calling a write tool, check the response for errors.
6. Only transfer after exhausting retry and alternative paths.
</tool_reliability>

```

Figure 1: BTM system prompt template. Placeholders are populated per-domain with recovery beliefs, fallback maps, and shared recovery constraints.