

Ready Cohorts: Bounding GPU Opportunity and Avoiding Host Round Trips in LLM-Agent Control

Josef Chen
Independent Researcher

August 2026

Abstract

LLM-agent services repeatedly execute small deterministic transitions between model and tool calls: route an outcome, update state, and emit the next effect. We ask when this control path exposes enough concurrent work for GPU execution, and what changes when a GPU-computed route decision remains on device. We formalize the *ready-cohort boundary* using fixed-partition share F , exact offline share P^* , local upper bound U , and online achieved share A .

For zero service time, unlimited capacity, and equal relative launch deadlines, a specialized dynamic program computes P^* exactly. In a prospectively frozen stationary Poisson replay of one pinned 851-session public trace panel, the primary condition at 100,000 target active sessions, $K = 256$, and a 50 ms launch deadline gives $F = 30.19\%$, $P^* = 43.00\%$, and $U = 45.85\%$. Exact packing recovers 81.83% of the opportunity lost at fixed window boundaries. The outcome-derived route key is a conditioning proxy, not proof of executable identity.

A separate mechanism study keeps a GPU-computed binary decision on device instead of returning four bytes to the host and redispatching. Across four named GPU placements, the device-resident path is faster in all 36 configurations; within-placement row-median ratios range from $1.19\times$ to $2.39\times$. Across both admissible mechanisms, all 14,557,440 tested batched invocations match a separately implemented host oracle. A fixed nested device graph that removes no host decision is slower in all 60 configurations across five placements.

Together, the studies establish two measurable gates for GPU agent control: deadline-feasible cohort supply and observation placement. They expose schedulable work missed by fixed windows. A joined finite online runtime is required to measure A , CPU displacement, and service-level benefit.

1 Introduction

An agent runtime performs deterministic control work between model and tool calls. It parses a typed outcome, advances a state machine, checks policy and budget state, selects a route, and emits the next effect. Each transition is small beside inference, but a service with many concurrent sessions executes them continuously.

This control path is already a datacenter concern. A recent production and open-source characterization found that agentic workflows repeatedly cross the CPU–GPU boundary, place host orchestration on the critical path, and create bursty CPU demand [26]. That result establishes the pressure. It leaves a more specific systems question open: when can the deterministic transition itself be grouped and executed profitably on a GPU?

Similarity across agents is not enough. A GPU route needs a cohort above its hardware and runtime crossover, all members must share executable semantics, and they must become ready before their launch deadlines. A decision returned to the host after every step also incurs copy, synchronization, branch, and redispatch overhead. We call the interface between cohort supply and observation placement the *ready-cohort boundary*.

For each route and hardware/runtime configuration, let K begin a measured safe suffix: every tested cohort from

K through a declared maximum clears a chosen admissible baseline. A workload supplies events with release times, launch deadlines, and declared grouping keys. The central workload question is how much same-group work can be packed above K . The corresponding mechanism question is how much of the control chain can proceed without exposing an intermediate decision to the host.

We answer these questions in two experiments. A public agent-trace replay compares fixed-window eligibility with an exact offline packing optimum and a local upper bound. A separate CUDA study holds the state transition and route bodies fixed while changing where one GPU-computed decision is observed. An earlier device-launch design provides a negative control. The experiments are kept numerically separate because the trace threshold $K = 256$ is swept rather than measured for the resident-policy source, and the 32-epoch mechanism horizon is not inferred from the trace.

The paper makes four contributions:

1. **A ready-cohort formulation.** We separate the hardware threshold K , fixed-partition share F , exact offline share P^* , local bound U , and online achieved share A . Each quantity has one source and a defined inference boundary.
2. **An exact opportunity instrument.** Under zero service, unlimited capacity, and equal relative launch

deadlines, a specialized dynamic program computes P^* . This gives a reproducible workload measurement without claiming algorithmic priority.

3. **Trace evidence for hidden cohort supply.** In the frozen primary replay, exact packing raises eligible share from 30.19% to 43.00% and recovers 81.83% of the fixed-window alignment gap. The full grid also identifies regimes with no qualifying cohort.
4. **Cross-provider mechanism evidence.** Across four named GPU placements and 36 cells, retaining the tested decision on device is $1.19\times$ to $2.39\times$ faster than the matched host-mediated GPU path. A fixed nested graph loses in all 60 cells across five placements, ruling out device launch alone as the explanation.

These experiments resolve two prerequisite questions for a GPU control plane: whether enough work can coexist under a declared grouping, and whether one device-side decision avoids measurable host-mediated overhead. The next system must join them with finite service and CPU fallback, then measure A , CPU use, raw tail latency, exact effects, task utility, and inference interference.

2 Execution and semantic scope

2.1 Unit of execution

Our unit is a deterministic control transition inside an agent runtime. It is smaller than an LLM request, a tool, or a complete workflow. A transition reads typed state and an already available event, then produces new typed state, a route, and possibly an effect descriptor. Model inference, tool execution, and the privileged commit of external effects remain outside the unit.

This separation matters for both performance and safety. A GPU may compute that an agent should call a tool, but the current paper does not ask the GPU to hold cloud credentials, create a virtual machine, or commit a side effect. A future runtime can keep pure state evolution on device while a CPU or DPU validates and commits ordered effect descriptors.

2.2 Compatibility and exactness

Two events are compatible only when one implementation can process them together without changing the declared semantics. The trace study cannot verify that condition. Its narrowest grouping is an outcome-derived route-key proxy, and even that key omits state-machine node, schema, arguments, policy context, and the identities in multi-tool outcomes. Coarser event classes and a pooled route are diagnostics. None of these groupings proves that fusion is semantically admissible.

Correctness in the mechanism studies means exact equality of every declared state field and the full decision sequence against a separately implemented host oracle. It does not establish correct recovery, distributed ordering, or real tool effects. Checksums are provenance guards

In scope	Out of scope in this paper
Typed deterministic transition	Arbitrary Python on a GPU
Route-key-conditioned cohorts	Verified semantic fusion
Latest launch time	End-to-end completion SLO
Device-resident pure decision	Privileged tool or VM lifecycle
Exact tested trajectory	Distributed commit and recovery
Named GPU placements	Hardware-population inference

Table 1: The execution contract. These exclusions are claim boundaries, not assumed properties of a future system.

rather than the definition of equality.

2.3 Launch deadlines, not completion SLOs

Every trace event has a latest admissible launch time. This is a bound on how long the scheduler may wait to form a cohort. Kernel service and queueing after launch are zero in the mathematical model. The 50 ms primary value is therefore not a 50 ms completion service-level objective. Finite service enters only in the proposed online system.

3 The ready-cohort model

3.1 Events and the hardware threshold

Let E be a set of control events. Event i has release time t_i , latest admissible launch time $d_i \geq t_i$, and route r_i . A route in the mathematical model means that one implementation can process the grouped events without changing their declared transition semantics. A trace label does not establish that condition by itself.

For route r and hardware/runtime configuration h , define $K_r(h, v, H)$ as the start of a measured safe suffix: every tested cohort size from K_r through a declared maximum beats a named admissible baseline. The model extrapolates that monotone threshold and has no upper batch limit. The arguments record state visibility v and observation-free horizon H because transfer, synchronization, and temporal fusion can move the crossover. We write K_r when the configuration is fixed.

A batch (τ, B) is feasible when

$$|B| \geq K_r, \quad r_i = r \quad \forall i \in B, \quad t_i \leq \tau \leq d_i \quad \forall i \in B. \quad (1)$$

A schedule contains feasible batches and assigns each event at most once. The model allows batches to have more than K_r events. It has no maximum batch size, service time, or device-capacity constraint.

3.2 Four shares with different meanings

Let π be a frozen partition of time into non-overlapping windows. Each event belongs to a bucket defined by




Figure 1: Evidence map. Solid boxes are the controlled or measured components in this paper; dashed boxes define the joined online experiment and its service-level outcomes. The shared notation connects the studies without treating the swept trace threshold as the resident source’s measured crossover.

its window and route. If bucket b has n_b events, fixed-partition eligibility is

$$F(\pi, K) = \frac{1}{|E|} \sum_b n_b \mathbf{1}[n_b \geq K_{r(b)}]. \quad (2)$$

F is exact only for schedulers constrained to π . Sliding deadlines can join events across a fixed boundary, so F is not a universal ceiling.

Let P^* be the maximum number of assigned events in any feasible offline schedule, divided by $|E|$. It uses future knowledge and therefore measures opportunity rather than online performance.

For route r , define the active count at time τ as

$$Q_r(\tau) = |\{j : r_j = r, t_j \leq \tau \leq d_j\}|. \quad (3)$$

Event i is locally eligible if $Q_{r_i}(\tau) \geq K_{r_i}$ at some $\tau \in [t_i, d_i]$. The local-overlap share is

$$U = \frac{1}{|E|} \sum_i \mathbf{1} \left[\max_{\tau \in [t_i, d_i]} Q_{r_i}(\tau) \geq K_{r_i} \right]. \quad (4)$$

U may count incompatible opportunities that reuse the same events. It is an upper bound, not necessarily an achievable schedule.

Finally, A is the share accelerated within deadline by a specified finite online runtime, including its queue, service, fallback, and capacity rules. To compare A with P^* , each accelerated batch must obey the same route grouping, threshold K_r , and launch deadline as the offline model; finite service and capacity may impose stricter constraints. Its denominator is the identical event set E and retained horizon used by P^* ; late, missing, failed, and fallback events remain in that denominator. The current paper does not measure A .

Proposition 1 (Boundary ordering). *If every batch admitted by the frozen partition is admissible under the event deadlines, and the batches counted by A obey the same route, threshold, deadline, and event-set constraints as the offline model, then*

$$F \leq P^* \leq U, \quad A \leq P^*. \quad (5)$$

Proof. Every bucket with $n_b \geq K_{r(b)}$ is a feasible batch, and buckets are disjoint, so the fixed schedule attains F .

Symbol	Source	Meaning
K_r	hardware	route-specific profitable cohort
F	workload, policy	fixed-partition eligible share
P^*	workload, offline	exact schedulable share
U	workload, local	necessary-overlap upper bound
A	online runtime	achieved accelerated share

Table 2: The quantities cannot be substituted for one another. In particular, $K = 256$ in the trace sweep is not a measured K_r for the resident-policy mechanism.

Every event in any feasible batch overlaps at least K_{r_i} same-route intervals at that batch’s launch time, so it is counted by U . An online schedule is one member of the offline feasible set. $\square$

3.3 Compatibility has a measurable tax

Suppose grouping g_f refines g_c , so every fine bucket lies inside one coarse bucket. For fixed π and K ,

$$F(\pi, K, g_f) \leq F(\pi, K, g_c). \quad (6)$$

This inequality measures fragmentation under a declared grouping. It does not make coarse fusion admissible. A pooled kernel may change control flow, memory access, actions, or numerical trajectory. The route-key proxy is therefore the narrowest grouping in the trace study.

4 Exact packing under equal relative deadlines

The trace experiment uses $d_i = t_i + \delta$ for a common δ . This special case permits an exact dynamic program. We keep the assumptions visible because the result does not extend unchanged to arbitrary deadlines or finite service.

Proposition 2 (Deadline launch times). *Under zero service time and unlimited simultaneous capacity, some optimal offline schedule launches every batch at an event deadline.*

Proof. Take a nonempty feasible batch launched at τ and let $d_{\min}$ be the smallest deadline among its events.

Feasibility gives $\tau \leq d_{\min}$. Every assigned event has release at most τ and deadline at least $d_{\min}$, so moving the launch to $d_{\min}$ preserves every assignment. Same-route batches moved to the same time can be merged; different routes may co-launch under the unlimited-capacity assumption. $\square$

Lemma 1 (Contiguous block form). *For one route with equal relative deadlines, there is an optimum whose batches are disjoint contiguous blocks in sorted release order.*

Proof. Sort releases so $t_1 \leq \dots \leq t_n$, and order batches by launch time. Suppose $i < j$, event i is assigned to a later batch, and event j to an earlier batch. Their feasibility gives

$$t_i \leq t_j \leq \tau_{\text{early}} \leq \tau_{\text{late}} \leq t_i + \delta \leq t_j + \delta.$$

Exchanging the two assignments is therefore feasible. Repeated exchanges remove crossings. An unassigned event between the first and last release of a batch can then be added to that batch: its release is no later than the batch launch, and its equal-length deadline is no earlier than the first event’s deadline. Thus each batch may be taken as a contiguous block. $\square$

Let $D[j]$ be the maximum number of assigned events among the first j releases of one route, with $D[0] = 0$. A feasible block ending at j starts at some $i \leq j - K_r + 1$ and satisfies $t_j - t_i \leq \delta$. Hence

$$D[j] = \max \left\{ D[j-1], \max_{\substack{i \leq j-K_r+1 \\ t_j-t_i \leq \delta}} (D[i-1] + j - i + 1) \right\}. \quad (7)$$

The inner term is $j + \max_i (D[i-1] - i + 1)$ over a sliding interval of valid starts. A grouped sort, route slices, a moving left pointer, and a monotone deque give an $O(N \log N)$ evaluator including sorting. The frozen evaluator used for the reported results instead scans the full group array once per route and finds each left boundary by binary search. Its bound is $O(NR + \sum_r n_r \log n_r)$ for R routes and n_r events per route, which is quadratic in the worst case. This affects solver cost, not the returned optimum. Back-pointers recover a maximum-cardinality witness.

Exact clock. The implementation rounds releases and relative deadlines to integer nanoseconds and uses inclusive comparisons. The claim is exact on that clock. It does not rely on a floating tolerance. The implementation agrees with subset brute force on tiny instances, including route-specific thresholds and adversarial boundary cases.

Role in this paper. For fixed K and δ , the trace oracle is equivalent to selecting the maximum number of ordered points that can be partitioned into clusters of at

Algorithm 1 Equal-relative-deadline packing for one route

Require: sorted integer releases $t_1, \dots, t_n$, threshold K , deadline δ

- 1: $D[0] \leftarrow 0$; initialize empty monotone deque Q
- 2: **for** $j \leftarrow 1$ to n **do**
- 3: $D[j] \leftarrow D[j-1]$
- 4: $i \leftarrow j - K + 1$
- 5: **if** $i \geq 1$ **then**
- 6: insert $(i, D[i-1] - i + 1)$ into Q , removing smaller tails
- 7: $\ell \leftarrow \text{LOWERBOUND}(t, t_j - \delta)$
- 8: remove heads whose start index is smaller than ℓ
- 9: **if** Q is nonempty **then**
- 10: $D[j] \leftarrow \max(D[j], j + Q.\text{head.value})$
- 11: **return** $D[n]$

least K points and diameter at most δ . This is the fixed-radius decision form of one-dimensional r -gathering with outliers: related work often fixes an outlier budget and minimizes radius, whereas we fix the radius and maximize retained points [2, 3, 13]. Classical scheduling also studies compatible batching under release times and deadlines [4]. We use Equation (7) only as an exact trace oracle and make no algorithmic-priority claim.

5 Trace study

5.1 Pinned public source

The source is the complete `tau2_airline`, `tau2_retail`, and `tau2_telecom` subset of the public Exgentic agent-trace dataset. The dataset revision is 70036b93a04e61b0ea2706a68b962f4f26774587 and the Parquet conversion revision is f7c94012d0bfbf66fe4d6ed627699508bb555ff; all 19 retained shard hashes match commit-resolved URLs [10]. The domain labels correspond to the airline, retail, and telecom environments released with τ^2 -Bench [5], which builds on the original τ -bench framework [28]. The selected panel contains 851 sessions and 9,031 recorded LLM spans across four harnesses.

Each span completion becomes one candidate control event. Its route key is derived from the recorded outcome: final or text, error, one named tool, or a generic multi-tool outcome. It omits benchmark and harness semantics, state-machine node, schema and version, arguments, policy context, and the tool identities inside a multi-tool outcome. The extraction retains timestamps, public identifiers, counts, lengths, and route labels. It excludes prompt text, tool arguments, and tool results. Source Parquet files and both derived outputs are content-hashed.

The selected data contain 70 route labels. Eight labels occur in more than one benchmark domain, and 28 occur under more than one harness. The generic `tool:<multi>` label alone covers 325 spans and 122 distinct recorded

tool-name encodings. The source audit also retains 52 failed-status spans, 52 nonpositive-duration spans, and 617 overlapping span starts. We do not remove these observations after inspecting outcomes.

This construction treats a model completion as the point at which a control transition could become ready. The route key is a declared conditioning proxy, not proof of executable compatibility. The construction does not claim that the recorded harnesses implemented our transition or that their span durations equal model service times.

5.2 Stationary replay

We use the prospectively frozen stationary swarm model from trace replay 003. Session arrivals follow a homogeneous Poisson process. A session template is sampled uniformly from the fixed empirical panel. For target mean active population C , the arrival rate is C divided by mean template duration. Arrivals begin one maximum template duration before measurement so that the retained 60-second interval is in steady state under the model. Fixed partitions are origin-aligned half-open windows of width δ ; F is conditional on that phase, whereas P^* is not.

The exact-packing grid contains:

- $C \in \{1,000, 10,000, 100,000\}$;
- $\delta \in \{10, 25, 50, 100, 250\}$ ms;
- pooled, event-class, and route-key grouping;
- $K \in \{32, 64, 128, 256\}$; and
- three replay seeds from root seed 20260811.

Every generated event is retained. The three population values crossed with three seeds produce nine generated swarms. Reusing each swarm across deadlines, groupings, and thresholds yields 180 design cells and 540 cell-seed rows. For each row we compute F , P^* , U , the exact batch count, and

$$G = \frac{P^* - F}{U - F} \quad \text{when } U > F. \quad (8)$$

G describes how much of the local boundary-alignment opportunity is jointly packable. The reported primary G is the mean of the three per-seed ratios, not the ratio formed from three mean shares.

5.3 Prospective freeze and validity gates

The exact solver, integer-clock contract, inputs, grid, primary cell, and directional hypothesis were frozen before any exact trace outcome was computed according to the artifact-recorded chronology. The plan was not externally registered or independently timestamped. Earlier fixed-window and local-bound results were permitted design data. Five invariants gate interpretation: $F \leq P^* \leq U$; monotonicity under grouping coarsening; monotonicity with δ ; antitonicity with K ; and equality of all three shares whenever the previously computed lower and upper bounds coincide.

Frozen item	Value
Source	Exgentic tau2 panel, two commit hashes
Empirical unit	one of 851 session templates
Event	recorded LLM-span completion
Grouping	outcome-derived route-key proxy
Replay	stationary Poisson session arrivals
Clock	integer nanoseconds, inclusive endpoints
Capacity/service	unlimited / zero
Uncertainty	three seeds conditional on one panel

Table 3: Trace-study contract. The replay is a controlled load model rather than a model of production arrival statistics.

Quantity	Primary value
Fixed-partition share F	30.19%
Exact offline share P^*	43.00%
Local-overlap bound U	45.85%
Alignment-gap closure	81.83%
Mean generated events	651,123
Mean exact batches	1,046.3

Table 4: Prospectively frozen primary trace cell: 100,000 target active sessions, route-key grouping, $K = 256$, and a 50 ms launch deadline. Shares and counts are means over three replay seeds conditional on one fixed panel.

The primary cell was $C = 100,000$, route-key grouping, $K = 256$, and $\delta = 50$ ms. The directional pilot hypothesis was only $P^* > F$. The three seeds quantify Monte Carlo variation under one fixed panel and arrival model. They are not independent traces from a deployment population, so no population p -value or confidence interval is reported.

6 Trace-conditioned opportunity

All 540 cell-seed rows from nine generated swarms pass the five validity gates. In the prospectively frozen primary cell, the replay generates a mean of 651,123 events. Fixed windows admit 30.19%, while exact sliding-deadline packing admits 43.00%. The exact share ranges from 42.43% to 43.41% across the three seeds. The local bound is 45.85%.

Exact packing therefore gains 12.81 percentage points over the frozen partition and remains 2.85 points below the local upper bound. The mean of the per-seed gap closures is 81.83%. This distinction matters operationally: the fixed partition leaves model-admissible cross-boundary cohorts unused, while U still overcounts opportunities that cannot all be selected together.

6.1 Cohort supply collapses below the boundary

Under route-key grouping at $K = 256$, P^* is zero for every tested deadline when $C \leq 10,000$. Even at $C = 100,000$, it remains zero at 10 and 25 ms. Thus a large nominal swarm does not imply that a route sees a profitable cohort




Figure 2: Route-key-conditioned opportunity at $C = 100,000$ and $K = 256$. The prospectively frozen primary deadline is 50 ms. Values are means across three replay seeds conditional on one panel and one arrival model, not population confidence intervals.

inside a short launch budget.

Reducing K changes the boundary sharply. At $C = 10,000$ and 50 ms, P^* is 22.2% for $K = 32$ but 0.0% for $K = 64$. At $C = 100,000$ and 50 ms, the exact shares for $K = 32, 64, 128, 256$ are respectively 66.8%, 66.0%, 48.4%, and 43.0%. Lowering the hardware threshold can matter more than admitting another boundary-crossing cohort.

The surface gives an online runtime a measurable workload budget. Under the model, F is the fixed-window baseline, P^* is the most that any legal scheduler can attain, and $P^* - F$ is the headroom available to a better packing policy. A real implementation must measure its route-specific K and report how much of that headroom becomes achieved share A .

7 Device-resident decision study

The trace study measures cohort supply. This study isolates the second gate: the placement of a decision over state that is already resident on the GPU. It is a mechanism experiment rather than an implementation of trace-driven route compaction.

7.1 Matched mechanisms

The frozen CUDA program maintains a 16-byte synthetic state for each agent and two route bodies, represented by per-epoch pre-instantiated branch or path graph executables. At each epoch, a GPU predicate computes one global binary route decision. All mechanisms use the

same initialized state, predicate, route functions, block size, and implied route sequence.

Host round trip. Launch the predicate graph, copy its four-byte result to pinned host memory, synchronize, and launch the selected per-epoch route graph from the host.

Device resident. Launch one root graph. A one-thread selector reads the predicate on device and tail-launches one of the uploaded per-epoch path graphs. Each nonfinal path executes the selected body and the next predicate and selector, so execution continues for H epochs without exposing the decision to the host.

No-decision floor. Replay the oracle route sequence as one graph while omitting predicate and selection work. This mechanism is a structural floor, not an admissible online scheduler.

Graph creation, instantiation, and upload are outside steady-state timing for all mechanisms. State reset, result copy, and validation are also outside. The predicate copy and synchronization remain inside the host-roundtrip interval. The primary metric is cohort-horizon wall time per batched invocation, averaged within each recorded technical row.

7.2 Grid and independent unit

The full grid is $N \in \{256, 2048, 16384\}$ agents and $H \in \{2, 8, 32\}$ epochs. Each mechanism-cell has five warmups, three calibration samples, and 30 measured rows. One common batch count, calibrated from the fastest mechanism, is applied to all mechanisms in a cell; each row runs for at least 100 ms of aggregate timed work, subject to a frozen cap.

The four named placements are a local GTX 1660 Ti, a Modal L4, a RunPod L4, and a Lambda H100 SXM5. The CUDA source hash is `4b5cdcb9496a734bd7801d5c419efb8eceb72fd6962800520101e89676d204da`. Provider receipts, device UUIDs, images, binaries, raw files, and manifests are bound where provider interfaces permit.

A named placement is the outer performance unit. Thirty rows reduce technical timing noise inside one placement and are not independent hardware replications. Effect magnitudes and directions are therefore reported by placement, with L4 $n = 2$, H100 $n = 1$, and GTX $n = 1$.

7.3 Correctness contract

A separately written host implementation computes both route functions and the predicate without calling the device transition functions. After every batched invocation, the experiment compares all four fields of every final agent state. It also compares the complete epoch-by-epoch decision trace for the host and resident mechanisms. Any mismatch, illegal launch, setup error, OOM, crash, or nonpositive timing blocks performance interpretation.

The no-decision floor receives the oracle route sequence by construction. Its final state is checked independently, but its decision sequence is not an independent observation. This is why the paper reports admissible-mechanism correctness separately from total tested work.

7.4 Prospective-plan deviations

A bounded local engineering smoke preceded the freeze. The full local run used the same physical GPU shortly afterward. The prospectively frozen bounded cloud stage allowed Modal plus one of RunPod or Lambda; the final report retains both external providers as a descriptive scope expansion, one placement beyond the frozen first-stage count. Neither fact strengthens the sampling claim.

The primary directional cell was $N = 256, H = 32$. Horizon scaling is reported as an exploratory diagnostic because “advantage increases” was not given a complete operational definition before the run.

8 Mechanism results

All 3,240 measured rows pass the frozen status, timing, duration, source, provider, and correctness gates. Across the two admissible mechanisms, 14,557,440 tested batched invocations are field-exact and decision-exact against the host oracle.

The device-resident path has a lower within-placement median than the host round trip in all 36 placement-cells. The ratios range from $1.19\times$ to $2.39\times$. At the primary $N = 256, H = 32$ cell, the named-placement ratios are $1.71\times$ on the local GTX 1660 Ti, $2.39\times$ on the Modal L4, $2.06\times$ on the RunPod L4, and $1.84\times$ on the Lambda H100.

At that cell, the device path takes 258 to 309 μs across the four named placements, compared with 467 to 625 μs for the host round trip. The absolute difference is 194 to 363 μs per 32-epoch cohort invocation. The device path is still $6.60\times$ to $8.17\times$ slower than the oracle floor. This undecomposed gap combines predicate, selector, and graph overhead, which remains large beside the synthetic route bodies.

8.1 Negative device-launch control

The earlier native-dispatch calibration compares a pre-instantiated graph launched from the host with a fixed child graph launched from a GPU kernel. The child path retains the host root launch, adds a launcher kernel, and removes no host decision. Across 5 named placements and all 60 cells, it is slower. The ratio of within-placement wall-time medians ranges from $1.07\times$ to $1.99\times$. All 12,000 rows are field-exact.

This negative control separates device residency from device launch. Adding a nested launcher while removing no host decision produces overhead rather than an alternative positive treatment.

The timed comparison isolates one control-path choice. Cold graph construction, ingress, effect egress, validation, and a tuned CPU implementation of a real route body enter the joined runtime evaluation in Section 9.





Figure 3: Within-placement ratio of batch-average row medians for the host round trip over the device-resident mechanism. Ratios above one favor the resident path. Placement is the outer unit; the plotted rows are technical repetitions rather than invocation-tail samples.

Provider	GPU	Ratio	Resident (μs)	Host (μs)	Floor (μs)
Local	GTX 1660 Ti	$1.71\times$	273.0	467.2	33.4
Modal	L4	$2.39\times$	261.9	625.3	39.7
RunPod	L4	$2.06\times$	258.3	533.3	37.3
Lambda	H100 SXM5	$1.84\times$	309.0	567.5	45.6

Table 5: Primary resident-policy cell, $N = 256, H = 32$. Times are medians of batch-average cohort-horizon wall time. The floor omits runtime predicate and selection work and is not a legal online policy.



Primary cell: $N=256, H=32$. The oracle floor removes predicate and selection work.

Figure 4: The three mechanisms at the primary cell. Device residency removes a matched host observation and dispatch epoch. The oracle floor removes the decision itself, so it is diagnostic rather than deployable.

9 Joining the evidence

The two studies define a staged systems test. Cohort supply determines whether any legal scheduler can find enough same-group work before launch deadlines. Observation placement determines whether an already resident decision chain pays a host copy, synchronization, branch, and redispach epoch. A proposed GPU route service must pass both gates. Failure at either gate is a concrete reason to keep that transition on the CPU.

The current numbers do not form a service-level acceleration estimate and must not be multiplied. The trace study sweeps candidate thresholds, while the resident study fixes three cohort sizes and a synthetic route body. The trace also contains no measurement that 32 consecutive control epochs can execute without a model, tool, policy, or commit observation. The value of the separation is that each missing quantity now has a named measurement rather than being hidden inside a broad GPU-agent claim.

9.1 The next systems test

The runtime implied by the boundary is a finite-capacity online route compactor. It receives typed completion events, updates compact state, queues events by a verified executable route and deadline, launches a route only above its measured safe-suffix threshold K_r , and falls back

to a tuned CPU path when a deadline or capacity limit prevents batching. The GPU may emit ordered effect descriptors; a privileged CPU or DPU remains the authority for external effects.

Such a system adds one essential quantity. Let $z_i = 1$ only when the frozen online policy accelerates event i with an exact output and observed device start no later than its launch deadline; otherwise $z_i = 0$. Then

$$A = \frac{1}{|E|} \sum_{i \in E} z_i. \quad (9)$$

Late, missing, failed, and fallback events have $z_i = 0$ and remain in E . The opportunity recovery above fixed windows is

$$R_A = \frac{A - F}{P^* - F}, \quad (10)$$

when $P^* > F$. This turns the offline result into a direct runtime target. A credible evaluation pairs A and R_A with raw invocation P99, deadline misses, CPU core-seconds per event, exact trajectories, task utility, network bytes, cost, and, for a shared inference GPU, TTFT and TPOT guardrails.

9.2 Deployment paths

The strongest architecture is a regional route service that aggregates typed events from many inference and tool workers. Aggregation attacks the cohort supply problem directly; measured ingress, state movement, and effect egress then determine whether the control-path savings survive the network boundary. A second path uses a low-priority queue on an inference GPU that is already allocated. Its economic advantage is marginal device cost, while its decisive constraint is noninterference with model TTFT and TPOT.

A dedicated control GPU is the weakest starting point because the present experiments do not establish enough utilization or CPU displacement to pay for one. GPU-initiated VM lifecycle operations are also outside the transition unit: a device can emit a typed prewarm request, but a privileged CPU or DPU control plane must authorize and commit it.

10 Related work

GPU state machines and device-side control. FLAME GPU 2 maps agent memory, state transitions, population partitioning, and communication to GPUs [21]. CUDA Graphs provide replay, conditional nodes, and device graph launch [20]. GPUOS uses a persistent GPU worker kernel and atomic queues fed from a host-managed work queue [27]; MPK and Event Tensor compile tensor task graphs into persistent megakernels [8, 14]. These systems provide mechanisms for device-side control and launch amortization. Our measurements ask a different question: whether agent traces supply enough work under

a declared grouping before launch deadlines, and what one matched host observation costs.

Agent and compound-AI serving. A production and open-source characterization by Yang et al. identifies repeated CPU–GPU crossings, host orchestration on the critical path, and bursty CPU demand in agentic workflows; its Agora prototype pools and schedules CPU resources while oversubscribing GPU memory [26]. ThunderAgent represents workflows as LLM Programs and jointly manages KV caches, system state, and tool environments with a program-aware scheduler [15]. Parrot exposes semantic variables and application dataflow for cross-request optimization [17]. Agentix schedules agent programs using execution progress [19]; SAGA uses KV-cache-aware execution graphs and session-affinity batching [11]; and InferCept manages inference state across pauses for external interactions [1]. Murakkab jointly maps declarative workflow components to models and hardware under SLOs [7]. The MARS preprint coordinates GPU inference and CPU tool execution through an external control plane [24]; the concurrent OpRAG preprint uses persistent workers, bounded queues, and batched GPU operators for multi-stage RAG [23]. AgentServe co-schedules multi-agent inference on one GPU [29]. These systems operate at model-call, tool, or workflow granularity. Our unit is the deterministic transition after a model or tool event has completed.

Non-model CPU and GPU placement. Agentic CPU-GPU Scheduling profiles a complete AI tool and selects immediate GPU, queued GPU, or CPU execution [18]. TokTier moves stateful tokenization across CPU and GPU while enforcing exact token identity [30]. Measurements of CPU-induced LLM slowdowns show that CPU starvation can delay launches, communication, and tokenization even with CUDA Graphs, and that adding CPU cores can be the economical remedy [9]. These are the closest tool-level and methodological comparisons. They make a tuned CPU implementation and CPU provisioning mandatory baselines for the proposed online runtime.

Batching and clustering. Classical real-time scheduling studies job families, time windows, and compatible batching [4]. Joint batching work addresses heterogeneous asynchronous arrivals and deadlines [6], while serial-batch scheduling includes minimum batch size, job families, and release times [12]. One-dimensional r -gathering studies minimum-occupancy clusters, outliers, contiguous solutions, and exact line algorithms [2, 3, 13, 22]. Univariate microaggregation with suppression supplies another dynamic-programming analogue [16]. GPU dynamic batching has also been modeled with batch-dependent service, stochastic arrivals, latency, and power [25]. The recurrence in this paper is a restricted trace oracle inside that established territory, not an algorithmic-priority claim.

Positioning. Prior agent systems characterize serving, scheduling, state management, and tool execution, while batching theory characterizes which arrivals can be served together under timing and occupancy constraints. The supply of route-key-conditioned post-event transitions above a hardware crossover lies at their interface. Observation placement adds the second axis: a cohort may exist, yet a host round trip can still dominate a short control chain. This paper gives those axes common boundary quantities and measures each with a separate, auditable experiment.

11 Scope of inference

Model and evidence join. The trace threshold is a swept candidate rather than the measured crossover of the resident-policy source, and the mechanism’s $H = 32$ horizon is absent from the trace model. The two result sets therefore cannot be multiplied. The offline optimum also assumes future knowledge, zero service time, unlimited capacity, no upper batch size, and deadlines on launch rather than completion. The safe-suffix abstraction extrapolates beyond tested cohort sizes and does not cover non-monotone benefit, arbitrary deadlines, or batch-size-dependent service.

Trace scope and executable identity. The replay conditions on one 851-session panel from three related customer-service domains and imposes stationary Poisson arrivals. Its three seeds measure Monte Carlo variation under that panel and model, not a workload population. Bursts, correlated releases, and other corpora can move the boundary. The outcome-derived route key omits state-machine node, schema, arguments, policy context, and multi-tool identities, so it is a conditioning proxy rather than verified semantic fusion. The packing arrays also omit a per-session sequence constraint; overlapping spans and completion-order inversions can affect the wider deadline surface.

Mechanism and sampling scope. Resident-policy-001 makes one global binary decision over a regular synthetic state array. A route service still needs per-event compaction, variable route bodies, ingress and egress, effect ordering, recovery, and CPU fallback. Setup, state reset, result copy, and validation are outside timing. The four named placements comprise two L4s, one H100, and one GTX; GPU, provider, host, image, driver, and region are confounded. The local full run reuses the development GPU, and one external placement extends the frozen first-stage scope. Timing rows are technical repetitions, so the current performance result supports named-placement effect sizes rather than a hardware-population inference.

Deployment and algorithmic scope. The mechanism metric is batch-average cohort-horizon wall time,

not invocation P99 or end-to-end task time. A tuned CPU implementation of the real transition, CPU core-seconds, energy, cost, model throughput, TTFT, TPOT, task utility, and external-effect reliability remain deployment measurements. The dynamic program is a specialized exact instrument within mature batching, clustering, and scheduling literatures; the paper makes no exhaustive algorithmic priority claim.

12 Reproducibility

The public code and release materials are at <https://github.com/josefchen/ready-cohorts>. A processed-evidence mirror is at <https://huggingface.co/datasets/josefchen/ready-cohorts>.

Raw measurements, processed tables, analysis code, preregistrations, and paper outputs are separate artifacts. New executions receive new experiment and placement identities; analysis does not overwrite a prior raw run.

All numerical macros and primary tables in the manuscript are generated by `scripts/build_paper_artifacts.py`. The generator validates declared hashes for the trace summary, repetition rows, and source dependencies, including all 19 local Parquet shards; it also validates the resident-policy contrasts and cell summary, and the native-dispatch contrasts. It checks the primary cell, selected row and placement counts, the pointwise boundary invariant, recorded trace-gate flags, and directional inequalities before emitting a machine-readable paper-data manifest. Session and span counts come from the source manifest rather than manuscript constants. This build validates retained and processed evidence; it does not rerun cloud experiments or repeat the remote retrieval.

The source manifest binds the trace extraction to dataset commit `70036b93a04e61b0ea2706a68b962f4f26774587` and Parquet conversion commit `f7c94012d0bfbf66fe4d6ed627699508bbb555ff`. The SHA-256 values of all 19 local shards match both the manifest and the commit-resolved remote bytes. Derived features retain timestamps, counts, lengths, route labels, and public identifiers, but no prompt text, tool arguments, or tool results.

The retained figures are hash-bound to their source table, notebook, and notebook-builder script. They are not regenerated by the LaTeX target. The claim-evidence map links the headline claims to proofs or artifacts. Placement is the performance sampling unit; timing rows and batched invocations remain technical repetitions.

For the packing result, the artifact separates the recurrence’s attainable $O(N \log N)$ grouped implementation from the frozen evaluator used here. The frozen code rescans the full grouping array once per route and performs a binary boundary search per event, for $O(NR + \sum_r n_r \log n_r)$ time in the stated accounting. Integer nanosecond normalization and brute-force tiny-instance tests define its exactness contract.

From the repository root, the manuscript is rebuilt and checked with:

```
make -C paper/arxiv clean all
.venv/bin/python scripts/check_arxiv_paper.py
```

Generative AI disclosure. OpenAI Codex assisted with implementation, experiment orchestration, literature search, quantitative checks, adversarial review, and language editing. Reported numbers are regenerated from retained artifacts, and citations are checked against primary sources. The author remains responsible for the scientific claims and the released artifact.

13 Conclusion

The ready-cohort boundary turns GPU agent control into a falsifiable systems question. A workload must supply enough same-group events before their launch deadlines, and the control path must account for where intermediate decisions are observed. Under the frozen trace model, exact sliding-deadline packing raises eligible share from 30.19% to 43.00%, recovering 81.83% of the opportunity lost by fixed windows. The full surface also shows where cohort supply collapses to zero.

The mechanism study establishes the second gate. Keeping the tested binary decision on device reduces cohort-horizon wall time in all 36 cells across four named placements, with ratios from $1.19\times$ to $2.39\times$. A nested device graph that removes no host decision loses in all 60 cells across five placements. Device launch alone is therefore insufficient; the gain appears only in the treatment that removes the matched host-mediated decision epoch.

These results provide the workload budget and the mechanism test for an online route compactor. Its decisive measurements are achieved share A relative to F and P^* , raw P99, CPU core-seconds, exact effects, task utility, cost, and shared-inference guardrails. If it cannot convert offline headroom into online work or displace CPU without harming model service, the boundary rejects the GPU design. If it can, the same quantities show exactly where GPU-resident agent control belongs in a datacenter.

References

- [1] Reyna Abhyankar, Zijian He, Vikranth Srivatsa, Hao Zhang, and Yiyang Zhang. Infercept: Efficient intercept support for augmented large language model inference. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pages 81–95. PMLR, 2024. URL <https://proceedings.mlr.press/v235/abhyankar24a.html>.
- [2] Gagan Aggarwal, Tomás Feder, Krishnaram Kenthapadi, Samir Khuller, Rina Panigrahy, Dilys Thomas,

- and An Zhu. Achieving anonymity via clustering. *ACM Transactions on Algorithms*, 6(3):1–19, 2010. doi: 10.1145/1798596.1798602. URL <https://doi.org/10.1145/1798596.1798602>.
- [3] Toshihiro Akagi and Shin ichi Nakano. On r -gatherings on the line. In *Frontiers in Algorithmics*, volume 9130 of *Lecture Notes in Computer Science*, pages 25–32. Springer, 2015. doi: 10.1007/978-3-319-19647-3_3. URL https://doi.org/10.1007/978-3-319-19647-3_3.
- [4] Amotz Bar-Noy, Sudipto Guha, Yoav Katz, Joseph Naor, Baruch Schieber, and Hadas Shachnai. Throughput maximization of real-time scheduling with batching. *ACM Transactions on Algorithms*, 5(2):18:1–18:17, 2009. doi: 10.1145/1497290.1497294. URL <https://doi.org/10.1145/1497290.1497294>.
- [5] Victor Barres, Honghua Dong, Soham Ray, Xujie Si, and Karthik Narasimhan. τ^2 -Bench: Evaluating conversational agents in a dual-control environment. In *Proceedings of the 43rd International Conference on Machine Learning*, volume 306 of *Proceedings of Machine Learning Research*. PMLR, 2026. URL <https://openreview.net/forum?id=OC2z7iSQKa>.
- [6] Yi Han Cang, Ming Chen, and Kaibin Huang. Joint batching and scheduling for high-throughput multiuser edge AI with asynchronous task arrivals. *IEEE Transactions on Wireless Communications*, 23(10):13782–13795, 2024. doi: 10.1109/TWC.2024.3404811. URL <https://doi.org/10.1109/TWC.2024.3404811>.
- [7] Gohar Irfan Chaudhry, Esha Choukse, Haoran Qiu, Inigo Goiri, Rodrigo Fonseca, Adam Belay, and Riccardo Bianchini. Murakkab: Resource-efficient agentic workflow orchestration in cloud platforms. In *20th USENIX Symposium on Operating Systems Design and Implementation (OSDI 26)*, pages 567–587, Seattle, WA, July 2026. USENIX Association. URL <https://www.usenix.org/conference/osdi26/presentation/chaudhry>.
- [8] Xinhao Cheng, Zhihao Zhang, Yu Zhou, Jianan Ji, Jincheng Jiang, Zepeng Zhao, Ziruo Xiao, Zihao Ye, Yingyi Huang, Ruihang Lai, Hongyi Jin, Bohan Hou, Mengdi Wu, Yixin Dong, Anthony Yip, Songting Wang, Wenqin Yang, Xupeng Miao, Tianqi Chen, and Zhihao Jia. MPK: A compiler and runtime for Mega-Kernelizing tensor programs. In *20th USENIX Symposium on Operating Systems Design and Implementation (OSDI 26)*, pages 1909–1926, Seattle, WA, July 2026. USENIX Association. ISBN 978-1-939133-55-7. URL <https://www.usenix.org/conference/osdi26/presentation/cheng>.
- [9] Euijun Chung, Yuxiao Jia, Aaron Jezghani, and Hyesoon Kim. Characterizing CPU-induced slowdowns in multi-GPU LLM inference, 2026. URL <https://arxiv.org/abs/2603.22774>.
- [10] Exgentic. Multi-benchmark LLM agent traces. Hugging Face dataset, 2026. URL <https://huggingface.co/datasets/Exgentic/agent-llm-traces/tree/f7c94012d0bfbf66fe4d6ed627699508bbb555ff>. Revision 70036b93a04e61b0ea2706a68b962f4f26774587; CDLA-Permissive-2.0; accessed 2026-08-12.
- [11] Dongxin Guo, Jikun Wu, and Siu Ming Yiu. SAGA: Workflow-atomic scheduling for AI agent inference on GPU clusters, 2026. URL <https://arxiv.org/abs/2605.00528>.
- [12] Jorge A. Huertas and Pascal Van Hentenryck. Constraint programming models for serial batch scheduling with minimum batch size. *Operations Research Perspectives*, 15:100352, 2025. doi: 10.1016/j.orp.2025.100352. URL <https://doi.org/10.1016/j.orp.2025.100352>.
- [13] Shin ichi Nakano. A simple algorithm for r -gatherings on the line. *Journal of Graph Algorithms and Applications*, 23(5):837–845, 2019. doi: 10.7155/jgaa.00514. URL <https://doi.org/10.7155/jgaa.00514>.
- [14] Hongyi Jin, Bohan Hou, Guan jie Wang, Ruihang Lai, Jinqi Chen, Zihao Ye, Yaxing Cai, Yixin Dong, Xinhao Cheng, Zhihao Zhang, Yilong Zhao, Yingyi Huang, Lijie Yang, Jincheng Jiang, Gabriele Oliaro, Jianan Ji, Xupeng Miao, Vinod Grover, Todd C. Mowry, Zhihao Jia, and Tianqi Chen. Event tensor: A unified abstraction for compiling dynamic megakernel. In *Proceedings of Machine Learning and Systems*, volume 8, pages 1917–1933. MLSys, 2026. URL https://proceedings.mlsys.org/paper_files/paper/2026/file/53d3f45797970d323bd8a0d379c525aa-Paper-Conference.pdf.
- [15] Hao Kang, Ziyang Li, Weili Xu, Xinyu Yang, Yinfang Chen, Junxiong Wang, Beidi Chen, Tushar Krishna, Chenfeng Xu, and Simran Arora. ThunderAgent: A simple, fast and program-aware agentic inference system, 2026. URL <https://arxiv.org/abs/2602.13692>.
- [16] Michael J. Laszlo and Sumitra Mukherjee. Optimal univariate microaggregation with data suppression. *Journal of Systems and Software*, 86(3):677–682, 2013. doi: 10.1016/j.jss.2012.10.901. URL <https://doi.org/10.1016/j.jss.2012.10.901>.
- [17] Chaofan Lin, Zhenhua Han, Chengruidong Zhang, Yuqing Yang, Fan Yang, Chen Chen, and Lili Qiu. Parrot: Efficient serving of LLM-based applications with semantic variable. In *18th USENIX Symposium*

- on *Operating Systems Design and Implementation (OSDI 24)*, pages 929–945, Santa Clara, CA, July 2024. USENIX Association. ISBN 978-1-939133-40-3. URL <https://www.usenix.org/conference/osdi24/presentation/lin-chaofan>.
- [18] Tianxi Lu and Sherief Reda. Agentic CPU-GPU scheduling for heterogeneous AI workloads, 2026. URL <https://arxiv.org/abs/2607.22242>.
- [19] Michael Luo, Xiaoxiang Shi, Colin Cai, Tianjun Zhang, Justin Wong, Yichuan Wang, Chi Wang, Yanping Huang, Zhifeng Chen, Joseph E. Gonzalez, and Ion Stoica. Agentix: An efficient serving engine for LLM agents as general programs. In *23rd USENIX Symposium on Networked Systems Design and Implementation (NSDI 26)*, pages 2443–2459, Renton, WA, May 2026. USENIX Association. ISBN 978-1-939133-54-0. URL <https://www.usenix.org/conference/nsdi26/presentation/luo>.
- [20] *CUDA Programming Guide*. NVIDIA Corporation, 2026. URL <https://docs.nvidia.com/cuda/cuda-programming-guide/04-special-topics/cuda-graphs.html>. Chapter 4.2, CUDA Graphs; accessed 2026-08-12.
- [21] Paul Richmond, Robert Chisholm, Peter Heywood, Mozghan Kabiri Chimeh, and Matthew Leach. FLAME GPU 2: A framework for flexible and performant agent based simulation on GPUs. *Software: Practice and Experience*, 53(8):1659–1680, 2023. doi: 10.1002/spe.3207. URL <https://doi.org/10.1002/spe.3207>.
- [22] Anik Sarker, Wing-Kin Sung, and M. Sohel Rahman. A linear time algorithm for the r -gathering problem on the line. *Theoretical Computer Science*, 866:96–106, 2021. doi: 10.1016/j.tcs.2021.03.015. URL <https://doi.org/10.1016/j.tcs.2021.03.015>.
- [23] Arup Kumar Sarker, Mills Staylor, Aymen Alsaadi, Gregor von Laszewski, Shantenu Jha, and Geoffrey Fox. OpRAG: A resource-deterministic runtime for gpu-backed multi-stage RAG workflows, 2026. URL <https://arxiv.org/abs/2608.08340>.
- [24] Yifei Wang, Hancheng Ye, Yechen Xu, Cong Guo, Chiyue Wei, Qinsi Wang, Dongting Li, Tingjun Chen, Hai Li, Danyang Zhuo, and Yiran Chen. MARS: Efficient, adaptive co-scheduling for heterogeneous agentic systems, 2026. URL <https://arxiv.org/abs/2604.26963>.
- [25] Yaodan Xu, Jingzhou Sun, Sheng Zhou, and Zhisheng Niu. SMDP-based dynamic batching for efficient inference on GPU-based platforms. In *2023 IEEE International Conference on Communications (ICC)*, pages 5483–5489. IEEE, 2023. doi: 10.1109/ICC45041.2023.10278962. URL <https://doi.org/10.1109/ICC45041.2023.10278962>.
- [26] Jirong Yang, Peizhe Liu, Chaojie Zhang, and Jovan Stojkovic. Architectural implications of agentic AI workflows, 2026. URL <https://arxiv.org/abs/2608.04458>.
- [27] Yiwei Yang, Xiangyu Gao, Yuan Zhou, Yuhang Gan, Yusheng Zheng, and Andi Quinn. GPUOS: A GPU operating system primitive for transparent operation fusion, 2026. URL <https://arxiv.org/abs/2604.17861>.
- [28] Shunyu Yao, Noah Shinn, Pedram Razavi, and Karthik Narasimhan. τ -bench: A benchmark for tool-agent-user interaction in real-world domains, 2024. URL <https://arxiv.org/abs/2406.12045>.
- [29] Yuning Zhang, Yan Yan, Nan Yang, and Dong Yuan. AgentServe: Algorithm-system co-design for efficient agentic AI serving on a consumer-grade GPU, 2026. URL <https://arxiv.org/abs/2603.10342>.
- [30] Zhenyu Zhang and Zhichao Cao. TokTier: Exact stateful CPU+GPU tokenization for agentic LLM serving, 2026. URL <https://arxiv.org/abs/2607.29678>.

A Proof and evaluator scope

A.1 Binary-program reference formulation

For arbitrary deadlines under the same zero-service and unlimited-capacity assumptions, candidate launch times may be restricted to unique deadlines by Proposition 2. Let $x_{i\tau}$ assign event i to deadline τ , let $y_{r\tau}$ indicate a batch for route r , and let $M_{r\tau}$ be the number of route- r event intervals containing τ . One reference formulation is

$$\max \sum_i \sum_{\tau} x_{i\tau} \quad (11)$$

$$\text{s.t.} \quad \sum_{\tau} x_{i\tau} \leq 1 \quad \forall i, \quad (12)$$

$$x_{i\tau} = 0 \quad \text{if } \tau \notin [t_i, d_i], \quad (13)$$

$$K_r y_{r\tau} \leq \sum_{i:r_i=r} x_{i\tau} \quad \forall r, \tau, \quad (14)$$

$$\sum_{i:r_i=r} x_{i\tau} \leq M_{r\tau} y_{r\tau} \quad \forall r, \tau, \quad (15)$$

$$x_{i\tau}, y_{r\tau} \in \{0, 1\}. \quad (16)$$

The objective does not minimize batch count or wait among maximum-cardinality schedules. The reported equal-deadline evaluator avoids this quadratic candidate assignment and returns one witness.

B Evidence inventory

Layer	Current evidence and outer unit	Admissible inference
Route-key trace packing	Replay-seed unit conditional on one panel; 540 cell-seed rows from nine swarms; all invariants pass	Conditional opportunity surface
Primary trace cell	Same outer unit; $F = 30.19\%$, $P^* = 43.00\%$, $U = 45.85\%$	Exact offline share under the model
Resident decision	Named-placement unit; four placements and 36 directional cells	Named-placement effect direction and size
Exactness stress	Tested-batched-invocation unit; 14,557,440 admissible-mechanism invocations	Exactness on tested invocations
Nested launch	Named-placement unit; five placements and 60 negative cells	Fixed nested-launch calibration

Table 6: Evidence layers, outer units, and admissible inference. Population and end-to-end claims require the joined confirmation design.

C Protocol deviations

Resident policy.

1. A correctness and engineering smoke preceded the source freeze. The smoke and full local run used the same GPU UUID and are not independent placements.
2. The cloud protocol authorized Modal plus one of RunPod or Lambda. Both external placements were ultimately retained. The additional placement is a disclosed descriptive scope expansion.
3. Horizon-ratio monotonicity is exploratory because the preregistration did not fully specify its operational test.
4. No unsupported account of failed Lambda provisioning attempts is used as scientific evidence. Retained receipts support the successful execution and final resource absence.

Native dispatch. The native-dispatch plan proposed two fresh placements per available provider/SKU and at least six H100 placements for nuisance estimation. That layout was not completed. The retained calibration contains five named placements, including one H100, three L4s, and one GTX, and supports only the descriptive negative result reported here.