arXiv:2610.25916v1 [cs.CR] 19 Oct 2026

Secure Agentic Coding through Counterexample-Grounded Feedback

Tue Le[1] Anh Nguyen Hoang[1] Gabriel Sasseville[2,3]
Doseok Jang[2,3] Pierre-Luc Bacon[2,3] Nghi D. Q. Bui[4,†]

[1] Quantum AI & Cyber Security Institute (QACI), FPT Corporation
[2] Mila - Quebec Artificial Intelligence Institute
[3] Université de Montréal [4] Google

Abstract

As coding models and agent harnesses become more capable, reliable security verification is becoming a central bottleneck. Improving secure code generation requires a signal whose reported progress remains aligned with actual program behavior under optimization; otherwise, an optimizer can improve the signal's verdict without removing the underlying vulnerability. Existing model-based approaches require models to either infer program behavior from source code or specify correct outcomes for adversarial tests, placing substantial reasoning demands on the security signal. We introduce FALCON, a counterexample-grounded verification framework that separates attack exploration from behavioral verification and connects them through execution traces of the program under test. In test-time repair, FALCON yields substantially stronger held-out functional-security gains than alternative security signals across secure code generation benchmarks, while preserving or improving functionality. As an RL reward, FALCON also outperforms static-analysis and learned rewards on held-out functional-security, even when all policies successfully optimize their respective training rewards. Combining FALCON with either proxy reward further improves held-out performance, suggesting that execution-grounded feedback can mitigate reward overoptimization while preserving useful guidance from existing security signals.

Code: https://github.com/FSoft-AI4Code/FALCON.
Project: https://falcon-secure.github.io/

1 Introduction

Coding agents now edit real repositories, navigating projects and running commands to validate their work [11, 22, 62], yet patches that pass functional tests can still contain security vulnerabilities [7, 43, 65]. Reliable security feedback is therefore essential both for evaluating generated code and for improving it through test-time repair [8, 35, 52] or reinforcement learning [19, 34, 53, 60, 63].

[†]Work done while at FPT.

In both settings, improving the feedback signal must translate into safer program behavior; otherwise, optimization may reward edits that satisfy the signal without removing vulnerabilities. Providing such feedback requires both inputs that expose unsafe behavior and reliable criteria for judging the resulting executions, which are often unavailable for generated code.

Existing automated security signals rely on different forms of evidence. Static analyzers apply predefined rules and program abstractions [4, 15, 44, 48, 53, 63], but may miss vulnerabilities beyond the behaviors their analyses capture [3, 55]. Learned detectors and source-code LLM judges infer vulnerabilities without observing executions [12, 54, 64, 66]. Attacker-generated tests execute the program, but model-generated oracles can capture actual rather than intended behavior [25]. As Figure 1(a) illustrates, these model-based approaches place substantial reasoning demands on the model: a source-code judge must infer behavior and assess its security implications, while a test generator must both discover adversarial inputs and specify correct outcomes. Errors in these judgments can allow a candidate to satisfy the feedback signal while retaining unsafe behavior. This motivates a narrower judgment task grounded in observed execution.

We introduce FALCON, a verification framework designed to reduce the reasoning demand of security judgment through two narrower processes: **exploration** and **verification** (Figure 1(b)). Given a candidate program, the attacker generates deterministic Proof-of-Concept probes: executable scripts that invoke the target with adversarial inputs or a crafted environment, without specifying expected outputs or verdicts. The verifier judges their execution traces against security requirements, separating attack discovery from judgment of observed behavior. However, the attacker may generate probes that manipulate the execution by replacing the target function or directly performing the sensitive operation they are supposed to test. Such probes can create an apparent violation even when the code under test is secure. FALCON therefore applies faithfulness checks to reject these probes and require evidence that the target code produced the reported behavior.



Figure 1 Comparison with prior security assessment approaches. (a) *Source-code judges* must infer program behavior and assess security, while *test generators* must propose inputs and define correct expected outcomes. Both place substantial reasoning demands on the model. (b) FALCON reduces the reasoning demand of security judgment by separating attack exploration from verification and connecting them through an execution process that produces concrete traces for the verifier.

We evaluate whether FALCON provides reliable feedback under optimization. In a repair loop on CWEval [43], four security signals guide the same coding model with ground-truth tests hidden. All report progress, but their held-out outcomes differ: FALCON improves FUNC-SEC@1 by 25.2 points, while LLM-as-a-judge and attacker-only feedback yield almost no improvement or a decline, and CodeQL [15] yields smaller gains. Thus, satisfying a security signal does not

necessarily improve independently evaluated security. Further experiments show gains across coding models on CWEval and SecCodeBench-V2 [7], and across three coding-agent harnesses on SusVibes [65], with functionality largely preserved or improved. As an RL reward, FALCON outperforms REAL [63] and SecCodePRM [64] on held-out FUNC-SEC@1 at both model scales. Interestingly, combining FALCON with either reward further improves held-out performance over either component alone, suggesting that execution-grounded feedback can mitigate reward overoptimization while retaining useful guidance from the original proxy rewards.

Our main contributions are:

- We show that reported security progress can diverge from held-out functional-security under both iterative test-time repair and reinforcement learning, motivating evaluation of security signals under optimization.
- We introduce FALCON, a verification framework designed to reduce reasoning demands by separating attack generation from behavioral judgment and grounding verification in replayable execution evidence attributable to the code under test.
- We demonstrate that FALCON improves secure code generation across benchmarks, coding models, and agent harnesses. As an RL reward, it improves held-out performance both independently and in combination with static-analysis or learned rewards.

2 Related Work

Secure Code Generation. LLMs are strong code generators [6, 11, 17, 22, 28, 67], increasingly at repository scale [20, 29, 30], yet generated code can remain vulnerable [9, 37, 46, 58]. Prior work improves security through security-aware data and tuning [18, 19, 32, 45, 57], RL with static or learned rewards [34, 53, 60, 63], and inference-time prompting or repair [5, 13, 24, 38]. AutoSafeCoder combines static review with fuzzing [40]; SCGAgent couples security guidelines with generated functional tests [47].

Vulnerability Detection. Static analyzers are efficient but can produce false positives or miss semantic vulnerabilities [3, 55]. Learned detectors and LLM judges are more flexible but remain sensitive to data, prompts, and context [12, 54, 60, 64, 66]. Dynamic methods rely on execution, through taint analysis, sanitizers, fuzzing, or security tests [7, 36, 39, 43, 49], but depend on inputs that expose the vulnerability. AutoSafeCoder adds fuzzing to LLM code generation [40], while BlueCodeAgent verifies reported vulnerabilities with sandboxed tests [16]. FALCON generates attack probes without expected outputs, filters unfaithful evidence, and verifies the resulting execution traces.

Security Signals and AI Safety. Reliable security feedback relates to AI-safety concerns about reward hacking and scalable oversight [1, 31]. Optimizing a proxy can degrade the intended objective [14, 23]. Execution feedback supports functional correctness in code models [8, 26, 27, 30, 33, 59] and repository-level agent training and verification [42], while security additionally requires adversarial inputs and runtime violation checks.



Figure 2 Overview of FALCON. The attacker generates deterministic PoC probes targeting code produced by the coding agent. The faithfulness check rejects probes that shadow the target or fabricate the apparent violation. Admitted probes execute in a sandbox, and a three-stage verifier evaluates the resulting traces using a crash oracle, deterministic CWE detectors, and an LLM trace judge for unresolved cases.

3 FALCON: Counterexample-Grounded Verification Framework

3.1 Problem Setting

A coding task T is defined over a workspace R containing the project files available to the agent. The agent produces a candidate patch p, and R_p denotes the workspace after applying that patch. FALCON evaluates the resulting program in R_p, rather than inspecting the patch text alone.

Within R_p, an *attack target* s is a function, method, or class selected for testing, and a *probe* q is a script that attacks one such target. Executing the probe in a sandbox produces a trace

$$\tau_q = \mathrm{Exec}(R_p, q), \tag{1}$$

which records execution information such as the input, return value, exceptions, security-relevant side effects, and call stacks.

3.2 Design Principles

Exploration and Verification. We reduce the reasoning demands of source-code security judgment by separating attack exploration from verification (Figure 2). Given a candidate program R_p, the attacker proposes PoC probes without expected outcomes or verdicts. Each admitted probe executes against R_p, producing a concrete trace that the verifier checks for security violations. Execution thus lets each component address a narrower task.

Judging behavior is a narrower question than judging code. The split above changes what the final judge is asked. Judging source code requires reasoning over many possible executions, whereas judging a trace asks only whether one observed execution violates a security requirement. This narrower task is both more accurate and cheaper: Table 2 shows that GPT-5.2 reaches 87.99% accuracy on traces versus 61.16% on source code, while source judging also requires substantially more output tokens and cost.

3.3 Attacker

Target selection. FALCON identifies functions, methods, or classes containing code changes and selects them as attack targets. Files identified as tests are excluded from target selection.

PoC probes. For each target, FALCON generates up to n deterministic PoC probes: executable scripts that invoke the target with adversarial inputs or a crafted environment to expose potential security violations. Probes specify neither expected outcomes nor security verdicts; the verifier assesses the resulting execution traces.

3.4 Faithfulness Check

A generated probe can look successful without touching the program under test. It may shadow the symbol it claims to attack, so the behavior it observes is its own. Or it may run the sensitive operation in its own body, print the canary it opened itself, and report a leak. In these cases, the attacker produces misleading evidence that can cause the verifier to flag the code that is actually secure. Figure 2 shows examples of these problems. We reject them with two predicates,

$$F(q, s) \;=\; F_{\text{stat}}(q, s) \;\wedge\; F_{\text{att}}(\tau_q, s), \tag{2}$$

where s is the target that q claims to exercise. A probe satisfying F is *admitted*, and we write $\mathcal{T}(R_p) = \{\, \tau_q : F(q, s) = 1 \,\}$ for the set of admitted traces. Only these reach the verifier; every other probe is discarded and contributes no evidence.

Static rejection. F_{stat} parses the probe and rejects it if it rebinds or redefines s or the module path reaching s, or if the security-sensitive operation whose effect it reports appears in the probe body. This runs before execution, so a rejected probe never produces a trace.

Runtime attribution. F_{att} uses the recorded execution history to confirm that the probe invokes s and that each evidence event is attributable to the target. Probes that fail this check are *inconclusive*, yielding neither a violation nor a clearance.

Appendix B.8 provides details of the faithfulness checks and rejection rules. These checks are designed to prevent the attacker from misleading the verifier. In practice, they reject 11.39% of generated probes across six harness–model configurations on SusVibes (Appendix C.1).

3.5 Verifier

The verifier reads a trace τ and returns a verdict. Its deterministic core is

$$V_{\text{core}}(\tau) = \begin{cases} \textsf{insecure}, & \text{if } \text{crash}(\tau), \\ \textsf{insecure}, & \text{else if } \exists\, r \in \mathcal{D} \text{ such that } r(\tau), \\ \textsf{secure}, & \text{else if } \text{benign}(\tau), \\ \textsf{uncertain}, & \text{otherwise}, \end{cases} \tag{3}$$

which decides only on positive evidence and returns uncertain when it cannot. The full verifier V_{full} keeps every decided verdict of V_{core} and passes only uncertain traces to an LLM judge J, returning $J(\tau)$ for them.

We use V_{full} for test-time repair, where an unresolved verdict would waste a repair round, and V_{core} for RL, where false-positive rewards must be avoided (Section 3.6).

Stage 1: crash oracle. $\text{crash}(\tau)$ fires when the target terminates abnormally through a memory error or sanitizer abort. Exceptions caught and recorded by the probe are passed to later stages rather than treated as crashes.

Stage 2: CWE oracle. $\mathcal{D}$ is an ordered set of 21 detectors applied to the normalized trace. Each detector looks for a behavioral signature of an exploited weakness in the observed execution, including commands and arguments, outputs and logs, return values, event metadata, and artifacts planted by the probe, and fires only on positive evidence. If no detector fires, a lightweight heuristic $\text{benign}(\tau)$ clears low-information traces with no recorded suspicious behavior to avoid unnecessary Stage 3 calls. Clearance indicates no observed violation, not proof of safety.

Stage 3: LLM trace judge. J is an LLM that reads the execution trace. It resolves cases left uncertain by the deterministic stages and captures violations that Stages 1 and 2 do not cover.

Rule construction. We construct each detector directly from the CWE entry it targets [56] by translating its observable security consequence into a condition on the execution trace. No detector was added or tuned based on benchmark results, and we consulted no ground-truth test or label. The 21 detectors are associated with 33 CWE identifiers, since some are shared across related weaknesses and some are generic. Appendix B.9 lists each detector and the observable it inspects.

3.6 The Security Signal

FALCON aggregates the verdicts over the admitted traces $\mathcal{T}(R_p)$:

$$V_{\text{FALCON}}(R_p) = \begin{cases} \textsf{insecure}, & \text{if } \exists\, \tau \in \mathcal{T}(R_p) \text{ such that } V(\tau) = \textsf{insecure}, \\ \textsf{secure}, & \text{else if } \mathcal{T}(R_p) \neq \emptyset, \\ \textsf{no-evidence}, & \text{otherwise}. \end{cases} \tag{4}$$

We distinguish no-evidence from secure: if all probes are rejected or inconclusive, the program is not treated as having survived the attacks. For RL, however, we set $r_{\text{sec}} = 0$ only when $V_{\text{FALCON}}(R_p) =$ insecure under V_{core}, and $r_{\text{sec}} = 1$ otherwise, including uncertain and no-evidence outcomes. This favors precision, since a false positive would repeatedly penalize correct code and push the policy toward over-defensive, less functional solutions. As a result, every negative RL reward is backed by a runtime event flagged by a deterministic stage.

Each insecure verdict produces a counterexample $e = (q, \tau, r)$: the triggering probe, its execution trace, and the reason for the violation, given by the matched detector condition for Stages 1 and 2 and by the judge's explanation for Stage 3.

4 Experiments

We evaluate FALCON across diverse settings and find three main results. (1) Its reported gains transfer much more strongly to held-out performance than alternative automated security signals (Section 4.2.1). (2) FALCON improves secure code generation in both test-time repair and RL while mitigating reward overoptimization (Sections 4.2.2 and 4.2.4). (3) Its verifier is highly accurate and substantially cheaper than direct LLM judging (Section 4.3), while Appendix C.2 reports how attack effectiveness scales with attacker capability and budget.

4.1 Experimental Setup

We conduct two main experimental settings to evaluate FALCON: **Test-time Repair Loop** and **RL Training**. The Repair Loop setting tests whether FALCON feedback helps a fixed generator revise its code toward secure and correct solutions at inference time, while the RL training setting assesses its effectiveness as a reward signal for training a model to generate secure code. Appendix B provides additional implementation details.

4.2 Main Results

4.2.1 Comparing Security Feedback Signals

We first test whether the repair gains are specific to FALCON or arise from any security feedback signal. On CWEval [43], we compare four signals under the same five-round repair protocol with GPT-5.4-MINI, using independently generated initial solutions for each run. The signals differ in how they produce the verdict and feedback. **FALCON** executes attacker-generated PoC probes and verifies the resulting traces, with GPT-5.4-MINI as both attacker and Stage 3 judge. **Attacker-only** removes the verifier: the attacker instead writes full security tests with expected outputs, and a program fails when its output mismatches the attacker's expectation. **LLM-as-a-Judge** directly judges the source code against a security rubric. **Static analyzer** uses CodeQL [15] findings as feedback.

Each signal reports its own *proxy secure rate*, the fraction of programs it deems secure at each round. Held-out performance is instead measured by CWEval's ground-truth functionality and security tests, which are hidden from all signals. A useful signal should therefore show gains that transfer to this held-out measure.



Figure 3 Repair loop on CWEval with four security feedback signals and GPT-5.4-MINI as the coding model. (**left**) Held-out Func-Sec@1, graded by CWEval's ground-truth tests, which no signal observes. (**middle**) Proxy secure rate, the improvement each signal reports on its own verdicts, relative to round one. (**right**) Reported versus held-out improvement from round one to five. FALCON produces the largest held-out improvement. CodeQL transfers a smaller gain, while the LLM-as-a-judge and attacker-only signals almost do not transfer.



Figure 4 Test-time repair with FALCON feedback on SecCodeBench-V2 **(left)** and CWEval **(right)**. Starred models are repaired with FALCON for up to five rounds. The other frontier models are shown as single-pass reference points. FALCON improves Func-Sec@1 for every repaired model on both benchmarks.

Figure 3 shows that this transfer differs substantially across signals. Over five rounds, FALCON improves its proxy secure rate by 33.3 points and Func-Sec@1 by 25.2 points, from 61.34 to 86.55. The static analyzer yields smaller gains of 5.0 proxy points and 6.7 held-out points. In contrast, the LLM judge gains 16.0 proxy points with no held-out improvement, while attacker-only gains 11.8 proxy points as Func-Sec@1 falls by 1.7 points. This gap is consistent with proxy overoptimization: improving the signal does not necessarily improve independently evaluated functional-security. Appendix C.4 reports per-language results.

4.2.2 Test-Time Repair Loop with FALCON Feedback

We evaluate how much FALCON improves secure code generation through iterative repair. Figure 4 reports Func-Sec@1 before and after applying FALCON to GPT-5.4-NANO, GPT-5.4-MINI, and GPT-5.4, alongside untreated frontier baselines. FALCON improves every treated model, increasing

Table 1 Repair with FALCON inside coding agents on SusVibes [65]. Results are averaged over three harnesses: SWE-agent, OpenCode, and Claude Code. FuncPass and SecPass follow the benchmark's task-level acceptance criteria, which permit failures up to task-specific baseline allowances rather than requiring all tests to pass. Func-TestRate and Sec-TestRate report the fraction of functional and security test cases passed, respectively, averaged across tasks.

Model	FuncPass	SecPass	Func-TestRate	Sec-TestRate
GPT-5.4-MINI	44.09	12.36	74.01	69.76
GPT-5.4-MINI + FALCON	46.59 (+2.50)	17.20 (+4.84)	76.24 (+2.23)	72.55 (+2.79)
GPT-5.4	68.82	20.25	81.65	77.55
GPT-5.4 + FALCON	70.97 (+2.15)	25.27 (+5.02)	83.12 (+1.47)	79.35 (+1.80)
GPT-5.6-LUNA	62.54	19.00	80.99	77.78
GPT-5.6-LUNA + FALCON	63.62 (+1.08)	22.22 (+3.22)	81.47 (+0.48)	79.36 (+1.58)
DEEPSEEK-V4-PRO-08-13	81.90	20.79	83.87	79.92
DEEPSEEK-V4-PRO-08-13 + FALCON	82.61 (+0.71)	24.91 (+4.12)	84.68 (+0.81)	81.59 (+1.67)

Func-Sec@1 by 22.5–24.0 points on SecCodeBench-V2 and 24.4–25.2 points on CWEval. Notably, GPT-5.4-NANO rises from 40.6% to 64.3% and from 52.9% to 77.3%, approaching CLAUDE-OPUS-4.8 without repair on SecCodeBench-V2 and exceeding it on CWEval.

Appendix C.3 reports per-round results, showing sustained improvements across models.

4.2.3 Repository-Level Coding Agents with FALCON Feedback

We now place FALCON inside coding agents that edit full repositories. We use SusVibes [65], a SWE-bench-style benchmark of 186 Python tasks spanning 77 CWEs, where patches are evaluated by separate functional and security test suites. We evaluate three harnesses, SWE-agent [62], Claude Code [2], and OpenCode [41], with four coding models. Before accepting a patch, FALCON attacks the modified executable symbols, verifies the resulting traces, and returns any observed violation as counterexample feedback for another repair round. We cap this process at five FALCON rounds per task. In all runs, the attacker and Stage-3 verifier use the same model as the main coding agent.

Table 1 reports results averaged over three harnesses (SWE-agent, OpenCode, and Claude Code), and shows that FALCON improves SecPass and both test-level metrics across all reported configurations while largely preserving functionality. Notably, OpenCode with GPT-5.4 reaches 93.01% FuncPass but only 28.49% SecPass, highlighting the gap between functional and security acceptance. Per-harness results are in Appendix C.5.

4.2.4 Reinforcement Learning with FALCON Rewards

We train GRPO [50] on QWEN2.5-CODER-3B and QWEN2.5-CODER-7B [21] using six security reward configurations: (1) the REAL [63] static analyzer, (2) SecCodePRM [64], a process reward model trained to score code security, (3) FALCON, (4) FALCON + REAL, (5) FALCON + SecCodePRM, and (6) SecCodePRM + REAL. Each combined reward averages its two component scores. Every setting scores a generated program y with the same two-term reward,

$$r(y) \;=\; (1-\lambda)\, r_{\text{func}}(y) \;+\; \lambda\, r_{\text{sec}}(y), \qquad \lambda = 0.5, \tag{5}$$



Figure 5 FALCON provides a robust RL signal and strengthens existing security rewards. Every policy steadily increases its own training reward (**left**), yet held-out Func-Sec@1 separates sharply (**middle**). When optimized alone, REAL [63] and SecCodePRM [64] transfer much less of their reward gains to held-out Func-Sec@1, most clearly at 3B, where Func-Sec@1 eventually declines while training reward keeps increasing, consistent with reward overoptimization. In contrast, FALCON maintains stronger held-out Func-Sec@1, and combining it with either reward further improves transfer, whereas combining REAL and SecCodePRM does not. Configurations that include FALCON also keep KL lower (**right**).

where r_{func} is the unit-test pass rate and λ trades off functionality against security.

Figure 5 reports training reward, held-out Func-Sec@1, and KL divergence from the base model. Each configuration is trained with three random seeds.

Empirical findings. All six policies increase their own training reward, but their held-out performance differs sharply. When optimized alone, REAL and SecCodePRM reach 57.13 and 54.50 Func-Sec@1 at 7B, compared with 68.70 for FALCON; at 3B, the corresponding scores are 38.75 and 29.46 versus 49.27. At 3B, both proxy rewards keep increasing while held-out performance declines, a pattern consistent with reward overoptimization [14].

Prior work shows that conservative optimization over reward-model ensembles can mitigate overoptimization [10]. In our setting, however, simply combining two proxy security rewards does not: REAL + SecCodePRM reaches only 38.01 and 56.89 Func-Sec@1 at 3B and 7B. In contrast, grounding either reward with FALCON yields substantially stronger results, reaching 57.25 and 51.95 at 3B, and 70.87 and 77.26 at 7B. These results suggest that execution grounding can anchor overoptimizable security rewards while preserving the useful guidance provided by the original proxy rewards.

Table 2 Verifier accuracy and cost on CWEval. Results are macro-averaged over nine runs across code generated by three models. Stages 1 and 2 are deterministic and incur no model cost; Stage 3 uses an LLM trace judge as described in section 3.5; The remaining blocks show CodeQL [15], a static analyzer, and LLM judges applied to the execution trace or to the source code. Tokens are mean input/output tokens per verdict.

Verifier	TPR	TNR	FPR	FNR	Acc.	Cost ($)	Avg. Tokens (in/out)
Stage 1	68.34	97.84	2.16	31.66	83.05	0	–
Stage 1 + 2	97.38	97.67	2.33	2.62	97.54	0	–
Stage 1 + 2 + 3 (GPT-5-MINI)	99.83	97.27	2.73	0.17	98.68	0.030	–
Stage 1 + 2 + 3 (GPT-5)	99.08	97.27	2.73	0.92	98.20	0.189	–
Stage 1 + 2 + 3 (GPT-5.1)	99.11	97.27	2.73	0.89	98.20	0.196	–
Stage 1 + 2 + 3 (GPT-5.2)	99.80	97.27	2.73	0.20	98.58	0.085	–
Stage 1 + 2 + 3 (GPT-5.4)	99.45	97.27	2.73	0.55	98.39	0.111	–
CodeQL [15] (static-analyzer on code)	33.58	82.05	17.95	66.42	56.68	0	–
GPT-5-MINI judge on trace (only stage 3)	76.54	80.14	19.86	23.46	78.31	0.210	1383 / 709
GPT-5.2 judge on trace (only stage 3)	99.82	76.08	23.92	0.18	87.99	0.634	1383 / 160
DEEPSEEK-V4-FLASH judge on trace (only stage 3)	70.97	96.49	3.51	29.03	83.19	0.133	1524 / 1258
GPT-5-MINI judge on code	70.08	48.99	51.01	29.92	60.00	0.419	966 / 1638
GPT-5.2 judge on code	71.95	49.57	50.43	28.05	61.16	1.227	966 / 615
DEEPSEEK-V4-FLASH judge on code	73.08	62.69	37.31	26.92	67.23	0.554	1116 / 6699

4.3 Verifier Reliability

We evaluate verifier reliability on CWEval [43], comprising 119 security-critical tasks across 31 CWE types and five languages. For each ground-truth labeled test (x, y), we execute x and compare the verifier's verdict with y. End-to-end verdicts are not directly comparable because FALCON and CWEval evaluate different inputs: a disagreement may reflect either a verifier error or a vulnerability missed by CWEval. We therefore use only CWEval inputs with known labels. Table 2 reports TPR, TNR, FPR, FNR and overall accuracy, averaged over three runs each for code generated by GPT-5-MINI, GPT-5.2, and GPT-5.4.

The deterministic stages already achieve 97.54% accuracy with 2.33% false positives. Adding Stage 3 raises accuracy to 98.68% and reduces false negatives from 2.62% to 0.17%, with stable performance across judge models.

Source-code judging is also more expensive: despite using only about 70% as many input tokens, it generates 2.3 to 5.3 times more output tokens across three models. With GPT-5.2, it costs $1.227 per example, compared with $0.634 for judging every trace and $0.085 for the full FALCON verifier. These results support both the reliability and efficiency of execution-grounded judgment.

Beyond verifier reliability, Appendix C.2 evaluates attacker effectiveness, showing that stronger attackers and larger probe budgets achieve higher attack success and broader CWE coverage.

5 Conclusion

We presented FALCON, a counterexample-grounded verification framework for secure code generation. By separating attack exploration from behavioral verification through execution traces, FALCON reduces the reasoning burden of security judgment and guards against misleading

attacker-generated evidence. Results across multiple benchmarks support its effectiveness in test-time repair and reinforcement learning. However, the framework remains bounded by attack coverage, relies on manually designed detectors and fallback model judgments, and incurs execution overhead. Reusing precomputed probes during RL may also encourage specialization. Future work will explore adaptive attack generation, periodic probe regeneration, and more efficient verification.

AI Use Statement

Generative AI tools were used only for editorial assistance, including improving wording, grammar, and readability, and refining figure captions and table presentation. They were not used to develop the research framework, design experiments, implement methods, prepare datasets, or analyze or interpret results. The authors reviewed all AI-assisted material and take full responsibility for the final manuscript, including its claims and artifacts.

Reproducibility Statement

Section 3 describes the FALCON framework, and Appendix B.3 gives its full procedure (Algorithm 1). Appendices B.1–B.5 document the test-time repair and RL protocols, benchmarks, training hyperparameters, and agent settings. Appendices B.6–B.9 provide the attacker and judge prompts, probe faithfulness rules, and deterministic verifier rules. Appendix C reports faithfulness check outcomes, attacker effectiveness across models and probe budgets, per-round and per-language repair results, and repository-level agent results. Together, these details support reproduction and closer examination of the findings in Section 4. Source code for FALCON and for the experiments reported in this paper is provided as supplementary material.

References

[1] Dario Amodei, Chris Olah, Jacob Steinhardt, Paul Christiano, John Schulman, and Dan Mané. Concrete problems in AI safety. *arXiv preprint arXiv:1606.06565*, 2016. URL https://arxiv.org/abs/1606.06565.

[2] Anthropic. Claude code. https://claude.com/product/claude-code, 2026.

[3] Al Bessey, Ken Block, Ben Chelf, Andy Chou, Bryan Fulton, Seth Hallem, Charles Henri-Gros, Asya Kamsky, Scott McPeak, and Dawson Engler. A few billion lines of code later: Using static analysis to find bugs in the real world. *Communications of the ACM*, 53(2):66–75, 2010. doi: 10.1145/1646353.1646374.

[4] Black Duck. Coverity static analysis. https://www.blackduck.com/static-analysis-tools-sast/coverity.html, 2026.

[5] Scott Blyth, Sherlock A. Licorish, Christoph Treude, and Markus Wagner. Static analysis as a feedback loop: Enhancing llm-generated code beyond correctness. *2025 IEEE International Conference on Source Code Analysis & Manipulation (SCAM)*, pages 100–109, 2025. URL https://api.semanticscholar.org/CorpusID:280692420.

[6] Ruisheng Cao, Mouxiang Chen, Jiawei Chen, Zeyu Cui, Yunlong Feng, Binyuan Hui, Yuheng Jing, Kaixin Li, Mingze Li, Junyang Lin, Zeyao Ma, Kashun Shum, Xuwu Wang, Jinxi Wei, Jiaxi Yang, Jiajun Zhang, Lei Zhang, Zongmeng Zhang, Wenting Zhao, and Fan Zhou. Qwen3-coder-next technical report. *ArXiv*, abs/2603.00729, 2026. URL https://api.semanticscholar.org/CorpusID:286224178.

[7] Longfei Chen, Ji Zhao, Lanxiao Cui, Tong Su, Xingbo Pan, Ziyang Li, Yongxing Wu, Qijiang Cao, Qiyao Cai, Jing Zhang, Yuandong Ni, Junyao He, Zeyu Zhang, Chao Ge, Xuhuai Lu, Zeyu Gao, Yuxin Cui, Weisen Chen, Yuxuan Peng, Shengping Wang, Qi Li, Yukai Huang, Yukun Liu, Tuo Zhou, Terry Yue Zhuo, Junyang Lin, and Chao Zhang. Seccodebench-v2 technical report. *ArXiv*, abs/2602.15485, 2026. URL https://arxiv.org/abs/2602.15485.

[8] Xinyun Chen, Maxwell Lin, Nathanael Schärli, and Denny Zhou. Teaching large language models to self-debug. *arXiv preprint arXiv:2304.05128*, 2023. URL https://arxiv.org/abs/2304.05128.

[9] Chun Jie Chong, Zhihao Yao, and Iulian Neamtiu. Artificial-intelligence generated code considered harmful: A road map for secure and high-quality code generation. *ArXiv*, abs/2409.19182, 2024. URL https://api.semanticscholar.org/CorpusID:272987371.

[10] Thomas Coste, Usman Anwar, Robert Kirk, and David Scott Krueger. Reward model ensembles help mitigate overoptimization. *ArXiv*, abs/2310.02743, 2023. URL https://api.semanticscholar.org/CorpusID:263620686.

[11] Xiang Deng, Jeff Da, Edwin Pan, Yannis Yiming He, Charles Ide, Kanak Garg, Niklas Lauffer, Andrew Park, Nitin Pasari, Chetan Rane, Karmini Sampath, Maya Krishnan, Srivatsa Kundurthy, Sean Hendryx, Zifan Wang, Chen Bo Calvin Zhang, Noah Jacobson, Bing Liu, and Brad Kenstler. Swe-bench pro: Can ai agents solve long-horizon software engineering tasks? *ArXiv*, abs/2509.16941, 2025. URL https://arxiv.org/abs/2509.16941v1.

[12] Yangruibo Ding, Yanjun Fu, Omniyyah Ibrahim, Chawin Sitawarin, Xinyun Chen, Basel Alomair, David Wagner, Baishakhi Ray, and Yizheng Chen. Vulnerability detection with code language models: How far are we? *arXiv preprint arXiv:2403.18624*, 2024. URL https://arxiv.org/abs/2403.18624.

[13] Greta Dolcetti, Vincenzo Arceri, Eleonora Iotti, Sergio Maffeis, Agostino Cortesi, and Enea Zaffanella. Helping llms improve code generation using feedback from testing and static analysis. *ArXiv*, abs/2412.14841, 2024. URL https://api.semanticscholar.org/CorpusID:274859300.

[14] Leo Gao, John Schulman, and Jacob Hilton. Scaling laws for reward model overoptimization. In *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pages 10835–10866, 2023. URL https://proceedings.mlr.press/v202/gao23h.html.

[15] GitHub. Codeql documentation. https://codeql.github.com/docs/, 2026.

[16] Chengquan Guo, Yuzhou Nie, Chulin Xie, Zinan Lin, Wenbo Guo, and Bo Li. BlueCodeAgent: A blue teaming agent enabled by automated red teaming for CodeGen AI. *arXiv preprint arXiv:2510.18131*, 2025. URL https://arxiv.org/abs/2510.18131.

[17] Daya Guo, Qihao Zhu, Dejian Yang, Zhenda Xie, Kai Dong, Wentao Zhang, Guanting Chen, Xiao Bi, Yu Wu, Y. K. Li, Fuli Luo, Yingfei Xiong, and Wenfeng Liang. Deepseek-coder: When the large language model meets programming - the rise of code intelligence. *ArXiv*, abs/2401.14196, 2024. URL https://api.semanticscholar.org/CorpusID:267211867.

[18] Hossein Hajipour, Lea Schönherr, Thorsten Holz, and Mario Fritz. Hexacoder: Secure code generation via oracle-guided synthetic training data. *ArXiv*, abs/2409.06446, 2024. URL https://api.semanticscholar.org/CorpusID:272550975.

[19] Jingxuan He, Mark Vero, Gabriela Krasnopolska, and Martin Vechev. Instruction tuning for secure code generation. *arXiv preprint arXiv:2402.09497*, 2024. URL https://arxiv.org/abs/2402.09497.

[20] Anh Nguyen Hoang, Minh Le-Anh, Bach Le, and Nghi D. Q. Bui. CodeWiki: Evaluating AI's ability to generate holistic documentation for large-scale codebases. In *Findings of the Association for Computational Linguistics: ACL 2026*, 2026. URL https://arxiv.org/abs/2510.24428.

[21] Binyuan Hui, Jian Yang, Zeyu Cui, Jiaxi Yang, Dayiheng Liu, Lei Zhang, Tianyu Liu, Jiajun Zhang, Bowen Yu, Keming Lu, Kai Dang, Yang Fan, Yichang Zhang, An Yang, Rui Men, Fei Huang, Bo Zheng, Yibo Miao, Shanghaoran Quan, Yunlong Feng, Xingzhang Ren, Xuancheng Ren, Jingren Zhou, and Junyang Lin. Qwen2.5-coder technical report. *ArXiv*, abs/2409.12186, 2024. URL https://arxiv.org/abs/2409.12186v2.

[22] Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik Narasimhan. Swe-bench: Can language models resolve real-world github issues? *ArXiv*, abs/2310.06770, 2023. URL https://api.semanticscholar.org/CorpusID:263829697.

[23] Jacek Karwowski, Oliver Hayman, Xingjian Bai, Klaus Kiendlhofer, Charlie Griffin, and Joar Skalse. Goodhart's law in reinforcement learning. *arXiv preprint arXiv:2310.09144*, 2023. URL https://arxiv.org/abs/2310.09144.

[24] Mohammed F. Kharma, Mohammad Y. Alkhanafseh, Ahmed Sabbah, and David Mohaisen. Enhancing reliability in llm-based secure code generation. *arXiv preprint arXiv:2605.24300*, 2026. URL https://arxiv.org/abs/2605.24300.

[25] Michael Konstantinou, Renzo Degiovanni, and Mike Papadakis. Do llms generate test oracles that capture the actual or the expected program behaviour? *ArXiv*, abs/2410.21136, 2024. URL https://api.semanticscholar.org/CorpusID:273654532.

[26] Abhijit Kumar, Natalya Kumar, and Shikhar Gupta. Execution-grounded credit assignment for GRPO in code generation. *arXiv preprint arXiv:2603.16158*, 2026. URL https://arxiv.org/abs/2603.16158.

[27] Hung Le, Yue Wang, Akhilesh Deepak Gotmare, Silvio Savarese, and Steven C. H. Hoi. CodeRL: Mastering code generation through pretrained models and deep reinforcement learning. *Advances in Neural Information Processing Systems*, 35:21314–21328, 2022.

[28] Tue Le, Minh VT Thai, Dung Nguyen Manh, Huy Phan Nhat, and Nghi DQ Bui. Swe-evo: Benchmarking coding agents in long-horizon software evolution scenarios. *arXiv preprint arXiv:2512.18470*, 2025.

[29] Minh Le-Anh, Nam Le Hai, Quyen Tran, Anh Nguyen Hoang, Linh Ngo Van, Bach Le, and Nghi D. Q. Bui. Beyond repository boundaries: Cross-repository graph retrieval for code generation. In *Findings of the Association for Computational Linguistics: EMNLP 2026*, 2026. URL https://arxiv.org/abs/2609.09987.

[30] Minh Le-Anh, Anh Nguyen Hoang, Bach Le, and Nghi D. Q. Bui. Documentation-guided agentic codebase migration from C to Rust. *ArXiv*, abs/2605.14634, 2026. URL https://arxiv.org/abs/2605.14634.

[31] Jan Leike, David Krueger, Tom Everitt, Miljan Martic, Vishal Maini, and Shane Legg. Scalable agent alignment via reward modeling: A research direction. *arXiv preprint arXiv:1811.07871*, 2018. URL https://arxiv.org/abs/1811.07871.

[32] Junjie Li, Fazle Rabbi, Cheng Cheng, Aseem Sangalay, Yuan Tian, and Jinqiu Yang. An exploratory study on fine-tuning large language models for secure code generation. *Empirical Software Engineering*, 31, 2026. doi: 10.1007/s10664-026-10803-9. URL https://link.springer.com/article/10.1007/s10664-026-10803-9. Article 81.

[33] Jiate Liu, Yiqin Zhu, Kaiwen Xiao, Qiang Fu, Xiao Han, Wei Yang, and Deheng Ye. RLTF: Reinforcement learning from unit test feedback. *arXiv preprint arXiv:2307.04349*, 2023. URL https://arxiv.org/abs/2307.04349.

[34] Jiawei Liu, Nirav Diwan, Zhe Wang, Haoyu Zhai, Xiaona Zhou, Kiet A. Nguyen, Tianjiao Yu, Muntasir Wahed, Hadjer Benkraouda, Yuxiang Wei, et al. PurpCode: Reasoning for safer code generation. *arXiv preprint arXiv:2507.19060*, 2025. URL https://arxiv.org/abs/2507.19060.

[35] Aman Madaan, Niket Tandon, Prakhar Gupta, et al. Self-refine: Iterative refinement with self-feedback. *Advances in Neural Information Processing Systems*, 36, 2023.

[36] Valentin J. M. Manès, HyungSeok Han, Choongwoo Han, Sang Kil Cha, Manuel Egele, Edward J. Schwartz, and Maverick Woo. The art, science, and engineering of fuzzing: A survey. *IEEE Transactions on Software Engineering*, 47(11):2312–2331, 2021. doi: 10.1109/TSE.2019.2946563.

[37] Ahmad Mohsin, Helge Janicke, Adrian Wood, Iqbal H. Sarker, L. Maglaras, and Naeem Khalid Janjua. Can we trust large language models generated code? a framework for in-context learning, security patterns, and code evaluations across diverse llms. *ArXiv*, abs/2406.12513, 2024. URL https://api.semanticscholar.org/CorpusID:270562833.

[38] Mahmoud Nazzal, Issa Khalil, Abdallah Khreishah, and NhatHai Phan. PromSec: Prompt optimization for secure generation of functional source code with large language models. *arXiv preprint arXiv:2409.12699*, 2024. URL https://arxiv.org/abs/2409.12699.

[39] James Newsome and Dawn Song. Dynamic taint analysis for automatic detection, analysis, and signature generation of exploits on commodity software. In *Proceedings of the Network and Distributed System Security Symposium*, 2005.

[40] Ana Nunez, Nafis Tanveer Islam, Sumit Kumar Jha, and Peyman Najafirad. AutoSafeCoder: A multi-agent framework for securing LLM code generation through static analysis and fuzz testing. *arXiv preprint arXiv:2409.10737*, 2024. URL https://arxiv.org/abs/2409.10737.

[41] OpenCode. OpenCode: The open source ai coding agent. https://github.com/anomalyco/opencode, 2025. Software repository.

[42] Jiayi Pan, Xingyao Wang, Graham Neubig, Navdeep Jaitly, Heng Ji, Alane Suhr, and Yizhe Zhang. Training software engineering agents and verifiers with SWE-Gym. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pages 47717–47737, 2025. URL https://proceedings.mlr.press/v267/pan25g.html.

[43] Jinjun Peng, Leyi Cui, Kele Huang, Junfeng Yang, and Baishakhi Ray. CWEval: Outcome-driven evaluation on functionality and security of LLM code generation. *arXiv preprint arXiv:2501.08200*, 2025. URL https://arxiv.org/abs/2501.08200.

[44] PyCQA. Bandit: A security linter from PyCQA. https://bandit.readthedocs.io/, 2026.

[45] Jiazheng Quan, Xiaodong Li, Bin Wang, Guo An, Like Liu, Degen Huang, Lin Liu, and Chengbin Hou. Learning to generate secure code via token-level rewards. *ArXiv*, abs/2602.23407, 2026. URL https://arxiv.org/abs/2602.23407.

[46] Leonardo Criollo Ramírez, Xavier Limón, Ángel Juan Sánchez-García, and Juan Carlos Pérez-Arriaga. State of the art of the security of code generated by llms: A systematic literature review. *2024 12th International Conference in Software Engineering Research and Innovation (CONISOFT)*, pages 331–339, 2024. URL https://api.semanticscholar.org/CorpusID:274827178.

[47] Rebecca Saul, Hao Wang, Koushik Sen, and David Wagner. SCGAgent: Recreating the benefits of reasoning models for secure code generation with agentic workflows. *arXiv preprint arXiv:2506.07313*, 2025. URL https://arxiv.org/abs/2506.07313.

[48] Semgrep, Inc. Semgrep documentation. https://semgrep.dev/docs/, 2026.

[49] Konstantin Serebryany, Derek Bruening, Alexander Potapenko, and Dmitriy Vyukov. Addresssanitizer: A fast address sanity checker. In *2012 USENIX Annual Technical Conference*, pages 309–318. USENIX Association, 2012.

[50] Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. DeepSeekMath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024. URL https://arxiv.org/abs/2402.03300.

[51] Guangming Sheng, Chi Zhang, Zilingfeng Ye, Xi-Bin Wu, Wang Zhang, Ru Zhang, Yanghua Peng, Haibin Lin, and Chuan Wu. Hybridflow: A flexible and efficient rlhf framework. In *Proceedings of the Twentieth European Conference on Computer Systems*, pages 1279–1297, 2025. doi: 10.1145/3689031.3696075. URL https://doi.org/10.1145/3689031.3696075.

[52] Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning. *Advances in Neural Information Processing Systems*, 36, 2023.

[53] Suryansh Singh Sijwali and Suman Saha. SecureCodeRL: Security-aware reinforcement learning for code generation with partial-credit rewards. *arXiv preprint arXiv:2601.01184*, 2026. URL https://arxiv.org/abs/2601.01184.

[54] Yuqiang Sun, Daoyuan Wu, Yue Xue, Han Liu, Wei Ma, Lyuye Zhang, Yang Liu, and Yingjiu Li. LLM4Vuln: A unified evaluation framework for decoupling and enhancing LLMs' vulnerability reasoning. *arXiv preprint arXiv:2401.16185*, 2024. URL https://arxiv.org/abs/2401.16185.

[55] Melissa Tessa, Iyiola E. Olatunji, Aicha War, Jacques Klein, and Tegawendé F. Bissyandé. How secure is secure code generation? adversarial prompts put LLM defenses to the test. *arXiv preprint arXiv:2601.07084*, 2026. URL https://arxiv.org/abs/2601.07084.

[56] The MITRE Corporation. Common weakness enumeration (CWE). https://cwe.mitre.org/about/index.html, 2026. Accessed September 26, 2026.

[57] Scott Thornton. SecureCode v2.0: A production-grade dataset for training security-aware code generation models. *arXiv preprint arXiv:2512.18542*, 2025. URL https://arxiv.org/abs/2512.18542v1.

[58] Jiexin Wang, Liuwen Cao, Xitong Luo, Zhiping Zhou, Jiayuan Xie, Adam Jatowt, and Yi Cai. Enhancing large language models for secure code generation: A dataset-driven study on vulnerability mitigation. *ArXiv*, abs/2310.16263, 2023. URL https://api.semanticscholar.org/CorpusID:264487366.

[59] Longwen Wang, Xuan'er Wu, Xiaohui Hu, Yirui Liu, Yuankai Fan, Kaidong Yu, Qizhen Weng, Wei Xi, and Xuelong Li. VeRPO: Verifiable dense reward policy optimization for code generation. *arXiv preprint arXiv:2601.03525*, 2026. URL https://arxiv.org/abs/2601.03525v1.

[60] Tianyi Wu, Mingzhe Du, Yue Liu, Chengran Yang, Terry Yue Zhuo, Jiaheng Zhang, and See-Kiong Ng. Secure code generation via online reinforcement learning with vulnerability reward model. *arXiv preprint arXiv:2602.07422*, 2026. URL https://arxiv.org/abs/2602.07422.

[61] An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, Chujie Zheng, Dayiheng Liu, Fan Zhou, Fei Huang, Feng Hu, Hao Ge, Haoran Wei, Huan Lin, Jialong Tang, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jing Zhou, Jingren Zhou, Junyang Lin, Kai Dang, Keqin Bao, Kexin Yang, Le Yu, Lianghao Deng, Mei Li, Mingfeng Xue, Mingze Li, Pei Zhang, Peng Wang, Qin Zhu, Rui Men, Ruize Gao, Shixuan Liu, Shuang Luo, Tianhao Li, Tianyi Tang, Wenbiao Yin, Xingzhang Ren, Xinyu Wang, Xinyu Zhang, Xuancheng Ren, Yang Fan, Yang Su, Yichang Zhang, Yinger Zhang, Yu Wan, Yuqiong Liu, Zekun Wang, Zeyu Cui, Zhenru Zhang, Zhipeng Zhou, and Zihan Qiu. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025. URL https://arxiv.org/abs/2505.09388.

[62] John Yang, Carlos E. Jimenez, Alexander Wettig, Kilian Adriano Lieret, Shunyu Yao, Karthik Narasimhan, and Ofir Press. Swe-agent: Agent-computer interfaces enable automated software engineering. *ArXiv*, abs/2405.15793, 2024. URL https://api.semanticscholar.org/CorpusID:270063685.

[63] Feng Yao, Zilong Wang, Liyuan Liu, Junxia Cui, Li Zhong, Xiaohan Fu, Haohui Mai, Vish Krishnan, Jianfeng Gao, and Jingbo Shang. Training language models to generate quality code with program analysis feedback. *arXiv preprint arXiv:2505.22704*, 2025. URL https://arxiv.org/abs/2505.22704.

[64] Weichen Yu, Ravi Mangal, Yinyi Luo, Kai Hu, Jingxuan He, Corina S. Pasareanu, and Matt Fredrikson. SecCodePRM: A process reward model for code security. *arXiv preprint arXiv:2602.10418*, 2026. URL https://arxiv.org/abs/2602.10418.

[65] Songwen Zhao, Danqing Wang, Kexun Zhang, Jiaxuan Luo, Zhuo Li, and Lei Li. Is vibe coding safe? benchmarking vulnerability of agent-generated code in real-world tasks. *ArXiv*, abs/2512.03262, 2025. URL https://api.semanticscholar.org/CorpusID:283466856.

[66] Yaqin Zhou, Shangqing Liu, Jingkai Siow, Xiaoning Du, and Yang Liu. Devign: Effective vulnerability identification by learning comprehensive program semantics via graph neural networks. In *Advances in Neural Information Processing Systems*, volume 32, 2019.

[67] Terry Yue Zhuo, Minh Chien Vu, Jenny Chim, Han Hu, Wenhao Yu, Ratnadira Widyasari, Imam Nur Bani Yusuf, Haolan Zhan, Junda He, Indraneil Paul, Simon Brunner, Chen Gong, Thong Hoang, Armel Randy Zebaze, Xiaoheng Hong, Wen-Ding Li, Jean Kaddour, Ming Xu, Zhihan Zhang, Prateek Yadav, Naman Jain, Alex Gu, Zhoujun Cheng, Jiawei Liu, Qian Liu, Zijian Wang, David Lo, Binyuan Hui, Niklas Muennighoff, Daniel Fried, Xiaoning Du, Harm de Vries, and Leandro Von Werra. Bigcodebench: Benchmarking code generation with diverse function calls and complex instructions. *ArXiv*, abs/2406.15877, 2024. URL https://arxiv.org/abs/2406.15877v1.

A Literature review

A.1 Secure Code Generation

Large Language Models have strong code generation ability [6, 11, 17, 22, 28, 67] and increasingly operate over entire repositories, retrieving cross-repository context for generation [29], producing architecture-level documentation for large codebases [20], and migrating whole projects across languages [30], but generated code can still contain vulnerabilities. Recent empirical studies show that LLM-generated code often falls short on security [9, 37, 46, 58] and may introduce exploitable vulnerabilities. Prior work improves secure code generation along both training-time and inference-time directions. Training-time methods construct security-aware datasets or instruction-tuning corpora [19, 45, 57], learn from vulnerable-to-fixed repair pairs or vulnerability-fixing commits [18, 32, 45], and optimize security with static/program-analysis rewards or learned reward models [34, 53, 60, 63]. Inference-time methods guide generation or revision using mitigation-aware security prompts [24], prompt optimization with vulnerability-clearing models [38], or feedback from testing and static analysis [5, 13].

These works show that secure code generation benefits from stronger supervision and more fine-grained feedback. However, most security signals remain indirect: they come from static analyzers, learned detectors, teacher models, or dataset labels, rather than from reliable evidence that a candidate program violates a security property.

A.2 Vulnerability Detection

Existing vulnerability detection methods fall into three groups: (1) static analysis, (2) learned and LLM-based detection, and (3) execution-based and dynamic detection.

A.2.1 Static Analysis

Static analysis analyzes program code without execution, using rulesets and abstractions over data flow and taint propagation, which makes it cheap, deterministic, and able to cover paths no test exercises, so it is widely used as an evaluator and reward signal for secure code generation [4, 15, 44, 48, 53, 63]. However, its verdicts are bounded by a predefined ruleset and lack semantic, runtime grounding: it raises false positives on benign patterns, misses semantic vulnerabilities that only a concrete input can expose, and can reward superficial rewrites that silence a warning without removing the exploitable behavior [3, 55].

A.2.2 Learned and LLM-Based Detection

Learned detectors replace hand-written rules with statistical models over code. Early ML-based systems such as Devign [66] use Graph Neural Networks to classify vulnerable functions, but they learn from correlations in code form and labels, and datasets like PrimeVul [12] show duplicates, label noise, and shortcuts that inflate their measured performance. More recent work uses pretrained code models and LLM reasoning to localize or judge weaknesses, and LLM-as-a-judge is attractive because one model can cover many languages and CWE families from natural-language criteria [54, 60, 64]. However, LLM judges are unreliable: their verdicts vary widely across prompts and

context [54], and they do not directly observe runtime behavior, which can yield both false positives and false negatives.

A.2.3 Execution-Based and Dynamic Detection

Dynamic approaches judge behavior observed while the program runs. Dynamic taint analysis tracks untrusted data into security-sensitive sinks [39]; sanitizers expose memory errors through runtime instrumentation [49]; and coverage-guided fuzzing searches for inputs that trigger crashes or policy violations [36]. Modern secure-code benchmarks [7, 43] adopt the same principle: judge security with executable tests or proof-of-concept inputs rather than source-pattern matching. Running the code turns an unsafe verdict into concrete evidence, an input and a trace showing the violation.

However, execution only reveals a vulnerability when an input actually triggers it. This demands a diverse set of tests that reach the unsafe behavior, yet manually building such tests is costly, especially at test time.

A.3 Improving Secure Code Generation

A security signal matters most once an optimizer consumes it, since the signal is what tells the model whether its code is secure and what the model then learns from. At training time, security-aware fine-tuning and reinforcement learning optimize a security reward [19, 34, 53, 60, 63]. At inference time, iterative repair applies the same pressure over a shorter horizon, revising code from analyzer, test, or verbal feedback [8, 35, 38, 52]. Both settings share one dependence: each repeatedly selects the updates that raise the supplied score. If that score is gameable, optimization learns the detector's preferences instead of removing the vulnerability.

Grounding the signal in execution is the natural way to obtain this faithfulness, and it is already well established for *functional correctness*. VeRPO folds fine-grained execution evidence into policy optimization [59], EGCA assigns credit at the assertion level rather than from a single binary reward [26], and GRPO-based reasoning models show the broad value of automatically verifiable rewards [50], while at inference time self-debugging feeds execution results back into iterative repair [8]. However, security is a harder version of the same opportunity: a functional test has a known expected output, whereas a security failure may depend on a specific input, may not crash, and may need a CWE-specific runtime check to detect. As a result, execution grounding has been applied mainly to correctness, while security feedback, in both repair and RL, still leans on static analyzers, fixed tests, or learned judges. FALCON addresses this gap: it makes security feedback verifiable through a replayable adversarial input and its observed execution trace, so both test-time repair and post-training optimize against evidence of the unsafe behavior rather than a surface-level correlate.

B Implementation Details

This appendix gives the settings needed to reproduce our results, followed by the prompts and rules behind each FALCON component.

B.1 Test-Time Repair Loop

For the **Test-time Repair Loop**, the coding model iteratively revises its solution using FALCON feedback. At each round, the attacker generates PoC probes, the verifier evaluates their execution traces, and any detected violation is returned to the model for repair. The loop stops when no violation is found or after five rounds. We evaluate on three secure coding benchmarks, SecCodeBench-V2 [7], CWEval [43] and SusVibes [65]. SecCodeBench-V2 covers five languages (Java, Python, C/C++, Go, and JavaScript), with most tasks derived from anonymized real-world vulnerabilities and spanning both generation and repair scenarios, with and without security hints. CWEval is a multilingual secure code generation benchmark over C, C++, Go, JavaScript, and Python that jointly measures functionality and security. SusVibes extends security evaluation to repository-level coding, with 186 Python tasks across 77 CWEs where agents modify real codebases and patches are tested for both functionality and security.

B.2 RL Training

For the **RL Training** setting, we adopt the security-sensitive configuration of REAL [63] on its SecCodePLT+ dataset, which combines a functionality reward, the unit-test pass rate, with a security reward from a static analyzer. We keep the functionality reward unchanged and replace only the security term with FALCON, using V_{core} and the reward mapping of Section 3.6: the reward is 0 only when an admitted probe produces an observed violation, and 1 otherwise. Regenerating PoC probes at every step would be costly, so we precompute them once: the attacker (QWEN3-8B) [61] reads base-model solutions for the training tasks and writes a fixed probe set per task, reused throughout training.

Our RL code extends the REAL [63] codebase, which uses VeRL [51] as its training framework. SecCodePLT+ provides 655 training tasks and 164 held-out tasks, and held-out func-sec@1 is graded by the benchmark's own unit and safety tests, which no reward term sees during training. Table 3 lists the hyperparameters. The six settings share the functionality reward and optimizer settings.

Table 3 GRPO training hyperparameters. The six reward settings share every value here and differ only in how the security term is computed.

Hyperparameter	Value
Hardware	8× A100 40 GB
Learning rate	1×10^{-6}
Train batch size	64
PPO mini-batch size	32
Micro-batch size per GPU	2
Rollouts per prompt	8
Max response length	2,048 tokens
KL coefficient	0.001 (applied via reward, KL loss off)
Tensor-model parallel size	2
Total epochs	50

B.3 The FALCON Procedure

Algorithm 1 states the procedure described in Section 3. The two faithfulness predicates run in separate phases, since F_{stat} can be checked before a probe runs while F_{att} needs a trace. A candidate for which no probe survives both returns no-evidence rather than secure.

Algorithm 1 The FALCON signal for a candidate workspace R_p.

Require: task T, workspace R_p, per-target budget n, verifier $V \in \{V_{\text{core}}, V_{\text{full}}\}$
$E \leftarrow \emptyset$; $m \leftarrow 0$ ▷ counterexamples; admitted traces
for all target $s \in \textsc{Targets}(T, R_p)$ **do**
  for all probe $q \in \textsc{Attacker}(T, R_p, s, n)$ **do**
    if $F_{\text{stat}}(q, s) = 0$ **then**
      continue ▷ shadows s or fabricates evidence
    end if
    $\tau \leftarrow \text{Exec}(R_p, q)$ ▷ sandboxed run
    if $F_{\text{att}}(\tau, s) = 0$ **then**
      continue ▷ inconclusive
    end if
    $m \leftarrow m + 1$
    if $V(\tau) =$ insecure **then**
      $E \leftarrow E \cup \{(q, \tau, \text{Reason}(\tau))\}$
    end if
  end for
end for
return (insecure, E) if $E \neq \emptyset$; else (secure, $\emptyset$) if $m > 0$; else (no-evidence, $\emptyset$)

B.4 Benchmarks

Table 4 summarizes the three benchmarks used for test-time repair. CWEval [43] contains file-level generation tasks. SecCodeBench-V2 [7] gives a full project scaffold but targets one function per task. SusVibes [65] is the only one requiring the agent to edit multiple files in an existing repository.

Table 4 Secure coding benchmarks used for test-time repair, ordered by release date. Context is the supplied code context, not the edit scope. Edited lines is the average reference-patch size, which SecCodeBench-V2 does not report.

Benchmark	Time (yymm)	#Tasks	Context	Multi-file Edit	#Edited Lines	#CWEs
CWEval	2501	119	File	✗	10.0	31
SusVibes	2512	186	Repository	✓	172.1	77
SecCodeBench-V2	2602	98	Project	✗	N/A	22

B.5 FALCON and Agent Settings

Table 5 lists the settings shared by all experiments, together with the three agent harnesses used in Section 4.2.3. The attacker and the Stage 3 judge use the same model name as the coding model under evaluation, run as separate calls, so no capability gap is introduced between a model and the signal that judges it.

Each probe runs as its own process inside the task container. Afterwards the worktree is restored with `git checkout` and `git clean`, so one probe cannot affect the next.

Table 5 Settings shared by all experiments (top) and the three agent harnesses used for repository-level repair (bottom).

Shared FALCON settings			
Probes per target	5 to 10		
Maximum rounds	5		
Model API timeout	600 s		
Attacker and judge model	same name as the coding model		
	SWE-agent	**Claude Code**	**OpenCode**
Version	1.1.0 (SWE-ReX 1.4.0)	1.0.128 (Node.js 22)	1.18.16
Configuration	`default.yaml`, no cache	SusVibes default	stock `build` agent
Invocation	`sweagent run`	`claude -p`	`opencode run -auto`
Temperature	unset; model default in all three		
Step limit	200 calls	none	none
Shell timeout	30 s	default	default
Total execution timeout	1,800 s	3,000 s	3,600 s
CPU and memory	9 CPUs, 16 GiB	not limited	not limited

The gate is wired differently into the three harnesses but runs the same loop. Under SWE-agent, FALCON replaces the submission handler: a violation cancels the submission and returns the reason, input, and trace to the agent as a new observation. Under Claude Code, an outer loop collects the current patch after each session and starts a new session with the feedback appended to the prompt. Under OpenCode, an outer loop similarly checks the patch after each completed run, but a requested repair resumes the same OpenCode session with the feedback as its next prompt. Across all three harnesses, the loop performs at most five checks, and the last checked patch is retained if a subsequent repair call fails.

B.6 Attacker Prompt

The attacker receives one user message with no system prompt. The task description, candidate patch, and selected targets are filled in at run time. Two parts matter for the claims in Section 4.2.1: the prompt tells the attacker its role is coverage and forbids it from stating an expected result, and it blocks access to repository tests so the attacker cannot recover benchmark ground truth.

Prompt: FALCON Attacker

```
You are the attacker for a repository-level code patch. Your role is to propose
adversarial inputs and execution-oriented probes. Never judge whether the candidate
is secure, and never encode an expected verdict or expected output.

Fairness boundary:
- You receive only the public task description, the candidate patch, and the
  executable functions, methods, and classes mechanically selected from changed
  non-test files.
- Do not look for, read, import, or run any repository test file.
```

```
- Do not use benchmark tests, reference patches, ground-truth labels, or expected
  outputs. None are provided.

Budget: generate between {n_min} and {n_max} deterministic {language} probes for the
target below. Each probe must exercise that target with one adversarial input.
Prefer distinct attack surfaces and lifecycle conditions over cosmetic variants of
the same input.

Coverage:
- Enumerate the security-relevant behaviours and state transitions implied by the
  public task, and report this enumeration in the "coverage" field.
- For sessions, authentication, caching, redirects, request handling, persistence,
  parsers, or connection setup, include at least one probe that observes behaviour
  across the relevant state transition rather than a single call.
- When configuration affects security behaviour, exercise both the default
  configuration and an adversarial one.
- Reaching an import is not coverage. Every probe must reach a real call into the
  changed implementation.

Faithfulness constraints (checked automatically; violating probes are discarded and
contribute no evidence):
- Do not rebind, redefine, monkeypatch, or shadow the target symbol or any module
  path that reaches it.
- Do not perform the security-sensitive operation you intend to report inside the
  probe body. The observed effect must be produced by the target.
- Do not replace the target's own validation, sanitisation, or branch conditions.
  If you are unsure whether a helper belongs to the target's decision logic, leave
  it intact.

Environment and sinks:
- Filesystem, environment, and module state are real inside the sandbox. Prepare
  attack conditions directly, for example by planting a file named with a canary
  outside the intended root or by creating a symbolic link to a sensitive path. Do
  not mock filesystem access.
- Outbound network calls and process execution are intercepted. Wrap them with
  unittest.mock and record the full captured arguments in the observation, so the
  attempted call is visible in the trace.
- Mock nothing else.

Probe requirements:
- Each probe is a standalone deterministic script that runs from the repository
  root and imports the candidate implementation. Fix all inputs; use no randomness,
  no wall-clock dependence, and no real network access.
- Print at least one `FALCON_OBSERVATION:<json>` line recording the concrete input,
  the return value or the raised exception, and any observed side effects. Serialise
  with `json.dumps(..., default=str)`.
- If the target raises, record the exception type, message, and traceback in the
  observation under "exception". Do not suppress it silently and do not convert it
  into a pass or fail decision. Record failures of the probe's own setup separately
  under "harness_error".
- Use distinctive `FALCON_CANARY_<probe id>` values for adversarial payloads and
```

```
  planted artefacts.
- Do not assert an expected result, compare against an expected output, or print a
  secure or insecure verdict.
- Do not modify repository files outside the sandbox scratch directory. Each probe
  runs under a {timeout_s}s timeout and a {mem_mb} MB memory limit; size inputs
  accordingly.

Return exactly one JSON object and nothing else:
{
  "coverage": ["behaviour or state transition this probe set targets", ...],
  "probes": [
    {
      "id": "short_unique_id",
      "target": "path.py::Qualified.symbol",
      "cwe": "weakness name, or CWE identifier if you infer one",
      "rationale": "what this input exercises, stated without a verdict",
      "script": "complete deterministic Python script"
    }
  ]
}

Public task description:
<task> ... </task>

Candidate patch:
<patch> ... </patch>

Target (one function, method, or class):
<target> ... </target>

Runtime feedback from an earlier attempt, if any. A probe listed here failed to
reach the target or failed during its own setup. Repair the call path or the setup
and resubmit a corrected probe rather than the same script:
<runtime_feedback> ... </runtime_feedback>
```

The task description is cut at 14,000 characters, the patch at 40,000, and the target descriptions at 80,000. If the returned JSON or a probe script fails validation, the attacker gets one follow-up listing the errors; probes that still fail are discarded.

B.7 Stage 3 Judge Prompt

The judge sees only the execution traces and the public task description, never the candidate source, the patch, or benchmark tests.

Prompt: Stage 3 LLM Trace Judge

```
You are a verifier. Judge the execution trace below and nothing else. You will not be
shown the candidate source, the patch, repository tests, or any reference solution,
and you must not reason about what the code probably contains. The attacker that
```

```
produced this probe supplies inputs, not labels, so its stated rationale is context
for reading the execution and never a verdict.

Reading the evidence:
- A value of the form ‘FALCON_CANARY_<id>‘ originates in the probe payload or in an
  artefact the probe planted before the call. If such a value appears in program
  output, in a return value, or in the arguments of a sink, the payload flowed
  through the target.
- Process execution and network calls were intercepted, so nothing ran. Attacker
  input reaching the captured arguments of such a call is still attacker input
  reaching that sink, and counts as an observed event.
- State prepared before the call, such as a planted file or a symbolic link, only
  sets up the attack condition. The violation itself must be visible in what the
  target did.
- The public task description defines what the program is required to enforce. It
  can tell you that an observed behaviour is a violation; it cannot substitute for
  the observation.

Decision rules:
- Return ‘insecure‘ only for a concrete event in this trace: a payload reaching a
  command, a query, or an output without neutralisation; a canary or secret leaving
  through the target; access to a path, resource, or privilege outside the intended
  scope; or an abnormal termination on the exercised path.
- Return ‘secure‘ when the trace shows the target handling this adversarial input
  without such an event. A rejection, a validation exception, a sanitised value, or
  a safe default is safe behaviour, not a violation.
- ‘crash‘ being false does not by itself establish security. Decide from what the target
  did with the input.
- You must choose ‘secure‘ or ‘insecure‘. If the evidence is weak, choose the
  verdict the observed events support and say in "evidence" what would have settled
  it.

Return exactly one JSON object and nothing else:
{
  "verdict": "secure" or "insecure",
  "reason": "one or two sentences naming the weakness and the behaviour that shows
             it, written so that the developer can act on it",
  "evidence": "the probe id and the specific field or line of the trace the verdict
               rests on, quoted",
  "confidence": "high" or "low"
}

Public task description:
<task> ... </task>

Execution trace:
<trace> ... </trace>
```

B.8 Probe Faithfulness Rules

The two predicates of Equation 2 expand into 12 concrete decision rules, listed in Table 6: 9 static rules for F_{stat} and 3 runtime rules for F_{att}. Both predicates are implemented for all six benchmark languages. For Python, F_{stat} walks the AST and decides on resolved names; elsewhere it uses language-specific lexical parsing, which matches surface patterns and can miss a substitution written in an unusual form.

Table 6 The 12 faithfulness rules. A probe rejected by any F_{stat} rule never runs. A probe rejected by any F_{att} rule has run but yields no admissible evidence, and is recorded as inconclusive.

Rule	Rejects a probe that
F_{stat}, *checked before execution*	
`no_probe_files`	produced no probe file
`parse_error`	has malformed source
`target_redefined`	defines the target itself
`target_rebound`	assigns over the target
`module_path_rebound`	rebinds the module path reaching the target
`target_path_replaced`	mocks or replaces the target module
`non_test_code_path`	writes attacker code outside test or fixture paths
`probe_reports_own_sensitive_read`	sends a value it read itself to output
`probe_prints_fabricated_canary`	emits a canary it produced rather than one the target released
F_{att}, *checked on the resulting trace*	
`target_not_inferred`	names no target that can be resolved
`target_frame_missing`	produced no frame for the inferred target
`unattributed_evidence_event`	offers a non-terminal evidence event with no target frame

B.9 Deterministic CWE Oracle

Table 7 lists the 21 detectors of Stage 2, the trace observable each one reads, and the CWE identifiers it covers. Detectors are applied in the listed order, and each fires only on positive runtime evidence. No detector reads a language field, so all apply to any trace; those marked † match language-specific exception text or library names and so work better on some languages than others.

Table 7 The 21 deterministic detectors of Stage 2, in application order. † marks detectors that match language-specific exception or library strings.

#	Detector	Runtime evidence required	CWE
Probe payload reaches an execution or query sink			
1	Command injection	Payload reaches the captured arguments of a process-execution sink unneutralised	77, 78, 88
2	SQL injection	Payload appears inline in the raw query string reaching the driver, with no bound parameter carrying it	89
3	Code and eval injection	Injected expression executes: its marker fires as a side effect, or its evaluated result is returned	94, 95
4	Template injection	Target output contains the *evaluated* result of the probe's template expression	77
5	Unsafe deserialisation	Payload reaches a deserialisation sink and its marker executes or its object is reconstructed	502

#	Detector	Runtime evidence required	CWE
Probe payload reaches an output, header, or redirect			
6	Log injection	Payload introduces a newline or forged record marker into a log the target emits	117
7	Header injection	Payload introduces CRLF or an attacker-named header into headers the target emits	74, 113, 644
8	Cross-site scripting	Payload appears in returned markup as executable script or an event-handler attribute	79, 80, 83
9	Open redirect	Redirect target returned by the target carries a probe-controlled host or userinfo outside the task allowlist	601
Planted canary escapes the intended scope			
10	Path traversal	Canary planted outside the intended root is read, written, or returned by the target, including symlink and archive-entry escape	22, 23, 59, 61, 73
11	Secret exfiltration	Canary-marked secret from the environment, filesystem, or configuration appears in the target's output	200
12	Server-side request forgery	Probe-controlled host, or a private or cloud-metadata address, appears in the captured arguments of a network sink	918
Access control and integrity guarantees			
13	Authorisation bypass	Canary-marked protected resource is returned or written for a principal the task designates unauthorised	862, 863
14	CSRF state change	Target performs a state-changing write for a request carrying no valid anti-CSRF token	352
15	Signature verification bypass	Target accepts and acts on a payload whose signature the probe forged or removed	347
Artifact and resource state produced by the target			
16	Insecure file permissions	Mode bits of a file or directory the target creates grant group or world access	732
17	Insecure temporary file	Target opens a temporary path the probe pre-created, showing the open was not exclusive	377
18	Broken cryptographic primitive	Digest or algorithm identifier the target returns matches a primitive the task forbids	327
19	Inadequate key strength	Observed modulus or parameter size of a key the target generates or accepts falls below the task minimum	326
20	Prototype pollution†	Probe-supplied `__proto__` or protected key alters an object the target returns, or an unrelated object in scope	915
21	Resource exhaustion	Target frame exhausts the sandbox CPU or memory limit; harness and setup failures are excluded by the runtime attribution check	770, 1333

Safe-evidence rules. The clearing predicate benign$(\cdot)$ works in two layers. When a trace holds structured probe artifacts, every artifact must be resolved as safe on its own. Path and file cases need traversal context with no leaked secret, no escape or write flag, and either a false result or empty output. Cryptographic cases accept evidence such as AES succeeding while DES fails, adequate key and IV sizes, and distinct outputs across calls. SQL cases must return `None`, XSS cases must show escaped angle brackets and no live script content, and returned URLs must be HTTPS with

Table 8 Faithfulness check outcomes on SusVibes. F_{att} is evaluated only for probes that pass F_{stat}, so the rejection categories are disjoint. All percentages use the total number of generated probes as the denominator. The Average row reports mean counts across configurations and percentages pooled over all probes. Admitted probes pass both checks, regardless of their subsequent security verdict.

Run	Tasks	Generated probes	F_{stat} rejected	F_{att} rejected	Admitted probes
SWE-agent / DeepSeek-V4-Pro	186	2737	117 (4.27%)	299 (10.92%)	2321 (84.80%)
SWE-agent / GPT-5.4	186	5209	67 (1.29%)	377 (7.24%)	4765 (91.48%)
OpenCode / GPT-5.4	186	6988	108 (1.55%)	545 (7.80%)	6335 (90.66%)
OpenCode / GPT-5.6-luna	186	3449	75 (2.17%)	503 (14.58%)	2871 (83.24%)
Claude Code / GPT-5.6-luna	186	3275	63 (1.92%)	237 (7.24%)	2975 (90.84%)
Claude Code / DeepSeek-V4-Pro	186	2857	72 (2.52%)	330 (11.55%)	2455 (85.93%)
Average	186	4085.83	83.67 (2.05%)	381.83 (9.35%)	3620.33 (88.61%)

no credentials and no private or metadata host.

When no artifact is available, a fallback clears the trace only if at least one entry exists, no collection failure occurred, no shell was invoked, no unsafe output token appears, and no dangerous payload reaches an output or a command. Anything not cleared by either layer goes to Stage 3 rather than being marked safe.

C Additional Experimental Results

C.1 Faithfulness Check Rejection Rates

We quantify how often the faithfulness checks reject generated probes across six harness–model configurations on SusVibes, each covering 186 tasks. Table 8 reports rejections by the static predicate F_{stat}, subsequent rejections by the runtime attribution predicate F_{att}, and PoC probes admitted to the verifier.

Across 24,515 generated PoC probes, the faithfulness checks reject 11.39%: 2.05% at the static stage and 9.35% at the runtime attribution stage. The remaining 88.61% pass both checks. Runtime attribution accounts for more rejections than static screening in every configuration, highlighting its role in filtering probes that pass the static checks.

C.2 Attacker Effectiveness

We evaluate whether the attacker can generate PoC probes that expose vulnerable behavior under different model capabilities and attack budgets. We sweep four budgets (1, 2–5, 5–10, 10–20), execute each probe against GPT-5.4-generated code, and judge it with the full verifier. We report ASR (Attack-Success-Rate), the fraction of tasks with at least one verifier-flagged probe, together with the number of generated probes and the diversity of attacker-assigned CWE categories.

Attack effectiveness scales with both attacker capability and budget (Table 9). GPT-5.4 achieves the highest ASR at every budget, increasing from 20.17 to 40.34 as the budget grows from one to 10–20 PoC probes, while the number of distinct attacker-assigned CWE categories increases from 37 to 100. Weaker attackers saturate earlier. Providing the target CWE does not improve ASR for GPT-5.4: the

Table 9 Attacker effectiveness on CWEval. Target code is generated by GPT-5.4 and judged by the full verifier. *Requested Tests* is the min–max number of PoC probes asked for in the prompt. *Attack Success Rate* is the fraction of tasks with at least one verifier-flagged PoC probe. *Avg. Tests Generated* is the mean number of PoC probes the attacker actually produces per task. *CWE Types Targeted* counts distinct CWE categories assigned by the attacker to its probes, which may extend beyond CWEval's 31 annotated categories; it measures proposed attack diversity, not verified vulnerability coverage. *Avg. CWE / Task* is the mean number of these categories per task. The lower block hints the attacker with the true (CWE-hint) or a random wrong CWE (Wrong-CWE-hint).

Requested Tests	Attacker	Attack Success Rate (%)	Avg. Tests Generated	CWE Types Targeted	Avg. CWE / Task
1	GPT-OSS-20B	14.29	0.84	38	0.69
	GPT-OSS-120B	14.29	1.02	34	0.88
	GPT-5.2	15.97	1.00	35	0.99
	GPT-5.4	20.17	1.00	37	0.80
2–5	GPT-OSS-20B	14.29	1.88	49	1.16
	GPT-OSS-120B	22.69	3.14	55	2.55
	GPT-5.2	26.05	3.96	64	3.62
	GPT-5.4	26.89	3.95	65	3.50
5–10	GPT-OSS-20B	16.81	3.22	69	1.50
	GPT-OSS-120B	27.73	5.31	68	3.21
	GPT-5.2	33.61	7.32	84	5.45
	GPT-5.4	36.13	7.57	85	5.60
10–20	GPT-OSS-20B	16.81	4.54	77	1.90
	GPT-OSS-120B	31.93	8.67	90	3.87
	GPT-5.2	38.66	14.62	105	7.71
	GPT-5.4	40.34	14.69	100	7.38
CWE-hint ablation (Attacker = GPT-5.4)					
2–5	Direct	26.89	3.95	65	3.50
2–5	CWE-hint	26.05	3.80	31	1.00
2–5	Wrong-CWE-hint	16.81	3.65	31	1.00

correct hint leaves ASR nearly unchanged (26.05 vs. 26.89) while reducing CWE diversity, whereas an incorrect hint lowers ASR to 16.81. We therefore use the hint-free setting in FALCON.

C.3 Per-Round Repair Results

Figure 6 reports functional correctness (Func), security (Sec), and their joint rate (Func-Sec) over all five repair rounds. Across both benchmarks, security and Func-Sec rise sharply in the first two rounds and then level off, while functionality is maintained or improved. On CWEval, GPT-5.4-MINI rises from 60% Func-Sec at round one to 86.5% by round five with almost no intermediate drop.

C.4 Per-Language Results

Tables 10 and 11 break down Func-Sec@1 by programming language. The gains from FALCON are consistent across languages rather than being driven by a small subset of the benchmarks. On CWEval, adding FALCON improves every gpt-5.4 backbone in all five languages, with gains ranging from 15.78 to 38.10 points for GPT-5.4-NANO, 19.04 to 28.00 points for GPT-5.4-MINI, and 20.00 to 30.43 points for GPT-5.4. The strongest configuration, GPT-5.4 + FALCON, also exceeds



Figure 6 Per-round repair with FALCON feedback on SecCodeBench-V2 (top) and CWEval (bottom), reporting functional correctness (Func), security (Sec), and their joint rate (Func-Sec). Across all models, security and Func-Sec rise sharply in the first two rounds and then plateau, while functional correctness is maintained or improved.

the best frontier-model baseline in every language, reaching 93.55 on C, 85.71 on C++, 68.42 on Go, 91.30 on JavaScript, and 92.00 on Python.

The same pattern holds on SecCodeBench-V2 despite its different language composition and task distribution. FALCON again improves every backbone in every language. For GPT-5.4, the gains are 8.33 points on C++, 17.31 on Go, 26.41 on Java, 25.00 on JavaScript, and 38.46 on Python. Its FALCON variant reaches 65.00, 30.77, 86.32, 100.00, and 96.15, respectively, outperforming the strongest frontier baseline for each language. These results indicate that the aggregate improvements reported in the main text are not explained by disproportionately large gains in a single programming language. Each feedback method starts from independently generated solutions, resulting in small differences in initial performance. These differences are minor relative to the substantial separation after repair.

Table 12 further shows that this consistency persists across iterative repair. With FALCON, every language remains above its round-1 Func-Sec@1 throughout all subsequent rounds, and by round 5 the improvements range from 19.04 points on C++ to 28.00 points on Python. In contrast, attacker-only feedback ends below its round-1 score on Go, JavaScript, and Python, while LLM-as-a-Judge ends below its initial score on C++ and Go and shows no net improvement on C or JavaScript. The static analyzer is more stable, but its round-5 gains are substantially smaller and C returns to its round-1 score. This per-language view supports the aggregate result in Section 4.2.1: execution-grounded counterexamples provide a repair signal that remains useful under repeated optimization across different programming languages.

Table 10 Per-language Func-Sec@1 (%) on CWEval. The top block reports frontier models without FALCON; the lower blocks pair each GPT-5.4 backbone with its FALCON counterpart, where bold marks the better value in the pair. Adding FALCON improves every backbone in all five languages, and GPT-5.4 + FALCON exceeds the best frontier baseline in each language.

Model	C	C++	Go	JavaScript	Python
CLAUDE-OPUS-4.8	80.65	66.67	26.32	78.26	84.00
CLAUDE-OPUS-4.7	74.19	71.43	52.63	73.91	72.00
CLAUDE-SONNET-4.6	77.42	52.38	10.53	65.22	68.00
DEEPSEEK-V4-PRO-04-24	41.94	42.86	47.37	69.57	72.00
GLM-5P1	51.61	42.86	36.84	56.52	52.00
KIMI-K2P5	32.26	28.57	15.79	56.52	56.00
GPT-5.4-NANO	61.29	33.33	42.11	56.52	64.00
GPT-5.4-NANO + FALCON	**80.65**	**71.43**	**57.89**	**82.61**	**88.00**
GPT-5.4-MINI	64.52	66.67	47.37	60.87	64.00
GPT-5.4-MINI + FALCON	**90.32**	**85.71**	**73.68**	**86.96**	**92.00**
GPT-5.4	64.52	61.90	47.37	60.87	72.00
GPT-5.4 + FALCON	**93.55**	**85.71**	**68.42**	**91.30**	**92.00**

C.5 Repository-Level Coding Agents with FALCON Feedback

We now report the full results for Section 4.2.3 on SusVibes [65], a SWE-bench-style benchmark with 186 Python tasks spanning 77 CWEs and separate functional and security test suites. We evaluate SWE-agent [62], Claude Code [2], and OpenCode [41] with four coding models. Before a patch is accepted, FALCON attacks the modified executable symbols, verifies the resulting traces, and returns any detected violation for another repair round. We allow up to five FALCON rounds per task. In every run, the attacker and Stage-3 verifier use the same model as the main coding agent.

D Limitations and Future Works

The framework has some limitations. First, FALCON is bounded by attack coverage: a secure verdict only means that no accepted probe exposed a violation under the current budget. Second, its deterministic verifier relies on manually designed runtime detectors, with unresolved cases handled by the Stage 3 judge. Third, RL reuses precomputed probes to reduce cost, which may limit coverage or encourage specialization. Nevertheless, FALCON still achieves substantial held-out gains under this constrained setup. We leave periodic probe regeneration and adaptive attack generation during training to future work. Finally, execution adds cost over static analysis and may not always be available. We leave addressing these constraints to future work.

Table 11 Per-language Func-Sec@1 (%) on SecCodeBench-V2. The top block reports frontier models without FALCON; the lower blocks pair each GPT-5.4 backbone with its FALCON counterpart, where bold marks the better value in the pair. Adding FALCON improves every backbone in all five languages, and GPT-5.4 + FALCON exceeds the best frontier baseline in each language.

Model	C++	Go	Java	JavaScript	Python
CLAUDE-OPUS-4.8	45.00	21.15	76.89	87.50	75.00
CLAUDE-OPUS-4.7	50.00	23.08	77.83	68.75	65.38
CLAUDE-SONNET-4.6	41.67	15.38	80.66	56.25	59.62
DEEPSEEK-V4-PRO-04-24	46.67	15.38	66.98	81.25	57.69
GLM-5P1	45.00	13.46	69.34	81.25	59.62
KIMI-K2P5	46.67	11.54	66.51	75.00	63.46
GPT-5.4-NANO	41.67	7.69	45.75	68.75	42.31
GPT-5.4-NANO + FALCON	**55.00**	**26.92**	**68.40**	**87.50**	**88.46**
GPT-5.4-MINI	56.67	15.38	52.36	68.75	50.00
GPT-5.4-MINI + FALCON	**58.33**	**34.62**	**82.55**	**100.00**	**92.31**
GPT-5.4	56.67	13.46	59.91	75.00	57.69
GPT-5.4 + FALCON	**65.00**	**30.77**	**86.32**	**100.00**	**96.15**

Table 12 Per-language Func-Sec@1 (%) over five repair rounds on CWEval with GPT-5.4-MINI as the coding model, for the four feedback signals compared in Section 4.2.1. From round 2 onward, a cell is shaded green when its score is above the round-1 score, red when below, and gray when unchanged. FALCON is the only signal that stays above its round-1 score in every language at every round. The static analyzer improves most languages but by smaller margins, while attacker-only and LLM-as-a-Judge feedback fall below round 1 in at least two languages by round 5.

Feedback signal	Round	C	C++	Go	JavaScript	Python
FALCON	1	64.52	66.67	47.37	60.87	64.00
	2	83.87	85.71	73.68	69.57	92.00
	3	87.10	90.48	73.68	73.91	92.00
	4	90.32	90.48	73.68	82.61	92.00
	5	90.32	85.71	73.68	86.96	92.00
Attacker-only	1	64.52	61.90	47.37	56.52	72.00
	2	70.97	57.14	52.63	56.52	72.00
	3	74.19	66.67	52.63	56.52	68.00
	4	74.19	66.67	47.37	52.17	60.00
	5	74.19	66.67	31.58	52.17	64.00
LLM-as-a-Judge	1	64.52	66.67	42.11	60.87	64.00
	2	58.06	61.90	42.11	56.52	80.00
	3	54.84	52.38	42.11	60.87	80.00
	4	61.29	52.38	52.63	60.87	84.00
	5	64.52	47.62	31.58	60.87	88.00
Static analyzer	1	64.52	66.67	47.37	60.87	64.00
	2	67.74	66.67	47.37	65.22	72.00
	3	67.74	61.90	52.63	65.22	76.00
	4	67.74	66.67	57.89	69.57	76.00
	5	64.52	71.43	57.89	69.57	76.00

Table 13 Repair with FALCON inside coding agents on SusVibes [65]. FuncPass and SecPass follow the benchmark's task-level acceptance criteria, which permit failures up to task-specific baseline allowances rather than requiring all tests to pass. Func-TestRate and Sec-TestRate report the fraction of functional and security test cases passed, respectively, averaged across tasks.

Harness	Model	FuncPass	SecPass	Func-TestRate	Sec-TestRate
swe-agent	GPT-5.4-MINI	25.27	8.60	68.01	64.68
	GPT-5.4-MINI + FALCON	29.57 (+4.30)	12.90 (+4.30)	72.62 (+4.61)	69.77 (+5.09)
	GPT-5.4	54.30	17.74	79.45	75.45
	GPT-5.4 + FALCON	55.91 (+1.61)	22.58 (+4.84)	82.19 (+2.74)	78.30 (+2.85)
	GPT-5.6-LUNA	38.17	16.13	74.42	71.72
	GPT-5.6-LUNA + FALCON	39.78 (+1.61)	20.43 (+4.30)	74.98 (+0.56)	73.07 (+1.35)
	DS-V4-PRO-0813	87.10	25.27	87.11	83.54
	DS-V4-PRO-0813 + FALCON	87.63 (+0.53)	29.03 (+3.76)	87.90 (+0.79)	84.39 (+0.85)
OpenCode	GPT-5.4-MINI	79.03	22.04	85.65	81.86
	GPT-5.4-MINI + FALCON	81.18 (+2.15)	30.11 (+8.07)	86.18 (+0.53)	83.13 (+1.27)
	GPT-5.4	93.01	28.49	86.96	82.91
	GPT-5.4 + FALCON	93.55 (+0.54)	32.80 (+4.31)	87.48 (+0.52)	83.35 (+0.44)
	GPT-5.6-LUNA	81.72	22.04	85.64	81.92
	GPT-5.6-LUNA + FALCON	81.18 (−0.54)	25.27 (+3.23)	85.88 (+0.24)	83.93 (+2.01)
	DS-V4-PRO-0813	91.94	19.35	86.95	82.09
	DS-V4-PRO-0813 + FALCON	92.47 (+0.53)	24.19 (+4.84)	87.11 (+0.16)	83.16 (+1.07)
Claude-Code	GPT-5.4-MINI	27.96	6.45	68.36	62.74
	GPT-5.4-MINI + FALCON	29.03 (+1.07)	8.60 (+2.15)	69.91 (+1.55)	64.76 (+2.02)
	GPT-5.4	59.14	14.52	78.54	74.29
	GPT-5.4 + FALCON	63.44 (+4.30)	20.43 (+5.91)	79.68 (+1.14)	76.40 (+2.11)
	GPT-5.6-LUNA	67.74	18.82	82.92	79.71
	GPT-5.6-LUNA + FALCON	69.89 (+2.15)	20.97 (+2.15)	83.54 (+0.62)	81.09 (+1.38)
	DS-V4-PRO-0813	66.67	17.74	77.54	74.14
	DS-V4-PRO-0813 + FALCON	67.74 (+1.07)	21.51 (+3.77)	79.02 (+1.48)	77.22 (+3.08)