

STAIR (STructure Aware Information Retriever): A novel dataset and LLM based retriever for document structure augmentation

Vineet Kumar* Meghanadh Pulivarthi Vishwajeet Kumar Jaydeep Sen
Riyaz Ahmad Bhat Sachindra Joshi

IBM

vineet.mundhra@gmail.com vishk024@in.ibm.com

jaydesen@in.ibm.com Riyaz.Bhat@ibm.com jsachind@in.ibm.com

Abstract

Retrieval Augmented Generation (RAG) is a key component for generating accurate and hallucination free answers using Large Language Models (LLMs). LLMs are improving at handling long context, but still suffer from “lost in the middle” problem. Thus, precise and accurate retrieval is important. Current retrievers chunk long context into length-based manageable chunks – in the process throwing away rich and informative semantic global structure in the corpus. We introduce a novel retrieval system **STAIR** that empowers an LLM to exploit global structure in a corpus such as a Table of Contents (**ToC**) to efficiently store and retrieve information from its model parameters. Our thorough and careful ablation studies with a finetuned Differentiable Search Index (DSI) system show that **ToC** helps build a low hallucination (less than 0.05%) generative Information Retrieval (IR) system and can generalize to examples where very few training samples are available. To further research in this novel direction of **ToC** based retrieval we release **SearchTome** – a diverse benchmark created from 18 books across 6 diverse domains to further research in this novel direction. **STAIR** achieves a high Recall@1 score of 82.6% on **SearchTome** as compared to DSI (76.9%), where the difference is found to be statistically significant. **STAIR** easily beats other strong baselines such as BM25 (59.5%), DPR (68.7%) and out-of-the-box Mistral (13.8%). The benchmark data and code used for training **STAIR** is available at https://anonymous.4open.science/r/s_331/README.md.

1 Introduction

The burgeoning interest in Retrieval Augmented Generation (RAG) has led to a significant surge in the development of advanced Information Retrieval (IR) systems. Large Language Models (LLMs) in

turn can now handle large contexts (Chen et al., 2023; Liu et al., 2024a), though they suffer from a “lost in the middle” problem (Liu et al., 2024c; Bai et al., 2024a,b; Li et al., 2024). Therefore, retrieving precise information (Pipitone and Alami, 2024) is extremely important to curb hallucinations (Laban et al., 2024) and generate accurate responses. Current retrievers address this by creating length based chunks (Setty et al., 2024) and throwing away rich and informative semantic global structure in the corpus. This leads to a sub-optimal retrieval quality – length-based chunks compete with each other due to a lack of semantic coherence and boundaries.

In this work, we address this key limitation by augmenting the retriever with a structured global view of the corpus. Global structured view over a long context helps knowledge ingestion (Liu et al., 2024b). Further, LLMs are capable of storing the entire corpus in its model parameters to directly generate a document identifier for a user query (Tay et al., 2022). We posit that by empowering an LLM with a global structure of the search corpus, it can store and retrieve information more accurately from its model parameters. Such a global structure already exists for a Wikipedia (Wikipedia, 2024) page, textbooks, and enterprise help and product feature webpages (SAP, 2024) and technical reports (SEC, 2024).

Figure 1 demonstrates that for a question such as “What is the plurality voting system?”, it is natural for a human to consult the **ToC** and first narrow down that it could be answered by the Chapter “Democracies and Democratization”. Further subsections reveal that perhaps the Section “Institutions within Democracy” and the subsection “Electoral Systems & Political Parties” could contain the answer. Content for this subsection indeed contains the definition for the plural voting system. Text content associated with **ToC** entries is semantically coherent organized around a topic as captured by

*Work done while at IBM. Currently at Amazon Books Science.

Table of Contents

Chapter 1: Why Study Comparative Politics	1
Chapter Outline	1
1.1: What is Comparative Politics?	1
Learning Objectives	1
1.1.1: Overview	2
1.1.2: A Brief History and Expanded Definition	10
Chapter 4: Democracies and Democratization	93
Chapter Outline	93
4.1: What is Democracy?	93
Learning Objectives	93
4.1.1: Origins, Definitions and Characteristics of Democracy	95
4.1.2: Types of Democracy	100
4.2: Institutions within Democracy	101
Learning Objectives	101
4.2.1: Executive, Legislative and Judicial	101
4.2.3: Electoral Systems & Political Parties	103
4.3: Systems of Democracy	104
Learning Objectives	104
4.4: Democratic Consolidation	107
Learning Objectives	107
4.5: Comparative Case Study – Pathways to Democratization: South Africa & Iraq	110
Learning Objectives	110
4.5.1: South Africa	111
4.5.2: Iraq	114

Content ⇒

Book Title: Introduction to Comparative Government and Politics

Query: What is the plurality voting system?

Rules that are relevant to an electoral system can include those that lay out when elections occur, who is allowed to vote, who is allowed to run as a candidate, how ballots are collected and can be cast, how ballots are counted, and what constitutes a victory. Usually, voting rules are set forth by constitutions, election laws, or other legal mandates / establishments. There are a number of different types of electoral systems. First, the **plurality voting system** is one where the candidate who gets the most votes, wins.

Figure 1: A human can answer “What is the plurality voting system?” by looking at the table of contents and picking Section 4.2.3 without even reading the book [Introduction to Comparative Government and Politics](#).

the title of the **ToC** entry. Further, a **ToC** entry has a clear semantic boundary with other **ToC** entries. **ToC** as a unit of retrieval is a novel yet intuitive way of organizing long context for retrieval.

In this work, we present **STAIR** (**ST**Structure **A**ware **I**nformation **R**etriever) for **ToC** based retrieval, inspired by how a human searches for information using **ToC**, and the fact that LLMs can store the entire corpus in the model’s parameters. Our careful and thorough ablation studies reveal that empowering an LLM with **ToC** helps in two critical dimensions - curbing hallucinations and generalizing for content with a low number of training examples. **STAIR** achieves a high Recall@1 score of 82.6, which is (+7.4%) better than its closest baseline Differentiable Search Index (DSI) ([Tay et al., 2022](#)). DSI needs to discover the book structure (indirectly) through the completion part of training examples, while **STAIR** can use exploit the structure provided as part of the input to accurately store and retrieve information from its model’s parameters.

We develop and release a new multi-domain benchmark **SearchTome**, made up of 18 books of varying sizes across 6 domains, parsed and cleaned to extract their **ToC** mapped to the text of the pertinent sections. We also release a set of train, dev and test queries for each book as part of the benchmark, with gold **ToC** entries labeled for each query serving as the retrieval output. We believe this will be a first step towards promoting further research

on **ToC** based retrieval, with **SearchTome** serving as a standard evaluation benchmark. We train and evaluate **STAIR** using **SearchTome** and compare it with strong baseline retrievers like BM25 and a fully fine-tuned Sequence-to-Sequence model, such as DSI ([Tay et al., 2022](#)), which does not utilize **ToC**. Our experimental results show that **STAIR** significantly benefits from incorporating **ToC** in its training and easily outperforms the traditional DSI. Our main contributions are as follows:

- We propose a novel direction leveraging the Table of Contents (**ToC**) of a lengthy corpus, like a book, as a valuable element for efficiently indexing corpus knowledge and utilizing **ToC** entries as effective retrieval units.
- We build and release a multi-domain and diverse benchmark **SearchTome**, consisting of 18 books from 6 diverse domains for the task of **ToC** retrieval
- We develop an LLM based **STAIR** and evaluate it on **SearchTome** and compare it with strong competitive baselines

2 Related Work

Efficient and precise retrieval is a critical research problem in natural language processing, with a wide range of applications such as semantic search ([Guha et al., 2003](#)), open domain question answering ([Chen and Yih, 2020](#); [Zhu et al., 2021](#)) and Retrieval Augmented Generation(RAG) ([Lewis et al., 2020](#)) to name a few.

With the rise of RAG applications, precise retrieval has become increasingly important, particularly in curbing hallucination in generative models. We can broadly classify all retrieval techniques into three main categories:

Dense Retrieval (Cai et al., 2021; Karpukhin et al., 2020) represent a query and document using a dense vector and compute the similarity based on the distance between their vectors. DPR (Karpukhin et al., 2020) uses dual encoder, ColBERT (Khattab and Zaharia, 2020) represents every token in the query and document using dense vector and performs late interaction to score query and document pairs. Recently, Sarthi et al. (2024) introduced RAPTOR, a method for building a hierarchical tree by recursively embedding, clustering, and summarizing content from lengthy documents to retrieve relevant text at various levels of abstraction. Our approach differs in two key aspects: while RAPTOR uses dense retrievers for indexing and retrieval, we adopt model-based indexing. Additionally, we enhance model-based indexing by leveraging table-of-contents (ToC) structures, unlike RAPTOR, which relies solely on dense retrievers to access information at multiple levels of abstraction.

Learned Sparse Retrieval systems use sparse vector representation for a query and document. Unlike traditional sparse retrieval methods like BM25 (Robertson and Zaragoza, 2009), which rely on exact token matches, these models learn to represent queries and documents in a sparse high-dimensional space, allowing for efficient lexical matching. SPLADE (Hai et al., 2023) (Sparse Lexical and Expansion Model for Information Retrieval) is a prominent example of such systems. Several other models have been developed to enhance sparse retrieval, including SPLADEv2 (Formal et al., 2021), DeepCT (Dai and Callan, 2019), uniCOIL (Lin and Ma, 2021) and DeepImpact (Basnet et al., 2024).

Model-based Indexing (Metzler et al., 2021) such as Differential Search Index (DSI) (Tay et al., 2022) embed knowledge of the entire corpus directly into its model parameters – greatly simplifying the retrieval process. **STAIR** takes this paradigm one step further by learning to exploit a rich hierarchical and semantic global structure within the corpus.

3 SearchTome: A new benchmark for Table of Contents based retrieval

3.1 Breaking the Mold: Why a New Benchmark Is Needed

There are multiple benchmarks proposed around long context applications such as ContractNLI (Koreeda and Manning, 2021) focused on NLI or **Scrolls** (Shaham et al., 2022) with seven challenging tasks. However, there doesn't exist any benchmark for long context retrieval with any form of structured view, which we hypothesize as the key for precise retrieval. Benchmarks such as GovReport (Huang et al., 2021), SummScreen (Chen et al., 2022), and QM-Sum (Zhong et al., 2021) focus on generating summaries of a lengthy document, whereas, Qasper (Dasigi et al., 2021), QuALITY (Pang et al., 2022) and NarrativeQA (Kočíský et al., 2018) focus on the generation aspect with **only answers** for a user query and **do not contain the gold passage for retrieval**. The closest benchmark is **LocoV1** (Saad-Falcon et al., 2024) which does include gold passages for each query. However, due to **lack of ToC or a global structure for the input document**, we cannot use this benchmark for our task.

To the best of our knowledge, **SearchTome** is the first benchmark which provides a clean structured view with Table of Contents for evaluating long context retrieval with structures.

3.2 SearchTome: A diverse and novel benchmark for ToC Retrieval

Our main motivation for a new benchmark is to evaluate how well a global semantic structure such as a **ToC** can help in better retrieval for long context applications which is typical for technical reports or voluminous books. Thus to create a clean and effective benchmark we turn to [opentextbooks](#), which is perhaps the largest collection of such textbooks. To make the benchmark a comprehensive one across domains, we picked six diverse domains namely – Education, Finance, Law, Medicine, Natural Sciences and Social Sciences and selected three books from each domain (Table 1). We parsed the PDF for each book and extracted Table of Contents using `pymupdf`¹. A sample of the final cleaned content for one of the books can be viewed [here](#). For each paragraph we ask a powerful LLM Mixtral 8x7b model (Jiang et al., 2024) to generate multiple questions covering all important topics in the

¹<https://pymupdf.readthedocs.io/en/latest/>

Table 1: **SearchTome** Book links & Statistics

Domain	Book	#Pages	#Leaves	Test	Train	Dev
Education	Open Music Theory	1297	429	7430	4493	1671
	The Whole Child: Development in the Early Years	182	129	1746	1056	388
	Teaching in a Digital Age	779	118	6150	3797	1489
Finance	Principles of Financial Accounting	318	98	4119	2395	981
	Accounting in the Finance World	572	80	4481	2747	1081
	Financial and Managerial Accounting	1077	107	7815	4692	1901
Law	Construction Contracting	403	103	3653	2249	866
	Criminal Procedure	897	106	5610	3401	1349
	Tort Law: Cases and Commentaries	948	396	18209	11174	4363
Medicine	Nursing Assistant	659	118	4586	2790	1093
	Nursing Fundamentals	1327	121	9065	5493	2200
	Nursing Management and Professional Concepts	599	74	3695	2277	885
Natural Sciences	Introduction to Genetics	513	70	2254	1345	527
	Principles of Mechanics	179	125	2341	1418	543
	Organic Chemistry	1249	321	11124	6601	2635
Social Sciences	Foundations of Aural Skills	674	118	2451	1421	559
	Introduction to Comparative Government and Politics	421	189	3893	2288	898
	A Practicum in Behavioral Economics	381	178	4627	2821	1073

paragraph (Zhang et al., 2024). Following the same technique as was proposed in DSI (Tay et al., 2022) to train the parametric index, we use a portion of these questions for training DSI (Tay et al., 2022) and **STAIR**, a small portion as development set which is to help us pick the best checkpoint. Majority of the generated questions were picked as test questions – to thoroughly test coverage of content by an IR system. We believe our benchmark **SearchTome** will further research in building IR systems which can leverage structure in a corpus and retrieve the most relevant chunks for a user query.

4 STAIR: Table of Contents Searcher

We now formally define the problem statement and the technique for retrieving a section title given a book and its Table of Contents (**ToC**)

4.1 Notations

We are given a long document D and its Table of Contents $\mathbf{ToC}_D = \{T_1, T_2, \dots, T_n\}$. An edge $e : T_p \rightarrow T_c$ between two nodes $T_p, T_c \in \mathbf{ToC}_D$ is defined as $T_p = \text{parent}(T_c)$, if the section represented by title T_p is further divided into multiple sub-sections including T_c . The set of leaf nodes can thus be defined as $LN_D = \{T_l \in \mathbf{ToC}_D | \exists! T_c \in \mathbf{ToC}_D, T_l = \text{parent_of}(T_c)\} \subseteq \mathbf{ToC}_D$. Our goal is to retrieve the correct leaf node $T_l \in LN_D$ whose content can answer a user query q .

4.2 Training STAIR

Figure 2 depicts the training pipeline for **STAIR** which learns two correlated but *different* tasks:

Corpus knowledge ingestion: **STAIR** needs to learn the information trove D by mapping a book’s text content to the corresponding section titles $T_i \in \mathbf{ToC}_D$. This is facilitated by the training data, which consists of a series of queries that are linked to their corresponding section titles. Consequently, this phase of training integrates the book’s knowledge into the LLM’s parameters, similar to model-based indexing systems like DSI, but with a key difference. Unlike other model-based indexing systems, the parameters in **STAIR** remember the corpus knowledge not by a document identifier, but by using fine-grained section title entries in the **ToC**, which are likely to have a much stronger semantic connection with the content being ingested into parametric knowledge.

Learning to generate from ToC: **STAIR** learns to pick the most relevant leaf node from the complete global structure (**ToC**) of a document.

We use the training split from **SearchTome** to train **STAIR** through supervised fine-tuning. During training, we provide the query q along with the complete $\mathbf{ToC}_D$ as input. Consequently, the complete input during training consists of *prompt* + $(q, \mathbf{ToC}_D)$. Note that $\mathbf{ToC}_D$, remains consistent across queries from the same book, while the prompt remains unchanged throughout the training process. We fine-tune the model to generate the correct leaf node $T_l \in LN_D$ that corresponds to




Figure 2: Overview of our pipeline. Stage 1 prepares synthetic QA data from the input book. Stage 2 fine-tunes a language model to map a ToC-augmented query to the correct leaf node. Stage 3 runs inference with constrained generation, restricting the output vocabulary to valid ToC leaf nodes.

the query q .

Table 2: Sample training example

Prompt
Book: Teaching in a Digital Age Pick the best section from the table of contents below which can answer the user query below. Only generate the section name, do not generate any explanation! ### Table of Contents 1 Chapter 1: Fundamental Change in Education ... leaf 12.7 Step five:master the technology leaf 12.8 Step six:set appropriate learning goals leaf 12.9 Step seven:design course structure and learning ... leaf 13.7 Building the future ### Query: What is the suggested time allocation for students studying a course or program? ### Section: leaf
Completion
12.9 Step seven: design course structure and learning

5 Experiments

We report Recall@1 (R@1), Recall@3 (R@3) and Normalized Discounted Cumulative Gain (nDCG@3) metrics on the test set for each book. BeIR (Thakur et al., 2021) is used for computing the metrics.

5.1 Baselines

Mistral (Out of the Box LLM): Beam search is used to generate the Top- K predictions for Mistral Instruct v0.2

BM25 (Robertson and Zaragoza, 2009): We index content using Elastic Search v 8.11.2. Leaf node acts as a unique document identifier for a book

DPR: We use NV-Embed-v2(Lee et al., 2024) out of the box with text lengths set to 512 for passages and 256 for queries. NV-Embed-v2 is the leading text-only embedding model with open weights on the MTEB leaderboard². The model is based on Mistral-7B-v0.1³, making it a suitable baseline for **STAIR** as both are finetuned over Mistral.

DSI (Tay et al., 2022) infuses the entire knowledge of a corpus in the parameters of an LLM and directly generates a document identifier. We fine-tune DSI using the train split for each book.

5.2 Fine-tuning STAIR and DSI

We fine-tune Mistral Instruct v0.2⁴ (Jiang et al., 2023) for a maximum of 200 epochs using a LoRA adapter (Hu et al., 2021) with a $r = 16$ and $\alpha = 32$. We early stop with a patience of 20 epochs, by computing Recall@1 on the dev set. We set the maximum input length to 14k tokens for **STAIR**

²As per Jan 23’2025 MTEB Leaderboard Snapshot.

³<https://huggingface.co/mistralai/Mistral-7B-v0.1>

⁴<https://huggingface.co/mistralai/Mistral-7B-Instruct-v0.2>

and 512 tokens for DSI and a maximum output length of 64 tokens. See Table 2 for a sample training input and output for **STAIR**.

6 Results and Analysis

Table 4 compares **STAIR** with all the baselines listed in Section 5.1 and addresses the following two research questions:

- **RQ1:** Does **ToC** based training makes **STAIR** more accurate as a retriever?
- **RQ2:** Can we finetune an LLM to learn the new task of generating leaf nodes from **ToC**?

Our key findings are as follows:

1. **STAIR** outperforms strong baselines such as BM25, DPR and fine-tuned DSI
2. R@1 for Mistral is much lower than BM25 – this suggests the LLM not only needs to learn the new task of picking the best section but also needs to ingest knowledge from the corpus
3. DPR performs much better than BM25 but worse than DSI. This result is expected, as NV-Embed-v2 is not fine-tuned for **SearchTome**
4. Tuning with **ToC** as input helps **STAIR**: The only difference in the input between DSI and **STAIR** is that **STAIR** leverages **ToC**. **STAIR** outperforms DSI by 7.4%, as it is able to access the entire structure of the book and better align it with the queries during fine-tuning. DSI on the other hand must learn the semantic alignment between queries and sections by looking at all the training data. We can thus conclude that **RQ1** and **RQ2** are answered in affirmative.

Statistical significance testing was done for the Recall@1 performance difference between DSI and **STAIR**. We follow the randomization test tailored to retrieval systems as described in [Smucker et al. \(2007\)](#). The null hypothesis for the significance testing is that outputs from SystemA (DSI) and SystemB (**STAIR**) may belong to the same underlying distribution and the difference of performance between SystemA (DSI) and SystemB (**STAIR**) is because of the sampling variance. We test the null hypothesis with the traditional p value of 0.05 at the domain level i.e. for each of the 6 domains separately (by combining all the books from a single domain). The significance test results conclude that the difference in DSI and **STAIR** is indeed statistically significant for all the 6 domains where the null hypothesis is successfully invalidated. More

specifically, through our sample runs for randomization test, we find that the probability of seeing this scale of Recall@1 performance difference as observed in Table 4 when being randomly sampled from the same distribution falls below $p = 0.05$. As with any statistical significance testing, the key takeaway from these experiments is a confirmation that the performance improvement seen in **STAIR** is statistically significant and therefore, it is a property of the **STAIR** design and not because of the data set size or data distribution in **SearchTome**.

6.1 Ablations

We conduct ablation studies to study the impact of using **ToC** as an input. Two key conclusions are as follows:

ToC reduces hallucinations: We define hallucination as the generation of a non-leaf node (invalid document identifier). Figure 3 illustrates the number of hallucinations per leaf node. We observed that the hallucination rate of **STAIR** remains nearly constant at close to zero, regardless of the number of training examples. This indicates that **STAIR** has effectively learned to generate outputs solely from the leaf nodes, making it inherently less prone to hallucination. In contrast, DSI, which does not use **ToC**, exhibits a higher hallucination rate than **STAIR**, particularly for leaf nodes with fewer training examples.

Remembering the structure is hard without ToC Figure 4 shows that for leaf nodes with less number of training examples, the Recall@1 difference between DSI and **STAIR** is much higher. This supports our hypothesis, that without **ToC**, DSI needs to discover the book structure and also remember it within its parameters. DSI attempts to learn this via the training data on query and associated **ToC** leaf node pairs. Thus, leaf nodes which have low representations in training data are prone to be missed by DSI. In contrast, **STAIR** does not need to “remember” the leaf nodes. As the number of training examples for a leaf node increase, Recall@1 gap between DSI and **STAIR** decreases – although **STAIR** consistently achieves higher Recall@1 numbers.

6.2 Error Analysis with Anecdotal Examples

We observe that out-of-the-box Mistral’s error rate is 86.20%, and 26.81% of its mistakes are as it predicts a non-leaf node, while 23.86% are hallucinations. This suggests that Mistral out-of-box needs knowledge ingestion and task finetuning. For

Table 3: Examples of model predictions. Gold leaf is highlighted in **bold** in Table of Contents

Example 1:	
Book: The Whole Child: Development in the Early Years Query: How do preschoolers react when caregivers and teachers belittle their autonomous actions?	
Table of Contents ... 2 Chapter Two: Theorists and Theories of Development leaf 2.1 Theories of Development 2.2 Psychosocial Theory leaf 2.2.1 Trust vs. Mistrust (Infancy) leaf 2.2.2 Autonomy vs. Shame/Doubt (Toddlerhood) leaf 2.2.3 Initiative vs. Guilt (Preschool Years) leaf 2.2.4 Industry vs. Inferiority (Elementary Years) leaf 2.2.5 Identity vs. Role-Confusion (Adolescence) leaf 2.2.6 Intimacy vs. Isolation (Early Adulthood) leaf 2.2.7 Generativity vs. Stagnation (Middle Adulthood) leaf 2.2.8 Integrity vs. Despair (Older Adulthood) ... 3 Chapter Three: Domains in Development	Content Initiative vs. Guilt (Preschool Years) The development of courage and independence If caregivers and preschool teachers encourage and support children's efforts while also helping them make realistic and appropriate choices, children develop a healthy sense of initiative in planning and undertaking activities. If, instead, adults discourage the pursuit of independent activities or dismiss them as silly and bothersome, children develop guilt about their needs and desires.
Mistral: 8.3.3 Moral Development, leaf 7.3.2 Hitting/Scratching and Temper Tantrums, leaf 2.2.3 Initiative vs. Guilt (Preschool Years) BM25: 8.3.2 Moral Development DPR: 2.2.2 Autonomy vs. Shame/Doubt (Toddlerhood) DSI: 2.2.2 Autonomy vs. Shame/Doubt (Preschool Years) STAIR: 2.2.3 Initiative vs. Guilt (Preschool Years)	
Example 2:	
Book: Nursing Fundamentals Query: In what way does a chronic illness affect an elderly person's ability to perform daily activities?	
Table of Contents ... leaf 30.5 Spiritual Care of Self leaf 30.6 Putting It All Together 31 Care of the Older Adult leaf 31.1 Care of the Older Adult Introduction leaf 31.2 Basic Concepts leaf 31.3 Applying the Nursing Process	Content Applying the Nursing Process ... It is also important to consider the impact of chronic disease on their ability to function and complete Activities of Daily Living (ADLs). older adults who are able to perform ADLs without assistance consider themselves healthy.
Mistral: 31.3 Applying the Nursing Process BM25: 11.2 Sensory Impairments Basic Concepts DPR: 31.2 Basic Concepts DSI: 31.2 Basic Concepts STAIR: 31.3 Applying the Nursing Process	
Example 3:	
Book: Introduction to Comparative Government and Politics Query: What are irregular armed organizations and how are they used by states?	
Table of Contents 9 Chapter 5: Non-Democracies and Democratic Backsliding ... 9.2 Strategies for staying in power leaf 9.2.1 Institutional channels leaf 9.2.2 Cultural and ideological controls 9.3 Varieties of non-democracy ...	Content Another powerful instrument of repression are paramilitaries. These refer to groups with access to military-grade weapons and training yet they are not part of the national military. They are "irregular armed organizations that carry out acts of violence against civilians on behalf of a state,"
Mistral: 9.3.5 Illiberal and hybrid regimes BM25: 15.3.1 Insurgencies/Civil Wars DPR: 15.2.2 External State-Sponsored Political Violence (State-Sponsored Terrorism) DSI: 15.2.1 Internal State-Sponsored Political Violence (Government Terrorism) STAIR: 9.2.1 Institutional channels	

DSI, the error rate drops to 24.31%, with 3.25% of its predictions being non-leaf nodes (suggesting knowledge infusion helps). **STAIR** has the lowest error rate of 18.67%, with only 0.05% of its predictions being non-leaf nodes.

Table 3 lists a few qualitative examples. We discuss next the first example "How do preschoolers react when caregivers and teachers belittle their


autonomous actions" from the book "The Whole Child: Development in the Early Years":

Mistral could correctly guess that the query can be answered by "2.2.3 Initiative vs. Guilt (Preschool Years)" using its world knowledge. It doesn't understand that it needs to pick only one option – due to lack of the task training **BM25** suffers from the known bias of keyword

Table 4: Recall@1, Recall@3 and nDCG@3 for **SearchTome**; Haiku is Claude haiku 4.5

	Education	Finance	Law	Med	NatSci	SocSci	Avg
Mistral	14.8/17.8/16.6	16.4/19.4/18.2	13.6/15.7/14.9	13.7/17.0/15.7	13.1/15.3/14.4	10.9/13.4/12.4	13.8/16.4/15.4
BM25	58.7/75.8/68.8	55.0/76.8/67.8	62.0/77.7/71.3	59.6/78.7/70.8	58.7/78.1/70.1	62.8/78.3/72.0	59.5/77.6/70.1
Haiku	59.8/80.4/72.0	37.7/56.3/48.4	41.1/60.6/52.3	46.1/65.0/57.2	54.6/73.7/65.7	34.0/48.8/42.6	45.6/64.1/56.4
DPR	71.5/86.8/80.6	66.4/85.5/77.7	69.6/84.1/78.2	72.7/88.8/82.2	63.0/84.1/75.7	68.8/83.1/77.3	68.7/85.4/78.6
DSI	76.2/84.1/80.9	78.1/87.8/83.9	73.3/82.9/79.0	82.1/89.9/86.8	76.2/84.7/81.3	75.4/82.2/79.4	76.9/85.3/81.9
STAIR	83.3/91.2/88.0	82.8/91.4/88.0	80.8/89.4/85.9	86.1/93.2/90.3	80.6/90.4/86.4	81.8/89.0/86.1	82.6/90.8/87.5

Figure 3: As number of training examples decrease, hallucination rate for DSI increases




matching where and picks the section “8.3.2. Moral Development” purely because of highest lexical overlap with query tokens, which is the incorrect answer

DPR is used out of the box and does a word sensed matching where it predicts “2.2.2 Autonomy vs. Shame/Doubt (Toddlerhood)” being most relevant to the query tokens mentioning “belittling of autonomous actions”. However, without the corpus specific training it falls short of identifying the correct section.

DSI is finetuned for the corpus but falters to find the precise section. It errs just like DPR in this example but might have chosen a more sensible match “2.2.2 Autonomy vs. Shame/Doubt (Preschool years)” which takes into account the importance of keyword “preschool” for getting a better topic match. However, careful consideration shows this is a hallucinated header not present in the input **ToC**. This correlates with our ablation in figure 3 on DSI hallucination.

STAIR: Our proposed system **STAIR** correctly identifies the gold leaf node as “Initiative vs. Guilt (Preschool Years)”.

The comparison between DPR, DSI and **STAIR**

Figure 4: Recall@1 for each leaf across **SearchTome**. **STAIR** shows high accuracy even with a low number of training examples

is interesting as they all are built on top of the same base LLM – Mistral. The difference between DSI and **STAIR** largely points towards the importance of having **ToC** as an input during training, which makes it easier for the LLM to align much better to the corpus. Other anecdotal examples in Table 3 also enumerate the same partial ordering seen among the baselines and provide more qualitative analysis to support the claim that the design of **STAIR** helps it do a much better retrieval.

7 Conclusion

We introduce **STAIR**, a novel LLM based IR system that leverages **ToC** to store and retrieve information from its parameters. Given a query, **STAIR** generates the most probable leaf section header from a **ToC** which could answer it. We use Mistral Instruct v0.2 to demonstrate that it is possible to instruction finetune the modern day LLMs to efficiently use the **ToC** structure to generate the correct leaf node while reducing the hallucinations to almost zero. **STAIR** outperforms all strong baselines such as BM25, finetuned DSI and DPR and achieves a Recall@1 score of 82.6% which is around 7.4% gain over the next best system

(DSI). We release a new comprehensive benchmark **SearchTome** across 6 domains with 18 books comprising of train, dev and test splits to further research in this novel direction.

As a future work, we want to explore directions where a **ToC** like structure is created dynamically over an unseen search corpus, as has been proposed by some previous works. We envision that having a **ToC**-based retrieval paradigm will gain more traction in future for agentic frameworks needing multi-hop retrieval and reasoning over retrieved context. To that end, we want to develop **STAIR** to work in a complete zero shot setup where it iteratively retrieves **ToC** leaf nodes and makes intelligent decisions by reasoning on the content of the leaf node to do precise information retrieval.

8 Limitations

Our current evaluation is limited to corpora where a global structure exists. While this setting is suitable for initial validation, it may not fully represent the diversity of real-world use cases. In future work, we plan to extend our evaluation to standard benchmarks by artificially inducing a Table of Contents structure. Additionally, we aim to test our model on enterprise datasets where such a structure already exists at a very large scale (possibly millions of URLs in the corpus).

References

- Yushi Bai, Xin Lv, Jiajie Zhang, Hongchang Lyu, Jiankai Tang, Zhidian Huang, Zhengxiao Du, Xiao Liu, Aohan Zeng, Lei Hou, Yuxiao Dong, Jie Tang, and Juanzi Li. 2024a. **LongBench: A bilingual, multilingual benchmark for long context understanding**. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 3119–3137, Bangkok, Thailand. Association for Computational Linguistics.
- Yushi Bai, Shangqing Tu, Jiajie Zhang, Hao Peng, Xiaozhi Wang, Xin Lv, Shulin Cao, Jiazheng Xu, Lei Hou, Yuxiao Dong, Jie Tang, and Juanzi Li. 2024b. **Longbench v2: Towards deeper understanding and reasoning on realistic long-context multitasks**. *arXiv preprint arXiv:2412.15204*.
- Soyuj Basnet, Jerry Gou, Antonio Mallia, and Torsten Suel. 2024. **Deeperimpact: Optimizing sparse learned index structures**. *arXiv preprint arXiv:2405.17093*.
- Yinqiong Cai, Yixing Fan, Jiafeng Guo, Fei Sun, Ruqing Zhang, and Xueqi Cheng. 2021. **Semantic models for the first-stage retrieval: A comprehensive review**. *ACM Transactions on Information Systems (TOIS)*, 40:1 – 42.
- Danqi Chen and Wen-tau Yih. 2020. **Open-domain question answering**. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics: Tutorial Abstracts*, pages 34–37, Online. Association for Computational Linguistics.
- Mingda Chen, Zewei Chu, Sam Wiseman, and Kevin Gimpel. 2022. **SummScreen: A dataset for abstractive screenplay summarization**. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 8602–8615, Dublin, Ireland. Association for Computational Linguistics.
- Shouyuan Chen, Sherman Wong, Liangjian Chen, and Yuandong Tian. 2023. **Extending context window of large language models via positional interpolation**. *arXiv preprint arXiv:2306.15595*.
- Zhuyun Dai and Jamie Callan. 2019. **Context-aware sentence/passage term importance estimation for first stage retrieval**. *arXiv preprint arXiv:1910.10687*.
- Pradeep Dasigi, Kyle Lo, Iz Beltagy, Arman Cohan, Noah A. Smith, and Matt Gardner. 2021. **A dataset of information-seeking questions and answers anchored in research papers**. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 4599–4610, Online. Association for Computational Linguistics.
- Thibault Formal, Carlos Lassance, Benjamin Piwowarski, and Stéphane Clinchant. 2021. **Splade v2: Sparse lexical and expansion model for information retrieval**. *arXiv preprint arXiv:2109.10086*.
- R. Guha, Rob McCool, and Eric Miller. 2003. **Semantic search**. In *Proceedings of the 12th International Conference on World Wide Web, WWW '03*, page 700–709, New York, NY, USA. Association for Computing Machinery.
- Nam Le Hai, Thomas Gerald, Thibault Formal, Jianyun Nie, Benjamin Piwowarski, and Laure Soulier. 2023. **Cosplade: Contextualizing splade for conversational information retrieval**. *ArXiv*, abs/2301.04413.
- J. Edward Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, and Weizhu Chen. 2021. **Lora: Low-rank adaptation of large language models**. *ArXiv*, abs/2106.09685.
- Luyang Huang, Shuyang Cao, Nikolaus Parulian, Heng Ji, and Lu Wang. 2021. **Efficient attentions for long document summarization**. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 1419–1436, Online. Association for Computational Linguistics.

- Albert Q Jiang, Alexandre Sablayrolles, Antoine Roux, Arthur Mensch, Blanche Savary, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Emma Bou Hanna, Florian Bressand, and 1 others. 2024. *Mixtral of experts*. *arXiv preprint arXiv:2401.04088*.
- Albert Qiaochu Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de Las Casas, Florian Bressand, Giana Lengyel, Guillaume Lample, Lucile Saulnier, L'elio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. 2023. *Mixtral 7b*. *ArXiv*, abs/2310.06825.
- Vladimir Karpukhin, Barlas Oğuz, Sewon Min, Patrick Lewis, Ledell Yu Wu, Sergey Edunov, Danqi Chen, and Wen tau Yih. 2020. *Dense passage retrieval for open-domain question answering*. *ArXiv*, abs/2004.04906.
- O. Khattab and Matei A. Zaharia. 2020. *Colbert: Efficient and effective passage search via contextualized late interaction over bert*. *Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information Retrieval*.
- Tomáš Kočiský, Jonathan Schwarz, Phil Blunsom, Chris Dyer, Karl Moritz Hermann, Gábor Melis, and Edward Grefenstette. 2018. *The NarrativeQA reading comprehension challenge*. *Transactions of the Association for Computational Linguistics*, 6:317–328.
- Yuta Koreeda and Christopher Manning. 2021. *ContractNLI: A dataset for document-level natural language inference for contracts*. In *Findings of the Association for Computational Linguistics: EMNLP 2021*, pages 1907–1919, Punta Cana, Dominican Republic. Association for Computational Linguistics.
- Philippe Laban, A. R. Fabbri, Caiming Xiong, and Chien-Sheng Wu. 2024. *Summary of a haystack: A challenge to long-context llms and rag systems*. In *Conference on Empirical Methods in Natural Language Processing*.
- Chankyu Lee, Rajarshi Roy, Mengyao Xu, Jonathan Raiman, Mohammad Shoeybi, Bryan Catanzaro, and Wei Ping. 2024. *Nv-embed: Improved techniques for training llms as generalist embedding models*. *arXiv preprint arXiv:2405.17428*.
- Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, and 1 others. 2020. *Retrieval-augmented generation for knowledge-intensive nlp tasks*. *Advances in Neural Information Processing Systems*, 33:9459–9474.
- Tianle Li, Ge Zhang, Quy Duc Do, Xiang Yue, and Wenhu Chen. 2024. *Long-context llms struggle with long in-context learning*. *ArXiv*, abs/2404.02060.
- Jimmy Lin and Xueguang Ma. 2021. *A few brief notes on deepimpact, coil, and a conceptual framework for information retrieval techniques*. *arXiv preprint arXiv:2106.14807*.
- Hao Liu, Wilson Yan, Matei Zaharia, and Pieter Abbeel. 2024a. *World model on million-length video and language with blockwise ringattention*. *arXiv preprint arXiv:2402.08268*.
- Kai Liu, Ze Chen, Zhihang Fu, Rongxin Jiang, Fan Zhou, Yaowu Chen, Yue Wu, and Jieping Ye. 2024b. *Structure-aware domain knowledge injection for large language models*.
- Nelson F. Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. 2024c. *Lost in the middle: How language models use long contexts*. *Transactions of the Association for Computational Linguistics*, 12:157–173.
- Donald Metzler, Yi Tay, Dara Bahri, and Marc Najork. 2021. *Rethinking search: Making experts out of dilettantes*. *ArXiv*, abs/2105.02274.
- Richard Yuanzhe Pang, Alicia Parrish, Nitish Joshi, Nikita Nangia, Jason Phang, Angelica Chen, Vishakh Padmakumar, Johnny Ma, Jana Thompson, He He, and Samuel Bowman. 2022. *QuALITY: Question answering with long input texts, yes!* In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 5336–5358, Seattle, United States. Association for Computational Linguistics.
- Nicholas Pipitone and Ghita Houir Alami. 2024. *Legalbench-rag: A benchmark for retrieval-augmented generation in the legal domain*. *ArXiv*, abs/2408.10343.
- Stephen Robertson and Hugo Zaragoza. 2009. *The probabilistic relevance framework: Bm25 and beyond*. *ACM Transactions on Information Systems*, 27(3):1–27.
- Jon Saad-Falcon, Daniel Y. Fu, Simran Arora, Neel Guha, and Christopher R'e. 2024. *Benchmarking and building long-context retrieval models with loco and m2-bert*. *ArXiv*, abs/2402.07440.
- SAP. 2024. *Sap-product-documentation*. https://help.sap.com/doc/saphelp_snc70/7.0/en-US/ef/c08d5377a0ec23e10000000a174cb4/frameset.htm.
- Parth Sarthi, Salman Abdullah, Aditi Tuli, Shubh Khanna, Anna Goldie, and Christopher D Manning. 2024. *Raptor: Recursive abstractive processing for tree-organized retrieval*. *arXiv preprint arXiv:2401.18059*.
- SEC. 2024. *Sec 10k structure*. <https://www.sec.gov/files/reada10k.pdf>.

- Spurthi Setty, Katherine Jijo, Eden Chung, and Natan Vidra. 2024. [Improving retrieval for rag based question answering models on financial documents](#). *ArXiv*, abs/2404.07221.
- Uri Shaham, Elad Segal, Maor Ivgi, Avia Efrat, Ori Yoran, Adi Haviv, Ankit Gupta, Wenhan Xiong, Mor Geva, Jonathan Berant, and Omer Levy. 2022. [SCROLLS: Standardized CompaRison over long language sequences](#). In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 12007–12021, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.
- Mark Smucker, James Allan, and Ben Carterette. 2007. [A comparison of statistical significance tests for information retrieval evaluation](#). pages 623–632.
- Yi Tay, Vinh Q. Tran, Mostafa Dehghani, Jianmo Ni, Dara Bahri, Harsh Mehta, Zhen Qin, Kai Hui, Zhe Zhao, Jai Gupta, Tal Schuster, William W. Cohen, and Donald Metzler. 2022. [Transformer memory as a differentiable search index](#). *ArXiv*, abs/2202.06991.
- Nandan Thakur, Nils Reimers, Andreas Rücklé, Abhishek Srivastava, and Iryna Gurevych. 2021. [BEIR: A heterogeneous benchmark for zero-shot evaluation of information retrieval models](#). In *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track (Round 2)*.
- Wikipedia. 2024. [wikipedia sample layout](https://en.wikipedia.org/wiki/Wikipedia:Manual_of_Style/Layout). https://en.wikipedia.org/wiki/Wikipedia:Manual_of_Style/Layout.
- Jiaxin Zhang, Wendi Cui, Yiran Huang, Kamalika Das, and Kumar Sricharan. 2024. [Synthetic knowledge ingestion: Towards knowledge refinement and injection for enhancing large language models](#). In *Conference on Empirical Methods in Natural Language Processing*.
- Ming Zhong, Da Yin, Tao Yu, Ahmad Zaidi, Mutethia Mutuma, Rahul Jha, Ahmed Hassan Awadallah, Asli Celikyilmaz, Yang Liu, Xipeng Qiu, and Dragomir Radev. 2021. [QMSum: A new benchmark for query-based multi-domain meeting summarization](#). In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 5905–5921, Online. Association for Computational Linguistics.
- Fengbin Zhu, Wenqiang Lei, Chao Wang, Jianming Zheng, Soujanya Poria, and Tat-Seng Chua. 2021. Retrieving and reading: A comprehensive survey on open-domain question answering. *arXiv e-prints*, pages arXiv–2101.