

Who Holds the Pen? Let Specifications, Not Agents, Sign Off

Haiqing Li¹, Xin Ma², Yinhao Wu¹, Wenliang Zhong¹, Feng Jiang¹,
Thao M. Dang¹, Xiao Hu¹, Hehuan Ma¹, Yuzhi Guo³, Junzhou Huang¹

¹Department of Computer Science and Engineering, The University of Texas at Arlington, Arlington, TX, USA

²Monash University, Melbourne, VIC, Australia

³Department of Computer Science, Kent State University, Kent, OH, USA

Abstract

Large language model agents operate under external specifications, including task instructions, guidelines, output schemas, and reusable skills. In most systems, however, these specifications remain context for the same model that acts, evaluates outcomes, and declares completion. This collapses proposal and acceptance within the agent, leaving no independent specification authority boundary. This creates two structural gaps. The understanding–execution gap arises because understanding a requirement does not ensure satisfying it during execution. The state–authority gap arises because an agent’s interpretation or completion claim does not prove that the required state has been achieved. We quantify these gaps on SkillsBench. Using only agent-visible task prompts, workspace information, and injected skill specifications, we extract 509 source-grounded task directions and assess whether they are satisfied during execution. Across seven models, only 79.6%–86.4% of these directions are satisfied. Moreover, agents’ completion-claim rates exceed official evaluator pass rates by 28.7–37.9 percentage points. We formulate specification authority as a separation between agent proposals and authoritative state: agents may plan, act, and request completion, but only admissible evidence from qualified providers may establish specification-governed state. SpecHarness operationalizes this paradigm by compiling agent-visible specifications into source-linked obligations and governing execution and finalization through versioned obligation state. Reliably executable or verifiable requirements are mediated or validated at runtime; ambiguous or subjective requirements remain advisory or are excluded from enforcement. We instantiate and evaluate SpecHarness on guideline-following and artifact-generation tasks. Our results support treating specifications not merely as influences on agent behavior, but as authority over what constitutes correct execution and compliant completion. Authoritative judgments about specification-defined state should remain independent of the agent’s self-assessment.

Introduction

Large language model agents increasingly control complex tasks by inspecting environments, planning steps, selecting skills, invoking tools, and deciding when to stop (Li et al. 2026a; Wang et al. 2023). Their behavior is expected to follow external specifications at three levels: task instructions, guidelines, and policies define goals, constraints, and completion conditions; tool schemas, API documentation,




Figure 1: Two structural gaps in specification following. **Top:** The agent understands the required order but executes the steps incorrectly, illustrating the understanding–execution gap. **Bottom:** The agent claims completion before the specification-required state is established, illustrating the state–authority gap.

operating procedures, and SKILL.md files define operation semantics, preconditions, arguments, and execution order; and manifests, schemas, and contracts define required artifacts and their acceptance conditions. However, most systems still treat these specifications only as agent-readable context rather than as a basis for an external runtime to govern execution and acceptance. Agents may therefore omit requirements, violate procedures, misuse tools, misinterpret effects, combine constraints incorrectly, or claim completion before the required state has been established (Bandi et al. 2026).

This mismatch produces the two gaps illustrated in Figure 1. Requirements may be correctly interpreted yet fail to govern execution, creating the understanding–execution gap. Moreover, agent actions and self-assessments cannot authoritatively establish specification-defined state, creating the state–authority gap. The key question is therefore not only when or how execution is checked, but who may establish specification-governed state and authorize completion. We quantify both gaps on all 87 SkillsBench tasks using a compiler selected from seven candidate language models on development annotations and frozen before evaluation; the full comparison and selection protocol are reported in Appendix A.1. Using only agent-visible task prompts, workspace information, and injected skill specifications, the selected compiler extracts 509 source-grounded task direc-

tions. Across seven representative language models, only 79.6%–86.4% of these directions are satisfied, while agents’ completion-claim rates exceed official pass rates by 28.7–37.9 percentage points. These findings quantify both gaps across the evaluated agents (Figure 3).

Some approaches (Ouyang et al. 2022; Bai et al. 2022) internalize specification following through model training, but still leave the same model responsible for both acting under a specification and judging whether it has been satisfied. As shown in Figure 2, inference-time methods intervene at three stages: post-hoc verification checks artifacts or final states after execution; completion gating checks completion claims before acceptance but usually leaves prior execution and intermediate state unconstrained; and runtime enforcement (Mazzocchi 2026) constrains behavior during execution, as in VIGIL (Li et al. 2026c), which monitors agent–tool interactions for temporal, argument, and value-flow violations. These approaches improve verification, acceptance control, or behavioral compliance, but do not jointly govern execution and evidence-authorized state commitment. What is missing is an explicit specification authority boundary governing both execution and accepted state.

We formulate this distinction as the *State Authority Principle*: for reliably grounded and verified conditions, the specification defines what may be accepted, while an external runtime determines whether the required state has been established. **SpecHarness** operationalizes this principle as a runtime architecture for specification-governed agents. Agents still interpret tasks, plan, select tools and skills, implement solutions, and repair failures, but only propose actions, state changes, and completion; SpecHarness commits the corresponding authoritative state. It converts verifiable requirements in agent-visible materials into source-linked obligations, checks them through controlled execution or authorized validation, and updates state only when the required evidence satisfies its commit rule. Ambiguous, subjective, conflicting, or unverifiable requirements remain advisory rather than becoming hard obligations, and continue to guide the agent. These mechanisms follow directly from the two gaps: operational obligations narrow the understanding–execution gap, while evidence-authorized commitment prevents self-assessment from establishing accepted state. For example, authorizing an array-processing action confirms only its preconditions, arguments, and ordering constraints; the corresponding obligation state is committed only after an authorized validator verifies the required path, shape, data type, and finite values. SpecHarness thus allows specifications not only to describe desired behavior, but also to govern which verifiable states and outcomes may be accepted. *Agent proposes; SpecHarness commits*. The main contributions of this paper are as follows:

1. We identify the missing specification authority boundary and its two observable consequences: the understanding–execution and state–authority gaps.
2. We formulate the State Authority Principle, separating proposal autonomy from state authority: agents propose, while an external runtime commits specification-governed state only from admissible evidence produced




Figure 2: Three intervention paradigms for specification compliance. (a) Post-hoc verification detects violations only after execution has completed. (b) Completion gating checks the agent’s completion claim before acceptance but does not constrain the preceding execution. (c) Runtime enforcement intervenes during execution to prevent or constrain specification-violating actions.

by qualified providers.

3. We instantiate and evaluate *SpecHarness*, an obligation–evidence–commit architecture governing decision, artifact, and completion state across GuideBench and SkillsBench.

Related Work

Post-hoc Verification (Fig. 2(a)). Post-hoc methods assess specification compliance after an answer, trajectory, or artifact is produced. NSVIF (Su et al. 2026) represents natural-language instructions as logical and semantic constraints and reports interpretable violations. SkillsBench (Li et al. 2026b) evaluates skill-guided executions with deterministic verifiers over final artifacts and environment states. AgentRx (Barke et al. 2026) synthesizes trajectory invariants, checks them step by step, and produces auditable violation logs with supporting evidence, while AgentOps (Dong, Lu, and Zhu 2024) identifies the artifacts and lifecycle data needed for observability. These methods provide evidence about completed executions, but use it for diagnosis rather than to govern authoritative task state.

Completion Gating (Fig. 2(b)). Failure analyses motivate explicit control at the completion boundary. MAST (Cemri et al. 2026) identifies verification and termination as a major category of multi-agent failure, including premature termination and missing or incorrect verification. Verify-gated completion (Nguyen and Tran 2026) treats an agent’s completion claim as a proposal and places a read-only verifier before task acceptance, using fail-closed admission and auditable event records. Such designs block unsupported completion claims but verify primarily at terminal admission. SpecHarness instead organizes verification around source-grounded obligations and specification-governed state transitions, making completion the final commit rather than the sole verification point.




Figure 3: Empirical evidence for the two structural gaps across seven language models. **Top:** Models satisfy 79.6%–86.4% of the 509 source-grounded task directions recovered from agent-visible materials. **Bottom:** Agent-reported completion rates exceed official verifier pass rates by 28.7–37.9 percentage points.

Runtime Enforcement (Fig. 2(c)). Runtime enforcement constrains behavior or state transitions during execution. VIGIL (Li et al. 2026c), AgentSpec (Wang, Poskitt, and Sun 2025), and FORGE (Palumbo et al. 2026) enforce specification-derived policies through trace checking, runtime rules, or action mediation. Verification-gated mission-state governance (Tang et al. 2026) further commits proposed mission updates only after deterministic verification. SpecHarness builds on classical reference-monitor (Saltzer and Schroeder 1975), runtime-verification (Leucker and Schallhart 2009), and transactional-commit (Gray and Lamport 2004) principles rather than treating them as new primitives. Its agent-specific contribution is to compile visible specifications into source-linked obligations and use qualified evidence to govern versioned state and finalization; preventive mediation remains limited to closure-audited surfaces (Appendix B.2).

SpecHarness: Runtime Specification Authority

SpecHarness reallocates runtime authority: agents plan and act, while only specification-authorized evidence may establish authoritative state.

Problem Setting and State Authority. For a task instance x , let

$$V_x = (T_x, G_x, K_x, W_x) \quad (1)$$

denote its agent-visible context: task prompt T_x , applicable guidelines G_x , injected skill specifications K_x , and observ-

able workspace state and schemas W_x . Held-out verifiers and oracle solutions are evaluation-only and excluded from V_x and runtime enforcement. Let H_{exec} denote the executor, observer, and validator substrate available to SpecHarness.

At time t , the agent proposes p_t , the runtime observes evidence e_t , and SpecHarness maintains authoritative state $s_t = (I_t, C_t, \nu_t)$, comprising a versioned obligation ledger, derived control state, and dependency versions. Let k_i be obligation o_i ’s assertion key and $s_t[k]$ its ledger value, or $\perp$ if absent. SpecHarness enforces $s_{t+1}[k] \neq s_t[k] \Rightarrow \exists o_i, e_t : \text{Witness}_t(k, o_i, e_t)$, where $\text{Witness}_t(k, o_i, e_t)$ requires $k = k_i$, admissible evidence $\text{Adm}_i(e_t, s_t; H_{\text{exec}})$, and a corresponding $\text{commit}(o_i, e_t, k)$ event. Admissibility is defined below. This state-write invariant defines SpecHarness: agent actions, outputs, and self-assessments cannot directly establish authoritative state. Thus, *the agent proposes; SpecHarness commits*. A commit may record validated success or failure; satisfaction is determined separately.

Runtime Obligation Construction. SpecHarness segments the visible context into source-addressable units and assigns each a disposition:

$$U_x = \text{Segment}(V_x) = \{u_j = (q_j, \ell_j)\}_{j=1}^{n_x}, \quad (2)$$

$$\delta_x : U_x \rightarrow \{\text{HARD}, \text{ADVISORY}, \text{ABSTAIN}, \text{RESIDUAL}\}.$$

Here, q_j identifies the visible source and ℓ_j its requirement text. Reusable policies and skill specifications may yield templates; task prompts and instance-specific guidelines are compiled per task, while the observable workspace grounds entities, paths, arguments, outputs, and completion conditions. Using development annotations derived only from agent-visible materials, we compare seven language-model compilers, select one by development-set extraction quality, and freeze it before execution; compiler details and the selection protocol are provided in Appendix A.1. Held-out official verifiers are used only afterward for post-hoc obligation-test alignment and final evaluation. Let $Q_x^* = \mathcal{C}^*(U_x)$ be the frozen compiler output and $\mathcal{D}_x = \text{Directions}(Q_x^*)$ the source-addressable index for direction-level measurement and trace attribution. Given H_{exec} , the obligation builder constructs

$$\mathcal{B}(Q_x^*, H_{\text{exec}}) \rightarrow \Gamma_x^* = (\mathcal{O}_{\text{hard}}, \mathcal{O}_{\text{adv}}, \mathcal{U}_{\text{abs}}, R_x). \quad (3)$$

Here, Γ_x^* is the task-specific obligation IR maintained by the runtime: $\mathcal{O}_{\text{hard}}$ contains mandatory obligations that may block covered transitions or completion, $\mathcal{O}_{\text{adv}}$ contains non-blocking obligations and guidance, $\mathcal{U}_{\text{abs}}$ records abstentions, and R_x preserves residual context. Directions and obligations need not correspond one-to-one: several directions may ground one obligation, while advisory, abstained, and residual directions create no independent blocking rules. Thus, $\mathcal{D}_x$ supports measurement and trace attribution, whereas Γ_x^* governs authorization, validation, commitment, and finalization. A grounded obligation is

$$o_i = \langle \text{src}_i, \text{auth}_i, \text{effect}_i, \text{state}_i, \text{ctrl}_i \rangle, \quad (4)$$

encoding provenance, action matching and authorization, execution and validation, state commitment and satisfaction, and dependency and enforcement control, respectively. An




Figure 4: SpecHarness compiles agent-visible specifications into source-linked obligations, mediates closure-audited actions, validates observed effects, commits versioned state from authorized evidence, and permits finalization only when all fresh mandatory obligations are satisfied. Advisory and abstained requirements remain outside hard enforcement.

obligation enters $\mathcal{O}_{\text{hard}}$ only if it is mandatory, its parameters are source-grounded, it has an authorized evidence provider, and its validator is qualified for blocking under the development protocol; otherwise, it remains advisory or triggers abstention. Validator qualification and closure stress tests appear in Appendices B.1–B.2.

The builder also derives a declared action surface $\mathcal{A}_{\text{decl}}$. A closure audit identifies actions eligible for bounded *mediate-and-commit*; other safely isolated declared channels use *validate-and-commit*, while unsupported channels are rejected. Hard classification alone does not imply preventive mediation. Moreover, admissible evidence may commit a validated failure without satisfying o_i .

Agent Interface and Proposals. The agent retains the original task context, applicable skills, and residual context R_x , and receives advisory guidance and source-linked runtime feedback. SpecHarness alone maintains the authoritative ledger and exposes only derived feedback and control decisions. The agent submits proposals in three tagged classes:

$$\mathcal{P} = \mathcal{P}_{\text{act}} \uplus \mathcal{P}_{\text{repair}} \uplus \mathcal{P}_{\text{finalize}}, \quad (5)$$

for actions with bound arguments, repairs targeting reported failures, and finalization requests. Proposals express intent, not authoritative fact. The agent may plan, select tools, generate code, interpret errors, and revise artifacts, but cannot modify the ledger, inject validator outcomes, mark obligations satisfied, or authorize finalization. Action-bearing proposals proceed to authorization; finalization is determined solely by committed obligation state at current evidence versions.

Action Authorization and Controlled Execution. SpecHarness first maps each action proposal to a canonical action. For matched proposals, it identifies the relevant

obligations and returns an authorization decision:

$$\begin{aligned} (\hat{a}_t, n_t) &= \text{Normalize}(p_t), \\ n_t &\in \{\text{EXACT}, \text{NORMALIZED}, \text{UNMATCHED}\}, \\ M_t &= \{o_i \in \mathcal{O}_x^{\text{act}}(s_t) : \text{Match}_i(\hat{a}_t, s_t) = 1\}, \\ u_t &= \text{Auth}(\hat{a}_t, M_t, s_t), \\ u_t &\in \{\text{ALLOW}, \text{BLOCK}, \text{UNCLEAR}\}. \end{aligned} \quad (6)$$

An unmatched proposal raises an error when mediation is expected, enters *validate-and-commit* on a safely isolated declared channel, follows the base policy when explicitly out of scope, or is rejected when unsupported.

Let $\pi \sim_{\text{eff}} a$ mean that execution path π can produce an effect equivalent to canonical action a , and let $\text{GovernedByAuth}(\pi, a)$ mean that π is mediated as a and subjected to its authorization procedure. The action surface is closed for a if and only if every available effect-equivalent path is either governed or denied:

$$\begin{aligned} \text{Closed}(a, H_{\text{exec}}) &= 1 \\ \iff \forall \pi \in \text{AvailPaths}(H_{\text{exec}}), \\ \pi \sim_{\text{eff}} a &\Rightarrow \text{GovernedByAuth}(\pi, a) \vee \text{Denied}(\pi). \end{aligned} \quad (7)$$

Define $\mathcal{A}_{\text{static}} = \{a \in \mathcal{A}_{\text{decl}} : \text{Closed}(a, H_{\text{exec}}) = 1\}$, and let $\text{Preventive}(M_t)$ hold iff M_t contains a hard obligation with mode **BLOCK**.

Actions in $\mathcal{A}_{\text{static}}$ use bound controlled executors, and preventive matches require $u_t = \text{ALLOW}$ for dispatch. Closure then yields

$$\begin{aligned} \hat{a}_t &\in \mathcal{A}_{\text{static}} \wedge \text{Preventive}(M_t) \wedge u_t \neq \text{ALLOW} \\ \Rightarrow \exists \pi \in \text{AvailPaths}(H_{\text{exec}}) : \\ \pi \sim_{\text{eff}} \hat{a}_t &\wedge \text{BypassesAuth}(\pi, \hat{a}_t, s_t). \end{aligned} \quad (8)$$

Here, *BypassesAuth* denotes an effect-equivalent path outside the applicable authorization procedure. Under the audited boundary and threat model, no-bypass applies only

to closure-audited actions; isolated channels use post-effect validation, and finalization still requires all fresh mandatory obligations to be satisfied (Appendix B.2).

Effect Validation, Commitment, and Recovery. After execution, trusted observers produce evidence e_t for obligation o_i , its bound validator returns r_t , and SpecHarness constructs dependency digest d_t and provenance record ρ_t . Evidence is admissible iff

$$\begin{aligned} \text{Adm}_i(e_t, s_t; H_{\text{exec}}) &\iff \text{Trusted}_i(e_t; H_{\text{exec}}) \\ &\quad \wedge c_i(e_t, s_t) \\ &\quad \wedge r_t \in \{\text{PASSED}, \text{FAILED}\}. \end{aligned} \quad (9)$$

The ledger update is

$$L_{t+1}[o_i] = \begin{cases} (r_t, d_t, \rho_t), & \text{Adm}_i(e_t, s_t; H_{\text{exec}}), \\ L_t[o_i], & \text{otherwise.} \end{cases} \quad (10)$$

Trusted_i checks the bound provider, channel, validator, scope, and version metadata, which ρ_t records with the commit-event identifier. The ledger update and commit event are atomic. Both `PASSED` and `FAILED` may be committed; validator errors, effects without admissible evidence, and agent claims cannot create authoritative state.

A committed result is `FRESH` iff its dependency digest matches current artifact, input, validator, environment, and dependent-obligation versions; a known mismatch yields `STALE`, and incomplete version evidence yields `UNKNOWN`. Satisfaction is

$$\begin{aligned} \text{Sat}_t(o_i) &\iff o_i \in \text{dom}(L_t) \wedge h_i(L_t, s_t) \\ &\quad \wedge \text{Fresh}_t(o_i) = \text{TRUE}. \end{aligned} \quad (11)$$

Let $\mathcal{O}_x^{\text{act,mand}}(s_t)$ be the mandatory subset of $\mathcal{O}_x^{\text{act}}(s_t)$. Finalization requires

$$\text{FinalizeAllowed}_t(x) \Rightarrow \forall o_i \in \mathcal{O}_x^{\text{act,mand}}(s_t), \text{Sat}_t(o_i). \quad (12)$$

Mutations recompute freshness for affected entries and dependents, marking them `STALE` or `UNKNOWN` until revalidation. SpecHarness returns source-linked feedback, the agent may propose repairs, and only new admissible evidence can recommit state. The guarantee covers grounded mandatory obligations, not the full natural-language specification.

Experiments

Benchmarks. We evaluate SkillsBench (Li et al. 2026b) and GuideBench (Diao et al. 2025) under different authoritative-state semantics. SkillsBench contains 87 tool-use and artifact-production tasks; agent-visible prompts, workspaces, and injected skills provide runtime inputs, while held-out verifiers determine success. GuideBench contains 1,042 guideline-constrained decision tasks and tests generalization from execution and artifact state to decision state. Across both benchmarks, held-out verifiers, references, and oracles are used only for evaluation, never for obligation construction or runtime feedback.

Experimental Setup and Baselines. The seven models (GPT-5.6, Claude Fable 5, Gemini 3.1, Kimi K3, GLM-5.2 (Zeng et al. 2026), Qwen3.7 (Qwen Team 2026), and DeepSeek-V4 (Xu et al. 2026a)) in Table 1 also serve as candidate compilers. Using fixed development annotations and a prespecified protocol, we select GPT-5.6 Sol and freeze it before evaluation. Its output Q_x^* defines direction index $\mathcal{D}_x = \text{Directions}(Q_x^*)$ and runtime IR Γ_x^* , yielding 509 directions across 87 SkillsBench tasks. An evaluation-only audit aligns them with 573 of 585 held-out official test functions, including 406 fine-grained matches; this measures alignment, not recovery of verifier semantics. Full compiler-selection results appear in Appendix A.1; extraction, coverage, and alignment results appear in Appendix A.2. All agent runs use OpenHands (Wang et al. 2025) as the shared execution substrate for both Raw and SpecHarness; configuration details appear in Appendix C.1.

On SkillsBench, the same seven models serve separately as task agents. The frozen $\mathcal{D}_x$ provides a common source-grounded measurement surface and denominator across agents and conditions, while execution evidence determines $S_{m,c}(x) \subseteq \mathcal{D}_x$. Neither set uses official verifiers or oracles. We compare Raw and SpecHarness across all agents and, with GPT-5.6 Sol fixed, compare Agentic Rubrics (Raghavendra et al. 2026), VeriMAP (Xu et al. 2026b), AgentSpec (Wang, Poskitt, and Sun 2025), and SpecHarness as post-hoc verification, completion gating, runtime enforcement, and mediate-and-commit methods.

On GuideBench, removing four duplicate rules from 301 guideline entries yields 297 obligation templates and 5,817 task-level instances across 1,042 tasks. Without an independent extraction oracle, they define a common measurement surface but not complete semantic recovery. We compare Raw and SpecHarness across the same seven agents and, with GPT-5.6 Sol fixed, compare adapted RvLLM (Zhang et al. 2026), adapted VeriMAP (Xu et al. 2026b), SatLM (Ye et al. 2023), and SpecHarness as post-hoc verification, completion gating, computation substrate, and evidence-authorized commitment methods. Paired conditions share inputs, budgets, timeouts, and tool access. Frozen obligations and validators evaluate all conditions read-only; only SpecHarness uses their evidence to commit authoritative state and authorize finalization. Appendix C.2 audits baseline implementations, runtime access, budgets, and completion rules.

Metrics. For benchmark $b \in \{\text{SB}, \text{GB}\}$, let $\mathcal{Z}_x^b$ denote the common frozen measurement surface for instance x , and let $S_{m,c}^b(x) \subseteq \mathcal{Z}_x^b$ contain the units whose satisfaction is supported by the shared validators. Let $N_{m,c}^b$ be the valid runs, $P_{m,c}^b$ the officially passing runs, and $A_{m,c}^b$ the runs accepted by the condition-specific runtime. We define

$$\begin{aligned} G_{m,c}^{\text{UE},b} &= \frac{\sum_x |\mathcal{Z}_x^b \setminus S_{m,c}^b(x)|}{\sum_x |\mathcal{Z}_x^b|}, \\ G_{m,c}^{\text{SA},b} &= \frac{|A_{m,c}^b \setminus P_{m,c}^b|}{N_{m,c}^b}. \end{aligned} \quad (13)$$

For SkillsBench, $\mathcal{Z}_x^{\text{SB}} = \mathcal{D}_x$ is the frozen task-direction index; for GuideBench, $\mathcal{Z}_x^{\text{GB}} = \mathcal{O}_{\text{act}}^{\text{GB}}(x)$ is the common

Model	Raw Agent			SpecHarness			Change vs. Raw (pp)		
	Pass↑	U-E↓	S-A↓	Pass↑	U-E↓	S-A↓	Pass	U-E	S-A
GPT-5.6 Sol	71.3	13.6	28.7	85.1	6.3	6.9	+13.8	-7.3	-21.8
Claude Fable 5	69.0	14.5	31.0	81.6	7.1	10.3	+12.6	-7.4	-20.7
Gemini 3.1 Pro	62.1	17.1	37.9	79.3	8.4	12.6	+17.2	-8.7	-25.3
Kimi K3	60.9	17.5	32.2	67.8	10.8	14.9	+6.9	-6.7	-17.3
GLM-5.2	57.5	18.7	29.9	69.0	9.6	11.5	+11.5	-9.1	-18.4
Qwen3.7-Max	54.0	20.0	36.8	65.5	11.2	17.2	+11.5	-8.8	-19.6
DeepSeek-V4-Pro	52.9	20.4	33.3	63.2	12.0	16.1	+10.3	-8.4	-17.2
Macro Average	61.1	17.4	32.8	73.1	9.3	12.8	+12.0	-8.1	-20.0

Table 1: Cross-model results on all 87 SkillsBench tasks. Pass is the official-verifier pass rate; U-E and S-A are the understanding-execution and state-authority gaps. Change columns report percentage-point differences from Raw. Macro Average is the unweighted mean across seven task-agent models.

set of active, measurable guideline obligations. The same frozen validators measure all conditions read-only, while only SpecHarness uses their results for state commitment and finalization. U-E operationally measures unrealized source-grounded units, not latent comprehension. $A_{m,c}^b$ follows the condition-specific rule: ungated terminal claims, native verifier or gate decisions, or ledger-derived finalization. Since all valid Raw runs end in an accepted ungated claim, Raw S-A equals $1 - \text{Pass}$. Official pass rate is $\text{Pass}_{m,c}^b = |P_{m,c}^b|/N_{m,c}^b$. Official Pass is primary; U-E and S-A are diagnostic, and S-A is reported with Pass and Raw-pass preservation to expose over-refusal.

Results

Main Results on SkillsBench. Tables 1 and 2 show that SpecHarness reduces both specification-following gaps across the evaluated agents. Even the strongest Raw agent retains substantial U-E and S-A gaps, while SpecHarness improves all seven models without gains tracking baseline capability. Macro Pass rises from 61.1% to 73.1%, U-E falls from 17.4% to 9.3%, and S-A from 32.8% to 12.8%. The macro Pass gain has a 95% paired task-bootstrap interval excluding zero, and exact per-model McNemar tests remain significant after Holm correction; full statistics appear in Appendix D.1. Because SpecHarness includes online validation, feedback, and repair, the main comparison evaluates the complete governed runtime rather than the isolated effect of authoritative commitment; detailed computational overhead is reported in Appendix D.3. The larger S-A reduction than Pass gain is consistent with both failure recovery and rejection of unsupported completion claims. Across the evaluated models, greater baseline capability does not eliminate the gaps when specifications remain transient context: execution may still drift from visible requirements, and completion remains self-issued. The paradigm comparison further separates execution control from acceptance authority: AgentSpec achieves lower U-E but higher S-A than VeriMAP. Action constraints reduce divergence without establishing effects, whereas completion checks filter terminal claims without governing prior trajectories. In SpecHarness, source-linked obligations govern covered execution, while finalization requires evidence-backed satisfaction of all fresh mandatory obligations. Remaining gaps reflect its bound-

Method	Pass↑	U-E↓	S-A↓	Prov.	Eff.	Cmt.
Post-hoc Verification						
Agentic Rubrics (ACL’26)	74.7	12.6	23.0	△	△	×
Completion Gating						
VeriMAP (EACL’26)	79.3	9.6	20.7	△	✓	×
Runtime Enforcement						
AgentSpec (ICSE’26)	78.2	8.8	24.1	✓	×	×
Mediate-and-Commit						
SpecHarness	85.1	6.3	6.9	✓	✓	✓

Table 2: SkillsBench paradigm comparison with GPT-5.6 Sol fixed. Pass is the official-verifier pass rate; U-E and S-A are the two structural gaps. Prov., Eff., and Cmt. denote source-linked provenance, observable-effect validation, and versioned authoritative commitment. Markers indicate full (✓), partial or adaptation-dependent (△), or no support (×) in the evaluated adaptations.

ary: ungrounded or unobservable requirements remain advisory or abstained, while safely isolated channels outside the closure-audited surface use validate-and-commit. Across the evaluated adaptations, the complete SpecHarness architecture yields smaller gaps than the compared alternatives.

Model	Raw → SpecHarness		
	Pass↑	U-E↓	S-A↓
GPT-5.6 Sol	91.3→ 95.1	8.2→ 3.5	8.7→ 3.8
Claude Fable 5	89.6→ 94.0	9.1→ 4.1	10.4→ 4.7
Gemini 3.1 Pro	88.2→ 93.2	8.7→ 3.8	11.8→ 5.2
Kimi K3	85.7→ 90.6	11.6→ 5.9	14.3→ 7.4
GLM-5.2	84.4→ 89.8	10.3→ 5.2	15.6→ 8.1
Qwen3.7-Max	82.8→ 88.7	12.8→ 6.7	17.2→ 9.3
DeepSeek-V4-Pro	81.5→ 87.5	11.9→ 6.1	18.5→ 10.1
Macro Average	86.2→ 91.3	10.4→ 5.0	13.8→ 6.9

Table 3: GuideBench results across seven agents. Each cell reports Raw → SpecHarness; U-E and S-A denote the two decision-state gaps.

Results on GuideBench. Tables 3 and 4 show that the state-authority problem extends to guideline-governed decisions. SpecHarness improves all seven agents, raising macro Pass from 86.2% to 91.3%, while reducing U-E from 10.4% to 5.0% and S-A from 13.8% to 6.9%. The results indicate that the abstraction transfers from artifact state to rule-local decision state: applicable rules induce obligations, and au-

thorized evidence supports the corresponding commitments. As in artifact tasks, agent proposals cannot establish authoritative state. High answer accuracy is therefore insufficient: a plausible answer may omit a rule, misresolve priority, or rely on unsupported judgments. SatLM lowers U–E by executing declarative rules with an external solver, but retains higher S–A because solver outputs are not committed as authoritative decision state. Post-hoc verification and completion gating inspect or reject outputs without maintaining committed rule-local state. SpecHarness instead derives acceptance from guideline applications committed through authorized evidence, extending obligation–evidence–commit from artifact to decision state. Category-level results and residual failures appear in Appendix D.2; benchmark mappings and execution traces appear in Appendices E.1–E.2.

Method	Pass↑	U–E↓	S–A↓	Prov.	Eff.	Cmt.
Post-hoc Verification						
RvLLM (NeurIPS’25)	90.5	7.0	7.8	△	△	×
Completion Gating						
VeriMAP (EACL’26)	91.7	6.2	6.7	△	✓	×
Computation Substrate						
SatLM (NeurIPS’23)	92.3	4.9	6.4	×	△	×
Evidence-Authorized Commitment						
SpecHarness	95.1	3.5	3.8	✓	✓	✓

Table 4: GuideBench paradigm comparison with GPT-5.6 Sol fixed. Metrics and markers follow Table 2.

Ablation and Operational Analysis

Complementary Authority Mechanisms. Table 5 evaluates architecture variants within the same interaction framework, but does not isolate commitment under matched trajectories or compute. Removing mediation primarily increases U–E, removing effect validation increases unsupported acceptance, and removing commitment produces the largest S–A degradation. Removing blocking qualification lowers S–A only by reducing Raw-pass preservation, showing that conservative rejection is not equivalent to reliable authority. Skill-derived obligations expand the procedural requirements governed by this chain rather than merely reminding the agent through context. Full SpecHarness therefore balances action control, effect evidence, authoritative acceptance, and selective blocking.

Variant	Pass↑	U–E↓	S–A↓	Pres.↑
Full SpecHarness	85.1	6.3	6.9	96.8
w/o Mediation	80.5	10.0	11.5	95.2
w/o Effect Validation	78.2	9.4	16.1	93.5
w/o Commitment	81.6	8.1	25.3	98.4
w/o Blocking Qualification	79.3	8.8	5.7	90.3
w/o Skill Obligations	77.0	12.0	14.9	91.9

Table 5: Runtime architecture ablation on SkillsBench with GPT-5.6 Sol fixed. Pres. denotes paired Raw-pass preservation.

Freshness-Governed State Validity. Table 6 evaluates 248 targeted dependency mutations. Without invalidation, every mutation leaves outdated evidence admissible for completion. Full SpecHarness invalidates all affected entries, re-

Variant	Stale Acc.↓	Invalid.↑	Revalid.↑	Recovery↑
Full SpecHarness	0.0	100.0	95.8	95.6
w/o Freshness	100.0	0.0	N/A	N/A

Table 6: Freshness invalidation and recovery (%) over 248 paired targeted SkillsBench mutations; protocol and denominators appear in Appendix B.3.

Runtime Mode	SkillsBench	GuideBench
Mediate-and-commit	44.0%	0.0%
Validate-and-commit	56.0%	100.0%

Table 7: Runtime-mode allocation among constructed hard obligations; GuideBench uses validate-and-commit exclusively.

stores 95.8% through revalidation, and recovers 95.6% of tasks after repair. These results show that versioned state is necessary to prevent stale completion under the evaluated mutations.

Enforcement Scope and Evaluation Independence. Table 7 summarizes the runtime modes assigned to constructed hard obligations. In SkillsBench, 44.0% of hard obligations lie on closure-audited action surfaces and use mediate-and-commit; the remaining 56.0% use validate-and-commit on safely isolated channels. GuideBench has no closure-audited physical action surface, so all rule-local decision-state obligations use validate-and-commit. These proportions bound our claim: SpecHarness governs the grounded, observable mandatory portion of the specification, not the full natural-language specification. The compiler is selected using development annotations derived only from agent-visible materials. Its output and the resulting obligation surface are then frozen before evaluation. The same frozen runtime validators evaluate all conditions read-only under a shared protocol; only SpecHarness uses their evidence for commitment and finalization. Held-out official evaluators are used only for final pass measurement and post-hoc alignment: they neither construct obligations nor provide runtime feedback.

Conclusion

SpecHarness reframes specification following as a problem of state authority rather than reasoning or verification alone. Its contribution is not a new validator or commit primitive in isolation, but an agent-specific authority boundary that prevents proposals, actions, and self-assessments from directly establishing specification-governed state. The obligation–evidence–commit architecture operationalizes this boundary across action authorization, effect validation, freshness, and finalization by compiling heterogeneous agent-visible specifications into source-linked conditions whose state may be updated only from admissible evidence. Our experiments evaluate the complete architecture, including its feedback-and-repair loop, rather than isolating commitment under matched compute. Within its stated scope of grounded and monitorable conditions, SpecHarness shows how specifications can serve as an external basis for execution and acceptance rather than remain transient behavioral context.

References

- Bai, Y.; Kadavath, S.; Kundu, S.; Askell, A.; Kernion, J.; Jones, A.; Chen, A.; Goldie, A.; Mirhoseini, A.; McKinnon, C.; et al. 2022. Constitutional ai: Harmlessness from ai feedback. *arXiv preprint arXiv:2212.08073*.
- Bandi, C.; Dumitru, R.-G.; Hertzberg, B.; Agarwal, D.; Boo, G.; Polakam, T.; Hassaan, S.; Da, J.; Kim, H.; Gupta, V.; et al. 2026. Mcp-atlas: A large-scale benchmark for tool-use competency with real mcp servers. *arXiv preprint arXiv:2602.00933*.
- Barke, S.; Goyal, A.; Khare, A.; Singh, A.; Nath, S.; and Bansal, C. 2026. AgentRx: Diagnosing AI Agent Failures from Execution Trajectories. *arXiv preprint arXiv:2602.02475*.
- Cemri, M.; Pan, M. Z.; Yang, S.; Agrawal, L. A.; Chopra, B.; Tiwari, R.; Keutzer, K.; Parameswaran, A.; Klein, D.; Ramchandran, K.; et al. 2026. Why do multi-agent llm systems fail? *Advances in Neural Information Processing Systems*, 38.
- Diao, L.; Xu, X.; Sun, W.; Yang, C.; and Zhang, Z. 2025. Guidebench: Benchmarking domain-oriented guideline following for llm agents. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 11361–11399.
- Dong, L.; Lu, Q.; and Zhu, L. 2024. Agentops: Enabling observability of llm agents. *arXiv preprint arXiv:2411.05285*.
- Gray, J.; and Lamport, L. 2004. Consensus on transaction commit. *arXiv preprint cs/0408036*.
- Leucker, M.; and Schallhart, C. 2009. A brief account of runtime verification. *The journal of logic and algebraic programming*, 78(5): 293–303.
- Li, H.; Zhong, W.; Wu, Y.; Ma, H.; Guo, Y.; Dang, T. M.; and Huang, J. 2026a. Guidelines as Environments: A World Model Approach to Rule Following. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 16302–16318.
- Li, X.; Liu, Y.; Chen, W.; You, B.; Di, Z.; He, Y.; Zheng, S.; Choe, K. W.; Sun, J.; Wang, S.; et al. 2026b. SkillsBench: Benchmarking how well agent skills work across diverse tasks. *arXiv preprint arXiv:2602.12670*.
- Li, Y.; Chen, Y.; Wen, H.; Zhang, B.; Liu, H.; Wang, P.; Feng, Y.; and Tian, Y. 2026c. VIGIL: Runtime Enforcement of Behavioral Specifications in AI Agent Skills. *arXiv preprint arXiv:2606.26524*.
- Mazzocchi, A. M. 2026. Cryptographic Runtime Governance for Autonomous AI Systems: The Aegis Architecture for Verifiable Policy Enforcement. *arXiv preprint arXiv:2603.16938*.
- Nguyen, H.-D.; and Tran, X.-T. 2026. Verify-Gated Completion as Admission Control in a Governed Multi-Agent Runtime: A Bounded Architecture Case Study. *arXiv preprint arXiv:2605.17998*.
- Ouyang, L.; Wu, J.; Jiang, X.; Almeida, D.; Wainwright, C. L.; Mishkin, P.; Zhang, C.; Agarwal, S.; Slama, K.; Ray, A.; et al. 2022. Training language models to follow instructions with human feedback. *arXiv preprint arXiv:2203.02155*.
- Palumbo, N.; Choudhary, S.; Choi, J.; Amir, G.; Chalasani, P.; and Jha, S. 2026. Formal policy enforcement for real-world agentic systems. *arXiv preprint arXiv:2602.16708*.
- Qwen Team. 2026. Qwen3.7-Plus: Multimodal Agent Intelligence.
- Raghavendra, M.; Gunjal, A.; Liu, B.; and He, Y. 2026. Agentic Rubrics as Contextual Verifiers for SWE Agents. In Liakata, M.; Moreira, V. P.; Zhang, J.; and Jurgens, D., eds., *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 15265–15290. San Diego, California, United States: Association for Computational Linguistics. ISBN 979-8-89176-390-6.
- Saltzer, J. H.; and Schroeder, M. D. 1975. The protection of information in computer systems. *Proceedings of the IEEE*, 63(9): 1278–1308.
- Su, Y.; Xu, K.; Gao, Y.; Yang, F.; Li, C.; Yang, M.; and Xu, T. 2026. Neuro-Symbolic Verification on Instruction Following of LLMs. *arXiv preprint arXiv:2601.17789*.
- Tang, G.; Jia, Q.; Tan, Y.; Huang, Z.; Ji, N.; and Chen, G. 2026. Verification-Gated Agentic Mission-State Governance for Intelligent Industrial Multi-Robot Systems. *arXiv preprint arXiv:2606.31339*.
- Wang, G.; Xie, Y.; Jiang, Y.; Mandlekar, A.; Xiao, C.; Zhu, Y.; Fan, L.; and Anandkumar, A. 2023. Voyager: An open-ended embodied agent with large language models. *arXiv preprint arXiv:2305.16291*.
- Wang, H.; Poskitt, C. M.; and Sun, J. 2025. Agentspec: Customizable runtime enforcement for safe and reliable llm agents. *arXiv preprint arXiv:2503.18666*.
- Wang, X.; Li, B.; Song, Y.; Xu, F. F.; Tang, X.; Zhuge, M.; Pan, J.; Song, Y.; Li, B.; Singh, J.; et al. 2025. Openhands: An open platform for ai software developers as generalist agents. In *International Conference on Learning Representations*, volume 2025, 65882–65919.
- Xu, A.; Lin, B.; Xue, B.; Wang, B.; Xu, B.; Wu, B.; Zhang, B.; Lin, C.; Dong, C.; Ling, C.; et al. 2026a. Deepseek-v4: Towards highly efficient million-token context intelligence. *arXiv preprint arXiv:2606.19348*.
- Xu, T.; Zhang, D.; Mitra, K.; and Hruschka, E. 2026b. Verification-aware planning for multi-agent systems. In *Proceedings of the 19th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, 7528–7546.
- Ye, X.; Chen, Q.; Dillig, I.; and Durrett, G. 2023. Satlm: Satisfiability-aided language models using declarative prompting. *Advances in Neural Information Processing Systems*, 36: 45548–45580.
- Zeng, A.; Lv, X.; Hou, Z.; Du, Z.; Zheng, Q.; Chen, B.; Yin, D.; Ge, C.; Huang, C.; Xie, C.; et al. 2026. Glm-5: from vibe coding to agentic engineering. *arXiv preprint arXiv:2602.15763*.
- Zhang, Y.; Emma, S.; En, A.; and Dong, J. S. 2026. Rvllm: Llm runtime verification with domain knowledge. *Advances in Neural Information Processing Systems*, 38: 80568–80588.

A Specification Compilation and Coverage

A.1 Compiler Selection and Freezing Protocol

We select the compiler solely on a task-disjoint development set. We compare seven candidates: GPT-5.6 Sol, Claude Fable 5, Gemini 3.1, Kimi K3, GLM-5.2, Qwen3.7, and DeepSeek-V4. The development set contains 14 tasks from the SkillsBench `tasks-extra/` partition and is disjoint at the task-instance level from the 87 evaluation tasks. Using only agent-visible prompts, workspace information, and injected skills, we segment these tasks into 65 source units and annotate 81 source-grounded directions; 55 units admit concrete machine-checkability candidates. Task-family and skill overlap are allowed, so the split ensures task-instance and evaluation-information separation rather than full distributional independence. All candidates receive the same visible materials, segmentation, instructions, output schema, and decoding settings. Development annotations are frozen before comparison and are not revised using candidate outputs. Official tests, evaluator implementations, reference solutions, task-agent trajectories, U-E or S-A results, Raw-versus-SpecHarness comparisons, and official pass outcomes are unavailable during selection. Let $\mathcal{U}_{\text{dev}}$ be the 65 source units, $\mathcal{D}_{\text{dev}}$ the 81 annotated directions, and $\widehat{\mathcal{D}}_c$ the directions extracted by compiler c . A prediction matches an annotation only if it uses the same source unit and preserves the annotated behavior or acceptance condition. Each annotation may be matched once; duplicates and unmatched predictions do not increase coverage:

$$\text{Cov}_{\text{dev}}(c) = \frac{|\{d \in \mathcal{D}_{\text{dev}} : \exists \hat{d} \in \widehat{\mathcal{D}}_c, \text{Match}(\hat{d}, d)\}|}{|\mathcal{D}_{\text{dev}}|}. \quad (14)$$

For an extracted direction $\hat{d}$, $\text{Acct}(\hat{d})$ requires an explicit disposition and a nonempty evaluation provider and criterion. $\text{Valid}(\hat{d})$ additionally requires a valid source anchor and Boolean machine-checkability field. $\text{Mapped}_c(u)$ holds when source unit u grounds a direction or is explicitly marked advisory, abstained, or residual:

$$\begin{aligned} \text{Accounted}(c) &= \frac{\sum_{\hat{d} \in \widehat{\mathcal{D}}_c} \mathbf{1}[\text{Acct}(\hat{d})]}{|\widehat{\mathcal{D}}_c|}, \\ \text{UnitMap}(c) &= \frac{\sum_{u \in \mathcal{U}_{\text{dev}}} \mathbf{1}[\text{Mapped}_c(u)]}{|\mathcal{U}_{\text{dev}}|}, \\ \text{ValidRec}(c) &= \frac{\sum_{\hat{d} \in \widehat{\mathcal{D}}_c} \mathbf{1}[\text{Valid}(\hat{d})]}{|\widehat{\mathcal{D}}_c|}. \end{aligned} \quad (15)$$

Development coverage is the prespecified selection criterion. The other metrics audit structural completeness and are not combined with coverage. Machine-checkability indicates a possible validator, not qualification for hard enforcement. Table 8 reports the development-set comparison.

As shown in Table 8, GPT-5.6 Sol achieves the highest development coverage and is selected as the compiler. Its instructions, output schema, decoding settings, and construction procedure are then frozen. No official test, evaluation trajectory, runtime result, or experimental comparison is used to revise the compiler or reconsider the selection.

A.2 Post-Selection Full-Task Coverage Audit

After selection and freezing, we apply all seven unchanged candidates to the 87 SkillsBench tasks as a post-selection sensitivity audit. This audit does not affect compiler selection, the selected output, the obligation surface, or any experimental setting. It checks full-task construction completeness and correspondence with independently defined benchmark requirements. A task is direction-accounted when every extracted direction has an explicit disposition, provider, and criterion. It is unit-mapped when every visible source unit grounds a direction or is explicitly marked advisory, abstained, or residual. Broad correspondence matches an official test to the same visible requirement dimension at the level of artifact, structure, numeric value, preservation, behavior, or order and coverage. Fine-grained correspondence additionally requires path-, field-, or multi-token semantic evidence. Table 9 reports the number of extracted directions, tasks with complete direction accounting, tasks with complete source-unit mapping, and correspondence with the 585 official test functions.

Table 9 supports, but does not define, the development-set choice. GPT-5.6 Sol is the only candidate with complete task-level direction accounting and source-unit mapping, and it also has the highest broad and fine-grained correspondence. Gemini 3.1 reaches 95.90% broad correspondence but remains incomplete on both construction measures. Official tests are inspected only after all candidate outputs are complete and frozen. They are never given to candidate compilers, task agents, runtime validators, or the feedback-and-repair loop. The audit does not revise extractions, construct obligations, produce repair feedback, or transfer evaluator logic into the runtime. Runtime obligations and validators are derived from agent-visible specifications and the execution substrate. The construction measures establish completeness over each compiler’s extracted direction surface, not complete recall of the natural-language specification. Broad correspondence shows that a direction covers the same visible requirement dimension as an official test; it does not imply recovery of the complete verifier logic. The selected 509 directions therefore form a common source-grounded measurement surface, not an exhaustive reconstruction of the specification or evaluator. Compiler selection uses only frozen development annotations. It never uses task-agent trajectories, completion claims, repair outcomes, U-E or S-A results, Raw-versus-SpecHarness comparisons, condition-specific execution results, official-test correspondence, or official pass outcomes. Official evaluators are used only after selection for this audit and final pass measurement, and never for runtime feedback or condition-specific obligation satisfaction.

B Runtime Implementation and Assurance

B.1 Validator Qualification and Commitment Protocol

Runtime validators are constructed from agent-visible specifications, observable workspace state, and criteria recorded by the frozen compiler. Official tests, reference solutions, evaluator outputs, and task-agent outcomes are unavailable

Compiler	Matched	Dev. Cov.↑	Accounted↑	Unit Map↑	Valid Rec.↑
GPT-5.6 Sol	77/81	95.1%	98.8%	100.0%	97.6%
Claude Fable 5	75/81	92.6%	100.0%	98.5%	98.7%
Gemini 3.1	73/81	90.1%	97.4%	96.9%	96.1%
Kimi K3	71/81	87.7%	98.6%	95.4%	97.2%
GLM-5.2	69/81	85.2%	96.0%	93.8%	94.7%
Qwen3.7	67/81	82.7%	97.2%	92.3%	96.0%
DeepSeek-V4	65/81	80.2%	94.8%	90.8%	93.5%

Table 8: Candidate-compiler results on 14 task-disjoint development tasks with 65 source units and 81 annotated directions. Matched is the numerator of development coverage. Accounted and Valid Rec. use extracted records as their denominator; Unit Map uses the 65 source units.

Audit Metric	GPT-5.6 Sol	Claude Fable 5	Gemini 3.1	Kimi K3	GLM-5.2	Qwen3.7	DeepSeek-V4
Directions	509	521	496	517	481	468	492
Direction-accounted tasks	87/87 (100.00%)	86/87 (98.85%)	86/87 (98.85%)	86/87 (98.85%)	85/87 (97.70%)	84/87 (96.55%)	85/87 (97.70%)
Unit-mapped tasks	87/87 (100.00%)	85/87 (97.70%)	86/87 (98.85%)	85/87 (97.70%)	84/87 (96.55%)	83/87 (95.40%)	84/87 (96.55%)
Broad test correspondence	573/585 (97.95%)	555/585 (94.87%)	561/585 (95.90%)	552/585 (94.36%)	546/585 (93.33%)	537/585 (91.79%)	526/585 (89.91%)
Fine-grained subset	406/585 (69.40%)	382/585 (65.30%)	389/585 (66.50%)	374/585 (63.93%)	365/585 (62.39%)	349/585 (59.66%)	337/585 (57.61%)
Below broad criterion	12/585 (2.05%)	30/585 (5.13%)	24/585 (4.10%)	33/585 (5.64%)	39/585 (6.67%)	48/585 (8.21%)	59/585 (10.09%)

Table 9: Post-selection construction and official-test correspondence for the seven frozen candidates. Task-level rates use 87 tasks; correspondence rates use 585 official test functions. These results do not participate in compiler selection.

during construction and qualification. Validators are frozen before task-agent execution and are not revised using Pass, U-E, S-A, ablation, or condition-comparison results. A validator qualifies for blocking only if its inputs are observable within the trusted boundary, its criterion is deterministic and source-linked, and the same workspace and dependency state reproduces the same output. Qualification covers satisfying cases, targeted violations, malformed or missing inputs, unavailable providers, and execution failures. Requirements without a qualified provider remain advisory, abstained, or residual. Table 10 reports qualification results obtained before task-agent evaluation. A validator enters the blocking set only after its full suite produces the prespecified outcomes; otherwise, it is excluded. Any qualification-time correction uses only these cases and occurs before freezing.

Validator Qualification	SkillsBench	GuideBench
Candidate validators	278	104
Qualified for blocking	250	96
Satisfying cases	556	208
Targeted violations	834	312
Malformed or missing cases	278	104
Provider or execution errors	278	104
Expected outcomes	1929/1946	720/728
Outcome mismatches	17	8

Table 10: Validator qualification before task-agent evaluation. Expected outcomes count cases producing the prespecified result.

For SkillsBench, the 250 qualified validators are grounded validator instances bound one-to-one to the 250 hard obligations; shared implementations with different grounded parameters are counted separately. Each invocation returns

$$r_t \in \{\text{PASSED}, \text{FAILED}, \text{ERROR}\} \quad (16)$$

with the obligation identifier, validator identity and version, dependency versions, and attributable evidence. A

qualified, admissible, and fresh PASSED result may establish satisfaction. A FAILED result may commit authoritative non-satisfaction and trigger repair, but cannot satisfy the obligation. An ERROR may enter the diagnostic trace but does not establish satisfaction or failure, update authoritative state, or permit finalization while the affected obligation remains mandatory. Commitment is atomic. Before updating the ledger, the runtime checks the obligation, provider, validator identity and version, scope, result type, and dependency versions. Agent actions, self-reports, completion claims, tool-return strings, and unqualified observations cannot modify authoritative state. Revalidation creates a new versioned commitment while preserving prior provenance. The same frozen validators measure all conditions read-only. Only SpecHarness uses their evidence online for commitment, source-linked feedback, repair, and finalization. The comparison therefore evaluates the complete architecture rather than commitment under matched online access, interaction, or compute.

B.2 Trusted Boundary, Closure Audit, and No-Bypass Tests

The trusted boundary contains the obligation ledger, authorization service, qualified validators, dependency-version store, and audited capability wrappers. The agent, its prompts and memory, proposed arguments, self-reports, and natural-language tool-return strings remain outside this boundary. For each candidate mediated surface, we construct a capability graph over agent-accessible tools, wrappers, subprocess interfaces, and artifact stores. A protected action class a qualifies for preventive mediation only if no reachable effect-equivalent path bypasses its authorization procedure:

$$\neg \exists p [\text{Reachable}(p) \wedge \text{EffectEq}(p, a) \wedge \text{BypassesAuth}(p, a)]. \quad (17)$$

Table 11 reports the stress tests, and Table 12 reports the re-

sulting obligation-level allocation. Stress-test cases and obligations use different denominators: one action surface may support multiple obligations. Thus, the 11 detected violations do not correspond one-to-one with the 140 validate-and-commit obligations.

Audit Class	Cases	Correct	Violations
Direct access	220	220	0
Alternate path	176	174	2
Path handling	264	261	3
Subprocess	132	128	4
Malformed proposal	220	220	0
Token scope	220	220	0
Stale token	220	220	0
Fallback path	176	174	2
Total	1628	1617	11

Table 11: Closure stress tests over candidate mediated surfaces. Detected violations exclude the corresponding paths or surfaces from closure-qualified mediation.

All 11 detected bypasses occurred on candidate paths or surfaces excluded from closure-qualified mediation; no unresolved bypass remained on any surface receiving the preventive no-bypass claim. Authorized proposals must pass obligation matching and authorization before execution. Unauthorized, ambiguous, stale, malformed, or effect-equivalent alternate proposals must be blocked or clarified. Authorization permits an attempt but does not establish satisfaction; the resulting effect must still be observed and validated.

Runtime Qualification	Obligations	Share
Closure-audited mediation	110/250	44.0%
Safely isolated validation	140/250	56.0%
Total hard obligations	250/250	100.0%

Table 12: Runtime-mode qualification of constructed SkillsBench hard obligations.

A preventive no-bypass claim applies only when every reachable effect-equivalent path is represented in the capability graph and mediated within the trusted boundary. Surfaces with unresolved bypasses are excluded. If their effects remain safely isolated and observable, they use validate-and-commit; otherwise, they remain outside hard enforcement. These guarantees are conditional on the audited graph, trusted boundary, effect-equivalence relation, and threat model. They exclude undeclared external channels, compromised trusted components, validator defects, and effects outside the observable environment.

B.3 Freshness Invalidation and Recovery Protocol

Each commitment is bound to the versions of the dependencies used by its evidence provider and is fresh only when all versions match:

$$\text{Fresh}(c_t) \iff \forall d \in \text{Deps}(c_t), \text{ver}_{c_t}(d) = \text{ver}_t(d). \quad (18)$$

A dependency mutation invalidates affected commitments and propagates through the dependency graph. Invalidated

entries remain in the historical trace but cannot support finalization. A known mismatch yields `STALE`; incomplete version information yields `UNKNOWN`. Both require new admissible evidence. The runtime updates dependency versions, invalidates affected entries, and reruns their validators. Passing revalidation creates a fresh satisfied commitment. Failed revalidation commits current non-satisfaction and may trigger repair. Errors enter the diagnostic trace without updating authoritative state. Repairs repeat invalidation and revalidation before finalization. A mutation trial may affect multiple ledger entries, and several trials may affect the same task. Trials count injected mutations, Affected Entries counts invalidated commitments, and Recovered uses Affected Tasks as its denominator.

As shown in Table 13, all 595 affected entries are invalidated, 570 are restored by revalidation, and 218 of 228 affected tasks recover after repair. Without freshness invalidation, all 248 mutations leave previously committed evidence eligible for reuse during finalization. Unrecovered cases remain unsatisfied or incomplete rather than reusing stale evidence. The protocol covers declared dependencies in the observable workspace, not untracked external state or undeclared dependencies.

C Experimental Protocol

C.1 Tasks, Models, and Execution Settings

All SkillsBench conditions use the same 87 tasks, initial workspaces, agent-visible prompts, injected skills, tool interfaces, and official evaluation procedure. All GuideBench conditions use the same 1,042 tasks, guideline entries, task inputs, and official evaluation. Four duplicate GuideBench rules are removed before constructing the 297 shared templates and 5,817 task-level obligation instances. SkillsBench agents run in OpenHands under the same execution image, workspace initialization, tool permissions, environment variables, and network policy across paired conditions. Each run starts from a fresh workspace, and no files or state are reused across runs. GuideBench uses the same prompt construction and model interface across paired conditions; each model retains the same decoding configuration within each comparison. We evaluate GPT-5.6 Sol, Claude Fable 5, Gemini 3.1 Pro, Kimi K3, GLM-5.2, Qwen3.7-Max, and DeepSeek-V4-Pro as task agents. Table 14 reports the provider model identifiers used in the experiments. The same model endpoint is retained within each paired comparison. The selected GPT-5.6 Sol compiler is invoked separately and shares no task-agent trajectory, memory, or evaluation outcome.

A run ends when its condition accepts completion, the interaction limit is reached, the wall-clock timeout expires, or an unrecoverable infrastructure failure occurs. Paired runs of the same task-agent model share task inputs, initial workspaces, base prompts, tool access, nominal interaction budgets, nominal token budgets, wall-clock timeouts, and condition-independent environment settings. These controls match configured ceilings, not realized calls, tokens, repair steps, or wall-clock time. No run is selectively repeated or reconfigured using official Pass, U-E, or S-A outcomes. Official SkillsBench verifiers and GuideBench answer labels are

Mutation Class	Trials	Affected Entries	Invalidated	Revalidated	Affected Tasks	Recovered
Artifact content	80	190	190	183	72	69
Path or identity	50	121	121	116	46	44
Schema or configuration	46	108	108	103	42	40
Upstream obligation	42	104	104	99	39	37
Validator or environment	30	72	72	69	29	28
Total	248	595	595	570	228	218

Table 13: Freshness results by dependency-mutation class. All 595 affected entries are invalidated; 570/595 (95.8%) are revalidated, and 218/228 (95.6%) affected tasks recover after repair.

Agent	Provider Model ID
GPT-5.6 Sol	gpt-5.6-sol
Claude Fable 5	claude-fable-5
Gemini 3.1 Pro	gemini-3.1-pro-preview
Kimi K3	kimi-k3
GLM-5.2	glm-5.2
Qwen3.7-Max	qwen3.7-max
DeepSeek-V4-Pro	deepseek-v4-pro

Table 14: Provider model identifiers used for the evaluated task agents. The same model endpoint is retained within each paired comparison.

invoked only after condition-specific execution ends. They do not enter prompts, obligation construction, runtime validation, repair feedback, or finalization. The measurement surfaces and runtime validators are frozen before task-agent evaluation.

C.2 Baseline Adaptation, Runtime Access, and Completion Rules

Baselines are adapted to the same benchmark interfaces and shared execution substrate. Each adaptation preserves the method’s defining intervention point without adding unsupported capabilities. Table 15 reports the implemented runtime access and completion semantics.

Raw agents receive the original task context and native tool outputs but no frozen runtime-validator feedback. Their terminal completion claims are accepted without an additional gate. Agentic Rubrics and RvLLM operate after output production and do not mediate or gate prior execution. VeriMAP evaluates terminal completion before acceptance but does not maintain versioned authoritative state. AgentSpec constrains matched actions but does not commit observed effects as authoritative obligation state. SatLM externalizes rule computation but does not maintain versioned evidence-authorized commitments. SpecHarness combines online validator evidence, source-linked feedback, repair, versioned commitment, and ledger-derived finalization.

Paired conditions share task inputs, initial workspaces, task-agent models, base prompts, tool access, and condition-independent environment settings. The same frozen validators measure all conditions read-only, but only SpecHarness consumes their outputs online. Thus, validator definitions and measurement criteria are shared, whereas condition-specific acceptance rules, online feedback, repair trajectories, and realized compute are not matched. The comparison

therefore evaluates the complete SpecHarness architecture rather than the isolated causal effect of commitment.

Acceptance follows each condition’s implemented rule. Raw and post-hoc methods retain the agent’s terminal claim without an additional runtime gate. Completion-gating methods accept only when their gate passes. Runtime-enforcement methods use their native termination rule, and SatLM returns its solver-derived answer. SpecHarness accepts only when every active mandatory obligation has a fresh satisfied commitment. Official benchmark Pass is computed independently after execution for all conditions.

Runs are paired by task and task-agent model. Infrastructure failures are handled under the same condition-independent policy within each paired comparison. No run is excluded, repeated, extended, or reconfigured because of its official Pass result, U–E value, S–A value, or contribution to a reported comparison.

D Statistical Analysis and Additional Results

D.1 Significance Tests and Confidence Intervals

All uncertainty estimates preserve the paired experimental design. For each benchmark, we draw 10,000 bootstrap samples by resampling tasks with replacement. Raw and SpecHarness use the same sampled task indices, and all measurement units associated with a sampled task remain in the same cluster. Within each replicate, metric changes are first computed separately for each task-agent model and then macro-averaged without model weighting. Percentile intervals use the 2.5th and 97.5th percentiles of the resulting paired bootstrap distribution.

For U–E, unrealized measurement units are aggregated over the complete frozen benchmark surface within each model before the seven model-level rates are macro-averaged. Thus, SkillsBench directions and GuideBench obligation instances are weighted by their occurrence in the frozen measurement surface, rather than by an equal-weighted average of task-level U–E rates.

For SkillsBench Pass, we additionally conduct an exact two-sided McNemar test for each task-agent model using its 87 paired outcomes. Holm correction controls the family-wise error rate across the seven tests.

The differences between the two discordant counts correspond to SpecHarness improvements of 12, 11, 15, 6, 10, 10, and 9 tasks, respectively. All seven comparisons remain significant after Holm correction. These tests establish paired end-to-end differences between the evaluated con-

Benchmark	Condition	Runtime Evidence	Validator Feedback	Action Mediation	State Commitment	Completion Rule
SkillsBench	Raw	No	No	No	No	Ungated agent claim
SkillsBench	Agentic Rubrics	No	No	No	No	Ungated agent claim
SkillsBench	VeriMAP	Terminal	Gate result	No	No	Verifier gate
SkillsBench	AgentSpec	Policy state	Rule decision	Yes	No	Native termination
SkillsBench	SpecHarness	Online	Source-linked	Closure-audited	Versioned	Fresh mandatory satisfaction
GuideBench	Raw	No	No	N/A	No	Ungated agent claim
GuideBench	RvLLM	No	No	N/A	No	Ungated agent claim
GuideBench	VeriMAP	Terminal	Gate result	N/A	No	Verifier gate
GuideBench	SatLM	Solver result	No	N/A	No	Solver-derived answer
GuideBench	SpecHarness	Online	Source-linked	N/A	Versioned	Fresh mandatory satisfaction

Table 15: Runtime access and completion semantics of the evaluated adaptations. Runtime Evidence denotes evidence available to the condition during execution; all conditions are evaluated afterward by the same frozen measurement validators. Entries describe the implemented conditions rather than every capability of the original systems.

Benchmark	Metric	Change	95% CI
SkillsBench	Pass	+12.0	[+9.1, +14.9]
	U-E	-8.1	[-9.0, -7.2]
	S-A	-20.0	[-22.8, -17.4]
GuideBench	Pass	+5.1	[+4.4, +5.8]
	U-E	-5.4	[-6.0, -4.8]
	S-A	-6.9	[-7.6, -6.2]

Table 16: Paired task-bootstrap changes from Raw to SpecHarness in percentage points. Intervals use 10,000 task-level replicates.

Agent	Raw Only	SpecHarness Only	Exact p	Holm p
GPT-5.6 Sol	1	13	0.00183	0.01099
Claude Fable 5	1	12	0.00342	0.01709
Gemini 3.1 Pro	1	16	0.00027	0.00192
Kimi K3	0	6	0.03125	0.03125
GLM-5.2	1	11	0.00635	0.02539
Qwen3.7-Max	1	11	0.00635	0.02539
DeepSeek-V4-Pro	1	10	0.01172	0.02539

Table 17: Exact paired McNemar tests for SkillsBench Pass. Raw Only and SpecHarness Only are discordant task counts; p -values are two-sided.

ditions; they do not isolate authoritative commitment from online validation, feedback, repair, or realized compute.

D.2 Category-Level Results and Residual Failures

Requirement categories are assigned only for analysis and do not alter the frozen compiler, validators, obligation state, or runtime decisions. SkillsBench categories partition the 509 source-grounded directions; GuideBench categories partition the 5,817 rule-local obligation instances. Rates are computed within category over the corresponding frozen measurement units.

Residual official failures are categorized from held-out evaluator outcomes after execution. Categories describe the immediate unresolved failure rather than a unique causal explanation. Requirements outside the grounded or observable hard-enforcement scope are distinguished from failures of qualified hard obligations. Validator errors and exhausted interaction limits leave affected mandatory obligations unre-

SkillsBench Category	Units	Raw U-E	Spec. U-E	Change
Artifact content	80	17.0	8.4	-8.6
Structural constraints	105	18.5	9.7	-8.8
Numeric constraints	92	16.8	8.6	-8.2
Preservation	74	15.9	8.2	-7.7
Behavioral requirements	86	18.8	10.6	-8.2
Order and coverage	72	16.9	9.9	-7.0
Overall	509	17.4	9.3	-8.1

Table 18: SkillsBench U-E by requirement category (%).

GuideBench Category	Instances	Raw U-E	Spec. U-E	Change
Applicability	1,300	10.1	4.8	-5.3
Priority	1,100	10.7	5.0	-5.7
Exceptions	900	11.2	5.5	-5.7
Required response	1,200	10.3	4.9	-5.4
Output constraints	800	9.8	4.7	-5.1
Other rule relations	517	10.4	5.1	-5.3
Overall	5,817	10.4	5.0	-5.4

Table 19: GuideBench U-E by rule-local analysis category (%).

solved.

SkillsBench Residual Failure	Count
Outside hard-enforcement scope	35
Qualified obligation unresolved	28
Validator error or unavailable	22
Repair or interaction exhausted	51
Held-out evaluator mismatch	28
Total	164

Table 20: Residual SkillsBench official failures under SpecHarness, aggregated over seven models. The total equals the sum of the per-model official-failure counts.

Condition-execution tokens include all task-agent input and output tokens, and calls count task-agent model invocations. Wall-clock time additionally includes online validator execution, source-linked feedback, and repair. Compiler selection, validator qualification, task-specific obligation construction, and official post-run evaluation are excluded from these paired execution costs. Task-specific preprocessing is

GuideBench Residual Failure	Count
Outside hard-enforcement scope	125
Qualified obligation unresolved	96
Validator error or unavailable	173
Repair or interaction exhausted	147
Held-out evaluator mismatch	96
Total	637

Table 21: Residual GuideBench official failures under SpecHarness, aggregated over seven models. The total satisfies $637 = 7 \times 1,042 - 6,657$, where 6,657 is the aggregate official-pass count.

reported separately.

For each task-agent model, token and wall-clock overheads are computed as the ratio of the mean SpecHarness cost per task to the corresponding Raw cost. Call overhead is the paired mean difference in task-agent calls per task. The final row macro-averages these model-level quantities without weighting models by token volume or execution time.

D.3 Absolute Runtime Cost and Diagnostic Traceability

This diagnostic comparison evaluates the information exposed by the complete conditions rather than diagnostic quality under matched trace access. Raw lacks the native ledger and source-linked runtime evidence that SpecHarness is designed to produce. The reported $1.24\times$ wall-clock ratio covers condition execution only; task-specific preprocessing is reported separately. SpecHarness averages $1.53\times$ task-agent tokens, $1.24\times$ condition-execution time, and 0.36 additional task-agent calls per task relative to Raw. These differences characterize the complete online validation, feedback, and repair architecture rather than commitment alone.

Diagnostic traceability is evaluated on a fixed SkillsBench failure-replay set shared by both conditions. Raw diagnostics use the native trajectory and terminal output without access to the SpecHarness ledger or online validator feedback; SpecHarness diagnostics use its native source-linked runtime trace. A report is actionable when it identifies the relevant source requirement, failed or unresolved condition, and repair target.

E Benchmark Instantiations and Execution Traces

E.1 SkillsBench and GuideBench Instantiations

Table 24 summarizes how the common obligation–evidence–commit abstraction is instantiated under the different state semantics of SkillsBench and GuideBench.

In SkillsBench, visible task and skill requirements are compiled into source-linked obligations over observable workspace state. Obligations on closure-audited action surfaces use mediate-and-commit, while safely isolated channels use validate-and-commit. Evidence records bind observed artifact state to the corresponding dependency versions.

In GuideBench, visible guidelines are compiled into rule-local obligations whose applicability depends on the supplied

decision context. Because the benchmark does not expose a closure-audited physical action surface, hard obligations use validate-and-commit. A bound rule validator checks both applicability and agreement of the proposed decision with the applicable guideline before committing rule-local evidence.

E.2 End-to-End Execution Traces

Table 25 follows one representative mandatory obligation through the end-to-end runtime protocol for each benchmark. Other active obligations are omitted for space but remain subject to the same evidence, commitment, freshness, satisfaction, and finalization rules. The examples are audited protocol replays instantiated from actual agent-visible task, skill, guideline, and context materials; they are not presented as verbatim logs of naturally occurring trajectories.

The SkillsBench example uses the `data-to-d3` task. Its visible task requires a browser-accessible application at `/root/output/index.html`, together with `js/d3.v6.min.js`, `js/visualization.js`, `css/style.css`, and copied input data. The visible `d3-visualization` skill additionally requires offline, deterministic dependency use.

The GuideBench example uses zero-based instance `chat_tasks.json[176]`. Its context states that the user has an existing booking and requests cancellation. Guideline `rule_6` requires cancellation of the booking and a response confirming successful cancellation. The observed dialogue satisfies both checks, making option A the supported decision.

For compactness, o_S denotes the selected SkillsBench layout obligation and q_S its bound validator. Similarly, o_G denotes the selected GuideBench rule-local obligation and q_G its bound validator. In the GuideBench replay, q_G checks both rule applicability and agreement of option A with the same active obligation.

For each selected obligation, the replay traverses the same state-transition discipline:

$$\begin{aligned}
\text{source} &\rightarrow \text{qualified obligation} \\
&\rightarrow \text{scoped proposal} \rightarrow \text{observed evidence} \\
&\rightarrow \text{versioned commitment} \rightarrow \text{freshness check} \\
&\rightarrow \text{global finalization check.}
\end{aligned} \tag{19}$$

The SkillsBench replay shows how one artifact obligation is authorized, observed, committed, invalidated, and revalidated. It does not enumerate the task’s other obligations concerning copied data, rendered content, layout, interaction, or visual behavior. The agent’s file writes remain proposals until trusted workspace observation produces admissible evidence. Changing a bound artifact invalidates the earlier commitment, and repair requires new evidence at the current dependency version.

The GuideBench replay follows `rule_6` and its supported decision while omitting unrelated or additional active rule-local obligations. The proposed option does not establish the answer state. The bound validator checks both applicability and decision agreement for the same obligation before committing authoritative evidence.

Agent	Raw Tokens/Task	SpecHarness Tokens/Task	Token Ratio	Time Ratio	Calls/Task Difference
GPT-5.6 Sol	68,161	104,286	1.53×	1.24×	+0.36
Claude Fable 5	65,000	97,500	1.50×	1.25×	+0.34
Gemini 3.1 Pro	72,000	113,040	1.57×	1.22×	+0.40
Kimi K3	69,000	106,950	1.55×	1.26×	+0.38
GLM-5.2	64,000	97,280	1.52×	1.23×	+0.35
Qwen3.7-Max	70,000	107,800	1.54×	1.25×	+0.37
DeepSeek-V4-Pro	68,000	102,000	1.50×	1.23×	+0.32
Macro average	–	–	1.53×	1.24×	+0.36

Table 22: Condition-execution cost over the 87 SkillsBench tasks. Ratios and call differences are computed separately for each task-agent model and then macro-averaged without model weighting.

Diagnostic Measure	Raw	SpecHarness
Actionable source-linked reports (%)	42.5	96.2
Normalized feedback time	1.00	0.44

Table 23: Diagnostic information exposed by the complete conditions. The comparison does not assume matched trace access.

These representative obligation-level replays demonstrate the shared authority discipline without treating a committed PASSED result as automatic satisfaction or treating satisfaction of the selected obligation as sufficient for task completion. In a complete run, an obligation is satisfied only when its commitment predicate holds and its evidence is fresh. The finalization gate ranges over the full active mandatory set and permits completion only when every member is satisfied.

Benchmark	Visible Specification	Governed State	Qualified Evidence	Runtime Mode
SkillsBench	Task, workspace, and skill	Artifact, execution, and completion state	Controlled execution and workspace validators	Mediate-and-commit or validate-and-commit
GuideBench	Guideline and decision context	Rule-local decision and completion state	Rule-application and decision validators	Validate-and-commit

Table 24: Instantiation of the SpecHarness authority model in SkillsBench and GuideBench.

Step	Runtime Boundary	SkillsBench: <code>data-to-d3</code>	GuideBench: <code>chat[176]</code>	Authority Invariant
1	Source compilation	Compile the required output paths and local D3 dependency from <code>task.md</code> and the visible D3 skill.	Compile <code>rule_6</code> : an existing booking plus cancellation intent requires cancellation and an explicit success confirmation.	Every obligation retains an agent-visible source anchor.
2	Disposition and qualification	Mark o_S mandatory and bind it to q_S , whose inputs are observable workspace paths.	Mark o_G mandatory and bind its applicability and decision checks to the same rule-local obligation.	Only grounded requirements with qualified evidence providers enter hard enforcement.
3	Dependency binding	Bind o_S to <code>index.html</code> , the local JS and CSS files, and copied data at workspace version v_0 .	Bind o_G to <code>rule_6</code> , the dialogue context, and the candidate-option set at input version g_0 .	Evidence remains valid only for its recorded dependency versions.
4	Agent proposal	Propose controlled writes under <code>/root/output</code> .	Propose option A: the dialogue follows the cancellation guideline.	Agent intent cannot directly update authoritative state.
5	Obligation matching	Match the proposed writes to o_S and return $u_1 = \text{ALLOW}$ for the canonical output paths.	Activate o_G ; rules whose antecedents are false remain inactive.	Authorization and applicability are scoped to matched obligations.
6	Controlled execution	Execute the allowed writes through the closure-audited file surface; writes outside the authorized path set require a new decision.	No physical action is mediated; the proposed answer remains a validate-and-commit decision.	Agent intent cannot bypass the applicable runtime procedure.
7	Trusted observation	Observe the files bound to o_S at version v_1 , independently of tool-return strings or the agent’s self-report.	Observe cancellation intent, existing booking, cancellation action, success confirmation, and the proposed option in the fixed context.	Evidence describes observed state rather than claimed state.
8	Validation	q_S returns <code>PASSED</code> : the required files exist and the page uses the local D3 v6 dependency.	q_G returns <code>PASSED</code> after checking both applicability of <code>rule_6</code> and agreement of option A with that rule.	Only qualified, attributable, version-matched evidence is admissible.
9	Atomic commitment	Commit $\langle o_S, \text{PASSED}, v_1, q_S \rangle$.	Commit $\langle o_G, \text{PASSED}, g_0, q_G \rangle$.	A committed <code>PASSED</code> result establishes authoritative evidence; satisfaction also requires its predicate and freshness.
10	Freshness check	A controlled edit to <code>index.html</code> advances the dependency to v_2 ; the commitment at v_1 becomes <code>STALE</code> .	The guideline and dialogue remain at g_0 , so the committed evidence remains fresh.	A committed result cannot support satisfaction after a bound dependency changes.
11	Repair and revalidation	Repair the local script reference, revalidate at v_2 , and commit new <code>PASSED</code> evidence that supersedes the v_1 entry.	No repair is required; options B–D remain unsupported because they contradict the active rule and observed dialogue.	Repair changes current state; it does not revive stale evidence.
12	Finalization gate	o_S is satisfied only if its evidence is fresh and its satisfaction predicate holds; other active obligations are checked separately.	o_G is satisfied only if its evidence is fresh and its rule-local satisfaction predicate holds.	Satisfaction of one obligation is necessary but not sufficient for global finalization.

Table 25: Representative obligation-level protocol replays embedded in the end-to-end SkillsBench and GuideBench workflows. Each row illustrates an authority boundary for the selected obligation; other active obligations are omitted for space. A committed `PASSED` result contributes authoritative evidence, while satisfaction additionally requires the obligation predicate and current freshness. Finalization requires satisfaction of all active mandatory obligations. The examples use actual agent-visible benchmark materials, and the SkillsBench dependency mutation is controlled.