

Off-Target Effects of Response-Style Alignment in a Korean 27B Language Model

Hyojung Han

ThakiCloud

hyojung.han@thakicloud.com

Abstract

We post-train Qwen3.8-27B [37] for Korean *response style* — verbosity, list and markdown usage, discourse structure and register — and measure two behaviours the objective never targets: abstention on ambiguous social questions in KoBBQ [16], where the benchmark-correct response is UNKNOWN, and unprompted disclosure in securities guidance. Both move, and in this pipeline the observed changes are expressed primarily through the model’s emission policy: how often it answers and how much it says.

Matched target-form controls show that answer propensity depends on the training target rather than on the prompt set or the fine-tuning recipe alone. Holding prompts, recipe, data volume and serving fixed and changing only the target text, and measuring against a base re-evaluated on the same serving configuration, the answer-rate point estimates across three style seeds are positive, mean +0.82 pp, while all three neutral seeds trained on the raw teacher responses are negative, mean −1.53 pp; the observed seed ranges do not overlap and the means differ by 2.34 pp. A short length-matched arm lies between them, and a fourth arm designed to stay short while preserving hedging is highly unstable across its three seeds, so *which* feature of the target’s form is responsible is unresolved.

For absolute stereotyped exposure, the decomposition into an answer-propensity term and a conditional-composition term is an exact algebraic identity, not an empirical finding. Its empirical content is where the movement went. Across the trained checkpoints the observed changes are dominated by the answer-propensity term while the composition term stays small. Because that term is evaluated on treatment-dependent subsets, we do not read its smallness as evidence about latent stereotype preference.

The disclosure axis behaves the same way. Style post-training reduces detector-identified disclosure by about 22 percentage points under both instruments, and most of the detector-measured gap is reproduced by directly assigned response length: with length assigned the gap is 3–5 pp at 400 characters and above and indistinguishable from zero at 200 characters and below. The compliance-distillation stage gains 59.7 to 82.1 pp at every assigned length while producing *shorter* responses than base. We do not interpret these rates as calibrated compliance estimates, because agreement between the detectors is itself treatment-dependent.

Two measurement results follow. A between-arm contrast in conditional stereotyped share does not identify a change in conditional content preference when answer status is treatment-dependent. And agreement between our two disclosure detectors is strongly treatment-dependent — conditional agreement between them runs from 0.44 to 0.99 depending on which checkpoint produced the text — which is observable without any reference labels at all.

1 Introduction

On a held-out set of 637 Korean prompts, the base model’s responses are long and list-formatted: 97.3% contain bullets, 85.1% contain markdown headings, the median response runs 22 sentences over 9 paragraphs, and the median length is at least 1,329 characters (Table 1). We post-train to change those observable properties. The objective does not mention safety, capability or disclosure, and this paper is about what happened to two of those anyway.

Terminology. We use *response style* to denote observable properties of output form — verbosity, list and markdown usage, discourse structure, and register. We make no claim that these features constitute human-likeness, and we operationalise the construct through the deterministic output features of Table 1 rather than through a learned composite score.

The two untargeted behaviours are the ones a deployed Korean assistant needs. A model asked a socially loaded question without sufficient evidence should say so rather than name a person; KoBBQ [16], following BBQ [34], measures this by pairing an *ambiguous* context in which the question cannot be answered with a *disambiguated* one in which it can. Our securities-guidance instrument tracks disclosure language drawn from the Korean Standard Investment Solicitation Rules [20], including the warnings that principal may be lost and that deposit insurance does not apply, and asks whether the model emits it unprompted.

Both behaviours moved, and the claim of this paper is about how.

In this pipeline, response-style alignment changes the model’s emission policy — how often it answers and how much it says — and those shifts move deployment-relevant bias exposure and disclosure emission, with most of the observed change in absolute exposure carried by answer propensity rather than by the observed conditional-composition term.

On the bias axis the style-aligned checkpoints answer ambiguous items more often, and the increase in absolute stereotyped exposure is accounted for almost entirely by that change in answer propensity rather than by a change in how answers are distributed. On the disclosure axis the style-aligned checkpoint emits far less required language, and assigning response length directly reproduces most of that loss in the base model itself. The distinction this forces is between a capability claim and an emission claim. “Style alignment degraded compliance capability” is not what we measured. “Style alignment reduced unprompted disclosure emission, and length assignment reproduces most of that reduction” is.

Four questions organise the results. **RQ1** (§4): does response-style alignment move deployment-relevant behaviours it does not target, and is the direction attributable to the style targets rather than to fine-tuning on this corpus at all? **RQ2** (§5), the main section: are the changes carried by emission policy — answer propensity and verbosity — or by conditional content behaviour? **RQ3** (§6): do the standard instruments remain valid when alignment changes the surface distribution of outputs? **RQ4** (§7): do independently trained safety and compliance repairs compose, and how do their downstream effects depend on training order? Descriptive only.

2 Related Work

Off-target regression from alignment. That optimising one objective degrades untargeted behaviour is not new. InstructGPT [32] named the alignment tax and measured RLHF’s regression on public benchmarks; Lin et al. [24] propose weight averaging to avoid paying it sequentially. Qi et al. [36] show the converse direction, in which a later and ostensibly benign fine-tune erodes an earlier safety objective, and Fraser et al. [9] find fine-tuning lowers safety while also disrupting the consistency of the evaluation itself. Our style stage plays the role of the benign fine-tune, but what it moves is neither a capability benchmark nor a refusal behaviour: it is abstention on ambiguous social questions and the presence of required disclosure. The mechanism literature is continual learning — catastrophic forgetting [19] and its measured LLM form [29] — and Sun et al. [45] frame the safety alignment tax as gradient interference in a sequential SFT→DPO pipeline of the same shape as ours. Liu [26] report an alignment tax on the emission side, response homogenization, with consequences for uncertainty estimation.

Threshold versus composition, and where the decomposition comes from. Kotha et al. [21] argue that fine-tuning-induced forgetting is drift in implicit task inference rather than lost knowledge. That distinction is the axis this paper measures, and the tool for measuring it is BBQ’s own. Parrish et al. [34] define the disambiguated bias score $s_{\text{DIS}} = 2(n_{\text{biased}}/n_{\text{non-UNKNOWN}}) - 1$ and the ambiguous score $s_{\text{AMB}} = (1 - \text{accuracy}) \cdot s_{\text{DIS}}$. Because the correct answer in an ambiguous context is UNKNOWN, the factor $(1 - \text{accuracy})$ is the answer rate, so the ambiguous score is already a product of an answer-propensity term and a conditional term. We use that factorisation as a method and claim nothing new for it; §5 is explicit that the decomposition is an identity and that only the *allocation* between its two terms is empirical.

The surrounding tools come from selective prediction: the risk-coverage tradeoff [11], answerable/unanswerable paired designs [39] of the kind BBQ and KoBBQ borrow, evidence that models carry usable self-knowledge about their own correctness [17], and work that trains the answer/abstain decision itself as an alignment target [28]. Ling et al. [25] show abstention can be a prompt artefact rather than genuine uncertainty; Manduru and Domeniconi [30] show a good bias score can conceal vacuous neutrality, which is what an answer-propensity shift produces in a share metric; and Kirichenko et al. [18] find reasoning fine-tuning degrades abstention by about 24%, which is our observation that abstention is movable by alignment training arriving from another direction.

Verbosity as a confound. Zheng et al. [51] document length bias in LLM judging, Singhal et al. [43] show RLHF quality gains are substantially length-confounded, Saito et al. [42] show preference labelling itself is verbosity-biased, Chen et al. [4] disentangle length from reward, and Dubois et al. [7] debias an automatic evaluator by controlling length directly. Our style stage shortens responses by an order of magnitude, so any claim that it cost a content-bearing behaviour has to survive a length control. We run one by assignment rather than by covariate adjustment, for reasons §5.3 makes concrete.

Measurement validity. That evaluation format changes what a bias benchmark reports is established: Merzlyakova et al. [31] run three instruction-tuned models on BBQ and OpinionQA across closed, Likert and open-ended formats

and find format substantially alters measured outcomes including ranking reversals, with refusal in free-text generation as the mechanism. That result varies format *type* across models; §6.3 varies option *position* within one fixed format across our own training arms, and neither touches the other’s detector-agreement or answered-set-selection results. Bean et al. [1] survey construct validity in LLM benchmarks and supply the vocabulary for §6; Contreras [6] demonstrate a self-report–behaviour gap across 25 models with an explicitly psychometric instrument. Skalse et al. [44] characterise reward hacking formally, Gao et al. [10] measure the over-optimisation curve, and Panickssery et al. [33] show an LLM grading its own generations favours them — which is why the rule engine that produced our training targets is never allowed to score them, and why the style measurement of Table 1 is deterministic rather than learned.

Composition and order. In weight space, task arithmetic [15] adds behaviours directly, TIES-merging [49] shows the additions interfere, and rewarded soups [40] interpolate independently tuned weights rather than chaining stages. In sequential fine-tuning, Gu et al. [12] show accumulated edits damage general ability order-dependently; Liu et al. [27] test controlled stage orderings across SFT, preference optimisation and safety tuning; Bhandari et al. [2] find sequential DPO forgetting non-uniform and order-dependent; Ung et al. [48] show chained tuning produces biased forgetting; Cha and Cho [3] give a minimal working explanation for why alignment must precede distillation; Chen et al. [5] ask directly whether fine-tuning order matters; Sweeney [46] predict transfer order without training both orderings; and Fernando et al. [8] prove sequential SFT→preference learning sub-optimal in a convex setting. **We make no novelty claim on this axis.** We trained both orderings of the same two deployment objectives and evaluated each on both downstream behaviours; §7 is descriptive.

Korean evaluation and the stack. KoBBQ [16] rebuilds BBQ for twelve categories of Korean society; KoSBi [23] supplies Korean social-group material used only as seeds for scenarios that do not overlap it. Alignment uses DPO [38] through LoRA [13]; disclosure uses context distillation in the sense of Llama 2 [47]. The base checkpoint is Qwen3.8-27B [37] and serving is vLLM [22].

3 Setup

3.1 The paired corpus and the stages

The artefact that is hard to rebuild is not the checkpoint but the corpus. Each record is a quadruple (prompt, raw teacher response, style-rewritten target, style metadata): the SFT set takes the style-rewritten target, DPO pairs take it as chosen and the raw response as rejected, and the control arms of §4 are built by swapping which field becomes the target.

Generation is fully synthetic with no external scraping. A style-anchored few-shot prompt writer produced 4,800 prompts, deduplicated to 4,782, with 226 non-Korean prompts discarded; a bf16 Qwen3.8-27B teacher answered them (*raw*); an MIT-licensed rule engine rewrote each answer along a light→standard→heavy ladder, giving the *style-rewritten target*. The internal artifact names that field *humanized*; we call it the style-rewritten target, or the style rewrite, throughout, because we make no human-likeness claim. Four admitting gates — script contamination suppressed at the decoder with 95,042 `logit_bias` entries (17.1% → 0.0%), truncation detection, Korean-purity discard, and minimal-pair validation on length bucket, bullets and register — reduced a pool that reached 5,145 items to 3,369 admitted pairs. Two decisions there generalise. Purity violations are discarded rather than repaired, because a sentence whose removed span is unknown should not become a training target. And a constraint expressed in the prompt is not a constraint: an instruction arm reading “do not write in Chinese” moved the contamination rate by 0.0, while the same requirement imposed on the decoder moved it to zero.

The first SFT trained on 2,992 records and barely moved the model, because its targets were nearly indistinguishable from the base model’s own output. Rebuilding the corpus with the style axes enforced at generation time and holding every hyper-parameter fixed, the second SFT trained on 519 records and produced the profile in Table 1.

All adapters are LoRA rank 8, $\alpha=16$, dropout 0, attached to every linear layer including the `in_proj` projections of the hybrid-attention blocks, and merged into the weights between stages. **Style SFT** trains on the 519 style-rewritten records, $lr \times 10^{-5}$, one epoch, three seeds; the seed axis moves data order and LoRA A initialisation together. **Safety DPO** trains 2,757 preference pairs, $\beta=0.15$, effective batch 8, 345 steps; scenarios are seeded from KoSBi categories mapped onto KoBBQ categories and written fresh by the teacher, which never sees a KoBBQ item, and every training pair is checked against all 16,240 KoBBQ items by 12-character substring match before training proceeds. **Compliance distillation** attaches a disclosure instruction to the teacher, filters generated responses through a rule gate at a 0.478 pass rate leaving 1,205 records, holds out 129, and trains on the remaining 1,076 *with the instruction removed* (1,076 steps, final training loss 0.7278, held-out evaluation loss 0.5282, 26 minutes on one H200). This is

Table 1: Response-style profile over 637 held-out prompts, $T=0.7$, no system prompt, one serving stack. Eleven deterministic features, each reported alone with its own paired bootstrap interval; we do not combine them into a style score. Ten features are defined over all 637 paired responses; formal-register share is reported conditionally on scoreable endings, with coverage shown separately. All reported base–style contrasts exclude zero under their corresponding bootstrap estimand. Rates are percentages of responses; sentence, paragraph and length figures are medians.

Feature	base	style	safety	compliance
Bullet rate	97.3%	0.6%	0.0%	0.5%
Heading rate	85.1%	0.0%	0.0%	0.0%
Length (characters)	$\geq 1,329^\dagger$	152	165	204
Length (tokens)	$\geq 700^\dagger$	77	85	99
Sentence count	22	2	3	3
Paragraph count	9	1	1	1
List items (mean)	12.29	0.07	0.00	0.04
Closing-summary rate	2.35%	0.47%	0.63%	0.94%
Formal register share [‡]	93.9%	50.9%	52.4%	89.5%
Repeated-sentence rate	1.26%	0.00%	0.00%	0.00%
Non-Korean contamination	9.11%	4.87%	20.72%	6.28%

[†] Right-censored: 74.6% of base responses hit the 700-token generation cap, so base’s length entries are floors and every length gap against base is a lower bound. An uncensored re-run of the base arm ($n=150$, cap 4096, 0 responses at the ceiling) gives a true median of 737 tokens and 1,478.5 characters.

[‡] Conditional on the response ending in a scoreable register marker; coverage differs by arm (627, 448, 510 and 611 of 637 responses respectively), so this row compares like with like only within each arm’s scored subset, and the unscored fraction is itself part of the style difference.

the FIN1 arm. **Both orderings** of the last two stages were trained, one run each: M4 is style→safety→compliance, M5 is style→compliance→safety.

Control arms. The neutral arm replaces the style-rewritten target with the raw teacher response; prompts verified identical, 519 of 519 matched, zero mismatches. The length-matched arm replaces it with that same raw response truncated at a sentence boundary to the paired style target’s character length — truncation only, never a rewrite, so every target is an exact contiguous prefix of its neutral counterpart. Three seeds per control arm.

3.2 What response-style alignment did to response style

We operationalise response style through eleven deterministic output features rather than a learned composite score. They were written for this task rather than derived from the rule engine that produced the training targets, so the suite does not score the model on its own optimiser’s metric; the one deliberate reuse is the non-Korean-script regex, taken verbatim from the project’s existing purity check. The suite was required to discriminate a known-different pair before being used for comparison, and it does: every feature separates base from the style arm with a paired bootstrap interval excluding zero under its own estimand.

3.3 Measurement

KoBBQ all-test is stratified to at most 2,000 items per category, giving 16,240 KoBBQ items of which 8,139 are ambiguous and 8,101 disambiguated; answer options are rotated by a deterministic function of the item identifier. Decoding is $T=0$, thinking off, `max_tokens=16`.

The template identifier used as the clustering unit throughout is the item identifier’s leading `category-NNN` field, so that all lettered variants of a template form one cluster. One provenance discrepancy is unresolved and we state it rather than smooth it. The published KoBBQ release [16] reports 268 templates over 76,048 samples; the copy of `all-test` we evaluate carries 269 template identifiers over 76,568 rows, of which 264 identifiers appear in the stratified ambiguous subset. We have not identified which build ours came from. The discrepancy does not affect the clustering: all 269 identifiers are well formed, per-category numbering is contiguous from 001 with no gaps, the variant structure is regular — 253 templates carry two lettered variants and 16, all in the race, ethnicity and nationality category, carry four — and no single template accounts for the 520 extra rows. The ambiguous evaluation subset covers 264 templates in 531 variants; the variant count is not twice the template count because the per-category cap admits only part of some templates’ variant sets, which is why an odd number is possible at all. We treat the key as sound and the sample count as not reconciled.

Disclosure is measured on 48 immutable prompts (16 solicitation, 16 product explanation, 8 plain information, 8 unsuitable solicitation) at $T=0.2$, three runs per arm, and on a 192-prompt expansion for the dose-response design of §5.3. The disclosure requirements are those of the Korean Standard Investment Solicitation Rules [20], the self-regulatory model rule of the Korea Financial Investment Association, provided for firms to adapt when establishing and operating their own investment-solicitation rules; our rule wording is operationalised from its current revision. We therefore treat the labels as benchmark disclosure requirements rather than as statutory obligations or as estimates of legal compliance. Four of the five rules cite that current text directly. The fifth, that past returns do not guarantee future returns, rests on an annex form for robo-advisory services together with a general prohibition on misleading statements rather than on a positive disclosure duty in the general text; we keep it in the instrument and record here that its basis is the narrower one.

Serving is vLLM 0.28.0, one GPU per arm — B200 for the control wave of §4, H200 for the pipeline arms of §7, with matching engine arguments: `max_num_seqs=256`, fp8 KV cache, prefix caching, `torch.compile` enabled, speculative decoding with a DFlash drafter ($K=7$), `max_model_len 32768`. Serving arguments were read back from the live pod for every arm and diffed against the reference arm; the diff is empty apart from the two lines naming the model. Before any datum was recorded, `/v1/models` was queried and the returned served-model name asserted against the expected one; a port-forward to another workstream’s endpoint returns HTTP 200 throughout and otherwise yields wrong-model data silently.

All statistical tests are computed by one shared module, which decides from the stored item-identifier sets rather than from the design as described which test is admissible: identical sets admit paired tests, disjoint sets admit independent tests, and partially overlapping sets admit neither and fall through to an overlap-aware bootstrap or a partition permutation. KoBBQ instantiates its items from a smaller set of templates, so items sharing a template share their wording and are not independent: all uncertainty estimates over KoBBQ items use the KoBBQ template as the resampling or clustering unit, except where a statistic is explicitly described as an item-level diagnostic.

4 RQ1: the untargeted behaviours move, and the target’s form is why

4.1 Two arms are not enough

That the style-aligned checkpoint differs from base on both untargeted axes is easy to measure and hard to attribute. Any supervised fine-tune on this corpus might produce the same drift. So we built control arms that hold the prompts, the recipe, the data volume, the holdout split and the serving configuration fixed and change only the target text.

Together with the base model this is ten arms on one item set of 8,139 ambiguous items, with zero unparseable completions and zero endpoint errors in every arm. All pairings are therefore classified as paired with overlap fraction 1.000, so item-level McNemar diagnostics are computable throughout, and because no arm drops an item all five exclusion conventions we considered give numerically identical results.

4.2 The sign reverses

Against the matched base the style arms raise the answer rate by +1.339, +0.455 and +0.651 pp and the neutral arms lower it by 1.388, 1.597 and 1.597 pp. The two observed seed ranges do not overlap — the style minimum (+0.455) exceeds the neutral maximum (−1.388) — and the mean gap of 2.343 pp is $6.9\times$ the pooled within-arm standard deviation of 0.339 pp and larger than either arm’s own seed range (0.885 and 0.209 pp). At the item level, McNemar tests give the same direction in all of these comparisons — $|z|$ from 2.52 to 9.64 against the matched base and 9.76 to 14.63 across the nine style-versus-neutral pairings — but they treat the items as independent and ignore KoBBQ’s template dependence, so we report them as checkpoint-conditional diagnostics and take the template bootstrap below as the inference. The mean gap is a difference between two arms and does not depend on which base they are measured against; the individual Δ values do, which is why the base was re-evaluated on the arm serving configuration before this section was written.

Those item-axis tests treat the 8,139 items as independent, and they are not: KoBBQ instantiates many items from a smaller set of templates, and the items sharing a template share their wording. We therefore recomputed the contrasts with a cluster bootstrap that resamples *templates* — the identifier prefix, so that all lettered variants of one template form one cluster — over the 264 templates the ambiguous split covers, 20,000 draws. The between-arm claim survives intact: all nine style-versus-neutral cross-pairings exclude zero on both answer rate and absolute stereotyped exposure, and the mean gap is +2.343 pp, CI [+1.177, +3.600], on answer rate and +2.072 pp, CI [+1.020, +3.216], on absolute exposure. The per-arm contrasts against base are weaker than the item-axis tests made them look.

Table 2: Ten arms on 8,139 ambiguous KoBBQ items and one serving configuration, read back from the live pods. The base arm was re-evaluated on the arm serving configuration for this table; it parses every item, so all ten arms score the same 8,139. Δ columns are against that matched base. The last two columns split Δ absolute stereotyped into the two terms of the exact identity of §5: the answer-propensity contribution $L_0\Delta A$ and the observed composition residual $A_1\Delta L$. Every arm here scores all 8,139 items with zero exclusions, so each contrast against base is on the full set; elsewhere a contrast is computed on the item set the two arms share, so n differs by pair. Median length is over the 637 held-out prompts of Table 1 and is right-censored on every row except the three style seeds, where under 1.3% of responses reach the generation cap against 55–75% elsewhere.

Arm	Answer rate	Δ answer rate	Δ abs. stereo.	Answer-propensity contribution	Observed comp. residual	Median len.
base	18.59%	—	—	—	—	1,329
style s1	19.93%	+1.339	+1.241	+1.154	+0.087	152
style s2	19.04%	+0.455	+0.565	+0.392	+0.173	74
style s3	19.24%	+0.651	+0.663	+0.561	+0.102	118
length-matched s1	18.01%	−0.577	−0.430	−0.498	+0.068	1,305
length-matched s2	18.58%	−0.012	+0.061	−0.011	+0.072	1,300
length-matched s3	17.72%	−0.872	−0.749	−0.752	+0.002	1,314
neutral s1	17.20%	−1.388	−1.167	−1.197	+0.029	1,292
neutral s2	16.99%	−1.597	−1.302	−1.377	+0.074	1,298
neutral s3	16.99%	−1.597	−1.278	−1.377	+0.099	1,293

Style seed 1 excludes zero (+1.339 pp, CI [+0.269, +2.577]), but **style seeds 2 and 3 cover zero** — +0.455 pp, CI [−0.513, +1.437] and +0.651 pp, CI [−0.424, +1.858] — as does the length-matched second seed, while all three neutral arms exclude zero. Resampling the 531 lettered variants instead narrows the intervals without changing any of these verdicts. So a single style seed’s shift against base is not established on the item axis at this clustering, and we do not claim it is. What is established is the between-arm separation, and the generalisation this section rests on is across the three training runs per arm rather than across items. We report the item-level McNemar statistics as diagnostics conditional on each checkpoint.

The three-against-three exact permutation test returns $p=0.100$, which needs reading rather than dismissing. With $\binom{6}{3} = 20$ assignments the two-sided floor is 0.100, so a p at the floor means the groups separated completely and a p above it means they did not. The strength here comes from three things a p -value cannot carry: the sign reverses, the observed seed ranges do not overlap, and the template-clustered intervals exclude zero in all nine style-versus-neutral cross-pairings. With $n=3$ per arm we report the observed seed range for every arm and a standard deviation only where it is used in a comparison, and lean on neither as an estimate of training-run variability.

So the direction is not a property of fine-tuning on this corpus. It is a property of the form of the training target: the neutral, length-matched and style arms are ordered monotonically by their mean effects.

4.3 Which property of the form, we do not know

The style and neutral arms differ on two axes at once: the style targets are short (median 143 characters) and the raw ones are long (median 1,076). The length-matched arm was built to separate them under a rule pre-specified before any evaluation number existed — inside the style range means length is the lever, inside the neutral range means the style rewrite is, strictly between means the design does not resolve it at $n=3$.

It landed strictly between: −0.577, −0.012 and −0.872 pp, mean −0.487 pp. We honour the rule as written. Neither “style alignment causes the shift” nor “target length causes it” survives as a clean single-lever claim. What the arm does establish is that it separates from both — 1.040 pp from neutral and 1.302 pp from style, non-overlapping in each direction — so it rules out either original target form as a complete explanation. It does not go further: because truncating to a length target also strips clarifying questions, hedges and enumerations, as the next paragraph measures, the arm does not identify separable contributions of target length and the broader style rewrite.

Two secondary checks pre-specified in advance both fired, in opposite directions. The first does not support a simple transfer-through-generation-length mechanism: if short training targets taught the model to write short answers, and short answers left less room to hedge, this arm’s generations should be short. They are not — median 1,305, 1,300 and 1,314 characters, within 12 characters of the neutral arm — so training-target length did not transfer to generation length at all. The second undermines the arm’s own label: truncating a raw response at a sentence boundary produces

Table 3: All four target-form arms, three training seeds each, change in ambiguous answer rate against the matched base on the same 8,139 items. The seed range is what separates the fourth arm from the other three; Appendix A gives the pre-specified decision rule and why it cannot discriminate at this dispersion. That rule’s landmarks were fixed before the base was re-evaluated, so the classification is reported as specified while the deltas here are on the matched base; the shift is a constant and does not change which landmark each seed falls nearest.

Arm (target form)	seed 1	seed 2	seed 3	mean	range
neutral (long, hedging)	−1.388	−1.597	−1.597	−1.528	0.21
length-matched (short, low hedging)	−0.577	−0.012	−0.872	−0.487	0.86
style (short, low hedging, rewritten)	+1.339	+0.455	+0.651	+0.815	0.88
hedge-preserving (short, hedging)	−0.639	+1.708	−2.519	−0.483	4.23

the response’s *opening*, which is the part that commits, and deletes the part that asks and qualifies. Over the 519 targets, clarifying questions fall from 33.7% to 8.7%, requests for more information from 25.4% to 7.1%, hedges from 51.5% to 23.5% and markdown enumerations from 58.0% to 15.2%, most landing near the style arm’s own rates. The arm is length-matched to the style target (per-record Pearson $r=0.9964$, median absolute residual 16 characters) and not discourse-matched. That the manipulation reached discourse-level features is also why we call the intervention response-style rather than surface-style: it is not a surface-only change.

The fourth cell

That leaves the cell the three arms do not cover: a target that is short *and* preserves hedges and clarifying questions. We built it, gated it, and trained it at three seeds on the same recipe and the same 8,139 items. The construction gate passed on all six checks against thresholds committed before the data existed; a first attempt failed one of them and we changed the construction rather than the threshold. The built targets carry hedges in 59.9% of records, a question in 32.2% and a request for more information in 47.8%, at a median of 153 characters. Unlike the length-matched arm, the short target transferred: median generated response 195 characters, against 115 for style, 1,294 for neutral and 1,306 for length-matched. The cell is genuinely short-and-hedging.

It does not identify the responsible feature. The three seeds are −0.639, +1.708 and −2.519 pp (Table 3), a range of 4.23 pp against 0.21–0.88 for the other three arms. That dispersion is too large for any location statistic computed on it to discriminate the hypotheses: the three seeds fall nearest three different landmarks, and every pairwise contrast involving the arm overlaps. Appendix A gives the pre-specified rule, why it was mis-specified for an arm this dispersed, and the accompanying detail.

The control also moved more than the feature it was built to isolate. A 150-character answer that keeps the teacher’s clarifying question usually has to end on it, and this arm ends on a question in 15.2% of targets against 3.1% for style and 4.6% for neutral, so hedging and turn-final structure vary together exactly as truncation varied length and discourse form together. Separately, the generator for this arm saw a system prompt carrying up to three sentences of raw teacher text and the style arm’s did not, which is a different conditioning distribution rather than a different instruction. Both differences are uncontrolled here.

We therefore do not write that response-style alignment in general raises answer propensity. The deployed checkpoint is the one trained on short style-rewritten targets, and for pipeline accounting the attribution to that stage is correct; the generalisation is not yet available.

One thing this design cannot do is measure length as a dose. Across the six style and neutral checkpoints the change in median generation length and the change in answer rate correlate at $r = -0.965$, but 1,140 of the x -axis’s 1,224-character span (93.1%) is a single gap between the two clusters, so that coefficient is the between-arm mean difference rewritten, not a dose-response. Within the style arm the sign is the opposite of the prediction. Assigning the dose is what §5.3 does on the other axis.

4.4 The second axis moved too

On the four arms that share one serving stack, over 456 (response, required-rule) pairs per arm, the strict detector marks disclosure in 27.6% of pairs for base, 6.1% for the style-only arm, 94.1% for the prompted arm and 94.5% for the compliance-distilled arm; a second, independently specified looser detector marks 36.4%, 14.0%, 98.5% and 95.2%. Both instruments register a large drop at the style stage and a large recovery at the distillation stage. These are detector-identified disclosure rates, not estimates of regulatory compliance: they measure how often the required

language is emitted in a form the instrument recognises, and §6.2 shows the instruments do not recognise it equally across arms.

5 RQ2: absolute exposure changes are dominated by answer propensity

5.1 The decomposition is an identity; the allocation is the result

Write A for the probability that the model answers an ambiguous item, L for the probability that an answer is the stereotyped option, and $S = A \cdot L$ for absolute stereotyped exposure. Then for any two arms, exactly and without approximation,

$$\Delta S = L_0 \Delta A + A_1 \Delta L.$$

This is algebra. Nothing about a model can make it fail, and the last two columns of Table 2 are its two terms rather than a prediction and an error — we verified that the observed-composition column equals $A_1 \Delta L$ to within floating-point tolerance on every arm. The smallness of that column is therefore not an empirical law fitted to within a band, and we do not report it as one.

The empirical content is where the movement went, and we state it in percentage points before any ratio. Restricting at the outset to the seventeen contrasts produced by training — the twelve control checkpoints of Tables 2 and 3 and all five pipeline stages of Table 7, sixteen distinct checkpoints in all, since the style checkpoint appears in two tables as its two runs — the answer-propensity term $L_0 \Delta A$ ranges from -13.42 to $+1.47$ pp, while the composition term $A_1 \Delta L$ stays between $+0.00$ and $+0.45$ pp — every one of the seventeen is positive and under half a point. The three seeds of the unstable fourth arm are inside that pattern rather than an exception to it: their answer-propensity terms are -0.55 , $+1.47$ and -2.17 pp, spanning more than any other control arm and supplying the upper end of the span above, while their composition terms are $+0.15$, $+0.09$ and $+0.27$ pp. What that arm destabilises is the magnitude and sign of the answer-propensity shift, not the observed allocation between the two terms. Adding the two precision arms below, which were measured for another purpose and are a generalisation check rather than an experiment we ran for this question, extends the propensity span to $+2.88$ pp; their composition terms are -0.03 and $+0.06$ pp, the same order of magnitude, and the NVFP4 arm’s is the one negative value we observe. The largest composition terms are $+0.445$ pp for the safety stage and $+0.445$ pp for M4 — both stages that raise abstention sharply — against answer-propensity terms of -9.56 and -8.85 pp on the same contrasts. The two remaining pipeline stages sit inside the same pattern: FIN1 has a composition term of $+0.220$ pp against a propensity term of -5.53 pp, and M5 $+0.123$ against -13.42 pp. Nothing forced that: a treatment could have moved L enough to reverse the sign of ΔS relative to ΔA , or to double it, and in this pipeline none did.

As a secondary summary, the share of ΔS carried by answer propensity runs from 93 to 116 percent. That ratio is a quantity only where ΔS is itself resolvable, and under the template clustering of §3 that is thirteen of the seventeen training contrasts: the two smaller style seeds, the second length-matched seed and the first seed of the fourth arm all have template-clustered intervals covering zero, and on those the denominator has collapsed rather than the composition term having grown. The W4A16 arm is in the same position. We quote the ratio only where ΔS resolves; the percentage-point statement above does not depend on that restriction, because a term is a term whether or not the difference it decomposes is distinguishable from zero.

Contrasts are computed on the item set the two arms share, pairwise, rather than on an intersection across every arm in a table — otherwise a two-arm comparison would depend on which other arms happen to be present. The five pipeline contrasts quoted here are on $n=8,139$ (base to style), $7,991$ (base to safety), $8,139$ (base to FIN1), $8,122$ (base to M4) and $8,139$ (base to M5); the matched base drops no item, so only the safety and M4 arms narrow their pairings.

Because the conditional term is evaluated on treatment-dependent answered subsets, we do not interpret the residual as evidence that latent stereotype preference is invariant. ΔL compares the stereotyped share of two different sets of answered items, and which items those are is itself an outcome of the treatment. §6.1 makes that argument properly. The claim here is narrower and is about where a deployment-visible quantity comes from: what a user encounters is S , and in this pipeline S moved because A moved.

Two further observations bear on how far that travels.

It runs in both directions. The neutral arms answer *less*, and their absolute stereotyped exposure falls, again dominated by the answer-propensity term. An allocation that held only for increases would be a weaker observation than one that also covers decreases produced by a different training target.

It is not confined to training interventions. Serving one checkpoint at three weight precisions with matching values for the four serving knobs the ledger records — KV-cache dtype, maximum sequence count, speculative decoding and memory utilisation, with no argument readback stored for these arms and different kernel paths for the two quantizers — on the 7,867 ambiguous items all three arms parsed so that every contrast is fully paired, the NVFP4 arm raises the answer rate by 3.11 pp against bf16 (template-clustered CI [+1.70, +4.83]) and absolute stereotyped exposure by 2.86 pp (CI [+1.50, +4.50]), with an answer-propensity term of +2.88 pp and a composition term of −0.03 pp. A W4A16 arm moves neither quantity (−0.29 pp, CI [−1.03, +0.46]; −0.23 pp, CI [−0.97, +0.52]), with a composition term of +0.06 pp. That compression moves bias measurements is itself reported: Rath and Maliakkal [41] find 3-bit quantization drives 6–21% of previously unbiased BBQ items into stereotypical behaviour while perplexity moves under 0.5% at 8-bit, and Hua et al. [14] find quantization flips bias on up to 21% of items with aggregate bias scores unchanged, correlated with model uncertainty. Both report item-level bias changes under quantization associated with uncertainty or with changes in unknown-option selection, which is prior evidence of a similar measurement channel; we have not shown that the mechanism is the same one. These arms are a single run each with unmeasured requantization build spread, so we use them only as a generalisation check and never as an effect size; they are also why a contrast crossing weight precision cannot be read as an alignment contrast.

5.2 The magnitude is a range

Three style seeds give absolute stereotyped increases of +1.241, +0.565 and +0.663 pp against the matched base (Table 2); only the first has a template-clustered interval excluding zero, so these are point estimates and the two smaller ones are not individually established. The spread of 0.676 pp between seeds is larger than the smallest seed’s whole effect. For scale, re-evaluating one checkpoint in the same session on the same node and serving spec moved its absolute stereotyped exposure by 0.013 pp, template-clustered CI [−0.151, +0.136], not distinguished; the same checkpoint measured once on an H200 and once on a B200 differed by 0.098 pp, likewise not distinguished. The first is a within-session reproducibility statement, the second a cross-hardware observation, and neither is an estimate of variance across training runs.

So a single training run’s value cannot be written as the effect. The defensible statement is that across the three style seeds the point estimates for absolute stereotyped exposure increase by 0.57–1.24 pp relative to the matched base, with the point-estimate direction the same at every seed and the magnitude varying 2.2×. Three points have a standard deviation; what they do not have is a stable estimate of variability across training runs, and it is that estimate the range is standing in for. The alignment step itself is resolvable: base to style is +1.143 pp on an identical item set of 8,139, template-clustered CI [+0.16, +2.27], with an answer-propensity term of +1.133 pp and a composition term of +0.010 pp.

5.3 On the compliance axis, the emission variable is length

The style-aligned checkpoint’s free-running disclosure gap against base is −22.25 pp under the loose detector (CI [−26.56, −17.94]) and −21.83 pp under the strict gate (CI [−26.44, −17.25]), pooled over 456 rule-pairs per arm with prompt-level clustering and overwhelmingly significant under bootstrap, GEE and GLMM. The same stage shortens responses by an order of magnitude (Table 1). The obvious hypothesis is that the second explains the first.

An observational version of that test — regressing disclosure on arm with log length as a covariate — appeared to support it and did so too strongly, flipping the arm coefficient’s sign. We do not use that result. Length is a post-treatment variable and conditioning on it over-adjusted. The correct design assigns the dose.

We did that with a neutral length instruction in the system prompt at four targets (100, 200, 400 and 800 characters) across three arms, over an expanded 192-prompt set giving 608 rule-pairs per cell and 7,296 record pairs in total, at $T=0.2$ with a generous token budget — `max_tokens` was never the length lever, because truncation would amputate a sentence-final disclosure and manufacture the effect under test, and the `finish_reason=="length"` count is zero in every cell. Arms ran sequentially on one B200 with byte-identical serving arguments apart from the model name. We report intention-to-treat by assigned target rather than by realised length, for the same reason we abandoned the covariate adjustment.

Most of the style stage’s detector-measured disclosure gap is reproduced by assigned length. Free-running it is about 22 points; with length assigned it is 3 to 5 points at the two longer targets, where the prompt-clustered intervals exclude zero under both detectors, and indistinguishable from zero at the two shorter ones, where every interval covers zero. But the curves do not coincide: 3 to 5 points survive at 400 characters and above under both detectors. The correct statement is that most of the detector-measured disclosure gap is reproduced by assigned verbosity, which establishes that response length is *sufficient* to reproduce most of the gap and does not identify it as the causal

Table 4: Detector-identified disclosure by assigned length target, intention-to-treat, in percentage points against base, with 95% bootstrap intervals resampled over the 160 prompts that contribute at least one applicable disclosure rule pair — the full set is 192, of which the 32 plain-information prompts carry no required rule — with 20,000 draws clustered on prompt rather than on rule-pair. Each cell is 608 rule-pairs. Bold marks intervals excluding zero.

Assigned target	Style-only arm vs base		Distilled arm vs base	
	Loose	Strict	Loose	Strict
100 characters	−1.97 [−4.12, +0.16]	−0.99 [−2.66, +0.66]	+59.7 [+54.7, +64.5]	+61.5 [+55.9, +66.9]
200 characters	+0.66 [−1.62, +2.88]	−0.33 [−2.30, +1.62]	+70.7 [+66.2, +75.0]	+76.5 [+72.1, +80.9]
400 characters	−5.10 [−7.80, −2.45]	−3.29 [−5.28, −1.31]	+71.2 [+67.5, +74.9]	+82.1 [+78.5, +85.5]
800 characters	−5.26 [−8.37, −2.20]	−4.44 [−7.00, −1.97]	+71.7 [+68.4, +75.0]	+81.9 [+78.8, +84.9]

mediator through which style post-training produced the original change. That is why the table is indexed by assigned target and not by realised length.

The compliance-distillation stage does not work by lengthening the response. Its advantage over base is +59.7 to +82.1 pp at every assigned target under both detectors, and at the 800-character target its median response is 620 characters against base’s 1,062 — it clears the bar by a wide margin while writing barely more than half as much. The observational analysis agrees on this arm, where the length-adjusted coefficient rises rather than falls; it is a log-odds coefficient and is not on the same scale as the assigned-dose percentages, so the two results support the same direction independently rather than calibrating each other.

5.4 Disambiguated-item accuracy as a task-local control

An emission account would read differently if the same task’s evidence-given condition had collapsed alongside it. It did not. On KoBBQ’s disambiguated items — where the context does support an answer — accuracy ranges from 86.24% to 89.82% across the evaluated checkpoints against 88.20% for base (Table 7). We report this descriptively: some stages sit above base and others below. It is a task-local control on the same benchmark and speaks to nothing outside it.

6 RQ3: evaluation changes with the output distribution

Alignment work of this kind is measured with instruments built before the treatment existed. When the treatment’s content is a change in the surface distribution of outputs, whether those instruments survive it is an empirical question — and one already answered in part for bias benchmarks, where Merzlyakova et al. [31] show that varying the answer format across closed, Likert and open-ended conditions moves measured gender bias enough to reverse rankings, with refusal as the channel. Two of ours did not survive, and both failures are results rather than housekeeping. Defects that changed a number but not a conclusion are in Appendix B.

6.1 Conditional-share contrasts are selection-confounded

The most widely used quantity on a paired bias benchmark is the share of *answered* items that are stereotyped, and the conditional bias score is a monotone transform of it. That share is perfectly measurable, and we measure it. What it does not do is identify what it is usually read as identifying: **a between-arm contrast in conditional stereotyped share does not identify a change in conditional content preference when answer status is treatment-dependent.**

The argument is short. The share is defined over each arm’s answered subset. When the treatment changes which items get answered, the answered subset is itself an outcome of the treatment, so comparing shares across arms conditions on a post-treatment variable. It is a selection effect, not a parsing problem, and careful reporting does not repair it.

It is measurable how large the selection is. Between base and the style arm — two arms with *zero* unparseable completions on either side — the answered sets overlap at a Jaccard index of 0.860. Between the safety arm and the

Table 5: Item-level transitions from the style checkpoint to the safety checkpoint, over the 8,139 ambiguous items both score. Rows are the style arm’s outcome, columns the safety arm’s. The safety stage removes 827 of the style arm’s 1,397 stereotyped answers and adds 11; the 517 that survive are 96.6% of the safety arm’s 535 stereotyped answers.

style ↓ / safety →	abstain	stereotyped	counter	unparsable	total
abstain	6,421	11	0	87	6,519
stereotyped	827	517	10	43	1,397
counter	168	7	30	18	223
total	7,416	535	40	148	8,139

Table 6: Agreement between the two disclosure detectors, by arm, over the 456 (response, required-rule) pairs each arm contributes on the shared serving stack. Counts only; no reference labels enter this table. Conditional agreement is $P(\text{strict} = 1 \mid \text{loose} = 1)$, i.e. “both” divided by “loose +”.

Arm	Strict +	Loose +	Both	Strict only	Loose only	Neither	Cond. agreement
base	126	166	112	14	54	276	0.675
style-only	28	64	28	0	36	392	0.438
prompted	429	449	427	2	22	5	0.951
distilled	431	434	428	3	6	19	0.986

style arm it is 0.346, the value Table 5 implies; between the style arm and the compliance arm, 0.603. The two arms in each pair are not scoring the same questions, and the difference between the question sets *is* part of the treatment effect.

The consequence is that the null distribution is not centred at zero. In this regime, permuting arm labels alone produces a non-zero share gap purely from composition. When we tested our own earlier claim that the safety stage raises the conditional share, an item-level partition permutation put the null between +4.73 and +7.04 pp and contained the observed value at $p=0.87$. That permutation treats the items as independent, so like the McNemar statistics it is a diagnostic and not one of this paper’s inferential results; we report it as evidence that arm-label exchangeability alone already produces a gap of the observed size, and the claim of this section does not rest on it. The claim is structural, and holds whatever a resampling test returns: when answer status is treatment-dependent, the contrast does not identify what it is read as identifying. Of the six conventions we considered for the one arm that drops items, the two defensible ones — dropping the unparsable items, and recovering their raw completions and scoring what they actually said — both fail to detect the effect. A third convention, scoring every unparsable item as counter-stereotyped, is superseded: recovering the raw text showed that of the 42 of 148 that had in fact chosen an option, 34 were stereotyped and 8 counter-stereotyped, so the assumption behind it is the reverse of what the outputs show. We drop it from the live comparison.

Table 5 shows the selection happening item by item, and it is the strongest support we have for this section’s claim. Going from the style checkpoint to the safety checkpoint, the conditional stereotyped share rises. Almost none of that rise is new stereotyped answering: the safety arm adds 11 stereotyped answers to items the style arm abstained on, and removes 827 of the 1,397 the style arm had. What is left is a residue — 517 items, 96.6% of the safety arm’s 535 stereotyped answers, every one of them already stereotyped before the safety stage. The share rises because the intervention disproportionately removes items that had contributed to the denominator, leaving a concentrated subset of previously stereotyped answers. That is a fact about which items remain in the denominator, not about what the model prefers on a fixed set of items.

We report conditional shares in Table 7 for completeness and use none of them as evidence about content preference. This is also why §5 stops at an allocation statement about S : a small composition term is what a treatment that changes answer propensity produces mechanically, and it cannot be turned into a claim about what the model latently prefers.

6.2 Disclosure-detector agreement is not invariant across treatments

We have two detectors for required disclosure. The strict one implements the five rules of §3 as regular expressions over the wording of the Standard Investment Solicitation Rules [20], with the basis qualification recorded there; the loose one uses broader per-rule patterns, and the two were specified independently. Both are reproducible. Neither is a measurement of regulatory compliance, and this section does not need it to be: the result here is about the *relationship between the two instruments*, which is observable without reference labels of any kind.

Table 6 is the result. Conditional agreement between the two instruments — the fraction of loose-positive rule-pairs the strict gate also marks positive — runs 0.675 on base, 0.438 on the style-only arm, 0.951 on the prompted arm and 0.986 on the distilled arm, a spread of 54.9 points. Which instrument you use therefore matters far more on some checkpoints than on others, and that is a property of the treatments, not of a labelling protocol. On an earlier, independent set of rollouts the same quantity spans 27.9 points, so this is not an artefact of the newer run.

The disagreement is directional rather than random, and the counts show where it lives. On base, 13 of the 14 pairs the strict gate catches and the loose one misses are the investor-responsibility rule, where the model writes the canonical clause in a word order the loose pattern cannot match. On the style-only arm the strict-only cell is exactly zero and the loose-only cell is 36, so on that arm the looser instrument is doing all of the additional marking. Median response length differs about thirteenfold across these arms, so each detector’s behaviour is entangled with the arm’s verbosity — the same channel §5.3 manipulates.

We had hypothesised that verbosity was therefore the *mechanism* of the non-invariance. Assigning length within a single arm does not support it: with the same prompt clustering §5.3 uses, conditional agreement is flat in length for base (+0.06, CI [−0.19, +0.31]) and for the style arm (−0.05, CI [−0.36, +0.25]), rising only for the distilled arm (+0.79, CI [+0.25, +1.34]). Pooling arms reverses the sign, which makes any cross-arm trend a mixing artefact. The emission result and this one are parallel; neither produces the other.

The 18-row fixture set on which the strict gate was adopted is a unit test rather than a validation: it holds sentences the author wrote to make the patterns fire and the same sentences with the phrasing deleted. It says nothing about how either instrument behaves on real output, which is why the claim in this section is built from the joint distribution of the two detectors and not from either one’s accuracy.

6.3 The pre-specified abstention verdict is format-sensitive

That option order moves multiple-choice results is established. Pezeshkpour and Hruschka [35] report performance gaps of approximately 13% to 85% under option reordering and attribute them to positional bias arising where the model is uncertain between its top choices, and Zheng et al. [50] identify a selection bias toward particular option IDs, trace it to token bias, and propose a label-free inference-time correction. We replicate that instability and extend it in one direction: to a *pre-specified pass/fail verdict* on a *social-bias* benchmark, where the unit that moves is the choice between answering and abstaining rather than the choice between two substantive options. We measure it on the shipped safety checkpoint, holding weights, decoding and the item set fixed and varying only where the answer options sit.

The primary design is a fully paired cyclic panel: every item in the panel is scored under all three cyclic rotations, so option position and item difficulty are separated by construction. The panel is a separate draw of 250 items per category from the test set, restricted to ambiguous items *afterwards* rather than drawn from them, under sampling seed 20260909; because every category in this build is exactly half ambiguous, that leaves 1,506 items at roughly 125 per category (observed 112 to 139), and the analysis keeps the 1,402 whose complete cycle came back scored (4,206 responses). Dropping an item whose cycle is incomplete was fixed in the scorer before any arm was run and is a requirement of the design rather than a filter applied to results: a partial cycle no longer visits every slot equally and would manufacture the very slot effect being measured. The 104 dropped items are counted and reported. Two effects appear. The chosen slot is not uniform — 31.8 / 34.1 / 34.2% against 33.3 expected, with template-clustered intervals excluding uniform on all three slots. And abstention itself depends on where the “unknown” option sits: 92.58% when it is in the first slot against 95.36 and 95.22% in the other two. Because the complete cycle gives every item one response per slot, that comparison is paired within item, and the template-clustered bootstrap on the paired differences is what carries it: +2.78 pp, CI [+0.87, +5.15], for the second slot against the first and +2.64 pp, CI [+0.56, +5.30], for the third. A random-intercept logistic fit on the same data, grouped by template rather than by item because items sharing a template are correlated, puts the slot dummies at $z=3.85$ and 3.64 in the same direction — but the penalised quasi-likelihood fitter does not report convergence for either the item or the template specification, so we report those coefficients as descriptive of the fitted model rather than as calibrated tests, and rest the conclusion on the bootstrap. In aggregate a single fixed rotation misstates position-neutral abstention by only 0.21 pp and the conditional share by −1.94 pp — but at the item level, **7.8% of items flip between abstaining and answering on option position alone**.

A secondary check varies the per-item rotation through ten independent salted hashes over the full 8,139-item set. Abstention comes out at 92.81% on average with a standard deviation of 0.17 pp, spanning 92.60 to 93.16%. Our pre-specified criterion was $\geq 93\%$. The conditional stereotyped share is directionally stable across the same ten (93.72–95.77%, every one above the value we report), so what moves here is the threshold verdict and not the direction.

The finding is not that option position matters — that is Pezeshkpour and Hruschka [35] and Zheng et al. [50] —

Table 7: Both orderings against the arms carrying one repair each, on 8,139 ambiguous KoBBQ items and 48 disclosure prompts. All rows are bf16 checkpoints, measured in different sessions across two clusters with matching engine arguments rather than in one wave; base was re-evaluated on the arm serving configuration. The KoBBQ denominators differ where an arm drops items: 8,139 for base, style, FIN1 and M5, 7,991 for safety and 8,122 for M4. The conditional share column is reported for completeness; a between-arm contrast in it is selection-confounded (§6.1). The disclosure column is the strict detector’s positive rate pooled over the shared 48-prompt set (456 rule-pairs per arm, three runs), and the loose column is the second detector’s positive rate on the same pairs. Neither is a compliance estimate (§6.2); both are shown because a single detector cannot carry a cross-arm comparison when detector agreement is itself arm-dependent. Both detectors are recorded for every arm evaluated on the disclosure axis; the safety arm was not, and its two disclosure cells are empty rather than imputed.

Arm	Stages	Abstention	Abs. stereo.	Cond. share	Strict	Loose	Dis. acc.
base	—	81.41%	16.02%	86.19%	0.276	0.364	88.20%
style	style	80.10%	17.16%	86.23%	0.061	0.140	89.82%
safety	style→safety	92.80%	6.70%	93.04%	—	—	88.57%
FIN1	style→compliance	87.82%	10.71%	87.99%	0.945	0.952	86.24%
M4	style→safety→compl.	91.79%	7.56%	92.05%	0.956	0.961	88.65%
M5	style→compl.→safety	96.98%	2.73%	90.24%	0.893	0.919	86.84%

nor that the 93% line is the wrong line. It is that this known instability is large enough near a decision boundary to move a pre-specified verdict on a social-bias benchmark: **the same checkpoint fails under eight of ten defensible rotations and passes under two**. We report the criterion as format-sensitive rather than as met. The cyclic panel is also what a rotation-robustness claim has to be built on: the same items under all rotations, with no seed involved.

7 RQ4: composition and order

Both orderings of the last two stages were trained, one run each. This section is descriptive. Order effects in sequential post-training are well covered [2, 3, 5, 8, 27, 46, 48], we make no novelty claim, and with $n=1$ per ordering we cannot attribute what we see to order as a cause.

Both orderings compose partially, and their observed off-target deviations again lie on emission variables — though the M4-versus-safety KoBBQ contrasts are not resolved under template clustering. M4 puts compliance last. On the shared 48-prompt set its strict-detector disclosure rate is 0.956 against FIN1’s 0.945 and its loose rate 0.961 against 0.952. Clustered on the 40 obligated prompts, neither detector distinguishes the pair — +1.10 pp, CI [−1.95, +4.30], strict and +0.88 pp, CI [−1.55, +3.61], loose — so both instruments agree that the disclosure stage survives being applied after safety and neither supports saying it does better. A random-intercept logistic on the same pairs reaches the opposite verdict on the log-odds scale. The two target different estimands, on different scales, under different modelling assumptions; we report both, and the marginal contrast in emission rate is the one the deployment-visible quantity here requires. The cost appears as answering, but not detectably at this clustering: on the items both arms score, M4 answers 0.68 pp more of them than the safety arm and emits 0.61 pp more stereotyped answers in absolute terms, and both template-clustered intervals cover zero ([−0.03, +1.41] and [−0.09, +1.34]). Under the item-level bootstrap these two contrasts were distinguished; template clustering withdraws them, and the M4-versus-safety difference is a point estimate we do not claim to have resolved. The conditional share contrast is not distinguished either, and would be selection-confounded if it were. M5 puts safety last, and that stage overshoots: it abstains on 96.98% of ambiguous items against the safety arm’s 92.80, a paired difference of 4.29 pp with a template-clustered interval of [+1.92, +7.24] that excludes zero, and against M4’s 91.79; its absolute stereotyped exposure falls to 2.73%. Both deviations increase abstention and reduce absolute stereotyped exposure on KoBBQ. What it costs is disclosure, and both detectors register it: on the same shared set its strict rate is 0.893 and its loose rate 0.919, 5.26 pp and 3.29 pp below FIN1 and 6.36 pp and 4.17 pp below M4. Clustering on the 40 obligated prompts rather than treating the 456 rule-pairs as independent — the same unit §5.3 uses — three of those four contrasts exclude zero: against FIN1 the strict interval is [−9.56, −1.16] and against M4 the strict and loose intervals are [−10.68, −2.38] and [−8.23, −0.66]. The fourth, M5 against FIN1 under the loose detector, covers zero at [−7.14, +0.44], so the two detectors agree on the direction but only one of them resolves that pair.

The two orderings differ by 4.83 pp on absolute stereotyped exposure. The right reference for a DPO-stage difference is the DPO stage’s own seed spread, which we measured by retraining the safety stage under two further seeds: 1.535 pp over the 7,036 items all three scored (SD 0.792), 1.941 pp over all 8,139 asked, 1.701 pp on each arm’s own scorable set. The order gap is therefore 2.5 to 3.2× the observed DPO seed spread under these denominator

conventions, rather than the $7\times$ that the SFT-stage spread of 0.676 pp would suggest. Three seeds give an observed spread, not a floor, and it is still one run per ordering: the seed replication measures rerunning *one* order, not the spread of each. The statement this supports is that the two orderings produced clearly different models, not that stage order is established as the cause.

Two things from that replication belong here because they are §6’s argument reappearing inside a seed experiment. Reseeding moves parse failure by four to five times — 1.8% for the shipped checkpoint against 7.2% and 9.3% for the two reseeds — while re-measuring the shipped checkpoint in the same session moved it from 148 items to 150. The answered set is a property of the checkpoint rather than of the harness, so any table over this benchmark has to name its denominator convention (§6.1). And the composition residuals across the three seeds are 0.046, 0.089 and 0.092 pp: variation under reseeding again falls primarily in the answer-propensity term while the observed composition residual stays small, the same allocation pattern §5 reports under treatment. As there, we do not read the small residual as invariant latent preference, for the reason §6.1 gives.

7.1 A third emission axis: surface form

One more thing the safety stage did, on prompts with nothing to do with safety. On the 637 held-out prompts of Table 1, non-Korean-script contamination rises to 20.72% of responses from the style arm’s 4.87%, and a per-script breakdown attributes the whole increase to simplified Chinese fragments: 30.74 characters per 10,000 against the style arm’s 5.08 and base’s 2.21, six times its own starting checkpoint, while Latin contamination over the same arms does not move (13.0% against 12.2% of responses). The compliance stage puts it back: FIN1 reads 5.35 per 10,000. We treat this as a surface-form change; by itself, it does not identify a preference or capability change.

The safety arm is also the only KoBBQ arm that drops items — 1.82% of ambiguous items unparseable, against zero for base and style, falling to 0.21% after the compliance stage. The two are tempting to merge and are not one phenomenon: in the 16-token scoring window there are zero Sino-Korean characters in all 416 excluded completions and zero in a context-matched control. What produces the exclusions is that this arm answers in prose that breaks the response format, compounded by a scoring regex whose word-boundary convention cannot see an option letter attached directly to Hangul — 146 of the 416 excluded completions named a letter the instrument then discarded. The exclusion asymmetry is real, its cause is surface form, and it is why every contrast involving this arm is classified as overlapping and tested accordingly.

8 Limitations

The bias axis rests on one benchmark family in one language on one base model. We have not shown the allocation result holds for disambiguated items, other bias benchmarks, or other model families. We recomputed the same decomposition on English BBQ from stored outputs, and it cannot answer the question: the base model already abstains on 95.6% of the ambiguous items, leaving 46 to 68 answered items per arm and a minimum detectable difference of 25 to 27 pp on the conditional share against observed differences of 3.7 to 5.7 pp. The English axis neither reproduces nor refutes the Korean result, and the compliance arm has no stored English data.

Every training arm is $n=3$ or smaller. At three against three the exact permutation test’s two-sided p cannot go below 0.100, so no arm comparison in §4 can carry a small p -value by construction, and the evidence is carried by the sign reversal, the observed seed-range non-overlap and the template-clustered between-arm intervals instead. The order comparison in §7 is $n=1$ per ordering. The two inference axes should not be confused: the item-level tests quantify uncertainty conditional on each trained checkpoint and do not substitute for uncertainty across training runs, so any generalisation across training stochasticity rests only on the three independent seeds per arm.

The lever behind the bias-axis direction is unresolved. Target length and the broader style rewrite remain entangled, and the fourth arm built to separate them (§4) does not settle it either: its three seeds are too dispersed to identify a mechanism, and it additionally varies turn-final question structure and the generator’s conditioning distribution alongside hedging. The defensible stopping point is that target form matters and this study does not identify the individual feature responsible.

The allocation result of §5 is descriptive of the contrasts we ran and is not a law. Nothing prevents a treatment from moving the composition term substantially, and a treatment that did would invalidate no identity, only the summary. The share statistic is also undefined in practice when ΔS is near zero. Under template-clustered inference four of the seventeen training contrasts have intervals covering zero, as does the W4A16 precision contrast; on length-matched seed 2 the ratio reads -17 percent on a composition term of $+0.072$ pp, the two terms having opposite signs on a

ΔS of +0.061 pp, and on W4A16 it reads 126 percent on a composition term of +0.056 pp. That is why percentage points are the primary presentation here and the ratio is quoted only where ΔS resolves.

The dose-response design shows length is sufficient to produce most of the disclosure effect, not that it was the causal path; assignment bounds the mediation question from one side only.

Neither detector has been validated against human semantic judgments, so we do not treat detector-positive rates as calibrated estimates of regulatory compliance. Our claims on this axis are restricted to detector-measured disclosure emission, intervention effects that reproduce under both detectors, and cross-arm detector non-invariance.

The precision arms of §5 are a single run each with unmeasured requantization build spread; a rebuild floor of 3.56 pp measured on a different task elsewhere in this project is why that matters. They abstain between 89.8% and 92.9%, so their magnitude should not be carried to a low-abstention arm, and the three parsed slightly different item sets (7,867 of 8,139 in common). We make no claim about quantizer quality and none about which quantizer to deploy.

The response-style profile of Table 1 has two known coverage problems, both stated in the table: base length is right-censored at the generation cap, so length gaps against base are lower bounds; and the register feature scores different fractions of each arm’s responses, so its row is conditional-on-scored rather than a population share. We report no combined style score, so no reader can be misled by a weighted average of features with unequal coverage.

$T=0$ is not determinism. Most KoBBQ checkpoint measurements are single evaluations. One checkpoint was repeated within one session on the same node, moving its absolute stereotyped exposure by 0.013 pp, and separately across an H200 and a B200, differing by 0.098 pp; the disclosure axis is three runs per arm throughout. Neither repeat estimates variability across training runs, which is why the seed replications and not the repeats carry the generalisation.

Finally, the training corpus is not released. Weights and evaluation harnesses are; we describe the corpus construction in enough detail to reproduce the method rather than the file.

9 Conclusion

Response-style alignment in this pipeline changed two behaviours it never targeted, and in both cases the deployment-visible changes were carried primarily by how often and how much the model emitted; our design does not identify whether latent conditional preferences changed. On the bias axis it answers ambiguous questions more often, and the change in what a user encounters is accounted for almost entirely by that. On the disclosure axis it says less, and most of the detector-measured loss of required language is reproduced when response length is assigned directly. Against a base re-evaluated on the same serving configuration, controls trained on the same prompts and recipe with unmodified teacher responses as targets move the first axis in the opposite direction from the style arms, the observed seed ranges not overlapping and their means differing by 2.34 pp, so what answer propensity depends on is the form of the training target rather than the prompt set or the recipe alone — though which feature of that form is responsible our four-arm design does not identify.

The decomposition that organises the bias result is an identity, and we are explicit about that. What is empirical is where the movement went: across seventeen training-checkpoint contrasts the answer-propensity term moves by up to 13.4 pp while the composition term never leaves the band from +0.00 to +0.45 pp, and two further contrasts produced by changing a quantizer rather than by training sit in the same place. That is a statement about a deployment-visible quantity, not about the model’s latent preferences, and we stop there deliberately — the conditional term is computed on answered subsets the treatment itself selects.

Two things follow for practice. A deployment-relevant bias or disclosure measure can be moved by an alignment stage that never mentions it, through a variable — how often and how much the model speaks — that a share-based metric does not report. And the instruments that would catch it have to survive the treatment: a contrast in a ratio conditioned on the answered set is selection-confounded once the treatment changes that set, and a detector keyed on surface form cannot be assumed to behave invariantly when the treatment changes surface form. Both are measurable before they are trusted, and in our case measuring them changed what we were entitled to say.

A The fourth control arm

The pre-specified rule for the short-and-hedging arm classified each seed by the nearest of three landmarks — NEUTRAL at -1.40 , ADDITIVE at -0.10 , STYLE at $+0.94$ pp — and declared the arm unresolved unless the three seeds agreed. They did not: on the base against which the landmarks were fixed the three seeds classify as ADDITIVE, STYLE and

NEUTRAL respectively. Re-evaluating the base on the arm serving configuration shifts all four arms by a common constant (the fourth arm’s seeds become -0.639 , $+1.708$ and -2.519 pp) and leaves that classification unchanged.

The rule was mis-specified for an arm this dispersed, and we record that rather than credit it with firing. With decision bands roughly 1.2 pp wide against a per-seed standard deviation of 2.12 pp, an arm whose true mean sat exactly on any landmark would still fail seed unanimity most of the time, so the rule cannot return a verdict here wherever the true mean sits. A rule keyed to the three-seed interval instead of to per-seed unanimity would have reported the additive band and flagged low power. The conclusion is unchanged either way, because every pairwise contrast involving this arm overlaps on its own: -1.30 pp against style at exact permutation $p \approx 0.4$, $+1.04$ pp against neutral at $p \approx 0.6$. The arm mean sits 0.26 pp from the additive prediction, which is 0.21 standard errors of a three-seed mean whose standard error is 1.22 pp; we read it as evidence about the additive model in neither direction.

Two further observations. The dispersion is not instrument variation: across the three seeds the number of answered items spans 344 of 8,139, against 72 for style, 70 for length-matched and 17 for neutral, and this arm has the highest held-out loss of the four (1.24–1.26 against 0.88–0.90 for style, 0.76–0.78 for length-matched and about 0.74 for neutral). A target that must be short *and* carry the teacher’s reservation is the hardest of the four to fit in one epoch, and if such targets place the model at a genuinely unstable point — hedging pulling toward abstention and brevity toward commitment — then a two-factor additive account would be mis-specified rather than merely untested. The data permit that reading and do not establish it, and it too rests on three seeds.

Finally, this arm’s mean of -0.483 pp sits 0.004 pp from the length-matched arm’s -0.487 — a gap that a common base shift leaves unchanged, so it holds on either base. The two arms can therefore be read as the same measurement — both “not style, not neutral, somewhere in between” — so the fourth cell may have added a second observation of ambiguity rather than resolving it. Nothing in the design rules that out.

B Instrument defects behind body claims

We audited every instrument supporting a quantitative claim in the main text for provenance and cross-arm applicability: whether the instrument the surrounding prose describes is the instrument that produced the number, and whether an instrument carrying a between-arm claim is applied uniformly across the arms it compares. Where it is not — the one arm whose parse failures give it a different scored set — the affected contrasts are classified as overlapping and tested accordingly (§7). Table 8 lists the defects that bear directly on a claim in this paper, with the section that carries the consequence. Each was found by asking a question the instrument had not been built to answer, and none raised an error.

Table 8: Instrument defects that changed something a reader sees, and where the consequence is carried.

Class	Instance	Consequence in the body
Tautology mistaken for a finding	The threshold/composition split, whose remainder is identically $A_1\Delta L$	§5 reports an allocation, not a fit
Instrument substitution	Prose described the five-rule gate; the disclosure figures came from the looser detector	Both detectors are named and re-reported (§6.2)
Measurement non-invariance	Agreement between the two disclosure detectors runs 0.44–0.99 by arm	§6.2 is built on their joint distribution
Protocol provenance mismatch	A flag documented as varying the answer-option layout varies the item subsample instead	§6.3 measures rotation directly
Locale-blind convention	A word-boundary regex cannot see an option letter attached to Hangul	The safety arm’s exclusions, §7
Stack-crossing contrast	A comparison crossing weight precision, KV dtype, speculative decoding and run date	Precision arms are separated from training contrasts (§5)

Two are worth a sentence beyond the table. The flag we described as varying the answer-option layout takes no part in the layout at all: the rotation is `md5(sample_id) % k`, and the stored layouts of all 16,240 benchmark items reproduce exactly under that function. What the seed argument does is shuffle the item pool before a per-category cap truncates it, and six of twelve categories sit exactly at the 2,000 cap, holding 12,000 of the 16,240 scored items, so 73.9% of the benchmark is a seed-dependent subsample and two runs under different seeds are not paired. And a verification step meant to confirm that training hyper-parameters had arrived in the job read back `adapter_config.json` from the output root, while both trainers write that file to `checkpoint-final/` inside it; no run could have passed, and completed training runs were logged as failures.

Reproducibility and provenance

Weights, model cards and evaluation harnesses are released; the paired training corpus is not. Every number in this paper resolves to a measurement ledger recording the checkpoint, cluster, serving configuration, item set and analysis script, and quantities whose ledger does not exist are marked missing there and omitted here rather than reproduced and inserted. Serving arguments were read back from live pods and the served model identity asserted before recording for every arm reported in §4, §5 and §7. Statistical tests are computed by one shared module, which selects the admissible test from the stored item-identifier sets rather than from the design as described; uncertainty over KoBBQ items is estimated with the KoBBQ template as the resampling or clustering unit, and the recomputation script is released with the harness. The `all-test` snapshot we evaluate has SHA-256 `42efee64...f3c00fc3`; with the build unidentified, that hash is the provenance we can offer.

References

- [1] Andrew M. Bean et al. Measuring what matters: Construct validity in large language model benchmarks. *arXiv preprint arXiv:2511.04703*, 2025.
- [2] Pranav Bhandari, Nicolas Fay, Amitava Datta, Usman Naseem, and Mehwish Nasim. Beyond uniform forgetting: A study of sequential direct preference optimization across preference settings. *arXiv preprint arXiv:2606.19744*, 2026.
- [3] Sungmin Cha and Kyunghyun Cho. Why alignment must precede distillation: A minimal working explanation. *arXiv preprint arXiv:2509.23667*, 2025.
- [4] Lichang Chen et al. ODIN: Disentangled reward mitigates hacking in RLHF. *arXiv preprint arXiv:2402.07319*, 2024.
- [5] Qihong Chen et al. Does the order of fine-tuning matter and why? *arXiv preprint arXiv:2410.02915*, 2024.
- [6] Juan Manuel Contreras. An LLM-native psychometric instrument reveals a self-report-behavior gap across 25 models. *arXiv preprint arXiv:2606.09843*, 2026.
- [7] Yann Dubois, Balázs Galambosi, Percy Liang, and Tatsunori B. Hashimoto. Length-controlled AlpacaEval: A simple way to debias automatic evaluators. In *Conference on Language Modeling (COLM)*, 2024. *arXiv:2404.04475*.
- [8] Heshan Fernando et al. Understanding forgetting in LLM supervised fine-tuning and preference learning – a convex optimization perspective. *arXiv preprint arXiv:2410.15483*, 2024.
- [9] Kathleen C. Fraser et al. Fine-tuning lowers safety and disrupts evaluation consistency. In *Proceedings of the First Workshop on Large Language Model Security (LLMSEC)*, pages 129–141, 2025. *arXiv:2506.17209*.
- [10] Leo Gao, John Schulman, and Jacob Hilton. Scaling laws for reward model overoptimization. *arXiv preprint arXiv:2210.10760*, 2022.
- [11] Yonatan Geifman and Ran El-Yaniv. Selective classification for deep neural networks. *arXiv preprint arXiv:1705.08500*, 2017.
- [12] Jia-Chen Gu, Hao-Xiang Xu, Jun-Yu Ma, Pan Lu, Zhen-Hua Ling, Kai-Wei Chang, and Nanyun Peng. Model editing harms general abilities of large language models: Regularization to the rescue. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 16801–16819, 2024. doi: 10.18653/v1/2024.emnlp-main.934.
- [13] Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations*, 2022. *arXiv:2106.09685*.
- [14] Stanley Z. Hua, Sanae Lotfi, and Irene Y. Chen. Investigating social bias changes in quantized language models. *arXiv preprint arXiv:2602.06181*, 2026.
- [15] Gabriel Ilharco, Marco Tulio Ribeiro, Mitchell Wortsman, Suchin Gururangan, Ludwig Schmidt, Hannaneh Hajishirzi, and Ali Farhadi. Editing models with task arithmetic. *arXiv preprint arXiv:2212.04089*, 2022.

- [16] Jiho Jin, Jiseon Kim, Nayeon Lee, Haneul Yoo, Alice Oh, and Hwaran Lee. KoBBQ: Korean bias benchmark for question answering. *Transactions of the Association for Computational Linguistics*, 12:507–524, 2024. doi: 10.1162/tac1_a_00661.
- [17] Saurav Kadavath et al. Language models (mostly) know what they know. *arXiv preprint arXiv:2207.05221*, 2022.
- [18] Polina Kirichenko, Mark Ibrahim, Kamalika Chaudhuri, and Samuel J. Bell. AbstentionBench: Reasoning LLMs fail on unanswerable questions. In *Advances in Neural Information Processing Systems*, 2025. arXiv:2506.09038.
- [19] James Kirkpatrick et al. Overcoming catastrophic forgetting in neural networks. *arXiv preprint arXiv:1612.00796*, 2016.
- [20] Korea Financial Investment Association. Standard Investment Solicitation Rules. <https://law.kofia.or.kr/service/law/lawFullScreenContent.do?seq=149>, 2026. Korean title: Pyojun Tuja Gwonyu Junchik; self-regulatory standard, current revision 2026-04-09.
- [21] Suhas Kotha, Jacob Mitchell Springer, and Aditi Raghunathan. Understanding catastrophic forgetting in language models via implicit inference. *arXiv preprint arXiv:2309.10105*, 2023.
- [22] Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph E. Gonzalez, Hao Zhang, and Ion Stoica. Efficient memory management for large language model serving with PagedAttention. In *Proceedings of the ACM SIGOPS 29th Symposium on Operating Systems Principles*, 2023. arXiv:2309.06180.
- [23] Hwaran Lee, Seokhee Hong, Joonsuk Park, Takyoung Kim, Gunhee Kim, and Jung-Woo Ha. KoSBI: A dataset for mitigating social bias risks towards safer large language model applications. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 5: Industry Track)*, pages 208–224, 2023. doi: 10.18653/v1/2023.acl-industry.21.
- [24] Yong Lin et al. Mitigating the alignment tax of RLHF. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 580–606, 2024. doi: 10.18653/v1/2024.emnlp-main.35.
- [25] Zipeng Ling et al. LLM abstention can be a prompt artifact, in addition to genuine uncertainty. *arXiv preprint arXiv:2507.16199*, 2025.
- [26] Mingyi Liu. The alignment tax: Response homogenization in aligned LLMs and its implications for uncertainty estimation. *arXiv preprint arXiv:2603.24124*, 2026.
- [27] Yichen Liu et al. Representation collapse in sequential post-training of large language models. *arXiv preprint arXiv:2605.30524*, 2026.
- [28] Gaoxiang Luo, Yifan Wu, Sinian Zhang, Aryan Deshwal, and Ju Sun. Aligning language models with selective prediction. *arXiv preprint arXiv:2607.03528*, 2026.
- [29] Yun Luo, Zhen Yang, Fandong Meng, Yafu Li, Jie Zhou, and Yue Zhang. An empirical study of catastrophic forgetting in large language models during continual fine-tuning. *arXiv preprint arXiv:2308.08747*, 2023.
- [30] Sumanth Manduru and Carlotta Domeniconi. Beyond bias scores: Unmasking vacuous neutrality in small language models. *arXiv preprint arXiv:2506.08487*, 2025.
- [31] Ksenia Merzlyakova, Sebastian Padó, and Franziska Weeber. Effects of answer format variation on gender bias in large language models. *arXiv preprint arXiv:2608.17516*, 2026.
- [32] Long Ouyang et al. Training language models to follow instructions with human feedback. In *Advances in Neural Information Processing Systems 35 (NeurIPS 2022)*, 2022. arXiv:2203.02155.
- [33] Arjun Panickssery, Samuel R. Bowman, and Shi Feng. LLM evaluators recognize and favor their own generations. *arXiv preprint arXiv:2404.13076*, 2024.
- [34] Alicia Parrish, Angelica Chen, Nikita Nangia, Vishakh Padmakumar, Jason Phang, Jana Thompson, Phu Mon Htut, and Samuel R. Bowman. BBQ: A hand-built bias benchmark for question answering. In *Findings of the Association for Computational Linguistics: ACL 2022*, 2022. arXiv:2110.08193.
- [35] Pouya Pezeshkpour and Estevam Hruschka. Large language models sensitivity to the order of options in multiple-choice questions. In *Findings of the Association for Computational Linguistics: NAACL 2024*, 2024. arXiv:2308.11483.

- [36] Xiangyu Qi, Yi Zeng, Tinghao Xie, Pin-Yu Chen, Ruoxi Jia, Prateek Mittal, and Peter Henderson. Fine-tuning aligned language models compromises safety, even when users do not intend to! In *International Conference on Learning Representations*, 2024. arXiv:2310.03693.
- [37] Qwen Team. Qwen3.8-27B. <https://huggingface.co/Qwen/Qwen3.8-27B>, 2026. Model release, Apache-2.0; the base checkpoint used in this work. License verified against the distributed LICENSE file, 2026-08-28.
- [38] Rafael Rafailov, Archit Sharma, Eric Mitchell, Stefano Ermon, Christopher D. Manning, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. In *Advances in Neural Information Processing Systems*, 2023. arXiv:2305.18290.
- [39] Pranav Rajpurkar, Robin Jia, and Percy Liang. Know what you don’t know: Unanswerable questions for SQuAD. *arXiv preprint arXiv:1806.03822*, 2018.
- [40] Alexandre Ramé, Guillaume Couaaron, Mustafa Shukor, Corentin Dancette, Jean-Baptiste Gaya, Laure Soulier, and Matthieu Cord. Rewarded soups: Towards Pareto-optimal alignment by interpolating weights fine-tuned on diverse rewards. In *Advances in Neural Information Processing Systems 36 (NeurIPS 2023)*, 2023. arXiv:2306.04488.
- [41] Plawan Kumar Rath and Rahul Maliakkal. Quantization undoes alignment: Bias emergence in compressed LLMs across models and precision levels. *arXiv preprint arXiv:2605.15208*, 2026.
- [42] Keita Saito, Akifumi Wachi, Koki Wataoka, and Youhei Akimoto. Verbosity bias in preference labeling by large language models. *arXiv preprint arXiv:2310.10076*, 2023.
- [43] Prasann Singhal, Tanya Goyal, Jiacheng Xu, and Greg Durrett. A long way to go: Investigating length correlations in RLHF. *arXiv preprint arXiv:2310.03716*, 2023.
- [44] Joar Skalse, Nikolaus H. R. Howe, Dmitrii Krashennnikov, and David Krueger. Defining and characterizing reward hacking. *arXiv preprint arXiv:2209.13085*, 2022.
- [45] Guanglong Sun, Siyuan Zhang, Liyuan Wang, Jun Zhu, Hang Su, and Yi Zhong. Safety alignment as continual learning: Mitigating the alignment tax via orthogonal gradient projection. *arXiv preprint arXiv:2602.07892*, 2026.
- [46] John Sweeney. The geometry of sequential learning: Lie-bracket prediction of transfer order. *arXiv preprint arXiv:2606.24993*, 2026.
- [47] Hugo Touvron et al. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*, 2023.
- [48] Megan Ung, Alicia Sun, Samuel J. Bell, Bhaktipriya Radharapu, Levent Sagun, and Adina Williams. Chained tuning leads to biased forgetting. *arXiv preprint arXiv:2412.16469*, 2024.
- [49] Prateek Yadav, Derek Tam, Leshem Choshen, Colin Raffel, and Mohit Bansal. TIES-merging: Resolving interference when merging models. In *Advances in Neural Information Processing Systems 36 (NeurIPS 2023)*, 2023. arXiv:2306.01708.
- [50] Chujie Zheng, Hao Zhou, Fandong Meng, Jie Zhou, and Minlie Huang. Large language models are not robust multiple choice selectors. In *International Conference on Learning Representations*, 2024. arXiv:2309.03882.
- [51] Lianmin Zheng et al. Judging LLM-as-a-judge with MT-bench and chatbot arena. In *Advances in Neural Information Processing Systems 36 (NeurIPS 2023), Datasets and Benchmarks Track*, 2023. arXiv:2306.05685.