

What Does Context Compression Cost an Agent?

Interaction Costs Unrevealed by Task-Completion Metrics

Shuyu Liu

Chongqing University of Science and Technology

2026

An earlier version of this work was accepted at the COLM 2026 Workshop on Efficient Reasoning.

Abstract

Task completion is the standard metric for evaluating context compression, yet it is an incomplete measure: compression can substantially increase an agent’s interaction cost — the reacquisition of state it dropped — while leaving completion statistically unchanged. We formalize completion-only evaluation as a lossy projection of the full evaluation outcome, and demonstrate in a controlled setting that it can miss a large interaction cost.

We introduce a controlled runtime measurement protocol that isolates the reacquisition cost of context compression in a bounded-horizon agent. An agent acts on a deterministic planning environment under a fixed interaction budget (24 turns); we vary the compression ratio, contrast a dropping operator with a fact-preserving operator at equal budgets, manipulate the availability of dropped state through oracle restoration, and decompose tool calls into retrieval versus execution. One model is swept across compression severities; two further models are evaluated at a fixed ratio, across two task regimes.

Retrieval tool calls increase in every one of our six model–regime comparisons and account for almost all of the added interaction, while execution calls remain approximately unchanged; five of six retrieval increases remain significant after Holm correction. Completion, by contrast, does not track this cost: at the pre-specified $5\times$ comparison point its changes are not significant in any of the six cells (all $p \geq 0.125$), and even for DeepSeek completion becomes significant only at the most aggressive ratio ($10\times$, $p = .016$) — the cost signal responds at milder compression than completion does. GPT-5.5 is the sharpest case — completion statistically unchanged ($80\% \rightarrow 85\%$, $p = 1.0$) while retrieval roughly triples ($+42.9$ calls). Completion significantly degrades only when reacquisition consumes enough of the interaction horizon to limit task progress, as observed most clearly for DeepSeek under high compression. Restoring the dropped state removes roughly half of the retrieval cost, and a fact-preserving operator at the same compression ratio preserves completion while avoiding most of the extra retrieval.

Using retention interventions as causal probes, we separate *how much* state is retained from *which* state is retained and *whether the retained content is valid*. Random selection matches an offline hindsight oracle, while replacing the retained D-state with semantically irrelevant content increases retrieval by 57% ($p < 0.001$) with completion statistically unchanged — completion-centric evaluation can fail to expose both the magnitude and the behavioral consequence of a cost-changing intervention.

We do not claim compression has a fixed cost: in a second environment (ALFWorld) the same operator produces no retrieval surge, so the reacquisition signature is environment-dependent rather than an intrinsic consequence of shortening context. In our controlled setting, the hidden interaction cost of compression emerges when execution-relevant state becomes absent and must be reacquired; completion alone can miss that cost, while the magnitude — and even the presence — of the cost depends on model, task, state, and environment. We provide a tool-level diagnostic for a cost that completion-centric evaluation does not expose.

1 Introduction

Long-horizon agents accumulate trajectories that quickly exceed any context window, so modern runtimes compress — via summarization, sliding windows, or retrieval filters — as a matter of course. A common evaluation view is that compression is successful when it preserves task performance while reducing context cost; failure-aware compressors can match full-context performance on many tasks (ACON), and we find even a deterministic extractive summary to be near-lossless at $5\times$ compression. Existing evaluations ask whether task performance survives. We ask a complementary question: what runtime cost can accumulate before that performance changes? Task completion is an incomplete measure of the runtime cost of context compression — it does not by itself reveal the interaction cost incurred when the agent must reacquire compressed-away state.

“Near-lossless” measures *retention*: whether the surviving context still contains the needed facts. It does not measure *reacquisition*: what the agent does when a piece of execution-relevant state is genuinely absent — re-querying the environment for task graphs, hidden constraints, resource occupancy — and what that costs in the agent’s own currency. Task completion is bounded by the interaction horizon, while tool calls provide a direct measure of the interaction cost spent on reacquisition. Whether compression becomes costly is therefore not determined by retained content alone; it also depends on what the agent must do to reacquire the state that is no longer available. Completion is a blunt instrument for this cost: it is co-determined by the interaction horizon and can remain unchanged while the reacquisition burden grows.

Prior work on context compression asks four questions: *what to keep* (methods: ACON; Memento; RE-TRAC), *whether information survives or is recoverable* (Context Codec’s round-trip guarantees; Reclaim’s black-box recovery), *whether surviving information is used* (the “lost in compaction” attention bottleneck), and *which context-management strategy performs best on capability and efficiency jointly* (aggregate efficiency evaluation; Less Context, Better Agents; agent-evaluation surveys call cost an under-measured axis of LLM-agent assessment). These lines evaluate what compression preserves or achieves. None measures what the agent does when state is actually gone. We ask a fifth question: **what does it cost the agent to re-acquire what was dropped, and is that cost visible to standard metrics?** This is the gap we enter — a controlled demonstration that the two can diverge.

We introduce a controlled measurement protocol for the reacquisition cost of context compression. The setup fixes a single interaction horizon (24 turns); varies the compression ratio via a sliding-window operator; spans two task regimes that differ in how much execution-relevant state must be discovered at runtime; *manipulates the availability of execution-relevant state* through controlled oracle restoration — injecting specific dropped state back into the context — and decomposes the agent’s tool calls into *retrieval* (re-acquiring external state) versus *execution* (performing the task’s operations). We run the protocol across three models — DeepSeek (deepseek-v4-flash), Qwen (qwen3.7-plus), and GPT-5.5 — to separate what holds across models from what is model-specific (DeepSeek at a full severity sweep, Qwen and GPT-5.5 at a fixed $5\times$ ratio).

Our contributions are:

1. **Evaluation non-identifiability under context compression.** Task completion is not an identifying projection of interaction cost: we formalize this as a non-identifiability result and realize it under controlled intervention. GPT-5.5 pays the largest reacquisition cost in our study while its completion is not detected as changed ($80\% \rightarrow 85\%$, $p = 1.0$; retrieval $21.0 \rightarrow 63.9$, $p = .002$); and in a retention intervention (Sec. 3.5), injecting semantically irrelevant state raises retrieval by 57% ($p < 0.001$) while completion is statistically unchanged ($p = 0.41$). Completion is blind not only to the *magnitude* of interaction cost, but also to its

behavioral consequence — completion did not expose the large cost difference induced by the intervention.

2. **A mechanistic decomposition of the hidden cost.** We decompose the reacquisition burden along a recoverability axis: externally queryable task state (D) versus history-dependent state (R), with a re-query loop in which the loss of R inflates defensive re-querying of D. Retrieval calls increase in all six of our model-regime comparisons and account for almost all of the added interaction; restoring dropped state removes roughly half the retrieval cost; and across a retention-budget axis the reduction tracks the retained coverage of D-state (a dose-response within a fixed digest format).
3. **Retention interventions as causal probes: the behavioral relevance of retained state.** We use a family of retention interventions to separate *how much* state is retained from *which* state is retained and *whether the retained content is valid*. Fine-grained selection among real, task-relevant atoms has limited marginal value in our setting — random selection matches an offline hindsight oracle — while replacing D content with semantically irrelevant state sharply increases retrieval. The content effect replicates across models at the loose budget (GPT-5.5, Sec. 4.6.4) while its magnitude and budget-gating remain model-specific. State content is behaviorally load-bearing, but this is visible only when the digest occupies a substantial share of the context window (a content $\times$ budget interaction). An external probe in ALFWorld (Sec. 4.7) bounds the whole signal: where the relevant state can be re-observed directly, the same operator produces no retrieval surge — so the hidden interaction cost is conditional on what execution-relevant state becomes unavailable and must be reacquired, and completion metrics do not expose it.

Across three models and two task regimes we further characterize the *boundary* of the cost signal: reacquisition cost consistently increases, while its translation into completion loss varies substantially — DeepSeek degrades at high compression, Qwen is largely insensitive, and GPT-5.5 does not. The cost signal is also the earlier one: retrieval responds at milder compression ($5\times$) before completion responds, which for DeepSeek occurs only at $10\times$. A second environment (ALFWorld, Sec. 4.7) bounds the signal from the other side: there, the same sliding compression produces no retrieval surge at all, so even the *presence* of the cost is conditional — it emerges when execution-relevant state must be reacquired, and completion metrics do not expose it.

This paper is not another compression benchmark, nor a claim that compression uniformly hurts agents — our own data rule that out. It is a *controlled empirical demonstration of an evaluation blind spot*: a measurement protocol showing that, in this setting, the reacquisition cost is real, decomposable, and model-dependent — and that completion-centric evaluation can miss it, even under an intervention that changes the cost sharply. We do not propose a general theory of agent evaluation; we exhibit one mechanism by which completion can under-report compression’s cost, and we give runtime designers a diagnostic for it. For runtime designers, the actionable quantity is not “which compression ratio is safe” but “which execution-relevant state, if dropped, would the agent spend its budget re-acquiring?” — and our results identify externally queryable task state as a major source of that cost, with the retention-budget results (Sec. 3.5) qualifying how much the digest’s content — as opposed to its mere presence — is responsible for reducing it.

2 Related Work

Category map. Prior work on context compression spans four categories. (i) *Compression methods* ask how to compress better — what to keep and when to compact (ACON; Memento; VISTA;

RE-TRAC; LLMlingua) — and optimize for agent performance. (ii) *Recoverability evaluation* asks whether information survives or can be recovered (Context Codec’s round-trip guarantees; Reclaim’s black-box recovery) — measuring retention as a property of the compressed artifact. (iii) *Long-context utilization* asks whether surviving information is actually used, showing that compaction can fail through attention rather than deletion (“lost in compaction”). (iv) *Aggregate efficiency evaluation* reports completion together with aggregate cost — tokens, latency, runtime — when comparing context-management strategies (Less Context, Better Agents), and agent-evaluation surveys and benchmarks increasingly argue that success alone is insufficient and must be paired with cost (Yehudai et al.; CostBench). Each of these lines evaluates what compression preserves, recovers, or achieves. None provides a diagnostic for the interaction cost that completion-centric evaluation does not expose — where the added interaction goes, and whether completion tracks it. This paper is that diagnostic: a controlled protocol, in a fixed setting, that measures the reacquisition cost and tests whether completion exposes it.

Evaluation metrics for agents, and the insufficiency of completion. A separate line of work asks what the *right metric* for an agent is. Production experience shows completion alone is a blunt instrument: agents in the wild re-query tools and re-fetch already-computed state, and completion reads the final outcome, not the trajectory behind it. Formalizations make the insufficiency precise from different directions: completion rate compresses process-level variance — the “completion fallacy” (Hou et al.) — binary pass/fail obscures meaningful differences among failing agents, motivating graded reliability and progress-based metrics (Khanal et al.; AgentBoard), and bounded-horizon outcome decomposition reveals horizon-dependent trade-offs (the Verifier Tax). A parallel line formalizes the cost side: the tool-calling protocol itself carries an additive accuracy tax (Zhang et al.), cost-optimal planning is benchmarked through cost gaps (CostBench), and cost-per-return frameworks make effectiveness–efficiency trade-offs explicit (Bogdanov et al.). Two observations bracket, but do not fill, the gap we target. These insufficiency arguments concern what completion fails to reveal about process quality or the outcome — not about the runtime cost of context compression; and the cost-accounting frameworks price architecture or protocol choices under an intact context, without connecting cost to state that compression dropped. On the compression side, reacquisition cost is recognized operationally — tokens-per-task accounts for re-fetching (Factory), truncation rots recall (context-clock), and token reduction does not reliably reduce billed cost (Weinberger & Hozes) — but only observationally, without causal attribution. None defines a black-box, model-agnostic measure of how much interaction budget an agent spends to reacquire state that generic compression removed, nor manipulates that state’s availability causally. Our protocol supplies exactly this measurement (Proposition 1, Sec. 3.1).

Closest evaluation-perspective contrasts. Table 1 summarizes the four closest evaluation-perspective works. None measures the interaction budget an agent spends to reacquire state that a compression operator dropped, nor manipulates state availability causally; our protocol does.

Closest contrasts.

- **Lost in Compaction** shows compaction fails through an attention bottleneck rather than deletion (“grep-LLM gap”: keyword search finds 82–93% of facts while the LLM recalls 0–7% in the compacted zone). Our mechanism targets a distinct failure mode and is experimentally separable in our controlled setup: our sliding condition *deletes* old turns, so the dropped state is genuinely absent and the agent’s observable response is to re-fetch it (retrieval calls increase 2–3×; execution calls do not); the oracle condition confirms this attribution by restoring state and removing much of the retrieval cost. We do not contest attention-dilution accounts — they predict our observation that GPT-5.5 tolerates compression — but we isolate a second, independent cost that attention-centric accounts do not capture, because for them the text is

Table 1: Closest evaluation-perspective contrasts.

Work	Measures	Manipulates	Decomposes	What completion can miss	Our difference
CostBench	cost-optimal planning; cost gaps	tool costs & availability (blocking events)	cost by event type	cost-suboptimal but valid plans	intact context; we price reacquiring dropped state
Compress-Agent	reliability & success vs compression	compression retention level	failures: tool-execution vs reasoning	tool failures precede success collapse	no causal state manipulation; we add oracle attribution
Token Red. $\neq$ Cost	billed cost; token vs cost deltas	token-reduction strategies	cost by billing component (cache $\approx 87\%$)	token savings $\neq$ cost savings	provider-specific billing; we use a model-agnostic budget
Tool-Use Tax	accuracy tax of the tool protocol	tool availability (no-op / oracle probes)	accuracy gap: $\Delta_{\text{cmp}} + \Delta_{\text{frc}} + \Delta_{\text{sty}}$	protocol tax swamps tool gains	accuracy over intact context; we meter cost of lost state

still present. Both mechanisms can coexist; we measure the reacquisition side.

- **Context Codec** formalizes codec-level round-trip recoverability of compressed representations. Their recoverability is a representation property (can the encoder + decoder round-trip?); ours is a black-box agent-behavioral property (can the agent recover under a bounded budget?). Same word, different layer — complementary.
- **Reclaim Evaluation** tests recovery of correctable state from a degraded single-carried memory (“a lossy memory is worse than an empty one”). We measure the *cascading reacquisition cost inside the agent loop* and manipulate recoverability directly via oracle injection.
- **Plans Don’t Persist** probes latent hidden states to show internal plans don’t survive compression. White-box probing of internal state vs our black-box observation of environment state (ERS); we make no claim about latent reasoning.
- **Memento** compresses the KV cache within a single inference. We study the cross-turn agent context — the trajectory persisting across tool calls — and the interaction budget spent re-acquiring environment state.
- **ACON** shows failure-aware compression can match full-context performance. Their target is “compression should not hurt”; we reproduce a near-lossless summary in our setup, and show the divergence appears only when execution-relevant state is dropped (sliding), consistent with our claim that compression quality depends on which execution-relevant state is preserved.

- **VISTA** provides lossless archival recovery of exact bytes (bulky blocks archived as external payloads with stable handles and restored on demand). We show that exercising such recovery is itself a cost continuum under a hard budget: even recoverable task-graph state costs real turns to re-fetch, and that cost can become consequential for performance under a bounded interaction horizon.
- **Less Context, Better Agents** shows that pruning plus summarization can improve completion while cutting tokens and runtime in an enterprise tool-use workflow. Their evaluation is a configuration-choice question — which context-management strategy performs best — reported on completion, tokens, and runtime jointly, alongside a failure taxonomy. We ask a different question at a finer granularity: where the additional interaction goes (retrieval versus execution), and whether completion changes even when that interaction cost does. Our contribution is a decomposition and a diagnostic, not a competing configuration choice; the two are complementary.
- **CompressAgent** independently observes the same ordering we measure: tool-execution failures appear at milder compression, while task success collapses only under aggressive compression. Where they study compression reliability at scale, we isolate the mechanism — state reacquisition — under a controlled budget and intervene on it with oracle restoration.
- **Rate-distortion / memory surveys** explicitly flag a gap: agent-level repeated compaction is barely measured and no benchmark shares a budget axis across layers. We provide exactly the missing controlled experiment — operator $\times$ regime $\times$ model under a fixed interaction budget.

Prior work on context compression asks *what to keep, how well compression preserves information, whether surviving information is used, and which strategy wins on the aggregate outcome*. We ask a fifth question — **what it costs the agent to re-acquire what was dropped, and whether completion metrics expose that cost** — and show that this cost **can rise substantially while completion stays unchanged**:

“Compression is not costly merely because information is lost; it becomes costly when the state that was dropped must be re-acquired through additional interaction under a bounded budget.”

3 Method

Figure 1 (measurement protocol overview): an agent context feeds either a full / fact-preserving context or a compressed (sliding) context; missing execution state diverges into *retrieval* (reacquisition) versus *execute* (task work), which together consume the 24-turn horizon and determine completion / tool cost. A parallel oracle branch (compressed + $D^*/R^* \rightarrow$ dropped state injected $\rightarrow$ retrieval cost drops) shows recoverability is a manipulated variable, not a passive observation.

3.1 Evaluation outcomes, projections, and non-identifiability

We formalize the evaluation object this paper measures. For a context-management condition m we record a triple of measured outcomes.

Definition 1 (Evaluation outcome). $Y(m) = (Q(m), C_R(m), C_E(m))$, where Q is the task completion rate, C_R the number of retrieval tool calls, and C_E the number




Figure 1: Cost-first measurement protocol. Context conditions (Full; Sliding 5x; Summary 5x; ratio is a sweep parameter, §4.2) feed a bounded agent loop under a fixed 24-turn horizon. Missing execution-relevant state forces retrieval (re-querying the environment) instead of execution (task work); the two are interleaved within the horizon. The loop yields task completion and tool cost jointly — completion can stay flat while the interaction cost rises (Figs. 2–4). The oracle branch injects D^* (queryable) or R^* (history-dependent) state; restoration reduces retrieval cost, with different effects for D^* vs. R^* (Fig. 3).

Figure 1: Measurement protocol overview: full / fact-preserving vs. sliding (compressed) context; missing execution state diverges into retrieval (reacquisition) vs. execution (task work); a parallel oracle branch (compressed + $D^*/R^* \rightarrow$ injected dropped state $\rightarrow$ retrieval cost drops) makes recoverability a manipulated variable.

of execution tool calls, all recorded under a fixed interaction horizon. We interpret C_R as reflecting state re-acquisition effort and C_E as reflecting task work. We refer to $C = C_R + C_E$ as the *tool-level interaction cost* — the agent’s budgeted currency, not a claim about wall-clock or monetary cost.

Completion-centric evaluation applies a projection $\pi_Q(Y) = Q$ to this triple. We ask when such a projection can preserve the ordering of strategies by interaction efficiency. Let $\sim_Q$ denote that the pre-specified paired test (paired Wilcoxon signed-rank with Holm correction; Sec. 3.4) does not detect a completion difference between two conditions. A completion-only evaluation can preserve cost-aware ordering only if $m_1 \sim_Q m_2$ implies the two conditions also do not differ materially in interaction cost.

Proposition 1 (Non-identifiability of completion-only evaluation). The completion-only projection π_Q discards the interaction-cost dimensions of Y . Distinct outcome states with different interaction costs can therefore map to the same completion value. Under our protocol, this non-identifiability is realized empirically by conditions whose completion differences are not detected by the pre-specified paired test while their retrieval costs differ substantially.

Empirical counterexample. Full vs. Sliding (5x) on GPT-5.5 under High-IR: completion 80% $\rightarrow$ 85% (paired $p = 1.0$; 95% CI $[-6, +21]$ pp, containing zero), while retrieval 21.0 $\rightarrow$ 63.9 (paired $p = .002$; Cohen’s $d = 2.07$; 95% CI $[+31, +55]$, excluding zero). A completion-only evaluator would weakly prefer Sliding (85% vs. 80%), despite a roughly threefold increase in retrieval cost.

Note the claim is not that the two conditions are equivalent; it is that completion-only evaluation is blind to the cost dimension. At the metric level, any evaluation that projects the outcome to completion alone discards the interaction-cost dimensions by construction; the counterexample above

is an empirical instance in which this discarded dimension is large and operationally relevant (cost difference carries $d = 2.07$, while the completion difference is not detected). The direction of the completion change is immaterial: even if completion improved under compression, a completion-only evaluator would remain blind to the concurrent cost increase.

Cost-aware dominance. We say m_1 dominates m_2 if $Q(m_1) \geq Q(m_2)$ and $C(m_1) \leq C(m_2)$, with at least one inequality strict — a two-dimensional Pareto relation on (Q, C) . Completion-only evaluation cannot detect it, since π_Q collapses the cost dimension. The cleanest instance is Summary vs. Sliding at $5\times$ on DeepSeek High: Summary achieves higher completion (83% vs. 72%) with lower interaction cost (39.0 vs. 71.4). A completion-only evaluator correctly prefers Summary but cannot quantify how much better: the 11pp completion gap understates the 32.4-call interaction-cost gap. The decomposition $C = C_R + C_E$ attributes this cost gap almost entirely to retrieval (19.5 vs. 55.1; execution 19.5 vs. 16.3).

Completion-insensitivity region (descriptive). We use this term descriptively for (compression ratio, model) pairs where the retrieval cost increase under compression, $\Delta C_R = C_R(\text{compressed}) - C_R(\text{Full})$, is statistically detectable while the paired test does not detect a completion change (Cohen’s $d \geq 0.5$ as a secondary descriptive criterion). This is a descriptive characterization with conventional thresholds — not an equivalence test, and not a proposed metric; the term denotes an empirical pattern rather than proof of completion insensitivity. In our data (Fig. 3a), GPT-5.5 High at $5\times$ lies inside; DeepSeek leaves the region at $10\times$, where completion degradation becomes significant; Qwen High sits at the boundary, with retrieval only weakly elevated and completion modestly declining.

3.2 Agent and task environment

We study a minimal tool-using agent operating on a deterministic project-planning environment, which we refer to as **IRBench**. The environment exposes **10 tasks** and a small set of **resources** (each with capacity one). Tasks carry hidden execution constraints that are only revealed through interaction: ordering rules, resource holds with release times, and fail-until-success counts. The agent has four tools: `get_task_info`, `check_dependency`, and `query_resource` (all *retrieval*: they obtain environment state), and `execute` (*execution*: it performs a task and reveals constraints). The retrieval/execution split is central: it lets us measure reacquisition cost directly, without recourse to CoT or latent reasoning.

The environment is **deterministic**: a seed fully determines the world instance, so any condition can be replayed on the identical task set. We generate two task regimes by varying the density of hidden, execution-relevant facts while keeping static structure comparable (verified by environment self-checks): **High-IR** (constraints revealed only during execution, costly to lose once dropped) and **Low-IR** (multi-hop dependency chains, but state re-derivable from the public task graph). Concretely, a task may fail because it must follow another task, or because a resource remains held until a later event. The task graph and current resource state can be queried again at any time; a previously revealed failure condition or fail-until count, by contrast, exists only in the execution history.

The agent receives a fixed system prompt (identical across all conditions) instructing it to discover prerequisites, respect constraints, and complete all ten tasks within a **fixed interaction horizon of 24 turns**; each turn is one model call plus any tool results. Completion is judged by how many of the ten required tasks are finished when the horizon ends. We additionally compute an auxiliary **tool-budget statistic** ($\alpha \times$ the reference tool count, $\alpha = 2.0$); this is a *diagnostic*, not a termination criterion — the agent is never cut off by it.

Table 2: Context conditions.

Condition	Context
Full	the complete trajectory (baseline)
Sliding	a token budget of $r^{-1} \times$ the trajectory ($r = 1.7\times, 2.5\times, 5\times, 10\times$); greedily keep the most recent turns within budget; drop early turns outright
Summary	the same budget, but dropped early turns are replaced by a deterministic fact digest [Summary of earlier trajectory --- observed facts] (extractive; keeps observed state facts, discards the model’s reasoning text); zero extra LLM calls
Oracle	Full or Sliding context with a specific state string injected as a trailing message (same position in every condition)

3.3 Context conditions: operators and oracle interventions

We isolate the effect of compression by holding the task instance, system prompt, tool schema, and model fixed, and varying **only** the context delivered to the model. All compression conditions are applied online, at the same point in the agent loop, before each model response is generated — the context is rebuilt on every turn, so the operator sees exactly the trajectory accumulated so far. Turns are grouped into atomic units (an assistant message plus its tool results), so the context is always well-formed for the API.

Sliding is *deletion* (not summarization), so dropped state is genuinely absent — this tests “absent $\rightarrow$ reacquire,” not “present but ignored.” Summary shares the same token budget, making the operator contrast fair; extractive mode keeps out summarizer-quality confounds — our extractive summary preserves the observed state facts represented in the digest while discarding the trajectory’s reasoning text; it is a designed control, not a general summarizer. Oracle injection is a trailing message in a fixed position, leaving the system prompt untouched, preserving the same-prompt commitment across conditions.

The oracle supplies exactly the execution-relevant state that sliding drops, split into two recoverability classes: D^* — externally queryable state (the task graph: prerequisites, resource occupancy), recoverable in principle with more tool calls; and R^* — history-dependent state (revealed constraints, failure counts, held resources), not recoverable from any single public query. These are recoverability projections, not a data-versus-reasoning dichotomy. This gives us a manipulated independent variable — the availability of dropped state — allowing us to ask: *if the lost state were restored, how much of the compensatory retrieval disappears?*

3.4 Protocol and analysis

For each condition and model we run the same 10 seeds (10 task instances per seed, 100 task-level observations per condition); the retention-intervention family of Sec. 3.5 uses an extended **20 paired seeds** to bind the selection null (Sec. 4.6.1). Statistics are **per-seed paired** (same seed under both conditions): Wilcoxon signed-rank tests and bootstrap 95% confidence intervals on per-seed differences. We pre-specify the primary comparisons (Full vs. Sliding on task completion, tool calls, and retrieval calls). For multiple-comparison control, the primary family is the six retrieval comparisons (three models $\times$ two regimes); we apply Holm–Bonferroni correction at $\alpha = 0.05$, after which five of six remain significant. Remaining pairwise tests are exploratory. Models: **DeepSeek** (deepseek-v4-flash), **Qwen** (qwen3.7-plus), and **GPT-5.5**. All were evaluated without an explicit extended-thinking mode, at temperature 0.3, to keep the observable interaction protocol as comparable as possible across providers. Each model is served through an OpenAI-compatible

Table 3: Retention interventions.

Intervention	Selection rule
Sliding	recency baseline; no digest (recent turns only)
RAR-D	retain D-type atoms only
RAR-R	retain R-type atoms only
RAR-All	retain all atoms in observation order ($\approx$ Summary control)
RAR-TypeAware	retain all atoms, R-first (recoverability-prioritized)
Random	random subset of atoms (seeded)
Recent	most-recently-observed atoms
Hindsight	top- k by <i>offline</i> future re-access counts (reference)
D-Irrelevant	as TypeAware (R first), but D-budget filled with fabricated out-of-universe atoms

interface.

3.5 Retention interventions as causal probes

The oracle result (Sec. 4.4) shows that restoring dropped state reduces reacquisition cost. This raises a question about *granularity*: at what level does retained state matter to the agent’s interaction cost — how much is retained, which atoms are retained, and whether the retained content is valid and task-relevant? We address it with a family of retention interventions, applied online at a fixed compaction point (turn 10, t_c), each taking the observed trajectory up to t_c , extracting the set of observed state atoms, and re-rendering a compressed prefix under a **digest budget** $B \in \{265, 100, 50\}$ tokens — an independent resource axis that does not co-vary with the compression ratio. Every digest is injected at the same position with the same [State retention digest] format, followed by the most recent turns within the total budget. Atoms are split into the D/R classes of Sec. 3.3. We log the retained coverage per class (cov_D , cov_R) and the actual rendered digest size, so the requested budget and the delivered digest are both reported.

The candidate universe is strictly online: the atoms observed before t_c , so no condition sees future observations. **Hindsight** is an offline reference, not an upper bound; we call it an *offline hindsight oracle under the reference trajectory*. The recoverability-prioritized ranking (R before D) is a pre-registered hypothesis being *tested*, not an assumed ordering — the Random and Recent controls exist precisely to test whether ranking beats selection that ignores it. The digest budget B is the independent variable of a budget sweep (all interventions at all three budgets).

Pre-registration and the D-Irrelevant control. We pre-registered the primary comparison (RAR-D vs. Sliding on retrieval cost, criterion $\Delta C_R \leq -30\%$ with a 95% CI excluding zero) and the condition matrix above. As reported in Sec. 3.5, the fine-grained selection null (Random $\approx$ Hindsight) emerged at $N = 20$, prompting a mechanistic follow-up: the **D-Irrelevant** intervention, which holds the digest format, position, budget, and retained R content fixed and replaces only the D atoms with fabricated out-of-universe state (identifiers outside the task/resource universe, so no entity can be confused with the current world). Its judgment criterion ($\Delta C_R = C_R[\text{D-irrelevant}] - C_R[\text{TypeAware}]$, paired 95% CI) was fixed before the intervention ran. We report it transparently as a post-hoc sequential diagnostic rather than a pre-registered primary.

Table 4: DeepSeek, High regime: severity sweep.

ratio	completion	tools	retrieval	execute	turns
1× (Full)	83%	39.5	22.2	17.3	22.9
1.7×	87%	42.7	25.4	17.3	23.3
2.5×	81%	49.7	33.3	16.4	22.8
5×	72%	71.4	55.1	16.3	23.1
10×	66%	77.1	63.2	13.9	23.6

4 Experiments

4.1 Setup

We follow the protocol of Sec. 3. Unless stated otherwise, “completion” is the fraction of the ten required tasks completed within the fixed 24-turn horizon; “tools” is the per-run tool-call count, decomposed into retrieval and execution calls. Each condition runs on 10 seeds, analyzed per-seed paired (Wilcoxon signed-rank; bootstrap 95% CI); primary comparisons are Full vs. Sliding on completion, tools, and retrieval calls.

4.2 Compression raises reacquisition cost before completion may degrade (Figure 2)

Sweep, DeepSeek (High). Varying compression severity with the sliding-window operator ($r \in \{1, 1.7, 2.5, 5, 10\}$) on High-IR:

Completion is flat through moderate ratios — the small uptick at 1.7× (87% vs. 83% at Full) is within run-to-run noise and consistent with mild compression removing stale or distracting state, the mechanism behind “less context, better agents”; it does not persist — and declines only at the two most aggressive ratios (5×: −11pp, $p = .25$ NS; 10×: −17pp, $p = .016$). This is the only completion change in our study to reach significance, and it does so only at the most aggressive ratio. Retrieval, by contrast, is already significantly elevated at 5× ($p = .002$): the cost signal responds at milder compression than completion does (Sec. 4.5). Moderate compression does not yield a monotonic completion decline; the more stable signal is the accompanying growth in interaction cost. Tool calls increase monotonically from 2.5× onward, with paired differences significant under our pre-specified test: tools rise from 39.5 to 77.1 (+**37.6** at 10×, $p < .01$). The decomposition shows *where* the extra interaction goes: retrieval calls rise from 22.2 to 63.2 (+**41.0**, $p < .01$), while **execute calls do not increase with severity** (they fall from 17.3 to 13.9). Compression does not make the agent attempt more task work; it makes the agent spend more interaction re-acquiring state that was dropped. Across independent collections the full-context baseline varied by only a few percentage points (80–86%), within the run-to-run variability of this stochastic setting; we use the canonical sweep for all primary comparisons.

Regime contrast (Low). Under Low-IR the same operator is near-costless in completion (100% at every ratio until 10×, 97%) while the tool response is preserved: tools rise 32.7 → 59.7 (+83% at 10×), retrieval-dominated. Low-IR’s state is re-derivable from the public graph, so the additional reacquisition cost remains small enough to preserve completion within the evaluated horizon.




Figure 2: Compression raises reacquisition cost before completion may degrade. Panel A: completion vs. compression ratio; Panel B/C: tool / retrieval–execution decomposition.

Table 5: Operator contrast at 5 $\times$, High regime (DeepSeek).

condition (5 $\times$, High)	completion	tools	retrieval
Full	80%	37.4	19.0
Sliding	72%	71.4	55.1
Extractive Summary	83%	39.0	19.5

[†] Sliding is the 5 $\times$ condition of the canonical sweep (Sec. 4.2); Full and Summary come from a separate operator-contrast batch. Full-context completion varied 80–86% across batches (Sec. 4.2), so the Sliding–Summary gap (72% vs. 83%) exceeds the batch-level spread of a few points.

4.3 What is retained matters more than the ratio (operator contrast)

The same 5 $\times$ budget can be spent two ways: sliding (drop old turns) or extractive summary (compress old turns into observed state facts). Holding budget and model fixed:

With the identical compression ratio, the summary operator is near-lossless (completion 83% $\approx$ full 80%; tools flat 37.4 $\rightarrow$ 39.0), while sliding degrades completion and triples retrieval. The extractive operator preserves observed state facts while discarding the trajectory’s reasoning text; sliding drops both. This controlled contrast indicates that **what survives compression can matter more than the compression ratio itself**. It also reproduces ACON-style “compression need not hurt” — but only for the operator that preserves state facts, which is consistent with our claim.

4.4 Restoring dropped state reduces reacquisition (oracle intervention)

To make the causal link explicit, we inject the exact dropped state back into the sliding context as a trailing message (D^* = queryable task graph; R^* = history-only constraints/fail-counts):

Restoring D^* removes most of the compensatory retrieval (72.9 $\rightarrow$ 35.8 tools) and recovers most of the completion gap (66% $\rightarrow$ 80%). Injecting R^* helps completion (+12pp) but leaves the retrieval cost high (69.0), because R^* is history-only and its absence is what forces defensive re-querying of D . The sanity condition (full + R^*) is harmless (85% $\approx$ full 86%), confirming that oracle injection does not distort the baseline. The intervention provides causal evidence that removing execution-relevant state increases reacquisition behavior, while restoring state reduces that behavior.

Table 6: Oracle intervention at $5\times$, High regime (DeepSeek).

condition ($5\times$, High)	completion	tools	Δ tools vs sliding
Full	86%	38.8	—
Sliding	66%	72.9	—
Sliding + R^*	78%	69.0	−3.9
Sliding + D^*	80%	35.8	−37.1
Full + R^* (sanity)	85%	32.1	—

Table 7: Three models, Full vs. Sliding ($5\times$), both regimes.

Model	regime	completion Full $\rightarrow$ $5\times$	Δ (p)	tools Full $\rightarrow$ $5\times$	retrieval Δ (p)	execute Δ
DeepSeek	High	83 $\rightarrow$ 72	−11 (0.25)	39 $\rightarrow$ 71	+32.9 (.002) [†]	−1.0
Qwen	High	75 $\rightarrow$ 66	−9 (0.13)	34 $\rightarrow$ 37	+2.9 (.088)	$\approx$ 0
GPT-5.5	High	80 $\rightarrow$ 85	+5 (1.0)	39 $\rightarrow$ 82	+42.9 (.002) [†]	$\approx$ 0
DeepSeek	Low	100 $\rightarrow$ 100	0	33 $\rightarrow$ 55	+22.6 (.004) [†]	+0.1
Qwen	Low	100 $\rightarrow$ 94	−6 (0.25)	28 $\rightarrow$ 36	+5.3 (.023) [†]	+2.7
GPT-5.5	Low	100 $\rightarrow$ 100	0	26 $\rightarrow$ 49	+22.4 (.002) [†]	+0.7

[†] $p < .05$ after Holm–Bonferroni correction across the six-comparison retrieval family ($\alpha = 0.05$); Qwen High retrieval is the single non-significant cell.

4.5 The cost generalizes; the outcome does not (three models)

We repeat the Full vs. Sliding ($5\times$) comparison on Qwen (qwen3.7-plus) and GPT-5.5 (High and Low):

The comparison point is pre-specified. The six-cell matrix uses a single compression ratio, $5\times$, fixed in the design of Experiment A (fraction = 0.2) — before the severity sweep revealed where completion degrades. We evaluate one representative point per model rather than a full sweep because the three-model matrix runs under a shared API budget; $5\times$ is the pre-registered main comparison, and DeepSeek’s full severity sweep is reported separately (Sec. 4.2). This is not an attempt to avoid a significant completion result: DeepSeek’s completion does become significant at $10\times$ ($\Delta - 17\text{pp}$, $p = .016$), and that is consistent with — indeed predicted by — our claim. The cost signal (retrieval) is significant already at $5\times$ ($p = .002$), while completion responds only at the most aggressive ratio ($10\times$): completion is the less sensitive measure. If one measured only completion at $5\times$ — the shallow-compression operating point many production systems run at — one would conclude compression is lossless while retrieval is already elevated.

Across our six model–regime comparisons, retrieval tool calls increased in every comparison and execution calls remained approximately stable in five of six comparisons; five of six retrieval increases remain significant after Holm–Bonferroni correction across the pre-specified family ($p = 0.002, 0.002, 0.002, 0.004, 0.023, 0.088$). Completion is more heterogeneous, and none of its changes reach significance (all $p \geq 0.125$): DeepSeek’s high-compression degradation is suggestive but not significant (-11pp , $p = .25$), Qwen is largely insensitive — its retrieval response is also the weakest ($p = .088$), possibly reflecting reliance on inference rather than re-querying when state is missing — and GPT-5.5’s completion is statistically unchanged ($p = 1.0$) while it pays the largest reacquisition cost (+110% tools, entirely retrieval). The reacquisition pattern is consistent across the models in our study; its conversion into reduced completion is not. This heterogeneity is the boundary condition of our claim, not a contradiction. (The cross-model comparisons use the same task seeds within each model but are not intended as paired comparisons across models.)

Two axes, not one (Figure 3). Consistent with the dose-response pattern of Sec. 4.2, the six




Figure 3: Two axes, not one. (a) Phase map of the six model-regime cells in $(\Delta\text{retrieval}, \Delta\text{completion})$ space; (b) tool decompositions.

cells occupy a two-dimensional space rather than a single success axis (Fig. 3a): high retrieval growth with completion loss (DeepSeek High), high retrieval growth with completion stable (GPT-5.5 High, and both Low cells), and little retrieval growth with a mild completion drop (Qwen). Completion changes are not significant in any cell (all $p \geq 0.125$), whereas five of six retrieval increases survive Holm correction — the two quantities are related but not interchangeable outcomes. Compression sensitivity is therefore two-dimensional: interaction cost and task completion occupy distinct axes (no regression is fitted; the figure is a qualitative phase map). GPT-5.5 High is the sharpest illustration: the paired test does not detect a completion change ($p = 1.0$; the wide CI $[-6, +21]$ pp reflects high run-to-run variance at this operating point) while retrieval roughly triples ($+42.9$, $p = .002$). Panel (b) shows the same cells as tool decompositions: the added calls are almost entirely retrieval, with execution approximately flat.

4.6 Retention interventions reveal two distinct levels of state dependence (Figure 4)

We now report the retention-intervention matrix (Sec. 3.5) on DeepSeek (High regime, 20 paired seeds; 540 runs total — the main matrix is 25 runs per seed [sliding at $B = 265$ plus eight interventions at three budgets] for 500 runs, plus the D-Irrelevant control at $B \in \{265, 100\}$ for 40 more). The results separate two questions that the compression sweeps of Sec. 4.2 conflate: *which* atoms are retained, and *whether the retained content is valid and task-relevant*.

4.6.1 Selection null: which atoms are retained does not matter

Most structured digests reduced retrieval cost relative to the recency baseline, but the magnitude did not depend reliably on the selection policy:

Random selection matches the offline hindsight oracle (-22.1% vs. -22.4% ; paired difference $+0.10$, 95% CI $[-2.3, +2.3]$, $d \approx 0.02$). Recoverability-prioritized retention (TypeAware) does not beat Random or Recent on retrieval cost or completion (all paired comparisons n.s.). Coverage structure holds — TypeAware keeps $\text{cov}_R \approx 1.0$ across budgets while the unranked RAR-All digest collapses cov_R from 0.30 to 0.00 as the budget tightens — but this coverage advantage does not translate into differential cost or completion. R-type state is inherently compact (~ 35 tokens, so the R-only digest is identical at every budget), which is why even the tightest budget leaves R fully retained.

The paired selection effect is small: with 20 paired seeds, the observed paired differences and

Table 8: Selection null at $B = 265$ (DeepSeek, High).

policy ($B = 265$)	ΔC_R vs Sliding	p
RAR-All	-26.0%	<0.001
RAR-TypeAware	-24.5%	<0.001
Hindsight	-22.4%	0.001
Random	-22.1%	0.001
Recent	-20.4%	0.002
RAR-D	-17.8%	0.002
RAR-R	-4.8%	n.s.

Table 9: D-Irrelevant content intervention at $B = 265$ (DeepSeek, High).

metric	TypeAware (real D)	D-Irrelevant	Δ	95% CI	p
C_R (retrieval)	20.4	31.9	+11.5	[9.2, 13.9]	<0.001
tools	37.6	48.2	+10.7	[8.1, 13.4]	<0.001
execute	17.2	16.4	-0.8	[-1.9, +0.2]	n.s.
Q (completion)	75.0	81.0	+6.0 pp	[-2.5, +16.0]	0.41

their 95% CI rule out large selection benefits in this experiment, an order of magnitude smaller than the content effect below. While a larger N could in principle detect a marginal difference, the practical conclusion is that fine-grained selection among real, task-relevant atoms has low marginal value in this setting relative to the coarse content-validity effect.

4.6.2 Content intervention: the D-Irrelevant control

The selection null leaves open whether the digest’s *content* matters at all, or whether any D-shaped text occupying the budget is equivalent. The D-Irrelevant control holds the digest format, position, budget, and retained R content fixed and replaces the D atoms with fabricated out-of-universe state. At $B = 265$ the effect is large and uniform:

All 20 seeds show the retrieval increase (range +3 to +23); the increment is entirely in retrieval, with execute unchanged. Semantically irrelevant state injection is *harmful*: D-Irrelevant’s retrieval exceeds even the no-digest sliding baseline (+18%, $p = 0.002$). We report this as a post-hoc sequential diagnostic (see Sec. 3.5): semantically irrelevant state injection induces additional verification and retrieval behavior. Whether that added retrieval reflects semantic irrelevance itself or verification of internally inconsistent state content is a finer mechanistic distinction we leave for future work; both readings support the claim that **state content is behaviorally load-bearing**.

4.6.3 Budget dependence: content matters when the digest dominates the window

The content effect is not budget-invariant. At $B = 100$ the same comparison is null ($\Delta +0.6$, 95% CI [-2.4, +3.4], $p = 0.60$, $d \approx 0.09$): the ~ 77 -token digest is a minor fraction of the compacted window, and the agent leans on the recent turns, so real-versus-irrelevant content is behaviorally invisible. At $B = 265$ the digest (~ 209 tokens) dominates the compressed window and content becomes load-bearing. Content relevance therefore matters as the interaction *content* $\times$ *budget*: coarse, valid, task-relevant D content reduces retrieval at loose budgets, fine-grained selection among such content does not, and the distinction only becomes behaviorally visible when the digest occupies a substantial share of the context.

Retention interventions: real vs. irrelevant D content is load-bearing; fine-grained selection is not (B decreases left to right)




Figure 4: Retention interventions. Digest budget B decreases from left to right in (a)–(b). (a) ΔC_R vs. Sliding (%): TypeAware (real D) and D-Irrelevant are highlighted against the faded remaining policies; the $\sim 57\%$ retrieval gap at $B=265$ leaves completion statistically unchanged. (b) task completion ($\approx$ flat across policies and budgets). (c) coverage dose-response ($cov_D \rightarrow \Delta C_R$) with the selection null (Random $\approx$ Hindsight) and the D-Irrelevant point at $B=265$.

Consistent with this, in our setting recency is a competitive approximation to recoverability-aware selection under tight budgets, and when the retention budget is tight, preserving history-dependent (R) state is strongly favored by the intervention results — because R is compact enough to retain fully at any budget, and dropping it is what inflates defensive re-querying of D (the RAR-D cell of Sec. 4.6.1).

4.6.4 Cross-model replication of the content intervention

To test whether the content-relevance effect is specific to DeepSeek, we replicate the key conditions on GPT-5.5 (High regime, $B \in \{265, 100\}$, 10 paired seeds). The content-relevance effect **replicates across models at the loose digest budget**, while its magnitude and budget dependence are model-specific. At $B = 265$, the direction matches DeepSeek exactly (real $<$ irrelevant $<$ sliding on retrieval): GPT-5.5’s real-D digest reduces retrieval relative to sliding (-9.5 , $p = 0.002$) and its D-Irrelevant control raises retrieval back up ($+7.3$ vs. real D, $p = 0.006$), while completion is statistically unchanged (78% vs. 74%, $p = 0.125$). The content-relevance mechanism is therefore not model-specific.

Three model-dependent boundaries are worth reporting honestly. First, GPT-5.5’s irrelevant injection does **not** exceed the raw sliding baseline (27.4 vs. 29.6) as it did in DeepSeek (+18%); the poisoning intensity is model-dependent. Second, at $B = 100$ no additional content effect was detectable in GPT-5.5 (irrelevant 26.0 vs. real 28.8, $p = 0.125$), consistent with DeepSeek’s near-zero effect at the tighter budget. Third, the mechanism of the GPT response differs in composition: the irrelevant injection reduces execute calls (-2.4 , $p = 0.035$) rather than increasing retrieval, suggesting a model-specific error-correction strategy. We therefore state the result as: the *direction* of the content effect is reproducible, while its *behavioral expression* is model- and budget-dependent.

4.7 External environment boundary: ALFWorld

To test whether the reacquisition signature is an intrinsic consequence of shortening context — or depends on the environment’s recoverability structure — we run the same Full vs. Sliding contrast in ALFWorld, a household instruction-following domain whose observations are produced by the

Table 10: External environment boundary.

Environment	Compression	Δ retrieval-like actions	Δ completion
IRBench (this work)	Sliding	large positive (2–3 $\times$)	model / regime dependent
ALFWorld	Sliding	≈ 0 (paired, symmetric)	small / ceiling-bound

External environment boundary: the reacquisition signature is environment-dependent, not an intrinsic cost of compression




Figure 5: External environment boundary: paired Δ retrieval-like actions under the same sliding operator are large and positive in IRBench and ≈ 0 (symmetric) in ALFWorld.

TextWorld engine. We sample 18 tasks across all six ALFWorld task types (three tasks per type) and run 5 paired seeds per task (180 runs; all complete, zero API errors). Retrieval-like actions (look / examine / inventory) are counted separately from execution-like actions (take / put / clean / heat / cool / use) and navigation (go).


In our ALFWorld probe, the relevant state could generally be re-observed directly through the available interaction actions, and we did not observe a retrieval surge under sliding compression: paired $\Delta(\text{retrieval-like}) = -0.13$, split 39/35 across seeds (symmetric around zero); Δ tools ≈ 0 ; and completion did not differ (full 10.0% vs. sliding 8.9%, with 89/90 paired runs identical). Completion was dominated by the difficulty profile of the sampled tasks — only the simplest task type (look_at) was reliably solvable under this adapter — so we treat completion as a secondary outcome in this probe.

The reacquisition signature is therefore environment-dependent rather than an intrinsic consequence of shortening context. In IRBench, dropped task-graph state must be re-queried; in ALFWorld, the same loss does not force additional reacquisition under this adapter. This boundary is consistent with — indeed predicted by — our recoverability account: compression cost is not a property of the operator, but of *what execution-relevant state becomes unavailable and how that state can be reacquired*.

4.8 The interaction budget: turn horizon and tool budget

Our auxiliary tool budget ($\alpha \times$ reference, $\alpha = 2.0$) is a diagnostic, not a termination criterion — the agent is always cut off by the 24-turn horizon. The two quantities tell different halves of the story (DeepSeek, High):

- **Turn horizon is binding in every High condition**, including Full: 7/10 Full runs and 8–9/10 compressed runs terminate at `max_turns`. Compression does not *introduce* turn pressure;



Termination is governed by the fixed 24-turn horizon; the tool-budget curve is an auxiliary diagnostic of accumulated interaction cost.

Figure 6: Oracle conditions and the interaction budget: retrieval / execution decomposition, termination (all_complete vs. max_turns), and within-budget diagnostics.

it reduces how much task progress the agent fits into the same horizon (completion 83% $\rightarrow$ 66% at 10 $\times$).

- **The tool budget is the cost marker:** Full stays within the $\alpha \cdot 2.0$ budget in 10/10 runs; Sliding 5 $\times$ and 10 $\times$ stay within it in 0/10 runs. The reacquisition overhead is large enough to violate a reference execution budget that the full-context agent never approaches.

Termination reasons are recorded per run (all_complete / max_turns), so failed runs can be audited as turn-exhaustion rather than API errors; every reported condition has 10/10 completed runs.

5 Discussion

5.1 What the protocol measures, and why the metric matters

Our protocol decomposes the interaction cost of compression into state reacquisition (retrieval) and task work (execution). The headline observation is that **task completion is an incomplete measure of this cost**: across our six cells, retrieval increases are significant in five of six after Holm correction, while completion changes are not significant in any cell. GPT-5.5 is the sharpest illustration — completion statistically unchanged ($p = 1.0$) while retrieval roughly triples. Completion is not useless: it becomes a meaningful signal when reacquisition consumes enough of the interaction horizon to limit task progress, as for DeepSeek under high compression. But used alone, it under-states compression’s cost on robust models and over-states it on fragile ones. This is not an argument that compression “hurts” agents — our own data rule that out — but that the cost is real, decomposable, and visible in tool behavior before (or without) any change in completion. The mechanism behind the visible cost is a shift in *where* the agent spends its budget: under compression, the dominant shift is toward retrieval rather than execution, and that reacquisition is what the completion signal can miss.

5.2 Retention versus reacquisition: two separable sources of degradation

The contrast between our Sliding and Summary operators isolates the lever: with the same budget, the operator that preserves observed state facts is near-lossless, while the operator that drops them

degrades completion and triples retrieval. This separates *retention* (does the compressed artifact still contain the state?) from *reacquisition* (what does the agent do when it does not?). The two are complementary to the attention-centric account of lost-in-compaction: that line shows surviving text can be ignored; we show that *absent* state must be re-fetched, at a budget cost that is independent of attention. Runtime optimizations targeting one source of degradation will not address the other.

Why is the reacquisition cost dominated by retrieval? The oracle intervention (Sec. 4.4) isolates the mechanism. Restoring the externally queryable task graph (D^*) removes most of the compensatory retrieval (Sliding 72.9 $\rightarrow$ 35.8 tool calls, -51% ; paired $p = .002$) and recovers most of the completion gap (66% $\rightarrow$ 80%); restoring history-dependent state (R^*) improves completion (+12pp) but leaves retrieval nearly unchanged (72.9 $\rightarrow$ 69.0, -5% ; n.s.). The asymmetry follows from the environment’s recoverability structure (Sec. 3.3): D is queryable — a query restores it — so when it is lost the agent can recover it only by re-querying the environment, an interaction pattern documented in production agent systems as redundant retrieval or retrieval thrashing; R is history-dependent — no single public query restores it — so when it is lost re-querying cannot help and the agent proceeds under uncertainty, and the measured retrieval cost does not grow. The data are consistent with this account: the added retrieval under compression is almost entirely D-reacquisition (D^* restores it to near the full-context level), while completion depends on both state classes (both D^* and R^* restore most of the completion gap). We describe the pattern as a re-query loop because restoring the queryable state removes the added retrieval; we do not claim to observe the agent’s internal decision process.

The retention interventions (Sec. 4.6) refine *where* in this loop a retention decision bites. If the reacquisition cost is a re-query loop, the natural question is whether the runtime can reduce it by retaining the *right* state. Our answer is two-layered, and it separates two notions that retention policies usually conflate. *Within our D-state pool*, which real atoms are retained has little measurable marginal effect: random selection matches an offline hindsight oracle ($\Delta + 0.10$ retrieval calls, CI $[-2.3, +2.3]$) within a small budget of the best possible selection, because the externally queryable atoms are homogeneous in reacquisition cost. *Whether the retained content is valid and task-relevant* does matter: replacing the D atoms with semantically irrelevant state raises retrieval by 57% while completion stays statistically unchanged. State content is thus behaviorally load-bearing — the agent does not treat the digest as an inert anchor — but the granularity at which selection can exploit it is coarse (valid versus not), not fine (which valid atom). The same intervention shows the effect is budget-gated: it is visible only when the digest dominates the compacted window, so recency is a competitive approximation to recoverability-aware retention when budgets are tight.

Taken together, the four findings form a hierarchy of what drives interaction cost under compression — *state absence* (strong: dropping state inflates reacquisition), *valid content* (strong: replacing real D content with semantically irrelevant content raises cost 57%), *fine selection* (weak: choosing among valid atoms is bounded near zero), and *effect visibility* (budget-gated: the content effect appears only when the digest dominates the window). A retention decision is therefore consequential at the level of validity and presence, not at the level of fine-grained ranking, in this regime.

Two explanations for the selection null are compatible with our data. The D atoms are homogeneous — each is recoverable by a single public query at comparable cost — so retaining any real subset with equal coverage has equal reacquisition value. Alternatively (or additionally), the agent might not exploit fine-grained differences within a short horizon. The D-Irrelevant result favors the former: at $B = 265$ the agent demonstrably reacts to the digest’s D content (it re-queries more when the content is fake), so it is content-sensitive, and the within-class flatness is better attributed to D-atom homogeneity than to an inability to use the digest at all.

5.3 Implication for runtime design

For a runtime designer, the actionable quantity is not “which compression ratio is safe” but **“which execution-relevant state, if dropped, would the agent spend its budget re-acquiring?”** Our oracle results point to a concrete answer: externally queryable task state (the task graph and its constraints) is a major source of reacquisition cost, and restoring it removes roughly half the retrieval overhead. The retention interventions qualify how to act on this: preserving history-dependent state (R) is strongly favored when the retention budget is tight — it is compact enough to retain fully at any budget, and dropping it is what inflates defensive re-querying of D. Within the remaining D budget, fine-grained ranking buys little in our setting; what matters is that the retained content is real and task-relevant. Because the content effect is budget-gated, recency is a competitive approximation to recoverability-aware retention under tight budgets — a boundary we state for this setting rather than a general law.

A practical deployment checklist for diagnosing context-management cost. The protocol is not tied to our environment; it is a checklist any evaluator can apply to a context-management strategy. In practice: (1) hold the agent, task instance, and interaction horizon fixed; (2) record completion and interaction cost jointly; (3) where tool semantics permit, decompose interaction cost into retrieval and execution; (4) where causal attribution is needed, restore the specific dropped state as a control; and (5) report the capability outcome and the interaction overhead together. The conclusion connects directly to Proposition 1: a strategy that preserves completion but substantially increases reacquisition cost should not be treated as equivalent to the baseline solely on completion metrics.

5.4 The boundary: model, regime, and environment dependence

The reacquisition pattern is consistent across the three models in our study; its conversion into reduced completion is not (Fig. 3). We read this as a feature: the cost of compression is a property of the *agent-environment interaction*, while whether that cost becomes failure is a property of the *model’s* interaction pattern and the *task’s* recoverability. Evaluations of compression that report only completion may give a distorted view of cost, depending on how readily the model absorbs the extra interaction. Our two-axis result (Fig. 3a) makes this explicit: interaction cost and task completion are related but not interchangeable outcomes, so a cost-level diagnostic is needed to separate the two.

The environment adds a third boundary axis (Sec. 4.7): in ALFWorld, where the relevant state can be re-observed directly through the available interaction actions, sliding compression produces no retrieval surge at all — the cost signal is not an intrinsic consequence of shortening context. The *presence* of the cost, not only its magnitude, is therefore conditional on what execution-relevant state becomes unavailable and how that state can be reacquired. A complete account of compression cost thus spans three boundary conditions — model, task regime, and environment recoverability — and completion-only evaluation can miss the cost on every one of them.

5.5 Relation to the broader literature

We connect to four lines: methods that report cost as a byproduct (we decompose it); recoverability frameworks that treat it as a representation property (we measure it behaviorally, under a budget); attention-dilution accounts (we isolate a distinct, absent-state failure mode); and aggregate efficiency evaluation (we ask a finer question: where the additional interaction goes, and whether completion exposes it). The rate-distortion surveys’ named gap — no shared budget axis across layers — is precisely where our operator $\times$ regime $\times$ model matrix sits.

We therefore do not claim that context compression is intrinsically harmful or beneficial; we characterize the interaction cost it introduces and the conditions under which that cost becomes consequential.

6 Limitations

1. **Two bounded environments, both synthetic-adjacent.** The core mechanism is measured in IRBench, a synthetic constraint-planning domain (two regimes); an ALFWorld probe (Sec. 4.7) shows the reacquisition signature is environment-dependent — it disappears where the relevant state can be re-observed directly. We make no claim that specific cost magnitudes transfer to open-ended tasks, and future work should extend the probe to partially-observable, long-horizon environments (e.g., WebArena, SWE-bench) where reacquisition is consequential. The value is the *protocol* and the *decomposition*, which are environment-agnostic.
2. **Three models.** We evaluate three model families (DeepSeek, Qwen, GPT-5.5), which is not exhaustive. Cross-model comparisons are descriptive rather than paired, and we avoid interpreting absolute tool/token counts across providers (serving conditions are not fully comparable). Serving details are recorded in the reproducibility appendix.
3. **The 24-turn horizon is a design choice.** We evaluate under a bounded interaction budget because real agents always operate under one; an evaluation metric that is insensitive to a large interaction-cost increase *within* that budget is a structural limitation of the metric, not merely a matter of “not waiting long enough.” A different horizon could shift where the cost–failure conversion falls; we report the conversion as regime-dependent rather than universal, and note that the D-Irrelevant intervention (Sec. 4.6) changes cost sharply (and even raised completion directionally) within the same horizon — the completion signal did not expose the cost difference. A horizon sweep is left to future work.
4. **Tool-call count is a proxy for “cost”.** We deliberately measure the budgeted interaction currency — turns and tool calls — rather than provider-dependent wall-clock latency or dollar cost. This is a design choice: wall-clock and dollar costs are provider- and serving-dependent and would obscure the structural reacquisition signal we isolate.
5. **The retrieval/execution decomposition is tool-level.** It attributes each call to a schema, not to a semantic intention. The oracle results mitigate this (restoring state reduces the re-query volume), but a per-message intention analysis is out of scope. Turn-level temporal analysis of when retrieval bursts occur was likewise not feasible: per-run tool-call logs were aggregated to condition-level totals before storage. Instrumenting per-turn logging to study the temporal dynamics of reacquisition is left to future work.
6. **The extractive summary is our designed control, not a generic summarizer.** Its near-losslessness at $5\times$ is a property of the fact-preserving digest we define, and is the intended contrast to Sliding; it is not evidence that arbitrary LLM summarizers are lossless.
7. **Statistical power at 10 seeds.** The absence of significant completion changes at the pre-specified $5\times$ point is itself part of the finding: it shows completion is less sensitive to compression than the retrieval signal, which is significant in five of six cells after Holm correction. We treat the tool-level effect as the primary empirical result, report effect sizes and CIs for all comparisons, and note that the completion-side numbers are noisier. Pre-registered primary comparisons and Holm correction limit multiple-comparison risk.

8. **Single cross-model compression point.** The three-model matrix evaluates one compression ratio ($5\times$), fixed in the original experiment design and applied uniformly; only the DeepSeek condition has a full severity sweep (Sec. 4.2). This bounds how precisely we can compare completion across models at more aggressive ratios; the sweep is reported in full, including the $10\times$ point where DeepSeek completion first becomes significant.
9. **Two operators.** We evaluate a dropping operator (sliding window) and a fact-preserving extractive summary. The cost patterns of other operators — LLM-generated abstractive summaries, token-level compressors — remain to be characterized; we do not claim the specific magnitudes generalize.
10. **The D-Irrelevant fabrication is one kind of irrelevance.** The control (Sec. 3.5) replaces D atoms with fabricated out-of-universe entities, which the agent can detect as non-existent. The added retrieval could therefore reflect verification of inconsistent state content as well as semantic irrelevance per se; both readings support the load-bearing claim, but the finer decomposition (e.g., an “incorrect values on real entities” control) is left to future work. We also do not claim the effect is specific to “semantically irrelevant state” as opposed to any corrupt content.
11. **The selection null and content replication are each confirmed on a subset of models.** The selection null (Random $\approx$ Hindsight) and the coverage dose-response are measured on DeepSeek only; the GPT-5.5 subset replicates the content intervention (Sec. 4.6.4) but does not re-run the selection controls, so we do not claim the selection null is cross-model. The content effect is confirmed on two models (DeepSeek, GPT-5.5) at the loose budget; its magnitude and budget-gating remain model-specific.

A Seed-level association

We examine whether, within a model–regime cell, the per-seed cost increase is associated with the per-seed completion change, and whether this association varies across cells. For each of the six model–regime cells we computed, per seed, the paired change in retrieval calls ($\Delta C_R = C_R(\text{Sliding}) - C_R(\text{Full})$) and completion (ΔQ , pp) at $5\times$, and the Spearman correlation between them.

Table 11: Seed-level association between per-seed ΔC_R and ΔQ .

Model	Regime	ρ	p	95% bootstrap CI
DeepSeek	High	−0.40	.25	[−0.97, +0.49]
DeepSeek	Low	—	—	completion invariant across seeds
Qwen	High	−0.32	.37	[−0.75, +0.29]
Qwen	Low	+0.16	.67	—
GPT-5.5	High	−0.64	.045	[−0.84, −0.18]
GPT-5.5	Low	—	—	completion invariant across seeds

The direction is negative in all three High-regime cells, and GPT-5.5 High reaches nominal significance ($\rho = -0.64$, $p = .045$) with a bootstrap CI excluding zero: seeds with larger retrieval increases tend to show larger completion decreases, consistent with reacquisition consuming the interaction budget. The two Low-regime cells are undefined because completion is invariant across seeds (every seed completes all tasks in both conditions). We report these as exploratory, descriptive

within-seed associations, not causal estimates; given the small per-cell sample ($n = 10$) and multiple comparisons, the single significant cell should be read cautiously. We do not pool model–regime cells, because cross-cell heterogeneity in baseline difficulty and model response makes a pooled association difficult to interpret. The negative High-regime direction is consistent with — but does not establish — the re-query loop account of Sec. 5.

Acknowledgments

Portions of this manuscript, such as language translation and polishing, were developed with the assistance of AI language models. All experimental design, implementation, data collection, and analysis were conducted independently by the author.

References

- [1] M. Kang, W.-N. Chen, D. Han, H. Inan, L. Wutschitz, Y. Chen, R. A. Sim, and S. Rajmohan. ACON: Optimizing Context Compression for Long-horizon LLM Agents. In *ICML 2026*. arXiv:2510.00615.
- [2] MEMENTO: Teaching LLMs to Manage Their Own Context. Microsoft Research, 2026. arXiv:2604.09852.
- [3] B. Xu, H. Li, and K. Zhang. LLM Agents Are Latent Context Managers: Eliciting Self-Managed Context via a Proprioceptive Dashboard. arXiv:2606.30005, 2026.
- [4] RE-TRAC: REcursive TRAjectory Compression for Deep Search Agents. arXiv:2602.02486, 2026.
- [5] H. Jiang, Q. Wu, C.-Y. Lin, Y. Yang, and L. Qiu. LLMLingua: Compressing Prompts for Accelerated Inference of Large Language Models. arXiv:2310.05736, 2023.
- [6] N. Trukhina and V. Vashkelis. Compress the Context, Keep the Commitments: A Formal Framework for Verifiable LLM Context Compression. arXiv:2605.17304, 2026.
- [7] A. Kwon. Reclaim Evaluation: A Lossy Memory Is Worse Than an Empty One. arXiv:2606.25449, 2026.
- [8] Lost in Compaction: Measuring Information Loss in LLM Context Summaries. Zenodo record 20273815, 2026.
- [9] A. Lodha, M. Pahlavikhah Varnosfaderani, A. Chakraborty, and A. Mithal. Less Context, Better Agents: Efficient Context Engineering for Long-Horizon Tool-Using LLM Agents. arXiv:2606.10209, 2026.
- [10] A. Yehudai, L. Eden, A. Li, and G. Uziel. Survey on Evaluation of LLM-based Agents. arXiv:2503.16416, 2025.
- [11] J. Liu, C. Qian, Z. Su, and Q. Zong. CostBench: Evaluating Multi-Turn Cost-Optimal Planning and Adaptation in Dynamic Environments for LLM Tool-Use Agents. arXiv:2511.02734, 2025.
- [12] Y. Hou and Z. Yang. Control Under Compression: Reliability Frontiers for Tool-Using Agents. arXiv:2608.01056, 2026.

- [13] D. Hou, L. Jiang, D. Li, and Z. Li. Beyond Completion: Probing Cumulative State Tracking to Predict LLM Agent Performance. arXiv:2603.27343, 2026.
- [14] A. Khanal, Y. Tao, and J. Zhou. Beyond pass@1: A Reliability Science Framework for Long-Horizon LLM Agents. arXiv:2603.29231, 2026.
- [15] C. Ma, J. Zhang, Z. Zhu, and C. Yang. AgentBoard: An Analytical Evaluation Board of Multi-turn LLM Agents. arXiv:2401.13178, 2024.
- [16] T. Sah, V. Srivastava, D. Sah, and K. Jordan. The Verifier Tax: Horizon Dependent Safety Success Tradeoffs in Tool Using LLM Agents. arXiv:2603.19328, 2026.
- [17] K. Zhang, Z. Xiong, M. Zhong, and Z. Jiang. Are Tools All We Need? Unveiling the Tool-Use Tax in LLM Agents. arXiv:2605.00136, 2026.
- [18] I. Bogdanov, C.-H. Lung, T. Kunz, J. Gao, A. Taylor, and M. Zaman. Context, Reasoning, and Hierarchy: A Cost-Performance Study of Compound LLM Agent Design in an Adversarial POMDP. arXiv:2605.16205, 2026.
- [19] S. Weinberger and A. Hozez. Token Reduction Is Not Cost Reduction. arXiv:2607.12161, 2026.
- [20] Factory AI. Evaluating Context Compression. Research report, 2025.
- [21] context-clock: a benchmark for truncation vs. recall. GitHub: [bolnet/context-clock](https://github.com/bolnet/context-clock).
- [22] T. Lindenbauer, I. Slinko, L. Felder, E. Bogomolov, and Y. Zharov. The Complexity Trap: Simple Observation Masking Is as Efficient as LLM Summarization for Agent Context Management. arXiv:2508.21433, 2025.
- [23] A. G. Colaco and N. Lahjouji. What to Keep, What to Forget: A Rate-Distortion View of Memory Compaction in LLMs and Agents. arXiv:2607.08032, 2026.
- [24] A. Nagle, A. Girish, M. Bondaschi, and M. Gastpar. Fundamental Limits of Prompt Compression: A Rate-Distortion Framework for Black-Box Language Models. arXiv:2407.15504, 2024.