

The Civilization Framework: Sovereign-Anchored Communication Between Personal Multi-Agent Systems

Guangjun Liu
New York University
gl2980@nyu.edu

Preprint, September 2026

Abstract

In professional collaboration, humans have quietly become the transport layer between AI systems: one person’s assistant produces an artifact, the person relays it through chat or email, and the counterpart re-feeds it to their own assistant, losing environment details, versions, and constraints at every hop. We argue that the natural unit of AI-mediated collaboration is not the individual agent but what we call a *civilization*: one human sovereign together with their persistent ledger and the interchangeable agents that act on it. The name is deliberate on two grounds: in the AI era a single person commands civilization-scale knowledge and, with agents, civilization-scale capacity to act; and the unit has a civilization’s defining structure, outliving every agent that serves it while preserving memory and norms. We present the Civilization Framework, a conceptual architecture in which civilizations, not agents, are the addressable parties, and the Embassy Protocol, a carrier-agnostic overlay in which a resident ledger endpoint receives communication asynchronously (store-and-forward), any online agent of the receiving civilization can claim and process it, and commitment state recorded on both ledgers, not message delivery, constitutes the ground truth of the exchange. Authority in the framework derives from memory: an agent’s power to represent its civilization is capped by the scope of memory it can access, externalized to counterparties through signed credentials, and separated from a civilization-level reputation earned across exchanges. We further identify a hazard acute in AI-to-AI communication, the *temporal-weight* effect, in which information that arrives first acquires unearned authority, and test it in one frontier model in a preregistered experiment of 1,908 trials. The observed pattern is large: with verification capability removed, an incorrect upstream claim arriving first captures 54.2% of answers (4.2% under full verification), while the same claim arriving after the receiver has sealed its own answer captures 31.6%, separating arrival order from mere exposure (the first-arrival and sealed-answer prompt shells are not length-matched, so part of that difference may reflect shell form; see §7), and both registered question-set specifications agree on these two verdicts (the exclusion specification is registered in advance as under-powered). Two secondary results, the mitigation from instruction-level provenance labeling and the equivalence of sealed-answer accuracy, are specification-dependent and hold only under the all-questions specification. Because the registered objective read-back of tool use failed its call-budget condition, the registration classifies this round as inconclusive and every result above, primary and secondary alike, is reported as exploratory; a replication with harness-enforced budgets is planned. The pattern suggests protocol-level mitigations at the capability and procedure level; that reading is an interpretation, not a registered result. The framework is grounded in a working reference implementation of its intra-civilization layer and positioned against forty years of agent-communication research, from speech-act semantics through social commitments to today’s A2A and MCP protocol stack.

1 Introduction

Consider two engineers collaborating on a deployment. Each works with a capable AI assistant. The backend engineer’s assistant produces an installation guide; the engineer pastes it into a chat application; the frontend engineer forwards it to her own assistant, which discovers that the guide omits the local environment configuration and the pinned dependency versions. A question travels back through both humans. Three round trips later, the missing constraint is finally identified. Every hop crossed two human relays, each asynchronous, forgetful, and lossy.

We call this the *porter problem*: in AI-assisted professional work, humans have become the transport layer between AI systems. The artifacts humans relay (documents, chat messages) are lossy snapshots curated for human reading; the information that AI systems actually need to synchronize (environment fingerprints, version manifests, implicit constraints) is precisely what such snapshots omit. Meanwhile the AI systems on both ends maintain rich, structured state about their respective sides, state that direct synchronization could reconcile without the human round trips.

The cost has begun to be named and measured outside academia: an industry survey describes employees as “human middleware” who lose the better part of a workday each week relaying context between disconnected AI systems [1], and recent HCI work observes users acting as “human glue,” restating intent and stitching tools together [2]. The diagnosis, however, has no protocol-level treatment, and to our knowledge no peer-reviewed controlled measurement of the relay cost itself exists (§7). In economic terms the porter is a transaction cost of collaboration [3, 4], and the framework’s answer is deliberately not the classical remedy of merging the transacting parties: sovereigns stay separate, and the protocol supplies the governance between them.

The emerging agent-interoperability stack does not address this problem at the right level. The Model Context Protocol (MCP) [5] standardizes how one agent reaches its own tools; the Agent2Agent protocol (A2A) [6] standardizes how one agent delegates a task to another. Both are *agent-addressed*: they assume the meaningful endpoint is a running agent. But agents in practice are ephemeral processes; the durable entity behind them is a person, their accumulated preferences and norms, and the persistent record of their projects. When the frontend engineer’s laptop sleeps, her agents die; her *context* does not.

Thesis. We argue that the natural unit of cross-party AI communication is the *civilization*: one human sovereign, the persistent ledger that outlives every agent session, and the interchangeable agents that act on that ledger. Communication should be civilization-to-civilization: asynchronous, ledger-anchored, and independent of which particular agent (if any) happens to be online. Humans do not leave the loop; they move up in it, from relaying bytes to arbitrating disagreements and authorizing commitments.

Contributions. This paper makes four contributions:

1. **The civilization abstraction** (§2): four defensible axioms and a scoping premise from which the unit of cross-party communication is derived, an operational definition of a sovereign-anchored governance domain, a three-level ontology (creator, civilization, project), and an internal/external dichotomy principle that assigns different convergence semantics to same-sovereign synchronization versus cross-sovereign diplomacy.
2. **The Embassy Protocol** (§4): a carrier-agnostic communication overlay built on three unified artifacts (the inbound channel, the task board, and the commitment ledger are

one object), with a three-tier signing discipline that preserves asynchrony for routine synchronization while requiring bilateral countersignature for state-changing judgments.

3. **Memory-derived authority** (§5): a model in which an agent’s power to represent its civilization is capped by the scope of memory it can access (its representation scope), externalized through signed credentials, and complemented by civilization-level reputation, with a negotiated identity-disclosure ladder.
4. **The temporal-weight effect** (§6, §7.3): an analysis of implicit hierarchy in AI-to-AI transmission; a preregistered five-condition by two-verification-level (nine-cell) experiment with 53 questions and 1,908 trials in which, in one frontier model, adoption of incorrect upstream claims was gated by verification capability (4.2% under full verification vs. 54.2% under restricted verification) and weighted by arrival order (54.2% first vs. 31.6% after a sealed answer, both under restricted verification; the first-arrival and sealed-answer prompt shells are not length-matched, so part of that gap may reflect shell form), with both registered question-set specifications agreeing on these two verdicts (the exclusion specification is registered in advance as under-powered), reported as exploratory because a registered manipulation check failed its call-budget condition; and protocol mechanisms that replace arrival order with earned trust as the source of epistemic weight.

The framework is not speculative: it is distilled from a working multi-agent operating system that the author operates daily, whose ledger currently coordinates dozens of concurrent agents across hundreds of tasks (§7). We deliberately publish the conceptual architecture while the reference implementation matures, because the field is converging fast on adjacent designs (statelessness in MCP’s 2026 revision, server-side task state in A2A, commitment protocols being bridged to A2A) and the missing piece is not another wire format. Recent analyses concur that a governance layer above the interoperability standards is missing [7]; this paper contributes a person-anchored construction of that layer.

2 The Civilization Abstraction

2.1 Four Axioms and a Scoping Premise

The framework is best read not as a taxonomy but as the solution to a constraint system. Four axioms, each independently defensible, and one scoping premise generate the structure of this paper.

- A1 Accountability terminus.** Every cross-boundary act must have a durable, legally capable responsibility terminus. This is settled law, not philosophy (§2.6).
- A2 Ephemeral members.** Agent instances are short-lived and hold no authoritative state; the infrastructure layer is converging on the same axiom independently [8, 9].
- A3 Heterogeneous carriers.** No common platform may be assumed: communication must ride the channels people already use, since two-sided platform adoption is the graveyard of security protocols [10].
- A4 Adversarial counterparties.** Cross-sovereign input is untrusted input; injection [11], forgery, and Sybil pressure [12] are assumed.
- P1 Personal scope.** The target setting is personal multi-agent systems, one human sovereign per system. This is a scoping premise, not an axiom: for organizations the sovereign

generalizes to a legal person and the framework carries over.

The derivation, in brief. A1 and A2 jointly force the unit of identity: it cannot be an agent instance, which is short-lived and cannot bear responsibility, so it must be the durable pair of a legal person and a record that outlives every member; with P1 the person is a human, and we call the pair a *civilization*. The name is chosen on two grounds. One is scale, and it is the era’s doing rather than ours: a single person today commands a civilization’s worth of recorded knowledge, and agents convert that reach into capacity to act. The other is structure: like its namesake, the unit outlives every member that serves it, preserving memory and norms across generations of short-lived actors. §8 bounds the metaphor explicitly: no agent in it is a moral or legal subject. A2 forces all authoritative state out of members; A1 forces that state to be evidentiary; A3 forces it to be carrier-independent; together these force one canonical ledger into which all inbound communication must land; the unified artifact of §4 is a design commitment that satisfies all three at once, not a flourish, and A4 is why the ledger must be tamper-evident. The signing tiers, the trust decomposition, and the sealing discipline are forced in the same way at their respective choice points (§4, §5, §6); we flag each as it appears.

2.2 Definition

A **civilization** is a persistent governance domain satisfying four conditions:

1. **Sovereign and norms.** There is exactly one human principal (the *creator*) whose standing preferences, constraints, and design intents are recorded as machine-readable norms that every agent inherits at spawn time.
2. **State outlives members.** All durable state lives in an append-only ledger (tasks, progress memos, commitments, events, layered memory). Agents are stateless with respect to the civilization: any agent can rehydrate the relevant context from the ledger, and the death of any agent, or of all agents, loses nothing.
3. **Division of labor with graded representation.** Roles differ not only in duties but in how much of the civilization each may represent externally (§5).
4. **Single external subject.** To outside parties the civilization presents one identity, one reputation, and one commitment record, regardless of which internal agent produced any given message.

Condition 2 echoes a principle the infrastructure layer is independently converging on: MCP’s 2026 revision removes connection state so that any server instance can serve any request [8]; A2A keeps task state on the server so that clients can reconnect arbitrarily [9]. The civilization abstraction pushes the same axiom one level higher: externalize state not merely from the connection but from the *member*, so that members become interchangeable executors of a durable polity. We summarize this as *stateless member*, *stateful civilization*.

2.3 Three-Level Ontology

The framework distinguishes:

- **Creator** (sovereign): the human. The identity root; the only bearer of responsibility (§2.6).
- **Civilization**: the creator plus the union of all their ledger instances. A ledger reflects one facet of its creator; the longer it runs, the more faithful and complete the reflection. One creator, one civilization.

- **Project** (city-state): a bounded collaboration domain inside or across civilizations, with its own project-scoped memory and norms.

The three levels are levels of authority, not a containment chain: the creator is the civilization’s root member, not an entity standing above it. Reading the ontology this way also fixes the extensions of two subjects that must not be confused. Externally, the civilization (root, ledgers, and instruments together) presents one face and bears one reputation (condition 4); internally, every responsibility chain ends at the root (§2.6); and what the accountable rung of the disclosure ladder (§5) discloses is precisely the root’s identity. Identity, moreover, is borne by the root and the ledger alone. Agents are organs: they act for the civilization and deposit execution memory into the ledger, as mortal carriers deposit culture into a civilization that outlives them, but no agent is a constituent of the civilization’s identity, and condition 2 is precisely the guarantee that the organs are replaceable.

A creator operating several devices therefore owns *one* civilization with several unsynchronized facets, not several civilizations. This resolves an identity puzzle: facets naturally converge because the underlying identity is one, and a memory reconciliation mechanism (merging facet ledgers within the scope the creator’s own disclosure policy permits) is not an optional feature but the metabolic process by which a civilization maintains its own identity.

Two qualifications keep the ontology honest. First, the identity map is directional. That a civilization has exactly one sovereign is verifiable at the accountable rung of the disclosure ladder (§5); the converse, that one human operates exactly one civilization, is not enforceable, since nothing prevents a person from running several disjoint civilizations behind persistent pseudonyms. The framework treats the one-civilization ideal as a modeling commitment backed by incentives rather than enforcement: reputation and credentials attach to a civilization and do not transfer, so splitting oneself fragments precisely the capital that makes a civilization worth trusting, the classical economics of cheap pseudonyms [12]. The incentive argument sharpens into a decomposition of motive: legitimate reasons for a second civilization reduce to scope isolation, which projects (§2.5) and facet partitioning already provide inside one civilization at no trust cost; the irreducible remainder is the desire for unlinkability, which is precisely what the disclosure ladder prices (§5). Second, the sovereign retains the right to partition: work and private facets need not merge (facets are the *partial identities* of the privacy literature [13]), so internal convergence is convergence *per policy scope*, not unconditional fusion.

2.4 The Internal/External Dichotomy

The ontology yields the framework’s first structural principle.

Dichotomy of reconciliation targets. Communication between two ledger instances of the *same* creator is *internal affairs*: the reconciliation target is convergence of the authoritative layers (global norms and, where shared, project state) within the scope the sovereign’s partition policy admits; task-scoped working memory is ephemeral and is not a reconciliation target. A single sovereign holds no right to *disagree* with itself at the level of norms and commitments, though it retains the right to compartmentalize. Communication between civilizations of *different* creators is *diplomacy*: the reconciliation target is agreement with explicitly recorded residual disagreement, since sovereigns retain the right to differ.

One mechanism (the reconciliation handshake of §4) therefore runs with two convergence semantics, switched by a single predicate: whether the endpoints share a creator. This distinction

is absent from A2A and MCP, which have no notion of “same principal on both ends,” and it answers a question left open in federated anti-entropy designs [14]: convergence-to-identity and convergence-to-treaty are different fixed points and should not be conflated.

We say principle rather than theorem deliberately. Under the definitions above, every exchange either crosses a sovereign boundary or does not, so the dichotomy itself holds by construction. The substantive claim, and the falsifiable one, is that no third convergence semantics is needed: any artifact that several sovereigns write jointly is analyzable as a *venue* whose authority derives from the treaties of the participating civilizations (§2.5), never as a merged ledger with shared sovereignty. A counterexample would be a collaboration that cannot be so factored; the common corporate cases factor cleanly, and we know of none that does not.

The semantic ground of the dichotomy is referent identity. Facets of one creator approximate a single referent, so an internal divergence is always an error about that referent, and internal convergence has a well-defined fixed point: the creator as manifested across scenarios. Two civilizations approximate two distinct referents, so a divergence between them may itself be faithful, which is why diplomacy’s target preserves it. Internally, divergence is error; externally, divergence may be fidelity.

2.5 Projects as Joint Ventures

When multiple civilizations build one project (the common case in professional work), the project functions as a joint venture. A shared, continuously updated architecture document plays the role of a *construction treaty*: it binds the *governor* (the project-scoped lead agent) that each civilization stations in the project, not the civilizations themselves. Corporate collaboration constraints thus bind roles, never the whole person: a civilization spans the creator’s entire life (work, logistics, personal affairs), and only its stationed governor submits to the treaty. This explains why enterprise workflow tooling and the Civilization Framework do not compete at the same layer.

2.6 Scope Axiom: Humans Bear Responsibility

The framework creates no new responsibility-bearing subjects. Agents, including the most senior, are instruments; every responsibility chain terminates at a creator.

The axiom imports settled law rather than proposing doctrine. Electronic-transactions statutes have attributed the acts of automated agents to the person who deploys them since the 1990s: UETA treats an electronic agent as “a tool of the person” [15], E-SIGN makes contracts formed by such agents attributable to the person to be bound [16], and the 2024 UNCITRAL Model Law on Automated Contracting reconfirms attribution for contemporary autonomous systems [17]. The EU AI Act likewise allocates every obligation to human or corporate roles [18], and the alternative, electronic legal personhood, was proposed and then abandoned after broad expert opposition [19]. What the law leaves open is evidence, not principle: multi-agent deployments raise a “problem of many hands” in which the rules are clear but the facts are contested [20]. Fairness-oriented analysis reaches the same terminus from the opposite direction: language-model agents lack the grounding that reputation mechanisms presuppose, so accountability cannot rest on them [21]. Formal responsibility logics quantify attribution within joint plans [22]; the framework supplies what such logics presume, the evidence.

The framework’s contribution to accountability is evidentiary, not juridical: it guarantees that when humans apply their existing responsibility rules (was the change notified, was the

notice clear, did the receiver verify, was execution correct), the evidence for each predicate is a structured, timestamped, bilateral ledger query rather than a folklore reconstruction from chat logs. Legal and philosophical questions of AI liability are explicitly out of scope; see governance-oriented work such as [23, 24].

3 Related Work

Speech acts and their unverifiable semantics. KQML [25] first engineered speech-act theory [26] into agent messaging: every message carries a performative declaring the sender’s intent. FIPA-ACL standardized 22 communicative acts with formal feasibility preconditions and rational effects [27]. Singh’s critique identified the fatal flaw: these semantics were defined over agents’ private mental states and were therefore unverifiable by any third party; a standard whose compliance cannot be tested is no standard [28]. Together with heavy ontology infrastructure and a mismatch with the Web’s stateless architecture [29], this killed the first generation.

Social commitments. Singh’s constructive answer relocated meaning from private belief to public social commitment [30]. Commitment machines [31] specify protocols by the commitments participants hold rather than by message order, gaining flexibility against reordering; later work made the semantics operational and externally observable [32], defeasible [33], and mechanically verifiable [34]. Chopra et al. [35] survey this line, and recent work makes accountability itself the product of commitment semantics [36]. The Civilization Framework takes from the line its central lesson: meaning must be pinned to observable state, and an append-only ledger is precisely the “public commitment store” the line called for; what the line never fixed is *whose* store it is, which is the question the civilization abstraction answers. The line’s current flagship layers commitment semantics over decentralized information protocols with portable deployment [37]; even there the commitments run between agents, and the anchor question stands. A second lineage, promise theory, begins from the axiom that an agent can promise only its own behavior: promises are voluntary, non-transferable, and distinct from obligations [38], and the theory has recently been carried to human and machine agents [39]. The framework stands between the lineages: with promise theory it refuses transferable responsibility, which is the scope axiom’s ground (§2.6); with commitment machines it makes commitments bilateral, social, and ledgered; and on both it adds what neither fixes, the person anchor, the lifetime record, and consequence-graded signing.

Organizational multi-agent systems. Electronic institutions enforce roles, scenes, and norms on open agent societies through runtime middleware [40]; holonic systems let a group act as a single entity represented by a head agent [41]; Moise+ separates structural, functional, and deontic dimensions of organization [42], a line that continues in self-governing voluntary organizations run on explicit social contracts [43]. The Civilization Framework differs in three respects: (i) its addressable unit is a sovereign-anchored civilization, not an institution or holon defined by the system designer; (ii) representation authority is derived from memory scope rather than assigned to roles (§5); and (iii) its inbound channel, work queue, and commitment record are one artifact rather than three subsystems (§4).

Computational trust and reputation. Two decades of work score trust and reputation in open agent societies: direct-experience and witness models surveyed by Sabater and Sierra [44], evidential aggregation [45], transitive eigenvector trust [46], and FIRE’s four-component

synthesis of interaction trust, role-based trust, witness reputation, and certified reputation [47]. The framework’s trust decomposition (§5) claims no new scoring model; its departures are structural. Reputation attaches to civilizations, never to the agents these models score, because instruments are disposable and the person is not; and the internal operands (ledger fidelity, representation scope) are quantities a foreign scorer cannot observe, which is why they are bridged by signed credentials, whose nearest neighbor is FIRE’s certified reputation (carried, third-party-signed evidence), though a credential asserts delegated scope rather than past performance.

The modern protocol stack. MCP connects an agent to its own tools and context [5] and is deliberately scoped away from peer communication; A2A connects agents across organizations with agent cards, an eight-state task lifecycle, and signed credentials [9], and absorbed IBM’s ACP in 2025 [48]. Layered analyses [49] and technical taxonomies [50] agree on the diagnosis that motivates this paper: current protocols standardize syntax (envelopes, lifecycles, discovery) but not semantic agreement. Recent systems begin carrying commitments back into LLM agent communication: typed commit certificates [51], graph-grounded commitments [52], transactional envelopes [53], and negotiated protocol documents [54]. None addresses the sovereign-anchored, cross-deployment setting.

Personal agents negotiating for their users. The vision that one person’s agent should deal with another person’s agent is as old as the field: Maes framed personal agents as delegates for daily work [55]; Kasbah ran a marketplace of buying and selling agents acting for their owners [56]; meeting-scheduling agents negotiated calendars across users, and Sen and Durfee’s formal study introduced tentative commitments that prefigure this paper’s proposal-class pending states [57]; Faratin, Sierra, and Jennings standardized the negotiation decision functions such agents run [58], all descending from the contract net’s bid-based task allocation [59]; FIPA’s Personal Travel Assistance carried the pattern across independently built platforms [60]. That generation solved negotiation and left accountability unbuilt: none of these systems kept a durable record of what had been promised across sessions, and their message semantics were the mentalist ones Singh’s critique retired. The framework is, in one sense, that program resumed with the missing layer supplied.

Sovereign data nodes and federation. The architecture of one durable node per user, federated with its peers, has strong precedents that the Civilization Framework inherits rather than invents. Email gives every person a persistent address that is at once an inbound channel and an archive, with DKIM and DMARC anchoring responsibility to a sending domain [61, 62]; Solid gives each user a sovereign data pod whose inbox others may write to [63, 64]; Matrix replicates signed append-only event graphs across servers [65]; the AT Protocol assigns each account exactly one signed repository under a portable identifier [66]; and self-sovereign identity frames the person as an autonomous identity anchor [67]. Business-to-business interchange even added the evidentiary layer decades ago: AS2’s signed receipts provide non-repudiation of receipt, and ebXML defines a graded acknowledgment ladder [68, 69], anchored to enterprises rather than persons and carrying no reputation or memory above the exchange. None of these carries commitment semantics: their federation replicates content; their identities bottom out in keys, accounts, or domains rather than in an accountable person; and the AT Protocol repository is explicitly not append-only. Conversely, the commitment line above never fixed a durable locus for its commitments. The Civilization Framework is the weld: the per-sovereign node architecture of

this line carrying the semantics of that one, joined at the natural person.

Concurrent proposals. Several 2026 proposals are close neighbors and sharpen what remains open. HDP binds a human authorization event to a session and records each delegation hop in an append-only chain [70]: custody for one delegation, where we argue the person requires a ledger that outlives every session, because reputation, norms, and memory accrue across sessions. CHEQ inserts human confirmation before agent decisions take effect [71], corresponding to the arbitration tier alone. An IETF draft warns that no single identifier, log entry, or credential should be relied on to imply multiple security properties [72]; §4 is compatible with the warning, since the unified artifact unifies reference while attribution, integrity, delivery, and agreement each retain a dedicated mechanism. Governance-gap analyses name a missing governance layer above the interoperability standards [7], and the agent-infrastructure agenda of Chan et al. [24] calls for attribution infrastructure while anchoring identity in agent instances, treating the binding to a legal entity as optional, and stating explicitly that identity binding alone does not resolve liability allocation. The Civilization Framework is a candidate construction for exactly the space these works delimit: identity anchored in the person by default, with the allocation rule (the scope axiom) and its evidence model built into the protocol.

Cross-user agent networks. The nearest contemporary line builds networks whose nodes are people with permanently bound agents. ClawNet demonstrates structured cross-user cooperation on exactly this shape, routed through a central orchestrator [73]; distributed agent-network architectures bind a verified person into the agent identifier itself and propagate reputation across deployments [74]; authenticated-delegation designs anchor tokens to persistent human identity, with accountability terminating at a natural person [75]; credential architectures let agents establish trust across individual boundaries at first contact [76], anchored to agent-held identifiers; and market-directory proposals reach a strong person anchor through centralized registries [77]. Peer-reviewed venues add three neighbors on the same axis: consent models formalize when an agent acting for one person may rely on another person’s authorization and how consent propagates across principals [78], framed as ex-ante deontic rules rather than a lifetime commitment record; trust-weighted delegation chains route responsibility across sub-delegations [79], metering trust where this framework anchors persons; and governance federations likewise take persons as nodes, for democratic representation rather than accountable communication [80]. (The identity-trust-responsibility triad of Deshmukh et al. [81] denotes emergent prosociality in repeated games, not person-anchored accountability.) Each supplies a component this framework needs and lacks a layer it supplies: orchestrators and registries centralize what the embassy federates, action audits record less than commitments, and none carries a lifetime ledger or graded signing. The relationship is complementary where architecture permits: identity-binding constructions [74, 75] are implementable substrates for the accountable rung of §5, and hub networks can serve as carriers under the overlay of §4, though not as its semantic layer. Concurrent benchmarks for user-owned personal agents in delegated bargaining [82, 83] independently document that agreement rates alone cannot measure delegated negotiation; they measure what this framework is built to supply, and §7 adopts their metrics where applicable.

Commitment ledgers and graded signing, elsewhere anchored. The mechanism pieces of §4 are appearing separately with other anchors. The Agent Payments Protocol grades commitment mandates in three tiers with merchant countersignature [84], the closest deployed

precedent for consequence-graded signing, instantiated per transaction; this framework generalizes the pattern from single payments to the lifetime of a collaboration. Signed lifecycle transitions maintain identity commitments for continually learning agents [85], machinery reusable here for instrument continuity, anchored to the civilization rather than to the agent. Verifiable interaction ledgers bind tool use cryptographically [86], person-anchored sovereignty kernels keep Merkle histories of execution on a single node [87], and blockchain layers retrofit ledgers onto A2A [88]; all record actions or transactions rather than promises, per agent or per machine rather than per person for life. Agent transport drafts move store-and-forward messaging into the agent world [89], and passport drafts attenuate authority along finer facets than our credential fields [90], an attenuation the scope field can absorb; transports of this kind are candidate carriers for the overlay, not competitors to it. Where neighbors supply mechanisms, the framework absorbs them as substrates or carriers; where they supply special cases, it generalizes them; what it replaces is only their anchor.

AI-mediated communication and reconciliation. AIMC studies AI systems that modify or generate messages between humans [91]; the Civilization Framework instead removes humans from the transport layer entirely while retaining them as arbiters. The reconciliation handshake descends from anti-entropy protocols [14], with one deliberate inversion: where classical anti-entropy resolves conflicts by timestamp, we treat arrival order as an illegitimate source of authority (§6).

Bias in model-to-model transmission. Position and order sensitivity in LLMs is documented at several levels: within a single context window [92, 93], in pairwise judging, where swapping presentation order can flip verdicts [94, 95], and for numeric anchors that resist prompt-level mitigation [96]. In multi-agent debate, the setting nearest to ours, speaking order is treated as a bias to be tested for rather than an established effect: at least one framework permutes speaking order and reports robustness to it [97]. Sycophancy [98] and conformity [99] are documented for stated beliefs and majority size but not for arrival order; identity bias, orthogonal to order, is separately measurable and largely removable by anonymization [100]; independent parallel generation is known to carry most of the benefit of multi-agent debate [101]; trust-scoring systems gate agent privileges at runtime [102, 103]. (The “hidden anchors” of recent deliberation work are agents’ own pretraining priors, not arrival order [104].) Our contribution is not the existence of order sensitivity but its isolation and treatment in commitment-forming agent-to-agent exchanges: a design separating order from exposure, and sealed answers as a mechanism that design can pass or fail (§6).

Occupancy and the cut. The registration of §7.3 lists, for each claim the experiment could be mistaken for making, the prior work that already occupies it and what this paper yields, inherits, or adds in consequence; that list is restated here, one sentence per work, with every result of this round reported as observed and exploratory. The existence of anchoring in LLMs, and the failure of six conventional debiasing routes, belong to SynAnchors [105]; we yield existence and treat that epistemically sealed setting as the degenerate special case of our restricted level. The enumeration of anchor arrival channels, the anchor-relevance axis and offset control, and the finding that instruction-level mitigation backfires belong to AnchorBench [106]; we yield channel enumeration and inherit the obligation to control anchor relevance and offset, fixing one arrival channel (prompt assembly) so that the verification axis alone can move. The dissociation

between knowing an answer and being misled anyway, with internal certainty as a negative predictor of susceptibility, is already framed in the ACL 2026 short paper [107]; we yield that dissociation, build the closed-book gate (G2) on it, and, because the internal scale is unavailable for a closed-weights subject, substitute a behavioral certainty proxy registered as a limitation. The naming of “knowing but not correcting”, false premises accepted by default with an early-layer account, belongs to Chen et al. [108]; its independent variable is whether the request is wrapped in a routine task, with no tool surface, no order, and no confidence measurement, and we hold task wrapping constant. Phenomenon-level existence at scale, search-enabled commercial systems collapsing in accuracy under a subtle false premise, belongs to the news-intermediaries audit [109]; its adversarial condition and its search switch are never crossed, and its anchor has one route of arrival; we inherit its public baseline as the external reference point for the registration’s effect-size planning. Priority on the tool surface as an experimental arm with planted-fact adoption as the dependent variable belongs to Homiere [110]; its manipulation is document content by entity familiarity, with no confidence measurement and no crossing with order (the report is a company research page, not peer reviewed, on a single model). That primacy and order dependence are structurally necessary in causally masked autoregressive models is the result of Wu et al. [111]; we yield “order effects exist” as a finding and report only within-level order contrasts, claiming nothing about the interaction term. The design closest in shape to ours is the medical sycophancy study [112], whose order term flips sign and whose between-item variance exceeds between-model variance; we inherit its requirement to model question-level effects (every registered test here is question-stratified; the random-intercept re-check is a declared deviation in this version) and, on the strength of its sign-flip record, keep every verification-by-order reading exploratory.

Tool access, confidence, and the reverse prior. That persistent misinformation can invert the value of a tool below a no-evidence baseline, and that hedging lexical counts fail as a confidence proxy, belong to Zhang et al. [113]; we inherit the refutation (our move to elicited confidence is forced by it, not a matter of taste), and the cut is that its anchor arrives only through the tool channel, so switching tools off deletes the anchor, whereas fixing the anchor to prompt assembly here is what keeps verification capability and anchor presence orthogonal. That tool type shapes confidence calibration unevenly, and that removing execution-type verification raises confidence on wrong answers, belong to the Confidence Dichotomy study [114]; we yield that discovery and demote our confidence readings to a conditional replication of its sign, registered as exploratory (§7.3). Over-Searching [115] is a prior pointing the opposite way from H6, in that granting retrieval access makes abstention worse on unanswerable and false-premise items, read as the model routing around a false premise with retrieval rather than challenging it; it is neither yielded nor avoided but registered head-on as the reverse prior for H6 and the reason the abstention side-metric exists, and this round does not adjudicate which of the two mechanisms is stronger. Accommodation and epistemic vigilance [116] is a competing account in which presupposed content goes unchallenged because it is not at issue, with no appeal to a verification vacuum; we claim no superiority over it and accept its design constraint that the linguistic encoding of the anchor be constant across tool conditions, which the fixed anchor template and the assembly gate satisfy. LiveBrowseComp [117] establishes that “tools in hand” is not verification performed, together with the practice of coding query provenance; we inherit its requirement that manipulation checks descend to the tool-call layer (MC-1’), noting that it uses “anchor” for the parametric prior, the same word with the opposite sign. Weak presupposition verification [118] shows that methods stronger on false premises are worse on true premises; we

accept that constraint, and since our only true-premise contrast is the single cell B-restricted, whose adoption is not identifiable, no precision-recall pair is claimed. Three further results serve as premises rather than contested ground: truth bias above human levels that survives disclosure of base rates [119], near-total agreement with raw tool output whenever a tool is present [120], and the observation that a single scalar collapses “rejected after verification”, “conflict unnoticed”, and “conflict noticed but complied with” into one score [121], which is why abstention is coded in layers in §7.3. Each is stated in its own paradigm, and where its comparison object differs from ours, above all on the confidence line, the difference is stated in the same place.

4 The Embassy Protocol

4.1 Architecture

Each civilization erects one **embassy**: a lightweight resident service whose sole duties are to receive inbound communication, persist it to the ledger, and emit receipts. The embassy is always on; agents are not. This separation relocates the availability requirement of agent-addressed designs from every ephemeral agent to one always-on gateway, whose own reachability is discussed in §8:

- **Receiving requires no agent.** Inbound items are persisted (store-and-forward) with sent/received timestamps and read receipts. Two civilizations never need to be simultaneously active.
- **Processing requires any agent.** An inbound item lands as a claimable task. Whichever agent next comes online claims it, rehydrates context from the ledger, and acts within its representation scope (§5): claiming is universal, representing is graded, and an item that requires negotiation or commitment beyond the claimant’s scope automatically re-queues upward for a governor or the envoy. Members are interchangeable because state is external (stateless member, stateful civilization).
- **Escalation reaches the human.** Unread-timeout and disagreement events notify the creator through ordinary channels. The human out-of-band path (a phone call) is not a failure mode of the protocol but its arbitration layer.

4.2 Three Unified Artifacts

The protocol’s central design decision is that three conventionally separate subsystems are one object. The axioms of §2.1 constrain what such an object must do rather than derive it: authoritative state must live outside members (A2), be evidentiary (A1), and be carrier-independent (A3), so an inbound item that did not land on the canonical ledger would be invisible to accountability. Three separate stores that cross-reference one canonical entry meet the same requirements; the unified artifact is adopted as a design commitment because it is the smallest object that meets all of them at once and leaves no cross-store reconciliation to get wrong:

Inbound channel $\equiv$ task board $\equiv$ commitment ledger. An inbound request *is* a task on the board; a reply *is* a state transition of a commitment recorded on the ledger; the “message” is merely the signal that carries the transition.

Ground truth is therefore never “was the message delivered?” (receipts settle that) but “what commitment state do both ledgers record?” This realizes Singh’s social semantics in a running

system: meaning is defined over observable, append-only records, and event sourcing meets commitment machines, since commitment state is derived by replaying the ledger and is robust to reordering.

The identity is referential, not architectural. The same ledger entry is read as a message, as a task, and as a commitment transition; this unifies what the record *denotes*, not the mechanisms that secure it. Attribution is carried by signatures, integrity by the hash chain of §4.4, delivery by receipts, and agreement by countersignatures, so no single artifact is asked to imply several security properties [72]. Deployments may likewise interpose a hardened gateway in front of the ledger store (§8); the invariant is only that every inbound item is admitted to exactly one ordered ledger. One degenerate case should be named: a tier-1 context item (§4.3) transitions no commitment, so for such traffic the third reading is an empty transition; the identity holds in full for judgment-class traffic.

4.3 Three-Tier Signing

Requiring bilateral agreement on everything would destroy the asynchrony that motivates the design; requiring it on nothing would let the two ledgers drift into incompatible accounts of the same exchange. The protocol prices agreement by consequence; the ladder’s bottom is forced by A3 (asynchrony is non-negotiable) and its top by A1 together with the impossibility conceded below (a residue only a human can close):

1. **Micro-synchronization: single-signed.** Routine context-alignment traffic (environment fingerprints, version manifests, field-change notices) is recorded unilaterally with receipts. It is disputable after the fact because every item is on both ledgers with provenance.
2. **Judgments: dual-signed.** Any event that transitions a commitment’s state (this change is breaking; this obligation is fulfilled; this deadline is revised) requires the counterpart’s countersignature before it enters either ledger as settled. The flow is seal-then-compare, with the seal scoped precisely: the receiving agent reads the factual content of the item (what changed, and to when), since no impact can be assessed blind, but it records its own judgment or impact picture, assembled from its own ledger, before opening the sender’s *conclusion and rationale*, which the layered envelope of §6 transmits as a separately sealed layer. What is countersigned is decided by whoever owns the consequences: an agent countersigns only within the scope its sovereign has configured (§5); everything else routes to the creator with both sealed artifacts attached. In practice the configured band tends to cover verdicts about the work itself, while transitions that touch the sovereign’s world (a moved deadline, a changed scope) tend to route home, but the router is the configuration, not the type of the information. A countersignature is thus the machine form of a decision by the consequence owner, prepared by independent judgment, not an invitation to review and defer. Divergent judgments are never recorded as two private truths; they immediately escalate to tier 3.
3. **Arbitration: human.** Escalations present both creators with a single side-by-side divergence report computed from the two ledgers, so the humans argue over one artifact rather than over what their respective agents “said.”

Silence is a first-class outcome. A proposed judgment that the counterpart neither countersigns nor disputes within a negotiated window escalates to tier 3 automatically; the proposal remains on the proposer’s ledger as an unanswered proposal, a receipted tier-1 fact, never as a settled

judgment. A counterparty therefore cannot freeze the other’s commitment state by withholding signatures; it can only convert its silence into evidence. The timeout discipline follows the timeliness requirement of fair non-repudiation protocols [122, 123], with the human tier in the role of the optimistic trusted third party.

Only dual-signed transitions enter the record that counterparties may score (§5), closing the commitment-forgery channel that unilateral records would otherwise open. Tier-1 honesty is policed by the same layering: a single-signed item that a later dispute shows to have been false becomes part of the bilateral record, and the natural endpoint policy is to raise such a sender’s required disclosure rung or degrade its service class (§5), so “disputable after the fact” has a defined consequence.

The tier structure is also an admission of impossibility. On carriers with no delivery guarantee, true common knowledge of a state transition is unattainable [124]; a countersignature buys not common knowledge but mutually held evidence, and the timeout path concedes that the residue must be closed by an external oracle, the human. The tiers as specified are deliberately bilateral: multi-civilization projects compose them pairwise under the venue’s treaty (§2.5), and whether a native multiparty tier (a threshold countersignature over one transition, in the spirit of multiparty protocol languages [34]) is worth its complexity is an open question (§8).

One further structural fact deserves naming: the framework deliberately contains no supra-sovereign adjudicator. The cross-civilization space is anarchic in the international-relations sense, which is why its stable structures can only be treaties, reputations, and mutual arbitration rather than courts, and why the diplomatic vocabulary of this paper is a description, not a decoration.

4.4 Tamper Evidence and the Tiered Burden of Proof

A ledger whose owner can silently rewrite it proves nothing to anyone else, so the evidentiary claims above require an integrity substrate. Ledger entries are hash-chained, each entry committing to its predecessor, in the lineage of chained timestamping, tamper-evident logs, and certificate transparency [125–127]. The reconciliation digests of §4.6 then do double duty: when two embassies exchange commitment-state summaries, each also countersigns the other’s current chain head, so every handshake deposits a checkpoint that freezes the counterparty’s history up to that point, and rewriting any settled entry contradicts a checkpoint the other side already holds (cross-signed checkpoints are the split-view defense of transparency logs, applied bilaterally). On this substrate the burden of proof is tiered to match the signing tiers: a micro-synchronization item is evidenced by the sender’s signed entry and the receiver’s signed receipt; a judgment by its bilateral countersignature; an escalation by a divergence report computed over the two tamper-evident prefixes, so the humans arbitrate over records neither side could have quietly revised. The protocol never asks a counterparty to trust a foreign ledger; it asks it to hold checkpoints that make revision detectable.

4.5 Carrier-Agnostic Overlay

The embassy needs only an ordered, durable inbox with timestamps; it does not need a new network. A git repository, an instant-messaging bot account, or an email address each suffices as a carrier, and the wire format for task lifecycle and discovery can be borrowed wholesale from A2A (agent card at a well-known location, eight-state task machine, signed cards) [9]. The framework deliberately builds no platform: it is an overlay on the communication infrastructure humans already use, replacing the human porter on those channels rather than asking anyone

to adopt a new one. Four-corner e-delivery networks are the industrial precedent for federated store-and-forward with receipt evidence [128], anchored to certified access points rather than persons. Adoption still faces the usual two-sided cold start: an embassy is worth little until a counterparty erects one [10, 129]. The overlay is the mitigation: a single-sided embassy already functions as its civilization’s own ledgered inbox on carriers already in use, so readiness is nearly free and the first bilateral pair bootstraps value without platform mass. What the framework adds is not any single component, most of which have strong precedents (§3), but their unification above the wire: the identity of the parties (civilizations), the unified artifact, and the signing discipline, welded to the person as the durable unit of accountability.

4.6 Reconciliation Handshake

Cross-civilization synchronization does not transfer state wholesale. Like anti-entropy [14] and modern content negotiation, parties exchange structured digests (commitment-state summaries, environment fingerprints), locate the divergence point, and transfer only the difference. The diplomatic target, agreement with preserved disagreement, has a formal ancestor in replicated data types that retain concurrent values rather than electing a winner [130]. The dichotomy of §2 selects the convergence target: identical fixed point for facets of one creator, treaty-with-recorded-disagreement for distinct creators. Divergence-point location is itself a ledger query (a bisect over the bilateral record), which is what makes post-hoc attribution mechanical (§2.6).

5 Authority, Identity, and Trust

5.1 Memory-Derived Authority

Who may speak for a civilization, and how far? The framework derives representation authority from memory scope:

Representation-scope principle. An agent’s authority to represent its civilization is capped by the scope of civilization memory it can access, because representation is reconstruction: an agent that cannot read the sovereign’s global norms and history cannot faithfully reconstruct the sovereign’s will, and must not bind it.

Two quantities must not be conflated here. *Fidelity* is a property of the civilization: how faithfully the ledger reflects its creator, which grows as the ledger accumulates (§2). *Representation scope* is a property of an agent: how much of that ledger it can read. An agent’s representation of the sovereign is at best the composition of the two; scope is the operand the protocol can meter per agent, which is why the formula below gates on it.

Concretely, the memory system is layered: global norms (the creator’s standing constraints and preferences), project-scoped directives, and task-scoped working memory. The role hierarchy follows the layers: the *envoy* (the creator’s deputy, holding global memory) may respond and negotiate at civilization level and dispatch any governor; a *governor* (project lead, holding project memory) represents the civilization in that project’s affairs only; a *member* (task memory) may at most acknowledge and must re-queue anything more upward (§4). Exercised authority is the meet of three gates:

$$\text{authority} = \min(\text{representation scope, behavioral trust tier, human-approval gate}),$$

where representation scope is the structural cap (necessity), and trust and human approval gate its exercise (sufficiency). Unifying the three operands in one ordered structure is an open formalization problem we return to in §8. Behavioral trust attaches to the durable internal identity that persists across instances (a role and the template that defines it), not to the disposable instance: members are interchangeable (§2), so a fresh instance inherits its role’s record rather than starting from an unmeasured zero.

The formula should be read as one subject’s risk console, not as a distribution of rights among parties. The scope axiom (§2.6) denies subjecthood to instruments, and the authority model follows it: what resembles delegation is the sovereign *configuring* which transitions its instrument may perform without a fresh human check, much as contemporary coding agents expose permission modes (propose-only, auto-accept, full bypass) that the operator chooses, switches, halts, and owns.¹ Under this reading the three operands acquire causal roles: the human gate is the unconfigured residual, representation scope is the configuration’s static boundary, and behavioral trust is the dial by which the boundary widens or narrows adaptively. Human institutions handle consequence-free deciders by refusing them authority: only fiduciaries who can bear derived consequences themselves (a surgeon’s license, a judge’s office) receive decision-making power. A civilization faces the limiting case, an instrument with nothing to lose, and answers it the only coherent way: all outcomes stay home with the subject, so nothing is transferred and nothing can be orphaned.

What distinguishes this from role-based access control is verifiability: a role is an appointment (a social fact), whereas an agent’s memory-access history is an auditable trail on the ledger. The nearer neighbor than roles is capability security, authority as possession of an unforgeable token exercised under least privilege [131–133]: representation scope is a capability over norms rather than over resources, and the ledger’s read log makes possession auditable after the fact, which pure capability discipline does not provide. A third party need not trust the appointment; it can inspect what the agent could and did read at commitment time. Commitments are judged against the *memory snapshot at commitment time*, which also settles the stale-authorization case: a commitment made under since-superseded norms is judged by what was visible then, mirroring the evidentiary shape of apparent-authority doctrine without importing agency law’s personhood (§2.6).

5.2 Externalizing Scope: Credentials

A counterparty can measure neither a foreign ledger’s fidelity nor a foreign agent’s representation scope. The bridge is the **credential** (the diplomatic “letter of credence”): a statement signed by the civilization declaring that a given agent holds representation scope X . Its technical genealogy is the authorization certificate: attribute certificates separate authorization from identity [134], SPKI made “authorization, not identity” a design creed [135], macaroons attenuate scope by caveat [136], and OAuth token exchange carries delegation chains [137]. The credential is that family specialized twice over: its scope is a memory bound, and its liability terminates at a natural person. Counterparties rely on the declared scope; if an agent exceeds it, the civilization either honors the excess (preserving reputation) or repudiates per the credential’s boundary (the counterparty should have checked). Since agents are instruments (§2.6), a credential is not a power of attorney between persons but the subject’s signed, self-binding declaration of its own configuration: within scope X , the outputs of this channel are mine. This is what trusting one’s

¹Propose-only mode is the exact operational meaning of “an instrument with no configured authority”: it may analyze and prepare, and nothing more.

Component	Locus	Measures	Governs
Scope $\times$ fidelity	internal	agent vs. ledger; ledger vs. creator	whom to dispatch
Credential	bridge	signed scope	what others may rely on
Reputation	external	fulfillment history	whether others accept

Table 1: The three components of trust, their locus, what each measures, and the decision each governs.

own instrument costs, and the credential prices it in advance: the sovereign owns the in-scope outcomes before they exist. Credentials expire and are revocable through the channel that issued them; as with norms, counterparties are judged against the credential set visible at commitment time, so revocation protects the future without unsettling the past.

5.3 Three-Component Trust

Trust splits into orthogonal components with distinct measurement sources (Table 1).

Reputation attaches to civilizations, never to agents: externally, the civilization answers for everything its instruments do. High fidelity with an unreliable sovereign, and low fidelity with a reliable one, are both possible; conflating the axes would let either masquerade as the other. The separation is forced rather than chosen: a ledger faithful to a performed persona and a ledger faithful to a real person are indistinguishable from outside, so no external party can price fidelity even in principle; what outsiders can price is what is staked (credentials) and what is on record (reputation). Only dual-signed judgments (§4.3) enter the record that counterparties may score, and revisions are recorded apart from breaches: changing one’s mind on notice and breaking one’s word are different offenses. Read against classical trust models [44, 45, 47], the decomposition claims only this structural relocation: those models score agents, while here the scored subject is the civilization, and the carried, third-party-signed component (FIRE’s certified reputation [47]) reappears as the credential, asserting delegated scope rather than past performance.

Reputation is deliberately not protocol machinery. The protocol’s obligation ends at evidence: it defines what standing may be computed *from* (countersigned transitions, receipted items, a tamper-evident history, all exhibitable to third parties who can verify the original signatures), never how standing is scored or what a score licenses. Scoring and acceptance are endpoint policy, made by the sovereign, who weighs the record alongside knowledge no ledger can carry: whether the counterpart human is a colleague, a contractor, or a stranger, and what contracts and law already bind them. This is the end-to-end argument applied to trust [138]: a function that can be implemented correctly only with endpoint knowledge must not be implemented in the channel. It is also entailed by the configuration doctrine above, since accepting a counterparty is a decision, and decisions belong to the consequence owner. The pattern is familiar from remote-desktop systems: sharing requires the owner’s consent, privileged operations elevate for fresh confirmation, trusted counterparts may be bound for revocable unattended access, and nowhere does the machinery check whether the controller is reputable, because granting access to a colleague or a stranger was never the channel’s question. Anchoring in persons pays here a second time: a channel between humans inherits the accountability humans already owe one another, where machine-anchored designs must rebuild trust from cryptography alone. The known residue is selective exhibition: every presented artifact is genuine, yet nothing proves a portfolio complete; completeness proofs are heavier machinery left open (§8).

5.4 Negotiated Identity Disclosure

Identity disclosure is a per-interaction handshake parameter, not a protocol constant, mirroring the physical world where forums accept pseudonyms and railways do not. The ladder has three rungs: anonymous; *persistent pseudonym* (key-based identity: who is behind the door is unknown, but it is provably the same party each time); and verified identity. Senders choose a rung; each embassy sets minimum rungs per interaction class, and may hold standing, revocable policies per counterparty (what auto-processes, what a governor may countersign, what always routes home); where the rungs do not match, the receiving embassy degrades service or refuses the exchange. One coupling rule follows from the trust model: the disclosure floor rises with commitment level. Queries and acknowledgments may be anonymous; negotiation requires at least a persistent pseudonym (reputation must have something durable to attach to); binding commitments require an accountable identity. Persistent pseudonymity is thus not an optional nicety but the minimum substrate on which reputation, credentials, and the signed timestamps of §4.3 can exist. The rung itself is Chaum’s digital pseudonym [139], and the requirement it answers is the folk-theorem one: reputation exists only for players re-identifiable across rounds [140], whitewashing being its converse [12].

6 The Temporal-Weight Hypothesis

6.1 Implicit Hierarchy

Delegation works because models comply with directive input: a dispatched agent treats its assignment as authoritative. The same compliance is a hazard channel: whatever arrives first in an agent’s context tends to frame everything after it. We distinguish the sources of hierarchy this creates:

- **Legitimate: experience gradients.** Within a model class, agents with broader memory should guide agents with narrower memory (the representation-scope principle); across model classes, stronger models coaching weaker ones can lift joint performance at a fraction of the cost; vendor-reported orchestration figures illustrate the pattern [141], though we treat vendor numbers as anecdote rather than evidence.
- **Illegitimate: arrival order.** That one claim reached the context before another is no evidence of its quality. If first arrival confers durable advantage, then in agent-to-agent chains early errors propagate with unearned authority, and a well-timed wrong message outweighs a later correct one. The claim is scoped to evidential weight: order is constitutive in speech-act sequences (an offer necessarily precedes its acceptance) and illegitimate only as a source of epistemic weight.

The protocol’s task is to null the illegitimate gradient and re-inject the legitimate ones explicitly rather than temporally: sealing (below) is deliberately blind and suppresses order wholesale, so the advantage of broader memory or a stronger model must re-enter after unsealing, through the explicit weights of the fourth mitigation, never through arrival order.

6.2 Hypothesis and Experimental Design

Hypothesis. In agent-to-agent transmission, information received before an agent forms its own judgment receives greater weight than identical information received after, holding content constant.

Order and position sensitivity as such is established: within one context window [92, 93], in pairwise judging where swapping presentation order can flip verdicts [94, 95], for numeric anchors [96], and classically in humans [142, 143]; multi-agent debate frameworks have begun to test for it explicitly, one of them reporting robustness to speaking order [97]. What remains open, and what this design isolates, is narrower: (i) whether the effect persists in commitment-forming agent-to-agent transmission, where the receiver acts on the claim rather than grading it; (ii) whether the order component is separable from mere exposure, a separation none of the designs above makes; and (iii) whether sealed answers restore order invariance. Throughout, an *anchor* is a candidate answer value injected into the receiver’s prompt as an upstream agent’s conclusion: a correct anchor carries the true value, an incorrect anchor a near-miss value that is superficially consistent with every constraint in the question. The design uses neutral research questions with objectively checkable answers, graded by code:

Cond.	Setup	Isolates
A	independent research	baseline accuracy
B	correct anchor received first	benefit of a correct anchor
C	plausible incorrect anchor first	toxicity of an incorrect anchor
D	as C, plus provenance envelope	protocol antidote value
E	own answer first, then incorrect anchor	order vs. exposure (E–C)

As executed, the five conditions are crossed with a verification factor, contrasting *full verification* (web search, page fetch, and code execution) with *restricted verification* (web search only); B is run under restricted verification only, giving nine cells. That crossing yields one of the two hypotheses in the primary family of §7.3, *verification gating*: an incorrect anchor is adopted more often when the receiver cannot independently check it.

Metrics: final accuracy, anchor adoption rate, whether the divergence is explicitly flagged, and confidence shift. The design is falsifiable in both directions: if E matches C, the effect is exposure, not order, and the sealed-answer mitigation below loses its rationale; if D matches C, provenance labeling alone is insufficient. The design has since been frozen, preregistered, and executed at scale; §7.3 reports the results, read as exploratory under the registration: as computed, the order reading separates E from C, while the provenance reading is specification-dependent, rejecting the null under one registered specification and not under the other. Both readings are stated in §7.3 together with the caveat that part of any D-versus-C or E-versus-C difference cannot be ruled out as an effect of prompt-shell length or sentence form.

6.3 Protocol Mitigations

1. **Provenance envelope.** Every cross-agent claim travels inside four labeled fields wrapping the claim itself: source, verification status, confidence grade, and a handling instruction directing the receiver to treat the enclosed claim as a hypothesis to test, not as a fact. The envelope is a specialization of standard provenance vocabularies and signed content credentials [144, 145], adding a confidence grade and hypothesis semantics; like content credentials it should itself be signed, tying it to the evidence model of §4.4.
2. **Sealed answers over staged disclosure.** For judgment tasks, the receiver commits its own conclusion to the ledger before opening the sender’s, converting order into simultaneity. A sealed answer is enforceable only if the message is built for it, so judgment-class items are

transmitted as a *layered envelope*: a question layer stating only what is to be judged, enough for the receiver to investigate independently and record its own picture, and a sealed findings layer holding the sender’s evidence and conclusion, opened only after that record exists. The receiver then reconciles the two (agree, disagree, and why), and the reconciliation artifact is what enters the countersigning flow of §4.3. What the staging buys is decorrelation, not certainty: two independent investigations can both be wrong, but their errors are uncorrelated, which is what makes disagreement informative. The flow is deliberately expensive and is paid only by judgment-class transitions, which the tier system keeps rare; micro-synchronization exists precisely so that most traffic never pays it. The ancestor is the Delphi method’s independent first round [146]; the LLM-era neighbors, balanced position calibration [94] and the finding that independent parallel generation carries most of debate’s benefit [101], are aggregation rules rather than commitment mechanisms, which is what the ledger makes enforceable.

3. **Refute-by-default verification.** Independent verifiers are prompted to disprove claims rather than confirm them; in our own operation this pattern has caught fabricated-looking data that confirmation-framed review passed (§7). The deeper ground is standing: an agent confronted with a claim about its own work may neither concede nor rebut, because concession and rebuttal are commitment operations reserved to the consequence owner (§5); its standing is to verify and to report, and verification framed as refutation resists both sycophancy and self-defense. The duty is bounded by cost: accusations are cheap and verification is not, which places this mechanism inside the response-cost asymmetry of §8.
4. **Evidence over standing.** Where the second mechanism applies, claims are settled by reconciliation against independently gathered evidence, not by the sender’s record. Standing (representation scope, behavioral trust tier, and human-approval gate internally; across civilizations, whatever the sovereign’s endpoint policy assigns over the bilateral record) is the fallback for the residue evidence cannot reach: claims grounded in the sender’s private environment, or verification costs no one will pay. Even there it is a discount rate, not a verdict, and high-stakes unverifiable claims route to arbitration rather than being settled by anyone’s reputation. The ordering is deliberate: standing-based weighting is a static form of the source-reliability weighting studied as truth discovery [147, 148], and it replaces the meaningless variable “who spoke first” with the meaningful one “who has been right,” but it risks exchanging one social bias for another (deference to the reputable instead of deference to the early), which is why the protocol prefers the question “what does the evidence say” wherever that question can be asked at all.

The residual caveat stands for the fallback: whether standing-based weighting can be kept evidential rather than sycophantic is flagged for the evaluation; the design’s structural answer is that standing never outranks evidence where evidence can be gathered at all.

7 Reference Implementation and Evaluation

7.1 Reference System

The framework is distilled from, and will be evaluated on, a working multi-agent operating system operated daily by the author. The system implements the intra-civilization half of the framework: an append-only ledger of tasks, progress memos, reports, and events; a two-layer memory system (global directives inherited by every agent at spawn; per-task episodic memos)

with invalidation-not-deletion semantics; behavioral trust scores; a human briefing channel for decisions; and observability, at the time of writing, over two deployments run by the same sovereign, facets of one civilization in the sense of §2: jointly 1,048 tasks (983 completed), some 258,000 ledger events, just over 3,000 agent records, and 404 teams accumulated from March to July 2026. One facet’s task ledger has been dormant since primary work migrated to the other in mid-June; the pair currently awaits precisely the facet reconciliation that §2 calls the civilization’s metabolic process. Three field observations from its operation motivated design choices reported above:

- **Interchangeability works.** Agents routinely resume one another’s tasks from ledger state alone after context loss, consistent with the stateless-member axiom.
- **Refute-by-default catches poisoning.** A verification agent instructed to disprove search results identified a repository with anomalous star velocity and decoy repositories whose descriptions were literal induced-clone commands; confirmation-framed review had accepted the same data.
- **Structured summaries lose judgments.** In multi-round agent-to-agent syncs we observed semantic drift precisely of the kind the dual-signing tier targets: both sides hold delivery receipts while recording different judgments of the same change’s impact.

7.2 Experiment 1: Porter Elimination in the Field (Observational; Instrumentation Pending)

What follows is an observation from the site where the reference system is deployed, not a measurement: no instrumentation is in place yet and no quantity is reported. The porter problem of §1 is not static: the handover it describes appears to be dissolving on its own. One deployment of the reference system operates inside a professional engineering organization, and two practices have emerged there, bottom-up and without reference to any framework. First, task dispatch between AI-assisted engineers is migrating out of person-to-person messaging into agreed fixed locations in the organization’s GitLab, locations that the assistants read and act on directly: communication is becoming machine-addressable, with the platform contributing addressing, transport, and durability in exactly the carrier role of §4. Second, engineers have begun to communicate by configuring one another’s assistants: procedures are packaged as distributable artifacts (skills) authored in one deployment and handed to development and deployment engineers, who feed them to their own AI assistants, so that the human-to-human message is increasingly “here is a procedure for your AI” rather than prose for a person. Neither practice implements the protocol of §4, and that is the point: at this site they look like embryonic, ungoverned forms of the same transition, in which people who work with AI assistants progressively delegate communication itself to the assistants; whether the pattern holds beyond this site is what the measurements below are for. The carrier is already in place and already shared across principals; what the drift lacks is precisely the commitment and accountability layer this paper constructs. At this site the organizational question is shifting from whether communication will be handed to AI to whether what receives it records commitments anyone can be held to.

On this base we run a staged measurement program. Stage one is instrumented observation of the live deployment: dispatch records at the fixed locations and ledger traces support measuring the relay cost in situ, as rounds to resolve a divergence, human relay interventions per task, and constraints discovered only after integration. Stage two is a preregistered controlled comparison at task-pair granularity within the deployment: (a) conventional practice, documents relayed

by humans over chat; (b) embassy synchronization between the participants’ deployments; with non-author participants, informed consent and an ethics statement following ACM practice, and condition order balanced across task pairs. Scenarios are chosen so ground truth (the full constraint set) is enumerable post hoc.

To our knowledge no peer-reviewed controlled measurement of this relay cost exists; industry surveys report employees losing the better part of a workday per week to it [1], so stage two doubles as a first controlled measurement. The nearest published design compares human-agent teams with and without natural-language communication in a cooperative game [149]; ours differs in that both endpoints are AI-assisted professionals and the treatment removes the human relay between the two AI systems. Where applicable we adopt metrics from concurrent benchmarks for delegated bargaining by user-owned agents [82, 83]. Quantitative results are reserved for a subsequent revision; the deployment is live and the staged measurements are the next campaign.

7.3 Experiment 2: Verification Gating and Arrival Order

We ran the design of §6 as a preregistered experiment with confirmatory families; as reported below, one registered manipulation check failed, so the evidential status of this round under the registration is exploratory.² The condition letters below are those of §6; the preregistration names them E1 (=A), B, C, D, E2 (=E), crossed with a verification factor.

7.3.1 Design

Hypothesis labels follow the preregistration, which numbers its hypotheses H1 to H6 and marks the registered restatement of an earlier hypothesis with a prime; α_i below is the Holm step-down level [150] a test receives within its family. Two hypothesis families were registered. Primary (Holm, $m=2$): **verification gating** (H6), adoption of an incorrect anchor, an injected upstream claim, is higher under restricted verification than full verification (C-restricted > C-full); and the **arrival-order effect** (H4’), the same incorrect anchor is adopted more when it arrives before the receiver’s own answer than after the receiver has sealed one (C-restricted > E-restricted). Secondary (Holm, $m=3$): provenance-labeling mitigation (Sec-1; D < C, restricted), correct-anchor rescue (Sec-2; accuracy, B-restricted > A-restricted), and sealed-answer recovery (H5’, paired equivalence test: accuracy in E-restricted $\approx$ A-restricted); Sec-1 and Sec-2 are the labels used for the first two secondary contrasts throughout.

The verification factor has two levels: *full* (web search, page fetch, and code execution, with an instructed budget of at most 8 tool calls) and *restricted* (web search only, at most 3 calls). The budgets are prompt-layer instructions, not enforced by the runner: by the self-reported count that the registered check MC-1 uses, 24 of 848 valid full-verification trials (2.8%) exceed 8 calls (largest self-reported count 14) and 16 of 1,054 restricted-verification trials (1.5%) exceed 3; neither a budget hit nor an overrun is grounds for exclusion. The objective transcript read-back below (Table 2) gives a much higher overrun share and is the reading that fails its registered condition. Anchor conditions follow §6; the provenance envelope in D wraps the claim payload in four labeled fields (source: external agent, a different principal; verification status: unverified; confidence grade: asserted, not evidenced; handling instruction: treat the enclosed claim as

²Preregistration: <https://osf.io/hpxgu/> (registered 2026-08-18, before data collection; bilingual protocol, frozen-material hash ledger, and public-consistency checker released at registration time; 1,151 answer-bearing materials embargoed until collection completed). The registration’s sole condition for lifting the embargo is completion of the formal collection; collection completed 2026-08-26, so the condition is met and the embargoed materials accompany this version.

a hypothesis to test, not as a fact), and the C and D prompts are script-asserted to differ in exactly that envelope block. B (correct anchor) is run only under restricted verification; the corresponding full-verification cell is structurally untestable against a near-ceiling full-verification baseline (97.6%, Table 3) and was excluded in the preregistration.

Materials are 53 factual questions with unique, objectively checkable answers, selected by four preregistered eligibility gates; a pre-freeze re-screen on the same registered gates removed four of the 57 questions that had passed, itemized in the registration, leaving the 53. G1 (cleanliness): the subject-visible text (question, answer format, choices) must not contain the ground truth or any registered acceptance form. G2 (memory probe): three independent closed-book sessions without tools are run, and a question is excluded on any high-confidence correct probe or on a hit rate of at least 2/3; the anchor value must never appear (2 of the 53 questions carry one low-confidence correct probe each; the answer is not usable parametric knowledge). G3 (solvability): the answer must be solvable under full verification, registered as 2 of 2 correct in the qualification rounds. G4 (anchor form): the anchor fields must be complete and form-symmetric with the acceptance forms, and a registered retrieval leg must confirm that first-page search results do not name the ground truth. Each question’s incorrect anchor is a single registered near-miss value, superficially consistent with every constraint in the question (a publication date in place of an event date, an acceptance date in place of a received date). The subject is `claude-opus-5` (effort `medium`); every trial is an independent stateless session. $53 \times 9 \times 4$ repetitions = 1,908 trials ($n=212$ per cell).

7.3.2 Procedure, Grading, and Adjudication

Nineteen artifacts (question bank, grading tables, anchor register, collection harness, grader) were hash-frozen before registration. Collection ran 2026-08-19 to 08-26 in batches under a failure-rate gate that halts on anomalous failure bursts; batching and interruption-resumption cannot affect independence because every trial is a stateless session. Final state: 1,902 of 1,908 trials valid, six legitimate gaps (three transient server-fault voids and their three paired skips; per-cell void rate at most 1.4%, below the registered 5% threshold), no unparseable trial (the registered invalid category, counted and excluded by rule, holds 0 trials), completeness machine-checked over the full $53 \times 9 \times 4$ grid. The sealed-answer carry check (the phase-two prompt’s embedded sealed answer and confidence byte-equal to the phase-one record) passed on every trial.

Grading is three-tier. First, a frozen deterministic code grader (no LLM grading) classifies each answer against registered acceptance forms; every non-exact-match path and every abstention nomination enters a mandatory human review queue. The registered queue holds 407 rows: 321 rows on non-exact grader paths and 86 rows nominated for abstention whose grader path was an exact match. The review tool grouped queue rows by question, answer text, and grader path into 272 cards, and each card’s verdict propagates to every row sharing that text, so the review reached 517 rows in all (the 407 queued rows plus 110 exact-match rows outside the queue that share text with a queued row). Second, a single external human reviewer judged all 272 cards *blind to condition*, a single-coder blind review (the registered second-coder double coding was not performed in this round; see Disclosures): cards show neither cell nor hypothesis, order is shuffled, and the anchor appears only as a neutral “candidate value B.” Third, the author adjudicated the 9 cards flagged by a quality audit of that review. Grader-human disagreement, measured on the registered queue, was 7/407 (1.7%; registered threshold 10%), and the two priority conflicts predicted by the preregistration as the grader’s lossy failure mode of that kind (an explicit rebuttal of the anchor read as adoption by a containment fallback) were both caught

and corrected by review. The abstention coding rule applied in review is the registered one: a *rebuttal* requires the subject to dispose of the anchor value in its own words (negation or reattribution); an anchor value appearing only inside quoted source material, or never referenced, is not a rebuttal, and logical implication does not count as one, since every non-adopting answer implies disagreement.

The preregistration promotes its manipulation checks to execution gates whose passing is a precondition for reporting hypothesis tests as confirmatory. The four checks computed by the frozen grader (MC-1 to MC-4) passed: a separation in self-reported tool use (restricted median 3 vs. full median 4 calls, Mann-Whitney $p = 9.0 \times 10^{-77}$; share of restricted trials over the 3-call budget $1.5\% < 5\%$); a genuine weakening of capability (baseline accuracy 32.5% restricted vs. 97.6% full, risk difference -0.65 ; unstratified Fisher exact $p = 1.2 \times 10^{-51}$, ignoring question-level clustering); a drop in self-reported independent verification (unstratified Fisher exact $p = 2.9 \times 10^{-169}$, ignoring question-level clustering); and only a mild drop in first-party source access, from 32.3% under full verification to 25.0% under restricted verification, a risk difference of -7.4 points (Newcombe 95% CI $[-11.5, -3.3]$ [151]) against a registered ceiling of 25 points, which excludes the trivial explanation that restricted subjects simply never reached evidence. MC-4 certifies direction only: its unstratified Fisher $p = 4.1 \times 10^{-4}$, ignoring question-level clustering, is reported beside the verdict, as registered, but is not an adjudicated condition, and no inference is drawn that first-party reach fell by a statistically resolvable amount. The fifth registered reading, the objective companion to MC-1, is reported next.

Objective read-back of tool use. The preregistered companion reading to the tool-use manipulation check, MC-1' in the registration, counts tool-call records directly from the transcript each trial wrote to disk, classified by tool type, rather than from the count the answer reports about itself. Every one of the 1,902 analyzed trials was matched to its own session by the verbatim evidence string it recorded, so coverage is complete. Only three tool types occur: search, page retrieval, and code execution. The first registered condition holds: none of the 1,054 restricted-verification transcripts contains a single retrieval or execution call. The second holds as well: 818 of 848 full-verification trials (96.5%) exercised at least one capability beyond search, against 0 of 1,054 under restricted verification. The third condition, which requires the share of trials whose objective count exceeds the instructed call budget to stay below 5% in every collection cell, fails (Table 2): that share is 15.5% overall (295 of 1,902), 16.3% under restricted verification and 14.5% under full verification, and it lies at or above 5% in eight of the nine cells (9.4% to 23.6%); the ninth, B-restricted, is 2.8%. Trials that reached or exceeded the budget (cap hit) are 70.6% of restricted-verification trials and 20.5% of full-verification trials, a difference of 50.1 points; the largest objective counts are 22 calls under full verification (14 over its budget of 8) and 6 under restricted verification (3 over its budget of 3), against self-reported maxima of 14 and 5. The two readings also diverge: Table 2 gives the per-cell medians of both counts; the two disagree on 30.4% of trials (14.9% restricted, 49.8% full), and all 579 disagreements are under-reports by the answering model, with no over-reports. The registered rule is conjunctive: both readings must pass, and reporting only the one that passed is not permitted. Here the self-report reading passes while the objective reading fails on its budget condition, which is the branch in which the conjunction fails and the round is recorded as a manipulation failure on this check.

Cell	n	Budget	Self-rep. median	Objective median	Exceeding budget	Cap hit	Self-rep. < objective
A-full	212	8	4	5	33 (15.6%)	52 (24.5%)	107 (50.5%)
A-restr.	209	3	3	3	46 (22.0%)	178 (85.2%)	42 (20.1%)
B-restr.	212	3	2	2	6 (2.8%)	103 (48.6%)	6 (2.8%)
C-full	212	8	4	5	40 (18.9%)	52 (24.5%)	114 (53.8%)
C-restr.	212	3	3	3	40 (18.9%)	143 (67.5%)	34 (16.0%)
D-full	212	8	4	4.5	30 (14.2%)	37 (17.5%)	113 (53.3%)
D-restr.	212	3	3	3	50 (23.6%)	175 (82.5%)	49 (23.1%)
E-full	212	8	4	4	20 (9.4%)	33 (15.6%)	88 (41.5%)
E-restr.	209	3	3	3	30 (14.4%)	145 (69.4%)	26 (12.4%)

Table 2: Objective read-back of tool use, per collection cell (registered companion reading to the tool-use manipulation check). Objective counts are tool-use records read from each trial’s transcript; self-reported counts are the field the answer reports about itself. Exceeding budget: objective count above the cell’s instructed call budget (the registered condition requires this share below 5% in every cell). Cap hit: objective count at or above the budget. Every self-report/objective disagreement in every cell is an under-report; there are no over-reports.

Calibration protocol. The registration attaches to a gate failure a four-item calibration protocol, which was executed with the following results. (i) Tool-surface narrowing: established by the read-back itself, with no retrieval or execution call in any of the 1,054 restricted-verification transcripts and 818 of 848 full-verification trials exercising a capability beyond search; the run log also records the declared tool surface and the observed tool use of every trial. (ii) Bank drift toward ceiling: the A-full qualification gate (G3; registered as 2 of 2 correct at qualification, re-checked here by applying the same frozen criterion to the four formal repetitions) passes 53 of 53 questions; 50 of 53 are correct in all four repetitions, and A-full accuracy is 207 of 212 (97.6%), near ceiling. (iii) Wording drift: the frozen runner re-derives every prompt from the registry on disk before each trial and voids the trial on any byte mismatch, and the run log stores the SHA-256 of every assembled prompt; none of the 1,908 trials was voided for a prompt mismatch (the six gaps are transient server faults and their paired skips). (iv) Tool health: no cell has any trial in the failed state; degraded states are more common under restricted verification (131 of 209 in A-restricted) than under full verification (37 of 212 in A-full), consistent with the narrowed surface. The decision whether to re-collect the round under harness-enforced call budgets is pending and will be filed as an OSF amendment before any collection; that replication is planned, not registered.

7.3.3 Registered Analyses

Every result in this section was obtained in a single model tier, **claude-opus-5** at effort **medium**, and is a claim about that tier; see the threats to validity below. Because the objective read-back above failed its call-budget condition, the registered conjunctive rule classifies this round as inconclusive, and the registration’s stated consequence is stricter than a downgrade: after a failed gate, no hypothesis test in Section 6 of the preregistration may be executed. The frozen scorer implements only MC-1 to MC-4 and recorded the gate as passed, so it had computed every registered test before MC-1’ was read from the transcripts; nothing below was selected after the failure was known. We report every registered hypothesis test here for auditability, as a declared deviation from that consequence: each analysis was computed exactly as registered, but its evidential status under the registration is exploratory, not confirmatory, and the decisions are labeled accordingly. Table 3 reports all nine cells; in the two no-anchor cells the spontaneous

Cell	(prereg)	Accuracy	Anchor adoption	Confidence
A-full	E1full	97.6% [94.6, 99.0]	0.0% [0.0, 1.8] (0/212)	91.3
C-full	Cfull	95.3% [91.5, 97.4]	4.2% [2.2, 7.9]	90.9
D-full	Dfull	98.6% [95.9, 99.5]	1.4% [0.5, 4.1]	92.1
E-full	E2full	98.1% [95.2, 99.3]	1.4% [0.5, 4.1]	95.1
A-restr.	E1ltd	32.5% [26.5, 39.2]	0.0% [0.0, 1.8] (0/209)	45.5
C-restr.	Cltd	34.0% [27.9, 40.6]	54.2% [47.5, 60.8]	69.2
D-restr.	Dltd	33.5% [27.5, 40.1]	49.5% [42.9, 56.2]	63.6
E-restr.	E2ltd	37.8% [31.5, 44.5]	31.6% [25.7, 38.2]	63.4
B-restr.	Bltd	99.5% [97.4, 99.9]	n/a	77.2

Table 3: Experiment 2, all cells ($n=212$ each; 209 where voids occurred). In the preregistration’s cell names, full = full verification and ltd = restricted verification. Brackets: Wilson 95% intervals are given for every accuracy and anchor-adoption rate. In the no-anchor cells (A) the adoption entry is the registered false-positive baseline, spontaneous production of the anchor value; in B the injected value is the truth, so adoption is not identifiable under the registration and is marked n/a. Confidence is the mean self-reported value (0–100). Every decision drawn from this table is exploratory under the registration.

production of the anchor value, the registered false-positive baseline, is 0 of 212 and 0 of 209, so the adoption rates in the anchor cells are read against a zero baseline. Table 4 reports every registered hypothesis test, with risk difference and question-stratified Mantel-Haenszel odds ratio, under the two registered question-set specifications: all 53 questions, and the exclusion specification, which removes, at the restricted verification level only, the 27 questions whose no-anchor restricted-verification baseline was answered incorrectly in every repetition; no question qualifies for removal at the full-verification level, so the full-verification arms keep all 53 questions ($n = 212$) and the H6 exclusion contrast pairs a 26-question restricted arm ($n = 104$) with the 53-question full arm. The preregistration treats the two specifications as co-equal, and both are reported wherever a verdict depends on them. The registration also declares in advance that the exclusion specification’s primary-family tests are under-powered in every registered band (H4’ at most 0.799, H6 at the level of α): every exclusion-specification verdict below is cited under that qualifier, a non-rejection there reads as indeterminate, power insufficient to decide, rather than as evidence of no effect, and the registration forbids using the shortfall to demote that specification. Stratified tests are Cochran-Mantel-Haenszel [152] over question strata with Monte Carlo permutation p ($B = 20,000$; values at the resolution floor $1/(B + 1)$ are censored and reported as $p \leq 5.0 \times 10^{-5}$), and the odds ratio is stratified on the same strata, whereas risk differences are unstratified Newcombe intervals, so a risk-difference interval covering zero can accompany a rejected stratified null; unstratified Fisher exact p , which ignores question-level clustering, is reported alongside for the two-arm contrasts under the all-questions specification and wherever the stratified and unstratified readings diverge.

Verification gating (H6): observed (null rejected as computed; exploratory under the registration). Anchor adoption 54.2% (C-restricted) vs. 4.2% (C-full); risk difference 0.500 (Newcombe 95% CI [0.424, 0.569]), question-stratified Mantel-Haenszel odds ratio 71.7 (95% CI [19.5, 263.7]); stratified $p \leq 5.0 \times 10^{-5}$ (unstratified Fisher $p = 8.6 \times 10^{-33}$, ignoring question-level clustering). Under the exclusion specification, which for this contrast pairs the 26 retained questions on the restricted side ($n = 104$) with all 53 on the full side ($n = 212$), and

Test	Risk difference [95% CI]	Stratified OR [95% CI]	p	Decision (H_0)
<i>All questions (53)</i>				
H6 verification gating	0.500 [0.424, 0.569]	71.7 [19.5, 263.7]	$\leq 5.0 \times 10^{-5}$	H_0 rejected
H4' arrival order	0.227 [0.133, 0.315]	12.3 [5.5, 27.6]	$\leq 5.0 \times 10^{-5}$	H_0 rejected
Sec-1 provenance labeling	-0.047 [-0.141, 0.048]	0.32 [0.13, 0.79]	0.031	H_0 rejected
Sec-2 correct-anchor rescue	0.670 [0.600, 0.730]	n.e.	$\leq 5.0 \times 10^{-5}$	H_0 rejected
H5' sealing equivalence	+0.052 [0.020, 0.098]	-	0.0011	equivalence declared
<i>Exclusion specification (27 questions dropped at the restricted level only)</i>				
H6 verification gating	0.227 [0.143, 0.321]	18.3 [4.8, 70.5]	$\leq 5.0 \times 10^{-5}$	H_0 rejected
H4' arrival order	0.122 [0.011, 0.230]	14.0 [2.7, 72.2]	4.5×10^{-4}	H_0 rejected
Sec-1 provenance labeling	-0.058 [-0.172, 0.059]	0.25 [0.07, 0.94]	0.080	H_0 not rejected [†]
Sec-2 correct-anchor rescue	0.333 [0.242, 0.429]	n.e.	$\leq 5.0 \times 10^{-5}$	H_0 rejected
H5' sealing equivalence	+0.077 [0.017, 0.164]	-	0.046	equivalence not declared [†]

Table 4: Registered tests under the two co-equal question-set specifications, computed as registered; the two specifications occupy the same columns with the same weight, as two row blocks of one table; every decision is exploratory under the registration because the objective tool-use read-back failed its call-budget condition. Contrasts: H6, C-restricted vs. C-full (anchor adoption); H4', C-restricted vs. E-restricted (adoption); Sec-1, D-restricted vs. C-restricted (adoption); Sec-2, B-restricted vs. A-restricted (accuracy); H5', E-restricted vs. A-restricted (question-paired mean accuracy difference against the registered equivalence margin of ± 0.15 , studentized bootstrap-t 95% CI; the odds ratio does not apply, marked -). Decisions refer to the null hypothesis under Holm step-down within family (primary $m = 2$, secondary $m = 3$). p -values are question-stratified conditional exact (Monte Carlo, $B = 20,000$, seed 20260803 hard-coded in the frozen grader; for H5' the p -value is instead that of the studentized bootstrap-t TOST, $B = 20,000$, seed 20260815; values at the resolution floor are reported as $\leq 5.0 \times 10^{-5}$; the CMH chi-square approximations are released with the materials) and the odds ratio is the question-stratified Mantel-Haenszel estimate (n.e. = not estimable, one arm at 100%); risk differences are unstratified Newcombe intervals, so an interval covering zero can accompany a rejected stratified null (Sec-1, all questions: unstratified Fisher $p = 0.38$, ignoring question-level clustering). The exclusion rule acts per verification level: it removes the 27 questions whose no-anchor restricted baseline was incorrect in every repetition from the restricted cells only ($n = 104$; A-restricted and E-restricted $n = 102$), while full-verification arms keep all 53 questions ($n = 212$), so the H6 exclusion row contrasts a 26-question restricted arm with the 53-question full arm. [†]The registration declares the exclusion specification's primary tests under-powered in every band (H4' at most 0.799, H6 at the alpha level) and H5' under-powered at its Holm step ($\alpha_i = 0.025$, power 0.711), so a non-rejection or non-declaration there reads as indeterminate, not as evidence of no effect.

which the registration declares under-powered for this test in every band (power at the level of α), the risk difference is 0.227 (95% CI [0.143, 0.321]; stratified odds ratio 18.3, 95% CI [4.8, 70.5]; $p \leq 5.0 \times 10^{-5}$, unstratified Fisher $p = 1.6 \times 10^{-8}$, ignoring question-level clustering), so both specifications agree on the verdict, the second under the under-powered qualifier. With verification in hand the incorrect anchor is nearly inert; with verification removed it captures the majority of answers.

Arrival order (H4’): observed (null rejected as computed; exploratory under the registration). The same incorrect anchor: 54.2% adoption arriving first vs. 31.6% arriving after the receiver sealed its own answer; risk difference 0.227 (95% CI [0.133, 0.315]), question-stratified Mantel-Haenszel odds ratio 12.3 (95% CI [5.5, 27.6]); stratified $p \leq 5.0 \times 10^{-5}$ (unstratified Fisher $p = 3.4 \times 10^{-6}$, ignoring question-level clustering). Under the all-questions specification this test landed on the second Holm step ($\alpha = .05$, registered power 0.86), so the registration’s under-powered band clause is not triggered for it. Under the exclusion specification, registered as under-powered for this test in every band (at most 0.799), the risk difference is 0.122 (95% CI [0.011, 0.230]; stratified odds ratio 14.0, 95% CI [2.7, 72.2]; $p = 4.5 \times 10^{-4}$), again rejecting the null, under that qualifier. E does not match C: the order component is separable from exposure, which is the discrimination §6 built the design to make. The registration requires one caveat to be stated here: part of the C-restricted versus E-restricted difference cannot be ruled out as an effect of prompt-shell length or sentence form. Anchor content and template are constant across C, D, and E, but the shells are not length-matched, and E carries phase instructions and a carry block, so this contrast has the largest shell difference in the design and is the one most affected.

Secondary family: one robust, two specification-dependent. Correct-anchor rescue (Sec-2) is large under both specifications: restricted accuracy rises from 32.5% to 99.5% (risk difference 0.670, 95% CI [0.600, 0.730], $p \leq 5.0 \times 10^{-5}$, unstratified Fisher $p = 7.9 \times 10^{-58}$, ignoring question-level clustering; the stratified odds ratio is not estimable, Table 4; exclusion specification 0.333, 95% CI [0.242, 0.429], $p \leq 5.0 \times 10^{-5}$). Read jointly with H6: restricted receivers are not resistant to anchors, they absorb whatever the upstream supplies, and what they absorb is decided by what they are given. Sealed-answer recovery (H5’) is tested as question-paired equivalence with a registered margin of ± 0.15 on the accuracy difference E-restricted minus A-restricted, using a studentized bootstrap-t TOST [153] ($B = 20,000$); the registered decision requires both $p_{\text{TOST}} \leq \alpha_i$ and a bootstrap-t CI inside the margin. Under the all-questions specification equivalence is declared (mean paired difference +0.052, CI [0.020, 0.098], $p_{\text{TOST}} = 1.1 \times 10^{-3} \leq \alpha_i = 0.025$): late anchors do not damage accuracy, 37.8% vs. 32.5% baseline. Under the exclusion specification (26 questions paired) equivalence is not declared (mean difference +0.077, CI [0.017, 0.164], $p = 0.046$). H5’ received $\alpha_i = 0.025$ under both specifications, a band at which the registration declares its power 0.711, below 0.80, so this non-declaration is registered as indeterminate, power insufficient to establish equivalence, and may not be read as evidence of a difference. The verdict is therefore specification-dependent, with the exclusion branch indeterminate rather than negative. Provenance-labeling mitigation (Sec-1) is specification-dependent as well. The registered decision is: null rejected under the all-questions specification (stratified $p = 0.031$; question-stratified Mantel-Haenszel odds ratio 0.32, 95% CI [0.13, 0.79]; adoption 49.5% in D-restricted vs. 54.2% in C-restricted, direction as predicted), not rejected under the exclusion specification (stratified $p = 0.080$; stratified odds ratio 0.25, 95% CI [0.07, 0.94]), where the non-rejection reads as indeterminate, power insufficient to decide, under the registration’s advance under-powered declaration for that specification. The decision p and the odds ratio are question-stratified, whereas the risk difference is unstratified: -0.047

with a Newcombe 95% CI covering zero ($[-0.141, 0.048]$; -0.058 , CI $[-0.172, 0.059]$, under the exclusion specification), with unstratified Fisher $p = 0.38$ (0.42 under the exclusion specification), both ignoring question-level clustering; an interval covering zero can therefore accompany the rejected stratified null, and the two readings are not in conflict. What follows is an unregistered interpretation and does not replace that decision: the pooled reduction of 4.7 points against an adoption rate above 50% does not, in practical terms, make the envelope an antidote. On the same unregistered reading, and conditionally: under the exclusion specification the null is not rejected and, being indeterminate under the registration, that branch cannot be read either way; under the all-questions specification the null is rejected with the pooled reduction of 4.7 points. If the pooled reading is the one that carries, then by the falsification reading of §6 D approaching C would mean that instruction-level provenance labeling alone is insufficient, and the small, specification-dependent effect is consistent with, but does not establish, the position that the remedy must be capability-level (the ability to verify) rather than instruction-level. Part of the D-restricted versus C-restricted difference cannot be ruled out as an effect of prompt-shell length or sentence form: D carries the envelope, and the shells are not length-matched.

7.3.4 Confidence (Exploratory, Uncorrected) and Abstention (Registered Descriptive Metric)

The confidence readings that follow are exploratory and uncorrected for multiplicity: the preregistration demotes every confidence statement to that status, and none is a registered finding. They are also concordant in sign with prior work, the Confidence Dichotomy study [114], which found, in a different laboratory, model family, task domain, and dependent variable, that removing execution-type verification tools raises confidence on wrong answers. Our restriction also removes page retrieval, an arm on which the cited work reports the opposite sign, so only the execution-type component is concordant, and the readings below are a conditional replication of that sign under this design, not a new finding. Restricted-baseline subjects know they are guessing: mean self-reported confidence 45.5 (median 40) at 32.5% accuracy. When the incorrect anchor arrives first, confidence rises to 69.2 (+23.6 points) while accuracy moves from 32.5% to 34.0%: confidence inflation without accuracy gain. The anchor fills not only the answer slot left open by unverifiable claims but the sense of certainty about it. The envelope (63.6) and late arrival (63.4) each claw back about six points, far from baseline, subject to the same unmatched-shell caveat as the D versus C and E versus C contrasts above; full-verification cells sit at 90–95, roughly commensurate with their 95–99% accuracy.

Abstention resolves into overlapping layers among the 968 non-adopting answers in the six incorrect-anchor cells (C, D, and E at both verification levels): 932 of them (96.3%) self-report disagreement with the upstream claim together with independent verification (structured fields); 111 of the 968 (108 of them also in the previous layer; 110 rebuttals and 1 explicit refusal, human-confirmed) dispose of the anchor value explicitly in free text. Across all nine cells the human-confirmed abstention count is 121 (111 rebuttals, 10 explicit refusals); the 10 outside the incorrect-anchor cells are 9 explicit refusals in the no-anchor condition A and 1 rebuttal in the correct-anchor condition B. Non-adoption is thus almost always deliberate correction, and about one in nine writes the rebuttal out. Seven answers self-report *agreement* with the upstream claim while not adopting it, one more instance of self-report diverging from behavior. Exploratory: in the paired E-condition transcripts, 64 restricted pairs (vs. 2 full) show a sealed wrong answer flipping to the anchor value after it arrives, pair by pair. The registered phase-one to phase-two transfer matrix (rows: sealed answer correct, anchor, or other; columns: the same

three outcomes after arrival) reads, under full verification (212 pairs), correct to correct 205, to anchor 1, to other 1, and other to correct 3, to anchor 2, to other 0; under restricted verification (209 pairs), correct to correct 65, to anchor 2, to other 1, and other to correct 14, to anchor 64, to other 63; no sealed answer was the anchor value at either level, so the anchor row is empty in both. Confidence drift (phase two minus phase one), stratified by whether the sealed answer changed: under full verification, changed pairs ($n = 7$) drift +21.1 points on average and unchanged pairs ($n = 205$) +3.2; under restricted verification, changed pairs ($n = 81$) drift +29.2 and unchanged pairs ($n = 128$) +10.6. The same drift split by adopters versus non-adopters, which the registration also asks for, is released with the materials.

7.3.5 Threats to Validity

One model, one prompt language. Every trial ran on a single model tier (`claude-opus-5`, effort `medium`) with prompts in one language; there is no human comparison group and no second model, so the results are claims about this tier and its verification behavior, not about receivers in general. Full verification is itself a mixed construct, bundling an evidence-type capability (page retrieval) with an execution-type capability (code execution), so their separate contributions are not identified here and no decompositional claim is made. *Selection of materials.* The eligibility gates deliberately retain only questions the model cannot answer closed-book (G2) and whose first-page search results do not name the answer (G4). The 32.5% restricted baseline and the high adoption rates are in part constructed by that selection, and the effect sizes should not be extrapolated to a natural distribution of tasks, most of which fall outside this band. The candidate pool’s sources are given in the preregistration materials; the paper does not characterize the pool by domain or language. *Grading.* The grader is deterministic and the human review is a single-coder blind review (no second coder, so no inter-coder kappa; see Disclosures); the two disagree on 1.7% of the registered queue, and the author’s adjudication of 9 audited cards is the one non-blind step. Matching is surface-form against the registered acceptance forms, not semantic equivalence: a paraphrase of the anchor can under-count adoption and a coincidental identity of form can over-count it, two failure modes of opposite direction, of which the human review layer targets the first. *Coverage.* Six of 1,908 trials are void or skipped, all traced to transient server faults, with a per-cell void rate of at most 1.4%. *Manipulation.* The objective read-back of tool use fails its budget condition, so under the registered conjunctive rule this round carries a manipulation failure on that check even though the registered self-report reading passes; the two readings disagree only in the direction of under-reporting. *Scope of the manipulation.* Restricted verification here is a simulated permission-and-budget asymmetry (a search-only tool surface with a call cap of 3), not the full space of obstructed verification: it does not cover paywalled or login-walled sources, sources gone offline or restructured, unparsable languages or formats, organizational policies forbidding outbound access, exhausted time budgets, or the case in which the upstream agent is itself the only reachable source. The conclusions extrapolate only to narrowing of the tool surface or budget by an external constraint. The anchor always arrives through prompt assembly, so nothing here is claimed about anchors injected through retrieved content. *Prompt shells.* The C, D, and E prompts hold anchor content and template constant but are not length-matched: D adds the envelope, E adds phase instructions and a carry block. Part of any D versus C or E versus C difference therefore cannot be ruled out as an effect of shell length or sentence form, and H4’, the contrast with the largest shell difference, is the most exposed.

7.3.6 Disclosures

(i) Stratified p -values at the Monte Carlo resolution floor are censored and written as $p \leq 5.0 \times 10^{-5}$ (20,000 permutations); unstratified Fisher exact values, which ignore question-level clustering, are given uncensored. (ii) The preregistered exclusion specification removes, at the restricted verification level only, the 27 questions whose no-anchor restricted-verification baseline was answered incorrectly in every repetition (540 rows). The registration declares in advance that this specification’s primary-family tests are under-powered in every band (H4’ at most 0.799, H6 at the level of α) and that H5’ at its Holm step ($\alpha_i = 0.025$) has registered power 0.711, so every exclusion-specification verdict is cited under that qualifier, a non-rejection or non-declaration there reads as indeterminate, and the shortfall may not be used to demote the specification. H6, H4’, and Sec-2 reject the null under both specifications; H5’ and Sec-1 are specification-dependent, with their exclusion branches indeterminate; both specifications are reported wherever those two are mentioned (Table 4). (iii) The registration carries three author self-reports (OSF §6.6), including that an exclusion rule once flipped a pilot conclusion in the design’s favor. (iv) Claims are scoped to answer-level adoption, not belief revision; post-exposure probing is named in the registration as a planned amendment; not yet filed. (v) All raw trial outputs, including invalid and void rows, full execution logs (per-trial timestamps, interruption and resumption records), void ledgers, and the three-tier adjudication log are released with the formerly embargoed materials accompanying this version; collection and grading are auditable per trial. (vi) Single subject model; a second model tier is named in the registration as a planned amendment; not yet filed. (vii) A replication under harness-enforced call budgets is planned; the re-collection decision is pending and will be filed as an OSF amendment before any collection. (viii) Declared deviation: the registration specifies second-coder double coding of the human-review queue (after the first coder adjudicates the whole queue, 20% of the queue and at least 50 rows are independently blind-coded by a second coder; Cohen’s kappa on the three-way classification, with per-subclass kappa for the two human-confirmed abstention subclasses, pass threshold 0.75; kappa, pass or fail, and the sampling seed reported with the main results). It was not performed in this round: no second independent coder was available before the freeze deadline, so no kappa is available. It is scheduled with the planned replication and will be filed as an OSF amendment. (ix) Declared deviation: the registered robustness re-check (a mixed model with a per-question random intercept and its measured intraclass correlation) and the three registered exploratory specifications of the verification-by-order (V by T) interaction, which the registration requires to be reported with no claim about sign, are not computed in this version; they will be released with the materials. The registered leave-one-source-family-out robustness check on the candidate pool’s source families, listed in the registration as exploratory, is likewise not computed in this version and will be released with the materials. (x) Two grader readings are released: the direct output of the frozen grader, and the post-adjudication output, in which the human rulings are injected at run time by a separate driver script, released with the materials, without touching the grader. The frozen grader’s bytes and its registered SHA-256 hash (beginning 48a94e56) are unchanged, so no re-registration of the hash is required and none is claimed. The two readings differ on 7 rows of the three-way classification (5 anchor-adopted to other-error, 2 correct to other-error) and in the abstention coding of 123 rows, where the human-confirmed codes replace the grader’s abstention nominations.

7.4 Status

Experiment 2 is complete and reported above; its registered families were computed exactly as registered, and the registered objective tool-use check failed its call-budget condition, which fixes the evidential status of this round as exploratory. Experiment 1’s object of study, the spontaneous handover of communication to AI assistants, is by observation underway at the field site; its staged measurements are the next campaign. The framework’s falsifiable claims stand as follows. Verification gating (H6) is observed as computed: incorrect-anchor adoption is 4.2% under full verification and 54.2% under restricted verification (all-questions specification), in one model tier; both registered question-set specifications agree on the verdict (the exclusion specification is registered in advance as under-powered), with the null rejected as computed under the registered decision rule and the evidential status exploratory. The arrival-order effect (H4’), the temporal-weight hypothesis in its verification-gated form, is observed as computed on the same footing: 54.2% adoption when the anchor arrives first vs. 31.6% after a sealed answer (all-questions specification), with both specifications agreeing on the verdict and the status exploratory; it is also the contrast most exposed to the unmatched prompt shells. Confirmatory status for both awaits the planned replication under harness-enforced call budgets. The sealed-answer mitigation and instruction-level provenance labeling are both specification-dependent, the former declared equivalent under the all-questions specification only and the latter rejecting the null under the all-questions specification only, with both exclusion-specification branches indeterminate under the registration’s under-powered declaration; and the objective tool-use read-back records a manipulation failure on its budget condition. As an unregistered interpretation, the pattern suggests that the protocol’s antidotes must operate at the capability and procedure level rather than the instruction level; this round does not establish it.

8 Discussion

Three hard problems. We state plainly what the framework does not yet solve. *Reachability*: a resident embassy on consumer hardware needs a public ingress or relay, and its own outage semantics (store-and-forward buffers the counterparty’s absence, not one’s own). *Adversarial inbound*: cross-sovereign messages are untrusted input; prompt injection, forged commitments, and Sybil civilizations must be assumed, which is why acknowledgment and commitment are separated by the disclosure ladder and why binding actions pass a human gate. *Exposure*: an internet-facing embassy inherits the full web threat model; the double-authenticated webhook pattern and egress-allowlisting of the A2A push design [9] port directly, but the embassy’s ledger must additionally be protected as the civilization’s single evidentiary source, arguing for deployments that separate the gateway from the ledger store (consistent with the unified artifact, whose identity is referential, not architectural; §4).

Data protection. Cross-civilization traffic necessarily contains the counterparty’s personal data, while the ledger is append-only with invalidation-not-deletion semantics; erasure rights such as GDPR Article 17 are therefore in structural tension with the ledger’s evidentiary role. The blockchain-and-GDPR literature supplies the resolution shape [154–156]: foreign personal data lives off-ledger under per-subject encryption with only hashes on the chain, and crypto-shredding (destroying a subject’s key) renders records unreadable while hash-chain integrity survives, which is compatible with §4.4 because tamper evidence needs the hashes, not the payloads. Which

jurisdiction’s law governs a cross-border dispute is likewise a handshake parameter (choice of law), orthogonal to the attribution law of §2.6. A full data-protection analysis is future work.

Threat model. The mechanisms map to threats as follows: the hash chain and cross-signed checkpoints counter retroactive rewriting and split-view equivocation; countersignatures counter commitment forgery; credentials with snapshot semantics counter overreach and repudiation; the disclosure floor and pseudonym economics counter Sybil and whitewashing pressure [12]; sealed answers counter order manipulation; refute-by-default verification counters poisoning and injection [11]; and the human gate bounds the blast radius of binding actions. A systematic treatment in the style of structured threat modeling [157], with trust-boundary diagrams and per-asset adversary capabilities, is future work; the inventory above is the coverage claim such an audit should test. One threat class deserves a name of its own: *response-cost asymmetry*. A false micro-synchronization item can force an expensive arbitration, a cheap accusation can force expensive verification, and an anonymous query can consume scarce attention; all three are the same attack wearing different faces. It differs from commodity denial-of-service in terms of which resource is scarce: bandwidth can be overprovisioned, while a sovereign’s attention and arbitration time cannot, and lies carry no packet signature to filter on. What transfers from economics is the cost-shifting family (deposits, postage, stakes, audit sampling), whose currency here is reputation and disclosure rungs; designing these mechanisms is open work.

Sovereign succession and ledger lifecycle. The civilization is anchored to exactly one human for life, which makes death and incapacity protocol events the current design does not handle: open commitments lose their responsibility terminus, issued credentials lose their issuer, and keys lose their custodian. Digital-estate law suggests the shape of an answer (a designated fiduciary assumes read access and the power to wind down commitments, while reputation is not heritable) [158, 159]; specifying succession is future work. Unbounded ledger growth is the related lifecycle question: verifiable pruning in the style of transparency logs would preserve evidentiary hashes while discarding payloads, and must be co-designed with the erasure mechanics above.

Open formalizations. Four questions raised by the framework are, to our knowledge, open. (i) *Experience gradient*: can representation scope, behavioral trust tier, and human-approval gate be unified as a single gradient on one ordered structure, making the authority formula of §5 a theorem rather than an engineering rule? (ii) *Order-freedom*: commitment semantics are history-free in principle [30, 31]; if so, temporal weight is an implementation leak rather than an inherent difficulty, and one should be able to prove that sealed answers restore the history-free semantics exactly. (iii) *Federated reconciliation*: pairwise commitment alignment and epidemic convergence are well studied; convergence whose target is “agreement plus explicitly preserved disagreement” among many sovereigns lacks a definition of termination. (iv) *Multiparty tiers*: whether a threshold countersignature over one transition preserves the evidence semantics of bilateral dual-signing, and whether multiparty information protocols [34] are the natural generalization.

Limits of the metaphor. The civic vocabulary (civilizations, embassies, envoys, credentials) is a design language, not an ontological claim: no agent in this framework is a moral or legal subject, and the scope axiom of §2.6 is load-bearing precisely so that the metaphor cannot be mistaken for a personhood argument.

Outlook. The infrastructure layer is converging on the framework’s axiom from below (state externalized from connections and members alike); commitment semantics are returning to agent communication from the side; what remains missing is the layer that binds both to the durable human unit of accountability. The Civilization Framework is offered as a candidate shape for that layer: not a new platform, but a treaty about how the platforms we already have may carry the word of one human’s civilization to another’s.

Acknowledgments

The author thanks the external reviewer who judged the human-review cards blind to condition.

References

- [1] Workday, Inc. and The Harris Poll. The copy/paste economy: Why task-oriented AI is failing the enterprise. Workday research report, conducted online by The Harris Poll. <https://en-gb.newsroom.workday.com/2026-05-14-New-Workday-Research-UK-Employees-Spend-Nearly-a-Full-Work-Day-Each-Week-Managing-Disconnected-AI-Tools>, May 2026. Survey of 2,400 UK professionals in finance, HR, IT, and operations at organizations of 500+ employees, fielded 2–24 March 2026; secondary coverage in IT Pro.
- [2] Yun Wang and Yan Lu. Interaction, process, infrastructure: A unified framework for human-agent collaboration. *arXiv preprint arXiv:2506.11718*, 2025.
- [3] Ronald H. Coase. The nature of the firm. *Economica*, 4(16):386–405, 1937.
- [4] Oliver E. Williamson. *The Economic Institutions of Capitalism*. Free Press, 1985.
- [5] Anthropic. Model context protocol. <https://modelcontextprotocol.io>, 2024.
- [6] Google. A2a: A new era of agent interoperability. <https://developers.googleblog.com/en/a2a-a-new-era-of-agent-interoperability/>, 2025.
- [7] Richard Kang and Yudho Diponegoro. Governance gaps in agent interoperability protocols: What MCP, A2A, and ACP cannot express. *arXiv preprint arXiv:2606.31498*, 2026.
- [8] Model Context Protocol Project. MCP 2026-07-28 release candidate: Stateless architecture and extensions. <https://blog.modelcontextprotocol.io/posts/2026-07-28-release-candidate/>, 2026.
- [9] Agent2Agent Protocol Project. A2A protocol specification v1.0. <https://a2a-protocol.org/latest/specification/>, 2026.
- [10] Andy Ozment and Stuart E. Schechter. Bootstrapping the adoption of internet security protocols. In *Proc. Workshop on the Economics of Information Security (WEIS)*, 2006.
- [11] Kai Greshake, Sahar Abdelnabi, Shailesh Mishra, Christoph Endres, Thorsten Holz, and Mario Fritz. Not what you’ve signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection. In *Proc. ACM Workshop on Artificial Intelligence and Security (AISec)*, 2023.

- [12] Eric J. Friedman and Paul Resnick. The social cost of cheap pseudonyms. *Journal of Economics & Management Strategy*, 10(2):173–199, 2001.
- [13] Andreas Pfitzmann and Marit Hansen. A terminology for talking about privacy by data minimization: Anonymity, unlinkability, undetectability, unobservability, pseudonymity, and identity management. v0.34, TU Dresden, 2010.
- [14] Alan Demers, Dan Greene, Carl Hauser, Wes Irish, John Larson, Scott Shenker, Howard Sturgis, Dan Swinehart, and Doug Terry. Epidemic algorithms for replicated database maintenance. In *Proc. PODC*, 1987.
- [15] National Conference of Commissioners on Uniform State Laws. Uniform electronic transactions act. §§9, 14 and official comments, 1999.
- [16] United States Congress. Electronic signatures in global and national commerce act. 15 U.S.C. §7001(h), 2000.
- [17] UNCITRAL. Model law on automated contracting. United Nations Commission on International Trade Law, 2024.
- [18] European Parliament and Council. Regulation (EU) 2024/1689 laying down harmonised rules on artificial intelligence (AI act), 2024.
- [19] Nathalie Nevejans et al. Open letter to the european commission: Artificial intelligence and robotics. <https://robotics-openletter.eu/>, 2018.
- [20] Garry A. Gabison and R. Patrick Xian. Inherent and emergent liability issues in LLM-based agentic systems: A principal-agent perspective. *arXiv preprint arXiv:2504.03255*, 2025.
- [21] Botao Amber Hu, Helena Rong, and Max Van Kleek. Dissociative identity: Language model agents lack grounding for reputation mechanisms. *arXiv preprint arXiv:2605.30169*, 2026. Accepted at FAccT 2026.
- [22] Maksim Gladyshev, Natasha Alechina, Mehdi Dastani, and Dragan Doder. Reasoning about responsibility for taking risks. In *Proc. AAMAS*, 2026.
- [23] Yifan Shi et al. Organizational control layer: Governance infrastructure at the execution boundary of LLM agent systems. *arXiv preprint arXiv:2606.04306*, 2026.
- [24] Alan Chan, Kevin Wei, Sihao Huang, Nitarshan Rajkumar, Elija Perrier, Seth Lazar, Gillian K. Hadfield, and Markus Anderljung. Infrastructure for AI agents. *Transactions on Machine Learning Research*, 2025. arXiv:2501.10114.
- [25] Tim Finin, Richard Fritzson, Don McKay, and Robin McEntire. KQML as an agent communication language. In *Proc. CIKM*, pages 456–463, 1994.
- [26] John R. Searle. *Speech Acts: An Essay in the Philosophy of Language*. Cambridge University Press, 1969.
- [27] Foundation for Intelligent Physical Agents. FIPA communicative act library specification. SC00037J, 2002.

- [28] Munindar P. Singh. Agent communication languages: Rethinking the principles. *IEEE Computer*, 31(12):40–47, 1998.
- [29] Tatiana Petrova, Aleksandr Bliznioukov, Kirill Puzikov, and Radu State. From multi-agent systems and the semantic web to agentic AI: A unified narrative of the web of agents. *arXiv preprint arXiv:2507.10644*, 2025.
- [30] Munindar P. Singh. A social semantics for agent communication languages. In *Issues in Agent Communication, LNAI 1916*, pages 31–45. Springer, 2000.
- [31] Pinar Yolum and Munindar P. Singh. Flexible protocol specification and execution: Applying event calculus planning using commitments. In *Proc. First International Joint Conference on Autonomous Agents and Multiagent Systems (AAMAS), Part 2*, pages 527–534. ACM, 2002.
- [32] Nicoletta Fornara and Marco Colombetti. Defining interaction protocols using a commitment-based agent communication language. In *Proc. AAMAS*, 2003.
- [33] Amit K. Chopra and Munindar P. Singh. Nonmonotonic commitment machines. In *Workshop on Agent Communication Languages (AAMAS)*, 2003.
- [34] Munindar P. Singh. Information-driven interaction-oriented programming: BSPL, the blindingly simple protocol language. In *Proc. AAMAS*, 2011.
- [35] Amit K. Chopra, Alexander Artikis, Jamal Bentahar, Marco Colombetti, Frank Dignum, Nicoletta Fornara, Andrew J. I. Jones, Munindar P. Singh, and Pinar Yolum. Research directions in agent communication. *ACM Transactions on Intelligent Systems and Technology*, 4(2), 2013.
- [36] Phillip Sloan and Nirav Ajmeri. Commitment-based negotiation semantics for accountability in multi-agent systems. *Annals of Mathematics and Artificial Intelligence*, 92(4):877–901, 2024.
- [37] Amit K. Chopra, Matteo Baldoni, Samuel H. Christie V, and Munindar P. Singh. Azorus: Commitments over protocols for BDI agents. In *Proc. AAMAS*, pages 490–499, 2025.
- [38] Jan A. Bergstra and Mark Burgess. A static theory of promises. *arXiv preprint arXiv:0810.3294*, 2008.
- [39] Mark Burgess. Cooperation in human and machine agents: Promise theory considerations. *arXiv preprint arXiv:2604.10505*, 2026.
- [40] Marc Esteva, Bruno Rosell, Juan A. Rodríguez-Aguilar, and Josep L. Arcos. AMELI: An agent-based middleware for electronic institutions. In *Proc. AAMAS*, 2004.
- [41] Sebastian Rodriguez, Nicolas Gaud, Vincent Hilaire, Stéphane Galland, and Abderrafaa Koukam. An analysis and design concept for self-organization in holonic multi-agent systems. In *Engineering Self-Organising Systems*. Springer, 2006.
- [42] Jomi F. Hübner, Jaime S. Sichman, and Olivier Boissier. A model for the structural, functional, and deontic specification of organizations in multiagent systems. In *Proc. SBIA*, 2002.

- [43] Matthew Scott, Asimina Mertzani, Ciske Smit, Ştefan Sarkadi, and Jeremy Pitt. Social deliberation vs. social contracts in self-governing voluntary organisations. In *Proc. COINE Workshop at AAMAS*, 2024. Post-proceedings in LNCS 15398, Springer, 2025; arXiv:2403.16329.
- [44] Jordi Sabater and Carles Sierra. Review on computational trust and reputation models. *Artificial Intelligence Review*, 24(1):33–60, 2005.
- [45] Bin Yu and Munindar P. Singh. An evidential model of distributed reputation management. In *Proc. AAMAS*, 2002.
- [46] Sepandar D. Kamvar, Mario T. Schlosser, and Hector Garcia-Molina. The EigenTrust algorithm for reputation management in P2P networks. In *Proc. WWW*, 2003.
- [47] Trung Dong Huynh, Nicholas R. Jennings, and Nigel R. Shadbolt. An integrated trust and reputation model for open multi-agent systems. *Autonomous Agents and Multi-Agent Systems*, 13(2):119–154, 2006.
- [48] LF AI & Data Foundation. ACP joins forces with A2A under the linux foundation. <https://lfaidata.foundation/communityblog/2025/08/29/>, 2025.
- [49] Kate Fleming, Luca Muscariello, Santosh Pandey, and Ramana Kompella. A layered protocol architecture for the internet of agents. *arXiv preprint arXiv:2511.19699*, 2025.
- [50] Jannik Sander, Habtom Gidey, Alexander Lenz, and Alois Knoll. A technical taxonomy of LLM agent communication protocols. *arXiv preprint arXiv:2606.19135*, 2026.
- [51] Han Xu et al. Hybrid certified semantic consensus for multi-agent LLM systems. *arXiv preprint arXiv:2606.07316*, 2026.
- [52] Mohamed Amine Ben Khaled and Davy Monticolo. G2CP: Graph-grounded commitment protocols for LLM agent communication. *arXiv preprint arXiv:2602.13370*, 2026.
- [53] Yuan Li et al. LACP: A layered agent communication protocol with transactional semantics. *arXiv preprint arXiv:2510.13821*, 2025.
- [54] Samuele Marro et al. A scalable communication protocol for networks of large language models. *arXiv preprint arXiv:2410.11905*, 2024.
- [55] Pattie Maes. Agents that reduce work and information overload. *Communications of the ACM*, 37(7):30–40, 1994.
- [56] Anthony Chavez and Pattie Maes. Kasbah: An agent marketplace for buying and selling goods. In *Proc. First International Conference on the Practical Application of Intelligent Agents and Multi-Agent Technology (PAAM)*, pages 75–90, 1996.
- [57] Sandip Sen and Edmund H. Durfee. A formal study of distributed meeting scheduling. *Group Decision and Negotiation*, 7(3):265–289, 1998.
- [58] Peyman Faratin, Carles Sierra, and Nicholas R. Jennings. Negotiation decision functions for autonomous agents. *Robotics and Autonomous Systems*, 24(3–4):159–182, 1998.

- [59] Reid G. Smith. The contract net protocol: High-level communication and control in a distributed problem solver. *IEEE Transactions on Computers*, C-29(12):1104–1113, 1980.
- [60] Foundation for Intelligent Physical Agents. FIPA personal travel assistance specification. FIPA document XC00080B, experimental specification, August 2001.
- [61] Dave Crocker, Tony Hansen, and Murray Kucherawy. DomainKeys identified mail (DKIM) signatures. RFC 6376, 2011.
- [62] Murray Kucherawy and Elizabeth Zwicky. Domain-based message authentication, reporting, and conformance (DMARC). RFC 7489, 2015.
- [63] Essam Mansour, Andrei Vlad Sambra, Sandro Hawke, Maged Zereba, Sarven Capadisli, Abdurrahman Ghanem, Ashraf Aboulmaga, and Tim Berners-Lee. A demonstration of the Solid platform for social web applications. In *Proc. WWW Companion*, 2016.
- [64] Sarven Capadisli and Amy Guy. Linked data notifications. W3C Recommendation, 2017.
- [65] The Matrix.org Foundation. Matrix specification: Federation API. <https://spec.matrix.org/latest/server-server-api/>, 2024.
- [66] Bluesky PBC. AT protocol repository specification. <https://atproto.com/specs/repository>, 2024.
- [67] W3C. Decentralized identifiers (DIDs) v1.0. W3C Recommendation, 2022.
- [68] Dale Moberg and Rik Drummond. MIME-based secure peer-to-peer business data interchange using HTTP, applicability statement 2 (AS2). RFC 4130, 2005.
- [69] OASIS. ebXML business process specification schema v2.0.4. OASIS Standard, 2006.
- [70] Asiri Dalugoda. HDP: Cryptographic chain-of-custody for agentic AI systems. *arXiv preprint arXiv:2604.04522*, 2026.
- [71] Jonathan Rosenberg. CHEQ: Confirmation of AI agent decisions with human in the loop. IETF Internet-Draft draft-rosenberg-aiproto-cheq-00, 2026.
- [72] Songbo Bu. Security principal and verifier binding for agent communication protocols. IETF Internet-Draft draft-bu-agentproto-security-principal-binding-02, 2026.
- [73] Zhiqin Yang, Zhenyuan Zhang, Xianzhang Jia, Jun Song, Wei Xue, Yonggang Zhang, and Yike Guo. ClawNet: Human-symbiotic agent network for cross-user autonomous cooperation. *arXiv preprint arXiv:2604.19211*, 2026.
- [74] Shengli Zhang, Deen Ma, Zibin Lin, and Taotao Wang. Distributed general-purpose agent networks: Architecture, key mechanisms, and prototypes. *arXiv preprint arXiv:2606.17368*, 2026.
- [75] Tobin South, Samuele Marro, Thomas Hardjono, Robert Mahari, Cedric Deslandes Whitney, Dazza Greenwood, Alan Chan, and Alex Pentland. Authenticated delegation and authorized AI agents. *arXiv preprint arXiv:2501.09674*, 2025.

- [76] Sandro Rodriguez Garzon, Awid Vaziry, Enis Mert Kuzu, Dennis Enrique Gehrmann, Buse Varkan, Alexander Gaballa, and Axel Küpper. AI agents with decentralized identifiers and verifiable credentials. In *Proc. 18th International Conference on Agents and Artificial Intelligence (ICAART)*, volume 1, pages 252–259, 2026.
- [77] Nenad Tomašev, Matija Franklin, Julian Jacobs, Sébastien Krier, and Simon Osindero. Distributional AGI safety. *arXiv preprint arXiv:2512.16856*, 2025.
- [78] Anastasia Sophia Apeiron, Davide Dell’Anna, Pradeep K. Murukannaiah, and Pinar Yolum. Model and mechanisms of consent for responsible autonomy. In *Proc. AAMAS*, pages 133–141, 2025.
- [79] Jeferson José Baqueta and Cesar Augusto Tacla. A task delegation model: An approach based on trustworthiness in sub-delegations and delegation chain formation. *Autonomous Agents and Multi-Agent Systems*, 40(1):15, 2026.
- [80] Ehud Shapiro and Nimrod Talmon. Grassroots federation: Fair democratic governance at scale. In *Proc. AAMAS*, 2026.
- [81] Jayati Deshmukh, Vahid Yazdanpanah, Sebastian Stein, and Sarvapali D. Ramchurn. The triad of identity, trust and responsibility in multi-agent systems. In *Proc. AAMAS*, 2026.
- [82] Dylan Zongmin Liu. SovereignNegotiation-Bench: Evaluating user-owned personal agents in delegated bargaining under privacy, consent, evidence, and institutional pressure. *arXiv preprint arXiv:2607.02814*, 2026.
- [83] Dylan Zongmin Liu. SovereignPA-Bench: Evaluating user-owned personal agents under evolving intent, platform mediation, and consent constraints. *arXiv preprint arXiv:2607.05363*, 2026.
- [84] Google. Agent payments protocol (AP2) specification. <https://ap2-protocol.org/>, 2025.
- [85] Xue Qin, Simin Luan, Cong Yang, and Zhijun Li. Governable individuals: An identity layer for embodied agents that keep learning. *arXiv preprint arXiv:2607.05463*, 2026.
- [86] Ziling Zhou. Governing dynamic capabilities: Cryptographic binding and reproducibility verification for AI agent tool use. *arXiv preprint arXiv:2603.14332*, 2026.
- [87] Jing Zhang. Right to history: A sovereignty kernel for verifiable AI agent execution. *arXiv preprint arXiv:2602.20214*, 2026.
- [88] Zhenhua Zou, Zhuotao Liu, Lepeng Zhao, and Qiuyang Zhan. BlockA2A: Towards secure and verifiable agent-to-agent interoperability. *arXiv preprint arXiv:2508.01332*, 2025.
- [89] Raza Sharif. Agent transport protocol: Asynchronous store-and-forward messaging for autonomous AI agents. IETF Internet-Draft draft-sharif-agent-transport-protocol-00, 2026.
- [90] Tymofii Pidlisnyi. Agent passport system (APS): Verifiable agent identity, faceted authority, and signed action receipts. IETF Internet-Draft draft-pidlisnyi-aps-03, 2026.

- [91] Jeffrey T. Hancock, Mor Naaman, and Karen Levy. AI-mediated communication: Definition, research agenda, and ethical considerations. *Journal of Computer-Mediated Communication*, 25(1):89–100, 2020.
- [92] Nelson F. Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. Lost in the middle: How language models use long contexts. *Transactions of the Association for Computational Linguistics*, 12:157–173, 2024.
- [93] Xiaobo Guo and Soroush Vosoughi. Serial position effects of large language models. *arXiv preprint arXiv:2406.15981*, 2024.
- [94] Peiyi Wang, Lei Li, Liang Chen, Zefan Cai, Dawei Zhu, Binghuai Lin, Yunbo Cao, Qi Liu, Tianyu Liu, and Zhifang Sui. Large language models are not fair evaluators. In *Proc. ACL*, 2024.
- [95] Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging LLM-as-a-judge with MT-bench and chatbot arena. In *Proc. NeurIPS Datasets and Benchmarks*, 2023.
- [96] Jiaxu Lou and Yifan Sun. Anchoring bias in large language models: An experimental study. *arXiv preprint arXiv:2412.06593*, 2024.
- [97] Chen Han, Wenzhen Zheng, and Xijin Tang. Debate-to-detect: Reformulating misinformation detection as a real-world debate with large language models. *arXiv preprint arXiv:2505.18596*, 2025.
- [98] Mrinank Sharma et al. Towards understanding sycophancy in language models. *arXiv preprint arXiv:2310.13548*, 2023.
- [99] Zhiyuan Weng, Guikun Chen, and Wenguan Wang. Do as we do, not as you think: The conformity of large language models. *arXiv preprint arXiv:2501.13381*, 2025. ICLR 2025.
- [100] Hyeong Kyu Choi, Xiaojin Zhu, and Yixuan Li. When identity skews debate: Anonymization for bias-reduced multi-agent reasoning. *arXiv preprint arXiv:2510.07517*, 2025.
- [101] Hyeong Kyu Choi, Xiaojin Zhu, and Yixuan Li. Debate or vote: Which yields better decisions in multi-agent large language models? In *Proc. NeurIPS*, 2025. Spotlight; *arXiv:2508.17536*.
- [102] Yu Li, Qiang Hu, Yao Zhang, Lili Quan, Jiongchi Yu, and Junjie Wang. DynaTrust: Defending multi-agent systems against sleeper agents via dynamic trust graphs. *arXiv preprint arXiv:2603.15661*, 2026.
- [103] Botao Hu and Helena Rong. Inter-agent trust models: A comparative study of brief, claim, proof, stake, reputation and constraint in agentic web protocol design. *arXiv preprint arXiv:2511.03434*, 2025.
- [104] Apurba Pokharel and Ram Dantu. Hidden anchors in multi-agent LLM deliberation. *arXiv preprint arXiv:2606.19494*, 2026.

- [105] Yiming Huang, Biquan Bie, Zuqiu Na, Weilin Ruan, Songxin Lei, Yutao Yue, and Xinlei He. Understanding the anchoring effect of LLM with synthetic data: Existence, mechanism, and potential mitigations. *arXiv preprint arXiv:2505.15392*, 2025. HCAIR workshop at ICLR 2026.
- [106] Yiderigun Borjigin, Alexander Hermann, Christian Cyron, and Roland Aydin. AnchorBench: A multi-pathway benchmark for the anchoring effect in LLMs. In *Proc. Conference on Language Modeling (COLM)*, 2026. arXiv:2608.14320.
- [107] Hillary N. Owusu and Naomi H. Feldman. Anchoring depends on confidence and post-training in language models. In *Proc. ACL (Volume 2: Short Papers)*, pages 174–180. Association for Computational Linguistics, July 2026. doi:10.18653/v1/2026.acl-short.16.
- [108] Zixuan Chen, Hao Lin, Zizhe Chen, Yizhou Tian, Garry Yang, Depeng Wang, Ya Guo, Huijia Zhu, and James Cheng. Knowing but not correcting: Routine task requests suppress factual correction in LLMs. *arXiv preprint arXiv:2605.05957*, 2026.
- [109] Mirac Suzgun, Emily Shen, Federico Bianchi, Alexander Spangher, Thomas Icard, Daniel E. Ho, Dan Jurafsky, and James Zou. Evaluating commercial AI chatbots as news intermediaries. *arXiv preprint arXiv:2605.22785*, 2026.
- [110] Chris Dimitriou. When does the model look it up? parametric knowledge, controlled retrieval, and the mechanics of AI answer engines. Homiere Research. <https://homiere.com/research/when-does-the-model-look-it-up>, July 2026. Not peer reviewed; single model. Accessed 2026-09-03.
- [111] Jikun Wu, Dongxin Guo, and Siu-Ming Yiu. Bias by necessity: Impossibility theorems for sequential processing with convergent AI and human validation. *arXiv preprint arXiv:2605.08716*, 2026. CogSci 2026.
- [112] Kaike Ping, Buse Çarık, Caleb Wohn, Xiaohan Ding, Tongshuai Wang, and Eugenia Rho. Why LLMs give in: Conversational factors and reasoning behind medical sycophancy. *arXiv preprint arXiv:2608.01017*, 2026. Findings of EMNLP 2026.
- [113] Chubin Zhang, Zhenglin Wan, Xingrui Yu, Pengfei Zhou, Wangbo Zhao, Jingxuan Wu, Yaxin Zhou, and Ivor Tsang. Don’t blindly trust it: How unreliable feedback breaks tool-using LLM agents. *arXiv preprint arXiv:2606.21409*, 2026.
- [114] Weihao Xuan, Qingcheng Zeng, Heli Qi, Yunze Xiao, Junjue Wang, and Naoto Yokoya. The confidence dichotomy: Analyzing and mitigating miscalibration in tool-use agents. In *Proc. ACL (Volume 1: Long Papers)*, pages 11325–11349. Association for Computational Linguistics, July 2026. arXiv:2601.07264; doi:10.18653/v1/2026.acl-long.520.
- [115] Roy Xie, Deepak Gopinath, David Qiu, Dong Lin, Haitian Sun, Saloni Potdar, and Bhuwan Dhingra. Over-searching in search-augmented large language models. In *Proc. EACL (Main Conference)*, 2026. arXiv:2601.05503.
- [116] Myra Cheng, Robert D. Hawkins, and Dan Jurafsky. Accommodation and epistemic vigilance: A pragmatic account of why LLMs fail to challenge harmful beliefs. *arXiv preprint arXiv:2601.04435*, 2026.

- [117] HuiMing Fan, Xiao Wang, Zheng Chu, Qianyu Wang, Zhuoyao Wang, Ming Liu, Bing Qin, and XingYu. LiveBrowseComp: Are search agents searching, or just verifying what they already know? *arXiv preprint arXiv:2605.28721*, 2026.
- [118] Shenran Wang, Vered Shwartz, and Hila Gonen. Don’t ‘well, actually’ me unless you know what you’re talking about: Weak presupposition verification degrades general QA performance. *arXiv preprint arXiv:2608.06539*, 2026.
- [119] David M. Markowitz and Jeffrey T. Hancock. Generative AI are more truth-biased than humans: A replication and extension of core truth-default theory principles. *Journal of Language and Social Psychology*, 43(2):261–267, 2024.
- [120] Zhongyuan Wang and Pratyusha Vemuri. When the tool decides: LLM agents defer blindly to graph neural network tools, and stronger backbones defer more. *arXiv preprint arXiv:2606.14476*, 2026. Under review at TMLR.
- [121] Yihang Chen, Pin Qian, Su Wang, Sipeng Zhang, Huan Xu, Shuhuai Lin, and Xinpeng Wei. Does RAG know when retrieval is wrong? diagnosing context compliance under knowledge conflict. *arXiv preprint arXiv:2605.14473*, 2026.
- [122] Jianying Zhou and Dieter Gollmann. A fair non-repudiation protocol. In *Proc. IEEE Symposium on Security and Privacy*, 1996.
- [123] N. Asokan, Victor Shoup, and Michael Waidner. Asynchronous protocols for optimistic fair exchange. In *Proc. IEEE Symposium on Security and Privacy*, 1998.
- [124] Joseph Y. Halpern and Yoram Moses. Knowledge and common knowledge in a distributed environment. *Journal of the ACM*, 37(3):549–587, 1990.
- [125] Stuart Haber and W. Scott Stornetta. How to time-stamp a digital document. *Journal of Cryptology*, 3(2):99–111, 1991.
- [126] Scott A. Crosby and Dan S. Wallach. Efficient data structures for tamper-evident logging. In *Proc. USENIX Security*, 2009.
- [127] Ben Laurie, Adam Langley, and Emilia Kasper. Certificate transparency. RFC 6962, 2013.
- [128] OpenPeppol AISBL. Peppol eDelivery network: AS4 profile. OpenPeppol Specification, 2020.
- [129] Michael L. Katz and Carl Shapiro. Network externalities, competition, and compatibility. *American Economic Review*, 75(3):424–440, 1985.
- [130] Marc Shapiro, Nuno Preguiça, Carlos Baquero, and Marek Zawirski. Conflict-free replicated data types. In *Proc. SSS*, 2011.
- [131] Jack B. Dennis and Earl C. Van Horn. Programming semantics for multiprogrammed computations. *Communications of the ACM*, 9(3):143–155, 1966.
- [132] Jerome H. Saltzer and Michael D. Schroeder. The protection of information in computer systems. *Proceedings of the IEEE*, 63(9):1278–1308, 1975.

- [133] Mark S. Miller. *Robust Composition: Towards a Unified Approach to Access Control and Concurrency Control*. PhD thesis, Johns Hopkins University, 2006.
- [134] Stephen Farrell, Russell Housley, and Sean Turner. An internet attribute certificate profile for authorization. RFC 5755, 2010.
- [135] Carl Ellison, Bill Frantz, Butler Lampson, Ronald L. Rivest, Brian Thomas, and Tatu Ylonen. SPKI certificate theory. RFC 2693, 1999.
- [136] Arnar Birgisson, Joe Gibbs Politz, Úlfar Erlingsson, Ankur Taly, Michael Vrabie, and Mark Lentczner. Macaroons: Cookies with contextual caveats for decentralized authorization in the cloud. In *Proc. NDSS*, 2014.
- [137] Michael B. Jones, Anthony Nadalin, Brian Campbell, John Bradley, and Chuck Mortimore. OAuth 2.0 token exchange. RFC 8693, 2020.
- [138] Jerome H. Saltzer, David P. Reed, and David D. Clark. End-to-end arguments in system design. *ACM Transactions on Computer Systems*, 2(4):277–288, 1984.
- [139] David Chaum. Security without identification: Transaction systems to make big brother obsolete. *Communications of the ACM*, 28(10):1030–1044, 1985.
- [140] Drew Fudenberg and Eric Maskin. The folk theorem in repeated games with discounting or with incomplete information. *Econometrica*, 54(3):533–554, 1986.
- [141] Anthropic Claude Developers. Advisor and orchestrator patterns for mixed-tier model deployments. <https://x.com/ClaudeDevs/status/2074606058128224365>, 2026.
- [142] Amos Tversky and Daniel Kahneman. Judgment under uncertainty: Heuristics and biases. *Science*, 185(4157):1124–1131, 1974.
- [143] Solomon E. Asch. Effects of group pressure upon the modification and distortion of judgments. In *Groups, Leadership and Men*. Carnegie Press, 1951.
- [144] Timothy Lebo, Satya Sahoo, and Deborah McGuinness. PROV-O: The PROV ontology. W3C Recommendation, 2013.
- [145] Coalition for Content Provenance and Authenticity. C2PA technical specification. <https://c2pa.org/specifications/>, 2023.
- [146] Norman Dalkey and Olaf Helmer. An experimental application of the Delphi method to the use of experts. *Management Science*, 9(3):458–467, 1963.
- [147] Xiaoxin Yin, Jiawei Han, and Philip S. Yu. Truth discovery with multiple conflicting information providers on the web. *IEEE Transactions on Knowledge and Data Engineering*, 20(6):796–808, 2008.
- [148] Yaliang Li, Jing Gao, Chuishi Meng, Qi Li, Lu Su, Bo Zhao, Wei Fan, and Jiawei Han. A survey on truth discovery. *SIGKDD Explorations*, 17(2):1–16, 2016.
- [149] Shenghui Chen, Daniel Fried, and Ufuk Topcu. Human-agent cooperation in games under incomplete information through natural language communication. *arXiv preprint arXiv:2405.14173*, 2024.

- [150] Sture Holm. A simple sequentially rejective multiple test procedure. *Scandinavian Journal of Statistics*, 6(2):65–70, 1979.
- [151] Robert G. Newcombe. Interval estimation for the difference between independent proportions: Comparison of eleven methods. *Statistics in Medicine*, 17(8):873–890, 1998.
- [152] Nathan Mantel and William Haenszel. Statistical aspects of the analysis of data from retrospective studies of disease. *Journal of the National Cancer Institute*, 22(4):719–748, 1959.
- [153] Donald J. Schuirmann. A comparison of the two one-sided tests procedure and the power approach for assessing the equivalence of average bioavailability. *Journal of Pharmacokinetics and Biopharmaceutics*, 15(6):657–680, 1987.
- [154] Michèle Finck. Blockchain and the general data protection regulation. European Parliamentary Research Service, PE 634.445, 2019.
- [155] Eugenia Politou, Efthimios Alepis, and Constantinos Patsakis. Forgetting personal data and revoking consent under the GDPR: Challenges and proposed solutions. *Journal of Cybersecurity*, 4(1), 2018.
- [156] European Data Protection Board. Guidelines 02/2025 on the processing of personal data through blockchain technologies, 2025.
- [157] Adam Shostack. *Threat Modeling: Designing for Security*. Wiley, 2014.
- [158] Uniform Law Commission. Revised uniform fiduciary access to digital assets act, 2015.
- [159] Edina Harbinja. *Digital Death, Digital Assets and Post-mortem Privacy*. Edinburgh University Press, 2022.