

# The Objective Is the Bottleneck: Latent World Models Encode What Their Planners Cannot Use

Joyjeet Singh

*Independent researcher*

ORCID 0009-0005-1512-7439

joyjeetsingh1@gmail.com

## Abstract

Latent world models are judged by how well they predict, so when planning over one fails at long horizons the natural reading is that the predictor degrades. On a reproduction of LeWorldModel on TwoRoom we show the binding constraint is the planner’s objective instead.

The predictor is not the limit: rolled out on real validation clips, its imagined state seventy-five environment steps ahead is still only 0.189 as wrong as assuming the world froze, while the planner never imagines beyond twenty-five. The objective is the limit. Cross-entropy-method planning minimises squared latent distance, which tracks true distance at  $r = 0.426$ , stops rising by about eighty arena units, and **decreases** beyond about a hundred and twenty — so moving away from the goal can lower the planner’s cost. The information is present throughout: a ridge probe recovers position from the same frozen embedding at  $R^2$  0.9922.

The pathology belongs to the method rather than to one reimplementation. It is present in the authors’ released weights, and across four checkpoints long-horizon success rank-orders exactly with the quality of this metric and inversely with one-step prediction accuracy — a mechanism for a dissociation the reproduction reports and leaves unexplained.

Replacing only the objective, with nothing retrained and no GPU, lifts goals reached at offset 100 from 26.0% to **98.0%**, equals the 98.0% reached at offset 25, and still reaches 92.0% under a third of the budget: planning stops depending on the horizon. The best cost is not the most accurate one. A head learned from frame separation alone predicts *spatial* distance worse than a position probe ( $r = 0.819$  against 0.9897) yet plans better, because it charges 24% more to cross the environment’s dividing wall where squared latent distance charges 4% *less*. It has learned reachability, not proximity.

We also report where the repair fails: on the authors’ weights the learned cost is beaten by the linear one, 34.0% against 70.0%, because a head fit on encoded frames is evaluated on imagined ones and their predictor drifts far enough for an MLP to extrapolate. A learned planning cost must be trained on the distribution the planner scores.

## 1 Introduction

Latent world models are trained to predict. A model that predicts the next latent state accurately is taken to have learned the dynamics, and planning over it is expected to follow. When it does not, the usual suspects are the predictor’s horizon, its capacity, or the amount of training.

This paper reports a case where none of those is the cause. Working from a published reproduction of LeWorldModel on the TwoRoom environment (arXiv:2608.10145), where planning reaches 94.0% of goals twenty-five steps away and 26.0% of goals a hundred steps away, we asked what the model would need in order to close that gap. The answer turned out to be nothing.

---

The reproduction paper reports the gap and, deliberately, offers no mechanism for it. It also reports something stranger: across three checkpoints, one-step prediction accuracy orders short-horizon planning success monotonically and fails to order long-horizon success at all, with the least accurate checkpoint the strongest long-horizon planner. Both observations have the same explanation, and it is not about prediction.

## Contributions

1. **The predictor is not the bottleneck.** Imagination stays informative to at least seventy-five environment steps; the planner uses twenty-five (§3).
2. **The planning objective saturates and then inverts.** Squared latent distance — the quantity CEM minimises — is not monotone in true distance beyond about a hundred and twenty units, so moving away from the goal can lower the planner’s cost (§4).
3. **The pathology belongs to the method, not to one reimplementation.** It is present in the original authors’ released weights (§5).
4. **A mechanism for the accuracy/planning dissociation.** Across four checkpoints, long-horizon success rank-orders exactly with metric quality and inversely with prediction accuracy (§5).
5. **The information is present; only the metric fails.** Position decodes from the frozen embedding at  $R^2$  0.9922 (§6).
6. **A repair with no retraining,** effective on the authors’ own weights, and not dependent on the environment having a readable state (§7, §8).
7. **Reachability, not proximity, is the right objective.** A cost that predicts spatial distance worse plans better, because it charges for the wall. Planning success across three objectives orders by how well each captures reachability (§7.3, §8).
8. **A learned cost must be trained on what the planner scores** — imagined embeddings, not encoded frames. Invisible on the checkpoint the method was developed on; decisive on the other (§7.4).
9. **A conditional prescription, including where the repair loses.** The learned cost wins where the predictor supports it and loses to a linear one where it does not (§8.2).

## Scope

One environment, one seed per checkpoint, four checkpoints. TwoRoom is a diagnostic environment and the strongest claims here are about it. §9 states what that does and does not license.

## 2 Setup

All experiments use the checkpoints and evaluation harness released with the reproduction. The world model is an 18.03M-parameter joint-embedding predictive architecture: a ViT-Tiny encoder at 224px producing 192-dimensional embeddings, and a six-layer predictor conditioned on an action encoding.

Planning is cross-entropy-method search over the learned dynamics, with the released configuration: 300 candidate sequences, 30 refinement iterations, 30 elite, horizon 5, and a receding horizon of 5. The planner emits a two-dimensional action which the environment executes for `frameskip` = 5 steps, so a planning horizon of 5 corresponds to 25 environment steps of imagination.

**The objective.** CEM scores each candidate by

$$\text{cost} = \|\hat{z}_T - z_{\text{goal}}\|_2^2$$

the squared Euclidean distance between the imagined final embedding and the embedding of the goal image. This is the quantity the paper is about.

**Protocols.** The released material publishes two evaluation protocols. The repository configuration places the goal 25 frames ahead with a 50-step budget; the paper’s appendix places it 100 frames ahead with a 150-step budget. We report both, and use the published runs as baselines throughout. Every comparison below draws the same episodes as its baseline, at the same seed, which we verified by replicating the draw.

**Compute.** Every experiment in this paper ran on a four-core laptop CPU. No model was trained or fine-tuned.

### 3 The predictor is not the bottleneck

If long-horizon planning fails because imagination degrades, the degradation should be visible in a rollout. We rolled the released checkpoint forward autoregressively on real validation clips under their recorded actions, comparing each imagined latent against the encoder’s true latent for that frame, and against a static baseline that predicts nothing moves.

| horizon (planner steps) | environment steps | imagined err / static |
|-------------------------|-------------------|-----------------------|
| 1                       | 5                 | 0.066                 |
| 5                       | 25                | 0.090                 |
| 10                      | 50                | 0.152                 |
| 15                      | 75                | 0.189                 |

*From `followup/rollout_h15_phase2_recal.txt`.*

At fifteen planner steps the imagined state is still only 19% as wrong as assuming the world froze, and the error grows slowly and smoothly. There is no collapse anywhere in the range a planner would need.

Horizon 20 could not be measured at all. A clip spanning three history frames and twenty predictor steps at frameskip 5 needs 102 raw frames, and the dataset’s episodes are capped at 101 — the same ceiling that makes the offset-100 protocol degenerate in the reproduction’s §4.2.

**The planner never asks for this.** With horizon 5 it imagines 25 environment steps, toward goals 100 steps away. The model can see three times farther than it is ever asked to.

### 4 The objective saturates, then inverts

The planner’s objective is only sensible if latent distance rises with true distance across the range it must cover. We measured that directly, with no planning involved: render real recorded positions, encode them, and compare pairwise latent distance against pairwise true distance.

| true distance (arena units) | pairs | mean latent distance | r within band |
|-----------------------------|-------|----------------------|---------------|
| 0–20                        | 648   | 15.92                | 0.668         |
| 20–40                       | 1288  | 18.52                | 0.182         |
| 40–60                       | 1208  | 19.68                | 0.115         |
| 60–80                       | 1329  | 20.04                | 0.104         |
| 80–100                      | 960   | 20.61                | 0.122         |
| 100–120                     | 733   | 20.68                | −0.029        |
| 120–150                     | 691   | 20.60                | falling       |
| 150–300                     | 283   | 19.93                | falling       |

*From `followup/latent_metric_phase2_recal.txt`, 7,140 pairs.*

Overall Pearson  $r = 0.426$ . Three things follow.

**The objective is informative only at short range.** Within-band correlation is 0.668 under twenty units and below 0.13 beyond forty.

**It saturates.** Across 80–300 units the mean varies by  $-3.3\%$ . Two states, one eighty units from the goal and one three hundred, receive almost the same score.

**It inverts.** Past about a hundred and twenty units the relationship turns negative. A planner minimising this cost can be led *away* from its goal and score itself as improving.

#### 4.1 This is the observed failure

The reproduction reports that offset-100 failures overshoot. Re-analysing its committed episode data: 26 of 37 failures finish farther from the goal than they began, at a median  $1.41\times$  the original separation. Success falls off with distance exactly where the metric goes blind — 100% under 60 units, 37% between 60 and 100, and 6% between 100 and 140.

A saturating, eventually inverting objective predicts all of this: short goals are solved, long goals are not, and the planner does not merely stall but travels confidently in the wrong direction.

## 5 The pathology is the method’s, and it explains the dissociation

### 5.1 The authors’ own weights

The same measurement on the original authors’ released checkpoint — weights we did not train:

|                   | Pearson | Spearman | monotone | 80–300 spread |
|-------------------|---------|----------|----------|---------------|
| authors’ released | 0.388   | 0.423    | no       | $-2.2\%$      |

*From `followup/latent_metric_authors.txt`.*

This is our checkpoint’s pathology almost exactly. Whatever produces it is a property of the method as released, not of a reimplementaion choice.

### 5.2 Metric quality orders long-horizon planning

Measuring all four available checkpoints and placing them beside their published planning results:

| checkpoint        | one-step error | offset 100, budget<br>150 | Spearman | monotone | 80–300 spread |
|-------------------|----------------|---------------------------|----------|----------|---------------|
| Run 2 recal       | 0.829          | 40/50 = 80.0%             | 0.872    | yes      | +38.6%        |
| Run 0 recal       | —              | 33/50 = 66.0%             | 0.846    | yes      | +34.9%        |
| phase2 recal      | 0.116          | 13/50 = 26.0%             | 0.445    | no       | $-3.3\%$      |
| authors’ released | 0.410          | 7/50 = 14.0%              | 0.423    | no       | $-2.2\%$      |

Long-horizon planning success rank-orders **exactly** with metric quality, and inversely with one-step prediction accuracy.

This supplies a mechanism for the dissociation the reproduction reports and declines to explain. The most accurate predictor is the worst long-horizon planner not because accuracy is irrelevant to planning, but because in these runs accuracy and metric usability move in opposite directions. Selecting on prediction loss selects against the geometry the planner depends on.

### 5.3 A correlate, not a cause

The split tracks the training pipeline. Both checkpoints with usable geometry used `history_size` 1 and `action_dim` 2; both pathological ones — ours and the authors’ — use the reference pipeline with `history_size` 3 and dense ten-wide actions.

Effective rank moves with it. The reproduction’s committed probe records 18.6 of 192 effective dimensions for Run 0 and 67.8 for phase2, a  $3.6\times$  spread across the same interval over which the metric degrades. This is a partial account of dimensions the reproduction explicitly declines to characterise: whatever they encode, it is not distance-relevant, and it dilutes an L2 taken over all 192 — which is consistent with a two-dimensional linear read-out recovering position at  $R^2$  0.99 from the same vector that L2 cannot order.

**We cannot separate these factors.** History size, action width and pixel normalisation change together across the four checkpoints, and each checkpoint is a single seed. This is a correspondence worth explaining, not a demonstrated cause.

## 6 The information is present

If the embedding did not contain the geometry, no objective could recover it. It does. A ridge probe fit on frozen embeddings of 350 rendered positions and evaluated on 150 held out:

|                            | latent L2 | decoded position |
|----------------------------|-----------|------------------|
| Pearson r vs true distance | 0.437     | <b>0.9897</b>    |
| monotone in true distance  | no        | <b>yes</b>       |
| spread across 80–300 units | +1.2%     | <b>+73.4%</b>    |

with probe  $R^2$  **0.9922** held out and mean absolute error **1.72** arena units. *From followup/probe\_metric\_phase2\_recal.txt.*

The same holds on the authors’ checkpoint: probe  $R^2$  0.9627, decoded-position distance monotone at  $r = 0.9573$  where their latent L2 is neither.

The encoder represents what the planner needs. The objective discards it.

## 7 Repair

We change the planner’s objective and nothing else. The encoder and predictor are the released weights, frozen.

**Decoded-position cost.** Fit a ridge probe from embeddings to position, and score candidates by distance between decoded positions rather than between embeddings. The probe is fit at startup on rendered positions.

**Learned temporal-distance cost.** The decoded-position cost leans on something TwoRoom happens to offer — a low-dimensional state a linear probe can read. To test whether the repair depends on that, we learn a cost from the only signal a deployed system always has: how many steps apart two observed frames were.

Training pairs are real recorded frames from the same episode, supervised by their frame separation. A small MLP maps ( $z_t, z_{goal}$ ) to predicted steps-to-reach, symmetrised over both orderings. Episodes are split disjointly between training and evaluation. **No position appears in the supervision.**

|                                    | latent L2 | learned temporal head |
|------------------------------------|-----------|-----------------------|
| Pearson r vs true spatial distance | 0.484     | <b>0.819</b>          |
| monotone in true distance          | no        | <b>yes</b>            |
| spread across 80–150 units         | +2.9%     | <b>+43.3%</b>         |

with held-out MAE 12.80 frames on disjoint episodes. *From followup/temporal\_head\_phase2.txt.*

A cost learned from temporal separation alone orders distance where the embedding metric does not. The repair is not a consequence of TwoRoom having a readable state.

### 7.3 The better objective is the less accurate one

The temporal head predicts spatial distance *worse* than the position probe —  $r = 0.819$  against  $0.9897$  — and yet plans better: **98.0%** of offset-100 goals against the probe’s 88.0% (§8). Spatial distance is not what a planner needs.

TwoRoom has a dividing wall with a door, so two states can be close in space and far in reachability. We tested whether the temporal head knows this, by matching pairs on true spatial distance and splitting them by whether they lie in the same room or across the wall:

| true distance | pairs same/cross | temporal head same →<br>cross | ratio | latent L2 ratio |
|---------------|------------------|-------------------------------|-------|-----------------|
| 20–40         | 62,142 / 21,713  | 23.5 → 27.2                   | 1.16  | 0.87            |
| 40–60         | 54,071 / 43,397  | 35.1 → 45.2                   | 1.29  | 0.95            |
| 60–80         | 36,724 / 51,276  | 45.0 → 56.4                   | 1.25  | 0.99            |
| 80–100        | 21,568 / 42,075  | 54.5 → 68.9                   | 1.26  | 1.02            |

From *followup/wall\_reachability.txt*, 460,320 pairs.

At matched spatial separation the temporal head charges **24% more** to cross the wall. Squared latent distance charges **4% less** — it is not merely blind to the wall, it is biased slightly the wrong way.

This orders the three objectives exactly as their planning results do:

| objective               | cross/same cost ratio | offset 100   |
|-------------------------|-----------------------|--------------|
| squared latent distance | 0.96                  | 26.0%        |
| decoded position        | 1.00 by construction  | 88.0%        |
| learned temporal head   | <b>1.24</b>           | <b>98.0%</b> |

The decoded-position cost cannot represent the wall at all: Euclidean distance between positions is the same whether or not a barrier lies between them. It recovers most of the gap because proximity is a good proxy for reachability in open space. The temporal head recovers the rest because it is not a proxy.

### 7.4 A learned cost must be trained on what the planner scores

The head above is fit on pairs of encoded **real** frames. At planning time CEM scores (**imagined** embedding, encoded goal). Those coincide only to the extent the predictor is accurate, and the difference is measurable. Evaluated on identical held-out pairs:

| checkpoint         | one-step error | head on real × real | head on imagined ×<br>real | degradation |
|--------------------|----------------|---------------------|----------------------------|-------------|
| ours, phase2 recal | 0.116          | 12.47               | 12.86                      | <b>+3%</b>  |
| authors’ released  | 0.410          | 10.37               | <b>18.04</b>               | <b>+74%</b> |

From *followup/temporal\_head\_v2\_\*.txt*, MAE in frames.

Our predictor keeps imagined states close enough to the encoding manifold that a head fit on real pairs transfers. The authors’ does not, and the cost becomes unreliable exactly where planning needs it.

Training on both kinds of pair — rolling the predictor forward under the recorded block-mean actions, precisely as the planner drives it — removes the mismatch on the authors’ checkpoint: 7.37 real against 8.21 imagined, +11% rather than +74%.

We report this because it was invisible on the checkpoint we developed the method on, where the two distributions happened to coincide. It took a second checkpoint to surface, and it is a condition on any learned planning cost, not a detail of this one.

## 8 Results

Every comparison is paired: the same checkpoint, the same protocol, the same episode draw as its published baseline, verified by replicating the draw. All three baseline columns reproduce their published figures exactly — 94.0%, 26.0% and 14.0% — which is what makes the harness trustworthy rather than merely self-consistent. McNemar is exact on the discordant pairs.

| checkpoint            | protocol                        | objective                | baseline      | repaired                 | discordant | McNemar                   |
|-----------------------|---------------------------------|--------------------------|---------------|--------------------------|------------|---------------------------|
| ours, phase2<br>recal | offset 25,<br>budget 50         | decoded<br>position      | 47/50 = 94.0% | 46/50 = 92.0%            | 3–4        | p = 1                     |
| ours, phase2<br>recal | offset 25,<br>budget 50         | <b>temporal<br/>head</b> | 47/50 = 94.0% | <b>49/50 =<br/>98.0%</b> | 3–1        | p = 0.625                 |
| ours, phase2<br>recal | offset 100,<br>budget 150       | decoded<br>position      | 13/50 = 26.0% | <b>44/50 =<br/>88.0%</b> | 31–0       | p = $9.3 \times 10^{-10}$ |
| ours, phase2<br>recal | offset 100,<br>budget 150       | <b>temporal<br/>head</b> | 13/50 = 26.0% | <b>49/50 =<br/>98.0%</b> | 37–1       | p = $2.8 \times 10^{-10}$ |
| ours, phase2<br>recal | offset 100,<br><b>budget 50</b> | <b>temporal<br/>head</b> | 10/50 = 20.0% | <b>46/50 =<br/>92.0%</b> | 37–1       | p = $2.8 \times 10^{-10}$ |
| authors’<br>released  | offset 100,<br>budget 150       | decoded<br>position      | 7/50 = 14.0%  | <b>35/50 =<br/>70.0%</b> | 28–0       | p = $7.5 \times 10^{-9}$  |
| authors’<br>released  | offset 100,<br>budget 150       | temporal head<br>v2      | 7/50 = 14.0%  | 17/50 = 34.0%            | 13–3       | p = 0.021                 |

All five baseline columns reproduce their published figures exactly — 94.0%, 26.0%, 20.0%, 14.0% and 14.0%.

### 8.1 Planning becomes horizon-independent

Under the published objective, success falls from 94.0% at goal offset 25 to 26.0% at offset 100. Under the temporal cost it is **98.0% at both**. The horizon dependence was a property of the objective, not of the model or the task.

It is also not bought with time. At offset 100 under the repository’s own 50-step budget — a third of the appendix budget — the temporal cost reaches **92.0%** against a 20.0% baseline. Hundred-step goals are being reached inside fifty environment steps.

### 8.2 Where the learned cost loses, and why

On the authors’ released checkpoint the ordering reverses: the linear decoded-position cost reaches 70.0% and the learned temporal head only 34.0%. Both beat the 14.0% baseline; the crude objective wins.

The reason is §7.4. The learned head is an MLP evaluated on imagined embeddings, and the authors’ predictor drifts far enough off the manifold of real encodings that the head extrapolates. A linear map degrades far more gracefully under the same drift. Training the head on imagined pairs (v2) narrows the gap in metric terms — +11% degradation instead of +74% — and lifts planning from the v1 head’s showing to 34.0%, but does not close it.

**The prescription is therefore conditional.** A learned reachability cost is the strongest objective where the predictor is accurate enough to keep its imagined states near the encoding manifold — our checkpoint, one-step error 0.116. Where it is not — theirs, 0.410 — the robust choice is the simplest cost that orders distance monotonically. What does not change is the diagnosis: on both checkpoints the published objective saturates and inverts, and on both, replacing it is worth a large, significant gain.

**The shape of the change.** Baseline failures exhaust the 150-step budget and finish 115–193 units from the goal having started 71–170 away. The repair typically arrives in 24–49 steps, a third of the budget.

**Three comparisons worth stating.** 88.0% already exceeds Run 2’s 80.0%, the best long-horizon planner among the released checkpoints; under a sound objective the most accurate predictor becomes the best long-horizon planner, and the dissociation of §5.2 dissolves rather than merely being explained.

---

98.0% at offset 100 **exceeds the 94.0% the same checkpoint achieves at offset 25** under the published objective. The long-horizon deficit was not a horizon problem at all.

And the ordering 26.0%  $\rightarrow$  88.0%  $\rightarrow$  98.0% tracks the cross/same ratio of §7.3 (0.96  $\rightarrow$  1.00  $\rightarrow$  1.24) rather than accuracy against spatial distance (0.437  $\rightarrow$  0.9897  $\rightarrow$  0.819). What a planning objective must get right is reachability.

## 9 Limitations

**One environment.** TwoRoom is a two-dimensional diagnostic environment. That the objective is the bottleneck *there* does not establish it elsewhere, and the decoded-position cost is available only where a low-dimensional state can be read out. The temporal-distance result (§7) is the part of this that is designed to travel, and it is demonstrated on the same environment.

**One seed per checkpoint.** The four-checkpoint correspondence of §5.2 rests on four models with one seed each. It is a correspondence, not a law, and we make no estimate of seed variance.

**Confounded conditions.** History size, action width and pixel normalisation differ together between the checkpoints with usable geometry and those without. We cannot attribute the metric degradation to any one of them without training runs we did not do.

**No claim about the cause of saturation.** We show that the embedding metric saturates and inverts, and that it matters. We do not explain why the representation is organised that way.

**The repair is a planner change.** It leaves the model’s own objective untouched. Whether training against a reachability-aware criterion would produce a representation whose plain L2 is usable is an open and more interesting question.

## 10 Related work

The failure mode identified here is the one Li, Wang and Liu (2026) argue for on general grounds: that Euclidean proximity in a latent space is a poor proxy for reachability, and that latent world models need horizon-matched metrics. Their argument is made against latent world models as a class; this paper supplies a direct measurement of the phenomenon on a specific published model — including the original authors’ own released weights — quantifies the range over which the metric fails, and shows what repairing it is worth in planning success.

The reproduction this work builds on (arXiv:2608.10145) established the protocol-dependence of the published planning figure, the four undocumented training conventions, and the accuracy/planning dissociation whose mechanism §5 addresses. It explicitly declines to offer that mechanism, which is the gap this paper fills.

## 11 Conclusion

A latent world model that predicts well can plan badly, and the reason need not be in the model. On this one, the predictor stays informative three times farther than the planner ever asks, the representation encodes position almost perfectly, and long-horizon planning still fails — because the objective the planner minimises stops distinguishing states beyond about eighty units and reverses beyond a hundred and twenty.

Fixing the objective, and nothing else, takes goals reached at the long horizon from 26.0% to 98.0% on our checkpoint and from 14.0% to 70.0% on the original authors’. It costs nothing at the short horizon. It does not require retraining, a GPU, or an environment with a readable state — the best of the three objectives we tried uses no state supervision at all.

The sharper lesson is what the objective must measure. Ranked by how well they predict spatial distance, the three objectives run 0.437, 0.9897, 0.819; ranked by planning success they run 26.0%, 88.0%, 98.0%. The ordering follows neither accuracy nor proximity but reachability — whether the cost charges for the

---

wall between two states. A planner needs to know how far away something is in *steps*, and a metric that is excellent at Euclidean distance is merely a good approximation to that in open space.

The practical consequence is a selection criterion. Choosing a world model by prediction loss selected, in these runs, against the property planning actually depends on. If a latent model is to be planned over, the geometry of its embedding space under the planner’s own objective is the thing to measure — and it is cheap to measure, needing no planning at all.

## References

Liangyu Li, Shengzhi Wang, and Qingwen Liu. Beyond Euclidean Proximity: Repairing Latent World Models with Horizon-Matched Trajectory Reachability Metrics. arXiv:2605.22164, 2026.

Lucas Maes, Quentin Le Lidec, Damien Scieur, Yann LeCun, and Randall Balestriero. LeWorldModel: Stable End-to-End Joint-Embedding Predictive Architecture from Pixels. arXiv:2603.19312, 2026.

Joyjeet Singh. The Evaluation Protocol Determines the Result: An Independent Reproduction of LeWorldModel on TwoRoom. arXiv:2608.10145, 2026.

Code, the released checkpoints, and every measurement reported here: [github.com/joyjeet-singh/tinylab](https://github.com/joyjeet-singh/tinylab)