

VLALIGHT: A VISION-LANGUAGE-ACTION MODEL FOR TRAFFIC SIGNAL CONTROL

Pan Zhang^{1*} Siqu Lai^{1*} Kemu Dong² Hao Liu^{1†}

¹The Hong Kong University of Science and Technology (Guangzhou)

²Dalian University of Technology

pzhang521@connect.hkust-gz.edu.cn

ABSTRACT

Traffic signal control (TSC) is essential for improving urban mobility and reducing congestion. Although roadside cameras are widely deployed at signalized intersections and provide rich visual observations of evolving traffic, existing TSC methods typically rely on manually engineered traffic states or separate perception modules, creating a gap between physical observations and control decisions. We present **VLALight**, the first vision-language-action (VLA) model for end-to-end traffic signal control from multi-view roadside videos. VLALight directly maps visual observations to coordinated signal actions through multi-target spatiotemporal traffic reasoning and topology-aware cooperative perception across intersections. To establish this capability, we develop a two-stage supervised cold-start training strategy for visual traffic understanding and signal decision-making, followed by cooperative agentic reinforcement learning that jointly optimizes local control and network-wide traffic efficiency. Furthermore, VLALight introduces adaptive fast and slow reasoning modes, enabling the policy to allocate deeper reasoning only when additional deliberation provides sufficient control benefits. Through balanced mode-aware rollouts and relative advantage optimization, VLALight learns to trade off decision quality and inference cost. Extensive experiments on seven real-world traffic-flow datasets across three urban networks demonstrate that VLALight consistently outperforms transportation-based, RL-based, and LLM/VLM-based baselines. Ablation studies validate the effectiveness of cooperative perception, network-level optimization, and adaptive reasoning. These results demonstrate the potential of VLA models for real-world physical traffic control. Our project is available at <https://github.com/usail-hkust/VLALight.git>.

1 INTRODUCTION

Traffic signal control (TSC) is a fundamental component of urban traffic management. By regulating conflicting movements at intersections, it directly affects vehicle delay, network throughput, and traffic-related emissions. Meanwhile, roadside cameras have become increasingly prevalent at signalized intersections, providing continuous and information-rich observations of vehicle movements, lane occupancy, and surrounding road conditions (Wang et al., 2021). Compared with conventional detector-based measurements (e.g., underground coils), such visual observations preserve substantially richer information about the physical traffic scene and are already available in many real-world deployments. This creates a natural opportunity to develop traffic signal controllers that directly perceive and act upon visual observations. However, despite the growing availability of roadside vision, existing TSC systems largely operate on manually engineered traffic states rather than raw physical observations, leaving end-to-end visual traffic control largely unexplored.

Existing traffic signal control research has evolved from transportation-engineering methods toward learning-based control. Classical approaches, including signal timing optimization (Koonce et al.,

*Equal contribution.

†Corresponding author.

2008), SCOOT (Hunt et al., 1982), and MaxPressure (Varaiya, 2013), are efficient and interpretable but rely on handcrafted control logic and simplified traffic-flow assumptions (Qadri et al., 2020; Wei et al., 2021). Reinforcement learning (RL) improves adaptability by learning control policies from environmental feedback (Abdulhai et al., 2003; Wei et al., 2018; Zheng et al., 2019; Wei et al., 2019a; Chen et al., 2020; Wei et al., 2019b; Wu et al., 2021a; Yu et al., 2020; Ruan et al., 2024). More recently, LLM-based methods such as LLMLight (Lai et al., 2025), Traffic-R1 (Zou et al., 2026), and CoLLMLight (Yuan et al., 2026) introduce stronger reasoning and interpretability. However, both RL- and LLM-based approaches generally rely on carefully constructed traffic states, such as queue lengths, vehicle counts, occupancy, and lane pressure. Although such states are readily available in traffic simulators, they can be incomplete or unreliable in real-world deployments because of limited sensor coverage, sensor failures, and communication interruptions (Mei et al., 2023). Vision-language models (VLMs) provide a promising way to bridge this perception-control gap by directly accessing traffic observations from traffic cameras, which preserve vehicle motion, road geometry, and evolving traffic patterns beyond predefined traffic measures (Zhou et al., 2024). However, existing VLM-based TSC methods primarily focus on scene understanding or high-level assistance, while delegating final signal actions to separate RL or language-model controllers (Wang et al., 2025b). Consequently, end-to-end signal control directly from physical visual observations remains largely underexplored.

Vision-language-action (VLA) models have recently emerged as a unified paradigm for embodied decision-making by grounding visual-language representations into executable actions (Brohan et al., 2023; Kim et al., 2024). This formulation is naturally suited for traffic signal control, as it enables an agent to directly interpret physical traffic scenes, reason about their dynamics, and generate signal actions within a unified policy. However, extending VLA to TSC introduces three substantial challenges. First, videos from traffic cameras contain dense and continuously evolving interactions among vehicles, lanes, and movement directions. Effective control therefore requires complex multi-target spatiotemporal reasoning to identify critical traffic dynamics and anticipate future evolution. Second, TSC is inherently a network-wide optimization problem: a signal decision at one intersection can reshape downstream arrivals, queue propagation, and spillback. A network-aware VLA controller needs to reason over spatially connected intersections and coordinate actions beyond local observations. Finally, the inference latency must satisfy strict efficiency requirements. While complex congestion may benefit from deeper deliberation, routine conditions should avoid unnecessary computation. The controller must consequently adapt its reasoning effort to traffic complexity while balancing decision quality and inference latency.

To address these challenges, we propose *VLALight*, an end-to-end vision-language-action model for traffic signal control that directly maps physical visual observations to executable signal actions. Given multi-view intersection videos, *VLALight* first performs multi-target traffic perception and spatiotemporal reasoning to capture evolving vehicle movements, queue dynamics, and traffic trends. To address the networked nature of TSC, it further incorporates observations from neighboring intersections through topology-aware cooperative perception, enabling coordinated signal decisions beyond isolated local control. To progressively establish these capabilities, we adopt a two-stage supervised fine-tuning strategy that separately develops spatiotemporal traffic understanding and executable signal decision-making. Building on this initialization, we introduce a cooperative agentic RL framework that optimizes network-wide control through environment interaction. The training objective jointly considers immediate local queue reduction and longer-horizon network-level traffic improvement, encouraging actions that improve both individual intersections and overall traffic efficiency. Furthermore, *VLALight* explicitly explores balanced fast- and slow-reasoning modes during RL rollouts, allowing the policy to compare direct responses with deeper deliberation under different traffic conditions. Through mode-wise advantage normalization, *VLALight* learns when additional reasoning provides sufficient control benefits to justify its computational overhead. As a result, *VLALight* unifies visual traffic understanding, cooperative multi-intersection control, and adaptive reasoning efficiency within a single VLA model.

Our contributions are threefold. (1) We introduce *VLALight*, an end-to-end VLA model that directly connects physical roadside observations with spatiotemporal traffic reasoning and coordinated signal control. To our knowledge, it is the first VLA model in traffic signal control. (2) We develop a cooperative training framework with staged supervised fine-tuning, followed by agentic reinforcement learning for coordinated multi-intersection control and cost-effective adaptive reasoning. (3)




Figure 1: The overview of VLALight.

Extensive experiments on seven real-world traffic datasets demonstrate that VLALight consistently improves network-wide traffic efficiency and cost-effectiveness across diverse traffic conditions.

2 PRELIMINARIES

Definition 1 (Road Network). We represent an urban road network as a directed graph $\mathcal{G} = (\mathcal{I}, \mathcal{L})$, where $\mathcal{I}$ is the set of signalized intersections and $\mathcal{L}$ is the set of directed lane connections between them. Each intersection has incoming and outgoing lanes, and each lane permits one or more traffic movements, such as going straight, turning left, or turning right. The graph captures the spatial pathways along which vehicles, congestion, and the effects of signal decisions propagate.

Definition 2 (Vision-Based Traffic Signal Control). Vision-based traffic signal control is formulated as a partially observable Markov decision process (POMDP) $\langle \mathcal{S}, \mathcal{O}, \mathcal{A}, R \rangle$:

- **State.** $\mathcal{S}$ is the latent traffic-state space. The local state $s_i^t \in \mathcal{S}$ at intersection i may include queue lengths, approaching-vehicle counts, waiting times, vehicle speeds, traffic density, and the current signal phase. The controller does not directly observe this complete state.
- **Observation.** $\mathcal{O}$ is the visual-observation space. Let $x_{i,d}^{t,k}$ denote the k -th image frame captured during control interval t by the roadside camera facing approach $d \in \{E, W, N, S\}$. The observation available to intersection i is the collection of frame sequences $o_i^t = \{x_{i,d}^{t,k}\}_{d \in \{E, W, N, S\}, k=1, \dots, K}$.
- **Action.** The feasible action set at intersection i is $\mathcal{A}_i = \{a_{i,1}, \dots, a_{i,m_i}\}$. An action $a_i^t \in \mathcal{A}_i$ selects a signal phase, i.e., a non-conflicting set of traffic movements that receives a green signal during the next control interval. The joint action space is $\mathcal{A} = \prod_{i \in \mathcal{I}} \mathcal{A}_i$.
- **Reward.** R evaluates the traffic outcome after an action. The network reward $R^t = R(s^t, \mathbf{a}^t, s^{t+1})$ measures system-wide traffic efficiency (e.g., queue length, travel time).

We consider a shared vision-based policy π_θ across intersections. At each signal-switching time step t , intersection i selects an action from its local frame observation o_i^t , neighbouring intersection context c_i^t , and its feasible phase set $\mathcal{A}_i$. The policy is optimized directly from visual observations to maximize long-term network-wide traffic efficiency:

$$\mathbf{a}^t = \{\pi_\theta(o_i^t, c_i^t, \mathcal{A}_i)\}_{i \in \mathcal{I}}, \quad \theta^* = \arg \max_{\theta} \mathbb{E}_{\pi_\theta} \left[\sum_{t=0}^{T-1} R^t(s^t, \mathbf{a}^t, s^{t+1}) \right]. \quad (1)$$

3 METHOD

We present VLALight, an end-to-end VLA model for cooperative traffic signal control. As illustrated in Figure 1, VLALight first extracts movement-level traffic conditions and temporal dynamics from multi-directional intersection videos. It then routes relevant perceptions from neighbouring intersections to support coordinated network-wide signal control. Our training proceeds in two stages: (1) supervised fine-tuning establishes visual traffic understanding and signal decision-making, and (2) cooperative agentic RL optimizes network-wide coordination using complementary local and network-level traffic rewards. During RL rollouts, the model explores Fast and Slow reasoning modes at each intersection, allowing different intersections in the same network-level rollout to use different modes and learning to balance decision quality and computational cost.

3.1 VISION-BASED TRAFFIC SIGNAL CONTROL

Spatiotemporal Traffic Perception. At each decision step t , the visual observation o_i^t contains K frames from the four approaches to intersection i . Rather than relying on precomputed traffic states, VLALight directly interprets these multi-frame observations to identify vehicles and their movements and to infer how traffic demand and queues evolve over the observation window. For each traffic lane l , the model reasons to summarize the visual dynamics as:

$$\tilde{o}_{i,l}^t = [v_{i,l}^t, q_{i,l}^t, \Delta v_{i,l}^t, \Delta q_{i,l}^t] = f_{\text{perc}}(o_{i,l}^t), \quad (2)$$

where $v_{i,l}^t$ and $q_{i,l}^t$ denote the observed vehicle count and queue length, $\Delta v_{i,l}^t$ and $\Delta q_{i,l}^t$ characterize their changes across the observed frames, and f_{perc} is the traffic perception process.

However, local perception is insufficient for coordinated control. Vehicles observed at one intersection will travel toward adjacent intersections and alter their near-future demand before they become visible to their views. To capture these neighbouring dynamics, VLALight aggregates movement-level perceptions according to lane connectivity and traffic-flow relations. For each intersection, we collect its perception results and transmit them to adjacent intersections as follows:

$$c_i^t = \{\tilde{o}_{i,j}^t \mid l \in \mathcal{N}(i), j \in \mathcal{L}_{l \rightarrow i}\}, \quad (3)$$

where $\mathcal{N}(i)$ is the set of intersections adjacent to i , and $\mathcal{L}_{l \rightarrow i} \subseteq \mathcal{L}_l$ are the lane connections from l to i . c_i^t preserves both the temporal dynamics observed at neighbouring intersections and the spatial connectivity, providing topology-aware context for coordinated traffic signal control. The detailed cooperative-context construction is described in Appendix A.8.

Efficiency-Aware Spatiotemporal Reasoning. VLALight integrates the local lane-level perceptions $\tilde{O} = \{\tilde{o}_{i,l}^t\}_{l \in \mathcal{L}_i}$ with the routed coordination context c_i^t to analyze traffic dynamics and select the signal action that maximizes network-wide traffic efficiency. The VLA model first selects a reasoning mode $m_i^t \in \{\text{fast}, \text{slow}\}$ according to the complexity of the observed traffic. Fast mode directly predicts a signal phase, whereas slow mode generates a structured reasoning sequence Y_i^t to perform deep reasoning on the traffic conditions and candidate phases before decision-making:

$$\pi_\theta(\tilde{O}_i^t, c_i^t, \mathcal{A}_i) = \begin{cases} (m_i^t, a_i^t), & \text{if } m_i^t = \text{fast}, \\ (m_i^t, Y_i^t, a_i^t), & \text{if } m_i^t = \text{slow}, \end{cases} \quad a_i^t \in \mathcal{A}_i. \quad (4)$$

Fast mode directly predicts a phase, whereas Slow mode additionally generates a reasoning sequence before selecting the phase. The resulting action is applied at intersection i during the next control interval, allowing VLALight to allocate additional computation only when deeper reasoning is beneficial. The detailed reasoning template is presented in Appendix A.10.

3.2 COOPERATIVE POLICY TRAINING

Effective multi-intersection control requires the policy to acquire video-grounded decision capabilities before learning how local phase choices affect neighbouring traffic and network-level outcomes. To establish this initial capability, we perform cold-start supervised fine-tuning from a pretrained vision-language model using video-grounded perception and signal-decision trajectories. To optimize coordination after initialization, we apply cooperative reinforcement learning with local and network-level traffic feedback. To allocate computation according to traffic complexity, we further train the policy with adaptive reasoning to balance decision quality and inference cost.

Cold-Start Supervised Training. Directly adapting pretrained VLMs to traffic signal control is unreliable because their pretraining rarely covers signal-control scenarios or the spatiotemporal reasoning required for traffic decision-making. We address this issue with a two-stage supervised cold start that separately establishes visual traffic understanding and signal decision-making. In the first stage, VLALight learns to extract movement-level traffic states from videos. Ground-truth traffic observations are converted into perception targets $\tilde{o}_{i,j}^t$, including vehicle counts, queue lengths, and their temporal variations, and used to supervise the mapping from visual observations to structured traffic perceptions. In the second stage, we construct reasoning trajectories using a frontier teacher model (e.g., DeepSeek-V4) with access to ground-truth traffic states. Given the perception labels and feasible action space, the teacher generates a reasoning sequence Y_i^t and a signal action a_i^t . We then assign the reasoning mode m_i^t based on the queue gap between the two candidate phases with the largest queues: samples with a gap of at least five vehicles are labeled Fast, and the others Slow. For Fast samples, we use the phase with the largest queue as the signal target, which agrees with the teacher-selected phase for most samples, and omit the reasoning target; for Slow samples, we retain the teacher-generated reasoning and signal. The resulting perception–reasoning–decision tuples are then used to jointly fine-tune VLALight with supervised training:

$$\mathcal{L}_{\text{SFT}} = - \sum_{\tau \in \mathcal{D}_{\text{SFT}}} [\log \pi_{\theta}(\tilde{o}_i^t | o_i^t) + \log \pi_{\theta}(m_i^t, Y_i^t, a_i^t | \tilde{o}_i^t, c_i^t, \mathcal{A}_i)], \quad (5)$$

where the second term includes the mode, reasoning, and action. Y_i^t is omitted when $m_i^t = \text{fast}$.

Efficiency-Aware Cooperative VLA RL. Building on the supervised initialization, we further optimize VLALight with RL to improve network-wide coordination while controlling reasoning cost. The online training data organization and hyperparameters are summarized in Appendix A.5. To help preserve video-grounded perception during RL, we retain a perception SFT loss and accumulate its gradients with those from decision rollouts before each optimizer step. We consider four optimization signals: local traffic efficiency $r_{i,\text{loc}}^t$, which measures traffic improvement at the controlled intersection; network-wide traffic efficiency r_{net}^t , which captures the impact on surrounding intersections; output-format consistency r_{fmt}^t ; and reasoning cost:

$$\kappa_i^t = \alpha \left[1 - \exp \left(-\frac{n_i^t}{\tau} \right) \right], \quad (6)$$

where n_i^t denotes the number of generated tokens, τ controls the growth rate, and α bounds the maximum cost. These signals differ substantially in scale and characterize different aspects of the policy. Following the reward-decoupled normalization principle of GDPO (Liu et al., 2026), we normalize each reward signal independently within each intersection’s rollout group, pooling candidates assigned to both reasoning modes. Specifically, for rollout k and reward signal d ,

$$A_{k,d}^t = \frac{r_{k,d}^t - \mu_d^t}{\sigma_d^t + \epsilon}, \quad (7)$$

where μ_d^t and σ_d^t are the group-wise mean and standard deviation of d , computed across candidates in the rollout group for the corresponding intersection. The reasoning-cost advantage is computed analogously from κ_k^t . We then construct the overall advantage as:

$$A_k^t = \lambda_{\text{loc}} A_{k,\text{loc}}^t + \lambda_{\text{net}} A_{k,\text{net}}^t + \lambda_{\text{fmt}} A_{k,\text{fmt}}^t - \lambda_{\text{cost}} A_{k,\text{cost}}^t, \quad (8)$$

where λ_d ($d \in \{\text{loc}, \text{net}, \text{fmt}, \text{cost}\}$) is the weight of reward signal d . This dimension-wise normalization prevents large-scale traffic rewards from overwhelming format or efficiency signals and provides a balanced learning signal for cooperative control and cost-effective reasoning.

However, the unconstrained sampling can lead to imbalanced reasoning-mode exploration, causing one mode to dominate the policy update before the model has learned their relative utility. We therefore explicitly construct balanced fast- and slow-mode rollouts. At each control step t , we generate a group of N candidate rollouts from the same visual observation and traffic state, and manually prepend an equal number of `<mode>fast</mode>` and `<mode>slow</mode>` tags as fixed generation prefixes for each intersection. Conditioned on the assigned mode, VLALight generates the corresponding reasoning sequence and the signal action. Using the group-normalized

rewards, we compare the mean utilities of the Fast and Slow rollouts within each intersection to guide mode selection. The optimization objective is to maximize the group-relative advantage:

$$\mathcal{L}_{RL} = -\mathbb{E}_k [\min(\rho_k A_k, \text{clip}(\rho_k, 1 - \epsilon, 1 + \epsilon) A_k)], \quad \rho_k = \frac{\pi_\theta(y_k | x_k)}{\pi_{\theta_{\text{old}}}(y_k | x_k)}. \quad (9)$$

where y_k is the generated rollout output, x_k is its conditioning context, and ϵ is the clipping epsilon.

4 EXPERIMENTS

We evaluate VLALight across traffic networks with diverse scales and demand patterns, and further analyze the contribution of each design component and its adaptive reasoning behavior. Specifically, we investigate the following research questions:

- **RQ1:** How does VLALight perform compared with existing transportation-based, RL-based, and LLM/VLM-based approaches in traffic signal control under diverse traffic scenarios?
- **RQ2:** How do cooperative information, the network-level cooperative reward, and balanced Fast/Slow rollouts contribute to traffic control performance beyond supervised fine-tuning?
- **RQ3:** How does VLALight allocate Fast and Slow reasoning in response to traffic pressure, and what trade-off does adaptive mode selection achieve among control performance, token usage, and inference latency?

4.1 EXPERIMENTAL SETUP

Datasets. We evaluate VLALight on seven real-world traffic-flow datasets (Jinan 1–3, Hangzhou 1–2, and New York 1–2) from three urban networks (Wei et al., 2019c). Detailed network configurations and trace statistics are provided in Appendix A.2.

Environment Settings. We use TranSimHub, a video-enabled three-dimensional traffic simulation platform built on the SUMO microscopic traffic simulator (Wang et al., 2025a; Lopez et al., 2018), to replay each trace and render the roadside observations. Each episode covers 3,600 s of simulated traffic. At every control step, each controlled intersection receives four directional roadside videos, and the controller selects one feasible phase from the common phase set. The four controlled phases are ETWT (east–west through), ELWL (east–west left-turn), NTST (north–south through), and NLSL (north–south left-turn). Each green phase lasts 25 s, followed by a 5 s yellow transition.

Compared Methods. We compare VLALight with representative controllers from four groups: transportation-engineering, RL-based, LLM-based, and VLM-based methods. Transportation-engineering and LLM-based controllers directly use complete and accurate traffic states provided by the simulator, whereas VLALight and VLM-based controllers operate on visual observations. Detailed descriptions of the compared methods are provided in Appendix A.3.

Evaluation Metrics. We evaluate traffic-control performance using Average Travel Time (ATT), Average Queue Length (AQL), and Average Waiting Time (AWT) (Zhang et al., 2022). ATT is the mean elapsed time for vehicles to travel from their origins to their destinations. AQL is the mean number of queued vehicles over the road network during the episode. AWT is the mean time vehicles spend waiting at intersections before completing their movements.

4.2 OVERALL PERFORMANCE (RQ1)

Table 1 compares traffic-control performance across seven datasets from Jinan, Hangzhou, and New York. The baselines reveal a clear progression. MaxPressure improves substantially over FixedTime by responding to traffic pressure. CoLight generally surpasses non-cooperative RL controllers by exchanging information across intersections. LLMLight and CoLLMLight further benefit from enhanced reasoning capabilities over structured traffic states. By contrast, off-the-shelf VLMs perform poorly, indicating that general visual-language capabilities alone are insufficient for traffic-specific spatiotemporal reasoning. Despite being optimized with online RL only on Jinan 1 and Hangzhou 1, VLALight successfully generalizes to all five unseen traffic traces.

VLALight achieves the best result in 16 of 21 dataset–metric comparisons despite using limited-view roadside videos, whereas transportation-engineering and LLM baselines receive complete simulator

Table 1: Traffic-control performance on the Jinan, Hangzhou, and New York datasets. Lower values are better. The best, second-best, and third-best results are highlighted through boldface, double underline, and underline, respectively. E- and A- denote Efficient and Advanced, respectively; Ge-4-31B-IT denotes Gemma-4-31B-IT.

Method	Jinan									Hangzhou									New York								
	ATT	1 AQL	AWT	ATT	2 AQL	AWT	ATT	3 AQL	AWT	ATT	1 AQL	AWT	ATT	2 AQL	AWT	ATT	1 AQL	AWT	ATT	2 AQL	AWT	ATT	1 AQL	AWT	ATT	2 AQL	AWT
Transportation-Engineering Methods																											
FixedTime	458.95	383.91	237.36	366.59	185.60	152.92	394.99	206.57	136.14	544.46	207.24	269.66	464.08	274.97	229.64	1464.24	2716.68	1171.09	1666.71	3940.70	1387.68						
MaxPressure	270.97	163.77	79.79	267.68	109.82	74.35	260.02	135.30	73.35	306.45	65.22	63.13	304.98	120.88	73.96	1215.43	2395.16	894.25	1467.47	4066.03	1202.50						
RL-Based Methods																											
PressLight	286.26	189.89	94.79	281.39	125.44	87.26	267.93	147.34	82.03	350.22	98.71	104.79	345.19	183.61	120.24	1511.56	3285.03	1322.43	1687.35	4661.39	1521.07						
MPLight	330.62	286.63	153.34	281.04	125.97	89.15	273.92	157.63	89.65	317.27	73.72	75.80	311.38	133.37	84.39	1229.75	2590.86	999.76	1526.80	4198.63	1303.49						
CoLight	272.15	166.55	81.70	267.35	108.98	75.03	262.32	138.57	76.43	308.80	66.23	66.64	307.51	126.48	79.17	1032.32	2056.00	734.90	1256.04	3339.83	970.57						
E-MPLight	293.79	204.88	103.39	349.17	201.84	152.36	312.26	215.90	127.38	384.44	132.26	145.23	456.64	342.78	250.48	1322.91	2665.49	1053.87	1638.79	4667.94	1426.80						
E-CoLight	273.99	169.18	82.40	265.66	107.91	72.17	259.71	135.48	73.14	306.85	64.88	62.95	306.35	122.76	76.42	1104.93	2183.63	784.81	1307.53	3521.47	1032.81						
A-CoLight	269.57	162.60	78.78	267.60	111.03	75.06	258.81	134.08	72.60	302.51	61.15	59.66	304.91	120.62	75.04	1094.28	2214.17	807.06	1303.36	3590.56	1051.77						
CityLight	364.87	317.15	171.01	322.59	171.63	127.74	321.50	222.25	133.37	360.27	107.85	115.80	528.86	389.34	310.30	1304.88	2685.88	1037.71	1525.28	4181.28	1290.92						
LLM-Based Methods																											
LLMLight	263.90	154.86	73.80	262.79	104.48	69.12	254.46	128.56	69.05	299.53	58.86	56.23	296.39	108.58	65.81	1051.99	1908.08	682.86	1347.41	3647.39	1032.21						
CoLLMLight	265.28	155.89	74.97	262.38	103.28	68.98	255.22	128.41	69.49	295.48	54.93	52.36	294.49	104.88	64.00	1009.34	1798.50	644.86	1263.85	3304.41	943.32						
VLM-Based Methods																											
VLMLight	381.64	368.59	196.32	295.38	140.70	99.90	415.10	567.78	370.77	310.73	64.44	61.22	318.51	140.60	95.84	1271.80	2610.89	993.17	1743.75	4928.48	1526.34						
Qwen3.5-27B	720.28	930.73	551.68	735.28	698.37	562.24	730.64	843.04	566.67	527.36	252.07	292.45	464.15	363.76	254.68	1620.75	3342.57	1397.52	1782.92	4943.55	1655.35						
Qwen3.5-9B	929.73	1216.28	754.35	891.58	870.12	709.09	786.08	952.59	615.97	767.84	463.15	550.13	615.56	572.92	416.91	1770.33	3781.35	1665.94	1909.77	5278.27	1816.58						
Ge-4-31B-IT	680.47	875.06	510.09	684.15	633.87	508.59	660.66	752.95	492.89	453.02	191.90	219.01	421.09	294.93	205.24	1592.13	3409.36	1367.92	1766.68	3409.36	1367.92						
VLALight	267.05	154.74	73.31	265.04	103.01	67.48	256.98	128.38	67.77	294.90	55.94	52.05	296.29	99.03	60.91	975.80	1565.44	566.82	1240.11	3121.64	880.49						

Table 2: Ablation results on New York 1 and New York 2. “w/o coop.” denotes removal of cooperative information, “w/o balance” denotes removal of balanced rollouts, and “w/o net. reward” denotes removal of the network-level cooperative reward.

Variant	New York 1			New York 2		
	ATT	AQL	AWT	ATT	AQL	AWT
SFT	1171.08	2439.95	866.98	1439.73	4021.12	1164.74
w/o coop.	1067.60	2365.90	914.98	1317.63	3690.11	1113.65
w/o balance	984.76	1654.22	595.02	1296.10	3328.31	938.46
w/o net. reward	991.34	1647.22	599.61	1261.11	3230.98	924.42
VLALight	975.80	1565.44	566.82	1240.11	3121.64	880.49




Figure 2: Slow-mode ratio across local queue-load groups.

states. Its advantage is significant on the two 196-intersection New York networks: it ranks first in ATT, AQL, and AWT on two datasets. This validates our cooperative multi-intersection RL design, which integrates topology-routed neighbouring perceptions with local and network-level rewards, enabling each agent to optimize immediate traffic conditions while accounting for downstream effects across the network. Compared with state-of-the-art baselines, VLALight reduces AQL and AWT by 13.0% and 12.1% on New York 1, and by 5.5% and 6.7% on New York 2. These results demonstrate effective network-wide coordination from partial visual observations.

4.3 ABLATION STUDIES (RQ2)

Table 2 evaluates cooperative information, network-level reward, and balanced Fast/Slow rollouts on both New York datasets. VLALight is initialized from Qwen3.5-4B. We exclude the original Qwen3.5-4B model because it cannot output structurally valid control actions. The post-trained VLALight consistently outperforms SFT across all metrics, demonstrating that online cooperative RL provides substantial gains beyond supervised initialization. Among the RL ablations, removing cooperative information causes the largest degradation, particularly in AQL and AWT. This result indicates that topology-routed neighbouring perceptions compensate for the limited field of view at each intersection and are essential for modeling network-wide traffic interactions. Removing the network-level reward also degrades every metric, showing that optimizing local traffic alone does not reliably produce network-wide improvements. Finally, removing balanced Fast/Slow rollouts reduces performance, especially on New York 2, indicating that explicit exposure to both reasoning modes improves exploration and policy learning. Together, these results validate the effectiveness of our proposed training procedure in VLALight.

Table 3: Adaptive reasoning token statistics and ATT on New York datasets. Fast and Slow report the percentages of decisions assigned to each mode.

Trace	Method	Reasoning statistics				Control performance
		Fast (%)	Slow (%)	Avg. Tokens (Slow)	Min-max Tokens (Slow)	ATT
New York 1	VLALight	51.92	48.08	220.47	54–545	975.80
New York 1	w/o balanced rollouts	27.56	72.44	209.42	62–649	984.76
New York 1	SFT	59.72	40.28	233.15	62–1,230	1171.08
New York 2	VLALight	51.24	48.76	208.26	58–682	1240.11
New York 2	w/o balanced rollouts	28.38	71.62	204.92	62–609	1296.10
New York 2	SFT	60.27	39.73	230.50	62–1,124	1439.73

Table 4: Control performance under forced and adaptive mode allocation.

Mode	Jinan 1			Hangzhou 2		
	ATT	AQL	AWT	ATT	AQL	AWT
Pure Fast	268.93	157.75	74.88	297.95	101.22	62.86
Pure Slow	263.48	154.97	72.86	295.28	97.09	59.90
VLALight	267.05	154.74	73.31	296.29	99.03	60.91

Table 5: Average per-decision inference latency on two H100 GPUs over 500 sampled intersection decisions (seconds).

Mode	Samples	Perception time	Decision time	Total
Pure Fast	174	2.601	0.265	2.866
Pure Slow	326	2.563	1.944	4.507
Overall	500	2.576	1.360	3.936

4.4 ADAPTIVE REASONING AND INFERENCE EFFICIENCY (RQ3)

Adaptive Mode Allocation. Table 3 examines how balanced rollout training affects inference-time mode allocation, slow-mode token usage, and control performance on the two New York datasets. Balanced rollout training produces a markedly different allocation policy. VLALight invokes slow reasoning for approximately 48% of decisions on both traces, whereas the variant without balanced rollouts selects slow-mode more than 72% of the time but still yields worse ATT. Thus, simply allowing the policy to choose a mode does not produce an effective computation strategy. Without balanced Fast/Slow exploration, training becomes biased toward the more expensive mode without a corresponding control benefit. SFT shows the opposite behavior: it invokes slow mode less frequently, but produces considerably longer slow-mode outputs and substantially weaker control performance. This indicates that our balanced rollout exploration enables VLALight to learn when additional deliberation is genuinely beneficial. As a result, the policy achieves a more cost-effective trade-off between control utility and reasoning overhead.

Control Quality and Inference Efficiency. To isolate the effect of reasoning depth, we fix the mode token at inference to construct Pure Fast and Pure Slow policies and compare them with VLALight’s adaptive allocation in Table 4. We further profile per-decision latency on two H100 GPUs over 500 sampled decisions; Table 5 reports the mean perception, decision, and total latency for Fast and Slow decisions and for the adaptive policy overall. Pure Slow achieves the best result on most metrics, confirming that extended reasoning benefits difficult control decisions, whereas Pure Fast is consistently weaker. Importantly, VLALight remains close to Pure Slow across both datasets and even achieves the lowest AQL on Jinan 1, showing that adaptive mode selection preserves most of the benefit of deeper reasoning without paying its cost for every decision. Fast and slow decisions require 2.866 s and 4.507 s on average, respectively. VLALight’s adaptive allocation reduces the overall mean to 3.936 s, 12.7% below the slow-mode latency. Perception time is nearly constant across modes, while decision time accounts for the efficiency difference, directly validating the contribution of adaptive reasoning.

4.4.1 TRAFFIC PRESSURE AND ADAPTIVE MODE SELECTION

We next examine whether the learned allocation responds meaningfully to traffic complexity. Using video-grounded perception records, we group decisions by the average queue load across the four candidate phases: queue-free observations and three positive-load groups separated at 0.5 and 1.75 vehicles per phase. As shown in Figure 2, the Slow-mode ratio rises monotonically from 38.86% in queue-free conditions to 49.81%, 60.39%, and 63.14% as queue pressure increases. This trend provides direct evidence that VLALight reserves additional computation for more demanding traffic states rather than selecting modes arbitrarily. The representative cases in Figure 3 further show that




Figure 3: Case study on adaptive reasoning.

fast reasoning is used when one local phase is clearly preferable, while slow reasoning is activated when competing phases or topology-routed neighbour pressure make the decision more ambiguous.

5 RELATED WORK

Traffic Signal Control. Traffic signal control (TSC) has evolved from fixed schedules and pressure-based rules to RL controllers that learn phase policies and coordinate neighbouring intersections through attention, graphs, and multi-agent communication (Koonce et al., 2008; Hunt et al., 1982; Varaiya, 2013; Oroojlooy et al., 2020; Wu et al., 2023; Devailly et al., 2022; Liang et al., 2022; Lou et al., 2022; Wei et al., 2018; Zheng et al., 2019; Wei et al., 2019a; Chen et al., 2020; Wei et al., 2019b; Wu et al., 2021a; Yu et al., 2020; Ruan et al., 2024; Mercader et al., 2020). LLM-assisted methods then introduced tool-based human-mimetic reasoning and arterial coordination, while iLLM-TSC uses an LLM to revise RL decisions under incomplete observations and rare events (Wang et al., 2024; Tang et al., 2024; Pang et al., 2026). LLMLight treats the LLM as a direct controller; CoLLMLight adds asynchronous network-wide cooperation; and Traffic-R1 applies reinforcement learning to improve reasoning and generalization (Lai et al., 2025; Yuan et al., 2026; Zou et al., 2026). VLMLight incorporates visual meta-control but delegates routine actions to RL (Wang et al., 2025b). Consequently, prior systems largely depend on structured simulator states or modular planners, which leaves end-to-end TSC from physical visual observations unexplored.

Vision-Language-Action Models. Vision-language-action (VLA) models directly map visual-language inputs to executable actions. RT-2 introduced action tokenization to transfer web-scale knowledge to robotic control, while OpenVLA provided an open generalist manipulation model (Brohan et al., 2023; Kim et al., 2024). Embodied Chain-of-Thought subsequently grounded intermediate reasoning in plans, objects, and robot states (Zawalski et al., 2024). Efficiency-oriented work explores state-space backbones, compact policies, frequency-space action tokenization, training-free compression, and adaptive token caching (Liu et al., 2024; Wen et al., 2025; Pertsch et al., 2025; Yang et al., 2025; Xu et al., 2025). AutoVLA extends unified action generation to autonomous driving, using supervised Fast/Slow modes and reinforcement fine-tuning to balance planning quality and reasoning cost (Zhou et al., 2025).

6 CONCLUSION

We introduced VLALight, the first VLA framework for end-to-end traffic signal control from multi-view roadside videos. VLALight directly connects physical visual observations with executable signal actions through multi-target spatiotemporal reasoning and topology-aware cooperative perception. Its two-stage supervised initialization and cooperative agentic RL enable network-level control with adaptive Fast/Slow reasoning that balances traffic efficiency and inference cost. Experiments on seven real-world traffic-flow datasets across Jinan, Hangzhou, and New York demonstrate consistent improvements over transportation-, RL-, and LLM/VLM-based controllers, while ablations validate the contributions of cooperative perception, network optimization, and adaptive reasoning. These results highlight the potential of VLA models for real-world physical traffic control.

REFERENCES

- Baher Abdulhai, Rob Pringle, and Grigoris J. Karakoulas. Reinforcement learning for true adaptive traffic signal control. *Journal of Transportation Engineering*, 129(3):278–285, 2003. doi: 10.1061/(ASCE)0733-947X(2003)129:3(278).
- Anthony Brohan, Noah Brown, Justice Carbajal, Yevgen Chebotar, Xi Chen, Krzysztof Choromanski, et al. RT-2: Vision-language-action models transfer web knowledge to robotic control. *arXiv preprint arXiv:2307.15818*, 2023.
- Chacha Chen, Hua Wei, Nan Xu, Guanjie Zheng, Ming Yang, Yuanhao Xiong, Kai Xu, and Zhenhui Li. Toward a thousand lights: Decentralized deep reinforcement learning for large-scale traffic signal control. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 3414–3421, 2020. doi: 10.1609/aaai.v34i04.5744.
- François-Xavier Devailly, Denis Larocque, and Laurent Charlin. IG-RL: Inductive graph reinforcement learning for massive-scale traffic signal control. *IEEE Transactions on Intelligent Transportation Systems*, 23(7):7496–7507, 2022. doi: 10.1109/TITS.2021.3070835.
- P. B. Hunt, D. I. Robertson, R. D. Bretherton, and M. C. Royle. The SCOOT on-line traffic signal optimisation technique. *Traffic Engineering & Control*, 23(4), 1982.
- Moo Jin Kim, Karl Pertsch, Siddharth Karamcheti, Ted Xiao, Ashwin Balakrishna, Suraj Nair, Rafael Rafailov, Ethan Foster, Grace Lam, Pannag Sanketi, Quan Vuong, Thomas Kollar, Benjamin Burchfiel, Russ Tedrake, Dorsa Sadigh, Sergey Levine, Percy Liang, and Chelsea Finn. OpenVLA: An open-source vision-language-action model. *arXiv preprint arXiv:2406.09246*, 2024.
- Peter Koonce, Lee Rodegertds, Kevin Lee, Shaun Quayle, Scott Beaird, Cade Braud, Jim Bonneson, Phil Tarnoff, and Tom Urbanik. Traffic signal timing manual. Technical Report FHWA-HOP-08-024, Federal Highway Administration, 2008.
- Siqi Lai, Zhao Xu, Weijia Zhang, Hao Liu, and Hui Xiong. LLMlight: Large language models as traffic signal control agents. In *Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining V.1*, pp. 2335–2346, 2025. doi: 10.1145/3690624.3709379.
- Enming Liang, Zicheng Su, Chilin Fang, and Renxin Zhong. OAM: An option-action reinforcement learning framework for universal multi-intersection control. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pp. 4550–4558, 2022. doi: 10.1609/aaai.v36i4.20378.
- Jiaming Liu, Mengzhen Liu, Zhenyu Wang, Pengju An, Xiaoqi Li, Kaichen Zhou, Senqiao Yang, Renrui Zhang, Yandong Guo, and Shanghang Zhang. RoboMamba: Efficient vision-language-action model for robotic reasoning and manipulation. In *Advances in Neural Information Processing Systems*, volume 37, pp. 40085–40110, 2024. doi: 10.52202/079017-1266.
- Shih-Yang Liu, Xin Dong, Ximing Lu, Shizhe Diao, Peter Belcak, Mingjie Liu, Min-Hung Chen, Hongxu Yin, Yu-Chiang Frank Wang, Kwang-Ting Cheng, Yejin Choi, Jan Kautz, and Pavlo Molchanov. GDPO: Group reward-decoupled normalization policy optimization for multi-reward RL optimization. *arXiv preprint arXiv:2601.05242*, 2026.
- Pablo Alvarez Lopez, Michael Behrisch, Laura Bieker-Walz, Jakob Erdmann, Yun-Pang Flötteröd, Robert Hilbrich, Leonhard Lücken, Johannes Rummel, Peter Wagner, and Evamarie Wiessner. Microscopic traffic simulation using SUMO. In *2018 21st International Conference on Intelligent Transportation Systems (ITSC)*, pp. 2575–2582, 2018. doi: 10.1109/ITSC.2018.8569938.
- Yican Lou, Jia Wu, and Yunchuan Ran. Meta-reinforcement learning for multiple traffic signals control. In *Proceedings of the 31st ACM International Conference on Information & Knowledge Management*, pp. 4264–4268, 2022. doi: 10.1145/3511808.3557640.
- Hao Mei, Junxian Li, Bin Shi, and Hua Wei. Reinforcement learning approaches for traffic signal control under missing data. In *Proceedings of the Thirty-Second International Joint Conference on Artificial Intelligence*, pp. 2261–2269, 2023. doi: 10.24963/ijcai.2023/251.

- Pedro Mercader, Wasim Uwayid, and Jack Haddad. Max-pressure traffic controller based on travel times: An experimental analysis. *Transportation Research Part C: Emerging Technologies*, 110: 275–290, 2020. doi: 10.1016/j.trc.2019.10.002.
- Afshin Oroojlooy, Mohammadreza Nazari, Davood Hajinezhad, and Jorge Silva. AttendLight: Universal attention-based reinforcement learning model for traffic signal control. In *Advances in Neural Information Processing Systems*, volume 33, pp. 4079–4090, 2020.
- Aoyu Pang, Maonan Wang, Man-On Pun, Chung Shue Chen, and Xi Xiong. iLLM-TSC: Integration reinforcement learning and large language model for traffic signal control policy improvement. *IEEE Transactions on Vehicular Technology*, 75(8):15762–15776, 2026. doi: 10.1109/TVT.2026.3674284.
- Karl Pertsch, Kyle Stachowicz, Brian Ichter, Danny Driess, Suraj Nair, Quan Vuong, Oier Mees, Chelsea Finn, and Sergey Levine. FAST: Efficient action tokenization for vision-language-action models. In *Robotics: Science and Systems XXI*, 2025. doi: 10.15607/rss.2025.xxi.012.
- Syed Shah Sultan Mohiuddin Qadri, Mahmut Ali Gökçe, and Erdinç Öner. State-of-art review of traffic signal control methods: Challenges and opportunities. *European Transport Research Review*, 12(1):55, 2020. doi: 10.1186/s12544-020-00439-1.
- Jingqing Ruan, Ziyue Li, Hua Wei, Haoyuan Jiang, Jiaming Lu, Xuantang Xiong, Hangyu Mao, and Rui Zhao. CoSLight: Co-optimizing collaborator selection and decision-making to enhance traffic signal control. In *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pp. 2500–2511, 2024. doi: 10.1145/3637528.3671998.
- Yiqing Tang, Xingyuan Dai, and Yisheng Lv. Large language model-assisted arterial traffic signal control. *IEEE Journal of Radio Frequency Identification*, 8:322–326, 2024. doi: 10.1109/JRFID.2024.3384289.
- Pravin Varaiya. Max pressure control of a network of signalized intersections. *Transportation Research Part C: Emerging Technologies*, 36:177–195, 2013. doi: 10.1016/j.trc.2013.08.014.
- Lefei Wang, Zhaoyu Zhang, Xin Di, and Jun Tian. A roadside camera-radar sensing fusion system for intelligent transportation. In *2020 17th European Radar Conference (EuRAD)*, pp. 282–285. IEEE, 2021. doi: 10.1109/EURAD48048.2021.00079.
- Maonan Wang, Aoyu Pang, Yuheng Kan, Man-On Pun, Chung Shue Chen, and Bo Huang. LLM-Assisted Light: Leveraging large language model capabilities for human-mimetic traffic signal control in complex urban environments. *arXiv preprint arXiv:2403.08337*, 2024.
- Maonan Wang, Yirong Chen, Yuxin Cai, Aoyu Pang, Yuejiao Xie, Zian Ma, Chengcheng Xu, Kemou Jiang, Ding Wang, Laurent Roullet, Chung Shue Chen, Zhiyong Cui, Yuheng Kan, Michael Lepech, and Man-On Pun. TranSimHub: A unified air-ground simulation platform for multi-modal perception and decision-making. *arXiv preprint arXiv:2510.15365*, 2025a.
- Maonan Wang, Yirong Chen, Aoyu Pang, Yuxin Cai, Chung Shue Chen, Yuheng Kan, and Man On Pun. VLMLight: Safety-critical traffic signal control via vision-language meta-control and dual-branch reasoning architecture. In *Advances in Neural Information Processing Systems*, volume 38, pp. 44266–44297, 2025b. doi: 10.52202/085713-1320.
- Hua Wei, Guanjie Zheng, Huaxiu Yao, and Zhenhui Li. IntelliLight: A reinforcement learning approach for intelligent traffic light control. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 2496–2505, 2018. doi: 10.1145/3219819.3220096.
- Hua Wei, Chacha Chen, Guanjie Zheng, Kan Wu, Vikash Gayah, Kai Xu, and Zhenhui Li. PressLight: Learning max pressure control to coordinate traffic signals in arterial network. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 1290–1298, 2019a. doi: 10.1145/3292500.3330949.

- Hua Wei, Nan Xu, Huichu Zhang, Guanjie Zheng, Xinshi Zang, Chacha Chen, Weinan Zhang, Yanmin Zhu, Kai Xu, and Zhenhui Li. CoLight: Learning network-level cooperation for traffic signal control. In *Proceedings of the 28th ACM International Conference on Information and Knowledge Management*, pp. 1913–1922, 2019b. doi: 10.1145/3357384.3357902.
- Hua Wei, Guanjie Zheng, Vikash V. Gayah, and Zhenhui Li. A survey on traffic signal control methods. *arXiv preprint arXiv:1904.08117*, 2019c.
- Hua Wei, Guanjie Zheng, Vikash Gayah, and Zhenhui Li. Recent advances in reinforcement learning for traffic signal control. *ACM SIGKDD Explorations Newsletter*, 22(2):12–18, 2021. doi: 10.1145/3447556.3447565.
- Junjie Wen, Yichen Zhu, Jinming Li, Minjie Zhu, Zhibin Tang, Kun Wu, Zhiyuan Xu, Ning Liu, Ran Cheng, Chaomin Shen, Yaxin Peng, Feifei Feng, and Jian Tang. TinyVLA: Toward fast, data-efficient vision-language-action models for robotic manipulation. *IEEE Robotics and Automation Letters*, 10(4):3988–3995, 2025. doi: 10.1109/LRA.2025.3544909.
- Libing Wu, Min Wang, Dan Wu, and Jia Wu. DynSTGAT: Dynamic spatial-temporal graph attention network for traffic signal control. In *Proceedings of the 30th ACM International Conference on Information & Knowledge Management*, pp. 2150–2159, 2021a. doi: 10.1145/3459637.3482254.
- Qiang Wu, Liang Zhang, Jun Shen, Linyuan Lü, Bo Du, and Jianqing Wu. Efficient pressure: Improving efficiency for signalized intersections. *arXiv preprint arXiv:2112.02336*, 2021b.
- Qiang Wu, Mingyuan Li, Jun Shen, Linyuan Lü, Bo Du, and Ke Zhang. TransformerLight: A novel sequence modeling based traffic signaling mechanism via gated transformer. In *Proceedings of the 29th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pp. 2639–2647, 2023. doi: 10.1145/3580305.3599530.
- Siyu Xu, Yunke Wang, Chenghao Xia, Dihao Zhu, Tao Huang, and Chang Xu. VLA-Cache: Efficient vision-language-action manipulation via adaptive token caching. In *Advances in Neural Information Processing Systems*, volume 38, pp. 182377–182402, 2025. doi: 10.52202/085713-5484.
- Yantai Yang, Yuhao Wang, Zichen Wen, Zhongwei Luo, Chang Zou, Zhipeng Zhang, Chuan Wen, and Linfeng Zhang. EfficientVLA: Training-free acceleration and compression for vision-language-action models. In *Advances in Neural Information Processing Systems*, volume 38, pp. 45758–45781, 2025. doi: 10.52202/085713-1365.
- Zhengxu Yu, Shuxian Liang, Long Wei, Zhongming Jin, Jianqiang Huang, Deng Cai, Xiaofei He, and Xian-Sheng Hua. MaCAR: Urban traffic light control via active multi-agent communication and action rectification. In *Proceedings of the Twenty-Ninth International Joint Conference on Artificial Intelligence*, pp. 2491–2497, 2020. doi: 10.24963/ijcai.2020/345.
- Zirui Yuan, Siqi Lai, and Hao Liu. CoLLMLight: Cooperative large language model agents for network-wide traffic signal control. In *The Fourteenth International Conference on Learning Representations*, 2026. URL <https://openreview.net/forum?id=KeJqoEVOeY>.
- Michał Zawalski, William Chen, Karl Pertsch, Oier Mees, Chelsea Finn, and Sergey Levine. Robotic control via embodied chain-of-thought reasoning. *arXiv preprint arXiv:2407.08693*, 2024.
- Jinwei Zeng, Chao Yu, Xinyi Yang, Wenxuan Ao, Qian Yue Hao, Jian Yuan, Yong Li, Yu Wang, and Huazhong Yang. CityLight: A neighborhood-inclusive universal model for coordinated city-scale traffic signal control. In *Proceedings of the 34th ACM International Conference on Information and Knowledge Management*, pp. 4036–4044, 2025. doi: 10.1145/3746252.3761285.
- Liang Zhang, Qiang Wu, Jun Shen, Linyuan Lü, Bo Du, and Jianqing Wu. Expression might be enough: Representing pressure and demand for reinforcement learning based traffic signal control. In *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 26645–26654. PMLR, 2022. URL <https://proceedings.mlr.press/v162/zhang22ah.html>.

- Guanjie Zheng, Yuanhao Xiong, Xinshi Zang, Jie Feng, Hua Wei, Huichu Zhang, Yong Li, Kai Xu, and Zhenhui Li. Learning phase competition for traffic signal control. In *Proceedings of the 28th ACM International Conference on Information and Knowledge Management*, pp. 1963–1972, 2019. doi: 10.1145/3357384.3357900.
- Xingcheng Zhou, Mingyu Liu, Ekim Yurtsever, Bare Luka Zagar, Walter Zimmer, Hu Cao, and Alois C. Knoll. Vision language models in autonomous driving: A survey and outlook. *IEEE Transactions on Intelligent Vehicles*, 2024. doi: 10.1109/TIV.2024.3402136.
- Zewei Zhou, Tianhui Cai, Seth Z. Zhao, Yun Zhang, Zhiyu Huang, Bolei Zhou, and Jiaqi Ma. AutoVLA: A vision-language-action model for end-to-end autonomous driving with adaptive reasoning and reinforcement fine-tuning. In *Advances in Neural Information Processing Systems*, volume 38, pp. 31725–31761, 2025. doi: 10.52202/085713-0942.
- Xingchen Zou, Yuhao Yang, Zheng Chen, Xixuan Hao, Yiqi Chen, Chao Huang, and Yuxuan Liang. Traffic-R1: Reinforced LLMs bring human-like reasoning to traffic signal control systems. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 21823–21838, 2026. doi: 10.18653/v1/2026.acl-long.995.

A APPENDIX

A.1 SETTINGS OF TRAFFIC SIGNAL CONTROL

The benchmark environments share the intersection geometry and phase design shown in Figure 4. Each four-arm intersection contains 12 incoming lanes. Four controlled phases serve through and left-turn movements, while right-turn movements remain permissive.




Figure 4: Traffic-signal-control setting used in our experiments. (A) A four-arm intersection. (B) Twelve incoming lanes and their permitted movements; right turns remain permissive. (C) Four controlled signal phases, each pairing non-conflicting movements: ETWT and NTST serve east-west and north-south through movements, respectively, whereas ELWL and NLSL serve the corresponding left-turn movements.

A.2 DATASETS AND TRAFFIC NETWORKS

We evaluate VLALight on seven real-world traffic-flow datasets from three urban networks. Each trace specifies vehicle departures and routes for a one-hour episode on its corresponding road network.

- **Jinan:** Located in the Dongfeng sub-district, the network contains 12 intersections arranged as a 3×4 grid and three datasets from different collection periods. Each intersection has two 400-m east-west roads and two 800-m north-south roads.
- **Hangzhou:** Located in the Gudang sub-district, the network contains 16 intersections arranged as a 4×4 grid and two datasets from different collection periods. Each intersection has two 800-m east-west roads and two 600-m north-south roads.
- **New York:** Covering Manhattan’s Upper East Side, the network contains 196 intersections arranged as a 28×7 grid. Its two large-scale datasets are derived from taxi-trip demand from different periods, with 300-m road segments.

Table 6 reports the number of vehicles and five-minute arrival statistics for every trace. Arrival statistics are computed from vehicle entry times using 300-s bins; $\mu \pm \sigma$ denotes the mean and population standard deviation across bins, and the final column gives the observed minimum and maximum.

Table 6: Traffic-flow trace statistics. Arrival rates are vehicles per 5 min; values are reported as mean $\pm$ standard deviation, followed by the observed range.

City	Trace	Grid	Vehicles	5-min arrivals ($\mu \pm \sigma$)	Min–max
Jinan	1	3×4	6295	524.58 ± 98.53	256–672
Jinan	2	3×4	4365	363.75 ± 74.66	237–493
Jinan	3	3×4	5494	457.83 ± 46.22	363–544
Hangzhou	1	4×4	2983	248.58 ± 40.45	212–333
Hangzhou	2	4×4	6984	582.00 ± 318.52	203–1146
New York	1	28×7	11058	850.62 ± 174.20	383–965
New York	2	28×7	16337	1256.69 ± 264.96	476–1441

A.3 COMPARED METHODS

This section briefly summarizes the control interfaces and design principles of the methods included in our comparison. The descriptions refer to the configurations used in our experiments.

FixedTime (Koonce et al., 2008): Applies a predetermined cycle and phase schedule, without adapting the signal plan to the current traffic state.

MaxPressure (Varaiya, 2013): Selects the phase with the largest pressure differential, computed from the queue imbalance between incoming and outgoing movements.

PressLight (Wei et al., 2019a): Learns a deep policy whose observation and optimization signal are derived from intersection pressure, thereby adapting the max-pressure principle through reinforcement learning.

MPLight (Chen et al., 2020): Uses pressure-based traffic features for both state representation and reward design within a multi-agent learning framework built on FRAP-style phase relations.

CoLight (Wei et al., 2019b): Models the road network as interacting agents and uses graph attention to exchange information between neighbouring intersections.

Efficient-MPLight and Efficient-CoLight (Wu et al., 2021b): Reduce the state complexity of pressure-based control by using compact pressure observations, while retaining the single-intersection and cooperative variants, respectively.

Advanced-CoLight (Zhang et al., 2022): Extends graph-based cooperative control with richer traffic-state features, including pressure and effective running-vehicle information.

CityLight (Zeng et al., 2025): Uses parameter-sharing MAPPO to learn a universal policy for heterogeneous intersections, with dedicated modules for encoding and aggregating neighbour influence in city-scale networks.

LLMLight (Lai et al., 2025): Uses a large language model as the signal-control agent. Given structured traffic descriptions, the model reasons over candidate phases and produces the control decision.

CoLLMLight (Yuan et al., 2026): Extends LLM-based signal control to network-wide coordination by allowing agents at connected intersections to use cooperative traffic information.

VLMLight (Wang et al., 2025b): Uses vision-language meta-control and dual-branch reasoning to interpret visual traffic observations and select signal-control actions. In our experiments, we adapt VLMLight by using Qwen3.5-72B to analyze four directional images and route control according to traffic pressure. Under normal conditions, a shared Advanced-CoLight policy selects the phase; high pressure activates VLM-based phase selection and validation. Unlike the original emergency-vehicle trigger, our implementation uses traffic pressure to activate this branch.

A.4 MODEL SETTINGS

All RL baselines are trained with shared hyperparameters, including a learning rate of 1×10^{-3} , a replay-buffer capacity of 12,000, a sample size of 3,000, and a hidden size of 20. VLALight is built

upon Qwen3.5-4B and supervised fine-tuned with LoRA using rank 16, scaling factor 32, dropout 0.05, and a learning rate of 1×10^{-4} . Each video input is represented by six frames at a resolution of 512×960 pixels.

A.5 AGENTIC RL SETTINGS

Starting from the cold-start Qwen3.5-4B policy, we perform agentic reinforcement learning with online SUMO streams from the Jinan 1 and Hangzhou 1 datasets. At each training step, we use two Jinan 1 and two Hangzhou 1 network instances with different random seeds. All intersections within each network instance jointly execute one 30-s control-cycle transition, yielding intersection-level decision records from the synchronized network snapshot. Each decision uses six synchronized candidates, with three Fast and three Slow rollouts. Network-level reward is evaluated for each complete network instance over three subsequent control cycles. The resulting records are updated intersection by intersection with a mini-batch size of 4, for 50 training steps, using a policy learning rate of 1×10^{-6} . After independent within-group normalization, the network, local, reasoning-cost, and format dimensions are combined with weights 0.5, 1.0, 0.5, and 1.0, respectively. During these updates, the perception supervised loss is retained with coefficient 0.1 to preserve visual traffic understanding while optimizing the cooperative decision policy.

A.6 COOPERATIVE VLA ROLLOUT AND POLICY UPDATE

Algorithm 1 summarizes the training procedure used by VLALight. Let $\mathcal{I}$ denote the controlled intersections. For each network decision snapshot, we collect the joint visual observations $\mathbf{V}^t = \{V_i^t\}_{i \in \mathcal{I}}$ and generate the corresponding local perceptions and routed cooperative contexts once, obtaining $\mathbf{P}^t$ and $\mathbf{C}^t$. These inputs are shared by all candidates in the rollout group. A rollout is defined at the network level: the b -th candidate jointly assigns a reasoning mode, reasoning sequence, and signal action to every intersection,

$$\mathbf{m}^{(b),t} = \{m_i^{(b),t}\}_{i \in \mathcal{I}}, \quad \mathbf{a}^{(b),t} = \{a_i^{(b),t}\}_{i \in \mathcal{I}}, \quad (10)$$

and produces one network trajectory $\tau^{(b)} = (s^t, \mathbf{a}^{(b),t}, s^{(b),t+1}, \dots, s^{(b),t+H})$. All actions in a candidate are applied jointly before the environment is advanced. The resulting network-level reward is shared by all intersection records belonging to that candidate, whereas local traffic, format, and reasoning-cost signals remain intersection-specific. Let q_i^t denote the queue at intersection i , and let $Q^t = \sum_{i \in \mathcal{I}} q_i^t$ and $Q^{(b),t+H} = \sum_{i \in \mathcal{I}} q_i^{(b),t+H}$ denote the total network queues at the initial and terminal states. We define the normalized queue-improvement scores as

$$\begin{aligned} r_{\text{net}}^{(b)} &= Q^t - Q^{(b),t+H}, \\ r_{\text{local},i}^{(b)} &= q_i^t - q_i^{(b),t+1}. \end{aligned} \quad (11)$$

Thus, the network reward measures the queue reduction from t to the rollout endpoint after three transitions, while the local reward measures the first-transition reduction from t to $t+1$. Positive values indicate queue reduction. The format penalty is assigned as

$$r_{\text{fmt},i}^{(b)} = \begin{cases} -1, & \text{if the signal is invalid,} \\ -\frac{1}{2}, & \text{if the signal is valid but the response format is invalid,} \\ 0, & \text{if the response is valid.} \end{cases} \quad (12)$$

The optimization then uses two complementary updates: a mode-selection update that compares Fast and Slow candidates separately, and a joint policy update that aggregates the rollout signals across all controlled intersections without splitting by reasoning mode.

Algorithm 1 Cooperative VLA Rollout

Require: Joint network observations $\mathbf{V}^t$, road network $\mathcal{G}$, policy π_θ , rollout number N

- 1: Generate $\mathbf{P}^t$ and routed contexts $\mathbf{C}^t = \mathcal{R}(\mathbf{P}^t, \mathcal{G})$ once from the network snapshot
- 2: Share $(\mathbf{P}^t, \mathbf{C}^t)$ across the N candidate rollouts
- 3: Construct N balanced mode maps $\{\mathbf{m}^{(b),t}\}_{b=1}^N$, with Fast and Slow balanced separately for each intersection
- 4: **for** each rollout $b = 1, \dots, N$ **do**
- 5: Generate $\{Y_i^{(b),t}, a_i^{(b),t}\}_{i \in \mathcal{I}}$ conditioned on $\mathbf{m}^{(b),t}$ and $(\mathbf{P}^t, \mathbf{C}^t)$
- 6: Apply the joint action $\mathbf{a}^{(b),t}$ and advance the network for $H = 3$ transitions; use temperature-zero continuation decisions
- 7: Compute one network reward $r_{\text{net}}^{(b)}$ and intersection-specific local, format, and cost signals
- 8: **end for**
- 9: Broadcast $r_{\text{net}}^{(b)}$ to every intersection in rollout b
- 10: Compare the Fast and Slow candidates for each intersection and update the mode selection
- 11: Update the shared policy with the joint rollout signals from all controlled intersections, without splitting the update by mode
- 12:
- 13: **return** updated policy π_θ

A.7 TWO-STAGE COOPERATIVE VLA INFERENCE

At deployment, the video agent extracts structured traffic states from the four approach videos and routes information through the road topology to form cooperative context. Stage 2 combines local and cooperative perceptions, selects Fast or Slow reasoning, and generates the signal action (Algorithm 2).

Algorithm 2 Two-Stage Cooperative VLA Inference

Require: Four-direction videos $\mathbf{V}_i^t$, topology-routed coordination evidence $\mathbf{N}_i^t$, current phase and history, policy π_θ

Ensure: Signal phase a_i^t

- 1: Generate the structured local perception P_i^t from the four-direction videos $\mathbf{V}_i^t$
- 2: Route relevant perceptions and coordination evidence through the directed road topology to obtain cooperative context C_i^t
- 3: Combine P_i^t and C_i^t into the Stage 2 decision context
- 4: Select $m_i^t \in \{\text{Fast}, \text{Slow}\}$ adaptively from the observed traffic context
- 5: Generate the signal decision conditioned on the combined context and selected mode
- 6: Parse the selected signal phase as a_i^t
- 7: **return** a_i^t

A.8 CONSTRUCTION OF COOPERATIVE INFORMATION

At each decision step, VLALight routes two complementary signals over the directed road network (Figure 5). For each candidate phase, it follows outgoing lanes to the connected downstream intersection and extracts one frame from its video window. This frame estimates potential arrivals on the corresponding target movement, forming the `local_coordination` field and representing vehicles not yet visible locally.

For the `neighbors` field, Stage 1 perceptions from actual neighboring intersections are mapped through the movement-route table to the target’s approach directions. Vehicle and queue counts on connected upstream movements are aggregated by direction and paired with estimated link travel time. This summarizes upstream pressure, not guaranteed arrivals, because upstream signals control whether and when vehicles are released. Stage 2 receives both fields alongside the target’s local perception.




Figure 5: Topology-routed cooperative information: (A) downstream-linked frames estimate potential arrivals; (B) upstream vehicle and queue counts with link travel time summarize directional demand.

A.9 CASE STUDY

We present two decision steps from the New York network to illustrate how VLALight adapts reasoning depth to traffic complexity. Each case contains six one-second-spaced observations, and each observation combines the north, east, west, and south views of the target intersection. The figures expose the video-grounded local perception, routed cooperative perception, routing mode, and selected phase; the following paragraphs explain why the two cases take different decision paths.




Figure 6: **Fast case.** A clear local-demand winner leads to fast routing.




Figure 7: **Slow case.** Competing local and cooperative evidence triggers slow reasoning.

A.9.1 FAST CASE

At intersection 1-19 (step 54), NTST is the clear local winner: it has the largest visible and queued demand ($v/q = 9/9$), the strongest recent increase ($\Delta v/\Delta q = +4/+8$), and the longest unserved age. The upstream context contains no direct phase-level arrivals and only modest neighbour pressure. VLALight can therefore trust the video-grounded local evidence, route the decision to the fast branch, and select NTST without spending tokens on deliberation. This case shows how the policy preserves low-latency control when one phase is already supported by consistent evidence.

A.9.2 SLOW CASE

At intersection 3-1 (step 52), local demand is ambiguous: ETWT has $v/q = 20/20$ and has waited for two intervals, while NTST and NLSL each have $v/q = 19/19$ and were served more recently. The routed context adds 19 direct ETWT arrivals and upstream pressure from the east, north, and west approaches. VLALight invokes the slow branch to reconcile these local and cooperative signals, identifies the waiting and arrival advantage of ETWT, and selects ETWT. This case demonstrates that the adaptive policy reserves explicit reasoning for decisions where network context changes the local preference rather than applying deliberation uniformly.

A.10 PROMPT TEMPLATES

This appendix records the prompt templates used by the video-grounded controller. The templates are shown in normalized form: runtime-specific values such as the intersection identifier, video objects, coordination frames, perception JSON, and neighbour summaries are inserted into the indicated placeholders. The output blocks are kept explicit because they define the interface between visual perception and signal control.

A.10.1 STAGE 1: VIDEO-GROUNDED PERCEPTION

The perception prompt supplies four direction-specific videos and the available upstream coordination frames. It asks the model to return traffic features for all four candidate phases and to keep local observations separate from predicted arrivals.

```
[system]
You are a visual traffic perception model for a four-way intersection.

You receive four direction-specific videos of the current intersection and any
available upstream coordination frames. Infer only the structured traffic features
supported by the visual evidence.

Right-turn movements are permanently permissive and are not controlled by the
four candidate signal phases.

Return exactly one <perception>...</perception> block. Do not output a mode,
reasoning, signal decision, or any text outside the perception block.

[user]
Intersection: <INTERSECTION_ID>
Current phase: <CURRENT_PHASE>

Visual inputs:
- East approach video: <VIDEO_E>
- West approach video: <VIDEO_W>
- North approach video: <VIDEO_N>
- South approach video: <VIDEO_S>

Upstream coordination frames, keyed by target entry direction:
<COORDINATION_FRAMES>

Use every supplied coordination frame. The frame label is the target
intersection's entry direction. Attribute counts as follows:
E -> ET and EL; W -> WT and WL; N -> NT and NL; S -> ST and SL.
Missing directions indicate unavailable upstream visual evidence, usually at a
road-network boundary. Do not treat a missing frame as zero vehicles.
Keep coordinated-arrival counts separate from current_v and current_q.

Controller-provided persistent-demand history:
<UNSERVED_HISTORY>

Temporal convention:
- Each approach video contains six synchronized frames sampled every 5 seconds:
  t=5, 10, 15, 20, 25, and 30 seconds in the current decision window.
- The decision is made at t=30 seconds.
```


- current_v and current_q describe the latest observation at t=30 seconds.
- dv and dq compare the latest and earliest observations.
- For a boundary movement, the coordinated-arrival estimate may use the t=30 versus t=15 observation; do not interpret it as a general demand trend.

For every candidate phase, estimate:

- the total visible vehicles and the two movement-level counts;
- the stopped subset of those vehicles;
- the recent changes in visible demand and queue size;
- the potential arrivals from available upstream frames.

Current V is the total visible service demand in the two movements released by a phase. Its movement breakdown must not be added again. Current q is a subset of current V. Coordinated arrivals are future-pressure estimates and must not be added to local visible demand.

Output exactly one structured perception block and nothing else:

```
<perception>
{
  "current_phase": "<CURRENT_PHASE>",
  "phases": {
    "ETWT": {
      "v": [<ET_V>, <WT_V>], "q": [<ET_Q>, <WT_Q>],
      "dv": <ETWT_DV>, "dq": <ETWT_DQ>, "age": <ETWT_AGE>,
      "coord": {
        "ET": {"count": <ET_ARRIVALS>, "is_boundary": "<yes/no>"},
        "WT": {"count": <WT_ARRIVALS>, "is_boundary": "<yes/no>"}
      }
    },
    "NTST": {
      "v": [<NT_V>, <ST_V>], "q": [<NT_Q>, <ST_Q>],
      "dv": <NTST_DV>, "dq": <NTST_DQ>, "age": <NTST_AGE>,
      "coord": {
        "NT": {"count": <NT_ARRIVALS>, "is_boundary": "<yes/no>"},
        "ST": {"count": <ST_ARRIVALS>, "is_boundary": "<yes/no>"}
      }
    },
    "ELWL": {
      "v": [<EL_V>, <WL_V>], "q": [<EL_Q>, <WL_Q>],
      "dv": <ELWL_DV>, "dq": <ELWL_DQ>, "age": <ELWL_AGE>,
      "coord": {
        "EL": {"count": <EL_ARRIVALS>, "is_boundary": "<yes/no>"},
        "WL": {"count": <WL_ARRIVALS>, "is_boundary": "<yes/no>"}
      }
    },
    "NLSL": {
      "v": [<NL_V>, <SL_V>], "q": [<NL_Q>, <SL_Q>],
      "dv": <NLSL_DV>, "dq": <NLSL_DQ>, "age": <NLSL_AGE>,
      "coord": {
        "NL": {"count": <NL_ARRIVALS>, "is_boundary": "<yes/no>"},
        "SL": {"count": <SL_ARRIVALS>, "is_boundary": "<yes/no>"}
      }
    }
  }
}
</perception>
```

Here v denotes visible vehicle count, q denotes stopped-vehicle count, dv and dq denote recent changes, and age records persistent unmet demand. The movement order is fixed as ETWT=[ET,WT], NTST=[NT,ST], ELWL=[EL,WL], and NLSL=[NL,SL].

A.10.2 STAGE 2: ROUTED SIGNAL DECISION

The decision prompt receives the structured local perception and the routed cooperative context. It constrains the output to a valid phase and selects Fast mode when one phase is clearly preferred, while using Slow mode when local and cooperative evidence require an explicit comparison.

[system]
You are the decision stage of a traffic signal controller.
The perception JSON below was produced by Stage 1 and has already been routed across the intersection. Choose exactly one phase from ETWT, NTST, ELWL, NLSL.

Return either:

```
<mode>fast</mode>
<signal>PHASE</signal>
```

or:

```
<mode>slow</mode>
<reasoning>brief comparison</reasoning>
<signal>PHASE</signal>
```

Do not emit markdown or text outside the required tags.

[user]
 You are an intelligent traffic signal controller for a four-phase intersection.
 Use the local and cooperative perceptions below to decide which candidate phase
 should be served next.

The controller operates in 30-second cycles: 25 seconds of green followed by a
 5-second signal-transition interval. The decision is made immediately before
 the transition, and the selected phase receives the next green interval.

```
<local_perception>
{
  "current_phase": "<CURRENT_PHASE>",
  "phases": {
    "ETWT": { "current_v": <ETWT_V>, "current_q": <ETWT_Q>,
              "dv": <ETWT_DV>, "dq": <ETWT_DQ>, "unserved_age": <ETWT_AGE> },
    "NTST": { "current_v": <NTST_V>, "current_q": <NTST_Q>,
              "dv": <NTST_DV>, "dq": <NTST_DQ>, "unserved_age": <NTST_AGE> },
    "ELWL": { "current_v": <ELWL_V>, "current_q": <ELWL_Q>,
              "dv": <ELWL_DV>, "dq": <ELWL_DQ>, "unserved_age": <ELWL_AGE> },
    "NLSL": { "current_v": <NLSL_V>, "current_q": <NLSL_Q>,
              "dv": <NLSL_DV>, "dq": <NLSL_DQ>, "unserved_age": <NLSL_AGE> }
  }
}
</local_perception>

<cooperative_perception>
{
  "local_coordination": {
    "ETWT": <ETWT_POTENTIAL_ARRIVALS>, "NTST": <NTST_POTENTIAL_ARRIVALS>,
    "ELWL": <ELWL_POTENTIAL_ARRIVALS>, "NLSL": <NLSL_POTENTIAL_ARRIVALS>
  },
  "neighbors": {
    "DIRECTION": { "total_v": <NEIGHBOR_V>, "total_q": <NEIGHBOR_Q>,
                  "travel_time_s": <TRAVEL_TIME> }
  }
}
</cooperative_perception>
```

Local-field meanings:

- current_phase is the phase currently receiving service.
- current_v is the visible serviceable vehicle count for a phase.
- current_q is the stopped-vehicle subset of current_v.
- dv and dq are recent changes in visible demand and queue size.
- unserved_age measures the number of decision intervals since service.

Cooperative-field meanings:

- local_coordination contains potential arrivals for each target phase.
 Keep these arrivals separate from current_v and current_q.
- neighbors contains broad directional pressure from connected intersections.
 Do not convert it into a fixed target phase or assume that all vehicles will
 definitely arrive, because the neighbour's future release is unknown.
- North/south neighbour pressure can adjust the priority of NTST and NLSL;
 east/west pressure can adjust the priority of ETWT and ELWL.
- travel_time_s indicates when broad neighbour pressure may reach the target.
- Missing directions are boundary directions and should be ignored.

Decision guidance:

- Prefer phases that can release the largest visible demand and queue pressure.
- Prioritize sustained or worsening pressure over brief fluctuations.
- Use direct local_coordination, persistent unmet demand, and queue urgency to
 break ties between otherwise comparable phases.
- Choose fast mode when one candidate phase is clearly preferable.
- Choose slow mode when multiple phases are comparable or when local trends,
 direct coordination, persistent demand, and neighbour context disagree.

Critical output format:

```
Fast mode:
<mode>fast</mode>
<signal>SELECTED_PHASE</signal>

Slow mode:
<mode>slow</mode>
<reasoning>concise decision reasoning</reasoning>
<signal>SELECTED_PHASE</signal>
```

Do not repeat the perception JSON. Do not output text before <mode> or after
 </signal>. SELECTED_PHASE must be exactly ETWT, NTST, ELWL, or NLSL.

Perception-to-Decision Interface. Stage 1 returns a structured <perception> object contain-
 ing movement-level observations for the four candidate phases. Before Stage 2, the router aggre-
 gates movement-level vehicle and queue counts into phase-level current_v and current_q,
 carries over dv and dq, and maps age to unserved_age. The movement-level coord en-
 tries are routed separately as phase-aligned potential arrivals in local_coordination. The
 resulting local summary and routed neighbor summaries are provided through two parallel blocks,

<local_perception> and <cooperative_perception>, respectively. Stage 2 combines these structured inputs to select the reasoning mode and signal phase, and outputs the corresponding mode, optional reasoning, and signal tags.

Code Availability. The source code is publicly available at <https://github.com/usail-hkust/VLALight.git>.