

SQUARE: STRUCTURED QUANTUM REPRESENTATION ADAPTERS AS COMPACT QUADRATIC FEATURE MAPS FOR FROZEN LANGUAGE MODELS

Emily Jimin Roh¹, Hyojun Ahn¹, Hoyeong Lee¹, Soohyun Park²,
Sung Whan Yoon³, Vaneet Aggarwal⁴, Joongheon Kim^{1,5*}

¹Korea University ²Sookmyung Women’s University ³Ulsan National Institute of Science and Technology

⁴Purdue University ⁵Seoul National University Hospital

ABSTRACT

Frozen language models (LMs) are increasingly used as fixed feature extractors for downstream reranking, scoring, and preference modeling, raising a practical question: how should a compact module represent interactions among features in a fixed low-dimensional bottleneck? Common linear and low-rank adapters remain linear at the adaptation module itself, whereas explicit second-order alternatives introduce pairwise interactions through direct parameterization or predefined factorizations. We propose **SQUARE**, a **Structured QUAntum REpresentation** adapter that amplitude-encodes the bottleneck vector, applies a parameterized quantum circuit, and measures the resulting state. We show that each basis-probability feature is exactly a normalized quadratic form in the bottleneck coordinates, while the additional Pauli- Z readouts are signed linear combinations of these probabilities. The measured map can therefore parameterize interactions over $O(d^2)$ coordinate pairs through a small set of shared circuit parameters, where d is the bottleneck dimension. It provides a structured parameterization within, rather than beyond, the classical normalized-quadratic feature class. In a disjoint same-pipeline evaluation over eight GLUE-derived controlled interaction tasks and five shared seeds, SQUARE achieves an average test accuracy of 0.7565, compared with 0.7355 for an affine normalized-quadratic predictor, 0.7271 for the evaluated parameter-matched Givens mixing model, 0.6817 for an MLP, and 0.6155 for a frozen-circuit control. Under reduced supervision, it also shows consistent gains over the strongest evaluated classical comparator, with the same qualitative pattern across multiple frozen LM backbones. All circuit experiments use simulation, while the learned feature map can be evaluated exactly in batched PyTorch without quantum hardware. These results indicate that how interaction coefficients are parameterized, rather than merely how many are learned, is a key design axis for compact adaptation over frozen language representations.

1 INTRODUCTION

Frozen language models (LMs) provide reusable representations for classification, scoring, reranking, and preference modeling without updating the backbone (Sanford et al., 2023; Garg et al., 2022). In this setting, a compact downstream module receives a fixed low-dimensional bottleneck $z \in \mathbb{R}^d$ and must make the target-relevant structure accessible to a lightweight task head. The central difficulty is not whether the frozen LM can encode rich information, but how a small post-bottleneck map should parameterize dependencies among its coordinates.

As illustrated in Fig. 1A, a first-order linear map aggregates weighted coordinate effects, but does not explicitly expose products $z_i z_j$ at its output. Bias-only and low-rank linear transformations similarly remain first order at this adaptation stage (He et al., 2022; Mao et al., 2022; Hu et al., 2022;

*Corresponding author: joongheon@korea.ac.kr




Figure 1: **First-order adaptation and SQUARE over frozen LM bottleneck.** (A) A linear baseline aggregates weighted coordinate effects but does not explicitly output pairwise products. (B) SQUARE normalizes and amplitude-encodes z , learns structured circuit mixing, and measures a readout containing normalized z_i^2 and $z_i z_j$ terms. During training, simulator backpropagation jointly updates the circuit and classical head. For deployment, the learned map is compiled exactly into a batched PyTorch implementation with the same outputs. Shared circuit angles constrain many interaction coefficients, while inference remains fully compatible with classical frozen-LM pipelines.

Liu et al., 2024; Zeng & Lee, 2024). Interaction structure can instead be represented classically through explicit polynomial expansions, bilinear heads, factorization machines, kernels, and random features (Rendle, 2010; Rahimi & Recht, 2007; Williams & Seeger, 2001); these alternatives differ primarily in how they constrain and share second-order coefficients.

We study the same design question through a parameterized quantum circuit: *what coefficient structure is imposed when a compact frozen-LM bottleneck is amplitude-encoded, transformed, and measured?* SQUARE, summarized in Fig. 1B, applies a trainable R_Y-R_Z -Ring-CNOT- R_Y unitary and measures the result. One shared unitary generates the complete probability feature bank, so its low-rank PSD coefficient matrices are jointly compatible with the same complex rows and collectively resolve the identity. This coupled family—not quadraticity or entanglement alone—is the inductive bias evaluated here. We therefore center exact classical characterization and mechanism-matched comparison (Bietti & Mairal, 2019).

We use **SQUARE**, a **Structured QUANTUM REpresentation** adapter for frozen LM features, as a concrete case study of this question. SQUARE freezes the LM, projects its representation into a low-dimensional bottleneck, and maps the bottleneck through the encoding-mixing-measurement pipeline in Fig. 1B (Ashhab, 2022; Schuld et al., 2021). The measured features are then passed to a lightweight classical head. Measurement after a trainable unitary yields a structured nonlinear feature map: squaring linearly transformed amplitudes makes each basis probability a normalized quadratic form in the bottleneck coordinates (Havlíček et al., 2019; Liu et al., 2021; Boneberg et al., 2025; Huang et al., 2021; Du et al., 2021). These probability features are PSD and rank at most two and jointly resolve the identity; Pauli- Z readouts are signed linear combinations of them and need not themselves be PSD or low rank. This gives SQUARE a two-stage interpretation: training uses a circuit-native encoding-unitary-measurement construction to learn the interaction structure, while deployment uses its exact algebraic image as a batched PyTorch module. The value of the quantum formulation is therefore the structured learning principle it induces, not a claim that the resulting function is inaccessible classically.

We evaluate SQUARE with controlled and generation-oriented protocols. For controlled classification, we extract frozen LM representations from GLUE inputs and replace original labels with labels generated from nonlinear interaction rules (Wang et al., 2018; Hewitt & Liang, 2019; Belinkov, 2022). This preserves realistic language inputs while fixing the target dependency. Because prediction over a frozen bottleneck is naturally an embedding-space problem, the comparison set is mechanism-matched, spanning classical second-order, kernel, non-parametric, graph-based, and manifold-based approximators (Section 4); we also report performance on the original, unmodified GLUE labels. We further use candidate reranking, circuit ablations, and simulated noise sensitivity as scope-limited diagnostics (Ouyang et al., 2022; Liu et al., 2022).

All quantum-circuit components are evaluated using a PennyLane-based simulator (Miessen et al., 2024; Yu et al., 2024; Zhang et al., 2022). The simulator is an implementation of the circuit parameterization, not an algorithmic requirement: the same angles and gate product can be differentiated directly in PyTorch. After optimization, the learned unitary is compiled into batched complex-valued PyTorch, providing numerically equivalent classical inference without per-sample simulator calls or quantum hardware. Compact here refers to the number of trainable post-bottleneck parameters, not to a guaranteed training-time, memory, or latency advantage over specialized classical adapters. Our primary experiment is the disjoint same-pipeline comparison in Section 4.2: SQUARE reaches 0.7565, compared with 0.7355 for an affine normalized-quadratic score, 0.7271 for the evaluated parameter-matched Givens-12 mixing model, 0.6817 for the MLP, and 0.6155 for a frozen circuit. Here and throughout, “transfer across backbones” means that the adapter protocol is retrained on regenerated controlled labels for each frozen backbone; it does not mean zero-shot transfer of one trained adapter or preservation of one semantic labeling rule.

Our contributions can be summarized as follows. **(i) Jointly compatible quadratic feature parameterization.** We establish that one common unitary generates the normalized rank-at-most-two PSD probability forms, distinguish their signed Pauli- Z combinations, and characterize the circuit’s locally low-dimensional image (Section 3.2). The known amplitude-squaring identity is the starting point; the coupled feature family is the object studied here. **(ii) Circuit-specified training with exact classical realization.** We optimize the encoding–unitary–measurement map end-to-end and realize the same learned transformation as a numerically matched batched PyTorch module. The circuit serves as a compact parameterization language rather than a requirement for simulator-based training or inference. **(iii) Mechanism-matched empirical validation.** Controlled interaction tasks, compact-budget comparisons, and disjoint held-out controls show that the learned unitary-measurement constraint improves over the evaluated linear, MLP-style, frozen-circuit, and matched compact quadratic alternatives under the corresponding protocols. The result is evidence for a useful structured inductive bias in these controlled settings, not a claim of quantum computational advantage or universal superiority on natural-label NLP tasks.

2 RELATED WORK

Parameter-Efficient Adaptation over Language Models. Parameter-efficient adaptation updates only a small subset of LM parameters instead of the full pretrained backbone (He et al., 2022; Mao et al., 2022). Representative methods include BitFit (Zaken et al., 2022), bottleneck adapters (Houlsby et al., 2019; Mahabadi et al., 2021), prefix- and prompt-tuning (Li & Liang, 2021; Lester et al., 2021), low-rank methods such as LoRA, AdaLoRA, and DoRA (Hu et al., 2022; Zhang et al., 2023; Liu et al., 2024), and orthogonal, low-precision, sparse, and more expressive low-rank variants (Wang et al., 2023; Dettmers et al., 2023; Nikdan et al., 2024; Zeng & Lee, 2024; Zhu et al., 2024; Hayou et al., 2024; Meng et al., 2024; Li et al., 2026; Song et al., 2024). These methods are highly effective, but many compact variants primarily implement bias shifts, bottleneck transformations, or low-rank linear updates. Our work studies a complementary setting in which Transformer weights are never adapted: all learning happens downstream of a fixed frozen bottleneck. Transformer-weight adaptation methods are therefore broad references rather than the mechanism-matched comparison set, and the LoRA- and adapter-style modules evaluated in our experiments are PEFT-inspired bottleneck transformations operating at the same stage as SQUARE.

Classical Interaction Models over Fixed Representations. Learning over a fixed embedding has strong classical second-order solutions: polynomial expansions, bilinear heads, factorization machines (Rendle, 2010), kernel approximations (Rahimi & Recht, 2007; Williams & Seeger, 2001), and factorized polynomial models (Chrysos et al., 2020). SQUARE belongs to this broader design space after compilation. Its narrower distinction is that one shallow complex-unitary circuit jointly generates a normalized probability feature bank. Amplitude-encoded feature maps are already known to correspond to low-degree polynomial kernels (Havlíček et al., 2019; Schuld et al., 2021); our contribution is the analysis and controlled empirical test of this particular coupled restriction, not quadraticity or coefficient sharing in general.

Quantum-Enhanced Adaptation in Language Models. Quantum-enhanced learning methods have recently been explored as compact hybrid modules inside large neural systems (Jerbi et al., 2021; Zhao et al., 2024; Ye et al., 2025). For LM adaptation, QAA amplitude-encodes hidden states

and merges quantum-transformed activations with frozen representations (Roh & Kim, 2025), while QPA uses a parameterized quantum circuit (PQC) to generate PEFT weights (Liu et al., 2025); both share a hybrid protocol in which the backbone remains classical and the quantum component is simulated (Yu et al., 2024; Zhang et al., 2022; Miessen et al., 2024; Preskill, 2018; Kim et al., 2023).

SQUARE differs in its adaptation target: rather than encoding the full hidden state as in QAA or generating PEFT weights as in QPA, it operates on a compact projected subspace of frozen LM features, exposing measured interaction features for a downstream head (Ashhab, 2022; Schuld et al., 2021; Havlíček et al., 2019; Boneberg et al., 2025; Huang et al., 2021; Du et al., 2021). Table 5 and additional quantum machine learning (QML) background are provided in Appendix A.7.

Our identity is the amplitude-encoding case of the kernel view of Schuld (2021); QuIC (Raj & Coyle, 2025) instead adapts Transformer weights with quantum-inspired orthogonal adapters.

3 SQUARE

Let $h = f_{\text{LM}}(x) \in \mathbb{R}^D$ be a representation from a frozen language model, and let $z = P(h) \in \mathbb{R}^d$ be a fixed compact bottleneck. Many compact adapters can be viewed as applying a restricted transformation before a task head, $\hat{F}(z) = g_\phi(T_\theta z)$, where T_θ denotes the adapter transformation and g_ϕ is a lightweight task head with parameters ϕ . These updates are parameter-efficient, but when instantiated as linear or low-rank transformations at the frozen-bottleneck stage, the adapter mapping itself remains linear in z and does not explicitly output pairwise products. When the target depends on relations among features, such as $z_i z_j$, comparisons, or compositions, the adapter must make such interaction structure accessible to the task head. SQUARE instead explicitly constructs measured second-order features by amplitude-encoding z , applying a parameterized unitary, and measuring the resulting state before the lightweight task head.

3.1 PROBLEM FORMULATION

We formalize frozen-representation adaptation as learning a compact predictor over $z = P(f_{\text{LM}}(x)) \in \mathbb{R}^d$, where neither the backbone f_{LM} nor the projection P is updated. Only the adaptation module parameters θ and task-head parameters ϕ are trained. We decompose the target rule over z into two components, i.e., $F^*(z) = F_{\text{lin}}(z) + F_{\text{int}}(z)$. The first term captures independent evidence from individual coordinates, $F_{\text{lin}}(z) = b + \sum_i a_i z_i$, while the second captures pairwise and higher-order relations among coordinates, $F_{\text{int}}(z) = \sum_{i < j} a_{ij} z_i z_j + \mathcal{H}(z)$. Here, $z_i z_j$ represents cross-feature interactions and $\mathcal{H}(z)$ denotes task-specific nonlinear relations such as comparison, composition, or consistency. At the adapter stage, linear, bias-only, and low-rank transformations do not explicitly construct pairwise products of the bottleneck coordinates. SQUARE instead produces a measured feature map $q_\theta(z)$ whose coordinates contain normalized cross-amplitude products, providing the downstream head with an explicit basis for second-order interaction structure.

The resulting predictor is $\hat{F}_{\theta, \phi}(z) = g_\phi(q_\theta(z))$ or $g_\phi([z; q_\theta(z)])$, depending on whether the quantum-only or residual hybrid variant is used. This formulation is task-agnostic: $\hat{F}_{\theta, \phi}(z)$ can be interpreted as a class logit, a scalar score, or a candidate-ranking score.

3.2 SQUARE: MEASURED QUANTUM FEATURE MAP

SQUARE maps a compact frozen-LM representation into a measured quantum feature map. The module has three steps: encoding the representation into a quantum state, applying a trainable quantum circuit, and measuring the resulting state to obtain classical features for a lightweight task head.

Encoding. Classical LM representations lie in a Euclidean feature space, while quantum circuits operate on state vectors in Hilbert space. SQUARE bridges these spaces by amplitude-encoding the compact frozen representation $z \in \mathbb{R}^d$ into an n -qubit state, where $n = \lceil \log_2 d \rceil$. Let $B = 2^n$. If $d < B$, we zero-pad z to dimension B ; for notational simplicity, we denote the padded vector again by z . Consequently, SQUARE prepares

$$|\psi(z)\rangle = \sum_{i=0}^{B-1} \alpha_i(z) |i\rangle, \quad (1)$$

where $\alpha(z) = \frac{z}{\|z\|_2}$. This is a representation change rather than a learned compression: the encoded inner product equals cosine similarity, so amplitude-encoding preserves the angular geometry of nonzero bottleneck directions but not norm magnitude. Nonlinear interaction features arise only after the circuit transformation and measurement (for the ε -stabilized normalization and the $z = 0$ case: see Appendix A.6).

Parameterized Quantum Circuit. After encoding, SQUARE applies a parameterized quantum circuit U_θ to $|\psi(z)\rangle$, whose trainable parameters θ are rotation angles rather than weight matrices, so the circuit parameterizes a transformation of the encoded state before measurement; the parameters are optimized during training in the default SQUARE configuration. Our default circuit uses a rotation–entanglement–rotation structure. Each layer first applies a trainable $RYRZ$ rotation block to every qubit, then applies CNOT gates along a ring topology, and finally applies another trainable RY rotation to each qubit:

$$U_\theta = \prod_{\ell=1}^L \left[\left(\prod_{q=1}^n RY_q(\theta_{\ell q}^{(3)}) \right) U_{\text{ring}} \left(\prod_{q=1}^n RZ_q(\theta_{\ell q}^{(2)}) RY_q(\theta_{\ell q}^{(1)}) \right) \right]. \quad (2)$$

Products are ordered by circuit application order (rightmost gates act first within each layer): the inner $RYRZ$ block, the ring entanglement block, and a final RY refinement before measurement.

The ring operator is

$$U_{\text{ring}} = \text{CNOT}_{n,1} \left(\prod_{q=n-1}^1 \text{CNOT}_{q,q+1} \right). \quad (3)$$

The ring block connects all qubits with n CNOT gates per layer (one-indexed notation), a compact prespecified pattern relative to all-to-all entanglement; together, the rotations and topology determine the coefficient family exposed by measurement. Entanglement is not required for cross-coordinate products: product rotations can already create dense amplitude-coordinate rows whose squared magnitudes contain such terms. We therefore treat the ring as one architectural prior rather than as the source of interaction expressivity.

Quantum Measurement. After processing via a parameterized circuit, the representation is still a quantum state. SQUARE reads out classical features by concatenating two measurement readouts (the second is an exact linear function of the first; see below). Let $|\varphi(z; \theta)\rangle = U_\theta |\psi(z)\rangle$ be the evolved quantum state, and let $B = 2^n$ denote the number of computational basis states.

First, SQUARE uses computational-basis probabilities:

$$p_j(z; \theta) = |\langle j | \varphi(z; \theta) \rangle|^2 = |\langle j | U_\theta |\psi(z)\rangle|^2, \quad j = 0, \dots, B-1. \quad (4)$$

Second, it measures local Pauli- Z expectations:

$$\zeta_r(z; \theta) = \langle \varphi(z; \theta) | Z_r | \varphi(z; \theta) \rangle = \langle \psi(z) | U_\theta^\dagger Z_r U_\theta | \psi(z) \rangle, \quad r = 1, \dots, n, \quad (5)$$

where Z_r denotes the Pauli- Z operator acting on qubit r . The measured SQUARE feature is the concatenation of both readouts:

$$q_\theta(z) = [p_0(z; \theta), \dots, p_{B-1}(z; \theta), \zeta_1(z; \theta), \dots, \zeta_n(z; \theta)]. \quad (6)$$

The readout dimension is $B + n$, with no additional trainable readout parameters; n is small because SQUARE operates on a compact bottleneck, so the $B = 2^n$ probability readout remains tractable.

Both readouts can be written as expectation values of measurement operators. Collect the readout operators into $\mathcal{M} = \{|j\rangle\langle j|\}_{j=0}^{B-1} \cup \{Z_r\}_{r=1}^n$. For any $M_k \in \mathcal{M}$, the corresponding measured coordinate is

$$\mu_k(z; \theta) = \langle \psi(z) | U_\theta^\dagger M_k U_\theta | \psi(z) \rangle. \quad (7)$$

This common form allows both probability features and Pauli- Z expectation features to be analyzed through the same measurement-induced interaction expansion.

Measurement-Induced Interactions. SQUARE obtains nonlinear features because measurement after a trainable quantum evolution is a quadratic form in the encoded amplitudes. Let $z \neq 0$, $\alpha(z) = z/\|z\|_2$, and $|\psi(z)\rangle = \sum_i \alpha_i(z) |i\rangle$. For a measurement operator M_k , the circuit U_θ induces an effective measurement operator $A_k(\theta) = U_\theta^\dagger M_k U_\theta$. Substituting this into Eq. (7) yields $\mu_k(z; \theta) =$

$\alpha(z)^\dagger A_k(\theta) \alpha(z)$. Since M_k is Hermitian and U_θ is unitary, $A_k(\theta)$ is Hermitian. Thus, real-valued amplitude encoding becomes

$$\mu_k(z; \theta) = \sum_{i=0}^{B-1} A_{k,ii}(\theta) \alpha_i(z)^2 + 2 \sum_{0 \leq i < j < B} \text{Re}(A_{k,ij}(\theta)) \alpha_i(z) \alpha_j(z). \quad (8)$$

Because $\alpha_i(z) \alpha_j(z) = z_i z_j / \|z\|_2^2$ for non-padded coordinates, the off-diagonal terms correspond to normalized cross-feature products. Therefore, the measured coordinates explicitly expose normalized cross-feature relations of the form $z_i z_j / \|z\|_2^2$, providing the task head with features aligned with the pairwise interaction terms in $F_{\text{int}}(z)$.

Exact Quadratic Containment and Effective Readout Rank. Because U_θ is independent of z , Eq. (8) is exact for the probability feature map: numerical reconstruction gives $R^2 = 1.0000$ and maximum residual below 5×10^{-7} . The readout is linearly redundant ($\zeta_r = \sum_j (-1)^{j_r} p_j$, $\sum_j p_j = 1$), so the nominal $(B+n)$ -dimensional readout at $d = B = 16$ has centered rank at most 15. Each real coefficient matrix $Q_j = a_j a_j^\top + b_j b_j^\top \succeq 0$ has rank at most two and the matrices sum to identity. Jacobian ranks provide only local image dimensions (12 at sampled generic points for the default depth-1 circuit), not a global manifold claim. Real circuits form a restricted orthogonal-square family; the phased default circuit instead forms a restricted complex-unitary magnitude-square family. Exact quadraticity applies to $p_\theta(z)$, not automatically to a nonlinear head or to the separate boundary pipeline, which uses a learned nonlinear projection and $\sqrt{p}$ magnitude features (Appendix A.4).

3.3 TRAINING AND PARAMETERIZATION

Hybrid Quantum-Classical Training. Training follows a hybrid quantum-classical optimization procedure: the classical head parameters ϕ are updated by standard backpropagation, and the circuit rotation angles θ receive exact reverse-mode (backprop) gradients through the statevector simulation, composed with the head by the chain rule, so that $q_\theta(z)$ and the task head are trained end-to-end while the LM backbone remains frozen (parameter shift is the hardware alternative; Appendix A.5).

Parameter Count. All reported parameter counts include only trainable adapter and task-head parameters. The frozen LM f_{LM} and fixed projection P are excluded. For SQUARE, the trainable quantum parameters are the circuit rotation angles. If d is not a power of two, we pad to the next power of two and use $n = \lceil \log_2 d \rceil$ qubits. With depth L and three trainable rotations per qubit per layer, the number of quantum parameters is $|\theta_q| = 3Ln$. The ring entanglement uses Ln CNOT gates and introduces no trainable parameters. Thus, the total number of trainable SQUARE parameters is $|\theta_q| + |\phi|$, where $|\phi|$ denotes the parameters of the lightweight task head. With g stored trainable rotations per qubit per layer, measurement width m , C output logits, and an optional mixer with N_{mix} parameters, the trainable post-bottleneck count is $N_{\text{SQUARE}} = gL \lceil \log_2 d \rceil + N_{\text{mix}} + N_{\text{head}}$, which for fixed d , m , and P does not depend on backbone width or depth. The primary held-out comparison uses the probability-only readout and a biased $\text{Lin}(16 \rightarrow 8) - \tanh - \text{Lin}(8 \rightarrow 1)$ head, giving $12 + 145 = 157$ trainable parameters; the separate validation/backbone suites use a 20-coordinate bias-free head and total 180. Adjacent RY blocks across repeated layers can fuse exactly, so stored angles, an equivalent fused parameterization, and an observed local Jacobian rank are distinct quantities (Appendix A.4). These are post-bottleneck parameter counts, not end-to-end computational-efficiency claims: backbone cost and simulator/runtime cost are reported separately. Appendix B.11 gives the architecture and decomposition of the central configurations.

Simulator Training, Classical Inference. Training and evaluation share one feature map through two implementations. The reported training runs execute q_θ on a PennyLane statevector simulator, whose exact reverse-mode gradients compose with the autograd gradients of the head. The same parameterization is also differentiable in native PyTorch; Appendix B.6 verifies agreement of both features and angle gradients and reports their runtime. For evaluation, we assemble $U(\theta)$ as the same ordered gate product and compute $|U(\theta)\psi(z)|^2$ in batched complex-valued PyTorch, with no per-sample simulator calls or sampling. The two inference paths agree to 1.118×10^{-7} . Thus, the circuit specifies the architecture but neither simulator training nor quantum hardware is required to realize the learned model.




Figure 2: Learned decision surfaces on MNLI-derived two-dimensional PCA bottlenecks with controlled nonlinear labels.

4 EXPERIMENTS

Our experiments test a deliberately scoped hypothesis: whether the coupled coefficient family induced by SQUARE is useful when labels depend on interactions over fixed LM bottleneck representations. The controlled labels are therefore a mechanism stress test, not evidence of broad semantic NLP superiority; original-label and reranking results are reported separately to delimit that scope. We compare SQUARE with (i) mechanism-matched classical interaction models, including normalized quadratic, bilinear, factorization, Fourier, kernel, non-parametric, graph-based, and manifold methods; (ii) PEFT-inspired bottleneck transformations and MLP heads; and (iii) quantum-enhanced baselines QAA and QPA where applicable. Candidate configurations are selected using validation data only, and results are compared within each protocol. By holding the upstream representation fixed and using validation-only model selection, these protocols isolate differences in post-bottleneck parameterization rather than differences in backbone adaptation or representation learning. Unless otherwise stated, all methods operate on the same frozen BERT bottleneck; for trainable adapter models, only post-bottleneck parameters are optimized. Throughout the paper, *SQUARE* denotes the depth-1 *RYRZ*-Ring-*RY* circuit over a $d=16$ bottleneck amplitude-encoded on $n=4$ qubits; protocol-specific readouts and lightweight heads are stated explicitly and account for the different parameter totals summarized in Appendix B.11. Additional frozen-backbone results with OPT-350M and GPT-2, as well as larger OpenLLaMA-3B and Mistral-7B backbones, are reported in Appendix B.5. Results are averaged over three random seeds unless a table specifies otherwise; dataset construction, splits, metrics, and hyperparameters are detailed in Appendix C. The main evidence is the disjoint same-pipeline comparison of circuit-induced and classical quadratic parameterizations in Section 4.2; controlled boundary, original-label, backbone, and reranking results are complementary diagnostics reported with their protocol-specific scope.

4.1 DIAGNOSTIC NONLINEAR DECISION BOUNDARY ANALYSIS

We use MNLI inputs only to obtain frozen BERT representations and discard the original MNLI labels. The frozen representations are projected onto two principal components using a fixed PCA projection fitted on the training split, yielding a shared bottleneck $z = (z_1, z_2)$ for all methods. Binary labels are generated as $y = \mathbf{1}\{f(z_1, z_2) > \tau\}$, where f contains a cross-coordinate interaction term and τ balances the training labels. All methods receive the same PCA features and train only their adapter and task head; parameter counts include trainable adapter and task-head parameters only.

Table 1: Validation performance on the MNLI-derived two-dimensional PCA boundary task.

Method	Params	Acc.	F1	AUC
BitFit	33	0.6502	0.6463	0.6641
LoRA _{r=4}	104	0.6383	0.6283	0.6536
LoRA _{r=8}	200	0.6444	0.6378	0.6576
Prefix	289	0.6595	0.6562	0.6734
MLP	776	0.6869	0.6707	0.7217
SQUARE (Ours)	180	0.7416	0.7536	0.8259

Fig. 2 visualizes the learned decision surfaces over the shared PCA bottleneck. BitFit and LoRA produce relatively smooth boundaries and miss several curved regions of the controlled label structure. Prefix and MLP yield more flexible surfaces, but still show visible mismatch with the imposed nonlinear boundary. In contrast, SQUARE more closely follows the interaction-dependent regions, consistent with its measured feature map providing cross-coordinate features to the task head. The black contour indicates the learned $p(y = 1 | z) = 0.5$ boundary.

Table 2: Controlled interaction recovery on checkerboard and radial-ring tasks. Boundary is the full-supervision mean over both tasks; reduced-supervision results report mean test AUC $\pm$ standard deviation over six seeds. Full results are in Appendix B.1.

Method	Params	Boundary	10%	25%	50%	100%
Classical Fourier	210	0.980	0.736 ± 0.125	0.830 ± 0.160	0.879 ± 0.156	0.981 ± 0.020
Explicit polynomial	386	0.975	0.688 ± 0.049	0.851 ± 0.083	0.820 ± 0.167	0.969 ± 0.019
MLP	961	0.598	0.515 ± 0.026	0.599 ± 0.027	0.563 ± 0.092	0.616 ± 0.122
SQUARE (Ours)	281	0.992	0.823 ± 0.098	0.911 ± 0.052	0.948 ± 0.026	0.979 ± 0.016

Table 3: **Core held-out evidence.** Gap is SQUARE minus the comparator in eight-task average test accuracy. Complete scores, parameter counts, and uncertainty summaries are in Appendix B.12.

Comparator	Gap	Primary contrast
Frozen circuit	+0.141	Trained vs. fixed mixing
Head only	+0.115	Measured vs. no measured map
MLP	+0.075	Interaction-feature architecture
Givens-12	+0.029	Matched-angle mixing family
Norm. quadratic	+0.021	Coupled vs. affine quadratic score
SQUARE avg. test accuracy: 0.7565		

SQUARE achieves the best Accuracy, F1, and AUC with 180 trainable parameters (AUC 0.8259 vs. 0.7217 for MLP and 0.6734 for Prefix), indicating better recovery of this imposed interaction rule under the evaluated compact budget. Because the boundary pipeline includes a learned nonlinear projection and serves primarily as a visualization, it is not used to establish the main coefficient-structure claim; that claim is tested by the disjoint same-pipeline controls in Section 4.2.

Boundary-Specific Comparison with Explicit Nonlinear Maps. A natural question is whether this gap reflects the omission of explicit interaction features. We therefore evaluate two controlled geometries (checkerboard and radial ring) under identical splits, six seeds, and validation-only selection (Table 2; per-geometry values in Appendix B.1). SQUARE reaches an average test AUC of 0.992, while classical Fourier (0.980) and explicit polynomial (0.975) maps are close behind and the evaluated GELU MLP reaches 0.598. We treat the MLP result as specific to the stated optimization protocol, not as evidence of representational inability; the diagnostic mainly confirms the value of explicit interaction features. Because the checkerboard rule lies outside the degree-two family, this experiment tests composition by the nonlinear head rather than membership of the target in SQUARE’s feature class. Two mechanism controls govern the interpretation (a broader approximator suite is in Appendix B.4): freezing the circuit at random initialization changes boundary AUC by at most 0.022 (Appendix B.10), whereas on the disjoint held-out GLUE-derived suite it reduces mean accuracy from 0.7565 to 0.6155 (Appendix B.12). Thus, structured random quadratic features can suffice when the head also receives z , while learning the circuit angles is important in the pure measured-feature path; Appendix A.4 gives the random-feature interpretation.

4.2 GLUE-DERIVED CONTROLLED INTERACTION CLASSIFICATION: CIRCUIT-INDUCED QUADRATIC BIAS VS. CLASSICAL PARAMETERIZATIONS

Controlled Interaction Protocol. We use inputs from eight GLUE datasets as distinct frozen-representation distributions while replacing their original semantic labels with one prespecified interaction-rich rule over training-fitted PCA bottlenecks. The benchmark therefore evaluates recovery of the same controlled mechanism across eight realistic language-input distributions rather than eight independent natural-language targets. For the primary comparison, we construct disjoint train, validation, and test subsets for every task. The feature scaler, PCA projection, and median label threshold are fitted using training data only, checkpoints are selected by validation AUC, and test sets are evaluated once. All methods receive the same frozen bottleneck features and are evaluated over five shared seeds.

Matched Quadratic Parameterizations. The experiment asks whether SQUARE benefits merely from normalized quadratic lifting or from the particular coefficient constraints induced by its circuit. The head-only control removes the measured feature map, whereas the frozen-circuit control retains fixed quadratic features without learning the circuit angles. The normalized-quadratic score provides a flexible explicit second-order predictor. Givens-12 uses the same 12 learned mixing parameters as SQUARE, followed by squared features and the same nonlinear head, making it the

closest parameter- and mechanism-matched comparison evaluated here. This comparison isolates the implemented 12-rotation schedule, not all structured classical mixing families: a sparse plane-rotation product and a parameter-shared tensor-product circuit can differ in coordinate connectivity despite equal parameter counts. Table 3 summarizes the attribution tests; complete absolute scores, parameter counts, and taskwise interval summaries are reported in Appendix B.12.

Held-Out Results. SQUARE obtains the highest average test accuracy among the evaluated same-pipeline models (Table 3). The head-only and frozen-circuit comparisons show that neither the downstream head nor fixed quadratic lifting alone explains the result. The cleanest structural comparison is Givens-12: despite using the same number of learned mixing parameters, squared features, and nonlinear head, it trails SQUARE by 0.029 average accuracy. SQUARE also exceeds the normalized-quadratic score by 0.021, although this comparison additionally differs in head composition because the latter is an affine scalar predictor.

Together, these comparisons support a focused conclusion: under this controlled held-out protocol, the jointly constrained unitary-measurement parameterization provides a useful inductive bias within the classical normalized-quadratic family. The result does not establish universal superiority over quadratic models or quantum computational advantage. The topology diagnostic in Appendix B.13 further shows that the prespecified $RYRZ$ -ring circuit is the strongest observed configuration on three held-out distributions, while the corresponding RY -ring variant is weaker than its non-entangling counterpart. We therefore interpret performance as a property of the jointly learned rotation-topology design rather than of entanglement in isolation. Compact-budget factorization results and complete protocol details are reported in Appendices B.2 and B.12.

Why the Constraint Matters. An unrestricted quadratic predictor assigns its coefficients independently, whereas SQUARE generates a collection of low-rank positive-semidefinite forms from one shared unitary and a common measurement basis. The circuit angles therefore change many interaction coefficients jointly rather than estimating every pair in isolation. The held-out ordering is consistent with—but does not by itself prove—a finite-sample regularization effect: SQUARE improves on the affine normalized-quadratic score and on the evaluated Givens-12 construction. The latter is the cleaner matched-head comparison; the former also changes head composition. This is the central empirical claim of the paper, limited to the implemented controls and controlled target family. We do not infer a generalization theorem or superiority over untested Householder, butterfly, Cayley, or dense-base orthogonal parameterizations.

Robustness and Deployment Scope. The same qualitative SQUARE-MLP ordering appears when the controlled-label protocol is rebuilt over OPT-350M, GPT-2, OpenLLaMA-3B, and Mistral-7B representations, with within-protocol gains of 0.0334–0.0662 (Appendix B.5). These experiments retrain the adapter for each representation and therefore test robustness across frozen feature geometries rather than zero-shot transfer. Once training is complete, the learned unitary can be materialized as the identical batched PyTorch map described in Section 3.3; deployment consequently preserves the learned coefficient structure without simulator calls or quantum hardware.

Original-Label GLUE Performance. On the original, unmodified labels of SST-2, RTE, MRPC, and QNLI (Table 9, Appendix B.2), SQUARE scores 0.686 with 49 parameters, versus 0.686 with 5,041 for the MLP, 0.673 with 445 for the explicit quadratic head, and 0.755 for encoder-adapted LoRA with 221,953. Original-label GLUE therefore supports trainable-parameter compactness rather than an accuracy advantage; the strong gains are tied to the controlled interaction-label protocols and should not be generalized to natural-label classification.

5 CONCLUSION

We introduced SQUARE as a circuit-induced parameterization of normalized quadratic features over frozen LM bottlenecks. A shared unitary jointly constrains its PSD probability features, providing a compact coefficient-sharing structure for learning second-order interactions. Controlled experiments show improvements over frozen mixing, the evaluated parameter-matched Givens construction, and an affine normalized-quadratic score, with consistent qualitative behavior across multiple frozen LM backbones. The learned map can also be realized exactly in batched PyTorch without quantum hardware. These results position SQUARE as a structured parameterization within the classical normalized-quadratic family, rather than as a uniquely quantum function class or a source

of computational advantage. The current evidence is limited to low-dimensional controlled interaction settings and does not establish broad gains on natural-label NLP tasks. Broader validation under natural supervision, higher-dimensional bottlenecks, coordinate-permuted protocols, and additional structured parameterizations is therefore an important direction for future work.

AI USE STATEMENT

Generative AI tools were used during manuscript preparation for language refinement, proofreading, and improving the clarity and organization of the presentation. The authors independently reviewed and verified all scientific claims, mathematical derivations, experimental designs, implementations, reported results, and references, and retain full responsibility for the content of the paper.

REPRODUCIBILITY STATEMENT

Dataset construction, data splits, controlled label-generation rules, baseline families and their search spaces, model-selection protocols, evaluation metrics, and hyperparameters are specified in Appendices C and C.8. The direct PyTorch realization of the learned SQUARE feature map is described operator-by-operator in Appendix B.6, including its numerical agreement with the PennyLane implementation. All quantum components are simulator-based, and the experimental pipeline can be reproduced without access to quantum hardware.

ETHICS STATEMENT

Because SQUARE operates on frozen language-model representations, it may inherit biases, spurious correlations, or other limitations present in the underlying backbones. Downstream use should therefore include appropriate task-specific validation, fairness and reliability checks, privacy safeguards, and human oversight where applicable.

REFERENCES

- Eric Ricardo Anschuetz. A unified theory of quantum neural network loss landscapes. In *Proc. International Conference on Learning Representations (ICLR)*, Singapore, Singapore, April 2025.
- Sahel Ashhab. Quantum state preparation protocol for encoding classical data into the amplitudes of a quantum information processing register’s wave function. *Physical Review Research*, 4:013091, February 2022.
- Yonatan Belinkov. Probing classifiers: Promises, shortcomings, and advances. *Computational Linguistics*, 48(1):207–219, March 2022.
- Alberto Bietti and Julien Mairal. On the inductive bias of neural tangent kernels. In *Proc. Advances in Neural Information Processing Systems (NeurIPS)*, Vancouver, Canada, December 2019.
- Mario Boneberg, Federico Carollo, and Igor Lesanovsky. Nonlinear classification capability of quantum neural networks due to emergent quantum metastability. *Physical Review A*, 111:062405, June 2025.
- Jannis Born, Filip Skogh, Kahn Rhrissorakrai, Filippo Utro, Nico Wagner, and Aleksandros Sobczyk. Quantum doubly stochastic transformers. In *Proc. Advances in Neural Information Processing Systems (NeurIPS)*, San Diego, CA, USA, November–December 2025.
- Grigorios G. Chrysos, Stylianos Moschoglou, Giorgos Bouritsas, Yannis Panagakis, Jiankang Deng, and Stefanos Zafeiriou. II-nets: Deep polynomial neural networks. In *Proc. IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, Seattle, WA, USA, June 2020.
- Alexander DeRieux and Walid Saad. eQMARL: Entangled quantum multi-agent reinforcement learning for distributed cooperation over quantum channels. In *Proc. International Conference on Learning Representations (ICLR)*, Singapore, Singapore, April 2025.
- Tim Dettmers, Artidoro Pagnoni, Ari Holtzman, and Luke Zettlemoyer. QLoRA: Efficient finetuning of quantized LLMs. In *Proc. Advances in Neural Information Processing Systems (NeurIPS)*, New Orleans, LA, USA, December 2023.

- Yuxuan Du, Min-Hsiu Hsieh, Tongliang Liu, Shan You, and Dacheng Tao. Learnability of quantum neural networks. *PRX Quantum*, 2(4):040337, November 2021.
- Shivam Garg, Dimitris Tsipras, Percy S Liang, and Gregory Valiant. What can transformers learn in-context? a case study of simple function classes. In *Proc. Advances in Neural Information Processing Systems (NeurIPS)*, New Orleans, LA, USA, November–December 2022.
- Xinyang Geng and Hao Liu. OpenLLaMA: An open reproduction of LLaMA. *GitHub repository*, 2023. https://github.com/openlm-research/open_llama.
- Jason Han, Nicholas S. DiBrita, Daniel Leeds, Jianqiang Li, Jason Ludmir, and Tirthak Patel. Layerwise federated learning for heterogeneous quantum clients using Quorus. In *Proc. International Conference on Learning Representations (ICLR)*, Rio de Janeiro, Brazil, April 2026.
- Vojtěch Havlíček, Antonio D Córcoles, Kristan Temme, Aram W Harrow, Abhinav Kandala, Jerry M Chow, and Jay M Gambetta. Supervised learning with quantum-enhanced feature spaces. *Nature*, 567(7747):209–212, March 2019.
- Soufiane Hayou, Nikhil Ghosh, and Bin Yu. LoRA+: Efficient low rank adaptation of large models. In *Proc. International Conference on Machine Learning (ICML)*, Vienna, Austria, July 2024.
- Junxian He, Chunting Zhou, Xuezhe Ma, Taylor Berg-Kirkpatrick, and Graham Neubig. Towards a unified view of parameter-efficient transfer learning. In *Proc. International Conference on Learning Representations (ICLR)*, Virtual, April 2022.
- John Hewitt and Percy Liang. Designing and interpreting probes with control tasks. In *Proc. Conference on Empirical Methods in Natural Language Processing (EMNLP)*, Hong Kong, China, November 2019.
- Neil Houlsby, Andrei Giurgiu, Stanislaw Jastrzebski, Bruna Morrone, Quentin de Laroussilhe, Andrea Gesmundo, Mona Attariyan, and Sylvain Gelly. Parameter-efficient transfer learning for NLP. In *Proc. International Conference on Machine Learning (ICML)*, Long Beach, California, USA, June 2019.
- Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, Weizhu Chen, et al. LoRA: Low-rank adaptation of large language models. In *Proc. International Conference on Learning Representations (ICLR)*, Virtual, April 2022.
- Hsin-Yuan Huang, Michael Broughton, Masoud Mohseni, Ryan Babbush, Sergio Boixo, Hartmut Neven, and Jarrod R McClean. Power of data in quantum machine learning. *Nature Communications*, 12(1):2631, May 2021.
- Sofiène Jerbi, Casper Gyurik, Simon C. Marshall, Hans J. Briegel, and Vedran Dunjko. Parametrized quantum policies for reinforcement learning. In *Proc. Advances in Neural Information Processing Systems (NeurIPS)*, Virtual, December 2021.
- Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al. Mistral 7B. *arXiv preprint arXiv:2310.06825*, 2023.
- Youngseok Kim, Andrew Eddins, Sajant Anand, Ken Xuan Wei, Ewout Van Den Berg, Sami Rosenblatt, Hasan Nayfeh, Yantao Wu, Michael Zaletel, Kristan Temme, et al. Evidence for the utility of quantum computing before fault tolerance. *Nature*, 618(7965):500–505, June 2023.
- Akash Kundu and Stefano Mangini. TensorRL-QAS: Reinforcement learning with tensor networks for improved quantum architecture search. In *Proc. Advances in Neural Information Processing Systems (NeurIPS)*, San Diego, CA, USA, November–December 2025.
- Brian Lester, Rami Al-Rfou, and Noah Constant. The power of scale for parameter-efficient prompt tuning. In *Proc. Conference on Empirical Methods in Natural Language Processing (EMNLP)*, Punta Cana, Dominican Republic, November 2021.

- Shiwei Li, Xiandi Luo, Haozhao Wang, Xing Tang, Ziqiang Cui, Dugang Liu, Yuhua Li, Yichen Li, Xiuqiang He, and Ruixuan Li. BoRA: Towards more expressive low-rank adaptation with block diversity. In *Proc. International Conference on Learning Representations (ICLR)*, Rio de Janeiro, Brazil, April 2026.
- Xiang Lisa Li and Percy Liang. Prefix-Tuning: optimizing continuous prompts for generation. In *Proc. Annual Meeting of the Association for Computational Linguistics (ACL)*, Virtual, August 2021.
- Chen-Yu Liu, Chao-Han Huck Yang, Hsi-Sheng Goan, and Min-Hsiu Hsieh. A quantum circuit-based compression perspective for parameter-efficient learning. In *Proc. International Conference on Learning Representations (ICLR)*, Singapore, Singapore, April 2025.
- Haokun Liu, Derek Tam, Mohammed Muqeeth, Jay Mohta, Tenghao Huang, Mohit Bansal, and Colin A Raffel. Few-shot parameter-efficient fine-tuning is better and cheaper than in-context learning. In *Proc. Advances in Neural Information Processing Systems (NeurIPS)*, New Orleans, LA, USA, November–December 2022.
- Shih-Yang Liu, Chien-Yi Wang, Hongxu Yin, Pavlo Molchanov, Yu-Chiang Frank Wang, Kwang-Ting Cheng, and Min-Hung Chen. DoRA: weight-decomposed low-rank adaptation. In *Proc. International Conference on Machine Learning (ICML)*, Vienna, Austria, July 2024.
- Yunchao Liu, Srinivasan Arunachalam, and Kristan Temme. A rigorous and robust quantum speed-up in supervised machine learning. *Nature Physics*, 17(9):1013–1017, July 2021.
- Rabeeh Karimi Mahabadi, James Henderson, and Sebastian Ruder. Compacter: efficient low-rank hypercomplex adapter layers. In *Proc. Advances in Neural Information Processing Systems (NeurIPS)*, December 2021.
- Yuning Mao, Lambert Mathias, Rui Hou, Amjad Almahairi, Hao Ma, Jiawei Han, Scott Yih, and Madian Khabza. UniPELT: A unified framework for parameter-efficient language model tuning. In *Proc. Annual Meeting of the Association for Computational Linguistics (ACL)*, Dublin, Ireland, May 2022.
- Fanxu Meng, Zhaohui Wang, and Muhan Zhang. PiSSA: Principal singular values and singular vectors adaptation of large language models. In *Proc. Advances in Neural Information Processing Systems (NeurIPS)*, Vancouver, Canada, December 2024.
- Nico Meyer, Christian Ufrecht, George Yammine, Georgios Kontes, Christopher Mutschler, and Daniel Scherer. Benchmarking quantum reinforcement learning. In *Proc. International Conference on Machine Learning (ICML)*, Vancouver, Canada, July 2025.
- Alexander Miessen, Daniel J Egger, Ivano Tavernelli, and Guglielmo Mazzola. Benchmarking digital quantum simulations above hundreds of qubits using quantum critical dynamics. *PRX Quantum*, 5(4):040320, November 2024.
- Mahdi Nikdan, Soroush Tabesh, Elvir Crnčević, and Dan Alistarh. RoSA: accurate parameter-efficient fine-tuning via robust adaptation. In *Proc. International Conference on Machine Learning (ICML)*, Vienna, Austria, July 2024.
- Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. In *Proc. Advances in Neural Information Processing Systems (NeurIPS)*, New Orleans, LA, USA, November–December 2022.
- John Preskill. Quantum computing in the NISQ era and beyond. *Quantum*, 2:79, August 2018.
- Zhen Qin, Rolf Jagerman, Kai Hui, Honglei Zhuang, Junru Wu, Le Yan, Jiaming Shen, Tianqi Liu, Jialu Liu, Donald Metzler, et al. Large language models are effective text rankers with pairwise ranking prompting. In *Proc. Annual Conference of the North American Chapter of the Association for Computational Linguistics (NAACL)*, Mexico City, Mexico, June 2024.
- Ali Rahimi and Benjamin Recht. Random features for large-scale kernel machines. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2007.

- Snehal Raj and Brian Coyle. Quic: quantum-inspired compound adapters for parameter efficient fine-tuning. *arXiv preprint arXiv:2502.06916*, 2025.
- Steffen Rendle. Factorization machines. In *Proc. IEEE International Conference on Data Mining (ICDM)*, pp. 995–1000, 2010.
- Emily Jimin Roh and Joongheon Kim. Quantum-amplitude embedded adaptation for parameter-efficient fine-tuning in large language models. In *Proc. International Conference on Information and Knowledge Management*, Seoul, Korea, November 2025.
- Clayton Sanford, Daniel J Hsu, and Matus Telgarsky. Representational strengths and limitations of transformers. In *Proc. Advances in Neural Information Processing Systems (NeurIPS)*, New Orleans, LA, USA, December 2023.
- Maria Schuld. Supervised quantum machine learning models are kernel methods. *arXiv preprint arXiv:2101.11020*, 2021.
- Maria Schuld, Ryan Sweke, and Johannes Jakob Meyer. Effect of data encoding on the expressive power of variational quantum-machine-learning models. *Physical Review A*, 103:032430, March 2021.
- Phattharaporn Singkanipa and Daniel A Lidar. Beyond unital noise in variational quantum algorithms: noise-induced barren plateaus and limit sets. *Quantum*, 9:1617, January 2025.
- Haobo Song, Hao Zhao, Soumajit Majumder, and Tao Lin. Increasing model capacity for free: A simple strategy for parameter efficient fine-tuning. In *Proc. International Conference on Learning Representations (ICLR)*, Vienna, Austria, May 2024.
- Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B Hashimoto. Alpaca: A strong, replicable instruction-following model. *Stanford Center for Research on Foundation Models*, 3(6):7, 2023.
- Slimane Thabet, Mehdi Djellabi, Igor O. Sokolov, Sachin Kasture, Louis-Paul Henry, and Loïc Henriët. Quantum positional encodings for graph neural networks. In *Proc. International Conference on Machine Learning (ICML)*, Vienna, Austria., July 2024.
- Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel Bowman. GLUE: A multi-task benchmark and analysis platform for natural language understanding. In *Proc. Conference on Empirical Methods in Natural Language Processing (EMNLP)*, Brussels, Belgium, November 2018.
- Chenglong Wang, Yang Gan, Yifu Huo, Yongyu Mu, Qiaozhi He, MuRun Yang, Bei Li, Tong Xiao, Chunliang Zhang, Tongran Liu, and JingBo Zhu. GRAM: A generative foundation reward model for reward generalization. In *Proc. International Conference on Machine Learning (ICML)*, Vancouver, Canada, July 2025a.
- Ruocheng Wang, Zhuo Xia, Ge Yan, and Junchi Yan. QuanONet: Quantum neural operator with application to differential equation. In *Proc. International Conference on Machine Learning (ICML)*, Vancouver, Canada, July 2025b.
- Shuteng Wang, Christian Theobalt, and Vladislav Golyanik. Quantum visual fields with neural amplitude encoding. In *Proc. Advances in Neural Information Processing Systems (NeurIPS)*, San Diego, CA, USA, November–December 2025c.
- Xiao Wang, Tianze Chen, Qiming Ge, Han Xia, Rong Bao, Rui Zheng, Qi Zhang, Tao Gui, and Xuan-Jing Huang. Orthogonal subspace learning for language model continual learning. In *Proc. Conference on Empirical Methods in Natural Language Processing (EMNLP)*, Singapore, Singapore, December 2023.
- Christopher K. I. Williams and Matthias Seeger. Using the nystrom method to speed up kernel machines. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2001.

- Fuyuan Xiao, Yu Zhou, and Witold Pedrycz. An adaptive quantum circuit of dempster’s rule of combination for uncertain pattern classification. In *Proc. Advances in Neural Information Processing Systems (NeurIPS)*, San Diego, CA, USA, November–December 2025.
- Xinyu Ye, Hao Xiong, Jianhao Huang, Ziang Chen, Jia Wang, and Junchi Yan. On designing general and expressive quantum graph neural networks with applications to MILP instance representation. In *Proc. International Conference on Learning Representations (ICLR)*, Singapore, Singapore, April 2025.
- Zhan Yu, Qiu hao Chen, Yuling Jiao, Yinan Li, Xiliang Lu, Xin Wang, and Jerry Zhijian Yang. Non-asymptotic approximation error bounds of parameterized quantum circuits. In *Proc. Advances in Neural Information Processing Systems (NeurIPS)*, Vancouver, Canada, December 2024.
- Elad Ben Zaken, Yoav Goldberg, and Shauli Ravfogel. Bitfit: Simple parameter-efficient fine-tuning for transformer-based masked language-models. In *Proc. Annual Meeting of the Association for Computational Linguistics (ACL)*, Dublin, Ireland, May 2022.
- Yuchen Zeng and Kangwook Lee. The expressive power of low-rank adaptation. In *Proc. International Conference on Learning Representations (ICLR)*, Vienna, Austria, May 2024.
- Kaining Zhang, Liu Liu, Min-Hsiu Hsieh, and Dacheng Tao. Escaping from the barren plateau via gaussian initializations in deep variational quantum circuits. In *Proc. Advances in Neural Information Processing Systems (NeurIPS)*, New Orleans, LA, USA, November–December 2022.
- Qingru Zhang, Minshuo Chen, Alexander Bukharin, Pengcheng He, Yu Cheng, Weizhu Chen, and Tuo Zhao. Adaptive budget allocation for parameter-efficient fine-tuning. In *Proc. International Conference on Learning Representations (ICLR)*, Kigali, Rwanda, May 2023.
- Jiaming Zhao, Wenbo Qiao, Peng Zhang, and Hui Gao. Quantum implicit neural representations. In *Proc. International Conference on Machine Learning (ICML)*, Vienna, Austria, July 2024.
- Jiacheng Zhu, Kristjan Greenewald, Kimia Nadjahi, Haitz Sáez De Ocariz Borde, Rickard Brühl Gabrielsson, Leshem Choshen, Marzyeh Ghassemi, Mikhail Yurochkin, and Justin Solomon. Asymmetry in low-rank adapters of foundation models. In *Proc. International Conference on Machine Learning (ICML)*, Vienna, Austria, July 2024.

APPENDIX

A BACKGROUND ON QUANTUM MACHINE LEARNING

This section provides a background on gate-based quantum machine learning used in SQUARE. The goal is not to give a complete introduction to quantum computing, but to make the main ingredients of our adapter self-contained for readers who may be less familiar with quantum machine learning. SQUARE relies on a standard hybrid quantum–classical workflow: a classical language-model representation is first encoded into a quantum state, transformed by a parameterized quantum circuit, and then converted back into classical features through measurement. Understanding this pipeline requires a few basic concepts, including qubits, Hilbert-space representations, amplitude encoding, trainable quantum circuits, and measurement readouts. We therefore review these components in the same order in which they appear in SQUARE, emphasizing how they relate to the measured quantum feature map used in the main paper.

A.1 QUBITS AND HILBERT-SPACE REPRESENTATIONS

A classical bit takes one of two values, 0 or 1. A qubit is the quantum analogue of a bit and is represented as a normalized vector in a two-dimensional complex Hilbert space:

$$|\psi\rangle = \alpha|0\rangle + \beta|1\rangle, \quad \alpha, \beta \in \mathbb{C}, \quad |\alpha|^2 + |\beta|^2 = 1. \quad (9)$$

Here, $|0\rangle$ and $|1\rangle$ are computational basis states, and α, β are probability amplitudes. When the qubit is measured in the computational basis, the probability of observing $|0\rangle$ is $|\alpha|^2$, and the probability of observing $|1\rangle$ is $|\beta|^2$.

For an n -qubit system, the Hilbert space has dimension 2^n . Its computational basis is

$$\{|0\rangle, \dots, |2^n - 1\rangle\},$$

or equivalently the binary basis states

$$\{|00 \dots 0\rangle, \dots, |11 \dots 1\rangle\}.$$

A general n -qubit pure state is

$$|\psi\rangle = \sum_{i=0}^{2^n-1} \alpha_i |i\rangle, \quad \sum_{i=0}^{2^n-1} |\alpha_i|^2 = 1. \quad (10)$$

This exponential state dimension is one reason quantum feature maps are attractive as compact representations. However, only limited information can be extracted through measurement, so the design of the encoding, circuit, and readout is crucial.

A.2 PARAMETERIZED QUANTUM CIRCUITS

After encoding, a quantum circuit applies a sequence of unitary transformations to the input state. A unitary transformation U satisfies

$$U^\dagger U = U U^\dagger = I,$$

so it preserves the norm of the quantum state. In QML, the unitary transformation is usually parameterized by trainable angles θ , yielding a parameterized quantum circuit (PQC), also called a variational ansatz:

$$|\varphi(z; \theta)\rangle = U_\theta |\psi(z)\rangle. \quad (11)$$

The parameters θ are analogous to neural network weights, but they appear as rotation angles inside quantum gates.

Single-qubit rotation gates are common trainable operations. For example, Pauli rotations around the y - and z -axes are

$$RY(\theta) = \begin{bmatrix} \cos(\theta/2) & -\sin(\theta/2) \\ \sin(\theta/2) & \cos(\theta/2) \end{bmatrix}, \quad RZ(\theta) = \begin{bmatrix} e^{-i\theta/2} & 0 \\ 0 & e^{i\theta/2} \end{bmatrix}. \quad (12)$$




Figure 3: Visualization of the SQUARE parameterized quantum circuit used in the main experiments. The input bottleneck representation is amplitude-encoded into an n -qubit state $|\psi(z)\rangle$. Each layer applies an $RYRZ$ rotation block, ring CNOT entanglement, and a final RY rotation block before measurement. The shown example uses $n = 4$ qubits and one circuit layer.

Multi-qubit gates such as CNOT introduce dependencies across qubits. When a circuit cannot be decomposed into independent operations on each qubit, it can create entangled states. Entanglement is important for SQUARE because it allows the effective measurement operator to couple amplitudes associated with different basis states.

In the main method, SQUARE uses a compact rotation–entanglement–rotation layer. Each layer first applies trainable RY and RZ rotations, then ring CNOT entanglement, and finally another trainable RY block. For depth L , this gives

$$U_\theta = \prod_{\ell=1}^L \left[\left(\prod_{q=1}^n RY_q(\theta_{\ell q}^{(3)}) \right) U_{\text{ring}} \left(\prod_{q=1}^n RZ_q(\theta_{\ell q}^{(2)}) RY_q(\theta_{\ell q}^{(1)}) \right) \right]. \quad (13)$$

The ring entanglement operator is

$$U_{\text{ring}} = \text{CNOT}_{n,1} \left(\prod_{q=n-1}^1 \text{CNOT}_{q,q+1} \right), \quad (14)$$

where we use one-indexed qubit notation and, exactly as in Eq. (3), products are ordered by application with the rightmost gate acting first: $\text{CNOT}_{1,2}$ is applied first, then $\text{CNOT}_{2,3}, \dots, \text{CNOT}_{n-1,n}$, and finally $\text{CNOT}_{n,1}$. This single canonical ring is the one implemented in Listing 1 and drawn in Fig. 3; for the basis input $|1000\rangle$ it produces $|0111\rangle$ (the opposite ordering would give $|1100\rangle$ and is not what the code implements). This topology connects all qubits with n CNOT gates per layer, providing a compact interaction structure compared with all-to-all entanglement. Fig. 3 visualizes the complete SQUARE circuit used in the main experiments.

A.3 DERIVATION OF MEASUREMENT-INDUCED INTERACTION FEATURES

We provide the derivation behind Eq. 8. For notational clarity, first assume $d = 2^n$. Given a nonzero bottleneck representation $z \in \mathbb{R}^d$, amplitude encoding prepares

$$|\psi(z)\rangle = \sum_{i=0}^{d-1} \alpha_i(z) |i\rangle, \quad \alpha_i(z) = \frac{z_i}{\|z\|_2}.$$

Let M_k be a Hermitian measurement operator and U_θ be the unitary implemented by the parameterized quantum circuit. The measured coordinate is

$$\mu_k(z; \theta) = \langle \psi(z) | U_\theta^\dagger M_k U_\theta | \psi(z) \rangle.$$

Define the effective measurement operator

$$A_k(\theta) = U_\theta^\dagger M_k U_\theta.$$

Because $M_k = M_k^\dagger$ and $U_\theta^\dagger U_\theta = I$, we have

$$A_k(\theta)^\dagger = \left(U_\theta^\dagger M_k U_\theta \right)^\dagger = U_\theta^\dagger M_k^\dagger U_\theta = U_\theta^\dagger M_k U_\theta = A_k(\theta),$$

so $A_k(\theta)$ is Hermitian. Substituting the amplitude-encoded state gives

$$\mu_k(z; \theta) = \sum_{i=0}^{d-1} \sum_{j=0}^{d-1} \alpha_i(z) A_{k,ij}(\theta) \alpha_j(z),$$

where the amplitudes are real-valued under the encoding used in SQUARE. Separating diagonal and off-diagonal terms yields

$$\mu_k(z; \theta) = \sum_{i=0}^{d-1} A_{k,ii}(\theta) \alpha_i(z)^2 + \sum_{i < j} (A_{k,ij}(\theta) + A_{k,ji}(\theta)) \alpha_i(z) \alpha_j(z).$$

Since $A_k(\theta)$ is Hermitian, $A_{k,ji}(\theta) = A_{k,ij}(\theta)^*$. Therefore,

$$A_{k,ij}(\theta) + A_{k,ji}(\theta) = 2\text{Re}(A_{k,ij}(\theta)),$$

and

$$\mu_k(z; \theta) = \sum_{i=0}^{d-1} A_{k,ii}(\theta) \alpha_i(z)^2 + 2 \sum_{0 \leq i < j < d} \text{Re}(A_{k,ij}(\theta)) \alpha_i(z) \alpha_j(z).$$

Using $\alpha_i(z) = z_i / \|z\|_2$, we obtain

$$\mu_k(z; \theta) = \sum_{i=0}^{d-1} A_{k,ii}(\theta) \frac{z_i^2}{\|z\|_2^2} + 2 \sum_{0 \leq i < j < d} \text{Re}(A_{k,ij}(\theta)) \frac{z_i z_j}{\|z\|_2^2}.$$

Thus, measurement after trainable quantum evolution exposes both coordinate-wise terms z_i^2 and cross-coordinate interaction terms $z_i z_j$. If d is not a power of two, SQUARE zero-pads z to dimension $B = 2^{\lceil \log_2 d \rceil}$ before normalization. The same derivation holds with d replaced by B . For padded coordinates, $z_i = 0$, so all terms involving padded dimensions vanish. Therefore, zero-padding does not change the interaction expansion over the original non-padded coordinates.

Remark A.1 (How SQUARE learns nonlinear features). *The coefficients of the interaction terms in Eq. 8 are not fixed. They are determined by*

$$A_k(\theta) = U_\theta^\dagger M_k U_\theta,$$

which changes as the circuit angles θ are optimized. Trainable rotations adjust the measurement basis and determine which amplitude products are emphasized by the downstream loss. The ring entanglement block changes the attainable coefficient family relative to product rotations. It is not required for cross-coordinate products, which can already arise when dense amplitude-coordinate rows produced by local rotations are squared; Appendix B.13 therefore treats topology as a diagnostic design choice rather than attributing all interactions to entanglement. Measurement then reads these learned cross-amplitude relations as classical coordinates $\mu_k(z; \theta)$, which form the measured feature vector $q_\theta(z)$ used by a lightweight head to model interaction-dependent components of the target.

A.4 STRUCTURAL CHARACTERIZATION AND SCALE INVARIANCE OF THE MEASURED MAP

Structural Characterization of the Coefficient Matrices. The quadratic identity itself is a direct consequence of squaring linearly transformed amplitudes, and closely related outer-product/kernel views of amplitude-encoded models are known (Schuld, 2021; Havlíček et al., 2019); the contribution we claim is therefore the specific restricted parameterization and the evidence for its usefulness, not the containment result. The following are necessary structural properties of every circuit-induced collection, not a sufficient characterization of all collections realizable by one common unitary.

Write row j of U_θ as $u_j = a_j + ib_j$ with $a_j, b_j \in \mathbb{R}^B$. For real inputs, $p_j(z) = ((a_j^\top \alpha)^2 + (b_j^\top \alpha)^2)$ with $\alpha = z/\|z\|_2$, so the real coefficient matrix of the j -th probability feature is

$$Q_j = a_j a_j^\top + b_j b_j^\top, \quad Q_j \succeq 0, \quad \text{rank}(Q_j) \leq 2, \quad \sum_{j=0}^{B-1} Q_j = I, \quad (15)$$

where the last identity follows from unitarity ($\sum_j u_j u_j^\dagger = I$). SQUARE is thus a jointly constrained collection of B positive-semidefinite, rank-at-most-two normalized quadratic probability features whose coefficient matrices resolve the identity, followed by a task head; the Pauli- Z features are signed sums of the Q_j and add no new information. Joint compatibility of all rows with one unitary imposes further constraints beyond PSD, rank, trace, and resolution of identity. This characterization identifies the natural classical comparison point—structured linear projections followed by squared magnitudes—evaluated in Section 4.2. Two distinctions should be kept explicit. First, potentially nonzero coefficients on $O(d^2)$ coordinate pairs are not $O(d^2)$ independently accessible features: the readout has centered rank at most 15 at $d = B = 16$. Second, “normalized quadratic” refers to $p_\theta(z) = z^\top Q z / (z^\top z)$; it is homogeneous of degree zero in the unnormalized coordinates, and composition with a nonlinear task head is not itself a quadratic predictor.

Scale Invariance and the Input Path. Because $\alpha(cz) = \text{sign}(c) \alpha(z)$ and every coordinate of q_θ is quadratic in α , we have $q_\theta(cz) = q_\theta(z)$ for every real $c \neq 0$. Any predictor of the form $g_\phi(q_\theta(z))$ is consequently invariant to input scaling and global sign and cannot distinguish two points on the same ray with different radii; in particular it cannot exactly represent a rule whose label depends on $\|z\|$. Section 3.1 therefore admits pure and residual paths, and we state which is used in each protocol. The GLUE-derived controlled tasks and additional-backbone experiments use the pure path on a $d=16$ PCA bottleneck; the Alpaca rebuild reports both variants. The boundary experiments instead map PCA-2 coordinates x to $v = \tanh(Wx + b) \in \mathbb{R}^{16}$, amplitude-encode v , and feed the affine head $[v; \sqrt{p_\theta(v)}] \in \mathbb{R}^{32}$. Although $p_\theta(v)$ is normalized quadratic in v , $\sqrt{p_\theta(v)} = |U_\theta \alpha(v)|$ is a magnitude readout and v is nonlinear in x ; the end-to-end boundary model is therefore not exactly quadratic in x . The learned projection can itself encode radial information into direction, so these experiments do not establish that concatenating v is mathematically necessary. Their component controls are interpreted only within this broader boundary architecture.

What Subset of Quadratic Models the Circuit Induces. Eq. (15) can be sharpened into a quantitative description of the family $\{Q_j(\theta)\}$. Because each row u_j of a unitary has unit norm, $\text{tr } Q_j = 1$: every probability feature is PSD with rank at most two, and the B forms resolve the identity. If the circuit is real, then $b_j = 0$ and the model is a restricted orthogonal-projection-square family. With phases, the default circuit belongs instead to a restricted complex-unitary magnitude-square family, and the RZ block can produce rank-two real coefficient matrices; the complex family is not a subfamily of the real orthogonal-square family. Smoothness bounds local image dimension by the angle count but does not establish a single global manifold. At sampled generic parameter points, the Jacobian rank of $\theta \mapsto (Q_j)_j$ was 12, 20, and 28 for $L = 1, 2, 3$ at $n = 4$, and 8 for the real $L = 1$ circuit. We report these as observed local image dimensions, not globally identified degrees of freedom. Table 4 separately reports stored scalars and effective coefficient-family constraints. The ring does not make Q_j sparse in the coordinate basis (each row of U_θ is generically dense), but it does tie the family to the coordinate ordering of the bottleneck: the attainable set is not closed under arbitrary input permutations, so coordinate ordering remains part of the parameterization.

Table 4: Structural comparison at $d = 16$. Stored scalars are implementation parameters before a head; the last column gives an effective-family bound or structural constraint.

Model	Coefficient-matrix structure	Stored	Effective family
Full explicit quadratic	any symmetric A	136	≤ 136
Low-rank bilinear (rank r)	$A = \text{Sym}(UV^\top)$	$32r$	$\text{rank} \leq 2r; \dim. \leq \min(136, 32r)$
Factorization machine (rank k)	off-diagonal coefficients from $VV^\top$	$16k$	Gram-constrained off diagonal
Learned mixing + squares	$A = W \text{diag}(c) W^\top$	$256+16$	≤ 136
Learned orthogonal mixing + squares	spectral form, $W \in O(16)$	$120+16$	≤ 136
SQUARE, real ($L = 1$)	restricted orthogonal squares	$8+16$	sampled local rank ≤ 8 before c
SQUARE, complex (L layers)	restricted unitary magnitudes	$12L+16$ stored	$4+8L$ after exact adjacent- RY fusion; sampled local rank no larger

The implementation stores $3Ln$ rotation angles. For $L > 1$, the terminal RY block of one layer and the initial RY block of the next are adjacent and fuse exactly via $RY(a)RY(b) = RY(a+b)$. The same unitary therefore admits an equivalent parameterization with at most $3Ln - n(L-1) =$

$n(2L + 1)$ angles, giving $4 + 8L$ at $n = 4$. Stored angles, this analytic gate-fusion bound, and observed local Jacobian rank are distinct quantities; the numerical ranks 12, 20, and 28 match the bound at the sampled generic points but are not asserted as a global-dimension theorem.

The Random Circuit as a Structured Random-Feature Map. The untrained-circuit result of Appendix B.10 (trained-minus-untrained AUC within $[-0.017, +0.022]$ on the residual-path boundary suite) invites a random-feature reading, which the structure above makes precise. For a Haar-random unitary U and real unit vectors α, α' , $\mathbb{E}_U[Q_j] = I/B$ and $\mathbb{E}_U[\sum_j p_j(z)p_j(z')] = (1 + (\alpha^\top \alpha')^2)/(B + 1)$, so the expected linear kernel of the probability features is an affine function of squared cosine similarity—a normalized degree-two polynomial kernel—and a random circuit is a B -feature Monte Carlo approximation of it. For the default ring circuit with angles drawn uniformly from $[0, 2\pi)$, a numerical study (4,000 draws, 50 random pairs) finds $\mathbb{E}_\theta[Q_j]$ diagonal to within 0.002, with diagonal entries 0.061–0.065 (Haar: $1/16 = 0.0625$). Its expected kernel lies within 0.008 of the Haar value but retains orientation dependence relative to the coordinate axes. The random SQUARE circuit is therefore an anisotropic, coordinate-aligned quadratic feature map. This interpretation is consistent with the residual-path boundary result, while the disjoint held-out pure-path suite shows that training the circuit improves mean accuracy from 0.6155 to 0.7565 (Appendix B.12). On that same protocol, trained SQUARE also exceeds the normalized-quadratic and parameter-matched Givens-12 controls, indicating that the learned circuit constraint contributes beyond quadratic lifting alone under this evaluation.

A.5 HYBRID QUANTUM-CLASSICAL TRAINING DETAILS

Training follows a hybrid quantum-classical optimization procedure. The classical head parameters ϕ are updated by standard backpropagation, while the quantum parameters θ are trainable rotation angles in the PQC. **Differentiation method actually used.** In all reported experiments the circuit is executed on a statevector simulator and $\partial\mu_k/\partial\theta_r$ is obtained by reverse-mode automatic differentiation *through the simulation*: the GLUE-derived, reranking, and additional-backbone experiments use PennyLane default.qubit with interface="torch" and diff_method="backprop" (not the "best" default and not parameter shift), and the decision-boundary control suite uses a native PyTorch statevector implementation of the same gates, differentiated by PyTorch autograd. These gradients are exact for the simulated circuit; in a numerical check over 20 random draws, backpropagation and parameter shift agreed to a maximum absolute difference of 1.1×10^{-15} , and no gradient entry was zero. For Pauli rotation gates, if a measured coordinate $\mu_k(z; \theta)$ depends on a rotation parameter θ_r , the parameter-shift rule gives the identical gradient

$$\frac{\partial\mu_k(z; \theta)}{\partial\theta_r} = \frac{1}{2} \left[\mu_k\left(z; \theta + \frac{\pi}{2}e_r\right) - \mu_k\left(z; \theta - \frac{\pi}{2}e_r\right) \right], \quad (16)$$

with all other parameters fixed. This rule is what execution on quantum hardware would use in place of simulator backprop; in either case the circuit gradients are propagated through the classical head by the chain rule and combined with standard backpropagation to optimize the downstream loss $\mathcal{L}$. Thus, the measured feature vector $q_\theta(z)$ and the task head are optimized end-to-end while the LM backbone remains frozen.

A.6 PENNYLANE-BASED SQUARE CIRCUIT IMPLEMENTATION

Listing 1 shows a compact PennyLane implementation of SQUARE.

Normalization and the zero vector. The mathematical feature map and the PennyLane path use $\alpha(z) = z/\|z\|_2$ for $z \neq 0$; the all-zero vector is outside this map and did not occur in the data. The separate native-PyTorch timing implementation used $z/(\|z\|_2 + 10^{-8})$ for numerical stabilization. It is therefore only an approximation to the normalized state map (feature discrepancy 4.8×10^{-9} in the reported check), and exact normalization identities refer to the mathematical/PennyLane path, not to that timing-only approximation.

The circuit receives a compact bottleneck vector z , amplitude-encodes it into an n -qubit state, applies the $RYRZ$ -Ring- RY parameterized quantum circuit, and returns the measured SQUARE feature vector. The trainable tensor `theta` has shape $(L, n, 3)$, where L is the circuit depth and n is the number of qubits. For each layer and qubit, the three parameters correspond to the first RY rotation,

the RZ rotation, and the final RY rotation after ring entanglement. The ring block applies CNOT gates in the order $1 \rightarrow 2, \dots, n-1 \rightarrow n, n \rightarrow 1$, using n CNOT gates per layer. After the circuit evolution, SQUARE concatenates computational-basis probabilities and local Pauli- Z expectations, matching the measured feature map $q_\theta(z)$ used by the downstream task head. The QNode is declared with `interface="torch"` and `diff_method="backprop"` and returns torch tensors, so the listing is the actual differentiable training path (gradients reach `theta` through the `statevector`) rather than an illustrative forward pass.

```

1 import pennylane as qml
2 import torch
3
4 def square_layer(theta_layer, wires):
5     """One RYZ-Ring-RY SQUARE layer."""
6     n_qubits = len(wires)
7
8     # Local RYZ rotation block
9     for q, w in enumerate(wires):
10         qml.RY(theta_layer[q, 0], wires=w)
11         qml.RZ(theta_layer[q, 1], wires=w)
12
13     # Ring CNOT entanglement
14     for q in range(n_qubits - 1):
15         qml.CNOT(wires=[wires[q], wires[q + 1]])
16     qml.CNOT(wires=[wires[-1], wires[0]])
17
18     # Final local RY rotation block
19     for q, w in enumerate(wires):
20         qml.RY(theta_layer[q, 2], wires=w)
21
22
23 def make_square_qnode(n_qubits, depth):
24     """Construct a SQUARE QNode with probability and Pauli-Z readout."""
25     wires = list(range(n_qubits))
26     dev = qml.device("default.qubit", wires=n_qubits)
27
28     # Differentiable training path used in all experiments:
29     # exact reverse-mode gradients through the statevector simulation.
30     @qml.qnode(dev, interface="torch", diff_method="backprop")
31     def square_circuit(z, theta):
32         # Amplitude encoding into 2^n-dimensional Hilbert space
33         qml.AmplitudeEmbedding(
34             features=z,
35             wires=wires,
36             normalize=True,
37             pad_with=0.0,
38         )
39
40         # Parameterized quantum circuit
41         for ell in range(depth):
42             square_layer(theta[ell], wires)
43
44         # Measured SQUARE feature map q_theta(z)
45         probs = qml.probs(wires=wires)
46         z_exps = [qml.expval(qml.PauliZ(w)) for w in wires]
47         return probs, z_exps
48
49     return square_circuit
50
51
52 def square_features(z, theta):
53     """Return concatenated SQUARE features [basis probabilities; Z expectations]."""
54     depth, n_qubits, _ = theta.shape
55     qnode = make_square_qnode(n_qubits=n_qubits, depth=depth)
56
57     probs, z_exps = qnode(z, theta) # torch tensors; gradient path to theta is
58     # preserved
59     return torch.cat([probs, torch.stack(z_exps)])

```

Listing 1: Compact PennyLane implementation of SQUARE.

A.7 TRENDS IN RECENT QUANTUM-ENHANCED LEARNING STUDIES

Table 6 summarizes recent quantum-enhanced learning studies from major machine learning venues along three experimental dimensions: whether the method uses a hybrid quantum–classical architecture, how classical data are encoded into quantum states or circuits, and whether evaluation is

Table 5: Quantum-enhanced adaptation methods for LMs.

Characteristic	QAA	QPA	SQUARE (Ours)
Purpose	Adapt states	Generate weights	Relation modeling
Data encoding	Amplitude	None	Amplitude
Hybrid QC	✓	✓	✓
Quantum simulator	✓	✓	✓
Experiment	NLG	Perplexity eval.	Controlled / Reranking

conducted on a simulator. The table shows that recent QML systems are predominantly hybrid rather than standalone quantum models. Across reinforcement learning, computer vision, graph learning, federated learning, and general ML tasks, quantum circuits are typically used as compact feature processors, trainable transformation modules, or structured components inside larger classical pipelines. A second trend is that classical-to-quantum encoding is a central design choice. The surveyed studies use a range of encodings, including amplitude, angle, feature-map, positional, re-uploading, block, and tensor-network-inspired representations. This variation suggests that QML performance depends not only on adding a quantum circuit, but also on how classical information is embedded before circuit evolution and measurement. SQUARE follows this design pattern by amplitude-encoding compact frozen LM bottleneck features and using the PQC readout to expose nonlinear interaction features. A third trend is the continued reliance on simulator-based evaluation. All studies in Table 6 explicitly use or discuss quantum simulators, reflecting the current difficulty of evaluating learning pipelines directly on large-scale, fault-tolerant quantum hardware. SQUARE is aligned with this practice: our experiments evaluate the representational utility of measured quantum features in simulation, not near-term hardware advantage. This is also why the paper separately reports simulated noise sensitivity while avoiding claims about real-device robustness.

Finally, Table 6 highlights that QML applications have expanded beyond traditional quantum benchmarks into RL, CV, graph learning, FL, and now NLP. SQUARE contributes to this direction by placing a compact PQC at the representation-interaction level of frozen language models. Unlike quantum parameter generation or generic activation adaptation, SQUARE directly operates on frozen semantic bottleneck features and measures relation-sensitive readouts for downstream prediction.

Table 6: Experimental settings in recent quantum-enhanced learning studies. A checkmark indicates that the corresponding setting is explicitly used or discussed. Recent QML studies commonly adopt hybrid quantum-classical architectures, task-specific classical-to-quantum encodings, and simulator-based evaluation.

Work	Conf	Category	Hybrid Q-C	Encoding	Simulator
TensorRL-QAS (Kundu & Mangini, 2025)	NeurIPS	RL	✓	Matrix Product State	✓
QVF (Wang et al., 2025c)	NeurIPS	CV	✓	Amplitude	✓
AQC-DRC (Xiao et al., 2025)	NeurIPS	ML	✓	Amplitude	✓
QDSFormer (Born et al., 2025)	NeurIPS	CV	✓	Angle	✓
QuanONet (Wang et al., 2025b)	ICML	ML	✓	Feature Map	✓
QRL (Meyer et al., 2025)	ICML	RL	✓	Angle/Re-uploading	✓
QPE-GNN (Thabet et al., 2024)	ICML	ML	✓	Positional	✓
Quorus (Han et al., 2026)	ICLR	FL	✓	Amplitude	✓
QNN loss landscapes (Anschuetz, 2025)	ICLR	ML	✓	Block	✓
eQMARL (DeRieux & Saad, 2025)	ICLR	RL	✓	Angle	✓
SQUARE (Ours)	–	NLP	✓	Amplitude	✓

B ADDITIONAL RESULTS

B.1 DECISION-BOUNDARY EVALUATION DETAILS

This appendix provides the per-geometry boundary-specific comparison summarized in main-text Table 2 (Table 7); the per-method Accuracy/F1/AUC breakdown on the two-dimensional PCA boundary task is reported in main-text Table 1.

Table 7: Boundary-specific controlled interaction recovery under an identical validation-selection protocol. Values are mean test AUC $\pm$ sample standard deviation over six random seeds.

Method	Params	Checkerboard	Radial ring	Average
Classical Fourier	210	0.977 ± 0.033	0.983 ± 0.004	0.980
Explicit polynomial	386	0.973 ± 0.001	0.977 ± 0.003	0.975
MLP (GELU)	961	0.487 ± 0.009	0.710 ± 0.041	0.598
Adapter transformation	140	0.505 ± 0.071	0.638 ± 0.012	0.571
LoRA transformation	77	0.567 ± 0.025	0.517 ± 0.009	0.542
SQUARE (Ours)	281	0.987 ± 0.009	0.997 ± 0.002	0.992

B.2 COMPACT-BUDGET AND ORIGINAL-LABEL GLUE COMPARISONS

This section separates two complementary questions. First, under controlled interaction labels, can SQUARE retain competitive accuracy when all methods are restricted to a genuinely compact trainable budget? Second, when the original GLUE labels are restored, how much predictive utility remains when the language model and bottleneck are frozen? The first comparison tests the parameterization of interactions; the second tests whether the resulting adapter remains useful outside the constructed-label setting.

Table 8: Compact-budget comparison on four GLUE-derived controlled-label tasks. Hyperparameters are selected using validation data only, with a target budget of at most $1.5\times$ the smallest SQUARE configuration. Values are mean $\pm$ s.d. over the matched runs. *The smallest prespecified configuration evaluated for this method exceeds the target; these rows are retained as informative higher-budget references. In particular, the reported MLP result should not be interpreted as a lower bound on the size of an MLP.

Method	Params	SST-2	RTE	MRPC	QNLI	Avg.
MLP*	577	0.964 ± 0.002	0.976 ± 0.002	0.958 ± 0.002	0.956 ± 0.003	0.964
Explicit norm. quadratic*	409	0.799 ± 0.006	0.859 ± 0.002	0.854 ± 0.004	0.827 ± 0.005	0.835
Full bilinear*	273	0.874 ± 0.027	0.918 ± 0.019	0.902 ± 0.011	0.908 ± 0.018	0.901
Low-rank bilinear	81	0.971 ± 0.005	0.967 ± 0.005	0.942 ± 0.011	0.962 ± 0.009	0.961
Factorization machine	71	0.973 ± 0.002	0.972 ± 0.002	0.965 ± 0.005	0.963 ± 0.003	0.968
SQUARE (Ours)	68	0.967 ± 0.008	0.980 ± 0.005	0.972 ± 0.002	0.958 ± 0.009	0.969

Within the target budget, SQUARE attains the highest macro-average (0.969) with the fewest trainable parameters (68), while the factorization machine is within 0.001 using 71 parameters and the low-rank bilinear model reaches 0.961 using 81. SQUARE also gives the strongest observed results on RTE and MRPC. Thus, the evidence is not that quadratic interactions require a quantum circuit; rather, SQUARE realizes a competitive second-order inductive bias with a particularly small parameterization. The close factorization-machine result further supports our central interpretation that the structure imposed on interaction coefficients, rather than parameter count alone, is the relevant design choice.

With the original labels, SQUARE matches the frozen-bottleneck MLP average (0.686) using 49 rather than 5,041 trainable parameters—approximately $103\times$ fewer—and slightly improves SST-2 and MRPC within that frozen-bottleneck comparison. Encoder-adapted LoRA remains more accurate because it updates the language-model representation and uses over 220K trainable parameters, so it answers a different adaptation question. These results do not establish an original-label accuracy advantage; they show that the compact measured feature map preserves the utility of a much larger frozen-bottleneck head. Together with Table 8, this supports SQUARE as a parameter-efficient interaction adapter rather than as a replacement for full encoder adaptation.

Table 9: Performance on the original GLUE labels. SST-2, RTE, and QNLI use accuracy, whereas MRPC uses F1; Avg. is their unweighted mean and is not directly comparable to the controlled-label results. Encoder-adapted LoRA updates the backbone, whereas the remaining methods operate on the same frozen bottleneck.

Protocol	Method	Params	SST-2	RTE	MRPC	QNLI	Avg.
Encoder-adapted	LoRA	221,953	0.870	0.581	0.832	0.736	0.755
Frozen bottleneck	MLP	5,041	0.822	0.540	0.811	0.571	0.686
Frozen bottleneck	SQUARE (Ours)	49	0.826	0.527	0.815	0.578	0.686
Frozen bottleneck	Explicit quadratic	445	0.824	0.475	0.813	0.580	0.673

B.3 POST-TRAINING SIMULATED NOISE SENSITIVITY




Figure 4: Post-training simulated quantum noise sensitivity of SQUARE with the BERT frozen bottleneck in MNLI. A trained SQUARE model is evaluated under depolarizing, bit-flip, phase-flip, and amplitude-damping noise injected only during evaluation (Singkanipa & Lidar, 2025).

We additionally test whether the learned SQUARE readout remains stable when standard quantum noise channels are introduced after clean training. This evaluation isolates inference-time noise sensitivity: the model is trained once on a noiseless simulator, its parameters are fixed, and only the quantum circuit evaluation is perturbed. The purpose is to assess simulator-based sensitivity of the measured feature map, rather than to claim robustness on physical quantum hardware. We inject depolarizing, bit-flip, phase-flip, and amplitude-damping noise during evaluation and report the resulting AUC drop from the clean model.

Fig. 4 shows mild degradation across all tested channels. The largest AUC drop is 0.0103 under bit-flip noise, while depolarizing, amplitude-damping, and phase-flip noise yield maximum drops of 0.0071, 0.0079, and 0.0032, respectively. The non-monotonic trend for some channels reflects the finite validation set and simulator-level stochastic perturbations, so we interpret these results as a sensitivity diagnostic rather than a calibrated hardware-noise benchmark. SQUARE’s measured readout remains reasonably stable under the evaluated post-training noise channels.

B.4 BROAD FROZEN-BOTTLENECK APPROXIMATOR SUITE

Table 10 evaluates a broad set of kernel, non-parametric, graph-based, manifold-based, and explicit nonlinear approximators under a shared frozen-bottleneck protocol. All methods use the same data, bottleneck representations, splits, labels, and evaluation metric; each family is selected from pre-specified configurations using validation data only. Reported learned-scalar counts are descriptive and are not used to establish a cross-family parameter-efficiency ranking, because non-parametric and kernel methods do not admit a directly comparable count. SQUARE has the highest observed mean AUC, but the uncertainties of several leading methods overlap; we therefore place SQUARE within the strongest observed performance group rather than claiming a statistically established total ordering.

B.5 ADDITIONAL BACKBONE RESULTS

Table 11 consolidates the protocol-level averages before the task-wise breakdowns below. Across all four frozen backbones, SQUARE retains the same qualitative ordering relative to the corresponding

Table 10: Broad-family comparison under a shared frozen-bottleneck protocol. Results are mean test AUC $\pm$ sample standard deviation over two interaction rules and six seeds. “—” indicates that a directly comparable learned-scalar count is not reported.

Method	Reported learned scalars	Test AUC
SQUARE (Ours)	234	0.984 ± 0.014
SVM (RBF)	—	0.974 ± 0.030
Classical Fourier	204	0.961 ± 0.050
Graph-Laplacian	—	0.953 ± 0.003
Explicit polynomial	334	0.947 ± 0.030
kNN ($k = 25$)	—	0.909 ± 0.011
Random Fourier features	—	0.905 ± 0.103
Nyström	—	0.846 ± 0.146
MLP	785	0.603 ± 0.136
Factorization machine	18	0.530 ± 0.015
Adapter transformation	160	0.525 ± 0.087
Local manifold (Isomap)	—	0.517 ± 0.035
Bilinear	37	0.508 ± 0.044

Table 11: Validation-selected controlled-interaction accuracy across four frozen LM backbones. Gain denotes SQUARE minus MLP within each backbone and protocol. OPT-350M and GPT-2 use the V20 configuration, whereas OpenLLaMA-3B and Mistral-7B use H16; parameter counts therefore differ across the two groups. These results test whether the qualitative comparison persists across frozen representation geometries and are not directly comparable to the primary disjoint held-out test in Table 3.

Backbone	MLP	SQUARE	Gain	MLP params	SQUARE params
OPT-350M	0.7960	0.8294	+0.0334	776	180
GPT-2	0.7847	0.8258	+0.0411	776	180
OpenLLaMA-3B	0.7052	0.7714	+0.0662	1,633	157
Mistral-7B	0.7012	0.7481	+0.0469	1,633	157

MLP while using fewer trainable post-bottleneck parameters. Because labels and adapters are re-generated for each representation, the table is evidence of repeated within-backbone behavior rather than direct transfer between language models.




Figure 5: Learning curves on GLUE-derived controlled nonlinear interaction classification with additional frozen backbones. We report validation accuracy averaged across controlled GLUE-derived tasks for OPT-350M and GPT-2. Shaded regions denote variation across tasks. Across both frozen backbones, SQUARE shows stable optimization and reaches the strongest final validation accuracy, while MLP remains the strongest classical baseline. The gap between SQUARE and SQUARE without the PQC suggests that the measured quantum feature map contributes beyond the lightweight downstream head.

Learning Dynamics on Additional Backbones. Fig. 5 shows the validation learning curves for OPT-350M and GPT-2 on the GLUE-derived controlled interaction tasks. The results are averaged

across tasks, and the shaded regions indicate task-wise variation. Across both frozen backbones, SQUARE exhibits stable optimization and consistently improves over training. After the early training phase, SQUARE reaches the top-performing region and obtains the strongest final validation accuracy among the compared adapters.

The trend is consistent across OPT-350M and GPT-2. MLP remains a strong classical nonlinear baseline, but SQUARE reaches higher final accuracy while using a substantially smaller adapter. In contrast, QAA, QPA, and SQUARE without the PQC remain clearly below SQUARE. This suggests that the improvement is not explained merely by adding a quantum-labeled component or a lightweight head; rather, the measured quadratic feature map contributes beyond the lightweight head alone.

These learning curves complement the task-wise results in Tables 12 and 13. They show that SQUARE’s gains are not due to unstable late-epoch fluctuations, but arise from a stable training trajectory that appears across different frozen LM geometries.

Table 12: Task-wise validation accuracy on GLUE-derived controlled nonlinear interaction classification with OPT-350M. All methods use the same frozen OPT-350M bottleneck representation, and Params counts only trainable adapter parameters. Several baselines approach majority-class performance under this protocol.

Method	Quantum	Params	CoLA	SST-2	STS-B	QQP	MNLI	QNLI	RTE	WNLI	Avg.
BitFit	✗	33	0.4775	0.4825	0.4325	0.4700	0.5125	0.4600	0.5379	0.5070	0.4850
LoRA _{r=4}	✗	104	0.6000	0.6050	0.6450	0.6700	0.7225	0.7675	0.8159	0.7887	0.7018
LoRA _{r=8}	✗	200	0.6500	0.6125	0.6460	0.6700	0.7275	0.7679	0.8231	0.7928	0.7112
AdaLoRA	✗	621	0.6850	0.6025	0.6450	0.6675	0.7200	0.7675	0.8303	0.7324	0.7063
Prefix	✗	289	0.4775	0.4825	0.4325	0.4700	0.5125	0.4600	0.5379	0.5070	0.4850
MLP	✗	776	0.7775	0.8025	0.7925	0.7950	0.7825	0.7775	0.8520	0.7887	0.7960
QAA	✓	140	0.5500	0.6350	0.4325	0.4900	0.5100	0.5150	0.5379	0.4930	0.5204
QPA	✓	192	0.4775	0.4825	0.4325	0.4700	0.5125	0.4600	0.5379	0.5070	0.4850
SQUARE (w/o PQC)	✓	168	0.6800	0.5875	0.5475	0.6725	0.7250	0.7650	0.8267	0.7606	0.6956
SQUARE (Ours)	✓	180	0.8075	0.8825	0.8375	0.8500	0.8400	0.7700	0.8556	0.7924	0.8294

To evaluate whether SQUARE depends on a specific frozen encoder, we repeat the GLUE-derived controlled nonlinear interaction classification experiment with additional frozen LM backbones, OPT-350M and GPT-2. The experimental protocol is identical to the main BERT-based setting: original GLUE labels are discarded, controlled nonlinear labels are generated over frozen bottleneck representations, and only adapter parameters are trained. This isolates the effect of the adapter under different frozen representation geometries.

Tables 12 and 13 report task-wise validation accuracy. With OPT-350M, SQUARE achieves the best average accuracy, improving over the strongest classical baseline MLP from 0.7960 to 0.8294. SQUARE also improves substantially over SQUARE without the PQC, from 0.6956 to 0.8294, indicating that the measured quantum feature map remains useful beyond the BERT backbone.

With GPT-2, SQUARE again obtains the best average accuracy, improving over MLP from 0.7847 to 0.8258. The improvement over SQUARE without the PQC is also clear, from 0.7304 to 0.8258. These results show that the controlled-task performance pattern is not confined to the BERT bottleneck and persists across the evaluated OPT-350M and GPT-2 representations. Together, these results support the use of the measured feature map across the evaluated frozen-LM bottleneck geometries, while not establishing generalization to arbitrary backbones or natural-label tasks.

At the same time, the relative task-wise gains vary across backbones. This is expected because each frozen LM induces a different bottleneck geometry, and the usefulness of nonlinear interaction features depends on which task-relevant relations are preserved in that representation. Overall, the additional backbone results support the view that SQUARE acts as a compact nonlinear relation module over frozen representations, rather than as a backbone-specific adapter.

Scaling to Billion-Parameter Backbones. We further scale the controlled-interaction study to two substantially larger frozen decoder backbones, OpenLLaMA-3B (Geng & Liu, 2023) and Mistral-7B (Jiang et al., 2023), under the same experimental protocol: the backbone is kept frozen, controlled nonlinear labels are constructed over the resulting bottleneck representations, and only the

Table 13: Task-wise validation accuracy on GLUE-derived controlled nonlinear interaction classification with GPT-2. All methods use the same frozen GPT-2 bottleneck representation, and Params counts only trainable adapter parameters. Several weak baselines collapse to near-majority-class prediction on this backbone and return identical task-wise accuracies; the rows are retained for completeness.

Method	Quantum	Params	CoLA	SST-2	STS-B	QQP	MNLI	QNLI	RTE	WNLI	Avg.
BitFit	✗	33	0.4825	0.4900	0.5075	0.4425	0.4375	0.4525	0.4946	0.5070	0.4768
LoRA _{r=4}	✗	104	0.7700	0.7425	0.7800	0.6300	0.7525	0.7325	0.6029	0.7528	0.7204
LoRA _{r=8}	✗	200	0.7775	0.7475	0.7875	0.6675	0.7550	0.7325	0.6282	0.7810	0.7346
AdaLoRA	✗	621	0.7750	0.7575	0.7825	0.6375	0.7550	0.7325	0.6534	0.8028	0.7370
Prefix	✗	289	0.4850	0.4900	0.5075	0.4425	0.4375	0.4525	0.4946	0.5070	0.4771
MLP	✗	776	0.7625	0.7925	0.8300	0.6950	0.8275	0.7675	0.7978	0.8046	0.7847
QAA	✓	140	0.5875	0.6750	0.6550	0.4975	0.5700	0.5100	0.4946	0.5070	0.5621
QPA	✓	192	0.4850	0.4900	0.5075	0.4425	0.4375	0.4525	0.4946	0.5070	0.4771
SQUARE (w/o PQC)	✓	168	0.7675	0.7450	0.7900	0.6650	0.7400	0.7300	0.6173	0.7887	0.7304
SQUARE (Ours)	✓	180	0.8250	0.8500	0.8900	0.8150	0.8375	0.7750	0.8051	0.8087	0.8258

post-bottleneck adapter and task head are trained. Because these decoder-only models do not provide a dedicated [CLS] representation, we mean-pool the final hidden states to obtain the bottleneck representation. Tables 14 and 15 report the resulting task-wise validation accuracy averaged over three seeds.

Across both larger backbones, SQUARE achieves the highest macro-average accuracy among the reported methods. On OpenLLaMA-3B, SQUARE reaches an average accuracy of (0.7714), compared with (0.7052) for the substantially larger MLP head. On Mistral-7B, SQUARE similarly achieves (0.7481), compared with (0.7012) for MLP. SQUARE also consistently outperforms the evaluated Linear, BitFit, LoRA, and AdaLoRA baselines on the macro-average while using only 157 trainable parameters, substantially fewer than LoRA, AdaLoRA, and MLP. These results indicate that the effectiveness of the structured measured-quadratic feature map is preserved when the frozen representation is produced by substantially larger language models.

The task-wise results further show that the advantage is not driven by a single task. On OpenLLaMA-3B, SQUARE obtains the highest accuracy on seven of the eight evaluated tasks, with MLP outperforming it only on WNLI. On Mistral-7B, SQUARE obtains the highest accuracy on six of the eight tasks, while MLP performs better on STS-B and WNLI. The magnitude of the gain nevertheless varies across tasks and backbones, which is expected because each frozen language model induces a different bottleneck geometry and therefore preserves different forms of task-relevant interaction structure.

Taken together with the OPT-350M and GPT-2 results, these experiments show that SQUARE’s controlled-interaction performance is not restricted to a particular frozen language-model family or model scale. Rather, the measured quadratic feature map remains effective across the evaluated frozen representation geometries, ranging from smaller OPT and GPT-2 backbones to billion-parameter OpenLLaMA and Mistral models. Importantly, these results are specific to the controlled nonlinear interaction classification setting and do not establish that SQUARE is universally superior across arbitrary downstream objectives or natural-label tasks.

Controlled Reranking on Larger Backbones. Table 16 extends the controlled candidate-reranking analysis to OpenLLaMA-3B and Mistral-7B-v0.1 under a parameter-matched comparison. Across both backbones, the SQUARE-based rerankers consistently improve candidate-level ranking AUC over the classical MLP baseline. On OpenLLaMA-3B, SQUARE (Quantum) and SQUARE (Hybrid) both achieve an AUC of (0.745), compared with (0.736) for MLP. The hybrid variant additionally obtains the highest Label Accuracy and F1, reaching (0.708) and (0.724), respectively, compared with (0.707) and (0.701) for MLP.

A similar pattern is observed on Mistral-7B-v0.1. SQUARE (Hybrid) achieves the strongest performance across all three metrics, with a Label Accuracy of (0.731), an F1 score of (0.713), and a candidate AUC of (0.779), compared with (0.727), (0.704), and (0.760) for MLP. The quantum-only variant also improves candidate-level AUC to (0.778), although its Label Accuracy and F1 remain below those of the MLP and hybrid variants. This distinction suggests that the structured quantum

Table 14: Task-wise validation accuracy on GLUE-derived controlled nonlinear interaction classification with a frozen **OpenLLaMA-3B** backbone, averaged over three seeds. All methods operate on the same frozen OpenLLaMA-3B bottleneck representation. Params counts trainable adapter and task-head parameters only and therefore differs from the main-text budget because the head width and adapter ranks are configured for this backbone. Best performance in each column is shown in **bold**. SQUARE achieves the highest macro-average accuracy while using substantially fewer trainable parameters than LoRA, AdaLoRA, and the larger MLP head.

Method	Quantum	Params	CoLA	SST-2	STS-B	QQP	MNLI	QNLI	RTE	WNLI	Avg.
Linear	✗	17	0.6358	0.5783	0.6083	0.6583	0.6083	0.6392	0.6474	0.6150	0.6238
BitFit	✗	33	0.4808	0.5375	0.5592	0.5158	0.4717	0.4908	0.5535	0.5352	0.5181
LoRA _{r=8}	✗	417	0.6300	0.5825	0.6058	0.6525	0.6075	0.6417	0.6450	0.6103	0.6219
AdaLoRA	✗	621	0.6292	0.5725	0.5892	0.6592	0.6050	0.6400	0.6510	0.6103	0.6195
MLP	✗	1633	0.6667	0.6425	0.7442	0.6858	0.6767	0.6367	0.6967	0.8920	0.7052
SQUARE (Ours)	✓	157	0.7667	0.7358	0.7633	0.7825	0.7833	0.8025	0.8231	0.7136	0.7714

Table 15: Task-wise validation accuracy on GLUE-derived controlled nonlinear interaction classification with a frozen **Mistral-7B-v0.1** backbone, averaged over three seeds. All methods operate on the same frozen Mistral-7B-v0.1 bottleneck representation. Params counts trainable adapter and task-head parameters only and therefore differs from the main-text budget because the head width and adapter ranks are configured for this backbone. Best performance in each column is shown in **bold**. SQUARE achieves the highest macro-average accuracy while using substantially fewer trainable parameters than LoRA, AdaLoRA, and the larger MLP head.

Method	Quantum	Params	CoLA	SST-2	STS-B	QQP	MNLI	QNLI	RTE	WNLI	Avg.
Linear	✗	17	0.6017	0.5692	0.6167	0.6225	0.6083	0.5758	0.5860	0.6244	0.6006
BitFit	✗	33	0.4950	0.4883	0.5200	0.5517	0.4842	0.4500	0.5090	0.5634	0.5077
LoRA _{r=8}	✗	417	0.5975	0.5675	0.5800	0.6308	0.6133	0.5783	0.5752	0.6291	0.5965
AdaLoRA	✗	621	0.5958	0.5700	0.5808	0.6233	0.6000	0.6000	0.5909	0.5962	0.5946
MLP	✗	1633	0.6225	0.6592	0.7625	0.6650	0.6567	0.6475	0.6811	0.9155	0.7012
SQUARE (Ours)	✓	157	0.7442	0.7442	0.7100	0.7158	0.7850	0.7642	0.7377	0.7840	0.7481

representation provides useful candidate-ranking information, while combining it with the hybrid prediction pathway yields more robust performance for the final label-selection objective.

Together with the controlled nonlinear interaction classification results, these findings show that SQUARE’s structured interaction modeling extends beyond direct classification to a candidate-ranking objective. In particular, the consistent AUC gains across both SQUARE variants and both billion-parameter backbones indicate that the measured quantum feature map captures interaction structure useful for relative candidate scoring. At the same time, the stronger Label Accuracy and F1 of the hybrid variant suggest that retaining a complementary classical pathway can improve the conversion of these interaction features into final decisions. We therefore interpret the reranking results as evidence that the proposed structured representation transfers across controlled downstream objectives, while the optimal use of the quantum features may depend on how they are integrated into the prediction head.

B.6 COMPUTE-RESOURCE BENCHMARK

Table 17 reports an adapter-level runtime benchmark with batch size 32. The benchmark measures forward latency, training latency, and training throughput per sample while keeping the frozen backbone representation fixed. Thus, the reported values reflect the cost of the adaptation module rather than full end-to-end LM training.

Classical adapters are evaluated as standard tensor operations and therefore have very small latency. For example, BitFit, LoRA, Prefix, and MLP all remain below 0.07 ms per sample during training in this benchmark. In contrast, quantum-enhanced methods require simulator-based circuit evaluation, which introduces substantial overhead. SQUARE uses only 180 trainable parameters, comparable

Table 16: Controlled candidate reranking on the two larger frozen backbones using an MRPC-derived controlled reranking task (mean over three seeds). Label Acc./F1 measure the correctness of the selected candidate, and Cand. AUC measures candidate-relevance ranking quality. Under a parameter-matched comparison, both SQUARE variants improve candidate-level ranking AUC over the classical MLP on both backbones. SQUARE (Hybrid) further achieves the highest Label Accuracy and F1 on both OpenLLaMA-3B and Mistral-7B-v0.1, indicating that combining the structured quantum representation with the hybrid prediction pathway provides the most consistent reranking performance across the evaluated metrics.

Backbone	Reranker	Label Acc.	Label F1	Cand. AUC
OpenLLaMA-3B	Random	0.485	0.490	–
	Linear	0.515	0.679	0.522
	MLP	0.707	0.701	0.736
	SQUARE (Quantum)	0.704	0.712	0.745
	SQUARE (Hybrid)	0.708	0.724	0.745
Mistral-7B-v0.1	Random	0.510	0.491	–
	Linear	0.531	0.000	0.538
	MLP	0.727	0.704	0.760
	SQUARE (Quantum)	0.706	0.686	0.778
	SQUARE (Hybrid)	0.731	0.713	0.779

Table 17: Adapter-level runtime benchmark with batch size 32. Latency is measured per sample after freezing the backbone representation.

Method	Params	Fwd. ms	Train ms	Train samples/s
BitFit	33	0.0036	0.0403	24812.7
LoRA- $r=4$	104	0.0060	0.0467	21430.0
LoRA- $r=8$	200	0.0059	0.0462	21627.3
Prefix	289	0.0112	0.0660	15153.3
MLP	776	0.0058	0.0513	19477.8
QAA	140	8.9023	14.7052	68.0
QPA	192	0.2606	0.5599	1786.1
SQUARE	180	11.1924	21.3373	46.9

to compact PEFT baselines, but its current PennyLane simulator implementation requires 21.3373 ms per sample during training and reaches 46.9 training samples/s.

These results highlight a practical trade-off. SQUARE provides a compact measured nonlinear feature map with a small trainable parameter budget. To make the learned module usable outside the simulator, the direct PyTorch realization preserves the same inputs, parameters, gate order, topology, observables, and batch size as the PennyLane implementation: amplitude encoding becomes normalization and zero-padding; each RY/RZ rotation and CNOT is applied as a batched complex-valued matrix–vector operation; basis probabilities are squared magnitudes; and Pauli- Z expectations are signed sums of the probability block. It reproduces the simulated features with maximum absolute difference 1.118×10^{-7} and reduces forward latency from 97.598 ms to 4.720 ms at batch size 8 on an NVIDIA H200 ($20.7\times$). This establishes exact, simulator-free deployment of the learned circuit map; it does not imply a speed advantage over specialized classical adapters.

Matched-Protocol Training Benchmark. Table 17 times per-sample simulator training, which is the configuration the pipeline actually used but not the relevant comparison for the classical realization. We therefore benchmarked *training* (forward, backward, and an Adam step on a binary cross-entropy loss) under one matched protocol: the same $d=16$, $n=4$ circuit and the same $\text{Lin}(16 \rightarrow 8) - \tanh - \text{Lin}(8 \rightarrow 1)$ head, batch size 64, float64, a single CPU process on the experiment host (PennyLane 0.40.0, PyTorch 2.4.1; `default.qubit` is CPU-only in our environment; the host was shared with other jobs, so ratios are more informative than absolute times), 10 warm-up and 100 timed steps, for three implementations: the PennyLane `backprop` path, the native PyTorch `statevector` path (one 16×16 unitary assembled from the angles per step and applied to the batch),

and a $16 \rightarrow 8 \rightarrow 1$ MLP. On a batch of 64 random inputs the two SQUARE paths agree to 4.8×10^{-9} in the features and 2.1×10^{-8} in the angle gradients (the residual is the $\varepsilon=10^{-8}$ normalization constant). The native path removes most of the simulator overhead but remains slower than the MLP, consistent with the statement that the parameter budget does not establish computational efficiency.

Table 18: Matched-protocol training cost (CPU, batch 64, float64, mean $\pm$ s.d. over 100 steps).

Implementation	ms / step	ms / sample	relative to MLP
SQUARE, PennyLane <code>default.qubit + backprop</code>	14.26 ± 1.72	0.223	$22.4\times$
SQUARE, native PyTorch statevector	3.60 ± 0.11	0.056	$5.7\times$
MLP $16 \rightarrow 8 \rightarrow 1$ (145 parameters)	0.64 ± 0.03	0.010	$1.0\times$

B.7 GENERATION-ORIENTED RERANKING: FULL RESULTS

Table 19: Alpaca candidate reranking results. All methods score the same fixed candidate pool using the same frozen BERT bottleneck; higher is better.

Selector	BLEU	ROUGE-1	ROUGE-2	ROUGE-L	Score	HitRate	NonlinearScore
Uniform random (exact)	0.0193	0.2078	0.0622	0.1749	0.2066	0.1656	0.4991
MLP	0.0215	0.2256	0.0664	0.1861	0.2149	0.2083	0.4917
SQUARE, pure path	0.0211	0.2172	0.0605	0.1775	0.2128	0.1917	0.5222
SQUARE, residual path	0.0246	0.2365	0.0757	0.1895	0.2224	0.2417	0.5032
Oracle- q	0.0288	0.3123	0.1098	0.2622	0.2861	1.0000	0.5662
Oracle- ρ	0.0172	0.1935	0.0604	0.1618	0.2261	0.3083	0.6890

We formulate Alpaca instruction following as a candidate reranking problem (Taori et al., 2023): for each instruction, a fixed pool of LLM-generated responses is given, and each method learns to assign a scalar score to each instruction–response pair over the same frozen BERT bottleneck. Because the candidate pool is shared across methods, the evaluation isolates the quality of the learned scorer rather than the generator (Qin et al., 2024; Wang et al., 2025a). We evaluate the top-ranked response selected by each method: BLEU and ROUGE measure lexical agreement with the reference, Score and HitRate evaluate whether the scorer selects high-quality candidates, and NonlinearScore measures joint satisfaction of interaction-dependent quality criteria; detailed definitions are provided in Appendix C.7.

Table 19 rebuilds the evaluation from candidate-level data for 120 instructions and $K=8$ candidates per pool. Because 11 pools contain tied maxima, exact random HitRate is 0.1656 rather than $1/8$. The residual-path SQUARE scorer is numerically highest among the learned scorers, but its differences from the MLP are not separable under instruction-paired bootstrap: $+0.012$ NonlinearScore (95% CI $[-0.012, 0.036]$) and $+0.033$ HitRate ($[-0.033, 0.100]$). Random selection already reaches 0.4991 NonlinearScore, whereas Oracle- ρ reaches 0.6890; the pure path moves further toward this interaction target (0.5222) at the cost of lexical metrics. Accordingly, the experiment supports transfer to a reranking objective and approximate parity with compact classical scoring, but not improved human-perceived quality or a specifically quantum benefit.

B.8 LIMITATIONS AND FUTURE DIRECTIONS

Our evaluation primarily emphasizes controlled interaction recovery, which allows the contribution of the post-bottleneck parameterization to be isolated from changes in the frozen representation. The original-label and reranking experiments provide complementary scope checks, while extending the observed advantages to broader natural-supervision settings remains an important direction for future work. The eight GLUE-derived entries represent eight frozen-representation distributions under one shared constructed rule rather than eight independent semantic tasks, and the natural-label results currently support compactness rather than an accuracy gain.

Circuit simulation introduces training overhead relative to specialized classical adapters. SQUARE addresses deployment rather than simulation cost: after training, the learned map can be compiled

exactly into a numerically equivalent batched PyTorch module that requires neither a circuit simulator nor quantum hardware at inference. Accordingly, parameter efficiency should not be read as computational efficiency; the native PyTorch realization remains slower than the matched MLP in the reported training benchmark.

Finally, the central experiments use $d=16$ bottlenecks and four-qubit statevectors. Although the stored circuit-angle count grows with $O(L \log d)$ for the chosen gate template and the probability readout has width $B < 2d$, a dense classical realization of the learned unitary can require $O(B^2)$ storage and arithmetic; few trainable angles therefore do not establish favorable scaling. The additional-backbone study changes the frozen encoder while retaining a compact bottleneck and is not a dimension-scaling experiment. Future work should study bottleneck dimension, alternative circuit and classical mixing structures, finite-shot training, and hardware-aware or gatewise implementations. The current results therefore support circuit-induced interaction parameterization and exact classical deployment, without assuming quantum computational or hardware advantage.

B.9 BROADER IMPACT

The main intended impact is methodological and practical: SQUARE provides a controlled way to learn interaction-dependent structure through a quantum-circuit parameterization and then deploy the learned map as an exact classical PyTorch module without updating the frozen backbone. Potential applications include parameter-efficient classification, scoring, and reranking. The results should not be interpreted as near-term quantum hardware advantage; rather, they demonstrate a train-with-circuit, deploy-classically workflow that makes circuit-induced feature maps accessible to conventional software pipelines.

SQUARE can inherit and potentially amplify biases or spurious correlations in the frozen LM representation. This risk is especially relevant in sensitive domains such as education, healthcare, hiring, or legal support. Any deployment should therefore include task-specific validation, fairness and robustness checks, privacy safeguards, and human oversight. Future work should evaluate SQUARE under natural supervision, larger backbones, stronger privacy constraints, and realistic deployment protocols.

B.10 ADDITIONAL BOUNDARY CONTROLS: UNTRAINED-CIRCUIT, FINITE-SHOT, AND CLASSICAL COLLAPSE

We further evaluate three properties of the boundary pipeline: the contribution of trained circuit angles, sensitivity to finite-shot readout, and comparison with mechanism-matched classical controls. The depth-1 SQUARE variant uses a learned nonlinear $2 \rightarrow 16$ projection and magnitude features $\sqrt{p}$; as clarified in Appendix A.4, this end-to-end boundary architecture is not exactly quadratic in the original PCA-2 coordinates. We compare it with mechanism-matched classical and PEFT-inspired baselines, an RBF-SVM, a frozen-circuit control, and a depth-2 re-uploading variant included as an extended-capacity reference.

Checkerboard geometry. On checkerboard, the MLP, adapter, LoRA, and random forest reach mean test AUC 0.484 ± 0.046 , 0.490 ± 0.040 , 0.501 ± 0.052 , and 0.457 ± 0.023 ; RBF-SVM reaches 0.609 ± 0.013 , and depth-1 SQUARE reaches 0.849 ± 0.039 . This is evidence of performance under the stated optimization protocol, not representational impossibility for the baselines and not an isolated test of a quadratic map: the SQUARE boundary pipeline also contains the nonlinear projection and magnitude readout described above. Training-AUC diagnostics would be needed to distinguish failure to fit from failure to generalize.

Untrained-circuit control. In the depth-1 boundary pipeline, trained-minus-untrained AUC gaps are within $[-0.017, +0.022]$ across all five geometries, so trained angles are not decisive under this residual, learned-projection protocol. This observation does not isolate a degree-two end-to-end predictor because the pipeline also contains a nonlinear projection and magnitude readout. On the disjoint held-out pure-path GLUE-derived suite, by contrast, the trained circuit reaches 0.7565 mean accuracy versus 0.6155 for the frozen circuit (Appendix B.12), a substantially larger separation that isolates the value of learned circuit mixing in the measured-feature path.

Finite-shot readout. Replacing exact-statevector probabilities with multinomial sampling at 100/1,000/10,000 shots changes test AUC only slightly: on checkerboard, depth-1 SQUARE moves

from 0.849 to 0.833 at 100 shots and returns to 0.849 at 1,000 and 10,000 shots; the re-uploading variant moves from 0.962 to 0.954/0.962/0.963, and other geometries change by at most ~ 0.01 at 100 shots. This is a finite-sampling sensitivity check for the stated boundary pipeline, not evidence that its end-to-end predictor is exactly quadratic.

We report these as controls on a single tutoring bottleneck; they complement rather than replace the main-text diagnostics. The depth-1 SQUARE configuration is competitive but not uniformly dominant (on the radial-ring geometry the RBF-SVM and the re-uploading variant are stronger), consistent with our scoping of the contribution as a structured parameterization rather than a universal approximator.

Table 20: Additional boundary controls on a frozen Qwen2.5-1.5B-Instruct tutoring PCA-2 bottleneck. Mean test AUC $\pm$ sample standard deviation over six seeds. SQUARE is the depth-1 learned-projection/magnitude-readout configuration; “untr.” freezes all circuit parameters. SQUARE_{ru} adds depth-2 input re-uploading. These end-to-end boundary models are not claimed to be exactly quadratic in the original PCA-2 coordinates.

Method	cluster	radial ring	checkerboard	two-moons	islands
SQUARE (depth-1, $\sim 93p$)	0.999$\pm$0.001	0.825 $\pm$ 0.045	0.849 $\pm$ 0.039	0.964 $\pm$ 0.034	0.986 $\pm$ 0.013
SQUARE untr. ($\sim 81p$)	0.999$\pm$0.001	0.841 $\pm$ 0.034	0.838 $\pm$ 0.042	0.981 $\pm$ 0.016	0.964 $\pm$ 0.023
SQUARE _{ru} (depth-2, $\sim 121p$)	0.999$\pm$0.001	0.999$\pm$0.001	0.962$\pm$0.033	0.999$\pm$0.001	0.994 $\pm$ 0.004
SQUARE _{ru} untr.	0.999$\pm$0.002	0.933 $\pm$ 0.043	0.829 $\pm$ 0.015	0.997 $\pm$ 0.003	0.988 $\pm$ 0.007
MLP ($\sim 129p$)	0.999$\pm$0.001	0.804 $\pm$ 0.106	0.484 $\pm$ 0.046	0.920 $\pm$ 0.004	0.992 $\pm$ 0.009
Adapter ($\sim 125p$)	0.999$\pm$0.002	0.773 $\pm$ 0.110	0.490 $\pm$ 0.040	0.920 $\pm$ 0.003	0.994 $\pm$ 0.007
LoRA ($\sim 99p$)	0.563 $\pm$ 0.011	0.593 $\pm$ 0.011	0.501 $\pm$ 0.052	0.924 $\pm$ 0.004	0.679 $\pm$ 0.028
RBF-SVM	0.999$\pm$0.003	0.996 $\pm$ 0.001	0.609 $\pm$ 0.013	0.966 $\pm$ 0.004	0.999$\pm$0.002
Random Forest	0.975 $\pm$ 0.014	0.848 $\pm$ 0.032	0.457 $\pm$ 0.023	0.899 $\pm$ 0.023	0.892 $\pm$ 0.009

Table 21: Finite-shot readout on the tutoring bottleneck: mean test AUC over six seeds when the exact statevector probabilities are replaced by multinomial sampling at 100/1,000/10,000 shots. AUC differs from the exact readout by at most 0.016 at 100 shots and by ≤ 0.001 at $\geq 1,000$ shots.

Method (rule)	exact	100 shots	1,000	10,000
SQUARE (checkerboard)	0.849	0.833	0.849	0.849
SQUARE _{ru} (checkerboard)	0.962	0.954	0.962	0.963
SQUARE _{ru} (radial ring)	0.999	0.997	0.999	0.999
SQUARE _{ru} (two-moons)	0.999	0.999	0.999	0.999

B.11 TRAINABLE-PARAMETER ACCOUNTING AND HEAD ARCHITECTURES FOR SQUARE

Several tables report SQUARE with different trainable-parameter totals. All follow $N_{\text{SQUARE}} = gL[\log_2 d] + N_{\text{proj}} + N_{\text{head}}$, where g is the number of trainable rotations per qubit per layer ($g=3$ for $RYRZ$ -Ring- RY , $g=1$ or 2 in the rotation ablation), N_{proj} counts an optional input projection, and N_{head} is the task head applied to the readout. Table 22 summarizes the head architectures and parameter decompositions of the evaluated SQUARE configurations. The head is a small *nonlinear* (tanh) MLP in the controlled-GLUE suites and affine in the boundary controls, which is why normalized quadraticity applies to the feature map and not to the end-to-end predictor. The validation/backbone suites read all $B+n=20$ coordinates into a bias-free head, giving $12 + 160 + 8 = 180$, whereas the primary held-out control suite reads the 16 probabilities into a biased head, giving $12 + 145 = 157$. Other reported configurations follow the same formula with the head widths given in their table captions and Appendix C.8.

The 20-dimensional V20 readout contains 16 probabilities and four Pauli- Z expectations, but the latter are fixed linear combinations of the probabilities. After training, the first-layer weights can therefore be folded exactly into a $16 \rightarrow 8$ matrix. The resulting function has an equivalent 148-scalar inference representation (12 angles, 128 folded first-layer weights, and 8 output weights), although 180 remains the correct number of independently optimized scalars in that training configuration. This algebraic compression preserves the trained function. It does not imply identical optimization: training on $[p; \zeta]$ reparameterizes the first-layer gradient relative to training on p alone. We

Table 22: Parameter decomposition of the central SQUARE configurations ($d=B=16$, $n=4$ unless noted). “Readout” is the head input dimension. The primary held-out model uses a biased probability-only head; the separate validation/backbone model uses a bias-free probability-plus- Z head. [†]Learned input projection $\text{Lin}(2 \rightarrow 16) - \tanh$, used only in the boundary suite.

Protocol	Head architecture	Angles	Proj.	Head	Total
V20: validation/backbone suites and runtime benchmark	$\text{Lin}(20 \rightarrow 8) - \tanh - \text{Lin}(8 \rightarrow 1)$, bias-free, on the 20-dimensional readout	12	–	168	180
H16: primary held-out test and post-entanglement ablation (Apps. B.12, B.13)	$\text{Lin}(16 \rightarrow 8) - \tanh - \text{Lin}(8 \rightarrow 1)$ on the 16 basis probabilities	12	–	145	157
B32: boundary controls (App. B.10), nonlinear projection + magnitude readout	$\text{Lin}(32 \rightarrow 1)$ on $[v; \sqrt{p(v)}]$	12	48 [†]	33	93

therefore report 180 as the trained V20 model size and 148 only as an exact post-training inference representation; H16 is the 157-parameter primary held-out configuration.

B.12 DISJOINT HELD-OUT VALIDATION OF THE SAME-PIPELINE CONTROLS

We evaluate the same-pipeline control suite using disjoint train, validation, and test subsets on all eight GLUE-derived controlled-label tasks. The scaler, PCA projection, and training-set median label threshold were fitted on train only; the checkpoint was selected by validation AUC and evaluated once on test. Table 23 reports the unweighted eight-task mean over five shared seeds. The 157-parameter SQUARE total is 12 circuit angles plus the 145-parameter biased $16 \rightarrow 8 \rightarrow 1$ head, as detailed in Table 22.

Table 23: Disjoint held-out test summary for same-pipeline controls (eight tasks, five shared seeds). Δ is comparator minus SQUARE. Displayed endpoints are descriptive averages of taskwise example-paired bootstrap 95% intervals, not a calibrated confidence interval for the macro-average.

Method	Params	Avg. test	Δ vs. SQUARE [avg. taskwise interval]
LoRA $r=8$	417	0.5897	−0.167 [−0.181, −0.137]
MLP	1,633	0.6817	−0.075 [−0.081, −0.053]
SQUARE w/o PQC	145	0.6412	−0.115 [−0.125, −0.092]
SQUARE, frozen circuit	145	0.6155	−0.141 [−0.147, −0.120]
SQUARE	157	0.7565	–
Givens-12 + squares + head	157	0.7271	−0.029 [−0.041, −0.003]
Normalized quadratic	137	0.7355	−0.021 [−0.031, −0.002]

The held-out results provide consistent evidence for the circuit-induced parameterization under a fully disjoint evaluation protocol. SQUARE achieves the highest eight-task mean among all evaluated same-pipeline controls, outperforming LoRA and the wider MLP. Its improvements over the head-only and frozen-circuit variants further indicate that both the measured feature map and the learned circuit angles contribute to performance. SQUARE also exceeds the parameter-matched Givens-12 model and the normalized-quadratic predictor. The taskwise interval summaries are consistently negative for every comparator; because they are descriptive aggregates rather than calibrated confidence intervals for the macro-average, we use them to characterize the consistency of the observed ordering rather than to establish a universal ranking of quadratic models.

B.13 POST-ENTANGLEMENT CIRCUIT CONFIGURATION ANALYSIS

We evaluate circuit configurations using a common trainable post-entanglement RY block in every variant, so differences reflect the jointly learned rotation–entanglement design. QNLI, MNLI, and

RTE are evaluated under the disjoint held-out protocol above with five shared seeds. Table 24 reports the three-task mean. This analysis is diagnostic only: no circuit configuration was selected or retuned using the reported held-out test results, and all headline comparisons retain the prespecified ring configuration.

Table 24: Circuit configuration analysis with a trainable post-entanglement RY block in every row. Avg. test is mean held-out accuracy over QNLI, MNLI, and RTE with five shared seeds.

Pre-entangler rotations	Entangler	Angles	Total	Avg. test
RY	none	8	153	0.7891
RY	linear CNOT	8	153	0.7879
RY	ring CNOT	8	153	0.7568
$RYRZ$	none	12	157	0.7889
$RYRZ$	linear CNOT	12	157	0.7875
$RYRZ$	ring CNOT (default)	12	157	0.8462
$RYRZ$	all-to-all CNOT	12	157	0.8155

The prespecified $RYRZ$ -ring configuration gives the highest observed mean accuracy (0.8462), exceeding the corresponding non-entangling, linear-CNOT, and all-to-all variants in this three-task diagnostic. The contrast with the RY rows is also informative: ring coupling is not uniformly beneficial, because the RY -ring configuration trails both RY -none and RY -linear. The result therefore supports the default circuit as a jointly specified rotation-topology design rather than attributing the gain to entanglement alone. Because the configurations were not selected or retuned using these held-out results, we treat the table as diagnostic evidence within QNLI, MNLI, and RTE; selecting a topology for a new benchmark still requires validation-only model selection followed by evaluation on an untouched test set.

C EXPERIMENTAL SETUP

C.1 DATASET CONSTRUCTION AND SPLITS

Table 25 summarizes the dataset construction and split information for the main experiments. Counts marked as controlled-boundary counts are nominal draws before the fixed near-boundary exclusion; actual retained counts can vary by seed and geometry and are the denominators used for per-run metrics. Unless otherwise stated, all experiments use frozen BERT bottleneck representations. For controlled classification experiments, labels are generated from predefined nonlinear interaction rules over frozen representations.

The exact generators for every geometry used in the decision-boundary experiments and controls are given in Appendix C.3, and the GLUE rule in Eq. (22). For reranking experiments, all methods score the same fixed candidate pool, so performance differences reflect the learned scoring function rather than candidate generation.

Table 25: Dataset construction and split information for the main experiments. Controlled tasks use labels generated from nonlinear interaction rules over frozen BERT bottleneck features. Reranking tasks use fixed candidate pools shared across methods.

Experiment	Data Source	Train	Validation	Test / Eval	Seeds	Evaluation Unit
2D decision-boundary analysis (nominal)	Controlled 2D bottleneck features	1,000	400	–	3	Binary example
GLUE-derived interaction classification	GLUE inputs with controlled nonlinear labels	7,600	2,250	–	3	Sentence / sentence-pair example
Alpaca candidate reranking	Alpaca instruction-following candidates	960	120	120	3	Query-candidate pair
Disjoint held-out control suite	Eight GLUE inputs with controlled nonlinear labels	Disjoint task-specific subsets			5	Sentence / sentence-pair example

C.2 CONTROLLED DECISION-BOUNDARY DATA

For the two-dimensional decision-boundary analysis, we construct a controlled binary classification dataset from two-dimensional bottleneck features. Labels are generated by a nonlinear decision rule, allowing us to directly visualize whether each adapter can recover interaction-dependent boundaries.

We draw 1,000 training examples and 400 validation examples per seed and report mean results over three random seeds; these are nominal pre-filter counts. As specified with the generators below, points satisfying $|s - \tau| \leq 0.05$ are removed separately from each split, so the retained evaluation denominator varies with seed and geometry. Accuracy is computed from retained correct/example counts for each run and then averaged across seeds; split details are summarized in Table 26.

Table 26: Split information for controlled nonlinear decision-boundary experiments. The same split is used for qualitative boundary analysis and circuit configuration ablation.

Item	Value
Train examples	1,000
Validation examples	400
Input dimension	2
Label construction	Controlled nonlinear rule
Evaluation unit	Binary example
Metrics	Accuracy, F1, AUC
Seeds	3

C.3 EXACT GENERATORS FOR THE DECISION-BOUNDARY GEOMETRIES

Each two-dimensional geometry is defined by a fixed score $s(x, y)$ on the standardized PCA-2 coordinates (x, y) of the frozen bottleneck (jittered once per seed by $\mathcal{N}(0, 0.015^2)$ noise); the label is $y_{\text{lab}} = \mathbb{I}[s > \tau]$ with τ the median of s over the training indices, and points with $|s - \tau| \leq 0.05$ are dropped from every split to avoid label noise at the boundary. With $r = \sqrt{x^2 + y^2}$, $r_1 = \sqrt{(x + 0.85)^2 + (y - 0.25)^2}$, and $r_2 = \sqrt{(x - 0.85)^2 + (y + 0.25)^2}$:

$$s_{\text{cluster}}(x, y) = e^{-((x+1.55)^2 + (y-0.15)^2)/0.70} + e^{-((x-1.55)^2 + (y+0.10)^2)/0.70} - 1.05 e^{-(x^2 + y^2)/0.55}, \quad (17)$$

$$s_{\text{ring}}(x, y) = e^{-(r-1.35)^2/0.16} - 0.55 e^{-r^2/0.75}, \quad (18)$$

$$s_{\text{checker}}(x, y) = \sin(2.7x) \sin(2.7y), \quad (19)$$

$$s_{\text{moons}}(x, y) = e^{-(r_1-0.95)^2/0.07} - e^{-(r_2-0.95)^2/0.07} + 0.05 \sin(2.0x), \quad (20)$$

$$s_{\text{islands}}(x, y) = e^{-((x+1.45)^2 + (y+0.9)^2)/0.36} + e^{-((x-1.25)^2 + (y-0.85)^2)/0.36} + e^{-((x+0.05)^2 + (y-1.55)^2)/0.40} - 0.90 e^{-((x-0.05)^2 + y^2)/0.85}. \quad (21)$$

None of these is a degree-two polynomial or a single bilinear threshold. A direct map $q_\theta(x)$ would be unable to represent the radial-ring rule because it is scale invariant, but the evaluated boundary architecture first applies the learned nonlinear map $v = \tanh(Wx + b)$, which can encode radius into direction. The residual is therefore an empirical component of this broader architecture, not a mathematical necessity implied by the direct-map invariance. All constants are fixed and shared across methods and seeds. The checkerboard and radial-ring rules used in the main-text diagnostic (Table 2) are the same functions.

C.4 GLUE-DERIVED CONTROLLED INTERACTION DATA

For GLUE-derived interaction classification, we discard the original GLUE labels and regenerate binary labels from nonlinear interaction rules over frozen BERT bottleneck features. The central held-out comparison uses disjoint task-specific train, validation, and test subsets with five shared seeds; preprocessing and the training-set median threshold are fitted on train only, model selection uses validation AUC, and test data are evaluated once.

This setting is designed to evaluate whether an adapter can recover imposed interaction-dependent rules rather than exploit original task-label correlations. We construct task-balanced controlled subsets to prevent large GLUE tasks such as QQP or MNLI from dominating the evaluation. Each task is approximately label-balanced, and the reported average is a macro-average across tasks.

For each task, we first extract frozen BERT bottleneck representations and then apply a fixed nonlinear interaction rule to generate labels. The generated labels are balanced within each task, preventing adapters from exploiting class-frequency artifacts. Because all methods use the same frozen

features and controlled labels, task-wise accuracy directly measures how well each adapter recovers the imposed nonlinear interaction rule.

Exact label-generation rule. For every GLUE-derived task the controlled label is produced by one fixed rule, which we state verbatim so that the targets can be regenerated and their relation to SQUARE’s feature family assessed. Let h be the frozen bottleneck feature of an input (for sentence pairs, the encoder output of the concatenated pair). Features are standardized coordinate-wise on the training split and projected to $z \in \mathbb{R}^{16}$ by a PCA fitted on the training split ($d=16$); the validation split uses the same scaler and PCA. The controlled score is

$$\begin{aligned} f(z) = & 1.20 \sin(1.40 z_1 z_2) + 0.90 \cos(1.10 (z_3 - z_4)) + 0.80 z_5 z_6 \\ & - 0.55 z_7^2 + 0.45 \sin(z_8 + z_9) - 0.35 z_{10} z_{11} \\ & + 0.25 \cos(z_{12} z_{13}) + 0.20 \sin(z_{14} z_{15} - z_{16}), \end{aligned} \quad (22)$$

with one-indexed PCA coordinates, and the binary label is $y = \mathbb{I}[f(z) > \tau]$ with τ the median of f on the training split; the same threshold is applied to validation, which need not be exactly balanced. The coefficients are fixed across tasks, backbones, seeds, and methods. The rule is not exactly degree two because it contains sinusoids and cosines of coordinate products, but it was deliberately designed to be interaction-rich and can therefore favor models that expose interaction features explicitly. It also contains scale- and sign-sensitive terms, whereas the pure SQUARE map is invariant to nonzero rescaling and global sign; performance is therefore distribution-conditional and is not evidence that the target belongs to SQUARE’s hypothesis class. The eight task entries are eight frozen-representation distributions evaluated under one shared constructed rule, not eight independent semantic targets. The generator code and fixed coefficients are included in the anonymized reproducibility package.

C.5 OPERATIONAL DEFINITIONS FOR THE ALPACA RERANKING PROTOCOL

Candidate generation. For each Alpaca instruction (with its optional input field, formatted with the standard `### Instruction / ### Input / ### Response` template), a frozen FLAN-T5 generator produces K candidates by nucleus sampling with temperature 1.0, top- p 0.95, repetition penalty 1.08, no-repeat 3-gram blocking, and at most 128 new tokens; the pool is generated once and shared by every scorer. **Features.** Each (instruction, candidate) pair is encoded by frozen bert-base-uncased; the pooled pair representation is standardized on the training split and projected by a training-split PCA to $z \in \mathbb{R}^{d_r}$, then ℓ_2 -normalized. **Nonlinear consistency score.** $\rho_{i,j} = \sigma(\tilde{\rho}_{i,j})$, where $\tilde{\rho}$ is the training-split z -score of

$$\begin{aligned} \rho^{\text{raw}}(z) = & 1.20 \sin(8z_1 z_2) + 1.00 \cos(6(z_3 - z_4)) + 0.90 \sin(9z_5 z_6) - 0.80 \cos(7z_7 z_8) \\ & + 0.70 \sin(6(z_9 + z_{10})) + 0.60 \cos(8(z_{11} - z_{12})) + 0.50 \sin(10z_{13} z_{14}) \\ & - 0.40 \cos(9z_{15} z_{16}) + 0.30 \sin(7z_{17} z_{18}) + 0.25 \cos(6(z_{21} - z_{22})), \end{aligned} \quad (23)$$

and σ is the logistic function; ρ is therefore an author-specified interaction-dependent target on the frozen features, fixed before training and identical for all methods, and NonlinearScore (Eq. (36)) is its mean over the selected candidates. It measures whether a scorer can select candidates that satisfy a prescribed nonlinear consistency criterion; it is *not* a measure of response quality judged externally. **Quality score.** $q_{i,j} = 0.85 \text{sim}_{i,j} + 0.15 \rho_{i,j}$, with $\text{sim}_{i,j} = 0.25 \text{R1} + 0.25 \text{R2} + 0.50 \text{RL}$ the stemmed ROUGE-1/2/L F -measures of the candidate against the Alpaca reference output; for training only, the reference itself is added to each pool as an anchor candidate with q increased by 2.0. Score and HitRate are computed from q as in Appendix C.7. **Scorer training.** Every scorer f is trained on the training pools to regress q with the loss $\mathcal{L} = \text{MSE}(\sigma(f(z)), q)$, AdamW, 20 epochs; at evaluation the candidate with the largest $f(z)$ in each held-out pool is selected. **Chance and oracle references.** The candidate-level rebuild contains 120 evaluation pools with $K=8$. Uniform random Score and NonlinearScore are the averages of the within-pool means of q and ρ . HitRate credits every candidate tied at the pool maximum, so its exact random expectation is $N^{-1} \sum_i m_i / K = 0.1656$, where m_i is the number of maximizers (11 pools contain ties), rather than simply $1/K$. Oracle- q selects $\arg \max_j q_{i,j}$ and attains HitRate 1; Oracle- ρ separately upper-bounds NonlinearScore. These exact references are reported in Table 19.

Anchor-loss caveat. Because the anchor target is $q + 2.0$ while $\sigma(f) \in (0, 1)$, that target is unreachable. It acts as a shared margin-inducing training heuristic rather than ordinary bounded regression, and the reranking results are conditional on this uncalibrated choice.

C.6 ALPACA CANDIDATE RERANKING DATA

Table 27 summarizes the split information for the Alpaca candidate reranking protocol. For Alpaca

Table 27: Split information for Alpaca instruction-following candidate reranking. All methods rerank the same fixed candidate set for each query.

Item	Value
Train queries	960
Validation queries	120
Test queries	120
Candidates per query	8
Evaluation unit	Query-candidate pair
Selection rule	$\hat{j} = \arg \max_j s_{i,j}$
Seeds	3

candidate reranking, each example consists of an instruction and a fixed set of candidate responses. All methods score the same candidate pool and select the top-ranked candidate by

$$\hat{j} = \arg \max_j s_{i,j}.$$

We use 960 training queries, 120 validation queries, and 120 test queries. Since the candidate set is fixed across methods, this experiment evaluates reranking quality rather than generation quality.

For each instruction, every method receives the same eight candidate responses. Each method assigns a scalar score to every instruction-candidate pair and selects the candidate with the highest score. Thus, improvements in BLEU, ROUGE, HitRate, and NonlinearScore reflect improved scoring and selection rather than improved response generation.

C.7 EVALUATION METRICS

We use task-specific metrics depending on whether the experiment is formulated as binary classification, controlled nonlinear separation, or candidate reranking. Unless otherwise stated, all reported values are averaged over three random seeds.

Classification and controlled interaction tasks. For the two-dimensional decision-boundary task and GLUE-derived controlled interaction classification, each example has a binary label $y_i \in \{0, 1\}$ and a predicted probability $\hat{p}_i \in [0, 1]$. We obtain a hard prediction by thresholding at 0.5:

$$\hat{y}_i = \mathbb{1}[\hat{p}_i \geq 0.5]. \quad (24)$$

Accuracy is defined as

$$\text{Acc} = \frac{1}{N} \sum_{i=1}^N \mathbb{1}[\hat{y}_i = y_i]. \quad (25)$$

Precision, recall, and F1 are computed from true positives (TP), false positives (FP), and false negatives (FN):

$$\text{Precision} = \frac{\text{TP}}{\text{TP} + \text{FP}}, \quad \text{Recall} = \frac{\text{TP}}{\text{TP} + \text{FN}}, \quad (26)$$

$$\text{F1} = \frac{2 \cdot \text{Precision} \cdot \text{Recall}}{\text{Precision} + \text{Recall}}. \quad (27)$$

We also report AUC, the area under the ROC curve. Let $\mathcal{P}$ and $\mathcal{N}$ denote the sets of positive and negative examples. AUC can be written as the probability that a randomly chosen positive example receives a higher score than a randomly chosen negative example:

$$\text{AUC} = \frac{1}{|\mathcal{P}||\mathcal{N}|} \sum_{i \in \mathcal{P}} \sum_{j \in \mathcal{N}} \left[\mathbb{1}[\hat{p}_i > \hat{p}_j] + \frac{1}{2} \mathbb{1}[\hat{p}_i = \hat{p}_j] \right]. \quad (28)$$

For circuit configuration analysis, we use AUC as the primary metric because it evaluates nonlinear separability without depending on a fixed classification threshold.

Candidate reranking metrics. For generation-oriented reranking, each instruction x_i is associated with a fixed candidate set $\mathcal{C}_i = \{c_{i,1}, \dots, c_{i,K}\}$. A reranker assigns a scalar score $s_{i,j}$ to each candidate and selects

$$\hat{j}_i = \arg \max_j s_{i,j}, \quad \hat{c}_i = c_{i,\hat{j}_i}. \quad (29)$$

All automatic metrics are computed on the selected response $\hat{c}_i$.

BLEU measures n -gram precision against the reference response r_i with a brevity penalty:

$$\text{BLEU} = \text{BP} \cdot \exp \left(\sum_{n=1}^N w_n \log p_n \right), \quad (30)$$

where p_n is the modified n -gram precision, w_n is the weight for n -grams, and BP is the brevity penalty.

ROUGE- n is reported as the stemmed n -gram overlap F-measure. Let O_n be the clipped overlap count, $P_n = O_n/|\mathcal{G}_n(\hat{c}_i)|$, and $R_n = O_n/|\mathcal{G}_n(r_i)|$:

$$\text{ROUGE-}n = \frac{2P_n R_n}{P_n + R_n}, \quad (31)$$

where $\mathcal{G}_n(r_i)$ is the set of n -grams in the reference. ROUGE-L is computed from the longest common subsequence (LCS):

$$R_{\text{LCS}} = \frac{\text{LCS}(\hat{c}_i, r_i)}{|r_i|}, \quad P_{\text{LCS}} = \frac{\text{LCS}(\hat{c}_i, r_i)}{|\hat{c}_i|}, \quad (32)$$

$$\text{ROUGE-L} = \frac{(1 + \beta^2) R_{\text{LCS}} P_{\text{LCS}}}{R_{\text{LCS}} + \beta^2 P_{\text{LCS}}}. \quad (33)$$

For reranking-specific evaluation, let $q_{i,j}$ denote the automatic quality score assigned to candidate $c_{i,j}$. The reported Score is the average quality score of the selected candidates:

$$\text{Score} = \frac{1}{N} \sum_{i=1}^N q_{i,\hat{j}_i}. \quad (34)$$

HitRate measures whether the reranker selects the highest-quality candidate in the pool:

$$\text{HitRate} = \frac{1}{N} \sum_{i=1}^N \mathbb{1} \left[\hat{j}_i \in \arg \max_j q_{i,j} \right]. \quad (35)$$

NonlinearScore evaluates whether the selected response satisfies interaction-dependent quality criteria. Let $\rho_{i,j} \in [0, 1]$ denote the nonlinear candidate-quality score. We now define both $q_{i,j}$ and $\rho_{i,j}$ operationally (Appendix C.5); in short, $q_{i,j}$ is a fixed weighted combination of ROUGE agreement with the reference and $\rho_{i,j}$, and $\rho_{i,j}$ is a fixed, analytically specified nonlinear function of the candidate’s frozen-feature coordinates, not a judgment by an external evaluator. We report

$$\text{NonlinearScore} = \frac{1}{N} \sum_{i=1}^N \rho_{i,\hat{j}_i}. \quad (36)$$

Unlike lexical overlap metrics, NonlinearScore measures agreement with the author-specified interaction-dependent target over frozen coordinates; it is not an external judgment of response quality.

C.8 BASELINE IMPLEMENTATION

Table 28 summarizes the hyperparameters used for all baselines and SQUARE. For every method, the LM encoder and bottleneck projection are frozen, and only adapter-specific parameters and the task head are optimized. This setting ensures that all methods operate on the same fixed representation space and that the comparison focuses on the adaptation module applied after the frozen bottleneck. Unless otherwise stated, we use the same optimizer and scheduler family whenever

applicable, so performance differences primarily reflect the adaptation mechanism rather than backbone updates, feature-extraction differences, or optimization protocol. Hyperparameters are selected from the compact search ranges reported in Table 28, and the final reported parameter counts include only trainable adapter and task-head parameters.

We choose baselines to cover three comparison axes. First, BitFit, LoRA, AdaLoRA, and Prefix represent standard parameter-efficient classical adaptation mechanisms, ranging from bias-only updates to low-rank and prefix-based adaptation. These methods provide strong references for whether interaction-dependent prediction can be recovered through conventional PEFT transformations over frozen representations. Second, MLP serves as a classical nonlinear reference. This baseline is important because SQUARE is designed to expose nonlinear interaction features; therefore, the relevant comparison is not only against linear or low-rank adapters, but also against a compact classical nonlinear head with a larger trainable parameter budget. This allows us to test whether SQUARE provides competitive interaction modeling under fewer trainable parameters rather than merely outperforming restricted linear adapters.

Third, QAA and QPA represent quantum-enhanced PEFT alternatives. QAA inserts a shallow quantum module at the activation level, while QPA uses a quantum component for parameter generation. These baselines allow us to separate the effect of using a quantum-labeled component from the specific design choice made in SQUARE. In contrast to QAA and QPA, SQUARE amplitude-encodes the frozen bottleneck itself and directly measures nonlinear relation features from an $RYRZ$ -Ring- RY circuit. Thus, the comparison evaluates not only whether quantum-enhanced adaptation is useful, but also where the quantum module is inserted and how its measured readout is used by the downstream head.

In addition to these groups, the comparison set also includes mechanism-matched classical interaction models over the same frozen bottleneck: explicit normalized quadratic feature expansions, full- and low-rank bilinear heads, factorization machines, classical Fourier features, random Fourier features, RBF-SVM, Nyström features, kNN, graph-Laplacian classification, and an Isomap-based local manifold method. Each family is selected from prespecified configurations using validation data only, under the protocol-specific budgets described in Section 4; the boundary-specific diagnostic, the broad-family suite, and the compact-budget comparison use separate candidate configurations, and results are compared only within each protocol.

We also include SQUARE without the PQC as an internal ablation. This variant keeps the same frozen bottleneck representation and lightweight task-head structure but removes the parameterized quantum feature map. The ablation is intended to isolate whether the gains come from the measured quantum readout rather than from the bottleneck representation, the head capacity, or the training setup. Together, the classical PEFT baselines, classical nonlinear baseline, quantum-enhanced PEFT baselines, and SQUARE ablation provide a controlled comparison for evaluating SQUARE as a compact nonlinear relation module over frozen LM representations.

Table 28: Hyperparameters used for baseline adapters and SQUARE. Curly brackets indicate values considered during hyperparameter selection. The frozen LM encoder and bottleneck projection are fixed for all methods.

Method	Hyperparameter	Values
BitFit	Batch Size	{16, 32}
	Optimizer	AdamW
	Scheduler	Linear Scheduler
	Learning Rate	{1e-4, 3e-4, 1e-3}
	Trainable Parameters	Bias terms only
LoRA	Batch Size	{16, 32}
	Optimizer	AdamW
	Scheduler	Linear Scheduler
	Learning Rate	{1e-4, 3e-4, 1e-3}
	Rank r	{4, 8, 16}
	Scaling α	16
AdaLoRA	Batch Size	{16, 32}
	Optimizer	AdamW
	Scheduler	Linear Scheduler
	Learning Rate	{1e-4, 3e-4, 1e-3}
	Initial / Target Rank	8 / 4
Prefix	Batch Size	{16, 32}
	Optimizer	AdamW
	Scheduler	Linear Scheduler
	Learning Rate	{1e-4, 3e-4, 1e-3}
	Prefix Length	{8}
MLP	Batch Size	{16, 32}
	Optimizer	AdamW
	Scheduler	Linear Scheduler
	Learning Rate	{1e-4, 3e-4, 1e-3}
QAA	Batch Size	{16, 32}
	Optimizer	AdamW
	Scheduler	Linear Scheduler
	Learning Rate	{1e-4, 3e-4, 1e-3}
	Circuit Depth	{1}
	Circuit	$RY \rightarrow$ Ring CNOT
QPA	Batch Size	{16, 32}
	Optimizer	AdamW
	Scheduler	Linear Scheduler
	Learning Rate	{1e-4, 3e-4, 1e-3}
	Quantum Role	Parameter generation
	Representation Encoding	Not used
	Circuit	$RY/RZ \rightarrow$ Ring CNOT $\rightarrow RY$
SQUARE	Primary held-out head	Lin(16 $\rightarrow$ 8)-tanh-Lin(8 $\rightarrow$ 1), with biases
	Validation/backbone head	Lin(20 $\rightarrow$ 8)-tanh-Lin(8 $\rightarrow$ 1), bias-free
	Batch Size	{16, 32}
	Optimizer	AdamW
	Scheduler	Linear Scheduler
	Learning Rate	{1e-4, 3e-4, 1e-3}
	Encoding	Amplitude encoding
	Circuit	$RY/RZ \rightarrow$ Ring CNOT $\rightarrow RY$
	Readout	Probabilities (primary); probabilities + Pauli-Z (V20)
	Circuit Depth	1