

SAFE, PERSISTENT, AND EVOLVING AGENT HARNESS FOR UNDERSTANDING PARTIALLY OBSERVABLE WORLDS

Yisen Gao¹, Yue Guo², Qing Zong¹, Yiwen Guo^{3*}, Yangqiu Song¹

¹The Hong Kong University of Science and Technology

²LIGHTSPEED

³Independent Researcher

{ygaodi}@cse.ust.hk

ABSTRACT

Large language model agents can invoke tools fluently, but enterprise workflows demand more than selecting the right tools: actions must strictly comply with organizational policies, tool feedback often conceals hidden side effects under partial observability, and long-horizon tasks require persistent state tracking across multiple records. To address these challenges, we introduce E-Ledger, a multi-agent harness for safe and persistent execution. E-Ledger employs a code approval layer that checks every proposed action against policy before execution, and maintains a world ledger of verified hidden rules alongside evidence-backed dynamic state. Because hidden rules are typically unknown a priori, we further propose WorldAbduct, an abductive, world-model-driven harness evolution framework. WorldAbduct diagnoses execution trajectories across four complementary views (state consistency, world-observation gap, policy-gate correctness, and goal judgment) to hypothesize latent rules, and verifies them through targeted abductive interactions before integrating them into the ledger. On the enterprise benchmark World of Workflows, E-Ledger with WorldAbduct improves safe task completion across four LLM backbones, outperforming the strongest evolution baseline by 5–15 percentage points. Experiments in ScienceWorld and DiscoveryWorld further show that abductive harness evolution carries over to scientific environments. Our code is available at <https://github.com/HKUST-KnowComp/E-LEDGER-WorldAbduct>.

1 INTRODUCTION

Large language model (LLM) agents increasingly complete multi-step tasks through tool use (Li et al., 2026; Xiao et al., 2026; Fan et al., 2025). By invoking APIs, databases, and software interfaces, they retrieve information, update records, and coordinate workflows (Zhang et al., 2025; Du et al., 2024; Bai et al., 2025). Enterprise applications (Nisar, 2025; Prabhakar et al., 2025) extend these capabilities to incident management, employee administration, asset operations, and knowledge-base maintenance.

Enterprise workflows pose three interrelated challenges. *First, actions are governed by strict policies, permissions, and approval requirements*, so a locally plausible action may still be impermissible. Whether an action is safe depends on record states, user permissions, and approval prerequisites. *Second, the environment is only partially observable*: tool responses reveal an interaction surface rather than the full transition dynamics, including hidden, cross-record, or delayed effects. Thus, a successful response does not necessarily confirm the resulting state, nor does an omitted field imply that it is absent or unchanged. *Third, tasks require long-horizon state tracking* across multiple objects, reads, and writes. Losing confirmed facts or outstanding subgoals can lead to repeated queries, incorrect actions, or premature termination. These challenges interact: in Fig. 1, a hidden priority change after assigning an asset to Alice makes a subsequent transfer violate policy. Safe execution therefore requires both persistent state tracking and knowledge of hidden transitions.

*Yiwen Guo is the corresponding author.




Figure 1: An enterprise workflow illustrating how hidden asset-priority changes can make an otherwise plausible transfer violate policy.

Directly deploying an agent in such enterprise environments remains unreliable. Previous work (Gupta et al., 2026) finds that agents often achieve low task-completion and safe-execution rates in enterprise environments: they not only fail to reach the requested end state, but can also violate constraints while attempting to do so. At the same time, agent harnesses (Lee et al., 2026; Yao et al., 2026; Meng et al., 2026) have emerged as a promising way to augment a base agent with structured guidance, persistent state maintenance, verification, and control around its tool calls. Code-based harnesses (Bai et al., 2026; Lin et al., 2026; Ning et al., 2026) further make environment reasoning and execution control explicit and executable, so that constraints are enforced by code rather than by the model’s own reasoning. For enterprise agents, this suggests combining policy checks with persistent state maintenance. However, even a correctly implemented check is only as good as the state it receives: an unobserved side effect can make that state stale and an apparently compliant action unsafe. A harness must therefore also learn the world that lies behind the tool interface.

We introduce E-LEDGER, a safe and persistent harness that separates runtime control from environment-specific knowledge. It compiles known organizational policies into code and routes every proposed action through pre-execution approval. The code can permit an action, request evidence or an approval prerequisite, or block execution, so the model cannot bypass a known policy through its own reasoning. A complementary world ledger maintains *static world knowledge* of hidden rules and side effects, alongside *dynamic world state* recording evidence-backed changes to task-relevant entities and goals. Together, these layers make constraints, learned dynamics, and execution progress available throughout the workflow.

Much of this static knowledge, however, is unknown in advance. An action’s hidden effect may only become visible several steps later, when the observed state or outcome contradicts expectations. The agent must then identify the earlier trigger and decide whether the effect reflects a stable rule or an isolated event. Reliable attribution is essential for turning trajectories into reusable knowledge, especially when several actions could explain the same outcome.

To address these challenges, we propose WorldAbduct, a world-model-driven evolution strategy that uses abductive reasoning to recover hidden environment rules and improve E-LEDGER. The evolution process diagnoses execution trajectories from four complementary perspectives. State consistency keeps state predictions and the dynamic ledger aligned with observable tool feedback, helping the agent fit the part of the world it can directly observe. World-observation-gap analysis then focuses on the unobservable part of the world and seeks to recover hidden effects that are absent from the tool interface. Policy-gate correctness improves the enforcement of known constraints, while goal judgment helps the agent distinguish successful completion from premature termination.

The outputs of these four perspectives are then divided into two types: direct modifications to the harness, and hypotheses about hidden rules that require further validation. A dedicated abduction agent receives the latter hypotheses and designs targeted interactions to verify or revise them; only supported rules enter the static world layer. Our method achieves the highest safe task completion rate on the enterprise workflow benchmark WOW (Gupta et al., 2026) across four LLM backbones, and also performs strongly in the scientific discovery environments ScienceWorld (Wang et al., 2022) and DiscoveryWorld (Jansen et al., 2024). Our contributions can be summarized as:

- We introduce E-LEDGER, a safe and persistent enterprise agent harness that combines code-based policy enforcement with a world ledger layer that maintains static knowledge of hidden rules and dynamic state for task-relevant information.
- We propose WorldAbduct, a world-model-driven evolution method that uses four diagnostic views to fit the observable world and hypothesize unobservable hidden rules, then validates these hypotheses through abductive interaction to build a reusable world model.
- Experiments on the enterprise benchmark WOW show substantial improvements in both task completion and safety, and results on ScienceWorld and DiscoveryWorld show that the approach extends beyond enterprise workflows.

2 RELATED WORK

Enterprise Agents LLM agents increasingly complete multi-step tasks by interleaving reasoning with actions and observations from external tools (Yao et al., 2022). However, enterprise deployment introduces challenges beyond general tool use (Nisar, 2025): actions operate over interconnected records, must obey organization-specific policies, and can trigger workflow side effects not revealed by an immediate tool response. WorkArena (Drouin et al., 2024) evaluates agents on common ServiceNow knowledge-work tasks, while the World of Workflows benchmark (Gupta et al., 2026) makes the additional challenge of hidden, cascading state changes explicit in partially observable workflows. These settings expose a gap between completing a visible interaction and establishing a safe final enterprise state.

Self-Evolving Agent Harnesses An agent harness is the external control layer around a base LLM model that organizes context, tools, memory, orchestration, and output handling. Rather than treating this control layer as fixed, recent work lets it evolve with execution experience and task feedback. Some approaches convert failed attempts into natural-language guidance or use textual feedback to optimize components of a compound LLM system (Shinn et al., 2023; Yuksekogonul et al., 2024). Others distill trajectory experience across multiple control dimensions or iteratively improve harness code using traces and evaluations (Huang et al., 2026; Lee et al., 2026). Some systems further perform test-time adaptation Nie et al. (2026), using feedback from the current task to revise their control strategy online. Another line of work Zhang et al. (2026); Dong et al. (2026) views the harness as a world model, evolving it to improve the agent’s understanding of environment dynamics and hidden state transitions. Our approach connects these two directions: four diagnostic views identify execution gaps, and targeted environment interactions test candidate hidden rules before the harness uses them for state tracking and policy approval.

3 METHOD

3.1 TASK DEFINITION

Following prior work (Gupta et al., 2026), we model the task environment as a partially observable Markov decision process (POMDP). Each constraint-based task is defined by $M = (U, P, S, A, T, O, \Omega)$. Here, U denotes the user query, including the task description; P is the constraint policy; S is the complete enterprise database state; A is the discrete action space; $T : S \times A \rightarrow S$ is the state-transition function; O is the space of tool responses; and $\Omega : S \times A \rightarrow O$ is the environment feedback function. At step t , the agent selects an action $a_t \in A$, consisting of an MCP tool and its parameters. We define $P(s_t, a_t) = 1$ if a_t satisfies the policy at state s_t , and $P(s_t, a_t) = 0$ otherwise. Under partial observability, the executing agent receives




Figure 2: Overview of E-Ledger (top) and WorldAbduct (bottom).

$o_{t+1} = \Omega(s_t, a_t) \in O$, which may omit state changes, cross-record effects, or transition rules induced by its actions.

Let $\tau = (o_0, a_0, o_1, \dots, a_{L-1}, o_L)$ be a trajectory. We write $C_U(\tau) = 1$ when it reaches the requested goal or correctly identifies that the task cannot be completed safely, as required by WOW’s infeasible tasks (Appendix A.2). The objective is

$$J(\tau) = C_U(\tau) \prod_{t=0}^{L-1} P(s_t, a_t), \quad (1)$$

where $s_{t+1} = T(s_t, a_t)$. Thus $J(\tau) = 1$ denotes safe task success. Writing $h_t = (o_0, a_0, o_1, \dots, a_{t-1}, o_t)$ for the available interaction history, the agent selects

$$a_t = \arg \max_{a \in A} p_{\theta, H}(a \mid U, P, h_t), \quad (2)$$

where θ denotes the model parameters and H the harness that organizes the history, world knowledge, and current task state.

3.2 MULTI-AGENT HARNESS ARCHITECTURE

As shown in Fig. 2, E-LEDGER is a multi-agent harness for partially observable environments. It maintains a world ledger for static hidden rules and dynamic task state, and at each interaction a task agent proposes an action, a policy-context agent supplies the evidence required for evaluation, a code-based approval layer checks it against organizational policies, and a state-tracking agent updates the ledger from the tool response.

World Ledger layer. To represent both hidden environment dynamics and task progress, the world ledger layer consists of *static world knowledge* $\mathcal{W}_S$ and *dynamic world state* $\mathcal{W}_D$. $\mathcal{W}_S$ stores hidden rules and tool-induced side effects that are absent from immediate tool feedback; for example, an asset change may also modify its priority. Formally, each rule is $r : (a, s, c) \longrightarrow \Delta s$, where c is its applicability condition and Δs is the induced state change. In contrast, $\mathcal{W}_D$ maintains a global, schema-aligned store of task-relevant information for the current task, including identifiers, attributes, and relations extracted from tool feedback. It is updated incrementally after each interaction, preserving the state needed for long-horizon execution without reconstructing it from the entire trajectory.

Task agent. The task agent chooses an action from the user query, policy, available tools, static rules, dynamic ledger, and interaction history. It also predicts the resulting state change, which is retained for comparison with observations and subsequent evolution:

$$(a_t, \widehat{\Delta s}_t) = \mathcal{A}_\theta(U, P, A, \mathcal{W}_S, \mathcal{W}_D^t, h_t), \quad (3)$$

where $a_t \in A$ is the proposed action and $\widehat{\Delta s}_t$ is its predicted state change.

Code approval layer. To approve a proposed action using the relevant policy context, we compile each textual policy into an executable program P_{code} and introduce a policy-context agent. Given the dynamic world state $\mathcal{W}_D^t$, the policy-context agent extracts and binds the policy-relevant fields needed for approval, such as a target user’s active-incident count or an asset’s cost. The approval code then evaluates the proposed action a_t together with this extracted context, rather than relying on the task agent’s claims. It returns one of four decisions: `{execute, query, probe, block}`. `execute` indicates that the action has passed approval and can be carried out. `query` or `probe` indicates that the available evidence is insufficient to determine whether the action complies with the policy, requiring additional information before approval. `block` indicates that the action violates the policy and must be replaced. Decisions other than `execute` are fed back to the task agent, which revises the proposed action accordingly. This approval process is non-bypassable.

Feedback and dynamic state update. After approval, the environment returns $o_{t+1} = \Omega(s_t, a_t)$. A response may confirm a creation or transfer without returning the resulting field values, or contain many irrelevant fields. The state-tracking agent $\mathcal{R}_\theta$ interprets the response and extracts task-relevant updates:

$$\mathcal{W}_D^{t+1} = \mathcal{R}_\theta(\mathcal{W}_D^t, a_t, o_{t+1}, \mathcal{W}_S). \quad (4)$$

Applicable static rules help interpret indirect effects. Updates retain their supporting evidence, while conflicts and unresolved fields are recorded for subsequent verification. The task agent then acts on the updated ledger and interaction history.

3.3 WORLDABDUCT: ABDUCTIVE WORLD-MODEL-DRIVEN HARNESS EVOLUTION

The runtime above relies on static world knowledge $\mathcal{W}_S$, which is empty at initialization: hidden rules appear neither in the policy nor in immediate tool feedback. As shown at the bottom of Fig. 2, WorldAbduct addresses this gap through world-model-driven harness evolution. It analyzes each execution from four complementary perspectives and produces either direct harness updates or hidden-rule hypotheses. The latter are passed to a hidden-rule abduction agent for validation before entering the static world layer.

3.3.1 EVOLUTION PROPOSAL AGENT

The evolution proposal agent $\mathcal{E}_\phi$ reads the task, policy, execution trajectory, task-agent predictions, tool feedback, and current harness. For each perspective, it identifies the corresponding gap and proposes the smallest appropriate harness update or hidden-rule hypothesis:

State consistency. State consistency first asks whether the agent can fit the part of the world that is observable. At each step, the task agent’s predicted state change $\widehat{\Delta s}_t$ should agree with the task-relevant tool feedback o_{t+1} . The state-tracking agent should record the same task-relevant facts in the ledger. It should not omit observable fields or add unrelated fields that are not supported by o_{t+1} or an applicable verified rule. Formally, the evolution proposal agent assesses this consistency at each step t :

$$\mathcal{J}_s = \mathcal{E}_\phi(\widehat{\Delta s}_t, o_{t+1}, \mathcal{W}_D^{t+1}, \mathcal{W}_S). \quad (5)$$

World observation gap. State consistency helps the agent predict and record the observable world, but it cannot recover rules that never appear in the tool response. We therefore use the world observation gap objective to identify parts of the trajectory that may reveal the unobservable part. The evolution proposal agent focuses on state information that can change the outcome of the policy code. For example, if a knowledge asset has a flag that is false before an action and becomes true later, an earlier action may have triggered this change even if the relevant side effect was absent

from the tool response. The agent identifies the actions that may have caused the change and formulates corresponding hidden-rule hypotheses for later validation. Its input is the complete trajectory, the executable policy code, and the dynamic world state:

$$\mathcal{J}_o = \mathcal{E}_\phi(\tau, P_{\text{code}}, \mathcal{W}_D). \quad (6)$$

where τ denotes the trajectory. The output provides hypotheses about suspicious actions and the effects they may have caused.

Policy-gate correctness. Policy-gate correctness aims to ensure that the agent’s proposed actions satisfy the policy before execution. An action that is blocked or returned as `query` requires an additional repair or information-gathering step, which increases the interaction cost. We therefore use the gate log to audit proposals that did not pass approval and ask the evolution proposal agent to identify why each action failed the code gate and how the agent or the policy context should be improved. Let $\mathcal{G}^-$ contain the non-approved proposals and their ledger contexts. This diagnostic objective is written as

$$\mathcal{J}_p = \mathcal{E}_\phi(\tilde{a}, \mathcal{W}_D, P_{\text{code}}), \quad (\tilde{a}, \mathcal{W}_D) \in \mathcal{G}^-. \quad (7)$$

The resulting proposal improves action selection and evidence binding, helping the agent satisfy prerequisites and avoid repeated approval failures.

Goal judgment. Goal judgment evaluates the full task using the query, policy, a compact trajectory, and evaluator feedback ρ_{eval} . It diagnoses premature termination, unmet goals, and violations missed by the approval layer, then considers whether safe completion or a justified refusal remains possible:

$$\mathcal{J}_g = \mathcal{E}_\phi(U, P, \tau, \rho_{\text{eval}}). \quad (8)$$

Together, the four views form the world-model-driven objective

$$\mathcal{J}_{\text{WM}} = (\mathcal{J}_s, \mathcal{J}_o, \mathcal{J}_p, \mathcal{J}_g), \quad (9)$$

whose components yield two kinds of proposals. The first is a direct update $\Delta H_{\mathcal{W}_S}$ to the other harness components, such as the task-agent protocol, state tracking, policy context, or policy code. The second is a hypothesis h about a hidden enterprise rule or side effect, which enters $\mathcal{W}_S$ only after validation. World-observation-gap analysis proposes hidden rules, while the other views can propose both kinds (Appendix A.3). Thus, evolution improves both the editable harness components and the harness’s knowledge of the hidden world. In each round, direct updates are applied, hypotheses are passed to the abduction agent below, and validation tasks select the resulting harness.

3.3.2 HIDDEN-RULE ABDUCTION AGENT

The hidden-rule abduction agent aims to infer the corresponding hidden rules from observed trajectories through abductive reasoning. Given the user query U , the policy P , the action space A , the source trajectory τ , and an initial hypothesis h , it designs a validation action sequence $\alpha_{1:K} = (\alpha_1, \dots, \alpha_K)$ in a fresh environment. Each $\alpha_k \in A$ is an action selected using the available tools; the agent observes the resulting feedback and updates its belief about h . It can accept the hypothesis when the evidence supports it, revise it when the evidence suggests a different rule, or leave it unresolved when verification is inconclusive. We denote the abduction agent by $\mathcal{B}_\phi$, where ϕ denotes its model parameters. Validation actions are chosen adaptively: given the current hypothesis h and validation history τ^{val} , each call returns a decision and its payload:

$$\mathcal{B}_\phi(U, P, A, \tau, h, \tau^{\text{val}}) \rightarrow (d, \text{payload}), \quad (10)$$

where $d \in \{\text{act}, \text{revise}, \text{verified}, \text{unresolved}\}$. An action extends the validation history; a revision updates h . A verified result supplies the rule, applicability condition, and supporting evidence, which are retained in $\mathcal{W}_S$ as $r : (a, s, c) \rightarrow \Delta s$.

4 EXPERIMENTS

4.1 EXPERIMENTAL SETUP

Datasets and evaluation protocol. We use World of Workflows (WOW) (Gupta et al., 2026) as the primary enterprise evaluation benchmark, and use the general scientific environments ScienceWorld

Table 1: Enterprise-agent task experiment on WOW. (Dark blue and light blue denote the best and second-best performance results within each backbone, respectively)

Backbone	Method		Performance			Efficiency	
	Harness	Evolution	STCR	TCR	PSR	Steps	Cost (\$)
GPT-5.6-Terra	ReAct	–	35.0	55.0	75.0	13.3	1.36
	E-LEDGER	–	35.0	35.0	100.0	20.6	2.78
	E-LEDGER	MemoHarness	50.0	50.0	100.0	20.8	3.00
	E-LEDGER	WorldEvolver	45.0	55.0	75.0	13.4	1.72
	E-LEDGER	WorldAbduct	65.0	65.0	100.0	22.4	3.75
Kimi-K3	ReAct	–	20.0	40.0	65.0	10.6	1.70
	E-LEDGER	–	25.0	35.0	85.0	17.4	3.90
	E-LEDGER	MemoHarness	65.0	85.0	80.0	25.9	6.84
	E-LEDGER	WorldEvolver	45.0	55.0	80.0	16.7	3.81
	E-LEDGER	WorldAbduct	70.0	75.0	95.0	22.0	8.10
GLM-5.3-Flash	ReAct	–	35.0	55.0	70.0	13.4	0.12
	E-LEDGER	–	30.0	45.0	85.0	17.4	0.23
	E-LEDGER	MemoHarness	65.0	75.0	90.0	25.5	0.45
	E-LEDGER	WorldEvolver	45.0	55.0	85.0	13.7	0.16
	E-LEDGER	WorldAbduct	75.0	80.0	95.0	20.9	0.52
DeepSeek-V4-Pro	ReAct	–	25.0	50.0	55.0	13.8	0.41
	E-LEDGER	–	50.0	55.0	95.0	20.5	0.69
	E-LEDGER	MemoHarness	75.0	90.0	85.0	26.9	1.14
	E-LEDGER	WorldEvolver	60.0	70.0	80.0	19.6	0.68
	E-LEDGER	WorldAbduct	80.0	85.0	95.0	22.5	0.90

(Wang et al., 2022) and DiscoveryWorld (Jansen et al., 2024) to assess the generality of WorldAbduct beyond enterprise workflows. All benchmarks use a 2:1:2 training, validation, and test split; training trajectories drive harness evolution, validation tasks select harness updates, and test tasks are held out for final evaluation. For WOW, we report safe task completion rate (STCR), task completion rate (TCR), policy safety rate (PSR), interaction steps, and test-time inference cost in USD. TCR includes correct refusal of infeasible tasks, and STCR additionally requires a compliant trajectory (Appendix A.2). For ScienceWorld, we report task success (Success), environment score (Score), and interaction steps; and for DiscoveryWorld, task success (Success), official procedural score (Procedural), and interaction steps. Further dataset details are provided in Appendix A.1.

Baselines. We compare with ReAct (Yao et al., 2022), which directly reasons and acts without an external harness, and with two evolution strategies applied to the same initial harness as our method. MemoHarness (Huang et al., 2026) updates six harness components, namely context, tools, generation, orchestration, memory, and output handling, using case-level diagnoses and distilled global patterns. WorldEvolver (Zhang et al., 2026) treats evolution as world-model refinement by constructing an action-level state-change library from observable trajectory evidence; unlike WorldAbduct, it does not test hidden-rule hypotheses through targeted interactions.

4.2 ENTERPRISE TASK PERFORMANCE

We evaluate the enterprise agents with four LLM backbones: DeepSeek-V4-Pro (Xu et al., 2026), GLM-5.3-Flash (Zeng et al., 2026), GPT-5.6-Terra, and Kimi-K3 (Team et al., 2026). Implementation details and agent prompts are provided in Appendix A.2. Table 1 reports their performance. Compared with ReAct, E-LEDGER consistently improves PSR by preventing locally plausible but disallowed writes from reaching the environment. The effect is clearest for DeepSeek-V4-Pro, where ReAct and E-LEDGER achieve similar TCR, but E-LEDGER doubles STCR because its remaining failures are mainly incomplete rather than unsafe.




Figure 3: Left: each evolution view occupies a different TCR–PSR region. Right: adding hidden rules improves localization accuracy on every backbone.

Across evolution methods, WorldAbduct achieves the highest STCR on all four backbones, exceeding the strongest baseline, MemoHarness, by 5–15 percentage points. WorldEvolver yields smaller gains, since its effect library only records changes visible in tool feedback. The advantage of WorldAbduct comes largely from safety: on Kimi and DeepSeek, MemoHarness reaches a slightly higher TCR but violates policy more often, whereas validated hidden rules keep WorldAbduct at 95% PSR. GPT-5.6-Terra is comparatively conservative: when an evolved task action raises a policy concern, it often stops instead of searching for a compliant repair. This behavior preserves a 100% PSR with E-LEDGER but limits further gains in TCR. Giving both baselines an additional evolution round leaves their GLM results unchanged (Appendix F), so the gap is not due to the number of rounds. WorldAbduct also uses fewer steps than MemoHarness on three of the four backbones at a comparable test-time cost.

4.3 ABLATION STUDIES

We conduct two complementary ablations with GLM-5.3-Flash. The runtime ablation removes individual components from the fully evolved harness, while the evolution ablation starts from E-LEDGER and isolates each diagnostic view and the abduction step that verifies its hypotheses.

For harness ablation, Table 2 reports STCR, TCR, and PSR after removing each component in E-Ledger: Removing the static world layer $\mathcal{W}_S$ is the most damaging change: after WorldAbduct, this layer stores the verified hidden rules that make side effects and constraints available at runtime; without it, the agent is again unaware of side effects that tool responses do not reveal. Removing state tracking, which maintains the dynamic world state $\mathcal{W}_D$, also hurts, because on long-horizon workflows the agent can lose the current record state mid-episode and later take incorrect or unsafe actions. Removing code approval layer leaves task completion rate unchanged but lowers policy safety rate and therefore safe task completion rate: even with hidden rules and textual policy already present, the model can still take a disallowed action to finish a task. The code gate is what turns known constraints into enforced ones.

Variant	STCR	TCR	PSR
Full	75.0	80.0	95.0
w/o $\mathcal{W}_S$	40.0	55.0	85.0
w/o $\mathcal{W}_D$	65.0	75.0	90.0
w/o Code Approval	<u>70.0</u>	80.0	<u>90.0</u>

Table 2: Harness ablation. (**Bold**: best, underline: second-best).

Fig. 3a isolates the contribution of each evolution view and of abduction (detailed results are provided in Appendix B). Single-view variants retain abduction, whereas the Without Abduction variant writes the four views’ hypotheses directly into $\mathcal{W}_S$ without live verification. State consistency and policy-gate correctness provide limited gains because they focus on observable state and known constraints, respectively. Goal judgment yields the largest completion gain but also introduces unsafe actions when optimized alone. World-observation gap reaches the full method’s policy safety rate by recovering hidden side effects, but its completion gain remains modest without improved observable-state tracking. Removing abduction does not reduce completion, but its unverified hy-

Table 3: Results on ScienceWorld and DiscoveryWorld. (**Bold**: best, underline: second-best).

Method	ScienceWorld			DiscoveryWorld		
	Success	Score	Steps	Success	Procedural	Steps
ReAct	25.0	43.4	37.2	43.8	0.68	62.0
MemoHarness	58.3	68.2	21.0	75.0	0.82	<u>27.1</u>
WorldEvolver	<u>70.0</u>	<u>68.6</u>	16.6	<u>87.5</u>	0.90	32.5
WorldAbduct	71.7	75.5	<u>18.4</u>	93.8	<u>0.88</u>	22.7

potheses can be too narrow or too broad, leading to unsafe actions and lower policy safety. The full method combines these complementary effects: it matches the best PSR while retaining 80% TCR, and achieves the highest STCR.

4.4 HIDDEN-RULE QUALITY AND VERIFICATION

We assess hidden-rule quality using WOW’s policy-violation localization task, which contains 50 action sequences. Given a sequence, the agent must return the exact set of violating action indices, including an empty set when no action violates a policy. We compare a prompt-only agent with one augmented by the frozen static world layer $\mathcal{W}_S$. Fig. 3b shows that the evolved rules improve localization for every backbone by 0.10–0.22 absolute points, indicating that they capture policy-relevant hidden effects.

We further audit the evolved rules manually against the gold hidden workflows of WOW (Appendix C). Across the four backbones, the frozen ledgers contain 54 facts, of which 49 are fully correct and five are partially correct: they capture the right mechanism but miss part of its applicability conditions. None is incorrect.

Verification does more than confirm hypotheses. Across backbones, abduction launches 11–23 checks, each using 13.3–19.1 environment interactions on average (Appendix E). Of the 64 checks, 50 are accepted directly, eight are accepted only after revision, and six remain unresolved. In the cost-revaluation case (Appendix D), incomplete evaluator feedback initially suggests a \$10,000 threshold for an automatic cost increase. Probes below that threshold overturn this explanation and recover a creation-time cost transformation, while a separate update test shows that an explicit correction persists. Verification also matters downstream: on GLM, removing it leaves TCR at 80% but lowers PSR from 95% to 85%, reducing STCR by 10 percentage points.

4.5 APPLICATION TO SCIENTIFIC ENVIRONMENTS

We evolve the harness separately in ScienceWorld and DiscoveryWorld. Since these environments have no organizational policy, we drop code approval and the policy-gate view, and evolve with the remaining three views. Environment-specific prompts appear in Appendix A.2. Table 3 shows that all evolution methods outperform ReAct while using fewer interactions. WorldAbduct achieves the highest success on both benchmarks, the best ScienceWorld score, and the fewest DiscoveryWorld steps, using about a third of ReAct’s interactions there. WorldEvolver remains competitive, particularly in ScienceWorld success and DiscoveryWorld procedural score. These results indicate that verifying hypotheses through interaction is also useful when the hidden dynamics are physical rather than organizational.

5 CONCLUSION

We presented E-LEDGER, a safe and persistent agent harness for enterprise workflows under partial observability. Its world ledger combines static knowledge of hidden rules with dynamic task-state tracking, while code-based policy approval enforces known organizational constraints. We further introduced WorldAbduct, which diagnoses execution from four complementary views and uses environment-grounded abduction to validate hidden rules before incorporating them into the harness. Experiments on WOW show substantial improvements in task completion and safety, and

results on ScienceWorld and DiscoveryWorld show that the approach extends beyond enterprise environments. Together, these results highlight the value of coupling persistent execution control with active experimentation that refines the agent’s knowledge of hidden transitions.

REFERENCES

- Jiaxin Bai, Zihao Wang, Yukun Zhou, Hang Yin, Weizhi Fei, Qi Hu, Zheye Deng, Jiayang Cheng, Tianshi Zheng, Hong Ting Tsang, et al. Top ten challenges towards agentic neural graph databases. *arXiv preprint arXiv:2501.14224*, 2025.
- Jiaxin Bai, Yue Guo, Yifei Dong, Jiaxuan Xiong, Tianshi Zheng, Yixia Li, Tianqing Fang, Yufei Li, Yisen Gao, Haoyu Huang, et al. Patchworld: Gradient-free optimization of executable world models. *arXiv preprint arXiv:2605.30880*, 2026.
- Guanting Dong, Junting Lu, Junjie Huang, Wanjuan Zhong, Longxiang Liu, Shijue Huang, Zhenyu Li, Yang Zhao, Xiaoshuai Song, Xiaoxi Li, et al. Agent-world: Scaling real-world environment synthesis for evolving general agent intelligence. *arXiv preprint arXiv:2604.18292*, 2026.
- Alexandre Drouin, Maxime Gasse, Massimo Caccia, Issam H Laradji, Manuel Del Verme, Tom Marty, Léo Boisvert, Megh Thakkar, Quentin Cappart, David Vazquez, et al. Workarena: How capable are web agents at solving common knowledge work tasks? *arXiv preprint arXiv:2403.07718*, 2024.
- Yu Du, Fangyun Wei, and Hongyang Zhang. Anytool: Self-reflective, hierarchical agents for large-scale api calls. *arXiv preprint arXiv:2402.04253*, 2024.
- Shiqing Fan, Xichen Ding, Liang Zhang, and Linjian Mo. Mcptoolbench++: A large scale ai agent model context protocol mcp tool use benchmark. *arXiv preprint arXiv:2508.07575*, 2025.
- Lakshya Gupta, Litao Li, Yizhe Liu, Sriram Ganapathi Subramanian, Kaheer Suleman, Zichen Zhang, Haoye Lu, and Sumit Pasupalak. World of workflows: a benchmark for bringing world models to enterprise systems. *arXiv preprint arXiv:2601.22130*, 2026.
- Yue Huang, Wenjie Wang, Han Bao, Yuchen Ma, Xiaonan Luo, Yi Nian, Haomin Zhuang, Zheyuan Liu, Yue Zhao, and Xiangliang Zhang. Memoharness: Agent harnesses that learn from experience. *arXiv preprint arXiv:2607.14159*, 2026.
- Peter A. Jansen, Marc-Alexandre Côté, Tushar Khot, Erin Bransom, Bhavana Dalvi Mishra, Bodhisattwa Prasad Majumder, Oyvind Tafjord, and Peter Clark. Discoveryworld: A virtual environment for developing and evaluating automated scientific discovery agents. In Amir Globersons, Lester Mackey, Danielle Belgrave, Angela Fan, Ulrich Paquet, Jakub M. Tomczak, and Cheng Zhang (eds.), *Advances in Neural Information Processing Systems 37: Annual Conference on Neural Information Processing Systems 2024, NeurIPS 2024, Vancouver, BC, Canada, December 10 - 15, 2024*, 2024. URL http://papers.nips.cc/paper_files/paper/2024/hash/13836f251823945316ae067350a5c366-Abstract-Datasets_and_Benchmarks_Track.html.
- Yoonho Lee, Roshen Nair, Qizheng Zhang, Kangwook Lee, Omar Khattab, and Chelsea Finn. Meta-harness: End-to-end optimization of model harnesses. *arXiv preprint arXiv:2603.28052*, 2026.
- Xiaoxi Li, Wenxiang Jiao, Jiarui Jin, Guanting Dong, Jiajie Jin, Yinuo Wang, Hao Wang, Yutao Zhu, Ji-Rong Wen, Yuan Lu, et al. Deepagent: A general reasoning agent with scalable toolsets. In *Proceedings of the ACM Web Conference 2026*, pp. 2219–2230, 2026.
- Jiahang Lin, Shichun Liu, Chengjun Pan, Lizhi Lin, Shiha Dou, Zhiheng Xi, Xuanjing Huang, Hang Yan, Zhenhua Han, Tao Gui, et al. Agentic harness engineering: Observability-driven automatic evolution of coding-agent harnesses. *arXiv preprint arXiv:2604.25850*, 2026.
- Qianyu Meng, Yanan Wang, Liyi Chen, Yihang Li, Wei Wu, Wenyan Jiang, Qimeng Wang, Chengqiang Lu, Yan Gao, Yi Wu, et al. Agent harness for large language model agents: A survey. 2026.
- Jun Nie, Yonggang Zhang, Jun Song, Qianshu Cai, Dahai Yu, Yike Guo, Xinmei Tian, and Bo Han. Tthe: Test-time harness evolution. *arXiv preprint arXiv:2607.08124*, 2026.
- Xuying Ning, Katherine Tieu, Dongqi Fu, Tianxin Wei, Zihao Li, Yuanchen Bei, Jiaru Zou, Mengting Ai, Zhining Liu, Ting-Wei Li, et al. Code as agent harness. *arXiv preprint arXiv:2605.18747*, 2026.

- Karan Nisar. Why enterprise agent deployments fail: A field taxonomy. *International Journal of Computer Technology and Electronics Communication*, 8(5):11592–11605, 2025.
- Akshara Prabhakar, Roshan Ram, Zixiang Chen, Silvio Savarese, Frank Wang, Caiming Xiong, Huan Wang, and Weiran Yao. Enterprise deep research: Steerable multi-agent deep research for enterprise analytics. *arXiv preprint arXiv:2510.17797*, 2025.
- Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning. *Advances in neural information processing systems*, 36:8634–8652, 2023.
- Kimi Team, Tongtong Bai, Yifan Bai, Yiping Bao, Jianfeng Cai, Xinyuan Cai, Peizhou Cao, Yuxuan Cao, Ziwei Chai, Y Charles, et al. Kimi k3: Open frontier intelligence. *arXiv preprint arXiv:2607.24653*, 2026.
- Ruoyao Wang, Peter Jansen, Marc-Alexandre Côté, and Prithviraj Ammanabrolu. Scienceworld: Is your agent smarter than a 5th grader? In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pp. 11279–11298, 2022.
- Qiao Xiao, Haochen Shi, Yisen Gao, Wenbin Hu, Huihao Jing, Tianshi Zheng, Baixuan Xu, Ziheng Zhang, Weiqi Wang, Haoran Li, et al. Sing: Synthetic intention graph for scalable active tool discovery in llm agents. *arXiv preprint arXiv:2606.16591*, 2026.
- Anyi Xu, Bangcai Lin, Bing Xue, Bingxuan Wang, Bingzheng Xu, Bochao Wu, Bowei Zhang, Chaofan Lin, Chen Dong, Chenchen Ling, et al. Deepseek-v4: Towards highly efficient million-token context intelligence. *arXiv preprint arXiv:2606.19348*, 2026.
- Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. React: Synergizing reasoning and acting in language models. *arXiv preprint arXiv:2210.03629*, 2022.
- Yilun Yao, Xinyu Tan, Chao-Hsuan Liu, Yaoming Li, Zhengyang Wang, Wenhan Yu, Zhewen Tan, Yuxuan Tian, Guangxiang Zhao, Lin Sun, et al. Harness-bench: Measuring harness effects across models in realistic agent workflows. *arXiv preprint arXiv:2605.27922*, 2026.
- Mert Yuksekgonul, Federico Bianchi, Joseph Boen, Sheng Liu, Zhi Huang, Carlos Guestrin, and James Zou. Textgrad: Automatic “differentiation” via text. *arXiv preprint arXiv:2406.07496*, 2024.
- Aohan Zeng, Xin Lv, Zhenyu Hou, Zhengxiao Du, Qinkai Zheng, Bin Chen, Da Yin, Chendi Ge, Chenghua Huang, Chengxing Xie, et al. Glm-5: from vibe coding to agentic engineering. *arXiv preprint arXiv:2602.15763*, 2026.
- Chaoyun Zhang, Shilin He, Liqun Li, Si Qin, Yu Kang, Qingwei Lin, Saravan Rajmohan, and Dongmei Zhang. Api agents vs. gui agents: Divergence and convergence. *arXiv preprint arXiv:2503.11069*, 2025.
- Xuan Zhang, Wenxuan Zhang, See-Kiong Ng, and Yang Deng. Self-evolving world models for llm agent planning. *arXiv preprint arXiv:2606.30639*, 2026.

A MORE DETAILS

A.1 DATASET DETAILS

We evaluate on three interactive benchmarks that feature distinct forms of partial observability, where agents can only observe limited local feedback rather than the complete underlying state or transition dynamics. **World of Workflows (WOW)** (Gupta et al., 2026) reflects enterprise partial observability governed by opaque workflow dynamics: tool responses only return surface-level execution feedback (e.g., operation success), while backend business rules trigger unobserved cross-table cascades, permission adjustments, and delayed side effects across interconnected databases. WOW contains 50 tasks spanning 10 task types, each with five variants. For each type, we use the

first two variants for training, the third for validation, and the last two for testing, giving 20/10/20 tasks. The test variants are held out from evolution. **ScienceWorld** (Wang et al., 2022) manifests partial observability through spatial constraints and latent physical states: the agent only receives local textual descriptions of its current room or inspected objects, leaving unexplored locations, container contents, and internal thermodynamic or chemical states hidden from direct observation. We use 150 tasks, split into 60 training, 30 validation, and 60 test tasks. For each of the 30 task types, we take the first two variations from the environment’s training list, the first variation from its development list, and the first two variations from its test list. We preserve the supplied ordering without shuffling. **DiscoveryWorld** (Jansen et al., 2024) represents partial observability within black-box scientific systems: the agent only perceives local sensor readings or experimental outcomes, while the underlying causal mechanisms, governing hypotheses, and latent procedural rules must be inferred through interaction. We use eight discovery themes at Easy difficulty, with seeds 0 and 1 for training, 2 for validation, and 3 and 4 for testing. This gives 40 episodes split into 16/8/16. Across all three benchmarks, training trajectories are used for harness evolution, validation tasks select the resulting updates, and held-out test tasks serve for final evaluation.

A.2 IMPLEMENTATION DETAILS AND AGENT PROMPTS

The task horizon is 50 steps on World of Workflows and ScienceWorld, and 100 steps on DiscoveryWorld. During training-time harness evolution, we run up to 3 evolution rounds. The hidden-rule abduction agent receives the same action budget as the task horizon: 50 actions per hypothesis on World of Workflows and ScienceWorld, and 100 on DiscoveryWorld. It interacts with a fresh sandbox and admits a hypothesis into the static world layer $\mathcal{W}_S$ only after that interaction supports it.

Backbones and harness selection. Both ScienceWorld and DiscoveryWorld experiments use GLM-5.3-Flash. For WOW, we select the harness with the highest validation STCR, retaining the newer version when scores are tied.

Task completion and safe refusal. WOW includes three task categories pre-labeled as infeasible under the policy and permission constraints. For a task with this label, the evaluator sets the completion indicator to one when the agent returns `task_cannot_be_completed=true`. This check evaluates the refusal decision against the task label; it does not score the accompanying explanation. For feasible tasks, completion requires reaching the requested final state. Thus, $C_U(\tau)$ in Section 3.1 covers both goal achievement and label-consistent refusal.

For N evaluation tasks, let C_i denote this completion indicator and $S_i = \prod_t P(s_t^{(i)}, a_t^{(i)})$ indicate that all executed actions respect policy and permission constraints. We report

$$\text{TCR} = \frac{100}{N} \sum_{i=1}^N C_i, \quad \text{PSR} = \frac{100}{N} \sum_{i=1}^N S_i, \quad \text{STCR} = \frac{100}{N} \sum_{i=1}^N C_i S_i. \quad (11)$$

A label-consistent refusal contributes to TCR and, when the executed trajectory is safe, to STCR. Refusal alone does not count as completion on a feasible task.

Environment access and cost reporting. During WOW harness evolution, all compared evolution methods, including the baselines, are permitted to inspect backend state through the available tools. WOW tasks run in ServiceNow, and the environment is cleaned after each task to prevent residual task state from contaminating subsequent runs. Static world knowledge is frozen before test evaluation. The Cost columns report mean test-time inference expenditure per task in US dollars, including calls to all runtime agents. Steps counts actions actually executed in the environment; proposals rejected by the policy gate do not contribute to this count. Reported test-time steps are averaged over the evaluated tasks. Training-time active-verification interactions are reported separately in Appendix E.

We present below the prompt templates utilized across our system. Dynamic placeholders enclosed in braces are instantiated at runtime from the active task, world ledger, trajectory history, and policy context. Scientific environments omit enterprise policy enforcement, so their evolution uses the task agent, three diagnostic views, and the hidden-rule abduction agent.

A.2.1 WORLD OF WORKFLOWS

Task Agent Prompt

```

[System]
You are a task-completion agent operating a ServiceNow environment.
Complete the task by executing one available MCP tool at a time.
Respect exact values and the order stated by the user.

## Environment
{environment context}

## Current known policies and permissions
{environment policies}

If the policy section says the setting is hidden or discoverable, do
not assume an unstated policy. Infer behavior only from supplied
evidence and tool responses.

## Operating rules
1. Execute task steps in the requested order; do not collapse
sequential steps.
2. Use only the native MCP tools supplied in the task prompt.
3. After a write, inspect objective evidence. HTTP success alone
does not prove that every requested field persisted.
4. If a policy or permission blocks an operation, use an allowed
recovery when possible. Do not switch credentials or invent privileges
.
5. Terminate only after the requested final state is verified, or
when the task genuinely cannot be completed safely under the current
environment.

[User]
## Task
{task description}

## Available Native MCP Tools
{available tools}

Use only these tools and conform to their input schemas. Do not
invent a tool, parameter, identifier, policy, permission, or tool
result.

## Static World Model
{static world knowledge}

Verified stable enterprise behavior. It is not policy, tool, or
current-task state. Prefer current task, tools, policies, and fresh
observations when they conflict with it.

## Current Actual Dynamic State
{dynamic world state}

Latest task-relevant state maintained by State Tracking. Treat
absent or conflicted facts as uncertainty, not proof.

## Compact Execution Trajectory
{compact trajectory}

Executed actions, rejections, and task progress. Do not repeat a
successful action or an unchanged rejected action. Preserve confirmed
IDs and exact task-provided literals. Verify important writes. Stop as
impossible only when no legal recovery remains.

```

```

## Evolution Instructions
{evolution instructions}

## ID Validation Feedback
{id validation feedback}

If present, revise this response using only confirmed IDs from the
supplied inputs. Do not invent or alter IDs.

## Complete Output Example
Before execution, predict the concrete state change expected from
your chosen action. A complete valid response for a create_user step
is:

{
  "thought": "The requested user is absent, so create the user with
the exact task-provided fields.",
  "action": {
    "tool_name": "create_user",
    "tool_params": {
      "user_name": "example.user",
      "first_name": "Example",
      "last_name": "User",
      "email": "example.user@example.com"
    }
  },
  "predicted_state_changes": [
    {
      "table": "sys_user",
      "field": "sys_id",
      "operation": "create",
      "new_value_summary": "<sys_id>",
      "direct_or_side_effect": "direct"
    },
    {
      "table": "sys_user",
      "field": "user_name",
      "operation": "create",
      "new_value_summary": "example.user",
      "direct_or_side_effect": "direct"
    },
    {
      "table": "sys_user",
      "field": "first_name",
      "operation": "create",
      "new_value_summary": "Example",
      "direct_or_side_effect": "direct"
    },
    {
      "table": "sys_user",
      "field": "last_name",
      "operation": "create",
      "new_value_summary": "User",
      "direct_or_side_effect": "direct"
    },
    {
      "table": "sys_user",
      "field": "email",
      "operation": "create",
      "new_value_summary": "example.user@example.com",
      "direct_or_side_effect": "direct"
    }
  ]
}

```

```

    ],
    "verification_plan": [
        "Use the returned <sys_id> to read the created sys_user record
    .",
        "Verify that user_name, first_name, last_name, and email
    persisted."
    ],
    "uncertainties": [
        "The actual <sys_id> and any server-generated/default fields are
    unknown until the tool result is returned."
    ],
    "terminate": false,
    "task_cannot_be_completed": false
}

```

Return exactly one JSON object with thought, action, predicted_state_changes, uncertainties, verification_plan, terminate, and task_cannot_be_completed. Predictions are hypotheses until confirmed by tool evidence.

State-Tracking Agent Prompt

[System]

You are a State Tracking Agent for a ServiceNow enterprise environment. Your role is to maintain the complete latest task-relevant Actual Dynamic State after one action. Use the task, current action, MCP contract, raw tool feedback, current Dynamic State, and applicable Static World Model facts.

Preserve facts that can affect later actions, entity resolution, policy, verification, or task progress. Omit transport noise and unrelated detail. Output evidence-backed updates and explicit removals for the Harness to apply. You cannot execute tools, modify policy, invent unsupported facts, or change the task objective.

[User]

```
## Current Task
{task description}
```

Use the task only to decide which observed facts, relationships, and progress are relevant to the current objective.

```
## Current Action
{proposed action}
```

This is the action that was actually submitted for this step.

```
## MCP Tool Contract
{tool schema}
```

Use the contract to interpret the action parameters and the structure and meaning of the tool result.

```
## Raw Tool Feedback
{tool response}
```

This is the current action's complete tool feedback. Treat successful writes, returned identifiers, read values, explicit failures, and omissions according to the tool contract. An omitted field is unknown, not automatically false or unchanged.

```

## Current Actual Dynamic State
{dynamic world state}

This is the latest task-relevant state before applying the current
feedback. Update it with newly observed facts, correct values
contradicted by stronger evidence, and remove only values proven stale
. Keep predictions separate from Actual Dynamic State.

Use only these canonical top-level collections: users, assets,
groups, locations, incidents, problems, articles, knowledge_bases,
categories, items, requests, request_items, records, task_progress.

Use records.<table>.<id>.<field> for tables without a dedicated
collection.

## Static World Model
{static world knowledge}

These are stable environment behaviors that may describe hidden or
indirect effects not returned by the tool. When an applicable fact and
the current action provide sufficient evidence, include the resulting
additional state change. Do not apply unrelated facts or invent
effects beyond the stated conditions.

## Evolution Instructions
{evolution instructions}

## ID Validation Feedback
{id validation feedback}

## Output
Return exactly one JSON object. Use:
- actual_state_updates: latest canonical path/value updates
supported by the feedback, action, current state, or an applicable
Static World Model fact;
- state_removals: existing paths proven stale or invalid;
- evidence_summary: the tool and concise evidence used;
- conflicts and verification_needed: contradictions or facts
requiring a later read;
- feedback_summary, unresolved_state, and recommended_next_step:
concise information for the next Task Agent step.

A complete valid example is:
{
  "conflicts": [],
  "verification_needed": [],
  "actual_state_updates": [
    {
      "path": "users.<confirmed_user_id>.active",
      "value": true,
      "evidence": ["tool_response.user_id", "tool_response.active"],
      "reason": "The tool feedback identifies the user and confirms
the active value."
    }
  ],
  "state_removals": [],
  "evidence_summary": {
    "tool_name": "get_user",
    "feedback_type": "tool_result",
    "used_information": ["The returned user_id and active field."]
  },

```

```

    "feedback_summary": "The user was read successfully and the
current active value was recorded.",
    "unresolved_state": [],
    "recommended_next_step": "Continue with the next task-required
action."
}

```

Use strict JSON with no Markdown or extra prose. Do not invent tools, IDs, facts, observations, or successful writes.

Policy-Context Agent Prompt

[System]

You are a Policy Gate Context Agent for a ServiceNow enterprise environment. Use the current action and the complete latest Actual Dynamic State to build the structured context required by applicable policy code.

You cannot execute tools, decide policy outcomes, modify policy code, weaken safety requirements, invent state, or treat Task Agent predictions as facts. Every supplied value must cite existing Actual Dynamic State paths or explicit current-action parameters. Deterministic policy code is authoritative.

[User]

```
## Current Task
{task description}
```

```
## Proposed Action
{proposed action}
```

```
## Proposed Tool Contract
{tool schema}
```

```
## Applicable Policy Code
{applicable policy code}
```

All supplied policies are deterministic Python policy code. Use the current action, each policy's required context, and the complete latest Actual Dynamic State to return only evidence-backed bindings for context the Gate needs. Current action parameters may be cited as parameters.<name>. Never guess IDs, facts, or negative/empty values from absence. Do not evaluate, pass, block, or rewrite a policy: the Harness validates accepted bindings and then executes the policy code.

Review every required_context path from every applicable policy, not only the missing paths below. Extract as much policy-relevant context as the current Action and Dynamic State support. You may derive a required value from clear enterprise semantics represented by the supplied state (for example, a location of New York supports country US). Cite the original path. Do not make an uncertain mapping or invent an absent business fact.

```
## Context Resolved by Context Resolver
{resolved policy context}
```

These are preliminary action-specific values extracted deterministically before this Agent runs. They are useful hints, but they are not guaranteed to be complete or correct. Check them against the Action, Dynamic State, and policy code.

```

## Missing Required Context
{missing required context}

Bind every path that can be supported from the Action or Dynamic
State. Keep a path in unresolved_context only when the available
evidence cannot safely determine it.

## Complete Latest Actual Dynamic State
{dynamic world state}

## Evolution Instructions
{evolution instructions}

## ID Validation Feedback
{id validation feedback}

Return exactly one JSON object:
{
  "context_bindings": [
    {
      "target_path": "state.target_user.active_incident_count",
      "value": 1,
      "source_paths": ["users.<confirmed_user_id>."
active_incident_count"],
      "derivation": "copy",
      "reason": "The current Dynamic State directly records one
active incident for the target user."
    }
  ],
  "unresolved_context": []
}

```

Evolution Proposal Agent Prompt

[System]
You are an Evolution Proposal Agent for an enterprise task-execution Harness.

Given the supplied Harness context and one objective trajectory episode, return exactly one minimal result: one additive Agent-prompt instruction, one typed unverified Static World Model hypothesis, or no_proposal.

Use an Agent-prompt target for a reasoning, state-tracking, policy-context, or policy-compilation deficiency. Use static_world_model only for a plausible stable enterprise side effect or conditional rule that needs active validation. If that hidden rule is already in the supplied Static World Model, return no_proposal.

The natural-language policy text is the criterion and must not be weakened. Compiled policy code is only an implementation of that text: it may later be repaired via policy_gate_init_prompt, but prefer changing Task Agent, State Tracking, or Policy Context first. Change code only when compatible context already reaches the Gate, or cannot safely be supplied by those agents.

Choose a target as follows:

- Use task_agent_prompt for reasoning or workflow discipline, or when the next action is the defect: omitted confirmed Dynamic State

values, guessed policy-sensitive parameters, or missing context that requires a new read before a write. Policy Context cannot execute tools, trigger read-backs, or direct the Task Agent. An unmet prerequisite is not a permanent stop if available tools can satisfy it ; require that path before retrying.

- Diagnose a failing policy field before choosing a context or compiler target:

1. Verify whether the Policy Context Agent actually supplied an accepted binding. An event record alone does not prove effective execution.

2. If there is no relevant accepted binding because Dynamic State already contained a State Tracking value, the field bypassed Policy Context. Select `state_tracking_agent_prompt` and specify the paths and value formats downstream policy requires.

3. Use `policy_context_agent_prompt` when available state can be normalized, completed, or bound to the policy-required paths and formats.

4. Use `policy_gate_init_prompt` only when compatible context already reaches the Gate, or cannot safely be supplied by Policy Context or State Tracking, and the policy code or its required-context metadata is still defective.

Do not weaken policy, bypass a Gate, alter tools, runtime code, evaluator, cleanup, or the base task. Return only the selected JSON object.

```
[User]
## Enterprise Environment
{environment description}

## Available MCP Tools
{available tools}

## Current Static World Model
{static world knowledge}

## Current Policy Code
{current policy code}

## Deterministic Policy Metadata Audit
{policy metadata audit}
```

```
## Current Agent Workflow and Harness
```

The fixed closed loop is: Task Agent uses Static World Model and Dynamic World State to select one action and predict its state delta. The Harness deterministically records that prediction; the State Tracking Agent does not see, store, or revise it. The fixed Context Resolver then projects action-related state -> the Policy Context Agent semantically completes policy context -> deterministic compiled Code Gate evaluates it. If Gate does not allow execution, the Harness records `action_executed=false` and an empty Actual State Delta; State Tracking is not called. If allowed, Runtime executes the native MCP action -> Evidence Projector removes task-irrelevant response material -> State Tracking reconciles Actual Dynamic State from those observations only -> Compact Trajectory Builder records progress -> Task Agent chooses the next action.

```
## Current Evolvable Versions
{current evolvable versions}
```

```
## Evolution Boundary
```

Modifiable targets: `task_agent_prompt`, `state_tracking_agent_prompt`, `policy_context_agent_prompt`, `policy_gate_init_prompt`, and

```

static_world_model. Fixed targets: native MCP tools/schemas; Harness
runtime code; evaluator/tasks; cleanup/rollback; deterministic
compiled Gate enforcement; base task semantics; and policy, permission
, or security constraints.

{view-specific instructions}

## Episode Evidence
{episode evidence}

## Required Result
Analyze this one objective episode and return exactly one minimal
result. Select exactly one target, or return no_proposal.

For no proposal:
{"target": "no_proposal", "thinking": "..."}

For an Agent Prompt target:
{
  "target": "task_agent_prompt | state_tracking_agent_prompt |
policy_context_agent_prompt | policy_gate_init_prompt",
  "thinking": "...",
  "evolution_prompt": "one minimal, general additive instruction"
}

For static_world_model:
{
  "target": "static_world_model",
  "thinking": "...",
  "hypothesis_type": "side_effect | hidden_rule",
  "hypothesis": "one uncertain, environment-specific behavior to
validate"
}

```

The proposal agent is instantiated with one of the four view-specific instruction blocks below.

Evolution View: State Consistency

```

## State-Diff Analysis Instructions
This is an executed write. Inspect only this step: the Task Agent
prediction, projected tool feedback, State Tracking output, and the
small Context Resolver / Policy Context records.

Feedback is not a complete world dump. A tool may return only
success, omit persisted fields, or hide side effects that create or
change extra fields. Thin feedback does not prove nothing else changed
; a field that is in feedback should not be silently dropped. If both
the prediction and the applied delta agree, still check whether they
both missed a reported fact or both invented a value feedback never
showed.

Compare those three sources yourself. Also consider whether an
applicable hidden rule already in the supplied Static World Model was
used by the Task Agent or State Tracking.

Candidate causes:
1. The Task Agent predicted the wrong delta.
2. State Tracking mis-assimilated an observation it had.
3. The observation surface was insufficient, so a read-back was
needed.
4. An unknown side effect or hidden rule.

```

5. An applicable policy's code or required-context metadata is wrong

Do not default to blaming the prediction. Select `static_world_model` only for case 4, and `policy_gate_init_prompt` only for case 5.

State-Track Analysis Instructions

This action is a read (`list_*` / `get_*` / `search_*`). It does not mutate enterprise state. Judge whether State Tracking registered bindable facts from the projected tool feedback into Actual Dynamic State. Prefer `state_tracking_agent_prompt` when feedback contained a bindable fact that was dropped, renamed, or misplaced. Use `task_agent_prompt` only when the query itself could not produce a bindable identity. Do not select `static_world_model` merely because a list payload is large.

Evolution View: Policy-Gate Correctness

Policy-Gate Analysis Instructions

The current action was not executed. Inspect the pre-execution chain : Task Agent -> fixed Context Resolver -> Policy Context -> deterministic Code Gate. Context Resolver is not evolvable. State Tracking was not called; Actual State Delta is empty. Do not treat this as State Diff. A query can mean missing or poorly propagated prior state. A block can be correct safety, bad context, or defective policy-code applicability. Never weaken a correct policy.

If the Gate stopped a write for missing policy parameters, do not only recommend another query. Teach the Task Agent to check confirmed Dynamic State first, put present values into the write using the tool schema's exact parameter names, and query only what is still unconfirmed. `require_approval` is a prerequisite, not a permanent stop: require the legal approval path, then retry. Do not terminate or refuse solely because approval is required.

For a cross-country asset transfer, the supplied tools include `create_change_request`, `submit_change_for_approval(change_id)`, and `approve_change_request(change_id)`. A resulting approved change request / approval record can provide the evidence from which Policy Context binds `state.approval=true` for a retried transfer.

If an approved change request / approval fact is already present in Actual Dynamic State but the Policy Context review has no binding and deterministic Gate did not receive `state.approval=true`, select `policy_context_agent_prompt` rather than `task_agent_prompt`.

Evolution View: Goal Judgment

Goal-Judgment Analysis Instructions

Judge whether the Agent correctly believed the goal was completed, should continue, or could not be completed safely. Inspect the compact trajectory, final task-relevant Dynamic State, final thinking, termination type, and whether it stopped before `max_steps`. Use only these evaluator signals: `goal_completed`, `policy_and_permission_safe`, `safe_task_success`, `task_completion_feedback`, and `constraint_and_permission_feedback`. Treat the feedback lists as concrete failure evidence and trace them to the relevant action, Dynamic State, Policy Context, and Gate decision.

Ground-truth cannot-complete labels are not provided. Stopping counts as safe completion only when the Agent established the correct unavoidable reason and no legal next action remained. Before accepting an early stop from an unmet prerequisite, check whether supplied tools provide a legal path to satisfy it. A missing user, ID, or record is not enough when the task requests creation and a legal create tool exists. If max_steps caused termination, there is no intentional final stop to infer from.

If evaluator evidence shows a persisted value that differs from an explicit earlier write, consider an unobserved side effect rather than only a missing final check.

A recovery is legal only if it can satisfy the remaining task requirements without violating a correct policy or world rule, and without dropping or inverting a task-stated end state.

A Gate block that names a forced side effect (surrender, cancel, clearing assigned_to, or any other required-state destruction) as the price of a still-required write is exclusivity evidence. Do not look for a restore, re-assign, or later undo of that forced effect. The Task Agent should finish every still-safe step, refuse the conflicting write, and set task_cannot_be_completed=true with that concrete pair.

Do not treat changing a task-specified clearance, deactivation, assignment, membership, or transfer target as a legal path. Those values are requirements, not knobs.

If the trajectory already performed a workaround, the Evolution lesson is still that the agent should have stopped at the first exclusivity evidence. Prefer task_agent_prompt for that termination discipline. Use static_world_model only when the exclusivity itself is still an unvalidated hidden effect, not when the Gate already stated the rule.

Evolution View: World Observation Gap

[System]

You are a World Observation Gap Agent in an enterprise Harness Evolution pipeline. Analyze one task's complete compact execution trajectory and identify whether the Harness-observed world may omit a policy-relevant state transition that occurred in the real enterprise environment.

Each trajectory step lists Task Agent, Context Resolver, Policy Context, then policy_code_gate. If that field is "this action did not require code-gate review", no compiled policy applied. Otherwise it lists each reviewed policy, whether it passed, and the exact decision / reason / missing_context it returned. Focus on policy-sensitive fields that were not reliably observed, actions that could have changed those fields directly or indirectly, later Gate feedback, corrective actions, and downstream success or failure. Do not use audit data. Do not modify any Agent prompt. Output only an unverified World Model hypothesis, or no hypothesis when the trajectory does not support one. If the relevant hidden rule is already present in the supplied Static World Model, output no_hypothesis instead of proposing it again.

For each policy-sensitive field implicated by a Gate or corrective action, inspect the entire preceding action chain. Treat every earlier action that could plausibly affect the field as a candidate trigger: direct writes, creation actions, relationship or ownership changes, status/workflow changes, and updates to related records. Do not stop at the action that created the record. List the meaningful alternatives in `candidate_trigger_actions`, and make `suggested_validation` distinguish them with a small ordered comparison. The purpose is to find side-effecting actions, not actions that directly write the policy-sensitive field itself. Ignore an update action that explicitly sets, clears, or otherwise directly changes that field when choosing candidate triggers; treat it only as evidence that the field required intervention. Read-only actions such as `get`, `list`, `search`, or `lookup` are observations, not candidate triggers, unless the trajectory contains concrete evidence that the specific read operation mutates enterprise state.

One-shot example:

Policy-sensitive field: `article.flagged`. Trajectory: an article is created without an observed `flagged` value; its author's department is changed; publication later requires `flagged` context; an explicit `update_article(flagged=false)` is performed; publication then succeeds. The later need to explicitly clear `article.flagged` suggests that an earlier operation may have triggered an unobserved transition that changed `article.flagged` to 1. Candidate triggers include `create_article` and the later action that changes the author's department.

```
[User]
## Basic Task Information
{task goal}

## Available MCP Tools
{available tools}

## Current Static World Model
{static world knowledge}

## Policies
{policies}

## Complete Compact Trajectory
{complete compact trajectory}

## Required Output
If the trajectory supports a possible policy-relevant observation
gap:
{
  "decision": "hypothesis",
  "hypothesis_type": "side_effect or hidden_rule",
  "thinking": "why the observed trajectory suggests a hidden
transition",
  "policy_fields": ["policy-sensitive field"],
  "candidate_trigger_actions": ["action that may have changed the
field"],
  "downstream_signals": ["later behavior suggesting the hidden
change"],
  "hypothesis": "one uncertain environment-specific behavior to
validate",
  "suggested_validation": "a small action/read-back sequence"
}

If not:
```

```
{
  "decision": "no_hypothesis",
  "thinking": "why no policy-relevant observation gap is supported"
}
```

Hidden-Rule Abduction Agent Prompt

[System]

You are a World Rule Abduction Agent. Investigate one unverified world-rule hypothesis through a ReAct loop using the supplied task goal, trajectory evidence, MCP tools, policies, current hypothesis, and validation history.

Your objective is to identify whether a candidate action changes a policy-sensitive field, and under which conditions. Design a fresh experiment; the historical trajectory is evidence only and cannot be resumed.

Use these rules:

1. Use fresh records and IDs only. Never reuse an ID from the source trajectory or proposal. Retain IDs returned during this validation run.
2. Before validating a policy-sensitive value, identify an authoritative table and field by the procedure below. A convenience read that omits the value is unknown, never false or unchanged. Name a table or field in a verified rule only when this run's schema or read-back returned it.
3. When the field can be read directly, test each meaningful candidate trigger with a comparable ordered experiment: create or establish the target state, read the field before, apply the trigger, then read the field after. A Gate result is downstream evidence, not primary proof in that case.
4. Reproduce material conditions from the source episode when they may matter, such as state, priority, role, department, ownership, country, or approval. Prefer a small control/treatment comparison and consider transient causes such as delayed processing or stale read-back before claiming a stable rule.
5. Test all meaningful source candidates when the action budget permits. If a candidate cannot be tested, retain it in the hypothesis or state why it is unresolved. Do not silently narrow to the easiest candidate.
6. Verify only what the experiment independently observed. If the available reads cannot distinguish the rule, revise the hypothesis or return unresolved rather than infer a fact from the final state alone.
7. Do not restrict a verified rule, its applicability, or the action guide to a specific hostname. State the rule as general enterprise behavior.

Environment manual. This is ServiceNow's general method for reading and checking records. Follow it in order. Do not skip ahead, and do not invent a table or field that this run has not returned.

- Schema first. Call `get_table_schema` once on the tables already named by the trajectory, the current record, the hypothesis, or a tool result. If the policy-sensitive field is on that schema, read it on that table.

- Field catalog. If it is not, call `search_any_table` on `sys_dictionary`. Set filters to `element=<field>` using a field name already present in the policy, hypothesis, or trajectory; use `elementLIKE<word>` only when the exact element is not known. Set fields

to name, element, and reference. Each hit's name is a candidate table

- Reverse references. If the value may sit on a related record, call `search_any_table` on `sys_dictionary` with filters of `reference=<known_table>^internal_type=reference`, the same fields, and a limit high enough that the page is not truncated. Each hit's name is a related table and element is the field that points back. Schema that table, then read the policy-sensitive field there, filtering by that join field back to the known record.
- Read each candidate field on its own table. Do not copy it from another record's convenience payload.

On every call, choose exactly one:

- act: provide the current hypothesis and exactly one next supplied MCP action;
- revise: provide one revised hypothesis;
- verified: provide the rule, applicability, and evidence-based conclusion;
- unresolved: explain why the rule cannot yet be verified.

The hypothesis may be revised at most three times. Return only the selected JSON object with no prose or Markdown fences.

```
[User]
## Source World-Model Proposal
{source world-model proposal}

## Original Task Goal
{original task goal}

## Trajectory Evidence
{trajectory evidence}

## Available MCP Tools
{available tools}

## Current Static World Model
{static world knowledge}

## Policies
{policies}

## Current Hypothesis
{current hypothesis}

## Validation History
{validation history}

## Remaining Budget
Actions: {remaining action budget}
Hypothesis revisions: {remaining revision budget}

## Required Output
Choose exactly one of act / revise / verified / unresolved.

If act:
{
  "decision": "act",
  "hypothesis": {
    "rule": "the current testable rule",
    "applicability": "where and when it applies",
    "predicted_observations": ["observable prediction"],
    "action_plan": ["current ordered validation plan"]
  }
}
```

```

    },
    "action": {"tool_name": "one supplied MCP tool", "tool_params":
    {}}
  }

  If revise:
  {
    "decision": "revise",
    "hypothesis": {
      "rule": "the revised testable rule",
      "applicability": "revised applicability",
      "predicted_observations": ["revised observable prediction"],
      "action_plan": ["revised ordered validation plan"]
    }
  }

  If verified:
  {
    "decision": "verified",
    "rule": "the non-empty verified world rule",
    "applicability": "where and when the verified rule applies",
    "conclusion": "how the validation evidence supports the rule"
  }

  If unresolved:
  {
    "decision": "unresolved",
    "conclusion": "why the available evidence cannot verify the rule"
  }

```

A.2.2 SCIENCEWORLD

ScienceWorld actions are short text commands. The state-consistency view sees one step, and the goal-judgment and world-observation-gap views see the full episode. The abduction agent tests one hypothesis in a fresh instance of the same task.

Fixed action demonstration. The example lookup, `example_for_type()`, contains one entry for `find-non-living-thing`. Other task types fall back to this entry, so tasks such as boiling and freezing receive the same demonstration. It illustrates action syntax and the sequence of opening a door, navigating, focusing on an object, and moving it. The task-agent prompt instructs the agent to use the demonstration for valid action strings and general workflow, and to take object names from the current task and observations. The `{example}` placeholder is populated with the following text.

ScienceWorld Fixed Demonstration

```

This room is called the hallway. In it, you see:
    the agent
    a substance called air
    a picture
You also see:
    A door to the art studio (that is closed)
    A door to the bedroom (that is closed)
    A door to the greenhouse (that is closed)
    A door to the kitchen (that is closed)
    A door to the living room (that is closed)
    A door to the workshop (that is closed)
Task Description:
Your task is to find a(n) non-living thing. First, focus on the thing.
Then, move it to the red box in the kitchen.

```

```

> think: I need a non-living thing, then focus on it, then move it to
the red box in the kitchen. The kitchen door is closed, so open it and
go there first.
OK.
> open door to kitchen
The door is now open.
> go to kitchen
You move to the kitchen.
> look around
This room is called the kitchen. In it, you see:
    the agent
    a substance called air
    a chair. On the chair is: nothing.
    a counter. On the counter is: a bowl (containing a red apple,
a banana, an orange, a potato), a drawer.
    a cupboard. The cupboard door is closed.
    a painting
    a red box (containing nothing)
    a table. On the table is: a glass cup (containing nothing).
You also see:
    A door to the bathroom (that is closed)
    A door to the hallway (that is open)
    A door to the outside (that is closed)
> think: A painting and a table are non-living. The red box is already
in this room. Focus on the table, then move it to the red box.
OK.
> focus on table
You focus on the table.
> move table to red box
You move the table to the red box.

```

ScienceWorld Task Agent Prompt

You are a ScienceWorld ReAct agent. Complete the science task with text actions. Think briefly, then choose exactly one next action. Return strict JSON only: {"thought": string, "action": string, "state_delta": string}. 'state_delta' is a short text prediction of what will change after this action (room, inventory, focus, device, object location). It is a hypothesis until the next observation confirms it. Use the example only to learn valid action strings and the usual plan. Do not copy objects from the example.

Doors usually start closed: first 'open door to <room>', then 'go to <room>'.

'focus on <object>' is the task's answer action, not a way to select an object before pouring, mixing, or moving. Follow the task text: if it says focus first then do the later step, focus on that target now; if it says focus when you are done, finish the procedure first and only then focus on the finished object. Do not focus on ingredients, rooms, doors, or other intermediates. A wrong 'focus on' can end the episode immediately.

Typical actions: look around, inventory, task, open/close <object>, go to <room>, pick up <object>, put down <object>, move <object> to <object>, focus on <object>, activate/deactivate <object>, use <object> on <object>, look at <object>, look in <object>, pour <object> in <object>, mix <object>, wait.

'<object>' and '<room>' must be short names copied from the latest observation or task text (e.g. 'red paint', 'glass cup', 'kitchen'). Do not invent longer descriptions such as 'wood cup with red paint'.

Do not dump or invent a long list of connect/disconnect actions.
Prefer the short commands above.

Static world knowledge (verified reusable rules; empty until evolution writes facts):

```
{world}
```

Prefer the current task and latest observations if they conflict with this layer.

```
{evolution_block}
```

Example of this task type:

```
{example}
```

Current task:

```
{task}
```

History:

```
{history}
```

ScienceWorld Evolution View: State Consistency

[System]

You are a State Diff Agent for ScienceWorld.

Compare only this step: predicted state_delta vs environment observation

(room, door, inventory, object location, focus text, illegal-action text).

Ignore score and goal_progress.

You see this step's Task Agent prompt, including its history. Return exactly one wow-style result. Do not output verdict, score analysis, or extra fields.

Return one JSON object, no Markdown:

```
{"target":"no_proposal","thinking":"why this step needs no change"}
```

```
{"target":"task_agent_prompt","thinking":"...", "evolution_prompt":"one additive instruction"}
```

```
{"target":"hidden_rule","thinking":"...", "hypothesis":"one unverified world behavior to validate"}
```

Use task_agent_prompt for naming, action form, or discipline that applies

to THIS task type only. Do not write a procedure other task families would inherit.

Use hidden_rule for a stable world mechanism the prompt could not know.

If the same rule is already in Static World, return no_proposal.

[User]

Task

```
{task}
```

Current Static World

```
{static world}
```

```

## Current Task Agent prompt
This is the prompt the Task Agent saw at this step, including history.
If you choose task_agent_prompt, write evolution_prompt as one
additive
instruction. Do not repeat unchanged text.

{task agent prompt}

## This step
{predicted state_delta, observation, and action}

```

ScienceWorld Evolution View: Goal Judgment

```

[System]
You are a Goal Judgment Agent for ScienceWorld.

Judge whether the agent finished, stopped on the wrong object, or
stalled.
Use the supplied Task Agent prompt (history is a placeholder), Static
World,
and the full episode history (goal_progress and score are in that
history).

Return exactly one wow-style result. No verdict labels or extra fields
.

Return one JSON object, no Markdown:

{"target":"no_proposal","thinking":"why this episode needs no change"}

{"target":"task_agent_prompt","thinking":"...", "evolution_prompt":"one
additive instruction"}

{"target":"hidden_rule","thinking":"...", "hypothesis":"one unverified
world behavior to validate"}

Use task_agent_prompt for workflow/stop discipline that applies to
THIS
task type only. Do not write a procedure that would be followed on
other
task families. Do not invent "focus immediately", "pick any menu
number",
or "open every container" as global rules.
Use hidden_rule when text success hides a scoring/submit rule.
If that rule is already in Static World, return no_proposal.

[User]
## Task
{task}

## Current Static World
{static world}

## Current Task Agent prompt
History below is a placeholder. The real episode history is in the
next block.
If you choose task_agent_prompt, write evolution_prompt as one
additive
instruction.

{task agent prompt}

```

```

## Initial observation
{initial observation}

## Initial goal_progress
{initial goal progress}

## Episode history
{episode history}

```

ScienceWorld Evolution View: World Observation Gap

```

[System]
You are a World Observation Gap Agent for ScienceWorld.

Find a hidden scoring rule: observation looks successful, but
goal_progress
stays false or score crashes (especially focus to -100).
You see the Task Agent prompt (history placeholder), Static World, and
the
full episode history.

Prefer hidden_rule. Do not rewrite the Task Agent prompt unless the
gap is
only workflow discipline for THIS task type. If the same rule is
already in
Static World, return no_proposal.

Return one JSON object, no Markdown:

{"target":"no_proposal","thinking":"why no observation gap is
supported"}

{"target":"task_agent_prompt","thinking":"...", "evolution_prompt":"one
additive instruction"}

{"target":"hidden_rule","thinking":"...", "hypothesis":"one unverified
world behavior to validate"}

[User]
## Task
{task}

## Current Static World
{static world}

## Current Task Agent prompt
History below is a placeholder. The real episode history is in the
next block.

{task agent prompt}

## Initial observation
{initial observation}

## Initial goal_progress
{initial goal progress}

## Episode history
{episode history}

```

ScienceWorld Hidden-Rule Abduction Agent Prompt

```
[System]
You are a World Rule Abduction Agent for ScienceWorld.

Test one hypothesis in a fresh instance of the same task. You may
replay
source actions, then change the critical step, or explore freely.
Goal is to verify the hypothesis, not to score 100.

Each act is one ScienceWorld text command. Feedback is observation,
score,
reward, done, goal_progress. Use short names from the latest
observation.

Return one JSON object, no Markdown. Choose exactly one:

{"decision":"act","thinking":"...","action":"one text command","
hypothesis":{"rule":"...","applicability":"...","
predicted_observations":["..."],"action_plan":["..."]}}

{"decision":"revise","thinking":"...","hypothesis":{"rule":"...","
applicability":"...","predicted_observations":["..."],"action_plan
":["..."]}}

{"decision":"verified","thinking":"...","rule":"...","applicability
":"...","conclusion":"..."}

{"decision":"unresolved","thinking":"...","conclusion":"..."}

If an action ends the episode (done=true or score -100), the harness
reloads a
fresh instance. Use that to run the other side of a control/treatment
comparison.
Verify only what this live run independently showed.

[User]
## Original task
{task}
task_name={task name} variation={variation}

## Hypothesis to test
{hypothesis}

## Source actions (replay then change if useful)
{source actions}

## Validation history
{validation history}

## Budget
actions_left={remaining actions} revisions_left={remaining revisions}
```

A.2.3 DISCOVERYWORLD

DiscoveryWorld actions are one JSON command per turn. The three views share one output contract: a proposal is either a task-prompt addition or a hidden-rule hypothesis, and a hypothesis must transfer across seeds of the same theme.

DiscoveryWorld Task Agent Prompt

You are a DiscoveryWorld ReAct agent playing a 2D top-down scientific discovery game.

You receive JSON observations (no image). Complete the assigned task with exactly one environment action per turn. Think briefly about the hypothesis, measurement, or navigation needed, then choose the action.

Return strict JSON only.

If you are NOT in dialog, use:

```
{"thought": string, "action": string, "arg1": value or null, "arg2": value or null, "state_prediction": string}
```

action must be one of the valid action names. arg1/arg2 are usually object UUIDs from inventory or accessibleEnvironmentObjects. Exceptions: MOVE_DIRECTION/ROTATE_DIRECTION use north/east/south/west; TELEPORT_TO_LOCATION uses a location name; TELEPORT_TO_OBJECT uses an object UUID; Discovery Feed post lookup uses an integer post id. state_prediction is the expected experimental result of this action (instrument reading, whether a sample looks contaminated, whether a mixture removes rust, whether a reactor accepts a frequency, what a translation/utterance will mean). It is a checkable hypothesis about what the world will reveal, not a ledger of inventory, location, or other state the next observation already lists. Navigation/pickup may use a short expected feedback (teleport succeeds, object is picked up). Do not treat it as ground truth until the next lastActionMessage confirms or contradicts it.

If you ARE in dialog, ignore the normal action schema and return:

```
{"thought": string, "chosen_dialog_option_int": integer, "state_prediction": string}
```

Rules:

- Interact only with inventory objects or objects in accessibleEnvironmentObjects (directly in front of you).
 - Prefer TELEPORT_TO_LOCATION or TELEPORT_TO_OBJECT over walking.
 - For USE/PUT, one object must be in inventory and you must be next to the other.
 - Do not invent UUIDs. Copy them from the observation.
 - If the last action failed, change strategy.
 - Do not stop early unless the task description is clearly finished.
- There is no SUBMIT action in this environment.

```
{action help}
```

Current task:

```
{task}
```

You are facing: {facing direction}

You can move: {valid directions}

Current observation:

```
{observation}
```

```
{dialog or actions}
```

Recent history:

```
{history}
```

When in dialog, {dialog or actions} is:

NOTE: You are currently in a dialog. Choose a dialog option integer.

Dialog:

```
{dialog box}
```

```

Otherwise it is:
Valid actions:
{known actions}

Valid teleport locations:
{teleport destinations}

Interactable objects (inventory + directly in front of you):
{interactable objects}

```

DiscoveryWorld Evolution View: State Consistency

You are the state-prediction evolution view.
 You see ONE step: the observation the acting agent saw, the action it took, its `state_prediction` (expected experimental result), and the actual environment feedback.
 Judge whether the prediction matches the feedback. Ignore inventory/location bookkeeping; navigation and pickup may be not-checkable. You do not receive the evaluator/scorecard. Do not invent hidden rules from scores you cannot see.
 If the prediction is the wrong kind of statement (e.g. a ledger of inventory instead of an experimental expectation), propose a `task_prompt`.
 If the experimental prediction contradicts instrument/dialog feedback in a way that suggests an unknown world rule, you may propose a `hidden_rule`.

Seed generalization: object names, UUIDs, and sampled values change across seeds of the same theme.
 A `task_prompt` or `hidden_rule` must describe general regularities (instrument classes, object types, conditions, outcomes) that would hold on other seeds.
 Never hard-code this episode's specific names, UUIDs, locations, or sampled values.

Return strict JSON only, with exactly these keys:
`{"thought": string, "type": "no_proposal" | "task_prompt" | "hidden_rule", "content": string or null}`

- `thought`: brief reason for this decision.
- `type=no_proposal`: nothing to change; content must be null.
- `type=task_prompt`: content is a direct improvement to the task-agent prompt. Do not put hidden world rules in content.
- `type=hidden_rule`: content is a free-text hypothesis about an internal core rule that must be verified later by abduction. Do not write a prompt patch.

Do not output a view field. Do not treat gold answers or evaluator text as something the acting agent already knows.

Task:
`{task}`

Scenario: `{scenario}` / `{difficulty}` / seed `{seed}`

Current task-agent prompt (the base harness under evolution; propose `task_prompt` edits as deltas against it):
`{task agent prompt}`

Task-prompt additions evolved in previous rounds (already applied on top of the base prompt; do not re-propose them):

```

{prompt additions}

Current static world knowledge W_S:
{static world}

This is step {step} of the episode.

Observation the acting agent saw before this action (compact JSON):
{observation}

Action taken:
{action}

The agent's state_prediction (expected experimental result):
{state prediction}

Actual environment feedback (lastActionMessage):
{last action message}

```

DiscoveryWorld Evolution View: Goal Judgment

You are the goal-judgement evolution view.
 Judge the episode globally: whether the scientific task succeeded, where the scorecard stalled, and whether the agent looped or finished the procedure without the goal.
 You receive the compressed action/feedback trace and the oracle evaluator (success, completed, procedure, scorecard, score curve). The acting agent never sees the evaluator.
 Learn from BOTH failure and success:

- On failure or partial credit, prefer task_prompt for protocol failures (idle loops, never placing/submitting, stopping early).
- On success or clear progress, also distill what worked (effective exploration order, instrument usage, how the agent concluded and committed its answer) into a task_prompt so the harness keeps successful experience, not only fixes.
- Propose hidden_rule only if the outcome looks governed by an unstated world rule, not a checklist reminder.

Seed generalization: object names, UUIDs, and sampled values change across seeds of the same theme.
 A task_prompt or hidden_rule must describe general regularities (instrument classes, object types, conditions, outcomes) that would hold on other seeds.
 Never hard-code this episode's specific names, UUIDs, locations, or sampled values.

Return strict JSON only, with exactly these keys:
 {"thought": string, "type": "no_proposal" | "task_prompt" | "hidden_rule", "content": string or null}

- thought: brief reason for this decision.
- type=no_proposal: nothing to change; content must be null.
- type=task_prompt: content is a direct improvement to the task-agent prompt. Do not put hidden world rules in content.
- type=hidden_rule: content is a free-text hypothesis about an internal core rule that must be verified later by abduction. Do not write a prompt patch.

Do not output a view field. Do not treat gold answers or evaluator text as something the acting agent already knows.

Task:

```

{task}

Scenario: {scenario} / {difficulty} / seed {seed}

Current task-agent prompt (the base harness under evolution; propose
task_prompt edits as deltas against it):
{task agent prompt}

Task-prompt additions evolved in previous rounds (already applied on
top of the base prompt; do not re-propose them):
{prompt additions}

Current static world knowledge W_S:
{static world}

Compressed trajectory (action, state_prediction, lastActionMessage).
No compact observation JSON.
{compressed trajectory}

Oracle evaluator for evolution only (success, scorecard, score curve).
Never shown to the acting agent. Gold hidden-answer strings are
stripped.
{evaluator}

```

DiscoveryWorld Evolution View: World Observation Gap

You are the world-observation-gap evolution view.
Find internal rules that are not stated in lastActionMessage but show up as experimental regularities or as evaluator items that never complete despite relevant actions.
You receive the compressed trace, the oracle evaluator, and any state-prediction mismatches (empty on the first pass).
Do not copy gold hypotheses. Prefer hidden_rule for candidate world rules. Use task_prompt only if the protocol itself blocked observation (e.g. never using instruments).

Seed generalization: object names, UUIDs, and sampled values change across seeds of the same theme.
A task_prompt or hidden_rule must describe general regularities (instrument classes, object types, conditions, outcomes) that would hold on other seeds.
Never hard-code this episode's specific names, UUIDs, locations, or sampled values.

Return strict JSON only, with exactly these keys:
{"thought": string, "type": "no_proposal" | "task_prompt" | "hidden_rule", "content": string or null}

- thought: brief reason for this decision.
- type=no_proposal: nothing to change; content must be null.
- type=task_prompt: content is a direct improvement to the task-agent prompt. Do not put hidden world rules in content.
- type=hidden_rule: content is a free-text hypothesis about an internal core rule that must be verified later by abduction. Do not write a prompt patch.

Do not output a view field. Do not treat gold answers or evaluator text as something the acting agent already knows.

Task:
{task}

```

Scenario: {scenario} / {difficulty} / seed {seed}

Current task-agent prompt (the base harness under evolution; propose
task_prompt edits as deltas against it):
{task agent prompt}

Task-prompt additions evolved in previous rounds (already applied on
top of the base prompt; do not re-propose them):
{prompt additions}

Current static world knowledge W_S:
{static world}

Compressed trajectory (action, state_prediction, lastActionMessage).
No compact observation JSON.
{compressed trajectory}

Oracle evaluator for evolution only (success, scorecard, score curve).
Never shown to the acting agent. Gold hidden-answer strings are
stripped.
{evaluator}

State-prediction mismatches from the state_prediction view (empty on
the first pass):
{state prediction mismatches}

```

DiscoveryWorld Hidden-Rule Abduction Agent Prompt

```

You are the hidden-rule abduction agent.
You are placed in a FRESH copy of the same DiscoveryWorld theme / Easy
/ seed as the source episode.
Your job is to verify, revise, or reject the given hidden-rule
hypothesis by taking environment actions yourself.
You do not receive the evaluator or scorecard. Judge only from
lastActionMessage and the observation.

You may:
- take actions that would support, refute, or narrow the hypothesis;
- revise the hypothesis if the evidence points to a different (still
general, seed-transferable) rule;
- stop early once the evidence is enough.

Do not try to finish the original scientific task unless that is how
you test the hypothesis.
Do not write a task-prompt patch. Do not keep seed-specific names/
UUIDs as the rule itself.

Return strict JSON only, one of:
{"thought": string, "kind": "act", "action": string, "arg1": value or
null, "arg2": value or null, "hypothesis": string}
{"thought": string, "kind": "act", "chosen_dialog_option_int": integer
, "hypothesis": string}
{"thought": string, "kind": "revise", "hypothesis": string}
{"thought": string, "kind": "done", "verdict": "accept" | "reject", "
hypothesis": string or null}

kind=act: one environment action. hypothesis is the current working
text (the original, or the latest revision).
kind=revise: replace "Hypothesis to verify" with this new hypothesis.
Stay in THIS episode: keep the abduction history, do not reset the

```

```

environment, take no action this turn, then continue verifying the new
text.
kind=done: stop this episode. accept writes hypothesis into W_S;
reject drops it (hypothesis may be null). Revising is not a stop.

Seed generalization: object names, UUIDs, and sampled values change
across seeds of the same theme.
A task_prompt or hidden_rule must describe general regularities (
instrument classes, object types, conditions, outcomes) that would
hold on other seeds.
Never hard-code this episode's specific names, UUIDs, locations, or
sampled values.

Source task:
{task}

Scenario: {scenario} / {difficulty} / seed {seed}

Hypothesis to verify (current working text; revise replaces this in
place):
{hypothesis}

Current static world knowledge W_S (already accepted rules; do not re-
test these):
{static world}

Compressed source trajectory (action, state_prediction,
lastActionMessage) from the episode that proposed this hypothesis:
{source trajectory}

You are now in a fresh environment copy. Choose the next verification
action, revise the hypothesis and continue in this episode, or finish.

{action help}

You are facing: {facing direction}
You can move: {valid directions}

Current observation:
{observation}

{dialog or actions}

Abduction history so far:
{abduction history}

```

A.3 EVOLUTION INTERFACES AND EVIDENCE FLOW

The four views use a shared proposal interface with view-specific evidence. In WOW, each invocation returns one minimal proposal or no proposal. Table 4 summarizes the routing implemented by the prompts. The world-observation-gap view focuses on hidden-rule hypotheses; the other views can also improve the task, tracking, policy-context, or policy-compilation prompts.

Execution and diagnostic records. The execution trajectory contains actions actually submitted to the environment and their observations. The diagnostic record additionally retains non-approved proposals, gate decisions, predictions, and tracking outputs. When a proposal is blocked, no environment transition occurs and the state-tracking agent is not called. This separates a failed approval attempt from an executed action with an unexpected effect.

Candidate routing. A prompt proposal adds an instruction to its designated component. A hidden-rule hypothesis is sent to the abduction agent in a fresh environment. Its interface permits an

Table 4: Evidence and proposal types for the four WOW evolution views.

View	Evidence	Proposal types
State consistency	Action prediction, tool response, tracking updates, and relevant context records	Prompt update or rule hypothesis
World observation gap	Compact trajectory, policy-sensitive fields, and downstream effects	Rule hypothesis
Policy-gate correctness	Non-executed proposal, required context, bindings, and gate decision	Prompt update or rule hypothesis
Goal judgment	Compact trajectory, final task state, termination, and evaluator feedback	Prompt update or rule hypothesis

action, a hypothesis revision, acceptance with evidence, or an unresolved outcome. Only accepted rules proceed to the static ledger, where near-duplicate facts are merged. Validation tasks select the resulting harness updates before held-out testing. The detailed role prompts specify which evidence and modifications are available at each stage.

Rule evidence during execution. Task-agent predictions remain separate from the dynamic ledger. State-tracking updates cite tool feedback, action parameters, or an applicable static rule. The tracker reports conflicts and fields requiring verification; fresh observations take precedence when they contradict stored knowledge. The policy-context agent supplies bindings with source paths, and the harness checks those bindings before executing the policy code.

B DETAILED ABLATION RESULTS

To comprehensively evaluate how each component contributes to harness optimization, Table 5 presents detailed numerical results on GLM-5.3-Flash, corresponding to the evolution-view ablation in Section 4.3 (Figure 3a). In this experiment, “No Evolution” represents the unevolved base harness E-LEDGER (E0). To isolate the role of each individual diagnostic perspective, the single-view variants (“Only State Consistency”, “Only Policy-Gate Correctness”, “Only Goal Judgment”, and “Only World Observation Gap”) retain updates and proposals generated strictly from that specific view while keeping the interactive abduction agent active for hypothesis verification. Conversely, the “Without Abduction” variant incorporates diagnostic proposals from all four views simultaneously but bypasses interactive verification, injecting candidate hypotheses directly into the static world layer $\mathcal{W}_S$.

Table 5: Evolution-view ablation experiment on **GLM-5.3-Flash**.

Variant	STCR	TCR	PSR	Steps	Cost (\$)
No Evolution	30.0	45.0	85.0	17.4	0.23
Only State Consistency	55.0	70.0	85.0	18.6	0.44
Only Policy-Gate Correctness	40.0	50.0	90.0	19.4	0.30
Only Goal Judgment	65.0	85.0	80.0	21.6	0.35
Only World Observation Gap	65.0	70.0	95.0	18.7	0.34
Without Abduction	65.0	80.0	85.0	20.3	0.52
WorldAbduct (Full)	75.0	80.0	95.0	20.9	0.52

C AUDIT OF EVOLVED HIDDEN RULES

After training-time evolution, each backbone’s verified world-model facts are merged into a frozen static world layer $\mathcal{W}_S$ and used at test time. Table 6 audits these final facts, not the larger set of unverified proposals. We compare each fact against the gold hidden workflows of the World of Workflows environment (asset cost rewrite, clearance decrement and surrender, group-role inheritance, priority-1 reassignment, department-triggered article flagging, and deactivation cascades). The audit is performed manually: each retained fact is checked against these gold workflows for

agreement in its trigger, applicability conditions, and induced effects, using the categories defined below.

Table 6: Audit of the frozen static world layer $\mathcal{W}_S$ after WorldAbduct. Evolved is the number of verified facts written into the harness. Fully correct, partially correct, and incorrect are mutually exclusive labels of those facts. High-value counts facts that encode a task-critical hidden workflow.

Backbone	Evolved	Fully correct	Partially correct	Incorrect	High-value
DeepSeek-V4-Pro	10	8	2	0	9
GLM-5.3-Flash	15	14	1	0	10
GPT-5.6-Terra	9	7	2	0	7
Kimi-K3	20	20	0	0	10

In Table 6, **Evolved** denotes the total number of verified facts after near-duplicate pruning and merging, where each fact describes a transition $r : (a, s, c) \rightarrow \Delta s$. **Fully correct** indicates that the mechanism and its critical conditions match the gold workflow. **Partially correct** indicates a valid core mechanism with an overly narrow or broad condition, such as restricting department-triggered article flagging to drafts or omitting a manager-reassignment exception in a deactivation cascade. **Incorrect** indicates a mechanism contradicted by the environment. The audit finds no incorrect core mechanisms, while the partially correct facts identify remaining errors in rule scope. **High-value** counts facts describing task-critical hidden workflows, excluding trivial tool-response echoes, default assignments, and uninformative negative observations.

The resulting ledgers contain 9–20 facts, of which 7–10 per backbone describe high-value hidden workflows. Kimi-K3 has the largest ledger and all 20 facts are fully correct under this audit. DeepSeek-V4-Pro obtains the highest downstream STCR with only 10 facts: rule count alone does not determine execution quality, which also depends on how well the backbone uses the ledger during execution.

D CASE STUDY: HARDWARE-ASSET COST REVALUATION

Task. The source episode is one World of Workflows training task. Its description asks the agent to register six hardware assets for two senior engineers. Create a PowerEdge T610, tag D001, valued at \$10,500, and assign it to Imani Okafor. Register a ThinkStation S20, tag I001, worth \$7,000, and an iPhone X, tag I002, worth \$6,000, both assigned to Elara Petrov. Register an iPhone 4, tag A001, valued at \$8,000, for Elara Petrov, and an iPad 3, tag A002, worth \$9,000, for Imani Okafor. Register a Laserjet 4240n, tag D002, valued at \$5,000, for Imani Okafor. Then transfer D002 from Imani Okafor to Elara Petrov, A001 from Elara Petrov to Imani Okafor, and A002 from Imani Okafor to Elara Petrov, and mark Elara Petrov inactive. The costs are literal amounts. The text does not mention a markup, a fee, or any later correction.

Evaluator feedback. GLM-5.3-Flash created all six assets, received a successful create response for each, finished the three transfers, deactivated Elara Petrov, and stopped. None of those create responses contained `cost`, and the trajectory never called `update_hardware_asset`. The agent did not read the stored costs back and did not correct them. The evaluator still returned only one completion error: asset D001 has cost 12575, expected 10500.

That single error is an artifact of the check order. The evaluator walks the assets in task order and returns at the first mismatch. D001, the only asset submitted at 10500, is first. The checks for 7000, 6000, 8000, 9000, and 5000 never run, so their rewritten costs never appear in the feedback.

Goal-judgment hypothesis. Goal judgment saw one failed asset and five assets that the evaluator did not mention. It treated the silence as evidence that those five costs had persisted. Its initial hypothesis can be summarized as follows:

Creating a hardware asset with a submitted cost above \$10,000 may trigger an automatic cost revaluation after creation. The task requested a cost of 10500, but the

evaluator reported a persisted value of 12575. Assets submitted at or below 10000 may have kept their submitted costs. The trigger, timing, and exact adjustment are unknown.

Abduction. The abduction agent tested this hypothesis in a fresh sandbox. It did not resume the source episode. Each step below records the action, the observation, and the hypothesis the agent kept afterward. The arithmetic relation appears only when the agent first wrote it down.

1. **Locate the field.** The agent reads the schema of `alm_hardware` and `alm_asset`. *Hypothesis.* Unchanged. A cost above 10000 may be rewritten after creation. The formula is unknown, and a successful create response will not be treated as proof that the submitted cost persisted.
2. **Prepare a fresh record.** The agent creates a new user and resolves a PowerEdge model. *Hypothesis.* Unchanged.
3. **Reproduce the source value.** The agent creates a PowerEdge T610 at 10500 and reads `alm_hardware`. The stored cost is 12575. The record was updated by `admin` about one second after creation, with `sys_mod_count` equal to 1. *Hypothesis.* The 10500 to 12575 change appears to follow creation. Whether 10000 is a threshold, and what the adjustment rule is, are still open.
4. **Test the threshold.** The agent creates two more PowerEdge T610 assets, at 9000 and at 10000, and reads all three hardware records. The stored costs are 10850 and 12000. *Hypothesis, revised.* The same rewrite occurs at 9000 and at 10000, so the agent drops the \$10,000 threshold. It is at this revision, and not before, that the agent writes the three pairs as

$$\text{cost}_{\text{stored}} = 1.15 \times \text{cost}_{\text{submitted}} + 500. \quad (12)$$

Whether other models follow the same relation is still open. The source episode never reported a cost error on them, because the evaluator had stopped at D001.

5. **Test another cost and another model.** A ThinkStation S20 submitted at 12000 is stored as 14300. A PowerEdge T610 submitted at 20000 is stored as 23500. Both agree with Eq. (12). *Hypothesis.* The relation is not limited to the original 10500 point or to a single model. The agent still treats the source episode’s apparently unchanged lower-cost assets as a possible exception.
6. **Test a later edit.** The agent calls `update_hardware_asset` and sets the first probe back to 10500, then reads it again. The stored cost stays 10500, and `sys_mod_count` is 2. *Hypothesis, revised.* Eq. (12) applies to creation. An explicit cost update after creation is kept as submitted. The agent also writes a tentative scope: the source ThinkStation at 7000, and the iPad, iPhone, and Laserjet assets, may lie outside the rule.
7. **Look for an implementing script.** The agent searches `sys_script` for a cost rule on `alm_hardware` or `alm_asset`. No such script is returned. *Hypothesis.* Unchanged. The relation remains a behavioral rule from the read-backs.
8. **Test the suspected exceptions.** The agent creates an iPad 3 at 9000 and a ThinkStation S20 at 9000. Both are stored as 10850. It also creates a Laserjet 4240n at 5000 and does not read it yet. *Hypothesis, revised.* The fresh probes remove the model exception. Eq. (12) holds for these models at 9000. Whether it holds below 9000 is still open.
9. **Test the lower end, then accept.** The agent creates a ThinkStation S20 at 7000, an iPhone X at 6000, and an iPhone 4 at 8000, and reads them together with the Laserjet. The stored costs are 8550, 7400, 9700, and 6250. These agree with Eq. (12). *Verified rule.* Creating a hardware asset with an explicit cost rewrites the persisted cost, about one second after insert, by Eq. (12). On the tested range 5000–20000, the rewrite does not depend on a 10000 cutoff or on the asset model. A later `update_hardware_asset` is exempt. The rule is written into $\mathcal{W}_S$ with this action guide: after creation, re-read `alm_hardware.cost`; when the task requires the submitted amount, restore it with an explicit update and read it back.

E ABDUCTION STATISTICS

Table 7 summarizes hidden-rule abduction on the WOW training tasks. Each launched verification run counts as one candidate. A directly verified candidate is accepted without revising the hypothesis; a candidate verified after revision is accepted only after at least one revision. The abduction agent does not emit an explicit rejection, so that column is zero. Unresolved candidates never receive a verified rule, including runs that exhaust the revision budget or remain incomplete. Average steps is the mean number of actual environment interactions across all launched runs, including repeated checks and unresolved or incomplete runs. Only the final rule count is deduplicated; verification outcomes and interaction costs are not.

Table 7: Abduction outcomes and actual interaction costs across all launched checks, including one incomplete GLM-5.3-Flash run. Dedup. rules counts the final distinct rules after merging.

Backbone	Candidates	Direct	Revised	Rejected	Unresolved	Avg. steps	Dedup. rules
DeepSeek-V4-Pro	14	10	3	0	1	14.7	10
GLM-5.3-Flash	16	13	2	0	1	19.1	15
GPT-5.6-Terra	11	7	2	0	2	13.3	9
Kimi-K3	23	20	1	0	2	16.5	20

F ADDITIONAL EVOLUTION ROUND

Besides the three evolution rounds shared by all methods, WorldAbduct spends additional environment interactions on hidden-rule abduction during evolution. On GLM-5.3-Flash, for example, it launches 16 checks with 19.1 interactions each on average (Appendix E). To compare the methods under a closer evolution budget, we give MemoHarness and WorldEvolver one additional evolution round on GLM-5.3-Flash, providing them with extra training trajectories and update opportunities. Table 8 shows that their STCR, TCR, and PSR remain unchanged from the three-round results in Table 1, and WorldAbduct retains a 10-point STCR advantage over MemoHarness and a 30-point advantage over WorldEvolver. The gap therefore cannot be closed simply by giving the baselines more evolution: additional trajectory-based updates do not substitute for targeted verification of hidden rules.

Table 8: Safe task completion rate (STCR), task completion rate (TCR), and policy safety rate (PSR) on GLM-5.3-Flash after one additional evolution round for MemoHarness and WorldEvolver, compared with WorldAbduct.

Method	Evolution rounds	STCR	TCR	PSR
MemoHarness	4	65.0	75.0	90.0
WorldEvolver	4	45.0	55.0	85.0
WorldAbduct	3	75.0	80.0	95.0

G LIMITATIONS

The interactive environments make full evolution and evaluation costly, so we report single-run results for each configuration.

H AI USE STATEMENT

We used generative AI tools to polish the language of the manuscript and to assist with writing, as well as to help implement experimental and analysis code. We have reviewed all AI-assisted text and code, and take full responsibility for the final content of this paper, including its claims, wording, and experimental results.