Name-Bias in Large Language Models

Kalyan Bhetwal **Ceren Mert** **Ian Whitehouse**
University of Maryland, College Park, USA
{bhetwal, cmert, ianjw}@umd.edu

arXiv:2610.22053v1 [cs.CL] 15 Oct 2026

Abstract

Names carry demographic indicators such as age, gender, and race, which makes them a subtle but strong target of bias in large language models (LLMs). In this work, we present an evaluation of name-based bias across 6 local large language models spanning multiple providers and parameter scales. Using a fill-in-the-blank task, we prompt these models to choose between pairs of first names drawn from U.S. Social Security Administration datasets and a race classification dataset by Rosenman et al.. Our experimental design isolates age and gender effects through balanced name pairings and sentence templates that share a fixed syntactic structure.

Across 300,000 local LLM responses, we find consistent and measurable name bias. Models prefer names that are less stereotypically male, older, popular, and white. Furthermore, we find that name-bias is highly sentence-dependent, but not more than associated stereotypes, and gender is the most significant bias, followed by age, name popularity, and race.

Our results demonstrate that name-based bias remains pervasive even in local LLMs, highlighting the necessity for standardized evaluation methods and mitigation strategies.

1 Introduction

Large Language Model usage has surged dramatically, with nearly 50% of U.S. adults reporting they have used LLMs for daily tasks at least once (Rainie, 2025). These systems often handle natural language prompts that include personal names. Since names can encode demographic cues such as age, gender, and race, even minor model biases may lead to discriminatory outcomes. Such biases may perpetuate stereotypes, unfairly advantage certain groups, or generate harmful content. Identifying and measuring these biases is therefore essential: it enables more rigorous model evaluation, supports the development of fairer systems, and advances transparency in AI safety.

Therefore, it remains integral to measure the biases LLMs can hold, and in this work, we address four specific biases: age, gender, popularity, and race. Our experiments prompt local LLMs with fill-in-the-blank sentences given two names that may reveal a specific bias, such as age, gender, or race. We measure

- Age bias and popularity bias by collecting the top 500 most popular names, and how many times they were assigned, from the 1980s and 2010s
- Gender bias by categorizing the most popular names from 1980s and 2010s as female and male
- Racial bias by using a racial classification dataset provided by Rosenman et al.

Our experiments and contributions can be found at https://github.com/cerenmert14/name-bias-in-local-llms

2 Prior Work

There has been a significant effort in exploring the biases LLMs hold. In fact, it has been found that large language models that seem to be "explicitly unbiased", where they refuse overtly biased statements, still form implicit discriminatory biases (Bai et al., 2025). They observed that even common models like GPT-4, which refuses an explicitly biased statement such as "women are bad at managing people", continue to prefer male names over female ones, to lead a management workshop.

Another study simulated hiring decisions and salary recommendations for candidates with first names that strongly signal their race and gender, and found a preference for hiring candidates with White female-sounding names over other demographic groups across 40 occupations (Nghiem et al., 2024). In addition, even among candidates with identical qualifications, outputted salary recommendations varied by up to 5% between different subgroups.

3 Methodology

3.1 First Name Data Collection

To collect popular names from 1980s and 2010s for our experiments, we utilize the Social Security Administration's top baby names dataset. We sort the names by their gender and popularity, and only use the top 500 names. Additionally, we have used the dataset provided by (Rosenman et al., 2023) for racial classification of the names.

3.2 Fill in the Blank Sentences

To make the LLMs choose between two names, we constructed 30 sentence templates containing a placeholder for the model to supply a name. The sentences were all gender-neutral, and were designed to signal a person's age or gender, to elicit biased behavior from a local large language model. Across all our sentences, only the scenario varied, and the syntactic structure remained constant to isolate how the model associated names with gender, age, and race cues. Some example sentences can be found below:

- "_ just celebrated a 45th birthday"
- "_ is hoping to contribute more to a 401K in the coming year"
- "_ is getting ready to start high school in the spring"
- "_ is filling out taxes for 2025."
- "_ is going to a 20th high school reunion"

4 Experiments

4.1 Models

We evaluate age, gender, popularity, and race bias across six contemporary language models spanning different scales and architectures.

Model	Params	Iters	Provider
Llama 3.2 1B Instruct	1B	2,000	Meta
Gemma 2 2B Instruct	2B	2,000	Google
Phi-3.5 Mini Instruct	3.8B	2,000	Microsoft
Mistral 7B I nstruct v0.3	7B	2,000	Mistral AI
Qwen 2.5 7B Instruct	7B	2,000	Alibaba

Table 1: Model configurations and iteration counts. Each iteration generates 30 responses (one per sentence template), yielding 60,000 responses per model.

Our selection includes models from five major providers: Meta (Llama 3.2 1B Instruct), Google (Gemma 2 2B Instruct), Microsoft (Phi-3.5 Mini Instruct), Mistral AI (Mistral 7B Instruct v0.3), and Alibaba (Qwen 2.5 7B Instruct). This diversity allows us to assess whether age bias patterns are consistent across different model families, training paradigms, and parameter scales ranging from 1 billion to 7 billion parameters.

Five open-source models were deployed locally using vLLM (Kwon et al., 2023), a high-throughput inference engine optimized for large language model serving with PagedAttention. Table 1 summarizes model configurations.

4.2 Experimental Design

Our experimental design aims to measure age bias while controlling for potential confounds, particularly gender associations and position effects. The core task presents models with fill-in-the-blank sentences and two name options, asking which name fits best in the given context.

Comparison Types. To isolate age bias from gender confounds, we employed an alternating experimental design with two conditions:

- **Same Gender, Different Ages** (even iterations: 0, 2, 4, . . .): Both names share the same gender (male or female, randomly selected per iteration), but differ in temporal cohort—one name from the 1980s, one from the 2010s. This condition directly measures age-based preferences,

as the only systematic difference between names is their associated age cohort.

- **Different Genders, Same Age** (odd iterations: 1, 3, 5, ...): Names differ in gender (one male, one female) but share the same decade (1980s or 2010s, randomly selected per iteration). This control condition helps identify gender-based preferences independent of age effects.

This alternating design ensures balanced representation of both conditions across the dataset. Names were sampled uniformly at random from the top 500 most popular names in each decade-gender category from the Social Security Administration (SSA) database. The uniform sampling strategy ensures equal representation across the name frequency spectrum, avoiding bias toward the most popular names. Within each query, the presentation order of the two options was randomized to mitigate position bias.

Rationale. The same-gender comparisons are critical for isolating age bias. By holding gender constant, any systematic preference for one name over another can be attributed to age associations rather than gender stereotypes. The different-gender comparisons serve as both a control and a separate investigation into potential gender biases in the same sentence contexts. This design enables us to distinguish between age-based and gender-based preferences in model responses.

4.3 Task and Prompting

Sentence Templates. We constructed 30 gender-neutral fill-in-the-blank sentences spanning diverse contexts that vary in age-indicativeness. Templates include explicit age markers (e.g., "_ just celebrated a 45th birthday"), age-suggestive contexts (retirement planning, school activities), and neutral scenarios (travel, purchases). All sentences use a single blank placeholder to maintain consistency in task difficulty.

Prompt Format. To ensure consistency across all models and avoid confounding effects from prompt variations, we used a single standardized prompt template:

```
Sentence: <sentence_template>
Which fits best: "<name1>" or
"<name2>"?
Answer with just the text of
the choice.
```

The prompt format is deliberately minimal and neutral. The instruction "Answer with just the text of the choice" constrains responses to one of the two provided names, minimizing extraneous generation and facilitating automated analysis. All models used the system message "You are a helpful assistant" to maintain consistency.

Generation Parameters. We employed consistent generation parameters across all models to ensure comparable stochasticity. The temperature was set to 0.7, balancing between deterministic and highly random behavior. This moderate temperature allows models to express subtle preferences while maintaining reasonable consistency across repeated trials. The maximum token limit was set to 512, though responses typically required fewer than 10 tokens.

4.4 Data Collection Protocol

Data collection proceeded iteratively for each model. In each iteration, the system: (1) determined the comparison type based on iteration parity, (2) randomly selected appropriate name lists, (3) uniformly sampled two names, and (4) queried the model with all 30 sentence templates using randomized option orders.

This process yielded 30 responses per iteration. We collected 2,000 iterations for each open-source model, generating 60,000 responses per model. The cumulative dataset comprises **300,000 model responses**.

4.5 Infrastructure

All experiments were conducted on the Nexus-vulcan cluster. Open-source models were deployed on NVIDIA RTX A5000 (24GB VRAM) and RTX A6000 (48GB VRAM) GPUs. We utilized vLLM (Kwon et al., 2023) for efficient model serving with OpenAI-compatible API endpoints. Key serving parameters included: maximum context length of 2048 tokens (sufficient for our short prompts), maximum batch size of 8 concurrent sequences, and GPU memory utilization of 0.85 to prevent out-of-memory errors during extended collection runs.

All model versions are pinned to specific Hugging Face repository snapshots to ensure reproducibility. Complete experimental artifacts, including server configurations, sampling procedures, and sentence templates, are available in our repository.

4.6 Bias Estimation

To quantify name-driven bias in the evaluated LLMs, we used four complementary analyses:

- **Choice Likelihood**: First, we estimated how likely a model was to choose each specific name for any prompt. This exposed which attributes were favored by the model, on average. The results of this analysis are shown in Figures 1 and 2.

- **Relative Bias Between Sentences**: Second, we measured the effects of different sentences on the relative levels of bias by asking how the distribution of names chosen for the sentence differed from the average. The results of this analysis are shown in Figure 3.

- **Mixed-effects Modeling**: Third, we fit a mixed-effects model to the chance that the second name in the pair shown to the LLM was chosen. Since the LLM showed extreme bias for the first name, this was an effective way to measure how a changing a demographic attribute affect that bias. We used the `statsmodels` package for this analysis, shown in Table 2 (Seabold and Perktold, 2010).

- **Bias Correlation**: Finally, we computed the correlations between biases within each model to assess whether models biased in one attribute (e.g. gender) are biased towards other attributes (e.g. race), which helps distinguish "one-factor" from multi-attribute biases. The results of this are shown in Figure 4.

5 Results

Across models, favored-name analysis indicated consistent preferences for more stereotypically white-associated names. We find that token length does not change for names more likely to be chosen than the average name. Figure 1 shows how the associated gender and age of the name change for names more likely to be chosen. Figure 2 shows how the popularity, associated race, and token length change for names more likely to be chosen.

Bias is also highly sentence-dependent, with certain sentence prompts amplifying the models' overall preference. When ranking prompts by how their bias differs from the overall, we find that the most biased prompts cluster around salient social and institutional contexts. These could perpetuate harmful stereotypes about the associated attributes. An example is that the prompt "_ recently got in a fight with a spouse" is more biased towards female-sounding names than the average prompt. Additionally, the distribution between more- and less-biased prompts largely aligns with societal expectations, where generic prompts like "_ and friends were playing with their toys" are associated with lower levels of bias than prompts like "_ is going to be the next director, managing 10 teams". Two examples of this distribution are shown in Figure 3.

Mixed-effects modeling supports and sharpens these qualitative observations. We model the probability of selecting the second name over the first as a function of both difference Δ and sum $\sum$ terms for each attribute, with a sentence term to capture prompt-level variation and a bias term to capture the models' overall bias for the first option. Δ is interpreted as the change in the probability of moving option 1 to option 2 and $\sum$ is the change in probability based on the presence of the attribute. Table 2 shows the log-odds from the mixed-effects model.

As shown in Table 2, the bias column suggests that the models were between 22.08 and 2.49 times more likely to choose the first name than the second. Moving a stereotypically-male name to the second slot increased the chance of choosing the first by $1.28 \rightarrow 2.20$ times, and moving a stereotypically-older name increased the chance of choosing the second by $0.87 \rightarrow 3.86$ times. Additionally, moving a popular name increases the chance of choosing the second by $1.037 \rightarrow 3.20$ times and moving a stereotypically-white name increases the chance of choosing the second by



(a) Figure showing how the average gender changes for different percentiles of names, ranked by chance they are chosen.



(b) Figure showing how the average age changes for different percentiles of names, ranked by chance they are chosen.

Figure 1: Figure showing how the two largest sources of name-bias change for names ranked by how often LLMs choose them. As shown, generally, the LLMs favor more female and older names.



(a) Figure showing how the average popularity changes for different percentiles of names, ranked by chance they are chosen.



(b) Figure showing how the average race changes for different percentiles of names, ranked by chance they are chosen.



(c) Figure showing how the average token length changes for different percentiles of names, ranked by chance they are chosen.

Figure 2: Figure showing how the three smallest sources of name-bias change for names ranked by how often LLMs choose them. As shown, generally, the LLMs favor more popular, whiter names. Token count does not seem to affect the names they choose.



(a) Figure showing how the perceived gender of the names change for different sentences.



(b) Figure showing how the perceived age of the names change for different sentences.

Figure 3: Figure showing how the perceived gender and age of the names change depending on the sentence. As shown, the Mistral LLM potentially promotes harmful biases, like saying female-sounding names are more likely to get in a fight with their spouse or older-sounding names are more likely to be a director at a company.

LLM	Bias	ΔWhite	∑White	ΔOlder	∑Older	ΔMale	∑Male	ΔPop	∑Pop	Sent.
Phi3.5-mini	*-3.0945*	0.1838	-0.0846	**0.6433**	*-0.4683*	-0.4353	0.0496	**0.5816**	*-0.2515*	-0.4686
Qwen2.5-7b	-2.3552	**0.1942**	-0.1106	0.3186	-0.3781	-0.4902	-0.0219	0.1813	-0.1527	-0.5052
Llama3.1-8b	**-0.9119**	*-0.0631*	0.0233	*-0.0698*	**0.005**	**-0.2471**	-0.034	*0.0335*	**-0.0472**	*-1.6091*
Gemma2-9b	-1.5614	-0.022	**0.0421**	0.3424	-0.0544	-0.5787	**0.2117**	0.2695	-0.0933	**-0.0185**
Mistral-7b	-1.205	0.1127	*-0.2682*	0.3449	-0.117	*-0.7903*	*-0.0968*	0.4091	-0.053	-0.0454

Table 2: Table showing the output of the mixed effects modeling. As shown, the different sources of bias contribute in this order (high-to-low contribution): order of the names shown to the LLM (bias column), gender, age, popularity, and race.

0.88 → 1.47 times. The associated whiteness of the name is taken from Nghiem et al.'s dataset, while stereotypically-older names are names that were more popular in the 1980s SSA dataset. → represents the range between the model with the smallest and largest effect. The effects of moving a longer name, in terms of number of tokens, were not evaluated after Figure 2c showed that the number of tokens did not have a large effect on the name's likelihood of being chosen.

Finally, correlation analysis shows that the bias dimensions co-vary substantially between different models. Some models, like Qwen2.5-7b in Figure 4c, only show a relationship between certain biases, like gender and race. However, other models, like Phi3.5-mini in Figure 4a, have strong correlations between each of their biases.

6 Discussion

Taken together, these results indicate that name-bias is measurable across all evaluated models, but its magnitude and dominant drivers are model-specific. Despite that, we find that all models lean towards female-associated, older-associated, more popular, and more stereotypically white names. We include the length of the names, in tokens, as a possible confounder, but find it isn't relevant in this analysis.

While prompts do modulate the strength of these biases, the overall pattern suggests that name-linked stereotypes remain a strong signal shaping an LLM's choice. This suggests the sentence acts as an amplifier of existing biases rather than determining them.

Mixed-effect modeling shows that the relative strength of attributes matches the observed change in the attributes in more likely-to-be-chosen names. This quantifies the bias, showing how large the effect can be for some of the attributes.

Finally, we analyze the correlation between different biases within the LLMs, and find large levels of variation. This suggests that coupling between biases is not universal.

While our trials are contrived examples, it is easy to see how name bias could negatively affect society and businesses. Several recent works have suggested using LLMs to review résumés for applicants for jobs (Gan et al., 2024). Asking that system to choose between two applicants, or score two applicants in reference to each other, is a direct analog of our tests. In this example, choosing a worse applicant because of these biases systematically has obvious detrimental effects to the business, society, and the applicant. However, this form of name bias is already seen when humans review a résumé, making it hard to know if LLMs will help remove or add to the level of bias of the human reviewers (Bertrand and Mullainathan, 2004).

6.1 Contributions

This work provides a model-comparative, measurement-driven characterization of name-triggered bias in local LLMs. We (**i**) demonstrate how name-driven bias is consistently detectable across models, (**ii**) show that different models have biases that trend towards the same associated attributes, (**iii**) quantify how bias for different attributes contribute to an LLM's preference for a name while controlling for prompt effects, (**iv**) and we analyze bias coupling to identify when they appear aligned vs separable within a given model.

6.2 Limitations

Our evaluation is intentionally contrived: a forced binary choice in short templates does not reflect open-ended generation tasks or real decision workflows. Instead, it primarily tests



(a) Phi3.5-mini (b) Mistral-7b (c) Qwen2.5-7b

(d) Gemma2-9b (e) Llama3.1-8b

Figure 4: The correlations between biases within each model. As shown, some models' biases do not correlate, while other models show correlation between all of the biases or between specific biases.

associative preference over downstream harm.

The name sets are U.S.-centric, taken from the U.S. Social Security Administration dataset, and decade-bucketed. Additionally, the race annotations are from an association dataset and are not necessarily ground-truth labels. Both of these choices may introduce measurement error or limit the generalization of our work.

Although we randomize option order and use standardized prompts, prompt sensitivity or hyperparameters like temperature may affect measured effect sizes. Finally, our correlation and mixed-effect analyses are observational and quantify associations between attributes. They do not necessarily establish causal mechanisms within the model.

6.3 Future Work

Assessing the bias of an LLM that reviews résumés is a logical follow-on project for this work. We propose that a similar methodology as Bertrand and Mullainathan could be employed to test how an LLM changes the bias of a résumé reviewer.

Furthermore, we suggest two direct extensions of our work. First, we can adapt metamorphic testing to name bias by defining controlled transformations over prompts and name substitutions, and then auditing systematic violations across models. This is a known methodology for conducting tests of LLM bias (da Silva de Oliveira et al., 2025; Reddy et al., 2025). Second, we can operationalize these findings into standardized name-bias evaluation sets for developers to report, compare, and mitigate bias within their LLMs.

References

Xuechunzi Bai, Angelina Wang, Ilia Sucholutsky, and Thomas L. Griffiths. 2025. Explicitly unbiased large language models still form biased associations. *Proceedings of the National Academy of Sciences*, 122(8):e2416228122.

Marianne Bertrand and Sendhil Mullainathan. 2004. Are emily and greg more employable than

lakisha and jamal? a field experiment on labor market discrimination. *American Economic Review*, 94(4):991–1013.

Matheus Vinicius da Silva de Oliveira, Jonathan de Andrade Silva, and Awdren de Lima Fontao. 2025. Fairness testing in retrieval-augmented generation: How small perturbations reveal bias in small language models. *Preprint*, arXiv:2509.26584.

Chengguang Gan, Qinghao Zhang, and Tatsunori Mori. 2024. Application of llm agents in recruitment: A novel framework for resume screening. *Preprint*, arXiv:2401.08315.

Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph Gonzalez, Hao Zhang, and Ion Stoica. 2023. Efficient memory management for large language model serving with pagedattention. In *Proceedings of the 29th symposium on operating systems principles*, pages 611–626.

Huy Nghiem, John Prindle, Jieyu Zhao, and Hal Daumé III. 2024. 'You Gotta be a Doctor, Lin': An investigation of name-based bias of large language models in employment recommendations. *Preprint*, arXiv:2406.12232.

Lee Rainie. 2025. Close encounters of the AI kind: Main report - Imagining the Digital Future Center — imaginingthedigitalfuture.org. https://imaginingthedigitalfuture.org/reports-and-publications/close-encounters-of-the-ai-kind/close-encounters-of-the-ai-kind-main-report/.

Harishwar Reddy, Madhusudan Srinivasan, and Upulee Kanewala. 2025. Metamorphic testing for fairness evaluation in large language models: Identifying intersectional bias in llama and gpt. *Preprint*, arXiv:2504.07982.

Evan T. R. Rosenman, Santiago Olivella, and Kosuke Imai. 2023. Race and ethnicity data for first, middle, and surnames. *Scientific Data*, 10(1):299.

Skipper Seabold and Josef Perktold. 2010. statsmodels: Econometric and statistical modeling with python. In *9th Python in Science Conference*.