

AgentHop: A Diagnostic Benchmark for Agentic Multi-Hop Scientific Question Answering

Chanhee Park¹, Jeongho Yoon¹, Sungbin Han¹, Hyeonseok Moon², Heuseok Lim^{1*}

¹Korea University ²Sookmyung Women’s University
 {pch7678, aa007878, sungbinhan9039, limhseok}@korea.ac.kr
 hyns.moon@sookmyung.ac.kr

Abstract

Agentic tasks require a large language model to interact with the world, navigating information and gathering evidence across multiple steps with restricted resources. Due to this complexity, agentic task failures arise from various sources, and pinpointing these failure causes is essential to diagnose and improve agentic systems. Existing benchmarks, however, tend to focus on a single leaderboard score, leaving the underlying failure modes opaque. To fill this gap, we introduce **AgentHop**, a diagnostic benchmark of 1,011 multiple-choice questions paired with a controlled seven-tool sandbox under fixed token, turn, and tool-call constraints. AgentHop reveals model vulnerabilities by dissecting a single accuracy score along four axes of agent operation: retrieval, synthesis, tool-call, and resource management. Across 19 models, we find that behavior clusters by model family, with tool-call signatures revealing distinct family fingerprints: GPT models commit early, Anthropic and GLM checkpoints verify before committing, DeepSeek and Kimi over-search, and Gemini-3 Pro stays balanced. Decomposed axes further expose within-family structure: Claude Opus 4.6 and Sonnet 4.6 land within one accuracy point yet diverge on retrieval-versus-synthesis emphasis, with Opus retrieving more and Sonnet synthesizing better. We release the full benchmark set² and the harness³ to support diagnostic agent benchmarking.

1 Introduction

A *language agent* is a system built on a large language model (LLM) that interacts with its environment by issuing tool calls and reading observations across multiple turns [1, 2]. On a multi-step task, such as an agent exercises retrieval, reasoning, planning, and execution within a single trajectory [3], and a failure may originate at any of these stages. Each stage calls for a different fix, and a developer choosing between models for deployment, or directing the next round of post-training, needs to know which stage is binding for which model.

The field has issued repeated calls for behavior-decomposed evaluation [4, 5], yet few benchmarks heed that call. Existing benchmarks for agentic tasks in scientific research [6–8], software engineering [9], and multi-service workflow [10] have largely inherited the single metric convention from non-agentic evaluation, prioritizing leaderboard comparability over diagnostic insight [11]. Recent decomposition efforts target only one or two axes, such as chain geometry [12], call-level correctness [13], or per-trajectory progress rate [14], leaving cross-axis interactions invisible.

To measure each core agent behavior systematically, we introduce a **novel four-axis decomposition framework** for agent evaluation that integrates one diagnostic axis per stage into a single per-model

*Corresponding author.

²<https://huggingface.co/datasets/nlpai-lab/agenthop>

³<https://github.com/JohnnyNLP/agenthop>

Table 1: Comparison of AgentHop with existing benchmarks along the four ability axes and a diagnostic indicator.

Benchmark	N	Search	Synth.	Tool-use	Resource	Diagnostic
HotpotQA [16]	113K	✓	✓			
2WikiMultiHopQA [17]	167K		✓			
OpenScholar [7]	2,967	✓	✓			
WebArena [18]	812	✓	✓	✓		
GAIA [19]	466	✓	✓	✓		
BrowseComp [20]	1,266	✓	✓	✓		
AgenticRAGTracer [12]	1,305	✓	✓	✓		✓
BFCL [21]	2,251			✓		
τ -bench [22]	165			✓		
TRAJECT-Bench [13]	5,670			✓		✓
AgentBoard [14]	1,013		✓	✓	✓	
SWE-bench [9]	2,294		✓	✓	✓	
AgentHop (Ours)	1,011	✓	✓	✓	✓	✓

report: search for retrieval, synthesis for reasoning, tool-use pattern for planning, and resource management for execution. This exposes each model’s binding sub-ability [5] and the cross-axis interactions that single-axis benchmarks miss, resonating with Burnell et al. [15]’s broader call for fine-grained reporting in AI evaluation. To put this framework into practice, we built **AgentHop**, a benchmark tailored to evaluate the four-axis agentic sub-abilities.

Our contributions are: (i) **AgentHop**, a 1,011-item multi-step scientific question-answering benchmark grounded in arXiv citation chains across 7,205 papers and over 450K citation edges, with seven-tool resource-constrained agentic evaluation; (ii) a **four-axis decomposition framework** that isolates search, synthesis, tool-use pattern, and resource management from a single evaluation run; and (iii) an **extensive evaluation of 19 models** that shows per-model strengths and weaknesses, family-level traits, and fine-grained per-axis diagnosis.

2 Related Work

We organise prior agent benchmarks around the four ability axes AgentHop measures: agentic search, knowledge synthesis, tool-use pattern, and resource management. We surface key differences below; Table 1 summarizes the comparison.

Agentic search. Agentic-search benchmarks measure how well a model navigates an open environment to locate evidence. WebArena [18], GAIA [19], and BrowseComp [20] score the run end-to-end, without separating navigation skill from synthesis skill at the per-sample level. AgenticRAGTracer [12], the closest concurrent neighbor, decomposes multi-hop failures along *chain geometry*, asking which hop went wrong rather than whether retrieval or reasoning was at fault. AgentHop’s independent recall and conversion metrics separate the two, distinguishing a model that retrieves correctly but reasons poorly from one that does the reverse.

Knowledge synthesis. Knowledge-synthesis benchmarks measure whether a model can reason across documents already retrieved for it. HotpotQA [16] established multi-hop QA as a canonical two-step retrieval-and-reasoning task; 2WikiMultiHopQA [17] scales hop depth on Wikipedia; OpenScholar [7] extends to open-ended scientific synthesis. These benchmarks supply the relevant evidence and evaluate the synthesis step in isolation. AgentHop instead requires the agent to locate the evidence first and then synthesize across it, with the conversion-rate axis isolating reasoning quality from retrieval success.

Tool-use pattern. Tool-use benchmarks measure whether a model can invoke external tools correctly: choosing the right function, supplying well-formed arguments, and respecting schema constraints. The Berkeley Function-Calling Leaderboard (BFCL) [21] scores single-call and multi-turn




Figure 1: Eight-stage construction pipeline. Four *generation* stages (top) seed citation chains from 953 source papers across nine CS venues, draft grounded question–answer pairs, and assign each pair three engineered distractors. Four *filtering* stages (bottom) retire candidates via an automated 3-model ensemble check, a structural-integrity sanity pass, a 7-auditor human review, and a post-audit recall-and-length pass; 1,011 items remain.

function-call correctness, while τ -bench [22] scores end-to-end task completion in multi-turn agent-user-tool interaction; TRAJECT-Bench [13] extends this to trajectory-aware diagnostics on tool selection, argument correctness, and dependency satisfaction. AgentHop adds the per-model action-pattern view via calls-per-turn and per-family bigram and trigram fingerprints, surfacing how each model composes its trajectory rather than just whether each call was well-formed.

Resource management. Staying within token, turn, or cost limits is rarely treated as a primary outcome in agent benchmarks. AgentBoard [14] comes closest by offering progress-rate decomposition alongside accuracy, though it does not budget resources; SWE-bench [9] treats efficiency only secondarily. Beyond these, the deployment-cost dimension is typically reported as supplementary metadata rather than as an evaluation parameter. AgentHop instead treats resource budgets as part of the task’s difficulty, decomposing non-submission failures by which cap is binding to attribute how each model spends its budget.

3 The AgentHop Benchmark

3.1 Task Definition

For each evaluation item, the agent receives a system prompt, the identifier of a single *seed* paper, a research question, and four options labeled A–D. The gold papers that hold the answer are not given; starting from the seed, the agent must navigate the citation graph, read paper sections, and gather evidence before committing to one of the four options. The sandbox of seven built-in tools and the per-run resource budget govern this navigation.

Tools. The agent operates inside a sandbox of seven tools. Five interact with the literature: `keyword_search` retrieves paper IDs whose titles or abstracts match a query; `get_paper_info` surfaces metadata (title, authors, abstract) for a paper ID; `get_references` exposes the citation list of a given paper; `list_sections` enumerates the section headers of a paper; `read_section` returns the full text of a named section. Of these five, only `read_section` returns paper content. The remaining two tools control the run: `think` writes a private deliberation note that does not change

the environment, and `submit_answer` commits to one of the four options and ends the run. Full function-calling schemas, input arguments, and per-call costs for all seven tools are listed in Table 20.

Resource limits. Each run is constrained on three axes: a 20-turn cap on model-to-tool exchanges, a 200K-token cap on the aggregated input and output tokens across all turns, and a 30-point tool-call budget from which each tool call subtracts a tool-specific cost. Because `read_section` returns the full section text, we set its cost at 5 points to discourage greedy reads. Runs that exhaust any of the three caps before reaching `submit_answer` are recorded as *non-submissions*, scored as incorrect, and reported separately as a fail-state diagnostic. When a tool call would overdraw the point budget, the harness rejects the call with an in-context warning and gives the agent one further turn to retry with a cheaper alternative before terminating; full rejection-and-retry semantics are detailed in Appendix F.2. The same protocol applies to every model with no per-model tuning.

Item structure. Each item is defined by two distinctions. **Target multiplicity** separates single-target items (ST), with one gold paper, from multi-target items (MT), which require both. **Depth** separates depth-1 paths, where the agent reaches a gold paper directly from the seed, from depth-2 paths, which pass through one intermediate bridge paper. Crossing the two yields four item types: ST/d1, ST/d2, MT/d1, MT/d2, distinguishing synthesis difficulty from search difficulty. The agent’s search space is the two-hop citation neighborhood of the seed, averaging 311 papers per item; this sets a realistic difficulty regime, large enough that navigation is genuinely challenging yet manageable within the resource budget.

3.2 Construction

AgentHop is built from 7,205 unique research papers connected by over 450K citation edges, all drawn from nine major computer-science venues over 2022–2025. After an eight-stage pipeline of four automatic-generation stages followed by four filtering and audit stages (Figure 1, full detail in Appendix C), 1,011 items survive: 568 single-target and 443 multi-target. Each item is a four-option MCQ grounded in specific sections of one or two of these papers. The seed, any bridge, and every gold paper of each surviving item are guaranteed to have parsed section text available to the agent. Other papers in the citation neighborhood may be metadata-only when their arXiv submission lacks HTML-parseable content; `list_sections` surfaces this status at 1-point cost before any `read_section` attempt. Answering correctly only requires reading gold papers, so partial neighborhood coverage does not block successful trajectories while preserving the full citation graph for navigation. Alongside the correct option, each item carries three engineered distractor options designed to vary along independent dimensions of plausibility: one drawn from the seed paper alone, one drawn from a non-gold paper adjacent to the seed in the citation graph, and one plausible-sounding paraphrase generated by GPT-5.4 without grounding in any supplied paper. We report a detailed analysis of the construction pipeline in Appendix C.

3.3 Evaluation Protocol: Four Diagnostic Axes

Headline accuracy is standard four-option multiple-choice accuracy. In addition, each evaluation run produces four diagnostic measures, defined below, that capture different aspects of the agent’s trajectory. For sample i , let $r_i \in \{0, 1\}$ indicate whether the agent satisfied paper recall, and $c_i \in \{0, 1\}$ whether it answered correctly.

Search axis: paper recall. Each item designates one or more gold papers whose content holds the answer. Paper recall on a sample is $r_i = 1$ iff `read_section` returned the content of at least one section of every gold paper of that sample; calls rejected for insufficient budget or malformed arguments do not count, since no content reaches the agent. `read_section` is the only tool through which an agent obtains evidence to read.

We additionally report *section recall*, a stricter variant: a sample scores 1 iff, for every gold paper, a delivered section contains a `direct`-labelled evidence location. Audit labels cite evidence at the papers’ native subsection granularity while the sandbox’s readable unit is the top-level section, so labels are resolved to their containing readable section before matching (mapping rule in Appendix E.1). Table 2 reports both metrics.

Synthesis axis: conversion rate. Conversion rate is $P(c_i = 1 \mid r_i = 1)$: among samples on which the agent satisfied paper recall, the fraction it answered correctly. Because the denominator is gated on recall, conversion isolates the synthesis ability from retrieval. A model that hits high recall but low conversion can locate the evidence but cannot combine it; the converse profile, low recall and high conversion, identifies a model whose accuracy ceiling is set by retrieval rather than by reasoning.

Tool-use pattern axis: parallel-sequential regime. The tool-use axis characterizes *how* an agent uses its sandbox via *calls per turn*: the mean number of tool calls emitted per assistant turn. A value of 1.0 identifies strictly sequential checkpoints that emit one call per turn; any value above 1.0 implies at least one parallel emission where the model batches related actions within a single turn. The metric has no inherent “higher is better” direction; it is read as a regime indicator alongside accuracy. Additionally, we provide tool-call bigram associations and per-family trigram fingerprints in Appendix E.2.

Resource axis: tokens, turns, and budget points. For each model we report the per-sample means of the three resources as *Avg. Tokens*, *Avg. Turns*, and *Avg. Budgets*, together with three matching *failure rates*: *Max Tokens* marks runs whose aggregate token usage exceeds the 200K cap, *Max Turns* marks runs that reach the 20-turn limit without submitting, and *Max Budgets* marks runs whose tool-call costs exhaust the 30-point budget, each expressed as the percentage of runs that hit the corresponding cap before reaching `submit_answer`. Tokens reflect deployment cost, turns reflect decision count, and budget points reflect tool-call accounting; the paired failure rates name which cap binds when a model fails to submit.

4 Experiments

This section evaluates 19 models on AgentHop. Section 4.1 describes the panel and protocol, Section 4.2 answers four diagnostic questions per axis, Section 4.3 probes three further questions, and Section 4.4 and Section 4.5 close with robustness checks and tool ablations.

4.1 Setup

We evaluate 19 models drawn from three capability tiers. The *closed-frontier* tier comprises six commercial checkpoints: Claude Opus 4.6 [23] and Sonnet 4.6 [24], GPT-5.3 codex [25] and GPT-5.4 [26], Gemini-3 Pro [27] and Gemini-3 Flash [28]. The *open-frontier* tier comprises five open-weight checkpoints: DeepSeek-chat and DeepSeek-reasoner [29], Moonshot Kimi-K2.5 [30], MiniMax M2.7 [31], and Z.ai GLM-5.1 [32]. The *compute-efficient* tier comprises eight open-weight checkpoints from the Gemma family [33, 34] (Gemma-3-27B, Gemma-4-31B, Gemma-4-26B-A4B) and the Qwen family [35–38] (Qwen3-32B, Qwen3-30B-A3B-Instruct, Qwen3.5-27B, Qwen3.5-35B-A3B, Qwen3.6-35B-A3B).

Every model runs the full 1,011 items under the same constraints: seven tools, 20 turns, a 200K-token cap on aggregated tokens across all turns, and a 30-point tool-call budget. Each model is additionally evaluated under a *closed-book protocol* on the same item set: no tools, single-turn answer from prior knowledge, system prompt in Appendix F, Prompt 9. We use the resulting closed-book accuracy as the zero-tool baseline in the ablation analysis in Section 4.5).

4.2 Main Results

Table 2 shows our main results. We ask four diagnostic questions, one per axis. The answers separate the panel by *family* rather than by tier.

RQ1. Does an agent know when to stop searching? The answer varies by family. MT recall is consistently lower than ST recall across all 19 models. Looking at what each model does after reaching a gold paper reveals distinct per-family signatures. GPT-5.3 codex and GPT-5.4 **commit early**: codex submits immediately on 47% of ST and 67% of MT-both items, and the same policy commits prematurely on 34–44% of MT failures. Opus 4.6, Sonnet 4.6, and GLM-5.1 **verify before commit**: nearly all submissions route through *think*, with Anthropic essentially never raw-submitting ($\leq 2\%$). Gemini-3 Flash, DeepSeek-reasoner, DeepSeek-chat, Kimi-K2.5, and MiniMax-M2.7 **over-search**: 61–89% keep reading after the ST gold and 54–62% after both MT golds; on MT failures, Flash

Table 2: Main AgentHop results across 19 models, grouped by capability tier and ranked by accuracy within each family. Highlighted cells mark tier leaders; **bold** marks the panel best. Axis and failure definitions in Section 3.3. Conversion cells are shaded only where a paired same-item test separates the tier leader from the runner-up, as reported in Appendix E.1.

Model	Search ↑				Synthesis ↑		Tool-use Calls /Turn	Resource ↓			Failure Ratio ↓			Outcome ↑
	Recall (ST)	Recall (MT)	SecRec (ST)	SecRec (MT)	Conversion (ST)	Conversion (MT)		Avg. Tokens	Avg. Turns	Avg. Budgets	Max Tokens	Max Turns	Max Budgets	
Closed Frontier														
Gemini-3 Pro	0.868	0.752	0.859	0.655	0.957	0.970	1.05	92.4	9.4	19.8	4.4	0.1	0.0	0.891
Gemini-3 Flash	0.724	0.501	0.680	0.386	0.625	0.644	1.01	180.3	14.1	27.9	27.7	2.1	0.2	0.547
GPT-5.3 codex	0.812	0.623	0.775	0.470	0.896	0.902	1.44	69.5	8.5	25.2	0.3	0.0	0.7	0.825
GPT-5.4	0.808	0.643	0.752	0.454	0.878	0.846	1.74	67.5	7.7	26.5	0.3	0.0	4.9	0.790
Claude Opus 4.6	0.873	0.777	0.854	0.639	0.871	0.855	1.25	110.5	10.6	19.2	6.7	0.0	0.0	0.775
Claude Sonnet 4.6	0.798	0.600	0.773	0.479	0.936	0.891	1.32	95.8	9.7	16.9	3.5	0.9	0.0	0.766
Open Frontier														
GLM-5.1	0.768	0.673	0.734	0.506	0.830	0.768	1.20	102.0	11.5	23.3	3.2	1.6	3.2	0.696
DeepSeek-reasoner	0.720	0.558	0.667	0.436	0.760	0.717	1.00	128.6	14.1	27.1	5.2	1.2	0.0	0.596
DeepSeek-chat	0.773	0.623	0.743	0.506	0.706	0.670	1.00	156.7	15.6	26.9	12.2	2.2	0.0	0.564
Kimi-K2.5	0.764	0.569	0.720	0.463	0.613	0.504	1.08	115.5	13.3	24.7	3.6	3.9	2.5	0.441
MiniMax-M2.7	0.667	0.553	0.604	0.334	0.636	0.465	1.33	84.3	10.5	24.6	1.0	1.4	4.8	0.413
Compute-Efficient														
Gemma-4-31B	0.621	0.521	0.579	0.348	0.788	0.861	1.01	87.6	10.9	22.6	2.4	0.1	0.0	0.648
Gemma-4-26B-A4B	0.352	0.158	0.236	0.093	0.425	0.557	1.01	163.7	14.7	25.3	37.0	6.9	0.3	0.236
Gemma-3-27B	0.139	0.054	0.106	0.025	0.342	0.250	1.00	33.6	6.5	9.5	0.1	0.0	0.0	0.186
Qwen3.5-27B	0.678	0.589	0.623	0.404	0.691	0.617	1.00	100.6	12.1	23.5	7.1	2.1	0.6	0.482
Qwen3.6-35B-A3B	0.505	0.302	0.456	0.174	0.672	0.657	1.00	109.5	12.6	24.5	11.2	3.7	0.8	0.381
Qwen3.5-35B-A3B	0.576	0.472	0.514	0.291	0.517	0.450	1.00	110.4	13.1	26.0	9.3	2.4	1.5	0.320
Qwen3-30B-A3B	0.470	0.460	0.423	0.309	0.318	0.225	1.00	101.7	12.3	18.8	4.8	6.4	0.3	0.160
Qwen3-32B	0.153	0.090	0.130	0.059	0.517	0.225	1.02	37.6	5.3	7.7	0.6	0.2	0.0	0.133

explores without reaching the second gold on 42% of items. Gemini-3 Pro stays **balanced** and is robust on MT failures, with 20% premature commit and 38% continued exploration. Full per-model decomposition is in Appendix E.1.

RQ2. How do models fail with the correct evidence? Synthesis abilities vary widely across the panel. Paired same-item tests, as shown in Appendix E.1, certify the ordering at the extremes: Gemini-3 Pro leads decisively with $p=0.0005$ against Claude Sonnet 4.6 on common recalled multi-target items and MiniMax-M2.7 trails DeepSeek-reasoner decisively ($p=0.0001$), while the four checkpoints between them form a cluster that pairwise testing cannot order at $n \approx 200$; we therefore rank conversion only where the tests separate. Crossing recall with conversion partitions the panel into three behavioral profiles. **Synthesis-bottlenecked** models reach gold papers at open-frontier rates but lose conversion sharply when combining two: MiniMax-M2.7 drops 17 pp ST→MT in conversion; Kimi-K2.5 drops 11 pp. **Retrieval-bottlenecked** models show the inverse: Gemma-4-31B converts 0.861 on the items where it locates both gold papers, near closed-frontier levels, despite a 0.521 MT recall ceiling. **Floor models** like Gemma-3-27B and Qwen3-32B fail at paper-reach upstream of either axis, indicating that the legacy training recipe is inadequate for agentic tasks.

RQ3. Do models act in parallel or in sequence? Both, with a wide empirical gap between the two regimes. **Parallel-emitting** checkpoints batch related actions, averaging 1.20–1.74 calls per turn: the Anthropic and OpenAI families, plus MiniMax-M2.7 and GLM-5.1. The remaining checkpoints are **strictly sequential**, with Gemini-3 Pro and Kimi-K2.5 in the middle at 5–7% multi-call. Family-specific trigrams sharpen the picture within the parallel regime: Anthropic doubles up `list_sections`→`list_sections`→`read_section` on ~ 40% of trajectories versus a 10.7% other-family mean, while OpenAI codex exits-then-relists with `read_section`→`get_paper_info`→`list_sections` on 30–44%. Read together, the emission regime and family trigrams act as training-artifact fingerprints: a model’s tool-call signature places it in a family, layering a provider-level interpretation onto the capability-axis decomposition.

RQ4. How do different models manage the resource constraint? We find three distinct patterns to AgentHop’s tight caps on tokens, turns, and tool-call points. Gemma-3-27B and Qwen3-32B show **under-engagement**, consuming only 33–38K tokens at accuracy below chance, with 29% and 45% of their trajectories never calling `read_section`; the minimalism reflects give-up, not discipline. Gemini-3 Flash and Gemma-4-26B-A4B **overspend** the token cap and retire as non-submissions before answering. **Productive engagement** appears in distinct patterns: GPT-5.4 keeps visible content compact, with no think tool args and minimal assistant text, while Gemini-3 Pro scales resource use with task difficulty; both self-bound well below every cap. Constraint-awareness is what separates the productive cluster from the two pathologies.

Table 3: Action distribution after a wrong-paper `read_section` call. Columns: *Recover* reads a gold paper next, *Stay* reads another non-gold section, *Think* invokes think, *Re-nav* calls any other navigation tool, and *Submit* commits an answer immediately.

Model	n	Recover	Stay	Think	Re-nav	Submit
Closed Frontier						
Gemini-3 Pro	882	3.2%	33.9%	5.4%	50.2%	7.3%
Gemini-3 Flash	2165	1.2%	39.7%	1.5%	50.2%	7.0%
GPT-5.3 codex	1559	1.9%	39.8%	0.0%	53.4%	4.9%
GPT-5.4	1652	3.1%	39.6%	1.8%	52.1%	3.0%
Claude Opus 4.6	904	1.4%	12.7%	82.3%	3.4%	0.1%
Claude Sonnet 4.6	723	7.3%	11.8%	70.5%	10.1%	0.3%
Open Frontier						
GLM-5.1	1564	1.4%	29.9%	38.4%	29.0%	1.1%
DeepSeek-reasoner	1729	6.2%	24.3%	1.2%	58.4%	9.9%
DeepSeek-chat	1448	0.8%	30.3%	20.0%	42.9%	5.9%
Kimi-K2.5	1497	2.7%	35.5%	16.1%	37.5%	7.4%
MiniMax-M2.7	1674	6.8%	39.3%	9.6%	37.3%	6.0%
Compute-Efficient						
Gemma-4-31B	1749	0.7%	38.7%	12.6%	39.6%	8.2%
Gemma-4-26B-A4B	2938	0.4%	58.8%	24.4%	8.9%	3.3%
Gemma-3-27B	405	0.7%	20.5%	0.2%	16.0%	62.2%
Qwen3.5-27B	1441	1.9%	37.8%	2.8%	47.6%	8.7%
Qwen3.6-35B-A3B	2243	1.8%	45.2%	3.8%	44.1%	4.1%
Qwen3.5-35B-A3B	1906	4.8%	40.8%	2.2%	41.2%	9.9%
Qwen3-30B-A3B	678	3.1%	44.2%	31.9%	16.4%	3.7%
Qwen3-32B	413	1.2%	26.6%	0.7%	10.9%	60.5%

4.3 Additional Analysis

In this section, we address three additional questions to sharpen the per-family attribution: how trajectories distinguish efficient navigators, when models fail to submit, and what within-family upgrades actually improve.

Do tool trajectories speak louder than words? Yes: trajectory patterns reveal a verification step that separates efficient navigators from the rest [39]. Bigram associations reproduce the action–observation–think regime of ReAct [2]: `read_section`→`think` associates with +9.8 pp mean accuracy, `think`→`submit_answer` with +10.6 pp, and back-to-back `read_section` without intervening think with −6.8 pp. Conditional on landing on a non-gold paper, Table 3 categorizes what each model does next. *Recover* is rare at $\leq 7\%$ across the panel; the discriminative split is between *Think* and the alternatives. Anthropic’s Opus 4.6 and Sonnet 4.6 *Think* after 70–82% of wrong reads and *Stay* only 12–13%, while GLM-5.1 follows less heavily at 38% *Think*. Other closed-frontier checkpoints and DeepSeek-reasoner *Re-nav* on over half of wrong reads; open-weight and compute-efficient checkpoints *Stay* 35–45% of the time, with Gemma-4-26B-A4B reaching 59%; floor models Gemma-3-27B and Qwen3-32B *Submit* on 60%+ of their wrong reads, a give-up pattern unique to the floor. Full bigram statistics and the permutation-test detail for the family trigrams are in Appendix E.2.

When do models fail? Three distinct mechanisms drive non-submission, each pointing to a different architectural deficit. **Token-cap exceeded** reflects insufficient self-bounding of trajectory length: sparse-active MoE checkpoints saturate the generation cap within a single turn, led by Gemma-4-26B-A4B at 37% and the Qwen MoE family at 7–11%, and long-trajectory checkpoints accumulate moderate per-turn output across many turns, with Gemini-3 Flash at 28% and DeepSeek-chat at 12%. **Max-turns exhausted** reflects an inability to commit: models loop on cheap tool calls without submitting, with Gemma-4-26B-A4B at 7%, Qwen3-30B-A3B at 6%, Kimi-K2.5 at 4%. **Budget exhausted** reflects unmanaged cost-per-call: parallel-emitters drain the 30-point pool by reading greedily, with GPT-5.4 at 5%, MiniMax-M2.7 at 5%, GLM-5.1 at 3%. Capability tier does not predict any of these: GPT-5.3 codex loses only 1% while Gemma-4-26B-A4B loses 44%, and Gemma-4-31B in the same compute-efficient tier loses only 2%. The decomposition therefore localizes the intervention per architecture: output-length discipline for token-cap failures, commitment training for max-turns, and cost-aware tool-call planning for budget; per-cap decomposition is in Appendix E.2.

Are the newer models better for agentic tasks? Mostly, but with one caveat. Figure 2 pairs older and newer checkpoints within the same family, and the four-axis decomposition exposes tradeoffs that headline accuracy hides. The Gemma 3→4 and Qwen-dense 3→3.5 transitions lift every axis simultaneously, dominated in both cases by a roughly five- to sixfold gain in paper recall: post-




Figure 2: Within-family generation gap on overall accuracy. Each panel pairs older-generation checkpoints (light fill) with newer-generation checkpoints (dark fill) within the same architectural cohort, with arrows annotated by the within-family Δ in percentage points.

training on these lineages is buying *search*. The Qwen MoE lineage 3.5→3.6 tells a different story. Headline accuracy rises modestly, but the lift is driven entirely by synthesis: single- and multi-target conversion both grow, while multi-target paper recall regresses below even the three-generation-old MoE baseline, from 0.472 to 0.302. Multi-paper navigation, the one capability the agent loop most directly exercises, is the axis the upgrade quietly gave up.

4.4 Robustness Checks

Three robustness checks validate AgentHop as a diagnostic instrument: cross-benchmark concordance, internal-consistency reliability, and run-to-run stability.

AgentHop accuracy correlates with reasoning and multi-step benchmarks; less so with domain-specialized ones. We compute Spearman rank correlations between AgentHop accuracy and seven external benchmarks on the 16-model overlap. The five reasoning/multi-step benchmarks cluster in a tight 0.67–0.73 band of moderate-to-strong concordance: GPQA-Diamond [40] ($\rho = 0.73$, $n = 15$), HLE [41] no-tools ($\rho = 0.72$, $n = 14$), Terminal-Bench 2.0 [42] ($\rho = 0.70$, $n = 15$), NL2Repo [43] ($\rho = 0.70$, $n = 10$), and HLE with tools ($\rho = 0.67$, $n = 10$). Two domain-specialized benchmarks correlate more weakly: SWE-Bench Pro/Public [9] ($\rho = 0.46$, $n = 12$) and BrowseComp [20] ($\rho = 0.38$, $n = 10$). This differential characterizes AgentHop’s position in the landscape. The high-correlation group (GPQA, HLE, Terminal-Bench, NL2Repo) places it at the intersection of knowledge, code, and tool-use evaluation, indicating that AgentHop taps the shared agentic-reasoning dimension these benchmarks expose. The lower correlation with domain-specialized benchmarks (SWE-Bench Pro/Public, BrowseComp) confirms AgentHop is not a generic capability proxy: it tracks a distinct competence, multi-paper scientific reasoning, beyond what the existing landscape covers. Per-benchmark scores are listed in Table 16 in Appendix E.3.

The instrument exhibits excellent internal-consistency reliability. Treating the per-sample correctness vector across the 19 evaluated models as a binary item-response matrix, we compute Cronbach’s $\alpha = 0.997$, comfortably above the conventional $\alpha \geq 0.9$ “excellent reliability” threshold. Per-item discrimination, measured as the corrected item-total correlation, has a median of 0.55 (Q1 0.39, Q3 0.67); 92.5% of items exceed the conventional $r > 0.2$ discrimination threshold and only 3.2% have $r \leq 0$. AgentHop therefore behaves as a well-formed psychometric instrument rather than a noisy aggregate of unrelated questions: most items contribute coherently to the across-model accuracy ranking.

Run-to-run variation is small relative to the cross-model spread, with one exception. For DeepSeek-chat, Gemma-4-31B, and GPT-5.3 codex we ran the full 1,011-item evaluation three times. Accuracy standard deviation is 0.009 for DeepSeek-chat and 0.006 for GPT-5.3 codex against a between-model spread of 0.758. Gemma-4-31B is the exception: accuracy std 0.031 and tokens std 10.2K (range 21.8K), the latter comparable to cross-model gaps between adjacent closed-frontier

checkpoints. Rank orderings on accuracy and the four axes are preserved across runs, as detailed in Appendix E.3.

4.5 Tool Ablations

To isolate which tools drive AgentHop’s accuracy, we ablate the seven-tool sandbox on three representative checkpoints.

Keyword search contributes only 3–10 pp on top of reference-following navigation, indicating that the citation graph carries most of the search work. On three checkpoints (DeepSeek-chat, Gemma-4-31B, GPT-5.3 codex) we run two ablations: *zero-tool* (closed-book) and *no-search* (full sandbox minus `search_papers`); protocol in Appendix E.4. Table 4 shows the decomposition. The no-search variant recovers most of the tool-conditioned lift over the zero-tool baseline (+23 to +35 pp); adding `search_papers` on top contributes only +3 to +10 pp. Reference-following navigation plus content reading delivers the bulk of the accuracy gain; keyword search is dispensable.

Table 4: Ablation on three checkpoints, with each delta paired between adjacent settings. *Zero-tool*: closed-book. *No-search*: full sandbox minus `search_papers`. *Full-tool*: seven-tool sandbox. Δ_{tools} is the lift from gaining a tool sandbox (zero-tool $\rightarrow$ no-search); Δ_{kw} is the additional lift from adding `search_papers` (no-search $\rightarrow$ full).

Model	Zero-tool (%)	Δ_{tools} (pp)	No-search (%)	Δ_{kw} (pp)	Full-tool (%)
DeepSeek-chat	18.3	+35.0	53.3	+3.1	56.4
Gemma-4-31B	31.7	+23.1	54.8	+10.0	64.8
GPT-5.3 codex	48.6	+30.7	79.3	+3.2	82.5

5 Discussion

Across the 19-model panel, agentic behavior on AgentHop separates by training composition and architecture rather than by capability tier. The four-axis decomposition localizes per-model deficits across search, synthesis, tool use, and resource discipline, surfacing per-family signatures that aggregate accuracy cannot recover.

These diagnoses translate into actionable information for both model developers and pipeline designers. For post-training, the per-model bottleneck attribution names which sub-ability is binding: synthesis-bottlenecked checkpoints benefit from cross-document integration scaffolding, retrieval-bottlenecked checkpoints from navigation training, resource-bound checkpoints from context-management policy. For agentic pipeline design, three regime-level findings distinguish which trade-offs each provider’s training has made: parallel-versus-sequential tool-call training, course-correction patterns after wrong reads, and architecture-clustered failure modes. Together they inform model-selection and trajectory-policy decisions on top of capability tier. Aggregate accuracy compresses these distinctions into one number; per-axis attribution is the natural next step as agent evaluation matures from leaderboard verdicts to mechanism-level diagnosis.

References

- [1] Theodore R. Sumers, Shunyu Yao, Karthik Narasimhan, and Thomas L. Griffiths. Cognitive architectures for language agents, 2024. URL <https://arxiv.org/abs/2309.02427>.
- [2] Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. React: Synergizing reasoning and acting in language models, 2023. URL <https://arxiv.org/abs/2210.03629>.
- [3] Lei Wang, Chen Ma, Xueyang Feng, Zeyu Zhang, Hao Yang, Jingsen Zhang, Zhiyuan Chen, Jiakai Tang, Xu Chen, Yankai Lin, Wayne Xin Zhao, Zhewei Wei, and Jirong Wen. A survey on large language model based autonomous agents. *Frontiers of Computer Science*, 18(6), March 2024. ISSN 2095-2236. doi: 10.1007/s11704-024-40231-1. URL <http://dx.doi.org/10.1007/s11704-024-40231-1>.

- [4] Sayash Kapoor, Benedikt Stroebl, Zachary S. Siegel, Nitya Nadgir, and Arvind Narayanan. Ai agents that matter, 2024. URL <https://arxiv.org/abs/2407.01502>.
- [5] Andrew M. Bean, Ryan Othniel Kearns, Angelika Romanou, Franziska Sofia Hafner, Harry Mayne, Jan Batzner, Negar Foroutan, Chris Schmitz, Karolina Korgul, Hunar Batra, Oishi Deb, Emma Beharry, Cornelius Emde, Thomas Foster, Anna Gausen, María Grandury, Simeng Han, Valentin Hofmann, Lujain Ibrahim, Hazel Kim, Hannah Rose Kirk, Fangru Lin, Gabrielle Kaili-May Liu, Lennart Luettgau, Jabez Magomere, Jonathan Rystrom, Anna Sotnikova, Yushi Yang, Yilun Zhao, Adel Bibi, Antoine Bosselut, Ronald Clark, Arman Cohan, Jakob Foerster, Yarin Gal, Scott A. Hale, Inioluwa Deborah Raji, Christopher Summerfield, Philip H. S. Torr, Cozmin Ududec, Luc Rocher, and Adam Mahdi. Measuring what matters: Construct validity in large language model benchmarks, 2025. URL <https://arxiv.org/abs/2511.04703>.
- [6] Michael D. Skarlinski, Sam Cox, Jon M. Laurent, James D. Braza, Michaela Hinks, Michael J. Hammerling, Manvitha Ponnampati, Samuel G. Rodrigues, and Andrew D. White. Language agents achieve superhuman synthesis of scientific knowledge, 2024. URL <https://arxiv.org/abs/2409.13740>.
- [7] Akari Asai, Jacqueline He, Rulin Shao, Weijia Shi, Amanpreet Singh, Joseph Chee Chang, Kyle Lo, Luca Soldaini, Sergey Feldman, Mike D’arcy, David Wadden, Matt Latzke, Minyang Tian, Pan Ji, Shengyan Liu, Hao Tong, Bohao Wu, Yanyu Xiong, Luke Zettlemoyer, Graham Neubig, Dan Weld, Doug Downey, Wen tau Yih, Pang Wei Koh, and Hannaneh Hajishirzi. Openscholar: Synthesizing scientific literature with retrieval-augmented lms, 2024. URL <https://arxiv.org/abs/2411.14199>.
- [8] Shuo Ren, Can Xie, Pu Jian, Zhenjiang Ren, Chunlin Leng, and Jiajun Zhang. Towards scientific intelligence: A survey of llm-based scientific agents, 2026. URL <https://arxiv.org/abs/2503.24047>.
- [9] Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik Narasimhan. Swe-bench: Can language models resolve real-world github issues?, 2024. URL <https://arxiv.org/abs/2310.06770>.
- [10] Frank F. Xu, Yufan Song, Boxuan Li, Yuxuan Tang, Kritanjali Jain, Mengxue Bao, Zora Z. Wang, Xuhui Zhou, Zhitong Guo, Murong Cao, Mingyang Yang, Hao Yang Lu, Amaad Martin, Zhe Su, Leander Maben, Raj Mehta, Wayne Chi, Lawrence Jang, Yiqing Xie, Shuyan Zhou, and Graham Neubig. Theagentcompany: Benchmarking llm agents on consequential real world tasks, 2025. URL <https://arxiv.org/abs/2412.14161>.
- [11] Samuel Bowman and George Dahl. What will it take to fix benchmarking in natural language understanding? In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 4843–4855, 2021.
- [12] Qijie You, Wenkai Yu, and Wentao Zhang. Agenticragtracer: A hop-aware benchmark for diagnosing multi-step retrieval reasoning in agentic rag, 2026. URL <https://arxiv.org/abs/2602.19127>.
- [13] Pengfei He, Zhenwei Dai, Bing He, Hui Liu, Xianfeng Tang, Hanqing Lu, Juanhui Li, Jiayuan Ding, Subhabrata Mukherjee, Suhang Wang, Yue Xing, Jiliang Tang, and Benoit Dumoulin. Traject-bench: a trajectory-aware benchmark for evaluating agentic tool use, 2025. URL <https://arxiv.org/abs/2510.04550>.
- [14] Chang Ma, Junlei Zhang, Zhihao Zhu, Cheng Yang, Yujiu Yang, Yaohui Jin, Zhenzhong Lan, Lingpeng Kong, and Junxian He. Agentboard: An analytical evaluation board of multi-turn llm agents, 2024. URL <https://arxiv.org/abs/2401.13178>.
- [15] Ryan Burnell, Wout Schellaert, John Burden, Tomer D. Ullman, Fernando Martinez-Plumed, Joshua B. Tenenbaum, Danaja Rutar, Lucy G. Cheke, Jascha Sohl-Dickstein, Melanie Mitchell, Douwe Kiela, Murray Shanahan, Ellen M. Voorhees, Anthony G. Cohn, Joel Z. Leibo, and Jose Hernandez-Orallo. Rethink reporting of evaluation results in ai. *Science*, 380(6641): 136–138, 2023. doi: 10.1126/science.adf6369. URL <https://www.science.org/doi/abs/10.1126/science.adf6369>.

- [16] Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William W. Cohen, Ruslan Salakhutdinov, and Christopher D. Manning. Hotpotqa: A dataset for diverse, explainable multi-hop question answering, 2018. URL <https://arxiv.org/abs/1809.09600>.
- [17] Xanh Ho, Anh-Khoa Duong Nguyen, Saku Sugawara, and Akiko Aizawa. Constructing a multi-hop qa dataset for comprehensive evaluation of reasoning steps, 2020. URL <https://arxiv.org/abs/2011.01060>.
- [18] Shuyan Zhou, Frank F. Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng, Tianyue Ou, Yonatan Bisk, Daniel Fried, Uri Alon, and Graham Neubig. Webarena: A realistic web environment for building autonomous agents, 2024. URL <https://arxiv.org/abs/2307.13854>.
- [19] Grégoire Mialon, Clémentine Fourrier, Craig Swift, Thomas Wolf, Yann LeCun, and Thomas Scialom. Gaia: a benchmark for general ai assistants, 2023. URL <https://arxiv.org/abs/2311.12983>.
- [20] Jason Wei, Zhiqing Sun, Spencer Papay, Scott McKinney, Jeffrey Han, Isa Fulford, Hyung Won Chung, Alex Tachard Passos, William Fedus, and Amelia Glaese. Browsecomp: A simple yet challenging benchmark for browsing agents, 2025. URL <https://arxiv.org/abs/2504.12516>.
- [21] Shishir G Patil, Huanzhi Mao, Fanjia Yan, Charlie Cheng-Jie Ji, Vishnu Suresh, Ion Stoica, and Joseph E. Gonzalez. The berkeley function calling leaderboard (BFCL): From tool use to agentic evaluation of large language models. In *Forty-second International Conference on Machine Learning*, 2025. URL <https://openreview.net/forum?id=2GmDdhBdDk>.
- [22] Shunyu Yao, Noah Shinn, Pedram Razavi, and Karthik Narasimhan. τ -bench: A benchmark for tool-agent-user interaction in real-world domains, 2024. URL <https://arxiv.org/abs/2406.12045>.
- [23] Anthropic. System Card: Claude Opus 4.6. Model release, 2026. URL <https://www-cdn.anthropic.com/14e4fb01875d2a69f646fa5e574dea2b1c0ff7b5.pdf>. Accessed 2026-04-27.
- [24] Anthropic. System Card: Claude Sonnet 4.6. Model release, 2026. URL <https://www-cdn.anthropic.com/bbd8ef16d70b7a1665f14f306ee88b53f686aa75.pdf>. Accessed 2026-04-27.
- [25] OpenAI. GPT-5.3-Codex System Card. Model release, 2026. URL <https://deploymentsafety.openai.com/gpt-5-3-codex/gpt-5-3-codex.pdf>. Accessed 2026-04-27.
- [26] OpenAI. GPT-5.4 Thinking System Card. Model release, 2026. URL <https://deploymentsafety.openai.com/gpt-5-4-thinking/gpt-5-4-thinking.pdf>. Accessed 2026-04-27.
- [27] Google DeepMind. Gemini 3 Pro Model Card. Model release, 2025. URL <https://storage.googleapis.com/deepmind-media/Model-Cards/Gemini-3-Pro-Model-Card.pdf>. Accessed 2026-04-27.
- [28] Google DeepMind. Gemini 3 Flash Model Card. Model release, 2025. URL <https://storage.googleapis.com/deepmind-media/Model-Cards/Gemini-3-Flash-Model-Card.pdf>. Accessed 2026-04-27.
- [29] DeepSeek-AI, Aixin Liu, Aoxue Mei, Bangcai Lin, Bing Xue, Bingxuan Wang, Bingzheng Xu, Bochao Wu, Bowei Zhang, Chaofan Lin, Chen Dong, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chenhao Xu, Chong Ruan, Damai Dai, Daya Guo, Dejian Yang, Deli Chen, Erhang Li, Fangqi Zhou, Fangyun Lin, Fucong Dai, Guangbo Hao, Guanting Chen, Guowei Li, H. Zhang, Hanwei Xu, Hao Li, Haofen Liang, Haoran Wei, Haowei Zhang, Haowen Luo, Haozhe Ji, Honghui Ding, Hongxuan Tang, Huanqi Cao, Huazuo Gao, Hui Qu, Hui Zeng, Jialiang Huang, Jiashi Li, Jiaxin Xu, Jiewen Hu, Jingchang Chen, Jingting Xiang, Jingyang Yuan, Jingyuan Cheng, Jinhua Zhu, Jun Ran, Junguang Jiang, Junjie Qiu, Junlong Li, Junxiao

Song, Kai Dong, Kaige Gao, Kang Guan, Kexin Huang, Kexing Zhou, Kezhao Huang, Kuai Yu, Lean Wang, Lecong Zhang, Lei Wang, Liang Zhao, Liangsheng Yin, Lihua Guo, Lingxiao Luo, Linwang Ma, Litong Wang, Liyue Zhang, M. S. Di, M. Y Xu, Mingchuan Zhang, Minghua Zhang, Minghui Tang, Mingxu Zhou, Panpan Huang, Peixin Cong, Peiyi Wang, Qiancheng Wang, Qihao Zhu, Qingyang Li, Qinyu Chen, Qiushi Du, Ruiling Xu, Ruiqi Ge, Ruisong Zhang, Ruizhe Pan, Runji Wang, Runqiu Yin, Runxin Xu, Ruomeng Shen, Ruoyu Zhang, S. H. Liu, Shanghao Lu, Shangyan Zhou, Shanhuang Chen, Shaofei Cai, Shaoyuan Chen, Shengding Hu, Shengyu Liu, Shiqiang Hu, Shirong Ma, Shiyu Wang, Shuiping Yu, Shunfeng Zhou, Shuting Pan, Songyang Zhou, Tao Ni, Tao Yun, Tian Pei, Tian Ye, Tianyuan Yue, Wangding Zeng, Wen Liu, Wenfeng Liang, Wenjie Pang, Wenjing Luo, Wenjun Gao, Wentao Zhang, Xi Gao, Xiangwen Wang, Xiao Bi, Xiaodong Liu, Xiaohan Wang, Xiaokang Chen, Xiaokang Zhang, Xiaotao Nie, Xin Cheng, Xin Liu, Xin Xie, Xingchao Liu, Xingkai Yu, Xingyou Li, Xinyu Yang, Xinyuan Li, Xu Chen, Xuecheng Su, Xuehai Pan, Xuheng Lin, Xuwei Fu, Y. Q. Wang, Yang Zhang, Yanhong Xu, Yanru Ma, Yao Li, Yao Li, Yao Zhao, Yaofeng Sun, Yaohui Wang, Yi Qian, Yi Yu, Yichao Zhang, Yifan Ding, Yifan Shi, Yiliang Xiong, Ying He, Ying Zhou, Yinmin Zhong, Yishi Piao, Yisong Wang, Yixiao Chen, Yixuan Tan, Yixuan Wei, Yiyang Ma, Yiyuan Liu, Yonglun Yang, Yongqiang Guo, Yongtong Wu, Yu Wu, Yuan Cheng, Yuan Ou, Yuanfan Xu, Yudian Wang, Yue Gong, Yuhan Wu, Yuheng Zou, Yukun Li, Yunfan Xiong, Yuxiang Luo, Yuxiang You, Yuxuan Liu, Yuyang Zhou, Z. F. Wu, Z. Z. Ren, Zehua Zhao, Zehui Ren, Zhangli Sha, Zhe Fu, Zhean Xu, Zhenda Xie, Zhengyan Zhang, Zhewen Hao, Zhibin Gou, Zhicheng Ma, Zhigang Yan, Zhihong Shao, Zhixian Huang, Zhiyu Wu, Zhuoshu Li, Zhuping Zhang, Zian Xu, Zihao Wang, Zihui Gu, Zijia Zhu, Zilin Li, Zipeng Zhang, Ziwei Xie, Ziyi Gao, Zizheng Pan, Zongqing Yao, Bei Feng, Hui Li, J. L. Cai, Jiaqi Ni, Lei Xu, Meng Li, Ning Tian, R. J. Chen, R. L. Jin, S. S. Li, Shuang Zhou, Tianyu Sun, X. Q. Li, Xiangyue Jin, Xiaojin Shen, Xiaosha Chen, Xinnan Song, Xinyi Zhou, Y. X. Zhu, Yanping Huang, Yaohui Li, Yi Zheng, Yuchen Zhu, Yunxian Ma, Zhen Huang, Zhipeng Xu, Zhongyu Zhang, Dongjie Ji, Jian Liang, Jianzhong Guo, Jin Chen, Leyi Xia, Miaojun Wang, Mingming Li, Peng Zhang, Ruyi Chen, Shangmian Sun, Shaoqing Wu, Shengfeng Ye, T. Wang, W. L. Xiao, Wei An, Xianzu Wang, Xiaowen Sun, Xiaoxiang Wang, Ying Tang, Yukun Zha, Zekai Zhang, Zhe Ju, Zhen Zhang, and Zihua Qu. Deepseek-v3.2: Pushing the frontier of open large language models, 2025. URL <https://arxiv.org/abs/2512.02556>.

- [30] Kimi Team, Tongtong Bai, Yifan Bai, Yiping Bao, S. H. Cai, Yuan Cao, Y. Charles, H. S. Che, Cheng Chen, Guanduo Chen, Huarong Chen, Jia Chen, Jiahao Chen, Jianlong Chen, Jun Chen, Kefan Chen, Liang Chen, Ruijue Chen, Xinhao Chen, Yanru Chen, Yanxu Chen, Yicun Chen, Yimin Chen, Yingjiang Chen, Yuankun Chen, Yujie Chen, Yutian Chen, Zhirong Chen, Ziwei Chen, Dazhi Cheng, Minghan Chu, Jialei Cui, Jiaqi Deng, Muxi Diao, Hao Ding, Mengfan Dong, Mengnan Dong, Yuxin Dong, Yuhao Dong, Angang Du, Chenzhuang Du, Dikang Du, Lingxiao Du, Yulun Du, Yu Fan, Shengjun Fang, Qiulin Feng, Yichen Feng, Garimugai Fu, Kelin Fu, Hongcheng Gao, Tong Gao, Yuyao Ge, Shangyi Geng, Chengyang Gong, Xiaochen Gong, Zhuoma Gongque, Qizheng Gu, Xinran Gu, Yicheng Gu, Longyu Guan, Yuanying Guo, Xiaoru Hao, Weiran He, Wenyang He, Yunjia He, Chao Hong, Hao Hu, Jiayi Hu, Yangyang Hu, Zhenxing Hu, Ke Huang, Ruiyuan Huang, Weixiao Huang, Zhiqi Huang, Tao Jiang, Zhejun Jiang, Xinyi Jin, Yu Jing, Guokun Lai, Aidi Li, C. Li, Cheng Li, Fang Li, Guanghe Li, Guanyu Li, Haitao Li, Haoyang Li, Jia Li, Jingwei Li, Junxiong Li, Lincan Li, Mo Li, Weihong Li, Wentao Li, Xinhang Li, Xinhao Li, Yang Li, Yanhao Li, Yiwei Li, Yuxiao Li, Zhaowei Li, Zheming Li, Weilong Liao, Jiawei Lin, Xiaohan Lin, Zhishan Lin, Zichao Lin, Cheng Liu, Chenyu Liu, Hongzhang Liu, Liang Liu, Shaowei Liu, Shudong Liu, Shuran Liu, Tianwei Liu, Tianyu Liu, Weizhou Liu, Xiangyan Liu, Yangyang Liu, Yanming Liu, Yibo Liu, Yuanxin Liu, Yue Liu, Zhengying Liu, Zhongnuo Liu, Enzhe Lu, Haoyu Lu, Zhiyuan Lu, Junyu Luo, Tongxu Luo, Yashuo Luo, Long Ma, Yingwei Ma, Shaoguang Mao, Yuan Mei, Xin Men, Fanqing Meng, Zhiyong Meng, Yibo Miao, Mingqing Ni, Kun Ouyang, Siyuan Pan, Bo Pang, Yuchao Qian, Ruoyu Qin, Zeyu Qin, Jiezhong Qiu, Bowen Qu, Zeyu Shang, Youbo Shao, Tianxiao Shen, Zhennan Shen, Juanfeng Shi, Lidong Shi, Shengyuan Shi, Feifan Song, Pengwei Song, Tianhui Song, Xiaoxi Song, Hongjin Su, Jianlin Su, Zhaochen Su, Lin Sui, Jinsong Sun, Junyao Sun, Tongyu Sun, Flood Sung, Yunpeng Tai, Chuning Tang, Heyi Tang, Xiaojuan Tang, Zhengyang Tang, Jiawen Tao, Shiyuan Teng, Chaoran Tian, Pengfei Tian, Ao Wang, Bowen Wang, Chensi Wang, Chuang Wang, Congcong Wang, Dingkun Wang, Dinglu Wang, Dongliang Wang, Feng Wang, Hailong Wang, Haiming Wang, Hengzhi Wang, Huaqing Wang, Hui Wang, Jiahao Wang,

Jinhong Wang, Jiuzheng Wang, Kaixin Wang, Linian Wang, Qibin Wang, Shengjie Wang, Shuyi Wang, Si Wang, Wei Wang, Xiaochen Wang, Xinyuan Wang, Yao Wang, Yejie Wang, Yipu Wang, Yiqin Wang, Yucheng Wang, Yuzhi Wang, Zhaoji Wang, Zhaowei Wang, Zhengtao Wang, Zhexu Wang, Zihan Wang, Zizhe Wang, Chu Wei, Ming Wei, Chuan Wen, Zichen Wen, Chengjie Wu, Haoning Wu, Junyan Wu, Rucong Wu, Wenhao Wu, Yuefeng Wu, Yuhao Wu, Yuxin Wu, Zijian Wu, Chenjun Xiao, Jin Xie, Xiaotong Xie, Yuchong Xie, Yifei Xin, Bowei Xing, Boyu Xu, Jianfan Xu, Jing Xu, Jinjing Xu, L. H. Xu, Lin Xu, Suting Xu, Weixin Xu, Xinbo Xu, Xinran Xu, Yangchuan Xu, Yichang Xu, Yuemeng Xu, Zelai Xu, Ziyao Xu, Junjie Yan, Yuzi Yan, Guangyao Yang, Hao Yang, Junwei Yang, Kai Yang, Ningyuan Yang, Ruihan Yang, Xiaofei Yang, Xinlong Yang, Ying Yang, Yi Yang, Yi Yang, Zhen Yang, Zhilin Yang, Zonghan Yang, Haotian Yao, Dan Ye, Wenjie Ye, Zhuorui Ye, Bohong Yin, Chengzhen Yu, Longhui Yu, Tao Yu, Tianxiang Yu, Enming Yuan, Mengjie Yuan, Xiaokun Yuan, Yang Yue, Weihao Zeng, Dunyuan Zha, Haobing Zhan, Dehao Zhang, Hao Zhang, Jin Zhang, Puqi Zhang, Qiao Zhang, Rui Zhang, Xiaobin Zhang, Y. Zhang, Yadong Zhang, Yangkun Zhang, Yichi Zhang, Yizhi Zhang, Yongting Zhang, Yu Zhang, Yushun Zhang, Yutao Zhang, Yutong Zhang, Zheng Zhang, Chenguang Zhao, Feifan Zhao, Jinxiang Zhao, Shuai Zhao, Xiangyu Zhao, Yikai Zhao, Zijia Zhao, Huabin Zheng, Ruihan Zheng, Shaojie Zheng, Tengyang Zheng, Junfeng Zhong, Longguang Zhong, Weiming Zhong, M. Zhou, Runjie Zhou, Xinyu Zhou, Zaida Zhou, Jinguo Zhu, Liya Zhu, Xinhao Zhu, Yuxuan Zhu, Zhen Zhu, Jingze Zhuang, Weiye Zhuang, Ying Zou, and Xinxing Zu. Kimi k2.5: Visual agentic intelligence, 2026. URL <https://arxiv.org/abs/2602.02276>.

- [31] MiniMax AI. MiniMax-M2.7. Hugging Face model card, 2026. URL <https://huggingface.co/MiniMaxAI/MiniMax-M2.7>. Accessed 2026-04-27.
- [32] Z.ai. GLM-5.1. Hugging Face model card, 2026. URL <https://huggingface.co/zai-org/GLM-5.1>. Accessed 2026-04-27.
- [33] Gemma Team, Aishwarya Kamath, Johan Ferret, Shreya Pathak, Nino Vieillard, Ramona Merhej, Sarah Perrin, Tatiana Matejovicova, Alexandre Ramé, Morgane Rivière, Louis Rouillard, Thomas Mesnard, Geoffrey Cideron, Jean bastien Grill, Sabela Ramos, Edouard Yvinec, Michelle Casbon, Etienne Pot, Ivo Penchev, Gaël Liu, Francesco Visin, Kathleen Kenealy, Lucas Beyer, Xiaohai Zhai, Anton Tsitsulin, Robert Busa-Fekete, Alex Feng, Naveen Sachdeva, Benjamin Coleman, Yi Gao, Basil Mustafa, Iain Barr, Emilio Parisotto, David Tian, Matan Eyal, Colin Cherry, Jan-Thorsten Peter, Danila Sinopalnikov, Surya Bhupatiraju, Rishabh Agarwal, Mehran Kazemi, Dan Malkin, Ravin Kumar, David Vilar, Idan Brusilovsky, Jiaming Luo, Andreas Steiner, Abe Friesen, Abhanshu Sharma, Abheesht Sharma, Adi Mayrav Gilady, Adrian Goedeckemeyer, Alaa Saade, Alex Feng, Alexander Kolesnikov, Alexei Bendebury, Alvin Abdagic, Amit Vadi, András György, André Susano Pinto, Anil Das, Ankur Bapna, Antoine Miech, Antoine Yang, Antonia Paterson, Ashish Shenoy, Ayan Chakrabarti, Bilal Piot, Bo Wu, Bobak Shahriari, Bryce Pettrini, Charlie Chen, Charline Le Lan, Christopher A. Choquette-Choo, CJ Carey, Cormac Brick, Daniel Deutsch, Danielle Eisenbud, Dee Cattle, Derek Cheng, Dimitris Paparas, Divyashree Shivakumar Sreepathihalli, Doug Reid, Dustin Tran, Dustin Zelle, Eric Noland, Erwin Huizenga, Eugene Kharitonov, Frederick Liu, Gagik Amirkhanyan, Glenn Cameron, Hadi Hashemi, Hanna Klimczak-Plucińska, Harman Singh, Harsh Mehta, Harshal Tushar Lehri, Hussein Hazimeh, Ian Ballantyne, Idan Szpektor, Ivan Nardini, Jean Pouget-Abadie, Jetha Chan, Joe Stanton, John Wieting, Jonathan Lai, Jordi Orbay, Joseph Fernandez, Josh Newlan, Ju yeong Ji, Jyotinder Singh, Kat Black, Kathy Yu, Kevin Hui, Kiran Vodrahalli, Klaus Greff, Linhai Qiu, Marcella Valentine, Marina Coelho, Marvin Ritter, Matt Hoffman, Matthew Watson, Mayank Chaturvedi, Michael Moynihan, Min Ma, Nabila Babar, Natasha Noy, Nathan Byrd, Nick Roy, Nikola Momchev, Nilay Chauhan, Naveen Sachdeva, Oskar Bunyan, Pankil Botarda, Paul Caron, Paul Kishan Rubenstein, Phil Culliton, Philipp Schmid, Pier Giuseppe Sessa, Pingmei Xu, Piotr Stanczyk, Pouya Tafti, Rakesh Shivanna, Renjie Wu, Renke Pan, Reza Rokni, Rob Willoughby, Rohith Vallu, Ryan Mullins, Sammy Jerome, Sara Smoot, Sertan Girgin, Shariq Iqbal, Shashir Reddy, Shruti Sheth, Siim Põder, Sijal Bhatnagar, Sindhu Raghuram Panyam, Sivan Eiger, Susan Zhang, Tianqi Liu, Trevor Yacovone, Tyler Liechty, Uday Kalra, Utku Evci, Vedant Misra, Vincent Roseberry, Vlad Feinberg, Vlad Kolesnikov, Woohyun Han, Woosuk Kwon, Xi Chen, Yinlam Chow, Yuvein Zhu, Zichuan Wei, Zoltan Egyed, Victor Cotruta, Minh Giang, Phoebe Kirk, Anand Rao, Kat Black, Nabila Babar, Jessica Lo, Erica Moreira, Luiz Gustavo Martins, Omar Sanseviero, Lucas

- Gonzalez, Zach Gleicher, Tris Warkentin, Vahab Mirrokni, Evan Senter, Eli Collins, Joelle Barral, Zoubin Ghahramani, Raia Hadsell, Yossi Matias, D. Sculley, Slav Petrov, Noah Fiedel, Noam Shazeer, Oriol Vinyals, Jeff Dean, Demis Hassabis, Koray Kavukcuoglu, Clement Farabet, Elena Buchatskaya, Jean-Baptiste Alayrac, Rohan Anil, Dmitry, Lepikhin, Sebastian Borgeaud, Olivier Bachem, Armand Joulin, Alek Andreev, Cassidy Hardin, Robert Dadashi, and Léonard Hussenot. Gemma 3 technical report, 2025. URL <https://arxiv.org/abs/2503.19786>.
- [34] Gemma Team. Gemma 4. Model release, 2026. URL <https://huggingface.co/google/gemma-4-31b-it>. Covers Gemma-4-31B and Gemma-4-26B-A4B. Accessed 2026-04-27.
- [35] An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, Chujie Zheng, Dayiheng Liu, Fan Zhou, Fei Huang, Feng Hu, Hao Ge, Haoran Wei, Huan Lin, Jialong Tang, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jing Zhou, Jingren Zhou, Junyang Lin, Kai Dang, Keqin Bao, Kexin Yang, Le Yu, Lianghao Deng, Mei Li, Mingfeng Xue, Mingze Li, Pei Zhang, Peng Wang, Qin Zhu, Rui Men, Ruize Gao, Shixuan Liu, Shuang Luo, Tianhao Li, Tianyi Tang, Wenbiao Yin, Xingzhang Ren, Xinyu Wang, Xinyu Zhang, Xuancheng Ren, Yang Fan, Yang Su, Yichang Zhang, Yinger Zhang, Yu Wan, Yuqiong Liu, Zekun Wang, Zeyu Cui, Zhenru Zhang, Zhipeng Zhou, and Zihan Qiu. Qwen3 technical report, 2025. URL <https://arxiv.org/abs/2505.09388>.
- [36] Qwen Team. Qwen3.5-27B. Hugging Face model card, 2026. URL <https://huggingface.co/Qwen/Qwen3.5-27B>. Dense 27B variant of the Qwen3.5 generation. Accessed 2026-04-27.
- [37] Qwen Team. Qwen3.5-35B-A3B. Hugging Face model card, 2026. URL <https://huggingface.co/Qwen/Qwen3.5-35B-A3B>. Mixture-of-experts variant of the Qwen3.5 generation with 35B total / 3B active parameters. Accessed 2026-04-27.
- [38] Qwen Team. Qwen3.6-35B-A3B. Hugging Face model card, 2026. URL <https://huggingface.co/Qwen/Qwen3.6-35B-A3B>. Mixture-of-experts variant of the Qwen3.6 generation with 35B total / 3B active parameters. Accessed 2026-04-27.
- [39] Noah Shinn, Federico Cassano, Edward Berman, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning, 2023. URL <https://arxiv.org/abs/2303.11366>.
- [40] David Rein, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R. Bowman. Gpqa: A graduate-level google-proof q&a benchmark, 2023. URL <https://arxiv.org/abs/2311.12022>.
- [41] Long Phan, Alice Gatti, Ziwen Han, Nathaniel Li, Josephina Hu, Hugh Zhang, Chen Bo Calvin Zhang, Mohamed Shaaban, John Ling, Sean Shi, et al. Humanity’s last exam. *arXiv preprint arXiv:2501.14249*, 2025.
- [42] Mike A Merrill, Alexander G Shaw, Nicholas Carlini, Boxuan Li, Harsh Raj, Ivan Bercovich, Lin Shi, Jeong Yeon Shin, Thomas Walshe, E Kelly Buchanan, et al. Terminal-bench: Benchmarking agents on hard, realistic tasks in command line interfaces. *arXiv preprint arXiv:2601.11868*, 2026.
- [43] Jingzhe Ding, Shengda Long, Changxin Pu, Huan Zhou, Hongwan Gao, Xiang Gao, Chao He, Yue Hou, Fei Hu, Zhaojian Li, Weiran Shi, Zaiyuan Wang, Daoguang Zan, Chenchen Zhang, Xiaoxu Zhang, Qizhi Chen, Xianfu Cheng, Bo Deng, Qingshui Gu, Kai Hua, Juntao Lin, Pai Liu, Mingchen Li, Xuanguang Pan, Zifan Peng, Yujia Qin, Yong Shan, Zhewen Tan, Weihao Xie, Zihan Wang, Yishuo Yuan, Jiayu Zhang, Enduo Zhao, Yunfei Zhao, He Zhu, Liya Zhu, Chenyang Zou, Ming Ding, Jianpeng Jiao, Jiaheng Liu, Minghao Liu, Qian Liu, Chongyang Tao, Jian Yang, Tong Yang, Zhaoxiang Zhang, Xinjie Chen, Wenhao Huang, and Ge Zhang. Nl2repo-bench: Towards long-horizon repository generation evaluation of coding agents, 2026. URL <https://arxiv.org/abs/2512.12730>.

A Limitations

Despite a rigorous data pipeline and evaluation process, AgentHop is not without limitations. Five caveats qualify the conclusions of the main paper: a parametric-knowledge floor, a single-domain corpus, generator-evaluator overlap, differential axis informativeness, and the observational nature of the trajectory findings.

Parametric floor. AgentHop evaluates models that have largely been trained on the cited literature; some fraction of each model’s accuracy is parametric familiarity rather than agentic competence. The Section 4.5 zero-tool ablation provides one bound: closed-book accuracy ranges 0.49–0.73 for closed-frontier and 0.18–0.38 for open-frontier checkpoints, while the no-search lift over closed-book is +23 to +35 pp on the three ablated models. We do not subtract this floor counterfactually; the four-axis decomposition surfaces per-model behavior on top of the floor rather than offering a counterfactual measure of agentic capability.

Single domain, single format. The corpus is restricted to nine computer-science venues over 2022–2025, and every item is a four-option multiple-choice question. Behaviour on other fields, on long-tail venues, and on open-ended response formats is not measured here, and we do not claim that the per-model bottleneck attributions generalize outside this distribution.

Generator–evaluator overlap. GPT-5.4 is used to generate the questions, the distractor options, and the audit-prep guides for all 1,011 released items. To bound the effect of generator identity, we rebuilt the pipeline with a disjoint generator (Inkling) on fresh seeds and obtained a 94-item subset. GPT-5.4 scores 78.7% on the subset it did not write, with a 95% confidence interval of 69.4–85.8, and 79.0% on the items it generated, a difference of 0.3 percentage points. However, the subset is small and therefore we cannot exclude subtler stylistic overlap and does not support per-axis comparison.

Differential axis informativeness. The four axes are not equally informative across the capability spectrum. Paper recall is most discriminating in the middle and bottom of the panel, where the difference between 0.10 and 0.83 recall is enormous; at the top, the closed-frontier paper-recall range (0.71–0.83) is narrow. Conversion rate, by contrast, separates closed-frontier checkpoints sharply (Pro 0.96, Opus 0.86) but compresses at the bottom where recall denominators are small. We do not claim equal diagnostic power on every axis at every tier; we expect different axes to carry the load for different models.

Inference confounds. Tool-call signatures such as calls per turn, think usage, and family trigrams are measured through each provider’s native serving interface. Reasoning modes, parallel tool-call support, and tool-call parsing differ across providers and are not controlled. The family fingerprints in Section 4 therefore characterize model-plus-interface systems, not model architecture alone.

Observational, not causal. The behavioral findings are correlational. Trigram-pattern signatures associate with model families and strategy concentration associates with capability tier, but trajectory data alone cannot establish that a particular tool-use pattern *causes* a particular accuracy level. We treat strategy–accuracy associations as diagnostic correlates rather than as architectural prescriptions.

B Ethical Considerations

We discuss ethical considerations and broader impacts of AgentHop as follows.

(1) Intellectual Property. AgentHop is built from 7,205 public arxiv papers across nine major computer-science venues (2022–2025), each under its respective arXiv-deposited license (predominantly arXiv-perpetual and CC-BY family). We use only paper identifiers, abstracts, and named-section text, consistent with research-fair-use of publicly available scholarly content; we do not reproduce figures, tables, or any non-textual content. Closed-frontier checkpoints (Anthropic Claude, OpenAI GPT, Google Gemini) are accessed under each provider’s API terms of service. Open-frontier checkpoints are accessed via two API providers: `deepseek-chat` and `deepseek-reasoner` (both resolving to DeepSeek-V3.2 [29] during our evaluation window) via DeepSeek’s own API; Kimi-K2.5, MiniMax-M2.7, and GLM-5.1 via the OpenAI-compatible Together.ai endpoint. Compute-efficient

open-weight checkpoints (Qwen3.x, Gemma 3/4) are served locally on a pair of H100 GPUs with vLLM. All evaluations use the model checkpoints solely for academic comparison and respect each provider’s terms of use. AgentHop will be released on Hugging Face under the CC-BY 4.0 license; the evaluation harness will be released on GitHub under the Apache-2.0 license, supporting reproduction of reported results by running models against the same protocol under the same resource budget.

(2) Broader Impacts. AgentHop is a diagnostic instrument for evaluating multi-step scientific question-answering agents. AgentHop scores can be reported as a leaderboard ranking; for deployment decisions, we recommend pairing them with established benchmarks for the target task and consulting the per-axis decomposition of Section 3.3 for failure-mode attribution. To preserve evaluation integrity, the benchmark items and gold-section labels should not be incorporated into LLM training corpora.

(3) Controlling Potential Risks. AgentHop items are multiple-choice questions over public scholarly content. The released dataset contains no personal information, no harmful or offensive content, and no generative model weights. The evaluation harness operates as a closed sandbox: tools are limited to the seven literature-interaction primitives in Section 3.1 and do not perform external API calls or web access beyond model inference itself.

(4) Human Annotation. Seven auditors (two master’s-level and five PhD-level computer-science students) reviewed audit-prep items during Stage 7 of the construction pipeline described in Appendix C. Auditors are members of the research team and participated voluntarily as part of the paper’s data-curation process; no external paid annotation was conducted. Each auditor used the audit-prep guide reproduced in Appendix F and the Gradio review interface to inspect machine-generated items, the relevant source-paper sections, and the proposed gold answer. No personal information of auditors is collected or released.

(5) LLM Usage. LLMs are used in three distinct roles in this work. *Construction:* GPT-5.4 is the primary generation model for question–answer pairs (Stage 3) and audit-prep items (Stage 7); the three-model shortcut-detection and consensus-filter ensemble in Stage 5 uses GPT-4.1, Claude Sonnet 4.6, and deepseek-chat (full prompts in Appendix F). *Evaluation:* the 19-model panel of Section 4 is the subject of the evaluation and is not used to generate or label test data after Stage 7; the generator–evaluator overlap involving GPT-5.4 is acknowledged as a limitation in Section A. *Writing assistance:* LLMs were used for editing and formatting only and did not contribute to scientific claims.

C Construction Pipeline Details

This appendix expands the eight-stage construction pipeline summarized in Section 3.2. Table 5 records the per-stage drop counts. The pipeline is symmetric by design: four *generation* stages assemble each candidate sample (seed → citation chain → Q/A → distractors) and four *filtering* stages then retire candidates that fail one or another quality criterion (model-ensemble checks → structural and content sanity → human audit → post-audit triage).

Stage 1: Seed selection. Venue and citation metadata are obtained from the Semantic Scholar API. The 953 seed papers are stratified across nine venues, NeurIPS, ICML, ICLR, ACL, EMNLP, NAACL, CVPR, ECCV, SIGIR, spanning publication years 2022–2025 to represent contemporary methodological breadth. Within each venue, seeds are sampled in three year-tiers with citation-count thresholds calibrated so that older papers must clear a higher bar to be included: *recent* (2024–2025, no citation requirement, target 500), *established* (2023, ≥ 50 citations, target 300), and *well-known* (2022, ≥ 300 citations, target 200). The decreasing-recency, increasing-citation rule keeps the seed pool dominated by genuinely recent work while ensuring that the older tier still admits only papers that have demonstrably sustained community attention. Stratification balances per-venue counts within $\pm 15\%$ of the target proportion, requires each seed to have 15–50 references (enough for chain construction, while excluding surveys), and removes position and tutorial papers via metadata filtering.

Table 5: Per-stage attrition through the eight-stage construction pipeline. Stages 1–4 grow each sample from a seed paper to a fully populated four-option MCQ; Stages 5–8 then filter the resulting pool.

Stage	Description	Drops	Cumulative
<i>Generation</i>			
1	Seed selection	—	953
2	Citation-chain expansion	—	17,983
3	Q/A generation (BFS + DFS)	—	1,651
4	Distractor generation (3-trap)	—	1,651
<i>Filtering</i>			
5	Model-ensemble filtering (shortcut detection −68 + consensus −434)	−502	1,149
6	Data sanity check (structural integrity)	−71	1,078
7	Human audit (116 flagged, 35 manually retired)	−35	1,043
8	Post-filtering (recall triage −5 + length filter −27)	−32	1,011

Stage 2: Citation-chain expansion. For each seed we follow outgoing citations one or two hops, retaining only chains in which every paper is recoverable through Semantic Scholar API and has at least one accessible PDF. Each candidate chain is then scored by a hierarchical filter: a Jaccard reference-overlap pre-filter (threshold ≥ 0.08 on shared references between adjacent hops, ensuring topical coherence), a citation-context substantiveness check (≥ 80 -character methodology- or result-intent contexts; “background”-only citations are skipped), and finally an LLM judge that rates the *curiosity gap* of the chain on a 1–5 scale conditioned on abstracts and citation context. The judge prompt (Appendix F, Prompt F.2) instructs GPT-5.4 to reason about whether a researcher reading the seed would naturally want to follow the citation to read the candidate paper, and only chains scoring ≥ 4 survive. Chains with broken edges, single-author dominance, or cited-paper publication years before 2020 are dropped. The 953 seeds yield 17,983 candidate chains: 11,046 at depth-1 and 6,937 at depth-2.

Corpus collection. After candidate chains are constructed in Stage 2, full text for every paper in the surviving citation neighborhoods is fetched and parsed. The arXiv API supplies titles, authors, abstracts, and references; body content is obtained from ar5iv (the arXiv HTML rendering service) for section-structured parsing, and falls back to arXiv-hosted HTML when ar5iv rendering fails. The fetched HTML is parsed into named sections and cached. Papers without an accessible arXiv source, conference accepted papers whose authors did not deposit a preprint, or older venues with gated proceedings, are retained as metadata-only nodes in the citation graph: `get_paper_info` and `get_references` continue to operate on them, while `read_section` returns a not-available signal. The nine venues used in Stage 1 are chosen for high arXiv-deposit rates, ensuring stable section-level coverage of the gold path. Across the 1,011 retained samples, two-hop neighborhoods average 311 papers per query (median 315, range 82–667), of which a median 137 carry parsed section text (range 8–274). The seed-to-bridge-to-target chain of every sample is guaranteed by the Stage 6 structural integrity check to have full content; metadata-only papers elsewhere in the neighborhood reflect realistic arxiv coverage gaps, and dead-end `read_section` calls on them surface in the tool-use and resource axes. Empirically, neighborhood size does not predict difficulty: across the 1,011 retained samples, the Spearman correlation between two-hop neighborhood size and panel-19 mean correctness is $+0.01$ ($p = 0.70$, n.s.), with per-model correlations all within $|\rho| < 0.07$. Pool size is therefore neighborhood breadth, not difficulty.

Stage 3: Q/A generation. GPT-5.4 generates one open-ended question–answer pair per chain that survives the pre-filters of Stage 2, following templated prompts that target the citation evidence (single-target / BFS) or the synthesis between two cited papers (multi-target / DFS); the verbatim system prompts are reproduced in Appendix F (Prompt F.2 for BFS and Prompt F.2 for DFS). The prompts explicitly forbid the generator from naming the target paper’s method names or title verbatim in the question, so an agent cannot shortcut to the gold paper by pattern-matching the question against paper titles or methodology vocabulary. Each call receives the full text of the seed paper, the gold target paper(s), and the chain edge metadata, and emits a structured record containing the question, the gold answer, and the verbatim answer-context span from the cited paper. The generator additionally tags each item with one of four *reasoning-type* labels reflecting what the question asks

for: **GROUND** (a paper-grounded factual claim), **METHOD** (a specific technical procedure used by a paper), **MOTIVE** (why a paper was written or how it relates to prior work), and **RESULT** (an empirical outcome the paper reports). The labels are assigned at generation time from the question structure and verified during Stage 7; they are not used to score answers and do not enter the four-axis decomposition of Section 3.3, but supply a categorical breakdown reported in Appendix E.1. Generations that violate the schema or fail the seed-grounding rules are retried up to three times before the chain is dropped. Stage 3 yields 1,651 grounded Q/A pairs ready for distractor generation, with reasoning-type counts of GROUND 330, RESULT 292, MOTIVE 265, and METHOD 124 in the final 1,011-item set.

Stage 4: Distractor generation. Each Q/A pair is then expanded into a four-option MCQ by generating the three diagnostic distractors of Section 3.2, **seed_only** and **wrong_paper**, both produced from Prompt F.2, a paper-grounded prompt where the generator answers from the seed paper or a sibling reference, and **no_context**, produced from Prompt F.2, a parametric prompt where the generator answers from internal knowledge alone. The generator never sees the words “distractor” or “wrong answer”; it genuinely tries to answer each question from the wrong or absent source, and the answer is incorrect because the source is wrong. Distractors with high lexical overlap against the gold answer are rejected so that the four options remain semantically separable. Stage 4 retains all 1,651 candidates, each now carrying a gold answer plus three diagnostic distractors.

Stage 5: Model-ensemble filtering. The 3-model ensemble (GPT-4.1, Claude Sonnet 4.6, deepseek-chat) runs two filters with complementary intents.

The *shortcut detection* pass, run with Prompt F.2, checks whether *additional retrieval is actually required*. Each model is given the seed paper text alongside the question and four options; if the ensemble can recover the gold answer from the seed alone, the sample is leaking its answer into the seed and the agent could shortcut past the cited target paper at evaluation time, so the sample is dropped (68 samples).

The *consensus filter*, run with Prompt F.2, checks whether the gold answer is *the most evident option once the cited paper is provided*. Each model is given the seed paper plus the gold target paper(s) alongside the question and options. We drop samples on which the ensemble cannot converge on the gold answer with full paper access (434 samples), these are weak-gold cases where, even with the cited paper in front of the model, a distractor is more parametrically plausible than the gold itself, so the gold would not stand out as the correct choice at evaluation time. This filter also retires samples whose seed-only or no-context distractor turns out to be factually correct on its own merits, since the ensemble cannot converge on the labeled gold in such cases.

The 502 dropped samples are recorded with their disagreement patterns. The retained 1,149 samples are also assigned a consensus tier from these patterns: **Gold** requires shortcut detection 0/3 and consensus 3/3 (no model could shortcut to the gold from the seed alone, and all three converge on the gold once the target paper is provided), **Silver** requires shortcut detection 1/3 with consensus 3/3, and **Bronze** covers consensus 2/3 (one of the three models disagrees on the gold). Empirically the tiers index construction rigour rather than designed difficulty: mean correctness across the six closed-frontier models is 81.8% on Silver, 79.3% on Gold, and 70.5% on Bronze. Silver outperforms Gold because Silver samples remain partially seed-answerable and so are easier in absolute terms, while Bronze is the hardest because the consensus filter isolates closer-call cases. The principled difficulty axes are question type and depth (Figure 4, panel (a)).

Stage 6: Data sanity check. Stage 6 enforces *structural integrity* of every retained sample’s gold path and retires 71 candidates. Six structural defects, any one of which retires the sample, are checked: SEED_NO_REFS (the seed has no outgoing references in the citation graph); BRIDGE_MISSING (a depth-2 BFS bridge node does not exist in the graph); NO_BRIDGE_PATH (no seed reference leads to the terminal paper); TERMINAL_GHOST (the terminal paper exists in the graph but lacks title metadata); TERMINAL_NO_CONTENT (the terminal has no body sections in the released paper pool); and TARGET_GHOST / TARGET_NO_CONTENT (the multi-target analogues for DFS). All 71 drops at this stage fall into one of these six codes, leaving 1,078 audit-ready candidates.

Two further automated checks run alongside the structural integrity check but do *not* drop samples directly. A *content-navigability* check verifies that distinctive keywords (numbers, proper nouns, technical terms) extracted from the gold answer appear in the gold-target paper’s body text; samples

that fail are recorded as warnings for the Stage 7 auditors but are not retired automatically. A separate *appendix-grounding* check flags samples whose gold answer fragments are found only in appendix sections rather than the main body. We deliberately do not retire appendix-grounded samples here, some of our gold answers genuinely live in supplementary material, and instead surface the flag as a hint to Stage 7 auditors who decide whether the appendix grounding is acceptable on a case-by-case basis.

Stage 7: Human audit. The 1,078 samples that pass Stage 6 are reviewed by seven auditors through the Gradio interface shown in Figure 3. Each sample is presented with the question, the four options, the GPT-5.4 audit-prep JSON described below (under *Audit-prep generation*), and links to the underlying paper PDFs. Auditors mark three quality axes: (i) whether the question is well-formed and unambiguously answerable from the cited papers, (ii) whether the gold answer is supported by the cited evidence, and (iii) whether the section-recall labels are accurate (with the option to add, remove, or re-classify labels). They submit one of three verdicts, Pass, Flag (with a free-text note), or Remove; the latter two collapse to a single *flagged* category at this stage and are not retired automatically. Across the 1,078 samples, 116 receive at least one non-Pass verdict and the remaining 962 are kept as Pass.

The 116 flagged samples are then reviewed in a follow-up triage pass by the lead author, who decides per-sample whether to retain or retire each one. 35 of the 116 are retired (the remaining 81 are retained with the flag preserved as metadata). Table 6 decomposes the 35 retired samples by auditor-note theme: roughly half are infrastructure issues that the automated Stage 6 sanity check missed (HTML-parser collapses or section-extraction errors on the gold paper), and the rest split between weak-chain / under-utilised target, trivial or low-quality question, and answer-not-addressing-question alignment problems.

Table 6: Themes among the 35 samples retired at Stage 7 after manual triage of the 116 audit-flagged candidates. The largest cluster is paper-content extraction failures that the automated structural-integrity check at Stage 6 could not catch because they occur deep inside section text rather than at the metadata level.

Theme	<i>n</i>	Description
Paper-content extraction broken	12	The gold paper’s HTML or section-extraction pipeline produced empty, mangled, or partially captured sections; the auditor saw that the cited paper content needed to ground the answer was missing.
Weak chain / target paper under-utilised	6	The synthesis relies on only one of the two cited papers, or the bridge → terminal step does not actually carry the information the question demands.
Trivial or low-quality question	6	The question or its gold answer is too simple to be diagnostic of multi-hop competence (e.g., the answer is a single-word fact derivable without genuine multi-paper reasoning).
Answer-question alignment failure	6	The gold answer is on-topic but does not satisfy what the question explicitly asks (<i>how</i> vs <i>what</i> , missing tradeoff or comparison, synthesis claim that doesn’t follow from the cited evidence).
Other (sundry, 1 each)	5	Option text misquotes the paper; a numerical detail is incorrect; a non-gold option is also defensible; the answer compares the wrong pair of methods; or the asserted target-paper claim actually originates in the seed paper.
Total retired at Stage 7	35	

Audit quality report. The audit team comprised seven volunteer auditors recruited from the authors’ research group, anonymised as Auditor A through G. All seven are graduate students in computer science (5 PhD candidates, 2 MS students) at the authors’ institution, with prior research experience in machine learning or NLP. Participation was voluntary and uncompensated, and the audit served as internal validation of a benchmark released alongside this paper.

Before the audit began, all auditors received a 30-minute in-person walk-through of the evaluation logics, the three quality axes, and several worked examples of Pass, Flag, and Remove cases.

Sample 1 / 1078 — [ht_0005](#)

[HUISS/taizger](#) / [depth](#) / [bronze](#) / [RESULT](#) / [review](#) / [ECOV](#)

[Seed](#) [GStream: Learning 3D Geometry and Feature Consistent Gaussian Splatting for Object Removal](#) — [Yun Wang, Qianyi Wu, Guofeng Zhang, Dan Xu \(2024\) \[pdf\]\(#\) \[arXiv\]\(#\)](#)

[Seed Abstract](#)

Question

GStream contrasts two implicit representation baselines as image domain guidance strategies before introducing its 3D Gaussian feature propagation: one that updates the scene using multi-view inpainted images, and another that instead starts from a single inpainted reference and simulates view-dependent effects for other views. What concrete supervision setup does each of those two baselines use for the masked regions, according to their own method descriptions?

(A) For the first strategy, the paper states that SRN-NeRF and DR-NeRF “utilize patch-based LPTTS loss in their optimization objective” and that prior approaches “rely on leveraging multi-view inpainted images to update NeRF/3DGS models.” For the second strategy, View Sub “offers an alternative by inpainting a single reference image and designing depth-guided warping and bilateral filtering techniques to guide the generation in other views,” and the paper also describes it as “producing view-dependent effects as a form of guidance.”

✓ (B) CORRECT

The multi-view guidance baseline uses SAM-predicted masks to drive a 2D inpainting model that generates color and depth priors, then optimizes the scene with color, depth, and patch-level perceptual losses. The single-reference baseline assumes a single inpainted reference view, supervises masked geometry with an aligned monocular depth loss, and supervises masked appearance with view-substituted target colours corrected by a bilateral solver, plus an additional disocclusion loss.

(C) The multi-view image baseline supervises masked regions by using SAM point-prompted masks to guide the LLaVA 2D inpainting model and generate color and depth priors. The single-reference variant uses free-form text supervision by modifying SAM to be text-aware during training: it prompts SAM with CLIP image embeddings from manually collected masks and then uses CLIP text embeddings as prompts at inference time.

(D) In GStream’s comparison, the first implicit representation baseline follows the MVP-style setup: it renders each training view and directly supervises the masked holes with the corresponding multi-view inpainted images, i.e., per-view pixel losses are applied to the inpainted RGB content in those masked regions across all views. The second baseline follows the single-reference strategy used by methods like LucidDreamer/MyDream-style pipelines: it takes one inpainted reference image as the only explicit masked-region supervision and uses a view-dependent image generator to synthesize the missing content for novel views, so the other views are not supervised by real inpainted targets but by simulated view.

AI Audit Guide

Query quality ☒

Answer validity ☒

✓ The multi-view guidance baseline uses masks to guide a 2D inpainting model that generates color and depth priors. → [DR-NeRF: Object Removing from 3D Scenes / IV Method](#) → [DR-NeRF](#) states it utilizes SAM to predict masks, uses masks to guide LLaVA, and generates color and depth priors.

✓ The multi-view guidance baseline optimizes the scene with color, depth, and patch-level perceptual losses. → [DR-NeRF: Object Removing from 3D Scenes / IV-B Scene Color + Perceptual](#) → Verified from equations and text defining color loss, depth supervision, perceptual loss, and text loss.

✓ The single-reference baseline assumes a single inpainted reference view. → [Reference-guided Controllable Inpainting / 4 Method](#)

✓ The single-reference baseline supervises masked geometry with an aligned monocular depth loss. → [Reference-guided Controllable Inpainting / 4.1 Supervising Reference View Geometry](#) → The paper describes monocular depth estimation, alignment of predicted disparity to rendered NeRF disparity, and masked depth supervision.

✓ The single-reference baseline supervises masked appearance with view-substituted target colours corrected by a bilateral solver. → [Reference-guided Controllable Inpainting / 4.2 View-dependent Effects by View-substitution](#) → Verified from sections 4.2.1-4.2.3 describing view substitution, bilateral solver for residuals, and masked reconstruction supervision.

✓ The single-reference baseline also uses an additional disocclusion loss. → [Reference-guided Controllable Inpainting / 4.3 Disoccluded Regions](#)

Synthesis check ☒

The question explicitly contrasts two different baseline strategies, each described in a different target paper, so both targets are required to form the full answer.

Section recall labels

✓ ☐ [GStream: Learning 3D Geometry and Feature](#) → 3.3 Cross-Attention Feature Regularization (supporting): Names the two contrasted implicit representation guidance strategies: multi-view in inpainted images and simulated view-dependent effects.

✓ ☐ [DR-NeRF: Object Removing from 3D Scenes](#) → IV Method (direct): Describes multiview segmentation with SAM and use of masks to guide LLaVA for generating color and depth priors.

✓ ☐ [DR-NeRF: Object Removing from 3D Scenes](#) → IV-B Scene Object Removal (direct): Defines the color loss, depth supervision, patch-level perceptual loss, and total training objective used for masked-region supervision.

✓ ☐ [Reference-guided Controllable Inpainting](#) → 4 Method (direct): States the single-inpainted reference view setup and summarizes the complete loss terms.

✓ ☐ [Reference-guided Controllable Inpainting](#) → 4.1 Supervising Reference View Geometry (direct): Explains aligned monocular depth/disparity supervision for masked geometry in the reference view.

✓ ☐ [Reference-guided Controllable Inpainting](#) → 4.2 View-dependent Effects by View-substitution (direct): Explains view substitution, bilateral solver residual correction, and masked appearance supervision using corrected target colours.

✓ ☐ [Reference-guided Controllable Inpainting](#) → 4.3 Disoccluded Regions (direct): Defines the additional disocclusion supervision and loss.

Structural integrity ☒

Most answer-relevant sections are present. One appendix section is truncated, but it does not affect verification of the query or correct answer. Missing sections: Appendix F Implementation Details (truncated)

Pipeline reasoning legitimate?

☒ Yes
 ☐ Partially
 ☐ No

Gold content reflected in Q&A?

☒ Yes
 ☐ Partially
 ☐ No

Verdict

☐ Pass
 ☐ Flag
 ☐ Remove

Notes

Submit & Next

Figure 3: Gradio human-audit interface used in Stage 7. Each sample is presented with the question, four options (gold and three distractors), the GPT-5.4 audit JSON, and links to underlying papers. Auditors mark three quality axes and submit one of three verdicts. The same interface is released alongside the benchmark, constrained to the seven-tool, 30-point budget environment, for future human-vs-LLM head-to-head studies.

Auditors were instructed to spend at most three minutes per sample to keep throughput steady and avoid fatigue; if a sample required longer the auditor was asked to flag it for review rather than continue.

Across the 1,078 samples we recorded 1,204 review events, with the additional events corresponding to auditor-initiated revisits (e.g., reopening a flagged sample after consulting the paper). Per-sample wall-clock time, measured between the moment a sample is presented and the moment a verdict is submitted, has a long tail. We treat any single review longer than 300 seconds as away-from-keyboard (AFK) and exclude 187 such events from the timing summary. On the remaining 1,017 engaged-time events, the median per-sample audit time is **88 seconds** (mean 97 seconds, p95 228 seconds), implying a per-auditor throughput of roughly 30–40 reviewed samples per hour at full engagement. Per-auditor medians range 56–211 seconds; we observe no systematic relationship between speed and verdict severity.

We prioritized full single-pass coverage, every one of the 1,078 samples reviewed by exactly one auditor, over partial coverage with designed double-coding for inter-rater agreement statistics, given the seven-auditor capacity budget. Consistency across auditors is therefore enforced procedurally rather than statistically: through the structured Gradio interface shown in Figure 3, the GPT-5.4 audit-prep guide (next paragraph) which front-loads claim decomposition and section-recall hypotheses, and a fixed three-axis verdict schema (Pass/Flag/Remove) with required free-text notes on Flag. We acknowledge this trade-off as a limitation of the present audit design.

Audit-prep generation. Each post-Stage-6 sample is paired with a structured audit JSON produced by GPT-5.4, which serves both as a verification record and as a guide that orients human reviewers. The same call decomposes the gold answer into atomic factual claims and verifies each against the cited sources (*answer_validity*); checks that the seed-to-bridge-to-target chain is necessary and well-formed for single-target samples (*chain_coherence*); checks that the answer genuinely synthesizes information from both targets for multi-target samples (*synthesis_check*); and emits a list of `section_recall_labels` naming the section headers that contain evidence for the gold answer. The structured artefact speeds the audit and enforces a uniform claim decomposition across auditors; in practice it expedited per-sample check time substantially and helped auditors stay focused throughout the session. The full audit prompt is Prompt F.2 in Appendix F.

20

Section-recall labels. Each `section_recall_label` pairs a section header from the gold target paper(s) with a relevance class: `direct` (the claim is stated explicitly in this section) or `supporting` (the section provides context needed to interpret the claim). Multiple sections may carry either class for a single sample, and a sample may have ≥ 1 section per gold paper. The headline search-axis metric in the main text is *paper recall*, the agent reads at least one section of every gold paper. *Section recall*, the stricter variant requiring a delivered section to contain a `direct`-labelled evidence location, is reported alongside paper recall in Table 2. Subsection labels are resolved to their containing readable section as described in Appendix E.1. Auditors may add, remove, or re-classify labels during Stage 7; the released labels are post-audit and post-Stage-8.

Stage 8: Post-filtering. A final two-step pass after the human audit drops 32 more samples.

Step 1: Recall-label triage (manual, −5 samples). The Stage 7 audit produces a section-recall label for every retained sample (the gold paper section in which each atomic claim from the gold answer is verifiable). The audit-prep guide that drafts these labels can mis-name a section header, point at a child header that does not exist verbatim in the released paper pool, or flag a claim as unverified at the labeled section even though the claim is in fact present elsewhere in the paper. To repair these label-level errors without losing samples unnecessarily, the lead author re-reviews every label that the Stage 7 cross-check flagged as suspicious, totaling 72 cases over 55 unique samples, comprising 48 verified-false claims (the labeled section did not contain the claim) and 24 unresolved labels (the labeled section header did not match any header in the gold paper). Each case receives one of five verdicts:

- **Repoint to parent** (23 cases), the label points at a fine-grained subsection that does not exist verbatim in the released pool, and the auditor supplies the parent section header that does.
- **Repoint section** (22 cases), the labeled section header is wrong outright; the auditor supplies the correct header.
- **Keep (rounding/precision ok)** (19 cases), the verbatim mismatch is innocuous (e.g., “94.1%” label vs “94.13%” in paper), no patch needed.
- **Drop claim only** (1 case), one specific claim is retired but the sample survives with its remaining claims intact.
- **Drop sample** (7 verdicts on 5 unique samples), the recall claim is fundamentally unrecoverable: the cited passage cannot be located in the released paper at any header, the gold paper’s released body is missing entirely (only the appendix is present), or the terminal paper has no parsed body at all. The 5 retired samples (`mt_0534`, `mt_0650`, `mt_0845`, `st_0461`, `st_0485`) cluster into three failure modes: *claim cannot be located* (2 of 5), *released paper pool missing the gold body* (2 of 5), and *cited terminal paper has no parsed content* (1 of 5).

The 64 *Repoint* and *Keep* verdicts patch label headers in place; the released section-recall labels are post-triage. Only the 5 *Drop sample* verdicts retire samples at this step.

Step 2: Length filter (automated, −27 samples). The remaining 1,038 samples are passed through a length filter that drops any sample whose gold-path papers (seed, bridge, or target) contain a single section longer than the p99.9 length cutoff of **70,015 characters**. These are HTML-parser collapse cases in which a parsing error has merged the main body and appendix into one giant section, making section-recall measurement meaningless. Twenty-seven samples meet this criterion, including cases where the labeled gold-evidence section is itself the parser-collapsed one, those samples are dropped because section-recall measurement on them would be ambiguous. The cutoff is calibrated so that legitimate long sections (e.g., dense methodology sections in foundation-model papers) are preserved.

Sample-difficulty distribution. Figure 4 characterizes the benchmark’s difficulty profile across three independent cuts, with each of the 1,011 items grouped by how many of the 19 evaluated models answered it correctly. The panel-19 coverage histogram (panel c) shows a smooth distribution centered on intermediate coverage: only 0.2% of items are solved by every model and 1.1% are failed by every model, with 44.8% in the mid-coverage bucket (7–12 correct) and 31.6% in the high-coverage bucket (13–19 correct). The joint distribution of question type and depth (panel a) gives a clear difficulty ordering: single-target depth-1 items are easiest (58.9% high-coverage), multi-target depth-2 items are hardest (21.3% high-coverage), and the intermediate cells (ST-d2, MT-d1) cluster at moderate difficulty, validating depth and target multiplicity as independent design




Figure 4: Sample-difficulty distribution across the 1,011-sample benchmark. Each sample is bucketed by how many of the 19 evaluated models answered it correctly: low (0–6, red), mid (7–12, yellow), high (13–19, green). **(a)** Stratified by question type × depth. **(b)** Stratified by consensus tier. **(c)** Per-sample coverage histogram, with bar color matching the low/mid/high coding.

axes. The consensus tier (panel b) acts as a separate construction-rigor signal: silver-tier samples (highest filter agreement during the audit) concentrate in high-coverage (50.9%), while bronze-tier samples (most ambiguous during the audit) concentrate in low-coverage (33.9%), reinforcing the tier as a measurement of construction confidence rather than a designed difficulty axis.

D Experimental Configuration

Model naming convention. The main text refers to each evaluated model by its conventional release name (e.g., Gemini-3 Pro, Claude Opus 4.6). For reproducibility, Table 7 records the exact API model identifier or Hugging Face repository path invoked at evaluation time: closed-frontier models were called via their providers’ production APIs at the snapshots indicated, and open-weight checkpoints were downloaded from the listed Hugging Face repositories.

Table 7: Mapping from each display name used in the paper (and in Table 2) to the canonical API model identifier or Hugging Face repository path actually invoked. Qwen3-30B-A3B is the Instruct-2507 snapshot. During our evaluation window (after the 2025-12-01 stable release of DeepSeek-V3.2 [29]), both DeepSeek API aliases resolve to the same underlying V3.2 checkpoint: `deepseek-chat` invokes the non-thinking mode and `deepseek-reasoner` the thinking mode. Reproducing our numbers therefore requires the V3.2 weights rather than the older V3/R1 weights to which these aliases pointed before the swap.

Display name	Identifier	Display name	Identifier
Gemini-3 Pro	<code>gemini-3-pro-preview</code>	MiniMax-M2.7	<code>MiniMaxAI/MiniMax-M2.7</code>
Claude Opus 4.6	<code>claude-opus-4-6</code>	Qwen3.5-27B	<code>Qwen/Qwen3.5-27B</code>
GPT-5.3-codex	<code>gpt-5.3-codex</code>	Qwen3.5-35B-A3B	<code>Qwen/Qwen3.5-35B-A3B</code>
Claude Sonnet 4.6	<code>claude-sonnet-4-6</code>	Qwen3.6-35B-A3B	<code>Qwen/Qwen3.6-35B-A3B</code>
GPT-5.4	<code>gpt-5.4</code>	Qwen3-32B	<code>Qwen/Qwen3-32B</code>
Gemini-3 Flash	<code>gemini-3-flash-preview</code>	Qwen3-30B-A3B	<code>Qwen/Qwen3-30B-A3B-Instruct-2507</code>
GLM-5.1	<code>zai-org/GLM-5.1</code>	Gemma-3-27B	<code>google/gemma-3-27b-it</code>
DeepSeek-chat	<code>deepseek-chat</code>	Gemma-4-31B	<code>google/gemma-4-31b-it</code>
DeepSeek-reasoner	<code>deepseek-reasoner</code>	Gemma-4-26B-A4B	<code>google/gemma-4-26b-a4b-it</code>
Kimi-K2.5	<code>moonshotai/kimi-k2.5</code>		

Backend choices. Closed-frontier models are accessed through the official APIs of their providers: Anthropic for Claude, OpenAI Responses API for GPT, and Google GenAI for Gemini. Open-frontier models are accessed via two API providers: `deepseek-chat` and `deepseek-reasoner` (both resolving to DeepSeek-V3.2 [29]; see Table 7 caption) through DeepSeek’s own API, and Kimi-K2.5, MiniMax-M2.7, and GLM-5.1 through the OpenAI-compatible Together.ai endpoint. Compute-efficient open-weight models (Qwen3.x and Gemma 3/4 variants) are served locally with vLLM 0.19.1 using two-way tensor parallelism on a pair of H100 GPUs.

Sampling and reasoning configurations. All models receive identical system prompts and tool schemas. Sampling temperatures are set to each provider’s defaults: 1.0 for Claude, 1.0 for GPT-5.x reasoning models, 0.6 with top- $p = 0.95$ for Qwen and DeepSeek, and 1.0 for Gemini. Reasoning configurations are model-specific: Claude Opus 4.6 uses extended thinking with an 8,192-token budget combined with the external `think` tool; Claude Sonnet 4.6 uses `think` alone; GPT-5.3-codex and GPT-5.4 use `reasoning_effort=medium`; MiniMax-M2.7 uses interleaved thinking; Qwen3.5/3.6 thinking variants use vLLM’s `qwen3` reasoning parser with the `qwen3_coder` tool-call parser to handle thinking blocks alongside tool calls.

Cost accounting. Per-model API cost and average per-sample token consumption for the 11 API-served models are reported in Table 8 for both the full-tool 19-model evaluation pass and the parallel zero-tool ablation; the 8 locally-served open-weight Qwen and Gemma checkpoints incur compute time on our local H100s but no API cost and are excluded. A single full-tool evaluation pass costs approximately \$1,294 across the 11 API models, ranging from \$11 (DeepSeek-chat) to \$406 (Claude Opus 4.6); the corresponding zero-tool ablation costs an additional \$259 across all 11 checkpoints. The two stability replicates (run-1 and run-2 on DeepSeek-chat and GPT-5.3 codex) add $\sim$ \$92 each, and the no-search ablation on the same two checkpoints adds another $\sim$ \$90. The data-generation pipeline (Stages 2–7 of Appendix C), driven primarily by GPT-5.4 for question, distractor, and audit-prep generation alongside the three-model ensemble filter, accounts for an additional $\sim$ \$700 in API cost. The aggregate API spend across the full project is approximately \$2.5K. Input-token consumption varies substantially with strategy: DeepSeek-chat averages 154K input tokens per sample reflecting sequential exploration, while GPT-5.3-codex averages 67K reflecting targeted retrieval. Reasoning-augmented models consume roughly $2\times$ the output tokens of non-reasoning models, indicating that the bottleneck on this task is action selection rather than answer generation.

Table 8: Per-model API cost and average per-sample token consumption for the 11 API-served models on the 1,011-sample full split, alongside zero-tool ablation cost. All costs use the official per-token pricing for each provider as recorded in the released harness. The 8 open-weight Qwen and Gemma checkpoints (Qwen3-32B, Qwen3-30B-A3B, Qwen3.5-27B, Qwen3.5-35B-A3B, Qwen3.6-35B-A3B, Gemma-3-27B, Gemma-4-26B-A4B, Gemma-4-31B) are served locally on a pair of H100 GPUs and excluded.

Model	Full-tool (\$)	Zero-tool (\$)	\$/sample (full)	Input/sample (K)	Output/sample
Gemini 3 Pro	159.27	37.14	0.158	87	5,003
Gemini 3 Flash	77.49	25.17	0.077	169	8,517
Claude Opus 4.6	405.54	79.47	0.401	107	3,890
Claude Sonnet 4.6	205.23	43.86	0.203	92	4,165
GPT-5.3-codex	80.32	14.80	0.079	67	2,208
GPT-5.4	78.99	28.14	0.078	65	2,444
DeepSeek-V3	11.00	0.80	0.011	154	2,818
DeepSeek-R1	25.11	5.16	0.025	124	4,702
GLM-5.1	155.66	12.56	0.154	98	3,734
Kimi-K2.5	66.72	10.49	0.066	112	3,588
MiniMax-M2.7	28.66	1.74	0.028	81	3,391
Total	1,293.99	259.33	—	—	—

E Diagnostic Detail and Robustness Checks

This appendix is organized as a section-by-section extension of Section 4: Section E.1 extends the per-axis decomposition of Section 4.2; Section E.2 extends the trajectory and failure analyses of Section 4.3; Section E.3 extends the robustness checks of Section 4.4; and Section E.4 extends the tool ablations of Section 4.5.

E.1 Per-axis decomposition (extends Section 4.2)

Per-model stopping behavior across three scopes. Section 4.2 reports four per-family stopping signatures derived from what each model does after reaching a gold paper. Table 9 gives the full-panel decomposition across three scopes: *MT-fail* (multi-target items on which paper recall failed;

categorized by the post-first-gold action), *ST* (single-target items, action after the gold read), and *MT-both* (multi-target items where both gold papers were reached; action after the second gold read). MT-fail uses four mutually exclusive categories: **0-Gold** (trajectory submitted without reaching any gold paper), **Prem** (reached a gold but made no further read or navigation tool call, premature commit), **Explored** (further navigation or non-gold reads, tried but missed the second gold), **Stayed** (further reads only on the already-reached gold). ST and MT-both each use three categories: **Imm** (submit immediately), **Thnk** (think before submit), **Read** (read additional sections before submit); a small residual ($\leq 25\%$) navigates without reading and is omitted.

Table 9: Stopping behavior across MT-fail, ST, and MT-both scopes for the 19-model panel. Each block’s n column reports trajectories in scope; subsequent columns report the within-scope share (%) of each category. MT-fail’s four categories sum to 100%; ST and MT-both’s three categories sum to $\leq 100\%$ (residual is navigation without reading).

Model	MT-fail					ST (after gold)				MT-both (after both)			
	n	0-Gold	Prem	Explored	Stayed	n	Imm	Thnk	Read	n	Imm	Thnk	Read
<i>Closed Frontier</i>													
Gemini-3 Pro	110	20.9	17.3	40.0	21.8	493	35.7	11.6	48.7	333	39.6	10.2	47.4
Gemini-3 Flash	221	24.0	4.1	56.6	15.4	411	5.1	1.5	89.1	222	13.1	3.6	74.3
GPT-5.3 codex	167	16.2	34.7	31.1	18.0	461	47.3	0.2	47.1	276	66.3	1.1	22.5
GPT-5.4	158	17.1	53.2	27.2	2.5	459	31.4	14.4	45.8	285	38.9	29.5	21.1
Claude Opus 4.6	99	33.3	37.4	13.1	16.2	496	0.4	67.7	31.7	344	2.0	64.8	33.1
Claude Sonnet 4.6	177	51.4	25.4	13.0	10.2	453	0.4	70.4	29.1	266	0.4	64.3	34.6
<i>Open Frontier</i>													
GLM-5.1	145	26.2	33.1	29.0	11.7	436	3.0	50.5	46.1	298	4.0	39.9	55.4
DeepSeek-reasoner	196	18.9	3.6	66.8	10.7	409	10.0	1.0	86.8	247	20.2	2.0	73.3
DeepSeek-chat	167	18.0	1.8	64.1	16.2	439	1.4	3.0	92.7	276	4.7	9.4	77.2
Kimi-K2.5	191	16.8	11.0	57.6	14.7	434	3.5	16.6	76.7	252	5.6	20.2	69.4
MiniMax-M2.7	198	26.8	17.7	40.9	14.6	379	5.0	28.8	64.4	245	7.3	29.0	62.9
<i>Compute-Efficient</i>													
Gemma-4-31B	212	34.4	12.7	31.6	21.2	353	45.0	9.6	45.3	231	13.0	38.1	48.9
Gemma-4-26B-A4B	373	66.2	7.0	9.1	17.7	200	14.0	6.5	78.0	70	32.9	18.6	48.6
Gemma-3-27B	419	68.5	20.0	6.2	5.3	79	78.5	0.0	21.5	24	62.5	0.0	37.5
Qwen3.5-27B	182	17.6	11.0	54.4	17.0	385	28.1	7.0	63.6	261	29.5	18.0	52.1
Qwen3.6-35B-A3B	309	45.3	7.4	30.1	17.2	287	12.9	16.4	69.7	134	17.9	29.9	52.2
Qwen3.5-35B-A3B	234	28.2	3.8	48.7	19.2	327	10.7	5.2	82.9	209	14.4	11.0	72.7
Qwen3-30B-A3B	239	49.8	6.3	27.6	16.3	267	3.7	34.8	61.4	204	5.4	65.7	28.4
Qwen3-32B	403	91.1	5.2	3.0	0.7	87	77.0	0.0	21.8	40	60.0	12.5	27.5

Per-cell decomposition for representative models. Crossing the question-type axis (single-target vs. multi-target) with the depth axis (depth-1 vs. depth-2) yields a 2×2 grid that exposes per-model discrimination patterns. Table 10 reports per-cell accuracy for one representative checkpoint from each tier; spreads across the four cells diagnose whether a model is bottlenecked by synthesis depth or by tool-environment overhead.

Table 10: Per-cell accuracy on the question-type $\times$ depth grid for one representative checkpoint from each tier (point estimate $\pm$ Wilson 95% CI half-width). Δ is the drop from the easiest to hardest cell. GPT-5.3 codex holds within 17 pp across all four cells; DeepSeek-chat collapses on multi-target depth-2; Gemma-4-31B is uniformly capped, suggesting that what limits its accuracy is tool-environment overhead rather than synthesis depth.

Model	st_d1 ($n = 90$)	st_d2 ($n = 478$)	mt_d1 ($n = 396$)	mt_d2 ($n = 47$)	$\Delta_{\text{st_d1} - \text{mt_d2}}$ (pp)
GPT-5.3 codex	94.4 ± 3.2	78.0 ± 3.5	85.4 ± 3.1	80.9 ± 8.7	+13.6
DeepSeek-chat	73.3 ± 8.0	53.8 ± 4.4	56.6 ± 4.8	48.9 ± 13.8	+24.4
Gemma-4-31B	72.2 ± 8.2	56.3 ± 4.4	72.7 ± 4.2	70.2 ± 11.1	+2.0

Reasoning-type breakdown. Each AgentHop item is tagged at construction with one of four reasoning-type labels. **GROUND** questions ask for a paper-grounded factual claim ($n = 330$); **METHOD** questions ask about a specific technical procedure used by a paper ($n = 124$); **MOTIVE** questions ask why a paper was written or how it relates to prior work ($n = 265$); **RESULT** questions ask about the empirical outcomes a paper reports ($n = 292$). The taxonomy was applied at Stage 3 of the construction pipeline of Appendix C by the Q/A-generation model and verified during the

Stage 7 audit; reasoning-type labels are not used to score answers and do not enter the four-axis decomposition of Section 3.3.

Across the 19-model panel, mean accuracy by reasoning type ranks METHOD (57.1%) > RESULT (54.5%) > GROUND (54.1%) > MOTIVE (53.1%); METHOD questions, which point to specific technical procedures often documented in named sections (*Architecture*, *Method*), are the easiest reasoning type for the panel; MOTIVE questions, which require integrating across the introduction and related-work content of one or more papers to reconstruct authorial intent, are the hardest. The spread is small (~ 4 pp), so reasoning type is too weak to support a main-body axis. The per-model breakdown does carry one diagnostic signal worth flagging: Claude Sonnet drops 12 pp from its METHOD accuracy (83.9%) to its MOTIVE accuracy (71.7%), the largest within-model spread in the panel and the clearest example of a model whose synthesis-heavy reasoning sub-type is bottlenecked relative to its lookup-style reasoning.

Joint view: accuracy vs. paper recall. Figure 5 plots accuracy against paper recall for all 19 models. Most checkpoints cluster near the diagonal $y = x$, indicating that retrieval success is the dominant driver of accuracy. Two diagnostic profiles diverge from this regime: models above the diagonal accumulate accuracy beyond what retrieval alone explains, while models below retrieve correctly but lose accuracy at the synthesis step.

Table 11: Evidence-contact decomposition of the 11,072 recall-credited trajectories, pooled over the 19-model panel. Conversion is cap-corrected. The zero-tool column reports the same models’ closed-book accuracy on the same items.

Group	n	Share	Conversion	Zero-tool
Read a <code>direct</code> -labelled section (header match)	4,725	42.7%	74.0%	35.2%
Read the labelled content inside its parent section	4,765	43.0%	78.1%	40.1%
Read no <code>direct</code> -labelled content	1,582	14.3%	49.3%	31.5%

Section-recall label mapping. Audit labels cite evidence at each paper’s native granularity. Across the 2,773 unique `direct` labels, 53.0% name a top-level section, 46.8% name a subsection, and five name citation targets such as tables; the five are repaired in the release. The sandbox’s readable unit is the top-level section, so a subsection label is credited when its header appears verbatim in the text of a delivered section. This is the same resolution rule the audit pipeline applies during label verification. Table 11 decomposes the 11,072 recall-credited trajectories by evidence contact: 85.7% verifiably received `direct`-labelled evidence text, and conversion separates the groups by roughly 25 points, which validates the labels as predictors of synthesis success.

Table 12: Exact McNemar tests on common recalled items (discordant pairs; two-sided p). Top: adjacent pairs among the six highest multi-target conversion scores. Bottom: tier conversion leader against tier runner-up, per axis.

	Pair	n	Discordant	p
MT	Gemini-3 Pro vs Claude Sonnet 4.6	226	20/3	0.0005
MT	Claude Sonnet 4.6 vs GPT-5.4	193	24/16	0.27
MT	GPT-5.4 vs GLM-5.1	227	36/22	0.09
MT	GLM-5.1 vs DeepSeek-reasoner	203	35/21	0.08
MT	DeepSeek-reasoner vs MiniMax-M2.7	168	42/12	0.0001
Closed, ST	Gemini-3 Pro vs Claude Sonnet 4.6	437	25/13	0.073
Closed, MT	Gemini-3 Pro vs Claude Sonnet 4.6	226	20/3	0.0005
Open, ST	GLM-5.1 vs DeepSeek-reasoner	368	56/28	0.0030
Open, MT	GLM-5.1 vs DeepSeek-reasoner	203	35/21	0.081
Comp.-eff., ST	Gemma-4-31B vs Qwen3.5-27B	315	56/30	0.0067
Comp.-eff., MT	Gemma-4-31B vs Qwen3.6-35B-A3B	98	22/5	0.0015

Paired conversion tests. Marginal confidence intervals on different item sets confound model ability with item difficulty. We therefore compare conversion with exact McNemar tests on common recalled items, cap-corrected. The top panel walks down the six highest multi-target conversion

scores; the bottom panel tests each tier’s conversion leader against its runner-up on both axes. Table 2 shades a conversion tier leader only where the corresponding test rejects at $p < 0.05$.




Figure 5: Accuracy versus paper recall across the 19-model panel, colored by tier. The diagonal $y = x$ marks accuracy tracking retrieval one-to-one. Models above the diagonal (Gemini-3 Pro, GPT-5.3 codex, Gemma-4-31B) combine retrieval with synthesis lift; models below (Kimi-K2.5, MiniMax-M2.7, the Qwen MoE family, DeepSeek-chat) retrieve correctly but fail to convert.

E.2 Trajectory and failure analysis (extends Section 4.3)

Trajectory deeper-dive. This subsection expands the strategy analysis of Section 4.3 with three lenses: bigram-level accuracy associations, per-family trigram fingerprints, the early-submit-after-wrong-paper signature, and per-model tool-call transition visualisations. Each lens isolates a different trajectory-shape signal that aggregate accuracy does not surface.

Bigram accuracy associations across all 19 models. For each ordered pair of tool-call actions (a_i, a_{i+1}) we compute the marginal accuracy difference between trajectories that contain the bigram and those that do not, applying a Bonferroni correction over the 49 candidate bigrams (7×7 tools). Table 13 reports the top productive and anti-productive bigrams ranked by panel-mean $|\Delta|$, restricted to bigrams that appear in at least 10 of 19 models so that the panel mean is well-defined.

Interpretation. Three families of habit emerge. The *deliberation* pair (read_section→think, think→submit_answer) reproduces the action–observation–think regime of Yao et al. [2] and is uniformly productive on AgentHop. The *scaffolded-exploration* cluster (list_sections→read_section, get_references→get_paper_info, get_paper_info→get_references, get_paper_info→list_sections) carries +7 to +8 pp regardless of which specific transition is involved, indicating that the productive signal is structural rather than tied to any single tool: any sequence that pauses to discover before committing pays off. The *anti-productive* cluster splits into two distinct pathologies. Three of the negative bigrams (get_paper_info→submit_answer, get_references→submit_answer, list_sections→submit_answer) capture an *abandon-after-metadata* pattern in which the model commits without reading any content; these are systematic −10 to −15 pp losses. Two more (read_section→read_section, get_references→read_section, get_paper_info→read_section) capture a *shortcut-read* pattern that skips deliberation or scaffolding before content access. AgentHop therefore rewards models that pace actions through deliberation or scaffolded exploration and punishes models that grab actions impulsively or abandon prematurely; the same conclusion is invisible from accuracy alone but reads directly off the bigram table.

Table 13: Top productive and anti-productive bigrams across the 19-model panel, ranked by panel-mean $|\Delta|$. Δ is the panel-mean accuracy difference between trajectories containing and not containing the bigram. *Sig. count* is the number of individual models for which the per-model effect remains significant after Bonferroni correction over the 7×7 candidate space; *Models* is the number with the bigram present in ≥ 1 trajectory.

Bigram	Δ (pp)	Sig. count	Models
<i>Productive (positive Δ)</i>			
read_section $\rightarrow$ think	+13.6	7/19	14/19
think $\rightarrow$ submit_answer	+12.6	6/19	14/19
list_sections $\rightarrow$ read_section	+8.4	2/19	13/19
get_references $\rightarrow$ get_paper_info	+8.3	5/19	15/19
get_paper_info $\rightarrow$ get_references	+8.2	4/19	14/19
get_paper_info $\rightarrow$ list_sections	+7.3	3/19	15/19
read_section $\rightarrow$ submit_answer	+5.3	7/19	15/19
<i>Anti-productive (negative Δ)</i>			
get_paper_info $\rightarrow$ submit_answer	-14.4	3/19	13/19
get_references $\rightarrow$ read_section	-11.7	1/19	14/19
read_section $\rightarrow$ read_section	-11.5	7/19	15/19
get_references $\rightarrow$ submit_answer	-10.8	1/19	10/19
list_sections $\rightarrow$ submit_answer	-10.6	0/19	11/19
get_paper_info $\rightarrow$ read_section	-9.9	2/19	15/19

Per-family trigram fingerprints. A complementary lens looks at length-3 sub-patterns: which trigram is each model’s most-frequent triple of consecutive tool calls, and how concentrated is that pattern. Table 14 reports each model’s top-1 trigram and the fraction of all observed trigrams it accounts for, grouped by tier. Tool abbreviations: gpi = get_paper_info, gr = get_references, ls = list_sections, rs = read_section, th = think, sub = submit_answer.

Table 14: Per-model top-1 trigram and concentration share. *Concentration* is the fraction of all length-3 sub-patterns occupied by the most-frequent trigram (higher = more strategically locked-in). Models grouped by tier; ranked within tier by concentration.

Model	Top-1 trigram	Concentration
<i>Closed Frontier</i>		
Gemini-3 Flash	gpi $\rightarrow$ ls $\rightarrow$ rs	0.100
Gemini-3 Pro	ls $\rightarrow$ rs $\rightarrow$ rs	0.091
Claude Sonnet 4.6	gpi $\rightarrow$ gr $\rightarrow$ th	0.090
GPT-5.4	ls $\rightarrow$ rs $\rightarrow$ rs	0.089
GPT-5.3 codex	gpi $\rightarrow$ ls $\rightarrow$ rs	0.089
Claude Opus 4.6	rs $\rightarrow$ th $\rightarrow$ sub	0.084
<i>Open Frontier</i>		
Kimi-K2.5	ls $\rightarrow$ rs $\rightarrow$ rs	0.087
MiniMax-M2.7	ls $\rightarrow$ rs $\rightarrow$ rs	0.079
DeepSeek-reasoner	gpi $\rightarrow$ ls $\rightarrow$ rs	0.079
GLM-5.1	ls $\rightarrow$ rs $\rightarrow$ rs	0.072
DeepSeek-chat	ls $\rightarrow$ rs $\rightarrow$ rs	0.071
<i>Compute-Efficient</i>		
Gemma-3-27B	gpi $\rightarrow$ gr $\rightarrow$ gpi	0.196
Qwen3.5-27B	gpi $\rightarrow$ ls $\rightarrow$ rs	0.144
Qwen3-32B	gpi $\rightarrow$ ls $\rightarrow$ rs	0.135
Qwen3-30B-A3B	gpi $\rightarrow$ gr $\rightarrow$ gpi	0.131
Gemma-4-26B-A4B	rs $\rightarrow$ rs $\rightarrow$ rs	0.125
Qwen3.6-35B-A3B	gpi $\rightarrow$ ls $\rightarrow$ rs	0.120
Gemma-4-31B	ls $\rightarrow$ rs $\rightarrow$ rs	0.102
Qwen3.5-35B-A3B	gpi $\rightarrow$ ls $\rightarrow$ rs	0.093

Interpretation. Strategic diversity decreases as one moves down the tier hierarchy, and the failure mode at the bottom is concrete. Closed-frontier checkpoints invent five different top-1 trigrams across

six models, with Claude Opus 4.6 the only model whose most-frequent trigram is the canonical ReAct chain itself ($rs \rightarrow th \rightarrow sub$); Sonnet’s $gpi \rightarrow gr \rightarrow th$ is the only think-terminating trigram outside Opus, consistent with the verify-before-commit family signature reported in Section 4.2. Open-frontier checkpoints converge: 4 of 5 share the greedy $ls \rightarrow rs \rightarrow rs$ pattern as top-1, suggesting less differentiated post-training across this group. Compute-efficient checkpoints are bimodal. Five of eight (the four Qwen variants plus Gemma-4-31B) reach the productive $gpi \rightarrow ls \rightarrow rs$ or $ls \rightarrow rs \rightarrow rs$ pattern at concentrations comparable to the closed tier. Three lock onto pathologies: Gemma-3-27B (19.6%) and Qwen3-30B-A3B (13.1%) concentrate on a metadata-only loop $gpi \rightarrow gr \rightarrow gpi$ that never enters `read_section`, and Gemma-4-26B-A4B locks onto $rs \rightarrow rs \rightarrow rs$ greedy reads (12.5%). The two patterns map directly to the Section 4.2 resource pathologies: metadata-only loops drive the under-engagement profile (Gemma-3-27B, Qwen3-32B floor accuracy), and greedy reads drive the token-cap exhaustion of Gemma-4-26B-A4B. Trigram concentration thus distinguishes *which kind* of failure a low-accuracy model is exhibiting, not just *whether* it is failing.

Early-submit-after-wrong-paper signature. A separate trajectory-level pattern is submitting an answer within three actions of reading a non-gold paper, which associates with $\Delta = -21.1$ pp accuracy on average across the panel and is significant in 12 of 19 models. The per-instance penalty is largest in checkpoints for which the behavior is atypical, Claude Sonnet, Claude Opus, Gemma-4-31B, and GLM-5.1 each lose at least forty percentage points on the trajectories where they make this mistake. In the compute-efficient checkpoints where the behavior is endemic (roughly a quarter to a third of all trajectories on Qwen3.5-27B, Gemma-4-31B, and Qwen3.6-35B-A3B), the per-instance penalty shrinks but absolute outcomes stay poor: the bottleneck has migrated from this single bigram to broader navigation failure.

Per-model tool-call transition matrices. Figure 6 visualises the 7×7 tool-call transition probabilities per model. Five visually distinct strategy archetypes are visible across the 19-checkpoint panel. The *Anthropic ReAct band*: Claude Opus 4.6 and Sonnet 4.6 show a strong `read_section` $\rightarrow$ `think` transition with darker bands originating from `think`, indicating deliberate post-reading reflection. The *OpenAI section-list dominance*: GPT-5.3 codex and GPT-5.4 emphasize `list_sections` $\rightarrow$ `read_section`, with section-listing as the canonical bridge between metadata and content. The *synthesis-bottlenecked greedy chain*: DeepSeek-chat and Kimi-K2.5 show long bands of `read_section` $\rightarrow$ `read_section` chains without intervening `think`, the visual signature of the synthesis-bottlenecked profile. The *metadata-only loop pathology*: Gemma-3-27B and Qwen3-30B-A3B concentrate transitions on `get_paper_info` $\rightarrow$ `get_references` $\rightarrow$ `get_paper_info`, with no `read_section` band at all. The *diffuse exploration* archetype: Gemini-3 Flash, GLM-5.1, MiniMax-M2.7, and the Qwen MoE checkpoints show heatmaps without strong dominant bands, consistent with their broader strategic inconsistency and lower top-1 trigram concentrations in Table 14.

Interpretation. The same five archetypes recur across all 1,011 samples per model, indicating that trajectory shape is largely a property of training composition rather than per-sample task content. Two stronger-form claims follow. First, the archetypes align cleanly with the per-family stopping signatures of Section 4.2 ¶1: ReAct band $\leftrightarrow$ verify-before-commit, section-list dominance $\leftrightarrow$ confident-commit, greedy chains $\leftrightarrow$ over-search. Second, the metadata-only loop archetype is observed only in legacy compute-efficient checkpoints whose pre-training predates broad agentic post-training, suggesting that the agent-loop competence is acquired during a specific phase of post-training that some lineages have undergone and others have not. Tool-call transition shape is therefore a training-artifact fingerprint that is stable per model and predictive of failure mode at the panel level.

Non-submission terminations across the 19-model pool. Table 15 extends the resource-axis analysis of Section 4.2 with the per-model breakdown of non-submission terminations across the three caps. Three failure modes recur, and each clusters by architecture rather than by capability tier. *Token overflow* is the dominant terminator on compute-efficient sparse-active checkpoints, Gemma-4-26B-A4B alone exhausts the token cap on more than a third of trajectories, and also drives the Gemini-3 Flash and DeepSeek-chat non-submission rates. *Max-turns* terminations cluster in the Qwen MoE and Gemma sparse-active families, where the model continues to issue cheap tool calls without ever committing. *Budget exhaustion* appears almost exclusively in checkpoints with parallel tool-call regimes (GPT-5.4, MiniMax-M2.7, GLM-5.1), which drain the 30-point pool faster than turns or tokens accumulate. The pattern reinforces the main-text observation that the binding




Figure 6: Per-model tool-call transition matrices for the 19 evaluated models. Each panel is a 7×7 heatmap whose rows index the previous tool action and whose columns index the next; cell color encodes the row-normalised conditional probability $P(\text{next} \mid \text{prev})$ (deeper blue = higher transition probability). Within every panel the tool order along both axes is, top-to-bottom and left-to-right: `get_paper_info`, `get_references`, `list_sections`, `search_papers`, `read_section`, `think`, `submit_answer`. Panels are ordered to keep within-family checkpoints adjacent.

resource constraint is itself a model signature: the pairing of architecture, reasoning channel, and serving environment determines which of the three caps a model meets first.

E.3 Robustness and validity (extends Section 4.4)

Cross-benchmark scores and correlations. The 16-model overlap drops the three lowest-tier compute-efficient checkpoints (Gemma-3-27B, Qwen3-30B-A3B, Qwen3-32B) for which public scores are not available on most external benchmarks. Table 16 reports per-model scores on seven external benchmarks spanning reasoning (GPQA-Diamond, HLE no-tools), code (SWE-Bench Pro/Public, Terminal-Bench 2.0, NL2Repo), and agent (BrowseComp, HLE with tools) categories. Each entry is the publicly-reported score for the specific checkpoint evaluated in Section 4; entries marked * are proxies imputed from a closely related sibling checkpoint where official scores for the exact variant are not available; † denotes a context-managed variant. Cells without verifiable public scores are marked —. The Spearman rank correlations of each benchmark against AgentHop accuracy summarized in Section 4.4 are GPQA-Diamond $\rho = +0.73$ ($n = 15$), HLE no-tools $\rho = +0.72$ ($n = 14$), Terminal-Bench 2.0 $\rho = +0.70$ ($n = 15$), NL2Repo $\rho = +0.70$ ($n = 10$), HLE with tools $\rho = +0.67$ ($n = 10$).

Run-to-run robustness on three multi-run checkpoints. For DeepSeek-chat, Gemma-4-31B, and GPT-5.3 codex we ran the full 1,011-item evaluation three times under the same protocol with independent sampling. The agentic loop is multi-turn and stochastic by construction: each trajectory chains 8–16 tool-call decisions before committing, and any single decision can re-route the rest

Table 15: Non-submission terminations across the 19-model panel under the cap-corrected protocol. NA is the fraction of trajectories that fail to produce a parseable answer letter; the three rightmost columns decompose NA by terminating cap (max-turns, budget, token-limit; % of all trajectories). A small residual (≤ 0.7 pp on Qwen3-32B and Qwen3-30B-A3B) reflects voluntary `submit_answer` calls with non-letter output. Termination categories are defined in Appendix F.2.

Model	Acc	NA	MaxT	Bud	Tok	Model	Acc	NA	MaxT	Bud	Tok
<i>Closed Frontier</i>						<i>Open Frontier</i>					
Gemini-3 Pro	89.1	4.5	0.0	0.0	4.5	GLM-5.1	69.6	7.9	0.4	3.2	4.4
GPT-5.3 codex	82.5	1.0	0.0	0.7	0.3	DeepSeek-R1	59.6	6.4	0.3	0.0	6.1
GPT-5.4	79.0	5.2	0.0	4.9	0.3	DeepSeek-V3	56.4	14.3	0.3	0.0	14.0
Claude Opus 4.6	77.5	6.7	0.0	0.0	6.7	Kimi-K2.5	44.1	9.9	2.0	2.4	5.5
Claude Sonnet 4.6	76.6	4.4	0.6	0.0	3.8	MiniMax-M2.7	41.3	7.2	1.3	4.8	1.1
Gemini-3 Flash	54.7	31.1	0.4	0.2	30.4						
<i>Compute-Efficient</i>											
Gemma-4-31B	64.8	2.5	0.1	0.0	2.4	Gemma-4-26B-A4B	23.6	44.2	5.7	0.3	38.2
Qwen3.5-27B	48.2	9.8	2.1	0.6	7.1	Gemma-3-27B	18.6	0.1	0.0	0.0	0.1
Qwen3.6-35B-A3B	38.1	15.6	3.7	0.8	11.2	Qwen3-30B-A3B	16.0	11.9	6.4	0.3	4.8
Qwen3.5-35B-A3B	31.9	13.2	2.4	1.5	9.3	Qwen3-32B	13.3	1.5	0.2	0.0	0.6

Table 16: Per-model scores on seven external benchmarks (publicly reported, normalised to percent) alongside AgentHop accuracy. Models grouped by tier and ranked by AgentHop accuracy. * denotes a proxy imputed from a closely related sibling checkpoint; † denotes a context-managed variant. deepseek-chat (the non-thinking V3.2 invocation) lacks public benchmark scores at the time of this submission and is reported as —.

Model	GPQA-D	HLE	SWE-B Pro	T-Bench 2.0	NL2Repo	BrowseComp	HLE+tools	AgentHop
<i>Closed Frontier</i>								
Gemini-3 Pro	91.9	37.5	43.3	56.9	—	59.2	—	89.1
GPT-5.3 codex	92.6	—	56.8	77.3	—	77.3	—	82.5
GPT-5.4	92.8	39.8	57.7	75.1	41.3*	82.7	52.1	79.0
Claude Opus 4.6	91.3	40.0	57.3*	65.4	49.8*	84.0	53.1	77.5
Claude Sonnet 4.6	89.9	33.2	—	59.1	—	74.0	49.0	76.6
Gemini-3 Flash	90.4	33.7	—	47.6	—	—	—	54.7
<i>Open Frontier</i>								
GLM-5.1	86.2	31.0	58.4	63.5	42.7	68.0	52.3	69.6
DeepSeek-reasoner	79.9*	19.8*	—	37.7*	—	40.1*	40.8†	59.5
DeepSeek-chat	—	—	—	—	—	—	—	56.4
Kimi-K2.5	87.6	30.1	50.7	50.8	32.0*	60.6	50.2	44.1
MiniMax-M2.7	87.0*	28.0*	56.2	57.0	39.8	—	—	41.3
<i>Compute-Efficient</i>								
Gemma-4-31B	84.3	19.5	35.7*	42.9*	15.5*	—	26.5	64.8
Qwen3.5-27B	85.5	24.3	51.2*	41.6	27.3*	61.0	48.5	48.2
Qwen3.6-35B-A3B	86.0	21.4	49.5	51.5	29.4	—	—	38.1
Qwen3.5-35B-A3B	84.2	22.4	44.6*	40.5	20.5*	61.0	47.4	31.9
Gemma-4-26B-A4B	82.3	8.7	13.8*	34.2*	11.6*	—	17.2	23.6

of the trajectory. The natural expectation is therefore that headline accuracy will drift across runs. Empirically it does not. DeepSeek-chat and GPT-5.3 codex hold within 1 pp of accuracy across all three runs (std ≤ 0.009), and the conversion-rate and per-trajectory-token figures are similarly tight. Gemma-4-31B is the exception: accuracy std 0.031, conversion std 0.046, and a 21.8K-token spread per trajectory, a spread comparable to the cross-model gap between adjacent closed-frontier checkpoints. Table 17 reports per-run values for accuracy and three representative axis metrics with across-run mean, standard deviation, and range; cross-model rank orderings on accuracy and on each diagnostic axis are preserved across all three runs.

E.4 Tool ablations (extends Section 4.5)

Parametric reliance: zero-tool baseline. To separate parametric capability from tool-augmented capability, we re-evaluate each model with all retrieval and reasoning tools removed: the model receives the question and four options and must commit to a letter from internal knowledge alone. Table 18 reports closed-book accuracy alongside full-tool accuracy and the resulting tool-conditioned lift (Δ) for all 19 evaluated models, ranked by full-tool accuracy. Closed-book performance is itself a measured per-model property complementary to the headline accuracy, and the gap between

Table 17: Run-to-run figures across three runs for the three multi-run checkpoints. The two closed-frontier-style checkpoints (DeepSeek-chat, GPT-5.3 codex) show very low variance (< 0.011 standard deviation on every metric except absolute tokens). Gemma-4-31B is more variable: accuracy std 0.032, conversion std 0.047, and notably tokens std 10.2K (range 21.8K), a spread comparable to the cross-model gap between adjacent closed-frontier checkpoints. Cross-model rank orderings on accuracy and on each of the four axes are nonetheless preserved across all three runs.

Model	Metric	Run 0	Run 1	Run 2	Mean	Std	Range
DeepSeek-chat	Accuracy	0.564	0.553	0.542	0.553	0.009	0.022
	Section recall	0.439	0.452	0.433	0.441	0.008	0.019
	Conversion	0.669	0.652	0.642	0.654	0.011	0.027
	Tokens (k)	156.7	156.1	155.1	156.0	0.7	1.6
Gemma-4-31B	Accuracy	0.648	0.585	0.581	0.605	0.031	0.067
	Section recall	0.275	0.242	0.251	0.256	0.014	0.033
	Conversion	0.795	0.722	0.685	0.734	0.046	0.110
	Tokens (k)	87.6	66.3	65.8	73.2	10.2	21.8
GPT-5.3 codex	Accuracy	0.825	0.818	0.810	0.818	0.006	0.015
	Section recall	0.380	0.371	0.370	0.374	0.004	0.010
	Conversion	0.888	0.888	0.888	0.888	0.000	0.000
	Tokens (k)	69.5	69.2	69.2	69.3	0.1	0.3

closed-book and full-tool accuracy is what tools contribute over and above prior knowledge of the cited literature.

Tool-conditioned lift scales inversely with closed-book strength. Among models that produce valid answers without tools, weaker closed-book performers gain more from tool access, as Table 18 shows. DeepSeek-chat is the extreme: the largest absolute lift in the panel, ending within a few percentage points of Gemini-3 Pro’s headline accuracy despite starting from a single-digit-teen closed-book floor. Closed-frontier checkpoints with stronger parametric coverage gain less because they are already answering more questions before retrieval ever helps. The pattern is consistent with the synthesis-axis interpretation in Section 4.2: tools substitute for parametric coverage on items the model can synthesize from what it retrieves.

Three checkpoints take a net loss from the agent loop. Three panel members show negative tool-conditioned Δ in Table 18: the seven-tool sandbox actively reduces their accuracy below the closed-book baseline. The mechanism differs in each case, but the diagnosis is the same: the agent loop disrupts a conversion path that closed-book inference handled directly. *Gemini-3 Flash* crosses the 200K-token cap on nearly a third of trajectories before reaching `submit_answer`, as detailed in Section E.2; *Gemma-4-26B-A4B*’s sparse-active verbose generation drives the non-submission rate past forty percent; *Qwen3-32B* falls into a metadata-only tool cycle that never reads paper content. None of these reflect a knowledge regression, parametric content is unchanged across conditions, but each documents a behavioral failure that only the full-tool sandbox surfaces.

Below-chance closed-book commitments expose distractor susceptibility. Ten of the nineteen checkpoints in Table 18 score below the random-four-option chance baseline of 25% on closed-book, led by Kimi-K2.5 and the Qwen3 MoE variants. Their commits are systematically anti-correlated with the correct answer rather than random, which we attribute to vulnerability to the engineered distractors: with no read access to the supplied papers, the `no_context` distractor, designed to be parametrically plausible, is confidently picked over the gold. The implication for panel-level reading is that a low closed-book number must be paired with the section-recall column of Table 2 to be interpretable. It can reflect either weak parametric coverage (which tools repair) or full-tool behavioral failure (which they do not), and only the joint reading of the two columns disambiguates the two. Because a near-chance checkpoint cannot express a gradient along any stratification axis, closed-book comparisons in this paper are read per tier.

Zero-tool accuracy by exposure strata. Table 19 stratifies closed-book accuracy by gold-paper citation count, seed publication year, and venue. Citation counts are the construction-time values recorded in the pipeline, and each sample takes the maximum over its gold papers. No axis shows a monotone gradient for the closed-frontier tier, and the most cited quartile is the lowest. The open and

Table 18: Parametric (zero-tool) vs. full-tool accuracy across the 19-model panel, tier-grouped and ranked by full-tool accuracy within each tier. Chance baseline is 25%; negative Δ indicates that the seven-tool sandbox reduces accuracy below the closed-book baseline.

Model	Zero	Full	Δ	Model	Zero	Full	Δ
<i>Closed Frontier</i>				<i>Open Frontier</i>			
Gemini-3 Pro	73.4	89.1	+15.7	GLM-5.1	37.6	69.6	+32.0
GPT-5.3 codex	48.6	82.5	+33.9	DeepSeek-reasoner	25.0	59.5	+34.5
GPT-5.4	59.3	79.0	+19.7	DeepSeek-chat	18.3	56.4	+38.1
Claude Opus 4.6	55.2	77.5	+22.4	Kimi-K2.5	12.1	44.1	+32.0
Claude Sonnet 4.6	48.5	76.6	+28.1	MiniMax-M2.7	14.5	41.3	+26.8
Gemini-3 Flash	57.3	54.7	-2.6				
<i>Compute-Efficient</i>							
Gemma-4-31B	31.7	64.8	+33.1	Gemma-4-26B-A4B	24.5	23.6	-0.9
Qwen3.5-27B	17.1	48.2	+31.1	Gemma-3-27B	7.8	18.6	+10.8
Qwen3.6-35B-A3B	14.0	38.1	+24.0	Qwen3-30B-A3B	13.4	16.0	+2.7
Qwen3.5-35B-A3B	13.2	31.9	+18.8	Qwen3-32B	18.9	13.3	-5.6

compute-efficient tiers sit near the 25% chance floor, so their strata are reported for completeness rather than comparison.

Table 19: Zero-tool accuracy (%) by stratum, with per-tier decomposition. Quartiles are rank-based over the 1,011 samples; ranges give citation counts.

Axis	Stratum	n	Closed	Open	Comp.-eff.
Citations	Q1 (1–224)	252	57.5	21.7	19.2
	Q2 (226–585)	253	59.2	22.2	17.8
	Q3 (586–1,554)	253	57.1	19.9	16.5
	Q4 (1,554–54,992)	253	54.4	22.2	16.7
Year	2022	72	53.5	18.3	19.6
	2023	355	54.7	19.7	15.9
	2024	544	58.9	23.4	18.5
	2025	40	58.8	17.5	16.6
Venue	ACL	113	57.5	21.2	18.0
	CVPR	133	55.8	19.1	16.1
	ECCV	102	57.4	21.8	16.3
	EMNLP	102	57.5	19.2	20.5
	ICLR	198	58.0	23.1	17.9
	ICML	96	55.2	22.1	15.8
	NAACL	79	61.4	25.3	22.0
	NeurIPS	153	55.7	22.0	16.7
	SIGIR	35	53.8	16.0	13.6

Three-checkpoint ablation protocol. For the three checkpoints in Section 4.5 (DeepSeek-chat, Gemma-4-31B, GPT-5.3 codex), the *no-search* variant removes only `search_papers` from the seven-tool sandbox, retaining the other four literature-interacting tools (`get_paper_info`, `get_references`, `list_sections`, `read_section`) plus `think` and `submit_answer`; the agent can still navigate by following references but cannot retrieve paper IDs by keyword. The *zero-tool* variant removes the sandbox entirely (system prompts in Appendix F, Prompts 8 & 9). The cost-bounded protocol prevents running these ablations on the full 19-model panel; the three-checkpoint cohort is chosen to span the accuracy range, and we do not extrapolate to the broader pool. Per-checkpoint deltas are reported in Table 4 of Section 4.5.

F Prompts and Tool Catalogue

This appendix collects the verbatim prompts used in the construction pipeline and at evaluation time, alongside the tool catalogue exposed to the agent at evaluation time. Dynamic budget templates and per-provider formatting wrappers are omitted for brevity but available in the released harness.

F.1 Tool catalogue

The agent has access to seven tools at every step. Each tool is presented to the model as a function-calling schema with the input arguments listed in Table 20; the per-call cost is deducted from the 30-point budget at invocation. Cost asymmetry is intentional: one-point navigation tools encourage broad exploration, the five-point reading tool forces selective use, and the two free tools (`think`, `submit_answer`) are unmetered so neither reasoning nor answering can be priced out.

Table 20: The seven tools exposed to the agent. Costs are per call, deducted from the per-trajectory 30-point budget at invocation. Identical schemas, identical input typings, and identical natural-language descriptions are presented to every model.

Tool	Cost	Input	Returns
<code>get_paper_info</code>	1	<code>paper_id</code>	Title, abstract, year, and venue of the paper.
<code>get_references</code>	1	<code>paper_id</code>	List of cited papers with their IDs, titles, years, and the citation context (the sentence in which they were cited).
<code>list_sections</code>	1	<code>paper_id</code>	Section headers with alphabet aliases and per-section character counts, for example (A) Introduction (5869 chars). Aliases may be passed to <code>read_section</code> in place of a full header, and the counts let an agent price a 5-point read before paying for it.
<code>search_papers</code>	1	<code>query</code> (str), <code>top_k</code> (≤ 10 , default 5)	Top- k matching papers from the available pool, each with title and abstract.
<code>read_section</code>	5	<code>paper_id</code> , <code>section</code>	Full text of the requested section. The <code>section</code> argument accepts the full header, the alphabet alias from <code>list_sections</code> , or a unique case-insensitive substring.
<code>think</code>	0	<code>thought</code> (str)	Acknowledgement; the thought is appended to the trajectory transcript and remains available for the agent’s later reasoning steps.
<code>submit_answer</code>	0	<code>option</code> (A/B/C/D)	Terminates the trajectory and records the agent’s final choice.

F.2 Error handling and budget enforcement

Budget rejection. Each tool call deducts its per-call cost from the trajectory’s 30-point pool at invocation. If the remaining budget is insufficient to cover a call’s cost, the harness rejects the call with the message: “REJECTED: Insufficient budget (X remaining, *tool* costs Y). You cannot use this tool. Call `submit_answer` immediately with your best guess based on evidence gathered so far.” No cost is deducted on rejection. The agent sees the rejection in its conversation history and may issue `submit_answer` on the next turn. If a second budget-rejected tool call occurs immediately after the first, the trajectory terminates as `terminated_by = "budget"`; the first successful (non-rejected) call resets this counter to zero. When budget reaches zero before the agent’s next turn, the harness additionally appends “Budget exhausted. You MUST call `submit_answer` now with your best guess” to the next user-side input as a soft nudge. The agent is informed of the total budget in the system prompt, and every tool result carries a one-line status footer with the current turn, cumulative token usage, and budget spent (e.g., Turn: 8 | Tokens used: 23,379 | Budget used: 20); resource-management behavior is therefore measured under full disclosure of resource state.

Token-limit enforcement. Cumulative tokens are checked against the 200K cap after every assistant response. If the cap is exceeded, the trajectory terminates immediately with `terminated_by = "token_limit"`.

Max-turns enforcement. The trajectory terminates with `terminated_by = "max_turns"` once the agent has issued 20 assistant turns without calling `submit_answer`. The live turn count appears in the same per-result status footer.

Termination categories. Trajectories end via one of five outcomes: "answer" (the agent calls submit_answer), "budget" (two consecutive budget rejections), "token_limit" (200K cap hit), "max_turns" (20-turn cap hit), or "error" (five consecutive non-transient API errors). The first four are expected outcomes and constitute the four submission/non-submission categories analyzed throughout the paper; "error" is reserved for systematic-failure review and is rare in practice.

Sample-level retry on hard error. A sample is permitted up to two retries (three attempts total) on hard errors: API authentication failure, persistent provider 5xx, or five consecutive non-transient API errors within a single attempt. Transient errors (rate-limit, temporary 5xx) trigger an in-place retry without consuming the turn budget or a sample-retry counter. Tool-level malformations (unknown tool name, missing required argument, malformed JSON envelope) are surfaced to the agent as an error message in the tool result and do not retry the sample.

The remaining subsections list the verbatim system prompts used at every stage of the pipeline and at evaluation time. Each prompt is shown inside a breakable framed box with a caption identifying the pipeline stage at which it is invoked. Prompts appear in pipeline order: chain-screening judge (Stage 2), question generation (single-target then multi-target), MCQ distractor generation (paper-grounded then parametric), the two automated filters (shortcut detection then consensus), the GPT-5.4 audit-prep generator that drives the human audit, and finally the agent and ablation system prompts used at evaluation time. The budget block is static across samples and appears in full in the agent system prompt.

Table 21: Stage 2 chain-screening prompt. GPT-5.4 scores each candidate (seed, hop1, candidate) chain on a 1–5 “curiosity gap” scale conditioned on the abstracts and citation path. Only chains scoring ≥ 4 are retained as MCQ-generation candidates.

You are screening candidate papers for a multi-hop research QA benchmark. Given a seed paper and a candidate paper reachable through citation links, evaluate whether the candidate is a good question target.

A good question target has:

1. A specific curiosity gap: a reader of the seed would have a natural reason to seek this paper
2. Specific factual content: the candidate’s abstract mentions concrete results, numbers, metrics, or findings
3. Non-obviousness: the answer requires actually navigating to and reading the candidate paper

You will receive the seed paper’s abstract, the candidate paper’s abstract, and the citation path connecting them. Focus on the content of the abstracts and the research narrative implied by the path.

=== FEW-SHOT EXAMPLES ===

Example 1 - KEEP (score: 4)

Seed: "RAG with Knowledge Graphs for Customer Service QA" (2024)

Candidate: "UniKGQA: Unified Retrieval and Reasoning for Multi-hop KGQA" (2022)

Path: Seed -> "Reasoning on Graphs" -> Candidate

Evaluation: {"score": 4, "curiosity_gap": "Seed uses KG-augmented RAG; hop1 discusses KG reasoning for LLMs and explicitly states it improves on prior KGQA methods; candidate is the SOTA method being improved upon - a reader would want to know what the baseline approach was", "candidate_fact": "UniKGQA unifies retrieval and reasoning in both architecture and parameter learning for multi-hop KGQA", "reasoning": "The citation path shows a clear improvement relationship with specific technical claims. The candidate has concrete contributions that a seed reader would naturally want to understand."}

Example 2 - REJECT (score: 2)

Seed: "MIRAGE: Metric-Intensive Benchmark for RAG Evaluation" (2025)

Candidate: "How Much Knowledge Can You Pack into Parameters of a Language Model?" (2020)

```
Path: Seed -> "RAG for Knowledge-Intensive NLP Tasks" -> Candidate
Evaluation: {"score": 2, "curiosity_gap": "The connection is tangential -
hop1 cites the candidate as a closed-book QA baseline for comparison, not
as a follow-up research question", "candidate_fact": "Mentions that storing
knowledge in parameters scales with model size, but no specific metrics in
abstract", "reasoning": "The candidate is cited as a contrasting paradigm
(retrieval vs parametric), not as part of a research trajectory a seed
reader would naturally follow."}
```

Example 3 - BORDERLINE (score: 3)

Seed: "MIRAGE: Metric-Intensive Benchmark for RAG Evaluation" (2025)

Candidate: "Dense Passage Retrieval for Open-Domain Question Answering" (2020)

Path: Seed -> "RAG for Knowledge-Intensive NLP Tasks" -> Candidate

```
Evaluation: {"score": 3, "curiosity_gap": "RAG uses DPR as its retriever -
a reader might want to understand the retrieval component, but this is more
of a technical dependency than a research curiosity gap", "candidate_fact":
"Dense retriever outperforms BM25 by 9-19% absolute in top-20 passage
retrieval accuracy", "reasoning": "The candidate has specific metrics but
the connection from the seed is about implementation detail (which
retriever RAG uses) rather than a research question. Useful but generic."}
```

=== END EXAMPLES ===

Score 1-5:

- 1 = no viable question (group citation, no specific facts, or answer is obvious from seed)
- 2 = weak (vague connection or abstract lacks specific findings)
- 3 = possible but generic (connection exists but question would be shallow)
- 4 = good (specific curiosity gap + concrete answerable facts in candidate)
- 5 = excellent (clear research narrative + specific metrics/findings)

Respond as JSON only:

```
{
  "score": N,
  "curiosity_gap": "what specific question would a seed reader have about
                    this paper?",
  "candidate_fact": "a specific fact/number from the candidate's abstract,
                    or null",
  "reasoning": "one sentence explaining your score based on the abstracts
                and path"
}
```

Table 22: System prompt used at the question-generation stage of the construction pipeline to generate single-target (depth-1 and depth-2) questions whose answer lies in a single terminal paper reachable from the seed.

You are creating research questions that model how a researcher THINKS while reading a paper.

A researcher reads the seed paper, notices a specific claim, comparison, or referenced technique, and follows citations to the terminal paper where they find the answer.

Your job: given a citation chain (seed -> ... -> terminal) with full paper content, create a question that captures this natural research curiosity. Each prompt includes a QUESTION MODE specifying the citation relationship and cognitive skill to target.

=== STEP 1: UNDERSTAND THE SEED PAPER ===

Before generating any question, first read the seed paper carefully

and identify:

1. What is the paper's core contribution or thesis?
2. What specific claims, comparisons, or design choices does it make?
3. How does it reference or rely on the cited works in this chain?

Articulate this understanding in the "seed_understanding" field. This grounds everything that follows -- a good question cannot come from a superficial reading.

=== ANSWER RULES ===

The answer must be 1-2 sentences stating a specific finding, design choice, or result as a direct factual claim. Write as if asserting the fact itself -- do NOT attribute it to a paper ("the paper reports...", "the cited work shows...", "the authors found..."). Just state the finding.

- WRONG: "The cited paper reports that the model achieves 94.1% accuracy on COCO."
- WRONG: "According to the referenced work, tiling reduces memory by 3x."
- RIGHT: "The model achieves 94.1% accuracy on COCO with a ResNet-50 backbone."
- RIGHT: "Tiling the attention computation reduces peak memory usage by 3x."

Do not give a bare number; describe the finding. Do not speculate or add reasoning beyond what the terminal paper states.

If no good answer exists in the terminal paper content, output "answer": null.

=== ANSWER_CONTEXT RULES ===

The answer_context field must be EXACT TEXT copied from the terminal paper content above. Do not add any framing, attribution, or modification:

- WRONG: "From Table 3: the model achieves 94.1%..."
- WRONG: "From the terminal paper: 'We use T=1000...'"
- WRONG: "The authors report that..."
- RIGHT: "We use T = 1000 for all experiments. We set the forward process variances to constants increasing linearly from $\beta_1 = 10^{-4}$ to $\beta_T = 0.02$."

If the answer comes from a table, copy the relevant row(s) exactly as they appear in the table content. Do not paraphrase or summarize table data.

=== QUESTION RULES ===

The question must be GROUNDED in a specific detail from the seed paper -- a claim, comparison, design choice, limitation, or cited result.

CRITICAL -- SEED DEPENDENCY: The question must require information from the seed paper to answer, not just as a navigation clue but as CONTEXT that determines what to look for in the terminal. The question text should reference a concrete detail from the seed (a number, a claim, a comparison, a stated limitation) that CONSTRAINS which part of the terminal paper is relevant.

Self-check: if someone receives ONLY the terminal paper and this question (without the seed), would they immediately know which of

the terminal's many findings to focus on? If yes, the seed is just a pointer -- rewrite so the seed's specific claim narrows the answer.

Good pattern: "Seed claims X about cited work -> what does cited work report about X?"

Bad pattern: "Seed mentions cited work -> what does cited work do?"

Naming:

- You MAY freely name the seed paper, its methods/models, and intermediate papers
- MUST NOT name the terminal paper by title -- the agent must discover it through navigation

Phrasing -- do NOT use any of these patterns:

- "In [paper], the authors..."
- "While reading [paper], a researcher..."
- "A researcher reading [paper]..."
- "To contextualize..."

Instead, write direct questions grounded in specific paper content.

Output as JSON:

```
{
  "seed_understanding": "2-3 sentences: the seed paper's core
    contribution and how the citation chain relates to it",
  "seed_detail": "The specific claim/comparison/detail from the seed
    paper that motivates the question",
  "seed_dependency": "Explain how the seed's detail constrains what
    to look for in the terminal -- why can't someone answer this
    from the terminal alone?",
  "question": "The research question (2-4 sentences, direct
    phrasing)",
  "answer": "1-2 sentence answer drawn from the terminal paper",
  "answer_context": "The sentence/paragraph containing the answer
    (copy verbatim from terminal content)",
  "hops_required": "what each hop contributes to answering"
}
```

Table 23: System prompt used at the question-generation stage of the construction pipeline to generate multi-target questions whose answer requires synthesizing claims across two or three cited papers.

You are creating research questions that require SYNTHESIZING information across multiple cited papers.

A researcher reads the seed paper, notices a passage discussing or comparing two or three cited works, and realizes they need to read BOTH cited works and combine their findings to fully understand the comparison.

Your job: given a seed paper and 2-3 target papers it cites (with full content), create a question that:

1. Guides the reader from the seed paper TOWARD the target papers through narrative clues
2. REQUIRES reading multiple target papers to answer

Each prompt includes a QUESTION MODE specifying the citation relationship and cognitive skill to target.

=== STEP 1: UNDERSTAND THE SEED PAPER ===

Before generating any question, first read the seed paper carefully and identify:

1. What is the paper's core contribution or thesis?
2. What specific passage discusses or compares the target papers together?
3. What role does each target paper play in the seed's narrative (baseline, inspiration, competing approach, etc.)?

Articulate this understanding in the "seed_understanding" field. This grounds everything that follows -- a good synthesis question cannot come from a superficial reading.

=== ANSWER RULES ===

The answer must be 1-2 sentences combining specific observations from both papers as direct factual claims. Write as if asserting the facts -- do NOT attribute them to papers ("the paper reports...", "the cited work shows...", "the authors found..."). Just state the findings.

- WRONG: "The first paper reports 94.1% AP while the second paper achieves 91.3% AP."
- RIGHT: "The sparse detector achieves 94.1% AP while the conditional query approach reaches 91.3% AP on COCO val2017."

MUST NOT name target papers -- use role descriptions ("the first approach", "the sparse detector"). Do not speculate or add reasoning beyond what the papers state.

If no good synthesis question exists, output null for all fields.

=== ANSWER_SOURCES RULES ===

Each "fact" in answer_sources must be EXACT TEXT copied from that paper's content above. Do not add any framing, attribution, or modification:

- WRONG: "Table 3 shows that the model achieves 94.1%..."
- WRONG: "The authors report that..."
- RIGHT: "achieves 94.1% accuracy on COCO val2017 with a ResNet-50 backbone"

If the fact comes from a table, copy the relevant row(s) exactly as they appear in the table content. Do not paraphrase or summarize table data.

=== QUESTION RULES ===

The question must be grounded in a specific passage from the seed paper where multiple cited works are discussed together. Describe each target paper by the ROLE or CHARACTERIZATION the seed gives it -- not by name.

CRITICAL -- SEED DEPENDENCY: The question must require information from the seed paper to answer, not just as a way to identify which papers to read. The seed should provide context that CONSTRAINS what to look for across the target papers -- a specific comparison frame, a claim to verify, or a characterization that narrows the relevant findings.

Self-check: if someone receives ONLY the target papers and this question (without the seed), would they immediately know which findings to compare and how? If yes, the seed is unnecessary -- rewrite so the seed's specific framing determines the answer.

Naming:

- You MAY freely name the SEED paper, its methods, models, and datasets
- MUST NOT name target papers by title, method name, model name, or acronym
- Instead, DESCRIBE each target paper by the role the seed gives it:
 - "a sparse detector that learns proposals directly" (not "Sparse R-CNN")
 - "an approach that accelerates convergence via conditional spatial queries" (not "Conditional DETR")
- The description must be specific enough that a reader of the seed paper can identify which citation to follow

Phrasing -- do NOT use any of these patterns:

- "In [paper], the authors..."
- "While reading [paper], a researcher..."
- "A researcher reading [paper]..."
- "To contextualize..."

Instead, write direct questions grounded in specific paper content.

Output as JSON:

```
{
  "seed_understanding": "2-3 sentences: the seed paper's core
    contribution and how the target papers relate to it",
  "seed_detail": "The specific passage from the seed paper
    motivating this question",
  "seed_dependency": "Explain how the seed's framing constrains what
    to look for across target papers -- why can't someone answer
    this from the targets alone?",
  "question": "The synthesis question (2-4 sentences, target papers
    described by role not name)",
  "answer": "1-2 sentence answer combining observations from both
    papers (no target paper names)",
  "answer_sources": {
    "paper_1": {"arxivId": "...", "fact": "specific fact from
      paper 1"},
    "paper_2": {"arxivId": "...", "fact": "specific fact from
      paper 2"}
  },
  "why_multi_paper": "Brief explanation of why reading multiple
    papers is required"
}
```

Table 24: Paper-grounded distractor system prompt used at the MCQ-generation stage of the construction pipeline. Invoked twice per chain: once with the seed paper text to produce the `seed_only` distractor (a finding genuinely supported by the seed but irrelevant to the cited claim), and once with a sibling target paper's text to produce the `wrong_paper` distractor (a real claim from a related-but-incorrect paper).

You answer research questions using the provided paper content.

=== ANSWER RULES ===

The answer must be 1-2 sentences describing a specific finding, design choice, or result from the paper. It must be drawn directly from what the paper states -- do not speculate, interpret, or add reasoning beyond what the paper says. Do not give a bare number; describe the finding.

If the provided content does not directly address the question, use the most relevant information available to construct a specific, affirmative answer. NEVER say "the paper does not", "does not discuss", "does not specify", "does not mention", "not directly addressed", or any similar qualification. Always answer with what IS in the content, never with what is missing.

=== ANSWER_CONTEXT RULES ===

The answer_context field must be EXACT TEXT copied from the paper content above. Do not add any framing, attribution, or modification:

- WRONG: "From Table 3: the model achieves 94.1%..."
- WRONG: "The authors report that..."
- RIGHT: "We use $T = 1000$ for all experiments. We set the forward process variances to constants increasing linearly from $\beta_{10^{-4}}$ to $\beta_T = 0.02$."

If the answer comes from a table, copy the relevant row(s) exactly as they appear in the table content. Do not paraphrase or summarize table data.

Output as JSON:

```
{"answer": "your 1-2 sentence answer", "answer_context": "exact text from source"}
```

Table 25: Parametric (closed-book) distractor system prompt used at the MCQ-generation stage of the construction pipeline to produce the no_context distractor: a confident, surface-plausible answer drawn solely from the model's parametric knowledge, with no paper text in the prompt.

You answer research questions based on your knowledge of the literature.

=== ANSWER RULES ===

The answer must be 1-2 sentences describing a specific finding, design choice, or result. Be concrete and specific -- include numbers, method names, and dataset names where possible. Do not give a bare number; describe the finding.

NEVER say "I don't know", "I'm not sure", or any similar qualification. Always give a specific, confident answer.

Output as JSON:

```
{"answer": "your 1-2 sentence answer"}
```

Table 26: Shortcut-detection-filter system prompt used at the model-ensemble filtering stage. The 3-model ensemble (GPT-4.1, Claude Sonnet 4.6, deepseek-chat) is asked to answer the MCQ given access to only one paper at a time: the seed paper or the terminal target paper. Samples answerable from a single paper alone are discarded.

You are answering a multiple-choice question about academic research. You have access to ONE paper. Use ONLY the provided paper to answer. If no option fits well, pick the closest one.

You MUST respond with ONLY this JSON and nothing else:

```
{"answer": "X"} where X is A, B, C, or D.
```

Table 27: Consensus-filter system prompt used at the model-ensemble filtering stage. The 3-model ensemble is asked the MCQ *without* any paper context. Samples on which the ensemble fails to converge on the gold answer are flagged for closer review and feed into the consensus-tier assignment described in Appendix C.

You are answering a multiple-choice question about academic research. You have access to all papers needed to answer. Read carefully and select the correct answer.

You MUST respond with ONLY this JSON and nothing else:
{"answer": "X"} where X is A, B, C, or D.

Table 28: GPT-5.4 audit-prep system prompt used to generate the structured guide that orients human auditors. Run once per post-filter sample with the full seed and target paper(s) attached, the prompt produces a JSON record (claim decomposition, chain or synthesis verification, and section-level recall labels) that is presented to human auditors during the Gradio audit pass and stored as the released ground truth for section-recall metrics.

You are an audit assistant for AgentHop, a multi-hop scientific reasoning benchmark.

You will receive:

- A benchmark question designed to test citation-chain navigation
- The correct answer to that question
- Full content of the seed paper and target paper(s), including appendix sections

Your job is to verify the QUERY and CORRECT ANSWER only. You are NOT selecting an answer from multiple options.

The sample type will be indicated as "single-target" or "multi-target". Apply the type-specific checks described below.

Return a JSON object with the following structure:

```
{
  "query_quality": {
    "verdict": "pass" | "warn" | "fail",
    "natural": true | false,
    "unambiguous": true | false,
    "requires_target": true | false,
    "note": "Brief explanation of any issues with the question
              wording, clarity, or scope. Empty string if none."
  },
  "answer_validity": {
    "verdict": "pass" | "warn" | "fail",
    "claims": [
      {
        "claim": "A specific factual assertion from the correct
                  answer",
        "source_paper": "Which paper contains this claim (seed
                        title or target title)",
        "source_section": "Exact section header where this claim
                          is found",
        "verbatim_match": true | false,
        "verified": true | false,
        "note": "Discrepancy detail if not verified, or empty
                string"
      }
    ]
  }
}
```

```

},
"chain_coherence": {
  "verdict": "pass" | "warn" | "fail",
  "seed_to_bridge": "Does the seed paper's citation context
    naturally point toward the bridge paper? Explain briefly.",
  "bridge_to_terminal": "Does the bridge paper lead to the
    terminal? Is the bridge necessary or could you skip it?",
  "bridge_necessary": true | false,
  "note": "Any issues with the citation chain logic. Empty
    string if none."
},
"synthesis_check": {
  "verdict": "pass" | "warn" | "fail",
  "both_targets_needed": true | false,
  "target_1_contribution": "What fact/evidence does target 1
    contribute to the answer?",
  "target_2_contribution": "What fact/evidence does target 2
    contribute to the answer?",
  "genuine_synthesis": true | false,
  "note": "Is this genuine cross-paper synthesis or just two
    independent facts? Empty string if fine."
},
"section_recall_labels": [
  {
    "paper": "Paper title (as provided in the content headers)",
    "arxiv_id": "arxiv ID if identifiable from the content
      header, else empty string",
    "section": "Section header containing answer-relevant
      evidence",
    "relevance": "direct" | "supporting",
    "what_it_contains": "Brief description of what evidence this
      section provides for the answer"
  }
],
"structural_integrity": {
  "verdict": "pass" | "warn" | "fail",
  "missing_sections": ["Section names that appear to be missing
    from the provided content, if any"],
  "note": "Brief explanation of structural issues, or empty
    string"
}
}

```

Type-specific instructions:

FOR SINGLE-TARGET SAMPLES:

- Focus on "chain_coherence". The key question is whether the seed -> bridge -> terminal path is natural and necessary.
- Check: does the seed paper's text contain a citation or reference that would lead a reader toward the bridge paper?
- Check: does the bridge paper connect to the terminal, or could you reach the terminal directly from the seed?
- Check: is the answer found ONLY in the terminal paper, not in the seed or bridge?
- Set "synthesis_check" fields to null -- not applicable for single-target.

FOR MULTI-TARGET SAMPLES:

- Focus on "synthesis_check". The key question is whether BOTH target papers are genuinely needed.
- Check: does the answer combine information from both targets, or could one target alone suffice?
- Check: is the synthesis genuine (comparing, contrasting,

- combining) or superficial (two unrelated facts)?
- Set "chain_coherence" fields to null -- not applicable for multi-target.

General guidelines:

- For "claims": decompose the correct answer into individual factual assertions. Each number, comparison, method name, or result is a separate claim.
- For "section_recall_labels": list ALL sections across ALL provided papers that contain evidence relevant to the answer. "direct" = the claim is stated here; "supporting" = provides context needed to interpret the claim.
- For "requires_target": true if the question cannot be answered from the seed paper alone (this should almost always be true).
- For "verbatim_match": true if the claim text appears nearly word-for-word in the source section.
- Be precise with section names -- use the exact header as it appears in the provided content.

IMPORTANT: Return ONLY the JSON object. No markdown, no explanation outside the JSON.

Table 29: Agent system prompt used at evaluation time in the full-tool condition. Identical text is presented to every model; the placeholders {tools_block} and {task_block} are filled at request time with the seven-tool catalogue of Table 20 and the per-sample question with four options. The budget block is identical for every sample and is printed in full above.

You are a research assistant tasked with answering a multi-hop scientific question. You will navigate a citation graph of academic papers using a set of tools. Your goal is to gather sufficient evidence from the papers to select the correct answer.

Task Overview

You are given a seed paper as your starting point. The answer requires information from one or more papers reachable through the citation graph -- papers cited by the seed, or papers cited by those papers (up to 2 hops). You must explore the graph strategically, read relevant sections, and synthesize evidence to choose the best answer.

{tools_block}

Constraints

You operate under three independent limits. The run terminates when any one is hit:

- **Budget**: 30 points total. Navigation tools cost 1 pt; read_section costs 5 pts.
- **Turns**: at most 20 conversational turns.
- **Tokens**: at most 200,000 cumulative prompt + completion tokens per sample.

After every tool result you will see a status line reporting counters only:

'Turn: T | Tokens used: U | Budget used: B'.

You are responsible for tracking these against the limits above.

Manage your resources strategically:

- Use navigation tools (1 pt) to identify the right papers and sections first.
- Use read_section (5 pts) only on sections you have reason to believe contain relevant evidence.

- Submit your answer when you have gathered enough evidence. Do not exhaust your budget exploring if you already have a strong basis for an answer.

{task_block}

Table 30: Zero-tool ablation system prompt used in the closed-book replicate (Section 4.5 and Appendix E.4). All retrieval, navigation, and reasoning tools are removed; the only function call available to the model is `submit_answer`.

You are a research assistant tasked with answering a multi-hop scientific question. You must answer based solely on your own knowledge -- no tools are available.

Read the question and answer options carefully. Use your knowledge of the scientific literature to reason about which answer is most likely correct. Consider the claims made in each option, whether the described findings are consistent with known results in the field, and the technical plausibility and specificity of each option.

{task_block}

You MUST call `submit_answer` with your best guess. Reason carefully, then choose.

No-search ablation prompt. The no-search condition reuses Prompt 8 verbatim, but the rendered {tools_block} omits the `search_papers` entry; the agent still has access to the six remaining tools and must navigate to evidence through citation traversal alone. No other prompt modifications are made, as specified in Section 4.5.

G Example Trajectories

To make the diagnostic decomposition concrete, we walk through one AgentHop sample (mt_0785, multi-target depth-2) end-to-end and contrast a successful Claude Opus 4.6 trajectory with a failed Kimi-K2.5 trajectory on the same item.

G.1 The sample

Sample mt_0785 (multi-target, depth-2)

Seed paper. *Reflexion: language agents with verbal reinforcement learning* (Shinn et al., 2023; arXiv 2303.11366).

Question. “Reflexion contrasts itself with earlier LLM-based agents that act in external environments, especially a browser-based question-answering system that depends on human demonstrations/comparisons and a robot planner that grounds candidate actions with affordance scores. Looking across those two foundations, what concrete training or control machinery does each one require, and what headline task outcomes show the kinds of grounded performance Reflexion is trying to replace with verbal reinforcement rather than weight updates?”

Options.

- A** (NC – no_context distractor) “WebGPT trains GPT-3 to use a text web browser with behavior cloning followed by reward modelling and RL fine-tuning, and on ELI5 humans preferred WebGPT $\approx 56\%$ of the time over human-written answers; SayCan multiplies LM skill scores by learned affordance estimates and reaches $\approx 74\%$ execution success on a real mobile manipulator.”
- B** (GOLD) “WebGPT fine-tunes GPT-3 with behavior cloning, reward modelling, PPO, and best-of- n , and its 175B best-of-64 system is preferred 56% of the time over human demonstrators;

SayCan multiplies LM skill probabilities by learned affordance/value estimates, reaching 84% planning success and 74% execution success across 101 instructions in the mock kitchen.”

- C (SO – seed_only distractor) “Earlier agents relied on different training or control machinery, WebGPT used demonstrations/comparisons, SayCan used affordance scores. Reflexion improves over baselines by 22% on AlfWorld, 20% on HotPotQA, and 11% on HumanEval.”
- D (WP – wrong_paper distractor) “Earlier methods include behavior cloning, reward modelling, RL, and rejection sampling; on toxicity reduction Self-Correct outperforms baselines while on math synthesis a GPT-3 Instruct generator improves from 84.90 to 90.90 on Multitask...”

The gold answer requires synthesizing specific numerical results from *two* different cited papers (WebGPT, arXiv 2112.09332; SayCan, arXiv 2204.01691). Distractor A is plausible-sounding without paper access (parametric reliance), C summarizes the seed paper’s own results (navigation failure, did not leave the seed), and D mixes details from a different paper entirely (retrieval error).

G.2 Successful trajectory: Claude Opus 4.6 (8 turns, 19/30 budget)

Trajectory 1: Claude Opus 4.6 on mt_0785 (correct, 8 turns, 19/30 budget)

```
T0: get_paper_info(Reflexion-seed)
→ “Title: Reflexion: language agents with verbal reinforcement learning”
get_references(Reflexion-seed)
→ “References for paper ... (30 papers): WebGPT, SayCan, ReAct, ...”
T1: think
T2: list_sections(WebGPT) → 19 sections: A.Introduction ... C.Methods,
D.Evaluation, ...
list_sections(SayCan) → 13 sections: A.Introduction ... C.SayCan, E.Experimental
Evaluation
T3: read_section(WebGPT, "C") // Methods
→ “3 Methods. 3.1 Data collection. Guidance from humans is central ... A language
model
pre-trained on natural language would not be able to use our text-based browser ...”
read_section(SayCan, "E") // Experimental Evaluation
→ “5 Experimental Evaluation. Figure 4: experiments performed in an office kitchen
and a
mock kitchen ... 5 locations, 15 objects ... 84% planning success, 74% execution
success ...”
T4: think
T5: read_section(WebGPT, "D") // Evaluation
→ “4 Evaluation. We focused on three WebGPT models, each trained with behavior
cloning
followed by rejection sampling against a reward model ... best-of-64 ... 56%
preference rate ...”
T6: think
T7: submit_answer("B") ✓ correct
```

Opus reaches both gold target papers in a single planning step (T0–T2), reads exactly the sections that hold the methodology and headline numbers in parallel (WebGPT Methods + SayCan Experimental Evaluation at T3), thinks, reads WebGPT Evaluation to confirm the 56% number, thinks again, and submits. Every read is paired with a think call. Budget consumed: 19 of 30 points; turns: 8.

G.3 Failed trajectory: Kimi-K2.5 (14 turns, 27/30 budget)

Trajectory 2: Kimi-K2.5 on mt_0785 (incorrect, 14 turns, 27/30 budget)

```
T0: get_paper_info(Reflexion-seed)
T1: get_references(Reflexion-seed)
T2: get_paper_info(WebGPT) + get_paper_info(SayCan)
T3: list_sections(Reflexion-seed)
T4: read_section(Reflexion-seed, "B") // Related work (wasted)
→ “2 Related work. Reasoning and decision-making. Self-Refine employs an iterative
framework ...”
```

```

T5: read_section(Reflexion-seed, "A") // Introduction (wasted)
→ "1 Introduction. Recent works such as ReAct, SayCan, Toolformer, ..."
T6: list_sections(WebGPT)
T8: read_section(WebGPT, "C") // Methods (gold-paper, gold-section: matches Opus
T3)
→ "3 Methods. 3.1 Data collection ..."
T9: read_section(WebGPT, "D") // Evaluation (gold-paper, gold-section)
→ "4 Evaluation ... 56% preference rate ..."
T10: list_sections(SayCan)
T11: read_section(SayCan, "C") // SayCan (gold paper but wrong section - this is the
method-description block, not the Experimental Evaluation that contains the 84%/74%
figures)
→ "REJECTED: Insufficient budget (3 remaining, read_section costs 5)."
T12: think
T13: submit_answer("A") ✗ wrong (selected NC distractor)

```

Kimi burns three early turns re-reading the seed paper (T4–T5, sections it already had abstracts for) before pivoting to the gold target papers. It reaches WebGPT successfully but, when it pivots to SayCan, it reads the descriptive “SayCan” section (C) rather than the “Experimental Evaluation” section (E) that contains the headline 84%/74% numbers, and the read is even *rejected* for insufficient budget. With only 3 budget points left and a single think call before submission, Kimi defaults to the plausible-sounding option A (NC). Budget consumed: 27 of 30; turns: 14.

G.4 What the diagnostic columns record

For this single sample, AgentHop’s diagnostic surface produces:

- **Opus:** accuracy 1, paper recall 1, section recall 1 (read both gold sections), conversion 1, budget 19/30, turns 8.
- **Kimi:** accuracy 0, paper recall 1 (reached both gold papers), section recall 0 on SayCan (read “SayCan” instead of “Experimental Evaluation”), conversion contribution 0, budget 27/30, turns 14, NC error.

Aggregate accuracy alone marks Kimi wrong without explanation; the decomposition reveals *where* it failed, navigation reached the right papers, but section-level retrieval missed the experimental-evaluation block that contains the gold numbers, and the model defaulted to the parametric distractor under uncertainty.