

Itgan at NADI 2026 shared task: Parameter-Efficient Whisper Adaptation for Robust, Mixed-Dialect and Code-Switched Arabic ASR

Ibrahim Almajai

Independent Researcher

i.almajai@gmail.com

Abstract

We describe the Itgan systems for the three ASR subtasks of NADI 2026, namely robust country-level ASR (1.1), mixed-dialect ASR (1.2), and Tunisian code-switched ASR (1.3). All three share one recipe, Whisper adapted with LoRA on consumer GPUs, and each was carried by a different addition to it. On 1.1, where the dialect label is given at test time, per-dialect specialists continued from a pooled adapter gave the largest gain, and the submitted system reached 57.1% country-average WER. A post-evaluation linear probe on frozen encoder features routes utterances without the label and recovers 44% of what oracle routing gives. On 1.2 the choice of base model mattered more than adapter capacity, and system combination helped only once we added a decorrelated member, reaching 46.7% WER. On 1.3 our system placed second at 14.49% WER with the lowest CER among the leading submissions, 5.38%. Its last 0.60 WER points came without further training, mostly from an exact weight-space average of independently trained runs, with ROVER voting adding the remainder. Every comparison carries a paired-bootstrap test, and we report eight directions that did not work.

1 Introduction

The NADI 2026 shared task (Sullivan et al., 2026) continues the multidialectal Arabic speech processing track introduced the previous year (Tallafha et al., 2025). We entered its three ASR subtasks: robust country-level ASR on noisy band-limited speech in eight national dialects, scored as an unweighted mean of per-country WER (1.1); mixed-dialect ASR without dialect labels (1.2); and Tunisian Arabic with frequent switching into French and English (1.3). Section 2 describes the data.

A single parameter-efficient recipe (Section 3) underlies all three systems, which differ only in

what had to be added on top. Our central finding is that the three subtasks reward different interventions, and that identifying which one applies is worth more than additional training. Per-dialect specialists carried 1.1, base-model choice carried 1.2 and training-free combination carried 1.3. On 1.2 the base model was worth 3.76 points while widening the adapter was a non-significant 1.02, and training-free combination was worth 0.60 points on 1.3 but nothing on 1.2 until we decorrelated the ensemble.

None of the components we use is new. LoRA, SpecAugment, weight averaging and ROVER are all established, and our contribution is in the measurements and the system design. We give a per-dialect specialization recipe that continues training from a pooled multi-dialect adapter, and a linear probe on frozen encoder features that routes to those specialists without the gold dialect label. The probe recovers 44% of the oracle gain, with the identifier rather than the specialists as the limit (Section 4, Appendix I). We show that base-model choice, not adapter capacity, is the binding constraint for dialectal word-form errors on 1.2, with a matched-capacity control. We argue that decoder depth is the likely reason for that advantage without isolating it from turbo’s post-pruning fine-tuning (Section 5). We give exact weight-space averaging across *independently trained* runs, which beats averaging within one run even when the runs differ only in seed (Section 6.1). We also give evidence that ROVER (Fiscus, 1997) gains come from decorrelation rather than system count (Section 5). Every comparison carries a paired-bootstrap test (Appendix C), and we report eight directions we rejected (Appendix G).

2 Data

Subtask 1.1. Eight country configurations with 1,600 training utterances each, a 10,808-utterance

development set holding 726 to 1,600 per country, and a 4,000-utterance blind test set split evenly. The audio is sharply band-limited, about 2.1 kHz effective bandwidth and under 0.01% of its energy above 4 kHz, and noise varies far more within a country than between countries (Appendix A). Adapter selection used the full development set, the cross-backbone comparison a 200-utterance-per-country subset.

Subtask 1.2. Only a development split of 3,152 utterances from more than fifteen sub-regional varieties, without dialect labels, and a blind test set. It is the only in-domain data for the task (Section 5).

Subtask 1.3. 38 hours of Tunisian training speech from the TEDxTN (Bougares et al., 2025) and TuniFra (Choux et al., 2025) corpora, as 24,893 training, 731 validation and 842 practice-test utterances, with a 2,123-utterance blind test set. We drop four training utterances over 30 s and two with empty cleaned targets, keeping 24,887. Training targets and all scoring use the organizers’ clean_transcription normalization, so the model is optimized for the text form the metric scores. Code-switching is pervasive, with 33.3% of reference words in the practice test split in Latin script.

3 Common Setup

Every system fine-tunes a Whisper checkpoint (Radford et al., 2023) with LoRA adapters (Hu et al., 2022; Mangrulkar et al., 2022) of rank $r = 32$ and $\alpha = 64$ applied to the attention projections `q_proj`, `k_proj`, `v_proj`, `out_proj` and the feed-forward layers `fc1`, `fc2` in every encoder and decoder block. We call this target set *wide*, against a *narrow* set of `q_proj` and `v_proj` only. The frozen base is held in `bfloat16` while adapter parameters are kept in `float32`, which makes even a 1.54B-parameter checkpoint trainable within 12 GB without quantization. All training and decoding ran on two consumer GPUs, an NVIDIA RTX 3080 (10 GB) and an RTX 3060 (12 GB). We used transformers (Wolf et al., 2020) 4.49, peft 0.14 and datasets 3.6. We report WER and CER computed with jiwer 4.0.0 (Vaessen, 2025), and use a paired bootstrap over utterances (Bisani and Ney, 2004) with 4,000 resamples. Throughout, P is the fraction of resamples in which the second system of a comparison has the lower WER, not a p -value, so 100% is decisive and 50% is chance.

WER and CER are percentages throughout. Differences between systems are absolute, in WER points, and every significance test is on an absolute difference. Where we instead give a relative WER reduction, such as the share of a dialect’s error a specialist removes, we say so. A percentage of a gain, such as the share of the oracle routing gain a classifier recovers, is a ratio of two absolute differences. Decoding is not matched across subtasks. Subtask 1.1 is greedy and 1.3 beam 5, both through transformers, while 1.2 is beam 5 through faster-whisper (Klein and Ashraf, 2023). Beam search on 1.1 went untested until after the evaluation (Appendix B).

Resources used. Every model is a publicly released Whisper checkpoint, either `whisper-large-v3` (1.54B parameters) or the smaller `whisper-large-v3-turbo` (0.81B), so all three submissions are well under the shared task’s 5B model-size threshold. We shorten these to `large-v3` and `turbo`. We used *no data external to NADI 2026*. Every system was trained only on its own subtask’s data. The single exception is one of the five Subtask 1.2 ensemble members, trained on 1.2 data pooled with 1.1 audio (Section 5).

4 Subtask 1.1: Robust Country-Level ASR

Pooled adapter. We first train one `whisper-large-v3-turbo` adapter jointly on all eight countries for six epochs (27.9M trainable parameters), reaching 57.6% country-average development WER against the organizers’ zero-shot baseline of 80%.

Per-dialect specialists. For four of the eight dialects we continue training that pooled adapter on the country’s own 1,600 utterances for three epochs at learning rate 5×10^{-5} . The specialist keeps the shared multi-dialect representation instead of competing with it, and a step-matched pooled control shows the gain is specialization rather than the extra epochs (Appendix H). Because the country is known at test time, routing is deterministic and needs no dialect classifier.

A second backbone and a length guard. For the remaining four countries the transcripts come from a wide LoRA fine-tune of full `whisper-large-v3`, 57.7M trainable, chosen per country on a matched 200-per-country subset. Its best checkpoint is epoch 4 of a six-epoch schedule. Finally we cap

Country	Backbone	Dev Δ	Test WER
Mauritania	turbo + spec.	-6.5	77
Algeria	turbo + spec.	-3.1	72
Morocco	turbo + spec.	-2.9	60
Egypt	turbo + spec.	-1.9	58
Yemen	large-v3	-2.8*	63
Jordan	large-v3	-2.7*	44
UAE	large-v3	-4.5*	44
Palestine	large-v3	-1.5*	39
Country average			57.1

Table 1: Subtask 1.1 submitted system, all figures in %. *Dev Δ* is the full-development WER change in WER points from the pooled adapter to that country’s specialist; starred rows give the change from turbo to large-v3 on the subset that decided the backbone. Every specialist gain is significant but Jordan’s (Appendix C). Deltas are scored without the length guard; the guarded progression of Table 4 is smaller on Mauritania and Yemen, where the guard does part of the specialist’s work (Appendix H).

any hypothesis longer than six words per second of audio. This affects about 12 of 10,808 development utterances but is worth 1.0 country-average WER point, because runaway outputs concentrate in the weakest country and every country counts equally. It also turns out to be what makes beam search safe (Appendix B).

Results. The system scores 57.1% country-average WER / 28% CER on the blind test set, seventh of nine teams, against 43.2% for the leader. We cannot say what separates them from us; our systems saw only this subtask’s 12,800 training utterances. Table 1 shows the specialist gain tracking each dialect’s headroom almost monotonically. Without the length guard, as Table 1 is scored, a specialist removes 4 to 8% of that dialect’s remaining error. Under the guard it removes 3.6 to 4.5%, because the guard overlaps with the specialist on the over-generating dialects (Appendix H). After the evaluation closed we completed the set of eight specialists, and found beam search with the guard worth a further 1.1 points on top of all eight, reaching 53.55% in *development* WER (Appendix B).

5 Subtask 1.2: Mixed-Dialect ASR

We partition the 3,152-utterance development split (Section 2) by SHA-1 hash of the utterance id into 2,537 training and 615 held-out utterances, make every design decision on the held-out portion, then retrain the submitted model on all 3,152. Retraining on everything was worth 1.0 WER point and

System	Trainable	WER
turbo, zero-shot	n/a	60.04
turbo + LoRA (narrow)	6.6M	56.54
turbo + LoRA (wide)	27.9M	55.51
large-v3, zero-shot (int8)	n/a	57.21
large-v3 + LoRA (wide, r 16)	28.8M	52.88
large-v3 + LoRA (wide)	57.7M	51.76

Table 2: Subtask 1.2, 615 held-out utterances (%). Differences quoted in the text are paired-bootstrap estimates (Appendix C) and can differ by about 0.01 from differences of the values printed here.

changed 86% of test transcripts. It also spent the local evaluation, since a model that has seen every held-out id can no longer be scored on it.

The base model is the lever. Table 2 isolates the effect of the base model. Switching from turbo to full large-v3 was worth 3.76 WER points, against 4.52 points for all of turbo’s fine-tuning. The decisive comparison is the fourth row against the third, where *untrained* large-v3, quantized to int8, nearly matches a fully fine-tuned turbo. Adapter size explains only part of the gap. The fifth row halves the large-v3 adapter’s rank to match turbo’s 27.9M trainable parameters, and large-v3 still leads turbo by 2.65 points ($P = 100\%$, 95% interval $[-3.85, -1.39]$); the extra rank is worth the remaining 1.11 points ($P = 99\%$). Decoder depth is the most plausible reason for what is left. turbo has 4 decoder layers against 32 in its encoder, whereas full large-v3 has 32 of each. This task’s dominant error is producing the correct dialectal word form, which is decoder work. The comparison does not isolate depth, however. The turbo checkpoint is large-v3 with the decoder pruned to 4 layers and then trained further, and that training also moved its encoder weights, which we verified against the released checkpoints. The two rows therefore differ in depth, in that extra training, and in int8 quantization on the zero-shot row, which if anything handicaps it. Separating depth from turbo’s extra training would take a pruned large-v3 without that training, which we did not run. The depth reading does account for an otherwise puzzling asymmetry. Widening the adapter target set was worth roughly 8 WER points on Subtask 1.1, whose wider run also trained twice as long, but only 1.02 on a schedule-matched pair here. Whatever the mechanism, adapter capacity did not substitute for the base-model change.

Decorrelation beats system count. Our submitted entry combines five systems by word-level ROVER voting, but the path there is the informative part. Our first ensemble combined two large-v3 fine-tunes with a turbo one and scored 48%, *identical to its own pivot* (the member whose hypothesis the vote defaults to), despite an offline gain that had promised -0.65 points. A fourth member, trained on 1.2 data pooled with 12,800 utterances of Subtask 1.1 audio at roughly 37% in-domain, changed that. It disagrees with the large-v3 fine-tune we can score offline on 91% of held-out lines, while scoring within 0.33 points of it. The four-system ensemble scored 46.7%. A fifth member, zero-shot large-v3, moved nothing further, and the submitted archive is that five-system build.

Results. Decoding merges the adapter, converts to CTranslate2 (Klein et al., 2020), and adds Silero VAD (Silero Team, 2024) with no conditioning on previous text. The leaderboard progression was 52% for a wide turbo fine-tune, 49% for large-v3 on the 2,537 partition, 48% for large-v3 on all 3,152, and 46.7% WER / 19% CER for the submitted ensemble, third of four teams. Roughly 5 WER points of the reported error on this subtask are unwinnable orthographic variation (Appendix F).

6 Subtask 1.3: Code-Switched ASR

Training and regularization. We fine-tune whisper-large-v3 with the wide target set (57.7M trainable, 3.6% of the model) for 5,000 steps (≈ 3.2 epochs) with an effective batch of 16, peak learning rate 5×10^{-4} , 50 warmup steps, linear decay and gradient checkpointing. Our first wide run memorized heavily, with training loss at 0.04–0.05 while held-out loss stagnated near 0.31. Raising LoRA dropout from 0.05 to 0.15 and enabling SpecAugment (Park et al., 2019) behaved as regularization should. At matched step 3,000, training loss *rose* from 0.229 to 0.293 while held-out loss *fell* from 0.340 to 0.322, shrinking the generalization gap by a factor of 3.9.

6.1 Cross-run adapter souping

Weight averaging of independently fine-tuned models improves accuracy (Wortsman et al., 2022; Izmailov et al., 2018), but applying it to LoRA requires care. The adapter’s contribution $\Delta W_i = \frac{\alpha}{r} B_i A_i$ is *bilinear* in the factors, so averaging A_i and B_i elementwise does not average the ΔW_i . Concatenating the factors does. For N adapters of

rank r , set

$$A' = [A_1^\top \cdots A_N^\top]^\top, B' = [B_1 \cdots B_N], \quad (1)$$

with $r' = Nr$, and keep $\alpha' = \alpha$. The scaling becomes $\alpha'/r' = \frac{1}{N} \cdot \frac{\alpha}{r}$ and

$$\frac{\alpha'}{r'} B' A' = \frac{1}{N} \sum_{i=1}^N \frac{\alpha}{r} B_i A_i = \frac{1}{N} \sum_{i=1}^N \Delta W_i, \quad (2)$$

i.e. the exact mean, as an ordinary rank- Nr adapter that any PEFT implementation can load and that we merge into the base before decoding, so the extra rank is free at inference. The construction is not new, and peft provides it as the cat combination type of `add_weighted_adapter` (Mangrulkar et al., 2022). We restate it because the elementwise mistake is easy to make, and verified it on the submitted soup (maximum deviation 9×10^{-8} in float32).

Our submitted soup averages the regularized run’s last three checkpoints plus the unregularized run’s final adapter. The gain is decorrelation, not ingredient count. At two ingredients, the cross-recipe pair, one checkpoint from each run, scores 18.06%, and the same-run pair 19.28%, a gap of 1.23 points ($P = 100\%$). A second checkpoint from the same run is worth only 0.18 points, which is not significant. Two ingredients from different runs beat three from one (18.66%), and six ingredients, with the weaker run at half weight, score 17.81%. The regularized and unregularized runs differ in seed as well as in regularization, so after the evaluation we retrained the regularized recipe at a second seed, changing nothing but initialization and data order. The second seed alone scores 18.71% against 19.46%, a spread that is not significant ($P = 87\%$). Averaging the two seeds scores 16.91%, which is 2.38 points below the same-run pair ($P = 100\%$), 1.16 points below the cross-recipe pair ($P = 99\%$), and indistinguishable from the submitted four-ingredient soup (17.19%, $P = 87\%$). Seed decorrelation alone accounts for the cross-run gain.

6.2 ROVER and results

We finally combine the soup as pivot with the two trained models as voters, by word-level majority voting over aligned token positions, with the pivot breaking the ties, which arise only where all three disagree. This modifies 63 of 2,123 blind utterances. Its effect is small and not uniformly positive, at -0.10 WER points on validation, -0.06

System	Trainable	Validation (731)		Practice test (842)		Blind test (2,123)
		WER	CER	WER	CER	WER / CER
Zero-shot whisper-large-v3 [†]	n/a	85.00	59.84	87.57	64.40	n/a
LoRA (q, v), 3k steps	15.7M	21.62	9.11	24.68	11.79	n/a
LoRA (wide), 5k steps	57.7M	19.84	8.26	21.74	10.16	n/a
+ dropout 0.15, SpecAugment	57.7M	19.46	8.29	21.19	10.08	15.09 / 5.56
+ adapter soup ($N=4$)	n/a	17.19	6.60	20.14	9.51	14.55 / 5.40
+ ROVER (3 systems)	n/a	17.09	6.61	20.15	9.56	14.49 / 5.38

Table 3: Subtask 1.3 results (%). [†]the organizers’ baseline notebook; under the beam-5 decode that all trained rows use, the checkpoint loops and scores 103.2 / 117.8. The final system reduces blind-test WER by 0.60 points over the best single trained model.

on the blind set, +0.01 on the practice test split, so it should be read as noise-level rather than an established gain.

Table 3 gives the progression. Fine-tuning accounts for the bulk of the improvement; the two training-free steps supply the last 0.60 points. The submission placed second among the six submissions, 0.08 WER points behind the first-placed system. Our CER of 5.38% is the lowest among the leading submissions, below the first-placed system’s 5.55%, although the subtask is ranked on WER. Embedded French and English words are recognized *better* than the surrounding Tunisian Arabic (Appendix E), so the bottleneck is the dialect, not the code-switching.

7 Discussion and Future Work

Our main lesson is to diagnose the binding constraint before spending GPU-hours. Each diagnosis was cheap: a loss gap, a zero-shot comparison, a disagreement rate.

The Subtask 1.2 description encourages combining dialect identification with transcription. We could not score that on 1.2, which has no dialect labels, but Subtask 1.1 lets us measure what it is worth, since there the label is known and routing can be scored. Oracle routing to the specialists gains 1.9 country-average WER points over the pooled adapter, a 3.4% relative reduction. A linear probe on frozen encoder features, at 65% identification accuracy, recovers 0.8 points of that, 44% (Appendix I). The shortfall is structural. A specialist costs 1.4 points on the seven dialects it did not train on against a 1.9 point gain on its own, so misrouting costs about seven tenths of what correct routing gains, and identification accuracy sets the return. The identifier, not the specialists, is where further effort belongs. Subtask 1.2 has more than fifteen varieties and no labels, against eight known

classes on 1.1, so the recoverable share there is likely lower. NADI 2026 ran a separate spoken dialect identification task, which we did not enter. On the evidence here that was the wrong call: an identifier built for that track drops straight into this front-end, so the two are complementary rather than separate problems.

8 Conclusion

We described three NADI 2026 ASR systems from one recipe on consumer hardware, reaching 57.1% country-average WER on 1.1 (seventh of nine), 46.7% on 1.2 (third of four), 14.49% on 1.3 (second of six). Each was carried by a different intervention: specialists, base-model choice, cross-run averaging.

Limitations

We made our Subtask 1.3 design decisions on a single 731-utterance development split, which our bootstrap analysis shows cannot resolve differences below roughly 1.5 WER points. Some reported development gains are therefore partly selection noise, as the transfer analysis in Appendix D quantifies. We trained one seed per configuration throughout, so run-to-run variance is not separated from the effect of the changes we made. Repeating the Mauritania specialist at a second seed moves its development WER by 0.4 points, against a guarded specialist gain of 2.8 points (Appendix H). Repeating the regularized Subtask 1.3 recipe at a second seed moves its validation WER by 0.75 points, against the 1.5 points the split can resolve. Both bound the concern without removing it. The one comparison we re-ran across seeds, cross-run averaging, survived (Section 6.1). For Subtask 1.2 we trained the submitted model on the entire development split, so it cannot be scored offline at all and its blind-test result is the only measurement of it we have.

We chose the Subtask 1.1 per-country backbone on a 200-utterance-per-country subset whose margin was, for three of the four countries it decided, under 3 WER points. We did not tune decoding hyperparameters beyond the ablation reported for Subtask 1.2, and Subtask 1.1 was decoded greedily throughout, a cost we later measured at 1.1 to 1.3 country-average WER points (Appendix B). Finally, our Subtask 1.3 error analysis uses script as a proxy for language, which counts French and English words written in Arabic script as Arabic.

References

- Maximilian Bisani and Hermann Ney. 2004. [Bootstrap estimates for confidence intervals in ASR performance evaluation](#). In *2004 IEEE International Conference on Acoustics, Speech, and Signal Processing*, volume 1, pages I–409–I–412. IEEE.
- Fethi Bougares, Salima Mdhaffar, Haroun Elleuch, and Yannick Estève. 2025. [TEDxTN: A three-way speech translation corpus for code-switched Tunisian Arabic - English](#). In *Proceedings of The Third Arabic Natural Language Processing Conference*, pages 278–287, Suzhou, China. Association for Computational Linguistics.
- Ruizhe Cao, Sherif Abdulatif, and Bin Yang. 2022. [CM-GAN: Conformer-based metric GAN for speech enhancement](#). In *Interspeech 2022*, pages 936–940.
- Alex Choux, Marko Avila, Josep Crego, Fethi Bougares, and Antoine Laurent. 2025. [TuniFra: A Tunisian Arabic speech corpus with orthographic transcriptions and French translations](#). In *Proceedings of The Third Arabic Natural Language Processing Conference*, pages 64–68, Suzhou, China. Association for Computational Linguistics.
- Jonathan G. Fiscus. 1997. [A post-processing system to yield reduced word error rates: Recognizer output voting error reduction \(ROVER\)](#). In *1997 IEEE workshop on automatic speech recognition and understanding proceedings*, pages 347–354. IEEE.
- Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2022. [LoRA: Low-rank adaptation of large language models](#). In *International Conference on Learning Representations (ICLR)*.
- Pavel Izmailov, Dmitrii Podoprikin, Timur Garipov, Dmitry Vetrov, and Andrew Gordon Wilson. 2018. [Averaging weights leads to wider optima and better generalization](#). In *Conference on Uncertainty in Artificial Intelligence (UAI)*, pages 876–885.
- Guillaume Klein and Mahmoud Ashraf. 2023. [faster-whisper: Faster Whisper transcription with CTranslate2](#). <https://github.com/SYSTRAN/faster-whisper>.
- Guillaume Klein, François Hernandez, Vincent Nguyen, and Jean Senellart. 2020. [The OpenNMT neural machine translation toolkit: 2020 edition](#). In *Proceedings of the 14th Conference of the Association for Machine Translation in the Americas (Volume 1: Research Track)*, pages 102–109, Virtual. Association for Machine Translation in the Americas.
- Haohe Liu, Qiuqiang Kong, Qiao Tian, Yan Zhao, DeLiang Wang, Chuanzeng Huang, and Yuxuan Wang. 2021. [VoiceFixer: Toward general speech restoration with neural vocoder](#). *arXiv preprint arXiv:2109.13731*.

Sourab Mangrulkar, Sylvain Gugger, Lysandre Debut, Younes Belkada, Sayak Paul, Benjamin Bossan, and Marian Tietz. 2022. PEFT: State-of-the-art parameter-efficient fine-tuning methods. <https://github.com/huggingface/peft>.

Daniel S. Park, William Chan, Yu Zhang, Chung-Cheng Chiu, Barret Zoph, Ekin D. Cubuk, and Quoc V. Le. 2019. SpecAugment: A simple data augmentation method for automatic speech recognition. In *Inter-speech 2019*, pages 2613–2617.

Alec Radford, Jong Wook Kim, Tao Xu, Greg Brockman, Christine McLeavey, and Ilya Sutskever. 2023. Robust speech recognition via large-scale weak supervision. In *International conference on machine learning*, pages 28492–28518. PMLR.

Silero Team. 2024. Silero VAD: pre-trained enterprise-grade voice activity detector (VAD), number detector and language classifier. <https://github.com/snakers4/silero-vad>.

Peter Sullivan, Bashar Talafha, Ahmed Ashraf, Fethi Bougares, Haroun Elleuch, Chiyu Zhang, AbdelRahim Elmadany, Youssef Mohamed, Salima Mdhafar, Yannick Estève, Mohamed Elhoseiny, Hamzah Luqman, Nizar Habash, and Muhammad Abdul-Mageed. 2026. NADI-2026: The second multidialectal Arabic speech processing shared task. In *Proceedings of the Fourth Arabic Natural Language Processing Conference (ArabicNLP 2026)*, Budapest, Hungary. Association for Computational Linguistics.

Bashar Talafha, Hawau Olamide Toyin, Peter Sullivan, AbdelRahim A. Elmadany, Abdurrahman Juma, Amirbek Djanibekov, Chiyu Zhang, Hamad Alshehhi, Hanan Aldarmaki, Mustafa Jarrar, Nizar Habash, and Muhammad Abdul-Mageed. 2025. NADI 2025: The first multidialectal Arabic speech processing shared task. In *Proceedings of The Third Arabic Natural Language Processing Conference: Shared Tasks*, pages 720–733, Suzhou, China. Association for Computational Linguistics.

Nik Vaessen. 2025. jiwer: Evaluate your speech-to-text system with similarity measures. <https://github.com/jitsi/jiwer/releases/tag/v4.0.0>. Version 4.0.0.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Remi Louf, Morgan Funtowicz, Joe Davison, Sam Shleifer, Patrick von Platen, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, and 3 others. 2020. Transformers: State-of-the-art natural language processing. In *Proceedings of the 2020 conference on empirical methods in natural language processing: system demonstrations*, pages 38–45.

Mitchell Wortsman, Gabriel Ilharco, Samir Yitzhak Gadre, Rebecca Roelofs, Raphael Gontijo-Lopes, Ari S. Morcos, Hongseok Namkoong, Ali Farhadi, Yair Carmon, Simon Kornblith, and Ludwig Schmidt.

2022. Model soups: Averaging weights of multiple fine-tuned models improves accuracy without increasing inference time. In *International conference on machine learning*, pages 23965–23998. PMLR.

A Acoustic Character of Subtask 1.1

Effective bandwidth is about 2.1 kHz, and under 0.01% of energy lies above 4 kHz in every country, so 43% of Whisper’s 128 mel bins peak above that line and carry nothing. A per-utterance SNR proxy, the ratio of the 90th to the 10th percentile of frame energy, runs from 11.2 to 40.0 dB between its 5th and 95th percentiles, with 14.1% of the 10,808 development utterances below 15 dB. Splitting each country at its *own* median, the noisier half decodes 8.6 WER points worse in all eight countries, whereas per-country mean SNR ranges only 21.0 to 29.9 dB, so country means hide the effect entirely. Across countries, dialect dominates instead: per-country WER spans 39 points. It correlates -0.14 with bandwidth and -0.52 with mean SNR, but with $n = 8$ those have 95% intervals of $[-0.77, +0.63]$ and $[-0.90, +0.29]$. Eight countries cannot separate either from zero, and we report them only to show that neither acoustic axis explains the spread.

Model selection on the training-time evaluation subset is unsafe here: it understated WER by about 2.4 points and reversed the ranking of two configurations that full-development scoring showed to be equivalent.

B Post-Evaluation

Every number in this appendix is *development* WER and none is comparable with the blind-test figures of Table 1. The test references were never released, so no post-evaluation change can be scored on the metric the task was ranked by.

All eight specialists. By the submission deadline six countries had specialists, the four of Table 1 at three epochs and Yemen and Jordan at a cheaper single annealed epoch, neither of which the backbone comparison kept. After the evaluation closed we added UAE and Palestine on that same one-epoch recipe. Against the pooled turbo adapter, unguarded as in Table 1, Yemen improved by 3.9 WER points, UAE by 1.6, Palestine by 1.1 and Jordan by 0.4, following the headroom order of Table 1 except for Jordan. All eight dialects are therefore reachable in under 3 GPU-hours on the one-epoch recipe, against the 4.6 hours the four three-epoch

specialists cost on their own. These four gains are measured against the pooled turbo adapter, not against the large-v3 transcripts the submission actually used for these countries, so they do not translate into a submission-time improvement.

Beam search, and why the length guard is what makes it usable. Every Subtask 1.1 number above was decoded greedily. Re-decoding the full development set with beam 5 at batch 8 costs about 2.3 times the greedy wall clock (Egypt’s 1,600 utterances: 306 and 348 s greedy against 754 s twice, on an idle RTX 3060, model load included) and is worth 1.3 country-average WER points on the pooled adapter. It is not safe on its own: on the two dialects that over-generate it makes things *worse*, taking Mauritania from 73.3 to 77.1 and Algeria from 66.6 to 68.5 relative to their greedy specialists. Beam search without a length penalty prefers longer hypotheses, and the number of runaway outputs the guard has to cut on the specialists rises from 8 to 26 across the corpus, 1 to 15 on Mauritania alone. On the pooled adapter it rises from 14 to 35. Applying the guard removes the interaction and beam search then improves *all eight* countries, Mauritania included (Table 4).

Configuration	Country-average WER (%)
pooled adapter, greedy	57.59
+ length guard	56.58
+ beam 5	55.31
all eight specialists + guard	54.67
+ beam 5	53.55

Table 4: Post-evaluation development results for Subtask 1.1. The length guard applies from the second row down, unlike the per-country deltas of Table 1, which are unguarded. The only training beyond Table 1 is the four one-epoch specialists described above; the guard and the beam are free.

Per country, adding beam to the guarded specialists helps everywhere, from 0.3 points on Mauritania to 1.7 on Morocco, at $P = 100\%$ on five of the eight and 98% on Yemen. The two exceptions are the over-generating pair, Algeria at 89% and Mauritania at 77%. Two cheap choices that each look marginal in isolation, a post-hoc cap worth 1.0 points and a decoder default, are worth 2.3 together on the pooled adapter. Neither is a model change, and we found the interaction only by testing them jointly.

C Statistical Significance

Every comparison below is a paired bootstrap over utterances with 4,000 resamples, the same test applied to all three subtasks. $P(\text{better})$ is the fraction of resamples in which the second system has the lower WER, and intervals are percentiles of the resampled difference. ΔWER is in WER points, and is the mean of the resampled differences rather than the difference of the two point estimates, so it can differ from a subtraction of the WERs printed in the result tables by a few hundredths of a point.

Subtask 1.3. Table 5 gives the comparisons behind Section 6.

Comparison (validation)	ΔWER	$P(\text{better})$
q, v $\rightarrow$ wide+reg	-2.17	99%
wide $\rightarrow$ wide+reg	-0.40	78%
wide+reg $\rightarrow$ soup ($N=3$)	-0.81	97%
wide+reg $\rightarrow$ soup ($N=4$)	-2.26	100%
soup ($N=4$) $\rightarrow$ soup ($N=6$)	+0.61	21%
same-run pair $\rightarrow$ two-seed pair	-2.38	100%
cross-recipe pair $\rightarrow$ two-seed pair	-1.16	99%
soup ($N=4$) $\rightarrow$ two-seed pair	-0.28	87%

Table 5: Paired bootstrap over utterances, 4,000 resamples. ΔWER is in WER points. Above the rule, the ablations behind Section 6; below it, the post-evaluation seed control of Section 6.1.

With 731 development utterances, differences below roughly 1.5 WER points cannot be resolved. The regularization step we nonetheless kept is *not* significant on its own ($P = 78\%$, 95% interval $[-1.36, +0.68]$), whereas the cross-run soup is unambiguous ($P = 100\%$, $[-3.91, -1.09]$). We report this because system papers often present chains of sub-point improvements as if each were established. Across the three subtasks this paper reports thirty-six bootstrap comparisons with no correction for multiplicity. The marginal ones, Jordan at 87%, the four-ingredient soup against the two-seed pair at 87%, and turbo’s widening at 88%, should be read as weaker than their numbers suggest.

Subtask 1.1. Each specialist is tested on its own country’s development split, against the pooled adapter. Seven of the eight are unambiguous; Jordan, the country with the least headroom, is not (Table 6).

Subtask 1.2. On the 615 held-out utterances, switching base model is decisive (-3.76 , $P =$

Country	n	ΔWER	$P(\text{better})$
Mauritania	1,600	-6.53	100%
Yemen	1,183	-3.90	100%
Algeria	726	-3.12	100%
Morocco	1,600	-2.88	99%
Egypt	1,600	-1.90	99%
UAE	1,600	-1.60	100%
Palestine	900	-1.05	100%
Jordan	1,599	-0.44	87%

Table 6: Subtask 1.1 specialists, in WER points.

100%, $[-5.02, -2.52]$) and all of turbo’s fine-tuning is too (-4.52 , $P = 100\%$). Widening turbo’s target set is *not* (-1.02 , $P = 88\%$, $[-2.96, +0.53]$), which sharpens Section 5. The 1.02 points we contrast with 8 points on 1.1 are themselves inside the noise. The matched-capacity control keeps 2.65 of the base-model gain ($P = 100\%$, $[-3.85, -1.39]$) and the extra rank on large-v3 is worth 1.11 points ($P = 99\%$, $[-2.04, -0.21]$). The member trained on 1.2 data pooled with Subtask 1.1 audio has no significant accuracy edge over the wide large-v3 fine-tune (-0.33 , $P = 69\%$), which is consistent with its value lying in decorrelation rather than accuracy.

D How Much Transfers (Subtask 1.3)

Because we submitted three systems, we can measure how development gains transfer to the blind test set. The soup’s 2.26-point development gain became 0.54 points (24%), and ROVER’s 0.10-point gain became 0.06 points (60%). That second ratio should not be read as stable, since the same step is neutral on the practice test split. Two factors compress the transfer: the blind test set is easier than our development split (15.09% vs. 19.46% for the same model, utterances averaging 3.1 s against 5.6 s). The soup was also *selected* on the development set, so part of its apparent advantage is selection noise. We encourage participants to report this ratio whenever multiple submissions make it measurable.

E Error Analysis by Script (Subtask 1.3)

Script	Ref. words	Share	Error
Arabic	7,887	66.7%	20.2%
Latin (Fr/En)	3,946	33.3%	12.5%

Table 7: Word error (substitutions + deletions) by script of the reference word, best single model, practice test split.

Table 7 splits the practice-test reference words by script. The embedded French and English words, the phenomenon the subtask is named for, are recognized *better* than the surrounding Tunisian Arabic despite being a third of all tokens. The practical implication is that effort spent on French-specific lexicons or language-model biasing is likely wasted, and that Arabic-centric post-correction risks damaging tokens that are already correct.

Our primary and hamza-normalized scores differ by only 0.27 points, 14.49 against 14.22, indicating that training on the organizers’ normalized targets taught the model the reference orthographic convention almost exactly. Collapsing hamza in our hypotheses only, rather than on both sides as the secondary metric does, degrades WER from 17.19% to 26.98%, confirming there is no free gain in orthographic post-processing.

F The Metric Noise Floor (Subtask 1.2)

The references for this subtask are not orthographically self-consistent. After folding hamza, tamarbuta and alif-maqsurā variants, 844 word types are still written more than one way, covering 21.9% of all tokens, often in near-even proportions, so no system can learn a spelling that is correct both times. Folding these variants on both sides drops the zero-shot turbo WER on the full 3,152-utterance split from 62.2% to 57.2%, so roughly 5 WER points of the reported error are unwinnable. We recommend reporting a folded score alongside the raw one when judging whether a change on this data is real.

G What Did Not Work

Speech enhancement and bandwidth extension (1.1). On the 200 noisiest development utterances, with the same adapter and decode settings and only the audio differing, a CMGAN (Cao et al., 2022) enhancement front-end cost +5.0 WER points and VoiceFixer (Liu et al., 2021) bandwidth extension cost +18.0, both worse in seven of eight countries. VoiceFixer did extend the bandwidth, taking energy above 4 kHz from under 0.01% to 1.07%, but its log-magnitude correlation to the original below 2 kHz was only 0.63: it rewrote the band that carries the information.

Constrained decoding instead of a length guard (1.1). Setting transformers’ no_repeat_ngram_size to 4, which forbids

any repeated 4-gram within a hypothesis, removes runaway generation on the pooled adapter completely: no development hypothesis then exceeds six words per second, so the length guard has nothing left to cut. It is nonetheless the weaker fix, buying 0.5 country-average WER points against the guard’s 1.0, because forbidding repeated 4-grams also blocks legitimate repetition. The two do not stack, and we submitted the guard.

Noise augmentation (1.1). In-batch babble and band-limited Gaussian noise at 8 to 25 dB SNR, over a matched six-epoch run, made no measurable difference to country-average WER, under 0.2 points either way.

Cross-task transfer (1.2). Applying the Subtask 1.1 adapter directly to Subtask 1.2 scored worse than the untouched base model. The model trained on that data helped only as an ensemble member, where its disagreement is the point.

Orthographic post-processing (1.2). Remapping each word to the spelling preferred in the training portion cost up to 1.4 WER points, and the harm *scaled with model quality*. A fine-tuned model’s context-sensitive spelling beats a corpus-wide frequency rule.

More adapter capacity (1.3). Doubling the LoRA rank to 64 (115.3M trainable) stalled: held-out loss sat at 0.645 then 0.649 at steps 250 and 500, where the $r = 32$ run was at 0.547 then 0.511 and still falling. The train/held-out gap predicted that regularization rather than capacity was the productive direction.

Utterance-level combination (1.3). Selecting the most central of three hypotheses per utterance, over the three individually trained models, scored 18.22%, short of the 17.19% the soup alone already reached, so word-level voting was the only combination we kept.

Mid-run comparisons across schedules (1.3). A 5,000-step run trailed a 3,000-step run on held-out loss at every matched step from 1,500 to 3,000, and only fell below the shorter run’s best value at step 3,750, during the final anneal. Comparing runs of different total length at matched steps is misleading.

H What the Specialists Learn

Section 4 scores each specialist against the pooled adapter on its own country. That comparison leaves

two questions open: whether the gain is specialization or merely more training, and whether it survives the length guard. Both are settled here on the full development set, guarded except where stated, so the numbers differ from the unguarded deltas of Table 1.

Specialization, not extra training. A specialist continues the pooled adapter on one country. The matched control continues the same adapter for the same number of optimizer steps on the *pooled* data, so only the dialect composition of the gradient differs. Three epochs over 1,600 utterances at an effective batch of 16 is 300 steps; one epoch is 100.

Country	Steps	Spec.	Control	Spec. only
Algeria	300	-3.1	-0.4	-2.7
Egypt	300	-1.8	-0.0	-1.7
Mauritania	300	-2.8	+0.1	-2.9
Morocco	300	-2.2	+0.6	-2.8
Jordan	100	-0.6	+0.2	-0.9
Palestine	100	-1.1	+0.2	-1.3
UAE	100	-1.6	-0.0	-1.6
Yemen	100	-2.0	-0.4	-1.6
Mean		-1.9	+0.0	-1.9

Table 8: Each specialist against a pooled control given the same number of optimizer steps. Guarded full-development WER change from the pooled adapter, in WER points. *Spec. only* is *Spec.* minus *Control*.

Neither control moves the pooled adapter (Table 8). Three hundred more steps of pooled training change country-average WER by less than 0.1 points and a hundred steps make it 0.2 worse, against the specialists’ -1.9. No country gains more than 0.4 points from continued pooled training and Morocco loses 0.6, so the specialist gain is specialization in full, on every dialect.

Continuing beats starting over. Section 4 claims the specialist keeps the shared representation instead of competing with it. Training a fresh adapter on the same country for the same 300 steps, rather than continuing the pooled one, is worse than not specializing at all. Mauritania reaches 80.1 and Algeria 74.0, against 76.2 and 69.7 for the pooled adapter itself and 73.3 and 66.6 for the specialists. Sixteen hundred utterances are not enough to learn a dialect from the base model, and the pooled initialization is what supplies the rest.

The guard does part of the specialist’s work. Unguarded deltas in this paragraph come from the same full-development re-scoring as the rest of this appendix, which reproduces Table 1’s unguarded

Spec.	Egy	Jor	Alg	UAE	Mor	Mau	Yem	Pal
Egy	-1.8	+2.3	-0.3	+1.8	+2.2	+0.6	+0.7	+2.1
Jor	+2.0	-0.6	+1.4	+1.5	+1.5	+0.2	+1.8	+1.1
Alg	+1.4	+1.9	-3.1	+1.0	+4.0	+0.6	+1.3	+1.8
UAE	+0.8	+1.4	-1.1	-1.6	+1.2	+0.3	-0.4	+1.2
Mor	+1.5	+2.9	+1.3	+1.9	-2.2	+1.2	+1.7	+2.4
Mau	+2.7	+3.7	+0.6	+2.5	+3.4	-2.8	+2.5	+2.0
Yem	+1.1	+1.6	+0.9	+1.3	+1.2	+0.7	-2.0	+1.4
Pal	+1.1	-0.3	+0.3	+0.3	+1.5	+0.0	+0.2	-1.1

Table 9: Change in guarded development WER, in WER points, from the pooled adapter when each specialist (row) decodes each country (column). Bold is the specialist’s own dialect.

deltas to within 0.2 points. Under the guard, six of the eight specialist gains move by at most 0.6 points, but Mauritania falls from -6.3 to -2.8 and Yemen from -3.9 to -2.0 . On the two dialects that over-generate, about half of what the specialist appeared to buy is runaway generation that the free post-hoc cap of Section 4 already removes. The two interventions are partly redundant, and exactly on the dialects where specialization looked strongest.

Specialists interfere. Table 9 decodes every specialist on every country.

Every specialist is the best of all the adapters we decoded on its own dialect, yet costs a mean of $+1.4$ points on the seven others against a mean own-dialect gain of -1.9 . A wrong route therefore costs about seven tenths of what a right one gains, which is what limits the front-end of Appendix I.

I Routing Without the Dialect Label

Subtask 1.1 gives the country at test time and Subtask 1.2 gives nothing, so we use 1.1 to measure what a front-end would recover, precisely because there the routing can be scored.

A linear probe on frozen features. We mean-pool the frozen whisper-large-v3-turbo encoder over each utterance’s valid frames and fit multinomial logistic regression on the 12,800 training utterances. There is no fine-tuning and no decoding. It identifies the country of 65.3% of the 10,808 development utterances against a 12.5% chance rate, and its confusions are regional rather than arbitrary: the largest are Algeria with Morocco, then Egypt with Jordan and Jordan with UAE. Utterance ids share a prefix across splits for 20.8% of the development set, but accuracy on that overlapping fifth is *lower* (60.1%) than on the rest (66.7%), so the figure is not inflated by having heard the source.

What routing recovers. Each utterance is transcribed by the specialist the probe predicts *for that utterance*. Composing a confusion matrix with Table 9 instead would flatter the result, because a router’s mistakes fall on the utterances a model is already likely to get wrong; that approximation gives 51% where the exact figure is 44%.

System	Country-avg WER	$P(\text{better})$
pooled adapter	56.56	—
soup of all eight	56.31	99%
routed by the probe	55.73	100%
oracle routing	54.66	100%

Table 10: Subtask 1.1 development, guarded, in %. $P(\text{better})$ is against the pooled adapter, paired bootstrap over utterances with 4,000 resamples. Scored by the per-utterance routing pass, which reproduces Appendix B’s pooled figure to within 0.02 points.

Gold routing is worth 1.9 country-average WER points, a 3.4% relative reduction. That is the most a router can recover, and we call it the prize below. The probe recovers 0.8 points of it, 44% (Table 10), at $P = 100\%$. The gap to the oracle is itself significant ($P = 100\%$, 95% interval $[-1.2, -0.9]$), so the identifier and not the specialists is the binding constraint. Routing *hurts* on Jordan, 48.7 to 49.5, the country with both the lowest router accuracy, 57.5%, and the smallest specialist gain.

Under a stronger decoder. Repeating the whole matrix at beam 5 reproduces the progression of Appendix B to within 0.04 points and leaves the conclusion intact. The oracle prize narrows a little, from 1.9 to 1.8 points, and probe routing recovers 41% of it rather than 44%, still at $P = 100\%$. Beam search and specialization are mildly redundant, as the length guard is, but routing survives both.

The identifier is the improvable part. Tuning the regularization of the same linear model, se-

lected on a held-out slice of the *training* split so the development set stays clean, raises accuracy from 65.3% to 69.5% and the recovered fraction from 44% to 47%. Small multilayer perceptrons on the same features do no better, so the ceiling is the representation rather than the classifier. That four points of accuracy are available this cheaply, while the gap to the oracle stays significant, is the clearest sign that the identifier and not the specialists is where further effort belongs. NADI 2026 ran a spoken dialect identification task alongside the ASR subtasks, and we entered only the ASR ones. On the evidence above that was a missed opportunity. An identifier built for that track drops directly into the front-end measured here, and the conversion is already visible. Tuning the same linear model bought four points of identification accuracy and three percentage points of the oracle prize.

Merging is not a substitute. If the specialists could be combined into one model the identifier would be unnecessary. Souping all eight into a single rank-256 adapter, by the same exact-mean construction as Section 6.1, reaches only 56.31, 13% of the prize and significantly worse than probe routing ($P = 100\%$). Averaging cancels most of the specialization, because each specialist's own-dialect gain is offset by the seven others' interference on that dialect. The router is a binding constraint, not an implementation detail.