DON'T STOP LONG-CONTEXT CONTINUAL PRE-TRAINING TOO EARLY: AN EMPIRICAL SCALING LAW

Ziqing Qiao[1]*, **Xiaoyue Xu**[2]*, **Sikui Zhang**[2], **Yinuo Xu**[1] **Bingxiang He**[1], **Chaojun Xiao**[1]†, **Xu Han**[1]†
[1]Department of Computer Science and Technology, Tsinghua University, Beijing, China
[2]OpenBMB
qzq24@mails.tsinghua.edu.cn, {xcj,han-xu}@tsinghua.edu.cn

arXiv:2610.29352v1 [cs.CL] 21 Oct 2026

ABSTRACT

Long-context continual pre-training (LCCP) is widely used to improve long-context capability, but how its benefits scale with the number of tokens used for LCCP remains unclear. We investigate this question through modeling, monitoring, and validating the benefits of scaling LCCP. First, we establish an empirical additive power law relating long-context performance to model size and the respective token budgets of short-context pre-training and LCCP. Experiments across five model scales and more than one hundred short- and long-context budget configurations show that the fitted law reproduces the observed trends and extrapolates well to held-out model scales. Second, we introduce CONSTANT-LAST4, a training and observation protocol that averages the four most recent consecutive checkpoints from a constant-learning-rate run to enable stable monitoring along a single extensible training trajectory. Under this protocol, the same scaling-law form fits well and accurately predicts the LCCP performance trajectory of a 1.22B-parameter model trained on approximately 100B LCCP tokens. Finally, downstream evaluations along this trajectory show continued improvements in long-context performance, with no clear sign of saturation within the evaluated range. These gains persist after both 128K context extension and supervised fine-tuning, with benefits extending to long-context understanding and agentic tasks. Together, these results argue for continuing to scale LCCP rather than stopping early: its gains are stably observable along an extensible trajectory, quantitatively predictable, and transferable to downstream tasks. [1]

1 INTRODUCTION

Long-context capability is fundamental to language models, supporting complex long-horizon tasks and agentic workflows (Kimi Team et al., 2026; Zeng et al., 2026; Liu et al., 2025). However, training on long sequences from the beginning of pre-training incurs substantial computational costs (Grattafiori et al., 2024). Long-context continual pre-training (LCCP) is therefore widely adopted, often as a brief stage following short-context pre-training. It uses longer sequences and a long-context-oriented data mixture to extend the context window and improve long-context performance (Xiong et al., 2024; Gao et al., 2025). A range of studies and models adopt relatively limited additional training to extend context windows (Liu et al., 2024; Fu et al., 2024; Hu et al., 2025).

As applications increasingly demand long-context understanding and sustained agentic interaction, some training recipes devote substantial token budgets to long-context pre-training (Grattafiori et al., 2024; Zeng et al., 2026). Yet how long-context performance scales with the LCCP training budget remains insufficiently characterized. We therefore ask: *Does continued LCCP yield sustained improvements in long-context capability, and can these gains be quantitatively predicted?*

In this work, we address this question by **modeling, monitoring, and validating** the benefits of scaling up LCCP. As illustrated in Figure 1, we conduct a systematic empirical study of how long-context performance evolves with increasing LCCP budgets, spanning short-context pre-training,

*Equal contribution.
†Corresponding authors.
[1]The code is released at https://github.com/thunlp/dont-stop-lccp.



Figure 1: Overview of our framework for modeling, monitoring, and validating long-context performance during LCCP scaling. We develop an empirical scaling law for long-context performance, introduce CONSTANT-LAST4 as an extensible training and observation protocol, and evaluate downstream performance gains after context extension and supervised fine-tuning.

32K LCCP, subsequent 128K context extension, and supervised fine-tuning(SFT). We first establish an empirical scaling law for **modeling** long-context performance during LCCP, jointly accounting for model size, short-context pre-training tokens, and long-context training tokens. We then introduce a stable observation protocol for extensible LCCP, enabling performance **monitoring** along a constant-learning-rate trajectory and, together with the scaling law, prediction from early checkpoints. Finally, we conduct downstream evaluations on long-context and agentic tasks, thereby **validating** whether gains from additional LCCP translate into downstream improvements and persist through subsequent training stages.

Modeling LCCP Scaling. Unlike pre-training from scratch, LCCP starts from a model that has already acquired basic capabilities, meaning that its long-context performance may depend on the preceding short-context pre-training stage (Wu et al., 2025b). We therefore jointly model the non-embedding parameter count N, short-context pre-training tokens D_s, and long-context training tokens D_l. Using LongPPL (Fang et al., 2025) as a proxy for long-context performance, we evaluate 109 training configurations across five model scales under a linear-decay learning-rate schedule. We find that an additive power law with an offset accurately captures the observed performance trends and extrapolates to held-out model scales under the evaluated budget settings, providing a quantitative basis for predicting long-context performance under different training budgets.

Monitoring LCCP Scaling. To study continued LCCP scaling, we need a training and observation protocol that enables consistent performance monitoring along a single extensible trajectory. Although linear-decay schedules provide stable endpoint performance, they require a predefined training budget and are therefore inconvenient for open-ended training. In contrast, a constant learning rate avoids this endpoint dependence, allowing cumulative long-context training tokens D_l to serve as a common coordinate for monitoring training progress.

Raw constant-learning-rate checkpoints, however, exhibit substantial performance fluctuations and underperform budget-matched linear-decay models. Motivated by prior work on training dynamics and checkpoint merging (Wen et al., 2024; Tian et al., 2026), we introduce the CONSTANT-LAST4 protocol, which averages the four most recent checkpoints for evaluation. Across evaluated configurations, this protocol provides more stable observations and closely matches linear-decay performance. Under this protocol, the same scaling-law form fits well and extrapolates from smaller models to the approximately 100B-token LCCP trajectory of a 1.22B model. Moreover, when model size and the short-context training budget are fixed, the law simplifies to a power law in D_l that predicts later LongPPL from a fit to early LCCP checkpoints. Together, CONSTANT-LAST4 and the empirical scaling law support stable monitoring and performance prediction when scaling up LCCP.

Validating Capability Gains. The practical value of the scaling law depends on whether the performance improvements it captures translate into gains in downstream long-context and agentic tasks. We therefore validate the scaling trend along the 32K LCCP trajectory using RULER (Hsieh et al., 2024), where aggregate performance improves as the long-context training budget increases, with no clear sign of saturation within the evaluated range. Since LCCP is typically not the final training stage, we further evaluate checkpoints obtained at different LCCP budgets after 128K context extension and SFT for long-context and agentic tasks, using identical training procedures within each setting. The benefits of LCCP scaling remain observable after both subsequent training stages and across multiple long-context and agentic benchmarks. Together, these findings provide a quantitative basis for assessing the downstream benefits of continued LCCP.

2 Related Work

2.1 Scaling Laws for Large Language Models

Scaling laws relate pre-training loss to model size and training data and characterize their trade-offs under fixed compute budgets (Kaplan et al., 2020; Hoffmann et al., 2022). Subsequent work has extended scaling-law analysis to continual pre-training, examining the effects of model size, additional training data, and data-mixture ratios (Que et al., 2024; Gu et al., 2024), and characterizing learning dynamics (Wang et al., 2025a), as well as to downstream performance prediction (Ivgi et al., 2022; Hu et al., 2024a; Chen et al., 2024). However, scaling-law analyses of long-context performance remain comparatively limited. Prior work has studied long-context scaling in hybrid architectures under single-stage pre-training (Qiao et al., 2026). We instead study LCCP, jointly modeling long-context performance using model size and separate short- and long-context training budgets.

2.2 Long-Context Continual Pre-Training

LCCP typically starts from a short-context pre-trained model and extends its context window through positional adjustments and continued training on longer sequences (Xiong et al., 2024; Chen et al., 2023), using a long-context-oriented data mixture to improve performance (Gao et al., 2025; Fu et al., 2024). Some methods emphasize token-efficient context extension (Wu et al., 2025a; Peng et al., 2024), whereas some leading large language models use long-context training budgets on the order of a trillion tokens (Grattafiori et al., 2024; Liu et al., 2025). These differing budget choices highlight the importance of understanding the benefits of continued LCCP and assessing whether training is sufficient.

Assessing the benefits of continued LCCP requires appropriate evaluation metrics. LongPPL (Fang et al., 2025) uses a reference model to identify tokens sensitive to distant context, providing a probabilistic measure of long-context performance. Recent work analyzes LCCP learning dynamics at the behavioral, probabilistic, and mechanistic levels and introduces a retrieval-head-based metric (Liang et al., 2026). The findings suggest that behavioral scores can plateau while probabilistic and mechanistic metrics may continue to capture changes during training. Complementing these analyses of learning dynamics, we focus on stable observation and quantitative prediction during continued LCCP. Drawing on studies of learning-rate dynamics in pre-training (Wen et al., 2024; Hägele et al., 2024) and checkpoint averaging (Tian et al., 2026; Sanyal et al., 2023), we develop Constant-Last4, an extensible protocol for LCCP training and LongPPL evaluation, and examine whether capability gains from additional LCCP persist after subsequent training stages.

3 An Empirical Scaling Law for LCCP

To quantify how long-context performance scales during LCCP, we develop an empirical scaling law that jointly accounts for model size and the token budgets of the two training stages. We evaluate both its fit to observed configurations and its predictive accuracy beyond the fitting range, across model scales and training budgets.

3.1 Experimental Setup and Evaluation Metric

Long-context performance after LCCP may depend not only on the amount of long-context training, but also on the model's short-context pre-training history (Wu et al., 2025b). This motivates treating the two stages separately rather than representing them by a single total token budget. Specifically, we use three predictors: the non-embedding parameter count N, the number of short-context pre-training tokens D_s, and the number of long-context training tokens D_l.

To study LCCP scaling, we train models at five scales, S1–S5, with N ranging from 31M to 821M, as shown in Table 1. As for the training budget, for S1–S4, we use

$$D_s/N \in \{90, 180, 270, 360, 450\}$$
$$D_l/N \in \{10, 20, 30, 40, 50\}$$

yielding 100 configurations. For larger-scale extrapolation, we construct five S5 configurations along the diagonal $D_s = 9D_l$, with $(D_s/N, D_l/N) \in \{(90, 10), (180, 20), (270, 30), (360, 40), (450, 50)\}$, and four off-diagonal configurations, $(D_s/N, D_l/N) \in \{(90, 50), (180, 40), (360, 20), (450, 10)\}$, to provide broad coverage of the configuration grid.

Table 1: Model configurations.

Scale	Layers	Dimensions		Heads		Parameters	
		Hidden	FFN	Attn.	KV	Non-emb.	Total
S1	12	512	1,280	8	2	31M	165M
S2	15	640	1,600	10	2	61M	228M
S3	18	768	1,920	12	2	104M	305M
S4	24	1,024	2,560	16	2	245M	513M
S5	36	1,536	3,840	24	2	821M	1.22B

For the training setup, the short-context stage uses a sequence length of 4K and the WSD learning-rate schedule (Hu et al., 2024b). The ratio between the number of tokens in the warmup+stable and decay phases is 8:1, and D_s includes tokens from all WSD phases. The LCCP stage uses a sequence length of 32K and a long-context data mixture. Following practices reported for open-source models (Olmo Team et al., 2025; Bakouch et al., 2025), we use a linear-decay learning-rate schedule during LCCP to obtain stable model performance. The learning rate starts from the value at the end of the short-context stage and decays to one tenth of that value. More details of training are provided in Appendix A.3.

For the fitting target, we use LongPPL (Fang et al., 2025) as a proxy for long-context performance. Following the original protocol, we use Llama-3.1-8B (Grattafiori et al., 2024) as the reference model and set the local chunk length to 4K tokens. For each token x_t, let $\ell_{\text{ref}}^{\text{full}}(x_t)$ and $\ell_{\text{ref}}^{\text{chunk}}(x_t)$ denote the negative log-likelihood under the full context and the local chunk, respectively. We select tokens that are well predicted under the full context and depend substantially on distant context:

$$\Delta_t = \ell_{\text{ref}}^{\text{chunk}}(x_t) - \ell_{\text{ref}}^{\text{full}}(x_t), \qquad \mathcal{K}_{\text{long}} = \left\{ t : \ell_{\text{ref}}^{\text{full}}(x_t) < 2,\ \Delta_t > 2 \right\}.$$

For an evaluated model M, LongPPL is computed from its full-context loss only on $\mathcal{K}_{\text{long}}$:

$$\text{LongPPL}(M) = \exp\left(\frac{1}{|\mathcal{K}_{\text{long}}|} \sum_{t \in \mathcal{K}_{\text{long}}} \ell_M^{\text{full}}(x_t) \right).$$

We use the same $\mathcal{K}_{\text{long}}$ set for all models. The evaluation sequences contain 32K tokens and are constructed from GovReport (Huang et al., 2021). We compute LongPPL for all 109 training configurations and use $\log(\text{LongPPL})$ as the target for subsequent scaling-law fitting, consistent with previous work (Qiao et al., 2026). Further details of the evaluation data are provided in Appendix A.1.

3.2 An Additive Two-Stage Scaling Law

Observation. To guide the choice of functional form, we examine how $\log(\text{LongPPL})$ changes with D_s or D_l while holding the other two predictors fixed. As shown in Figure 2, the observed trends are consistent with power-law decay with an offset across the tested model scales and budgets. Guided by these trends and the additive structure of the Chinchilla scaling law (Hoffmann et al., 2022), we consider the following formulation

$$\log(\text{LongPPL}) = \frac{A}{N^{\alpha}} + \frac{B_s}{D_s^{\beta_s}} + \frac{B_l}{D_l^{\beta_l}} + C, \tag{1}$$

where A, B_s, and B_l are scale coefficients, α, β_s, and β_l are scaling exponents, and C is an offset. All seven parameters are fitted empirically.



Figure 2: $\log(\text{LongPPL})$ versus D_s and D_l, varying one budget while holding model size and the other budget fixed. Both trends are consistent with power-law decay with an offset.



Figure 3: Scale-extrapolation parity plots for fits from S1–S3 to S4 (left) and S1–S4 to S5 (right), with the fitted laws shown above each panel. Dashed lines denote ideal predictions ($y = x$). R^2 and MAPE are computed in $\log(\text{LongPPL})$ space on held-out configurations.

Fitting and scale extrapolation. We evaluate the fitting and scale-extrapolation performance of Eq. 1 using two held-out-scale experiments. First, we fit the scaling law using the 75 configurations from S1–S3 and evaluate it on the 25 configurations from S4. Second, we fit it using the 100 configurations from S1–S4 and evaluate it on the 9 configurations from S5. In each experiment, we exclude configurations at the target model scale from fitting. As shown in Figure 3, Eq. 1 fits the observed data well and extrapolates to both held-out model scales, achieving $R^2 > 0.95$ and mean absolute percentage error (MAPE) below 2% in $\log(\text{LongPPL})$ space. Precise fitted parameter values are reported in Appendix A.5.

Notably, the fitted offset satisfies $C < 0$. Since $\log(\text{LongPPL})$ is a mean negative log-likelihood and is nonnegative, we interpret Eq. 1 as a finite-range empirical law rather than a valid asymptotic law. Nevertheless, our extrapolation tests extend substantially beyond the fitting range: S5 has more than three times the parameter count of S4, the largest model used for fitting, with token budgets scaling by the same factor at matched D_s/N and D_l/N.

We also compare several alternative formulations, including variants with no offset or a nonnegative offset, formulations using effective data or the combined budget $D = D_s + D_l$, and formulations with interaction terms among the three predictors. Among these formulations, Eq. 1 attains the best overall extrapolation performance; details are provided in Appendix A.2. These comparisons provide additional empirical support for Eq. 1 as a predictive model of long-context performance during LCCP within the evaluated range.

4 An Extensible Training and Observation Protocol

Under the linear-decay setup, we successfully fit an additive power-law model for $\log(\text{LongPPL})$, which suggests that increasing the LCCP training budget can yield continued and predictable benefits within the studied range. Although the linear-decay schedule provides stable model performance, the learning-rate schedule is tied to a prespecified training endpoint, making it less convenient for



(a) Observation rules

(b) Training and observation protocols

Figure 4: Comparison of training and observation protocols using ShortPPL and LongPPL. (a) Different observation rules on S4 with $D_s = 450N$ and $D_l = 50N$. (b) CONSTANT-RAW, CONSTANT-LAST4, and matched LINEAR-DECAY across 25 S4 configurations. CONSTANT-RAW yields higher and noisier values for both metrics, whereas CONSTANT-LAST4 closely matches LINEAR-DECAY. CCC denotes Lin's concordance correlation coefficient (Lin, 1989).

open-ended LCCP scaling. In this section, we therefore explore a training and observation protocol that supports both extensible training and stable performance evaluation, facilitating the application of the scaling law to LCCP scaling in practice.

4.1 CONSTANT-LAST4: CONSTANT LEARNING RATE WITH MODEL MERGING

We use a constant learning rate to support open-ended LCCP without prespecifying a final training budget (Liu et al., 2024; Blakeman et al., 2026). The cumulative number of long-context training tokens D_l then serves as a natural coordinate along a single training trajectory, which brings two practical benefits: additional long-context data can be incorporated by resuming from the latest checkpoint, and model performance can be evaluated at any training budget without running a separate experiment for each budget. To mitigate the elevated and fluctuating evaluation loss that can arise under constant-learning-rate training (Wen et al., 2024), we consider checkpoint merging without additional training (Tian et al., 2026). We treat merging as an *observation* mechanism: evaluation uses merged checkpoints, while the training trajectory remains unchanged.

Observation rules and metrics. We take the raw constant-learning-rate checkpoint as the simplest observation rule and compare it with a family of checkpoint-merging methods. As the reference for all rules, we use the LINEAR-DECAY checkpoint trained with the same (N, D_s, D_l).

For judging observation rules, we retain LongPPL as the long-context metric and introduce ShortPPL as a complementary diagnostic. Reusing the same reference model and token-level statistics as in LongPPL, we select tokens for which the local chunk yields a lower loss than the full context and compute perplexity over these positions:

$$\mathcal{K}_{\text{short}} = \left\{ t : \Delta_t < 0,\ \ell^{\text{full}}_{\text{ref}}(x_t) < 2 \right\}, \qquad \text{ShortPPL}(M) = \exp\left(\frac{1}{|\mathcal{K}_{\text{short}}|} \sum_{t \in \mathcal{K}_{\text{short}}} \ell^{\text{full}}_{M}(x_t) \right).$$

Since the selected tokens do not benefit from distant context, ShortPPL primarily reflects general language-modeling performance, and thus serves as a complementary metric.

Comparison setup. Starting from the S4 short-context checkpoint with $D_s = 450N$, we continue constant-learning-rate training to $D_l = 50N$ and denote the resulting raw model by CONSTANT-RAW. Along the trajectory, we save checkpoints at intervals of $2N$ in D_l, yielding a pool of 25 checkpoints. Within this pool we evaluate several representative merging methods: LASTM, which assigns equal weight to the final M consecutive checkpoints (Sanyal et al., 2023), the recency-



Figure 5: Scaling-law fitting and extrapolation under CONSTANT-LAST4: held-out S4 predictions from an S1–S3 fit (left and middle) and held-out S5 trajectory predictions from an S1–S4 fit (right). In the middle panel, dot colors indicate the absolute percentage error between predicted and measured $\log(\text{LongPPL})$. Precise fitted parameter values are reported in Appendix A.5.

weighted profiles 1-SQRT (Tian et al., 2026) and EMA, and DARE (Yu et al., 2024), a task-vector method. Additional implementation details are provided in Appendix B.

Observation rule selection. As shown in Figure 4a, CONSTANT-RAW has substantially higher LongPPL and ShortPPL than the budget-matched LINEAR-DECAY checkpoint, whereas checkpoint merging recovers most of this gap on both metrics. Considering performance, simplicity, and storage requirements, we select LAST4 as the default observation rule: it averages only the four most recent consecutive checkpoints while preserving the latest raw checkpoint for continued training.

To further assess the stability of LAST4 merging, we compare CONSTANT-RAW and CONSTANT-LAST4 with LINEAR-DECAY across all S4 configurations in Figure 4b. Across training budgets, CONSTANT-LAST4 closely matches the corresponding LINEAR-DECAY checkpoint on both ShortPPL and LongPPL. In summary, CONSTANT-LAST4 combines the extensibility of constant-learning-rate training with the stable performance of a decayed endpoint in our setting, providing a practical training and observation protocol for LCCP scaling.

4.2 SCALING-LAW VALIDATION UNDER CONSTANT-LAST4

For the new CONSTANT-LAST4 protocol, we need to test whether the empirical scaling law Eq. 1 remains valid under it. We adopt a $(D_s/N, D_l/N)$ budget grid for S1–S4 similar to the one in Section 3. The realized token counts and details are provided in Appendix A.3. Because a single constant-learning-rate trajectory provides checkpoints at multiple D_l values, one run covers several long-context training budgets and reduces the experimental cost relative to LINEAR-DECAY. We run each LCCP trajectory independently three times from the same short-context checkpoint and use the mean LongPPL across runs for S1–S4 models.

We follow the scale-extrapolation setup used in Section 3. First, we fit the scaling law on S1–S3 and evaluate it on S4. We then fit it on S1–S4 and extrapolate to the S5 trajectory. Whereas the LINEAR-DECAY experiments used nine S5 configurations, here we extend pointwise scale extrapolation to prediction along an entire training trajectory. Specifically, we fix the short-context budget at $D_s = 450N$ and continue constant-learning-rate training to $D_l = 120N$ (approximately 100B tokens). This setting provides dense observations of $\log(\text{LongPPL})$ as a function of D_l at a fixed model scale and short-context budget. For S5, we save checkpoints at $1N$ intervals and apply LAST4 to the four most recent checkpoints every $5N$, yielding 24 merged evaluation points. Appendix B.1 shows that the results are insensitive to checkpoint spacing within the evaluated range.

As shown in Figure 5, Eq. 1 fits the CONSTANT-LAST4 configurations well and extrapolates accurately to an unseen model scale. Notably, the S5 trajectory reaches approximately 100B long-context training tokens, more than eight times the largest absolute long-context budget in the fitting set, yet the scaling law accurately predicts $\log(\text{LongPPL})$ across the entire trajectory. Thus, the scaling law works under both LINEAR-DECAY and CONSTANT-LAST4 within the tested range.

4.3 A SIMPLIFIED LAW FOR FIXED-MODEL LCCP

In practical LCCP, one often starts from a fixed model that has undergone substantial short-context pre-training and continues training it with additional long-context data. In this setting, the main question is how performance evolves with D_l and whether early observations can predict the benefits of further training. When N and D_s are fixed, their contributions in Eq. 1 can be absorbed into a single offset, yielding

$$\log(\text{LongPPL}) = \frac{B_l}{D_l^{\beta_l}} + C', \tag{2}$$

where $C' = A/N^{\alpha} + B_s/D_s^{\beta_s} + C$.We re-estimate B_l, β_l and C' jointly from the given trajectory rather than taking them from the joint fit. This lower-dimensional form is practical for fixed-model LCCP because it can be fitted using a small number of early checkpoints from a single training trajectory, avoiding the costly multi-scale, multi-budget training grid required for fitting the joint law.



Figure 6: Prefix fitting of $\log(\text{LongPPL})$ along the S5 CONSTANT-LAST4 run.

We evaluate the S5 CONSTANT-LAST4 trajectory with D_s fixed at $450N$ and D_l extending to $120N$, evaluating one merged checkpoint every $5N$. We fit Eq. 2 using Huber loss on prefixes up to $20N$, $40N$, and $60N$, respectively, and evaluate each fit on all subsequent held-out checkpoints through $120N$. As shown in Figure 6, even a short prefix provides a reasonable estimate of the remaining trajectory, suggesting that early observations can help estimate later LongPPL for a fixed-model LCCP trajectory. We further fit the same power-law form to ShortPPL and compare it with that of LongPPL to assess LongPPL's usefulness as a long-context proxy; details are provided in Appendix D.1.

5 DOWNSTREAM VALIDATION OF LCCP SCALING

For both LINEAR-DECAY and CONSTANT-LAST4, LongPPL decreases predictably as the LCCP budget increases. To test whether this improvement translates into long-context capability, we evaluate from three complementary perspectives: capability gains during 32K LCCP, their transfer to 128K context extension, and their preservation after SFT. We conduct these evaluations using checkpoints sampled from the S5 32K CONSTANT-LAST4 trajectory introduced in Section 4.2. Additional training and evaluation details for this section are provided in Appendix C.

5.1 CAPABILITY GAINS DURING 32K LCCP

To test whether the decrease in LongPPL translates into genuine long-context capability, we evaluate the LCCP trajectory of the S5 model using RULER (Hsieh et al., 2024). We construct 500 samples for each subtask and evaluate both CONSTANT-RAW and CONSTANT-LAST4 checkpoints every $5N$ along the trajectory.



Figure 7: RULER-32K scores along the 32K LCCP trajectory of the S5 model.

As shown in Figure 7, the RULER scores of CONSTANT-LAST4 exhibit an overall upward trend throughout the observed LCCP trajectory, with no clear sign of saturation. CONSTANT-RAW follows a similar trend but shows larger fluctuations and generally lower scores at comparable training budgets. Detailed per-subtask results in Appendix C.1 show that the aggregate gains are driven primarily by intermediate-difficulty retrieval subtasks. These results link continued LCCP scaling to improved long-context benchmark performance within the evaluated range, with CONSTANT-LAST4 providing a more stable capability signal under a constant learning rate.



Figure 8: Downstream performance after 128K extension and SFT at varying 32K LCCP budgets. Shaded regions in (b) show the range across 3 training seeds. Across these subsequent training stages, larger 32K LCCP budgets generally lead to improved downstream performance.

5.2 Capability Gains after 128K Context Extension

Multi-stage LCCP is common in practical training pipelines, where a model is first trained extensively at a moderate context length and then extended to a longer context with a smaller additional budget (Grattafiori et al., 2024; The Microsoft AI Team, 2026). To test whether gains from 32K LCCP transfer to a longer context, we select checkpoints at $D_l/N \in \{10, 20, 40, 60, 80, 100, 120\}$ from the previous S5 32K LCCP trajectory and apply the same 128K context-extension procedure to both Constant-Raw and Constant-Last4 models. Specifically, we use ABF (Xiong et al., 2024) to increase the RoPE base frequency from 500,000 to 5,000,000, use a 128K-stage data mixture with a higher proportion of long-context sequences than the 32K LCCP mixture, and continue training for 2.10B tokens at a sequence length of 128K. The learning rate starts from the constant rate used during 32K LCCP and follows a linear decay to one hundredth of its initial value.

For evaluation, we construct 100 128K-length samples per RULER subtask. As shown in Figure 8(a), the performance of both Constant-Raw and Constant-Last4 models generally improves with increasing 32K budget, especially on NIAH-related tasks. These results suggest that the benefits of a larger 32K LCCP budget carry over to the longer-context regime after context extension.

5.3 Capability Gains after Supervised Fine-Tuning

The goal of scaling LCCP is to improve downstream model performance. Since models typically undergo SFT to adapt their pretrained capabilities to practical use, we evaluate whether the benefits of larger LCCP budgets persist after SFT. We consider two settings, long-context SFT and agentic SFT, using the same checkpoints of the 32K LCCP trajectory of the S5 model as in Section 5.2. Within each setting, we apply the same SFT procedure to checkpoints obtained at different LCCP budgets. More training details are provided in Appendices A.3– A.4; evaluation protocols and supplementary results are provided in Appendix C.3.

Long-context SFT. We apply the same 2.10B-token SFT recipe to each checkpoint, using the non-thinking response format. We evaluate the SFT models on four long-context benchmarks: LongBench (Bai et al., 2024), GraphWalks (OpenAI, 2025), LongReason (Ling et al., 2025), and BABILong (Kuratov et al., 2024), and report their equal-weight average. As shown in Figure 8(b), downstream performance generally improves with the LCCP training budget under the same SFT procedure. Each point reports the mean over three independent SFT runs with different data seeds, with the shaded region indicating the minimum-to-maximum range across the three runs.

Agentic SFT. We further examine whether the benefits extend to agentic scenarios. We consider two task categories: search agents, evaluated on GAIA (Mialon et al., 2024) and BFCL-WebSearch (Patil et al., 2025), and tool-use agents, evaluated on τ^2-telecom (Barres et al., 2025). Each checkpoint undergoes the same 4.20B-token agentic SFT recipe with thinking mode enabled during training. Each benchmark score is averaged over three evaluation runs, and the two search benchmark scores

are further averaged with equal weights. As shown in Figure 8(c), performance in both categories generally improves with larger LCCP budgets, despite fluctuations across checkpoints.

Taken together, these evaluations show that, for the 1B-scale S5 model, the benefits of scaling 32K LCCP to approximately 100B tokens remain evident after 128K context extension and after SFT for both long-context and agentic tasks. These results support further LCCP scaling as a promising direction for improving downstream capabilities when sufficient long-context data are available.

6 CONCLUSION

We establish an empirical scaling law for LCCP that relates long-context performance to model size and separate token budgets for short-context pre-training and LCCP, while supporting extrapolation to held-out model scales and token budgets. We introduce CONSTANT-LAST4, enabling stable observation along an extensible trajectory. In our 1B-scale experiments, we observe continued improvements in long-context performance along the evaluated 32K LCCP trajectory, up to $\approx 100B$ tokens. These gains remain after 128K context extension and SFT, including downstream long-context and agentic tasks. Taken together, these findings establish continued LCCP as a predictable and practically effective path toward improving long-context and agentic capabilities.

AI USE STATEMENT

We used generative AI tools to assist with translation, correct grammatical and stylistic issues, improve the clarity and academic presentation of the manuscript, refine scientific visualizations, and format LaTeX tables and figures. We did not use generative AI to generate data, formulate scientific claims or hypotheses, design experiments or develop methods, conduct a literature review or perform qualitative analysis, or generate citations. All AI-assisted work was reviewed and verified by the authors. The authors independently determined all interpretations and conclusions based on the original experimental results and take full responsibility for the final content of this work.

ETHICS STATEMENT

This work studies the scaling behavior of long-context continual pre-training. Improved long-context and agentic capabilities may amplify existing language-model risks, including harmful outputs, bias, privacy leakage, and misuse of automated tools. The use of large-scale training corpora also warrants attention to data provenance, licensing, and potentially sensitive content. Our capability evaluations do not establish deployment safety; downstream applications require task-specific safety evaluation and appropriate safeguards. Further scaling should weigh capability gains against these risks and the computational and environmental costs of training.

REPRODUCIBILITY STATEMENT

Sections 3–5 describe our experimental design, scaling-law formulation, and evaluation protocols. Appendix A documents metric computation and evaluation-set construction, model and training configurations, realized token budgets, hardware, and training-data composition and processing. It also specifies the scaling-law fitting procedure, held-out evaluation splits, and fitted parameters. Appendix B details the checkpoint-merging methods and their comparison protocol. Appendix C provides supplementary downstream results and evaluation settings, including the use of multiple data seeds or repeated evaluation runs where applicable. These details support replication of our experimental procedures and results.

REFERENCES

Yushi Bai, Xin Lv, Jiajie Zhang, Hongchang Lyu, Jiankai Tang, Zhidian Huang, Zhengxiao Du, Xiao Liu, Aohan Zeng, Lei Hou, et al. Longbench: A bilingual, multitask benchmark for long context understanding. In *Proceedings of the 62nd annual meeting of the association for computational linguistics (volume 1: Long papers)*, pp. 3119–3137, 2024.

Elie Bakouch, Loubna Ben Allal, Anton Lozhkov, Nouamane Tazi, Lewis Tunstall, Carlos Miguel Patiño, Edward Beeching, Aymeric Roucher, Aksel Joonas Reedi, Quentin Gallouédec, Kashif Rasul, Nathan Habib, Clémentine Fourrier, Hynek Kydlicek, Guilherme Penedo, Hugo Larcher, Mathieu Morlon, Vaibhav Srivastav, Joshua Lochner, Xuan-Son Nguyen, Colin Raffel, Leandro von Werra, and Thomas Wolf. SmolLM3: smol, multilingual, long-context reasoner. `https://huggingface.co/blog/smollm3`, 2025.

Victor Barres, Honghua Dong, Soham Ray, Xujie Si, and Karthik Narasimhan. τ^2-bench: Evaluating conversational agents in a dual-control environment, 2025. URL `https://arxiv.org/abs/2506.07982`.

Akhiad Bercovich, Itay Levy, Izik Golan, Mohammad Dabbah, Ran El-Yaniv, Omri Puny, Ido Galil, Zach Moshe, Tomer Ronen, Najeeb Nabwani, et al. Llama-nemotron: Efficient reasoning models. *arXiv preprint arXiv:2505.00949*, 2025.

Aaron Blakeman, Aaron Thomas, Aastha Jhunjhunwala, Abhibha Gupta, Abhinav Khattar, Adam Rajfer, Adi Renduchintala, Adil Asif, Aditya Vavre, Adriana Flores Miranda, et al. Nemotron 3 ultra: Open, efficient mixture-of-experts hybrid mamba-transformer model for agentic reasoning. *arXiv preprint arXiv:2606.15007*, 2026.

Shouyuan Chen, Sherman Wong, Liangjian Chen, and Yuandong Tian. Extending context window of large language models via positional interpolation. *arXiv preprint arXiv:2306.15595*, 2023.

Yangyi Chen, Binxuan Huang, Yifan Gao, Zhengyang Wang, Jingfeng Yang, and Heng Ji. Scaling laws for predicting downstream performance in llms. *arXiv preprint arXiv:2410.08527*, 2024.

Ona De Gibert, Graeme Nail, Nikolay Arefyev, Marta Bañón, Jelmer Van Der Linde, Shaoxiong Ji, Jaume Zaragoza-Bernabeu, Mikko Aulamo, Gema Ramírez-Sánchez, Andrey Kutuzov, et al. A new massive multilingual dataset for high-performance language technologies. In *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pp. 1116–1128, 2024.

Lizhe Fang, Yifei Wang, Zhaoyang Liu, Chenheng Zhang, Stefanie Jegelka, Jinyang Gao, Bolin Ding, and Yisen Wang. What is wrong with perplexity for long-context language modeling? In *International Conference on Learning Representations*, volume 2025, pp. 94541–94563, 2025.

Yao Fu, Rameswar Panda, Xinyao Niu, Xiang Yue, Hannaneh Hajishirzi, Yoon Kim, and Hao Peng. Data engineering for scaling language models to 128k context. *arXiv preprint arXiv:2402.10171*, 2024.

Tianyu Gao, Alexander Wettig, Howard Yen, and Danqi Chen. How to train long-context language models (effectively). In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 7376–7399, 2025.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

Jiawei Gu, Zacc Yang, Chuanghao Ding, Rui Zhao, and Fei Tan. Cmr scaling law: Predicting critical mixture ratios for continual pre-training of language models. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 16143–16162, 2024.

Alexander Hägele, Elie Bakouch, Atli Kosson, Loubna B Allal, Leandro Von Werra, and Martin Jaggi. Scaling laws and compute-optimal training beyond fixed training durations. *Advances in Neural Information Processing Systems*, 37:76232–76264, 2024.

Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, Elena Buchatskaya, Trevor Cai, Eliza Rutherford, Diego de Las Casas, Lisa Anne Hendricks, Johannes Welbl, Aidan Clark, et al. Training compute-optimal large language models. *arXiv preprint arXiv:2203.15556*, 2022.

Cheng-Ping Hsieh, Simeng Sun, Samuel Kriman, Shantanu Acharya, Dima Rekesh, Fei Jia, Yang Zhang, and Boris Ginsburg. Ruler: What's the real context size of your long-context language models? *arXiv preprint arXiv:2404.06654*, 2024.

Shengding Hu, Xin Liu, Xu Han, Xinrong Zhang, Chaoqun He, Weilin Zhao, Yankai Lin, Ning Ding, Zebin Ou, Guoyang Zeng, et al. Predicting emergent abilities with infinite resolution evaluation. In *International Conference on Learning Representations*, volume 2024, pp. 18027–18047, 2024a.

Shengding Hu, Yuge Tu, Xu Han, Chaoqun He, Ganqu Cui, Xiang Long, Zhi Zheng, Yewei Fang, Yuxiang Huang, Weilin Zhao, et al. Minicpm: Unveiling the potential of small language models with scalable training strategies. *arXiv preprint arXiv:2404.06395*, 2024b.

Zhiyuan Hu, Yuliang Liu, Jinman Zhao, Suyuchen Wang, Yan Wang, Wei Shen, Qing Gu, Luu Anh Tuan, See Kiong Ng, Zhiwei Jiang, et al. Longrecipe: Recipe for efficient long context generalization in large language models. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 11857–11870, 2025.

Luyang Huang, Shuyang Cao, Nikolaus Parulian, Heng Ji, and Lu Wang. Efficient attentions for long document summarization. In *Proceedings of the 2021 conference of the north American chapter of the association for computational linguistics: Human language technologies*, pp. 1419–1436, 2021.

Siming Huang, Tianhao Cheng, Jason Klein Liu, Weidi Xu, Jiaran Hao, Liuyihan Song, Yang Xu, Jian Yang, Jiaheng Liu, Chenchen Zhang, et al. Opencoder: The open cookbook for top-tier code large language models. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 33167–33193, 2025.

Maor Ivgi, Yair Carmon, and Jonathan Berant. Scaling laws under the microscope: Predicting transformer performance from small scale experiments. In *Findings of the Association for Computational Linguistics: EMNLP 2022*, pp. 7354–7371, 2022.

Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. Scaling laws for neural language models. *arXiv preprint arXiv:2001.08361*, 2020.

Kimi Team, Tongtong Bai, Yifan Bai, Yiping Bao, Jianfeng Cai, Xinyuan Cai, Peizhou Cao, Yuxuan Cao, Ziwei Chai, Y Charles, et al. Kimi k3: Open frontier intelligence. *arXiv preprint arXiv:2607.24653*, 2026.

Yuri Kuratov, Aydar Bulatov, Petr Anokhin, Ivan Rodkin, Dmitry Sorokin, Artyom Sorokin, and Mikhail Burtsev. Babilong: Testing the limits of llms with long context reasoning-in-a-haystack. *Advances in Neural Information Processing Systems*, 37:106519–106554, 2024.

Yupu Liang, Shuang Chen, Guanwei Zhang, Shaolei Wang, and Suncong Zheng. Revealing the learning dynamics of long-context continual pre-training. *arXiv preprint arXiv:2604.02650*, 2026.

Lawrence I-Kuei Lin. A concordance correlation coefficient to evaluate reproducibility. *Biometrics*, 45 1:255–68, 1989. URL `https://api.semanticscholar.org/CorpusID:32656801`.

Zhan Ling, Kang Liu, Kai Yan, Yifan Yang, Weijian Lin, Ting-Han Fan, Lingfeng Shen, Zhengyin Du, and Jiecao Chen. Longreason: A synthetic long-context reasoning benchmark via context expansion. *arXiv preprint arXiv:2501.15089*, 2025.

Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang, Bochao Wu, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chenyu Zhang, Chong Ruan, et al. Deepseek-v3 technical report. *arXiv preprint arXiv:2412.19437*, 2024.

Aixin Liu, Aoxue Mei, Bangcai Lin, Bing Xue, Bingxuan Wang, Bingzheng Xu, Bochao Wu, Bowei Zhang, Chaofan Lin, Chen Dong, et al. Deepseek-v3. 2: Pushing the frontier of open large language models. *arXiv preprint arXiv:2512.02556*, 2025.

Anton Lozhkov, Raymond Li, Loubna Ben Allal, Federico Cassano, Joel Lamy-Poirier, Nouamane Tazi, Ao Tang, Dmytro Pykhtar, Jiawei Liu, Yuxiang Wei, et al. Starcoder 2 and the stack v2: The next generation. *arXiv preprint arXiv:2402.19173*, 2024.

Grégoire Mialon, Clémentine Fourrier, Thomas Wolf, Yann LeCun, and Thomas Scialom. Gaia: a benchmark for general ai assistants. In *International Conference on Learning Representations*, volume 2024, pp. 9025–9049, 2024.

MiroMind Team, Song Bai, Lidong Bing, Carson Chen, Guanzheng Chen, Yuntao Chen, Zhe Chen, Ziyi Chen, Jifeng Dai, Xuan Dong, et al. Mirothinker: Pushing the performance boundaries of open-source research agents via model, context, and interactive scaling. *arXiv preprint arXiv:2511.11793*, 2025.

Dhruv Nathawani, Igor Gitman, Somshubra Majumdar, Evelina Bakhturina, Ameya Sunil Mahabaleshwarkar, Jian Zhang, and Jane Polak Scowcroft. Nemotron-Post-Training-Dataset-v1, 2025. URL https://huggingface.co/datasets/nvidia/Nemotron-Post-Training-Dataset-v1.

Olmo Team, Allyson Ettinger, Amanda Bertsch, Bailey Kuehl, David Graham, David Heineman, Dirk Groeneveld, Faeze Brahman, Finbarr Timbers, Hamish Ivison, et al. Olmo 3. *arXiv preprint arXiv:2512.13961*, 2025.

OpenAI. GraphWalks: a multi hop reasoning long context benchmark. https://huggingface.co/datasets/openai/graphwalks, 2025. Released alongside GPT-4.1 (April 2025); see https://openai.com/index/gpt-4-1/.

Shishir G. Patil, Huanzhi Mao, Charlie Cheng-Jie Ji, Fanjia Yan, Vishnu Suresh, Ion Stoica, and Joseph E. Gonzalez. The berkeley function calling leaderboard (bfcl): From tool use to agentic evaluation of large language models. In *Forty-second International Conference on Machine Learning*, 2025.

Guilherme Penedo, Hynek Kydlíček, Anton Lozhkov, Margaret Mitchell, Colin Raffel, Leandro Von Werra, Thomas Wolf, et al. The fineweb datasets: Decanting the web for the finest text data at scale. *Advances in Neural Information Processing Systems*, 37:30811–30849, 2024.

Bowen Peng, Jeffrey Quesnelle, Honglu Fan, and Enrico Shippole. Yarn: Efficient context window extension of large language models. In *International Conference on Learning Representations*, volume 2024, pp. 31932–31951, 2024.

Ziqing Qiao, Yinuo Xu, Chaojun Xiao, Zhou Su, Zihan Zhou, Yingfa Chen, Xiaoyue Xu, Xu Han, and Zhiyuan Liu. Rethinking the role of efficient attention in hybrid architectures. *arXiv preprint arXiv:2606.15378*, 2026.

Haoran Que, Jiaheng Liu, Ge Zhang, Chenchen Zhang, Xingwei Qu, Yinghao Ma, Feiyu Duan, Zhiqi Bai, Jiakai Wang, Yuanxing Zhang, et al. D-cpt law: Domain-specific continual pre-training scaling law for large language models. *Advances in Neural Information Processing Systems*, 37: 90318–90354, 2024.

Qwen Team. Qwen3 technical report, 2025. URL https://arxiv.org/abs/2505.09388.

Sunny Sanyal, Atula Neerkaje, Jean Kaddour, Abhishek Kumar, and Sujay Sanghavi. Early weight averaging meets high learning rates for llm pre-training. *arXiv preprint arXiv:2306.03241*, 2023.

Yunchong Song, Jushi Kai, Liming Lu, Kaixi Qiu, and Zhouhan Lin. Towards compressive and scalable recurrent memory. *arXiv preprint arXiv:2602.11212*, 2026.

The Microsoft AI Team. Mai-thinking-1: Building a hill-climbing machine. Technical report, Microsoft AI, 2026. URL https://microsoft.ai/pdf/mai-thinking-1.pdf.

Changxin Tian, Jiapeng Wang, Qian Zhao, Kunlong Chen, Jia Liu, Ziqi Liu, Jiaxin Mao, Xin Zhao, Zhiqiang Zhang, and Jun Zhou. Wsm: decay-free learning rate schedule via checkpoint merging for llm pre-training. In *International Conference on Learning Representations*, volume 2026, pp. 134767–134795, 2026.

Mathurin Videau, Badr Youbi-Idrissi, David Lopez-Paz, and Kartik Ahuja. Skaling: Chinchilla's exponents meet kaplan's coupling, 2026. URL https://arxiv.org/abs/2608.07222.

Xingjin Wang, Howe Tissue, Lu Wang, Linjing Li, and Daniel Dajun Zeng. Learning dynamics in continual pre-training for large language models. *arXiv preprint arXiv:2505.07796*, 2025a.

Yudong Wang, Zixuan Fu, Jie Cai, Peijun Tang, Hongya Lyu, Yewei Fang, Zhi Zheng, Jie Zhou, Guoyang Zeng, Chaojun Xiao, et al. Ultra-fineweb: Efficient data filtering and verification for high-quality llm training data. *arXiv preprint arXiv:2505.05427*, 2025b.

Kaiyue Wen, Zhiyuan Li, Jason Wang, David Hall, Percy Liang, and Tengyu Ma. Understanding warmup-stable-decay learning rates: A river valley loss landscape perspective. *arXiv preprint arXiv:2410.05192*, 2024.

Jeffrey Willette, Heejun Lee, and Sung Ju Hwang. Delta attention: Fast and accurate sparse attention inference by delta correction. *Advances in Neural Information Processing Systems*, 38:12052–12080, 2026.

Longyun Wu, Dawei Zhu, Guangxiang Zhao, Zhuocheng Yu, Junfeng Ran, Xiangyu Wong, Lin Sun, and Sujian Li. Longattn: Selecting long-context training data via token-level attention. In *Findings of the Association for Computational Linguistics: ACL 2025*, pp. 19367–19380, 2025a.

Wenhao Wu, Yizhong Wang, Guangxuan Xiao, Hao Peng, and Yao Fu. Retrieval head mechanistically explains long-context factuality. In *International Conference on Learning Representations*, volume 2025, pp. 62143–62156, 2025b.

Wenhan Xiong, Jingyu Liu, Igor Molybog, Hejia Zhang, Prajjwal Bhargava, Rui Hou, Louis Martin, Rashi Rungta, Karthik Abinav Sankararaman, Barlas Oguz, et al. Effective long-context scaling of foundation models. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pp. 4643–4663, 2024.

Yijun Yang, Zeyu Huang, Wenhao Zhu, Zihan Qiu, Fei Yuan, Jeff Pan, and Ivan Titov. A controllable examination for long-context language models. *Advances in Neural Information Processing Systems*, 38, 2026.

Kazuki Yano, Shun Kiyono, Sosuke Kobayashi, Sho Takase, and Jun Suzuki. Pre-training llm without learning rate decay enhances supervised fine-tuning. *arXiv preprint arXiv:2603.16127*, 2026.

Linyan Yu, Bowen Yu, Haiyang Yu, Fei Huang, and Yongbin Li. Language models are super mario: Absorbing abilities from homologous models as a free lunch. In *Icml*, volume 2, pp. 21, 2024.

Aohan Zeng, Xin Lv, Zhenyu Hou, Zhengxiao Du, Qinkai Zheng, Bin Chen, Da Yin, Chendi Ge, Chenghua Huang, Chengxing Xie, et al. Glm-5: from vibe coding to agentic engineering. *arXiv preprint arXiv:2602.15763*, 2026.

Wenzhen Zheng, Wenbo Pan, Xu Xu, Libo Qin, Li Yue, and Ming Zhou. Breaking language barriers: Cross-lingual continual pre-training at scale, 2024. URL https://arxiv.org/abs/2407.02118.

A Experimental Setup and Reproducibility

A.1 Details about LongPPL and ShortPPL

This section supplements the metric definitions in the main text and records statistics of the test set used for all PPL evaluations. LongPPL and ShortPPL use the same GovReport documents (Huang et al., 2021), reference model, and full-context forward pass; they differ only in the token positions over which losses are aggregated.

Token selection. We precompute token annotations with Llama-3.1-8B and its tokenizer and keep them fixed for every evaluated model. As in the main text, let

$$\Delta_t = \ell_{\text{ref}}^{\text{chunk}}(x_t) - \ell_{\text{ref}}^{\text{full}}(x_t),$$

where the local context contains 4,096 tokens. LongPPL selects positions that are easy for the reference model under full context but become substantially harder without distant context, whereas ShortPPL selects a complementary set of positions that are also easy under full context but have lower loss with only local context:

$$\mathcal{K}_{\text{long}} = \left\{ t : \ell_{\text{ref}}^{\text{full}}(x_t) < 2,\ \Delta_t > 2 \right\},$$
$$\mathcal{K}_{\text{short}} = \left\{ t : \ell_{\text{ref}}^{\text{full}}(x_t) < 2,\ \Delta_t < 0 \right\}.$$

The two sets are therefore disjoint. At evaluation time, each document is decoded to text, retokenized with the evaluated model's tokenizer, and the fixed character intervals are mapped to that model's token positions. This permits the same text spans to be used when the evaluated tokenizer differs from the reference tokenizer.

Test-set construction. The test set contains 10,000 GovReport documents. Candidate documents contain 32,768–39,999 tokens under the Llama-3.1 tokenizer; each document is then retokenized with the evaluated model's tokenizer and truncated to at most 32,768 tokens. Because the tokenizers have different granularities, a small fraction of the retokenized sequences are shorter than this cap. In the final evaluation inputs, 9,434 sequences contain exactly 32,768 tokens; across all 10,000 sequences, the mean and median lengths are 32,751 and 32,768 tokens, respectively.

Table 2: Statistics of the GovReport PPL test set. Document length is measured with the Llama-3.1 tokenizer; the remaining rows use the tokenizer shared by our evaluated models after truncation at 32,768 tokens.

Quantity	Samples	Total tokens	Mean	Median	Min–max
Source document length	10,000	362,174,270	36,217	36,121	32,768–39,999
Evaluated sequence length	10,000	327,512,254	32,751	32,768	24,709–32,768
Long key tokens	10,000	4,662,555	466.3	330	6–7,127
Short key tokens	10,000	82,542,674	8,254.3	8,137	1,978–18,737

As shown in Table 2, Long key tokens account for 1.42% of all evaluated tokens, compared with 25.20% for Short key tokens. Because the number of selected tokens varies substantially across documents, we compute both metrics by averaging negative log-likelihoods over all selected tokens in the test set and then exponentiating, rather than weighting documents equally.

A.2 Alternative Scaling-Law Formulations

We compare Eq. 1 with alternative offset constraints, data-aggregation assumptions, and interaction terms on both the Linear-Decay and Constant-Last4 data.

Within each learning-rate setting, every log-space variant uses the same data, held-out-scale splits, sample weighting, exponent regularization, and multi-start optimization as the corresponding main result: S4 is predicted from S1–S3, while S5 is predicted from S1–S4.

For scaling-law evaluation, let $y_i = \log(\text{LongPPL}_i)$ and $\hat{y}_i$ denote its prediction. We report $R^2 = 1 - \sum_i (\hat{y}_i - y_i)^2 / \sum_i (y_i - \bar{y})^2$ and $\text{MAPE} = \frac{100}{n} \sum_i |\hat{y}_i - y_i| / |y_i|$, with MAPE expressed as a

Table 3: Scale-extrapolation results for formula ablations on the LINEAR-DECAY data. Both R^2 and MAPE are computed in $\log(\text{LongPPL})$ space. S5 contains five diagonal and four off-diagonal budget configurations. For the three powered-pair variants, k is allowed to vary over $0 < k \leq 2$.

Variant	Full formula	S4		S5	
		R^2	MAPE	R^2	MAPE
No offset	$\log(\text{LongPPL}) = \frac{A}{N^\alpha} + \frac{B_s}{D_s^{\beta_s}} + \frac{B_l}{D_l^{\beta_l}}$	0.7995	3.62%	-0.1031	9.05%
Nonnegative offset	$\log(\text{LongPPL}) = \frac{A}{N^\alpha} + \frac{B_s}{D_s^{\beta_s}} + \frac{B_l}{D_l^{\beta_l}} + C,\ C \geq 0$	0.7995	3.62%	-0.1031	9.05%
Free offset (ours)	$\log(\text{LongPPL}) = \frac{A}{N^\alpha} + \frac{B_s}{D_s^{\beta_s}} + \frac{B_l}{D_l^{\beta_l}} + C$	**0.9663**	**1.43%**	**0.9516**	1.71%
Combined budget	$\log(\text{LongPPL}) = \frac{A}{N^\alpha} + \frac{B}{(D_s+D_l)^\beta} + C$	0.8935	2.53%	0.8494	2.40%
Effective data	$\log(\text{LongPPL}) = \frac{A}{N^\alpha} + \frac{B}{(D_l+KD_s)^\beta} + C$	0.9079	2.14%	0.8280	2.94%
Scale-dependent effective data	$\log(\text{LongPPL}) = \frac{A}{N^\alpha} + \frac{B}{(D_l+KN^\nu D_s)^\beta} + C$	0.0980	7.68%	0.8346	3.19%
Powered pair (N–D_s)	$\log(\text{LongPPL}) = \left(\frac{A}{N^\alpha} + \frac{B_s}{D_s^{\beta_s}}\right)^k + \frac{B_l}{D_l^{\beta_l}} + C,\ 0 < k \leq 2$	0.5311	5.44%	0.7990	2.82%
Powered pair (N–D_l)	$\log(\text{LongPPL}) = \left(\frac{A}{N^\alpha} + \frac{B_l}{D_l^{\beta_l}}\right)^k + \frac{B_s}{D_s^{\beta_s}} + C,\ 0 < k \leq 2$	0.4370	6.37%	0.4530	5.22%
Powered pair (D_s–D_l)	$\log(\text{LongPPL}) = \frac{A}{N^\alpha} + \left(\frac{B_s}{D_s^{\beta_s}} + \frac{B_l}{D_l^{\beta_l}}\right)^k + C,\ 0 < k \leq 2$	0.7984	3.58%	0.9488	**1.57%**
CPT interaction	$\log(\text{LongPPL}) = \frac{A}{N^\alpha} + \frac{B_s}{D_s^{\beta_s}} + \frac{B_l}{D_l^{\beta_l} N^\eta} + C$	0.7557	4.14%	0.7163	3.50%

Table 4: The same formula ablations on the CONSTANT-LAST4 data, with both R^2 and MAPE computed in $\log(\text{LongPPL})$ space. S4 contains a 5×5 grid, whereas S5 contains 24 points that hold N and D_s fixed and vary only D_l. For the three powered-pair variants, k is allowed to vary over $0 < k \leq 2$.

Variant	Full formula	S4		S5	
		R^2	MAPE	R^2	MAPE
No offset	$\log(\text{LongPPL}) = \frac{A}{N^\alpha} + \frac{B_s}{D_s^{\beta_s}} + \frac{B_l}{D_l^{\beta_l}}$	0.9354	1.89%	-4.0917	11.01%
Nonnegative offset	$\log(\text{LongPPL}) = \frac{A}{N^\alpha} + \frac{B_s}{D_s^{\beta_s}} + \frac{B_l}{D_l^{\beta_l}} + C,\ C \geq 0$	0.9354	1.89%	-4.0917	11.01%
Free offset (ours)	$\log(\text{LongPPL}) = \frac{A}{N^\alpha} + \frac{B_s}{D_s^{\beta_s}} + \frac{B_l}{D_l^{\beta_l}} + C$	**0.9747**	**1.08%**	**0.9718**	**0.66%**
Combined budget	$\log(\text{LongPPL}) = \frac{A}{N^\alpha} + \frac{B}{(D_s+D_l)^\beta} + C$	0.8901	1.95%	0.1388	4.02%
Effective data	$\log(\text{LongPPL}) = \frac{A}{N^\alpha} + \frac{B}{(D_l+KD_s)^\beta} + C$	0.9155	1.46%	0.7943	1.49%
Scale-dependent effective data	$\log(\text{LongPPL}) = \frac{A}{N^\alpha} + \frac{B}{(D_l+KN^\nu D_s)^\beta} + C$	0.4727	5.45%	-0.7878	6.20%
Powered pair (N–D_s)	$\log(\text{LongPPL}) = \left(\frac{A}{N^\alpha} + \frac{B_s}{D_s^{\beta_s}}\right)^k + \frac{B_l}{D_l^{\beta_l}} + C,\ 0 < k \leq 2$	0.8190	3.20%	-0.3086	5.49%
Powered pair (N–D_l)	$\log(\text{LongPPL}) = \left(\frac{A}{N^\alpha} + \frac{B_l}{D_l^{\beta_l}}\right)^k + \frac{B_s}{D_s^{\beta_s}} + C,\ 0 < k \leq 2$	0.7268	4.19%	-2.3259	8.86%
Powered pair (D_s–D_l)	$\log(\text{LongPPL}) = \frac{A}{N^\alpha} + \left(\frac{B_s}{D_s^{\beta_s}} + \frac{B_l}{D_l^{\beta_l}}\right)^k + C,\ 0 < k \leq 2$	0.9454	1.61%	0.0805	4.58%
CPT interaction	$\log(\text{LongPPL}) = \frac{A}{N^\alpha} + \frac{B_s}{D_s^{\beta_s}} + \frac{B_l}{D_l^{\beta_l} N^\eta} + C$	0.9537	1.59%	-0.2800	5.34%

percentage. For numerical conditioning, define $\widetilde{N} = N/10^8$, $\widetilde{D}_s = D_s/10^9$, and $\widetilde{D}_l = D_l/10^9$. These normalizations are absorbed into the fitted amplitudes and do not change the function class of any formula. For compactness, Tables 3 and 4 report only the held-out scale-extrapolation metrics. As a diagnostic, across both training splits and all formulas, the unweighted training-set R^2 ranges from 0.9633 to 0.9943 on the LINEAR-DECAY and from 0.9740 to 0.9954 on the CONSTANT-LAST4 data. The lower training-fit values arise mainly from the combined-budget and effective-data variants. These results show that training fit alone does not adequately distinguish the predictive performance of different formulations. We therefore emphasize held-out scale extrapolation when evaluating the proposed law and its alternatives.



Figure 9: Zero contours of the free-offset additive scaling law fitted on S1–S4. The left and right panels show the LINEAR-DECAY and CONSTANT-LAST4 fits, respectively. Each curve contains the (D_s, D_l) combinations for which the fitted $\log(\text{LongPPL})$ equals zero at the indicated non-embedding parameter count N.

Offset constraints. A zero-offset additive law, as used in some prior scaling analyses (Qiao et al., 2026), has a plausible asymptotic interpretation: loss may approach zero as model and data scales grow, especially for the chosen predictable key tokens in LongPPL. It is nevertheless substantially less accurate over the finite experimental range under both learning-rate settings. For both settings, constraining $C \geq 0$ gives the same result as the zero-offset law because the optimizer drives C to numerical zero. The fitted values are 1.6×10^{-48} and 4.6×10^{-37} for the LINEAR-DECAY S1–S3 and S1–S4 fits, respectively, and 2.5×10^{-49} and 2.0×10^{-36} for their CONSTANT-LAST4 counterparts. Allowing C to be free instead yields $C = -0.60$ and $C = -0.82$ for the LINEAR-DECAY S1–S3 and S1–S4 fits, respectively, and $C = -0.71$ and $C = -0.61$ for the corresponding CONSTANT-LAST4 fits.

Importantly, a negative offset alone does not imply negative predictions within the relevant scaling regime, since the model- and data-dependent terms remain positive. To stress-test this behavior, Figure 9 plots the zero contours of the S1–S4 fits at several extrapolated model sizes. Finite zero contours emerge only at larger model scales and extreme data budgets. For example, at $N = 10$B, setting $D_s = D_l$ gives a zero crossing at approximately 11.0T tokens per stage for LINEAR-DECAY and 29.5T tokens per stage for CONSTANT-LAST4. These budgets are orders of magnitude beyond the S1–S4 fitting range, whose maxima are approximately 0.11T short-context tokens and 0.012T long-context tokens. Predictions below zero imply $\text{LongPPL} < 1$, indicating that the fitted law has been extrapolated beyond its valid range. The negative offset should therefore be interpreted as a finite-range correction rather than an asymptotic loss floor.

Combining the two training stages. We test whether short-context pre-training and LCCP data can be collapsed into a single data variable using three formulations. The combined-budget baseline, $D_s + D_l$, assumes that the two types of tokens are interchangeable. The effective-data formulation, $D_l + KD_s$, learns a fixed conversion factor between them, while the scale-dependent formulation, $D_l + K\widetilde{N}^{\nu}D_s$, allows this conversion factor to vary with model scale.

All three formulations are less accurate than our additive law, which models D_s and D_l separately. On the linear-decay data, our law achieves $R^2_{\log} = 0.9663$ on S4 and 0.9516 on S5, compared with 0.8935 and 0.8494 for the combined-budget baseline. The effective-data formulation improves some results but remains inferior overall, while the scale-dependent formulation is unstable across extrapolation settings. The same conclusion holds for the constant-learning-rate data, where our law achieves $R^2_{\log} = 0.9747$ on S4 and 0.9718 on S5 and outperforms all three alternatives.

Interaction terms. We test two types of interaction terms to examine whether the additive law overlooks coupling among the scaling variables. First, motivated by a previously proposed coupled form (Videau et al., 2026), we replace each pairwise sum of the terms associated with N, D_s, and D_l by $(x_i + x_j)^k$ in turn, while leaving the third term additive. The three resulting formulas are given explicitly in Tables 3 and 4. We constrain the coupling exponent to $0 < k \leq 2$. Across

Table 5: Short-context pre-training configurations. All runs use a 4,096-token sequence length and RoPE base 10,000. Token counts are in billions and correspond, from left to right, to the nominal $90N$, $180N$, $270N$, $360N$, and $450N$ budgets.

Scale	N (M)	η_{stable}	η_{end}	GBS	MBS	Warmup	Realized D_s (B)				
							$90N$	$180N$	$270N$	$360N$	$450N$
S1	31.470	9.7656×10^{-4}	9.766×10^{-5}	128	8	500	2.83	5.66	8.49	11.32	14.16
S2	60.845	9.5419×10^{-4}	9.542×10^{-5}	128	8	1,000	5.48	10.96	16.43	21.91	27.39
S3	104.427	9.7656×10^{-4}	9.766×10^{-5}	256	8	1,000	9.40	18.80	28.20	37.59	46.99
S4	245.417	9.7656×10^{-4}	9.766×10^{-5}	256	4	1,000	22.08	44.17	66.25	88.33	110.42
S5	821.147	9.7656×10^{-4}	9.766×10^{-5}	512	4	1,000	73.99	147.98	221.96	295.95	369.94

both datasets, both held-out scales, and all three pairings, the fitted value reaches the upper bound to numerical precision. The tested constrained fits provide no consistent extrapolation advantage over the additive law.

Second, following the motivation of prior work on continued pretraining (Zheng et al., 2024), we consider the interaction $C + A/N^{\alpha} + B_s/D_s^{\beta_s} + B_l/(D_l^{\beta_l} N^{\eta})$. This formulation allows model size to modulate the contribution of LCCP data to long-context learning. This interaction is less accurate than the free-offset additive law in all four extrapolation tests. On the linear-decay data, it achieves $R^2_{\log} = 0.7557$ on S4 and 0.7163 on S5. On the constant-learning-rate data, it remains relatively accurate on S4, with $R^2_{\log} = 0.9537$, but deteriorates to $R^2_{\log} = -0.2800$ on S5.

Overall, the tested interaction parameterizations provide no consistent extrapolation benefit. This does not rule out interactions among the scaling variables, but indicates that these particular forms do not outperform the simpler additive law over the measured range.

A.3 Training Details

This section records the complete training procedure used for the S1–S5 scaling experiments and for the 128K extension and supervised fine-tuning experiments in Sections 5.2 and 5.3. We report realized training token counts, rather than only their nominal multiples of N, since training budgets must be rounded to optimizer steps. Below, N denotes the non-embedding parameter count in Table 1, and GBS/MBS denote the global and per-device micro batch sizes in sequences.

Common settings. All stages use the Muon optimizer, bfloat16 training, weight decay 0.1, and gradient clipping at 1.0. Attention and hidden-state dropout are both zero. The 4K, 32K, and 128K stages use RoPE base frequencies of $10{,}000$, $500{,}000$, and $5{,}000{,}000$, respectively, and the 128K stage uses full activation recomputation. All runs were performed on two nodes of eight NVIDIA H800 GPUs each (16 GPUs in total).

4K short-context pre-training. For every model scale, we train five WSD runs with realized budgets close to $90N$, $180N$, $270N$, $360N$, and $450N$. Each run consists of a linear warmup, a constant-learning-rate stable phase, and a linear decay phase; the warmup-plus-stable portion and the decay portion contain tokens in an $8{:}1$ ratio, and D_s counts both. The decay phase reduces the learning rate linearly from η_{stable} to $\eta_{\text{end}} = \eta_{\text{stable}}/10$; this terminal value is also the starting learning rate of the subsequent 32K stage. Warmup lasts 1,000 optimizer steps at every scale except S1, where we use 500: at S1 a 1,000-step warmup would consume 0.52B tokens, or 18.5% of the smallest ($90N$) budget, whereas 500 steps gives a warmup fraction of 9.3%, comparable to the 9.6% at S2. Table 5 lists the realized budgets.

32K long-context continual pre-training. When increasing the sequence length from 4K to 32K, we reduce the global batch size by a factor of eight so that the number of tokens per optimizer step is unchanged. Every 32K run uses MBS 1 and a RoPE base $500{,}000$. The Linear-Decay runs have no warmup, begin at the terminal learning rate of 4K pre-training, and linearly decay to one tenth of that rate. For S1–S4, we train the full 5×5 grid of short- and long-context budgets; for S5, we train the nine diagonal and off-diagonal configurations described in Section 3.

Table 6: LINEAR-DECAY 32K LCCP configurations. All runs use a 32,768-token sequence length, RoPE base 500,000, and no warmup. Token counts are in billions and correspond, from left to right, to the nominal $10N$, $20N$, $30N$, $40N$, and $50N$ budgets.

Scale	N (M)	η_{start}	η_{end}	GBS	MBS	Warmup	Realized D_l (B)				
							$10N$	$20N$	$30N$	$40N$	$50N$
S1	31.470	9.766×10^{-5}	9.766×10^{-6}	16	1	0	0.31	0.63	0.94	1.26	1.57
S2	60.845	9.542×10^{-5}	9.542×10^{-6}	16	1	0	0.61	1.22	1.83	2.43	3.04
S3	104.427	9.766×10^{-5}	9.766×10^{-6}	32	1	0	1.04	2.09	3.13	4.18	5.22
S4	245.417	9.766×10^{-5}	9.766×10^{-6}	32	1	0	2.45	4.91	7.36	9.81	12.27
S5	821.147	9.766×10^{-5}	9.766×10^{-6}	64	1	0	8.22	16.44	24.66	32.88	41.10

Table 7: CONSTANT-RAW/CONSTANT-LAST4 32K LCCP configurations. Each row reports the realized short- and long-context token counts. All runs use a 32,768-token sequence length, RoPE base 500,000, and no warmup. The identical start and end learning rates indicate a constant schedule. Token counts are in billions; \ denotes an unavailable configuration.

Scale	N (M)	Realized D_s (B)	η_{start}	η_{end}	GBS	MBS	Warmup	Realized D_l (B)					
								$10N$	$20N$	$30N$	$40N$	$50N$	$120N$
		2.83						0.31	0.63	0.94	1.26	1.57	\
		5.66						0.31	0.63	0.94	1.26	1.57	\
S1	31.470	8.49	9.766×10^{-5}	9.766×10^{-5}	16	1	0	0.31	0.63	0.94	1.26	1.57	\
		11.32						0.31	0.63	0.94	1.26	1.57	\
		14.16						0.31	0.63	0.94	1.26	1.57	\
		5.48						0.60	1.21	1.82	2.43	3.04	\
		10.96						0.60	1.21	1.82	2.42	3.04	\
S2	60.845	16.43	9.542×10^{-5}	9.542×10^{-5}	16	1	0	0.59	1.20	1.81	2.42	3.04	\
		21.91						0.59	1.20	1.81	2.41	3.04	\
		27.39						0.58	1.19	1.80	2.41	3.04	\
		9.89						1.12	2.22	3.32	4.42	5.49	\
		19.78						1.14	2.24	3.34	4.44	5.49	\
S3	104.427	29.67	9.766×10^{-5}	9.766×10^{-5}	32	1	0	1.16	2.26	3.36	4.46	5.49	\
		39.56						1.18	2.28	3.38	4.48	5.49	\
		49.45						1.20	2.30	3.40	4.50	5.49	\
		22.08						2.45	4.91	7.36	9.81	12.27	\
		44.17						2.45	4.91	7.36	9.81	12.27	\
S4	245.417	66.25	9.766×10^{-5}	9.766×10^{-5}	32	1	0	2.45	4.91	7.36	9.81	12.27	\
		88.33						2.45	4.91	7.36	9.81	12.27	\
		110.42						2.45	4.91	7.36	9.81	12.27	\
S5	821.147	369.94	9.766×10^{-5}	9.766×10^{-5}	64	1	0	8.22	16.44	24.66	32.88	41.10	98.65

The CONSTANT-RAW trajectories use the same batch sizes, data mixture, and starting learning rates as the LINEAR-DECAY runs, but keep the learning rate constant. For S1, S2, S4, and S5, the trajectories are initialized from the same short-context checkpoints as their corresponding LINEAR-DECAY runs. For S3, we retrained the short-context models because the original checkpoints were no longer available; the replacement runs have slightly different realized short-context training budgets, as reported in Table 7. S1–S4 are continued through approximately $50N$ of long-context data. The S5 trajectory fixes the nominal short-context budget at $D_s = 450N$ and continues LCCP through $D_l = 120N$. We evaluate this trajectory every $5N$, starting at $D_l = 5N$, with adjacent checkpoints for merging spaced by $1N$. The realized budgets are summarized in Table 7. All scaling-law fits use the realized model sizes and token counts of the corresponding runs.

128K context extension and supervised fine-tuning. For the experiment in Section 5.2, we apply the same 128K extension recipe to the selected S5 CONSTANT-RAW and CONSTANT-LAST4 checkpoints. We increase the RoPE base to 5,000,000 and use a data mixture with a larger fraction

Table 8: Training configurations applied after 32K LCCP. The token counts are the realized values obtained from the listed sequence length, GBS, and number of optimizer steps.

Stage	Seq. len.	Steps	GBS/MBS	Tokens (B)	LR schedule	RoPE base
128K extension	131,072	1000	16/1	2.10	linear: $9.766 \times 10^{-5} \rightarrow 9.766 \times 10^{-7}$	5,000,000
Long-context SFT	32,768	2000	32/1	2.10	linear: $9.766 \times 10^{-5} \rightarrow 9.766 \times 10^{-7}$	500,000
Agentic SFT	32,768	4000	32/1	4.20	linear: $9.766 \times 10^{-5} \rightarrow 9.766 \times 10^{-7}$	500,000

of sequences longer than 64K. For long-context SFT in Section 5.3, every selected checkpoint undergoes the same 2.10B-token training stage on a mixture of general instruction-following examples and high-quality long-context question-answering data. Because agentic SFT requires a larger capability shift from the preceding training stages, we double the training budget to 4.20B tokens while retaining the same linear-decay learning-rate schedule. All three stages use span-based attention to isolate packed documents. Table 8 provides the remaining settings.

A.4 Training Data

LCCP data. The LCCP corpus combines publicly available and internally curated data, primarily covering Chinese and English. Public sources include filtered web text, such as FineWeb- and HPLT-derived collections (Penedo et al., 2024; Wang et al., 2025b; De Gibert et al., 2024); books and long-form documents; academic papers and PDF text; legal, financial, and patent documents; source code and technical documentation, such as data derived from RefineCode and Stack v2 (Huang et al., 2025; Lozhkov et al., 2024); and publicly released synthetic and instruction data from the Nemotron family (Bercovich et al., 2025; Nathawani et al., 2025). The same 32K mixture is used across all model scales and training-budget configurations.

Length-aware LCCP mixtures. Documents are grouped by their tokenized source-document lengths before sequence construction. Table 9 reports the configured sampling mass of each length bucket. These values describe the source-document lengths, rather than the lengths of the final training sequences, which are fixed at 32,768 and 131,072 tokens for the 32K and 128K stages, respectively.

In the 32K mixture, documents shorter than 16K tokens account for approximately 52.57% of the sampling mass, while documents shorter than 32K tokens account for approximately 65.11%. Documents of at least 32K tokens account for approximately 34.89%. For the 128K extension, the same broad source pool is retained while more sampling mass is assigned to longer documents. The share of documents shorter than 16K tokens decreases to approximately 40.60%, and the share of documents shorter than 32K tokens decreases to 50.00%. Accordingly, the share of documents of at least 32K tokens increases to 50.00%. More specifically, the share of documents in the 32K–128K range increases from 19.80% to 28.38%, while the share of documents of at least 128K tokens increases from 15.09% to 21.62%.

LCCP data processing. Documents longer than the target sequence length are split into consecutive segments of the target length, starting from the beginning of each document, with a one-token overlap between adjacent segments. All resulting segments are retained rather than selecting a random window. Instruction-form examples that exceed the target length are filtered instead of segmented to preserve their supervision structure. The 32K LCCP stage uses standard causal attention without document-boundary masking, whereas the 128K extension uses span-based attention to isolate packed documents. We perform exact document-level matching between the LCCP training corpus and the GovReport documents used for LongPPL evaluation, and find no exact matches. This check is limited to exact document overlap.

Supervised fine-tuning data. The SFT mixture is fixed across all evaluated initializations and training budgets, including checkpoints obtained from different 32K LCCP budgets and the two checkpoint-selection strategies. For long-context SFT, we use the non-thinking response-format variant. Table 10 reports the aggregate task-family composition. The long-context component consists of history-based question answering (11.52%), multi-hop reasoning (2.24%), structured re-

Table 9: Aggregate LCCP sampling weights by tokenized source-document length. Values denote percentages of the configured sampling mass.

Source-document length	32K LCCP	128K extension
$[0, 4\mathrm{K})$	27.63%	21.90%
$[4\mathrm{K}, 8\mathrm{K})$	14.39%	10.79%
$[8\mathrm{K}, 16\mathrm{K})$	10.55%	7.91%
$[16\mathrm{K}, 32\mathrm{K})$	12.54%	9.40%
$[32\mathrm{K}, 64\mathrm{K})$	11.12%	15.94%
$[64\mathrm{K}, 128\mathrm{K})$	8.68%	12.44%
$[128\mathrm{K}, 256\mathrm{K})$	7.37%	10.56%
$[256\mathrm{K}, 512\mathrm{K})$	4.98%	7.13%
$[512\mathrm{K}, \infty)$	2.74%	3.93%
Total	100.00%	100.00%

Table 10: Task-level composition of the SFT mixture. Percentages denote configured sampling mass.

Task family	Sampling mass
General and multilingual instruction following	10.00%
Long-context question answering and reasoning	40.00%
Search-agent trajectories	30.00%
Function and tool calling	20.00%
Total	100.00%

trieval tasks (4.84%), and additional long-context reasoning data (21.40%). For agentic SFT, we use the thinking response-format variant. The mixture consists of 60% search-agent trajectories, in which the model interleaves reasoning with calls to a search engine, a web-page extractor, and a Python sandbox, and 40% function and tool calling trajectories, ranging from single-step tool selection to long-horizon multi-step tool chaining. The loss is computed only on assistant turns. SFT examples are packed into sequences of 32,768 tokens, with span-based attention preventing attention across packed-example boundaries.

A.5 Scaling-Law Fitting Details

Eq. 1 contains seven parameters to estimate. Although S1–S4 provide 100 configurations in total, a direct seven-parameter nonlinear fit can be ill-conditioned or nearly non-identifiable: distinct parameter combinations can yield similar predictions over the observed range, making coefficients and exponents sensitive to noise and extrapolation unreliable. We therefore use the experimental-grid structure to stabilize estimation.

At each model scale, the grid varies the short- and long-context budgets separately. Every fixed (N, D_s) pair has five observations at distinct D_l values, and every fixed (N, D_l) pair has five observations at distinct D_s values. With N and D_s fixed, the remaining terms and offset are constant on the D_l slice, so we fit $y = b_l D_l^{-\beta_l} + c$ to obtain a local estimate of β_l. We repeat this over all available slices in the training split and use the median as a training-data-driven reference; the analogous procedure yields the reference for β_s. Taking the median limits the effect of a small number of anomalous slices. These slice fits provide initialization and empirical thresholds for the exponent regularization; they do not replace the final joint fit.

The joint fit uses Huber loss in $\log(\mathrm{LongPPL})$ space, with equal weight assigned to each training configuration. We set `f_scale=0.05` by pilot fits on the training set before held-out evaluation.

Table 11: Fitted parameters of the joint scaling law. LD denotes LINEAR-DECAY, and CL4 denotes CONSTANT-LAST4. Training scales are shown in parentheses. Fits on S1–S3 predict S4; fits on S1–S4 predict S5. Parameters are rounded to six decimal places.

Fit	A	α	B_s	β_s	B_l	β_l	C
LD (S1–S3)	74.297012	0.223528	261.977808	0.239361	71.681123	0.235262	-0.600638
LD (S1–S4)	61.738434	0.208380	186.719700	0.220593	69.742890	0.234577	-0.817910
CL4 (S1–S3)	94.293321	0.232590	225.443760	0.231024	50.066563	0.223068	-0.710403
CL4 (S1–S4)	108.446353	0.244348	228.854134	0.231342	52.141761	0.225344	-0.613778

We apply the one-sided exponent regularizer

$$\lambda_s\big[\max(\beta_s - \bar{\beta}_s, 0)\big]^2 + \lambda_l\big[\max(\beta_l - \bar{\beta}_l, 0)\big]^2, \qquad \lambda_s = \lambda_l = 1.$$

The thresholds $\bar{\beta}_s$ and $\bar{\beta}_l$ are obtained from the slice fits for the corresponding training split. The regularizer penalizes above-threshold exponents without fixing them or directly constraining the fitted coefficients and offset C.

For each held-out-scale experiment, slice-based exponent estimates, initialization settings, and regularization hyperparameters are determined exclusively from the training split. Specifically, the S4 extrapolation uses only S1–S3 for these choices, whereas the S5 extrapolation uses only S1–S4. The held-out scale is used only for evaluation.

Additionally, the one-variable experiments in Section 4.3 show that an axis exponent can be estimated reliably when the other two variables are fixed and sufficient observations are available along that axis. For future fits of the same scaling law, the multiple D_l observations on a single CONSTANT-LAST4 trajectory can first define a reasonable range for β_l, followed by joint fitting.

Table 11 reports the parameters of $\log(\text{LongPPL}) = AN^{-\alpha} + B_s D_s^{-\beta_s} + B_l D_l^{-\beta_l} + C$, where N is the non-embedding parameter count and D_s, D_l are token counts, all expressed as absolute counts. Figures and evaluation metrics use the unrounded parameters.

B MODEL MERGING

We provide implementation details for the checkpoint-merging methods considered in Section 4.1. For the observation-rule comparison in Figure 4(a), all merging methods use the same pool of 25 checkpoints from the S4 constant-learning-rate trajectory with $D_s = 450N$ and a target budget of $D_l = 50N$, ordered from the oldest checkpoint θ_1 to the newest checkpoint θ_K. All methods in this comparison are evaluated on the same first 1,000 evaluation samples.

Agreement with linear decay. For Figure 4(b), we measure agreement using Lin's concordance correlation coefficient (CCC):

$$\text{CCC} = \frac{2s_{xy}}{s_x^2 + s_y^2 + (\bar{x} - \bar{y})^2},$$

where x_i and y_i are the perplexities of the matched LINEAR-DECAY and constant-learning-rate models, respectively, across the $n = 25$ S4 configurations. Here, $\bar{x}$ and $\bar{y}$ are sample means; s_x^2, s_y^2, and s_{xy} are the variances and covariance computed with denominator n. CCC is computed separately for ShortPPL and LongPPL, and for CONSTANT-RAW and CONSTANT-LAST4.

Model merging methods. For a weighted parameter average, we write

$$\theta_{\text{merge}} = \sum_{i=1}^{K} w_i \theta_i, \qquad w_i \geq 0, \qquad \sum_{i=1}^{K} w_i = 1. \tag{3}$$

The representative deterministic weighting rules are illustrated in Figure 10.

LASTM. LASTM assigns equal weight to the final M consecutive checkpoints and zero weight to all earlier checkpoints:

$$w_i = \begin{cases} 1/M, & i > K - M, \\ 0, & i \leq K - M. \end{cases} \tag{4}$$



Figure 10: Normalized checkpoint-weight profiles on a common 25-position axis, including LAST4, LAST8, LAST12, LAST25, 1-SQRT, and EMA with $\beta = 0.9$. Checkpoints are ordered from oldest to newest.

We evaluate several window sizes and use LAST4, i.e., four weights of 0.25, as the default method in the paper. This rule performs a local trajectory average: it suppresses checkpoint-level fluctuations while avoiding the stale parameters of much earlier checkpoints.

1-Sqrt. Let t_i denote the training iteration of checkpoint i, and define its normalized age relative to the newest checkpoint as

$$a_i = \frac{t_K - t_i}{t_K - t_1}. \tag{5}$$

The unnormalized and normalized 1-SQRT weights are

$$\widetilde{w}_i = 1 - \sqrt{a_i}, \qquad w_i = \frac{\widetilde{w}_i}{\sum_{j=1}^{K} \widetilde{w}_j}. \tag{6}$$

Thus, the oldest checkpoint receives zero weight, and the weight rises increasingly quickly near the end of the trajectory. Unlike a rank-only rule, our implementation uses the actual iteration gaps through t_i.

EMA. We implement post-hoc exponential moving averaging over all available checkpoints. With one nominal checkpoint interval equal to Δ optimizer iterations, its weights are

$$\widetilde{w}_i = \beta^{(t_K - t_i)/\Delta}, \qquad w_i = \frac{\widetilde{w}_i}{\sum_{j=1}^{K} \widetilde{w}_j}. \tag{7}$$

We sweep $\beta \in \{0.1, 0.5, 0.9\}$; Figure 10 shows the representative $\beta = 0.9$ setting used in the main comparison. A smaller β concentrates more mass on recent checkpoints, whereas a larger β approaches a more uniform average over the trajectory.

Beyond weighted parameter averaging, we evaluate two representative task-vector merging methods, DARE and TIES. For both methods, we use the oldest selected checkpoint as the reference θ_1 and define the task vector for each source checkpoint as $\delta_i = \theta_i - \theta_1$.

DARE. We evaluate the DARE-LINEAR variant (Yu et al., 2024). For each coordinate of each task vector, DARE samples an independent Bernoulli mask with retention probability ρ, sets dropped coordinates to zero, and rescales retained coordinates by $1/\rho$. We then average the sparsified task vectors and add the resulting update to θ_1. We use random seed 42 and evaluate $\rho \in \{0.1, 0.5\}$.

TIES. For each task vector and parameter tensor, TIES retains the fraction ρ of coordinates with the largest absolute magnitudes and sets the remaining coordinates to zero. It then elects a sign for each coordinate based on the sum of the trimmed task vectors, averages the nonzero updates whose signs agree with the elected sign, and adds the resulting update to θ_1. We evaluate $\rho \in \{0.1, 0.5\}$.

For visual clarity, Figure 4a focuses on the better- performing merging methods. We report TIES separately because its best-performing configuration underperforms both DARE and the final CONSTANT-RAW checkpoint.



Figure 11: LAST4 window-spacing ablation on the S5 32K CONSTANT trajectory. (a) LongPPL versus long-context budget. (b) Relative difference from the default LAST4(1N) window, computed as $100 \times (\text{LongPPL} - \text{LongPPL}_{1N})/\text{LongPPL}_{1N}$ (%).

Interpreting the Advantage of Simple Averaging. TIES and DARE were developed primarily to control interference when combining task vectors from models with different fine-tuning objectives or acquired capabilities. Our setting is structurally different: all checkpoints lie on one continuous training trajectory, so their updates are strongly correlated and temporally nested rather than representing independent capability directions. In this regime, local or recency-weighted parameter averaging directly smooths trajectory noise while preserving the many small, consistently accumulated updates. Magnitude trimming in TIES and random dropping in DARE can remove part of this shared trajectory signal, while their use of the full checkpoint range also assigns influence to relatively stale states. Consistent with this interpretation, the best tested TIES setting ($\rho = 0.5$) obtains a LongPPL of 3.7950, which is worse than the raw final checkpoint at 3.6233, while the best tested DARE setting ($\rho = 0.5$) reaches 3.5217 but remains behind 1-SQRT at 3.4724 and EMA with $\beta = 0.9$ at 3.4720.

These results do not imply that TIES or DARE is generally inferior. Rather, they suggest that the mechanisms designed to resolve interference are less well suited to our setting, where checkpoints are highly correlated and lie along a single training trajectory. In this regime, simple weighted averaging is more effective, stable, and inexpensive.

B.1 SENSITIVITY OF LAST4 TO CHECKPOINT SPACING

The S5 CONSTANT-LAST4 protocol in Section 4.2 averages the four most recent checkpoints with equal weight and uses a $1N$ gap between adjacent source checkpoints. This choice balances evaluation stability against checkpoint storage, but it leaves open whether LAST4 LongPPL depends on that $1N$ spacing.

We therefore run a spacing ablation on the same S5 32K constant-learning-rate trajectory, with $D_s = 450N$ and targets every $10N$ from $D_l = 20N$ to $D_l = 120N$. For each target budget T and spacing $s \in \{1N, 2N, 3N, 4N, 5N\}$, Last4($s$) uniformly averages the checkpoints $\{T - 3s, T - 2s, T - s, T\}$. For example, the $1N$ window at $20N$ uses $17N/18N/19N/20N$, whereas the $5N$ window uses $5N/10N/15N/20N$. As a control, we report the unmerged CONSTANT-RAW checkpoint at the same target. All protocols are evaluated on the same first 1,000 32K samples for LongPPL, ShortPPL, and PPL, so differences among spacings are not due to a changing evaluation set.

Figure 11(a) and Table 12 give the same conclusion. Merging improves over Raw at every one of the eleven budgets: mean LongPPL falls from 2.284 to about 2.20. By contrast, stretching the source spacing from $1N$ to $5N$ changes the merged result only slightly. The $2N$–$5N$ windows have mean LongPPL 0.008 to 0.012 below the default $1N$ window. ShortPPL follows the same pattern: the improvement over Raw is about an order of magnitude larger than the differences among spacings.

Table 12: Mean LongPPL and ShortPPL over the eleven target budgets. Δ is the original-space difference against Last4(1N).

Protocol	LongPPL		ShortPPL	
	Mean	Δ vs $1N$	Mean	Δ vs $1N$
Constant-Raw	2.284	$+0.074$	2.082	$+0.041$
Last4 ($1N$)	2.210	0.000	2.041	0.000
Last4 ($2N$)	2.202	-0.008	2.036	-0.005
Last4 ($3N$)	2.199	-0.011	2.034	-0.007
Last4 ($4N$)	2.200	-0.010	2.033	-0.008
Last4 ($5N$)	2.198	-0.012	2.032	-0.009

Thus, the $1N$ Last4 protocol used for S5 is not a fragile choice. Within the tested $1N$–$5N$ range, Last4 is insensitive to checkpoint spacing, and the stabilization gain of merging over Raw dominates residual effects of the window geometry. Wider checkpoint spacing yields slightly lower perplexity on average, but the differences are small relative to the benefit of merging.

The ablation covers only this S5 trajectory and perplexity metrics, so we read it as a robustness check of the main-text $1N$ Last4 choice rather than as a universal guarantee for arbitrary spacings or downstream tasks.

C Downstream Evaluation Details

C.1 RULER-32K Results by Subtask

Section 5.1 reports the aggregate RULER-32K score along the S5 32K LCCP trajectory. Figure 12 shows the corresponding scores on all 13 subtasks for both Constant-Raw and Constant-Last4.

The easiest retrieval tasks saturate early: `niah_single_1` remains at ceiling throughout training, while `niah_single_2` and `niah_multikey_1` are already close to ceiling near the beginning of the trajectory. The clearest gains instead occur on intermediate-difficulty retrieval tasks. Under Constant-Last4, the scores of `niah_multikey_2`, `niah_multivalue`, and `niah_multiquery` increase from 51.20, 10.20, and 18.75 at $5N$ to 71.20, 28.75, and 45.00 at $120N$, respectively, despite checkpoint-level fluctuations. The corresponding Constant-Raw curves are less stable and show smaller endpoint gains.

The improvement is not uniform across all capabilities. The hardest multi-key retrieval setting, `niah_multikey_3`, and the more compositional Variable Tracking and Common Words tasks remain near the bottom of their respective scales. Scores on the QA tasks and Frequent Words also fluctuate rather than improve monotonically. Despite this uneven progress, gains on several intermediate-difficulty retrieval subtasks indicate continued benefits from additional LCCP.

C.2 RULER-128K Results by Subtask

Similarly, Section 5.2 reports aggregate RULER-128K performance after applying the same 2.10B-token 128K context-extension stage to checkpoints selected from the S5 32K LCCP trajectory. We present the corresponding per-subtask scores in Figure 13.

The 128K results exhibit a pattern similar to the 32K evaluation in the previous section. The score on `niah_single_1` remains at the ceiling of 100, while scores on `niah_single_2` and `niah_multikey_1` remain high across all checkpoints. The most visible transfer gains occur on `niah_multikey_2` and `niah_multiquery`. As the preceding 32K LCCP budget increases from $10N$ to $120N$, `niah_multikey_2` rises from 5 to 20 for Constant-Raw and from 8 to 25 for Constant-Last4, reaching 33 at the $100N$ Last4 checkpoint. `niah_multiquery` likewise rises from 23.00 to 37.50 for Raw and from 26.75 to 36.25 for Last4, with a Last4 peak of 45.25 at $80N$.



Figure 12: Per-subtask RULER-32K performance along the S5 32K LCCP trajectory. Scores are computed from 500 samples per subtask.

Other tasks remain substantially harder at 128K. In particular, `niah_multikey_3`, Variable Tracking, and Common Words stay close to the floor, while Frequent Words and the two QA tasks vary across checkpoints without a reliable upward trend. The benefits of additional 32K LCCP therefore vary across subtasks and are not consistently monotonic, but gains in multi-key and multi-query retrieval contribute to the improvement in the aggregate 128K score.

C.3 Evaluation after Long-Context and Agentic SFT

Long-context SFT. The experiment in Section 5.3 applies a 2.10B-token SFT stage to checkpoints selected along the S5 32K LCCP trajectory. For each starting checkpoint and checkpoint-selection method, we train three SFT models using different data seeds. We then evaluate each model on LongBench, GraphWalks, LongReason, and BABILong. Figure 14 reports the mean score over the three seeds for each benchmark separately, complementing the equal-weight four-task averages reported in the main text.



Figure 13: Per-subtask RULER-128K performance after the fixed 128K context-extension stage. The horizontal axis denotes the amount of 32K LCCP completed before context extension. All results use 100 fixed samples per subtask.

To test whether this benefit persists with a larger SFT budget, we extend SFT to 4.20B tokens (4,000 steps) from the same CONSTANT-LAST4 and CONSTANT-RAW starting checkpoints. Apart from doubling the SFT duration, we keep the training and evaluation protocols consistent with the 2.10B-token experiment. We evaluate LongBench, GraphWalks, LongReason, and BABILong and report both the individual scores and their equal-weight average. Due to the additional training cost, these 4,000-step experiments use only one data seed and should therefore be interpreted as supporting evidence rather than a seed-robust comparison.

Figure 15 provides preliminary evidence that the main conclusion persists after doubling the SFT budget. For CONSTANT-LAST4, the four-benchmark average initially decreases from 26.49 at $10N$ to 25.74 at $20N$, but then rises consistently to 29.97 at $120N$. For CONSTANT-RAW, the average fluctuates more across intermediate checkpoints but still increases from 26.40 to 29.49 over the same range. Individual benchmarks remain noisy, so the gain is not uniformly monotonic on every task. Nevertheless, the overall trend is consistent with the hypothesis that the benefits of additional



Figure 14: Per-task performance after 2.10B tokens of SFT from checkpoints selected along the S5 32K LCCP trajectory for both CONSTANT-LAST4 and CONSTANT-RAW. Each point is the mean over three SFT runs trained with different data seeds.



Figure 15: Performance after 4.20B-token SFT from S5 checkpoints at varying 32K LCCP budgets. Individual benchmark scores and their equal-weight average follow the 2.10B-token evaluation protocol. These single-data-seed results serve as a supplementary robustness check.

LCCP persist when the SFT budget is doubled, while the single-seed setting limits the strength of this conclusion.

Agentic SFT. The agentic SFT experiment in Section 5.3 applies a 4.20B-token SFT stage to checkpoints selected along the S5 32K LCCP trajectory. We evaluate each model on three long-horizon agentic benchmarks, covering two task types: search agent (GAIA and the web search category of BFCL v4(hereafter, BFCL-WebSearch)) and multi-turn tool calling (τ^2-telecom). In all three, the context accumulates over interactions and reaches tens of thousands of tokens (Table 13), exercising long-context capability. Inference uses the thinking response format with temperature



Figure 16: GAIA and BFCL-WebSearch performance after 4.20B-token agentic SFT along the S5 32K LCCP trajectory. Each point averages three evaluation runs.

0.6 and a maximum context length of 32,768 tokens, and we report the average score over three independent runs (avg@3).

For GAIA, we use the text-only subset of the validation set, totaling 103 examples, and evaluate with the MiroThinker agent framework (MiroMind Team et al., 2025). The agent runs a tool-calling loop of up to 200 turns with web search, web-page reading, and Python-interpreter tools. To fit long trajectories into the context budget, only the five most recent tool results are kept in the prompt while earlier ones are replaced by a placeholder. Final answers are judged by GPT-4.1 against the reference.

For BFCL-WebSearch, the benchmark consists of 100 multi-hop questions whose answers must be retrieved from the live web, and we follow the official protocol for evaluation. The agent runs a native function-calling loop of up to 20 steps with a web search tool and a web-page reading tool. We report the mean accuracy over its two settings (*base*, where search results include text snippets, and *no-snippet*, where the model must open web pages instead).

For τ^2-telecom, we evaluate on the telecom domain of τ^2-bench, totaling 114 tasks. The user is simulated by Qwen3-235B-A22B-Instruct-2507 (Qwen Team, 2025) with temperature 0, and each dialogue is capped at 100 steps. A trial scores 1 only if all task-specified checks on the final environment state and required tool calls pass, and 0 otherwise.

Table 13 summarizes the context lengths observed during evaluation. For GAIA, we report both the final context (the input of the last LLM call) and the peak context (the largest input over the course). BFCL-WebSearch and τ^2-telecom keep the full history in context, so the final context equals the peak. BFCL trajectories exceeding the context limit are scored 0 and excluded from the table.

Table 13: Context lengths (tokens) of agentic evaluation trajectories.

Benchmark	Context	Avg	P50	P75	P90	Max
GAIA	final	7,036	6,603	10,470	13,361	31,512
GAIA	peak	12,533	12,749	21,074	21,167	31,512
BFCL-WebSearch	final (peak)	16,259	15,615	22,977	28,900	32,758
τ^2-telecom	final (peak)	10,844	10,543	11,376	12,376	32,766

D Additional Analyses

D.1 Comparing LongPPL and ShortPPL Improvement Rates

Although LongPPL is widely used as a measure of long-context performance (Willette et al., 2026; Song et al., 2026) and correlates well with a range of long-context downstream tasks (Qiao et al., 2026; Fang et al., 2025), it is still a perplexity-based metric. A lower LongPPL need not result



Figure 17: Ratio of the log-scale elasticities of LongPPL and ShortPPL along the S5 CONSTANT-LAST4 LCCP trajectory. Markers show measurements through ($D_l = 120N$). Solid curves show fits over the measured range; dashed curves extend these fits to ($D_l = 240N$).

exclusively from better use of distant context: it can also reflect broad next-token prediction gains, adaptation to the evaluation domain, or changes in local token statistics. We therefore compare changes in LongPPL and ShortPPL to examine whether tokens with different dependence on distant context improve at different rates during LCCP.

We use ShortPPL as a matched control metric. It is computed on tokens whose prediction has limited dependence on distant context, and thus provides a proxy for perplexity changes that do not require long-range information. ShortPPL is not a pure measure of general language-modeling ability, but it helps capture broad improvements under the same model, data, and evaluation procedure. Along the S5 CONSTANT-LAST4 trajectory, we fit the same saturating power-law form independently to both metrics over 24 checkpoints, from $D_l = 5N$ to $D_l = 120N$ (approximately 100B tokens):

$$\log M(D_l) = E_M + A_M D_l^{-\alpha_M}, \qquad M \in \{\text{LongPPL}, \text{ShortPPL}\}.$$

For metric M, we define the log-scale elasticity

$$e_M(D_l) = \left| \frac{\partial \log M}{\partial \log D_l} \right|.$$

For the fitted form, this is $e_M(D_l) = \alpha_M A_M D_l^{-\alpha_M}$, so it measures the relative rate of improvement at a given training budget. We then compare the two metrics using

$$R(D_l) = \frac{e_{\text{Long}}(D_l)}{e_{\text{Short}}(D_l)}.$$

This ratio is a descriptive comparison: it indicates whether LongPPL is changing faster than the matched ShortPPL control, but it is not an exact causal decomposition of the total perplexity gain.

As shown in Figure 17, $R(D_l)$ is largest at the beginning of the trajectory and gradually decreases as LCCP proceeds. Numerically, it declines from approximately 3.35 at $5N$ to 2.22 at $120N$, but remains above 2 throughout the observed range. Thus, LongPPL improves substantially faster than ShortPPL, although the difference in the relative improvement rates of LongPPL and ShortPPL narrows as training proceeds. In conjunction with the downstream evaluations in Section 5, the result supports using LongPPL as a useful proxy for long-context performance during extended LCCP.

D.2 EFFECTS OF CHECKPOINT MERGING ACROSS TRAINING STAGES

During extended LCCP, CONSTANT-LAST4 lowers LongPPL and improves average RULER-32K performance relative to CONSTANT-RAW. Table 14 summarizes these differences and compares performance after subsequent training initialized from the corresponding raw and merged checkpoints.

Table 14: Mean performance of CONSTANT-RAW and CONSTANT-LAST4 over comparable evaluation points. The training stage identifies where each metric is evaluated. For all rows, Δ = LAST4 − RAW; negative values indicate improvement for LongPPL, whereas positive values indicate improvement for other task scores.

Metric	Training stage	n	RAW	LAST4	Δ
32K LongPPL	32K LCCP	24	2.312	2.241	-0.071
RULER-32K	32K LCCP	24	44.29	45.48	$+1.19$
RULER-128K	128K LCCP	7	39.88	40.48	$+0.60$
SFT-4-avg (2.10B)	SFT	7	23.91	24.42	$+0.51$
SFT-4-avg (4.20B)	SFT	7	27.98	27.82	-0.16
Agentic-3-avg (4.20B)	SFT	7	35.21	35.37	$+0.15$

After 128K context extension, models initialized from CONSTANT-LAST4 outperform those initialized from CONSTANT-RAW by 0.60 points on average on RULER-128K. Similarly, after 2.10B tokens of SFT, the four-benchmark average is 0.51 points higher for CONSTANT-LAST4. However, with a larger SFT budget of 4.20B tokens, this difference narrows and slightly favors CONSTANT-RAW by 0.16 points. In agentic SFT, CONSTANT-LAST4 retains a small 0.15-point advantage over CONSTANT-RAW. Thus, the advantage of checkpoint merging observed during LCCP does not consistently persist through subsequent training.

A related finding is that learning-rate decay can improve pre-training metrics while yielding worse performance after SFT than training without decay (Yano et al., 2026). Although this concerns learning-rate schedules rather than checkpoint merging, it similarly highlights that better performance before SFT need not imply better performance afterward. Our limited experiments do not establish when merging advantages persist. One tentative hypothesis is that these advantages may survive a modest amount of additional training or with a similar objective, as in context extension, but diminish or reverse with longer training or larger shifts in training data and objectives, as in SFT. Further controlled experiments are needed to distinguish these factors.

We therefore primarily view checkpoint merging as a stable *observation* mechanism for assessing long-context performance along an extensible constant-learning-rate trajectory, rather than as a strategy for consistently improving subsequent training outcomes. In this protocol, merging is used for evaluation, while continued LCCP proceeds from the latest raw checkpoint.

D.3 DYNAMICS OF THE RETRIEVAL-HEAD DURING LCCP

Previous work suggests that retrieval-head metrics can serve as mechanistic probes of model development over the course of LCCP (Liang et al., 2026). Following the definition in that work, we measure the copy-retrieval behavior of individual attention heads. For each teacher-forced answer token, a head records a retrieval hit when its maximum-attended input position lies within the reference sentence and contains the same token_id as the current target token. The per-instance score of a head is the fraction of answer tokens producing such hits, and its checkpoint-level retrieval score is obtained by averaging the per-instance scores over our 2,400 LongBio single-needle instances (Yang et al., 2026). A head is classified as a retrieval head if its checkpoint-level score exceeds 0.1. For longitudinal comparison, we identify 10 retrieval heads at the raw $5N$ checkpoint and track the mean score of this fixed set at all subsequent checkpoints. The retrieval-head count, by contrast, is recomputed independently at each checkpoint as the number of heads whose checkpoint-level score exceeds 0.1.

As shown in Figure 18, the retrieval-head metrics capture substantial learning during the early stages of training. The mean score of the fixed retrieval heads rises rapidly, while the number of heads above the threshold increases from 10 to 13–14. After around $D_l = 30N$, however, the fixed-head score reaches a noisy plateau and exhibits no sustained upward trend. This plateau does not coincide with saturation in behavioral performance. The RULER-32K score continues to improve up to $D_l = 120N$, with additional gains on several multi-key and multi-query tasks. These results suggest that the selected retrieval-head probes do not capture all behavioral improvements that occur later in LCCP. Retrieval-head metrics are therefore useful as early-stage diagnostic signals, but they should



Figure 18: Retrieval-head metrics and RULER-32K performance along the S5 CONSTANT-LAST4 trajectory. The three square panels show the fixed-head retrieval score, retrieval-head count, and RULER-32K score.

be considered alongside LongPPL and behavioral evaluations rather than used alone to determine whether LCCP training has saturated.