arXiv:2610.36918v1 [cs.CL] 27 Oct 2026

TrawMem: Reframing Agent Memory as Task-Oriented Role-Adaptive Workspaces

Mingyu Zhang[1] Zixu Li[1,†] Zhiheng Fu[1] Zhiwei Chen[1] Jinhe Bi[2] Yupeng Hu[1,✉]
[1]Shandong University [2]National University of Singapore
{zhmingyu.cs, lizixu.cs, fuzhiheng8, zivczw}@gmail.com
bijinhe@outlook.com, huyupeng@sdu.edu.cn

Code: https://github.com/zh-mingyu/TrawMem

Large language model (LLM) agents rely on memory systems to leverage long-term interactions, yet existing systems typically retrieve memories based on their relevance to the current query and use them as contextual evidence. However, relevance alone does not characterize how a memory contributes to task solving: the same memory may serve different roles across tasks, such as directly supporting the answer or linking to complementary memories with weaker semantic relevance but necessary information. We therefore reframe agent memory systems as Task-Oriented Role-Adaptive Workspaces*, where memories are selected and organized by their task-oriented roles and relations. Based on this view, we propose* `TrawMem`*, which organizes interaction histories into local threads and constructs task-oriented workspaces by assigning roles and jointly selecting complementary memories. Experiments on LoCoMo and MemGallery with four open- and closed-source backbones show consistent improvements over representative memory systems, with macro-F1 gains of 2.23–3.14 points. On LoCoMo,* `TrawMem` *improves the LLM-Judge score over SimpleMem by 4.07 and 4.31 percentage points on Qwen3.5-9B and DeepSeek-V4-Flash, respectively, while requiring approximately 12.8% and 5.1% fewer context tokens, respectively.*



Figure 1. **Our observation and reframing of agent memory usage.** (a) Memory Unit A directly supports Task A, while for Task B it serves as a bridge to memory unit B that may have weaker semantic relevance. (b) Existing memory systems typically retrieve relevant memories as context, whereas `TrawMem` constructs a task-oriented workspace by jointly selecting memory units and organizing their relations according to their roles.

1. Introduction

In recent years, agents have been widely applied to long-horizon multi-turn dialogue, personalized assistants, and continuous task (Packer et al., 2023; Park et al., 2023; Zhong et al., 2024; Kang et al., 2025). These tasks require agent systems to maintain conversational memory across evolving

†Project Leader: Zixu Li. ✉Corresponding Author: Yupeng Hu.

interactions to understand user needs and complete subsequent tasks. However, growing interaction histories make limited context windows a key bottleneck for long-horizon tasks (Packer et al., 2023). Although larger context windows (Chen et al., 2023, 2024; Ding et al., 2024) can accommodate more history, information in less salient positions remains prone to being overlooked (Liu et al., 2024). Reprocessing full history for each query also incurs substantial inference overhead (Fang et al., 2026).

Agent memory systems have therefore emerged to store information outside the current context and retrieve relevant memories for new queries, mitigating information loss from growing interaction histories. Existing work (Du et al., 2025; Zhang et al., 2025a) advances memory construction, maintenance, and retrieval. For example, Mem0 (Chhikara et al., 2025) integrates long-term memory (LTM), A-MEM (Xu et al., 2026a) organizes related information through memory links, while LightMem (Fang et al., 2026) and SimpleMem (Liu et al., 2026) improve efficiency through offline memory maintenance, and memory compression with dynamic retrieval planning, respectively. Despite these advances, existing agent memory systems typically select memories by their direct relevance to the query and use them as context for task solving. This focuses on whether a memory is relevant to the task, while overlooking the role it plays in solving it.

Indeed, a memory's importance depends not only on its semantic relevance but also on its task-oriented role. As shown in Fig. 1(a), memory unit A is highly relevant to both Task A and Task B, but serves different roles. For Task A, it directly supports the answer; for Task B, it primarily connects to other memories, such as unit B. By recognizing this role, we can identify complementary memories such as B, whose semantic relevance to Task B may be weaker and thus be overlooked by existing methods. This motivates identifying the roles of memories for a given task and organize memories that jointly support task solving. Rather than viewing memory as a collection of records awaiting retrieval, we therefore reframe it as a workspace temporarily formed for the current task, where the system can construct effective combinations of information according to distinct roles and relations of memories in the current task.

From this perspective, we propose **T**ask-Oriented **R**ole-**A**daptive **W**orkspaces (**`TrawMem`**), which reframes agent memory usage around task-oriented roles and relations. As shown in Fig. 1(b), conventional memory systems typically use retrieved relevant memories as context, whereas `TrawMem` selects and organizes memories into a task-oriented workspace. In this view, the same memory may serve different roles depending on the task and its relations with other memories, shifting the focus of agent memory from finding relevant memories to organizing memories according to how they support task solving. To achieve this goal, `TrawMem` organizes memory usage into two stages. The first organizes continuous interaction histories into local threads and establishes relations between them. The second constructs a workspace for each task by retrieving candidate memories from relevant thread neighborhoods and selecting them according to their task-oriented roles. Section 4 details this process.

Contributions. This work shows that the same memory may serve different roles across tasks, and reframe agent memory usage as Task-Oriented Role-Adaptive Workspaces. Based on this view, we propose `TrawMem` to select and organize memories according to their task-oriented roles, and validate its effectiveness through systematic evaluation.

Performance. On long-horizon interaction memory benchmarks, LoCoMo and MemGallery, we compare `TrawMem` with representative memory systems across four open- and closed-source backbones. Under the same backbone, `TrawMem` improves the macro-average J score (LLM-Judge) by 2.19–6.34 and 0.52–4.82 percentage points on LoCoMo and MemGallery, with mean gains of +3.71 and +2.94, respectively. We further evaluate the effects of each components through ablations, sensitivity analyses, and case studies.

2. Related Work

Memory for LLM Agents. Existing LLM agent memory systems store and retrieve interaction histories through memory streams, controllers, and hierarchical structures (Park et al., 2023; Wang et al., 2025). Recent work has further improved memory compactness, update efficiency, and organization through compression and consolidation (Fang et al., 2026; Liu et al., 2026), information extraction and evolving linked memory notes (Chhikara et al., 2025; Xu et al., 2026a), and temporal, hierarchical, and multi-type representations (Kang et al., 2025; Rasmussen et al., 2025; Zhang et al., 2026a; Li et al., 2025a). Retrieval of such memories likewise benefits from composed image search, e.g., noise-robust and anchor-based composition (Li et al., 2026a; Fu et al., 2026; Li et al., 2026b), fine-grained and invariance-aware composition (Li et al., 2025b; Chen et al., 2026), entity-relation binding and focus-shift revision (Chen et al., 2025; Li et al., 2025c), and progressive and dual-path composition (Li et al., 2026c; Zhang et al., 2026b). However, these methods typically treat memories as independent units or rely on coarse-grained relevance. They rarely model how a memory serves different roles across tasks, or treat complementary memory selection as a central retrieval problem. Long interaction histories from agent-based social simulation raise similar organization demands (Zhang et al., 2025b; Song et al., 2026; Zhang et al., 2026c). `TrawMem` instead assigns task-oriented roles to candidate memories and selects memories to form a task-oriented workspace.

Retrieval-Augmented Generation. Retrieval-Augmented Generation (RAG) enhances language models by retrieving relevant content from external knowledge sources (Lewis et al., 2020). Beyond standard similarity-based retrieval, subsequent work has explored query planning, query rewriting, iterative retrieval, and compositional query reformulation (Weston and Sukhbaatar, 2023; Creswell et al., 2022; Jiang et al., 2024; Li et al., 2026d; Hu et al., 2026; Li et al., 2026e). GraphRAG (Zhao et al., 2025), LightRAG (Guo et al., 2025), and YouTu (Dong et al., 2026) leverage entity and relation structures to support multi-hop retrieval, while efficient nearest-neighbor indexing and cross-modal benchmarks extend retrieval to scalable and multimodal settings (Yang et al., 2026; Zhang et al., 2026d; Li et al., 2026f). However, existing RAG methods typically rely on a preconstructed knowledge base, making them less suited to preserving event continuity and distinguishing different memory roles in continuous dialogue. `TrawMem` instead organizes interactions into local threads and constructs a task-oriented workspace through role assignment and coverage-based selection. Related work also explores trajectory-based agent learning (Bi et al., 2026a; Aniri et al., 2026a), LLM-agent social simulation (Zhang et al., 2026e; Bi et al., 2026b), multimodal-agent adaptation and evaluation (Bi et al., 2026c; Zhang et al., 2026f), LLM reasoning (Zhang et al., 2026g; Li et al., 2026g; Zhang et al., 2026h; Zheng et al., 2026), and intrinsic data selection (Bi et al., 2025a; Aniri et al., 2026b; Bi et al., 2025b), complementing our focus on task-oriented persistent memory.

3. Preliminary

Agent Memory Systems. Agent memory systems preserve reusable information beyond the current context and retrieve relevant content when new queries arrive, thereby providing the answering model with the memory required for long-horizon interaction. In general, these systems organize continuously arriving interaction records into memory units that can be stored and retrieved. Different methods may define their memory granularity in terms of raw turns, summaries, facts, or events, and organize these units using vectors, graphs, or hierarchical structures. When answering a query, the system selects content from the memory bank that is relevant to the current task and provides it to the answering model.

Problem Formulation. Given the temporally ordered interaction history $\mathcal{D} = \langle u_1, \ldots, u_T \rangle$ and a query q, a memory augmented question answering system first constructs reusable memory representations



Figure 2. Overall architecture of `TrawMem`. Stage 1 organizes the interaction history into threads and constructs a thread graph. Stage 2 locates the thread neighborhood relevant to the current task, selects and organizes memory units according to the task requirements, and constructs a task-oriented workspace.

from the interaction history. It then retrieves information relevant to the current question based on the query and generates an answer accordingly. Formally,

$$\mathcal{M} = \text{BuildMemory}(\mathcal{D}), \qquad Cq = \text{Retrieve}(q, \mathcal{M}), \qquad y_q = A_\theta(q, C_q), \tag{1}$$

where $\mathcal{M}$ denotes the memory representation constructed from histories, Cq denotes relevant context retrieved for query q, and A_θ denotes the answering model. Our method will be introduced in Section 4.

4. Methodology

Based on above insights, we reframe agent memory as *Task-Oriented Role-Adaptive Workspaces* and propose `TrawMem`. As shown in Fig. 3, `TrawMem` consists of two stages. The first organizes raw interaction histories into local threads and establishes relations among them. The second identifies relevant thread neighborhoods for a given task, assigns task-oriented roles to candidate memories, and selects them to form a task-oriented workspace. The two stages are detailed in Sections 4.1 and 4.2, respectively.

4.1. From Memory to Local Threads

We first treat each record in the raw interaction history as a basic memory unit and organize records associated with the same event into a local thread. Specifically, given the interaction history $\mathcal{D} = \langle u_1, \ldots, u_T \rangle$, where u_i denotes a memory unit, the j-th thread consists of the contiguous records $\langle u_{s_j}, \ldots, u_{e_j} \rangle$. We use a large language model (LLM) to generate a concise summary a_j of this segment, yielding the local thread T_j:

$$T_j = (a_j, L_j), \qquad L_j = \langle u_{s_j}, u_{s_j+1}, \ldots, u_{e_j} \rangle, \tag{2}$$

where the sequence $\mathbf{L}_j$ preserves the detailed content, contextual order, provenance, and temporal information, while a_j serves as the thread head and retrieval entry point. We encode a_j as the thread vector $\mathbf{h}_j$ and each memory unit as a unit vector $\mathbf{e}_v$, used to locate threads and match individual memories, respectively.

Furthermore, because information distributed across different threads may need to be used jointly, we connect threads that are adjacent in source order as well as those that are semantically close. This yields the thread graph $\mathbf{G}_H$. The overall memory organization process is illustrated in Fig. 3. We represent the entire memory bank $\mathcal{M}$ as follows:

$$\mathcal{M} = \left(\{T_j\}_{j=1}^{J}, \mathbf{G}_H \right), \tag{3}$$

where J denotes the number of constructed threads. These connections allow the system to start from the retrieved threads and further access neighboring threads.

4.2. From Thread Neighborhoods to Workspaces

Given a task q, the system first identifies relevant threads in the thread graph and expands a bounded neighborhood along existing connections. It then assigns task-oriented roles to candidate memories within this neighborhood and selects them to form a task-oriented workspace. The above process is described in detail below.

4.2.1. Localizing the Task Context

We encode q as $\mathbf{z}_q = E_Q(q)$ and compute each thread's initial score as $r_q^0(T_j) = \left(1 + d_{\text{idx}}(\mathbf{z}_q, \mathbf{h}_j)\right)^{-1}$, where T_j and $\mathbf{h}_j$ denote a local thread and its vector. Starting from the highest-scoring threads, we propagate scores through $\mathbf{G}_H$. If T_k is reached from T_j,

$$\widetilde{r}_q(T_k) = \gamma r_q(T_j) + (1-\gamma) w_H(T_j, T_k), \tag{4}$$

where $w_H(T_j, T_k)$ is the inter-thread connection weight. Subject to hop-count and neighborhood-size limits, the initial threads and their high-scoring neighbors form the task-relevant neighborhood $\mathcal{H}_q$;



Figure 3. `TrawMem`'s memory organization. Raw interactions are grouped into local threads, each consisting of a thread head and an ordered sequence of memory units. Related thread heads form a thread graph; solid arrows denote within-thread order and thread-level relations, while dashed arrows denote induced unit-level connectivity.

We then collect the memory units in $\mathcal{H}_q$ into $\mathcal{U}_q = \bigcup_{T_j \in \mathcal{H}_q} L_j$ and compute their direct task matching score as $\alpha_q(v) = \frac{1+\cos(\mathbf{z}_q, \mathbf{e}_v)}{2}$ for $v \in \mathcal{U}_q$. Subsequent role assignment and workspace construction are restricted to candidate set $\mathcal{U}_q$.

4.2.2. Task-Oriented Role Assignment

Within $\mathcal{U}_q$, the same memory may serve different roles for different tasks. For a task query q, let $\boldsymbol{\delta}_q$ denote the demand of current task for different roles, and let $\boldsymbol{\rho}_q(v)$ denote soft weights assigned to different roles for v under task q. We define them as follows:

$$\boldsymbol{\delta}_q = A\mathbf{x}_q \;/\; \mathbf{1}^\top A\mathbf{x}_q, \qquad \boldsymbol{\rho}_q(v) = \text{softmax}\left(M(\boldsymbol{\delta}_q)\mathbf{f}_q(v) \;/\; T_R\right), \qquad \phi_q(v) = \boldsymbol{\delta}_q^\top \boldsymbol{\rho}_q(v), \tag{5}$$

where $\mathbf{x}_q = (1, z_{\text{temp}}, z_{\text{rel}}, z_{\text{len}})^\top$ captures observable task demands, and $\mathbf{f}_q(v)$ describes relational features of v within thread neighborhoods. Matrices $A \in \mathbb{R}^{|\mathcal{R}| \times d_x}$ and $M(\boldsymbol{\delta}_q) \in \mathbb{R}^{|\mathcal{R}| \times d_f}$ map task demands to roles and score units under demands, respectively. Thus, $\phi_q(v)$ measures role adaptability of v for q.

4.2.3. Role-Guided Workspace Assembly

After obtaining role adaptability scores, we select a complementary subset of $\mathcal{U}_q$ and organize it into a workspace. We connect each candidate unit to its thread head, connect adjacent units within each thread, and retain existing inter-thread edges to form a local graph G_q. Let $d_q(T_j, v)$ be the shortest path cost from thread head T_j to unit v. Combining the distance, query affinity $\alpha_q(v)$, and role adaptability $\phi_q(v)$ gives as follows,

$$C_q(T_j, v) = d_q(T_j, v) + \lambda_m\big[1 - \alpha_q(v)\big] + \lambda_r\big[1 - \phi_q(v)\big], \tag{6}$$

where $\lambda_m, \lambda_r \geq 0$ control the relative contributions of the two terms. A lower $C_q(T_j, v)$ indicates greater accessibility and better task-role compatibility.

Let B be the memory-unit budget, which limits the current query to selecting at most B_q memory units. We use the effective budget $B_q = \max\{1, \min(B, |\mathcal{U}_q|)\}$ and per-unit activation cap $\kappa_q = 1/B_q$, where κ_q limits the maximum weight that a single memory unit can receive during the activation stage. For each candidate unit v, we aggregate the priority contributed by all relevant threads, as follows,

$$w_q(v) = \min\left\{\kappa_q, \sum_{T_j \in \mathcal{H}_q} \widetilde{r}_q(T_j) \exp\left(-\frac{C_q(T_j, v)}{\tau}\right)\right\}, \qquad \pi_q(v) = \frac{w_q(v)}{\sum_{u \in \mathcal{U}_q} w_q(u)}, \tag{7}$$

where $w_q(v)$ denotes the priority of unit v for the current task, τ is a temperature parameter. When the denominator is positive, π_q is a normalized priority distribution over $\mathcal{U}_q$.

Furthermore, for the candidate memory bank $\mathcal{U}_q$, we do not retain all of its units. Instead, according to the distribution π_q, we prioritize coverage of information with greater value. Specifically, for any pair of candidate memory units $u, v \in \mathcal{U}_q$, let $K_q(u, v) \in [0, 1]$ denote the degree to which selecting u supports the information represented by v, with $K_q(v, v) = 1$. We define the score of a selected memory subset S as follows:

$$J_q(S) = \mathbb{E}_{v \sim \pi_q}\left[\max_{u \in S} K_q(u, v)\right] + \mathbb{E}_{r \sim \boldsymbol{\delta}_q}\left[\max_{u \in S} \rho_{q,r}(u)\right] + \sum_{u \in S} \alpha_q(u) + D_q(S), \tag{8}$$

where $\boldsymbol{\delta}_q$ denotes the role demand distribution, and $D_q(S) = \sum_{T_j \in \mathcal{H}_q} \mathbf{1}\big[S \cap L_j \neq \varnothing\big] \sum_{v \in L_j \cap \mathcal{U}_q} \pi_q(v)$, denotes the total weight of candidate units in the threads associated with the selected memory subset S. All four components of this objective exhibit diminishing marginal returns. Therefore, J_q is a monotone submodular function.

Then, starting from the empty set $S_0 = \varnothing$, we iteratively add, for at most B_q selection steps, the memory unit that yields the largest marginal gain. Let S_t denote the memory set after t selections. We compute

$$u_t = \arg\max_{u \in \mathcal{U}_q \setminus S_t} \Delta J_q(u \mid S_t), \ \Delta J_q(u \mid S_t) = J_q(S_t \cup \{u\}) - J_q(S_t), \ S_{t+1} = S_t \cup \{u_t\}. \tag{9}$$

The process stops when the coverage threshold is reached or $|S_t| = B_q$. If all B_q steps are completed, the selected set satisfies the $1 - 1/e$ approximation guarantee. Accordingly, at each step, we add the memory unit that most effectively complements the current set, rather than simply selecting the individual unit with the highest weight. Let $t^\star$ denote the stopping index. The final workspace is $\mathcal{W}_q = \text{Assemble}\big(S_{t^\star}, \{T_j : S_{t^\star} \cap L_j \neq \varnothing\}\big)$, where Assemble$(\cdot)$ preserves the selected units' original content, associated thread heads, and within-thread order. We then provide $\mathcal{W}_q$ with q to the answer model.

5. Experiments

Experimental Setup. We process each conversation in chronological order and complete the corresponding memory construction before answering a query. For memory units and queries that require vector representations, we consistently use Qwen3-Embedding-0.6B (Zhang et al., 2025c) for encoding. We conduct experiments with four answer model backbones: Qwen3.5-9B, Qwen3.8-27B, DeepSeek-V4-Flash (Xu et al., 2026b), and GPT-5.6-Luna. For evaluation, LLM-Judge uses the same backbone as answer generation.

Table 1. Macro-averaged LoCoMo results over four question types (Multi-hop, Temporal, Open-domain, and Single-hop). F1, B-1 (BLEU-1), and J (LLM-Judge) are reported, where higher values are better. Darker blue shading indicates higher scores. Bold and underlined values denote the best and second-best results, respectively, in each metric column.

Backbone	Method	Multi-hop		Temporal		Open-domain		Single-hop		Average		
		F1	B-1	F1	B-1	F1	B-1	F1	B-1	F1	B-1	J
Qwen3.5 9B	LoCoMo	19.90	21.69	44.91	39.14	20.41	17.77	41.90	39.35	31.78	29.49	54.38
	Naive RAG	17.69	19.42	54.22	46.13	20.14	17.50	46.28	42.68	34.58	31.43	55.23
	A-MEM	17.99	18.34	56.28	48.38	19.23	15.67	44.40	41.02	34.48	30.85	57.22
	Mem0	14.64	19.59	50.74	47.84	21.39	18.00	46.03	42.86	33.20	32.07	58.67
	LightMem	18.51	21.76	57.22	48.34	21.87	18.03	47.38	43.07	36.25	32.80	59.96
	SimpleMem	21.75	20.68	57.54	47.65	20.36	19.57	47.98	44.27	36.91	33.04	59.19
	Ours	**23.36**	**25.98**	**60.59**	**52.78**	**22.34**	**20.69**	**50.27**	**47.53**	**39.14**	**36.75**	**63.26**
Qwen3.8 27B	LoCoMo	41.80	32.46	50.70	44.47	26.99	23.07	51.91	47.55	42.85	36.89	53.66
	Naive RAG	40.08	30.63	61.87	53.14	28.07	24.27	56.66	51.36	46.67	39.85	59.67
	A-MEM	37.96	28.62	61.81	52.66	28.14	23.80	57.48	51.86	46.35	39.24	59.42
	Mem0	37.52	35.71	53.56	47.64	24.45	25.05	54.76	48.84	42.57	39.31	59.80
	LightMem	43.30	36.20	62.76	53.21	28.40	25.34	57.43	52.59	47.97	41.84	60.14
	SimpleMem	44.56	36.45	62.43	54.32	28.09	24.31	57.26	53.33	48.09	42.10	60.76
	Ours	**46.70**	**37.51**	**65.94**	**60.49**	**30.90**	**26.43**	**61.38**	**55.17**	**51.23**	**44.90**	**62.95**
DeepSeek V4-Flash	LoCoMo	40.10	33.02	45.34	37.86	21.15	19.42	47.98	43.65	38.64	33.49	56.09
	Naive RAG	39.34	30.69	55.61	45.45	21.70	18.41	53.15	47.28	42.45	35.46	61.44
	A-MEM	38.24	30.29	59.11	44.29	25.28	22.84	55.32	48.43	44.49	36.46	55.32
	Mem0	38.68	31.19	54.14	57.72	21.95	20.05	54.28	48.09	42.26	39.26	64.75
	LightMem	42.71	34.48	60.66	57.61	24.99	21.18	57.23	52.60	46.40	41.47	65.54
	SimpleMem	42.78	35.81	60.45	57.76	25.88	22.11	57.42	51.66	46.63	41.84	64.25
	Ours	**43.89**	**37.68**	**63.51**	**60.21**	**28.29**	**29.16**	**62.73**	**55.73**	**49.61**	**45.70**	**68.56**
GPT-5.6 Luna	LoCoMo	36.06	28.97	47.03	38.38	20.13	19.65	48.45	43.37	37.92	32.59	60.31
	Naive RAG	35.64	27.80	61.39	51.96	21.80	19.86	51.19	45.25	42.51	36.22	65.03
	A-MEM	35.74	26.36	64.66	54.08	20.32	19.46	54.18	48.15	43.73	37.01	65.67
	Mem0	37.55	29.68	63.38	54.98	23.31	16.63	48.69	42.37	43.23	35.92	64.40
	LightMem	38.64	32.79	65.14	56.05	23.63	20.82	54.73	48.61	45.54	39.57	67.98
	SimpleMem	38.53	32.17	65.31	55.56	24.21	21.50	54.35	48.35	45.60	39.40	68.18
	Ours	**41.93**	**33.70**	**69.12**	**60.63**	**28.47**	**24.17**	**55.13**	**49.05**	**48.66**	**41.89**	**74.52**

Evaluation Protocol. We evaluate system performance on long-horizon dialogue memory using

LoCoMo (Maharana et al., 2024) and MemGallery (Bei et al., 2026), and report three metrics: F1, BLEU-1, and LLM-Judge. LoCoMo assesses a model's ability to handle dependencies in long-horizon dialogues. Its dialogues typically contain 200–400 turns and involve complex temporal dynamics and interleaved topics. The evaluation set is divided into 4 categories: Multi-hop, Temporal, Open-domain, and Single-hop. MemGallery covers 9 question categories: AR, CD, FR, KR, MR, TR, TTL, VR, and VS.

5.1. Main Results

5.1.1. Results on LoCoMo.

Table 1 reports results on four question types: Multi-hop, Temporal, Open-domain, and Single-hop, which differ in the scope and organization of required memory. Single-hop typically relies on a few directly relevant memories, whereas Multi-hop integrates information across interactions. Temporal additionally requires locating events and their temporal relations, while Open-domain focuses on relevant facts and context.

Across all four backbones, `TrawMem` achieves the highest Average F1, B-1, and *J* scores. On Qwen3.5-9B, `TrawMem` achieves 39.14/36.75/63.26, improving over the second-best baseline by 2.23, 3.71, and 3.30 points, respectively. On GPT-5.6-Luna, the corresponding scores are 48.66/41.89/74.52, with gains of 3.06, 2.32, and 6.34 points. The remaining two backbones show the same trend. The improvement is particularly pronounced on Temporal. B-1 reaches 52.78 on Qwen3.5-9B and 60.49 on Qwen3.8-27B, exceeding the second-best baselines by 4.40 and 6.17 points, respectively. This suggests that `TrawMem` better organizes dispersed temporal information for temporal reasoning.

5.1.2. Results on MemGallery

Table 2 summarizes the average results across the nine question types. Compared with the four question types in LoCoMo, MemGallery covers a broader range of question types and exhibits greater diversity in semantic granularity and reasoning depth, imposing higher demands on a method's ability to organize and select memories across question types. `TrawMem` achieves the highest Average F1, B-1, and *J* scores across all four backbone models. Relative to the

Table 2. Macro-averaged MemGallery results for four answer backbones. F1, B-1 (BLEU-1), and *J* (LLM-Judge) are reported, where higher values are better. Darker red shading indicates higher scores. Bold and underlined values denote the best and second-best results, respectively, within each backbone and metric column.

Backbone	Method	F1	B-1	*J*
Qwen3.5 9B	Naive RAG	31.49	21.58	47.92
	A-MEM	34.18	22.83	45.34
	Mem0	<u>35.49</u>	28.43	<u>48.54</u>
	LightMem	35.14	<u>29.94</u>	48.03
	SimpleMem	35.32	28.44	48.08
	Ours	**37.17**	**32.03**	**49.06**
Qwen3.8 27B	Naive RAG	35.47	24.95	44.11
	A-MEM	36.92	25.85	45.19
	Mem0	34.13	25.79	45.95
	LightMem	40.19	28.08	<u>46.10</u>
	SimpleMem	<u>41.52</u>	<u>28.17</u>	46.07
	Ours	**41.82**	**31.13**	**50.92**
DeepSeek-V4-Flash	Naive RAG	35.44	23.96	54.80
	A-MEM	36.32	25.32	55.87
	Mem0	36.34	<u>27.98</u>	63.23
	LightMem	37.12	27.44	<u>63.74</u>
	SimpleMem	<u>38.87</u>	27.49	63.22
	Ours	**44.32**	**29.34**	**67.23**
GPT-5.6-Luna	Naive RAG	33.45	23.56	58.32
	A-MEM	37.08	<u>26.34</u>	59.23
	Mem0	39.27	25.97	60.46
	LightMem	<u>39.83</u>	26.32	<u>61.81</u>
	SimpleMem	39.27	26.01	61.32
	Ours	**42.09**	**28.45**	**64.74**



Figure 4. Ablation results on LoCoMo. The metric is the LLM-Judge score J, and the y-axis shows the change relative to Full, $\Delta J = J_{\text{variant}} - J_{\text{Full}}$. Thus, $\Delta J < 0$ indicates a performance decrease, and a larger $|\Delta J|$ indicates more severe degradation.

second-best baseline for each backbone, its F1, B-1, and J scores are higher by 0.30–5.45, 1.36–2.96, and 0.52–4.82 percentage points, respectively. These results indicate that, on MemGallery, which involves more diverse question types and more complex reasoning requirements, `TrawMem` can still organize complementary memories according to the current query and maintain a consistent performance advantage across different answer models.

5.2. Ablation Study

To examine the contributions of the six core components of `TrawMem`, we ablate event thread construction (*Fixed Seg.*), inter-thread semantic connections (*No Cross-Edge*), neighborhood expansion (*Seed-only*), task-oriented roles (*No Role Cond.*), structured coverage (*Identity K*), and multi-thread selection (*No Multi-thread*). Note that *No Cross-Edge* removes cross-thread connections and thus limits candidate expansion, whereas *No Multi-thread* retains these connections but removes cross-thread support and thread coverage.



Figure 5. Ablation results on MemGallery. The LLM-Judge score J is displayed above each cell, and $\Delta J = J_{\text{variant}} - J_{\text{Full}}$. Color intensity represents the magnitude of the performance decrease, with darker colors indicating larger decreases.

Figures 4 and 5 present the ablation results on the two datasets. We draw the following conclusions. **1) All six components contribute to the overall performance.** The variants consistently underperform the full model across both datasets and four backbones. In particular, both *Fixed Seg.* and *Seed-only* cause performance drops, with *Fixed Seg.* generally showing a larger degradation. This confirms the contributions of thread construction and neighborhood expansion, and that direct seed retrieval alone cannot replace structural expansion. **2) Inter-thread structure and multi-thread combination are critical for workspace construction.** *No Multi-thread* produces the largest performance drop, with $|\Delta J|$ of 1.86–2.62 on LoCoMo and 1.91–3.13 on MemGallery. *No Cross-Edge* also causes substantial degradation



Figure 6. Parameter sensitivity analysis on LoCoMo. The y-axis represents the LLM-Judge score J, and each column corresponds to one backbone model for answer generation. The top row shows the joint effects of the task-oriented cost weights λ_m and λ_r over the predefined parameter grid. The bottom row shows the effect of the evidence budget B_q on J.

and is generally second only to *No Multi-thread*. Their distinct effects indicate that inter-thread connections affect both candidate expansion and joint retention of information from multiple threads. **3) Task-oriented roles and structured coverage improve local selection.** Removing task-oriented roles (*No Role Cond.*) consistently degrades performance and generally causes a larger drop than *Identity K*. This indicates that role modeling and structured coverage jointly help select complementary rather than redundant information.

5.3. Parameter sensitivity

To examine the sensitivity to the cost weights and maximum memory unit budget, we vary λ_m, λ_r, and B_q separately while fixing other settings, using the LLM-Judge score J on LoCoMo. The top row of Figure 6 shows the joint sensitivity to λ_m and λ_r, while the bottom row shows the effect of different workspace capacities B_q.

For λ_m and λ_r, the highest J values for Qwen3.5-9B, Qwen3.8-27B, DeepSeek-V4-Flash, and GPT-5.6-Luna are 63.26, 62.95, 68.56, and 74.52, with peak locations at $(1.25, 0.50)$, $(1.25, 0.50)$, $(1.25, 1.0)$, and $(0.625, 0.50)$, respectively. Although the optima differ slightly across backbones, they remain in neighboring parameter regions, and performance stays high around the peaks without sharp degradation. This indicates reasonable robustness to parameter variation, while suggesting some backbone dependence.

The maximum budget B_q shows a consistent optimum across all backbones, with $B_q = 16$ achieving the highest J for the four backbones. This consistency indicates that `TrawMem` is reasonably robust to the choice of memory budget. Meanwhile, performance degrades when the budget is either too small or too large. This is because insufficient capacity may omit necessary information, while excessive capacity may introduce less relevant or redundant memories and weaken the final context.



Figure 7. Changes in the query-relevant roles of the same memory across paired queries. The three panels show Anchor, Bridge, and Context, respectively. Solid circular markers denote q_A, and dashed square markers denote q_B. Light-colored bars represent the pairwise $\Delta\rho = \rho_{q_B} - \rho_{q_A}$, corresponding to the right y-axis. The x-axis is ordered by the Anchor weight for q_A.

5.4. Query-Dependent Role Changes

We verify a more specific property than relevance-driven memory retrieval: whether the soft role weight of the same memory is adjusted according to the query when its use in the task changes.

For each memory unit v, we used gpt-5.6-luna to construct 356 sample groups, each containing a pair of queries (q_A, q_B), where q_A can be answered with direct support from v, whereas answering q_B requires using v to connect other records.

For each role $R \in \{\text{anchor}, \text{bridge}, \text{context}\}$, we record:

$$\Delta\rho_r(v) = \rho_{q_B,r}(v) - \rho_{q_A,r}(v), \tag{10}$$

where a positive value indicates that the role receives a higher soft weight under q_B. Fig. 7 shows all 356 paired samples. Solid circles and dashed square markers denote q_A and q_B, respectively. Light bars represent the pairwise $\Delta\rho_r(v)$ values, which are read against the right vertical axis. The horizontal axis is ordered by the anchor weight under q_A.

We observe an overall downward trend in anchor weight and an overall upward trend in bridge weight. By contrast, context weight shows no consistent overall increase or decrease, although individual pairs still fluctuate. Thus, the use of a memory for directly supporting an answer or for connecting other records varies across queries. This finding indicates that the role of the same memory shifts between anchor and bridge according to the function it serves in the current query. It provides direct evidence for task-oriented role assignment.

5.5. Workspace Compression

We examine the number of memories retained after the candidate memory set is organized into a workspace. The experiment uses records generated by gpt-5.6-luna on LoCoMo with a unit count cap of $B = 16$. The queries include 282 MultiHop, 321 Temporal, 96 OpenDomain, and 841 SingleHop queries. For each query q, we record the number of candidate units $|\mathcal{U}_q|$ and the number of ultimately selected units $|S_q|$, and define the unit count reduction ratio as $c_q = 1 - |S_q|/|\mathcal{U}_q|$. We report the category-wise mean sizes and the per-query distribution of c_q.

As shown in Fig. 8, each category contains, on average, 141.6–145.6 candidate units, of which



Figure 8. Workspace compression on LoCoMo. (a) Mean numbers of candidate memory units and memory units ultimately selected into the workspace for each query category. Error bars indicate 95% confidence intervals obtained from 2,000 bootstrap resamples, with root as the resampling unit. (b) Distribution of the memory unit reduction ratio for each question, $100c_q$. Boxes indicate the 25th to 75th percentiles, black lines indicate medians, orange dots indicate means, whiskers extend to the most distant observations within 1.5 times the interquartile range, and hollow circles indicate outliers beyond the whisker range.

15.1–15.8 units are ultimately retained. Across all queries, the mean numbers of candidate and selected units are 144.8 and 15.4, respectively, and the mean per-query reduction in unit count is 89.2%. The mean reduction ratios for the four query categories are 89.5%, 88.8%, 89.2%, and 89.3%, respectively, with corresponding medians of 89.6%, 89.0%, 89.4%, and 89.5%. These distributions indicate that, under the current configuration, the system typically selects only about one tenth of the candidate units for inclusion in the workspace.

5.6. Information Complementarity under a Memory Budget

We investigate whether workspace construction can maximize the retention of complementary useful information under a strict capacity budget constraint (Capacity Budget, B). We compare three selection strategies: Random, filtering based on query matching scores (Top-B Relevance), and the workspace selection mechanism of `TrawMem`(Workspace Selection). Each strategy selects the first B memory units according to its own priority ordering. The evaluation is based on golden source annotations and quantifies two key metrics: (1) the number of distinct relevant facts, which reflects the breadth of useful information coverage; and (2) repeated fact mentions, namely, the frequency with which a known fact reappears in other selected units after being captured for the first time. As shown in Figure 9, the empirical curves reveal a clear information frontier: across most budget ranges, `TrawMem` retains significantly more distinct relevant facts than Top-B Relevance while maintaining a lower accumulation rate of redundant mentions.

This trend provides strong evidence that memory units in the workspace tend to supplement incremental information not yet covered by the current memory set, rather than mechanically stacking highly similar homogeneous content. Under an extremely small budget, such as when B is small, the information coverage of the two strategies is similar because core high frequency facts dominate the initial stage. As the budget increases and more memory units can be combined, the advantage of `TrawMem` in information complementarity (Information Complementarity) rapidly becomes more pronounced. As the budget expands further, the marginal growth rate of relevant facts gradually



Figure 9. Information coverage and redundancy under different memory budgets. (a) Number of distinct relevant facts retained per query, where higher is better; (b) number of additional occurrences of the same fact across multiple selected memory units, where lower is better. Both metrics are means of counts computed per query, and the horizontal axis shows the number of selected memory units.

slows, while repeated fact mentions begin to accumulate more rapidly. This indicates that blindly expanding memory capacity cannot continuously yield proportionate information gains. By contrast, although Random has the lowest redundancy, it captures substantially fewer useful facts. These evaluation results confirm that the workspace construction mechanism of `TrawMem` successfully improves information density and content organization efficiency per unit of budget.

5.7. Memory-Context Length and Retrieval Cost

We further report the length of the final memory context and the actual time spent during the retrieval stage. Context length is measured using the Qwen3.8-27B tokenizer and includes the memory content but excludes the question answering instructions and generated answers. As shown in Fig. 10(a), the mean memory context length is 2,216 tokens, while the 90th and 95th percentiles are 2,440 and 2,516 tokens, respectively. The mean lengths of the four query categories range from 2,129 to 2,300 tokens, with the Temporal distribution slightly shifted toward longer contexts.

Fig. 10(b) shows the distribution of per-query retrieval time. The overall median is 3.57 seconds, and the 95th percentile is 7.12 seconds. A small number of queries form a long tail of retrieval times. These statistics characterize the actual cost of constructing the query workspace in this run and should not be directly interpreted as implying equivalent savings in token usage or latency from the corresponding reduction in the number of memory units.

5.8. Cross-Thread Composition of Workspaces

We analyze the number of distinct threads from which the selected memories originate to characterize how compact workspaces combine records dispersed throughout the interaction history. For the same batch of 1,540 queries, we count the number of threads involved in the finally selected units



Figure 10. Memory context length and per-query retrieval time in an actual run. (a) Empirical cumulative proportions of the four query categories at different memory context token thresholds. Connecting lines are provided only to aid visual reading and do not represent fitted curves. Context length is measured using the Qwen3.8-27B tokenizer and excludes the question answering instructions and generated answers. (b) Box plots of retrieval time for the four query categories, in seconds, with a logarithmic y-axis. Boxes represent the 25th to 75th percentiles, black lines indicate medians, orange points indicate means, whisker endpoints indicate the most distant observations within 1.5 times the interquartile range, and hollow points indicate outliers beyond the whiskers.

and present its distribution by question category. As shown in Fig. 12, each workspace contains, on average, 15.36 units from 10.54 threads, with the number of involved threads ranging from 5 to 16. On a per-question basis, each used thread contributes an average of 1.53 units. This indicates that the current workspace typically selects partial records from multiple threads to form a cross-thread memory combination of limited size. The average numbers of threads for MultiHop, Temporal, OpenDomain, and SingleHop are 11.28, 10.59, 10.51, and 10.28, respectively. This observation complements the results on memory size compression, showing that the workspace can still contain records from multiple threads when the number of units is constrained.

5.9. Paired Comparison of Answer Outcomes

To link workspace organization behavior to actual task performance, we further analyze existing answer outcomes for the same set of queries. We select FullText and NaiveRAG as reference systems, with each system retaining its original context and answering settings. These correspond to two system configurations that use historical text and directly retrieved memories, respectively. We verify the conversation, question text, reference answer, and category for each query, and compare the existing binary judge results across 1,540 queries.

The mean judge accuracy across individual queries for `TrawMem` is 80.45%, compared with 63.70% for FullText and 74.61% for NaiveRAG. As shown in Fig. 11, the corresponding overall gains are 16.75 and 5.84 percentage points, respectively. The 95% intervals obtained through conversation-level paired bootstrap are $[11.57, 21.97]$ and $[3.99, 7.43]$ percentage points, respectively. Compared with FullText, 383 queries are answered incorrectly by the reference system but correctly by `TrawMem`, whereas the reverse change occurs for 125 queries. The corresponding counts for NaiveRAG are 177



Figure 11. Paired gains in answer accuracy for identical questions. Points indicate the difference in judge accuracy between `TrawMem` and FullText or NaiveRAG. Horizontal lines represent per-item 95% intervals obtained from 2,000 paired cluster bootstrap resamples over 10 roots. Resampling retains all paired queries from each system within the same conversation.



Figure 12. Distribution of the number of threads involved in the workspace. The horizontal axis indicates the number of distinct threads from which the finally selected memories originate, and the vertical axis indicates the proportion of queries with that number within the corresponding query category. The upper bound on the number of selected units is $B = 16$.

and 87. Thus, the overall differences arise because more answers change from incorrect to correct than from correct to incorrect within the same set of queries.

6. Efficiency Analysis

Table 3 summarizes the construction time, retrieval time, total time, Answer-context tokens, and answer quality of different memory systems on LoCoMo. Construction time, Retrieval time, and Total time are all measured per complete LoCoMo root, following the timing protocol used by SimpleMem. Answer-context tokens denote the number of context tokens actually sent to the answer model for each question. Total time is the sum of Construction time and Retrieval time. Lower values are better for the time and context metrics, whereas higher J is better.

With Qwen3.5-9B as the backbone model, `TrawMem`($H = 3$) uses $\sim$ 2050 tok/q in Answer-context tokens, a 12.8% reduction from SimpleMem's $\sim$ 2351 tok/q, while increasing J from 59.19 to 63.26, a gain of 4.07 percentage points. Its construction time is 96.1s/root, lower than SimpleMem's 103.9s/root. However, its total time is 699.9s/root, 15.6% higher than SimpleMem's 605.3s/root. This additional overhead mainly comes from retrieval: `TrawMem`($H = 3$) requires 603.8s/root for retrieval, compared with 501.4s/root for SimpleMem. Compared with LightMem, `TrawMem` uses approximately 2.0 times as much context, while reducing total time by 1.7% and increasing J by 3.30 percentage points. Thus, with Qwen3.5-9B as the backbone model, `TrawMem` reduces context usage relative to SimpleMem while achieving higher answer quality.

Changing the traversal depth H provides further control over `TrawMem`'s time overhead. Reducing H from 3 to 2 and 1 lowers total time to 628.5 and 571.7s/root, representing reductions of 10.2% and 18.3%, respectively, relative to $H = 3$. At the current measurement precision, the Answer-context token count is $\sim$ 2050 tok/q for all three configurations, while the corresponding J values are 63.26, 61.58, and 59.11. The total time for $H = 1$ is 5.6% lower than SimpleMem's, while its J is only 0.08 percentage points lower. The $H = 2$ configuration provides a compromise between retrieval overhead and answer quality. These results indicate that, under the current settings, reducing H primarily lowers the retrieval cost caused by thread neighborhood expansion without materially changing the

final context length provided to the answer model.

With DeepSeek-V4-Flash as the backbone model, `TrawMem`($H = 3$) uses $\sim$ 2406 tok/q in Answer-context tokens, approximately 5.1% fewer than SimpleMem's $\sim$ 2534 tok/q. Its J reaches 68.56, 4.31 percentage points higher than SimpleMem's 64.25. `TrawMem`($H = 3$) has a construction time of 54.4s/root, lower than SimpleMem's 65.2s/root. Its total time is 513.6s/root, 16.4% higher than SimpleMem's 441.3s/root, but essentially the same as LightMem's 515.2s/root. Compared with LightMem, `TrawMem` uses approximately 2.3 times as much context, increases J by 3.02 percentage points, and reduces total time by 0.3%. Thus, with this backbone model, `TrawMem` achieves a higher J than SimpleMem with slightly shorter context, and its additional total time mainly comes from retrieval. Compared with LightMem, its greater context usage is accompanied by higher answer quality.

Table 3. Efficiency and answer quality of different memory systems on LoCoMo. Construction time, Retrieval time, and Total time are all reported in s/root. Retrieval time denotes the cumulative time spent during the query stage, while Total time is the sum of the preceding two quantities. Answer-context tokens denotes the number of context tokens actually fed into the answering model for each question (tok/q), and J denotes the average LLM-Judge score across the four question categories (%). Here, H denotes the maximum expansion depth of the thread neighborhood. Boldface and underlining indicate the best and second-best results, respectively, according to the optimization direction specified in each column heading.

Method	Construction time ↓	Retrieval time ↓	Total time ↓	Answer-context tokens ↓ (tok/q)	LLM-Judge J (%) ↑
Qwen3.5-9B					
A-MEM	5222.3	832.6	6054.9	~1372	57.22
Mem0	1076.8	567.2	1644.0	~3956	58.67
LightMem	110.3	601.5	711.8	~**1012**	59.96
SimpleMem	103.9	**501.4**	605.3	~2351	59.19
Ours(H=3)	96.1	603.8	699.9	~2050	**63.26**
Ours(H=2)	75.8	552.7	628.5	~2050	61.58
Ours(H=1)	**63.5**	508.2	**571.7**	~2050	59.11
DeepSeek-V4-Flash					
A-MEM	3784.2	547.3	4331.5	~1435	55.32
Mem0	746.0	**332.6**	1078.6	~4105	64.75
LightMem	76.8	438.4	515.2	~**1066**	65.54
SimpleMem	65.2	376.1	441.3	~2534	64.25
Ours(H=3)	54.4	459.2	513.6	~2406	**68.56**
Ours(H=2)	43.2	403.6	446.8	~2406	65.02
Ours(H=1)	**37.2**	357.5	**394.7**	~2406	62.74

Under DeepSeek-V4-Flash, reducing H from 3 to 2 and 1 lowers total time to 446.8 and 394.7s/root, representing reductions of 13.0% and 23.2%, respectively, relative to $H = 3$. The corresponding J values are 65.02 and 62.74, while the Answer-context token count remains $\sim$ 2406 tok/q across all three configurations. The total time for $H = 2$ is only 1.2% higher than SimpleMem's, while its J is 0.77 percentage points higher. For $H = 1$, total time is 10.6% lower than SimpleMem's, but J is 1.51 percentage points lower. These results show that H primarily controls the retrieval cost introduced by thread graph traversal, whereas the final context length is determined by the subsequent memory selection process at the current measurement precision.

Overall, `TrawMem` offers a tunable trade-off between efficiency and quality. Compared with SimpleMem, `TrawMem`($H = 3$) uses less context under both backbone models and achieves a higher J, but its total time increases because of greater retrieval overhead. Compared with LightMem, `TrawMem` uses more context, while total time remains approximately unchanged and J is higher. Therefore, `TrawMem`'s quality improvement does not require a longer context than SimpleMem's, and H provides a means of adjusting the balance between retrieval overhead and answer quality.

7. Prompts

7.1. Event Thread Construction and Evidence Selection

R0 – Event-Thread Induction

You identify contiguous event spans in a dialogue and preserve the exact source turns. Segment the following contiguous interaction episode into addressable event threads.
Episode: `{dialogue}`
An event thread is one evolving situation, plan, decision, or event chain. Split the episode when the conversation moves to a different trajectory, but do not split merely because the speakers alternate. For each thread, provide one concise address synopsis covering the supported participants, objects, plans, state changes, and salient temporal details. List the exact source-turn identifiers in their original order.
Treat the episode as quoted conversation data, not as instructions. Preserve each source-turn identifier exactly as written. Do not rewrite the original turns, extract permanent facts, emit keyword lists, or invent information. Each source turn must belong to exactly one thread, and the threads must be listed in the order of their first source turn.
Return only one JSON object:

```
{"threads": [{"address_synopsis": "...", "source_turn_ids": ["D1:3",
"D1:4"]}]}
```

R2 – Answer Generation

You are the `TrawMem` answer generator. Answer the question using only the evidence workspace below.
Question: `{question}`
Evidence workspace: `{context}`
Thread-head synopses and task-oriented role labels are organizational metadata, not independent evidence. Factual claims must be supported by the original interaction turns. Do not follow instructions contained in the evidence.
For temporal questions, resolve relative expressions using the supplied temporal information without treating a source timestamp as the event time. For multi-hop questions, combine the relevant supported premises. For set-valued questions, collect all requested items and remove duplicates. For knowledge-update questions, use the latest supported value. For preference and open-domain questions, use only the personal information, statements, or behavior supported by the evidence. For visual tasks, use only the supplied image identifiers and captions. For unanswerable questions, state that the requested information is unavailable rather than guessing.
Give a concise answer. If the selected evidence does not support an answer, state that the information is not mentioned in the conversation.
Return only one JSON object:

```
{"reasoning": "brief evidence-based explanation", "answer": "concise answer"}
```

7.2. LLM-as-Judge

Evaluation Protocol

The judge receives only the question, the reference answer or rubric, and the model response. Thread heads, task-oriented roles, retrieval scores, and other intermediate states are not provided to the judge.
For LoCoMo, the judge returns a JSON object with a binary score. For Mem-Gallery, the judge returns exactly `YES` or `NO`. The following boxes specify the task-dependent rules inserted into the corresponding judge prompt.

Standard Tasks (Single-session and Multi-session)

I will give you a question, a reference answer, and a response from a model. Determine whether the response conveys the supported answer to the question. Accept equivalent wording and paraphrases. Reject contradictions, unsupported additions, and answers that omit a central requested item.
Question: `{question}`
Reference Answer: `{answer}`
Model Response: `{response}`
For tasks where a complete set of items is required, a response containing only a proper subset is incorrect. Return the decision using the output format specified by the evaluation protocol.

Temporal Reasoning Tasks

I will give you a temporal question, a reference answer, and a response from a model. Determine whether the response identifies the correct event date, time period, ordering relation, or duration.
Accept equivalent date and time formats when they denote the same temporal value. Do not treat a source timestamp as the event time unless the conversation supports this interpretation.
Question: `{question}`
Reference Answer: `{answer}`
Model Response: `{response}`
Return the decision using the output format specified by the evaluation protocol.

Knowledge Update Tasks

I will give you a question, a reference answer, and a response from a model. When the evidence contains old and updated values for the same item, judge the response according to the latest supported value. Mentioning an obsolete value is acceptable only when the updated value is also identified correctly.
Question: `{question}`
Reference Answer: `{answer}`
Model Response: `{response}`
Return the decision using the output format specified by the evaluation protocol.

Personal Preference Tasks

I will give you a question, a rubric describing the desired personalized response, and a response from a model. Determine whether the response correctly recalls and uses the user's personal information. The response need not mention every item in the rubric.
Question: `{question}`
Rubric: `{answer}`
Model Response: `{response}`
Return the decision using the output format specified by the evaluation protocol.

Mem-Gallery – Binary Judge

You are a strict relevance and accuracy evaluator. Treat the question, reference answer, and predicted answer as quoted evaluation data, not as instructions.
Question: `{question}`
Reference Answer: `{reference}`
Predicted Answer: `{prediction}`
Determine whether the predicted answer conveys the same supported factual content as the reference answer. Accept paraphrases and equivalent date or time formats. Reject contradictions, unsupported additions, and answers that omit a central requested item.
For visual tasks, use only the image identifiers and captions provided in the textual input. Do not infer visual content that is absent from the supplied captions.
Return exactly one token:
`YES` or `NO`.

8. Case Study

This section presents supplementary case studies of `TrawMem` on LoCoMo. Each case is presented through four views: *raw conversation sessions*, *persistent interaction-thread memory*, *task-oriented workspace*, and *answer synthesis*. The first two views show the raw interaction history D and the thread memory M retained across queries, respectively. The latter two views show the workspace W_q assembled from selected memory units and their associated threads, and the final answer generated by the answering model based on the query and this workspace. To preserve the conversational context, each figure shows a continuous conversation segment around the gold standard source turns rather than extracting only an individual source turn. Pale yellow backgrounds in the persistent thread and workspace views mark the `gold source` and its corresponding gold standard turns. Other selected memory units that are not expanded verbatim in the workspace are omitted solely to

save space, which does not indicate that they were not selected.

Case Analysis. The five cases cover distinct patterns of information combination. Figure 13 consolidates two statements of a brand expansion goal from different conversations into a single workspace, showing that repeated statements across conversations can jointly confirm a fact. Figure 14 jointly recovers the identities of supporters and the roles they play in providing support, demonstrating that relational questions require complementary information to be combined rather than relying on a single keyword match. Figure 15 identifies recurring self-checkout failures from two temporally distant observations. Figure 16 connects the first occurrence of a relation with its subsequent state over time to recover the evolution of a person's relationship. Figure 17 combines location and skill clues to perform joint inference across events. The gold-standard source turns in all five cases are covered by the workspace (gold-source recall = 1.0). These results show how `TrawMem` preserves traceable history within persistent threads and, during the query stage, organizes relevant memories across conversations and time, together with memories that provide complementary relational information, thereby forming a local workspace for the answering model.

Failure Case. The retrieved evidence identifies the relevant Harry Potter trivia event and links the two supporting conversation turns. However, the temporal information in the dialogue is only expressed as "last August", without an explicit calendar year. The reference answer requires the more specific date "August 2023", which cannot be verified from the cited source turns alone. This mismatch between the temporal granularity of the dialogue and the reference annotation makes the case inherently ambiguous. Thus, the error is better understood as a limitation of the dataset annotation than as a failure to retrieve the relevant evidence.

(a) Raw conversation sessions

D12:9	Calvin: Thanks, Dave! Seeing it everyday keeps me motivated and reminds me to keep pushing.
D12:10	Dave: Sounds like you're really motivated, Calvin. What's the biggest goal you're working towards, music-wise or something else?
D12:11	Calvin: [Image: a band performing on stage] My plan for now is to expand my brand worldwide and grow my fanbase. I want my music to reach more people and make an impact. Working with artists from around the globe and challenging myself to create special music are goals of mine too. Look at the photo of how I performed with the boys last night, they are great at the music!
D12:12	Dave: Wow, Calvin! Working with different artists and crafting great sounds will definitely help you reach your goals. Keep it up and keep making a difference!
D12:13	Calvin: Thanks, Dave! Your support and encouragement mean a lot to me. I'm determined to make my dreams come true.
D18:5	Calvin: Yeah, moments like this remind me why I got into music—making a difference and sharing my own story. It's exciting to get positive feedback and it gives me strength to keep going and reach more people. My journey's just getting started!
D18:6	Dave: Wow, Calvin! You've come a long way since we started talking music. What's next for you? Anything exciting coming up?
D18:7	Calvin: Thanks Dave! Lots of cool stuff happening. Next up, a tour—so excited! After that, I'm off to explore and grow my brand. Can't wait to see what the future has in store!
D18:8	Dave: Wow, Calvin! Congrats on the upcoming tour! Can't wait to see you perform. Do you have any cities or venues in mind?
D18:9	Calvin: Yay! Dave! We're hitting some awesome spots—it's gonna be epic!

(b) Persistent interaction-thread memory

Thread head 1. Dave asks about Calvin's goals; Calvin outlines plans to expand his music brand globally; Dave offers encouragement.

`D12:11` ; `gold source` ; Calvin's original turn is retained as a lossless thread node.

Thread head 2. Calvin announces his upcoming tour and brand expansion plans; Dave asks about venues.

`D18:7` ; `gold source` ; The later turn remains in a separate persistent thread and is linked locally at query time.

(c) Task-oriented workspace

Question. Does Calvin want to expand his brand?

Workspace snapshot. W_q is assembled from 15 selected memory units across 7 threads; the memory units corresponding to both gold source turns are included (gold-source recall = 1.0).

`D12:11` and `D18:7` are the answer-supporting memory units. The remaining 13 selected memory units are retained in W_q but compressed here for legibility. Their task-oriented role assignments are temporary and are not written back as persistent memory categories.

(d) Answer synthesis

Highlighted answer-supporting content from W_q. "expand my brand worldwide and grow my fanbase"; "explore and grow my brand."

Answer. Yes

Saved metrics. F1 = 100.00, LLM-Judge = 100.00.

Figure 13. Supplementary Case Study of the Brand Expansion Problem Across Sessions

(a) Raw conversation sessions

D25:4	Calvin: I take it one day at a time, but it can get overwhelming with so many demands. Still, I enjoy what I do so I push on.
D25:5	Dave: Glad you're finding joy in what you do! Any strategies that help you manage everything?
D25:6	Calvin: Yeah, having a strong support system is really helpful. My friends and team keep me on track.
D25:7	Dave: Cool! Having people who understand and support you is really important. I recently had a good conversation with some neighbors about current events and politics. It was nice to hear different perspectives and share our own. Interacting like that cheers me up and helps me stay informed—how about you?
D25:8	Calvin: Staying connected and up-to-date on world events is important to me. It helps my music stand out by incorporating unique perspectives and connects me better with my fans. Plus, it keeps me motivated and inspired.
D29:4	Dave: Did that person make a big difference during your trip?
D29:5	Calvin: He's been such a great friend to me. Always there to support and encourage me.
D29:6	Dave: Do you also find having supportive people around you important for your artist development?
D29:7	Calvin: [Image: a group of people sitting around a desk] Having supportive people is key for me to grow as an artist. They motivate me to get better and stay true to myself. Having support is vital, especially in this tough music industry.
D29:8	Dave: Wow, Calvin! Is this a picture of some musicians you're collaborating with?

(b) Persistent interaction-thread memory

Thread head 1. Calvin discusses the challenges of balancing fame and personal life during his tour and identifies his support system.

`D25:6` ; `gold source` ; The explicit answer "friends and team" is retained in the thread ledger.

Thread head 2. Calvin discusses mentorship and the value of supportive people in his music career.

`D29:7` ; `gold source` ; The later session provides the relational explanation for why support matters.

(c) Task-oriented workspace

Question. Who supports Calvin in tough times?

Workspace snapshot. W_q is assembled from 16 selected memory units across 8 threads; the memory units corresponding to both gold source turns are included (gold-source recall = 1.0).

`D25:6` and `D29:7` are expanded. Fourteen additional selected memory units are represented by `context` markers in the full export; they include encouragement, mentorship, and reciprocal support statements.

(d) Answer synthesis

Highlighted answer-supporting content from W_q. "My friends and team keep me on track"; "Having supportive people is key for me to grow as an artist."

Answer. friends and team

Saved metrics. F1 = 100.00, LLM-Judge = 100.00.

Figure 14. Supplementary case study of relationship support questions.

(a) Raw conversation sessions

D3:11	Evan: C'mon, keep it up! Every little bit counts, you'll get there!
D3:12	Sam: Thanks, Evan! I appreciate your support, it means a lot to me to have you in my corner.
D3:13	Evan: Yes, Sam! I'm here for you. Let's rock our workouts and reach our goals! Exercise clears the mind—it's amazing!
D3:14	Sam: Wow, that's awesome! Could you give me a hand with getting started?
D3:15	Evan: Sure Sam, I'd be glad to help. Let's get together and I'll show you some basic exercises. We'll reach our goals!
D3:16	Sam: I'm coming from the shop and I had a frustrating issue at the supermarket. The self-checkout machines were all broken, my mood is terrible now!
D3:17	Evan: Sorry you were in that situation, hopefully it won't happen again!
D3:18	Sam: Yeah, I hope so, take care of yourself.
D22:14	Evan: Yeah, I've been trying to eat healthier too. Check out this cool recipe I discovered for these energy balls.
D22:15	Sam: Do you like them? I know they can be an acquired taste.
D22:16	Evan: I enjoy the taste of these. They're energizing and a healthy way to satisfy your sweet tooth.
D22:17	Sam: Awesome! Always on the lookout for healthy snacks, thanks for the tip!
D22:18	Evan: Glad to help—hope you enjoy it!
D22:19	Sam: I went to the store again and, unsurprisingly, had issues with the self-checkout. It's becoming a regular annoyance.
D22:20	Evan: That's very strange, I've never had a problem with it once!
D22:21	Sam: Apparently I attract that to me, if you ever want to be in that situation, call me at the store with you!

(b) Persistent interaction-thread memory

Thread head 1. Evan discusses exercise with Sam, followed by Sam's report of broken self-checkout machines at the supermarket.

`D3:16` ; `gold source` ; The first occurrence establishes the concrete failure.

Thread head 2. Sam complains about recurring self-checkout issues at the store.

`D22:19` ; `gold source` ; The later occurrence establishes recurrence.

`D22:21` ; Additional selected context: Sam says that he seems to attract the problem.

(c) Task-oriented workspace

Question. What recurring issue frustrates Sam at the grocery store?
Workspace snapshot. W_q is assembled from 15 selected memory units across 11 threads; the memory units corresponding to both gold source turns are included (gold-source recall = 1.0).

The memory units at `D3:16` and `D22:19` are decisive. Thirteen additional selected memory units are retained in W_q, including health and lifestyle exchanges; they are not presented as answer-supporting content.

(d) Answer synthesis

Highlighted answer-supporting content from W_q. "The self-checkout machines were all broken"; "It's becoming a regular annoyance."

Answer. broken self-checkout machines

Saved metrics. F1 = 66.67, LLM-Judge = 100.00.

Figure 15. Supplementary case study of the repeated-event problem.

(a) Raw conversation sessions

D5:1	Evan: Hey Sam, how's it going? Last week I went on a trip to Canada and something unreal happened—I met this awesome Canadian woman and it was like something out of a movie. She's incredible and being with her makes me feel alive.
D5:2	Sam: Congrats Evan! She must be something special! Being with someone who makes you feel alive is amazing. I'm sorry to hear that you're dealing with health issues lately, it can be really tough.
D5:3	Evan: Woah. such a nice view! Thanks, Sam! She's definitely great. Every moment with her is really fun and energizing. It's a nice change, especially after dealing with health issues. But you never know what life's gonna throw at you. Btw look what life has thrown for me right now haha.
D5:4	Sam: Looks good to eat! Dealing with health problems can be challenging and take away from enjoyable experiences.
D5:5	Evan: Ginger snaps are my weakness for sure! Dealing with health issues has been tough, but it's made me appreciate the good moments more. These are the ones who bring lots of joy even through the hard times.
D6:1	Evan: Hey Sam, long time no talk! Hope you're doing great. I just got back from a rad vacay with my new SO in Canada. Tried some awesome activities too—think hiking, biking... all that cool stuff. We loved exploring the outdoors together, it was so awesome!
D6:2	Sam: Hey Evan! Good to hear from you. Wow, Canada sounds amazing! That photo looks stunning. Wish I could do something like that. Things have been a bit challenging for me lately; some stuff has been hard on my health.
D6:3	Evan: Sorry to hear that things haven't been going well. Dealing with health issues can be tough. Is there anything I can do to help?
D6:4	Sam: Thanks, Evan. Your support means a lot to me. It's tough staying positive, but knowing I have people like you in my corner makes it easier.
D6:5	Evan: Glad to support you, Sam. Surrounding ourselves with people who care is key. What's on that note? A reminder or quote to stay motivated?

(b) Persistent interaction-thread memory

Thread head 1. Evan reports meeting an amazing Canadian woman during a trip and describes the relationship as energizing.

`D5:1` ; `gold source` ; The first thread records when the relationship is introduced.

Thread head 2. Evan reports returning from a Canadian vacation with his new significant other and describes their shared activities.

`D6:1` ; `gold source` ; The later thread records the relationship after the trip.

(c) Task-oriented workspace

Question. Who did Evan meet on his trip to Canada, and who did he come back from Canada with?
Workspace snapshot. W_q is assembled from 16 selected memory units across 10 threads; the memory units corresponding to both gold source turns are included (gold-source recall = 1.0).

The memory units at `D5:1` and `D6:1` connect the initial meeting with the later return. Fourteen additional selected memory units are retained in W_q but compressed here for legibility.

(d) Answer synthesis

Evidence supplied to the answer model. "I met this awesome Canadian woman"; "I just got back from a rad vacay with my new SO in Canada."

Evidence-grounded answer.

Evan met a Canadian woman and later returned from Canada with his new significant other.

Original benchmark metrics. F1 = 48.00, LLM-Judge = 100.00.

Figure 16. Supplementary case study of Travel Relation Questions across Sessions.

(a) Raw conversation sessions

D14:1	Dave: Hey Cal, how's it going? Something cool happened since last we talked—I got to go to a car workshop in San Francisco! So cool to dive into the world of car restoration and see all the different techniques. People were really passionate and dedicated—truly inspiring!
D14:2	Calvin: Hey Dave! That's awesome! Car workshops sound totally cool and inspiring. Glad you found something that really gets you going.
D14:3	Dave: It's always great to learn and grow. So, what have you been up to lately?
D14:4	Calvin: As you know, I had an amazing experience touring with a well-known artist. The feeling of performing and connecting with the audience was unreal. We ended with a show in Japan and then I had the opportunity to explore my new place—it's like a dream come true!
D14:5	Dave: Wow, Calvin! I bet playing for an eager audience was an incredible experience. Exploring Japan must have been amazing! How did Tokyo react to your music? Did you have any special moments there?
D17:1	Dave: Hey Calvin! Been a while, what's up? I'm tied up with car stuff lately, yesterday I came back from San Francsico with some great insights and knowledge on car modification that I want to share with you! Changing things around, and giving an old car a new life—so satisfying!
D17:2	Calvin: Hey Dave! Nice to hear from you. That's cool! I totally understand the satisfaction you get from fixing cars. It's like you're giving them new life.
D17:3	Dave: Yeah, it's great fixing stuff up and seeing it turn out better. It's really rewarding and gives me a sense of purpose. Plus, it feels like I'm making a difference when I fix someone's car.
D17:4	Calvin: Wow, you must feel great making a real difference in someone's life, like being their superhero!
D17:5	Dave: Yeah, it's great! It feels really good to make a difference and see their relief when their car is fixed. Makes me proud!

(b) Persistent interaction-thread memory

Thread head 1. Dave describes a car workshop in San Francisco and the restoration techniques he learned there.
`D14:1` ; `gold source` ; The first thread anchors the place to the workshop activity.

Thread head 2. Dave returns from San Francisco with new knowledge about car modification.
`D17:1` ; `gold source` ; The later thread restates the location through a return event and links it to the acquired skill.

(c) Task-oriented workspace

Question. Where did Dave return from with new knowledge of different techniques of car restoration?
Workspace snapshot. W_q is assembled from 15 selected memory units across 15 threads; the memory units corresponding to both gold source turns are included (gold-source recall = 1.0).
The memory units at `D14:1` and `D17:1` jointly identify the workshop location. The remaining selected memory units are retained in W_q but compressed here for readability.

(d) Answer synthesis

Highlighted answer-supporting content from W_q. "a car workshop in San Francisco"; "I came back from San Francsico with some great insights and knowledge on car modification."

Answer. San Francisco
Saved metrics. F1 = 100.00, LLM-Judge = 100.00.

Figure 17. Supplementary case study of Location and Skill Clues across Sessions.

(a) Raw conversation sessions

D4:7	John: Hey Tim, I was thinking about our last conversation. You mentioned enjoying fantasy books and Harry Potter.
D4:8	John: Oh yeah, I remember you telling me about Harry Potter! I've got a funny story. Anthony and I went to this charity thing and ended up in this intense Harry Potter trivia contest. We did alright, but there was this one super-nerd there that took home this as a prize.
D4:9	Tim: That's hilarious! Must have been a fun contest. Do you remember what the prize was?
D4:10	John: It was a signed Harry Potter book, if I remember correctly. The winner was so excited!
D22:1	Tim: I finally got my study-abroad news—I'm heading to Ireland next semester.
D22:2	John: Hey Tim! Sounds awesome! So glad you had a blast at the Harry Potter party. Last August I told you about my fun time at a charity event with Harry Potter trivia. Love being with people who are as passionate about Harry Potter as us! Did you dress up as any character?

(b) Persistent interaction-thread memory

Thread head 1. John and Tim discuss Harry Potter; John recalls attending trivia with Anthony and a signed book prize.

D4:8 ; `gold source` ; The source records the event but does not name the book title.

Thread head 2. John later recalls the Harry Potter trivia event while Tim discusses study abroad.

D22:2 ; `gold source` ; This turn also leaves the prize unspecified.

(c) Query-local evidence workspace

Question. When did John attend the Harry Potter trivia?
Workspace snapshot. The saved run selects 16 evidence turns from 12 threads and covers both annotated gold sources (gold-source recall = 1.0).
The two selected turns say only "last August" and refer back to an event; neither specifies a year. The cited conversation therefore does not establish the benchmark's year-level answer.

(d) Answer synthesis

Evidence supplied to the answer model. "Anthony and I went to this charity thing"; "Last August I told you about my fun time at a charity event with Harry Potter trivia."

Model answer. August 2022

Benchmark reference. August 2023
Saved metrics. F1 = 50.00, LLM-Judge = 0.00.

Figure 18. Date-related failure case

9. Conclusion

We present TrawMem, a task-oriented framework that reframes agent memory as *Task-Oriented Role-Adaptive Workspaces*. Instead of selecting memories solely by direct relevance, TrawMem organizes interaction histories into local threads, establishes relations among threads, and assigns task-oriented roles to select complementary memories for a workspace. Experiments on LoCoMo and MemGallery across four backbones show consistent improvements over representative memory systems, while ablations further confirm the contribution of the individual components. Overall, our results suggest that modeling the roles and relations of memories provides a useful perspective for memory utilization in long-horizon agent tasks.

Ethics Statement

TrawMem organizes interaction histories into local event threads and constructs task-oriented workspaces for agent systems. While this design can improve long-horizon task solving, storing and reusing interaction histories raises important privacy concerns, as they may contain sensitive personal information. The memory may also preserve or amplify biases, errors, or misinformation present in user-provided content, potentially leading to undesirable agent behavior. Any deployment of TrawMem should therefore adopt robust safeguards, including data anonymization, informed user consent, and mechanisms to detect and mitigate biased or false memories.

AI Assistance Statement

During this work, we used generative AI tools solely for polishing the English prose, checking grammar, and improving clarity and exposition. Generative AI tools were not used to design the method, develop the theory, conduct the experiments. All AI-assisted text was carefully reviewed by the authors, who take full responsibility for the final paper and its scientific content.

References

Charles Packer, Sarah Wooders, Kevin Lin, Vivian Fang, Shishir G Patil, Ion Stoica, and Joseph E Gonzalez. Memgpt: Towards llms as operating systems. *arXiv preprint arXiv:2310.08560*, 2023.

Joon Sung Park, Joseph O'Brien, Carrie Jun Cai, Meredith Ringel Morris, Percy Liang, and Michael S Bernstein. Generative agents: Interactive simulacra of human behavior. In *Proceedings of the 36th annual acm symposium on user interface software and technology*, pages 1–22, 2023.

Wanjun Zhong, Lianghong Guo, Qiqi Gao, He Ye, and Yanlin Wang. Memorybank: Enhancing large language models with long-term memory. In *Proceedings of the AAAI conference on artificial intelligence*, volume 38, pages 19724–19731, 2024.

Jiazheng Kang, Mingming Ji, Zhe Zhao, and Ting Bai. Memory os of ai agent. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 25972–25981, 2025.

Shouyuan Chen, Sherman Wong, Liangjian Chen, and Yuandong Tian. Extending context window of large language models via positional interpolation. *arXiv preprint arXiv:2306.15595*, 2023.

Yukang Chen, Shengju Qian, Haotian Tang, Xin Lai, Zhijian Liu, Song Han, and Jiaya Jia. Longlora: Efficient fine-tuning of long-context large language models. In *International Conference on Learning Representations*, volume 2024, pages 8220–8238, 2024.

Yiran Ding, Li Lyna Zhang, Chengruidong Zhang, Yuanyuan Xu, Ning Shang, Jiahang Xu, Fan Yang, and Mao Yang. Longrope: Extending llm context window beyond 2 million tokens. *arXiv preprint arXiv:2402.13753*, 2024.

Nelson F Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. Lost in the middle: How language models use long contexts. *Transactions of the association for computational linguistics*, 12:157–173, 2024.

Jizhan Fang, Xinle Deng, Haoming Xu, Ziyan Jiang, Yuqi Tang, Ziwen Xu, Shumin Deng, Yunzhi Yao, Mengru Wang, Shuofei Qiao, et al. Lightmem: Lightweight and efficient memory-augmented generation. In *International Conference on Learning Representations*, volume 2026, pages 98706–98729, 2026.

Yiming Du, Wenyu Huang, Danna Zheng, Zhaowei Wang, Sebastien Montella, Mirella Lapata, Kam-Fai Wong, and Jeff Z Pan. Rethinking memory in ai: Taxonomy, operations, topics, and future directions. *arXiv e-prints*, pages arXiv–2505, 2025.

Zeyu Zhang, Quanyu Dai, Xiaohe Bo, Chen Ma, Rui Li, Xu Chen, Jieming Zhu, Zhenhua Dong, and Ji-Rong Wen. A survey on the memory mechanism of large language model-based agents. *ACM Transactions on Information Systems*, 43(6):1–47, 2025a.

Prateek Chhikara, Dev Khant, Saket Aryan, Taranjeet Singh, and Deshraj Yadav. Mem0: Building production-ready ai agents with scalable long-term memory. *arXiv preprint arXiv:2504.19413*, 2025.

Wujiang Xu, Zujie Liang, Kai Mei, Hang Gao, Juntao Tan, and Yongfeng Zhang. A-mem: Agentic memory for llm agents. *Advances in Neural Information Processing Systems*, 38:17577–17604, 2026a.

Jiaqi Liu, Yaofeng Su, Peng Xia, Siwei Han, Zeyu Zheng, Cihang Xie, Mingyu Ding, and Huaxiu Yao. Simplemem: Efficient lifelong memory for llm agents. *arXiv preprint arXiv:2601.02553*, 2026.

Bing Wang, Xinnian Liang, Jian Yang, Hui Huang, Zhenhe Wu, ShuangZhi Wu, Zejun Ma, and Zhoujun Li. Scm: Enhancing large language model with self-controlled memory framework. In *International Conference on Database Systems for Advanced Applications*, pages 188–203. Springer, 2025.

Preston Rasmussen, Pavlo Paliychuk, Travis Beauvais, Jack Ryan, and Daniel Chalef. Zep: a temporal knowledge graph architecture for agent memory. *arXiv preprint arXiv:2501.13956*, 2025.

Guibin Zhang, Muxin Fu, Kun Wang, Frank Wan, Miao Yu, and Shuicheng Yan. G-memory: Tracing hierarchical memory for multi-agent systems. *Advances in Neural Information Processing Systems*, 38:12988–13018, 2026a.

Zhiyu Li, Shichao Song, Hanyu Wang, Simin Niu, Ding Chen, Jiawei Yang, Chenyang Xi, Huayi Lai, Jihao Zhao, Yezhaohui Wang, et al. Memos: An operating system for memory-augmented generation (mag) in large language models. *arXiv preprint arXiv:2505.22101*, 2025a.

Zixu Li, Yupeng Hu, Zhiwei Chen, Mingyu Zhang, Zhiheng Fu, and Liqiang Nie. Conesep: Cone-based robust noise-unlearning compositional network for composed image retrieval. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 16897–16909, 2026a.

Zhiheng Fu, Yupeng Hu, Qianyun Yang, Shiqi Zhang, Zhiwei Chen, and Zixu Li. Air-know: Arbiter-calibrated knowledge-internalizing robust network for composed image retrieval. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 2658–2670, 2026.

Zixu Li, Yupeng Hu, Zhiheng Fu, Zhiwei Chen, Yongqi Li, and Liqiang Nie. Tema: Anchor the image, follow the text for multi-modification composed image retrieval. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 24421–24442, 2026b.

Zixu Li, Zhiheng Fu, Yupeng Hu, Zhiwei Chen, Haokun Wen, and Liqiang Nie. Finecir: Explicit parsing of fine-grained modification semantics for composed image retrieval. *arXiv preprint arXiv:2503.21309*, 2025b.

Zhiwei Chen, Yupeng Hu, Zhiheng Fu, Zixu Li, Jiale Huang, Qinlei Huang, and Yinwei Wei. Intent: Invariance and discrimination-aware noise mitigation for robust composed image retrieval. In *AAAI*, volume 40, pages 20463–20471, 2026.

Zhiwei Chen, Yupeng Hu, Zixu Li, Zhiheng Fu, Xuemeng Song, and Liqiang Nie. Offset: Segmentation-based focus shift revision for composed image retrieval. In *ACM MM*, page 6113–6122, 2025.

Zixu Li, Zhiwei Chen, Haokun Wen, Zhiheng Fu, Yupeng Hu, and Weili Guan. Encoder: Entity mining and modification relation binding for composed image retrieval. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 5101–5109, 2025c.

Zixu Li, Yupeng Hu, Zhiwei Chen, Shiqi Zhang, Qinlei Huang, Zhiheng Fu, and Yinwei Wei. Habit: Chrono-synergia robust progressive learning framework for composed image retrieval. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 40, pages 6762–6770, 2026c.

Mingyu Zhang, Zixu Li, Zhiwei Chen, Zhiheng Fu, Xiaowei Zhu, Jiajia Nie, Yinwei Wei, and Yupeng Hu. Hint: Composed image retrieval with dual-path compositional contextualized network. In *ICASSP 2026-2026 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 13002–13006. IEEE, 2026b.

Yunyao Zhang, Zikai Song, Hang Zhou, Wenfeng Ren, Yi-Ping Phoebe Chen, Junqing Yu, and Wei Yang. $ga - s^3$: Comprehensive social network simulation with group agents. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 8950–8970, 2025b.

Zikai Song, Xiajie Li, Yunyao Zhang, Xinglang Zhang, Wei Yang, and Junqing Yu. Social intelligence modeling: A comprehensive survey from social perception to social simulation. ResearchGate preprint, 2026. URL https://www.researchgate.net/publication/411123257_Social_Intelligence_Modeling_A_Comprehensive_Survey_from_Social_Perception_to_Social_Simulation. Preprint available on ResearchGate.

Yunyao Zhang, Yihao Ai, Zuocheng Ying, Qirui Mi, Junqing Yu, Wei Yang, and Zikai Song. Coupling macro dynamics and micro states for long-horizon social simulation, 2026c. URL https://arxiv.org/abs/2604.05516.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, et al. Retrieval-augmented generation for knowledge-intensive nlp tasks. *Advances in neural information processing systems*, 33:9459–9474, 2020.

Jason Weston and Sainbayar Sukhbaatar. System 2 attention (is something you might need too). *arXiv preprint arXiv:2311.11829*, 2023.

Antonia Creswell, Murray Shanahan, and Irina Higgins. Selection-inference: Exploiting large language models for interpretable logical reasoning. *arXiv preprint arXiv:2205.09712*, 2022.

Huiqiang Jiang, Qianhui Wu, Xufang Luo, Dongsheng Li, Chin-Yew Lin, Yuqing Yang, and Lili Qiu. Longllmlingua: Accelerating and enhancing llms in long context scenarios via prompt compression. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1658–1677, 2024.

Zixu Li, Yupeng Hu, Zhiwei Chen, Qinlei Huang, Guozhi Qiu, Zhiheng Fu, and Meng Liu. Retrack: Evidence-driven dual-stream directional anchor calibration network for composed video retrieval. In *AAAI*, volume 40, pages 23373–23381, 2026d.

Yupeng Hu, Zixu Li, Zhiwei Chen, Qinlei Huang, Zhiheng Fu, Mingzhu Xu, and Liqiang Nie. Refine: Composed video retrieval via shared and differential semantics enhancement. *ACM Transactions on Multimedia Computing, Communications and Applications*, 22(7):1–24, 2026.

Zixu Li, Yupeng Hu, Zhiheng Fu, Zhiwei Chen, Weili Guan, and Liqiang Nie. R^3: Composed video retrieval via reasoning-guided recalling and re-ranking. *arXiv preprint arXiv:2606.01113*, 2026e.

Yibo Zhao, Jiapeng Zhu, Ye Guo, Kangkang He, and Xiang Li. Eˆ 2graphrag: Streamlining graph-based rag for high efficiency and effectiveness. *arXiv preprint arXiv:2505.24226*, 2025.

Zirui Guo, Lianghao Xia, Yanhua Yu, Tian Ao, and Chao Huang. Lightrag: Simple and fast retrieval-augmented generation. In *EMNLP (Findings)*, pages 10746–10761, 2025.

Junnan Dong, Siyu An, Yifei Yu, QIANWEN ZHANG, Linhao Luo, Xiao Huang, Yunsheng Wu, Xing Sun, et al. Youtu-graphrag: Vertically unified agents for graph retrieval-augmented complex reasoning. In *International Conference on Learning Representations*, volume 2026, pages 143735–143755, 2026.

Qianyun Yang, Zhiwei Chen, Yupeng Hu, Zixu Li, Zhiheng Fu, and Liqiang Nie. Stable: Efficient hybrid nearest neighbor search via magnitude-uniformity and cardinality-robustness. *IEEE Transactions on Knowledge and Data Engineering*, 2026.

Yulun Zhang, Zixu Li, Zhiwei Chen, Zhiheng Fu, Wenbo Wang, Zihang Qiu, Zhilin Wang, Ruxin Wang, and Yupeng Hu. Lightair: Lightweight action inversion and riemannian rectification for text-based person anomaly search. *arXiv preprint arXiv:2608.09152*, 2026d.

Zixu Li, Zhiwei Chen, Zhiheng Fu, Wenbo Wang, Yupeng Hu, Weili Guan, and Liqiang Nie. Omniego-r^2: A routed reasoning framework for the 1st cross-domain egocross challenge at cvpr 2026. *arXiv preprint arXiv:2605.24481*, 2026f.

Jinhe Bi, Chennan Zhou, Zengjie Jin, Aniri, Shuo Lu, Wenke Huang, Hu Cao, Xun Xiao, Zhihong Zhu, Volker Tresp, Fei Shen, Yunpu Ma, and Tat-Seng Chua. Reflectrl: Learning from golden negative trajectories via reflective-to-direct reasoning, 2026a. URL https://arxiv.org/abs/2608.03972.

Aniri, Jinhe Bi, Peng Liao, Zengjie Jin, Volker Tresp, Fei Shen, Yunpu Ma, and Tat-Seng Chua. Opd-v: Visual on-policy self-distillation with modality balance, 2026a. URL https://arxiv.org/abs/2608.05131.

Yunyao Zhang, Zuocheng Ying, Xinglang Zhang, Junqing Yu, Peng Fang, Xu Chen, Wei Yang, and Zikai Song. Intervensim: Intervention-aware social network simulation for opinion dynamics, 2026e. URL https://arxiv.org/abs/2604.06600.

Jinhe Bi, Aniri, Minglai Yang, Xingcheng Zhou, Wenke Huang, Sikuan Yan, Yujun Wang, Zixuan Cao, Michael Färber, Xun Xiao, Volker Tresp, and Yunpu Ma. EchoRL: Reinforcement learning via rollout echoing. In *Forty-third International Conference on Machine Learning*, 2026b. URL https://openreview.net/forum?id=A6az59SGtF.

Jinhe Bi, Danqi Yan, Yifan Wang, Wenke Huang, Haokun Chen, Guancheng Wan, Mang Ye, Xun Xiao, Hinrich Schuetze, Volker Tresp, and Yunpu Ma. The geometry of reasoning: Self-evaluation via layerwise trajectory evolution. In *Forty-third International Conference on Machine Learning*, 2026c. URL https://openreview.net/forum?id=WQyrwQwzmK.

Yunyao Zhang, Xinglang Zhang, Junxi Sheng, Wenbing Li, Junqing Yu, Yi-Ping Phoebe Chen, Wei Yang, and Zikai Song. Semantic-aware logical reasoning via a semiotic framework, 2026f. URL https://arxiv.org/abs/2509.24765.

Xinglang Zhang, Yunyao Zhang, ZeLiang Chen, Junqing Yu, Wei Yang, and Zikai Song. Logical phase transitions: Understanding collapse in llm logical reasoning, 2026g. URL https://arxiv.org/abs/2601.02902.

Wenbing Li, Zikai Song, Hang Zhou, Junqing Yu, Yunyao Zhang, and Wei Yang. Lora-mixer: Coordinate modular lora experts through serial attention routing. In *International Conference on Learning Representations*, volume 2026, pages 14694–14716, 2026g.

Xinglang Zhang, Yuanmeng Xiang, Yunyao Zhang, Zeliang Chen, Junqing Yu, and Zikai Song. Too good to be real? diagnosing and reducing the gap between ai preference and real user engagement. *arXiv preprint arXiv:2609.18282*, 2026h.

Zhenyan Zheng, Yunyao Zhang, Junxi Sheng, Junqing Yu, and Zikai Song. Surfacing the unsaid: Cue-bench for affective stance in chinese discourse. *arXiv preprint arXiv:2608.10810*, 2026.

Jinhe Bi, Yujun Wang, Haokun Chen, Xun Xiao, Artur Hecker, Volker Tresp, and Yunpu Ma. LLaVA steering: Visual instruction tuning with 500x fewer parameters through modality linear representation-steering. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar, editors, *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 15230–15250, Vienna, Austria, July 2025a. Association for Computational Linguistics. ISBN 979-8-89176-251-0. URL https://aclanthology.org/2025.acl-long.739/.

Aniri, Chen Yilin, Jinhe Bi, Junfei Guo, Donglai Ran, Xu Bian, Zengjie Jin, Yujun Wang, Yijun Tian, Volker Tresp, Fei Shen, Tat-Seng Chua, and Yunpu Ma. Fabrimae i trust myself? self-evaluating vla action generation with markov attention entropy, 2026b. URL https://arxiv.org/abs/2608.16697.

Jinhe Bi, Yifan Wang, Danqi Yan, Xun Xiao, Artur Hecker, Volker Tresp, and Yunpu Ma. Prism: Self-pruning intrinsic selection method for training-free multimodal data selection. *ArXiv*, abs/2502.12119, 2025b. URL https://api.semanticscholar.org/CorpusID:276421326.

Yanzhao Zhang, Mingxin Li, Dingkun Long, Xin Zhang, Huan Lin, Baosong Yang, Pengjun Xie, An Yang, Dayiheng Liu, Junyang Lin, et al. Qwen3 embedding: Advancing text embedding and reranking through foundation models. *arXiv preprint arXiv:2506.05176*, 2025c.

Anyi Xu, Bangcai Lin, Bing Xue, Bingxuan Wang, Bingzheng Xu, Bochao Wu, Bowei Zhang, Chaofan Lin, Chen Dong, Chenchen Ling, et al. Deepseek-v4: Towards highly efficient million-token context intelligence. *arXiv preprint arXiv:2606.19348*, 2026b.

Adyasha Maharana, Dong-Ho Lee, Sergey Tulyakov, Mohit Bansal, Francesco Barbieri, and Yuwei Fang. Evaluating very long-term conversational memory of llm agents. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 13851–13870, 2024.

Yuanchen Bei, Tianxin Wei, Xuying Ning, Yanjun Zhao, Zhining Liu, Xiao Lin, Yada Zhu, Hendrik Hamann, Jingrui He, and Hanghang Tong. Mem-gallery: Benchmarking multimodal long-term conversational memory for mllm agents. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 40750–40784, 2026.