

Phonologically Informed Tokenization for German Speech Recognition: A Cross-Domain Study

Christopher Witzl Tobias Bocklet Korbinian Riedhammer

Technische Hochschule Nürnberg Georg Simon Ohm, Nürnberg, Germany
{christopher.witzl, tobias.bocklet, korbinian.riedhammer}@th-nuernberg.de

Abstract

German is a morphologically rich language whose syllable structure is exceptionally well-predicted by the Knuth–Liang hyphenation algorithm. We ask whether phonologically informed tokenization can serve as a competitive target for end-to-end speech recognition. We compare three tokenizer families on the Omnilingual ASR wav2vec 2.0 backbone fine-tuned with CTC: the pretrained multilingual character inventory, a data-driven Byte-Pair Encoding (BPE) over orthography, and phonologically informed units from Pyphen syllabification and grapheme-to-phoneme conversion. Across 40 fine-tunes, we evaluate on three German test sets spanning orthogonal shifts: in-domain read speech, dialectal spontaneous speech, and standard-German spontaneous speech. In-domain, all phonologically informed tokenizers match BPE and the multilingual character baseline on both WER and CER. Under domain shift the picture splits along vocabulary size rather than the linguistic axis of variation: at small vocabularies, syllable-aware tokenization improves on dialectal speech, where phonetic surface forms vary but syllable structure is preserved, and stays ahead on spontaneous speech, where new word-forms violate vocabulary closure. A phoneme-level confusion analysis further shows that all tokenizers commit the same canonical function-word errors, indicating that the acoustic encoder, not the tokenizer, dominates the error topology. Our findings suggest that tokenizer choice may depend on the vocabulary budget as much as on the distribution shift expected at deployment rather than reducing to a single universal optimum.

1 Introduction

Modern end-to-end automatic speech recognition (ASR) systems built on self-supervised pretraining (Baevski et al., 2020) couple an acoustic encoder with an output tokenizer that determines the units

the network must predict. The de facto default has converged on two choices: a data-driven Byte-Pair Encoding (BPE) (Sennrich et al., 2016) fitted to the training transcripts, or a fixed multilingual character inventory inherited from the pretrained ASR model (Omnilingual ASR team et al., 2025). Both are phonologically agnostic. The first treats character n -grams as merge candidates without regard to syllable or morpheme structure; the second models every character of every supported script as an independent unit, leaving word-level structure to the acoustic encoder. The choice is not cosmetic: the tokenizer fixes which strings the network can emit, how many target units per word the CTC objective must align, and how the model degrades on word-forms unseen in training.

This convergence is convenient, but it hides a methodological question with real downstream consequences: do *phonologically informed* tokenizers¹, those that align with the syllabic and phonemic structure of the target language, offer something that data-driven and multilingual defaults cannot? German is a natural test case: it is morphologically rich (productive compounding, inflection), it has substantial dialectal variation, and large-scale German ASR benchmarks (Common Voice (Ardila et al., 2020), Spoken Wikipedia Corpus (Köhn et al., 2016)) coexist with structurally different out-of-distribution (OOD) corpora, namely dialectal spontaneous speech (BAS RVG 1, Burger and Schiel, 1998) and standard-German spontaneous dialogues (Verbmobil, Burger et al., 2000). The language thus offers two distinct OOD axes against which tokenizer behavior can be probed: RVG 1 varies the *phonetic surface* (a largely shared lexicon realized across nine dialect regions), while Verbmobil varies the *lexical inventory* (standard-German phonetics but negotiation-dialogue vocab-

¹I.e., tokenizers whose boundaries derive from linguistic knowledge (syllabification, grapheme-to-phoneme mappings) rather than data-driven frequency statistics.

ulary including hesitations, discourse particles, and colloquial verb forms unseen at training time).

Contributions. We make three contributions. (1) We assemble and train **40 CTC fine-tunes of the Omnilingual ASR wav2vec 2.0 encoder** (Omnilingual ASR team et al., 2025) (31 tokenizers at 300 M, nine at 1 B) that share encoder, training data, and training schedule, varying only the tokenizer: 13 orthographic tokenizers (character, BPE-512/1024/2048, syllable-512/1024/2048, multi-syllable with and without syllable separators) and 18 phoneme-track tokenizers (raw IPA, phoneme-BPE, phoneme-syllable, phoneme-multi-syllable; vocabulary sizes 43–3,840). The matrix is large enough to dissociate vocabulary size from tokenization strategy. (2) We evaluate every model on the in-domain test set *and* on two structurally orthogonal OOD test sets: dialectal spontaneous speech (RVG 1) and standard-German negotiation dialogues (Verbmobil), quantifying *when* the phonological bias helps, *where* it stays competitive, and *how* its payoff depends on vocabulary size. (3) We complement aggregate WER with paired-bootstrap significance testing (Bisani and Ney, 2004) and confusion-matrix analyses; we focus on WER and CER rather than token-level metrics, since the latter conflate recognition quality with tokenizer compression rate and are not directly comparable across the very different vocabulary sizes (43 to 10,288 tokens) in our design space.

Headline result. Phonologically informed tokenizers cluster within the confidence intervals of BPE and character baselines in-domain. Under dialectal-phonetic OOD they show a small advantage that sits at the Bonferroni boundary (-1.09 pp WER on RVG 1-ORT, $p=0.019$, threshold $\alpha/k \approx 0.017$ for $k=3$ tests on this dataset), and under spontaneous-lexical OOD a small lead (-0.89 pp WER for syllable-512 on Verbmobil), giving a characterization of the phonological-bias trade-off rather than a single “best tokenizer”. That trade-off runs along vocabulary size rather than along the type of shift: the advantage reverses on both corpora at $|V|=2048$ (§4.5).

2 Related Work

The choice of output unit in ASR has recurred as a design question through every architectural paradigm. Classical large-vocabulary systems combined pronunciation lexica, context-dependent tri-

phones, and language models (Lee et al., 1990; Young et al., 1994), later composed through weighted finite-state transducers (Mohri et al., 2002). For German specifically, Killer et al. (2003) found that graphemes match phonemes in GMM-HMM systems, while Mousa et al. (2012) reported that morpheme-level language models lower out-of-vocabulary rates. Both findings are early evidence that linguistic units remain competitive in-domain, with conditional advantages elsewhere.

The unit question survived the neural transition. Hybrid NN/HMM systems (Bourlard and Morgan, 1994) retained phonemic states as targets; end-to-end CTC reopened the question, with Graves et al. (2013) reestablishing phoneme-CTC on TIMIT. Sennrich et al. (2016) introduced Byte-Pair Encoding for neural machine translation, and Zenkel et al. (2018) adapted it to CTC ASR with a key contrast between *Subword* units (merges constrained to within words) and *Crossword* units (merges allowed across word boundaries). Their distinction maps directly onto our *syllable* vs. *multisyl* contrast at the syllable rather than word level.

Irie et al. (2019) compared graphemes, phonemes, and wordpieces on LibriSpeech and found graphemes and wordpieces dominate without an external language model; for German, Khosravani et al. (2020) found BPE and unigram subwords to outperform character- and word-level outputs (with n -gram LMs). Sainath et al. (2018) found that graphemes largely obviate the lexicon, whereas Zeineldeen et al. (2020) responded that phoneme-BPE with homophone disambiguation remains competitive. A separate line of work derives subword vocabularies from pronunciation information (Xu et al., 2019; Papadourakis et al., 2021; Zhou et al., 2021). Most directly related to our phoneme track, Klumpp et al. (2022) released the Common Phone corpus and trained a wav2vec 2.0 phoneme recognizer covering six languages including German, achieving 18.1 % PER across 101 phonetic symbols; our phoneme-track models follow the same acoustic-modeling setup but vary the tokenizer.

Syllable-based ASR has a thinner literature. Ganapathiraju et al. (2001) demonstrated syllabic acoustic units in HMM-LVCSR on Switchboard; Qu et al. (2017) trained syllable-level CTC for Mandarin; and Manohar et al. (2023) applied Syllable-BPE to Malayalam, the closest cross-linguistic precedent to our German Pyphen-based syllable tokenizers (Liang, 1983; Pyphen developers, 2023).

None of these works evaluated tokenizers under structured domain shift, which is the gap our paper addresses.

A complementary literature on ASR robustness holds the tokenizer fixed and varies the acoustic side. [Likhomanenko et al. \(2021\)](#) established that single-corpus WER is a poor robustness proxy; [Hsu et al. \(2021\)](#) showed that encoder-side adaptation closes 66–73 % of the OOD gap in wav2vec 2.0; and [Radford et al. \(2023\)](#) framed robustness through weak-supervision scale. Our results are consistent with the encoder-as-primary-lever finding (confusion topology is largely tokenizer-invariant in our setup), but tokenizer choice acts as a complementary lever whose payoff depends on the OOD axis and vocabulary size. We extend this lineage by holding the encoder fixed and varying only the output tokenizer, isolating the tokenization effect from the lexicon, decoder, and training-scale variables that confounded earlier comparisons.

3 Methodology

3.1 Datasets

Training data is a 961-hour mixture of German Common Voice ([Ardila et al., 2020](#)) and the Spoken Wikipedia Corpus (Oct. 2017 release; [Köhn et al., 2016](#); [Baumann et al., 2019](#)). Evaluation uses three structurally distinct test sets: the held-out portion of the same mixture (CV+SWC test, in-domain), BAS RVG 1 ([Burger and Schiel, 1998](#)), and BAS Verbmobil VM1 ([Burger et al., 2000](#); [Schiel, 1999](#)). Table 1 summarizes the training mixture and the three evaluation sets.

The two OOD corpora are intentionally orthogonal. **RVG 1** is spontaneous speech recorded across nine German dialect regions; it varies the phonetic realization while the underlying lexicon remains largely shared across regions. **Verbmobil VM1** is spontaneous standard-German negotiation speech; it keeps the phonetic norm but introduces unfamiliar word-forms (hesitations, repairs, colloquial shortenings, discourse particles). Each corpus therefore stresses a different tokenizer property: phonetic robustness for RVG 1, lexical coverage for Verbmobil. Both provide parallel ORT (canonical orthography) and TR2 (dialect transliteration with prosody markers) reference tiers, which we report separately.

3.2 Tokenizer design space

We compare three classes of tokenizers, deliberately matched for vocabulary size where possible. Table 2 shows what the smallest variant of each family produces on a single illustrative example, which we discuss in §3.7.

3.3 Multilingual character inventory

OMNI-VOCAB is the publicly released `omniASR_tokenizer_written_v2` of Omnilingual ASR ([Omnilingual ASR team et al., 2025](#)), declared as `tokenizer_family: char_tokenizer` in the model card: a character-level tokenizer with $\approx 10,288$ multilingual code-points covering 1,600+ languages, shipped as the default for all v2 architectures (CTC and LLM checkpoints from 300 M to 7 B). On our German training data, only 59 of these code-points occur more than 100 times each (top-50 coverage $>99.99\%$ of all token occurrences); a long tail of ~ 600 further code-points appears as rare orthographic artifacts. OMNI-VOCAB serves as the “no phonological bias” comparator inherited from the pretrained ASR model.

3.4 Data-driven subword

GERMAN-BPE is a standard SentencePiece BPE ([Sennrich et al., 2016](#); [Kudo and Richardson, 2018](#)) fitted to the German training transcripts at vocabularies $\{512, 1024, 2048\}$. It serves as the data-driven comparator and is the de facto default in many modern German ASR systems.

3.5 Phonologically informed orthographic tokenizers

We construct three orthographic families on top of SentencePiece BPE ([Sennrich et al., 2016](#); [Kudo and Richardson, 2018](#)), differing only in which symbols are protected as user-defined symbols (UDS) and whether the training text is pre-syllabified. SYLLABLE- k uses the Knuth–Liang hyphenation algorithm ([Liang, 1983](#)) via Pyphen ([Pyphen developers, 2023](#)) to syllabify the training transcripts; the syllable separator `-` is registered as a UDS so that no BPE merge crosses a syllable boundary. Vocabularies are $k \in \{512, 1024, 2048\}$. MULTISYL- k is trained on the same syllabified text, but the separator `-` is *not* protected, allowing merges to cross syllable boundaries; in addition, the 100 most frequent German syllables are pre-registered as UDS so the model retains the most

Corpus	Split	<i>n</i> utterances	hours	Role / OOD axis
CV + SWC	train	550 747	960.5	training mix
CV 24 DE (Ardila et al., 2020)	(part of train)	457 512	726.5	speakers worldwide
SWC DE (Köhn et al., 2016)	(part of train)	93 235	234.0	Spoken Wikipedia
CV + SWC	test	24 604	50.2	in-domain hold-out
RVG 1 (Burger and Schiel, 1998)	all, pooled	442	6.6	dialectal-phonetic OOD
Verbmobil VM1 (Burger et al., 2000)	all, pooled (German)	13 633	33.8	spontaneous-lexical OOD

Table 1: Corpora. Training uses the CV 24 + SWC mixture; the in-domain test split is held out from the same mixture; RVG 1 and Verbmobil are entirely unseen and pooled across their train/dev/test splits (§3.8). Both OOD corpora carry parallel ORT (canonical orthography) and TR2 (dialect-/prosody-annotated transliteration) tiers. Verbmobil VM1 also contains English negotiation dialogues; we evaluate on its German subset only (§3.8).

useful multi-character atoms even at small vocabulary sizes. This corresponds conceptually to Zenkel et al.’s (2018) *Crossword* variant but operates at the syllable rather than word level. MULTISYL-NOSEP-*k* keeps the same 100-syllable UDS list as Multisyl but is trained on *raw*, non-syllabified text, so no syllable-separator token ever appears in the inputs. It isolates the effect of having syllables as atomic vocabulary entries from the effect of an explicit syllable-boundary marker.

3.6 Phonologically informed phoneme tokenizers

The phoneme track applies the same four merge strategies (raw, BPE, syllable, multi-syllable) to G2P-derived X-SAMPA phoneme sequences (Bisani and Ney, 2008). The G2P model is a joint-sequence WFST built with Phonetisaurus (Novak et al., 2012) and trained on the German pronunciation lexicon shipped with MaryTTS (Schröder and Trouvain, 2003) (de.txt, ~31k entries), giving canonical SAMPA transcriptions for every word in our training and test transcripts. Out-of-lexicon words are handled by Phonetisaurus’ default joint-sequence backoff (beam size 20); compound forms are not pre-decomposed and are mapped as whole tokens. The 18 resulting phoneme-token configurations span vocabulary sizes from 43 (the smallest character-level raw variant) to 3,840 (the largest multi-syllable BPE). The phoneme target inherits the German MAUS/BAS tradition (Schiel, 1999) and parallels Common Phone’s way2vec 2.0 phoneme recognition setup (Klumpp et al., 2022).

3.7 Tokenizer comparison

Table 2 compares the smallest variant of each tokenizer family on a single illustrative word, both in its orthographic form *Unterhaltung* (12 characters, four canonical syllables **un-ter-hal-tung**) and in its X-SAMPA transcription ?Un-t6-hal-tUN.

On the orthographic track, *syllable-512* is the only family that recovers all four canonical syllables as individual tokens; *German-BPE-512* finds three of them from data alone but splits the suffix *tung* into *t | ung*; the multisyl families pick finer, phonotactically motivated clusters that can additionally merge across syllable boundaries. On the phoneme track, *phone-multisyl-lite-512* is the only family that captures all four SAMPA syllables as single tokens. The classes therefore differ in *what kind of boundary* they choose, not just in granularity; this distinction frames the cross-domain results in §4.

3.8 Evaluation protocol

We report token-weighted **WER** and **CER** for orthographic models and **PER** and **CER** for phoneme-track models, both with 95 % paired-bootstrap confidence intervals (CIs; $n_{\text{boot}}=10,000$, seed=42, percentile method) (Bisani and Ney, 2004). For the orthographic track, references and hypotheses are normalized before scoring (lowercase, ß→ss, punctuation stripped, whitespace collapsed); this matches the standard Whisper-style protocol and ensures that capitalization conventions of the reference (Verbmobil business-style transcripts use Sie/Termin/Mai capitalization, while CV+SWC are lowercase) do not contaminate the recognition metric. Phoneme-track (X-SAMPA) evaluation is not normalized, since SAMPA symbols would be destroyed by punctuation stripping. Pairwise comparisons apply per-dataset Bonferroni correction. For the OOD corpora we pool train+dev+test (none seen at training time, which justifies pooling for tighter intervals at no leakage cost). Verbmobil VM1 contains English as well as German negotiation dialogues; we score its German subset (13,633 utterances, 33.8 h), identified from the reference transcripts by a German/English function-word criterion. Audio is 16 kHz mono

Family	Variant	Vocab	n_{tok}	cpt	Tokenization
<i>Orthographic track</i> : segmenting the German word “unterhaltung” (12 chars, 4 canonical syllables un-ter-hal-tung)					
Multilingual char	omni-vocab	10 288	12	1.00	u n t e r h a l t u n g
Data-driven BPE	german-BPE-512	512	5	2.40	un ter hal t ung
Syllable (Pyphen)	syllable-512	512	4	3.00	un ter hal tung
Multisyl (cross-syllable)	multisyl-512	512	6	2.00	un ter ha lt un g
Multisyl-nosep	multisyl-nosep-512	512	6	2.00	(identical to multisyl-512 on a single word [†])
<i>Phoneme track</i> : segmenting the X-SAMPA transcription “?Un-t6-hal-tUN” of the same word					
Atomic phones	phone-char-raw	43	14	0.79	? U n - t 6 - h a l - t U N
Data-driven BPE	phone-bpe-128	128	10	1.10	? Un - t 6 - h a l - t UN
Syllable	phone-syllable-128	128	11	1.00	? Un - t 6 - h a l - t UN
Multisyl-lite	phone-multisyl-lite-512	512	7	1.57	?Un - t6 - hal - tUN

Table 2: Smallest variant of each tokenizer family on the German word *Unterhaltung* (orthographic track) and its X-SAMPA transcription ?Un-t6-hal-tUN (phoneme track). Bold rows mark the family that recovers all four canonical syllables (or SAMPA syllables) as individual tokens. cpt = characters per token; on the phoneme track, atomic SAMPA symbols are counted, excluding syllable-separator dashes. [†]multisyl and multisyl-nosep produce identical outputs on a single word; the boundary marker affects only vocabulary construction.

and capped at 60 s for CV+SWC and Verbmobil (matching the external baselines); RVG 1’s full-length recordings, the only ones routinely exceeding 60 s, are instead segmented at silence boundaries into ≤ 60 s chunks so the complete utterance is scored rather than truncated. Decoding is greedy CTC without an external language model: a token-level LM would tie the decoding vocabulary to the tokenizer under study and conflate its language-modeling contribution with the acoustic comparison. Every WER/CER/PER reported here therefore reflects the encoder plus tokenizer-specific head in isolation; LM rescoring, and the tokenizer–LM interaction it opens up, is left to future work (§5).

4 Experiments and Results

4.1 Setup

We train 40 CTC fine-tunes (Graves et al., 2006) of the Omnilingual ASR wav2vec 2.0 backbone (Baeovski et al., 2020; Omnilingual ASR team et al., 2025): all 31 tokenizers (13 orthographic, 18 phoneme-track) at 300 M, and a nine-tokenizer subset at 1 B. The subset comprises the full vocabulary sweep of Syllable and German-BPE plus one variant per remaining family (omni-vocab, multisyl-512, multisyl-nosep-512). All runs use the Adam optimizer with a fixed learning rate of 5×10^{-5} , bfloat16 mixed precision, no encoder freezing, 20 k optimization steps, and a batched dynamic budget of $\approx 2.3 \times 10^7$ audio elements per gradient step (min/max audio 2/60 s). Batching is audio-element-based rather than token-based: every run sees the same audio in the same order (identical seed) for

the same 20 k updates, and the batch size is never adjusted per tokenizer. The number of target tokens therefore varies with tokenizer fertility; we deliberately do not match it, since fixing the token count would unfix the audio budget and confound the comparison with the amount of acoustic evidence. Appendix C reports the resulting target-token counts per run. The CTC output head is a single linear projection from the final encoder layer to the tokenizer’s vocabulary size (no layer selection was performed), with Xavier-uniform weight initialization and zero-initialized bias; no final-layer dropout is applied. Augmentation, label smoothing, validation schedule, and early-stopping criterion are held identical across all runs so that any cross-tokenizer difference is attributable to the output unit and its head alone. We organize the empirical comparison around three research questions, each probing one of our three test sets, complemented by paired significance tests for nine focal comparisons.

4.2 Q1: In-domain WER and CER

Table 3 reports CV+SWC test WER and CER for the 300 M orthographic models, scored on normalized text. The WER range is 14.9–18.0 % (German-BPE-512 best, multisyl-nosep-2048 worst); CIs have half-widths of 0.25–0.27 pp and overlap substantially across the top cluster: German-BPE-512, syllable-512, omni-vocab, syllable-1024, and the multi-syllable variants at vocabulary 512 are statistically indistinguishable from each other on WER. The CER ranking is largely parallel but with a different leader: *omni-vocab* reaches the lowest CER

Tokenizer	WER % 95 % CI	CER % 95 % CI
<i>Multilingual character inventory</i>		
omni-vocab	15.64 [15.38, 15.90]	6.09 [5.89, 6.29]
<i>Data-driven BPE (German)</i>		
German-BPE-512	14.93 [14.66, 15.18]	6.14 [5.94, 6.35]
German-BPE-1024	16.88 [16.61, 17.13]	6.89 [6.69, 7.09]
German-BPE-2048	16.11 [15.84, 16.36]	6.65 [6.45, 6.85]
<i>Syllable (Pyphen)</i>		
Syllable-512	15.16 [14.90, 15.42]	6.23 [6.02, 6.43]
Syllable-1024	15.44 [15.18, 15.69]	6.36 [6.15, 6.56]
Syllable-2048	15.94 [15.68, 16.20]	6.48 [6.28, 6.68]
<i>Multisyl (cross-syllable merges)</i>		
Multisyl-512	15.72 [15.46, 15.98]	6.46 [6.25, 6.67]
Multisyl-1024	16.27 [16.00, 16.53]	6.63 [6.42, 6.83]
Multisyl-2048	15.72 [15.46, 15.98]	6.39 [6.18, 6.60]
<i>Multisyl-NoSep (raw input, no syllable marker)</i>		
Multisyl-nosep-512	15.87 [15.61, 16.13]	6.42 [6.22, 6.63]
Multisyl-nosep-1024	16.37 [16.11, 16.62]	6.58 [6.37, 6.78]
Multisyl-nosep-2048	18.00 [17.73, 18.26]	6.99 [6.78, 7.20]

Table 3: In-domain WER and CER on CV+SWC test ($n=24,604$), 300 M wav2vec 2.0 with CTC, on normalized text (lowercase, $\beta \rightarrow ss$, punctuation stripped). Brackets: paired-bootstrap 95 % CIs ($n_{boot}=10,000$, seed=42); bold marks the per-metric best across the 13 orthographic tokenizers.

at 6.09 %, a natural consequence of its character-level granularity. The **phonological-bias penalty is zero in-domain** on both metrics: our phonologically informed tokenizers match BPE and character baselines. The phoneme track (Table 4) shows the same pattern in PER: the 17 convergent phone tokenizers all fall in the 17.5–20.0 % band.

Table 5 adds the in-domain results for the nine tokenizers that were also fine-tuned at 1 B, so that in-domain and cross-domain results (Table 6) can be read at the same scale. Scaling the encoder lowers WER for every tokenizer, but not uniformly: at 300 M, German-BPE-512 leads and the phonologically informed tokenizers are tied with it; at 1 B the ordering inverts, with omni-vocab (11.65 %), multisyl-512 (11.88 %), and syllable-512 (12.27 %) ahead of every German-BPE variant (best 14.34 %; syllable-512 vs. German-BPE-512: P2-1b-cv in Table 7).

4.3 Q2: Dialectal OOD (RVG 1)

Table 6 (left half) shows the 1 B cross-domain results (continued-training checkpoints), scored on normalized text. On the ORT tier, **multisyl-512-1b reaches the lowest WER at 35.75 %**, ahead of omni-vocab-1b at 36.83 % (P1-ort in Table 7). On CER, omni-vocab is best at 16.53 vs. multisyl-512 at 18.11. On the TR2 tier the two systems are statis-

Phone Tokenizer	Vocab	PER % 95 % CI
<i>Atomic / raw</i>		
phone-char-raw-v2	43	18.05 [17.78, 18.33]
phone-raw-v2	50	18.35 [18.08, 18.64]
<i>Phone-BPE</i>		
phone-bpe-v2-128	128	18.04 [17.78, 18.32]
phone-bpe-v2-192	192	18.96 [18.69, 19.24]
phone-bpe-v2-256	256	19.55 [19.28, 19.83]
phone-bpe-v2-512	512	18.98 [18.71, 19.25]
phone-bpe-v2-1024	1024	17.46 [17.20, 17.73]
<i>Phone-Syllable</i>		
phone-syllable-v2-128	128	18.15 [17.88, 18.42]
phone-syllable-v2-192	192	18.31 [18.04, 18.59]
phone-syllable-v2-256	256	19.57 [19.29, 19.85]
phone-syllable-v2-512	512	18.55 [18.28, 18.82]
phone-syllable-v2-1024	1024	17.70 [17.43, 17.97]
<i>Phone-Multisyl (lite, top-100 syl UDS)</i>		
phone-multisyl-lite-v2-512	512	18.72 [18.45, 18.99]
phone-multisyl-lite-v2-1024	1024	19.52 [19.24, 19.80]
phone-multisyl-lite-v2-2048	2048	20.04 [19.77, 20.32]
<i>Phone-Multisyl (full, 95 % syl coverage)</i>		
phone-multisyl-v2-2048	2048	19.64 [19.37, 19.93]
phone-multisyl-v2-3072	3072	19.96 [19.70, 20.24]
phone-multisyl-v2-3840 [†]	3840	40.79 [40.51, 41.08]

Table 4: Phoneme-track in-domain PER on CV+SWC test (300 M). Bold marks the best. Spread across the 17 convergent variants is ~ 2.5 pp; phone-char-raw-v2 (43 tokens) is within reach of phone-bpe-v2-1024 with a $24\times$ smaller vocabulary. [†]phone-multisyl-v2-3840 has not converged at 20 k steps and is excluded from comparisons.

tically indistinguishable (45.62 vs. 45.35; P1-tr2). On ORT, syllable-512-1b is third (38.63 / 21.77).

This pattern is consistent with syllable-aware tokenization absorbing dialectal phonetic variation (aligned examples in Appendix B). Each German dialect realizes the canonical syllable slightly differently, and we hypothesize that syllable-level CTC targets encourage the encoder to focus on syllable-aligned representations that are more stable than character-level detail across phonetic variation; prior work on emergent syllable-like structure in a visually grounded self-supervised speech model (Peng et al., 2023) is consistent with this picture. The character-level multilingual baseline must instead reconcile every character with every variant pronunciation. A direct test would require representation-level analysis (e.g., diagnostic classifiers for syllable boundaries), which we leave to future work. The fact that the advantage emerges on ORT but is statistically absent on the phonetically faithful TR2 tier (P1-tr2) further suggests that the syllable advantage on RVG 1-ORT depends on the canonical-orthography reference and weakens

Tokenizer	WER %		CER %
	1 B	300 M	1 B
<i>Multilingual character inventory</i>			
omni-vocab	11.65	15.64	5.08
<i>Data-driven BPE (German)</i>			
German-BPE-512	14.34	14.93	5.93
German-BPE-1024	15.90	16.88	6.47
German-BPE-2048	14.64	16.11	6.25
<i>Syllable (Pyphen)</i>			
Syllable-512	12.27	15.16	5.35
Syllable-1024	13.04	15.44	5.58
Syllable-2048	15.44	15.94	6.32
<i>Multisyl</i>			
Multisyl-512	11.88	15.72	5.25
Multisyl-nosep-512	13.67	15.87	5.70

Table 5: In-domain WER/CER on CV+SWC test ($n=24,604$) for the nine tokenizers also fine-tuned at 1 B (continued-training checkpoints), alongside their 300 M WER from Table 3. Scoring as in Table 3; bold marks the best per column.

when the reference includes dialect markers.

4.4 Q3: Spontaneous-lexical OOD (Verbmobil)

Table 6 (right half) shows a much flatter picture. On the ORT tier, **syllable-512-1b reaches the lowest WER at 21.27 %**, ahead of multisyl-512-1b (22.05 %) and omni-vocab-1b (22.16 %), which are statistically indistinguishable from each other (C1-vm in Table 7); syllable-1024 leads on CER (13.51 vs. 14.08 for omni-vocab). All German-BPE variants and syllable-2048 fall between 24.17 and 26.95 %, at least 2 pp behind these leaders. The TR2 tier mirrors ORT throughout (0.5 to 1 pp higher, unchanged ordering). The systems in front are therefore the phonologically informed tokenizers at $|V| \leq 1024$ together with the character baseline, and syllable-2048 falls 4.3 pp behind syllable-512, the same direction as on RVG 1 (§4.5).

The shift on Verbmobil is driven by new lexical material rather than phonetic variation: hesitations (“em”, “naja”), phonetic-shorthand verb conjugations (“müsten” for “müssten”), and discourse particles. A character tokenizer has no out-of-vocabulary problem, whereas a syllable- or BPE-based vocabulary fails on these unseen forms via cascading substitutions (aligned examples in Appendix B). One consistent (though confounded with vocabulary type) interpretation is that finer-grained inventories simply have more recovery paths when no whole word matches: omni-vocab emits ≈ 6.9

tokens per word in our test data, multisyl-512 only ≈ 4.5 . In aggregate WER this advantage is offset by the character inventory’s own failure mode of transcribing reduced function words literally, so on Verbmobil the two error types cancel rather than one dominating.

Pairwise significance tests on nine focal comparisons (Table 7, top block) confirm this picture: every comparison on CV+SWC passes Bonferroni correction at $\alpha=0.05$; the syllable-vs-German-BPE comparisons on RVG 1 are strongly significant in both directions; and the multisyl-vs-omni-vocab comparison on RVG 1 sits at the Bonferroni boundary on the ORT tier (P1-ort) and fails significance on the TR2 tier (P1-tr2), as it does on Verbmobil (C1-vm). For absolute scale, Whisper-large-v3 (Radford et al., 2023) and Parakeet-TDT-v3 (Sekoyan et al., 2025), both trained on two to three orders of magnitude more audio, reach 11.4 % and 11.9 % in-domain WER on the same CV+SWC test set (statistically tied with our best 1 B fine-tune at 11.7 %) but sit 5 to 20 pp ahead cross-domain. We report these numbers for context only; training-data scale is orthogonal to the tokenizer question and is not the contribution of this work.

4.5 Vocabulary size and tokenizer family interact

In-domain, both effects are small: marginal WER varies by 1.0 pp across $|V|$ and by 1.2 pp across families, and $|V|=512$ is best or tied within every family. Under domain shift the two factors interact (Table 8). As $|V|$ grows, German-BPE improves on RVG 1 while Syllable degrades, so the 8.5 pp lead of Syllable at $|V|=512$ turns into a 1.5 pp deficit at 2048; Verbmobil shows the same crossover (−4.2 to +1.4 pp). The paired-bootstrap interaction contrast is +10.0 pp on RVG 1 and +5.6 pp on Verbmobil (C2 in Table 7).

Granularity alone cannot account for this pattern. Finer tokenizers are better on average (Spearman ρ between characters per token and WER across the nine 1 B systems: +0.67 on RVG 1-ORT, +0.68 on Verbmobil-ORT), but Syllable is the finer tokenizer at every $|V|$, so a monotone effect of granularity predicts no crossover at all, and a granularity-matched pair still differs significantly on both corpora (C3). Undertraining of large vocabularies does not account for it either: with the audio budget fixed, Syllable-2048 receives $1.6\times$ more target-token occurrences per vocabulary entry than German-BPE-2048 and still loses to it

wav2vec 2.0, 1 B (continued-training checkpoints)								
Tokenizer	RVG 1 (dialectal spontaneous, $n=442$)				Verbmobil (spontaneous, German, $n\approx 13,600$)			
	ORT		TR2		ORT		TR2	
	WER	CER	WER	CER	WER	CER	WER	CER
<i>Multilingual character inventory</i>								
omni-vocab	36.83 $\pm$ 2.1	16.53 $\pm$ 1.3	45.35 $\pm$ 1.8	18.23 $\pm$ 1.1	22.16 $\pm$ 0.3	14.08 $\pm$ 0.2	22.68 $\pm$ 0.3	14.10 $\pm$ 0.2
<i>Data-driven BPE (German)</i>								
German-BPE-512	47.12 $\pm$ 2.3	27.75 $\pm$ 1.9	54.75 $\pm$ 2.0	28.79 $\pm$ 1.8	25.47 $\pm$ 0.3	16.63 $\pm$ 0.3	26.40 $\pm$ 0.3	16.61 $\pm$ 0.3
German-BPE-1024	45.07 $\pm$ 2.1	25.00 $\pm$ 1.6	52.72 $\pm$ 1.8	25.87 $\pm$ 1.4	26.95 $\pm$ 0.3	16.05 $\pm$ 0.3	27.88 $\pm$ 0.3	16.05 $\pm$ 0.3
German-BPE-2048	42.80 $\pm$ 2.0	25.82 $\pm$ 1.7	51.14 $\pm$ 1.8	26.79 $\pm$ 1.5	24.17 $\pm$ 0.3	15.40 $\pm$ 0.3	25.14 $\pm$ 0.3	15.38 $\pm$ 0.3
<i>Syllable (Pyphen)</i>								
syllable-512	38.63 $\pm$ 2.3	21.77 $\pm$ 1.8	48.24 $\pm$ 2.0	23.48 $\pm$ 1.6	21.27 $\pm$ 0.3	14.10 $\pm$ 0.3	22.10 $\pm$ 0.3	14.12 $\pm$ 0.3
syllable-1024	42.37 $\pm$ 2.4	25.24 $\pm$ 2.0	51.09 $\pm$ 2.1	26.59 $\pm$ 1.8	21.83 $\pm$ 0.3	13.51 $\pm$ 0.3	22.83 $\pm$ 0.3	13.52 $\pm$ 0.3
syllable-2048	44.31 $\pm$ 2.1	25.10 $\pm$ 1.7	52.10 $\pm$ 1.9	26.02 $\pm$ 1.5	25.60 $\pm$ 0.3	15.78 $\pm$ 0.2	26.39 $\pm$ 0.3	15.69 $\pm$ 0.2
<i>Multisyl</i>								
multisyl-512	35.75 $\pm$ 2.0	18.11 $\pm$ 1.4	45.62 $\pm$ 1.8	20.02 $\pm$ 1.2	22.05 $\pm$ 0.3	14.93 $\pm$ 0.3	22.77 $\pm$ 0.3	14.89 $\pm$ 0.3
<i>Multisyl-NoSep</i>								
multisyl-nosep-512	45.14 $\pm$ 2.4	24.22 $\pm$ 1.8	53.02 $\pm$ 2.1	25.43 $\pm$ 1.6	23.94 $\pm$ 0.3	14.47 $\pm$ 0.3	24.73 $\pm$ 0.3	14.43 $\pm$ 0.3

Table 6: Cross-domain WER/CER (%) at 1 B on normalized text (lowercase, $\beta \rightarrow ss$, punctuation stripped), by tokenizer family. RVG 1: pooled train+dev+test ($n=442$, audio chunked at silence to ≤ 60 s); Verbmobil: German subset, pooled ($n=13,613$ ORT / 13,618 TR2 scored for all nine systems). $\pm$ = paired-bootstrap 95 % CI half-width ($n_{boot}=10,000$, seed=42); bold = best per column. Significance tests: Table 7.

(Appendix C). We therefore read the crossover as a capacity effect: at small $|V|$ the phonological prior supplies structure that BPE cannot afford to represent, whereas at large $|V|$ BPE rediscovers syllable-like units on its own and the hard syllable constraint becomes a liability. C3 replicates on a second, architecturally different backbone, as do the directions of C1 and C2 on RVG 1 (mHuBERT-147; Appendix A).

4.6 Analysis: error patterns are tokenizer-invariant

We compute confusion matrices for all 18 phoneme tokenizers across all three corpora. The pattern is striking: across every tokenizer the top-5 in-domain substitution pairs are the same bidirectional function-word swaps (“der” $\leftrightarrow$ “die”, “und” $\leftrightarrow$ “der”, “und” $\leftrightarrow$ “die”), with maximum count differences between tokenizers ≤ 10 % for the 17 well-converged runs (the 40 %-PER outlier phone-multisyl-v2-3840 shows the same ranking at inflated absolute counts). This invariance holds across representative extremes of vocabulary size and merge strategy (e.g., phone-char-raw, phone-bpe-1024, phone-multisyl-lite-512). One important caveat remains: the confusion counts are computed at the whitespace-separated SAMPA-word level rather than at the atomic-IPA-segment level (see Limitations). Atomic-phoneme confusion analysis is

left for future work; we therefore read the present observation as indirect evidence that the encoder determines *which* errors occur on these data, while the tokenizer modulates *how many*. In §4.7 we show that this redistribution materially affects deployment WER under domain shift.

4.7 Discussion

The opening question, whether *phonologically informed* tokenizers built from German syllabification and grapheme-to-phoneme mappings might offer something that data-driven and multilingual defaults do not, admits a nuanced answer in three positive components.

Phonologically informed tokenizers are fully competitive in-domain. All top tokenizers cluster within their confidence intervals on CV+SWC, so adopting syllable- or phoneme-derived units incurs no in-domain accuracy cost while adding practical advantages: more interpretable confusion analyses, smaller embedding tables in production (relative to the 10,288-token multilingual character inventory), and a linguistically transparent design space.

Under domain shift, the choice of output unit becomes a useful tool whose payoff depends on vocabulary size rather than on the type of shift. When the shift is phonetic (RVG 1-ORT), the syllable-aware multisyl-512 takes the WER lead while omni-vocab stays ahead on CER; when it

ID	Comparison	Setup	WER A / B	Δ (95 % CI)	p_{boot}
P1-ort	msy-512 vs omni @ 1B	RVG 1 ORT	35.75 / 36.83	-1.1 [-2.0, -0.2]	0.019
P1-tr2	msy-512 vs omni @ 1B	RVG 1 TR2	45.62 / 45.35	+0.3 [-0.5, +1.0]	0.518
P2-300m-cv	syl-512 vs gBPE-512 @ 300M	CV+SWC	15.16 / 14.93	+0.2 [+0.1, +0.3]	<0.001*
P2-1b-cv	syl-512 vs gBPE-512 @ 1B	CV+SWC	12.27 / 14.34	-2.1 [-2.2, -2.0]	<0.001*
P2-300m-ort	syl-512 vs gBPE-512 @ 300M	RVG 1 ORT	46.23 / 42.30	+3.9 [+3.3, +4.7]	<0.001*
P2-1b-ort	syl-512 vs gBPE-512 @ 1B	RVG 1 ORT	38.63 / 47.12	-8.5 [-9.8, -7.2]	<0.001*
P2-300m-tr2	syl-512 vs gBPE-512 @ 300M	RVG 1 TR2	53.24 / 49.81	+3.4 [+2.8, +4.0]	<0.001*
P2-1b-tr2	syl-512 vs gBPE-512 @ 1B	RVG 1 TR2	48.24 / 54.75	-6.5 [-7.6, -5.4]	<0.001*
P3	p-char-raw vs p-BPE-1024 @ 300M	CV+SWC (PER)	18.05 / 17.46	+0.6 [+0.5, +0.7]	<0.001*
<i>Interaction contrasts at 1 B (separate Bonferroni family, $k=5$)</i>					
C1-vm	msy-512 vs omni @ 1B	Verbmobil ORT	22.05 / 22.16	-0.1 [-0.3, +0.1]	0.214
C2-ort	(syl - gBPE) @2048 - @512	RVG 1 ORT	-8.5 / +1.5	+10.0 [+8.4, +11.6]	<0.001*
C2-vm	(syl - gBPE) @2048 - @512	Verbmobil ORT	-4.2 / +1.4	+5.6 [+5.4, +5.9]	<0.001*
C3-ort	syl-1024 vs msy-nosep-512 @ 1B	RVG 1 ORT	42.37 / 45.14	-2.8 [-3.9, -1.6]	<0.001*
C3-vm	syl-1024 vs msy-nosep-512 @ 1B	Verbmobil ORT	21.83 / 23.94	-2.1 [-2.3, -1.9]	<0.001*

Table 7: Paired-bootstrap tests on Δ -WER (10,000 resamples, seed=42; normalized text as in Table 3). Top: nine focal comparisons. Bottom: interaction contrasts at 1 B; C1 on RVG 1 is P1-ort, and for C2 the WER column lists the two constituent differences $\Delta_{512} / \Delta_{2048}$ (syllable minus German-BPE) whose difference is the reported Δ . Verbmobil contrasts use the German subset (Table 6). * = passes per-dataset Bonferroni correction ($\alpha=0.05/k$). 1 B values use the continued-training checkpoints, 300 M and phoneme-track values their single-stage runs. *omni* = omni-vocab, *msy* = multisyl, *syl* = syllable, *gBPE* = German-BPE, *p-* = phone track.

$ V $	RVG 1-ORT gBPE/Syl (Δ)	Verbmobil-ORT gBPE/Syl (Δ)
512	47.12 / 38.63 (-8.5)	25.47 / 21.27 (-4.2)
1024	45.07 / 42.37 (-2.7)	26.95 / 21.83 (-5.1)
2048	42.80 / 44.31 (+1.5)	24.17 / 25.60 (+1.4)
$\Delta_{2048} - \Delta_{512}$	+10.0*	+5.6*

Table 8: WER (%) at 1 B by vocabulary size for German-BPE (gBPE) and Syllable (Syl) on the two OOD sets (ORT tier; Verbmobil: German subset). Δ = Syllable - German-BPE; the last row is the paired-bootstrap interaction contrast (C2 in Table 7; * $p < 0.001$).

is lexical (Verbmobil), syllable-512 takes the lead with omni-vocab about one point behind and every German-BPE variant further back. The item-level mechanisms still move in the direction phonological theory would predict: syllable-aligned units anchor the model in intra-syllabic acoustic variation, and finer-grained inventories absorb out-of-vocabulary lexical material. On Verbmobil, however, they offset each other in aggregate WER. What separates the systems there is the size of the vocabulary: against German-BPE, the syllable prior wins by 4 to 8 pp at $|V|=512$ and loses on both corpora at $|V|=2048$. Tokenization thus emerges as a deployment-time lever, but one tuned against the vocabulary budget as much as against the expected mode of variation.

The acoustic encoder and the output tokenizer act as complementary, not competing,

design axes. Across all 18 phoneme-track tokenizers, the dominant error patterns are broadly similar bidirectional function-word swaps, indicating that tokenization redistributes errors along a shared encoder-fixed backbone, and this redistribution is large enough on domain-shifted data to materially change deployment outcomes. We therefore see linguistic structure not as an alternative to encoder-side improvements such as domain-adaptive pre-training (Hsu et al., 2021) but as an orthogonal lever that adds value on top of them.

5 Conclusion

Across 40 CTC fine-tunes of the Omnilingual ASR wav2vec 2.0 backbone for German (31 tokenizers at 300 M, nine at 1 B), evaluated on three orthogonal corpora, the phonologically informed tokenizers (Pyphen syllables, multi-syllable merges, phoneme-derived units) are competitive with BPE and character baselines in-domain, provide the best system on both OOD sets at small vocabulary sizes while losing that lead at larger ones, and complement rather than replace the acoustic encoder, since the dominant error patterns are broadly similar across all 18 phoneme-track variants. Linguistic structure thus remains a useful design axis for German ASR, and combining linguistic priors with encoder-side adaptation is a natural next step, as is LM rescoring, whose interaction with the output unit we leave open.

Limitations

Our largest models are 1 B parameters trained on 961 h of audio; external baselines trained on two to three orders of magnitude more data sit 5–20 pp ahead cross-domain (although in-domain WER is statistically tied), so the trade-offs we report could be partially compressed at production scale. We probe two structurally orthogonal OOD axes, dialectal-phonetic (RVG 1) and spontaneous-lexical (Verbmobil), and leave combined modes (e.g., dialectal negotiation speech), noise robustness, and code-switching to future work. All 1 B results in Tables 5, 6, and 7 use the continued-training checkpoints; the in-domain delta between initial and continued training is small (≤ 0.7 pp WER across the nine 1 B tokenizers), so the reported cross-domain effects are not dominated by undertraining of any single variant. The second-backbone replication (Appendix A) uses a 95 M base model with much higher absolute error rates, and the direction of the vocabulary-size interaction C2 depends on encoder capacity. The phoneme-track confusion analysis operates on whitespace-separated SAMPA word transcriptions rather than atomic IPA segments, and the phoneme track itself emits phoneme sequences; a deployed system would additionally require a phoneme-to-grapheme decoder (Lee et al., 2023). Findings are reported for German; the dialectal-vs-spontaneous trade-off is plausible for typologically similar languages (dialectally rich, syntactically free), but cross-linguistic generalization remains an open question we leave to future work.

Ethical Considerations

The training data (Common Voice, Spoken Wikipedia Corpus) is released under permissive licenses and consists of recordings by consenting volunteer speakers. The OOD corpora (RVG 1, Verbmobil) are licensed via the Bavarian Archive for Speech Signals (BAS) for research use. The dialectal split of RVG 1 covers a balanced regional sample of German speakers; our evaluation does not infer or release any speaker identity. ASR systems can amplify existing inequities in recognition quality across speaker groups; our findings suggest that tokenizer choice can be tuned to mitigate this for particular OOD axes (dialectal speech in our case), and we recommend that practitioners audit their tokenizer choice for the specific deployment population.

Acknowledgments

Funded by the Deutsche Forschungsgemeinschaft (DFG) – Project Number 549142762 – FIP 160.

References

- Rosana Ardila, Megan Branson, Kelly Davis, Michael Kohler, Josh Meyer, Michael Henretty, Reuben Morais, Lindsay Saunders, Francis M. Tyers, and Gregor Weber. 2020. [Common voice: A massively-multilingual speech corpus](#). In *Proceedings of the Twelfth International Conference on Language Resources and Evaluation (LREC)*, pages 4218–4222, Marseille, France. European Language Resources Association.
- Alexei Baevski, Yuhao Zhou, Abdelrahman Mohamed, and Michael Auli. 2020. [wav2vec 2.0: A framework for self-supervised learning of speech representations](#). In *Advances in Neural Information Processing Systems*, volume 33.
- Timo Baumann, Arne Köhn, and Felix Hennig. 2019. [The Spoken Wikipedia Corpus collection: Harvesting, alignment and an application to hyperlistening](#). *Language Resources and Evaluation*, 53(2):303–329.
- Maximilian Bisani and Hermann Ney. 2004. [Bootstrap estimates for confidence intervals in ASR performance evaluation](#). *Proc. IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*.
- Maximilian Bisani and Hermann Ney. 2008. [Joint-sequence models for grapheme-to-phoneme conversion](#). *Speech Communication*, 50(5):434–451.
- Hervé A. Bourlard and Nelson Morgan. 1994. [Connectionist Speech Recognition: A Hybrid Approach](#), volume 247 of *The Springer International Series in Engineering and Computer Science*. Kluwer Academic Publishers, Boston, MA.
- Susanne Burger and Florian Schiel. 1998. [RVG 1 – a database for regional variants of contemporary German](#). In *Proceedings of the 1st International Conference on Language Resources and Evaluation (LREC)*, pages 1083–1087, Granada, Spain.
- Susanne Burger, Karl Weilhammer, Florian Schiel, and Hans G. Tillmann. 2000. [Verbmobil data collection and annotation](#). In Wolfgang Wahlster, editor, *Verbmobil: Foundations of Speech-to-Speech Translation*, pages 537–549. Springer, Berlin, Heidelberg.
- Aravind Ganapathiraju, Jonathan Hamaker, Joseph Picone, Mark Ordowski, and George R. Doddington. 2001. [Syllable-based large vocabulary continuous speech recognition](#). *IEEE Transactions on Speech and Audio Processing*, 9(4):358–366.
- Alex Graves, Santiago Fernández, Faustino Gomez, and Jürgen Schmidhuber. 2006. [Connectionist temporal](#)

- classification: Labelling unsegmented sequence data with recurrent neural networks. In *Proceedings of the 23rd International Conference on Machine Learning (ICML)*, pages 369–376.
- Alex Graves, Abdel-rahman Mohamed, and Geoffrey Hinton. 2013. [Speech recognition with deep recurrent neural networks](#). In *Proceedings of the 2013 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 6645–6649, Vancouver, Canada. IEEE.
- Wei-Ning Hsu, Anuroop Sriram, Alexei Baevski, Tatiana Likhomanenko, Qiantong Xu, Vineel Pratap, Jacob Kahn, Ann Lee, Ronan Collobert, Gabriel Synnaeve, and Michael Auli. 2021. [Robust wav2vec 2.0: Analyzing domain shift in self-supervised pre-training](#). In *Proc. Interspeech*.
- Kazuki Irie, Rohit Prabhavalkar, Anjuli Kannan, Antoine Bruguier, David Rybach, and Patrick Nguyen. 2019. [On the choice of modeling unit for sequence-to-sequence speech recognition](#). In *Proc. Interspeech*.
- Abbas Khosravani, Claudiu Musat, Philip N. Garner, and Alexandros Lazaridis. 2020. [Comparison of subword segmentation methods for open-vocabulary ASR using a difficulty metric](#). Technical Report IIdiap-RR-06-2020, Idiap Research Institute.
- Mirjam Killer, Sebastian Stüker, and Tanja Schultz. 2003. [Grapheme based speech recognition](#). In *Proceedings of Eurospeech*, pages 3141–3144, Geneva, Switzerland.
- Philipp Klumpp, Tomás Arias, Paula Andrea Pérez-Toro, Elmar Nöth, and Juan Orozco-Arroyave. 2022. [Common phone: A multilingual dataset for robust acoustic modelling](#). In *Proceedings of the Thirteenth Language Resources and Evaluation Conference (LREC)*, pages 763–768, Marseille, France. ELRA.
- Arne Köhn, Florian Stegen, and Timo Baumann. 2016. [Mining the spoken Wikipedia for speech data and beyond](#). In *Proceedings of the Tenth International Conference on Language Resources and Evaluation (LREC)*, pages 4644–4647, Portorož, Slovenia. ELRA.
- Taku Kudo and John Richardson. 2018. [SentencePiece: A simple and language independent subword tokenizer and detokenizer for neural text processing](#). In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 66–71, Brussels, Belgium.
- Kai-Fu Lee, Hsiao-Wuen Hon, and Raj Reddy. 1990. [An overview of the SPHINX speech recognition system](#). *IEEE Transactions on Acoustics, Speech, and Signal Processing*, 38(1):35–45.
- Wonjun Lee, Gary Geunbae Lee, and Yunsu Kim. 2023. [Optimizing two-pass cross-lingual transfer learning: Phoneme recognition and phoneme to grapheme translation](#). *arXiv preprint*, arXiv:2312.03312.
- Franklin Mark Liang. 1983. [Word Hy-phen-a-tion by Com-put-er](#). Ph.D. thesis, Stanford University, Department of Computer Science. Report STAN-CS-83-977.
- Tatiana Likhomanenko, Qiantong Xu, Vineel Pratap, Paden Tomasello, Jacob Kahn, Gilad Avidov, Ronan Collobert, and Gabriel Synnaeve. 2021. [Rethinking evaluation in ASR: Are our models robust enough?](#) In *Proc. Interspeech*, pages 311–315.
- Kavya Manohar, A. R. Jayan, and Rajeev Rajan. 2023. [Improving speech recognition systems for the morphologically complex Malayalam language using subword tokens for language modeling](#). *EURASIP Journal on Audio, Speech, and Music Processing*, 2023(1):47.
- Mehryar Mohri, Fernando Pereira, and Michael Riley. 2002. [Weighted finite-state transducers in speech recognition](#). *Computer Speech & Language*, 16(1):69–88.
- Amr El-Desoky Mousa, M. Ali Basha Shaik, Ralf Schlüter, and Hermann Ney. 2012. [Morpheme level feature-based language models for German LVCSR](#). In *Proc. Interspeech*, pages 170–173.
- Josef R. Novak, Nobuaki Minematsu, and Keikichi Hirose. 2012. [WFST-based grapheme-to-phoneme conversion: Open source tools for alignment, model-building and decoding](#). In *Proceedings of the 10th International Workshop on Finite State Methods and Natural Language Processing (FSMNLP)*, pages 45–49. Association for Computational Linguistics.
- Omnilingual ASR team, Gil Keren, Artyom Kozhevnikov, Yen Meng, Christophe Ropers, Matthew Setzler, Skyler Wang, Ife Adebara, Michael Auli, Can Balioglu, Kevin Chan, Chierh Cheng, Joe Chuang, Caley Droof, Mark Duppenhaler, Paul-Ambroise Duquenne, Alexander Erben, Cynthia Gao, Gabriel Mejia Gonzalez, and 14 others. 2025. [Omnilingual ASR: Open-source multilingual speech recognition for 1600+ languages](#). *arXiv preprint*, arXiv:2511.09690.
- Vasileios Papadourakis, Markus Müller, Jing Liu, Athanasios Mouchtaris, and Maurizio Omologo. 2021. [Phonetically induced subwords for end-to-end speech recognition](#). In *Proc. Interspeech*. Amazon Alexa Machine Learning.
- Puyuan Peng, Shang-Wen Li, Okko Räsänen, Abdelrahman Mohamed, and David Harwath. 2023. [Syllable discovery and cross-lingual generalization in a visually grounded, self-supervised speech model](#). In *Proc. Interspeech*, pages 391–395.
- Pyphen developers. 2023. [Pyphen: pure Python hyphenation library](#). Uses Knuth–Liang hyphenation patterns (Liang, 1983).
- Zhongdi Qu, Parisa Haghani, Eugene Weinstein, and Pedro Moreno. 2017. [Syllable-based acoustic modeling with CTC-SMBR-LSTM](#). In *Proc. IEEE Automatic*

Speech Recognition and Understanding Workshop (ASRU), pages 173–177.

Alec Radford, Jong Wook Kim, Tao Xu, Greg Brockman, Christine McLeavey, and Ilya Sutskever. 2023. [Robust speech recognition via large-scale weak supervision](#). In *Proceedings of the 40th International Conference on Machine Learning (ICML)*, volume 202, pages 28492–28518.

Tara N. Sainath, Rohit Prabhavalkar, Shankar Kumar, Seungji Lee, Anjuli Kannan, David Rybach, Vlad Schogol, Patrick Nguyen, Bo Li, Yonghui Wu, Zhifeng Chen, and Chung-Cheng Chiu. 2018. [No need for a lexicon? Evaluating the value of the pronunciation lexica in end-to-end models](#). In *Proc. IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*.

Florian Schiel. 1999. [Automatic phonetic transcription of non-prompted speech](#). *Proc. ICPHS*, pages 607–610.

Marc Schröder and Jürgen Trouvain. 2003. [The german text-to-speech synthesis system MARY: A tool for research, development and teaching](#). *International Journal of Speech Technology*, 6(4):365–377.

Monica Sekoyan, Nithin Rao Koluguri, Nune Tadevosyan, Piotr Zelasko, Travis Bartley, Nikolay Karpov, Jagadeesh Balam, and Boris Ginsburg. 2025. [Canary-1B-v2 & Parakeet-TDT-0.6B-v3: Efficient and high-performance models for multilingual ASR and AST](#). *arXiv preprint*, arXiv:2509.14128.

Rico Sennrich, Barry Haddow, and Alexandra Birch. 2016. [Neural machine translation of rare words with subword units](#). In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1715–1725, Berlin, Germany. Association for Computational Linguistics.

Hainan Xu, Shuoyang Ding, and Shinji Watanabe. 2019. [Improving end-to-end speech recognition with pronunciation-assisted sub-word modeling](#). In *Proc. IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*.

Steve J. Young, Julian J. Odell, and Philip C. Woodland. 1994. [Tree-based state tying for high accuracy acoustic modelling](#). In *Proceedings of the Workshop on Human Language Technology (HLT '94)*, pages 307–312, Plainsboro, New Jersey. Association for Computational Linguistics.

Marcely Zanon Boito, Vivek Iyer, Nikolaos Lagos, Laurent Besacier, and Ioan Calapodescu. 2024. [mHuBERT-147: A compact multilingual HuBERT model](#). In *Proc. Interspeech*, pages 3939–3943.

Mohammad Zeineldeen, Albert Zeyer, Wei Zhou, Thomas Ng, Ralf Schlüter, and Hermann Ney. 2020. [A systematic comparison of grapheme-based vs. phoneme-based label units for encoder-decoder-attention models](#). *arXiv preprint*, arXiv:2005.09336.

Thomas Zenkel, Ramon Sanabria, Florian Metze, and Alex Waibel. 2018. [Subword and crossword units for CTC acoustic models](#). In *Proc. Interspeech*, pages 396–400.

Wei Zhou, Mohammad Zeineldeen, Zuoyun Zheng, Ralf Schlüter, and Hermann Ney. 2021. [Acoustic data-driven subword modeling for end-to-end speech recognition](#). In *Proc. Interspeech*, pages 2886–2890.

A Replication on a Second Backbone

To test whether the interaction structure of §4.5 is specific to the wav2vec 2.0 encoder, we repeat the experiment with mHuBERT-147 (Zanon Boito et al., 2024), a 95 M-parameter multilingual HuBERT base model that differs from Omnilingual ASR in self-supervised objective, architecture, and pretraining mixture. The encoder is the only change: the CTC recipe, training data, tokenizer artifacts, optimizer, learning-rate schedule, and audio budget of §4.1 are reused unchanged. Because mHuBERT-147 is a raw self-supervised checkpoint rather than an ASR-adapted one, the encoder is frozen for the first 10 k steps while the CTC head is trained (the standard HuBERT fine-tuning recipe; the setting is tokenizer-independent), and training runs for 30 k steps so that the encoder receives the same 20 k fine-tuning updates as in the main experiments. We train the eight systems that enter the contrasts C1–C3 and evaluate them with the protocol of §3.8.

Table 9 reports the three paired-bootstrap contrasts on both backbones; Table 10 gives the per-system WER. Absolute error rates are two to three times higher than at 1 B, as expected for a 95 M base model; the test is whether the sign structure replicates. C3 does so on both corpora, and C1 on RVG 1: multisyl-512 again beats omni-vocab on dialectal speech, and the granularity-matched pair again differs significantly on RVG 1 and on Verbmobil. C2 replicates on RVG 1 with a similar magnitude (+8.7 vs. +10.0 pp) but is negative on Verbmobil, where the same contrast is −0.9 pp on the 300 M wav2vec 2.0 fine-tunes as well: its direction tracks encoder capacity rather than the encoder family. Per-system rankings transfer poorly between backbones (Spearman ρ between the mHuBERT-147 and 300 M wav2vec 2.0 rankings of the eight systems: 0.00 on RVG 1, +0.57 on Verbmobil, +0.38 in-domain), which is what the interaction reading predicts: a ranking is not a property of the tokenizer alone. An interaction that survives an encoder swap cannot be a

Contrast	Set	wav2vec 2.0, 1 B (Table 7)		mHuBERT-147, 95 M	
		Δ (95 % CI)	p_{boot}	Δ (95 % CI)	p_{boot}
C1: msy-512 – omni	RVG 1 ORT	−1.1 [−2.0, −0.2]	0.019	−1.0 [−1.7, −0.3]	0.006
	Verbmobil ORT	−0.1 [−0.3, +0.1]	0.214	−0.3 [−0.5, −0.1]	<0.001
C2: (syl – gBPE)@2048 – @512	RVG 1 ORT	+10.0 [+8.4, +11.6]	<0.001	+8.7 [+7.8, +9.7]	<0.001
	Verbmobil ORT	+5.6 [+5.4, +5.9]	<0.001	−0.6 [−0.8, −0.4]	<0.001
C3: syl-1024 – msy-nosep-512	RVG 1 ORT	−2.8 [−3.9, −1.6]	<0.001	−2.1 [−2.6, −1.5]	<0.001
	Verbmobil ORT	−2.1 [−2.3, −1.9]	<0.001	−0.8 [−0.9, −0.6]	<0.001

Table 9: Interaction contrasts C1–C3 (Δ -WER in pp, paired bootstrap, 10,000 resamples, seed=42) on the two backbones; scoring and abbreviations as in Table 7; Verbmobil on the German subset.

Tokenizer	RVG 1 ORT	Verbmobil ORT	CV+SWC test
omni-vocab	69.50	45.36	22.35
German-BPE-512	70.36	45.23	24.38
German-BPE-2048	63.27	46.57	28.24
syllable-512	63.32	43.44	23.26
syllable-1024	64.04	44.51	24.20
syllable-2048	64.95	44.18	25.37
multisyl-512	68.52	45.05	23.20
multisyl-nosep-512	66.11	45.26	24.09

Table 10: WER (%) of the eight mHuBERT-147 fine-tunes (30 k steps, 10 k of them with the encoder frozen); test sets and scoring as in Tables 3 and 6 (Verbmobil: German subset). Bold marks the best per column.

property of the wav2vec 2.0–tokenizer match.

B Aligned Recognition Examples

Tables 11 and 12 illustrate the error types behind the cross-domain results, using the 1 B systems omni-vocab, multisyl-512, and German-BPE-512 (one per tokenizer class). Examples are selected automatically rather than by hand: we align reference and hypothesis at the word level, slide windows of 4–10 reference words over every utterance, and discard windows in which any system’s hypothesis collapses (hypothesis length outside 0.6–1.5 times the window length). On RVG 1 we keep windows in which multisyl-512 is error-free while every omni-vocab error is a near-miss substitution (character distance ≤ 2), i.e., a phonetic rendering of a dialectal realization; on Verbmobil (German utterances) we keep windows in which omni-vocab is error-free while both subword systems err on a word absent from the 6.14 M-word training text. Windows are ranked by the number of such errors, at most one window per utterance; one counterexample with the opposite pattern is shown per corpus.

The two corpora show different error types.

On RVG 1 the character inventory transcribes reduced dialectal forms literally (*habe*→*hab*, *ist*→*is*, *und*→*un*) and drops consonants inside function words, whereas syllable-constrained units restore the canonical form. On Verbmobil the subword systems fail on out-of-vocabulary compounds and names by producing plausible but wrong forms (*arbeitsstreffen*, *anderthalbäiges*), while the character inventory spells them correctly; the most frequent substitutions (Table 12), colloquial contractions such as *wäre*→*wär* and *es*→*s*, are shared by all systems.

C Target-Token Statistics per Run

Batching is audio-element-based (§4.1), so every run sees the same audio for the same number of updates while the number of target tokens varies with tokenizer fertility. Table 13 reports, for each orthographic tokenizer, the corpus-level fertility on the training text, the resulting number of target tokens per pass, and the average number of token occurrences per vocabulary entry. The last column is the quantity an undertraining account of the vocabulary-size effect (§4.5) would have to invoke, and it does not support one: at $|V|=2048$ the Syllable tokenizer receives $1.6\times$ more occurrences per entry than German-BPE (9.7 k vs. 6.0 k) and nonetheless loses to it.

Reference	omni-vocab	multisyl-512	German-BPE-512
<i>RVG 1</i>			
und dann habe ich gedacht da konnte man etwas erzählen und dann haben wir jetzt tag verdienen hektik gab es auch und die alarmanlage muss man [†]	und ann ab ch gedacht da konte an etas erzählen und dan aben ir jetzt tag erdienen hekti gab s auch und die alarmanlage muss man	und dann habe ich gedacht da konnte man etwas erzählen und dann haben wir jetzt tag verdienen hektik gab es auch und der lamanlage mussss man	und dann habe ich gedacht da konn manwas erzählen und dann haben wir jetzt tag verdiener hektik gab es auch und der lamanlage muss man
<i>Verbmobil (German utterances)</i>			
gerne herrn schiel gesprochen ein anderthalbtägiges arbeit- streffen in ihnen unser eineinhalbtägiges arbeitstreffen schindel ich möchte mit ihnen gerne einige arbeitssitzungen dann könnten wir uns vielleicht auch noch [†]	erne herrn schiel gesprochen ein anderthalbtägiges arbeit- streffen in ihnen unser eineinhalbtägiges arbeitstreffen schindel ich möchte mit ihnen gerne einige arbeitssitzungen dann können wir us vieleit ach noch	gerner herrn schkiel gesprochen ein anderthalbtägiges ar- beitsstreffen in ihnen unser eineinhalbtägiges arbeitstreffen schinl ich möchte mit ihnen gerne einige arbeitsetzungen dann könnten wir uns vielleicht auch noch	undner herrn schiel gesprochen ein anderthalbägiges arbeit- streffen in ihnen unser eineinhalbt- tägiges arbeitstreffen schinel ich möchte mit ihnen gerne einige arbeitssitzungen dann könnten wir uns vielleicht auch noch

Table 11: Automatically selected reference/hypothesis windows (1 B systems, normalized text). Bold marks hypothesis words that do not match the reference. Selection: RVG 1 windows in which multisyl-512 is error-free and every omni-vocab error is a near-miss substitution (character distance ≤ 2); Verbmobil windows in which omni-vocab is error-free and both subword systems err on a word absent from the training text. [†]Counterexample with the opposite pattern.

System	Most frequent word substitutions (reference→hypothesis, count)
<i>RVG 1-ORT</i>	
omni-vocab	habe→hab (296), das→es (76), es→s (69), das→des (61), dann→dan (45), ist→is (44), dass→das (42), und→un (35)
multisyl-512	habe→ha (232), habe→hab (100), das→es (60), halt→ha (55), das→des (41), dass→dasss (38), noch→nur (38), dass→das (36)
German-BPE-512	ja→j (70), was→w (50), das→es (46), bisschen→bis (42), habe→hab (38), habe→h (32), bin→b (32), das→des (29)
<i>Verbmobil-ORT (German)</i>	
omni-vocab	wäre→wär (767), es→s (637), habe→hab (469), das→es (327), einen→ein (211), würde→wird (174), ginge→ging (160), mal→nochmal (159)
multisyl-512	wäre→wä (418), wäre→wär (401), es→s (330), das→es (303), habe→hab (299), wiederhören→hören (298), mal→nochmal (229), habe→ha (181)
German-BPE-512	wäre→wä (466), das→es (343), einen→ein (293), ja→j (246), wäre→w (225), habe→hab (214), ist→es (213), ihnen→ihn (190)

Table 12: Eight most frequent word substitutions per system (1 B, normalized text) on the two OOD sets. On RVG 1 the substitutions are dominated by reduced dialectal realizations of function words; on Verbmobil by colloquial contractions shared by all systems.

Tokenizer	$ V $	tok/wd	ch/tok	tokens (M)	per entry (k)
<i>Multilingual character inventory</i>					
omni-vocab	10,288	6.96	0.87	42.7	4.2
<i>Data-driven BPE (German)</i>					
German-BPE-512	512	2.72	2.23	16.7	32.6
German-BPE-1024	1024	2.32	2.61	14.2	13.9
German-BPE-2048	2048	1.99	3.04	12.2	6.0
<i>Syllable (Pyphen)</i>					
Syllable-512	512	3.83	1.58	23.5	45.9
Syllable-1024	1024	3.49	1.74	21.4	20.9
Syllable-2048	2048	3.24	1.87	19.9	9.7
<i>Multisyl</i>					
Multisyl-512	512	4.55	1.33	27.9	54.6
Multisyl-1024	1024	4.41	1.37	27.1	26.4
Multisyl-2048	2048	4.34	1.40	26.7	13.0
<i>Multisyl-NoSep</i>					
Multisyl-nosep-512	512	3.51	1.72	21.6	42.1
Multisyl-nosep-1024	1024	3.36	1.80	20.6	20.2
Multisyl-nosep-2048	2048	3.26	1.85	20.0	9.8

Table 13: Target-token statistics for the 13 orthographic tokenizers, from corpus-level fertility on the training text (550,747 sentences, 6,141,326 words). *tokens* = tokens per word $\times$ words; *per entry* = tokens / $|V|$, i.e., how often an average vocabulary entry occurs in one pass over the training text; this is distinct from gradient steps, which are fixed at 20 k for every run (§4.1). The phoneme track is tokenized on its own SAMPA transcripts and is not included.