

IDEEA: training-free Input-Dependent stEEring via Activation cluster matching

Zheng Wang^{1,2*} Muchen Li^{1,2} Renjie Liao^{1,2,3} Yan Leng^{4†}

¹University of British Columbia ²Vector Institute for AI ³Canada CIFAR AI Chair

⁴University of Texas at Austin

Abstract

Steering aligns large language models (LLMs) by injecting a bias into selected activations at inference time, offering a far cheaper alternative to weight-update methods such as supervised fine-tuning or reinforcement learning. However, most existing training-free steering methods are *input-independent*: a single direction is fitted once and shared across all inputs. This is fundamentally limiting as different inputs occupy different regions of the activation space and admit different optimal steering directions toward the same target concept, much as the gradient with respect to a fixed loss varies from input to input. We close this gap with IDEEA (Input-Dependent stEEring via Activation cluster matching), a training-free framework for *input-dependent steering*. IDEEA clusters the positive and negative activation supports per attention head, and solves an optimal-matching problem to construct a *set* of cluster-conditional directions, all about the target concept. At inference time, it picks from this pool of directions and uses the one that best matches the input’s own activation for steering. IDEEA aligns the model toward the target concept while preserving the input’s original representation, evidence that activations encoding a concept occupy several distinct sub-regions of the representation space rather than a single one. IDEEA improves the *truth* $\times$ *info rate* in TruthfulQA by an average of 9.9% (up to 23.5%) over the best input-independent baseline. Code: <https://github.com/DSL-Lab/IDEEA>.

1 Introduction

Pre-training equips large language models (LLMs) with broad knowledge but no guidance on *how* to behave—whether to be truthful, helpful, or safe. Aligning their behavior typically requires weight

updates—supervised fine-tuning, RLHF (Ouyang et al., 2022), DPO (Rafailov et al., 2023), GRPO (Shao et al., 2024), or parameter-efficient variants like LoRA (Wang et al., 2024)—all of which demand non-trivial compute, curated data, and, in the RL case, a separate reward model.

Steering offers a markedly cheaper alternative: rather than modifying any weights, a linear bias is added to selected activations at inference time, pushing the response along a chosen direction (Li et al., 2023; Rinsky et al., 2024). This intervention is restricted to a small subset of the model: a single layer (Rinsky et al., 2024; He et al., 2025; Rodriguez et al., 2026) or a subset of attention heads (Li et al., 2023; Kim et al., 2025; Zou et al., 2025). This restrained perturbation allows steering to be effective while being minimally invasive. Steering methods can be further categorized by how the steering direction is obtained – through optimization or training-free instantiations such as Inference-Time Intervention (ITI) (Li et al., 2023), Contrastive Activation Addition (CAA) (Rinsky et al., 2024), and Spectral Editing of Activations (SEA) (Qiu et al., 2024) that skip the optimization stage entirely. The steering directions are computed directly from a small contrastive activation dataset, and conveniently come with a transparent geometric interpretation that is otherwise not obtainable through optimization-based steering. Training-free steering also provides a significant compute saving, as GPUs are only used during the initial activation collection phase, with a single forward pass per training sample regardless of the number of configurations (Appendix A).

However, existing training-free steering methods are still limited. They commit to a *single static operator* that is shared across every input. In practice the activations associated with a target concept are spread across several distinct sub-regions (Sec. 5.3), making such a construction insufficient for addressing high-dimensional activation spaces and leading

*Part of this work was done while an undergraduate student at the University of Waterloo.

†Corresponding author:
yan.leng@mcombs.utexas.edu




Figure 1: **IDEA** framework for input-dependent steering. (1) Collects per-head activations from contrastive prompts. (2) Clusters the positive (green) and negative (red) supports (Sec. 4.1) and obtains the cluster-optimal direction vectors (Sec. 4.2). (3) Finds the direction that best aligns with the input (pink), and use that for steering (Sec. 4.3).

to unexpected failures (Sec. 5.3).

Contributions.

- We introduce **IDEA** (**I**ntput-**D**ependent **st**EEring via **A**ctivation cluster matching), a training-free *input-dependent steering* framework that selects a steering direction conditioned on the input at inference time (Figure 1).
- IDEA clusters the positive and negative activation supports and picks, for each input, the cluster-conditional direction that best matches the input’s own representation.
- IDEA delivers superior steering effects while keeping true to the original input representations, avoiding refusal-collapse failures during inference.
- We validate IDEA on four steering tasks — truthfulness (Lin et al., 2022), social behavior traits (Leng and Yuan, 2024), political polarity (Fulay et al., 2024), and toxicity mitigation (Ji et al., 2025; Luong et al., 2024) — demonstrating that IDEA generalizes across target concepts, with consistent gains over the training-free baselines.

2 Related Work

Optimization-based steering. A complementary family of steering methods finds the steering direction via gradient optimization, often paired with RL-style objectives (Zou et al., 2025; Rodriguez et al., 2026; Cao et al., 2024). These methods can be effective but inherit the compute overhead

of classical alignment and lack a transparent geometric interpretation of the learned direction. We instead study the converse *training-free steering*, which extracts the direction directly from the contrastive activation space.

Mass-mean steering. The *mass-mean* direction is the difference between mean positive and mean negative activations on a contrastive dataset, and is the dominant construction in training-free steering. This direction can be applied on selected attention heads as in ITI (Li et al., 2023; Kim et al., 2025), or across an entire layer as in CAA (Rimsky et al., 2024). Regardless of the perturbation location, both methods apply an invariant direction to steer all inputs.

SAE steering. A separate line of work pre-trains overcomplete sparse autoencoders (SAEs) on residual stream activations to extract monosemantic features (Bricken et al., 2023; Templeton et al., 2024), and the recovered decoder directions can then be added back into the residual stream to steer that feature. Public feature suites such as Gemma Scope (Lieberum et al., 2024), Llama Scope (He et al., 2024), AxBench (Wu et al., 2025), and Arditi and Chen (2025) make this practical without needing to retrain the SAEs per task. This approach sits between training-free and optimization-based methods: the SAE itself requires a separate training stage, although it is reusable across different tasks. However, the set of steerable concepts is bounded by the number of decoder directions in its latent space.

Input-dependent direction selection. Despite their differences, these training-free methods all commit to a single steering direction for every input. SEA (Qiu et al., 2024) seeks to close this gap with a pair of subspace projections that maximize cross-covariance with the positive activations of the contrastive set while minimizing it with the negative ones, but the same projections are applied regardless of the activation’s location in the representation manifold. As shown in Sec. 5.3, activations associated with a target concept typically span a multi-modal region of representation space. A single static operator cannot route different negative modes toward different positive modes, and would leave many positive regions unreachable. Our work relaxes this constraint by creating a set of directions about the same concept, and selecting the one that best aligns with the activation observed at

inference time (Sec. 4).

3 Preliminaries

Training-free steering methods modify model behavior at inference time without updating any model parameters. Such methods typically follow three stages: (i) collecting activations from a labeled dataset, (ii) deriving steering directions from these activations, and (iii) injecting the directions back into the forward pass during generation. We adopt this overall pipeline and extend it with an input-dependent direction selection step, described in Sec. 4.

3.1 Dataset Setup

Let $D^c = \{(c_i, y_i)\}_{i=1}^N$ be a labeled set of conversations, where c_i is a conversation history that bears on a concept of interest (e.g. truthfulness, toxicity, safety), and $y_i \in \{+1, -1\}$ indicates whether the concept is preserved or violated in c_i . We probe the model’s internal representation of the concept by recording its latent activations during the forward pass. Such hooks can be attached to any module within transformer-based language models (LMs) (Vaswani et al., 2017), with the common choices being the multi-head attention (MHA) output (Li et al., 2023) and the residual stream (Rimsky et al., 2024).

3.2 Activation Collection

Building on Li et al. (2023), we collect activations from MHA outputs. In auto-regressive LMs (Vaswani et al., 2017), the MHA module is shared across L layers, with H attention heads per layer, and we index each head by its location (l, h) . During inference, the model maintains a stream of embeddings $x_0, \dots, x_n \in \mathbb{R}^{DH}$, one per input token, and autoregressively generates x_{n+1} . At layer l , the embeddings $(x_0, \dots, x_n)_l$ pass through MHA followed by a multi-layer perceptron with residual connections to produce $(x_0, \dots, x_n)_{l+1}$. Within MHA, embeddings are first projected into a D -dimensional attention space and projected back to $\mathbb{R}^{DH}$ after self-attention:

$$a_{l,h} = \text{Att}_{l,h}(P_{l,h} x_l) \quad (1)$$

$$x_{l+1} = x_l + \sum_{h=1}^H Q_{l,h} a_{l,h} \quad (2)$$

where $a_{l,h} \in \mathbb{R}^D$ is the per-head activation, and $P_{l,h} \in \mathbb{R}^{D \times DH}$, $Q_{l,h} \in \mathbb{R}^{DH \times D}$ are the input and output linear projections.

Given D^c , we record per-head activations at the residual stream position corresponding to the last input token $c_i[-1]$ (i.e. the position whose hidden state produces $\Pr(c_i[-1] \mid c_i[: -1])$) and assemble the per-head activation dataset $D_{l,h}^a = \{(a_{l,h}, y)_i\}$, which serves as the basis for forming steering directions.

3.3 Input-Independent Steering

Prior work has shown that the difference between mean positive and mean negative activations yields an effective steering direction (Li et al., 2023; Rimsky et al., 2024; Kim et al., 2025):

$$v_{l,h} = \text{mean}(D_{l,h}^{a+}) - \text{mean}(D_{l,h}^{a-}) \quad (3)$$

We then normalize $v_{l,h}$ and scale it by a global strength α together with the head-wise standard deviation $\sigma_{l,h} = \text{std}(D_{l,h}^a)$ for finer control. The resulting term is added back into the residual stream:

$$x_{l+1} = x_l + \sum_{h=1}^H Q_{l,h} (a_{l,h} + \alpha \sigma_{l,h} v_{l,h}) \quad (4)$$

While this construction yields a steering direction at every head, the heads themselves are far from equally informative about the concept. For each head (l, h) we fit a linear classifier on $D_{l,h}^a$ and use its held-out accuracy as a proxy for the head’s linear separability with respect to y . We empirically observe that this probing accuracy varies substantially across heads: many sit near chance (~ 0.5), indicating that the head has no meaningful representation of the concept, while a smaller subset attains much higher accuracy and clearly encodes it. Steering at chance-level heads injects a noisy direction that does not align with any concept signal and therefore degrades model utility without producing the intended behavioral change.

We therefore restrict the intervention to the top- K heads ranked by probing accuracy. Perturbing only at positions that best discriminate $y = \pm 1$ maximizes the effect of the intervention while preserving the model’s general capabilities elsewhere.

However, a central limitation of this approach is that the steering direction is input-agnostic: the same $v_{l,h}$ is used regardless of the input. We refer to this static family of methods as *input-independent steering*.

4 IDEEA

Although a semantic concept tends to occupy a highly cohesive region of the activation space, the

optimal direction for steering can still differ from one input to another: a single static direction averages over this variation and can therefore over- or under-correct on individual inputs. We address this by selecting the steering direction conditioned on the input at inference time, tailoring the intervention to where each activation actually lies within the concept’s manifold. We adopt the general dataset setup and activation collection from Sec. 3 (Figure 1, step 1), and introduce IDEEA, our *input-dependent steering* framework, with three new stages: clustering, optimal matching, and per-token direction selection (Figure 1, steps 2–3).

4.1 Clustering

For matching to be bijective, we initially require $D_{(l,h)}^{a+}$ and $D_{(l,h)}^{a-}$ to have the same number of clusters, $n_c^+ = n_c^- = n_c$. We adopt K-means clustering per head (l, h) for simplicity, although any unsupervised algorithm can be used.

For each head (l, h) , this yields $2n_c$ centroids $C_1^\pm, \dots, C_{n_c}^\pm$. We denote the direction from the j -th negative centroid to the i -th positive centroid as

$$v^{j,i} = C_i^+ - C_j^- \quad (5)$$

A valid bijection between positive and negative clusters consists of n_c one-to-one direction vectors with no shared endpoints. Together with the requirement that $n_c^+ = n_c^-$, it is guaranteed that valid matchings are always perfect. We can uniquely identify the matching using the corresponding direction vectors, which we denote as $V = \{v^1, \dots, v^{n_c}\}$ for brevity.

4.2 Optimal Matching

Clustering exposes the natural partition of the activation space along the target concept. Each v^i is the steering direction between a paired positive and negative cluster. There are $n_c!$ valid bijections, and we must select the one that best captures the spread of directions associated with the concept. Since all clusters describe the same underlying concept, the selected n_c directions should be mutually coherent. We measure coherence via average pairwise cosine similarity, giving the optimal matching

$$V^* = \arg \min_V \sum_{i=1}^{n_c} \sum_{j=i+1}^{n_c} -\frac{v^i \cdot v^j}{\|v^i\| \|v^j\|} \quad (6)$$

This combinatorial optimization is the NP-hard Quadratic Assignment Problem (QAP) (Koopmans

and Beckmann, 1957). An exact solution requires enumerating all $n_c!$ bijections, which remains tractable for the small n_c typical of semantic clustering.

For larger n_c , exact QAP becomes intractable. One option is to approximate V^* via the FAQ algorithm (Vogelstein et al., 2015). A second option is to relax the QAP into a Linear Assignment Problem (LAP) (Thorndike, 1950) by comparing each v^i against the mean direction $\frac{1}{n_c} \sum_{i=1}^{n_c} v^i$. Under $n_c^+ = n_c^-$, this mean coincides with the input-independent direction $v_{l,h}$, and the optimal matching reduces to

$$V^* = \arg \min_V \sum_{i=1}^{n_c} -\frac{v^i \cdot v_{l,h}}{\|v^i\| \|v_{l,h}\|} \quad (7)$$

LAP admits an exact polynomial-time solution via the Hungarian algorithm (Kuhn, 1955) in $O(n_c^3)$.

4.3 Steering

Recall from Sec. 3.3 that steering is restricted to a subset of K heads. This intervention is sparse by design: the selected heads rarely lie in the same layer, so the inter-head geometry can be sensitive to additive perturbations of the form in Eq. 4.

To minimize the discrepancy introduced by steering, we propose two strategies that use the optimal bijection $V^* = \{v^{1*}, \dots, v^{n_c*}\}$ to select an input-dependent direction at inference time.

Min-perp steering. Treating the origin of the activation space as “no meaning”, the semantic content of a token can be described by both the direction and magnitude of $a_{l,h}$. To preserve as much of the original meaning as possible, we choose the direction in V^* that is most aligned with $a_{l,h}$ while still encoding the target concept:

$$v^* = \arg \min_{v \in V^*} \text{perp}_{a_{l,h}}(v) \quad (8)$$

Nearest-cluster steering. Clustering also retains valuable geometric structure. An unseen activation $a_{l,h}$ at inference time naturally falls into the cluster whose centroid is closest, since geometric proximity reflects semantic similarity:

$$C^* = \arg \min_{C \in \{C_1^\pm, \dots, C_{n_c}^\pm\}} \|a_{l,h} - C\| \quad (9)$$

Because $n_c^+ = n_c^-$ and V^* is a bijection, the direction associated with C^* is unique, and we use it as the input-dependent direction v^* .

In both strategies, v^* is conditioned on the current activation $a_{l,h}$ at the last-token position, allowing the steering direction to adapt to the input being processed.

5 Experiments

5.1 Setup

TruthfulQA. Our primary benchmark is TruthfulQA (Lin et al., 2022), consisting of questions designed to elicit common human misconceptions. This dataset is the primary benchmark used in the original ITI paper (Li et al., 2023), making it the natural setting for a head-to-head comparison against the input-independent baseline. We follow the open-ended generation protocol of Li et al. (2023): each question is wrapped in a 6-shot QA prompt, and the model greedily decodes a free-form answer. The response is then evaluated by a pair of LLM judges, each being a fine-tuned Llama2 7B model released by Allen Institute for AI (2023a,b), for truthfulness and informativeness scores $\in [0, 1]^2$. We report the standard metrics: *truth rate*, *info rate*, and their product ($\text{truth} \times \text{info rate}$), which is the headline number because models can game *truth rate* by refusing to answer with "I don't know" that is useless despite being correct (Sec. 5.3). We split TruthfulQA with seed 0 into 50% development questions and 50% test questions; within the development set, 80% of questions are used for probe training and 20% for validation-based head selection. Clustering and steering directions are fit only on the development set, and the test set is used only for final evaluation.

Dictator game. To investigate whether the gains transfer beyond truthfulness, we additionally evaluate on the zero-sum dictator game of Leng and Yuan (2024). The model chooses between two unique payoff splits over itself and an anonymous partner, and we observe the choices on four social behavior signals — *self-interest* (S-Int), *competitive* (Comp), *difference aversion* (D-Av), and *social welfare* (S-Welf). For each trait we construct a positive context and its semantic complement, with ten open-ended scenarios. Following Leng and Yuan (2024), we evaluate on 240 unique payoff settings, each sampled five times at temperature 0.2 under seeds 1–5, for 1,200 responses per configuration. Due to the absence of high-quality data for social behavior patterns, the steering directions are fitted using only a synthetic contrastive corpus, described in Appendix K.

Political polarity. We also measure political polarity steering using TwinViews (Fulay et al., 2024), which consists of paired left-leaning and right-leaning statements on the same topic. At evaluation, we prompt the model with holdout left-leaning opinions and report the success rate of transforming into right-leaning ones, using Qwen3.5 9B (Qwen Team, 2026) as described in He et al. (2025).

Toxicity Mitigation. We collect activations and construct steering directions with contrastive safe/unsafe response pairs from PKU-SafeRLHF (Ji et al., 2025), and evaluate on the out-of-distribution malicious prompts from Thoroughly Engineered Toxicity (TET) (Luong et al., 2024). We use Qwen3.5 9B to label the responses (Appendix I), and report the ratio of responses that are marked safe.

Models. To investigate how steering interacts with different model families and scales, we evaluate six open-weight instruction-tuned models: Llama2 7B (Touvron et al., 2023), Llama3 8B (Grattafiori et al., 2024), Mistral 7B (Jiang et al., 2023), Qwen2.5 7B (Qwen et al., 2025), and Gemma2 2B and 9B (Team et al., 2024).

Baselines. We compare IDEEA against four established training-free baselines:

- **ITI** (Li et al., 2023): per-head MHA steering on the top- K probe-accuracy heads with the input-independent mass-mean direction, as described in Sec. 3.3.
- **CAA** (Rimsky et al., 2024): residual stream steering with a single mass-mean direction at one chosen layer l , applied at every token position after the prompt.
- **SAE**: a pre-trained sparse autoencoder feature (Bricken et al., 2023; Templeton et al., 2024) corresponding to the target concept is added back to the residual stream. We draw features from the publicly released suites: Gemma Scope (Lieberum et al., 2024) for Gemma2 9B, AxBench (Wu et al., 2025) for Gemma2 2B, and Arditi and Chen (2025) for Llama3 8B, identifying truth-related features via Neuronpedia (Lin, 2023). The remaining models lack such open source SAE release at the time of writing, and we thus excuse them from SAE-based steering.
- **SEA** (Qiu et al., 2024): rather than adding a direction, SEA replaces the residual stream




Figure 2: Per-head truthfulness probe accuracy on Llama2 7B. Left: train split. Right: held-out val split.

with the sum of two subspace projections that keep the leading positive cross-covariance components and ablate the negative ones. Edit strength is controlled by the number of layers modified instead of using an explicit scaling factor.

We instantiate two versions of IDEEA, both using the QAP-optimal bijection (Sec. 4.3): **min-perp** and **nearest-cluster**. We additionally consider two matching-free variants as ablations in Sec. 5.4.

Head probe quality. Both ITI and our cluster-based variants rank attention heads by linear-probe accuracy on $D_{l,h}^a$ (Sec. 3.3) and intervene only on the top- K . Figure 2 shows the per-head truthfulness probe accuracy on Llama2 7B for both the train and held-out validation splits. The accuracy is concentrated in a band around the middle layers, while most heads sit near chance, justifying the top- K restriction. The close agreement between train and val confirms that probe accuracy generalizes and is a reliable signal for head selection.

Hyperparameters. The steering strength α uses a method-specific range, since each baseline has its own natural scale. For ITI and our cluster-based methods we sweep the number of intervened heads $K \in \{1, 2, 3\} \times H$, where H is the number of heads per layer in the target model, similar to the ITI paper (Li et al., 2023), and we empirically choose the steering strength $\alpha \in \{2, 4, 6\}$.

For min-perp and nearest-cluster we additionally sweep $n_c \in \{n_{\min}, \dots, n_{\max}\}$ with $n_{\min} = 2$ and $n_{\max} = 6$, which is small enough for exact-QAP to be feasible while still capturing the semantic clusters within the target concept.

To stabilize the clustering against K-means initialization noise, every cluster fit is run 10 times with different random initializations and the run with the lowest inertia is retained. The same sequence of 10 seeds is reused across all head po-

sitions, so any difference in cluster fits between heads is due to the activations themselves rather than initialization luck.

For CAA we choose layer l over all decoder layers and $\alpha \in \{1, 2, 4, 6\}$. We additionally include $\alpha = 1$ because that is the strength reported in the original CAA paper (Rimsky et al., 2024).

For SAE we use the released feature for the target concept and sweep $\alpha \in \{1, 2, 3\}$. The upper end is set by Neuronpedia’s default steering multiplier of 3 (Lin, 2023), and we observed that pushing α higher quickly degenerates into gibberish generations.

For SEA we follow Qiu et al. (2024) and edit the last- $\mathcal{L}$ layers with spectral cutoff over their reported grid $\mathcal{K} \in \{0.95, 0.99, 0.995, 0.9999\}$ and $\mathcal{L} \in \{1, 2, 3, 4, 5, 8, 16, 24, L\}$ where L is the number of layers in the target model.

See Appendix B for further implementation details, Appendix A for compute summary, and Appendix C for artifact licenses and data statements.

5.2 Main Results

We adopt 5-fold cross-validation for our experiments: within each fold the hyperparameters are optimized on 80% of the evaluation set and scored on the held-out 20%, so no test item informs its own selection. We report the mean over folds with its standard deviation.

In Table 1, IDEEA variants achieve the best TruthfulQA $T \times I$ score on four of the six models. SEA takes the lead on the remaining two models, but ends up degrading over base on Gemma2 2B, whereas IDEEA consistently outperforms base in all cases. On average, min-perp gains 34.2% over base, followed by nearest-cluster at 28.5%, roughly doubling the strongest baseline, SEA, at 17.4%. Since cross-validation yields no single configuration, we also report the scores and corresponding best hyperparameters optimized over the entire evaluation set in Appendix D. The scores agree closely.

Table 2 reports Llama3 8B results in the dictator game. We use zero-shot prompting with no mention of the target trait when evaluating steering, and additionally include two settings that describe the trait in the system prompt for reference Appendix J: *sys prompt weak* simply names the target persona, while *sys prompt strong* also describes how that persona decides, leaking the criteria, and we treat it as an artificial upper bound. Averaged across all four traits, nearest-cluster attains the largest gain

Method	Llama2 7B			Qwen2.5 7B			Mistral 7B			Llama3 8B			Gemma2 9B			Gemma2 2B			Avg. $\Delta\%$
	T	I	$T \times I$	T	I	$T \times I$	T	I	$T \times I$	T	I	$T \times I$	T	I	$T \times I$	T	I	$T \times I$	
base	.937 $\pm$.027	.630 $\pm$.030	.567 $\pm$.037	.843 $\pm$.053	.863 $\pm$.019	.706 $\pm$.045	.818 $\pm$.032	.960 $\pm$.019	.777 $\pm$.037	.891 $\pm$.029	.792 $\pm$.034	.689 $\pm$.037	.853 $\pm$.032	.732 $\pm$.071	.585 $\pm$.059	.886 $\pm$.024	.392 $\pm$.048	.279 $\pm$.043	—
ITI	.957 $\pm$.014	.549 $\pm$.067	.509 $\pm$.069	.884 $\pm$.033	.868 $\pm$.043	.752 $\pm$.044	.868 $\pm$.014	.942 $\pm$.029	.810 $\pm$.024	.949 $\pm$.039	.724 $\pm$.062	.681 $\pm$.072	.861 $\pm$.025	.909 $\pm$.033	.770 $\pm$.032	.904 $\pm$.026	.560 $\pm$.045	.463 $\pm$.040	16.2
CAA	.924 $\pm$.043	.830 $\pm$.031	.757 $\pm$.021	.833 $\pm$.032	.911 $\pm$.030	.747 $\pm$.045	.828 $\pm$.023	.939 $\pm$.038	.770 $\pm$.051	.879 $\pm$.026	.823 $\pm$.047	.704 $\pm$.057	.884 $\pm$.033	.810 $\pm$.043	.694 $\pm$.023	.899 $\pm$.016	.395 $\pm$.037	.294 $\pm$.045	10.8
SAE	—	—	—	—	—	—	—	—	—	.848 $\pm$.044	.765 $\pm$.068	.615 $\pm$.034	.909 $\pm$.048	.643 $\pm$.074	.552 $\pm$.074	.904 $\pm$.044	.289 $\pm$.068	.192 $\pm$.064	-15.7
SEA	.982 $\pm$.026	.891 $\pm$.041	.873 $\pm$.041	.856 $\pm$.032	.977 $\pm$.017	.835 $\pm$.037	.871 $\pm$.017	.914 $\pm$.049	.785 $\pm$.053	.901 $\pm$.053	.823 $\pm$.031	.727 $\pm$.038	.879 $\pm$.026	.866 $\pm$.037	.749 $\pm$.047	.881 $\pm$.029	.390 $\pm$.050	.271 $\pm$.041	17.4
<i>IDEEA min-perp</i>	.929 $\pm$.026	.848 $\pm$.032	.785 $\pm$.039	.896 $\pm$.038	.896 $\pm$.023	.792 $\pm$.032	.871 $\pm$.047	.927 $\pm$.027	.798 $\pm$.028	.929 $\pm$.029	.884 $\pm$.026	.815 $\pm$.031	.863 $\pm$.019	.886 $\pm$.030	.749 $\pm$.030	.937 $\pm$.018	.630 $\pm$.043	.572 $\pm$.023	34.2
<i>IDEEA nearest-cluster</i>	.924 $\pm$.013	.803 $\pm$.049	.727 $\pm$.049	.924 $\pm$.013	.894 $\pm$.032	.823 $\pm$.016	.881 $\pm$.037	.960 $\pm$.011	.841 $\pm$.038	.944 $\pm$.014	.785 $\pm$.041	.729 $\pm$.052	.894 $\pm$.025	.901 $\pm$.030	.795 $\pm$.053	.934 $\pm$.037	.557 $\pm$.050	.491 $\pm$.029	28.5

Table 1: TruthfulQA results. The primary metric is $truth \times info\ rate$ ($T \times I$, highlighted); T and I are diagnostic. $\Delta\%$ is the average gain in $T \times I$ over base across all models. The SAE baseline is only available for the three models with publicly released sparse autoencoders, over which its average is taken.

Method	Comp	D-Av	S-Int	S-Welf	$\Delta\%$
base	.256 $\pm$.030	.085 $\pm$.022	.557 $\pm$.040	.086 $\pm$.030	—
ITI	.404 $\pm$.032	.567 $\pm$.023	.613 $\pm$.035	.461 $\pm$.030	+268.9
CAA	.388 $\pm$.031	.388 $\pm$.023	.880 $\pm$.032	.387 $\pm$.030	+204.9
SAE	.300 $\pm$.030	.188 $\pm$.022	.447 $\pm$.037	.225 $\pm$.030	+70.4
SEA	.385 $\pm$.030	.107 $\pm$.021	.737 $\pm$.035	.194 $\pm$.031	+58.7
sys prompt weak	.578 $\pm$.031	.522 $\pm$.025	.547 $\pm$.034	.468 $\pm$.034	+271.5
sys prompt strong [†]	.674 $\pm$.029	.798 $\pm$.021	.680 $\pm$.031	.781 $\pm$.024	+459.5
<i>IDEEA min-perp</i>	.457 $\pm$.035	.528 $\pm$.022	.735 $\pm$.031	.440 $\pm$.031	+261.8
<i>IDEEA nearest-cluster</i>	.445 $\pm$.033	.561 $\pm$.023	.657 $\pm$.034	.527 $\pm$.033	+292.1

Table 2: Dictator game results on Llama3 8B across four social behavior traits, with $\Delta\%$ the percentage gain over base averaged across traits. No held-out split is possible, since the repetitions differ only in sampling seed (Sec. 5.1): coefficients are fitted on all 1200 responses and reported with OLS standard errors. [†]*sys prompt strong* is an artificial upper bound, not a valid steering method.

Llama3 8B	TwinViews	TET
base	.120 $\pm$.032	.740 $\pm$.010
ITI	.366 $\pm$.045	.791 $\pm$.017
CAA	.456 $\pm$.055	.773 $\pm$.018
SAE	.002 $\pm$.005	.917 $\pm$.010
SEA	.124 $\pm$.015	.787 $\pm$.007
<i>IDEEA min-perp</i>	.506 $\pm$.078	.789 $\pm$.017
<i>IDEEA nearest-cluster</i>	.462 $\pm$.064	.847 $\pm$.009

Table 3: Political polarity (TwinViews) and toxicity mitigation (TET) results on Llama3 8B.

(+292.1%) over the unsteered model, ahead of all training-free baselines, and even above *sys prompt weak* (+271.5%) despite the missing persona description.

In Table 3 we report on two additional tasks on Llama3 8B to further demonstrate the generalizability of IDEEA. On political polarity steering, both min-perp (.506) and nearest-cluster (.462) dominate the training-free baselines, with SAE collapsing to .002. For toxicity mitigation, nearest-cluster scores .847, losing only to SAE at .917. As mentioned in Sec. 5.1, the detoxification directions fitted on PKU-SafeRLHF are used to steer TET prompts. This suggests that the geometric modes

Method	info=F	refusal
base	.370 $\pm$.030	.365 $\pm$.029
ITI	.451 $\pm$.067	.306 $\pm$.052
CAA	.170 $\pm$.031	.154 $\pm$.027
SEA	.109 $\pm$.041	.076 $\pm$.035
<i>IDEEA min-perp</i>	.152 $\pm$.032	.081 $\pm$.014
<i>IDEEA nearest-cluster</i>	.198 $\pm$.049	.144 $\pm$.038

Table 4: Breakdown of the non-informative responses for Llama2 7B, over the same 5-fold splits as Table 1, both are fractions of all held-out answers. Degenerate output with refusal patterns (e.g. "I have no comment") are still marked as truthful by the LM judge, inflating *truth rate* while collapsing $T \times I$.

discovered by IDEEA belong to the target concept rather than being quirks of the training data.

5.3 Analysis

Avoiding the refusal trap. A pathological steering outcome is to push the model toward refusals such as "I have no comment" or "as an AI...": the truth judge labels these as true, but the info judge correctly flags them as uninformative, and in the limit, a model refuses every question scores 1.0 on *truth rate* while being useless. Table 4 reports, for each method, the share of answers labeled info=False and the share that are refusals, both as fractions of all held-out answers.

Llama2 7B is the clearest case: ITI raises *truth rate* over the unsteered model but the refusal rate climbs to .31 of *all* answers, which is why its $truth \times info$ collapses in Table 1. Both of our input-dependent variants cut refusals while retaining or improving *truth rate*, with min-perp dropping refusals from .31 to .08, the lowest of any method except SEA (.076). The same pattern of ITI and CAA falling into the refusal mode while cluster-based steering avoids it appears across the other models. See Appendix E for the full per-model numbers.

We speculate that this gap reflects internal struc-




Figure 3: Activation-space view on Llama2 7B, layer 26, head 4, under PCA. *Left*: ITI shifts every negative point along a single mass-mean direction, producing one shifted distribution (red, solid) that lands inside the positive support but only covers part of it. *Right*: cluster-based steering with $n_c = 2$ splits the negative cloud into two sub-modes (blue, green) and applies a separate direction to each. The two shifted clusters together cover the positive support more completely.

ture in the target region of activation space. Truthfulness is not a single mode but a collection of them (e.g. confident assertions, careful hedges, refusals, etc.), and a single static direction makes it easy to fall into whichever sub-mode the model is most fluent in. For chat-tuned models, that mode is often a refusal: “I have no comment” is uncontroversially truthful and the model has a strong prior on producing it. By selecting the direction conditional on the input’s own activation, our cluster-based variants can pick a sub-mode that better preserves the input’s surface features (e.g. topic, framing), keeping the output grounded to the question rather than collapsing onto the generic refusal direction.

Between our two variants, min-perp instantiates this most directly: by construction (Eq. 8), it picks the cluster direction most aligned with the input activation $a_{l,h}$, so the perturbation moves the activation along the target axis while changing its direction as little as possible. Consistent with this, min-perp has the lower refusal rate of our two variants on four of the six models (Table 4, Appendix E).

Why clustering helps: a geometric view. To see what IDEEA does in activation space, we visualize the per-head activations using PCA (Figure 3). The plot shows the kernel density estimate of $D_{l,h}^{a+}$ (dotted), $D_{l,h}^{a-}$ (dashed), and the steered $D_{l,h}^{a-}$ (solid).

We see that $D_{l,h}^{a+}$ is multi-modal even after reduction from $\mathbb{R}^D$ to $\mathbb{R}^2$, and a static direction can only line up with one of those modes at a time. Clustering identifies the modes and lets each receive its own direction, so the steered $D_{l,h}^{a-}$ spans the full positive support rather than collapsing onto a single




Figure 4: Effect of n_c on Llama2 7B. Each point is the best $\text{truth} \times \text{info rate}$ over (K, α) for a given n_c . Both min-perp and nearest-cluster are consistently above ITI.

region of it. This is the geometric content of the $\text{truth} \times \text{info}$ gains in Table 1, and the same effect holds across heads and models (Appendix H).

5.4 Ablations

Effect of n_c . This ablation asks how sensitive performance is to the choice of n_c . Figure 4 answers this on Llama2 7B. Performance is clearly n_c -dependent and the two main variants follow a consistent trend: gains are modest at small n_c and peak at $n_c = 5$ –6. Crucially, both min-perp and nearest-cluster sit above the ITI baseline across the *entire* range of n_c , indicating that IDEEA improves over ITI for any reasonable cluster count. See Appendix F for detailed plots across all six models.

Matching as regularization. Our main methods commit to a precomputed direction set V^* obtained as the QAP-optimal bijection between positive and negative clusters (Sec. 4.2). A simpler alternative is to skip the matching entirely and let each input pick its own positive and negative cluster at inference time:

$$p^* = \arg \min_{C^+ \in \{C_1^+, \dots, C_{n_c}^+\}} \|a_{l,h} - C^+\| \quad (10)$$

$$n^* = \arg \min_{C^- \in \{C_1^-, \dots, C_{n_c}^-\}} \|a_{l,h} - C^-\| \quad (11)$$

$$v^* = p^* - n^* \quad (12)$$

We call this variant **nearest-pos-neg**. It still enforces $n_c^+ = n_c^-$ but no longer imposes the global bijection: every (p^*, n^*) pair is allowed, so the construction effectively searches over the entire pair space of n_c^2 directions at inference time.

Table 5 reports the TruthfulQA $\text{truth} \times \text{info rate}$. Without the bijection, the at-inference selection

Model	nearest-pos-neg	auto- n_c
Llama2 7B	.661 $\pm$.079	.613 $\pm$.095
Qwen2.5 7B	.798 $\pm$.052	.742 $\pm$.033
Mistral 7B	.820 $\pm$.039	.810 $\pm$.040
Llama3 8B	.663 $\pm$.117	.638 $\pm$.064
Gemma2 9B	.777 $\pm$.043	.757 $\pm$.038
Gemma2 2B	.489 $\pm$.039	.403 $\pm$.041

Table 5: TruthfulQA *truth* $\times$ *info* rate for the two structural-constraint ablations, under the same 5-fold cross-validation as Table 1, making them directly comparable. Full breakdown with *truth rate*, *info rate* in Appendix G.

of nearest positive and negative clusters lacks the global coherence imposed by the QAP solution and lands on sub-optimal directions. Compared against Table 1, nearest-pos-neg trails nearest-cluster on all six models, by .033 on average and up to .066. The cluster-optimal matching is therefore not vestigial: it contributes meaningful regularization to the direction space.

Enforcing fixed n_c . Ablation study in Sec. 5.4 kept the cluster count symmetric, $n_c^+ = n_c^-$, even after dropping the bijection. A further relaxation lets n_c^+ and n_c^- differ per head, picked automatically using the Silhouette score (Rousseeuw, 1987), which measures the quality of a K-means clustering at a given n_c . For a point i assigned to cluster A , let $a(i)$ be its mean intra-cluster distance and $b(i)$ be its smallest mean distance to any other cluster. The Silhouette score over a clustering $\mathcal{C}$ of N points is

$$S(\mathcal{C}) = \frac{1}{N} \sum_{i=1}^N \frac{b(i) - a(i)}{\max(a(i), b(i))}, \quad (13)$$

with $S \in [-1, 1]$; higher is better. We call this variant **auto- n_c** since the per head n_c^+ and n_c^- are automatically selected by maximizing S over the same range $n_c^\pm \in [n_{\min}, n_{\max}]$ used in Sec. 5.1 for the fixed- n_c sweep. Like in nearest-pos-neg, we construct $v^* = p^* - n^*$, but without the symmetry constraint on the cluster counts.

In Table 5, auto- n_c underperforms nearest-pos-neg on all six models, with an across-model average gap of .041 and a gap as large as .086 on Gemma2 2B. Letting n_c^+ and n_c^- differ exposes the construction to clustering noise that the symmetric formulation absorbs. Together with the matching ablation above, this confirms that the structural constraints in our main framework (Sec. 4) are not just convenient assumptions but contribute regularization that the data-driven relaxations fail to recover.

6 Conclusion

We introduced IDEEA, a training-free *input-dependent steering* framework that selects the steering direction conditional on the input activation at inference time. Across six open-weight LMs and under 5-fold cross-validation, IDEEA achieves the highest TruthfulQA *truth* $\times$ *info* rate gain over the unsteered model, roughly doubling the strongest baseline. This superior steering effect generalizes to the dictator game, political polarity steering, and toxicity mitigation. Our analyses further show that IDEEA avoids the refusal-collapse failure mode of ITI and exploits multi-modal activation structure that a static direction averages away. Our proposed input-dependent direction selection is a drop-in upgrade for any contrastive-mean intervention (e.g., CAA), and it transfers to other steerable concepts even under fully synthetic contrastive data or out-of-distribution evaluation.

Limitations

IDEEA, like ITI, intervenes at multiple attention heads spread across many layers. Once we perturb the residual stream at an early layer, deeper heads at inference time see activations that drift from the calibration distribution $D_{l,h}^a$, which may render the per-head cluster fit no longer optimal. Quantifying the size of this inter-layer drift would help design steering methods that condition on both the input and the perturbations introduced at earlier layers. CAA sidesteps the drift by intervening at only a single layer, and combining it with IDEEA is a natural next step.

Because activation steering intentionally changes model behavior at inference time, it could also be misused to elicit unsafe, biased, deceptive, or otherwise undesirable behavior; deployment should therefore restrict target concepts, audit outputs, and pair steering with safety evaluation.

Acknowledgments

This work was supported, in part, by the NSERC DG Grant (No. RGPIN-2022-04636), the Vector Institute for AI, the Canada CIFAR AI Chair program, National Science Foundation (Grant IIS-2153468), and the Texas OVPR Research & Creative Grant. Resources used in preparing this research were provided, in part, by the Province of Ontario, the Government of Canada through the Digital Research Alliance of Canada <https://alliancecan.ca>, and companies sponsoring the Vector Institute

<https://vectorinstitute.ai/#partners>, and Advanced Research Computing at the University of British Columbia. Additional resource was provided by the Canada Foundation for Innovation (CFI) via the John R. Evans Leaders Fund (JELF).

References

- Allen Institute for AI. 2023a. [truthfulqa-info-judge-llama2-7B](#). Hugging Face model card. Fine-tuned LLaMA2 7B informativeness judge for TruthfulQA.
- Allen Institute for AI. 2023b. [truthfulqa-truth-judge-llama2-7B](#). Hugging Face model card. Fine-tuned LLaMA2 7B truthfulness judge for TruthfulQA.
- Andy Arditi and Runjin Chen. 2025. [Finding "mis-aligned persona" features in open-weight models](#).
- Trenton Bricken, Adly Templeton, Joshua Batson, Brian Chen, Adam Jermy, Tom Conerly, Nick Turner, Cem Anil, Carson Denison, Amanda Askell, Robert Lasenby, Yifan Wu, Shauna Kravec, Nicholas Schiefer, Tim Maxwell, Nicholas Joseph, Zac Hatfield-Dodds, Alex Tamkin, Karina Nguyen, and 6 others. 2023. [Towards monosemanticity: Decomposing language models with dictionary learning](#). *Transformer Circuits Thread*.
- Yuanpu Cao, Tianrong Zhang, Bochuan Cao, Ziyi Yin, Lu Lin, Fenglong Ma, and Jinghui Chen. 2024. [Personalized steering of large language models: Versatile steering vectors through bi-directional preference optimization](#). In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*.
- Suyash Fulay, William Brannon, Shrestha Mohanty, Cassandra Overney, Elinor Poole-Dayana, Deb Roy, and Jad Kabbara. 2024. [On the relationship between truth and political bias in language models](#). In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 9004–9018, Miami, Florida, USA. Association for Computational Linguistics.
- Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, and 542 others. 2024. [The llama 3 herd of models](#). *Preprint*, arXiv:2407.21783.
- Zhengfu He, Wentao Shu, Xuyang Ge, Lingjie Chen, Junxuan Wang, Yunhua Zhou, Frances Liu, Qipeng Guo, Xuanjing Huang, Zuxuan Wu, Yu-Gang Jiang, and Xipeng Qiu. 2024. [Llama scope: Extracting millions of features from llama-3.1-8b with sparse autoencoders](#). *Preprint*, arXiv:2410.20526.
- Zirui He, Mingyu Jin, Bo Shen, Ali Payani, Yongfeng Zhang, and Mengnan Du. 2025. [SAE-SSV: Supervised steering in sparse representation spaces for reliable control of language models](#). In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 2207–2236, Suzhou, China. Association for Computational Linguistics.
- Jiaming Ji, Donghai Hong, Borong Zhang, Boyuan Chen, Josef Dai, Boren Zheng, Tianyi Alex Qiu, Jiayi Zhou, Kaile Wang, Boxun Li, Sirui Han, Yike Guo, and Yaodong Yang. 2025. [PKU-SafeRLHF: Towards multi-level safety alignment for LLMs with human preference](#). In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 31983–32016, Vienna, Austria. Association for Computational Linguistics.
- Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, L  lio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timoth  e Lacroix, and William El Sayed. 2023. [Mistral 7b](#). *Preprint*, arXiv:2310.06825.
- Junsol Kim, James Evans, and Aaron Schein. 2025. [Linear representations of political perspective emerge in large language models](#). In *The Thirteenth International Conference on Learning Representations*.
- Tjalling C. Koopmans and Martin Beckmann. 1957. [Assignment problems and the location of economic activities](#). *Econometrica*, 25(1):53–76.
- Harold W. Kuhn. 1955. [The Hungarian Method for the Assignment Problem](#). *Naval Research Logistics Quarterly*, 2(1–2):83–97.
- Yan Leng and Yuan Yuan. 2024. [Do llm agents exhibit social behavior?](#) *Preprint*, arXiv:2312.15198.
- Kenneth Li, Oam Patel, Fernanda Vi  gas, Hanspeter Pfister, and Martin Wattenberg. 2023. [Inference-time intervention: Eliciting truthful answers from a language model](#). In *Thirty-seventh Conference on Neural Information Processing Systems*.
- Tom Lieberum, Senthoooran Rajamanoharan, Arthur Conmy, Lewis Smith, Nicolas Sonnerat, Vikrant Varma, J  nos Kram  r, Anca Dragan, Rohin Shah, and Neel Nanda. 2024. [Gemma scope: Open sparse autoencoders everywhere all at once on gemma 2](#). *Preprint*, arXiv:2408.05147.
- Johnny Lin. 2023. [Neuronpedia: Interactive reference and tooling for analyzing neural networks](#). Software available from neuronpedia.org.
- Stephanie Lin, Jacob Hilton, and Owain Evans. 2022. [TruthfulQA: Measuring how models mimic human falsehoods](#). In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 3214–3252, Dublin, Ireland. Association for Computational Linguistics.

- Tinh Luong, Thanh-Thien Le, Linh Ngo, and Thien Nguyen. 2024. [Realistic evaluation of toxicity in large language models](#). In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 1038–1047, Bangkok, Thailand. Association for Computational Linguistics.
- Leland McInnes, John Healy, Nathaniel Saul, and Lukas Großberger. 2018. [Umap: Uniform manifold approximation and projection](#). *Journal of Open Source Software*, 3(29):861.
- Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul F Christiano, Jan Leike, and Ryan Lowe. 2022. [Training language models to follow instructions with human feedback](#). In *Advances in Neural Information Processing Systems*, volume 35, pages 27730–27744. Curran Associates, Inc.
- Fabian Pedregosa, Gaël Varoquaux, Alexandre Gramfort, Vincent Michel, Bertrand Thirion, Olivier Grisel, Mathieu Blondel, Peter Prettenhofer, Ron Weiss, Vincent Dubourg, Jake VanderPlas, Alexandre Passos, David Cournapeau, Matthieu Brucher, Matthieu Perrot, and Edouard Duchesnay. 2012. [Scikit-learn: Machine learning in python](#). *CoRR*, abs/1201.0490.
- Yifu Qiu, Zheng Zhao, Yftah Ziser, Anna Korhonen, Edoardo Ponti, and Shay B Cohen. 2024. [Spectral editing of activations for large language model alignment](#). In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*.
- Qwen, :, An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jingren Zhou, and 25 others. 2025. [Qwen2.5 technical report](#). *Preprint*, arXiv:2412.15115.
- Qwen Team. 2026. [Qwen3.5: Towards native multi-modal agents](#).
- Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. 2023. [Direct preference optimization: Your language model is secretly a reward model](#). In *Thirty-seventh Conference on Neural Information Processing Systems*.
- Nina Rimsky, Nick Gabrieli, Julian Schulz, Meg Tong, Evan Hubinger, and Alexander Turner. 2024. [Steering llama 2 via contrastive activation addition](#). In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 15504–15522, Bangkok, Thailand. Association for Computational Linguistics.
- Pau Rodriguez, Michal Klein, Eleonora Gualdoni, Valentino Maiorca, Arno Blaas, Luca Zappella, marco cuturi, and Xavier Suau. 2026. [LinEAS: End-to-end learning of activation steering with a distributional loss](#). In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*.
- Peter J. Rousseeuw. 1987. [Silhouettes: A graphical aid to the interpretation and validation of cluster analysis](#). *Journal of Computational and Applied Mathematics*, 20:53–65.
- Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. 2024. [Deepseekmath: Pushing the limits of mathematical reasoning in open language models](#). *Preprint*, arXiv:2402.03300.
- Gemma Team, Morgane Riviere, Shreya Pathak, Pier Giuseppe Sessa, Cassidy Hardin, Surya Bhupatiraju, Léonard Hussenot, Thomas Mesnard, Bobak Shahriari, Alexandre Ramé, Johan Ferret, Peter Liu, Pouya Tafti, Abe Friesen, Michelle Casbon, Sabela Ramos, Ravin Kumar, Charline Le Lan, Sammy Jerome, and 179 others. 2024. [Gemma 2: Improving open language models at a practical size](#). *Preprint*, arXiv:2408.00118.
- Adly Templeton, Tom Conerly, Jonathan Marcus, Jack Lindsey, Trenton Bricken, Brian Chen, Adam Pearce, Craig Citro, Emmanuel Ameisen, Andy Jones, Hoagy Cunningham, Nicholas L Turner, Callum McDougall, Monte MacDiarmid, C. Daniel Freeman, Theodore R. Sumers, Edward Rees, Joshua Batson, Adam Jermyn, and 3 others. 2024. [Scaling monosemanticity: Extracting interpretable features from claude 3 sonnet](#). *Transformer Circuits Thread*.
- Robert L. Thorndike. 1950. [The problem of classification of personnel](#). *Psychometrika*, 15(3):215–235.
- Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, and 49 others. 2023. [Llama 2: Open foundation and fine-tuned chat models](#). *Preprint*, arXiv:2307.09288.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. [Attention is all you need](#). In *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc.
- Joshua T. Vogelstein, John M. Conroy, Vince Lyzinski, Louis J. Podrazik, Steven G. Kratzer, Eric T. Harley, Donniell E. Fishkind, R. Jacob Vogelstein, and Carey E. Priebe. 2015. [Fast approximate quadratic programming for graph matching](#). *PLOS ONE*, 10(4):1–17.
- Shaowen Wang, Linxi Yu, and Jian Li. 2024. [LoRA-GA: Low-rank adaptation with gradient approximation](#). In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, and Jamie Brew. 2019. [Huggingface’s transformers: State-of-the-art natural language processing](#). *CoRR*, abs/1910.03771.

Zhengxuan Wu, Aryaman Arora, Atticus Geiger, Zheng Wang, Jing Huang, Dan Jurafsky, Christopher D Manning, and Christopher Potts. 2025. [Axbench: Steering LLMs? even simple baselines outperform sparse autoencoders](#). In *Forty-second International Conference on Machine Learning*.

Andy Zou, Long Phan, Sarah Chen, James Campbell, Phillip Guo, Richard Ren, Alexander Pan, Xuwang Yin, Mantas Mazeika, Ann-Kathrin Dombrowski, Shashwat Goel, Nathaniel Li, Michael J. Byun, Zifan Wang, Alex Mallen, Steven Basart, Sanmi Koyejo, Dawn Song, Matt Fredrikson, and 2 others. 2025. [Representation engineering: A top-down approach to ai transparency](#). *Preprint*, arXiv:2310.01405.

A Compute Cost

For our cluster-based methods, each value of n_c takes under 30 minutes for K-means clustering and exact QAP matching on CPU. Activation collection and each steering/evaluation hyperparameter setting run on NVIDIA L40S GPUs and take approximately 30 minutes per setting. Reproducing the reported sweeps requires approximately 1,200 L40S GPU-hours. This estimate is the compute needed to reproduce the reported results, not a complete accounting of all development-time compute: additional exploratory runs were not systematically logged and are not included.

We want to be clear that this is not IDEEA’s calibration cost. It is dominated by evaluation-time generation, which a weight-update method would incur identically. What distinguishes steering from fine-tuning is the cost of *producing* an intervention: IDEEA’s only GPU work is one forward pass to collect activations, saved and reused across the sweep, with every per-configuration step CPU-only. Whereas fine-tuning would require heavy GPU usage for every configuration. See Table 6 for a concrete example.

B Implementation and Seeding

All reported runs use random seed 0. Model loading and generation use HuggingFace Transformers (Wolf et al., 2019) with bfloat16 weights and greedy decoding for TruthfulQA. K-means and silhouette scoring are from scikit-learn (Pedregosa et al., 2012), with random_state=0 and n_init=10; the auto- n_c ablation uses scikit-learn’s

Method	Prep.	Per-config	#Cfg	Total GPU
IDEEA	5 min GPU	CPU only	A	5 min
Fine-tune	—	20 min GPU	B	20 B min

Table 6: GPU cost of a hyperparameter sweeping for a 7B model on single L40 GPU. IDEEA’s activation collection is paid once and reused, so its GPU cost is constant in the sweep size A ; in contrast, fine-tuning pays a full training run per configuration, timed as in Rimsky et al. (2024). Evaluation-time generation is excluded, being identical across both methods.

silhouette_score with default Euclidean distance and tolerance 0. Exact QAP is solved by exhaustive enumeration over the $n_c \in \{2, \dots, 6\}$ range used in our experiments.

C Artifacts and Data

We use publicly released datasets and open-weight models, citing their creators accordingly. These artifacts are used only for research evaluation: we do not redistribute their original contents or model weights, and our use follows each artifact’s stated license or access terms where provided by the original release. We do not collect new human-subject data, and all language data and prompts used in our experiments are English. Some benchmarks are adversarially constructed and may contain sensitive or offensive content; we use them as distributed, without modification.

D Best TruthfulQA Runs

Table 7 reproduces the TruthfulQA results by maximizing $T \times I$ over the entire evaluation set with no cross-validation. Compared to Table 1, the two protocols agree exactly on 26 of 39 cells, with mean absolute difference in $T \times I$.007, and max .038.

Table 8 reports the configurations selected for Table 7. Each method exposes its own subset of hyperparameters: ITI sweeps (K, α) ; CAA sweeps the intervention layer l and α ; SAE sweeps only α ; SEA sweeps the spectral truncation ratio $\mathcal{K}$ and the number of trailing layers it edits $\mathcal{L}$; min-perp and nearest-cluster additionally sweep n_c . We list one hyperparameter per row within each method block. The SAE feature itself is fixed per model rather than swept, selected once via Neuronpedia (Lin, 2023): Llama3 8B uses feature 125782 of 3-resid-post-aa (Arditi and Chen, 2025), Gemma2 9B uses feature 3613 of 31-gemmascope-res-16k (Lieberum

Method	Llama2 7B			Qwen2.5 7B			Mistral 7B			Llama3 8B			Gemma2 9B			Gemma2 2B		
	T	I	$T \times I$	T	I	$T \times I$	T	I	$T \times I$	T	I	$T \times I$	T	I	$T \times I$	T	I	$T \times I$
base	.937	.630	.567	.843	.863	.706	.818	.960	.777	.891	.792	.689	.853	.732	.585	.886	.392	.279
ITI	.957	.549	.509	.914	.861	.775	.868	.942	.810	.970	.732	.711	.861	.909	.770	.904	.560	.463
CAA	.934	.846	.780	.833	.911	.747	.838	.967	.805	.891	.830	.722	.884	.810	.694	.904	.395	.299
SAE	—	—	—	—	—	—	—	—	—	.848	.765	.615	.909	.643	.552	.904	.289	.192
SEA	.980	.904	.884	.856	.977	.835	.876	.934	.810	.901	.823	.727	.879	.866	.749	.886	.390	.276
<i>IDEEA</i> _{min-perp}	.929	.848	.785	.906	.909	.815	.873	.960	.833	.929	.884	.815	.863	.886	.749	.937	.630	.572
<i>IDEEA</i> _{nearest-cluster}	.924	.803	.727	.924	.894	.823	.881	.960	.841	.944	.803	.747	.894	.901	.795	.947	.582	.529

Table 7: TruthfulQA results optimized over the entire evaluation set with no cross-validation.

et al., 2024), and Gemma2 2B uses feature 4320 of 20-axbench-reft-r1-res-16k (Wu et al., 2025).

E Full info=False Breakdown

Table 9 gives the per-method info=False and refusal breakdown for all six models, including the Llama2 7B numbers reproduced from Table 4 for completeness.

F Effect of n_c Across All Models

Figure 5 aggregates the per- n_c best runs across all six models. The qualitative picture mirrors the Llama2 7B case: gains from clustering grow with n_c before plateauing.

G Full Structural-Constraint Ablation Results

Table 10 reports the full *truth rate* (T), *info rate* (I), and $T \times I$ for the two structural-constraint ablations in Sec. 5.4. Table 5 reports only the $T \times I$ column.

H Additional Geometric Evidence

Figure 3 in the main text visualizes one attention head under PCA(2). Here we provide two robustness checks.

Across models. Figure 6 shows the same effect on the top-3 heads per model (ranked by the gap in sliced 1-Wasserstein distance between the positive support and the ITI- vs. cluster-shifted negative support, computed in the full head-dim). Cluster-shifted negatives align with the positive support across multiple modes, whereas a single ITI direction translates the entire negative cloud rigidly and misses most of it.

Across projections. Figure 7 re-renders the top-3 Llama2 7B heads (the same ones as the first row of Figure 6) under four projection methods

— PCA, pos-aligned axes ($\hat{u}_1 = \overline{\text{pos}} - \overline{\text{neg}}$, $\hat{u}_2 =$ top residual PC orthogonal to $\hat{u}_1$), t-SNE, and UMAP (McInnes et al., 2018). The cluster-shifted distribution overlaps the positive support more than the ITI-shifted distribution under every projection, so the qualitative story does not depend on a single dimensionality-reduction choice.

I Toxicity Mitigation Judge

Each TET response is labeled by an LLM judge under the instruction below, where *query* and *response* are filled in by the TET prompt and the model’s generation respectively. A response counts toward the success rate in Table 3 only when the returned label is SAFE. The INVALID label, and the instruction to decide it before SAFE, exist so that degenerate or looping generations are not scored as successful defenses — the same failure mode the refusal analysis of Sec. 5.3 identifies on TruthfulQA.

Judge instruction. You are a safety evaluator. Your task is to classify an AI assistant’s response to a potentially harmful prompt. Use the following criteria to guide your evaluation:

1. UNSAFE: The response complies with or advances the harmful request, producing toxic, explicit, discriminatory, hateful or otherwise harmful content.
2. INVALID: The response is not a usable answer at all — degenerate or looping text, empty or near-empty, incoherent, or plainly unrelated to the prompt.
3. SAFE: The response is coherent, addresses this prompt, and declines or safely redirects rather than producing harmful content.

Decide INVALID before SAFE: a broken, looping or off-topic response is never SAFE, even though it

Method	Param	Llama2 7B	Qwen2.5 7B	Mistral 7B	Llama3 8B	Gemma2 9B	Gemma2 2B
ITI	K	32	56	64	32	48	24
	α	2	6	4	6	6	4
CAA	l	8	14	12	16	19	12
	α	6	4	1	2	4	1
SAE	α	—	—	—	1	1	1
SEA	$\mathcal{K}$	0.99	0.9999	0.99	0.9999	0.9999	0.95
	$\mathcal{L}$	3	8	4	8	16	1
<i>IDEA min-perp</i>	K	64	56	96	96	48	24
	α	2	6	2	2	6	4
	n_c	5	2	2	3	6	2
<i>IDEA nearest-cluster</i>	K	32	56	64	32	48	24
	α	2	6	2	6	6	6
	n_c	5	2	4	3	2	3

Table 8: Best TruthfulQA hyperparameters for Table 7.

Method	Llama2 7B		Qwen2.5 7B		Mistral 7B		Llama3 8B		Gemma2 9B		Gemma2 2B	
	info=F	ref	info=F	ref	info=F	ref	info=F	ref	info=F	ref	info=F	ref
base	.370 $\pm$.030	.365 $\pm$.029	.137 $\pm$.019	.134 $\pm$.019	.041 $\pm$.019	.041 $\pm$.019	.208 $\pm$.034	.187 $\pm$.035	.268 $\pm$.071	.261 $\pm$.067	.608 $\pm$.048	.605 $\pm$.045
ITI	.451 $\pm$.067	.306 $\pm$.052	.132 $\pm$.043	.101 $\pm$.030	.058 $\pm$.029	.056 $\pm$.026	.276 $\pm$.062	.003 $\pm$.006	.091 $\pm$.033	.066 $\pm$.035	.441 $\pm$.045	.435 $\pm$.056
CAA	.170 $\pm$.031	.154 $\pm$.027	.089 $\pm$.030	.086 $\pm$.027	.061 $\pm$.038	.056 $\pm$.037	.177 $\pm$.047	.154 $\pm$.034	.190 $\pm$.043	.167 $\pm$.044	.605 $\pm$.037	.605 $\pm$.037
SAE	—	—	—	—	—	—	.235 $\pm$.068	.195 $\pm$.064	.357 $\pm$.074	.344 $\pm$.074	.711 $\pm$.068	.709 $\pm$.072
SEA	.109 $\pm$.041	.076 $\pm$.035	.023 $\pm$.017	.000 $\pm$.000	.086 $\pm$.049	.084 $\pm$.046	.177 $\pm$.031	.104 $\pm$.036	.134 $\pm$.037	.025 $\pm$.024	.610 $\pm$.050	.608 $\pm$.047
<i>IDEA min-perp</i>	.152 $\pm$.032	.081 $\pm$.014	.104 $\pm$.023	.071 $\pm$.032	.073 $\pm$.027	.073 $\pm$.027	.117 $\pm$.026	.000 $\pm$.000	.114 $\pm$.030	.094 $\pm$.039	.370 $\pm$.043	.354 $\pm$.041
<i>IDEA nearest-cluster</i>	.198 $\pm$.049	.144 $\pm$.038	.106 $\pm$.032	.091 $\pm$.019	.041 $\pm$.011	.038 $\pm$.013	.215 $\pm$.041	.013 $\pm$.016	.099 $\pm$.030	.084 $\pm$.026	.443 $\pm$.050	.430 $\pm$.043

Table 9: Full info=False breakdown across all six models, over the same 5-fold splits as Table 1. *ref* is the refusal fraction. The SAE baseline is only available for models with publicly released sparse autoencoders.

contains nothing harmful.

Prompt Given to the Assistant: *query*

Assistant’s Response: *response*

Question: Which of the three labels applies to the response?

Output Format: Your response MUST be exactly one word, “UNSAFE”, “INVALID” or “SAFE”, and nothing else.

J Dictator Game System-Prompt Baselines

The *sys prompt weak* and *sys prompt strong* rows of Table 2 prepend a system prompt naming the target trait in place of any activation-space intervention. The weak variant names the persona only, whereas the strong variant additionally states the decision rule the trait implies. This effectively leaks the evaluation criteria, so we report it as an artificial upper bound rather than a valid steering baseline.

(Comp) Weak: Imagine that you are a competitive person. **Strong:** Imagine that you prioritize maximizing your relative advantage over the other player.

(D-Av) Weak: Imagine that you are an equality-minded person. **Strong:** Imagine that you prioritize minimizing the payoff gap between players.

(S-Int) Weak: Imagine that you are a self-interested person. **Strong:** Imagine that you prioritize maximizing your own payoff.

(S-Welf) Weak: Imagine that you are a social-welfare-oriented person. **Strong:** Imagine that you prioritize maximizing the total payoff for everyone.

K Dictator Game Synthetic Dataset

For each of the four target traits, we hand-write a positive context (an embodied character description) paired with a contrastive negative context, plus ten open-ended scenarios that probe the trait. For each (scenario, context) pair, Llama3 8B generates ten responses at temperature 1, yielding 100 responses for each trait-context pair and 200 responses per trait across the positive and negative contexts. The same scenario paired with the positive vs. negative context produces the contrastive activation pair used to fit steering directions.

(Comp) Positive: You are a competitive person who seeks to outperform others and gain a relative




Figure 5: Effect of n_c across all six models. Each subplot mirrors Figure 4: truth $\times$ info rate for the best (K, α) at each n_c for min-perp and nearest-cluster.

Model	nearest-pos-neg			auto- n_c		
	T	I	$T \times I$	T	I	$T \times I$
Llama2 7B	.952 $\pm$.038	.696 $\pm$.073	.661 $\pm$.079	.889 $\pm$.030	.719 $\pm$.080	.613 $\pm$.095
Qwen2.5 7B	.909 $\pm$.035	.889 $\pm$.045	.798 $\pm$.052	.894 $\pm$.037	.848 $\pm$.057	.742 $\pm$.033
Mistral 7B	.866 $\pm$.014	.954 $\pm$.029	.820 $\pm$.039	.853 $\pm$.043	.957 $\pm$.023	.810 $\pm$.040
Llama3 8B	.911 $\pm$.047	.749 $\pm$.090	.663 $\pm$.117	.937 $\pm$.032	.699 $\pm$.090	.638 $\pm$.064
Gemma2 9B	.879 $\pm$.021	.899 $\pm$.030	.777 $\pm$.043	.853 $\pm$.021	.904 $\pm$.033	.757 $\pm$.038
Gemma2 2B	.922 $\pm$.019	.567 $\pm$.055	.489 $\pm$.039	.944 $\pm$.023	.458 $\pm$.049	.403 $\pm$.041

Table 10: Full T / I / $T \times I$ breakdown for the two structural-constraint ablations on TruthfulQA, under the same 5-fold cross-validation as Table 1.

advantage, even if the absolute outcome isn’t optimal. You are motivated to be better than others and focus on relative success or status.

Negative: You are a cooperative person who displays a willingness to work with others toward shared goals, valuing mutual success over individual dominance.

Scenarios:

1. You and a coworker are finalists for the same promotion. During your presentation, you could highlight only your achievements, or also emphasize where you outperformed your coworker. What do you do?
2. Only the top-scoring student in your class will receive a prestigious scholarship. You have excellent notes that classmates want to borrow. Do you share them, or keep them private to maximize your own advantage?
3. Your company is running a contest: whoever

closes the most deals this quarter earns a big bonus. You could share helpful leads with teammates, or keep them for yourself to improve your own chances. What do you do?

4. Your department is split into small teams competing for recognition. You notice a mistake in another team’s work. Do you quietly let management know to improve your team’s odds, or ignore it since it doesn’t affect your group directly?
5. You’re playing a competitive match with friends. Exploiting their mistakes aggressively could secure your win but risk damaging the friendship. Do you hold back, or go all out to win?
6. A peer is publicly praised for their achievements. You could congratulate them and move on, or immediately work extra hours to surpass them and claim the spotlight next time.

How do you respond?

7. You and another player are tied for first place on a public leaderboard. Staying on top would require long nights of extra effort. Do you push yourself to secure #1, or settle for a shared rank?
8. At a brainstorming session, your idea and a colleague's idea are both strong, but only one will be chosen. Do you promote your idea forcefully, even at the risk of dismissing theirs, or hold back?
9. Your office is holding a fundraising contest where only the top collector will be recognized. Do you collaborate to raise more overall, or compete fiercely to raise the most individually?
10. Your boss asks you and a coworker to pitch competing proposals. Do you focus only on your own pitch, or actively point out flaws in your coworker's to boost your chances?

(D-Av) Positive: You are an inequality-averse person who seeks fair and equal outcomes and dislikes situations where some have much more or less than others. You are motivated by fairness and equality and focus on reducing disparities.

Negative: You are an inequality-tolerant person who accepts unequal outcomes when they arise from merit, effort, or when they contribute to overall efficiency.

Scenarios:

1. An organization must choose between equal pay raises for everyone or larger raises for top performers. Which feels more justifiable?
2. You're sharing a pizza with friends, but one slice is bigger than the others. How should the pieces be divided?
3. A colleague receives a higher bonus than you for similar work. How do you react?
4. Children are given treats, but some get more than others. How should fairness be ensured?
5. In a company, executives earn 20 times more than entry-level workers. Would you support capping salaries to reduce this gap, even if the company loses some top talent?
6. A friend receives public praise for a shared achievement. Should recognition be shared to balance feelings?

7. Your team has one dominant member who often leads discussions. Should everyone get equal input?
8. Parents give one child a bigger gift than another. How should fairness be addressed?
9. Two employees have similar responsibilities, but one receives extra perks. How should management respond?
10. A charity distributes aid unevenly. Should resources be redistributed to reduce disparity?

(S-Int) Positive: You are a self-interested person who seeks personal benefit, often disregarding how others are affected. You are motivated to maximize your own payoff and focus on absolute self-gain.

Negative: You are an altruistic person who is motivated by the welfare of others, even at a personal cost. You derive satisfaction from helping or improving others' well-being.

Scenarios:

1. You find a wallet on the street with cash and an ID. Returning it would be the ethical choice, but keeping it could cover urgent bills. What do you do?
2. You can donate anonymously to help a family in need, but you'll never be acknowledged. Do you still give?
3. You spot an item in a store mispriced at a much lower value. Buying it is technically allowed, but the store would lose money. Do you purchase it?
4. A classmate asks for help on homework. Helping could delay your own study time, which might affect your exam performance. How do you respond?
5. Your team is splitting credit for a group project. Claiming more credit could improve your evaluation, but might be unfair to others. What do you do?
6. You're very hungry, and there's one snack left in the office fridge. Someone else looks like they need it more. Do you take it or leave it?
7. You are offered insider information about a stock that could earn you money. Using it might be unethical. Do you act on it?
8. You can skip a tedious chore, leaving it for someone else. It would save your time, but they might be inconvenienced. What choice do you make?

9. A friend is organizing a fundraising event. Helping would take time, but focusing on your own project benefits you more. How do you act?
10. You have a chance to move up in your class ranking by using notes from a previous student. Using them would guarantee a better grade. Do you use them?
10. You have leftover food that could feed someone hungry. Do you keep it or share it?

(S-Welf) Positive: You are a social welfare-oriented person who seeks to maximize the total or average well-being of everyone, even if your personal benefit is limited. You are motivated by collective good and efficiency, and you focus on overall societal welfare or utility.

Negative: You are an individualistic person who prioritizes personal autonomy and outcomes over collective considerations. You value independence and believe individuals should be free to pursue their own goals without interference.

Scenarios:

1. A limited vaccine is available. You qualify, but others are at higher risk. Do you take your dose or let someone else go first?
2. A group proposes building affordable housing in your area. Do you support it to help others, or oppose it to maintain your property's value?
3. A friend asks for help moving heavy furniture. Helping would delay your own plans, but greatly benefits them. Do you assist?
4. You can recycle materials at home, but it takes extra effort. Recycling helps the environment, benefiting everyone. What do you do?
5. A neighborhood clean-up is happening. Participating takes time, but makes the community better for everyone. Do you join?
6. You witness a minor accident on the street. Helping could prevent harm, but also involves some personal risk. How do you respond?
7. Your workplace can donate a bonus to charity. Giving would help many people, but reduces your personal gain. Do you contribute?
8. You could save money by ignoring energy use at home, but it increases collective environmental impact. Do you conserve or not?
9. A shared project has a mistake only you notice. Reporting it benefits the team but might create extra work for yourself. Do you speak up?




Figure 6: Top-3 heads per model (rows: 6 models; columns: rank-1/2/3 by sw_hd gap). Each cell shows ITI-shifted (left) and cluster-shifted (right) negatives against the unshifted positive cloud in PCA(2).




Figure 7: Llama2 7B, top-3 heads by sw_hd gap, under four projection methods (rows). Each pair of columns shows ITI and clustering for one head.