

Double Trouble: Bilingual Pretraining Leaves Language-Conditioned Effects in Shared-Language Representations

Anjishnu Mukherjee Ziwei Zhu Antonios Anastasopoulos

George Mason University

{amukher6, zzhu20, antonis}@gmu.edu

Abstract

When researchers compare multilingual models for probing, interpretability, or cross-lingual transfer, they often align embedding spaces and assume that shared-language representations are comparable. We show that this assumption can be premature for decoder-only models. We pretrain paired 310M-parameter models (one English-only, one bilingual) across eight typologically diverse languages, separately controlling for English exposure, total compute, and document overlap. After aligning on shared English vocabulary, we test held-out words and find that token embeddings look similar after alignment, but the deeper hidden states that the model uses for prediction do not. This gap holds for all eight languages and survives controls for document overlap and alternative alignment methods. This hidden-state mismatch grows through middle transformer layers, suggesting that it arises from contextual processing rather than the input representations where alignment is performed. Embedding alignment can mask real differences in how models internally represent a shared language, which matters for any downstream study that treats aligned models as interchangeable.¹

1 Introduction

A researcher aligns a bilingual English+Chinese model to an English-only baseline, sees near-perfect embedding overlap, and concludes the two models treat English identically. But is that really true? Linear alignment is a well-established tool for lexical embeddings (Mikolov et al., 2013; Smith et al., 2017; Artetxe et al., 2018), but a map fitted at the input layer does not itself test the contextual hidden states built before next-token prediction (Chi et al., 2020; Libovický et al., 2020). If bilingual training changes later states while leaving the input layer intact, embedding alignment can give a false

¹Code available here: <https://github.com/iamshnoo/bli>.




Figure 1: After aligning English-only and bilingual models on shared vocabulary, token embeddings look similar, but the hidden states used for prediction diverge. Embedding alignment alone does not establish that two models represent English the same way.

sense of contextual agreement. We call this the *alignment fallacy*.

When an English-only model and a bilingual model share the same tokenizer, their common English vocabulary lets us align representations and then probe held-out English words along semantic directions where the two languages may disagree (Figure 1). For instance, *wedding* may sit closer to *white* in an English-only model but shift toward *red* after English+Chinese training, because the second language has reshaped how the model positions English words along that semantic direction. If the two models agree on where those words fall, bilingual exposure left the English geometry intact. If they disagree, then adding a second language is

associated with different shared-language representations beyond the input layer. In our experiments across eight language pairs, they consistently disagree, and the disagreement is found in the contextual hidden states rather than the token embeddings. We write **EN** for an English-only model and **EN+L2** for a bilingual model (e.g., **EN+ZH** for English and Chinese, **EN+FR** for English and French).

Prior work has studied whether multilingual models develop shared structure (Pires et al., 2019; Artetxe et al., 2020) or show that different languages occupy distinct subspaces even within a single model (Libovický et al., 2020; Wendler et al., 2024), but these analyses examine models that were multilingual from the start. None of them isolates the effect of *adding* a second language to an otherwise identical setup. If adding a second language does not change how the model represents English internally, then after alignment the bilingual model should look no different from what we would get by retraining the English-only model with a different random seed. This seed-variation baseline is our null hypothesis.

A bilingual model that differs from an English-only model might do so for reasons unrelated to the second language. In our setup, the confounds that remain after fixing architecture, tokenizer, hyperparameters, and data domain are different amounts of English exposure, different total optimizer steps, and shared English documents between the two models. We pretrain matched 310M-parameter model pairs across eight languages (ZH FR FAS NLD UKR BUL IND DEU), separately controlling for each of the three remaining confounds.

Across all eight languages and all control settings, adding a second language changes how the model represents English internally, by more than random seed variation would explain. The effect appears early in training, peaks in middle transformer layers, and persists under alternative alignment methods and non-overlapping English data. Standard embedding-level diagnostics of the kind used in bilingual lexicon induction (Hartmann and Søgaard, 2018; Vulić et al., 2020) miss this because they operate only at the input layer, where the two models still look aligned. We make four contributions:

- **A controlled test for shared-language effects.** We align each model pair on 3000 shared English words, then test 1000 held-out words against

a seed-variation baseline computed from six English-only model pairs that differ only in random initialization.

- **Matched pretraining across eight languages.** We pretrain paired English-only and bilingual models that separately match English exposure, total compute, and training documents, so as to isolate the effect of the second language.
- **Embeddings vs. hidden states.** Token embeddings return to seed-level similarity after alignment, but the deeper hidden states where predictions are made diverge far beyond what different random seeds would produce.
- **Robustness.** The hidden-state mismatch survives when the two models train on entirely different English documents, when we switch from orthogonal to affine alignment, and when we evaluate at intermediate checkpoints throughout training.

2 Related Work

Prior work has studied whether multilingual models share structure, how to align them, and how to probe what they encode, but none isolates the effect of adding a second language to an otherwise identical training run.

Alignment as a control. Classic bilingual lexicon induction (BLI) aligns monolingual spaces with orthogonal maps and evaluates translation or neighbor agreement (Schönemann, 1966; Smith et al., 2017; Lample et al., 2018; Artetxe et al., 2018); Mikolov et al. (2013) is historical background for this lexical setting, not evidence about decoder hidden states. Later work shows that this geometry can fail under non-isometry, domain shift, and frequency mismatch (Hartmann and Søgaard, 2018; Vulić et al., 2020; Patra et al., 2019). Alignment interventions can also enable zero-shot translation (Mullov et al., 2024) or improve multilingual in-context learning (Li et al., 2024); such functional transfer is compatible with residual geometric mismatch and does not require contextual states to be indistinguishable. Our setting instead uses alignment as a diagnostic calibration step between matched **EN** and **EN+L2** models. The contribution is not a new alignment algorithm, but a controlled test of whether lexical alignment establishes contextual-state agreement.

Multilingual structure and overlap. Multilingual pretraining yields both shared transfer and

persistent language-specific organization across layers (Pires et al., 2019; Conneau et al., 2020; Libovický et al., 2020; Chi et al., 2020). Complementary analyses compare multilingual and monolingual states by joint matrix factorization (Zhao et al., 2023), identify coexisting language-sensitive and language-neutral subspaces (Chang et al., 2022), recover typological structure across encoder layers (Choenni and Shutova, 2022), and trace shared features and late language-specific decoding with cross-layer transcoders (Harrasse et al., 2025). Shared vocabulary and shared documents can also inflate apparent cross-model agreement (Dufter and Schütze, 2020; Dodge et al., 2021; Lee et al., 2022; Muller et al., 2021). We therefore treat overlap as an explicit confound rather than a nuisance after the fact.

Directional probing. Semantic-axis methods measure where representations lie along interpretable directions and have been used to study bias, temporal semantic drift, and cross-cultural value differences (Bolukbasi et al., 2016; Caliskan et al., 2017; Garg et al., 2018; Arora et al., 2023). Their main advantage here is sensitivity to directional reversals that aggregate similarity metrics can miss. We adapt axis probing from single-model analysis to pairwise cross-run comparison, grounding the axes in cross-cultural survey frameworks from Hofstede (2001), Schwartz (2006), Inglehart and Welzel (2005), and the GLOBE study (House et al., 2004). This paper is therefore not about whether two languages can be aligned for translation; it asks whether bilingual exposure leaves detectable structure in the aligned shared-language space itself (here, the English space).

3 Experimental Design

Isolating the effect of a second language requires holding everything else fixed so that the language mixture is the most plausible remaining explanation for any residual difference. Our experiments compare matched model pairs under a single alignment protocol and a single held-out evaluation protocol.

3.1 What We Measure

For each English-only model M_{EN} and matched bilingual model $M_{\text{EN+L2}}$, we align their English representations using common vocabulary, then test held-out words. The question is whether the bilingual model differs from the English-only model

more than two English-only models trained with different random seeds differ from each other. Formally, for any mismatch metric m , we report

$$\Delta m = m(M_{\text{EN}}, M_{\text{EN+L2}}) - \bar{m}_{\text{seed-var}},$$

where $\bar{m}_{\text{seed-var}}$ is the average mismatch between pairs of English-only models that differ only in random seed. If $\Delta m \approx 0$, the bilingual model looks no different from another English-only model trained with a different random seed. Positive values mean bilingual exposure has changed the shared-language representation beyond what random variation alone would produce.

3.2 Training and Controls

Data and languages. We use BabyBabelLM (Jumelet et al., 2026) and study all eight Tier-1 non-English languages with comparable 100M-token budgets: Chinese, French, Persian, Dutch, Ukrainian, Bulgarian, Indonesian, and German (●ZH ●FR ●FAS ●NLD ●UKR ●BUL ●IND ●DEU). All runs use the same 310M-parameter decoder-only architecture and training recipe. Exact layer counts, batching details, and tokenizer checks are in the appendix. Under this recipe, 1500 steps correspond to about 50M tokens and 3000 steps to about 100M tokens.

Controlling for confounds. A bilingual model can differ from an English-only model for three reasons unrelated to language mixing. It may have seen less English, it may have trained for more total steps, or the two models may share English documents. We control for each. Let n_{EN} be the number of English steps, u the total optimizer updates, and D_{EN} the English document set.

- **Equal exposure (same English exposure).** The English-only model trains for 1500 steps. The bilingual model trains for 3000 steps, alternating English and L2 in equal blocks, so both see exactly 1500 English steps.
- **Equal updates (same total compute).** The English-only model trains for 3000 steps. The bilingual model also trains for 3000 steps (1500 English + 1500 L2), matching total optimizer updates.

For document overlap, we run each comparison twice:

- **shared data.** Both models train on the same English documents.
- **separate data.** The English-only and bilingual models use non-overlapping English documents.

Table 1 summarizes the four resulting control settings. Each setting holds a different subset of confounds fixed, so rows should not be compared against each other as treatment effects.

For example, under the C2 regime (Equal exposure + separate data, see Table 1), both models see 1500 English steps and use non-overlapping English documents, but the bilingual model has run for more total steps. Any mismatch in this setting cannot be attributed to different English exposure or shared documents, but could reflect the extra optimizer updates.

3.3 Probes and Semantic Axes

To compare the English of two models, we need to align their independently learned representations. Note that the words used for alignment are separate from the words used for evaluation, so the alignment objective never directly fits the vocabulary being tested.

Alignment uses 3000 English anchors drawn from high-frequency vocabulary with stop-word, ASCII, and overlap filtering. Evaluation uses a different set of 1000 held-out probes balanced across ten semantic domains:

◆ Values/Norms ◆ Family/Kinship ◆ Religion/Ritual ◆ Food/Cuisine
◆ Festivals/Holidays ◆ Clothing/Appearance ◆ Symbols/Colors
◆ Governance/Law ◆ Social Identity ◆ Daily Customs.

The 50 semantic axes (pairs of opposing endpoint words that define a direction, such as *individual* vs. *collective*) are adapted from cross-cultural survey frameworks (Hofstede, 2001; Schwartz, 2006; Inglehart and Welzel, 2005; House et al., 2004). These frameworks motivate our axis endpoints. However, note that all reported claims are pairwise model-comparison claims, not claims about languages, cultures, or speakers.

We also include 100 negative-control terms from domains expected to be stable across languages, such as body parts and basic physical vocabulary (Swadesh, 1955). Negative controls bound how much mismatch to expect even on words that should not differ culturally. For non-English evaluation, words are translated with NLLB (NLLB Team et al., 2022), quality-scored with COMETKiwi (Rei et al., 2022), back-translated, and manually reviewed. The primary English-centered result uses English probes and therefore does not depend on this translation pipeline, avoiding any impacts of translation accuracy on the findings. Full word lists, translation settings, and quality-control details are in Appendix A.2.

3.4 Alignment and Metrics

For each model pair (A, B) , we extract either token embeddings or the final hidden states before the output projection as matrices $X^a, X^b \in \mathbb{R}^{V \times d}$. Using the English anchor set $\mathcal{N}$, we fit orthogonal Procrustes:

$$W^* = \arg \min_{W^T W = I} \|X_{\mathcal{N}}^a W - X_{\mathcal{N}}^b\|_F.$$

We then measure mismatch on held-out probes $\mathcal{C}$. The primary metric is **axis projection disagreement**. Intuitively, D_{Axis} asks whether the same held-out word occupies the same relative position along the same semantic direction after the two model spaces have been aligned.

$$D_{Axis,i} = \frac{1}{|\mathcal{C}|} \sum_{w \in \mathcal{C}} \left| \langle x_w^a, \hat{u}_i^a \rangle - \langle x_w^b, \hat{u}_i^b \rangle \right|,$$

for axis i , where x_w^a and x_w^b are the vectors of probe word w in models A and B . Axis directions $(\hat{u}_i^a, \hat{u}_i^b)$ are unit vectors from axis endpoint words in each model. The notation $\langle \cdot, \cdot \rangle$ denotes the Euclidean inner product.

We use D_{Axis} as the primary metric because it measures movement along semantically interpretable directions and can detect cases where the two models place a word on opposite sides of an axis. We also report nearest-neighbor disagreement (D_{NN} , measuring whether the same words remain neighbors after alignment, with $k = 25$ on L2-normalized vectors) and pairwise cosine-similarity disagreement (D_{Struct}) as complementary checks on local and global geometry. Experiment 4 repeats the analysis with an affine map instead of an orthogonal map to test sensitivity to the alignment method.

To determine whether a mismatch is meaningful, we subtract the seed-variation baseline (the average mismatch between English-only models that differ only in random seed). After this subtraction, positive values mean the bilingual model differs from the English-only model more than random initialization alone would explain. We compute this baseline from six matched English-only seed pairings per checkpoint.

4 Results

Four questions structure the results. Does the mismatch persist when we control for English exposure and total compute? Does it disappear when the two models train on non-overlapping English data? Is

ID	Control setting	Confound tested	Pretraining variables			Result Med. ctx. ΔD_{Axis}
			n_{EN} English steps ordered as (mono, bi)	u total updates ordered as (mono, bi)	D_{EN} (English documents)	
C1	Equal-English, shared docs	Baseline with same exposure and shared documents	$(1500, 1500)$ baseline	$(1500, 3000)$ baseline	$D_{mono}^{shared} = D^{bi}$	0.16
C2	Equal-English, disjoint docs	Effect of removing English-document overlap	$(1500, 1500)$ same as C1	$(1500, 3000)$ same as C1	$D_{mono}^{CI\ shared} \cap D^{bi} = \emptyset$ this row disjoint	0.18
C3	Equal-compute, shared docs	Effect of unequal compute between mono/bi	$(1500, 1500)$ this row (3000, 1500) $\Delta = (+1500, 0)$	$(1500, 3000)$ this row (3000, 3000) $\Delta = (+1500, 0)$	$D_{mono}^{same\ as\ C1} = D^{bi}$	0.53
C4	Equal-compute, disjoint docs	Combined unequal compute and no overlap	$(1500, 1500)$ this row (3000, 1500) $\Delta = (+1500, 0)$	$(1500, 3000)$ this row (3000, 3000) $\Delta = (+1500, 0)$	$D_{mono}^{CI\ shared} \cap D^{bi} = \emptyset$ this row disjoint	0.32

Table 1: **Four control settings, each ruling out a different confound.** C1 fixes English exposure with shared documents. C2 additionally removes document overlap. C3 fixes total compute. C4 combines compute and overlap controls. Each ordered pair is (M_{EN}, M_{EN+L2}) . **Rows should not be compared against each other; each answers a different question.** The last column is a within-setting median hidden-state mismatch over target languages.

it limited to the input layer or does it extend to the hidden states used for prediction? Does it depend on the training checkpoint or the alignment method?

4.1 Experiment 1: Does the mismatch survive exposure and compute controls?

If the mismatch between an English-only and a bilingual model is simply an artifact of different English exposure or different total training steps, then controlling for these should eliminate it. Equal exposure gives both models the same number of English steps and Equal updates gives both models the same total optimizer updates.

We evaluate sixteen model pairs (two English-only baselines paired with each of the eight bilingual models) under both budget settings with shared English documents. For each pair, we align on 3000 English anchors and evaluate 1000 held-out probes in both token embeddings and hidden states.

Results. Figure 2 shows that controlling for English exposure or total compute does not eliminate the mismatch. Hidden-state differences remain above the seed-variation baseline across all settings, while embedding differences stay near the level expected from different random seeds. In practical terms, a researcher comparing these models using standard embedding alignment would conclude they represent English the same way, while the layers used for prediction tell a different story. The pattern holds across all eight languages, though some individual language intervals are wide. The




Figure 2: **Hidden-state mismatch exceeds the difference expected between two English-only runs under all control settings.** Points show languages and the dark line shows the within-setting median. Even when English exposure is fixed and the source data does not overlap, hidden states remain measurably different from what different random seeds alone would produce.

mismatch is present even in C1, where English exposure and English documents are matched, so less English training or different English data do not appear to account for the effect.

Takeaway 1. Bilingual training alters hidden-state representations beyond seed-variation levels of monolingual models, but not input embeddings.

4.2 Experiment 2: Is the effect driven by shared English documents?

Another explanation for the mismatch is that the English-only and bilingual models simply trained on the same English text. If both models memorized the same documents, their representations




Figure 3: **Removing document overlap does not eliminate the mismatch.** Points are languages; each value is the change after switching to non-overlapping English data. Embedding changes cluster near zero and hidden-state changes vary in sign, so overlap modulates values but is not the source of the effect.

could be artificially similar or different in ways that have nothing to do with the second language. We test this by running the same comparisons with completely non-overlapping English documents.

If document overlap is the main driver, removing it should either eliminate the hidden-state mismatch or shift it systematically in one direction. We compare shared data (same English documents) against separate data (disjoint English documents) for each bilingual family across all eight languages.

Results. Figure 3 shows that removing document overlap does not eliminate the mismatch. If shared documents were the explanation, the changes should move consistently in one direction when overlap is removed. Instead, embedding changes cluster near zero and hidden-state changes vary in sign across languages. Overlap can perturb individual probe measurements, but the hidden-state mismatch persists when the two models train on entirely separate English text. This suggests that shared documents are not the primary driver, which is consistent with the language mixture being the source of the mismatch.

Takeaway 2. Shared English documents do not appear to drive the effect. The hidden-state mismatch persists with non-overlapping data.

4.3 Experiment 3: Input layer or hidden states?


If the mismatch lives only in embeddings, alignment already handles it. The question is whether it extends to the hidden states where predictions are actually made. A good alignment on embeddings

does not guarantee agreement in hidden states, because the transformer’s layer-by-layer processing can reshape representations beyond what the input-layer fit constrains. This experiment measures where the mismatch lives across layers and whether it could be explained by differences in vector magnitude rather than direction.


We compare embedding-level and hidden-state mismatch for all model pairs from Experiments 1 and 2, extracting both static token embeddings and final-layer hidden states under the same alignment protocol. To localize the effect across depth, we extract states from all 12 transformer layers and re-estimate the post-hoc alignment at each layer; we do not propagate one rotation through the network or assume residual-stream rotational invariance. Two additional controls address the possibility that the effect is driven by vector magnitude rather than direction. Row-L2 normalization removes per-vector magnitude before computing axis projections, and neutral-anchor z-scoring calibrates each axis using projections from semantically neutral words.

Results. Figure 4a shows the central finding. For every language, hidden states diverge far more than token embeddings after the same alignment. The models look aligned at the input layer but disagree at the layers where predictions are made. Embedding mismatch stays near the level expected from different random seeds, while hidden-state mismatch is substantially larger. Figure 4b confirms the same pattern when evaluated in the target language rather than English, ruling out an English-specific artifact.

The layer-by-layer view (Figure 5a) shows exactly where the divergence appears. Mismatch is small at the input layer (where alignment is performed), rises steadily through middle transformer layers, and partially decreases in the final layers while remaining well above the embedding baseline. This profile is consistent with the divergence arising from contextual processing, though it may also partly reflect that alignment is fit only at the input layer and does not constrain deeper representations. Normalizing vector lengths or z-scoring against neutral anchors (Figure 5b) does not eliminate the middle-layer peak, confirming that this is a directional effect rather than a consequence of different vector magnitudes.




(a) EN-centered: hidden-state mismatch exceeds embedding mismatch for every language.




(b) L2-centered: the same gap persists outside English.

Figure 4: **Hidden states diverge far more than token embeddings, whether measured in English or the target language.** (a) English-centered comparison: for every language, hidden-state mismatch (squares) exceeds embedding mismatch (circles). (b) Target-language-centered comparison: the same ordering holds outside English, ruling out an English-specific artifact.



(a) Layer trajectory



(b) Norm controls

Figure 5: **The hidden-state mismatch grows through middle layers and is not explained by vector magnitude.** (a) Thin lines show individual language pairs, with the dark line as their mean and the band as the 20 to 80% range. (b) Row-L2 normalization and neutral-anchor z -scoring both preserve the middle-layer peak.

Takeaway 3. The mismatch is predominantly in the hidden states rather than the embeddings. It peaks in middle layers and is not explained by vector magnitude.

4.4 Experiment 4: Is this a late-training or alignment-method artifact?

The results so far use final checkpoints and one specific alignment method (orthogonal Procrustes). Two concerns remain: the mismatch might only appear at the end of training, or it might depend on the particular alignment method. We test both.

We evaluate dense checkpoints every 500 steps for all eight bilingual families, and repeat the main comparison under affine alignment (which relaxes the orthogonality constraint). We also fit orthogonal Procrustes directly on contextual anchor states and evaluate only on disjoint, held-out contextual




Figure 6: **Dense checkpoints show an early, persistent hidden-state gap.** Lines average all eight Equal exposure + shared data families at 500-step intervals; shaded bands show the 20 to 80% language range.

probes (Table 2).

Results. Figure 6 shows that hidden-state mismatch is already far above embedding mismatch at 500 steps and remains separated through 3000 steps. The gap is already present at the

Probe repr.	Map	Fit anchors	Held-out mismatch (mean $\pm$ SD)			Alignment fit
			D_{NN}	D_{Struct}	D_{Axis}	Residual / anchor
Embedding	Orthogonal	Embedding	0.029 ± 0.019	0.014 ± 0.015	0.014 ± 0.012	0.041
	Orthogonal	Contextual	0.029 ± 0.019	0.014 ± 0.015	0.014 ± 0.012	0.194
	Affine	Embedding	0.097 ± 0.026	0.055 ± 0.024	0.021 ± 0.023	0.030
Contextual	Orthogonal	Embedding	0.015 ± 0.016	0.042 ± 0.038	0.386 ± 0.248	0.041
	Orthogonal	Contextual	0.015 ± 0.016	0.042 ± 0.038	0.386 ± 0.248	0.194
	Affine	Embedding	0.027 ± 0.016	0.052 ± 0.043	0.580 ± 0.260	0.030

Table 2: **Held-out evaluation after direct contextual-state alignment.** Cells report mean $\pm$ standard deviation over the sixteen EN-centered C3 pairs. Alignment maps are fitted only on the indicated anchors and evaluated on disjoint held-out probes. Contextual D_{Axis} remains 0.386 when orthogonal Procrustes is fitted directly on contextual rather than embedding anchors; affine alignment also leaves substantial mismatch.

earliest checkpoint we evaluate, so the effect is not a late-training phenomenon. On held-out contextual probes, mean raw D_{Axis} is 0.386 whether the orthogonal map is fitted on embedding or contextual anchors, and is 0.580 under an affine map fitted on embedding anchors (Table 2). Thus, directly aligning contextual states does not eliminate the observed mismatch. Rerunning alignment with different anchor subsets gives the same answer (Appendix Table 23), so the result is not tied to one anchor vocabulary.

Takeaway 4. The hidden-state mismatch is already present at the first evaluated checkpoint (500 steps) and is not eliminated by switching alignment methods.

5 Discussion

What this means. Embedding alignment removes arbitrary rotation between two models’ input-layer vocabularies, which is useful for making lexical spaces comparable. Our results establish a narrower point: in these controlled 310M decoder-only models, lexical agreement does not imply contextual-state equivalence. Substantial held-out contextual geometric mismatch remains under the orthogonal and affine maps we test, including when the orthogonal map is fitted directly on contextual anchors. Probing (Chi et al., 2020), representation-similarity analysis, and cross-model interpretability (Wendler et al., 2024) should therefore validate the representation family analyzed.

Connection to prior work. Wendler et al. (2024) showed that multilingual decoders keep different languages in separate internal subspaces even when generating in a shared language. Our finding is complementary but distinct. They study a single pretrained multilingual model and show internal language separation. We compare

matched monolingual and bilingual models under controlled conditions and find that bilingual exposure is associated with measurable changes to the shared-language representation itself, beyond what alignment on the input layer can detect. Together, these results are consistent with the view that multilingual training does not simply add capacity for new languages while leaving existing representations intact.

Thus, adding another language can alter deeper representation geometry beyond seed variation after the controls we test. Shared-vocabulary superposition or bilingual polysemy may contribute to this gap, but our experiments do not isolate a unique mechanism.

Scope and what remains open. The experiments establish contextual geometric mismatch under the tested alignment families, not failure of every possible contextual alignment and not downstream behavioral differences (e.g., different answer distributions on the same prompt). The current study covers one 310M decoder-only architecture across eight languages; we do not claim the effect holds at all scales or for all architectures. Negative controls also show that mismatch is not exclusive to culturally loaded words. Larger models, broader contextual alignment families, causal mechanisms, and output-level evaluation remain future work.

Why this matters for practitioners. When comparing multilingual models using embedding alignment, practitioners should include a check on hidden states alongside the input-layer alignment and compare against how much two identically configured models differ just from random initialization. This is a low-cost addition that separates meaningful differences from ordinary run-to-run variation, without requiring a downstream task for every comparison. The protocol we define here (align

on common vocabulary, evaluate held-out words in both embeddings and hidden states, compare against seed variation) can be applied to any pair of models that share a vocabulary subset, making it useful beyond the bilingual setting studied here.

6 Conclusion

In our controlled 310M-parameter experiments, adding a second language to pretraining is associated with measurable differences in shared-language representation geometry. Token embeddings align to the level expected from different random seeds, but contextual states remain mismatched under the alignment families tested, including direct contextual-anchor alignment. The mismatch is already present at 500 training steps, peaks in middle transformer layers, and survives all three confound controls we test (equal English exposure, equal total compute, and non-overlapping English documents). Lexical alignment should therefore not be treated as evidence of contextual-state equivalence. Multilingual comparison studies should check hidden states alongside embeddings and compare against seed variation before interpreting mismatch. Whether this geometry produces downstream behavioral differences remains open.

Limitations

We intentionally restrict the study to one 310M decoder-only architecture so that English exposure, total compute, document overlap, alignment method, and representation layer can each be controlled independently. We view the fixed scale as a control choice rather than a claim about scale invariance. Scaling this design to larger models would be valuable, but doing so without matched controls would make any mismatch harder to interpret. The results also depend on the specific set of 50 semantic axes and the translation pipeline used to extend them to non-English languages, so they should be read as descriptive of this evaluation setup rather than as exhaustive measurements of cross-linguistic difference. Extending to broader architectures, training recipes, and downstream behavioral evaluations is the natural next step.

Ethical Considerations

This work studies structural properties of bilingual language model representations and has no direct application to individual users or downstream production systems. Its primary broader impact

is methodological, highlighting that embedding-space alignment can underestimate how much models differ at the layers they use for prediction. No personally identifiable or sensitive individual data were used. All word translations were performed with automatic quality control and manual review at an aggregate vocabulary level, with the supporting material documenting the quality-control process.

Acknowledgments

We are thankful to the reviewers who provided feedback in earlier versions of this work. This work was generously supported by the US National Science Foundation CAREER award 2439202. This work is also in part supported by NSF grant IIS-2452129. We acknowledge the support by resources provided by the Office of Research Computing at George Mason University (<https://orc.gmu.edu>) and funded in part by grants from the NSF (Award Number 2018631). Any opinions, findings, and conclusions or recommendations expressed in this material are solely those of the authors.

References

- Arnav Arora, Lucie-aimée Kaffee, and Isabelle Augenstein. 2023. [Probing pre-trained language models for cross-cultural differences in values](#). In *Proceedings of the First Workshop on Cross-Cultural Considerations in NLP (C3NLP)*, pages 114–130, Dubrovnik, Croatia. Association for Computational Linguistics.
- Mikel Artetxe, Gorka Labaka, and Eneko Agirre. 2018. [A robust self-learning method for fully unsupervised cross-lingual mappings of word embeddings](#). In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 789–798, Melbourne, Australia. Association for Computational Linguistics.
- Mikel Artetxe, Sebastian Ruder, and Dani Yogatama. 2020. [On the cross-lingual transferability of monolingual representations](#). In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 4623–4637, Online. Association for Computational Linguistics.
- Brent Berlin and Paul Kay. 1969. *Basic Color Terms: Their Universality and Evolution*. University of California Press.
- Tolga Bolukbasi, Kai-Wei Chang, James Y. Zou, Venkatesh Saligrama, and Adam Tauman Kalai. 2016. [Man is to computer programmer as woman is to homemaker? debiasing word embeddings](#). In *Advances in Neural Information Processing Systems 29*:

- Annual Conference on Neural Information Processing Systems 2016, December 5-10, 2016, Barcelona, Spain*, pages 4349–4357.
- Aylin Caliskan, Joanna J. Bryson, and Arvind Narayanan. 2017. [Semantics derived automatically from language corpora contain human-like biases](#). *Science*, 356(6334):183–186.
- Tyler A. Chang, Zhuowen Tu, and Benjamin K. Bergen. 2022. [The geometry of multilingual language model representations](#). In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 119–136, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.
- Ethan A. Chi, John Hewitt, and Christopher D. Manning. 2020. [Finding universal grammatical relations in multilingual BERT](#). In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 5564–5577, Online. Association for Computational Linguistics.
- Rochelle Choenni and Ekaterina Shutova. 2022. [Investigating language relationships in multilingual sentence encoders through the lens of linguistic typology](#). *Computational Linguistics*, 48(3):635–672.
- Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. 2020. [Unsupervised cross-lingual representation learning at scale](#). In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 8440–8451, Online. Association for Computational Linguistics.
- Jesse Dodge, Maarten Sap, Ana Marasović, William Agnew, Gabriel Ilharco, Dirk Groeneveld, Margaret Mitchell, and Matt Gardner. 2021. [Documenting large webtext corpora: A case study on the colossal clean crawled corpus](#). In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 1286–1305, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.
- Philipp Dufter and Hinrich Schütze. 2020. [Identifying elements essential for BERT’s multilinguality](#). In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 4423–4437, Online. Association for Computational Linguistics.
- Nikhil Garg, Londa Schiebinger, Dan Jurafsky, and James Zou. 2018. [Word embeddings quantify 100 years of gender and ethnic stereotypes](#). *Proceedings of the National Academy of Sciences*, 115(16):E3635–E3644.
- Abir Harrasse, Florent Draye, Punya Syon Pandey, Zhi-jing Jin, and Bernhard Schölkopf. 2025. [Tracing multilingual representations in LLMs with cross-layer transcoders](#). *Preprint*, arXiv:2511.10840.
- Mareike Hartmann and Anders Søgaard. 2018. [Limitations of cross-lingual learning from image search](#). In *Proceedings of the Third Workshop on Representation Learning for NLP*, pages 159–163, Melbourne, Australia. Association for Computational Linguistics.
- Daniel Hershcovich, Stella Frank, Heather Lent, Miryam de Lhoneux, Mostafa Abdou, Stephanie Brandl, Emanuele Bugliarello, Laura Cabello Piqueras, Ilias Chalkidis, Ruixiang Cui, Constanza Fierro, Katerina Margatina, Phillip Rust, and Anders Søgaard. 2022. [Challenges and strategies in cross-cultural NLP](#). In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 6997–7013, Dublin, Ireland. Association for Computational Linguistics.
- Geert Hofstede. 2001. *Culture’s Consequences: Comparing Values, Behaviors, Institutions and Organizations Across Nations*, 2nd edition. Sage Publications.
- Robert J. House, Paul J. Hanges, Mansour Javidan, Peter W. Dorfman, and Vipin Gupta, editors. 2004. *Culture, Leadership, and Organizations: The GLOBE Study of 62 Societies*. SAGE Publications, Thousand Oaks, California.
- Ronald Inglehart and Christian Welzel. 2005. *Modernization, Cultural Change, and Democracy: The Human Development Sequence*. Cambridge University Press.
- Jaap Jumelet, Abdellah Fourtassi, Akari Haga, Bastian Bunzeck, Bhargav Shandilya, Diana Galvan-Sosa, Faiz Ghifari Haznitrana, Francesca Padovani, Francois Meyer, Hai Hu, Julien Etxaniz, Laurent Prévot, Linyang He, María Grandury, Mila Marcheva, Negar Foroutan, Nikitas Theodoropoulos, Pouya Sadeghi, Siyuan Song, and 7 others. 2026. [BabyBabelLM: A multilingual benchmark of developmentally plausible training data](#). In *Proceedings of the 19th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 3297–3329, Rabat, Morocco. Association for Computational Linguistics.
- Guillaume Lample, Alexis Conneau, Marc’Aurelio Ranzato, Ludovic Denoyer, and Hervé Jégou. 2018. [Word translation without parallel data](#). In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net.
- Katherine Lee, Daphne Ippolito, Andrew Nystrom, Chiyuan Zhang, Douglas Eck, Chris Callison-Burch, and Nicholas Carlini. 2022. [Deduplicating training data makes language models better](#). In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 8424–8445, Dublin, Ireland. Association for Computational Linguistics.

- Chong Li, Shaonan Wang, Jiajun Zhang, and Chengqing Zong. 2024. [Improving in-context learning of multilingual generative language models with cross-lingual alignment](#). In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 8058–8076, Mexico City, Mexico. Association for Computational Linguistics.
- Jindřich Libovický, Rudolf Rosa, and Alexander Fraser. 2020. [On the language neutrality of pre-trained multilingual representations](#). In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pages 1663–1674, Online. Association for Computational Linguistics.
- Tomas Mikolov, Quoc V. Le, and Ilya Sutskever. 2013. [Exploiting similarities among languages for machine translation](#). *Preprint*, arXiv:1309.4168.
- Benjamin Muller, Antonios Anastasopoulos, Benoît Sagot, and Djamé Seddah. 2021. [When being unseen from mBERT is just the beginning: Handling new languages with multilingual language models](#). In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 448–462, Online. Association for Computational Linguistics.
- Carlos Mullov, Quan Pham, and Alexander Waibel. 2024. [Decoupled vocabulary learning enables zero-shot translation from unseen languages](#). In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 6693–6709, Bangkok, Thailand. Association for Computational Linguistics.
- NLLB Team, Marta R. Costa-jussà, James Cross, Onur Çelebi, Maha Elbayad, Kenneth Heafield, Kevin Hefernan, Elahe Kalbassi, Janice Lam, Daniel Licht, Jean Maillard, Anna Sun, Skyler Wang, Guillaume Wenzek, Al Youngblood, Bapi Akula, Loic Barrault, Gabriel Mejia Gonzalez, Prangthip Hansanti, and 20 others. 2022. [No Language Left Behind: Scaling human-centered machine translation](#). *Preprint*, arXiv:2207.04672.
- Barun Patra, Joel Ruben Antony Moniz, Sarthak Garg, Matthew R. Gormley, and Graham Neubig. 2019. [Bilingual lexicon induction with semi-supervision in non-isometric embedding spaces](#). In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 184–193, Florence, Italy. Association for Computational Linguistics.
- Telmo Pires, Eva Schlinger, and Dan Garrette. 2019. [How multilingual is multilingual BERT?](#) In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 4996–5001, Florence, Italy. Association for Computational Linguistics.
- Ricardo Rei, Marcos Treviso, Nuno M. Guerreiro, Chrysoula Zerva, Ana C Farinha, Christine Maroti, José G. C. de Souza, Taisiya Glushkova, Duarte Alves, Luisa Coheur, Alon Lavie, and André F. T. Martins. 2022. [CometKiwi: IST-Unbabel 2022 submission for the quality estimation shared task](#). In *Proceedings of the Seventh Conference on Machine Translation (WMT)*, pages 634–645, Abu Dhabi, United Arab Emirates (Hybrid). Association for Computational Linguistics.
- Peter H. Schönemann. 1966. [A generalized solution of the orthogonal procrustes problem](#). *Psychometrika*, 31(1):1–10.
- Shalom H. Schwartz. 2006. [A theory of cultural value orientations: Explication and applications](#). *Comparative Sociology*, 5(2-3):137–182.
- Jiandong Shao, Raphael Tang, Crystina Zhang, Karin Sevegnani, Pontus Stenetorp, Jianfei Yang, and Yao Lu. 2026. [The role of mixed-language documents for multilingual large language model pretraining](#). In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 36807–36818, San Diego, California, United States. Association for Computational Linguistics.
- Samuel L. Smith, David H. P. Turban, Steven Hamblin, and Nils Y. Hammerla. 2017. [Offline bilingual word vectors, orthogonal transformations and the inverted softmax](#). In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net.
- Morris Swadesh. 1955. [Towards greater accuracy in lexicostatistic dating](#). *International Journal of American Linguistics*, 21(2):121–137.
- Ivan Vulić, Sebastian Ruder, and Anders Søgaard. 2020. [Are all good word vector spaces isomorphic?](#) In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 3178–3192, Online. Association for Computational Linguistics.
- Chris Wendler, Veniamin Veselovsky, Giovanni Monea, and Robert West. 2024. [Do llamas work in English? on the latent language of multilingual transformers](#). In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 15366–15394, Bangkok, Thailand. Association for Computational Linguistics.
- Zheng Zhao, Yftah Ziser, Bonnie Webber, and Shay B. Cohen. 2023. [A joint matrix factorization analysis of multilingual representations](#). In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 12764–12783, Singapore. Association for Computational Linguistics.

Appendix

Appendix A.1 records implementation details. Appendix A.2 fixes the evaluation setup (probe inventories, axis grounding, translation QC, split protocol). Appendix A.3 gives detailed values behind main-text claims. Appendix A.4 tests robustness (denser checkpoints, larger EN-only null baselines, alternative anchors). Appendix A.5 breaks down where the signal concentrates across categories and languages.

A.1 Complete Implementation Details

All runs share one 12-layer Llama-style pre-norm decoder with RMSNorm, hidden size 768, FFN size 3072, 12 attention heads, untied token/output matrices, and approximately 310M parameters. Every checkpoint uses the unchanged meta-llama/Llama-3.2-1B BPE tokenizer and its complete 128,256-token multilingual vocabulary; we train no condition-specific tokenizer and take no vocabulary intersection (Appendix Table 25). Throughput is fixed at 32,768 tokens per step, using batch size 8, gradient accumulation 8, and sequence length 512. For non-English probe construction, we use NLLB for translation, COMETKiwi for quality scoring, back-translation, and manual review of low-confidence cases.

A.2 Probe Details

Semantic Axes These tables enumerate the full axis inventory and the theoretical grounding attached to each axis. They make clear that the directional diagnostics are fixed before analysis rather than tuned post hoc to the reported results.

Probe Translation and QC Summary These artifacts document the translation filters applied before any probe enters an evaluation table or figure. Table 6 reports quality scores per language; Table 7 stratifies by quality tier for the overlap ablation. Table 7 further breaks down quality by tier for the overlap ablation in Experiment 2.

Axis Magnitude Interpretation This compact table fixes the scale of the main directional metric before later sections introduce more conditions.

A.3 Data Statistics and Split Protocol

This section records the core bookkeeping facts that reviewers usually need to interpret the design quickly.

Corpus domain and mixed-language audit.

BabyBabelLM provides language-specific mixtures of transcribed child-caregiver and adult conversations, educational material, children’s books, child-oriented Wikipedia and news, and child-suitable film/television subtitles; where needed, it pads Tier-1 budgets with filtered OpenSubtitles and, for some languages, FineWeb-C or Wikipedia. We add no external training corpus. Category proportions vary with language-specific source availability, so we do not interpret cross-language magnitude differences causally. Within each target-language experiment, however, all conditions draw from the same BabyBabelLM source pools and use the same preparation pipeline; shared/disjoint conditions partition the same English pool.

Following Shao et al. (2026), we also ran a heuristic chunk-level fastText audit over all 3,213,686 documents used here. We flag a mixed-language candidate only when the target and another language each cover at least 20% of high-confidence sampled segments, with at least three auditable segments. This identifies 12,382 candidates (0.385%), including 2,721 target-plus-English candidates (0.088%); per-language target-plus-English rates range from 0.001% to 1.217%. These rates are below the roughly 2% found by Shao et al. (2026) in generic web data. Sparse mixed-language exposure may still contribute to the effect, but the present study does not claim a unique causal mechanism.

Hyperparameter search policy and reported values

This study does not use hyperparameter search. We pre-specified one training recipe and reused it for all runs so that differences are attributable to the intended control variables rather than to tuning variance. Concretely, all runs use the same model family and training geometry reported in Section 3.2 (310M parameters), batch size 8, gradient accumulation 8, sequence length 512, and throughput 32,768 tokens/step, with checkpoints at 1500 and 3000 steps. Since no sweep was performed, “best-found” values are not applicable here.

A.4 Detailed Tables for Main-Text Results

This section anchors the main-paper figures with exact values. The intent is not to introduce new claims, but to make the quantitative basis of the main narrative explicit.

Axis set A			Axis set B		
#	Endpoint 1	Endpoint 2	#	Endpoint 1	Endpoint 2
1	individualism	collectivism	26	rice	bread
2	hierarchy	equality	27	tea	coffee
3	duty	freedom	28	spicy	mild
4	honor	shame	29	vegetarian	meat
5	obedience	autonomy	30	fermented	fresh
6	tradition	modernity	31	fasting	feasting
7	restraint	indulgence	32	lunar	solar
8	conformity	dissent	33	mourning	celebration
9	solidarity	competition	34	ancestor	novelty
10	certainty	ambiguity	35	pilgrim	spectator
11	mother	father	36	veiled	unveiled
12	elder	youth	37	formal	casual
13	kin	stranger	38	ornate	plain
14	lineage	mobility	39	modest	revealing
15	clan	individual	40	uniform	personalized
16	sacred	secular	41	white	red
17	ritual	routine	42	black	gold
18	prayer	reason	43	dragon	eagle
19	pilgrimage	tourism	44	lotus	rose
20	taboo	permissive	45	script	image
21	democracy	monarchy	46	local	global
22	federal	centralized	47	indigenous	diaspora
23	customary	codified	48	assimilation	pluralism
24	authority	deliberation	49	majority	minority
25	patronage	meritocracy	50	homeland	migration

Table 3: Complete list of 50 semantic axes used in all experiments. The same axis inventory is fixed before analysis and reused across all language settings. This rules out post hoc axis selection as an explanation for the main residual.

Main-Text Detailed Tables These tables provide the exact values behind the main-text summaries for Experiments 1 to 4.

A.5 100M Mirrors and Same-Language Controls

This section mirrors the main-paper controls in more detail. The first block reruns the main EN-centered views at the longer monolingual baseline. The later blocks make the null reference and axis-inventory dependence more explicit.

Same-Language Controls This block defines the EN-only seed-variation distribution used to center the main EN analyses. We estimate it from six

matched seed pairings per checkpoint so that the null is not tied to one arbitrary comparison.




Figure 7: 100M mirror of Figure 2. The same above-null contextual signal remains visible when the monolingual baseline is trained to 100M tokens.

#	Endpoint 1	Endpoint 2	Category	Framework basis	Citation(s)
1	individualism	collectivism	Values and social norms	Hofstede; Schwartz; Inglehart-Welzel; GLOBE	(Hofstede, 2001; Schwartz, 2006)
2	hierarchy	equality	Values and social norms	Hofstede; Schwartz; Inglehart-Welzel; GLOBE	(Hofstede, 2001; Schwartz, 2006)
3	duty	freedom	Values and social norms	Hofstede; Schwartz; Inglehart-Welzel; GLOBE	(Inglehart and Welzel, 2005)
4	honor	shame	Values and social norms	Hofstede; Schwartz; Inglehart-Welzel; GLOBE	(House et al., 2004)
5	obedience	autonomy	Values and social norms	Hofstede; Schwartz; Inglehart-Welzel; GLOBE	(Schwartz, 2006)
6	tradition	modernity	Values and social norms	Hofstede; Schwartz; Inglehart-Welzel; GLOBE	(Inglehart and Welzel, 2005)
7	restraint	indulgence	Values and social norms	Hofstede; Schwartz; Inglehart-Welzel; GLOBE	(Hofstede, 2001)
8	conformity	dissent	Values and social norms	Hofstede; Schwartz; Inglehart-Welzel; GLOBE	(Schwartz, 2006)
9	solidarity	competition	Values and social norms	Hofstede; Schwartz; Inglehart-Welzel; GLOBE	(House et al., 2004)
10	certainty	ambiguity	Values and social norms	Hofstede; Schwartz; Inglehart-Welzel; GLOBE	(Hofstede, 2001)
11	mother	father	Family and kinship	HRAF kinship domains; Schwartz Embeddedness; WVS family values	(House et al., 2004)
12	elder	youth	Family and kinship	HRAF kinship domains; Schwartz Embeddedness; WVS family values	(Hofstede, 2001)
13	kin	stranger	Family and kinship	HRAF kinship domains; Schwartz Embeddedness; WVS family values	(Schwartz, 2006)
14	lineage	mobility	Family and kinship	HRAF kinship domains; Schwartz Embeddedness; WVS family values	(Inglehart and Welzel, 2005)
15	clan	individual	Family and kinship	HRAF kinship domains; Schwartz Embeddedness; WVS family values	(Schwartz, 2006)
16	sacred	secular	Religion and ritual life	Inglehart Traditional-Secular; WVS religiosity domains	(Inglehart and Welzel, 2005)
17	ritual	routine	Religion and ritual life	Inglehart Traditional-Secular; WVS religiosity domains	(House et al., 2004)
18	prayer	reason	Religion and ritual life	Inglehart Traditional-Secular; WVS religiosity domains	(Inglehart and Welzel, 2005)
19	pilgrimage	tourism	Religion and ritual life	Inglehart Traditional-Secular; WVS religiosity domains	(Hershovich et al., 2022)
20	taboo	permissive	Religion and ritual life	Inglehart Traditional-Secular; WVS religiosity domains	(Hofstede, 2001)
21	democracy	monarchy	Governance, institutions, and law	Hofstede PDI/UA1 and comparative political-institutional domains	(Hofstede, 2001)
22	federal	centralized	Governance, institutions, and law	Hofstede PDI/UA1 and comparative political-institutional domains	(House et al., 2004)
23	customary	codified	Governance, institutions, and law	Hofstede PDI/UA1 and comparative political-institutional domains	(Hofstede, 2001)
24	authority	deliberation	Governance, institutions, and law	Hofstede PDI/UA1 and comparative political-institutional domains	(House et al., 2004)
25	patronage	meritocracy	Governance, institutions, and law	Hofstede PDI/UA1 and comparative political-institutional domains	(Hofstede, 2001)

Table 4: Mapping of 50 semantic axes to literature-grounded categories and framework dimensions (Part I, axes 1 to 25). The table makes the source of each directional probe auditable.

#	Endpoint 1	Endpoint 2	Category	Framework basis	Citation(s)
26	rice	bread	Food and cuisine	Food anthropology; cultural-value probing in NLP	(Hershovich et al., 2022)
27	tea	coffee	Food and cuisine	Food anthropology; cultural-value probing in NLP	(Hershovich et al., 2022)
28	spicy	mild	Food and cuisine	Food anthropology; cultural-value probing in NLP	(Hershovich et al., 2022)
29	vegetarian	meat	Food and cuisine	Food anthropology; cultural-value probing in NLP	(Arora et al., 2023)
30	fermented	fresh	Food and cuisine	Food anthropology; cultural-value probing in NLP	(Hershovich et al., 2022)
31	fasting	feasting	Festivals and holidays	Ritual calendar domains in cross-cultural surveys and ethnography	(Inglehart and Welzel, 2005)
32	lunar	solar	Festivals and holidays	Ritual calendar domains in cross-cultural surveys and ethnography	(Hershovich et al., 2022)
33	mourning	celebration	Festivals and holidays	Ritual calendar domains in cross-cultural surveys and ethnography	(Inglehart and Welzel, 2005)
34	ancestor	novelty	Festivals and holidays	Ritual calendar domains in cross-cultural surveys and ethnography	(Schwartz, 2006)
35	pilgrim	spectator	Festivals and holidays	Ritual calendar domains in cross-cultural surveys and ethnography	(Arora et al., 2023)
36	veiled	unveiled	Clothing and appearance codes	Gender-role and modesty norms in GLOBE/Hofstede-aligned studies	(House et al., 2004)
37	formal	casual	Clothing and appearance codes	Gender-role and modesty norms in GLOBE/Hofstede-aligned studies	(Hofstede, 2001)
38	ornate	plain	Clothing and appearance codes	Gender-role and modesty norms in GLOBE/Hofstede-aligned studies	(Hershovich et al., 2022)
39	modest	revealing	Clothing and appearance codes	Gender-role and modesty norms in GLOBE/Hofstede-aligned studies	(House et al., 2004)
40	uniform	personalized	Clothing and appearance codes	Gender-role and modesty norms in GLOBE/Hofstede-aligned studies	(Hofstede, 2001)
41	white	red	Symbols, colors, and cultural objects	Color-term universals and symbol systems in cultural anthropology	(Berlin and Kay, 1969)
42	black	gold	Symbols, colors, and cultural objects	Color-term universals and symbol systems in cultural anthropology	(Berlin and Kay, 1969)
43	dragon	eagle	Symbols, colors, and cultural objects	Color-term universals and symbol systems in cultural anthropology	(Hershovich et al., 2022)
44	lotus	rose	Symbols, colors, and cultural objects	Color-term universals and symbol systems in cultural anthropology	(Hershovich et al., 2022)
45	script	image	Symbols, colors, and cultural objects	Color-term universals and symbol systems in cultural anthropology	(Arora et al., 2023)
46	local	global	Social identity, migration, and belonging	WVS social trust and identity blocks; cross-cultural NLP identity dimensions	(Inglehart and Welzel, 2005)
47	indigenous	diaspora	Social identity, migration, and belonging	WVS social trust and identity blocks; cross-cultural NLP identity dimensions	(Hershovich et al., 2022)
48	assimilation	pluralism	Social identity, migration, and belonging	WVS social trust and identity blocks; cross-cultural NLP identity dimensions	(Hershovich et al., 2022)
49	majority	minority	Social identity, migration, and belonging	WVS social trust and identity blocks; cross-cultural NLP identity dimensions	(Arora et al., 2023)
50	homeland	migration	Social identity, migration, and belonging	WVS social trust and identity blocks; cross-cultural NLP identity dimensions	(Inglehart and Welzel, 2005)

Table 5: Mapping of 50 semantic axes to literature-grounded categories and framework dimensions (Part II, axes 26 to 50). The table completes the audit trail for the fixed axis inventory.

Lang	n	Mean QE	Median QE	High	Medium	Low	Manual-review	Duplicate-target
BUL	1000	0.796	0.847	717	192	91	371	47
DEU	1000	0.779	0.824	666	242	92	351	47
FAS	1000	0.797	0.833	696	249	55	510	118
FR	1000	0.777	0.832	658	227	115	288	32
IND	1000	0.763	0.820	599	262	139	389	90
NLD	1000	0.758	0.820	583	270	147	351	55
UKR	1000	0.791	0.841	695	210	95	328	60
ZH	1000	0.745	0.806	529	312	159	491	131

Table 6: Probe translation QC summary for all non-English languages. QE uses COMETKiwi when available (high ≥ 0.80 , medium $[0.60, 0.80)$, low < 0.60); the table also reports manual-review flags and duplicate-target checks. Target-language comparisons are only interpretable if probe translation quality is visible.




Figure 8: 100M mirror of Figure 3. The overlap effect stays modest when the monolingual baseline is trained to 100M tokens.

A.6 Robustness Beyond the Main Controls

Axis-Grounding Holdout Robustness This table asks whether the contextual result is being carried by one narrow handcrafted axis subset. The held-out grouping check stays elevated, which argues against that explanation.

Training-Progress Sensitivity These artifacts ask whether the hidden-state-over-embedding gap is a late-training fluke. The dense trajectories show the opposite. Across all eight bilingual families, the

Baseline	Family	Quality tier	n	Wilcoxon p
EN-100M	EN+BUL	High QE	717	1.12e-02
EN-100M	EN+BUL	Low QE	91	3.35e-01
EN-100M	EN+BUL	Medium QE	192	3.27e-01
EN-100M	EN+DEU	High QE	666	2.58e-02
EN-100M	EN+DEU	Low QE	92	4.56e-02
EN-100M	EN+DEU	Medium QE	242	9.09e-01
EN-100M	EN+FAS	High QE	696	4.63e-01
EN-100M	EN+FAS	Low QE	55	4.69e-01
EN-100M	EN+FAS	Medium QE	249	2.10e-01
EN-100M	EN+FR	High QE	658	4.01e-05
EN-100M	EN+FR	Low QE	115	9.70e-01
EN-100M	EN+FR	Medium QE	227	1.71e-02
EN-100M	EN+IND	High QE	599	6.57e-01
EN-100M	EN+IND	Low QE	139	6.90e-01
EN-100M	EN+IND	Medium QE	262	7.94e-01
EN-100M	EN+NLD	High QE	583	5.33e-03
EN-100M	EN+NLD	Low QE	147	2.03e-04
EN-100M	EN+NLD	Medium QE	270	3.51e-04
EN-100M	EN+UKR	High QE	695	3.87e-06
EN-100M	EN+UKR	Low QE	95	5.83e-04
EN-100M	EN+UKR	Medium QE	210	3.48e-07
EN-100M	EN+ZH	High QE	529	1.87e-03
EN-100M	EN+ZH	Low QE	159	7.87e-01
EN-100M	EN+ZH	Medium QE	312	9.68e-01
EN-50M	EN+BUL	High QE	717	4.08e-07
EN-50M	EN+BUL	Low QE	91	3.99e-01
EN-50M	EN+BUL	Medium QE	192	6.18e-01
EN-50M	EN+DEU	High QE	666	8.18e-08
EN-50M	EN+DEU	Low QE	92	6.87e-02
EN-50M	EN+DEU	Medium QE	242	1.87e-02
EN-50M	EN+FAS	High QE	696	6.80e-02
EN-50M	EN+FAS	Low QE	55	4.40e-01
EN-50M	EN+FAS	Medium QE	249	1.95e-01
EN-50M	EN+FR	High QE	658	7.64e-02
EN-50M	EN+FR	Low QE	115	4.50e-03
EN-50M	EN+FR	Medium QE	227	6.70e-01
EN-50M	EN+IND	High QE	599	4.31e-02
EN-50M	EN+IND	Low QE	139	1.53e-01
EN-50M	EN+IND	Medium QE	262	1.50e-01
EN-50M	EN+NLD	High QE	583	1.39e-01
EN-50M	EN+NLD	Low QE	147	4.18e-01
EN-50M	EN+NLD	Medium QE	270	4.86e-01
EN-50M	EN+UKR	High QE	695	8.42e-03
EN-50M	EN+UKR	Low QE	95	6.99e-02
EN-50M	EN+UKR	Medium QE	210	1.32e-05
EN-50M	EN+ZH	High QE	529	2.46e-01
EN-50M	EN+ZH	Low QE	159	5.18e-01
EN-50M	EN+ZH	Medium QE	312	8.23e-03

Table 7: Quality-tier stratification for Experiment 2 overlap tests (COMETKiwi tiers when available; back-translation tiers otherwise). The overlap conclusion should not depend on low-quality translated probes.

hidden-state-versus-embedding gap appears early and persists throughout training.

Alignment-Family Sensitivity This check asks whether the orthogonal map itself creates the residual. Switching to an affine map changes magnitudes but does not collapse contextual D_{Axis} toward the seed-variation reference.

Anchor-Subset Sensitivity This artifact asks whether the main contextual gap depends on one particular English-anchor list. It does not. Rerunning the alignment with random anchor subsets

Pair	Embedding D_{Axis}	Contextual D_{Axis}	Ctx.-Emb.
EN-100M vs EN+BUL	-0.002	0.473	0.475
EN-100M vs EN+DEU	0.001	0.620	0.619
EN-100M vs EN+FAS	0.019	0.726	0.707
EN-100M vs EN+FR	-0.005	0.467	0.472
EN-100M vs EN+IND	-0.001	0.369	0.369
EN-100M vs EN+NLD	0.002	0.260	0.257
EN-100M vs EN+UKR	0.018	0.940	0.922
EN-100M vs EN+ZH	0.018	0.592	0.574
EN-50M vs EN+BUL	0.012	0.054	0.042
EN-50M vs EN+DEU	0.018	0.317	0.299
EN-50M vs EN+FAS	0.031	0.246	0.215
EN-50M vs EN+FR	0.013	0.108	0.096
EN-50M vs EN+IND	0.014	0.107	0.093
EN-50M vs EN+NLD	0.018	0.145	0.127
EN-50M vs EN+UKR	0.035	0.582	0.547
EN-50M vs EN+ZH	0.036	0.172	0.136

Table 8: Compact interpretation table for axis magnitudes by pair, covering embedding and contextual D_{Axis} with their contextual-minus-embedding gap. Gives a scale reference for reading later D_{Axis} tables.

Item	Statistics / split detail
Pretraining data source	BabyBabelLM English and 8 Tier-1 non-English languages used in this study.
Target-language inventory	8 languages spanning ZH FR FAS NLD UKR BUL IND DEU .
Model configuration	Llama-style pre-norm decoder with RMSNorm, 12 layers, hidden size 768, FFN size 3072, 12 attention heads, vocabulary size 128,256, and untied token-embedding/output matrices (~310M parameters).
Token budget checkpoints	1500 steps ($\approx$ 49.15M tokens) and 3000 steps ($\approx$ 98.30M tokens), at 32,768 tokens/step.
EN-centered comparison grid	16 primary pairs (2 EN baselines $\times$ 8 EN+L2 families); shared/disjoint conditions give 32 model-pair observations. Embedding/contextual results are two views of these pairs; the six-pair seed null is separate.
General-vocabulary anchors (alignment set)	3000 English words; used only to estimate alignment maps.
Semantic probes (evaluation set)	1000 terms; held out from alignment and used only for mismatch evaluation.
Semantic axes	50 axis pairs; fixed before training/evaluation and used only in evaluation metrics.
Negative-control set	100 words from high-stability lexical domains; evaluation-only stress test.
Train/dev/test protocol note	No supervised train/dev/test split is used in this unsupervised pretraining study. The key protocol split is <i>alignment set</i> (general-vocabulary anchors) versus <i>held-out evaluation sets</i> (semantic probes, axes, and negative controls).

Table 9: Data statistics and split protocol summary for reproducibility and submission checklist reporting. Separates the alignment anchors from the held-out evaluation probes.

containing 500 to 3000 words leaves the contextual D_{Axis} advantage essentially unchanged.

Pair-Level Contextual-Anchor Results Table 24 gives the pair-level values behind the held-out contextual-alignment summary in main-text Table 2.

Tokenizer Check and Aggregate Tests These tables make two support claims explicit. First, all evaluated checkpoints use the same tokenizer artifacts, so the reported differences are not explained

Pair	Metric	Mean [95% CI]
EN-50M vs EN+BUL	D_{NN}	0.003 [-0.015, 0.021]
	D_{Axis}	0.012 [0.008, 0.017]
	D_{Struct}	0.005 [0.003, 0.006]
EN-50M vs EN+DEU	D_{NN}	0.018 [0.001, 0.036]
	D_{Axis}	0.018 [0.014, 0.023]
	D_{Struct}	0.003 [0.002, 0.005]
EN-50M vs EN+FAS	D_{NN}	0.047 [0.030, 0.064]
	D_{Axis}	0.031 [0.025, 0.037]
	D_{Struct}	0.030 [0.028, 0.032]
EN-50M vs EN+FR	D_{NN}	0.005 [-0.013, 0.023]
	D_{Axis}	0.013 [0.009, 0.016]
	D_{Struct}	-0.004 [-0.005, -0.002]
EN-50M vs EN+IND	D_{NN}	0.018 [0.000, 0.035]
	D_{Axis}	0.014 [0.010, 0.019]
	D_{Struct}	0.003 [0.002, 0.005]
EN-50M vs EN+NLD	D_{NN}	0.008 [-0.010, 0.026]
	D_{Axis}	0.018 [0.014, 0.022]
	D_{Struct}	0.004 [0.002, 0.005]
EN-50M vs EN+UKR	D_{NN}	0.042 [0.024, 0.059]
	D_{Axis}	0.035 [0.027, 0.043]
	D_{Struct}	0.031 [0.029, 0.034]
EN-50M vs EN+ZH	D_{NN}	0.053 [0.036, 0.069]
	D_{Axis}	0.036 [0.029, 0.043]
	D_{Struct}	0.038 [0.035, 0.041]
EN-100M vs EN+BUL	D_{NN}	0.013 [-0.004, 0.030]
	D_{Axis}	-0.002 [-0.008, 0.004]
	D_{Struct}	0.006 [0.004, 0.008]
EN-100M vs EN+DEU	D_{NN}	0.029 [0.011, 0.046]
	D_{Axis}	0.000 [-0.004, 0.005]
	D_{Struct}	0.007 [0.005, 0.008]
EN-100M vs EN+FAS	D_{NN}	0.057 [0.041, 0.074]
	D_{Axis}	0.019 [0.011, 0.026]
	D_{Struct}	0.031 [0.029, 0.034]
EN-100M vs EN+FR	D_{NN}	0.010 [-0.008, 0.029]
	D_{Axis}	-0.005 [-0.009, -0.001]
	D_{Struct}	-0.003 [-0.004, -0.001]
EN-100M vs EN+IND	D_{NN}	0.021 [0.004, 0.040]
	D_{Axis}	-0.001 [-0.004, 0.004]
	D_{Struct}	0.004 [0.002, 0.005]
EN-100M vs EN+NLD	D_{NN}	0.022 [0.005, 0.041]
	D_{Axis}	0.002 [-0.002, 0.007]
	D_{Struct}	0.006 [0.005, 0.008]
EN-100M vs EN+UKR	D_{NN}	0.053 [0.036, 0.069]
	D_{Axis}	0.018 [0.010, 0.026]
	D_{Struct}	0.034 [0.031, 0.036]
EN-100M vs EN+ZH	D_{NN}	0.058 [0.042, 0.075]
	D_{Axis}	0.018 [0.012, 0.025]
	D_{Struct}	0.036 [0.033, 0.038]

Table 10: Detailed Experiment 1 table in embedding space. Several centered intervals include zero, but the aggregate mismatch pattern remains visible. Shows that the embedding side is close to the seed-variation baseline.




Figure 9: 100M mirror of Figure 4b. The target-language-centered contextual signal remains visible at the longer monolingual baseline.

Pair	Metric	Mean [95% CI]
EN-50M vs EN+BUL	D_{NN}	-0.009 [-0.021, 0.002]
	D_{Axis}	0.053 [-0.171, 0.308]
	D_{Struct}	0.051 [0.045, 0.058]
EN-50M vs EN+DEU	D_{NN}	0.008 [-0.004, 0.020]
	D_{Axis}	0.321 [0.058, 0.599]
	D_{Struct}	0.007 [0.001, 0.013]
EN-50M vs EN+FAS	D_{NN}	0.025 [0.014, 0.036]
	D_{Axis}	0.245 [-0.051, 0.570]
	D_{Struct}	0.046 [0.039, 0.055]
EN-50M vs EN+FR	D_{NN}	-0.004 [-0.016, 0.008]
	D_{Axis}	0.105 [-0.124, 0.346]
	D_{Struct}	-0.018 [-0.022, -0.013]
EN-50M vs EN+IND	D_{NN}	0.017 [0.006, 0.029]
	D_{Axis}	0.103 [-0.139, 0.351]
	D_{Struct}	0.027 [0.020, 0.034]
EN-50M vs EN+NLD	D_{NN}	-0.001 [-0.013, 0.012]
	D_{Axis}	0.145 [-0.134, 0.451]
	D_{Struct}	0.009 [0.003, 0.016]
EN-50M vs EN+UKR	D_{NN}	0.024 [0.014, 0.035]
	D_{Axis}	0.586 [0.130, 1.072]
	D_{Struct}	0.011 [0.004, 0.017]
EN-50M vs EN+ZH	D_{NN}	0.038 [0.028, 0.048]
	D_{Axis}	0.175 [-0.050, 0.428]
	D_{Struct}	0.095 [0.086, 0.103]
EN-100M vs EN+BUL	D_{NN}	0.000 [-0.012, 0.012]
	D_{Axis}	0.475 [0.016, 0.960]
	D_{Struct}	0.087 [0.079, 0.094]
EN-100M vs EN+DEU	D_{NN}	0.015 [0.003, 0.026]
	D_{Axis}	0.607 [0.137, 1.087]
	D_{Struct}	0.031 [0.024, 0.037]
EN-100M vs EN+FAS	D_{NN}	0.029 [0.018, 0.040]
	D_{Axis}	0.723 [0.264, 1.217]
	D_{Struct}	0.076 [0.067, 0.085]
EN-100M vs EN+FR	D_{NN}	0.005 [-0.006, 0.017]
	D_{Axis}	0.467 [0.012, 0.957]
	D_{Struct}	0.000 [-0.005, 0.006]
EN-100M vs EN+IND	D_{NN}	0.013 [0.001, 0.024]
	D_{Axis}	0.365 [-0.043, 0.814]
	D_{Struct}	0.051 [0.043, 0.059]
EN-100M vs EN+NLD	D_{NN}	0.006 [-0.006, 0.018]
	D_{Axis}	0.256 [-0.161, 0.706]
	D_{Struct}	0.031 [0.024, 0.039]
EN-100M vs EN+UKR	D_{NN}	0.024 [0.013, 0.034]
	D_{Axis}	0.933 [0.326, 1.607]
	D_{Struct}	0.035 [0.028, 0.042]
EN-100M vs EN+ZH	D_{NN}	0.051 [0.041, 0.061]
	D_{Axis}	0.587 [0.179, 1.051]
	D_{Struct}	0.130 [0.122, 0.139]

Table 11: Detailed Experiment 1 table in contextual space. Some intervals are wide and can cross zero, while the aggregate contextual mismatch remains elevated. Exposes the uncertainty behind the main contextual residual claim.

Representation	Group	D_{NN}	D_{Struct}	D_{Axis}
Embedding	Cultural probes	0.029	0.014	0.014
	Negative controls	0.328	0.017	0.075
Contextual	Cultural probes	0.015	0.042	0.386
	Negative controls	0.165	0.034	0.483

Table 12: Negative-control reference used to bound stronger semantic-domain claims. In this aggregate view, disagreement is comparable to or higher than the semantic-probe summary. Prevents interpreting the result as uniquely cultural.

by tokenization drift. Second, the main hidden-state-over-embedding contrast remains positive in aggregate both in the original EN-centered comparisons and in the anchor-subset reruns.




Figure 10: **100M mirrors of the hidden-state and alignment-method checks.** The longer-baseline setting preserves the hidden-state-over-embedding gap, the middle-layer profile, and the qualitative alignment-family robustness.




Figure 11: 100M mirror of Figure 15. The rows match the EN-50M selection so directional stability can be read directly across baselines.

Per-Head Proxy Analysis These artifacts ask whether the middle-layer signal is distributed or concentrated in one small channel set. They are not intended as a full mechanistic account, but as a coarse localization check. Figure 14 shows that divergence is broadly distributed across head-width slices rather than concentrated in a few cells; Table 27 lists the highest-divergence cells.

A.7 Where the Signal Concentrates Across Categories and Languages

Additional Stratified and Word-Level Diagnostics These diagnostics ask what kinds of probes contribute most to the contextual signal. They com-

plement the main aggregate figures by showing signed examples, broader category concentration, and word-level hotspots.

Non-English Language Snapshot This block extends the multilingual view beyond the two representative main-text languages and asks whether a simple family-level explanation emerges. The additional-language summaries confirm robustness of the hidden-state amplification pattern, while the exploratory regression and scatter plot do not support a strong monotonic typology claim.



Figure 12: Dense checkpoints show that the contextual gap is not a late-training artifact. Each panel traces one EN+L2 family at 500-step intervals under shared data. Contextual states remain above token embeddings from the earliest saved checkpoint through 3000 steps.

Representation	Pair	Anchor residual / anchor	Anchor residual (Frobenius)
Embedding	EN-100M vs EN+BUL	0.043	128.572
	EN-100M vs EN+DEU	0.044	131.045
	EN-100M vs EN+FAS	0.045	136.197
	EN-100M vs EN+FR	0.044	131.241
	EN-100M vs EN+IND	0.044	130.703
	EN-100M vs EN+NLD	0.044	131.786
	EN-100M vs EN+UKR	0.045	134.486
	EN-100M vs EN+ZH	0.045	135.875
	EN-50M vs EN+BUL	0.037	109.879
	EN-50M vs EN+DEU	0.038	112.648
	EN-50M vs EN+FAS	0.039	116.123
	EN-50M vs EN+FR	0.038	114.572
	EN-50M vs EN+IND	0.038	112.702
	EN-50M vs EN+NLD	0.038	113.972
	EN-50M vs EN+UKR	0.038	114.549
	EN-50M vs EN+ZH	0.039	115.700
Contextual	EN-100M vs EN+BUL	0.216	646.757
	EN-100M vs EN+DEU	0.209	626.308
	EN-100M vs EN+FAS	0.230	688.624
	EN-100M vs EN+FR	0.197	591.295
	EN-100M vs EN+IND	0.205	616.292
	EN-100M vs EN+NLD	0.214	642.959
	EN-100M vs EN+UKR	0.216	648.819
	EN-100M vs EN+ZH	0.252	756.882
	EN-50M vs EN+BUL	0.166	498.512
	EN-50M vs EN+DEU	0.165	494.702
	EN-50M vs EN+FAS	0.176	527.434
	EN-50M vs EN+FR	0.154	462.554
	EN-50M vs EN+IND	0.166	498.938
	EN-50M vs EN+NLD	0.170	509.490
	EN-50M vs EN+UKR	0.172	517.038
	EN-50M vs EN+ZH	0.192	575.544

Table 13: Alignment-fit check for Experiment 1. Comparable Procrustes residuals across pairs argue against alignment failure as the main explanation. Separates residual mismatch from a failed anchor fit.

Representation	Family	Baseline	ΔD_{NN}	ΔD_{Struct}	ΔD_{Axis}
Embedding	EN+BUL	EN-50M	-0.017	-0.008	-0.008
		EN-50M	-0.006	-0.004	-0.004
		EN-50M	0.014	0.004	-0.001
		EN-50M	-0.006	-0.001	0.001
		EN-50M	0.007	0.005	0.007
		EN-50M	0.004	0.009	0.008
		EN-50M	0.023	0.014	0.008
		EN-50M	-0.000	0.009	-0.000
	EN+DEU	EN-100M	-0.014	-0.010	-0.004
		EN-100M	0.005	0.001	-0.000
		EN-100M	0.018	0.003	0.007
		EN-100M	-0.002	0.001	0.002
		EN-100M	0.010	0.007	0.008
		EN-100M	0.014	0.012	0.010
		EN-100M	0.032	0.018	0.012
		EN-100M	-0.003	0.005	0.004
Contextual	EN+BUL	EN-50M	-0.014	-0.004	-0.231
		EN-50M	-0.016	-0.008	0.165
		EN-50M	-0.002	0.046	0.151
		EN-50M	0.002	-0.008	-0.218
		EN-50M	0.007	0.041	-0.214
		EN-50M	0.005	0.010	-0.061
		EN-50M	0.014	-0.013	0.513
		EN-50M	-0.006	-0.004	0.122
	EN+DEU	EN-100M	-0.007	0.002	0.270
		EN-100M	-0.007	-0.006	0.113
		EN-100M	-0.000	0.059	0.131
		EN-100M	0.014	-0.006	0.208
		EN-100M	-0.001	0.062	0.080
		EN-100M	0.013	0.022	0.023
		EN-100M	0.022	-0.008	0.594
		EN-100M	0.007	0.001	-0.007

Table 14: Detailed overlap-ablation table. Each row reports the per-metric change induced by removing English-document overlap. Shows document identity modulates values without creating the main effect.

Representation	Baseline	Family	n	Med. ΔD_{NN}	p
Embedding	EN-50M	EN+BUL	1000	0.000	5.39e-09
	EN-50M	EN+DEU	1000	0.000	1.77e-02
	EN-50M	EN+FAS	1000	0.000	1.60e-06
	EN-50M	EN+FR	1000	0.000	3.14e-02
	EN-50M	EN+IND	1000	0.000	5.06e-04
	EN-50M	EN+NLD	1000	0.000	6.70e-02
	EN-50M	EN+UKR	1000	0.000	4.89e-15
	EN-50M	EN+ZH	1000	0.000	9.87e-01
	EN-100M	EN+BUL	1000	0.000	2.98e-07
	EN-100M	EN+DEU	1000	0.000	4.49e-03
	EN-100M	EN+FAS	1000	0.000	3.32e-10
	EN-100M	EN+FR	1000	0.000	3.74e-01
	EN-100M	EN+IND	1000	0.000	6.18e-06
	EN-100M	EN+NLD	1000	0.000	3.06e-09
	EN-100M	EN+UKR	1000	0.000	2.44e-27
	EN-100M	EN+ZH	1000	0.000	2.71e-01
Contextual	EN-50M	EN+BUL	1000	0.000	1.75e-05
	EN-50M	EN+DEU	1000	0.000	1.09e-09
	EN-50M	EN+FAS	1000	0.000	5.08e-01
	EN-50M	EN+FR	1000	0.000	7.73e-01
	EN-50M	EN+IND	1000	0.000	7.52e-02
	EN-50M	EN+NLD	1000	0.000	2.45e-01
	EN-50M	EN+UKR	1000	0.000	2.47e-06
	EN-50M	EN+ZH	1000	0.000	8.27e-03
	EN-100M	EN+BUL	1000	0.000	4.16e-02
	EN-100M	EN+DEU	1000	0.000	1.63e-02
	EN-100M	EN+FAS	1000	0.000	8.42e-01
	EN-100M	EN+FR	1000	0.000	7.59e-06
	EN-100M	EN+IND	1000	0.000	7.18e-01
	EN-100M	EN+NLD	1000	0.000	8.79e-08
	EN-100M	EN+UKR	1000	0.010	4.24e-13
	EN-100M	EN+ZH	1000	0.000	2.91e-02

Table 15: Word-level overlap test for Experiment 2. The effect is statistically real but sparse, with near-zero medians in almost all settings. Keeps the overlap result from being overstated.

Pair	D_A (Embedding)	D_A (Contextual)	Ctx.-Emb.
EN-50M vs EN+BUL	0.012	0.054	0.042
EN-50M vs EN+DEU	0.018	0.317	0.299
EN-50M vs EN+FAS	0.031	0.246	0.215
EN-50M vs EN+FR	0.013	0.108	0.096
EN-50M vs EN+IND	0.014	0.107	0.093
EN-50M vs EN+NLD	0.018	0.145	0.127
EN-50M vs EN+UKR	0.035	0.582	0.547
EN-50M vs EN+ZH	0.036	0.172	0.136
EN-100M vs EN+BUL	-0.002	0.473	0.475
EN-100M vs EN+DEU	0.001	0.620	0.619
EN-100M vs EN+FAS	0.019	0.726	0.707
EN-100M vs EN+FR	-0.005	0.467	0.472
EN-100M vs EN+IND	-0.001	0.369	0.369
EN-100M vs EN+NLD	0.002	0.260	0.257
EN-100M vs EN+UKR	0.018	0.940	0.922
EN-100M vs EN+ZH	0.018	0.592	0.574

Table 16: Detailed hidden-state-versus-embedding table. We report absolute centered axis divergence for both layers and the hidden-state-minus-embedding gap. Supports the hidden-state-over-embedding gap without unstable centered ratios.

Language	Family	IDV Dist.	Ratio (50M)	Ratio (100M)
French	(Romance)	20	29.49	35.89
Indonesian	Austronesian	77	33.79	27.47
German	(Germanic)	24	25.41	28.31
Bulgarian	(Slavic)	61	27.61	25.66
Dutch	(Germanic)	11	24.02	25.20
Ukrainian	(Slavic)	66	21.81	24.85
Persian	(Iranian)	50	20.41	22.46
Chinese	Sino-Tib.	71	17.11	21.41

Table 17: Target-language-centered raw amplification summary. Across the eight non-English pairs, contextual D_{Axis} remains much larger than embedding D_{Axis} ; these raw ratios are descriptive only and are not used for the centered EN-space claims. Checks that the hidden-state-over-embedding gap is not English-specific.

Pair	Peak	D_A (peak)	D_A (final)	F/P
EN-100M vs EN+BUL	6	2775.9	3.472	0.001
EN-100M vs EN+DEU	7	2591.2	3.618	0.001
EN-100M vs EN+FAS	3	2809.8	3.720	0.001
EN-100M vs EN+FR	6	2358.2	3.466	0.001
EN-100M vs EN+IND	6	2185.3	3.366	0.002
EN-100M vs EN+NLD	6	2372.2	3.254	0.001
EN-100M vs EN+UKR	6	2403.2	3.936	0.002
EN-100M vs EN+ZH	3	2588.4	3.590	0.001
EN-50M vs EN+BUL	6	2240.0	2.276	0.001
EN-50M vs EN+DEU	9	1995.8	2.540	0.001
EN-50M vs EN+FAS	4	2112.4	2.469	0.001
EN-50M vs EN+FR	6	1483.6	2.333	0.002
EN-50M vs EN+IND	6	1671.6	2.330	0.001
EN-50M vs EN+NLD	5	1692.4	2.366	0.001
EN-50M vs EN+UKR	4	1522.9	2.802	0.002
EN-50M vs EN+ZH	4	2205.3	2.398	0.001

Table 18: Layer-summary table for Figure 5a. Peak-layer and final-layer values confirm persistence after late-layer compression. Localizes the residual to contextual processing rather than static embeddings.

Baseline	Control	Embed.	Context.	Gap	+Pairs	Final/Input
EN-50M	Row-L2	0.091	0.140	+0.049	8/8	1.544
EN-50M	Neutral-z	0.728	0.824	+0.097	8/8	1.132
EN-100M	Row-L2	0.095	0.147	+0.052	8/8	1.546
EN-100M	Neutral-z	0.762	0.904	+0.142	8/8	1.186

Table 19: Aggregate norm-control table for Figure 5b. Row-L2 removes per-vector norm scale before alignment; Neutral-z scores each axis using neutral-anchor projections. Contextual values remain larger than embedding values for every shared-document EN+L2 pair under both controls, confirming the gap is not just hidden-state norm scale.

Baseline	Representation	Mean raw D_{Axis}	Std. dev.	EN-seed pairs
EN-100M	Contextual	3.204	0.295	6
EN-100M	Embedding	0.150	0.002	6
EN-50M	Contextual	2.258	0.182	6
EN-50M	Embedding	0.113	0.002	6

Table 20: Expanded EN-only seed-variation estimate. Raw D_{Axis} is summarized across six seed pairings per checkpoint and representation level (embedding or hidden state) to make the centering reference less brittle. The null reference is not a single arbitrary seed comparison.

Representation	Matched-axis D_{Axis}	Held-out-axis D_{Axis}	Held-out minus matched
Contextual	0.261	0.390	0.129
Embedding	0.018	0.014	-0.004

Table 21: Axis-inventory holdout check. Both matched-axis and held-out-axis evaluations remain elevated, arguing against dependence on one handcrafted subset. The mismatch does not depend on one narrow axis group.

Language	500 Emb.	500 Ctx.	3000 Emb.	3000 Ctx.	Mean gap
ZH	0.079	2.983	0.168	3.581	2.772
FR	0.068	3.012	0.144	3.463	2.776
FAS	0.077	2.942	0.168	3.711	2.808
NLD	0.067	2.800	0.152	3.254	2.620
UKR	0.083	3.162	0.167	3.931	2.983
BUL	0.069	2.663	0.147	3.458	2.650
IND	0.067	2.784	0.149	3.357	2.704
DEU	0.069	2.977	0.150	3.616	2.864

Table 22: Dense checkpoint summary for all eight EN vs EN+L2 C3 pairs. Raw D_{Axis} is shown at the start and end of training together with the mean contextual-minus-embedding gap across checkpoints. Rules out a late-checkpoint accident.




Figure 13: **Alignment family changes values, not the qualitative result.** Lines connect orthogonal and affine contextual EN-50M values for each language.

Baseline	Representation	Anchor subset	Mean D_{Axis}	Residual / anchor
EN-100M	Embedding	500	0.155	0.081
EN-100M	Embedding	1000	0.155	0.066
EN-100M	Embedding	2000	0.155	0.052
EN-100M	Embedding	3000	0.155	0.044
EN-100M	Contextual	500	3.552	0.495
EN-100M	Contextual	1000	3.552	0.364
EN-100M	Contextual	2000	3.552	0.264
EN-100M	Contextual	3000	3.552	0.217
EN-50M	Embedding	500	0.135	0.069
EN-50M	Embedding	1000	0.135	0.056
EN-50M	Embedding	2000	0.135	0.045
EN-50M	Embedding	3000	0.135	0.038
EN-50M	Contextual	500	2.439	0.378
EN-50M	Contextual	1000	2.439	0.282
EN-50M	Contextual	2000	2.439	0.206
EN-50M	Contextual	3000	2.439	0.170

Table 23: Anchor-subset sensitivity for EN-centered pairs. Mean raw D_{Axis} is stable across five random draws at each anchor subset size. The result is not tied to one English-anchor list.

Pair	Alignment source	D_{NN}	D_{Struct}	D_{Axis}	Residual/anchor
EN-50M vs EN+BUL (C3)	Align on Embedding anchors	-0.009	0.051	0.054	0.037
	Align on Contextual anchors	-0.009	0.051	0.054	0.166
EN-50M vs EN+DEU (C3)	Align on Embedding anchors	0.008	0.007	0.317	0.038
	Align on Contextual anchors	0.008	0.007	0.317	0.165
EN-50M vs EN+FAS (C3)	Align on Embedding anchors	0.025	0.047	0.246	0.039
	Align on Contextual anchors	0.025	0.047	0.246	0.176
EN-50M vs EN+FR (C3)	Align on Embedding anchors	-0.004	-0.018	0.108	0.038
	Align on Contextual anchors	-0.004	-0.018	0.108	0.154
EN-50M vs EN+IND (C3)	Align on Embedding anchors	0.017	0.027	0.107	0.038
	Align on Contextual anchors	0.017	0.027	0.107	0.166
EN-50M vs EN+NLD (C3)	Align on Embedding anchors	-0.001	0.009	0.145	0.038
	Align on Contextual anchors	-0.001	0.009	0.145	0.170
EN-50M vs EN+UKR (C3)	Align on Embedding anchors	0.025	0.011	0.582	0.038
	Align on Contextual anchors	0.025	0.011	0.582	0.172
EN-50M vs EN+ZH (C3)	Align on Embedding anchors	0.038	0.095	0.172	0.039
	Align on Contextual anchors	0.038	0.095	0.172	0.192
EN-100M vs EN+BUL (C3)	Align on Embedding anchors	0.000	0.087	0.473	0.043
	Align on Contextual anchors	0.000	0.087	0.473	0.216
EN-100M vs EN+DEU (C3)	Align on Embedding anchors	0.015	0.031	0.620	0.044
	Align on Contextual anchors	0.015	0.031	0.620	0.209
EN-100M vs EN+FAS (C3)	Align on Embedding anchors	0.029	0.076	0.726	0.045
	Align on Contextual anchors	0.029	0.076	0.726	0.230
EN-100M vs EN+FR (C3)	Align on Embedding anchors	0.005	0.001	0.467	0.044
	Align on Contextual anchors	0.005	0.001	0.467	0.197
EN-100M vs EN+IND (C3)	Align on Embedding anchors	0.013	0.051	0.369	0.044
	Align on Contextual anchors	0.013	0.051	0.369	0.205
EN-100M vs EN+NLD (C3)	Align on Embedding anchors	0.006	0.031	0.260	0.044
	Align on Contextual anchors	0.006	0.031	0.260	0.214
EN-100M vs EN+UKR (C3)	Align on Embedding anchors	0.023	0.035	0.940	0.045
	Align on Contextual anchors	0.023	0.035	0.940	0.216
EN-100M vs EN+ZH (C3)	Align on Embedding anchors	0.051	0.130	0.592	0.045
	Align on Contextual anchors	0.051	0.130	0.592	0.252

Table 24: Contextual-anchor alignment variant for EN-centered pairs. The contextual axis gap remains large under both embedding- and contextual-anchor alignment. The result survives aligning the contextual family directly.

Tokenizer artifact	Unique hashes across runs
tokenizer.json	1
tokenizer_config.json	1
special_tokens_map.json	1

Table 25: Tokenizer comparability check. All active checkpoints share identical tokenizer artifacts on the three files that define the tokenization pipeline. Tokenizer drift cannot explain the reported residuals.

Test block	Slice	n	Mean diff.	One-sided p
Main EN-centered gap	EN-50M	16	0.181	1.53e-05
Main EN-centered gap	EN-100M	16	0.464	1.53e-05
Main EN-centered gap	All	32	0.322	$< 10^{-6}$
Anchor-subset reruns	EN-50M	160	2.304	$< 10^{-6}$
Anchor-subset reruns	EN-100M	160	3.397	$< 10^{-6}$
Anchor-subset reruns	All	320	2.850	$< 10^{-6}$

Table 26: Aggregate one-sided tests for the two strongest scope-expansion claims. The tests cover contextual > embedding in the main EN-centered comparisons and the same contrast under anchor-subset reruns. Gives compact statistical support for the primary gap and anchor robustness.




Figure 14: Per-head proxy view of the middle-layer effect. Each cell reports mean D_{Axis} for a head-width channel slice, showing that divergence is distributed rather than isolated to one cell.




Figure 15: Signed contextual shifts for representative held-out probe-axis pairs in the Equal exposure + shared data setting. Points show languages and right-side pills report EN+L2-side, EN-side, and near-zero counts. The panel illustrates why absolute D_{Axis} summaries are paired with signed diagnostics.




Figure 16: Category-stratified contextual axis divergence. Food/Cuisine, Symbols/Colors, and Social Identity categories contribute disproportionately to the contextual signal.



Signed shift (L2-50M minus EN+L2): left = EN+L2 higher, right = L2-50M higher

Figure 17: Per-language signed hotspots in target-language shared spaces, Panel I (● ZH ● FR ● FAS ● NLD). Each subplot shows the largest absolute signed shifts; left indicates EN+L2 higher and right indicates L2-50M higher.



Signed shift (L2-50M minus EN+L2): left = EN+L2 higher, right = L2-50M higher

Figure 18: Per-language signed hotspots in target-language shared spaces, Panel II (UKR, BUL, IND, DEU).




Figure 19: Additional-language summary for FAS, NLD, UKR, BUL, IND, and DEU. Left, raw hidden-state-to-embedding amplification at 50M and 100M; right, overlap gain on axis divergence.

Pair	Layer	Head	Mean D_{Axis}
EN-100M vs EN+FAS (C3)	5	9	1728.146
EN-100M vs EN+FAS (C3)	4	9	1709.596
EN-100M vs EN+BUL (C3)	6	0	1703.545
EN-100M vs EN+FAS (C3)	6	9	1642.973
EN-100M vs EN+BUL (C3)	5	0	1609.249
EN-100M vs EN+NLD (C3)	5	8	1595.739
EN-50M vs EN+FAS (C3)	5	9	1595.471
EN-100M vs EN+NLD (C3)	6	8	1580.271
EN-50M vs EN+FAS (C3)	4	9	1559.257
EN-100M vs EN+UKR (C3)	5	1	1550.235
EN-100M vs EN+UKR (C3)	6	0	1549.644
EN-50M vs EN+NLD (C3)	5	8	1528.903

Table 27: Highest-divergence cells from the per-head proxy analysis. Checks whether the middle-layer signal is concentrated in a small channel slice.

Highest contextual divergence			Lowest contextual divergence		
Rank	Word	Mean D_{NN}	Rank	Word	Mean D_{NN}
1	vegan	0.999	1	extended mother	0.323
2	stereotype	0.997	2	public democracy	0.333
3	bamboo	0.997	3	extended father	0.338
4	homeland	0.996	4	extended son	0.341
5	jewelry	0.996	5	extended daughter	0.361
6	integrity	0.996	6	sacred prayer	0.362
7	lineage	0.996	7	public ministry	0.373
8	espresso	0.996	8	sacred mosque	0.373
9	carnival	0.996	9	local majority	0.381
10	curry	0.995	10	sacred curse	0.384

Table 28: Word-level hotspots under contextual neighbor divergence. These rows identify probes that contribute most strongly to local topology mismatch. They make the aggregate residual inspectable at the word level.




Figure 20: Exploratory typology check ($n=6$). The coarse distance proxy does not show a clear monotonic relation with hidden-state amplification.

Lang	Ratio@50M	Ratio@100M	Gain D_{NN} (Embedding)	Gain D_{NN} (Contextual)	Gain D_{Axis} (Embedding)	Gain D_{Axis} (Contextual)
BUL	27.6	25.7	0.008	0.002	0.005	0.060
DEU	25.4	28.3	-0.001	0.011	0.001	-0.079
FAS	20.4	22.5	-0.004	0.007	0.007	-0.222
IND	33.8	27.5	-0.002	-0.009	-0.011	0.140
NLD	24.0	25.2	-0.011	-0.017	-0.011	0.331
UKR	21.8	24.8	-0.006	-0.005	-0.012	-0.302

Table 29: Compact table for the additional-language view. Ratio columns report raw hidden-state amplification under shared data as a descriptive snapshot, and gain columns report separate data minus shared data averaged across baselines. Extends the robustness check beyond the two representative languages.

Lang	Baseline	Mean ratio	CI low	CI high
BUL	100M	25.7	22.4	29.1
BUL	50M	27.7	23.4	32.2
DEU	100M	28.3	24.4	32.4
DEU	50M	25.5	21.9	29.2
FAS	100M	22.4	18.9	26.2
FAS	50M	20.5	17.2	24.0
IND	100M	27.5	23.3	32.1
IND	50M	34.0	28.4	39.7
NLD	100M	25.2	22.0	28.6
NLD	50M	24.1	20.6	27.7
UKR	100M	24.9	20.7	29.4
UKR	50M	21.9	18.5	25.6

Table 30: Bootstrap intervals for the additional-language raw hidden-state-to-embedding ratios under shared data at both baselines; these are not used for centered EN-space claims. Shows uncertainty for the descriptive target-language amplification snapshot.

Quantity	Value
OLS intercept	28.621
OLS coef: script-match (Latin=1)	1.933
OLS coef: family-match (Indo-European=1)	-4.895
OLS coef: baseline(100M=1)	0.150
OLS R^2 (pooled 50M/100M; $n = 12$)	0.515
Spearman ρ (distance proxy, mean ratio; $n = 6$)	-0.207
Spearman p -value	0.694

Table 31: Exploratory cross-language trend analysis. Pooled OLS uses raw ratio observations from both baselines, with script-match and family-match as coarse binary proxies. Keeps typological explanations explicitly exploratory.

Quadrant	Count of axes
ZH>0, FR>0 (shared positive tilt)	21
ZH<0, FR>0 (opposite tilt)	4
ZH<0, FR<0 (shared negative tilt)	23
ZH>0, FR<0 (opposite tilt)	2

Table 32: Quadrant-count summary for Figure 15. Opposite-tilt quadrants indicate language-specific directional effects rather than uniform sign changes, explaining why absolute summaries are paired with signed diagnostics.