CrisiLangs: A Multilingual Resource for Crisis Warning Generation

Giacomo Gonella[1, 2], **Stefano Menini**[1], **Marco Guerini**[1]
[1]Fondazione Bruno Kessler, Italy
[2]University of Trento, Italy
{ggonella, menini, guerini}@fbk.eu

arXiv:2610.31356v1 [cs.CL] 22 Oct 2026

Abstract

Communicating with the public during an emergency entails issuing warning messages promptly. In Europe, it often requires producing them in more than one language. Recent work has shown that language models can be trained to generate warning messages as a crisis unfolds, but the available data covers only English. To fill this gap, we present *CrisiLangs*, a multilingual extension of *CrisiText* (an English dataset of crisis events paired with warning messages written according to expert communication guidelines) to Italian, Bulgarian, German, and Greek. Expert native speakers translated the warning messages of 1,000 events drawn from 411 scenarios, for a total of 5,000 event-message pairs across five languages. We test the resource to fine-tune a multilingual model on all five languages jointly, with and without the emergency guidelines in the prompt, and compare it with a zero-shot baseline. The fine-tuned models outperform the baseline on ROUGE-L, BLEU and BERTScore in every language and configuration. In a human preference study, low decoding temperatures receive the most preferences in all five languages and in both configurations, while the effect of the guidelines varies by language.

1 Introduction

Timely and effective communication is a critical aspect of crisis management: during an emergency, authorities must inform the population about what is happening and about what to do, and they must do it repeatedly as the situation evolves. This has to be done under time pressure and the volume of information handled during an event is a recognized source of stress for emergency operators (Misra et al., 2020). The issue is even worse in Europe, where nations are linguistically diverse (and many have multiple official languages) and there is a high cross-border mobility. Therefore, warnings issued in a single language can fail to reach part of the population they are meant to protect. Issuing the same alert in several languages, at the speed an emergency requires, complicates the work of operators. Recent advances in Artificial Intelligence, and in particular Large Language Models (LLMs), which can interpret and produce text, offer a way to support this task (Foubert et al., 2026).

Crisis NLP has largely worked on analyzing text produced by users, with tasks such as detecting events in social media feeds and extracting informative content (Olteanu et al., 2014; Alam et al., 2021), but recent work has also studied how to use LLMs to assist operators in writing warning messages for ongoing crises. For instance, the *CrisiText* dataset (Gonella et al., 2026a) contains crisis scenarios as chronological chains of events, each paired with a warning message.

Existing resources and related models such as *CrisiText* focus only on English. Multilingual coverage in crisis Natural Language Generation (NLG) has been addressed separately as a translation problem, by applying domain-adapted machine translation to existing crisis text (Staiano et al., 2025; Castaldo et al., 2026). Crisis content, however, is sensitive to automatic translation. Ticona and Anastasopoulos (2026) report lower quality for low-resource languages and when translating out of English. One way to avoid sending automatically translated content to civilians would be to generate messages directly in the target language. However, to the best of our knowledge, no comparable training resource is available for languages other than English.

To address this gap, we present *CrisiLangs*[1], a multilingual extension of *CrisiText* including Italian, Bulgarian, German, and Greek, chosen to

[1]The dataset can be found at https://huggingface.co/datasets/LanD-FBK/CrisiLangs



Figure 1: Workflow for the creation of *CrisiLangs*. Event descriptions and FEMA guidelines are machine-translated into each target language, while the warning messages are translated and adapted by a native speaker.

cover different writing systems and alphabets. In collaboration with crisis communication experts we manually translated a subset of the *CrisiText* dataset into their native languages. The subsample covers 1,000 events from 411 crisis scenarios for a total of 5,000 event-message pairs across the five languages.

We then use the resource to jointly fine-tune a multilingual model on all five languages in two configurations: with and without the emergency guidelines in the prompt. We tested the two configurations in two ways. First, we evaluate the generations with automatic metrics at five decoding temperatures, with a zero-shot model used as the baseline. Since warning messages have to follow specific communication and behavioral guidelines, we varied the temperature to assess which level of lexical variation is best suited to the task. Second, to assess the quality of the generations, we asked native speakers to evaluate them in all five languages.

2 Related Work

Most NLP work on crises relies on social media data, and the resulting resources are designed for classification and information extraction rather than automatic generation (Imran et al., 2015; D. Lewis et al., 2025). Datasets of user-created content collected during floods, earthquakes or tornadoes (Olteanu et al., 2014; Imran et al., 2016) are annotated for informativeness, crisis detection or crisis type recognition, and are used to train classifiers (Alam et al., 2021; Liu et al., 2021). Fewer resources cover languages other than English: HumSet (Fekih et al., 2022) provides humanitarian response documents in English, French and Spanish, and Kawarith (Alharbi and Lee, 2021) collects Arabic crisis tweets. Relatedly, Sánchez et al. (2023) study the cross-lingual transfer of classifiers trained on English crisis data to Spanish and Italian, and Vitiugin and Purohit (2024) detect and rank help requests posted in English, Spanish and Turkish during natural disasters.

Crisis NLP does, however, include generation, mainly in the form of summarization. The CrisisFACTS track (McCreadie and Buntain, 2023) recasts disaster response as the production of fact-based daily summaries from social media and news, and recent systems address it by combining retrieval with instruction-following LLMs (Seeberger and Riedhammer, 2024). A related line

works at the level of the individual emergency call, extracting the relevant information and presenting it to the call-taker (Otal et al., 2024). In both cases the output supports the response effort and is derived from text that already exists. Warning messages, on the other hand, are directly addressed to the population, and they are not produced by recapping existing textual reports.

How to reach speakers of different languages during an emergency has been studied in translation research under the name of crisis translation (OBrien and Federici, 2019), which looks at language needs in disaster settings and at how translation can be included in emergency planning. In NLP, the same problem has been approached as machine translation. Staiano et al. (2025) evaluate general-purpose LLM and NMT systems on Italian civil protection texts, while Castaldo et al. (2026) fine-tune a small model for crisis-domain translation to produce simplified English output, proposed as a "lingua franca" when full multilingual coverage is not feasible. This transfer is not uniformly reliable: Ticona and Anastasopoulos (2026) evaluate MT systems and LLMs on crisis-domain data in 30 languages and report substantial quality degradation, particularly for low-resource languages and in the direction from English into other languages.

Finally, a different line of work addresses the production of the message itself. The setting differs from the translation work described above, which starts from existing crisis text and moves it into another language. *CrisiText* (Gonella et al., 2026a) pairs chronologically ordered crisis events with English warning messages written according to crisis guidelines, and has been used to fine-tune LLMs for message generation and post-editing. Other work addresses different communication settings: Hong et al. (2025) generate replies to individual social media posts in which affected people express their needs. Guidance can also be grounded in the spatial layout of the affected area: Gonella et al. (2026b) benchmark vision-language models on the generation of narrowcast guidance, i.e. guidance tailored to the individual civilian, in a simulated evacuation environment. These works produce messages in English, leaving the task in other languages unexplored.

3 Multilingual Dataset

Training an LLM to produce warning messages requires event-message data pairs. In order to address the task in a multilingual setting, we built *CrisiLangs* by extending the English *CrisiText* data. Specifically, we used a manually curated subset of the original dataset and had its warning messages translated into Italian, Bulgarian, German, and Greek by four expert native speakers, one for each language. The four languages were selected to ensure diversity in writing systems and language families, including three scripts (Latin, Cyrillic and Greek) and four European language families (Romance, Slavic, Germanic and Hellenic). Figure 1 shows the workflow used to create the dataset.

Source Data. *CrisiText* (Gonella et al., 2026a) contains more than 100,000 event-message pairs, where each event is labeled with one or more crisis categories (e.g., attack, flood or tornado). The messages were synthetically generated with an LLM following expert guidelines on communicative tone (Sutton and Kuligowski, 2019) and the behavioral guidance of the corresponding crisis categories, extracted from the official FEMA website.[2] Events are also grouped into *scenarios*, in the form of chronological chains of events describing the unfolding of a single crisis, and each scenario is entirely contained in one of the original training, development, and test splits.

Selected Data. As part of the data quality assessment of *CrisiText*, two crisis communication experts reviewed a sample of 1,000 event-message pairs, balanced between human-caused and natural disasters. We built our multilingual extension on this expert-reviewed sample. The pairs were drawn from the original training, development, and test splits in an 80/10/10 proportion. Table 1 reports the distribution of message and event categories. Events can carry multiple labels: the table reports only the main category of each event, i.e. the first label listed for its scenario, and omits the remaining labels assigned to the same scenario. The sample is balanced by construction, with 500 human-caused and 500 natural events.

Multilingual Translation. The subsample was given to four native speakers, one per target language (details about them are reported in Ap-

[2] https://www.ready.gov/



Figure 2: Example of event and warning message from *CrisiLangs* in the five languages. The English event and message are the originals from *CrisiText*. In the other four languages the messages are human translations produced by native speakers, while the events are machine-translated.

Category	Scenarios	Events
Human-caused	**253**	**500**
explosion	105	201
fire	76	153
attack	72	146
Natural	**158**	**500**
tornado	33	111
hurricane	26	95
flood	21	59
winter weather	14	49
heat	17	48
thunderstorm	16	48
avalanche	10	35
earthquake	7	12
landslide	4	12
volcano	3	12
wildfire	4	10
tsunami	3	9
Total	**411**	**1,000**

Table 1: Distribution of the event and message main categories over the 1,000 selected elements, grouped into human-caused and natural crises.

All	EN	IT	DE	EL	BG
306.9	268.6	316.4	324.1	331.1	294.4

Table 2: Mean warning message length in characters per language in *CrisiLangs*.

pendix C). Each translator received the original description of the event (both in English and automatically translated into their own language) and its associated warning message in English. The FEMA guidelines used to generate the warning messages in *CrisiText* were also automatically translated.[3] Translators were asked to render the English message in their own language and to adapt it where necessary so that it would sound more natural and well formed.[4] In both the messages and the guidelines we replaced the US emergency number "9-1-1" with the European one, "112", since the target audience is European. This localized version of the guidelines is also the one used at training and generation time (Section 4).

Human translation was limited to the warning messages. This was a deliberate design choice: the message is what the model has to produce and what the human evaluation judges, whereas the event description and the guidelines only enter as input. Translation noise on the input side is therefore less critical, and it reflects a realistic deployment setting, where the input is processed automat-

[3]The translation was done with GOOGLETRANSLATE API.

[4]Translators were allowed to use machine translation tools as support, provided that they revised the output.

ically. Translators could rely on the English source in case of doubt. In total, we obtained 5,000 event-message pairs (1,000 per language, including English), from 411 unique scenarios. Figure 2 shows one such pair in all five languages, with the machine-translated event alongside the human-translated message. These parallel versions differ slightly in length, with per-language mean lengths reported in Table 2.

4 Experimental Design

We used the dataset to fine-tune a model in two configurations and to establish a zero-shot baseline for comparison. In order to assess which settings produce the most appropriate warning messages and how generation quality changes across the different languages, the generations were evaluated with automatic metrics and with a human preference study. The aim is to give future work on the resource a benchmark to compare against.

Model and Training Data Construction. Following the original *CrisiText* work, we fine-tuned a single model, `Llama-3.1-8B-Instruct`, with LoRA (Hu et al., 2021), keeping the same hyperparameters. To allow comparison with it we also kept the original prompt template (Figure 3), in which the instructions are in English while the events description are in the target language. In a preliminary zero-shot check we observed that the model consistently produced the warning message in the language of the input, so we did not add any explicit indication of the output language to the template. In particular, each training instance contains an event description to be used as the basis for the warning message, plus the preceding events description to be used as context. The message is generated only for the last event of the sequence. Training was performed jointly across all five languages using a single multilingual model, rather than separate models for each language, with the aim of simplifying deployment in real-world settings.

Training Configurations. We trained the model in two configurations. In the *plain* setup, the user prompt contains only the event descriptions. On the other hand, in the +*guidelines* setup, the prompt additionally contains the translated FEMA guidelines of the crisis categories of the event. When an event belongs to more than one category, the corresponding guidelines are concatenated in the order in which the categories are listed. The comparison tests whether the guidelines have to be given explicitly at generation time, or whether fine-tuning on the data is enough for the model to infer them. Further details on the settings and on the hyperparameters are given in Appendix A.

USER

†{Based on the provided guidelines,} Create a warning message informing on the current happening, providing a suggestion, for the last line in the following chain of events (be short, max 300 characters). No other output other than the message.

†Guidelines: [GUIDELINES]

Chain of events: [EVENTS]

Figure 3: Prompt example. The instruction is always in English, while `[EVENTS]` is replaced by the chain of events of the instance, in its language, with the target event as its last line. The segments marked with † appear only in the +*guidelines* configuration, where `[GUIDELINES]` is replaced by the translated FEMA guidelines of the crisis categories of the event.

Generation and Automatic Metrics. After training, we generated warning messages for the 100 test events in all five languages, in both configurations and at five decoding temperatures (1.0, 0.8, 0.6, 0.4 and 0.2), to assess the trade-off between output variety and conformity to the crisis guidelines. As a baseline, we also ran the same generations with the off-the-shelf model in a zero-shot setting, using the same prompt as in training. In order to measure the effect of fine-tuning and of the decoding temperature, all generations were evaluated against the reference messages with two overlap metrics, ROUGE-L and BLEU, and with BERTScore, which is a semantic metric based on contextual embeddings. These scores were then used to select the data included in the human study. More information on the metrics is given in Appendix B.

Human Preference Study. Since automatic metrics are only a proxy for the quality of a warning message, we complemented them with a human preference study. On the basis of the automatic evaluation we restricted the study to the three best-performing decoding temperatures. For each of the two training configurations, one native speaker per language was presented with 50 test event-message pairs in their own language, each accompanied by the three corresponding gen-

			All			English			Italian			German			Greek			Bulgarian		
		T	R-L	B	BS	R-L	B	BS	R-L	B	BS	R-L	B	BS	R-L	B	BS	R-L	B	BS
Zero-shot	*plain*	1.0	.168	.037	.878	.209	.072	.890	.175	.041	.882	.185	.038	.884	.130	.019	.865	.143	.016	.871
		0.8	.184	.043	.884	.232	.083	.893	.196	.045	.886	.202	.047	.888	.145	.021	.874	.148	.021	.878
		0.6	.201	.048	.888	.234	.084	**.895**	.215	.049	.891	.218	.055	.892	.176	.032	.883	.166	.021	.883
		0.4	.205	.051	.890	.232	.083	.894	.214	.053	.890	.226	.050	.894	.174	.036	.887	.181	.035	.887
		0.2	**.211**	**.056**	**.892**	**.240**	**.090**	.894	**.221**	**.056**	**.892**	**.233**	**.059**	**.896**	**.182**	**.039**	**.888**	**.182**	**.035**	**.889**
	+guid.	1.0	.187	.049	.881	.231	.080	.892	.175	.047	.881	.211	.056	.884	.146	.032	.872	.170	.031	.878
		0.8	.196	.054	.885	.226	.068	.890	.191	.056	.886	.236	.072	.892	.154	.040	.878	.171	.031	.882
		0.6	.207	.056	.889	.247	.088	.895	.196	.051	.888	.229	.066	.890	.174	.035	.883	.191	.038	.888
		0.4	.218	.067	.890	.248	.094	.894	.213	.067	.890	.247	.076	.893	.178	**.048**	**.885**	**.202**	**.051**	**.890**
		0.2	**.220**	**.069**	**.891**	**.259**	**.104**	**.896**	**.216**	**.070**	**.891**	**.247**	**.077**	**.894**	**.179**	.044	.884	.198	.050	**.890**
Fine-tuned	*plain*	1.0	.259	.111	.902	.311	.159	.915	.245	.106	.901	.278	.110	.903	.236	.089	.893	.224	.079	.897
		0.8	.284	.134	.907	.350	.189	.920	.269	.125	.906	.308	.137	.909	.256	.111	.900	.235	.093	.902
		0.6	.307	.158	.912	.366	.211	.922	.297	.145	.912	.328	.161	.913	.282	.138	.905	.258	.122	.908
		0.4	.320	.169	.914	.387	.226	.924	.308	.159	.912	.340	.176	.915	.291	.136	.910	.271	.123	.910
		0.2	**.331**	**.177**	**.916**	**.389**	**.227**	**.925**	**.331**	**.171**	**.915**	**.345**	**.177**	**.916**	**.306**	**.150**	**.911**	**.281**	**.138**	**.912**
	+guid.	1.0	.258	.116	.901	.342	.190	.917	.240	.101	.901	.269	.112	.900	.215	.081	.892	.220	.082	.896
		0.8	.287	.135	.907	.370	.214	.921	.258	.114	.905	.303	.132	.907	.260	.121	.901	.243	.089	.902
		0.6	.308	.154	.911	.378	.221	.922	.299	.145	.910	.329	.163	.913	.286	.136	.907	.247	.099	.905
		0.4	.322	.165	**.914**	**.396**	**.233**	**.924**	.297	.149	.911	**.341**	**.172**	**.915**	.299	.144	.909	.277	.120	.910
		0.2	**.330**	**.171**	**.914**	.393	.232	.922	**.319**	**.162**	**.913**	**.341**	.167	.914	**.318**	**.159**	**.910**	**.283**	**.128**	**.911**

Table 3: ROUGE-L F1 (R-L), BLEU (B) and BERTScore F1 (BS) on the test split, per configuration, temperature and language. Bold marks the best temperature within each block. Zero-shot uses the un-finetuned `Llama-3.1-8B-Instruct` with identical configuration.

erations. The two configurations were annotated separately, and the three candidates were shown anonymized, without any indication of the temperature that distinguished them. Annotators were asked to choose the message they considered grammatically better and more compliant with the task, and could leave free-text comments to motivate the choice or report problems the selection alone could not express. At the end of the annotation, we also asked which of the two configurations they preferred overall.

5 Results

This section reports what the experiments described in Section 4 indicate about the resource. The automatic evaluation serves two purposes: it establishes whether fine-tuning on the resource is necessary, and it narrows the set of decoding temperatures presented to the annotators. The human preference study then addresses what the metrics cannot capture, namely whether the generations are appropriate in each language and which of the two training configurations should be preferred.

5.1 Automatic Evaluation

Table 3 reports ROUGE-L, BLEU and BERTScore on the test split for each language and decoding temperature, in the two training configurations and in the corresponding baselines. The comparison is intended as intra-language, across temperatures and configurations. All three metrics are sensitive to language-specific factors such as tokenization and morphology, so inter-language differences do not indicate a quality ranking.

The fine-tuned models score higher than the baseline on all three metrics in every language, temperature and prompt configuration. ROUGE-L and BLEU reward two aspects of a generation at once, its length and its wording. BLEU keeps them separate, as the product of the brevity penalty and the n-gram precision term. As Table 4 shows, at $T = 0.2$ the fine-tuned models match the length of the human references, while the baseline with the plain prompt produces little more than half of the 300 characters. The table also reports BLEU without the brevity penalty: the n-gram precision term rises from .114 to .177, so fine-tuning also improves the wording. Adding the guidelines to the baseline prompt recovers part of the length gap, but the gain is small compared to fine-tuning and the n-gram precision term does not improve (.114 to .104). BERTScore shows the same pattern: at T=0.2 fine-tuning raises it from .892 to .916, while adding the guidelines to the baseline prompt leaves it virtually unchanged (.891). Therefore, these results indicate that fine-tuning on this data contributes substantially to both the length and the wording of the generations, and we restrict the rest

of the evaluation to the fine-tuned models.

	Length	BLEU w/o BP
Gold	304	–
ZS, plain	173	.114
ZS, +guid.	205	.104
FT, plain	295	.177
FT, +guid.	299	.171

Table 4: Mean generation length in characters and BLEU without the brevity penalty (BP), at T=0.2, over all five languages, for the zero-shot (ZS) and fine-tuned (FT) models. Per-language values are in Appendix B.

Across all setups, zero-shot and fine-tuned alike, scores rise as temperature decreases. This pattern reflects the fact that lower temperatures sharpen the probability around the most likely sequence, yielding wording that is less likely to include rare or unexpected choices, and thus closer to the reference text (which these metrics reward by construction). Whether such messages are also better is assessed in the human study (Section 5.2). When results are pooled across languages, both ROUGE-L and BLEU increase in a strictly monotonic way from temperature 1.0 down to 0.2. BERTScore does the same, except for a tie between 0.4 and 0.2 in the fine-tuned +guidelines configuration (.914). At the language level, however, the trend holds but is not always monotonic: in the +guidelines configuration, for example, ROUGE-L for English and BLEU for German are marginally lower at 0.2 than at 0.4. In fine-tuned models these deviations are less relevant, never exceeding .005.

The two training configurations are close to each other. In the 0.6-0.2 range, ROUGE-L and BLEU favor the +guidelines configuration for English and Greek, while the plain configuration is better on Italian. On German the two are close, with the plain configuration slightly ahead at temperature 0.2. Bulgarian is the only language where the two overlap metrics disagree: at the two lowest temperatures the plain configuration is ahead on BLEU and the +guidelines one on ROUGE-L. BERTScore separates the two configurations even less, with differences of at most .003 in every language in this range, and does not reproduce the advantage of the guidelines on English and Greek. Considering the aggregated metrics over all languages, the two configurations are virtually identical. No configuration is consistently better, so the automatic metrics do not settle which configuration to prefer, motivating the human evaluation described in Section 5.2.

Based on the automatic scores, we focused on temperatures 0.6, 0.4 and 0.2 for the human evaluation.

	plain				*+guidelines*			
	0.6	0.4	0.2	N	0.6	0.4	0.2	N
English	8	15	27	50	12	8	30	50
Italian	6	15	29	50	7	15	27	49
German	12	13	24	49	7	17	26	50
Greek	11	2	37	50	4	22	24	50
Bulgarian	4	17	29	50	3	9	25	37

Table 5: Preference counts per configuration and language. N is the number of annotated events out of 50.

5.2 Human Preference Study

The automatic scores rank the temperatures consistently, but they do not indicate which generation a reader would prefer, and they do not separate the two training configurations. We therefore asked one native speaker per language, with expertise in crisis communication, to compare the three generations and to select the one they considered most natural, grammatical and consistent with the task. The annotation covered 50 test events, with the candidates generated at temperatures 0.6, 0.4 and 0.2, and was repeated for both training configurations. When no candidate was acceptable, the annotator could leave the item unannotated.

Temperature. Table 5 shows that temperature 0.2 receives the most preferences in all five languages and in both training configurations, although the trend is not uniformly evident in all cases (e.g., for the +guidelines model). In Bulgarian, the generations using the guidelines led to the rejection of all three candidates in 13 items because of errors in the generated text. In the plain configuration a choice was always made, although the comments indicate that some candidates were still flawed. Lastly, Greek in the +guidelines configuration shows the smallest margin in the table, with only two preferences separating temperature 0.2 and 0.4, so the annotation does not indicate a clear preference between them.

Training Configuration. At the end of the task, each annotator also indicated which of the two models they preferred overall. All chose the plain model except the Greek annotator, who preferred the +guidelines one. The Italian annotator reported the plain model to have a better use of ter-

minology and more specific warnings about the event, and the German annotator a better quality of the German text and slightly more accurate warning messages. Similarly, the English annotator motivated the preference with the accuracy of the messages, although reporting a narrower difference between the two models. The Bulgarian annotator's justification was negative, referring to the amount of non-compliant content produced by the +guidelines model. On the other hand, the Greek annotator described the +guidelines generations as clearer, better structured and more effective in conveying urgency. ROUGE-L and BLEU favor +guidelines in the 0.6-0.2 range only for Greek and English, matching the Greek annotator but not the English one, while BERTScore does not separate the two configurations in either language.

Qualitative Feedback. In addition to the preference judgment, annotators could leave free-text comments. These were optional and used to different extents, so they are reported as qualitative evidence rather than as a systematic annotation. They point to a difference between the two configurations that the automatic metrics do not capture. The Greek, Italian and English annotators motivated their choices based on the wording of the warning and the appropriateness of the recommended actions. In Greek these reasons differ between the two configurations: the plain model was chosen for its simpler wording and calmer tone, the +guidelines model for the specificity of its information and of the recommended actions. In Bulgarian and German the comments instead report defects in the generations, most frequently grammatical errors and unfinished text. These are concentrated on the +guidelines model, consistent with the overall preference for the plain configuration reported above. None of these problems is visible in the automatic scores, and this is where the human study contributes most.

6 Discussion

Our experiments show that fine-tuning on *CrisiLangs* yields a single model that produces warning messages in all five languages, above the baseline in the automatic evaluation, but the human study suggests that quality is not uniform across languages. For English, Italian, German and Greek, the annotators expressed a preference for almost every item, and their comments mostly point to specific flaws rather than to unusable generations. By contrast, with the Bulgarian plain model a choice could always be made, even when candidates were non-compliant or contained errors. With the +guidelines model, 13 items were left unannotated because none of the three candidates was acceptable. The resource therefore supports warning generation in all five languages, with the Bulgarian +guidelines output being less reliable, mostly for limitations of the LLM.

Across the five languages we evaluated, low decoding temperatures are consistently preferred. The automatic metrics increase as the temperature decreases, as they favor wording closer to the reference by construction, so the more informative evidence comes from the human study: among the three temperatures compared, 0.2 receives the most preferences in all languages and in both training configurations (Table 5). Since annotators were asked to judge grammaticality and compliance with the task, this indicates that they found lower-temperature messages better on these criteria. The pattern holds in both the plain and the +guidelines configuration, so it does not depend on having the guidelines in the prompt. For practical use of this resource, low temperatures appear to be the safer choice.

The effect of the guidelines in the prompt is less uniform. Four of the five annotators preferred the plain model overall, citing better wording and more relevant content, and only the Greek annotator preferred the +guidelines one, for its clarity and structure. These preferences, together with the automatic metrics (where neither configuration is consistently ahead), suggest that in-prompt guidelines are not consistently beneficial. One possible explanation is that fine-tuning on the gold messages already induces much of the intended compliance, making the guidelines largely redundant; moreover, adding a long block of instructions increases prompt length and can dilute attention to the event-specific details, which may ultimately hurt generation quality.

A final observation concerns the relation between the two evaluations. The automatic metrics rank the temperatures consistently, but none of them, BERTScore included, anticipates the Bulgarian result: in Table 3 the +guidelines scores for Bulgarian are close to the plain ones at every temperature, yet the annotator found none of the three candidates acceptable in 13 of the 50 items in that configuration and in none of the plain ones. Human validation therefore remains necessary when

crisis warning generation is extended to new languages.

7 Conclusion

We presented *CrisiLangs*, a multilingual extension of *CrisiText* to Italian, Bulgarian, German, and Greek. The resource contains 1,000 events from 411 scenarios, with human-translated warning messages in four languages alongside the original English ones, for a total of 5,000 event-message pairs.

To benchmark this resource we fine-tuned `Llama-3.1-8B-Instruct` on the five languages and compared it with a zero-shot baseline. We evaluated the generations in the five languages both with automatic metrics and with a human preference study. We observed that, compared to the baseline, fine-tuning improved ROUGE-L, BLEU and BERTScore in every language and prompt configuration (with or without guidelines). Lower decoding temperatures lead to higher automatic scores, which can be expected from reference-based metrics, this is then confirmed by the annotators where the temperature 0.2 received the most preferences in all five languages and in both configurations.

The human evaluation suggests that providing the emergency guidelines to the model during generation does not reliably improve the output: four of the five annotators preferred the plain configuration overall, and only the Greek annotator preferred the configuration with guidelines. In our evaluation, the automatic metrics did not reveal the problems found by the annotators: the Bulgarian +guidelines generations score close to the plain ones, yet in 13 of the 50 items none of the candidates was acceptable. This points to the importance of expert native-speaker assessment when benchmarking warning message generation.

Limitations

In the current setup the model receives the event in the target language and generates the warning message in the same language, so automatic translation is used only on the input side. The resource also supports feeding the model the English event directly and generating the message in the target language in a single pass, removing automatic translation from the pipeline entirely, but we do not evaluate this setting, as it would require a further round of automatic and human evaluation.

A second limitation is that we focus on fine-tuning a single multilingual model. Complementary comparisons (e.g., comparisons with language-specific pretrained LLMs, particularly for Greek and Bulgarian, which use non-Latin scripts, and with a model fine-tuned exclusively on English data to assess the added value of target-language supervision) are natural next steps that we leave to future work. Translation and preference annotation were carried out by a single native speaker per language, reflecting the specialized expertise required for crisis communication. Future work with additional annotators would enable measuring inter-annotator agreement; nonetheless, the preference for temperature 0.2 is shared by all five annotators.

Finally, the resource provides 1,000 expert-reviewed event-message pairs per language; by comparison, *CrisiText* contains more than 100,000 English pairs, as our extension focuses on the expert-reviewed subset. Human translation was also limited to the warning messages: the messages are what the model produces and what the annotators judge, whereas the events and guidelines only enter as input. Translation noise on the input side therefore remains in the data.

References

Firoj Alam, Hassan Sajjad, Muhammad Imran, and Ferda Ofli. 2021. Crisisbench: Benchmarking crisis-related social media datasets for humanitarian information processing. *Proceedings of the International AAAI Conference on Web and Social Media*, 15(1):923–932.

Alaa Alharbi and Mark Lee. 2021. Kawarith: an Arabic Twitter corpus for crisis events. In *Proceedings of the Sixth Arabic Natural Language Processing Workshop*, pages 42–52, Kyiv, Ukraine (Virtual). Association for Computational Linguistics.

Antonio Castaldo, Maria Carmen Staiano, Johanna Monti, Sheila Castilho, and Francesca Chiusaroli. 2026. Translating under pressure: Domain-aware llms for crisis communication. *Preprint*, arXiv:2604.26597.

William D. Lewis, Haotian Zhu, Keaton Strawn, and Fei Xia. 2025. Tapping into social media in crisis: A survey. In *Proceedings of the Fourth Workshop on NLP for Positive Impact (NLP4PI)*, pages 306–331, Vienna, Austria. Association for Computational Linguistics.

Selim Fekih, Nicolo' Tamagnone, Benjamin Minixhofer, Ranjan Shrestha, Ximena Contla, Ewan Oglethorpe, and Navid Rekabsaz. 2022. HumSet:

Dataset of multilingual information extraction and classification for humanitarian crises response. In *Findings of the Association for Computational Linguistics: EMNLP 2022*, pages 4379–4389, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

Samsara Foubert, Minjung Park, Kanad Pardeshi, Thomas Manzini, Robert McDaniel, David Merrick, Robin Murphy, Aarti Singh, and Hoda Heidari. 2026. Investigating the role of ai in emergency management: Use cases, challenges, and opportunities. In *Proceedings of the 2026 ACM Conference on Fairness, Accountability, and Transparency*, FAccT '26, page 20552091, New York, NY, USA. Association for Computing Machinery.

Giacomo Gonella, Gian Maria Campedelli, Stefano Menini, and Marco Guerini. 2026a. CrisiText: A dataset of warning messages for LLM training in emergency communication. In *Findings of the Association for Computational Linguistics: EACL 2026*, pages 6657–6677, Rabat, Morocco. Association for Computational Linguistics.

Giacomo Gonella, Stefano Menini, and Marco Guerini. 2026b. Guide me out: A framework to benchmark vlm operators communication in crisis scenarios. *Preprint*, arXiv:2606.09428.

Lingzi Hong, Xiaoying Song, Anirban Saha Anik, and Vanessa Frias-Martinez. 2025. Dynamic fusion of large language models for crisis communication. *Proceedings of the International ISCRAM Conference*, 22.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2021. Lora: Low-rank adaptation of large language models. *Preprint*, arXiv:2106.09685.

Muhammad Imran, Carlos Castillo, Fernando Diaz, and Sarah Vieweg. 2015. Processing social media messages in mass emergency: A survey. *ACM computing surveys (CSUR)*, 47(4):1–38.

Muhammad Imran, Prasenjit Mitra, and Carlos Castillo. 2016. Twitter as a lifeline: Human-annotated Twitter corpora for NLP of crisis-related messages. In *Proceedings of the Tenth International Conference on Language Resources and Evaluation (LREC'16)*, pages 1638–1643, Portorož, Slovenia. European Language Resources Association (ELRA).

Junhua Liu, Trisha Singhal, Lucienne T.M. Blessing, Kristin L. Wood, and Kwan Hui Lim. 2021. Crisisbert: A robust transformer for crisis classification and contextual crisis embedding. In *Proceedings of the 32nd ACM Conference on Hypertext and Social Media*, HT '21, page 133141, New York, NY, USA. Association for Computing Machinery.

Richard McCreadie and Cody Buntain. 2023. Crisisfacts: building and evaluating crisis timelines. *Proceedings of the 20th ISCRAM Conference*.

Shalini Misra, Patrick Roberts, and Matthew Rhodes. 2020. Information overload, stress, and emergency managerial thinking. *International Journal of Disaster Risk Reduction*, 51:101762.

Alexandra Olteanu, Carlos Castillo, Fernando Diaz, and Sarah Vieweg. 2014. Crisislex: A lexicon for collecting and filtering microblogged communications in crises. In *Proceedings of the international AAAI conference on web and social media*, volume 8, pages 376–385.

Hakan T. Otal, Eric Stern, and M. Abdullah Canbaz. 2024. Llm-assisted crisis management: Building advanced llm platforms for effective emergency response and public collaboration. In *2024 IEEE Conference on Artificial Intelligence (CAI)*, pages 851–859.

Sharon OBrien and Federico Marco Federici. 2019. Crisis translation: considering language needs in multilingual disaster settings. *Disaster Prevention and Management*, 29(2):129–143.

Cinthia Sánchez, Hernan Sarmiento, Andres Abeliuk, Jorge Pérez, and Barbara Poblete. 2023. Cross-lingual and cross-domain crisis classification for low-resource scenarios. In *Proceedings of the international AAAI conference on web and social media*, volume 17, pages 754–765.

Philipp Seeberger and Korbinian Riedhammer. 2024. Multi-query focused disaster summarization via instruction-based prompting. *arXiv preprint arXiv:2402.09008*.

Maria Carmen Staiano, Lifeng Han, Johanna Monti, and Francesca Chiusaroli. 2025. ITALERT: Assessing the quality of LLMs and NMT in translating Italian emergency response text. In *Proceedings of Machine Translation Summit XX: Volume 1*, pages 566–577, Geneva, Switzerland. European Association for Machine Translation.

Jeannette Sutton and Erica D. Kuligowski. 2019. Alerts and warnings on short messaging channels: Guidance from an expert panel process. *Natural Hazards Review*, 20(2).

Belu Ticona and Antonios Anastasopoulos. 2026. Llm-powered automatic translation and urgency in crisis scenarios. *Proceedings of the International ISCRAM Conference*, 23.

Fedor Vitiugin and Hemant Purohit. 2024. Multilingual serviceability model for detecting and ranking help requests on social media during disasters. In *Proceedings of the International AAAI Conference on Web and Social Media*, volume 18, pages 1571–1584.

A Hyperparameters and Generation Settings

LoRA Adapter Configuration. We fine-tuned `meta-llama/Llama-3.1-8B-Instruct` with a `peft` LoRA adapter: rank 16, alpha 16, dropout 0, no bias adaptation, task type `CAUSAL_LM`. The adapter targets `q_proj`, `k_proj`, `v_proj`, `o_proj`, `gate_proj`, `up_proj` and `down_proj`. The base model was loaded in `bfloat16` without quantization, and the adapter was merged back into the base weights before generation.

SFT. Training used `trl`'s `SFTTrainer`. Sequences were capped at 1024 tokens; the learning rate was $3e{-}4$ with a cosine schedule, weight decay 0.01 and warmup ratio 0.03. We used a batch size of 2 for training and 4 for evaluation, with gradients accumulated over 4 steps, for an effective batch size of 8. We ran for up to 10 epochs, evaluating and checkpointing every 50 steps with early stopping patience 5, and kept the checkpoint with the lowest validation loss. Data were shuffled with seed 42 and the trainer ran with seed 0. The two configurations differ only in the prompt: PLAIN receives the instruction and the chain of events, +GUIDELINES additionally receives the localized guideline blocks. Both were trained with the same hyperparameters on the same 4,000 training examples.

Chat Formatting. Padding used Llama-3.1's `<|finetune_right_pad_id|>` on the right, and turns were formatted with the Llama-3.1 chat template.

Llama Generation. Decoding used sampling with a top-p of 1 and a cap of 128 new tokens, sufficient for a warning message. Each test prompt was decoded once per temperature (1, 0.8, 0.6, 0.4, 0.2), giving 2,500 generations per model configuration (100 test records $\times$ 5 languages $\times$ 5 temperatures).

Zero-shot Baseline. The zero-shot baseline was the same `meta-llama/Llama-3.1-8B-Instruct` without the LoRA adapter, and was run over the same test split with the same prompts, the same five temperatures and the same decoding arguments and post-processing.

Compute. All fine-tuning and generation runs were performed on a single NVIDIA A40 GPU.

B Automatic Metrics

Evaluation Packages. For automatic metrics we used Hugging Face's `evaluate` library (`evaluate` 0.4.6, `rouge-score` 0.1.2, `nltk` 3.10.2) for ROUGE, `sacrebleu` 2.6.0 for BLEU, and `bert-score` 0.3.13 (`transformers` 4.57.6) for BERTScore, all computed per language, configuration and temperature.

ROUGE-L is the F1 of the longest common subsequence, computed over the message as a single token sequence, and aggregated as the median of 1,000 bootstrap resamples. `rouge_score`'s default tokenizer lowercases and keeps only Latin letters and digits, discarding all Cyrillic and Greek characters: with this configuration only about 2% of Bulgarian and 5% of Greek reference tokens survive, and what remains is digits and Latin-script names. We therefore passed a Unicode-aware tokenizer, so that all five languages are scored on their own scripts.

BLEU was computed at corpus level with SacreBLEU's default settings[5], including the script-agnostic `13a` tokenizer. Scores were divided by 100 to match the 0–1 scale of the other metrics.

BERTScore was computed with `xlm-roberta-large` for all five languages, without idf weighting and without baseline rescaling, as no rescaling baseline is available for Bulgarian and Greek. Each reported score is the mean of the per-item F1 scores. Without rescaling, all scores in Table 3 fall between .865 and .925, so BERTScore differences are small in absolute terms and should only be compared within its own columns.

All reported scores were computed on CPU directly from the released generation files.

Per-Language Metrics. Table 6 reports the per-language values behind the aggregated numbers of Table 4. Both components move in the same direction in all five languages: the fine-tuned models are closer to the reference length than the corresponding baseline, and the n-gram precision term is higher in every language and in both prompt configurations.

[5] Signature: `nrefs:1|case:mixed|eff:no|tok:13a|smooth:exp|version:2.6.0`

	All	EN	IT	BG	DE	EL
mean length (characters)						
Gold	304	267	315	289	317	330
ZS, plain	173	188	163	163	182	168
ZS, +guid.	205	204	214	192	221	195
FT, plain	295	269	297	272	326	309
FT, +guid.	299	270	312	284	317	314
BLEU without brevity penalty						
ZS, plain	.114	.137	.129	.076	.117	.101
ZS, +guid.	.104	.139	.102	.080	.112	.080
FT, plain	.177	.227	.184	.138	.177	.156
FT, +guid.	.171	.232	.162	.128	.167	.162

Table 6: Per-language mean generation length in characters and BLEU without the brevity penalty, at $T{=}0.2$, for the zero-shot (ZS) and fine-tuned (FT) models with the plain and +guidelines (+guid.) prompts. As in Table 3, the comparison is intra-language. Languages are English (EN), Italian (IT), Bulgarian (BG), German (DE) and Greek (EL).

C Human Annotations

The annotators were members of organizations engaged in crisis management, selected if native speakers in the target language and according to their professional experience. For the translation and annotation work, annotators were compensated fairly by their respective organizations in compliance with applicable national laws.

For each language and each of the two model configurations, annotators compared the outputs of the three best-scoring temperatures (0.6, 0.4, 0.2) on 50 test events. The three outputs were presented as blind candidate A/B/C, and annotators selected one candidate per event and could optionally leave a free-text comment.

Figure 4 reproduces verbatim the instructions given to the annotators for the translation and for the preference task.

TRANSLATION TASK

The task consists in creating alert messages in your language based on the English alert messages we provide. We ask you to translate the messages and, when necessary, adapt them to sound more natural and appropriate as alert messages in your language.

PREFERENCE TASK

Your task is to:

– For each row, select your preferred message using the dropdown menu, based on grammaticality and consistency with the task.

– At the top of each sheet, indicate which configuration (column) you preferred overall, and briefly explain why.

– Let us know which of the two models (sheets) you preferred overall, and why.

(Note: there is no need to correct the text of the messages.)

Figure 4: Instructions given to the annotators, reproduced verbatim. The translation instructions were provided together with the English source; the preference instructions accompanied one spreadsheet per training configuration.