ELARSpeech: A 30K-Hour Dataset Across 675 Underrepresented Languages for Long-Tail Multilingual Speech Technologies

Sangmin Lee[1], Yejin Jeon[2,3], David Ifeoluwa Adelani[2,3,4]

[1]Yonsei University, [2]McGill University, [3]Mila - Quebec AI Institute, [4]Canada CIFAR AI Chair

Correspondence: sangmin_lee@dsp.yonsei.ac.kr,david.adelani@mila.quebec

arXiv:2610.19388v1 [cs.CL] 14 Oct 2026

Abstract

Massively multilingual speech modeling has made remarkable progress in recent years, yet existing training resources and benchmarks still underrepresent much of the linguistic long tail. To address this gap, we introduce ELARSpeech, a large-scale multilingual speech resource comprising 30,202 hours of speech across 675 underrepresented languages, curated from the Endangered Languages Archive. Combining human-annotated and unlabeled recordings, the corpus spans diverse recording conditions, domains, and language families. Beyond corpus construction, our experiments show how ELARSpeech supports extending ASR and TTS capabilities to diverse underrepresented languages, with further benefits from pseudo-labeling unlabeled data. At the same time, our speech representation analysis reveals remaining limitations in transferring existing multilingual models to the linguistic long tail. Together, ELARSpeech provides both a resource and a testbed for extending multilingual speech technology further into the linguistic long tail. We publicly release the dataset, all trained ASR and TTS models, and the complete data construction pipeline to facilitate research on long-tail multilingual speech technologies.[1]

1 Introduction

Recent advances in multilingual speech modeling have dramatically expanded the linguistic coverage of speech technologies, enabling automatic speech recognition (Radford et al., 2023; Zhang et al., 2023; Pratap et al., 2024; Keren et al., 2025) and speech synthesis (Pratap et al., 2024; Zhu et al., 2026) across hundreds to thousands of languages. As modeling approaches become more sophisticated and models continue to scale successfully, continued progress toward the linguistic long tail requires multilingual speech resources to advance in both scale and diversity.

Meanwhile, parallel efforts have significantly increased the volume and language coverage of multilingual speech resources. Large-scale efforts such as MMS (Pratap et al., 2024) provide labeled speech for around 1,000 languages alongside unlabeled speech for around 3,000 languages, and recent web-crawled corpora (Chen et al., 2024) have further expanded the diversity of resources. While these advances have considerably expanded multilingual speech resources, three key challenges remain in supporting the linguistic long tail.

The first challenge is the gap between language coverage and accessibility. Publicly available corpora typically cover only a few hundred languages (Ardila et al., 2020; Valk and Alumäe, 2021; Conneau et al., 2023; Li et al., 2023), whereas datasets spanning thousands of languages (Pratap et al., 2024; Keren et al., 2025) often follow restrictive licenses or are not publicly released. Consequently, speech data for many long-tail languages remain difficult to access, limiting reproducible research further into the linguistic long tail.

The second challenge is constrained acoustic and domain diversity. Existing multilingual corpora draw heavily from a single source, such as parliamentary proceedings (Wang et al., 2021; Pfisterer et al., 2026; Asonitis et al., 2026) or Bible readings (Meyer et al., 2022; Chen et al., 2024; Guzmán et al., 2026), which naturally concentrate the resulting data around particular recording conditions, speaking styles, and domains. This leaves broader communicative settings, including spontaneous and conversational speech recorded in diverse real-world environments, less represented.

The third challenge is the lack of suitable evaluation resources for the linguistic long tail. Despite advances in multilingual speech foundation models trained on increasingly large and diverse language collections (Pratap et al., 2024; Chen et al., 2024; Keren et al., 2025), their effectiveness on underrepresented languages remains insufficiently char-

[1]https://github.com/sanghyang00/elarspeech/

acterized. Existing multilingual evaluations (Shi et al., 2023, 2024) tend to focus on higher-resource languages, making it challenging to systematically assess whether improvements in multilingual pretraining translate into stronger representations for long-tail languages (Boulianne, 2022; Le Ferrand et al., 2025; Li and Niehues, 2026).

To address these challenges, we introduce **ELARSpeech**, a massively multilingual speech corpus that extends speech resource coverage into the linguistic long tail. By drawing on field recordings from diverse languages, it enables training and evaluation of speech models on broader underrepresented languages. In terms of scale, **ELARSpeech comprises 30,202 hours across 675 underrepresented languages** and language varieties (hereafter, languages), making it one of the largest publicly available speech resources for underrepresented languages. This includes 2,791 hours of labeled speech-text pairs across 443 languages and 27,412 hours of unlabeled speech across 665 languages.

In experiments, we investigate automatic speech recognition (ASR) and text-to-speech (TTS) adaptation, pseudo-labeled scaling, and representation analysis using ELARSpeech. Our ASR and TTS experiments demonstrate that ELARSpeech supports effective adaptation across diverse underrepresented languages, while pseudo-labeling further improves performance by leveraging unlabeled speech. Additionally, we evaluate existing speech self-supervised models (S3Ms) on ELARSpeech, showing that advances in conventional multilingual settings do not necessarily transfer to the linguistic long tail. These findings highlight the broader utility of ELARSpeech as a resource for advancing speech technologies in underrepresented languages and a foundation for evaluating speech models across the linguistic long tail.

Our contributions are summarized as follows:

- We introduce ELARSpeech, a massively multilingual speech corpus comprising 30,202 hours of curated speech from 675 languages, encompassing both human-labeled and unlabeled subsets.
- ELARSpeech substantially extends the long tail of open multilingual speech resources while preserving the linguistic, acoustic, and domain diversity of real-world field recordings.
- We demonstrate ELARSpeech's utility in extending ASR and TTS capabilities to underrepresented languages and uncover challenges in transferring existing S3Ms to the linguistic long tail.

Dataset	Labeled	Content	# Langs.	Size (H)
Closed-Source Datasets				
Google USM	×	Variety	568	12.1M
MMS-Unlab		Bible	2809	8K
Whisper	✓	Variety	98	680K
MMS-Lab		Bible	1107	45K
ALLASR		Variety	1690	121K
Open-Source Datasets				
MMS-Unlab v2	×	Bible	2778	838
Wikitongues		Conversation	700	70
JesusDramas		Bible	430	643
VoxLingua107		Variety	107	7K
WAXAL	△	Spontaneous	32	16K
YODAS v3		Variety	147	1.1M
FLEURS	✓	Wikipedia	102	1K
CommonVoice26		Wikipedia	290	14K
OpenBibleTTS		Bible	42	4K
WorldSpeech		Parliament	76	65K
Omnilingual ASR		Spontaneous	348	3K
Ours				
ELARSpeech	△	**Variety**	**675**	**30K**

Table 1: Comparison of existing low-resource multilingual speech datasets. "△" indicates the mixture across labeled, pseudo-labeled, and unlabeled data.

2 Related Work

2.1 Labeled Multilingual Speech Corpora

Labeled speech corpora have advanced considerably in both language coverage and scale. Early efforts such as CommonVoice (Ardila et al., 2020) and FLEURS (Conneau et al., 2023) provide read speech through crowdsourcing and controlled recordings, respectively, while the more recent WorldSpeech (Asonitis et al., 2026) scales transcribed speech to over 65K hours. For underrepresented languages, the Omnilingual ASR corpus (Keren et al., 2025) extends ASR data to 348 languages, while OpenBibleTTS (Guzmán et al., 2026) provides TTS data for 37 languages derived from Bible recordings. Nevertheless, corpora combining broad low-resource language coverage with diverse environments still remain scarce.

2.2 Unlabeled Multilingual Speech Corpora

Unlabeled speech resources enable collections at even broader linguistic scales; MMS (Pratap et al., 2024) collected Bible recordings across thousands of languages, though its underlying corpus is not publicly distributed. Subsequently, XEUS (Chen et al., 2024) further improves accessibility by reconstructing the unlabeled MMS collection while crawling additional long-tail speech resources from JesusDramas and WikiTongues. Despite their broad language coverage, these resources still leave room to further diversify recording domains and conditions with real-world speech data.



(a) Global language coverage of ELARSpeech in the Mollweide projection (Snyder, 1997).



(b) Domain distribution of ELARSpeech.



(c) Language family distribution of ELARSpeech.

Figure 1: Geographic, domain, and language family distributions of ELARSpeech.

3 ELARSpeech

3.1 Corpus Overview

Design Objectives. We design ELARSpeech with two main objectives: (1) extending resource coverage toward underrepresented languages that remain unsupported by existing multilingual speech models, and (2) broadening acoustic and domain diversity across diverse communicative settings and recording environments.

Data Source. To meet these objectives, we select the Endangered Languages Archive[2] (ELAR) as our primary data source. Specifically, ELAR is a digital archive dedicated to preserving endangered languages through multimodal language documentation, hosting diverse resources including audio and video recordings, transcriptions, and field notes contributed by language communities and field linguists. However, as ELAR is designed primarily for language documentation and preservation rather than as a training dataset, its recordings are largely uncurated, consisting of long-form audio with heterogeneous recording conditions and varying levels of transcription availability. We therefore develop a curation pipeline to transform these archival collections into a standardized speech dataset, as detailed in Sections 3.2 and 3.3. Following ELAR's licensing requirements, ELARSpeech is distributed under the CC BY-NC-SA 4.0 license, with details on the access permissions and licensing conditions of the underlying collections provided in Appendix A.

Corpus Characteristics. ELARSpeech comprises 30,202 hours of speech spanning 675 languages, with their geographic, language-family, and domain distributions summarized in Figure 1. The corpus exhibits broad linguistic diversity while dramatically extending speech resource coverage toward the long tail. Geographically, ELARSpeech covers languages distributed across diverse continents (Figure 1a), while its linguistic coverage spans 78 language families (Figure 1c). Among the

[2]https://www.elararchive.org/

Type	Split	# Lang.	# Utt. (M)	Duration (H)
Labeled	Train	409	3.09	2367.08
	Dev	233	0.17	132.77
	Test	233	0.35	266.14
	Multi	82	0.04	24.82
	Total	443	3.64	2790.81
Unlabeled	Train	592	19.14	26763.37
	Multi	200	0.41	648.29
	Total	665	19.56	27411.65
Overall		**675**	**23.20**	**30202.46**

Table 2: Dataset statistics of ELARSpeech. "Multi" denotes recordings categorized as multilingual.

675 languages, 259 are not supported by existing multilingual models trained on public (Chen et al., 2024) or non-public resources (Pratap et al., 2024; Keren et al., 2025), and 53 are not represented in the ISO 639-3 standard. Beyond linguistic coverage, ELARSpeech captures broad diversity in communicative domains and recording conditions inherited from archival language documentation. As shown in Figure 1b, the corpus encompasses conversations, narratives, interviews, elicitation sessions, and read speech, with considerable variation in recording environments. Detailed curation principles and additional corpus statistics are provided in Appendices B and C, respectively.

Corpus Composition. As summarized in Table 2, ELARSpeech consists of two subsets: (1) `ELARSpeech-L`, containing 2,791 hours of human-annotated speech across 443 languages, and (2) `ELARSpeech-U`, containing 27,412 hours of preprocessed unlabeled speech across 665 languages. For both subsets, recordings associated with multiple languages or those that cannot be reliably assigned to a single language are categorized as a separate multilingual split. Subsequently, ELARSpeech-L is split at the session level into training, development, and test sets with an 85/5/10 ratio, while languages with less than 5 minutes of development data are retained only in the training set. Two subsets are constructed through separate curation pipelines as described below.

3.2 Constructing Labeled Subset

When timestamped annotations are available, we segment recordings into utterances using timestamps and pair them with annotations to construct ELARSpeech-L through the following three stages.

Audio-Annotation Matching We first identify candidate audio-annotation pairs using filename matching. In most ELAR collections, transcription files are named after their corresponding audio recordings, occasionally with additional metadata such as the annotation date appended to the filename (e.g., `AUD001_20260101.eaf`). Accordingly, we first normalize all filenames to lowercase and then pair an audio file with a transcription file whenever the annotation filename contains the audio filename as an exact substring.

Valid Annotation Parsing. The most challenging step in constructing ELARSpeech-L is identifying valid transcription tiers, as annotation tier names are not standardized across ELAR collections and vary substantially across field linguists. For example, transcriptions may appear in a dedicated tier such as `tx` or in tiers named after individual speakers. We therefore develop a tier selection algorithm that scores candidate tiers based on common naming conventions. High-confidence tiers are directly accepted, medium-confidence tiers undergo manual verification, and low-confidence tiers are discarded. Detailed scoring criteria, thresholds, and the algorithm are provided in Appendix D.

Speech Segmentation. After selecting valid transcription tiers, we segment each recording using the timestamps from the accepted tiers to obtain time-aligned speech-text pairs. When annotation timestamps fall outside the bounds of the corresponding recording, we interpret this as potential audio-annotation misalignment and discard all segments derived from the affected recording.

3.3 Constructing Unlabeled Subset

For recordings without timestamped annotations, we preprocess the long-form audio through the following pipeline to construct ELARSpeech-U.

Overlapping Recording Exclusion. First of all, we exclude all source recordings included in ELARSpeech-L from the unlabeled pool to ensure that the two subsets remain disjoint, preventing potential data leakage in downstream experiments.

Quality-Based Pruning. Subsequently, we assess the acoustic quality of each recording using `Brouhaha` (Lavechin et al., 2023), which estimates the signal-to-noise ratio (SNR) and speech clarity (C50). Recordings with either SNR or C50 below 0 dB are discarded to remove severely degraded audio. Unlike previous in-the-wild dataset construction pipelines (He et al., 2024; Ma et al., 2024; Ogun et al., 2024) that apply speech enhancement, we use these quality estimates solely for filtering (Kwon et al., 2026) and retain the original audio without enhancement. This preserves the

original acoustic characteristics and avoids potential alterations to language-specific phonetic cues that may be crucial for underrepresented languages.

Speaker Diarization and Segmentation. We then apply the `pyannote-Precision-2` (Bredin, 2017; Bredin et al., 2020; Bredin, 2023) speaker diarization pipeline to partition each recording into speaker-homogeneous regions. Overlaps shorter than 0.5 seconds are retained, as they often reflect natural conversational backchannels rather than speaker interference. For segments exceeding 30 seconds, we apply `Silero VAD` (Team, 2024) and recursively split them at the longest silence until the duration constraint is satisfied. Detailed segmentation algorithms are provided in Appendix E.

3.4 Normalization and Filtering

For both subsets, we apply the following common normalization and filtering procedures to ensure consistency across the corpus.

Speech Normalization. First, all the speech segments are resampled to 24 kHz and encoded as 16-bit PCM FLAC format. We then apply RMS-based loudness normalization to -23 dBFS, with the gain constrained to $[-6, +6]$ dB to prevent excessive amplification or attenuation, followed by a peak ceiling of -1 dBFS to prevent clipping.

Metadata Normalization. Next, we standardize language metadata across ELAR collections, where naming conventions vary widely. Language labels are assigned based on collection-level metadata and subsequently normalized using the Ethnologue[3] language catalog, mapping aliases and naming variants to canonical language identifiers.

Data Filtering. Finally, we remove sign language recordings, which typically contain little or no spoken content, and discard samples with no detectable speech using `Silero VAD`.

4 Experiments

4.1 Long-Tail Speech Modeling

Experimental Setup. We first investigate whether ELARSpeech can extend the language coverage of existing speech models into the linguistic long tail. Both ASR and TTS are evaluated in monolingual and multilingual settings. Monolingual adaptation focuses on 30 pivot languages across resource levels for model comparisons (Appendix F), whereas the multilingual counterpart jointly trains a single model on all 233 languages represented across the train, development, and test splits. Models are initially trained on human-annotated ELARSpeech-L, with language-specific Whisper models additionally fine-tuned for all 233 languages to pseudo-label ELARSpeech-U. Pseudo-labeled scaling is then examined by progressively augmenting the training data with pseudo-labeled ELARSpeech-U.

Models. For ASR, we fine-tune two distinct modeling paradigms: Whisper-large-v3 (Radford et al., 2023), an encoder-decoder model, and OmniASR-CTC-v2 (Keren et al., 2025), a CTC-based (Graves et al., 2006) model. For TTS, we fine-tune OmniVoice (Zhu et al., 2026), a diffusion LLM-based (Yang et al., 2025; Gong et al., 2025) multilingual model. Following prior findings on the importance of data quality in low-resource TTS (Ogun et al., 2023), we restrict TTS training data to utterances with both SNR and C50 above 20 dB.

Evaluation Metrics. For ASR, we report character error rate (CER) against human transcriptions. For TTS, we evaluate intelligibility using CER from monolingual Whisper models and perceptual quality using mean opinion score (MOS), following the evaluation protocol of Pratap et al. (2024). For evaluation across all 233 languages, we report UTMOS (Baba et al., 2024) as an automatic proxy. Details of the MOS evaluation protocol are provided in Appendix G.

Training Details. All models are optimized using AdamW (Loshchilov and Hutter, 2017) until convergence, and the checkpoint achieving the best development-set performance is selected for final evaluation. Detailed training configurations and hyperparameter settings are provided in Appendix H.

4.2 Long-Tail Representation Analysis

Evaluation Protocol. We subsequently investigate how well existing multilingual S3Ms generalize to the linguistic long tail represented in ELARSpeech. Following the ML-SUPERB protocol (Shi et al., 2023), we evaluate these models under 10-minute and 1-hour supervision. We consider four tasks from the original benchmark: monolingual ASR, multilingual ASR, language identification (LID), and joint ASR with LID.

Models. We benchmark five multilingual S3Ms: XLS-R (Babu et al., 2021), w2v-BERT 2.0 (Barrault et al., 2023), MMS (Pratap et al., 2024), XEUS (Chen et al., 2024), and OmniASR-W2V (Keren et al., 2025), together with mel-filterbank features as a baseline.

[3] https://www.ethnologue.com/

Languages with ISO 639-3 Codes							*Languages without ISO 639-3 Codes*						
Language	**Code**	**Data (H)**	**Monolingual OmniASR 300M**	**Monolingual OmniASR 1B**	**Monolingual Whisper 1.5B**	**Multilingual Whisper 1.5B**	**Language**	**Code**	**Data (H)**	**Monolingual OmniASR 300M**	**Monolingual OmniASR 1B**	**Monolingual Whisper 1.5B**	**Multilingual Whisper 1.5B**
Masela, Central	mxz	136.8	28.90	**26.22**	28.39	28.31	Jitotoltec	–	18.6	15.16	15.25	**13.31**	20.84
Jul'hoansi	ktz	79.9	41.89	**41.71**	42.93	53.06	Zok	–	18.4	**35.04**	36.95	38.35	47.55
Yoloxóchitl Mixtec	xty	66.5	8.76	**8.58**	8.70	16.84	Sri Lankan Portuguese Creole	–	17.2	18.78	17.86	**16.89**	22.81
Tzeltal	tzh	69.9	22.92	**22.03**	23.20	30.05	Chiapas Zoque	–	12.7	16.44	**16.28**	17.11	23.37
Iñapari	inp	25.6	20.69	25.10	**11.37**	37.62	Caijia	–	10.0	31.05	32.03	**28.35**	37.53
Minyag, Eastern	emq	12.5	29.38	32.61	**19.84**	44.65	Muyu	–	6.3	23.76	23.72	**23.58**	27.08
Zenzontepec Chatino	czn	12.0	10.88	**10.57**	10.73	16.34	San Martín Duraznos Mixtec	–	6.2	39.64	**39.10**	47.29	50.58
Araona	aro	11.4	26.42	28.14	**23.43**	33.28	Gargarnaye	–	6.0	29.82	**29.39**	29.97	35.71
Abui	abz	11.0	35.64	35.62	**15.90**	38.20	Dzardzongke	–	5.4	15.73	**15.47**	15.70	19.63
Wardaman	wrr	10.9	32.40	33.56	**30.26**	38.56	Western Algerian Amazigh	–	5.2	25.73	24.77	**24.24**	30.58
Fungwa	ula	4.3	21.30	21.60	**20.65**	27.53	Awiakay	–	3.2	38.21	**37.30**	37.86	44.35
Notre	bly	4.2	29.32	31.26	**19.03**	44.26	Thiek	–	3.2	16.20	15.89	**15.69**	19.57
Ulwa	yla	4.2	17.98	18.41	**17.33**	21.08	Nese	–	2.2	**28.82**	30.30	30.50	33.47
Nheengatu	yrl	4.1	14.97	16.14	**12.42**	19.67	Kichwa de Chibuleo	–	2.2	11.21	10.42	**9.57**	10.56
Tonsawang	tnw	3.9	21.20	21.71	**20.78**	24.39	Jowshaqani	–	2.0	21.85	22.91	**20.98**	23.81
Macro Average			24.18	24.88	**20.33**	31.59	**Macro Average**			**24.50**	24.51	24.63	29.83
Win Rate			0.0%	33.3%	**66.7%**	0.0%	**Win Rate**			13.3%	33.3%	**53.3%**	0.0%

Table 3: Monolingual and multilingual ASR performance across 30 pivot languages of ELARSpeech. Languages are sorted by data duration within each category, and we report CER (%) for every result. Best and second-best results are shown in bold and underlined, respectively. Macro CER is averaged across languages, while win rate denotes the proportion of languages for which each model achieves the lowest CER.

Evaluation Metrics. Consistent with the original ML-SUPERB protocol, we report CER for ASR and accuracy for LID, with all aggregate results reported as macro averages across languages.

Training Details. We follow the original ML-SUPERB training recipe for all experiments.



Figure 2: ASR performance with increasing amounts of pseudo-labeled ELARSpeech-U.

5 Results

5.1 Automatic Speech Recognition

Monolingual Adaptation. Table 3 demonstrates that ELARSpeech-L enables ASR adaptation across diverse long-tail languages. In the monolingual setting, Whisper achieves the lowest CER for 18 of the 30 pivot languages, with a macro CER of 22.48. OmniASR-CTC is more competitive on languages without ISO 639-3 codes, as the 300M model attains a macro CER of 24.50, which is comparable to Whisper's 24.63 despite having substantially fewer parameters. However, Whisper remains ahead on ISO-coded languages (20.33 vs. 24.18). This trend is consistent with prior findings on the effectiveness of CTC-based models in low-resource settings (Kim et al., 2017; Moritz et al., 2019; Nayeem et al., 2025), suggesting that their advantages may extend further into the linguistic long tail. For OmniASR-CTC variants, scaling model size from 300M to 1B parameters improves performance on 16 of the 30 languages, but the gains are not consistent across languages. Specifically, all four languages with over 60 hours of training data benefit from the larger model, while results remain mixed for lower-resource languages.

Multilingual Knowledge Transfer. In contrast, massively multilingual adaptation shows signs of linguistic interference, as the multilingual model increases macro CER from 22.48 to 30.71, outperforming the monolingual counterpart on only one of the 30 pivot languages. This suggests that scaling the number of languages alone does not necessarily yield positive cross-lingual transfer, when supervision is limited and distributed across heterogeneous long-tail languages, such as diverse language families and recording environments.

Pseudo-Labeled Scaling. Figure 2 shows how pseudo-labeled ELARSpeech-U affects ASR performance across 233 languages. Specifically, we compute the confidence of each pseudo-labeled utterance as the mean confidence across its predicted tokens and apply language-specific quartile cutoffs to vary the amount of retained data. Across these settings, augmenting ELARSpeech-L with pseudo-labeled speech consistently improves transcription performance, achieving up to a 6.1% relative reduction in CER. However, retaining the entire pseudo-labeled corpus does not yield the best performance, with moderate confidence filtering leading to greater improvements. This suggests that effective scaling with unlabeled speech depends not only on quantity but also on pseudo-label quality.

Language (Code)	Test	CER ↓ Original	+L	+LU
CommonVoice 26 (CV26)				
Dawoodi (dmk)	ELAR	93.99	**22.68**	22.72
	CV26	**4.47**	4.81	5.58
Imbabura Highland Quichua (qvi)	ELAR	47.48	7.13	**6.71**
	CV26	1.28	1.12	**1.10**
Dargwa (dar)	ELAR	46.11	11.42	**11.00**
	CV26	1.63	1.69	**1.56**
INEL Corpus (INEL)				
Kalmyk-Oirat (xal)	ELAR	69.37	36.37	**35.21**
	INEL	29.85	27.09	**25.59**

Table 4: Cross-domain ASR performance on ELARSpeech and external test sets: CV26 and INEL.

Cross-Domain Robustness. To assess whether the benefits of ELARSpeech extend beyond its source archive, we conduct a cross-domain ASR evaluation on four languages from two external corpora (Ardila et al., 2020; Baranova, 2025). We compare models trained on the original external data, augmented with ELARSpeech-L, and further augmented with pseudo-labeled ELARSpeech-U, evaluating each on both domains. As shown in Table 4, external-only models perform notably worse on ELARSpeech, indicating a considerable domain mismatch between ELARSpeech and existing speech corpora. Moreover, augmenting the training data with ELARSpeech generally improves performance on the external domains, with gains observed in three of the four languages. Together, these results suggest that ELARSpeech broadens domain coverage without compromising performance on the original domains.

5.2 Text-to-Speech

Low-Resource Adaptation. Table 5 presents TTS results across the 14 pivot languages with at least 5 hours of training data after SNR/C50 filtering. Despite the limited amount of transcribed speech available for many languages, the models yield intelligible speech across a diverse set of low-resource languages, including those with only a few hours of data. In several cases, synthesized speech even achieves lower CER than the ground-truth recordings, providing further evidence of strong intelligibility under the ASR-based evaluation, although this may partly reflect the more standardized acoustic characteristics of synthesized speech relative to real-world field recordings. Overall, these results demonstrate that ELARSpeech can support TTS adaptation even for languages with extremely limited speech resources. Compared with the monolingual setting, the multilingual counterpart yields slightly higher CER overall but improves MOS for the majority of evaluated languages, suggesting a trade-off between intelligibility and perceptual quality.

Language	Code	Data (H)	Reference (Ground Truth) CER ↓	MOS ↑	Monolingual OmniVoice CER ↓	MOS ↑	Multilingual OmniVoice CER ↓	MOS ↑
Languages with ISO 639-3 Codes								
C. Masela	mxz	124.9	28.39	4.04	14.71	**3.88**	**12.87**	3.79
Y. Mixtec	xty	64.8	8.70	4.12	**4.75**	3.58	4.83	**3.82**
Tzeltal	tzh	19.8	23.20	3.76	**12.58**	3.33	12.93	**3.45**
Iñapari	inp	13.1	11.37	3.94	15.43	**3.60**	**14.97**	3.59
Araona	aro	7.7	23.43	3.75	**15.52**	3.04	16.65	**3.26**
E. Minyag	emq	6.0	19.84	3.88	**25.78**	3.54	27.66	**3.96**
Jul'hoansi	ktz	5.1	42.93	3.48	**41.60**	2.90	46.39	**2.94**
Z. Chatino	czn	5.1	10.73	4.06	**5.45**	3.46	5.94	**3.55**
Macro Average			21.07	3.88	**16.98**	3.42	17.78	**3.55**
Win Rate			–	–	**75.0%**	25.0%	25.0%	**75.0%**
Languages without ISO 639-3 Codes								
Jitotoltec	–	12.6	13.31	3.96	**9.17**	3.52	10.20	**3.79**
C. Zoque	–	10.1	17.11	4.13	**11.24**	3.59	11.79	**3.82**
Caijia	–	6.4	28.35	4.40	**26.98**	3.96	27.72	**4.17**
S. L. P. C.	–	6.0	16.89	4.02	**6.62**	**3.88**	7.00	3.69
Zok	–	5.2	38.35	3.69	**38.48**	3.27	38.71	**3.42**
Muyu	–	5.0	23.58	3.88	**14.80**	**3.19**	15.84	3.06
Macro Average			22.93	4.01	**17.88**	3.57	18.54	**3.66**
Win Rate			–	–	**100.0%**	33.3%	0.0%	**66.7%**

Table 5: Monolingual and multilingual TTS performance on pivot languages with at least 5 hours of training data, with MOS ratings from non-native listeners. Multi-word language names are abbreviated.



Figure 3: TTS performance with increasing amounts of pseudo-labeled ELARSpeech-U.

Pseudo-Labeled Scaling. Figure 3 shows the effect of scaling pseudo-labeled ELARSpeech-U on TTS performance. Unlike ASR, increasing the amount of pseudo-labeled speech does not improve intelligibility, with CER instead showing a slight increase as more pseudo-labeled data are added. In contrast, UTMOS initially improves with additional pseudo-labeled speech, reaches its highest score at an intermediate retention level, and declines when the entire pseudo-labeled corpus is retained. This suggests that pseudo-labeled speech can provide useful additional acoustic variation for TTS, improving perceptual quality at moderate scale despite a slight degradation in intelligibility, while lower-confidence pseudo-labels diminish these gains as more data are retained.

Model	Data (H)	# Langs.	# ELAR	# Params.	Mono. ASR CER ↓	Multi. ASR CER ↓	Multi. LID Acc. ↑	Multi. ASR + LID Acc. ↑	Multi. ASR + LID CER ↓	Score
w2v-BERT 2.0†	*4.5M*	*143*	–	*600M*	*41.0 / 29.2*	*24.6 / 20.3*	*70.0 / 86.8*	*83.2 / 90.6*	*24.2 / 20.3*	–
XLS-R†	*436K*	*128*	–	*300M* *1B*	*39.7 / 30.6* *40.5 / 30.9*	*29.3 / 22.0* *30.4 / 26.3*	*66.9 / 87.9* *70.9 / 85.8*	*55.6 / 85.6* *66.4 / 87.1*	*28.4 / 22.9* *28.6 / 25.2*	– –
MMS†	*491K*	*1,406*	–	*300M* *1B*	*33.8 / 30.5* *33.3 / 25.7*	*28.7 / 24.0* *21.3 / 18.1*	*62.3 / 84.3* *84.8 / 86.1*	*71.9 / 74.3* *73.3 / 74.8*	*31.5 / 30.0* *26.0 / 25.5*	– –
XEUS†	*1M*	*4,057*	–	*600M*	*30.3 / 25.1*	*21.1 / 20.1*	*81.5 / 87.3*	*86.4 / 91.3*	*22.9 / 19.6*	–
Mel-Filterbank	–	–	–	–	71.6 / 64.9	73.8 / 70.2	6.4 / 8.5	30.9 / 43.3	73.0 / 69.6	0.0 / 0.0
w2v-BERT 2.0	4.5M	143	6 (4.2%)	600M	53.8 / 45.8	57.6 / 51.7	50.6 / 57.7	54.1 / 79.4	57.7 / 51.9	901.9 / 944.2
XLS-R	436K	128	7 (5.5%)	300M 1B	53.5 / 45.7 52.1 / 44.9	59.2 / 53.1 58.9 / 53.0	49.3 / 56.5 49.9 / 55.9	49.4 / 81.3 51.9 / 82.2	58.9 / 52.8 59.2 / 52.2	848.5 / 921.7 880.8 / 935.2
MMS	491K	1,406	333 (23.7%)	300M 1B	53.6 / 46.0 **51.9 / 44.6**	58.4 / 52.7 **56.9 / 51.5**	53.7 / **61.9** **54.4** / 57.7	54.2 / 81.0 55.3 / **83.1**	58.6 / 52.3 **56.7 / 50.8**	901.6 / 949.8 **968.4 / 980.1**
XEUS	1M	4,057	342 (8.4%)	600M	52.2 / 45.0	60.2 / 54.4	49.4 / 57.6	**63.6** / 82.1	59.8 / 53.5	898.4 / 915.6
OmniASR-W2V	4.3M	1,690	140 (8.3%)	300M 1B	52.1 / 45.5 52.3 / 45.1	58.9 / 52.7 57.9 / 51.9	45.5 / 41.9 49.0 / 59.3	49.5 / 79.8 52.1 / 81.0	58.5 / 52.4 57.7 / 51.3	854.3 / 857.8 901.4 / 967.8

Table 6: ML-SUPERB-style evaluation on ELARSpeech. Results are reported under 10-minute / 1-hour supervision. Data and # Langs. denote the amount and reported language coverage of SSL pretraining data. # ELAR denotes the number of languages in each model's publicly available language inventory that overlap with ELARSpeech, with the percentage relative to its reported language coverage shown in parentheses. Gray italicized rows (†) show the original (non-long-tail) ML-SUPERB results reported in Chen et al. (2024) for reference.

5.3 Representation Analysis

Low-Resource Representation Transfer. As shown in Table 6, all pretrained representations consistently outperform the mel-filterbank baseline across the evaluated tasks, indicating that multilingual pretraining remains beneficial for the long-tail languages in ELARSpeech. These improvements persist under both supervision budgets, suggesting that pretrained representations can provide useful features even when language-specific supervision is extremely limited.

Beyond Existing Benchmarks. However, despite these consistent gains over the baseline, the relative advantages among pretrained representations become less pronounced on ELARSpeech. For example, 10-minute monolingual ASR CER ranges from 30.3 to 41.0 on ML-SUPERB (26.1% relative difference), compared with only 51.9 to 53.8 (3.5% relative difference) on ELARSpeech. Meanwhile, all models perform consistently worse on ELARSpeech than on ML-SUPERB under matched supervision budgets. These results show that existing S3Ms exhibit weaker absolute performance on ELARSpeech, losing much of the relative advantage observed on the original benchmark across high-resource languages.

Pretraining Scale, Coverage, and Exposure. Interestingly, these differences are not well explained by pretraining scale or nominal language coverage alone. While XEUS has the largest absolute overlap with ELARSpeech, this represents only a small fraction (8.4%) of its broader language inventory; in contrast, MMS exhibits a considerably higher proportion (23.7%) of ELARSpeech languages and achieves the strongest overall performance. This suggests that effective long-tail transfer may depend less on simply scaling the number of pretraining languages and more on maintaining balanced exposure to low-resource languages, highlighting the need for linguistic long-tail resources to drive further advances in multilingual speech models.

6 Conclusion

In this work, we introduced ELARSpeech, a large-scale speech corpus comprising 30,202 hours across 675 underrepresented languages. Beyond its scale, ELARSpeech extends multilingual speech resources further into the linguistic long tail while preserving the acoustic and domain diversity of real-world field recordings. Subsequently, our experiments demonstrate that ELARSpeech supports effective ASR and TTS adaptation across diverse underrepresented languages, with pseudo-labeled data providing further opportunities for scaling beyond limited human annotations on long-tail languages. At the same time, representation analysis shows that pretraining scale and language coverage alone are insufficient predictors of long-tail transfer, highlighting the importance of speech resources that enable balanced exposure to low-resource languages. We anticipate ELARSpeech to serve as a foundation for advancing multilingual speech technology further into the linguistic long tail.

Limitations

As ELARSpeech is constructed from archival collections, its language and recording metadata may contain inconsistencies or uncertainties inherited from the original deposits. While our processing pipeline standardizes and filters the collected data, it cannot fully resolve inaccuracies in archival metadata. Additionally, our MOS evaluation relies primarily on non-native listeners due to the difficulty of recruiting native speakers across hundreds of low-resource languages. Accordingly, the evaluation focuses on general perceptual qualities such as naturalness, artifacts, and listening comfort rather than linguistic accuracy or native-like pronunciation and prosody. We complement these human judgments with automatic measures of intelligibility and perceptual quality, but this aspect remains an important direction for future work.

Ethical Statement

ELARSpeech is derived from archival recordings of endangered and underrepresented language communities, for which responsible use requires particular attention to the rights and conditions associated with the source materials. Prior to data collection, we consulted the ELAR team regarding the use of archived materials for machine-learning research and follow their guidance on access, attribution, and downstream use. We include only materials designated as *Open* or *User Access*, exclude *Subscriber Access* materials that require permission from collection stewards, and preserve collection-level provenance and attribution information. We recognize that permission to access archival materials does not remove the responsibility to respect the individuals and communities represented in them. We acknowledge the agency of language communities in determining how their linguistic resources are used and commit to honoring requests to remove materials from ELARSpeech. Accordingly, ELARSpeech is intended for non-commercial research, with downstream use subject to the applicable licensing and collection-specific conditions.

References

Rosana Ardila, Megan Branson, Kelly Davis, Michael Kohler, Josh Meyer, Michael Henretty, Reuben Morais, Lindsay Saunders, Francis Tyers, and Gregor Weber. 2020. Common Voice: A massively-multilingual speech corpus. In *Proceedings of the Language Resources and Evaluation Conference*, pages 4218–4222.

Antonis Asonitis, Luca A Lanzendörfer, Frédéric Berdoz, and Roger Wattenhofer. 2026. Worldspeech: A multilingual speech corpus from around the world. *arXiv preprint arXiv:2605.09167*.

Kaito Baba, Wataru Nakata, Yuki Saito, and Hiroshi Saruwatari. 2024. The t05 system for the VoiceMOS Challenge 2024: Transfer learning from deep image classifier to naturalness MOS prediction of high-quality synthetic speech. In *IEEE Spoken Language Technology Workshop (SLT)*, pages 818–824.

Arun Babu, Changhan Wang, Andros Tjandra, Kushal Lakhotia, Qiantong Xu, Naman Goyal, Kritika Singh, Patrick Von Platen, Yatharth Saraf, Juan Pino, and 1 others. 2021. Xls-r: Self-supervised cross-lingual speech representation learning at scale. *arXiv preprint arXiv:2111.09296*.

Vlada Baranova. 2025. Inel kalmyk corpus.

Loïc Barrault, Yu-An Chung, Mariano Coria Meglioli, David Dale, Ning Dong, Mark Duppenthaler, Paul-Ambroise Duquenne, Brian Ellis, Hady Elsahar, Justin Haaheim, and 1 others. 2023. Seamless: Multilingual expressive and streaming speech translation. *arXiv preprint arXiv:2312.05187*.

Gilles Boulianne. 2022. Phoneme transcription of endangered languages: an evaluation of recent asr architectures in the single speaker scenario. In *Findings of the Association for Computational Linguistics: ACL 2022*, pages 2301–2308.

Hervé Bredin. 2017. pyannote. metrics: A toolkit for reproducible evaluation, diagnostic, and error analysis of speaker diarization systems. *hypothesis*, 100(60):90.

Hervé Bredin. 2023. pyannote. audio 2.1 speaker diarization pipeline: principle, benchmark, and recipe. In *24th Interspeech Conference (INTERSPEECH 2023)*, pages 1983–1987. ISCA.

Hervé Bredin, Ruiqing Yin, Juan Manuel Coria, Gregory Gelly, Pavel Korshunov, Marvin Lavechin, Diego Fustes, Hadrien Titeux, Wassim Bouaziz, and Marie-Philippe Gill. 2020. Pyannote. audio: neural building blocks for speaker diarization. In *ICASSP 2020-2020 IEEE International conference on acoustics, speech and signal processing (ICASSP)*, pages 7124–7128. IEEE.

Sanyuan Chen, Chengyi Wang, Zhengyang Chen, Yu Wu, Shujie Liu, Zhuo Chen, Jinyu Li, Naoyuki Kanda, Takuya Yoshioka, Xiong Xiao, and 1 others. 2022. Wavlm: Large-scale self-supervised pre-training for full stack speech processing. *IEEE Journal of Selected Topics in Signal Processing*, 16(6):1505–1518.

William Chen, Wangyou Zhang, Yifan Peng, Xinjian Li, Jinchuan Tian, Jiatong Shi, Xuankai Chang, Soumi Maiti, Karen Livescu, and Shinji Watanabe. 2024. Towards robust speech representation learning for thousands of languages. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 10205–10224.

Alexis Conneau, Min Ma, Simran Khanuja, Yu Zhang, Vera Axelrod, Siddharth Dalmia, Jason Riesa, Clara Rivera, and Ankur Bapna. 2023. FLEURS: Few-shot learning evaluation of universal representations of speech. In *IEEE Spoken Language Technology Workshop*, pages 798–805. IEEE.

Brecht Desplanques, Jenthe Thienpondt, and Kris Demuynck. 2020. Ecapa-tdnn: Emphasized channel attention, propagation and aggregation in tdnn based speaker verification. *arXiv preprint arXiv:2005.07143*.

Shansan Gong, Shivam Agarwal, Yizhe Zhang, Jiacheng Ye, Lin Zheng, Mukai Li, Chenxin An, Peilin Zhao, Wei Bi, Jiawei Han, and 1 others. 2025. Scaling diffusion language models via adaptation from autoregressive models. In *International Conference on Learning Representations*, volume 2025, pages 5046–5073.

Alex Graves, Santiago Fernández, Faustino Gomez, and Jürgen Schmidhuber. 2006. Connectionist temporal classification: labelling unsegmented sequence data with recurrent neural networks. In *Proceedings of the 23rd international conference on Machine learning*, pages 369–376.

David Guzmán, Luel Hagos Beyene, Jesujoba Oluwadara Alabi, Yejin Jeon, Dietrich Klakow, and David Ifeoluwa Adelani. 2026. Openbibletts: Large-scale speech resources and tts models for low-resource languages. *arXiv preprint arXiv:2606.09553*.

Haorui He, Zengqiang Shang, Chaoren Wang, Xuyuan Li, Yicheng Gu, Hua Hua, Liwei Liu, Chen Yang, Jiaqi Li, Peiyang Shi, and 1 others. 2024. Emilia: An extensive, multilingual, and diverse speech dataset for large-scale speech generation. In *2024 IEEE Spoken Language Technology Workshop (SLT)*, pages 885–890. IEEE.

Gil Keren, Artyom Kozhevnikov, Yen Meng, Christophe Ropers, Matthew Setzler, Skyler Wang, Ife Adebara, Michael Auli, Can Balioglu, and 1 others. 2025. Omnilingual asr: Open-source multilingual speech recognition for 1600+ languages. *arXiv preprint arXiv:2511.09690*.

Suyoun Kim, Takaaki Hori, and Shinji Watanabe. 2017. Joint ctc-attention based end-to-end speech recognition using multi-task learning. In *2017 IEEE international conference on acoustics, speech and signal processing (ICASSP)*, pages 4835–4839. IEEE.

Ki-Joong Kwon, Junho So, and Sang-Hoon Lee. 2026. Coreaspeech: Korean speech corpus via jamo-based coreset selection for efficient and robust korean speech generation. *Advances in Neural Information Processing Systems*, 38.

Mingfei Lau, Qian Chen, Yeming Fang, Tingting Xu, Tongzhou Chen, and Pavel Golik. 2025. Data quality issues in multilingual speech datasets: The need for sociolinguistic awareness and proactive language planning. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 7466–7492.

Marvin Lavechin, Marianne Métais, Hadrien Titeux, Alodie Boissonnet, Jade Copet, Morgane Rivière, Elika Bergelson, Alejandrina Cristia, Emmanuel Dupoux, and Hervé Bredin. 2023. Brouhaha: Multi-task training for voice activity detection, speech-to-noise ratio, and c50 room acoustics estimation. In *2023 IEEE Automatic Speech Recognition and Understanding Workshop (ASRU)*, pages 1–7. IEEE.

Matthew Le, Apoorv Vyas, Bowen Shi, Brian Karrer, Leda Sari, Rashel Moritz, Mary Williamson, Vimal Manohar, Yossi Adi, Jay Mahadeokar, and 1 others. 2023. Voicebox: Text-guided multilingual universal speech generation at scale. *Advances in neural information processing systems*, 36:14005–14034.

Éric Le Ferrand, Cian Mohamed Bashar Hauser, Joshua Hartshorne, and Emily Prud'hommeaux. 2025. Faithful transcription: Leveraging bible recordings to improve asr for endangered languages. In *Proceedings of the 14th International Joint Conference on Natural Language Processing and the 4th Conference of the Asia-Pacific Chapter of the Association for Computational Linguistics*, pages 333–342.

Xinjian Li, Shinnosuke Takamichi, Takaaki Saeki, William Chen, Sayaka Shiota, and Shinji Watanabe. 2023. Yodas: Youtube-oriented dataset for audio and speech. In *2023 IEEE Automatic Speech Recognition and Understanding Workshop (ASRU)*, pages 1–8. IEEE.

Zhaolin Li and Jan Niehues. 2026. Multimodal in-context learning for asr of low-resource languages. In *Findings of the Association for Computational Linguistics: ACL 2026*, pages 24745–24760.

Ilya Loshchilov and Frank Hutter. 2017. Decoupled weight decay regularization. *arXiv preprint arXiv:1711.05101*.

Linhan Ma, Dake Guo, Kun Song, Yuepeng Jiang, Shuai Wang, Liumeng Xue, Weiming Xu, Huan Zhao, Binbin Zhang, and Lei Xie. 2024. Wenetspeech4tts: A 12,800-hour mandarin tts corpus for large speech generation model benchmark. *arXiv preprint arXiv:2406.05763*.

Josh Meyer, David Ifeoluwa Adelani, Edresson Casanova, Alp Öktem, Daniel Whitenack Julian Weber, Salomon Kabongo, Elizabeth Salesky, Iroro Orife, Colin Leong, Perez Ogayo, and 1 others. 2022. Bibletts: a large, high-fidelity, multilingual,

and uniquely african speech corpus. *arXiv preprint arXiv:2207.03546*.

Niko Moritz, Takaaki Hori, and Jonathan Le Roux. 2019. Streaming end-to-end speech recognition with joint ctc-attention based models. In *2019 IEEE Automatic Speech Recognition and Understanding Workshop (ASRU)*, pages 936–943. IEEE.

Md Nayeem, Md Shamse Tabrej, Kabbojit Jit Deb, Shaonti Goswami, and Md Azizul Hakim. 2025. Automatic speech recognition in the modern era: Architectures, training, and evaluation. *arXiv preprint arXiv:2510.12827*.

Sewade Ogun, Vincent Colotte, and Emmanuel Vincent. 2023. Can we use common voice to train a multi-speaker tts system? In *2022 IEEE Spoken Language Technology Workshop (SLT)*, pages 900–905. IEEE.

Sewade Ogun, Abraham T Owodunni, Tobi Olatunji, Eniola Alese, Babatunde Oladimeji, Tejumade Afonja, Kayode Olaleye, Naome A Etori, and Tosin Adewumi. 2024. 1000 african voices: Advancing inclusive multi-speaker multi-accent speech synthesis. *arXiv preprint arXiv:2406.11727*.

Samuel Pfisterer, Florian Grötschla, Luca Lanzendörfer, Florian Yan, and Roger Wattenhofer. 2026. Eurospeech: A multilingual speech corpus. *Advances in Neural Information Processing Systems*, 38.

Vineel Pratap, Andros Tjandra, Bowen Shi, Paden Tomasello, Arun Babu, Sayani Kundu, Ali Elkahky, Zhaoheng Ni, Apoorv Vyas, Maryam Fazel-Zarandi, and 1 others. 2024. Scaling speech technology to 1,000+ languages. *Journal of Machine Learning Research*, 25(97):1–52.

Alec Radford, Jong Wook Kim, Tao Xu, Greg Brockman, Christine McLeavey, and Ilya Sutskever. 2023. Robust speech recognition via large-scale weak supervision. In *International conference on machine learning*, pages 28492–28518. PMLR.

Jiatong Shi, Dan Berrebbi, William Chen, Ho-Lam Chung, En-Pei Hu, Wei Ping Huang, Xuankai Chang, Shang-Wen Li, Abdelrahman Mohamed, Hung-yi Lee, and 1 others. 2023. Ml-superb: Multilingual speech universal performance benchmark. *arXiv preprint arXiv:2305.10615*.

Jiatong Shi, Shih-Heng Wang, William Chen, Martijn Bartelds, Vanya Bannihatti Kumar, Jinchuan Tian, Xuankai Chang, Dan Jurafsky, Karen Livescu, Hung-yi Lee, and 1 others. 2024. Ml-superb 2.0: Benchmarking multilingual speech models across modeling constraints, languages, and datasets. *arXiv preprint arXiv:2406.08641*.

John P Snyder. 1997. *Flattening the earth: two thousand years of map projections*. University of Chicago press.

Silero Team. 2024. Silero vad: pre-trained enterprise-grade voice activity detector (vad), number detector and language classifier. https://github.com/snakers4/silero-vad.

Jörgen Valk and Tanel Alumäe. 2021. Voxlingua107: a dataset for spoken language recognition. In *2021 IEEE spoken language technology workshop (SLT)*, pages 652–658. IEEE.

Changhan Wang, Morgane Riviere, Ann Lee, Anne Wu, Chaitanya Talnikar, Daniel Haziza, Mary Williamson, Juan Pino, and Emmanuel Dupoux. 2021. Voxpopuli: A large-scale multilingual speech corpus for representation learning, semi-supervised learning and interpretation. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 993–1003.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, and 1 others. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

Yu Zhang, Wei Han, James Qin, Yongqiang Wang, Ankur Bapna, Zhehuai Chen, Nanxin Chen, Bo Li, Vera Axelrod, Gary Wang, and 1 others. 2023. Google usm: Scaling automatic speech recognition beyond 100 languages. *arXiv preprint arXiv:2303.01037*.

Han Zhu, Lingxuan Ye, Wei Kang, Zengwei Yao, Liyong Guo, Fangjun Kuang, Zhifeng Han, Weiji Zhuang, Long Lin, and Daniel Povey. 2026. Omnivoice: Towards omnilingual zero-shot text-to-speech with diffusion language models. *arXiv preprint arXiv:2604.00688*.

Appendix

A License and Terms of Use

As mentioned in Section 3.1, ELARSpeech is derived from materials archived in the Endangered Languages Archive (ELAR). Prior to data collection and processing, we contacted the ELAR team to clarify the permitted use of archived materials for machine-learning research. ELAR confirmed that such use, including model training and research outputs, is permissible provided that downstream use complies with the applicable licensing and access conditions of the source materials.

We restrict ELARSpeech to materials designated as *Open* or *User Access*, excluding all *Subscriber Access* materials, which involve additional permission procedures and may require explicit authorization from individual collection stewards beyond access approval from ELAR. For each included collection, we preserve its provenance, including the ELAR permanent identifier and collection steward information where available, as well as the applicable access and licensing conditions.

ELARSpeech consists of machine-learning-oriented derivatives produced through our preprocessing pipeline and is released under the Creative Commons Attribution-NonCommercial-ShareAlike 4.0 International (CC BY-NC-SA 4.0) license. This license does not supersede the ownership, copyright, attribution requirements, or access conditions of the original ELAR materials. Downstream use and redistribution must comply with both the ELARSpeech license and the applicable collection-specific terms, while preserving the attribution and provenance of the source collections.

B Dataset Design Principles

The source archival collections were created for language documentation, where language identities, varieties, and orthographic conventions are determined by the source collections and their communities. Given that language labels, orthographic conventions, and language-dialect boundaries can introduce ambiguity in massively multilingual speech datasets, particularly for low-resource languages (Lau et al., 2025), we follow several principles to avoid imposing additional assumptions during dataset construction.

Preservation Over Normalization. First, we preserve the language names, variety distinctions, and orthographic conventions provided by the original collections whenever possible. In particular, we do not normalize different orthographies or merge language varieties solely to obtain a more uniform representation. This approach prioritizes preserving the linguistic distinctions in the source archive over enforcing consistency across collections.

No Forced ISO Mapping. Second, we retain languages and varieties without ISO 639-3 codes rather than assigning them to potentially related ISO-coded languages. This approach avoids imposing standardized identifiers that may not accurately reflect the linguistic distinctions in the original collections. Consequently, the reported language coverage includes both ISO-coded entries and those identified only by their original language names.

Minimal Linguistic Intervention. Third, we do not redefine whether two documented varieties constitute distinct languages or dialects, nor do we systematically merge entries based on linguistic similarity. Such distinctions can depend on sociolinguistic, historical, and community-specific factors that cannot be reliably inferred from the recordings alone. We therefore defer to the distinctions represented in the source collections rather than introducing a new linguistic taxonomy during data processing.

Known Limitations. Aforementioned principles preserve the structure of the original archive but do not eliminate ambiguities already present in archival metadata. Language names may vary across collections, boundaries between languages and dialects may be sociolinguistically complex, and orthography may differ within or across collections. Accordingly, the language counts reported for ELARSpeech should be interpreted as reflecting the documented language and variety identities represented in the source archive, rather than as an independently verified linguistic taxonomy.

C Detailed Statistics of ELARSpeech

We provide additional statistics on the linguistic, resource, and acoustic characteristics of ELARSpeech. Specifically, Figure 4 presents the number of languages and total speech hours across 78 language families, illustrating the broad linguistic diversity and resource distribution of the corpus. Additionally, Table 7 provides detailed statistics for 606 canonical languages out of 675 languages, excluding the multilingual subset whose samples cannot be unambiguously assigned to a single language. The table reports the total duration per split for each language.



Figure 4: Language family distribution from 78 unique language families of ELARSpeech.

Algorithm 1 Automatic Transcription Tier Selection and Heuristic Scoring Rules

(a) Transcription tier selection

Require: ELAN file set $\mathcal{E}$, acceptance threshold $\tau_a = 70$, review threshold $\tau_r = 50$
Ensure: Accepted tiers $\mathcal{T}_a$ and tiers requiring manual review $\mathcal{T}_r$

$\mathcal{T}_a \leftarrow \emptyset$
$\mathcal{T}_r \leftarrow \emptyset$
for all $e \in \mathcal{E}$ **do**
  $\mathcal{C}_e \leftarrow \emptyset$
  for all tier $t \in e$ **do**
    $n_t \leftarrow \textsc{Normalize}(\textsc{TierID}(t))$
    $l_t \leftarrow \textsc{Normalize}(\textsc{LinguisticType}(t))$
    $p_t \leftarrow \textsc{Normalize}(\textsc{ParentRef}(t))$
    $s(t) \leftarrow \textsc{ScoreTier}(n_t, l_t, p_t)$
    $s(t) \leftarrow \min(100, \max(0, s(t)))$
    $\mathcal{C}_e \leftarrow \mathcal{C}_e \cup \{(t, s(t))\}$
  end for
  $t^* \leftarrow \arg\max_{t \in \mathcal{C}_e} s(t)$
  if $s(t^*) \geq \tau_a$ **then**
    $\mathcal{T}_a \leftarrow \mathcal{T}_a \cup \{(e, t^*)\}$
  else if $s(t^*) \geq \tau_r$ **then**
    $\mathcal{T}_r \leftarrow \mathcal{T}_r \cup \{(e, t^*)\}$
  else
    $\textsc{RejectCandidate}(e, t^*)$
  end if
end for

(b) Heuristic scoring rules

Category	Markers and scores
Exact source text	*tx*, *txt*, *text*, *texto*, *transcription* $(+90)$
Strong transcription	*transcription*, *orthography*, *utterance*, *sentence*, *clause*, *intonation unit* $(+80)$
Weak text	*text*, *word*, *phrase*, *line* $(+35)$
Structural bonus	Top-level tier or transcription-like parent $(+10)$
Structural penalty	Other child tier (-5)
Speaker condition	Non-native (-15); background (-30)
Identifiers	Number, reference, ID, or clip (-60)
Metadata	Comment, note, or metadata (-70)
Interlinear annotation	Gloss, morpheme, lemma, or POS (-80)
Translation	Translation, free translation, or literal translation (-100)

Scoring. All applicable rules are accumulated, and the resulting score is clipped to $[0, 100]$. For labels such as `tx@Speaker1`, the substring preceding `@` is additionally compared with conventional source-text labels.

D Automatic Annotation Tier Selection

As described in Section 3.2, ELAR's annotation files exhibit heterogeneous tier naming and contain multiple annotation types, including transcriptions, translations, glosses, and metadata, requiring automatic identification of valid transcription tiers.

To automatically identify time-aligned transcription tiers, we assign each annotation tier a heuristic score based on its tier ID, linguistic type, and parent-tier information. The scoring function incorporates both positive indicators associated with source transcriptions (e.g., *transcription*, *tx*, and *utterance*) and negative indicators associated with auxiliary annotations (e.g., *translation*, *gloss*, and *note*). Scores from all applicable rules are accumu-

lated and clipped to the range $[0, 100]$. For each ELAN file, the highest-scoring tier is selected as the candidate transcription tier.

Algorithm 1 summarizes the complete tier selection procedure and heuristic scoring rules. Candidate tiers with scores of at least 70 are accepted automatically, while those scoring between 50 and 70 are manually verified. Candidates scoring below 50 are discarded. This combination of heuristic ranking and selective manual verification enables us to accommodate heterogeneous annotation conventions across ELAR collections without requiring manual inspection of every annotation file.

Specifically, across 39,338 unique annotation tiers, 7,144 received scores of 70 or higher, 3,936 received scores between 50 and 70, and 28,258 received scores below 50. We automatically accept tiers scoring at least 70, manually review those scoring between 50 and 70, and reject those scoring below 50. Manual validation estimated a 99.3% precision for automatically accepted tiers, with 993 of 1,000 randomly sampled tiers confirmed as valid transcriptions, while 99.9% of automatically rejected tiers were confirmed to be invalid (999 of 1,000). Among the 3,936 intermediate-score tiers, manual review identified 1,035 as valid transcription tiers (26.3%).

E Unlabeled Data Segmentation

Algorithm 2 describes the procedure used to transform long-form recordings into training-ready clips for ELARSpeech-U. Following the diarization post-processing described in Section 3.3, the resulting speaker-homogeneous segments are used as input to the segmentation pipeline.

We first discard segments shorter than or equal to 0.3 seconds, as such short clips are unlikely to contain sufficient speech content for reliable model training. Subsequently, segments of at most 30 seconds are directly retained, while longer segments are recursively split using `Silero VAD`.

For each segment exceeding 30 seconds, we prioritize the longest silence that leaves at least 0.3 seconds of audio on both sides. If no silence exists, we use the nearest valid VAD boundary; if no valid boundary is available, the segment midpoint is used as a fallback. This procedure is recursively applied until all resulting clips are at most 30 seconds long. Overlap information is retained as metadata to enable flexible filtering in downstream use.

Algorithm 2 Clip Extraction with Recursive Split

Require: Merged segments $\mathcal{M}$, audio root $\mathcal{D}_{\text{in}}$, output root $\mathcal{D}_{\text{out}}$, $\tau_{\min} = 0.3$s, $T = 30$s, VAD threshold θ
Ensure: Final clips $\mathcal{F}$, excluded set $\mathcal{X}$
$\mathcal{F} \leftarrow \emptyset$, $\mathcal{X} \leftarrow \emptyset$
// Stage 1: discard short spans, write initial clips
for all recording f with $\mathcal{G}_f \subseteq \mathcal{M}$ **do**
  $\mathcal{A} \leftarrow \{s \in \mathcal{G}_f : d(s) > \tau_{\min}\}$
  $\mathcal{X} \leftarrow \mathcal{X} \cup (\mathcal{G}_f \setminus \mathcal{A})$, $\mathcal{L} \leftarrow \emptyset$
  for all $s \in \mathcal{A}$ **do**
    WRITECLIP$(f, s, \mathcal{D}_{\text{out}})$
    if $d(s) \le T$ **then** $\mathcal{F} \leftarrow \mathcal{F} \cup \{s\}$ **else** $\mathcal{L} \leftarrow \mathcal{L} \cup \{s\}$
  end for
// Stage 2: recursively split clips longer than T
  if $\mathcal{L} \neq \emptyset$ **then** $\mathcal{V} \leftarrow$ SILEROVAD(f, θ)
  for all $s \in \mathcal{L}$ **do**
    $\mathcal{P} \leftarrow$ SPLITSEGMENT$(s, \mathcal{V}, T, \tau_{\min})$
    WRITECLIP$(f, p, \mathcal{D}_{\text{out}})$ for all $p \in \mathcal{P}$
    $\mathcal{F} \leftarrow \mathcal{F} \cup \mathcal{P}$
  end for
end for
function SPLITSEGMENT$(s, \mathcal{V}, T, \tau_{\min})$
  if $d(s) \le T$ **then return** $\{s\}$
  $c \leftarrow$ longest silence in $\mathcal{V} \cap s$ with $\ge \tau_{\min}$ on both sides; else nearest VAD boundary; else midpoint of s
  return SPLITSEGMENT$(s_{<c})$ $\cup$ SPLITSEGMENT$(s_{>c})$
end function

F Pivot Language Selection

We select 30 pivot languages to provide a representative evaluation across diverse resource levels and linguistic groups.

First, we divide ELARSpeech languages into three resource bins based on the amount of available training data: high-resource ($>$ 20 hours), mid-resource (10-20 hours), and low-resource ($<$ 10 hours), and sample languages across these bins to ensure diversity in resource availability.

Second, given our primary focus on long-tail and previously underrepresented languages, we select 15 of the 30 pivot languages from languages without an ISO 639-3 code. We also balance these languages across resource bins to avoid concentrating the evaluation on a particular resource level.

Finally, we maximize language-family diversity within the resulting language pool. When multiple selected languages belong to the same language family, we replace overlapping languages, where possible, with candidates from different families with comparable amounts of training data. This procedure yields 30 pivot languages spanning diverse resource levels and language families, while maintaining balanced representation of languages that are rarely covered by existing benchmarks.



Figure 5: Instruction page provided to participants.

G MOS Evaluation Protocol

Participants. We recruited 36 listeners through community outreach. As the TTS evaluation covers 14 extremely low-resource languages that participants were not expected to speak, listeners were instructed to assess only *acoustic naturalness and listening quality*, considering human-likeness, audible artifacts (e.g., noise, glitches, metallic timbre, muffling, or dropouts), and overall listening comfort. They were explicitly instructed not to consider intelligibility, pronunciation or intonation, or familiarity with the language, which were evaluated separately using automatic metrics. Ratings were collected on a 5-point scale. The detailed evaluation instructions are shown in Figure 5.

Evaluation Procedure. We constructed a pool of 210 utterances by sampling five clips for each of 42 system-language pairs (three systems $\times$ 14 languages). Each utterance was rated by 9 listeners. Participants were required to listen in a quiet environment over headphones or earphones; loudspeakers were not allowed, to reduce variability in acoustic presentation.

H Training Details

Automatic Speech Recognition. For monolingual ASR, Whisper-large-v3 and OmniASR-CTC-v2 are fine-tuned for 25 and 50 epochs, respectively, with a batch size of 32. For multilingual ASR, Whisper-large-v3 is fine-tuned for 150K steps with a batch size of 128. The two models also require different strategies to accommodate languages unsupported during pretraining. Whisper uses a BPE-based vocabulary together with language-ID tokens. Since its BPE vocabulary can represent text in the newly introduced languages, no vocabulary expansion is required. For languages without a pretrained language-ID token, we introduce a new language token and warm-start its embedding from that of the <en> language token before fine-tuning on the target language. In contrast, OmniASR-CTC-v2 uses a fixed output vocabulary for CTC decoding. When the training data contain tokens absent from its original vocabulary, we extend the vocabulary with the missing tokens and expand the corresponding linear head, randomly initializing the newly added rows.

Text-to-Speech. Unlike the utterance-based batching used for ASR, OmniVoice employs packed-sequence training to improve training efficiency. Accordingly, monolingual TTS models are fine-tuned for 50 epochs with a total batch duration of 2.5 minutes, while the multilingual OmniVoice model is fine-tuned for 100K steps. Similar to ASR, we adapt OmniVoice to languages unsupported during pretraining by introducing a new language token for each language and initializing its embedding from the <en> token, as its BPE vocabulary can represent text in the newly introduced languages without expansion.

Optimization. All models are optimized using the AdamW (Loshchilov and Hutter, 2017) optimizer, with a tri-stage learning rate schedule on 8 H100 GPUs. The warmup, hold, and decay phases follow a ratio of 0.1, 0.5, and 0.4, respectively. The learning rate increases from $5e{-}7$ to $1e{-}5$ during warmup, remains at $1e{-}5$ during the hold phase, and decays to $5e{-}7$. For multilingual training, we adopt the language sampling strategy of Pratap et al. (2024); Keren et al. (2025), with sampling probabilities defined as $p_l \propto (n_l/N)^{\beta_L}$. Here, n_l denotes the number of samples for language l, and N is the total number of samples. We set $\beta_L = 0.5$.

I Full Evaluation Results

Tables 8 and 9 present the full ASR and TTS evaluation results, respectively, across the 233 languages included in all three data splits (train, development, and test). For the full TTS evaluation, we additionally report speaker similarity (SIM-O), computed as the cosine similarity between speaker embeddings of synthesized speech and ground-truth utterances extracted using the WavLM-based ECAPA-TDNN model (Desplanques et al., 2020; Chen et al., 2022), following VoiceBox (Le et al., 2023).

Language	ISO 639-3	Labeled (H) Train	Dev	Test	Unlabeled (H)	Language	ISO 639-3	Labeled (H) Train	Dev	Test	Unlabeled (H)
Abui	abz	10.97	0.64	1.32	129.08	Ainu	ain	0.00	0.00	0.00	2.78
Ainu (Saru)	aib	0.00	0.00	0.00	6.28	Aiome	aki	0.00	0.00	0.00	0.42
Aisi	mmq	0.00	0.00	0.00	5.16	Ajumbu	muc	0.27	0.00	0.00	62.98
Akan	aka	0.49	0.00	0.00	1.44	Akha	ahk	5.49	0.33	0.64	2.29
Akpes	ibe	10.80	0.63	1.25	107.75	Aleut	ale	0.00	0.00	0.00	263.10
Alta, Northern	aqn	2.83	0.20	0.35	118.97	Amami-Oshima, Southern	ams	0.70	0.00	0.00	100.80
Amba (Suwa)	rwm	0.00	0.00	0.00	64.12	Ambel	wgo	5.53	0.29	0.62	137.85
Amurdak	amg	0.00	0.00	0.00	48.70	Anal	anm	8.52	0.49	1.01	6.99
Angaité	aqt	1.63	0.10	0.18	15.07	Animere	anf	4.98	0.26	0.54	77.32
Anindilyakwa	aoi	0.00	0.00	0.00	9.97	Antia Whistling Language	–	0.00	0.00	0.00	0.83
Anus	auq	0.00	0.00	0.00	6.82	Apalaí	apy	0.00	0.00	0.00	5.88
Apurinã	apu	3.30	0.18	0.44	9.92	Arabic, Judeo-Iraqi	yhd	2.35	0.14	0.28	9.68
Arandic (Family)	–	0.00	0.00	0.00	2.43	Araona	aro	11.38	0.71	1.40	414.79
Arapaho	arp	14.40	0.84	1.72	51.04	Aro	tei	6.77	0.37	0.78	26.87
Arta	atz	0.04	0.00	0.00	15.95	Ashéninka, Perené	prq	0.00	0.00	0.00	18.16
Assyrian Neo-Aramaic	aii	0.71	0.00	0.00	82.59	Asuri	asr	0.00	0.00	0.00	11.68
Avatime	avn	3.46	0.21	0.42	67.33	Awiakay	–	3.16	0.18	0.41	18.07
Awutu	afu	1.83	0.10	0.22	29.96	Axamb	ahb	0.00	0.00	0.00	112.27
Ayoreo	ayo	1.87	0.08	0.21	134.72	Ayutla Mixtec	miy	0.00	0.00	0.00	81.45
Babanki	bbk	1.59	0.00	0.00	2.31	Babar, North	bcd	0.03	0.00	0.00	30.24
Babar, Southeast	vbb	0.10	0.00	0.00	31.90	Badaga	bfq	0.00	0.00	0.00	1.66
Bafia	ksf	0.00	0.00	0.00	37.63	Bafut	bfd	0.09	0.00	0.00	0.48
Bai, Panyi	bfc	0.03	0.00	0.00	30.69	Bajjika	vjk	0.00	0.00	0.00	1.57
Balochi	bal	0.00	0.00	0.00	22.39	Banam Bay	vrt	9.13	0.53	1.10	29.56
Bandial	bqj	9.24	0.56	1.11	11.37	Bandial (Kujireray)	bqj	1.17	0.00	0.00	0.09
Baniwa	bwi	7.84	0.51	0.87	26.08	Baram	brd	18.88	1.14	2.23	2.27
Barein	bva	1.74	0.09	0.20	15.78	Baskeet	–	0.23	0.00	0.00	23.72
Bastimentos Creole English	–	8.58	0.51	0.99	0.91	Bathari	bhm	0.00	0.00	0.00	132.96
Bati	btc	9.28	0.51	1.08	240.67	Bauni	bpe	0.00	0.00	0.00	24.00
Bayot	bda	0.00	0.00	0.00	5.32	Baïnounk Gubëëher	–	0.15	0.00	0.00	2.70
Beezen	bnz	0.00	0.00	0.00	3.98	Belait	beg	14.64	0.90	1.65	42.07
Betta Kurumba	xub	0.00	0.00	0.00	5.53	Bih	ibh	2.10	0.11	0.26	2.29
Bikya	byb	0.00	0.00	0.00	4.59	Bine	bon	2.90	0.17	0.32	64.73
Bitur	mcc	0.00	0.00	0.00	0.52	Blablanga	blp	6.43	0.37	0.78	94.85
Bogo■	–	0.00	0.00	0.00	66.47	Bolivian Guaraní	–	0.00	0.00	0.00	5.97
Bom	bmf	0.01	0.00	0.00	14.59	Bom-Kim	bmf	0.24	0.00	0.00	13.05
Bongu	bpu	1.42	0.10	0.16	9.95	Brahui	brh	1.11	0.00	0.00	12.58
Brem	buq	1.59	0.11	0.17	1.09	Bribri	bzd	0.00	0.00	0.00	45.91
Bullom So	buy	0.16	0.00	0.00	1.40	Bum	bmv	5.47	0.30	0.61	118.09
Bunak	bfn	5.60	0.33	0.67	0.53	Burarra	bvr	4.42	0.28	0.55	69.17
Burarra (Gun-nartpa)	bvr	6.13	0.36	0.64	87.66	Busuu	bju	0.00	0.00	0.00	11.80
Buu	lfb	0.69	0.00	0.00	21.61	Caac	msq	0.96	0.00	0.00	0.84
Cabiyarí	cbb	1.58	0.12	0.19	12.34	Cabécar	cjp	0.00	0.00	0.00	12.90
Cahuilla	chl	2.44	0.17	0.31	5.06	Caijia	–	10.01	0.55	1.17	160.65
Calderón Highland Quichua	qud	19.11	1.15	2.24	12.78	Camsá	kbh	4.62	0.28	0.52	22.34
Caquinte	cot	0.00	0.00	0.00	102.62	Central !Kung (Mangetti Dune)	–	0.71	0.00	0.00	0.00
Chamalal	cji	0.01	0.00	0.00	36.65	Chatino, Tataltepec	cta	0.48	0.00	0.00	5.10
Chatino, Zacatepec	ctz	0.03	0.00	0.00	277.18	Chechen	che	0.00	0.00	0.00	2.22
Cheyi	–	0.68	0.00	0.00	18.29	Chiapas Zoque	–	12.69	0.78	1.46	7.51
Chimalapa Zoque	zoh	9.80	0.62	1.13	0.24	Chimborazo Highland Quichua	qug	14.60	0.88	1.78	7.34
Chini	afi	5.74	0.34	0.68	39.27	Chiquitano (Bésiro)	cax	1.62	0.11	0.19	8.84
Chorote (Family)	–	0.00	0.00	0.00	8.40	Chukchi	ckt	0.00	0.00	0.00	26.19
Chulym (Melet)	clw	1.06	0.00	0.00	120.14	Chulym (Tutal)	clw	0.00	0.00	0.00	10.76
Chácobo	cao	20.92	1.25	2.51	237.61	Cicipu	awc	6.00	0.34	0.69	146.24
Cineni	cie	1.66	0.00	0.00	64.69	Cofán	con	5.68	0.31	0.72	21.38
Cora (Family)	–	4.10	0.24	0.51	72.10	Cubeo	cub	0.44	0.00	0.00	3.39
Curripaco	kpc	2.60	0.17	0.29	5.70	Cuvok	cuv	1.04	0.00	0.00	13.57
Dahalo	dal	0.00	0.00	0.00	7.44	Dalabon	ngk	0.00	0.00	0.00	63.27
Damakawa	dam	0.00	0.00	0.00	0.96	Danau	dnu	0.00	0.00	0.00	7.45
Dao	–	0.00	0.00	0.00	26.67	Dargwa (Chirag)	dar	35.29	2.10	4.08	80.95
Dari	prs	0.00	0.00	0.00	43.77	Datooga	tcc	2.06	0.12	0.24	0.00
Datooga (Asimjeeg)	tcc	27.35	1.58	3.27	95.09	Dawoodi	dmk	7.59	0.43	0.90	79.96
Desano	des	0.00	0.00	0.00	8.04	Dghwede	dgh	1.74	0.00	0.00	49.42
Dhao	nfa	0.00	0.00	0.00	12.26	Djauan	djn	0.00	0.00	0.00	4.10
Doe	doe	0.00	0.00	0.00	0.57	Dolgan	dlg	17.45	1.02	1.97	0.00
Domari	rmt	0.00	0.00	0.00	36.72	Drung	duu	0.22	0.00	0.00	34.15
Dwang	nnu	0.79	0.00	0.00	2.66	Dza	jen	0.00	0.00	0.00	164.56
Dzardzongke	–	5.35	0.32	0.69	30.80	Dzongkha	dzo	0.00	0.00	0.00	15.26
Dâw	kwa	7.17	0.37	0.84	30.90	Eastern Huasteca Nahuatl	nhe	0.00	0.00	0.00	3.69
Ehueun	ehu	0.06	0.00	0.00	23.85	Eibela	ail	8.90	0.51	1.04	393.93
Emae	mmw	5.51	0.30	0.66	34.79	Emplawas	emw	37.45	2.25	4.51	265.91
Enawené-Nawé	unk	3.94	0.25	0.45	22.51	Enga	enq	0.00	0.00	0.00	76.30
English	eng	0.00	0.00	0.00	5.19	Enxet	enx	2.26	0.13	0.27	27.07
Ersu	ers	1.75	0.10	0.20	306.47	Ese Ejja	ese	0.00	0.00	0.00	23.43
Eton	etn	0.00	0.00	0.00	24.68	Even	eve	12.84	0.78	1.56	0.53
E'ñapa Woromaipu	pbh	13.35	0.79	1.53	41.08	Fanbak	fnb	0.08	0.00	0.00	25.65
Fang	fak	0.02	0.00	0.00	11.50	Fania	fni	3.23	0.18	0.36	90.53
Farefare	gur	0.00	0.00	0.00	35.11	Fas	fqs	0.71	0.00	0.00	2.79
Fon	fon	0.00	0.00	0.00	4.13	Fungwa	ula	4.29	0.26	0.50	40.73

Continued on next page

Continued from previous page

Language	ISO 639-3	Labeled (h) Train	Dev	Test	Unlabeled (h)	Language	ISO 639-3	Labeled (h) Train	Dev	Test	Unlabeled (h)
Gadaba, Bodo	gbj	9.47	0.57	1.15	76.60	Gadjerawang	gdh	0.22	0.00	0.00	96.25
Ganda	lug	0.45	0.00	0.00	7.22	Gants	gao	0.00	0.00	0.00	0.50
Gargarnaye	–	6.03	0.36	0.68	0.26	Garifuna	cab	2.68	0.19	0.33	18.48
Gavião of Jiparaná	gvo	0.00	0.00	0.00	47.50	Gbanziri	gbg	0.00	0.00	0.00	7.10
German	deu	0.00	0.00	0.00	0.32	Ghanongga	ghn	5.59	0.33	0.67	14.43
Ghulfan	ghl	0.44	0.00	0.00	11.20	Gitxsan	git	1.33	0.00	0.00	3.00
Glavda	glw	0.00	0.00	0.00	9.54	Glio-Oubi	oub	0.00	0.00	0.00	1.45
Goemai	ank	1.32	0.00	0.00	0.00	Golpa	lja	0.84	0.00	0.00	42.34
Gongduk	goe	2.62	0.15	0.29	36.28	Gorap	goq	0.09	0.00	0.00	5.93
Gorwaa	gow	73.29	4.28	8.67	641.39	Great Andamanese, Mixed	gac	0.00	0.00	0.00	72.00
Griko	–	0.00	0.00	0.00	1.61	Guarayu	gyr	3.62	0.18	0.43	13.94
Guató	gta	4.14	0.24	0.46	28.87	Guduf-Gava	gdf	0.17	0.00	0.00	0.00
Guernésiais	nrf	2.30	0.13	0.27	5.25	Gulf Arabic	afb	5.96	0.36	0.75	13.48
Gumuțească	–	1.11	0.00	0.00	1.29	Gun	guw	0.00	0.00	0.00	1.54
Gurindji Kriol	gjr	0.35	0.00	0.00	1.40	Gweno	gwe	7.82	0.49	0.95	61.46
Gyalsumdo	gyo	0.00	0.00	0.00	6.87	Gyeli	gyi	0.00	0.00	0.00	10.71
Hadza	hts	4.23	0.24	0.49	424.80	Hahon	hah	0.00	0.00	0.00	19.43
Hahon (Ratsua)	hah	0.00	0.00	0.00	3.92	Hakka Chinese	hak	0.00	0.00	0.00	94.57
Harsusi	hss	0.79	0.00	0.00	31.93	Heiyoho	auk	4.91	0.25	0.57	52.63
Herero	her	0.00	0.00	0.00	4.31	Highland Popoluca	poi	5.75	0.33	0.64	3.97
Hixkaryána	hix	0.00	0.00	0.00	17.79	Hmong Daw	mww	0.10	0.00	0.00	1.77
Hobyót	hoh	0.00	0.00	0.00	52.51	Horpa	ero	0.45	0.00	0.00	38.67
Hruso	hru	2.38	0.15	0.28	130.41	Huastec (South Eastern)	hus	0.48	0.00	0.00	25.12
Huilliche	huh	8.20	0.51	0.96	68.92	Hupa	hup	0.02	0.00	0.00	0.54
Ibatan	ivb	16.22	0.95	1.84	74.31	Ibibio	ibb	1.58	0.10	0.21	4.83
Igbo	ibo	0.00	0.00	0.00	0.98	Imbabura Highland Quichua	qvi	13.89	0.83	1.64	6.58
Imroing	imr	0.46	0.00	0.00	19.86	Inari Saami	smn	0.00	0.00	0.00	27.88
Inga	inb	1.59	0.00	0.00	13.59	Ingrian	izh	2.95	0.16	0.33	459.54
Ipiko	ipo	0.00	0.00	0.00	121.75	Ipili	ipi	0.00	0.00	0.00	2.05
Irántxe (Myky)	irn	0.19	0.00	0.00	46.37	Isanzu	isn	49.18	2.92	5.80	351.44
Itelmen	itl	0.79	0.00	0.00	0.15	Itene	ite	0.00	0.00	0.00	0.84
Ixcatec	ixc	1.03	0.00	0.00	60.45	Ixil	ixl	0.00	0.00	0.00	14.29
Iñapari	inp	25.55	1.50	3.05	122.83	Jabutí	jbt	6.51	0.37	0.75	101.01
Jawe	jaz	7.82	0.42	0.90	0.67	Jejueo	jje	3.60	0.21	0.45	179.81
Jitotoltec	–	18.56	1.08	2.10	3.96	Jowshaqani	–	2.05	0.11	0.22	23.60
Jul'hoansi	ktz	79.90	4.71	9.48	267.56	Júma	jua	1.61	0.09	0.20	19.25
Kaapor	urb	3.95	0.20	0.45	172.38	Kabardian	kbd	1.16	0.00	0.00	2.79
Kadazan Dusun	dtp	1.37	0.00	0.00	55.83	Kagulu	kki	0.00	0.00	0.00	0.11
Kaike	kzq	2.99	0.19	0.35	15.02	Kainji (Family)	–	0.00	0.00	0.00	52.96
Kakabe	kke	4.15	0.26	0.52	24.96	Kakataibo-Kashibo	cbr	3.41	0.19	0.40	123.56
Kalmyk-Oirat	xal	2.43	0.14	0.28	28.41	Kalmyk-Oirat (Durvud)	xal	1.94	0.11	0.21	24.59
Kam	kdx	16.02	0.96	1.86	77.91	Kamas	xas	34.28	1.99	4.00	0.00
Kanamarí	knm	0.30	0.00	0.00	25.91	Kandozi-Chapra	cbu	2.68	0.15	0.32	21.05
Kangjia	kxs	1.75	0.11	0.22	66.53	Kanum, Smärky	kxq	0.57	0.00	0.00	0.00
Karagas	kim	5.35	0.32	0.64	71.17	Karara	–	0.00	0.00	0.00	27.47
Karbi	mjw	1.39	0.00	0.00	2.19	Kateviri	bsh	0.00	0.00	0.00	4.02
Katla (Julud)	kcr	0.00	0.00	0.00	2.44	Kelabit	kzi	11.47	0.70	1.35	1.78
Kerinci (Koto Keras)	–	3.22	0.20	0.36	5.34	Kgalagadi	xkv	17.28	1.00	2.15	41.11
Khamyang	ksu	0.00	0.00	0.00	18.55	Khanty (Eastern)	kca	0.00	0.00	0.00	60.81
Khengkha	xkf	0.00	0.00	0.00	32.19	Khoekhoe	naq	0.00	0.00	0.00	0.77
Khoibu Naga	nkb	10.50	0.62	1.23	54.25	Kholosi	–	0.00	0.00	0.00	1.70
Kibala (Lubolo)	blv	0.00	0.00	0.00	65.89	Kichwa de Chibuleo	–	2.18	0.13	0.26	197.76
Kimbu	kiv	0.24	0.00	0.00	24.20	Kinnauri, Chitkuli	cik	3.05	0.18	0.35	4.27
Kiong	kkm	0.19	0.00	0.00	0.99	Klon	kyo	0.00	0.00	0.00	12.33
Kol	ekl	4.42	0.24	0.51	16.69	Komo	xom	1.26	0.00	0.00	49.13
Konda	knd	0.12	0.00	0.00	46.27	Konomala	koa	15.11	0.87	1.76	3.92
Korana	kqz	0.00	0.00	0.00	1.08	Koreguaje	coe	0.00	0.00	0.00	23.78
Koro	kxr	0.00	0.00	0.00	166.15	Koryak	kpy	24.95	1.47	2.89	312.24
Koshin	kid	0.64	0.00	0.00	25.51	Kove	kvc	0.80	0.00	0.00	9.24
Koyee	kkt	0.00	0.00	0.00	1.67	Kpasham	pbn	8.08	0.48	0.96	59.78
Kuke	ght	2.93	0.18	0.36	11.82	Kula	tpg	4.03	0.24	0.48	27.26
Kumarbhag Paharia	kmj	0.00	0.00	0.00	22.45	Kumiai	dih	0.93	0.00	0.00	0.42
Kuna, San Blas	cuk	0.00	0.00	0.00	31.45	Kunbarlang	wlg	1.54	0.00	0.00	67.92
Kundal Shahi	shd	2.84	0.14	0.31	0.53	Kung	kfl	0.00	0.00	0.00	6.56
Kung-Ekoka	knw	0.00	0.00	0.00	3.21	Kursav	faj	0.50	0.00	0.00	5.16
Kurtokha	xkz	0.00	0.00	0.00	57.55	Kurudu	kjr	0.34	0.00	0.00	216.91
Kushi	kuh	0.00	0.00	0.00	18.15	Kusua	–	0.00	0.00	0.00	185.43
Kwa	kwb	4.39	0.26	0.51	115.44	Kwak'wala	kwk	0.10	0.00	0.00	121.48
Kwatl	–	0.45	0.00	0.00	0.00	Kwegu	xwg	0.00	0.00	0.00	0.71
K'iche'	quc	15.30	0.94	1.77	4.84	Lacandon	lac	0.00	0.00	0.00	15.57
Lachi	lbt	0.00	0.00	0.00	26.71	Laitu Chin	clj	0.00	0.00	0.00	27.21
Lakurumau	lxm	12.65	0.82	1.46	6.82	Lavatbura-Lamusong	lbv	2.71	0.18	0.31	35.16
Laz	lzz	2.22	0.12	0.28	205.38	Lelepa	lpa	3.95	0.25	0.47	10.49
Leti	lti	22.22	1.29	2.69	3.56	Lezgi	lez	0.57	0.00	0.00	0.77
Lhokpu	lhp	0.00	0.00	0.00	80.19	Liki	lio	0.40	0.00	0.00	58.51
Limassa	bme	1.15	0.00	0.00	92.52	Longgu	lgu	0.00	0.00	0.00	2.57
Lundayeh	lnd	1.85	0.00	0.00	2.74	Macaguaje	mcl	0.00	0.00	0.00	8.43
Maco	wpc	0.14	0.00	0.00	8.22	Mae	mme	1.82	0.08	0.18	0.00
Mafea	mkv	11.57	0.60	1.26	0.83	Magi	mgu	0.00	0.00	0.00	4.89
Mah Meri	mhe	0.00	0.00	0.00	3.38	Makuráp	mpu	7.28	0.44	0.86	121.40
Mal Paharia	mkb	1.58	0.00	0.00	60.47	Malaccan Portuguese Creole	mcm	0.28	0.00	0.00	3.24
Maleng	pkt	0.68	0.00	0.00	50.10	Maléku Jaíka	gut	0.00	0.00	0.00	218.11

Continued on next page

Continued from previous page

Language	ISO 639-3	Labeled (h) Train	Dev	Test	Unlabeled (h)	Language	ISO 639-3	Labeled (h) Train	Dev	Test	Unlabeled (h)
Manat	pmr	0.40	0.00	0.00	7.99	Mand	ate	0.78	0.00	0.00	14.47
Manep	mkr	0.96	0.00	0.00	2.43	Mansi	mns	0.00	0.00	0.00	0.57
Maquiritari	mch	1.70	0.00	0.00	13.31	Maragus	mrs	4.46	0.27	0.51	50.22
Maring Naga	nng	0.00	0.00	0.00	8.11	Masela, Central	mxz	136.79	7.95	16.03	35.61
Masela, East	vme	0.01	0.00	0.00	30.49	Masela, West	mss	0.02	0.00	0.00	30.20
Massep	mvs	22.47	1.36	2.68	373.42	Matlatzinca, San Francisco	mat	19.56	1.14	2.29	48.25
Matses	mcf	0.00	0.00	0.00	62.25	Matukar Panau	mjk	16.53	0.93	1.92	144.11
Maung	mph	0.00	0.00	0.00	28.91	Mazandarani	mzn	0.00	0.00	0.00	1.56
Mbukushu	mhw	0.00	0.00	0.00	0.82	Mbyá Guaraní	gun	1.74	0.13	0.18	15.82
Meakambut	–	0.00	0.00	0.00	9.47	Mehri	gdq	5.11	0.28	0.63	60.46
Meitei	mni	0.00	0.00	0.00	1.59	Mele-Fila	mxe	9.46	0.54	1.17	5.61
Mewahang, Eastern	emg	0.53	0.00	0.00	31.72	Mewahang, Western	raf	17.18	0.96	1.96	115.08
Mezquital Otomi	ote	3.74	0.22	0.43	78.82	Miahuatlán Zapotec	zam	0.00	0.00	0.00	19.25
Minyag, Eastern	emq	12.49	0.73	1.42	68.05	Minyag, Western	wmg	8.06	0.46	0.99	17.17
Misak	gum	0.00	0.00	0.00	39.73	Mixtec (Family)	–	0.00	0.00	0.00	1.94
Mocho	mhc	9.59	0.56	1.17	113.57	Mocoví	moc	1.06	0.00	0.00	70.77
Mongolian, Peripheral (Jirim)	mvf	8.78	0.50	1.00	97.42	Monpa, Tawang	twm	0.00	0.00	0.00	56.29
Monsang Naga	nmh	0.61	0.00	0.00	6.27	Mor	mhz	2.57	0.17	0.28	5.72
Morori	mok	2.38	0.14	0.29	3.09	Mulao	giu	18.64	1.10	2.13	3.31
Mundabli-Mufu	boe	0.00	0.00	0.00	91.65	Mungbam	mij	1.09	0.00	0.00	194.32
Mungbam (Ngun)	mij	2.18	0.13	0.25	2.74	Mursi	muz	0.00	0.00	0.00	0.63
Murut, Bookan	bnb	14.58	0.85	1.80	33.88	Muyu	–	6.30	0.38	0.74	26.26
Myene	mye	3.44	0.21	0.41	22.03	Ménik	tnr	0.22	0.00	0.00	4.19
Naki	mff	0.49	0.00	0.00	106.91	Nalu	naj	0.00	0.00	0.00	35.33
Nalögo	nlz	2.30	0.15	0.26	68.07	Namuyi	nmy	0.00	0.00	0.00	8.75
Nar Phu	npa	0.00	0.00	0.00	2.23	Nar Phu (Nar)	npa	0.03	0.00	0.00	8.64
Nasa	pbb	0.29	0.00	0.00	27.78	Nasal	nsy	0.32	0.00	0.00	281.90
Nawuri	naw	0.00	0.00	0.00	3.03	Nda'nda'	nnz	0.73	0.00	0.00	53.38
Negidal	neg	0.40	0.00	0.00	33.77	Nenets (Tundra)	yrk	0.00	0.00	0.00	0.45
Nese	–	2.18	0.11	0.26	4.87	Ngaanyatjarra	ntj	0.00	0.00	0.00	4.56
Ngan'gityemerri	nam	1.08	0.00	0.00	9.08	Nheengatu	yrl	4.10	0.25	0.50	11.44
Nigeria Mambila	mzk	1.56	0.00	0.00	38.51	Nihali	nll	1.06	0.00	0.00	18.57
Nila	nil	0.13	0.00	0.00	17.89	Ninde	mwi	0.60	0.00	0.00	31.59
Nivaclé	cag	0.84	0.00	0.00	23.29	Nkami	nkq	8.37	0.56	1.04	15.55
Nkoroo	nkx	0.13	0.00	0.00	17.36	Noon	snf	1.58	0.00	0.00	1.60
North Ambrym	mmg	1.41	0.00	0.00	48.23	Northern Altai (Teleut)	atv	2.95	0.20	0.35	65.28
Notre	bly	4.20	0.24	0.52	56.56	Nsiteu	bko	7.89	0.51	0.83	285.94
Nuer	nus	0.00	0.00	0.00	3.96	Nyenkha	neh	0.50	0.00	0.00	1.69
Nǁng (Western)	ngh	0.00	0.00	0.00	25.08	N'kep	sku	0.07	0.00	0.00	27.36
Oinam	–	0.00	0.00	0.00	115.92	Okiek	oki	15.33	0.91	1.80	2.66
Olekha	ole	0.00	0.00	0.00	26.93	Olekha (Northeastern)	ole	0.00	0.00	0.00	77.27
Ongota	bxe	0.05	0.00	0.00	2.80	Opo	lgn	0.88	0.00	0.00	19.66
Oroha	ora	1.48	0.00	0.00	58.25	Ososo	oso	9.18	0.53	1.08	62.09
Otomi (Family)	–	0.00	0.00	0.00	29.48	Paama	pma	1.86	0.12	0.21	17.59
Pahari	phj	7.02	0.43	0.82	34.09	Pai Tavytera	pta	0.86	0.00	0.00	1.11
Paicoca	sey	13.90	0.82	1.70	0.73	Palikúr	plu	0.42	0.00	0.00	8.28
Panará	kre	0.96	0.00	0.00	13.76	Pantar, Western	lev	0.80	0.00	0.00	3.90
Papapana	ppn	6.94	0.42	0.82	45.16	Parachi	prc	0.00	0.00	0.00	0.33
Parecís	pab	1.47	0.00	0.00	2.31	Parintintin (Family)	–	26.43	1.54	3.01	112.03
Pashai (Family)	–	0.00	0.00	0.00	4.74	Paunaka	pnk	6.64	0.41	0.81	52.41
Pech	pay	9.68	0.54	1.10	4.93	Pela	bxd	1.66	0.00	0.00	7.20
Penan, Eastern	pez	0.00	0.00	0.00	0.07	Phola	ypg	16.89	0.96	1.98	313.63
Piaroa	pid	25.20	1.47	2.86	125.55	Pinghua, Southern	csp	0.00	0.00	0.00	22.67
Pite Saami	sje	0.02	0.00	0.00	66.35	Puma	pum	0.01	0.00	0.00	20.19
Pumi, Northern	pmi	0.01	0.00	0.00	49.18	Purepecha	tsz	0.64	0.00	0.00	7.55
Pushto	pus	0.00	0.00	0.00	7.98	Qabiao	laq	0.00	0.00	0.00	1.28
Qiang, Southern	qxs	3.14	0.20	0.38	108.53	Quetzaltepec Mixe	pxm	0.00	0.00	0.00	9.34
Queyu	qvy	0.73	0.00	0.00	461.57	Quichua, Loja Highland	qvj	0.00	0.00	0.00	10.14
Q'anjob'al	kjb	0.00	0.00	0.00	56.90	Rama	rma	0.00	0.00	0.00	4.12
Ratahan	rth	0.48	0.00	0.00	44.39	Rengmitca	–	0.03	0.00	0.00	2.01
Rongga	ror	0.06	0.00	0.00	1.53	Russian	rus	0.00	0.00	0.00	7.94
Saaroa	sxr	0.00	0.00	0.00	1.55	Sadu	–	5.54	0.33	0.70	9.04
Sakapulteko	quv	0.00	0.00	0.00	37.11	Salasaca Highland Quichua	qxl	0.56	0.00	0.00	5.62
San Martín Duraznos Mixtec	–	6.21	0.34	0.73	20.39	San Mateo del Mar Huave	huv	0.98	0.00	0.00	15.94
Sanapaná	spn	2.58	0.16	0.29	99.49	Saparua	spr	13.83	0.77	1.61	265.42
Sa'ban	snv	2.28	0.14	0.27	5.61	Scots	sco	0.00	0.00	0.00	10.96
Seenku	sos	3.36	0.17	0.45	109.95	Seke	skj	11.70	0.70	1.38	28.38
Sekpele	lip	0.48	0.00	0.00	29.79	Seluwasan	sws	0.00	0.00	0.00	10.10
Seluwasan (Makatian)	sws	0.63	0.00	0.00	15.07	Serili	sve	0.08	0.00	0.00	51.42
Serua	srw	0.00	0.00	0.00	11.48	Sgi Bara	jil	1.59	0.09	0.20	10.88
Shabo	sbf	0.00	0.00	0.00	0.50	Shangaji	–	0.00	0.00	0.00	4.28
Sharanahua	mcd	0.09	0.00	0.00	0.00	She	shx	0.10	0.00	0.00	2.15
Shehri	shv	1.75	0.10	0.23	30.44	Sheko (Guraferdan)	she	0.49	0.00	0.00	28.24
Sherbro	bun	2.12	0.11	0.23	9.74	Sholaga	sle	1.63	0.10	0.21	12.02
Shughni	sgh	0.00	0.00	0.00	6.70	Shuhi	sxg	0.00	0.00	0.00	72.69
Sibe	nco	0.38	0.00	0.00	0.62	Sihan	spg	1.59	0.00	0.00	18.74
Sikule	skh	0.00	0.00	0.00	30.72	Simaa (Mwenyi)	sie	0.00	0.00	0.00	3.08
Simbali	smg	4.90	0.27	0.55	84.89	Sinasina (Kere)	sst	3.91	0.24	0.46	2.81

Continued on next page

Continued from previous page

Language	ISO 639-3	Labeled (h) Train	Dev	Test	Unlabeled (h)	Language	ISO 639-3	Labeled (h) Train	Dev	Test	Unlabeled (h)
Singpho	sgp	0.00	0.00	0.00	38.37	Siona	snn	8.69	0.55	1.02	4.45
Sirionó	srq	0.00	0.00	0.00	25.12	Sirva	sbq	0.66	0.00	0.00	7.01
Ske	ske	0.08	0.00	0.00	63.73	Smar-Skad	–	0.92	0.00	0.00	62.53
Somyev	kgt	0.00	0.00	0.00	0.01	Sonsorolese	sov	17.26	1.05	2.05	30.96
Soq	mdc	0.88	0.00	0.00	9.35	Sotkena	–	0.61	0.00	0.00	32.53
Sowa	sww	0.00	0.00	0.00	5.63	Sri Lankan Portuguese Creole	–	17.21	1.14	2.09	2.23
Suki	sui	2.62	0.15	0.33	33.98	Sukur	syk	12.82	0.75	1.52	1.23
Sumi Naga	nsm	0.00	0.00	0.00	20.84	Sumtu Chin	csv	1.66	0.00	0.00	21.64
Sunwar (Surel)	suz	0.47	0.00	0.00	0.01	Supapya	bbw	0.00	0.00	0.00	0.03
Suruí	sru	0.00	0.00	0.00	51.25	Swati	ssw	13.67	0.83	1.64	103.38
Syuba	syw	2.09	0.13	0.26	23.29	Tabaq	–	16.54	0.90	2.01	14.94
Tagoi	tag	0.00	0.00	0.00	1.27	Tal	tal	0.15	0.00	0.00	1.81
Tamang	–	2.63	0.14	0.31	32.78	Tangshang Naga (Champang)	nst	3.04	0.19	0.36	56.77
Tanimuca-Letuama	tnc	0.55	0.00	0.00	17.82	Taromi, Upper	tov	0.94	0.00	0.00	5.79
Tatuyo	tav	0.49	0.00	0.00	22.22	Tehuelche	teh	1.50	0.00	0.00	17.56
Teiwa	twe	0.00	0.00	0.00	9.86	Tela-Masbuar	tvm	0.23	0.00	0.00	16.99
Tena Lowland Quichua	quw	23.23	1.35	2.79	63.14	Teribe	tfr	16.41	0.95	1.89	85.07
Terik	tec	2.06	0.11	0.26	19.36	Te'un	tve	0.25	0.00	0.00	16.02
Thado Chin (Saihriem)	tcz	9.64	0.53	1.10	135.20	Thiek	–	3.17	0.18	0.34	130.24
Tidikelt-Tuat Tamazight	–	0.01	0.00	0.00	0.00	Tikar	tik	0.00	0.00	0.00	3.17
Tinigua	tit	5.35	0.32	0.60	36.55	Tobian	tox	0.01	0.00	0.00	40.55
Tok Pisin	tpi	0.00	0.00	0.00	108.85	Tol	jic	1.35	0.00	0.00	39.27
Tom Tatar (Eushta)	–	1.25	0.00	0.00	68.85	Tonsawang	tnw	3.89	0.22	0.44	16.52
Totonac, Atlequizayan	–	0.00	0.00	0.00	0.27	Totonac, Filomena Mata-Coahuitlán	tlp	0.00	0.00	0.00	10.22
Totonac, Zongozotla	–	1.60	0.10	0.20	3.14	Totonaco del cerro Xinolatépetl	tqt	0.00	0.00	0.00	7.08
To'abaita	mlu	0.00	0.00	0.00	305.07	Tshuwau	hio	2.66	0.15	0.31	11.68
Tsimané	cas	0.00	0.00	0.00	41.99	Tsúut'ínà	srs	2.45	0.15	0.29	26.22
Tucano	tuo	0.00	0.00	0.00	25.64	Tuha	–	0.16	0.00	0.00	0.79
Tujia, Southern	tjs	4.10	0.22	0.46	0.00	Tulehu	tlu	0.00	0.00	0.00	12.80
Tunen	tvu	0.00	0.00	0.00	1.42	Turoyo	tru	2.95	0.17	0.33	40.96
Turung	try	0.00	0.00	0.00	38.04	Tuvan (Dukhan)	tyv	0.13	0.00	0.00	0.00
Tuyuca	tue	0.81	0.00	0.00	5.98	Tzeltal	tzh	69.86	4.09	8.20	182.01
Tîrî (Xaa Méa)	cir	0.00	0.00	0.00	0.73	Ubang	uba	1.23	0.00	0.00	35.04
Ukaan	kcf	2.24	0.15	0.26	26.35	Ukaan (Ikaan)	kcf	25.33	1.48	3.05	114.81
Ulwa	yla	4.19	0.27	0.49	6.01	Urarina	ura	0.00	0.00	0.00	15.46
Uripiv-Wala-Rano-Atchin (Atchin)	upv	10.98	0.64	1.33	98.03	Uru-Eu-Wau-Wau	urz	1.30	0.00	0.00	11.71
Uruangnirin	urn	8.27	0.46	0.93	131.68	Uspanteko	usp	0.00	0.00	0.00	65.36
Vamale	mkt	1.93	0.12	0.25	69.87	Vurës	msn	0.64	0.00	0.00	13.39
Vute	vut	0.00	0.00	0.00	21.43	V'ënen Taut	nmb	5.01	0.28	0.63	2.60
Waata	ssn	7.76	0.46	0.88	53.60	Wabo	wbb	1.22	0.00	0.00	28.07
Waima	rro	0.00	0.00	0.00	6.68	Waimaha	bao	3.27	0.18	0.39	4.08
Wakhi	wbl	0.00	0.00	0.00	3.68	Walman	van	0.00	0.00	0.00	3.31
Wanano	gvc	18.02	1.06	2.18	22.00	Wancho Naga	nnp	0.00	0.00	0.00	0.06
Wardaman	wrr	10.90	0.67	1.30	72.62	Warlpiri	wbp	0.00	0.00	0.00	10.90
Waskia	wsk	2.01	0.13	0.27	2.35	Wayoró	wyr	2.76	0.17	0.33	32.78
Western Algerian Amazigh	–	5.18	0.28	0.58	71.81	Western Highland Chatino	ctp	21.84	1.33	2.76	79.80
Western Tarahumara	tac	0.00	0.00	0.00	1.47	Wutunhua	wuh	0.00	0.00	0.00	12.27
Xicotepec de Juárez Totonac	too	0.00	0.00	0.00	15.68	Xârâgurè	axx	0.00	0.00	0.00	0.74
Yabong	ybo	4.66	0.30	0.60	63.42	Yakama	yak	0.00	0.00	0.00	0.02
Yakkha	ybh	1.62	0.00	0.00	1.29	Yami	tao	0.00	0.00	0.00	11.13
Yaminahua	yaa	1.54	0.09	0.18	134.09	Yan-nhangu	jay	1.70	0.09	0.21	53.38
Yaqay	jaq	0.89	0.00	0.00	14.58	Yaur	jau	0.23	0.00	0.00	11.91
Yawuno Teneyo	itr	0.54	0.00	0.00	18.45	Yei	jei	2.01	0.13	0.23	47.89
Yeresiam	ire	0.75	0.00	0.00	9.24	Yeretuar	gop	0.00	0.00	0.00	3.58
Yil	yll	0.65	0.00	0.00	174.98	Yoloxóchitl Mixtec	xty	66.49	3.87	8.01	50.38
Yopno	yut	0.11	0.00	0.00	37.82	Yucatec Maya	yua	0.54	0.00	0.00	52.26
Yucuna	ycn	9.08	0.52	1.13	133.56	Yugur, West	ybe	0.13	0.00	0.00	45.69
Yuhup	yab	0.33	0.00	0.00	60.85	Yukuben	ybl	0.00	0.00	0.00	4.97
Yura	mts	1.43	0.09	0.16	49.44	Yuracare	yuz	0.31	0.00	0.00	35.68
Zaghawa	zag	1.33	0.00	0.00	94.40	Zapotec, Yatee	zty	2.30	0.13	0.28	0.00
Zauzou	zal	0.29	0.00	0.00	129.27	Zayse	zay	11.48	0.69	1.39	42.43
Zenzontepec Chatino	czn	11.96	0.72	1.41	14.94	Zerenkel	zrn	2.31	0.17	0.27	3.85
Zok	–	18.35	1.08	2.17	49.86	Äiwoo	nfl	4.16	0.24	0.50	15.12
ǀGwi	gwj	0.00	0.00	0.00	0.00	ǁ'Amkhoe (Sasi)	huc	0.10	0.00	0.00	78.73

Table 7: Per-language hours of labeled and unlabeled speech in ELARSpeech. Labeled data are divided into train, development, and test splits, and durations below 0.01 hours are denoted as 0.00. Groups of languages within a family are denoted as "Family" in parentheses, while dialects are denoted by their dialect names in parentheses (e.g., Saru). Multilingual subsets are excluded since their durations cannot be reliably attributed to individual languages.

Language	Code	Data (H)	CER ↓		Language	Code	Data (H)	CER ↓		Language	Code	Data (H)	CER ↓	
			Mono	Multi				Mono	Multi				Mono	Multi
Masela, Central	mxz	136.8	28.39	28.31	Eibela	ail	8.9	10.35	32.72	Apurinã	apu	3.3	49.09	55.42
Jul'hoansi	ktz	79.9	42.93	53.06	Mongolian, Peripheral (Jirim)	mvf	8.8	45.09	48.78	Waimaha	bao	3.3	34.65	45.13
Gorwaa	gow	73.3	62.82	89.33	Siona	snn	8.7	34.99	32.91	Fania	fni	3.2	14.92	31.82
Tzeltal	tzh	69.9	23.20	30.05	Bastimentos Creole English	–	8.6	55.60	49.91	Kerinci (Koto Keras)	–	3.2	15.22	21.52
Yoloxóchitl Mixtec	xty	66.5	8.70	16.84	Anal	anm	8.5	37.23	43.47	Thiek	–	3.2	15.69	19.57
Isanzu	isn	49.2	75.03	83.02	Nkami	nkq	8.4	28.92	37.94	Awiakay	–	3.2	37.86	44.35
Emplawas	emw	37.5	6.86	11.87	Uruangnirin	urn	8.3	8.55	18.51	Qiang, Southern	qxs	3.1	37.95	46.72
Dargwa (Chirag)	dar	35.3	11.28	16.85	Huilliche	huh	8.2	8.24	20.10	Kinnauri, Chitkuli	cik	3.0	35.43	39.03
Kamas	xas	34.3	10.79	19.08	Kpasham	pbn	8.1	24.44	33.12	Tangshang Naga (Champang)	nst	3.0	21.73	26.19
Datooga (Asimjeeg)	tcc	27.3	13.60	23.02	Minyag, Western	wmg	8.1	24.56	29.07	Kaike	kzq	3.0	29.56	32.86
Parintintin (Family)	–	26.4	4.51	22.07	Nsiteu	bko	7.9	31.67	38.42	Turoyo	tru	3.0	12.92	18.78
Iñapari	inp	25.6	11.37	37.62	Baniwa	bwi	7.8	20.18	32.86	Ingrian	izh	2.9	8.65	12.30
Ukaan (Ikaan)	kcf	25.3	30.13	38.03	Gweno	gwe	7.8	50.31	66.57	Northern Altai (Teleut)	atv	2.9	89.55	89.15
Piaroa	pid	25.2	8.20	30.20	Jawe	jaz	7.8	14.59	24.66	Kuke	ght	2.9	58.05	59.91
Koryak	kpy	24.9	32.35	43.40	Waata	ssn	7.8	12.23	32.16	Bine	bon	2.9	56.01	60.30
Tena Lowland Quichua	quw	23.2	16.57	23.37	Dawoodi	dmk	7.6	22.87	40.62	Kundal Shahi	shd	2.8	33.35	34.47
Massep	mvs	22.5	28.81	34.47	Makuráp	mpu	7.3	17.35	24.91	Alta, Northern	aqn	2.8	17.92	21.85
Leti	lti	22.2	3.97	23.40	Dâw	kwa	7.2	81.68	68.63	Wayoró	wyr	2.8	19.54	24.23
Western Highland Chatino	ctp	21.8	27.60	36.29	Pahari	phj	7.0	26.68	41.63	Lavatbura-Lamusong	lbv	2.7	13.75	27.88
Chácobo	cao	20.9	15.93	37.22	Papapana	ppn	6.9	30.91	37.45	Garifuna	cab	2.7	31.29	38.04
Matlatzinca, San Francisco	mat	19.6	14.60	20.22	Aro	tei	6.8	12.03	15.40	Kandozi-Chapra	cbu	2.7	35.60	36.45
Calderón Highland Quichua	qud	19.1	9.59	22.42	Paunaka	pnk	6.6	26.50	32.12	Tshuwau	hio	2.7	7.84	14.06
Baram	brd	18.9	13.46	17.19	Jabutí	jbt	6.5	31.51	34.88	Tamang	–	2.6	25.43	30.38
Mulao	giu	18.6	88.67	92.21	Blablanga	blp	6.4	16.78	22.29	Gongduk	goe	2.6	15.60	20.72
Jitotoltec	–	18.6	13.31	20.84	Muyu	–	6.3	23.58	27.08	Suki	sui	2.6	32.04	37.08
Zok	–	18.4	38.35	47.55	San Martín Duraznos Mixtec	–	6.2	47.29	50.58	Curripaco	kpc	2.6	23.49	28.70
Wanano	gvc	18.0	38.05	45.53	Burarra (Gun-nartpa)	bvr	6.1	16.29	30.37	Sanapaná	spn	2.6	34.56	39.78
Dolgan	dlg	17.4	39.98	40.02	Gargarnaye	–	6.0	29.97	35.71	Mor	mhz	2.6	25.81	30.31
Kgalagadi	xkv	17.3	4.64	22.45	Cicipu	awc	6.0	32.22	41.24	Tsúut'ínà	srs	2.4	23.23	26.07
Sonsorolese	sov	17.3	29.27	86.33	Gulf Arabic	afb	6.0	22.28	29.91	Cahuilla	chl	2.4	6.33	8.64
Sri Lankan Portuguese Creole	–	17.2	16.89	22.81	Highland Popoluca	poi	5.8	17.82	23.45	Kalmyk-Oirat	xal	2.4	34.36	38.63
Mewahang, Western	raf	17.2	13.05	53.76	Chini	afi	5.7	66.23	72.94	Morori	mok	2.4	27.87	34.61
Phola	ypg	16.9	28.71	40.76	Cofán	con	5.7	26.48	33.99	Hruso	hru	2.4	14.85	19.41
Tabaq	–	16.5	24.87	82.17	Bunak	bfn	5.6	68.18	49.78	Arabic, Judeo-Iraqi	yhd	2.4	16.18	21.80
Matukar Panau	mjk	16.5	20.83	44.58	Ghanongga	ghn	5.6	8.82	11.05	Zerenkel	zrn	2.3	22.06	24.33
Teribe	tfr	16.4	34.58	38.51	Sadu	–	5.5	124.35	107.87	Zapotec, Yatee	zty	2.3	58.17	65.07
Ibatan	ivb	16.2	20.26	26.39	Ambel	wgo	5.5	22.84	29.34	Guernésiais	nrf	2.3	38.98	36.06
Kam	kdx	16.0	28.01	42.49	Emae	mmw	5.5	14.23	17.19	Nalögo	nlz	2.3	20.72	27.73
Okiek	oki	15.3	18.30	25.43	Akha	ahk	5.5	14.92	19.63	Sa'ban	snv	2.3	10.65	15.54
K'iche'	quc	15.3	18.59	23.45	Bum	bmv	5.5	10.40	27.01	Enxet	enx	2.3	11.36	14.49
Konomala	koa	15.1	4.10	8.32	Karagas	kim	5.4	29.64	38.39	Ukaan	kcf	2.2	15.88	20.54
Belait	beg	14.6	25.80	50.40	Dzardzongke	–	5.4	15.70	19.63	Laz	lzz	2.2	7.90	10.89
Chimborazo Highland Quichua	qug	14.6	10.42	25.86	Tinigua	tit	5.3	27.87	31.81	Nese	–	2.2	30.50	33.47
Murut, Bookan	bnb	14.6	61.59	64.90	Western Algerian Amazigh	–	5.2	24.24	30.58	Kichwa de Chibuleo	–	2.2	9.57	10.56
Arapaho	arp	14.4	23.88	33.21	Mehri	gdq	5.1	21.86	30.80	Mungbam (Ngun)	mij	2.2	88.31	74.66
Paicoca	sey	13.9	17.84	23.49	V'ënen Taut	nmb	5.0	20.98	31.32	Sherbro	bun	2.1	103.07	104.73
Imbabura Highland Quichua	qvi	13.9	6.88	17.25	Animere	anf	5.0	38.98	42.29	Bih	ibh	2.1	18.04	21.83
Saparua	spr	13.8	26.39	33.78	Heiyoho	auk	4.9	18.38	29.10	Syuba	syw	2.1	26.06	30.46
Swati	ssw	13.7	32.84	36.03	Simbali	smg	4.9	104.50	102.67	Datooga	tcc	2.1	16.37	23.58
E'ñapa Woromaipu	pbh	13.4	48.45	69.68	Yabong	ybo	4.7	11.06	13.09	Terik	tec	2.1	34.02	36.71
Even	eve	12.8	5.07	20.77	Camsá	kbh	4.6	24.12	27.31	Jowshaqani	–	2.0	20.98	23.81
Sukur	syk	12.8	14.84	19.32	Maragus	mrs	4.5	14.88	20.54	Waskia	wsk	2.0	5.99	9.71
Chiapas Zoque	–	12.7	17.11	23.37	Burarra	bvr	4.4	20.48	25.04	Yei	jei	2.0	48.78	53.37
Lakurumau	lxm	12.6	15.64	19.21	Kol	ekl	4.4	15.36	23.05	Kalmyk-Oirat (Durvud)	xal	1.9	36.05	37.92
Minyag, Eastern	emq	12.5	19.84	44.65	Kwa	kwb	4.4	35.94	44.22	Vamale	mkt	1.9	30.94	45.38
Zenzontepec Chatino	czn	12.0	10.73	16.34	Fungwa	ula	4.3	20.65	27.53	Ayoreo	ayo	1.9	50.45	54.22
Seke	skj	11.7	28.53	33.34	Hadza	hts	4.2	36.38	83.46	Paama	pma	1.9	71.99	66.92
Mafea	mkv	11.6	10.80	17.00	Notre	bly	4.2	19.03	44.26	Awutu	afu	1.8	36.16	40.04
Zayse	zay	11.5	23.23	36.58	Ulwa	yla	4.2	17.33	21.08	Mae	mme	1.8	19.35	23.08
Kelabit	kzi	11.5	8.17	12.29	Äiwoo	nfl	4.2	16.47	23.52	Kangjia	kxs	1.8	24.43	28.68
Araona	aro	11.4	23.43	33.28	Kakabe	kke	4.1	19.44	26.22	Shehri	shv	1.8	23.55	30.53
Uripiv-Wala-Rano-Atchin (Atchin)	upv	11.0	4.87	19.29	Guató	gta	4.1	14.81	21.62	Ersu	ers	1.7	15.90	19.65
Abui	abz	11.0	15.90	38.20	Cora (Family)	–	4.1	30.61	35.64	Barein	bva	1.7	23.58	27.89
Wardaman	wrr	10.9	30.26	38.56	Nheengatu	yrl	4.1	12.42	19.67	Mbyá Guaraní	gun	1.7	26.18	31.27
Akpes	ibe	10.8	20.46	27.87	Tujia, Southern	tjs	4.1	20.16	24.02	Yan-nhangu	jay	1.7	13.07	15.41
Khoibu Naga	nkb	10.5	34.21	41.00	Kula	tpg	4.0	25.60	29.55	Angaité	aqt	1.6	16.79	22.73
Caijia	–	10.0	28.35	37.53	Kaapor	urb	4.0	18.44	27.69	Sholaga	sle	1.6	10.96	15.78
Chimalapa Zoque	zoh	9.8	14.94	18.18	Lelepa	lpa	3.9	28.56	33.26	Chiquitano (Bésiro)	cax	1.6	6.35	10.21
Pech	pay	9.7	28.73	36.71	Enawené-Nawé	unk	3.9	27.52	63.78	Júma	jua	1.6	1.71	4.25
Thado Chin (Saihriem)	tcz	9.6	11.75	32.43	Sinasina (Kere)	sst	3.9	22.53	27.43	Totonac, Zongozotla	–	1.6	24.79	22.57
Mocho	mhc	9.6	25.27	29.85	Tonsawang	tnw	3.9	20.78	24.39	Sgi Bara	jil	1.6	14.38	17.39
Gadaba, Bodo	gbj	9.5	16.82	25.82	Mezquital Otomi	ote	3.7	55.23	62.92	Brem	buq	1.6	15.40	18.19
Mele-Fila	mxe	9.5	11.37	16.70	Guarayu	gyr	3.6	28.13	33.24	Cabiyarí	cbb	1.6	49.77	59.15
Bati	btc	9.3	23.44	31.61	Jejueo	jje	3.6	41.10	36.54	Ibibio	ibb	1.6	55.32	59.13
Bandial	bqj	9.2	26.21	35.52	Avatime	avn	3.5	40.71	47.41	Yaminahua	yaa	1.5	2.94	6.19
Ososo	oso	9.2	37.38	43.63	Myene	mye	3.4	25.48	33.86	Yura	mts	1.4	20.62	25.31
Banam Bay	vrt	9.1	32.16	39.94	Kakataibo-Kashibo	cbr	3.4	23.16	27.63	Bongu	bpu	1.4	18.32	18.92
Yucuna	ycn	9.1	27.39	43.21	Seenku	sos	3.4	45.11	50.72					

Table 8: Character Error Rate (CER) of Whisper on the ELARSpeech test set across all 233 languages. Mono denotes a monolingual Whisper model fine-tuned separately for each language; Multi denotes a single multilingual Whisper model fine-tuned on all languages. Both are evaluated on the same test utterances. Languages are sorted by training-set duration and read down each column. Data (H) denotes the amount of the human-annotated training data. Languages without an ISO 639-3 code are marked "–".

Language	Code	Data (H)	Reference (Ground Truth)		OmniVoice		
			CER↓	UTMOS↑	CER↓	UTMOS↑	SIM-O↑
Masela, Central	mxz	136.8	28.39	2.660	12.87	2.786	0.769
Jul'hoansi	ktz	79.9	42.93	2.072	46.39	2.635	0.526
Gorwaa	gow	73.3	62.82	2.220	70.45	2.463	0.538
Tzeltal	tzh	69.9	23.20	2.188	12.93	2.603	0.692
Yoloxóchitl Mixtec	xty	66.5	8.70	2.692	4.83	2.817	0.829
Isanzu	isn	49.2	75.03	2.482	80.54	2.170	0.402
Emplawas	emw	37.5	6.86	2.703	5.92	2.810	0.752
Dargwa (Chirag)	dar	35.3	11.28	2.149	3.53	2.534	0.830
Kamas	xas	34.3	10.79	2.124	13.43	2.578	0.526
Datooga (Asimjeeg)	tcc	27.3	13.60	2.497	13.34	2.626	0.762
Parintintin (Family)	–	26.4	4.51	2.046	6.12	2.436	0.684
Iñapari	inp	25.6	11.37	2.517	14.97	2.752	0.698
Ukaan (Ikaan)	kcf	25.3	30.13	2.493	32.71	2.618	0.668
Piaroa	pid	25.2	8.20	2.484	13.14	2.669	0.715
Koryak	kpy	24.9	32.35	2.264	22.73	2.551	0.738
Tena Lowland Quichua	quw	23.2	16.57	2.273	11.81	2.653	0.717
Massep	mvs	22.5	28.81	1.993	7.08	2.312	0.651
Leti	lti	22.2	3.97	2.234	4.21	2.608	0.657
Western Highland Chatino	ctp	21.8	27.60	2.517	17.62	2.753	0.744
Chácobo	cao	20.9	15.93	2.451	15.62	2.743	0.732
Matlatzinca, San Francisco	mat	19.6	14.60	2.415	8.71	2.704	0.708
Calderón Highland Quichua	qud	19.1	9.59	2.003	10.63	2.689	0.610
Baram	brd	18.9	13.46	2.483	6.62	2.665	0.751
Mulao	giu	18.6	88.67	2.307	84.43	2.434	0.684
Jitotoltec	–	18.6	13.31	3.000	10.20	3.110	0.810
Zok	–	18.4	38.35	1.974	38.71	2.437	0.696
Wanano	gvc	18.0	38.05	1.873	71.97	2.653	0.603
Dolgan	dlg	17.4	39.98	2.623	34.70	2.796	0.802
Kgalagadi	xkv	17.3	4.64	2.221	7.39	2.382	0.678
Sonsorolese	sov	17.3	29.27	2.433	72.01	2.699	0.568
Sri Lankan Portuguese Creole	–	17.2	16.89	2.413	7.00	2.774	0.785
Mewahang, Western	raf	17.2	13.05	2.295	25.19	2.586	0.665
Phola	ypg	16.9	28.71	1.868	24.64	2.211	0.596
Tabaq	–	16.5	24.87	2.334	62.02	2.792	0.584
Matukar Panau	mjk	16.5	20.83	2.397	51.08	2.773	0.533
Teribe	tfr	16.4	34.58	2.229	16.73	2.604	0.727
Ibatan	ivb	16.2	20.26	2.303	5.27	2.620	0.662
Kam	kdx	16.0	28.01	2.282	37.19	2.648	0.700
Okiek	oki	15.3	18.30	2.719	11.48	2.866	0.745
K'iche'	quc	15.3	18.59	1.994	8.70	2.192	0.751
Konomala	koa	15.1	4.10	2.392	3.38	2.707	0.752
Belait	beg	14.6	25.80	1.945	20.87	2.520	0.705
Chimborazo Highland Quichua	qug	14.6	10.42	2.170	16.50	2.650	0.634
Murut, Bookan	bnb	14.6	61.59	2.415	69.76	2.771	0.670
Arapaho	arp	14.4	23.88	1.592	10.56	2.231	0.701
Paicoca	sey	13.9	17.84	2.415	5.71	2.666	0.784
Imbabura Highland Quichua	qvi	13.9	6.88	2.000	9.58	2.528	0.613
Saparua	spr	13.8	26.39	1.828	26.06	2.307	0.571
Swati	ssw	13.7	32.84	2.444	26.37	2.749	0.749
E'ñapa Woromaipu	pbh	13.4	48.45	2.425	21.71	2.682	0.659
Even	eve	12.8	5.07	1.794	24.06	2.486	0.712
Sukur	syk	12.8	14.84	2.237	6.40	2.483	0.713
Chiapas Zoque	–	12.7	17.11	2.634	11.79	2.722	0.748
Lakurumau	lxm	12.6	15.64	2.528	7.93	2.766	0.774
Minyag, Eastern	emq	12.5	19.84	2.422	27.66	2.701	0.686
Zenzontepec Chatino	czn	12.0	10.73	2.315	5.94	2.474	0.730
Seke	skj	11.7	28.53	1.920	17.66	2.353	0.721
Mafea	mkv	11.6	10.80	2.413	8.78	2.717	0.804
Zayse	zay	11.5	23.23	2.275	25.19	2.622	0.648
Kelabit	kzi	11.5	8.17	2.029	3.56	2.470	0.721
Araona	aro	11.4	23.43	1.976	16.65	2.155	0.714
Uripiv-Wala-Rano-Atchin (Atchin)	upv	11.0	4.87	2.187	6.10	2.643	0.699
Abui	abz	11.0	15.90	1.861	35.19	2.402	0.577
Wardaman	wrr	10.9	30.26	2.076	16.46	2.584	0.682
Akpes	ibe	10.8	20.46	2.117	20.24	2.514	0.651
Khoibu Naga	nkb	10.5	34.21	2.134	20.37	2.583	0.663
Bum	bmv	5.5	10.40	1.715	16.85	2.165	0.589
Karagas	kim	5.4	29.64	1.905	12.75	2.293	0.781
Dzardzongke	–	5.4	15.70	2.404	7.95	2.796	0.712
Tinigua	tit	5.3	27.87	2.135	20.19	2.219	0.693
Western Algerian Amazigh	–	5.2	24.24	2.511	12.50	2.806	0.701
Mehri	gdq	5.1	21.86	2.360	20.34	2.674	0.705
V'ënen Taut	nmb	5.0	20.98	2.334	13.47	2.618	0.718
Animere	anf	5.0	38.98	2.071	38.62	2.308	0.655
Heiyoho	auk	4.9	18.38	2.211	15.32	2.390	0.659
Simbali	smg	4.9	104.50	2.055	74.13	2.172	0.596
Yabong	ybo	4.7	11.06	2.600	5.53	2.765	0.839
Camsá	kbh	4.6	24.12	2.258	13.90	2.701	0.839
Maragus	mrs	4.5	14.88	2.155	7.37	2.557	0.728
Burarra	bvr	4.4	20.48	2.115	6.12	2.738	0.709
Kol	ekl	4.4	15.36	2.251	12.09	2.699	0.696
Kwa	kwb	4.4	35.94	1.989	23.53	2.453	0.711
Fungwa	ula	4.3	20.65	2.529	14.51	2.961	0.718
Hadza	hts	4.2	36.38	2.339	76.48	2.369	0.509
Notre	bly	4.2	19.03	2.025	16.27	2.639	0.606
Ulwa	yla	4.2	17.33	2.169	8.98	2.397	0.755
Äiwoo	nfl	4.2	16.47	2.586	10.00	2.829	0.686
Kakabe	kke	4.1	19.44	2.070	11.14	2.757	0.741
Guató	gta	4.1	14.81	2.210	11.78	2.525	0.749
Cora (Family)	–	4.1	30.61	2.628	23.02	2.866	0.774
Nheengatu	yrl	4.1	12.42	1.901	13.21	2.408	0.807
Tujia, Southern	tjs	4.1	20.16	2.548	15.15	2.931	0.773
Kula	tpg	4.0	25.60	2.224	12.07	2.458	0.774
Kaapor	urb	4.0	18.44	2.594	10.85	2.669	0.734
Lelepa	lpa	3.9	28.56	2.437	22.51	2.661	0.736
Enawené-Nawé	unk	3.9	27.52	2.309	50.58	2.607	0.676
Sinasina (Kere)	sst	3.9	22.53	2.670	16.24	2.748	0.733
Tonsawang	tnw	3.9	20.78	2.863	18.37	2.856	0.678
Mezquital Otomi	ote	3.7	–	–	–	–	–
Guarayu	gyr	3.6	28.13	2.034	15.65	2.689	0.708
Jejueo	jje	3.6	41.10	1.858	25.62	2.214	0.625
Avatime	avn	3.5	40.71	2.278	31.72	2.370	0.648
Myene	mye	3.4	25.48	2.044	28.57	2.388	0.684
Kakataibo-Kashibo	cbr	3.4	23.16	2.646	15.64	2.719	0.757
Seenku	sos	3.4	45.11	2.502	30.46	2.752	0.758
Apurinã	apu	3.3	49.09	1.586	62.46	1.894	0.591
Waimaha	bao	3.3	34.65	1.957	27.69	2.297	0.655
Fania	fni	3.2	14.92	2.120	15.49	2.438	0.639
Kerinci (Koto Keras)	–	3.2	15.22	2.482	3.73	2.813	0.797
Thiek	–	3.2	15.69	2.168	7.52	2.457	0.709
Awiakay	–	3.2	37.86	1.970	15.21	2.402	0.587
Qiang, Southern	qxs	3.1	37.95	2.478	71.29	2.708	0.614
Kinnauri, Chitkuli	cik	3.0	35.43	2.073	22.47	2.550	0.725
Tangshang Naga (Champang)	nst	3.0	21.73	2.325	6.91	2.771	0.760
Kaike	kzq	3.0	29.56	2.383	16.95	2.610	0.736
Turoyo	tru	3.0	12.92	1.953	10.81	2.440	0.692
Ingrian	izh	2.9	8.65	2.402	6.28	2.794	0.746
Northern Altai (Teleut)	atv	2.9	89.55	2.339	81.86	2.515	0.764
Kuke	ght	2.9	58.05	1.980	34.46	2.280	0.636
Bine	bon	2.9	56.01	1.980	57.70	2.475	0.516
Kundal Shahi	shd	2.8	33.35	2.477	23.57	2.967	0.824
Alta, Northern	aqn	2.8	17.92	2.423	15.69	2.594	0.763
Wayoró	wyr	2.8	19.54	2.397	10.30	2.426	0.715
Lavatbura-Lamusong	lbv	2.7	13.75	2.090	12.73	2.772	0.731
Garifuna	cab	2.7	31.29	2.439	20.58	2.731	0.696
Kandozi-Chapra	cbu	2.7	35.60	2.130	17.59	2.595	0.778
Tshuwau	hio	2.7	7.84	2.723	14.54	2.828	0.712
Tamang	–	2.6	25.43	2.280	18.29	2.546	0.713
Gongduk	goe	2.6	15.60	2.630	9.58	2.791	0.709
Suki	sui	2.6	32.04	2.284	9.82	2.537	0.703
Curripaco	kpc	2.6	23.49	2.276	13.46	2.616	0.739
Sanapaná	spn	2.6	34.56	1.881	45.66	2.304	0.544

Continued on next page

Continued from previous page

Language	Code	Data (H)	Reference (Ground Truth)		OmniVoice			Language	Code	Data (H)	Reference (Ground Truth)		OmniVoice		
			CER↓	UTMOS↑	CER↓	UTMOS↑	SIM-O↑				CER↓	UTMOS↑	CER↓	UTMOS↑	SIM-O↑
Caijia	–	10.0	28.35	2.789	27.72	2.985	0.691	Mor	mhz	2.6	25.81	2.440	22.86	2.634	0.648
Chimalapa Zoque	zoh	9.8	14.94	2.614	6.00	2.895	0.812	Tsúut'ínà	srs	2.4	23.23	2.544	21.88	2.635	0.726
Pech	pay	9.7	28.73	2.060	21.84	2.566	0.721	Cahuilla	chl	2.4	6.33	3.190	5.30	3.018	0.807
Thado Chin (Saihriem)	tcz	9.6	11.75	2.111	13.81	2.305	0.603	Kalmyk-Oirat	xal	2.4	34.36	1.617	17.75	2.401	0.731
Mocho	mhc	9.6	25.27	2.386	25.07	2.425	0.715	Morori	mok	2.4	27.87	2.079	20.12	2.413	0.682
Gadaba, Bodo	gbj	9.5	16.82	2.013	13.83	2.464	0.668	Hruso	hru	2.4	14.85	2.734	12.95	3.010	0.776
Mele-Fila	mxe	9.5	11.37	2.804	7.37	3.055	0.785	Arabic, Judeo-Iraqi	yhd	2.4	16.18	2.414	10.81	2.774	0.698
Bati	btc	9.3	23.44	2.311	19.63	2.630	0.662	Zerenkel	zrn	2.3	22.06	2.456	11.90	2.880	0.787
Bandial	bqj	9.2	26.21	2.065	16.88	2.376	0.668	Zapotec, Yatee	zty	2.3	58.17	2.385	63.97	2.535	0.678
Ososo	oso	9.2	37.38	2.355	27.70	2.738	0.783	Guernésiais	nrf	2.3	38.98	2.113	31.86	2.497	0.723
Banam Bay	vrt	9.1	32.16	2.145	22.20	2.430	0.643	Nalögo	nlz	2.3	20.72	2.333	14.35	2.657	0.704
Yucuna	ycn	9.1	27.39	2.633	11.72	2.979	0.764	Sa'ban	snv	2.3	10.65	2.729	7.90	2.797	0.763
Eibela	ail	8.9	10.35	1.983	19.84	2.427	0.601	Enxet	enx	2.3	11.36	2.570	6.80	2.692	0.715
Mongolian, Peripheral (Jirim)	mvf	8.8	45.09	2.203	34.77	2.455	0.626	Ukaan	kcf	2.2	15.88	2.441	19.65	2.712	0.706
Siona	snn	8.7	34.99	2.267	22.29	2.558	0.783	Laz	lzz	2.2	7.90	2.852	4.46	2.834	0.799
Bastimentos Creole English	–	8.6	55.60	2.607	32.90	2.984	0.594	Nese	–	2.2	30.50	2.332	13.87	2.615	0.717
Anal	anm	8.5	37.23	2.036	20.72	2.623	0.594	Kichwa de Chibuleo	–	2.2	9.57	1.531	4.11	1.996	0.719
Nkami	nkq	8.4	28.92	1.881	21.35	2.517	0.641	Mungbam (Ngun)	mij	2.2	88.31	2.001	49.64	2.505	0.596
Uruangnirin	urn	8.3	8.55	2.292	12.10	2.602	0.694	Sherbro	bun	2.1	103.07	2.240	94.36	2.622	0.675
Huilliche	huh	8.2	8.24	2.391	8.12	2.785	0.716	Bih	ibh	2.1	18.04	2.320	9.92	2.618	0.778
Kpasham	pbn	8.1	24.44	2.865	19.38	3.086	0.659	Syuba	syw	2.1	26.06	2.274	19.58	2.572	0.673
Minyag, Western	wmg	8.1	24.56	2.538	12.15	2.777	0.747	Datooga	tcc	2.1	16.37	1.819	11.51	2.449	0.683
Nsiteu	bko	7.9	31.67	2.028	23.69	2.348	0.529	Terik	tec	2.1	34.02	2.207	28.07	2.701	0.603
Baniwa	bwi	7.8	20.18	2.402	10.49	2.775	0.761	Jowshaqani	–	2.0	20.98	2.477	10.19	2.827	0.777
Gweno	gwe	7.8	50.31	2.325	44.95	2.549	0.717	Waskia	wsk	2.0	5.99	2.203	3.83	2.612	0.797
Jawe	jaz	7.8	14.59	2.204	9.72	2.539	0.735	Yei	jei	2.0	48.78	2.479	39.94	2.654	0.671
Waata	ssn	7.8	12.23	2.176	14.78	2.507	0.657	Kalmyk-Oirat (Durvud)	xal	1.9	36.05	1.715	22.89	2.289	0.632
Dawoodi	dmk	7.6	22.87	1.939	24.26	2.326	0.851	Vamale	mkt	1.9	30.94	2.156	21.83	2.484	0.678
Makuráp	mpu	7.3	17.35	2.171	10.96	2.427	0.759	Ayoreo	ayo	1.9	50.45	0.291	22.73	1.604	0.329
Dâw	kwa	7.2	81.68	2.096	65.31	2.354	0.729	Paama	pma	1.9	71.99	2.360	72.38	2.475	0.507
Pahari	phj	7.0	26.68	2.160	29.04	2.450	0.692	Awutu	afu	1.8	36.16	2.731	24.53	2.943	0.763
Papapana	ppn	6.9	30.91	2.354	25.75	2.792	0.716	Mae	mme	1.8	19.35	2.514	11.41	2.670	0.745
Aro	tei	6.8	12.03	2.254	7.71	2.401	0.819	Kangjia	kxs	1.8	24.43	2.389	12.28	2.744	0.801
Paunaka	pnk	6.6	26.50	2.300	11.83	2.873	0.658	Shehri	shv	1.8	23.55	2.565	23.02	2.802	0.726
Jabutí	jbt	6.5	31.51	2.365	23.17	2.449	0.691	Ersu	ers	1.7	15.90	2.547	13.21	2.801	0.718
Blablanga	blp	6.4	16.78	2.497	23.38	2.744	0.740	Barein	bva	1.7	23.58	2.710	16.67	2.869	0.725
Muyu	–	6.3	23.58	2.269	15.84	2.513	0.677	Mbyá Guaraní	gun	1.7	26.18	2.428	20.01	2.792	0.815
San Martín Duraznos Mixtec	–	6.2	47.29	2.257	31.72	2.637	0.735	Yan-nhangu	jay	1.7	13.07	2.541	6.49	2.862	0.760
Burarra (Gun-nartpa)	bvr	6.1	16.29	2.338	14.40	2.639	0.671	Angaité	aqt	1.6	16.79	2.179	13.06	2.467	0.769
Gargarnaye	–	6.0	29.97	2.193	18.49	2.509	0.717	Sholaga	sle	1.6	10.96	1.948	17.31	2.019	0.711
Cicipu	awc	6.0	32.22	2.571	29.94	2.721	0.677	Chiquitano (Bésiro)	cax	1.6	6.35	2.305	76.02	2.615	0.574
Gulf Arabic	afb	6.0	22.28	2.147	13.49	2.528	0.748	Júma	jua	1.6	1.71	1.713	5.15	2.108	0.773
Highland Popoluca	poi	5.8	17.82	2.415	11.37	2.556	0.756	Totonac, Zongozotla	–	1.6	–	–	–	–	–
Chini	afi	5.7	66.23	2.111	73.65	2.300	0.472	Sgi Bara	jil	1.6	14.38	2.201	10.67	2.291	0.722
Cofán	con	5.7	26.48	1.920	23.33	2.358	0.686	Brem	buq	1.6	15.40	2.149	11.37	2.615	0.765
Bunak	bfn	5.6	68.18	2.471	54.48	2.784	0.666	Cabiyarí	cbb	1.6	49.77	1.963	44.80	2.071	0.705
Ghanongga	ghn	5.6	8.82	2.475	4.65	2.722	0.778	Ibibio	ibb	1.6	55.32	1.699	39.76	2.679	0.675
Sadu	–	5.5	124.35	2.426	112.49	2.621	0.556	Yaminahua	yaa	1.5	2.94	2.213	2.97	2.397	0.714
Ambel	wgo	5.5	22.84	2.065	13.38	2.579	0.718	Yura	mts	1.4	20.62	2.113	15.52	2.355	0.677
Emae	mmw	5.5	14.23	2.416	11.52	2.710	0.797	Bongu	bpu	1.4	18.32	2.385	7.40	2.536	0.749
Akha	ahk	5.5	14.92	1.996	11.94	2.213	0.785								

Table 9: CER, UTMOS, and speaker similarity (SIM-O) of the multilingual OmniVoice model on the ELARSpeech test set. UTMOS and OmniVoice results for Mezquital Otomi and Totonac, Zongozotla are unavailable because no test samples remain after SNR/C50 filtering. Languages are sorted by training-set duration and read down each column. Data (H) denotes the hours of human-annotated training data. Languages without an ISO 639-3 code are marked "–". Reference CER and UTMOS were measured with a monolingual Whisper model and UTMOS-v2, respectively, on ground-truth speech.