

Transfiver: Human–AI Co-Inference through a Shared Editable State

Minji Park, Seunghyun Yoon, Hyuk Lim

Korea Institute of Energy Technology (KENTECH)

{minjipark, syoon, hlim}@kentech.ac.kr

September 4, 2026

Abstract

Long-term human–AI interaction is difficult because the information that guides inference is updated implicitly by the model and is not directly inspectable or controllable by the user. We introduce the TRANSPARENT Framework for Interactive, Verifiable, Editable Representation (Transfiver), an architecture for human–AI co-inference through a shared editable state. Its central idea is that interaction-specific information is maintained in a single persistent state S_t that both the model and the human update.

Transfiver distinguishes two modes of state evolution. In an implicit stream update, the model interprets ongoing interaction and decides whether new information revises an existing state item or creates a new one. In an explicit directed edit, a human inspects and modifies an addressed item. Both act on the same underlying state, so a human correction changes the state that subsequent computation reads, rather than adding another instruction or separate record.

The architecture separates shared parameters θ , learned before ordinary use, from the persistent state S_t , which evolves during deployment without parameter retraining. Extending Transfiver to rich natural-language, relational, and large-scale shared states remains open.

1 Introduction

When an assistant is used over months, some of what it was told stops being true. A meeting moves, a password is retired, a rule that held for one project is not meant for another. Somebody has to decide that an old entry no longer counts, and the question this paper asks is who that somebody is.


The prevailing answer is the model. Recent work trains agents to keep the current value of a changed fact and to stop answering from stale ones, and reports that this is both a real failure and a trainable one [17]. The person is the one who knows that the meeting moved, and the correction they make should be an operation on the state the assistant actually reads, not another sentence added to a context window that a later turn may reassemble without it.

This requires the memory a user sees and edits to be the same state S_t the model computes from. Transfiver makes that identity the architectural requirement: interaction-specific information lives in one persistent state that both parties update, implicitly when the model folds an ongoing interaction into it, explicitly when a person retires, restores or rewrites an addressed entry. Omitting an entry when assembling one turn’s context looks like retiring it, and on that turn the model sees exactly the same lines. The difference appears on the next turn, when the omitted entry returns and the retired one does not.

When humans interact with a language model over a long time, it accumulates corrections, obsolete beliefs, user-specific meanings, unresolved conflicts, evidence of use, and decisions that may later be revived. Transformer activations encode the current sequence [22]; recurrent and state-space models compress the past into latent state [10]; retrieval systems preserve explicit records outside the generator [13, 6]; and agent frameworks move records between memory tiers [16]. These approaches do not guarantee that the state a user sees and edits is the only state the model keeps and uses for future answers.

A user may commit an edit, but another hidden computational path may still carry the old information. Transfiver requires:

A permitted failure: two separate states



Transfiver: one state




Figure 1: Many current designs permit the state a person can inspect and edit to remain separate from the state that produces the next output, so a correction need not take effect. Transfiver binds them into one state: editing what you see edits the computation, and restoring it restores the computation.

Memory, reasoning, and output are not divided. The state underlying what a person sees and corrects is the state from which the system computes, updates, and answers.

Transfiver is intended to operate at the same architectural level as a Transformer or a state-space model. It may also be embedded within a larger system, provided that Transfiver remains the sole persistent interaction-specific state through which prior interaction can affect future computation. Trained on language, Transfiver may become a language model. Applied to an information environment, the same architecture may become the interface through which that environment is read and changed.

Contributions.

1. We introduce Transfiver’s information model and its human-facing renderings, and specify the distinctions that the state must preserve.
2. We turn “memory, reasoning, and output in one living state” into a history-sufficiency and causal-intervention contract that distinguishes Transfiver from a memory attachment, a post-hoc explanation, or a display the computation can ignore.
3. We provide a small working implementation that tests some of Transfiver’s core principles. It is not intended to represent the full Transfiver architecture.
4. We show, on an earlier persistent-state implementation, in a single held-out evaluation with controls fixed in advance, that one frozen persistent state retains enough temporal structure to support four disagreeing read rules, and that replacing the named rule or reference redirects the readout accordingly.

2 Related Work

We group prior work by the question it answers about a persistent state: who writes it, who may read it, and whether it is the only path from past interaction to future computation.

Self-updating computational memory. Neural Turing Machines and memory-augmented networks learn to address external memory [9, 18]. Fast weights, test-time training, and Titans add state that changes on a faster time scale than ordinary parameters [3, 21, 4]. Transfiver differs in requiring its persistent state to be directly inspectable and editable, while also serving as the state used for computation.

Transformers retain token-level context through attention [22]; selective state-space models learn compact recurrent dynamics with strong efficiency and sequence performance [10]. Transfiver’s additional requirement is that persistent, addressable, human-viewed state be the causal computational substrate across interactions.

State-first agent memory. Recent work measures the same failure we target from the model’s side. Supersede shows that when an agent maintains a bounded self-managed memory instead of full context, accuracy on questions about changed facts drops from .92 to .77, and that the gap widens with conversation length rather than with compression ratio; it releases a reinforcement-learning environment that rewards answering from the current value and penalizes stale ones, and reports that fine-tuning nearly doubles held-out accuracy [17]. That line of work makes the model a better custodian of its own memory. Transfiver takes the complementary position: the model may judge which stored item an incoming event concerns, but the authority to retire, restore and correct that item belongs to the user, and the item the user acts on is the item subsequent computation reads. Supersede does not expose the memory for human inspection or editing, and does not test intervention, rollback, or save-restore.

k NN language models, RAG, and RETRO combine a generator with explicit external records [11, 13, 6]; MemGPT manages memory tiers around an LLM [16]; and Larimar adds an editable episodic memory that supports one-shot knowledge updates without retraining the language model for each edit [7]. Memory Layers at Scale is closer in spirit, making a large addressable key-value store part of the forward computation rather than a retrieval sidecar [5]. Transfiver treats the separation between the readable store and the computing model as the object of study, and requires the readable state to be the sole persistent interaction-specific state on which future computation depends.

ROME and MEMIT intervene on factual associations in Transformer parameters [14, 15]. Transfiver instead separates slowly learned shared dynamics θ from an online, user- or task-specific S . This avoids gradient editing during ordinary use, while imposing the stronger burden that state edits be causally localized and serializable.

Shared mental models in human-agent teams. Teaming research has long argued that effective human-agent collaboration depends on sufficiently aligned internal representations of the task, the equipment, the team members and their roles, and that these representations are what let one party anticipate the other. Scheutz, DeLoach and Adams [19] observe that most of this literature quantifies the benefit of such alignment while leaving open the data structures and processes that would operationalize it, and propose a formal framework to fill that gap. Transfiver can be read as one such operationalization at the level of a single persistent computational state, with two differences worth stating. Alignment here is not achieved by copying one party’s model into the other, and the state is not merely a shared view: it is the object both parties write to and the object the model reads from.

States a person can see, and states a person can change. Concept bottleneck models let people edit predicted concepts and propagate the change to outputs [12]. Concept Bottleneck Memory Models retain past interventions and learn when to reapply them [20], making them a particularly close comparison for persistent human correction. Self-explaining networks build faithfulness into model design [1]. Transfiver shares the commitment to intervention and to faithfulness-by-design over post-hoc visualization. It differs by making the faithful, intervenable object *persistent and dynamically evolving* across interactions, and by requiring all persistent interaction-specific information that can affect future output to remain in that state. Causal-abstraction work supplies a stricter language for testing whether an interpreted high-level variable has the claimed causal role under interchange interventions [8]; Transfiver’s view/edit contract should ultimately be evaluated at that standard rather than by decoding alone.

Reading an item’s current standing by combining its own history with activation from currently active neighbors is not new; it is the core of ACT-R’s declarative memory [2]. Transfiver’s claim is architectural: the persistent state that supports such readings is exposed to the user and is also the state on which future computation depends, so changing that state changes future behavior.

Evaluation. LongMemEval identifies extraction, multi-session reasoning, temporal reasoning, knowledge update, and abstention as central long-term-memory abilities [23]. Transfiver adds architectural audits: whether the state that appears correct is actually the state the system uses, and whether correction takes effect without parameter changes.

3 Transfiver Architecture: How Information Lives in Transfiver

3.1 One folder is not enough

In Transfiver, an item is not limited to a single folder or context. The same item can belong to several projects without being copied. Items that look similar are not necessarily related, while very different items may be strongly connected by a real event or relationship. For example, a bank password and a server password are lexically similar, but should not be merged, whereas a particular server and its random password may be lexically distant but joined by a specific event. Transfiver therefore represents both what an item means and how it is connected to other items.

3.2 A full conceptual state

A mature Transfiver realization may use

$$S_t = (\{s_{t,i}\}_{i=1}^{N_t}, R_t, \Gamma_t), \quad s_{t,i} = (\kappa_i, v_{t,i}, o_{t,i}, \tau_{t,i}, w_{t,i}, u_{t,i}, p_{t,i}, \sigma_{t,i}), \quad (1)$$

where R_t contains current relations, Γ_t records relation or event history retained in the state, and the fields of $s_{t,i}$ denote identity, content, occupancy, event time, standing, use evidence, provenance, and lifecycle, respectively. Identity κ_i is stable, while the remaining fields may change as the state evolves.

Relations are sparse. Write z_t for the encoding of the event arriving at step t ; it is the only new information a step receives. A contextual message may take the form

$$m_{t,i} = G_\theta(z_t, s_{t,i}, \{(r_{ij}, s_{t,j}) : (i, j) \in R_t\}). \quad (2)$$

The message influences the current read. It is not written into a neighbor unless the transition observes a new event about that neighbor. This keeps derived influence reversible and attributable.

3.3 The canonical interaction boundary

The state contract applies at the boundary where interaction enters Transfiver. A turn may contain user-authored text, a model statement, a tool or world result, or text quoted or carried into a later user turn. The raw turn and its local context are retained in the event history. Transport is evidence about how text arrived. A user may quote an assistant, approve it, reject it, or issue a new instruction next to it. Interpretation and uncertainty therefore belong to the learned transition and its readable provenance, rather than to a hard-coded “user text is true” flag.

For an implementation to count as Transfiver, the canonical state must contain every interaction-specific record that can affect a later output, including event order, source, modality, relations, lifecycle changes, and edit records. The same serialized state must be sufficient to restore the next transition and the pre-decode output; a cache, hidden conversation window, or model-specific history outside the serialization would violate the one-state contract.

4 How Transfiver Learns and Changes

4.1 Two ways a state changes: directed edit and stream update

A living state changes in two ways, and only one of them is exercised by an edit interface.

In a *directed edit* a person selects a visible item and supplies a new value. The address is chosen by the person, and the system must make the correction take effect, leave unrelated items alone, and allow exact restoration. This is what the protocols of Section 5 measure.

In a *stream update* no address is supplied. An event arrives that concerns something the state already holds: a password is replaced, a decision is superseded, a claim is retracted. Nothing marks the event as an update. The system itself must decide that it touches something already present rather than introducing something new.

The two fail differently. A system with a correct edit interface and no stream-update capability does not accumulate memory: repeated mentions of the same thing either leave no trace or create fresh items, and the

state drifts toward the condition described in the introduction, where nothing indicates which copy is current. Transfiver requires both, and they should be evaluated separately.

A judgment need not be made irreversibly at write time. When the current event alone does not determine whether an encounter is a genuine update or an incidental repetition, the transition can preserve the encounter and let later evidence determine how it should be read. The item is touched and can become the anchor for subsequent relations. A design that simply suppresses a write because the event resembles something already stored risks discarding a real update.

4.2 Offline learning and online state evolution

Transfiver separates learning the dynamics from using the learned dynamics. During offline training, future task loss must reach the transition:

$$S_{t+1} = T_\theta(S_t, z_t), \quad \theta \leftarrow \theta - \eta \nabla_\theta \sum_{t=1}^H \mathcal{L}(y_t, y_t^*). \quad (3)$$

where H is the training horizon. During deployment, θ is fixed and stream updates evolve S through the forward transition:

$$\theta \text{ fixed}, \quad S_{t+1} = T_\theta(S_t, z_t). \quad (4)$$

Directed edits are the other route by which S changes: they modify S directly at an address the user supplies, without changing θ . Neither route touches the parameters. Thus “learning from one event” means persistent state change without gradient retraining.

The constraint here is not that Transfiver avoids rules or avoids numbers. *No fixed value may occupy the place of a judgment that belongs to the user.*

Would changing this number change how the system computes, or would it change whose opinion the system expresses? A state dimension, a loss weight, or a layer count belongs to the first kind. How far a source is trusted, when an item stops counting as live, what outranks what: these are the second. A rule might, for example, fuse an item’s own trace with its neighbors’ in a fixed proportion—seventy percent borrowed and thirty percent its own. Transfiver forbids such a fixed semantic weighting, because those proportions differ across users, tasks, and histories, and drift for one user over time.

Deterministic routing is not automatically a hand rule. The test is where the distinction comes from. Whether a passage was typed by the user, emitted by a model, or pasted from a document is a delivery address that arrives with the input. A dictionary of marker words that tries to decide from the text itself that something matters is a different object: it recognizes surface form, and its coverage saturates. Each extension of such a dictionary buys recall with false positives, because the surface forms of significance are open-ended in a way that channel of origin is not.

A new failure is not a license for a new semantic flag; the first move is to ask whether an existing distinction, read expressively enough, already yields the behavior, and to delete the proposed concept when it does.

If Transfiver learns user-dependent judgments such as importance or source priority, the learning signal must be specified. One possible signal is subsequent user behavior: whether an item is retrieved again, used in later work, or explicitly marked as important. The absence of such behavior is not treated as negative evidence, since an unused item may still be valid or important. Because a single action may be noisy, repeated use provides stronger evidence than one isolated interaction.

4.3 Derive before adding

The same constraint applies to architecture design. A new failure should not automatically create a new semantic flag, state field, or task-specific module. The first question is whether the existing distinctions—content, context, source, time, use, importance, and relation—produce the required behavior when an expressive learned read combines them. “Dead,” for example, need not be a stored binary label if the relevant behavior follows from recency, continued use, blocking events, importance, and surviving relations. A false

completion need not be a special state kind if an unsupported self-report and a relevant external receipt receive different standing.

Representing scope may require a learned pairwise or multiplicative comparison between a claim and evidence. Such an operator belongs to Transfiver only if it implements the shared context/relation distinction and works beyond one completion benchmark. A new primitive is justified only after the existing state, equipped with a read capable of expressing its own principles, fails the corresponding hostile tests.

5 What Makes a System Transfiver?

If two copies of Transfiver have exactly the same saved state, then the same future input should induce the same distribution over future behavior. If those distributions differ, some information must still be stored somewhere outside the state the user can see and edit. We call this requirement *history sufficiency*.

5.1 The requirement: history sufficiency

Let $H_t = (x_1, \dots, x_t)$ denote everything that has happened up to time t . The state S_t is what Transfiver has kept from that history. The shared parameters θ may contain general abilities learned before use, but they may not quietly store facts that belong to one user’s interaction history.

Formally, if two histories leave Transfiver in the same state, no future continuation should be able to tell those histories apart. Here, $\text{Law}(F_\theta(H_t, c))$ denotes the distribution over future behavior induced by history H_t under continuation c . Importantly, F_θ denotes the behavior of the deployed system and is not assumed in advance to factor only through S_t .

$$S(H_t) = S(H'_t) \implies \text{Law}(F_\theta(H_t, c)) = \text{Law}(F_\theta(H'_t, c)) \quad \text{for every admissible continuation } c. \quad (5)$$

If this condition fails, some history-dependent information remains outside the state Transfiver shows.

Different applications may translate their inputs into different forms before Transfiver reads them, and may translate Transfiver’s output into different forms afterwards. We write these temporary input and output adapters for a domain d as A_d^{in} and A_d^{out} . They may translate information, but they may not keep their own memory between interactions:

$$(S_{t+1}, L_t, C_t) = \mathcal{M}_\theta(S_t, A_d^{\text{in}}(x_t)), \quad y_t = A_d^{\text{out}}(L_t), \quad (6)$$

Here, $\mathcal{M}_\theta$ denotes one complete Transfiver step. Its state component is the transition T_θ defined above: if $\mathcal{M}_\theta(S, z) = (S', L, C)$, then $S' = T_\theta(S, z)$.

Here, S_t is the persistent state, L_t is the model’s output before the final decoding step, and C_t records which state entries contributed to that output. The human-readable view is

$$V_t = \text{View}(S_t, C_t). \quad (7)$$

The adapters may differ by domain, but they may not become a second hidden memory or a separate history-dependent route to the answer.

5.1.1 Audit: nothing persistent outside the state

Save (θ, S_t) , restore it in a fresh process, and give the same next input. Under matched randomness, the restored system should reproduce the same next state and pre-decode output. It should induce the same distribution over future behavior.

Definition 1 (Nothing persistent outside S). Every interaction-specific persistent variable that can affect the distribution of future outputs is a member of S_t and is included in serialization. Step-local queries, activations, and fresh random draws may be temporary, but interaction-specific information may not persist through an unlogged cache.

5.2 Optional: tracing which state entries produced the answer

The small test model uses one extra restriction so that an answer can be checked entry by entry. For each active address, the implementation logs a contribution

$$\hat{L}_{t,i} = Q_\theta(z_t, s_{t,i}, m_{t,i}), \quad \hat{L}_t = \sum_{i \in \mathcal{I}(S_t)} \hat{L}_{t,i}, \quad (8)$$

where L_t denotes the actual pre-decode logits produced by the implementation and $\hat{L}_t$ denotes the logits reconstructed solely from the logged state-entry contributions.

Here, $\mathcal{I}(S_t)$ is the set of active addresses together with the unsupported sentinel $\perp$ of Section 6, whose contribution is logged like any other, and $\hat{L}_{t,i}$ is the logged contribution from entry i . This lets us check whether an answer came from the visible state rather than from an unlogged route.

We audit path completeness with

$$\epsilon_{\text{path}}(t) = \|L_t - \hat{L}_t\|.$$

A system whose decoder receives no trainable history-dependent input outside the logged contributions should have $\epsilon_{\text{path}}(t)$ equal to zero up to numerical precision. In the small model of Section 6 the pre-decode logits are the sum of the logged per-slot contributions and the logged sentinel contribution, so ϵ_{path} is zero by construction.

5.3 Audit: what is shown must be what is used

Let $g_\theta(S, x)$ denote Transfiver’s one-step answer under state S and input x . A successful edit should change the answer supported by the edited item, leave unrelated answers alone, and return to the original behavior when the edit is undone. Let $\text{Edit}(S, i, q)$ replace the visible payload at address i with q . Then we measure

$$\text{target}(i, q) = \Pr[g_\theta(\text{Edit}(S, i, q), x) = q \mid x \in X_i], \quad (9)$$

$$\text{locality}(i, q) = \mathbb{E}_{x \in X_{\rightarrow i}} d(g_\theta(\text{Edit}(S, i, q), x), g_\theta(S, x)), \quad (10)$$

$$\text{rollback}(i, q) = d_S(\text{Undo}(\text{Edit}(S, i, q)), S), \quad (11)$$

$$\text{path}(t) = \|L_t - \hat{L}_t\|. \quad (12)$$

The first quantity asks whether the target changed as intended. The second asks whether unrelated outputs changed. The third checks whether undo restores the original state. The last checks whether the logged contributions add up to the actual pre-decode output.

5.4 Symmetry, lifecycle, and rollback

If slot numbers have no meaning, simply reordering the slots should not change the model’s behavior. For a permutation P , the next-state distribution should permute in the same way while the output distribution remains unchanged:

$$T_\theta(PS, x) \stackrel{d}{=} PT_\theta(S, x), \quad g_\theta(PS, x) \stackrel{d}{=} g_\theta(S, x), \quad (13)$$

where $\stackrel{d}{=}$ denotes equality in distribution. This matters for lifecycle operations as well: retiring or restoring an item should depend on its state and history, not on an arbitrary storage index.

Proposition 1 (Rollback restoration). Assume fixed θ and history sufficiency. If an edit and its undo restore the serialized state exactly,

$$\text{Undo}(\text{Edit}(S, i, q)) = S,$$

then an identical future continuation induces the same distribution over future behavior as it did from S . Under matched randomness, a deterministic transition conditioned on that randomness reproduces the same trajectory.

6 A Small Test Model

The current implementation is smaller than Equation 1. Its purpose is to test whether a learned state can be the sole persistent computational path while supporting semantic intervention. It uses

$$S = (K, V, O, A), \quad (14)$$

with slot keys K , values V , occupancy O , and trainable empty-slot anchors A . There is no persistent recurrent hidden state. The current event is encoded into a step-local vector h_t , and a shared key encoder gives query q_t .

For occupied slot i , addressing is

$$b_{t,i} = \langle \bar{q}_t, \bar{K}_i \rangle + \log(O_i + \epsilon), \quad (15)$$

$$(\alpha_{t,1:N}, \alpha_{t,\perp}) = \text{softmax}([b_{t,1:N}, b_{t,\perp}]/\tau_{\text{soft}}), \quad (16)$$

where a bar denotes L_2 normalization, $\perp$ is a learned unsupported sentinel and $\tau_{\text{soft}} > 0$ is the softmax temperature. Each slot produces

$$L_{t,i} = \alpha_{t,i} W_o (\tanh(W_v V_i) \odot \tanh(W_q h_t)), \quad (17)$$

and the pre-decode logits are exactly $\sum_i L_{t,i} + L_{t,\perp}$, where the sentinel term $L_{t,\perp}$ is logged alongside the slot terms and is the only source of the unsupported coordinate.

The transition learns a write probability and a hard forward address with a straight-through gradient estimator. A hierarchical router first chooses between touching an existing identity and creating a new identity, then chooses among available anchors.

The semantic interface is deliberately bounded. It decodes each occupied slot into a public categorical schema (key, value) and permits a user to replace one visible item. It owns no persistent cache. The edited key and value are written into the canonical K, V tensors, after which ordinary answers continue through the same readout. The fixed schema limits what the public interface can carry and makes exact round-trip evaluation possible.

7 Experiments and Results

7.1 Real interaction records

The synthetic tests use a state we control. We now run the same contract on real interaction records, where the state is built from a public benchmark of multi-session human–assistant conversations in which a user states a value and later replaces it. We keep the 44 items in which two annotated evidence turns carry an old and a new value for the same subject, place them in the state, and let a learned read select four entries for the model.

We run three open models to separate what belongs to the store from what belongs to the reader. We compare two ways of acting on a superseded entry. *Prompt deletion* omits the entry when assembling this turn’s context, the operation available to any retrieval system. *State retraction* calls **retract** on the entry, so the read no longer selects it while the entry remains in the state. Both arms show the model the same number of entries, and the removed slot is refilled from the same ranking, so neither arm wins by showing one line more.

First, on the current value the two arms are identical by construction: they render the same lines, so a one-shot accuracy gap would be an artifact rather than a result. Second, the arms separate on what happens next. A prompt deletion changes nothing in the state, so on the following turn the old entry returns in 31 of 44 items and next-turn accuracy falls below the intervention level in every reader (.432–.523; for Mistral, .659 to .432); a retraction holds, the entry never returns, and next-turn accuracy stays at the intervention level (.659–.705). Third, only the state arm can answer what the value used to be, because the retracted entry is still there to be read when the question asks for it.

	Mistral-7B		Qwen2.5-7B		Phi-3-mini	
	del.	retr.	del.	retr.	del.	retr.
Intervention: current value	.659	.659	.705	.705	.659	.659
Recovering the earlier value	0	17	0	14	0	17
Old entry returns next turn	31	0	31	0	31	0
Current value next turn	19	29	23	31	20	29
Restore after retraction	n/a	31	n/a	31	n/a	31
Same view after save and reload	n/a	44	n/a	44	n/a	44

Table 1: The same contract on real records, under prompt deletion (del.) and state retraction (retr.). The first row is accuracy; the remaining rows are counts out of 44 items. Four entries are shown, so chance is .25. A control that withholds both evidence turns answers 0/44 in every model. The three rows that describe the state rather than the answer—return, restore, reload—are identical across models, as they should be: they are properties of the store, not of the reader.

The recovered-earlier-value rate of 14–17 out of 44 is far from the 31/44 items in which the old entry is visible, so making an entry available is not the same as using it. And our serialization carries content, standing and relations; event times are restored in relative order, while provenance, importance and usage counts are not yet serialized, so the save–restore result covers the part of the state the read consumes.

8 Limitations, Predictions, and Open Problems

8.1 Falsifiable predictions and proposed tests

Table 2 summarizes design-level predictions of Transfiver and corresponding tests that could falsify them. Some predictions are partially exercised by the synthetic experiments in this paper, while others remain untested.

8.2 Open problems

Scaling the architecture to free-form language and comparison with full-scale long-term-memory systems remain the next steps. A fuller realization should also incorporate human-readable visualization, source tracking, information liveness, complex relations, and reversible lifecycle in one learned system.

The architecture may create new failure modes. If errors identified by humans are not corrected by humans, problems such as incorrect identity assignment, forced merging of different meanings, splitting of a single meaning into multiple, false source maintenance, self-read history contamination, and the discarding of quiet but important information may occur.

Finally, an architecture that makes user-specific state persistent creates privacy, security, and governance obligations. Provenance, deletion, export, access control, and user-visible uncertainty are part of a deployable system even when they are not all part of the learning architecture. Personalization can also adapt to harmful user behavior, creating safety risks beyond privacy alone.

9 Conclusion

Transfiver begins with a picture of information that cannot be reduced to tokens in one folder or values ordered only by recency. Its state is intended to jointly represent information that may be quiet but still alive, retired but recoverable, shared across projects, interpreted differently by different people, or changed through subsequent use.

The architectural claim of Transfiver is that one evolving state must remember, support reasoning, produce output, expose what it contains, and accept correction. The history-sufficiency, intervention, and restoration requirements make that claim falsifiable. The small test model establishes only that part of this contract can be built and audited in a narrow learned system.

Table 2: Falsifiable predictions and proposed tests. Each row states a predicted property and a construction that would refute it.

Prediction	What must hold	Refuting construction
No hidden persistent path	Holding S fixed, no additional persistent interaction-specific variable changes future behavior	Restore the same S in a fresh process; identify any unlogged persistent cache or history-dependent route that changes the output distribution
A forward obligation is state	What is still expected is held, not implied	Schedule an obligation; withhold the event; require the absence to be reported
Intention is not accomplishment	Plan, claim and receipt occupy different standing	Plan without receipt; claim without receipt; receipt without claim
One cause does not close a question	An explanation carries the scope in which it was established	Supply a sufficient-looking cause covering part of the observations only
User-marked importance remains distinct	Marked importance stays distinguishable from frequency and recency	Mark an item; bury it under unrelated volume and time; query it
Judgment follows a declared source	Review and translation bind to the source, not to fluency	Remove the source; provide a conflicting source; supply an unsupported source
Scope travels with what was learned	A rule learned in one project does not fire in another	Teach in project A; query in project B; re-scope; re-query
An instruction need not be repeated	Held instruction survives a session boundary	Instruct once; serialize; restore; require the behavior without restatement
Omission is visible	An unmet obligation appears as an absence in the view	Hold a list; satisfy all but one; require the missing one to be reported
What was learned is inspectable	The learned detail, not only the output, can be corrected	Train where a surface cue and a real quality both predict; ablate the cue; require the judgment to move
Deposits are cheaper than gradients	A fact placed in state costs less than a fact pressed into weights	Same fact, same budget: state deposit versus gradient acquisition
Quiet or dead need not be final	Retirement is reversible	Retire, distract, revive, partial inheritance, exact rollback

The dissociations the broader architecture is intended to preserve—context without fragmentation, multiple belonging without copying, relation without similarity shortcuts, liveness without a recency shortcut, qualified observation without self-amplification, and correction without a hidden bypass—are design goals rather than results reported here. Testing them together in one system is the work described under open problems.

A Synthetic tests

The following tests use a state we construct and a model we train, so they establish that parts of the contract are satisfiable rather than that the whole contract holds in the wild. The real-record results in Section 7.1 carry that claim.

A.1 Contexts and overlap

We test whether the same content can stay separate when it is placed in two different contexts. The address here is formed in two halves, one from the key and one from the context; nothing else about the model changes. An episode writes four facts on context 0 and the same four keys on context 1, giving two of those keys deliberately different values in the two contexts; the events of the two contexts are interleaved in random order. The query names a key *and* a context, and the correct answer is the value that key holds in the named context, not the value written most recently. Two conditions differ in how the context reaches the model. In the easier condition the context is a field on every event. In the harder condition a single header event announces the context and the following events carry no context field at all, so the current context has to be carried forward in the state. Values are 16-way, so chance is $1/16 = .0625$ and the pre-specified threshold is

chance + 3SE = .095; each seed is evaluated on 512 queries from episodes generated with an evaluation seed disjoint from training.

How each number is measured.

Context-conditioned accuracy Fraction of evaluation queries whose answer, the arg-max over the 16 value coordinates, equals the value the queried key holds in the named context.

Recency collapse Fraction whose answer equals the value the same key holds in the *other* context. By construction the two differ, so this isolates one specific failure: answering from the other, in general more recent, binding rather than from the one asked for.

Flipping the queried context returns the other value The state is left untouched and only the context coordinate of the query is switched; the fraction whose answer becomes the other context’s value. This is the causal form of the first row: the context in the query, not the key alone, selects the answer.

Same key placed on different items The read attends over slots; this is the fraction of queries for which the arg-max slot for (key, context 0) differs from the arg-max slot for (key, context 1) – that is, the two bindings occupy different entries instead of one entry that was overwritten.

Context withdrawal changes the prior answer Every slot whose context axis is nearest to context 0 has its occupancy set to zero; contents are not touched. Fraction of queries whose context 0 answer then differs from what it was before. It measures that the answer changes, not that the model reports the entry as unsupported; the stricter form is reported separately below.

Restoring the context returns it exactly The saved occupancy vector is written back into the withdrawn state; the fraction whose answer equals the pre-withdrawal answer, together with a check that the restored state is tensor-identical to the original.

Overlap The overlap between two contexts is computed at read time as a max-match on the content half of the slot keys: for every item placed on c , the cosine similarity to the most similar item placed on c' , averaged over the items of c (self pairs excluded when $c = c'$). Nothing is stored in either context; the value exists only while the view is drawn.

Items created per episode Mean number of occupied slots at the end of an episode; eight facts written on two contexts should occupy eight entries if the two contexts do not merge, and nine in the second condition, where the header event opens an entry of its own.

Table 3: Context test, five seeds, 512 evaluated queries per seed. The same key appears in two contexts with different values, so the value the key holds in the other context is always a distinct wrong answer. Chance is $1/16 = .0625$ and the pre-specified threshold is chance + $3SE = .095$. In the second block the context is announced once by a header event and must be carried forward in the state.

Metric	Seed 0	Seed 1	Seed 2	Seed 3	Seed 4
<i>Context given on every event</i>					
Context-conditioned accuracy	1.000	1.000	.486	1.000	1.000
Recency collapse (lower is better)	.000	.000	.436	.000	.000
Flipping the queried context returns the other value	1.000	1.000	.486	1.000	1.000
Same key placed on different items	1.000	1.000	.135	1.000	1.000
Withdrawing the context changes its prior answer	1.000	1.000	.547	1.000	1.000
Withdrawn context answered as unsupported	.000	.000	1.000	.000	.000
Restoring the context returns it exactly	1.000	1.000	1.000	1.000	1.000
Overlap, different contexts	.999	1.000	.190	1.000	.999
Overlap, within one context	.149	.135	.070	.152	.138
Items created per episode	8.0	8.0	3.9	8.0	8.0
<i>Context announced once, then carried in the state</i>					
Context-conditioned accuracy	1.000	1.000	1.000	1.000	1.000
Recency collapse (lower is better)	.000	.000	.000	.000	.000
Flipping the queried context returns the other value	1.000	1.000	1.000	1.000	1.000
Same key placed on different items	1.000	1.000	1.000	1.000	1.000
Withdrawing the context changes its prior answer	1.000	1.000	1.000	1.000	1.000
Withdrawn context answered as unsupported	.000	.000	.000	.000	.000
Restoring the context returns it exactly	1.000	1.000	1.000	1.000	1.000
Overlap, different contexts	.891	.904	.900	.885	.886
Overlap, within one context	.165	.177	.154	.148	.169
Items created per episode	9.0	9.0	9.0	9.0	9.0

Four of the five seeds in the first condition and all five in the second reach a solution in which the two contexts stay separate: the same key occupies two entries, the answer follows the context named in the query rather than the most recent write, and switching only the context coordinate of the query returns the other context’s value. Withdrawing a context by clearing the occupancy of the items placed on it changes the answer previously supported by that context, and writing the saved occupancy back reproduces the previous answer from a state that is tensor-identical to the original; the items themselves are never edited. After withdrawal the model answers from the remaining context and never routes to the sentinel $\perp$ of Section 6, so the “unsupported” row of Table 3 is .000 in every seed that separates the contexts. Abstention on withdrawn evidence, which LongMemEval lists as a core ability [23], is therefore not established by this experiment.

One seed of five does not reach this solution in the first block. It opens 3.9 entries per episode instead of eight, which is consistent with the two contexts being merged into shared entries, and the other quantities move with that failure: context-conditioned accuracy falls to .486, the other context’s value is returned in .436 of queries, and cross-context overlap falls from near one to .190. The same seed succeeds in the second block, where the context has to be carried in the state. Five seeds do not establish how often the solution is reached: as a sign test, four successes against one failure gives $p = .375$, and five against none gives $p = .0625$.

A.2 Reading four rules out of one state

A necessary condition for a state to expose multiple temporal distinctions is that those distinctions remain recoverable from the same frozen state. This section tests that condition on an earlier implementation of a persistent state built from the same commitments—items held in slots, joined by relations that carry the time and the count of the events that formed them—using a single held-out evaluation fixed in advance. It is not the model of Section 6, whose slots hold a key, a value and an occupancy and no relation history, so this question cannot be put to that model.

The task. An episode is 512 tokens long. Fifty-eight keys are each written four times, interleaved with unrelated filler, and the episode is divided into eight numbered sections that act as coarse timestamps. Each episode ends with eight queries. A query names a key and one of four rules:

1. *most recent* — the last value written for that key;
2. *earliest* — the first value written for that key;
3. *as of a named section* — the value that was in force just before a named section of the episode;
4. *the n th value* — the n th value ever written for that key.

The last two rules carry a number with them, and in this evaluation that number is always the second or the third. All four rules appear in the same episode, two queries each, so the same key can be asked about under different rules and the four rules disagree with one another; the text of the episode alone does not determine the answer. Which values a key may take is fixed by a hash into three disjoint pools, one used while training, one while selecting, and one reserved for the held-out test, so the values that appear as answers in the final test never appeared as answers earlier.

The readout. The trained model is frozen. For a query about a key, the *candidates* are the 205 values that key is allowed to take in this pool; four of them were actually written. From the frozen state we take five numbers per candidate, and nothing else:

1. whether the state currently holds a relation from the queried key to that candidate;
2. how long before the query that relation was formed, as a fraction of the episode;
3. where that relation falls in time among the key’s own relations, as a rank scaled to $[0, 1]$;
4. the numbered section in which it was formed, minus the section the query named;
5. its rank in time, minus the number the query named.

The last two are zero for the two rules that name no number, which is how the named number reaches the readout at all. Raw keys, raw values, and absolute positions in the episode are excluded by construction and recorded as excluded. These five numbers, together with a four-way indicator naming which rule is in force, go to one small network of 385 parameters—capped at 400 in advance— which scores each candidate separately; the answer is the highest-scoring candidate. The same network serves all four rules. The four-way indicator identifies which rule to apply, while the final two features carry the numeric reference for the two rules that require one. Each rule is a short arithmetic function of these five numbers—extremes of the time rank for the first two, the signed section difference for the third, the signed rank difference for the fourth—so what the readout has to find in the state is those five quantities, kept separable, rather than a rule. The readout is trained on one set of episodes, selected on a second, and the test partition was fixed before evaluation and opened once, with retries and regeneration forbidden.

Result. Table 4 reports the held-out test over five independently trained models, 1,280 queries per rule and 5,120 in total. Guessing uniformly among a key’s 205 permitted values scores .005, but the first feature already separates the four values written for that key from the other 201, so the baseline the table should be read against is one of those four, .250.

Table 4: Held-out readout test, five trained models, 1,280 queries per rule. The upper block is accuracy under each rule; the lower blocks are the controls that were required to pass for the result to count. In the two substitution controls the informative number is not that accuracy on the originally named rule falls to zero, but that the readout then answers the substituted rule instead, which separates “it stopped working” from “it followed the instruction it was given”.

	Most recent	Earliest	As of a section	The n th value
Accuracy	1.000	1.000	.984	.996
<i>The named rule is replaced by a different rule</i>				
Accuracy on the rule originally named	.000	.000	.004	.000
Answers the substituted rule instead	1.000	1.000	.996	.984
<i>The named number is replaced (only the two rules that carry one)</i>				
Accuracy on the number originally named	—	—	.000	.008
Answers the substituted number instead	—	—	.980	.992
<i>Invariance and leakage, over all 5,120 queries</i>				
Every key renamed: predictions identical, largest change in score 0.0				
Items moved within the episode: predictions identical, largest change in score 0.0				

These results show that the temporal distinctions required by the four rules remain recoverable from the frozen state. They do not show that the model’s own answer path uses the same readout. The task is also synthetic: keys, values, and sections are symbols, and the two rules that name a number were tested at two of the eight sections rather than across all of them.

References

- [1] David Alvarez-Melis and Tommi S. Jaakkola. Towards robust interpretability with self-explaining neural networks. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, NIPS’18, page 7786–7795, Red Hook, NY, USA, 2018. Curran Associates Inc.
- [2] John R. Anderson, Daniel Bothell, Michael D. Byrne, Scott Douglass, Christian Lebiere, and Yulin Qin. An integrated theory of the mind. *Psychological Review*, 111(4):1036–1060, October 2004.
- [3] Jimmy Ba, Geoffrey Hinton, Volodymyr Mnih, Joel Z. Leibo, and Catalin Ionescu. Using fast weights to attend to the recent past. In *Proceedings of the 30th International Conference on Neural Information Processing Systems*, NIPS’16, page 4338–4346, Red Hook, NY, USA, 2016. Curran Associates Inc.
- [4] Ali Behrouz, Peilin Zhong, and Vahab Mirrokni. Titans: Learning to memorize at test time. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025.
- [5] Vincent-Pierre Berges, Barlas Oguz, Daniel HAZIZA, Wen tau Yih, Luke Zettlemoyer, and Gargi Ghosh. Memory layers at scale. In *Forty-second International Conference on Machine Learning*, 2025.
- [6] Sebastian Borgeaud, Arthur Mensch, Jordan Hoffmann, Trevor Cai, Eliza Rutherford, Katie Millican, George Bm Van Den Driessche, Jean-Baptiste Lespiau, Bogdan Damoc, Aidan Clark, Diego De Las Casas, Aurelia Guy, Jacob Menick, Roman Ring, Tom Hennigan, Saffron Huang, Loren Maggiore, Chris Jones, Albin Cassirer, Andy Brock, Michela Paganini, Geoffrey Irving, Oriol Vinyals, Simon Osindero, Karen Simonyan, Jack Rae, Erich Elsen, and Laurent Sifre. Improving language models by retrieving from trillions of tokens. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvari, Gang Niu, and Sivan Sabato, editors, *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pages 2206–2240. PMLR, 17–23 Jul 2022.
- [7] Payel Das, Subhajit Chaudhury, Elliot Nelson, Igor Melnyk, Sarathkrishna Swaminathan, Sihui Dai, Aurélie Lozano, Georgios Kollias, Vijil Chenthamarakshan, Jiří Navrátil, Soham Dan, and Pin-Yu Chen. Larimar: large language models with episodic memory control. In *Proceedings of the 41st International Conference on Machine Learning*, ICML’24. JMLR.org, 2024.

- [8] Atticus Geiger, Duligur Ibeling, Amir Zur, Maheep Chaudhary, Sonakshi Chauhan, Jing Huang, Aryaman Arora, Zhengxuan Wu, Noah Goodman, Christopher Potts, and Thomas Icard. Causal abstraction: A theoretical foundation for mechanistic interpretability, 2025.
- [9] Alex Graves, Greg Wayne, and Ivo Danihelka. Neural turing machines, 2014.
- [10] Albert Gu and Tri Dao. Mamba: Linear-time sequence modeling with selective state spaces. In *First Conference on Language Modeling*, 2024.
- [11] Urvashi Khandelwal, Omer Levy, Dan Jurafsky, Luke Zettlemoyer, and Mike Lewis. Generalization through memorization: Nearest neighbor language models. In *International Conference on Learning Representations*, 2020.
- [12] Pang Wei Koh, Thao Nguyen, Yew Siang Tang, Stephen Mussmann, Emma Pierson, Been Kim, and Percy Liang. Concept bottleneck models. In Hal Daumé III and Aarti Singh, editors, *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 5338–5348. PMLR, 13–18 Jul 2020.
- [13] Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. Retrieval-augmented generation for knowledge-intensive NLP tasks. In *Proceedings of the 34th International Conference on Neural Information Processing Systems*, NIPS ’20, Red Hook, NY, USA, 2020. Curran Associates Inc.
- [14] Kevin Meng, David Bau, Alex J Andonian, and Yonatan Belinkov. Locating and editing factual associations in GPT. In Alice H. Oh, Alekh Agarwal, Danielle Belgrave, and Kyunghyun Cho, editors, *Advances in Neural Information Processing Systems*, 2022.
- [15] Kevin Meng, Arnab Sen Sharma, Alex J Andonian, Yonatan Belinkov, and David Bau. Mass-editing memory in a transformer. In *The Eleventh International Conference on Learning Representations*, 2023.
- [16] Charles Packer, Sarah Wooders, Kevin Lin, Vivian Fang, Shishir G. Patil, Ion Stoica, and Joseph E. Gonzalez. MemGPT: Towards llms as operating systems, 2024.
- [17] Vedant Patel. Supersede: Diagnosing and training the memory-update gap in LLM agents, 2026.
- [18] Adam Santoro, Sergey Bartunov, Matthew Botvinick, Daan Wierstra, and Timothy Lillicrap. Meta-learning with memory-augmented neural networks. In *Proceedings of the 33rd International Conference on International Conference on Machine Learning - Volume 48*, ICML’16, page 1842–1850. JMLR.org, 2016.
- [19] Matthias Scheutz, Scott A. DeLoach, and Julie A. Adams. A framework for developing and using shared mental models in human-agent teams. *Journal of Cognitive Engineering and Decision Making*, 11(3):203–224, 2017.
- [20] David Steinmann, Wolfgang Stammer, Felix Friedrich, and Kristian Kersting. Learning to intervene on concept bottlenecks, 2024.
- [21] Yu Sun, Xinhao Li, Karan Dalal, Jiarui Xu, Arjun Vikram, Genghan Zhang, Yann Dubois, Xinlei Chen, Xiaolong Wang, Sanmi Koyejo, Tatsunori Hashimoto, and Carlos Guestrin. Learning to (learn at test time): RNNs with expressive hidden states, 2025.
- [22] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, NIPS’17, page 6000–6010, Red Hook, NY, USA, 2017. Curran Associates Inc.
- [23] Di Wu, Hongwei Wang, Wenhao Yu, Yuwei Zhang, Kai-Wei Chang, and Dong Yu. Longmemeval: Benchmarking chat assistants on long-term interactive memory, 2025.