

Unbiased Top- k Estimation for On-Policy Distillation

Linjian Meng^{*1}, Siyuan Gan^{*2}, YuHan Li¹, Xiran Wang¹,
Ziyang Ding¹, Zitang Gou¹, Yiming Wu¹, Zhen Zhao^{1†}

¹Shanghai Artificial Intelligence Laboratory, Shanghai, China

²State Key Laboratory of Novel Software Technology, Nanjing University, Nanjing, China
menglinjian@pjlab.org.cn, gansiyuan@smail.nju.edu.cn, zhaozhen@pjlab.org.cn

Abstract

On-policy distillation (OPD) is becoming an important component of large language model (LLM) post-training for transferring the reasoning capability of a strong teacher LLM to a weaker student LLM. OPD trains the student by minimizing the reverse KL divergence between the teacher and the student via rollouts generated by the student’s policy. However, estimating the gradient of the reverse KL divergence in OPD remains a challenge. Using only the sampled token from the student-generated rollout is computationally cheap but provides limited distributional supervision, which will degrade accuracy. In addition, using the full vocabulary provides complete distributional supervision but is computationally expensive. Therefore, recent works propose Top- k OPD (TK-OPD) that use selected top- k tokens, which provides richer distributional supervision than sampled-token estimation at substantially lower computational cost than full-vocabulary estimation. Unfortunately, using only the selected top- k tokens induces bias, leading to accuracy degradation, as the probability mass outside the selected top- k tokens is discarded. To address the bias of TK-OPD, we propose *Tail-Corrected Top- k On-Policy Distillation* (TT-OPD). It preserves the advantages of TK-OPD, including rich distributional supervision and low computational cost, while providing an unbiased estimator of the gradient of the reverse KL divergence. The key insight of TT-OPD is to use not only the selected top- k tokens, but also the sampled token from the student-generated rollout, thereby recovering the discarded probability mass in expectation, avoiding the bias. Experimental results demonstrate that TT-OPD significantly outperforms other tested OPD variants.

1 Introduction

On-policy distillation (OPD) (Agarwal et al. 2024; Kevin and Lab 2025) is becoming an important component of large language model (LLM) post-training, as evidenced by its utilization in various frontier-level LLMs (Yang et al. 2025; Zeng et al. 2026; Xu et al. 2026; Xiao et al. 2026). This is due to OPD’s ability to transfer the reasoning capability of a strong teacher LLM to a weaker student LLM (Gu et al. 2024; Xu et al. 2025; Fu et al. 2026; Oh et al. 2026; Xiao et al. 2026; Zheng et al. 2026; Zhu et al. 2026; Zhao et al. 2026; Yang et al. 2026; Hübotter et al. 2026; Shenfeld et al. 2026; Yang et al. 2026; Wu, Han, and Cai 2026; Hou et al. 2026; Wang

^{*}These authors contributed equally.

[†]Corresponding author.




Figure 1: **Overview of TT-OPD.** The notation $sg(\cdot)$ denotes the stop-gradient operator. At each student-visited state Z_t , the selected top- k tokens S_t^k provide rich distributional supervision, while the sampled token y_t in the student-generated rollout provides an unbiased gradient tail correction. This only induces $O(k+1)$ computational cost.

et al. 2026; Xie et al. 2026). Specifically, unlike off-policy distillation, which trains the student on teacher-generated rollouts, OPD minimizes the reverse KL divergence between the teacher and the student using rollouts generated by the student’s own policy. This on-policy setting enables the student to refine its behavior on states it actually visits (Li et al. 2026). It reduces the substantial exposure bias inherent in off-policy distillation that hinders the transfer of reasoning capability from a strong teacher LLM to a weaker student LLM (Song and Zheng 2026; Hou et al. 2026).

Unfortunately, estimating the gradient of the reverse KL divergence in OPD remains a challenge. Vanilla OPD, also called Sampled-Token OPD (ST-OPD), uses only the sampled token in the student-generated rollout to estimate the

	Unbiased Gradient?	Rich Distributional Supervision?	Computational Cost
ST-OPD	✓	✗	$O(1)$
FV-OPD	✓	✓	$O(\mathcal{V})$
TK-OPD	✗	✓	$O(k)$
TT-OPD	✓	✓	$O(k + 1)$

Table 1: Comparison between our TT-OPD and other OPD variants. The notation $\mathcal{V}$ denotes the vocabulary.

gradient of the reverse KL divergence (Kevin and Lab 2025). While this approach incurs low computational cost, it provides limited distributional supervision, which will degrade accuracy. To overcome this limitation, some works propose Full-Vocabulary OPD (FV-OPD) that computes the gradient of the reverse KL divergence using the full vocabulary (Xu et al. 2026). However, this incurs prohibitive computational cost. For example, Qwen3 (Yang et al. 2025) has a vocabulary of 151,646 tokens, so FV-OPD evaluates 151,646 terms at each position, inducing 151,646 times larger computational cost than ST-OPD. To trade off the richness of distributional supervision and computational cost, recent works introduce Top- k OPD (TK-OPD) that adopts selected top- k tokens to provide rich distributional supervision (Hübottter et al. 2026; Li et al. 2026), where k is much smaller than the vocabulary size. However, this induces bias as the probability mass outside the selected top- k tokens is discarded (Zhu et al. 2026), leading to accuracy degradation.

To address the bias of TK-OPD, we propose a novel OPD variant called *Tail-Corrected Top- k On-Policy Distillation* (TT-OPD). It preserves the advantages of TK-OPD, including rich distributional supervision and low computational cost, while providing an unbiased estimator of the gradient of the reverse KL divergence. As shown in Figure 1, the key insight of TT-OPD is to use not only the selected top- k tokens, but also the sampled token in the student-generated rollout. Specifically, since the sampled token is drawn from the full student distribution, it provides a tail correction to recover the probability mass outside the selected top- k tokens in expectation, thereby avoiding the bias of TK-OPD. More importantly, TT-OPD also retains all advantages of TK-OPD, e.g., rich distributional supervision and low computational cost. To more clearly illustrate the differences between TT-OPD and other OPD variants, we present Table 1.

To evaluate TT-OPD, we employ the Qwen3 (Yang et al. 2025) and DeepSeek (Guo et al. 2025) model series and conduct experiments on mathematical reasoning benchmarks and code-generation benchmarks. Experimental results demonstrate that TT-OPD yields significant accuracy improvements over ST-OPD and TK-OPD across student scales, model series, selected top- k tokens, values of k , and tasks.¹

2 Related Work

Off-Policy Distillation. A major challenge in LLM post-training is transferring the reasoning capability of a strong teacher LLM to a weaker student LLM. The initial approach, off-policy distillation, trains the student using teacher-

generated rollouts. One line of off-policy distillation algorithm aligns the student’s distribution with that of the teacher on a static dataset, typically through a forward-KL objective (Hinton, Vinyals, and Dean 2015; Xu et al. 2024; Liu et al. 2024; Guo et al. 2026; Deng et al. 2026; Ko et al. 2025). Another line of off-policy distillation algorithms trains the student on teacher-generated tokens, as in supervised fine-tuning (SFT) style imitation (Wang et al. 2023; Guo et al. 2025; Zhang et al. 2026a; Cha et al. 2024; Zhang et al. 2025). However, because off-policy distillation uses states from teacher-generated rollouts, these states may differ from those the student actually visits, inducing substantial exposure bias that hinders reasoning capability transfer (Song and Zheng 2026; Hou et al. 2026).

On-Policy Distillation. To reduce the exposure bias in off-policy distillation, recent works adopt on-policy distillation (OPD) (Agarwal et al. 2024; Kevin and Lab 2025), as exemplified by various frontier-level LLMs (Yang et al. 2025; Zeng et al. 2026; Xu et al. 2026; Xiao et al. 2026). OPD trains the student through student-generated rollouts, ensuring that the training states match those the student actually visits to reduce the exposure bias. Specifically, after sampling rollouts from the student’s policy, OPD trains the student by minimizing the reverse KL divergence at each position of the student-generated rollouts (see more details in Section 3).

Gradient Estimation for the Reverse KL Divergence in OPD. A central challenge in OPD is estimating the gradient of the reverse KL divergence under the large vocabulary of modern LLMs. Sampled-Token OPD (ST-OPD) uses only the sampled token, achieving low computational cost, but providing limited distributional supervision, which degrades accuracy (Kevin and Lab 2025; Oh et al. 2026). Full-Vocabulary OPD (FV-OPD) uses full-vocabulary distributional supervision by summing all tokens over the full vocabulary, but its computational cost scales with vocabulary size, making it expensive for modern large-vocabulary LLMs (Xu et al. 2026). Top- k OPD (TK-OPD) trades off the richness of distributional supervision and computational cost by using the selected top- k tokens to estimate the gradient of the reverse KL divergence (Hübottter et al. 2026; Li et al. 2026). However, discarding probability mass outside the selected top- k tokens introduces bias (Zhu et al. 2026).

In contrast to these three OPD variants, our TT-OPD retains all advantages of TK-OPD, rich distributional supervision and low computational cost independent of vocabulary size, while also inheriting the unbiasedness of the estimated gradient of ST-OPD and FV-OPD. Consequently, TT-OPD is as suitable for modern large-vocabulary LLMs as ST-OPD and TK-OPD, yet significantly outperforms both.

¹Due to the prohibitive computational cost of FV-OPD, we are unable to compare with it.

3 Preliminaries

3.1 OPD Framework

We first formalize the OPD framework used in this paper. Let π_θ denote the student policy and π_{tea} denote the fixed teacher policy over a shared vocabulary $\mathcal{V}$. Given a prompt $x \sim \mathcal{D}$, OPD samples a rollout from the student’s policy:

$$y = (y_1, \dots, y_T) \sim \pi_\theta(\cdot | x), \quad T = |y|,$$

where T is the realized rollout length. We refer to y as the student-generated rollout since it is sampled via student’s policy π_θ . For each position $t \in \{1, \dots, T\}$, let $Z_t = (x, y_{<t})$ denote the student-visited state before token y_t . The student and teacher next-token distributions at Z_t are

$$\begin{aligned} p_t(v) &\triangleq \pi_\theta(v | Z_t), \\ q_t(v) &\triangleq \pi_{\text{tea}}(v | Z_t), \quad v \in \mathcal{V}. \end{aligned}$$

At position t , the full-vocabulary reverse KL divergence is

$$d_t(\theta) \triangleq D_{\text{KL}}(p_t \| q_t) = \sum_{v \in \mathcal{V}} p_t(v) \log \frac{p_t(v)}{q_t(v)}.$$

In practical training, OPD constructs a single-sample empirical objective over the finite training set. Specifically, for each prompt $x \in \mathcal{D}$, it samples one rollout

$$y^{(x)} = (y_1^{(x)}, \dots, y_{T_x}^{(x)}) \sim \pi_\theta(\cdot | x), \quad T_x = |y^{(x)}|.$$

Let $d_{x,t}(\theta)$ denote the divergence defined above, evaluated at $Z_{x,t} = (x, y_{<t}^{(x)})$. Using token-mean aggregation, the resulting OPD objective is

$$\mathcal{L}_{\text{OPD}}(\theta) \triangleq \frac{1}{\sum_{x \in \mathcal{D}} T_x} \sum_{x \in \mathcal{D}} \sum_{t=1}^{T_x} d_{x,t}(\theta).$$

Following standard OPD training, the sampled rollouts, their realized lengths, and the visited states are treated as fixed during backpropagation; gradients do not propagate through the rollout-sampling process. Let $g_{x,t}^* \triangleq \nabla_\theta d_{x,t}(\theta)$. The corresponding training gradient targeted by all estimators in this paper is

$$g_{\text{OPD}}(\theta) \triangleq \nabla_\theta \mathcal{L}_{\text{OPD}}(\theta) = \frac{1}{\sum_{x \in \mathcal{D}} T_x} \sum_{x \in \mathcal{D}} \sum_{t=1}^{T_x} g_{x,t}^*.$$

When discussing a generic rollout below, we omit the prompt index and write g_t^* for $g_{x,t}^*$. Unlike off-policy distillation algorithms, OPD evaluates this token-level objective on states visited by the student’s own policy. This on-policy setting reduces the exposure bias caused by training on teacher-generated data (Li et al. 2026; Song and Zheng 2026).

3.2 Three OPD Variants

One of the computational bottlenecks of the OPD training lies in estimating g_t^* for modern large-vocabulary LLMs. Existing OPD variants mainly differ in the number of vocabulary tokens used to form this estimate, leading to different trade-offs among bias, richness of distributional supervision, and computational cost.

Sampled-Token OPD (ST-OPD). Vanilla OPD, also called ST-OPD, uses only the token y_t sampled from the student-generated rollout (Kevin and Lab 2025). Since $y_t \sim p_t$ at a fixed state Z_t , its stop-gradient surrogate is

$$\mathcal{L}_t^{\text{ST}}(\theta) = \text{sg} \left(\log \frac{p_t(y_t)}{q_t(y_t)} \right) \log p_t(y_t),$$

where $\text{sg}(\cdot)$ denotes the stop-gradient operator. Its gradient is an unbiased estimator of the gradient of the reverse KL divergence (Oh et al. 2026):

$$\mathbb{E}_{y_t \sim p_t} [\nabla_\theta \mathcal{L}_t^{\text{ST}}(\theta) | Z_t] = g_t^*.$$

ST-OPD therefore has low computational cost, but its reliance on one sampled token provides limited distributional supervision, which degrades accuracy.

Full-Vocabulary OPD (FV-OPD). FV-OPD evaluates the reverse KL divergence over the entire vocabulary (Xu et al. 2026):

$$\mathcal{L}_t^{\text{FV}}(\theta) = D_{\text{KL}}(p_t \| q_t) = \sum_{v \in \mathcal{V}} p_t(v) \log \frac{p_t(v)}{q_t(v)}.$$

Consequently,

$$\nabla_\theta \mathcal{L}_t^{\text{FV}}(\theta) = g_t^*.$$

This estimator provides full-vocabulary distributional supervision, but it incurs prohibitive computational cost because it evaluates token-level terms over the full vocabulary.

Top- k OPD (TK-OPD). To trade off the richness of distributional supervision and computational cost, TK-OPD restricts the reverse KL computation divergence to a selected subset of the full vocabulary (Hübner et al. 2026; Li et al. 2026; Oh et al. 2026; Zhu et al. 2026). Let S_t^k denote the selected top- k tokens at position t that can be the student’s top- k tokens $S_{t,\text{stu}}^k$, the teacher’s top- k tokens $S_{t,\text{tea}}^k$, or their overlap $S_{t,\text{stu}}^k \cap S_{t,\text{tea}}^k$. For every $v \in S_t^k$, TK-OPD renormalizes the student and teacher distributions within S_t^k :

$$\begin{aligned} p_t^{S_t^k}(v) &\triangleq \frac{p_t(v)}{\sum_{u \in S_t^k} p_t(u)}, \\ q_t^{S_t^k}(v) &\triangleq \frac{q_t(v)}{\sum_{u \in S_t^k} q_t(u)}. \end{aligned}$$

Its per-position loss is

$$\begin{aligned} \mathcal{L}_t^{\text{TK}}(\theta) &= D_{\text{KL}}(p_t^{S_t^k} \| q_t^{S_t^k}) \\ &= \sum_{v \in S_t^k} p_t^{S_t^k}(v) \log \frac{p_t^{S_t^k}(v)}{q_t^{S_t^k}(v)}. \end{aligned}$$

TK-OPD provides richer distributional supervision than ST-OPD and its computational cost is much cheaper than FV-OPD because $1 \ll k \ll |\mathcal{V}|$. However, TK-OPD introduces bias because the probability mass outside the selected top- k tokens is discarded (Zhu et al. 2026):

$$\nabla_\theta \mathcal{L}_t^{\text{TK}}(\theta) \neq g_t^*.$$

Thus, although TK-OPD provides a trade-off between the richness of distributional supervision and computational cost, it cannot provide an unbiased estimator of the gradient of the reverse KL divergence, leading to accuracy degradation.

4 Methodology

To mitigate the bias of estimating the gradient in TK-OPD, we propose *Tail-Corrected Top-k On-Policy Distillation* (TT-OPD). Its key insight is to use not only the selected top- k tokens, but also the sampled token in the student-generated rollout. Specifically, it retains the tokens S_t^k used by TK-OPD but also reuses the token y_t sampled in the student-generated rollout y . Because y_t is drawn from the full student distribution, it provides a tail correction to recover the discarded probability mass outside the selected top- k tokens in expectation. In other words, the selected top- k tokens provide rich distributional supervision, while the sampled token y_t provides an unbiased correction for the discarded tail contribution. More importantly, TT-OPD incurs a vocabulary-independent computational cost of only $O(k+1)$, which is nearly identical to the $O(k)$ computational cost of TK-OPD and substantially lower than the $O(|\mathcal{V}|)$ computational cost of FV-OPD.

4.1 Overview of TT-OPD

TT-OPD uses the on-policy token distributions defined in Section 3.1. At a student-visited state $Z_t = (x, y_{<t})$, the student distribution is p_t , the teacher distribution is q_t , and the sampled token y_t satisfies $y_t \sim p_t$. Let S_t^k denote the same selected tokens used by TK-OPD.

The selected set S_t^k specifies which token-level gradient contributions are computed exactly, while the sampled token y_t provides the tail correction. TT-OPD defines the following per-position loss:

$$\begin{aligned} \mathcal{L}_t^{\text{TT}}(\theta) = & \sum_{v \in S_t^k} \text{sg} \left(\log \frac{p_t(v)}{q_t(v)} \right) p_t(v) \\ & + \mathbb{1}\{y_t \notin S_t^k\} \text{sg} \left(\log \frac{p_t(y_t)}{q_t(y_t)} \right) \log p_t(y_t). \end{aligned} \quad (1)$$

The first term exactly computes the contributions of tokens in S_t^k to the gradient of the reverse KL divergence. The second term estimates the omitted contribution from the tail $\mathcal{V} \setminus S_t^k$. When $y_t \in S_t^k$, this tail correction is omitted because the sampled token is already covered by the first term. The computational cost of TT-OPD at each position is at most $O(|S_t^k| + 1)$, which is $O(k+1)$.

Now, we provide a theoretical analysis to demonstrate that TT-OPD provides an unbiased estimator of the gradient of the reverse KL divergence, as shown in Theorem 4.1.

Theorem 4.1. *[Proof is in Section A.] At any fixed $Z_t = (x, y_{<t})$, the TT-OPD loss in Eq. (1) satisfies*

$$\mathbb{E}_{y_t \sim p_t} [\nabla_{\theta} \mathcal{L}_t^{\text{TT}}(\theta) \mid Z_t] = g_t^*. \quad (2)$$

4.2 Discussion of TT-OPD

Compared with ST-OPD, FV-OPD, and TK-OPD, TT-OPD combines their complementary advantages without inheriting their main limitations. Firstly, like ST-OPD and FV-OPD, TT-OPD provides an unbiased estimator of the gradient of the reverse KL divergence. However, ST-OPD provides limited distributional supervision, which can degrade accuracy, while FV-OPD incurs a prohibitive computational cost of

$O(|\mathcal{V}|)$. In contrast, TT-OPD provides rich distributional supervision at a vocabulary-independent cost of only $O(k+1)$. Secondly, TT-OPD retains the rich distributional supervision and low computational cost of TK-OPD, while avoiding its gradient bias. Consequently, TT-OPD is as suitable for modern large-vocabulary LLMs as ST-OPD and TK-OPD, while significantly outperforming both in our experiments.

Additionally, the core of TT-OPD is to replace only the per-position OPD loss. This makes TT-OPD compatible with improvements to other components of the OPD pipeline. For example, TT-OPD can be combined with OPD variants that avoid sampling complete rollouts through fixed, progressive, truncated, or adaptive rollout horizons. These include Early Stopping Rollout (ESR) (Zhou et al. 2026), Progressive OPD (POPD), Truncated OPD (TOPD) (Zhang et al. 2026b), and KAT (Xin et al. 2026). Under these combinations, the TT-OPD loss is computed only at the retained positions. Moreover, TT-OPD can be combined with OPD variants that reweight token positions. Examples include Teachability-Aware OPD (TA-OPD) (Wang et al. 2026) and Importance-Weighted OPD (IW-OPD) (Xie et al. 2026). These variants determine the position weights, whereas TT-OPD determines how the gradient of the reverse-KL divergence is estimated. These examples are not exhaustive; due to space limitations, we do not enumerate all compatible OPD improvements.

5 Experiments

5.1 Experimental Setup

Models and Training Data. Unless otherwise stated, we employ the Qwen3 model series (Yang et al. 2025). Specifically, the teacher is Qwen3-8B-Base-GRPO-Math, which is obtained by training Qwen3-8B-Base with GRPO on DAPO-Math-17K (Li et al. 2026). The students are Qwen3-4B-Base and Qwen3-1.7B-Base. All models used in this paper have thinking mode enabled to achieve the highest possible accuracy. Unless otherwise stated, all OPD variants tested in this paper are trained on DAPO-Math-17K for two epochs.

Baselines and Training Configuration. Unless otherwise stated, we compare TT-OPD against ST-OPD and TK-OPD. FV-OPD is omitted as using the entire vocabulary at every position is prohibitively expensive. Unless otherwise stated, TK-OPD and TT-OPD both use the student’s top-16 set tokens, following the default configuration of Li et al. (2026). We use a training temperature of 1.0, batch size of 256, one rollout per prompt, a maximum prompt length of 2,048, a maximum response length of 8,192, a learning rate of 10^{-6} , and top- $p = 1.0$. Our implementation is based on verl (Sheng et al. 2024), and all experiments are run on a server with eight NVIDIA H200 GPUs and 1,600 GB of system memory.

Evaluation Configuration. Unless otherwise stated, we evaluate on seven mathematical reasoning benchmarks: AIME 2024, AIME 2025, AIME 2026, AMC, MATH, Minerva, and Olympiad. We sample 32 responses per prompt for AIME 2024, AIME 2025, AIME 2026, and AMC, and 8 responses per prompt for others. All responses are sampled with temperature 0.6, top- $p = 0.95$, top- $k = 20$, and a maximum response length of 32,768 tokens.

	AIME24	AIME25	AIME26	AMC	MATH	Minerva	Olympiad	Avg.
Teacher	31.15	24.69	22.71	70.63	88.02	38.10	58.91	47.74
<i>Qwen3-4B-Base Student</i>								
Student	8.02	5.31	6.15	30.80	54.07	22.79	25.22	21.77
ST-OPD	21.04	19.17	14.27	57.83	84.67	34.33	53.44	40.68
TK-OPD	19.79	19.17	14.27	59.04	85.23	35.29	52.31	40.73
TT-OPD	26.77	23.33	22.92	64.87	86.08	36.81	54.70	45.07
<i>Qwen3-1.7B-Base Student</i>								
Student	3.65	1.04	2.81	25.34	52.45	15.99	22.93	17.74
ST-OPD	9.79	2.50	2.08	37.05	66.33	20.59	30.91	24.18
TK-OPD	8.54	2.40	4.90	35.54	68.00	22.47	31.39	24.75
TT-OPD	14.17	6.98	8.33	42.13	69.60	24.63	36.48	28.90

Table 2: **Main results on mathematical reasoning (accuracy, %).** Qwen3-8B-Base-GRPO-Math is the teacher for all tested algorithms. All tested algorithms use DAPO-Math-17K as the training set. The student’s top-16 tokens are used as the selected top- k tokens. **Bold** = best among the tested algorithms within each student block.

5.2 Main Results on Mathematical Reasoning

Finding 1. TT-OPD consistently outperforms ST-OPD and TK-OPD across student scales.

To evaluate our TT-OPD, we compare it with ST-OPD and TK-OPD on seven mathematical reasoning benchmarks. We report accuracy and pass@ k in Table 2 and Table 7 (Appendix B), respectively. In terms of accuracy, TT-OPD achieves the highest average for both students. Compared with ST-OPD, it improves average accuracy by 4.39 and 4.72 percentage points for Qwen3-4B-Base and Qwen3-1.7B-Base, respectively. Compared with TK-OPD, the corresponding improvements are 4.34 and 4.15 percentage points. Moreover, TT-OPD outperforms both baselines on all seven benchmarks for each student. In terms of pass@ k , TT-OPD again achieves the highest average for both students. It improves over ST-OPD by 4.20 and 1.63 percentage points and over TK-OPD by 7.88 and 1.73 percentage points for Qwen3-4B-Base and Qwen3-1.7B-Base, respectively. These results demonstrate the superior performance of TT-OPD over the other OPD variants across student scales.

5.3 Sensitivity to the Number of Selected Tokens

Finding 2. TT-OPD consistently outperforms ST-OPD and TK-OPD across all tested values of k .

To evaluate the sensitivity of TT-OPD to the number of selected tokens, we vary k . The accuracy and pass@ k results are shown in Table 3 and Table 8 (Appendix B), respectively. TT-OPD achieves the highest average accuracy and average pass@ k for every tested k . Across the four values of k , TT-OPD improves average accuracy over ST-OPD and TK-OPD by 4.03–5.03 and 3.86–5.17 percentage points, respectively, while improving average pass@ k by 2.38–8.71 and 6.97–8.71 percentage points. These results demonstrate that TT-OPD consistently achieves better performance than TK-OPD.

5.4 Training Efficiency

Finding 3. TT-OPD increases training time by at most approximately 2% over TK-OPD.

To evaluate the computational cost of TT-OPD, we compare its training time with TK-OPD for $k \in \{8, 16, 32, 64\}$. The experimental results are shown in Table 4. Across the eight matched configurations, TT-OPD adds only 10–15 minutes. The largest relative increase is about 2%. This result is consistent with TT-OPD’s vocabulary-independent computational cost of $O(k + 1)$, which is nearly identical to the $O(k)$ computational cost of TK-OPD. These results demonstrate that TT-OPD introduces only marginal additional computational cost over TK-OPD.

5.5 Robustness to Different Selected Top- k Tokens

Finding 4. TT-OPD consistently outperforms TK-OPD across different selected top- k tokens.

To evaluate the robustness of TT-OPD across different selected top- k tokens, we use the student’s top- k tokens, the teacher’s top- k tokens, or their overlap. The accuracy and pass@ k results are shown in Table 5 and Table 9 (Appendix B), respectively. TT-OPD improves average accuracy over TK-OPD by 4.10–4.34 percentage points and average pass@ k by 5.36–7.88 percentage points. These results demonstrate the robustness of TT-OPD across different constructions of the top- k token set.

5.6 Robustness to Different Model Series

Finding 5. TT-OPD consistently outperforms ST-OPD and TK-OPD across different model series.

To examine the robustness of TT-OPD across different model series, we employ DeepSeek-R1-Distill-Qwen-7B (Guo et al. 2025) as the student and Skywork-OR1-Math-

	AIME24	AIME25	AIME26	AMC	MATH	Minerva	Olympiad	Avg.
ST-OPD	21.04	19.17	14.27	57.83	84.67	34.33	53.44	40.68
$k = 8$								
TK-OPD	16.46	17.50	14.58	55.72	84.90	34.15	53.50	39.54
TT-OPD	27.60	22.60	21.88	62.88	85.70	36.35	55.96	44.71
$k = 16$								
TK-OPD	19.79	19.17	14.27	59.04	85.23	35.29	52.31	40.73
TT-OPD	26.77	23.33	22.92	64.87	86.08	36.81	54.70	45.07
$k = 32$								
TK-OPD	20.21	18.65	16.67	58.73	85.50	35.06	52.69	41.07
TT-OPD	28.02	24.17	21.98	64.38	85.90	37.27	56.06	45.40
$k = 64$								
TK-OPD	22.19	20.00	15.42	60.24	84.00	37.55	53.57	41.85
TT-OPD	28.85	22.60	24.79	65.06	86.00	37.50	55.20	45.71

Table 3: **Sensitivity to the number of selected tokens (accuracy, %).** Qwen3-8B-Base-GRPO-Math is the teacher, Qwen3-4B-Base is the student, and all tested algorithms use DAPO-Math-17K as the training set. The student’s top-16 tokens are used as the selected top- k tokens. ST-OPD does not depend on k . **Bold** = best among the tested algorithms for each value of k .

k	TK-OPD	TT-OPD
<i>Qwen3-4B-Base Student</i>		
$k = 8$	13 h 27 min	13 h 41 min
$k = 16$	13 h 27 min	13 h 41 min
$k = 32$	13 h 36 min	13 h 48 min
$k = 64$	13 h 49 min	13 h 59 min
<i>Qwen3-1.7B-Base Student</i>		
$k = 8$	12 h 42 min	12 h 54 min
$k = 16$	12 h 51 min	13 h 01 min
$k = 32$	12 h 55 min	13 h 06 min
$k = 64$	13 h 42 min	13 h 57 min

Table 4: **Training time of TK-OPD and TT-OPD.** Qwen3-8B-Base-GRPO-Math is the teacher. Except for k range in {8, 16, 32, 64}, all other configurations are identical to those described in Section 5.1 .

7B (He et al. 2025) as the teacher that is obtained by further RL post-training from DeepSeek-R1-Distill-Qwen-7B. Except for replacing the training set with DeepScaleR (Tan et al. 2025), all configurations are identical to those described in Section 5.1. The accuracy and pass@ k results are shown in Table 6 and Table 10 (Appendix B), respectively. TT-OPD improves average accuracy over ST-OPD and TK-OPD by 4.21 and 2.20 percentage points, respectively, while improving average pass@ k by 1.15 and 2.76 percentage points. Together with the Qwen3 results in Table 2, these results demonstrate the robustness of TT-OPD across different model series.




Figure 2: **Code-generation results (average accuracy, %).** Qwen3-8B-Base-GRPO-Code is the teacher, Qwen3-4B-Base is the student, and all tested algorithms use the Code subset of Eurur-2-RL-Data as the training set. The student’s top-16 tokens are used as the selected top- k tokens.

5.7 Robustness to Different Tasks

Finding 6. TT-OPD consistently outperforms ST-OPD and TK-OPD on code generation task.

To test the robustness of TT-OPD across different tasks, we conduct experiments on the code-generation task. The teacher is Qwen3-8B-Base-GRPO-Code, which is trained from Qwen3-8B-Base with GRPO on 25K code-generation samples from the Code subset of Eurur-2-RL-Data (Cui et al. 2025), as done in Hou et al. (2026). We use Qwen3-4B-Base as the student and train on the same 25K samples for three epochs. We evaluate on HumanEval+ (Liu et al. 2023), MBPP+ (Liu et al. 2023), and LiveCodeBench (v6 only) (Jain et al. 2025), as done in Hou et al. (2026). We sample four responses per prompt. All other configurations are identical to those described in Section 5.1. The average accuracy results are shown in Figure 2, while the corresponding per-dataset accuracy and pass@4 results are reported in Tables 11 and 12 (Appendix B). We observe that TT-OPD improves

	AIME24	AIME25	AIME26	AMC	MATH	Minerva	Olympiad	Avg.
<i>Student Top-k</i>								
TK-OPD	19.79	19.17	14.27	59.04	85.23	35.29	52.31	40.73
TT-OPD	26.77	23.33	22.92	64.87	86.08	36.81	54.70	45.07
<i>Teacher Top-k</i>								
TK-OPD	21.56	17.71	14.90	57.83	84.75	35.66	53.76	40.88
TT-OPD	27.08	25.83	20.21	64.83	86.58	35.66	54.70	44.98
<i>Teacher-Student Top-k Overlap</i>								
TK-OPD	20.21	18.33	15.73	59.30	85.02	35.02	53.22	40.98
TT-OPD	26.77	24.17	23.96	62.69	86.83	37.50	55.33	45.32

Table 5: **Results with different selected top- k tokens (accuracy, %).** Qwen3-8B-Base-GRPO-Math is the teacher, Qwen3-4B-Base is the student, and all tested algorithms use DAPO-Math-17K as the training set. We set $k = 16$. **Bold** = best among the tested algorithms within each top- k block.

	AIME24	AIME25	AIME26	AMC	MATH	Minerva	Olympiad	Avg.
Teacher	64.69	56.15	64.17	89.68	96.95	41.18	74.78	69.66
<i>DeepSeek-R1-Distill-Qwen-7B Student</i>								
Student	54.58	40.00	47.50	82.83	94.27	37.50	67.15	60.55
ST-OPD	57.19	46.15	55.31	86.60	95.15	38.51	72.09	64.43
TK-OPD	58.12	51.15	61.56	87.50	95.08	38.47	73.17	66.44
TT-OPD	63.96	54.90	62.50	88.55	96.38	40.49	73.69	68.64

Table 6: **Results on another model series (accuracy, %).** Skywork-OR1-Math-7B is the teacher, DeepSeek-R1-Distill-Qwen-7B is the student, and all tested algorithms use DeepScaleR as the training set. The student’s top-16 tokens are used as the selected top- k tokens. **Bold** = best among the tested algorithms.

average accuracy over ST-OPD and TK-OPD by 1.49 and 0.72 percentage points, respectively, while improving average pass@4 by 1.07 and 2.32 percentage points. Together with the results on mathematical reasoning tasks, these results show the robustness of TT-OPD across different tasks.

5.8 Importance of the Tail Correction

Finding 7. Tail correction is important to TT-OPD’s performance gains.

To evaluate the importance of the tail correction, we construct TT-OPD w/o TC by removing only the tail correction term, *e.g.*, the second term in Eq. (1). The experimental results are shown in Figure 3, and the corresponding per-dataset accuracy and pass@ k results are reported in Tables 13 and 14 (Appendix B). Removing the tail correction reduces average accuracy by 5.79 and 10.76 percentage points for Qwen3-4B-Base and Qwen3-1.7B-Base, respectively. Relative to TK-OPD, the ablated variant is 1.45 and 6.61 percentage points worse for the 4B and 1.7B students, whereas TT-OPD is 4.34 and 4.15 percentage points better. Therefore, the tail correction is needed to account for probability mass outside the selected top- k tokens. These results show that tail correction is important to TT-OPD’s performance gains.




Figure 3: **Tail-correction ablation (average accuracy, %).** Qwen3-8B-Base-GRPO-Math is the teacher, Qwen3-4B-Base and Qwen3-1.7B-Base are the students, and all tested algorithms use DAPO-Math-17K as the training set. The student’s top-16 tokens are used as the selected top- k tokens.

6 Conclusions

In this paper, we propose TT-OPD, a novel OPD variant that provides unbiased reverse KL divergence gradient estimation, rich distributional supervision, and low computational cost. To the best of our knowledge, TT-OPD is the first OPD variant to simultaneously provide all three properties. Experiments across student scales, model series, selected top- k tokens, values of k , and tasks demonstrate that TT-OPD significantly outperforms other tested OPD variants.

References

- Agarwal, R.; Vieillard, N.; Zhou, Y.; Stanczyk, P.; Ramos Garea, S.; Geist, M.; and Bachem, O. 2024. On-Policy Distillation of Language Models: Learning from Self-Generated Mistakes. In *Proceedings of the 12th International Conference on Learning Representations*.
- Cha, J.; Kang, W.; Mun, J.; and Roh, B. 2024. Honeybee: Locality-Enhanced Projector for Multimodal LLM. In *Proceedings of the 41st IEEE/CVF Conference on Computer Vision and Pattern Recognition*.
- Cui, G.; Yuan, L.; Wang, Z.; Wang, H.; Zhang, Y.; Chen, J.; Li, W.; He, B.; Fan, Y.; Yu, T.; et al. 2025. Process Reinforcement through Implicit Rewards. *arXiv preprint arXiv:2502.01456*.
- Deng, X.; Zhong, H.; Ai, R.; Feng, F.; Wang, Z.; and He, X. 2026. Less Is More: Improving LLM Alignment via Preference Data Selection. In *Proceedings of the 39th International Conference on Neural Information Processing*.
- Fu, Y.; Huang, H.; Jiang, K.; Liu, J.; Jiang, Z.; Zhu, Y.; and Zhao, D. 2026. Revisiting On-Policy Distillation: Empirical Failure Modes and Simple Fixes. *arXiv preprint arXiv:2603.25562*.
- Gu, Y.; Dong, L.; Wei, F.; and Huang, M. 2024. MiniLLM: Knowledge Distillation of Large Language Models. In *Proceedings of the 12th International Conference on Learning Representations*.
- Guo, D.; Yang, D.; Zhang, H.; Song, J.; Wang, P.; Zhu, Q.; Xu, R.; Zhang, R.; Ma, S.; Bi, X.; et al. 2025. DeepSeek-R1: Incentivizing Reasoning Capability in LLMs via Reinforcement Learning. *arXiv preprint arXiv:2501.12948*.
- Guo, Y.; Yang, W.; Sun, Z.; Ding, N.; Liu, Z.; and Lin, Y. 2026. Learning to Focus: Causal Attention Distillation via Gradient-Guided Token Pruning.
- He, J.; Liu, J.; Liu, C. Y.; Yan, R.; Wang, C.; Cheng, P.; Zhang, X.; Zhang, F.; Xu, J.; Shen, W.; et al. 2025. Skywork Open Reasoner 1 Technical Report. *arXiv preprint arXiv:2505.22312*.
- Hinton, G.; Vinyals, O.; and Dean, J. 2015. Distilling the Knowledge in a Neural Network. *arXiv preprint arXiv:1503.02531*.
- Hou, W.; Peng, S.; Wang, W.; Ruan, Z.; Zhang, Y.; Zhou, Z.; Gao, M.; Chen, Y.; Wang, K.; Yang, H.; et al. 2026. Uni-OPD: Unifying On-Policy Distillation with a Dual-Perspective Recipe. *arXiv preprint arXiv:2605.03677*.
- Hübötter, J.; Lübeck, F.; Behric, L.; Baumann, A.; Bagatella, M.; Marta, D.; Hakimi, I.; Shenfeld, I.; Buening, T. K.; Guestrin, C.; et al. 2026. Reinforcement Learning via Self-Distillation. *arXiv preprint arXiv:2601.20802*.
- Jain, N.; Gu, A.; Li, W.-D.; Yan, F.; Zhang, T.; Wang, S.; Solar-Lezama, A.; Sen, K.; and Stoica, I. 2025. Live-CodeBench: Holistic and Contamination Free Evaluation of Large Language Models for Code. In *Proceedings of the 13th International Conference on Learning Representations*.
- Kevin, L.; and Lab, T. M. 2025. On-Policy Distillation.
- Ko, J.; Chen, T.; Kim, S.; Ding, T.; Liang, L.; Zharkov, I.; and Yun, S.-Y. 2025. DistillM-2: A Contrastive Approach Boosts the Distillation of LLMs. *arXiv preprint arXiv:2503.07067*.
- Li, Y.; Zuo, Y.; He, B.; Zhang, J.; Xiao, C.; Qian, C.; Yu, T.; Gao, H.-a.; Yang, W.; Liu, Z.; et al. 2026. Re-thinking On-Policy Distillation of Large Language Models: Phenomenology, Mechanism, and Recipe. *arXiv preprint arXiv:2604.13016*.
- Liu, J.; Xia, C. S.; Wang, Y.; and Zhang, L. 2023. Is Your Code Generated by ChatGPT Really Correct? Rigorous Evaluation of Large Language Models for Code Generation. In *Proceedings of the 36th International Conference on Neural Information Processing*.
- Liu, J.; Zhang, C.; Guo, J.; Zhang, Y.; Que, H.; Deng, K.; Bai, Z.; Liu, J.; Zhang, G.; Wang, J.; et al. 2024. DDK: Distilling Domain Knowledge for Efficient Large Language Models. In *Proceedings of the 37th International Conference on Neural Information Processing*.
- Oh, M.; Song, S.; Choi, G.; Choi, Y.; and Jo, Y. 2026. KL for a KL: On-Policy Distillation with Control Variate Baseline. *arXiv preprint arXiv:2605.07865*.
- Shenfeld, I.; Damani, M.; Hübötter, J.; and Agrawal, P. 2026. Self-Distillation Enables Continual Learning. *arXiv preprint arXiv:2601.19897*.
- Sheng, G.; Zhang, C.; Ye, Z.; Wu, X.; Zhang, W.; Zhang, R.; Peng, Y.; Lin, H.; and Wu, C. 2024. Hybridflow: A flexible and efficient rlhf framework. *arXiv preprint arXiv:2409.19256*.
- Song, M.; and Zheng, M. 2026. A Survey of On-Policy Distillation for Large Language Models. *arXiv preprint arXiv:2604.00626*.
- Tan, S.; Luo, M.; Wong, J.; Cai, C.; Shi, X.; Tang, W. Y.; Roongta, M.; Zhang, T.; Li, L. E.; Popa, R. A.; et al. 2025. DeepScaleR: Effective RL Scaling of Reasoning Models via Iterative Context Lengthening.
- Wang, Y.; Kordi, Y.; Mishra, S.; Liu, A.; Smith, N. A.; Khazabi, D.; and Hajishirzi, H. 2023. Self-Instruct: Aligning Language Models with Self-Generated Instructions. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics*.
- Wang, Y.; Lu, S.; Gu, Y.; Wang, P.; Yang, Y.; Yan, Z.; Xie, C.; Wu, J.; and Yang, H. 2026. Not All Disagreement Is Learnable: Token Teachability in On-Policy Distillation. *arXiv preprint arXiv:2605.26844*.
- Wu, Y.; Han, S.; and Cai, H. 2026. Lightning OPD: Efficient Post-Training for Large Reasoning Models with Offline On-Policy Distillation. *arXiv preprint arXiv:2604.13010*.
- Xiao, B.; Xia, B.; Yang, B.; Gao, B.; Shen, B.; Zhang, C.; He, C.; Lou, C.; Luo, F.; Wang, G.; et al. 2026. MiMo-V2-Flash Technical Report. *arXiv preprint arXiv:2601.02780*.
- Xie, Y.; Zhu, S.; Wen, T.; Chen, B.; and Wang, Y. 2026. On the Position Bias of On-Policy Distillation. *arXiv preprint arXiv:2606.22600*.
- Xin, H.; Zhao, A.; Sun, Y.; Li, J.; Shen, X.; and Xiong, H. 2026. Escaping the KL Agreement Trap in On-Policy Distillation. *arXiv preprint arXiv:2606.09471*.

Xu, A.; Lin, B.; Xue, B.; Wang, B.; Xu, B.; Wu, B.; Zhang, B.; Lin, C.; Dong, C.; Ling, C.; et al. 2026. DeepSeek-V4: Towards Highly Efficient Million-Token Context Intelligence. *arXiv preprint arXiv:2606.19348*.

Xu, W.; Han, R.; Wang, Z.; Le, L.; Madeka, D.; Li, L.; Wang, W.; Agarwal, R.; Lee, C.-Y.; and Pfister, T. 2025. Speculative Knowledge Distillation: Bridging the Teacher-Student Gap through Interleaved Sampling. In *Proceedings of the 13th International Conference on Learning Representations*.

Xu, X.; Li, M.; Tao, C.; Shen, T.; Cheng, R.; Li, J.; Xu, C.; Tao, D.; and Zhou, T. 2024. A Survey on Knowledge Distillation of Large Language Models. *arXiv preprint arXiv:2402.13116*.

Yang, A.; Li, A.; Yang, B.; Zhang, B.; Hui, B.; Zheng, B.; Yu, B.; Gao, C.; Huang, C.; Lv, C.; et al. 2025. Qwen3 Technical Report. *arXiv preprint arXiv:2505.09388*.

Yang, W.; Liu, W.; Xie, R.; Yang, K.; Yang, S.; and Lin, Y. 2026. Learning beyond Teacher: Generalized On-Policy Distillation with Reward Extrapolation. *arXiv preprint arXiv:2602.12125*.

Zeng, A.; Lv, X.; Hou, Z.; Du, Z.; Zheng, Q.; Chen, B.; Yin, D.; Ge, C.; Huang, C.; Xie, C.; et al. 2026. GLM-5: From Vibe Coding to Agentic Engineering. *arXiv preprint arXiv:2602.15763*.

Zhang, K.; Wu, K.; Yang, Z.; Li, B.; Hu, K.; Wang, B.; Li, X.; and Bing, L. 2026a. OpenMMReasoner: Pushing the Frontiers in Multimodal Reasoning with an Open and General Recipe. In *Proceedings of the 43th IEEE/CVF Conference on Computer Vision and Pattern Recognition*.

Zhang, Y.; Chai, J.; Fu, Y.; Tu, S.; Wang, X.; Lin, W.; Yin, G.; Zhang, Q.; Zhu, Y.; and Zhao, D. 2026b. Are Full Roll-outs Necessary for On-Policy Distillation? *arXiv preprint arXiv:2605.31490*.

Zhang, Y.; Ni, B.; Chen, X.-S.; Zhang, H.-R.; Rao, Y.; Peng, H.; Lu, Q.; Hu, H.; Guo, M.-H.; and Hu, S.-M. 2025. Bee: A High-Quality Corpus and Full-Stack Suite to Unlock Advanced Fully Open MLLMs. *arXiv preprint arXiv:2510.13795*.

Zhao, S.; Xie, Z.; Liu, M.; Huang, J.; Pang, G.; Chen, F.; and Grover, A. 2026. Self-Distilled Reasoner: On-Policy Self-Distillation for Large Language Models. *arXiv preprint arXiv:2601.18734*.

Zheng, B.; Ma, X.; Liang, Y.; Ruan, J.; Fu, X.; Lin, K.; Zhu, B.; Zeng, K.; and Cai, X. 2026. SCOPE: Signal-Calibrated On-Policy Distillation Enhancement with Dual-Path Adaptive Weighting. *arXiv preprint arXiv:2604.10688*.

Zhou, Z.; Li, J.; Tang, H.; Wu, Y. N.; and Terzopoulos, D. 2026. Less Is More: Early Stopping Rollout for On-Policy Distillation. *arXiv preprint arXiv:2605.27028*.

Zhu, S.; Ye, X.; Lu, H.; Shi, W.; and Liu, G. 2026. The Many Faces of On-Policy Distillation: Pitfalls, Mechanisms, and Fixes. *arXiv preprint arXiv:2605.11182*.

A Proof of Theorem 4.1

Proof. We condition on a fixed student-visited state $Z_t = (x, y_{<t})$ and its selected token set S_t^k . For simplicity, write $S = S_t^k$, $p(v) = p_t(v)$, $q(v) = q_t(v)$, and $A(v) = \log \frac{p(v)}{q(v)}$. Following the stop-gradient treatment in Eq. (1), we have

$$\begin{aligned} \nabla_{\theta} \mathcal{L}_t^{\text{TT}}(\theta) &= \sum_{v \in S} A(v) \nabla_{\theta} p(v) \\ &\quad + \mathbb{1}\{y_t \notin S\} A(y_t) \nabla_{\theta} \log p(y_t). \end{aligned}$$

Since $y_t \sim p_t$, taking expectation over the sampled token gives

$$\begin{aligned} &\mathbb{E}_{y_t \sim p_t} [\nabla_{\theta} \mathcal{L}_t^{\text{TT}}(\theta)] \\ &= \sum_{v \in S} A(v) \nabla_{\theta} p(v) + \sum_{v \notin S} p(v) A(v) \nabla_{\theta} \log p(v) \\ &= \sum_{v \in \mathcal{V}} A(v) \nabla_{\theta} p(v). \end{aligned} \tag{3}$$

On the other hand, the FV-OPD loss at this position satisfies

$$\begin{aligned} \nabla_{\theta} \mathcal{L}_t^{\text{FV}}(\theta) &= \nabla_{\theta} \sum_{v \in \mathcal{V}} p(v) \log \frac{p(v)}{q(v)} \\ &= \sum_{v \in \mathcal{V}} \nabla_{\theta} p(v) \left(\log \frac{p(v)}{q(v)} + 1 \right) \\ &= \sum_{v \in \mathcal{V}} A(v) \nabla_{\theta} p(v), \end{aligned} \tag{4}$$

where the last equality follows from $\sum_{v \in \mathcal{V}} \nabla_{\theta} p(v) = \nabla_{\theta} 1 = 0$. Combining Eq. (3) and Eq. (4) yields

$$\mathbb{E}_{y_t \sim p_t} [\nabla_{\theta} \mathcal{L}_t^{\text{TT}}(\theta)] = \nabla_{\theta} \mathcal{L}_t^{\text{FV}}(\theta). \tag{5}$$

Eq. (5) is exactly Eq. (2), which proves Theorem 4.1. $\square$

B Full Experimental Results

This section provides the complete per-dataset results that supplement the main paper: pass@ k results for the mathematical-reasoning experiments, and both accuracy and pass@ k results for code generation and the tail-correction ablation.

	AIME24	AIME25	AIME26	AMC	MATH	Minerva	Olympiad	Avg.
Teacher	53.33	40.00	40.00	86.75	93.20	46.32	70.81	61.49
<i>Qwen3-4B-Base Student</i>								
Student	26.67	26.67	20.00	63.86	76.20	36.03	42.37	41.69
ST-OPD	40.00	40.00	33.33	79.52	90.40	42.65	63.70	55.66
TK-OPD	43.33	26.67	26.67	71.08	88.60	41.91	65.63	51.98
TT-OPD	56.67	43.33	43.33	80.72	92.20	37.87	64.89	59.86
<i>Qwen3-1.7B-Base Student</i>								
Student	20.00	10.00	10.00	53.01	70.80	28.31	35.70	32.55
ST-OPD	30.00	10.00	6.67	59.04	76.00	27.57	43.56	36.12
TK-OPD	23.33	10.00	16.67	54.22	76.80	29.78	41.33	36.02
TT-OPD	26.67	20.00	23.33	59.04	70.80	26.47	37.93	37.75

Table 7: **Pass@ k results on mathematical reasoning (%)**. Unlike average accuracy, which averages correctness over all sampled responses, pass@ k is the percentage of problems for which at least one of the k sampled responses is correct. We report pass@32 on AIME24, AIME25, AIME26, and AMC, and pass@8 on MATH, Minerva, and Olympiad. All other settings are identical to those in Table 2. **Bold** = best among the tested algorithms within each student block.

	AIME24	AIME25	AIME26	AMC	MATH	Minerva	Olympiad	Avg.
ST-OPD	40.00	40.00	33.33	79.52	90.40	42.65	63.70	55.66
$k = 8$								
TK-OPD	40.00	23.33	26.67	73.49	90.60	41.18	62.22	51.07
TT-OPD	56.67	36.67	43.33	81.93	92.40	37.50	57.78	58.04
$k = 16$								
TK-OPD	43.33	26.67	26.67	71.08	88.60	41.91	65.63	51.98
TT-OPD	56.67	43.33	43.33	80.72	92.20	37.87	64.89	59.86
$k = 32$								
TK-OPD	40.00	33.33	30.00	75.90	91.60	41.91	60.74	53.35
TT-OPD	56.67	36.67	50.00	80.72	91.40	43.38	66.07	60.70
$k = 64$								
TK-OPD	46.67	30.00	36.67	80.72	91.20	42.28	62.07	55.66
TT-OPD	56.67	53.33	50.00	87.95	94.00	43.01	65.63	64.37

Table 8: **Pass@ k results for different numbers of selected tokens (%)**. We report pass@32 on AIME24, AIME25, AIME26, and AMC, and pass@8 on MATH, Minerva, and Olympiad. All other settings are identical to those in Table 3. ST-OPD does not depend on k . **Bold** = best between TK-OPD and TT-OPD within each k block.

	AIME24	AIME25	AIME26	AMC	MATH	Minerva	Olympiad	Avg.
<i>Student Top-k</i>								
TK-OPD	43.33	26.67	26.67	71.08	88.60	41.91	65.63	51.98
TT-OPD	56.67	43.33	43.33	80.72	92.20	37.87	64.89	59.86
<i>Teacher Top-k</i>								
TK-OPD	46.67	30.00	30.00	72.29	88.20	37.87	62.37	52.49
TT-OPD	43.33	33.33	43.33	81.93	92.40	44.85	65.78	57.85
<i>Teacher-Student Top-k Overlap</i>								
TK-OPD	40.00	26.67	30.00	77.11	89.00	44.49	61.33	52.66
TT-OPD	50.00	46.67	40.00	80.72	90.80	40.44	63.26	58.84

Table 9: **Pass@ k results with different selected top- k tokens (%)**. We report pass@32 on AIME24, AIME25, AIME26, and AMC, and pass@8 on MATH, Minerva, and Olympiad. All other settings are identical to those in Table 5. **Bold** = best among the tested algorithms within each top- k block.

	AIME24	AIME25	AIME26	AMC	MATH	Minerva	Olympiad	Avg.
Teacher	86.67	80.00	80.00	100.00	99.00	47.06	82.37	82.16
<i>DeepSeek-R1-Distill-Qwen-7B Student</i>								
Student	83.33	73.33	76.67	96.39	98.00	44.85	82.52	79.30
ST-OPD	83.33	76.67	80.00	97.59	98.80	47.06	82.22	80.81
TK-OPD	80.00	70.00	76.67	98.80	98.60	47.06	83.26	79.20
TT-OPD	83.33	80.00	80.00	100.00	98.40	48.16	83.85	81.96

Table 10: **Pass@ k results on another model series (%)**. We report pass@32 on AIME24, AIME25, AIME26, and AMC, and pass@8 on MATH, Minerva, and Olympiad. All other settings are identical to those in Table 6. **Bold** = best among the tested algorithms.

	HumanEval+	MBPP+	LiveCodeBench	Avg.
Teacher	77.44	71.96	27.43	58.94
<i>Qwen3-4B-Base Student</i>				
Student	18.14	13.16	16.14	15.81
ST-OPD	72.10	68.72	24.29	55.04
TK-OPD	74.70	68.72	24.00	55.81
TT-OPD	75.00	69.44	25.14	56.53

Table 11: **Per-dataset code-generation results (accuracy, %)**. Qwen3-8B-Base-GRPO-Code is the teacher, Qwen3-4B-Base is the student, and all tested algorithms use the Code subset of Euror-2-RL-Data as the training set. The student’s top-16 tokens are used as the selected token set. **Bold** = best among the tested algorithms.

	HumanEval+	MBPP+	LiveCodeBench	Avg.
Teacher	87.20	80.42	31.43	66.35
<i>Qwen3-4B-Base Student</i>				
Student	48.78	41.27	28.00	39.35
ST-OPD	84.15	78.84	28.00	63.66
TK-OPD	81.71	77.51	28.00	62.41
TT-OPD	85.37	79.10	29.71	64.73

Table 12: **Per-dataset code-generation results (pass@4, %)**. All other settings are identical to those in Table 11. **Bold** = best among the tested algorithms.

	AIME24	AIME25	AIME26	AMC	MATH	Minerva	Olympiad	Avg.
Teacher	31.15	24.69	22.71	70.63	88.02	38.10	58.91	47.74
<i>Qwen3-4B-Base Student</i>								
Initial Student	8.02	5.31	6.15	30.80	54.07	22.79	25.22	21.77
TK-OPD	19.79	19.17	14.27	59.04	85.23	35.29	52.31	40.73
TT-OPD w/o TC	21.56	20.63	19.58	57.27	72.70	33.92	49.30	39.28
TT-OPD	26.77	23.33	22.92	64.87	86.08	36.81	54.70	45.07
<i>Qwen3-1.7B-Base Student</i>								
Initial Student	3.65	1.04	2.81	25.34	52.45	15.99	22.93	17.74
TK-OPD	8.54	2.40	4.90	35.54	68.00	22.47	31.39	24.75
TT-OPD w/o TC	4.69	1.88	3.02	20.75	56.93	12.50	27.22	18.14
TT-OPD	14.17	6.98	8.33	42.13	69.60	24.63	36.48	28.90

Table 13: **Per-dataset tail-correction ablation results (accuracy, %)**. Qwen3-8B-Base-GRPO-Math is the teacher, Qwen3-4B-Base and Qwen3-1.7B-Base are the students, and all tested algorithms use DAPO-Math-17K as the training set. The student’s top-16 tokens are used as the selected token set. “w/o TC” removes only the tail-correction term, i.e., the second term in Eq. (1). **Bold** = best among the tested algorithms within each student block.

	AIME24	AIME25	AIME26	AMC	MATH	Minerva	Olympiad	Avg.
Teacher	53.33	40.00	40.00	86.75	93.20	46.32	70.81	61.49
<i>Qwen3-4B-Base Student</i>								
Initial Student	26.67	26.67	20.00	63.86	76.20	36.03	42.37	41.69
TK-OPD	43.33	26.67	26.67	71.08	88.60	41.91	65.63	51.98
TT-OPD w/o TC	33.33	26.67	30.00	74.70	89.40	38.24	64.15	50.93
TT-OPD	56.67	43.33	43.33	80.72	92.20	37.87	64.89	59.86
<i>Qwen3-1.7B-Base Student</i>								
Initial Student	20.00	10.00	10.00	53.01	70.80	28.31	35.70	32.55
TK-OPD	23.33	10.00	16.67	54.22	76.80	29.78	41.33	36.02
TT-OPD w/o TC	20.00	10.00	10.00	53.01	76.00	27.21	41.04	33.89
TT-OPD	26.67	20.00	23.33	59.04	70.80	26.47	37.93	37.75

Table 14: **Per-dataset tail-correction ablation results (pass@k, %)**. We report pass@32 on AIME24, AIME25, AIME26, and AMC, and pass@8 on MATH, Minerva, and Olympiad. All other settings are identical to those in Table 13. **Bold** = best among the tested algorithms within each student block.

C Case Studies

We present three AIME-2024 examples for which TT-OPD produces the correct answer while ST-OPD and TK-OPD both fail. Each page compares one rollout from the three algorithms under the same student model. To preserve the character of the original generations, the lightly typeset excerpts retain first-person deliberation, reversals, and verification steps. Ellipses mark only repetitive or space-limited passages; the displayed final answers follow the original rollouts.

C.1 Qwen3-4B-Base Student

Question. Find the largest possible real part of

$$(75 + 117i)z + \frac{96 + 144i}{z}, \quad |z| = 4.$$

Reference answer: 540.

ST-OPD (Incorrect)

Model rollout (excerpt). “Alright, I have this problem to solve. First, I need to understand what’s being asked.” It sets

$$z = 4e^{i\theta}, \quad \frac{1}{z} = \frac{1}{4}e^{-i\theta},$$

but then rewrites the reciprocal coefficient as

$$\frac{96 + 144i}{z} = 24(1 + 2i)e^{-i\theta}.$$

“Wait, perhaps there’s a better way. Maybe I can express z in terms of its real and imaginary parts.” After briefly trying $z = x + iy$, it says, “This seems complicated. Maybe I can use the polar form after all.”

... continued reasoning omitted ...

Expanding the two terms, it writes

$$\operatorname{Re}(T_1) = 300 \cos \theta - 468 \sin \theta,$$

$$\operatorname{Re}(T_2) = 24 \cos \theta + 48 \sin \theta.$$

It nevertheless combines them as

$$\operatorname{Re}(T_1 + T_2) = 324 \cos \theta - 468 \sin \theta$$

and obtains $\sqrt{324^2 + 468^2} = 180\sqrt{10}$. After rechecking the square root, the rollout repeats the same answer several times.

Model answer:

$$\boxed{180\sqrt{10}}$$

TK-OPD (Incorrect)

Model rollout (excerpt). “Let’s compute each part separately.” With $z = 4e^{i\theta}$, it writes

$$(75 + 117i)z = 4(75 + 117i)e^{i\theta}$$

and

$$\frac{96 + 144i}{z} = 24(2 + 3i)e^{-i\theta}.$$

It denotes $A = 75 + 117i$ and $B = 2 + 3i$, giving

$$4A(\cos \theta + i \sin \theta) + 24Be^{-i\theta}.$$

The response then claims, “The real part here is $4A \cos \theta$,” and similarly takes the second real contribution to be $24B \cos \theta$.

... continued reasoning omitted ...

Thus it obtains

$$(4A + 24B) \cos \theta = (348 + 540i) \cos \theta.$$

“Wait, that doesn’t seem right.” It then discards the imaginary coefficient, concludes that the real part is $348 \cos \theta$, and maximizes it at $\cos \theta = 1$.

Model answer:

$$\boxed{348}$$

TT-OPD (Correct)

Model rollout (excerpt). “Let’s compute each part separately.” The rollout sets $z = 4e^{i\theta}$ and correctly keeps

$$\frac{96 + 144i}{4e^{i\theta}} = (24 + 36i)e^{-i\theta}.$$

Writing $w = e^{i\theta}$, it expands

$$300w + 468iw + 24\bar{w} + 36i\bar{w}.$$

It then checks the four contributions one at a time:

$$300w = 300 \cos \theta + 300i \sin \theta,$$

$$468iw = -468 \sin \theta + 468i \cos \theta,$$

$$24\bar{w} = 24 \cos \theta - 24i \sin \theta,$$

$$36i\bar{w} = 36 \sin \theta + 36i \cos \theta.$$

After combining like terms, the real part is

$$324 \cos \theta - 432 \sin \theta.$$

“Recall that $A \cos \theta + B \sin \theta$ has maximum $\sqrt{A^2 + B^2}$.” Therefore,

$$\sqrt{324^2 + 432^2} = \sqrt{291600} = 540.$$

Model answer:

$$\boxed{540}$$

Comparison. ST-OPD changes $(96 + 144i)/4$ into $24(1 + 2i)$, and TK-OPD incorrectly takes the real part of expressions with complex coefficients. TT-OPD preserves both sine and cosine contributions and therefore reaches the reference answer.

C.2 Qwen3-1.7B-Base Student

Question. Aya walks 9 kilometers and then spends t minutes in a coffee shop. At s km/h, the total time is 4 hours; at $s + 2$ km/h, it is 2 hours 24 minutes. How many minutes does the trip take at $s + \frac{1}{2}$ km/h, including the same coffee-shop time?

Reference answer: 204.

ST-OPD (Incorrect)	TK-OPD (Incorrect)	TT-OPD (Correct)
Model rollout (excerpt). “Alright, I have this problem about Aya’s morning walk. Let’s break it down step by step.” It correctly converts 2 hours 24 minutes to 2.4 hours, but then treats t itself as hours: $\frac{9}{s} + t = 4, \quad \frac{9}{s+2} + t = 2.4.$ Subtracting gives $\frac{18}{s(s+2)} = 1.6, \quad s^2 + 2s - 11.25 = 0.$ The quadratic formula yields $s = 2.5$ or -4.5, and it rejects the negative speed. ... continued reasoning omitted ... Substituting into its first equation, it writes $\frac{9}{2.5} + t = 4, \quad 3.6 + t = 4,$ then states $t = 0.4$ “minutes.” For the requested speed, $s + \frac{1}{2} = 3, \quad \frac{9}{3} = 3 \text{ hours}.$ It converts only this walking time to 180 minutes and nevertheless claims that the result includes the coffee-shop stop. Model answer: 180	Model rollout (excerpt). “First, I notice that the total times are given in hours and minutes.” Unlike ST-OPD, it converts the stop consistently: $\frac{9}{s} + \frac{t}{60} = 4, \quad \frac{9}{s+2} + \frac{t}{60} = 2.4.$ Eliminating $t/60$, it derives $\frac{18}{s(s+2)} = 1.6, \quad s^2 + 2s - 11.25 = 0,$ and selects $s = 2.5$. It then computes $3.6 + \frac{t}{60} = 4 \implies t = 24.$... continued reasoning omitted ... At $s + \frac{1}{2} = 3$, the response obtains $\frac{9}{3} + \frac{24}{60} = 3.4 \text{ hours} = 3 \text{ hours } 24 \text{ minutes}.$ Its prose conclusion is therefore correct. However, after the heading “Final Answer,” the emitted answer abruptly changes to 32, with no supporting calculation. Model answer: 32	Model rollout (excerpt). “We’ll set up equations based on the first two scenarios and solve for s and t.” It first records $t \text{ minutes} = \frac{t}{60} \text{ hours},$ and consequently uses $\frac{9}{s} + \frac{t}{60} = 4, \quad \frac{9}{s+2} + \frac{t}{60} = 2.4.$ Subtracting the equations gives $\frac{18}{s(s+2)} = 1.6, \quad s^2 + 2s - 11.25 = 0.$ It explicitly checks both quadratic roots and keeps $s = 2.5$ because speed cannot be negative. ... continued reasoning omitted ... Returning to the first equation, $\frac{9}{2.5} + \frac{t}{60} = 4 \implies t = 24.$ Finally, $\frac{9}{2.5 + \frac{1}{2}} + \frac{24}{60} = 3.4 \text{ hours},$ and the rollout performs the requested unit conversion: $3.4 \times 60 = 204 \text{ minutes}.$ Model answer: 204

Comparison. ST-OPD mixes minutes and hours and drops the coffee-shop time. TK-OPD reaches the correct intermediate result but emits an unrelated final answer. TT-OPD maintains unit consistency and agreement between its derivation and final answer.

C.3 DeepSeek-R1-Distill-Qwen-7B Student

Question. Let p be the least prime for which $p^2 \mid n^4 + 1$ for some positive integer n . Find the least positive integer m such that $p^2 \mid m^4 + 1$.

Reference answer: 110.

ST-OPD (Incorrect)

Model rollout (excerpt). After testing smaller primes, the response says, “Wait, perhaps $p = 17$.” It observes

$$2^4 = 16 \equiv -1 \pmod{17}$$

and checks $f'(2) = 4 \cdot 2^3 = 32 \not\equiv 0 \pmod{17}$, so Hensel’s lemma guarantees a lift.

... continued reasoning omitted ...

It considers only $x \equiv 2 \pmod{17}$. With $x = 2 + 17k$, the rollout obtains

$$17 + 255k \equiv 0 \pmod{289},$$

then divides by 17:

$$15k \equiv 16 \pmod{17}.$$

Hence $k \equiv 9 \pmod{17}$, so $x = 2 + 17 \cdot 9 = 155$. The response repeatedly asks, “Wait, is 155 the least positive integer m ?” It checks 138, 121, 104, 87, ..., all from the same residue class, and then concludes: “The minimal solution mod 289 is $m = 155$, because the lift from 2 mod 17 is unique.” It never enumerates the other three roots modulo 17.

Model answer:

155

TK-OPD (Incorrect)

Model rollout (excerpt). The rollout first follows the $x \equiv 2 \pmod{17}$ branch and obtains $x = 155$. It then pauses: “Wait, perhaps there is another solution where $x \equiv -2 \pmod{17}$.” Taking $x = 15 + 17k$, it expands

$$50 + 34k \equiv 288 \pmod{289}.$$

After dividing by 17, it solves

$$2k \equiv 14 \pmod{17}.$$

Thus $k \equiv 7 \pmod{17}$, giving $x = 15 + 17 \cdot 7 = 134$.

... continued reasoning omitted ...

The response directly verifies the new candidate:

$$134^2 \equiv 38 \pmod{289},$$

and

$$134^4 = 38^2 = 1444 \equiv -1 \pmod{289}.$$

It then states, “The solutions mod 289 are 155 and 134. So the minimal positive solution is 134.” This improves upon the first branch but still omits the roots 8 and 9 modulo 17. Its final summary reports both p and m .

Model answer:

17, 134

TT-OPD (Correct)

Model rollout (excerpt). The response initially finds the lift $2 \mapsto 155$, but then asks, “Perhaps there is a smaller m that is not 2 mod 17.” It enumerates every root:

$$x \equiv 2, 8, 9, 15 \pmod{17}.$$

For the $x \equiv 8$ branch, write $x = 8 + 17k$. The rollout computes

$$(8 + 17k)^4 + 1 \equiv 51 + 136k \pmod{289},$$

so $51 + 136k \equiv 0 \pmod{289}$. Dividing by 17 gives

$$8k \equiv 14 \pmod{17}.$$

Hence $k \equiv 6 \pmod{17}$, so $x = 8 + 17 \cdot 6 = 110$. It verifies

$$110^2 \equiv 251 \pmod{289},$$

and

$$110^4 = 251^2 = 63001 \equiv -1 \pmod{289}.$$

... continued reasoning omitted ...

After checking the remaining residue classes, it summarizes

$$2 \mapsto 155 \quad 8 \mapsto 110$$

$$9 \mapsto 179 \quad 15 \mapsto 134$$

and concludes, “Among all four cases, the minimal m is 110.”

Model answer:

110

Comparison. The incorrect answers arise from incomplete branch enumeration: ST-OPD lifts one root and TK-OPD lifts two. TT-OPD checks all four roots modulo 17, so its comparison of the lifted solutions correctly identifies the global minimum.