

Zero-shot Dependency Parsing with Unsupervised Cross-Lingual Bootstrapping

Lalita Lowphansirikul¹, Attapol Rutherford², Jian Gang Ngui³,
Sarana Nutanong¹, Peerat Limkonchotiawat³

¹VISTEC, Thailand ²Chulalongkorn University, Thailand ³AI Singapore, Singapore

lalita.l_s22@vistec.ac.th snutanon@vistec.ac.th

attapol.t@chula.ac.th

jiangangngui@aisingapore.org peerat@aisingapore.org

Abstract

Pre-trained language models (PLMs) with encoder-based architectures have shown impressive capabilities in zero-shot cross-lingual transfer for various language understanding tasks. However, applying this technique to dependency parsing remains a significant challenge due to its syntactic nature. To boost model generalizability across linguistic typologies, we propose a cross-lingual unsupervised bootstrapping method to improve syntactic knowledge within the PLM. We show that our method achieves a significant improvement in zero-shot parsing performance in low-resource languages. Analysis of these bootstrapped models uncovers increased robustness in recognizing syntactic structures, evidenced by higher scores in parameter-free tree probing tests.

1 Introduction

Encoder-based multilingual pre-trained language models (PLMs) demonstrate promising cross-lingual transferability (Wu and Dredze, 2019; Pires et al., 2019), enabling them to generalize knowledge across languages. This capability benefits language understanding tasks such as natural language inference and reasoning. Despite success in sequence-level tasks, cross-lingual transferability in syntactic tasks relies on syntactic similarity. Tran and Bisazza (2019) shows that dependency parsing transferability relies on shared subject-verb-object word order. These findings highlight the importance of syntactic similarity in cross-lingual tasks.

Previous works have aimed to mitigate the structural similarity constraint in dependency parsing with various approaches. Kondratyuk and Straka (2019) propose joint training on multiple treebanks. Further improvements include

difficulty-based batch selection (de Lhoneux et al., 2022), meta-learning (Langedijk et al., 2022), and adapter modules contextualized by linguistic features (Üstün et al., 2020; Ji et al., 2023). Liu et al. (2020) rearrange words based on part-of-speech tags to match target language structure. Arviv et al. (2023) improve performance with word permutation while preserving syntax. Although these approaches have narrowed the cross-lingual transfer gap, they remain limited to supervised fine-tuning. Our research question is as follows: “*To what extent can unsupervised representation learning uplift multilingual PLM’s zero-shot dependency parsing performance?*”

We propose a PLM bootstrapping method using an unsupervised contrastive representation learning, without using multilingual datasets, to enhance representation similarity, as measured by a robust word-swap metric called centered kernel alignment (CKA) (Kornblith et al., 2019), between sentences and their syntax-modified counterparts. Our preliminary observations show pre-trained mBERT’s sensitivity to word order changes (Figure 1). For example, the similarity between unmodified and verb-object reordered sentences decreases, similar to randomly swapped words with a 5% distance change. Therefore, the model training process must be invariant to various valid syntactic structures while preserving knowledge already learned.

We distinguish our work from previous studies by aiming to improve cross-lingual transferability through three components. First, we implement syntax-aware sentence augmentation by rotating subtrees, given our findings that a multilingual PLM invariant to syntactic structures can improve cross-lingual transfer for tasks requiring syntactic knowledge. Second, we choose masked language

L5	99.72	99.68	99.43	99.22	99.06
L6	99.59	99.56	99.18	98.46	98.37
L7	99.37	99.13	98.36	97.73	97.37
L8	99.02	98.63	97.36	97.00	96.55
L9	98.73	98.17	96.53	96.46	95.84
L10	98.37	97.75	95.64	95.82	95.10
L11	98.13	97.30	94.76	95.44	94.52
L12	98.16	97.07	94.45	95.66	94.14
L1-L12 avg	99.23	98.91	97.92	97.92	97.51
L6,L12 avg	98.88	98.32	96.81	97.06	96.26
	Postposition	NounAdj	SOV	Rand-5	Rand-10

Figure 1: Layer-wise CKA similarity between original and modified English sentences obtained from pre-trained mBERT representations. A higher score means more robustness for word swapping. We use the English EWT test treebank (UD v2.8) in this experiment.

modeling (MLM) as an auxiliary loss to preserve the lexicon and contextual understanding already learned in the PLM. Finally, we apply layer combination during model bootstrapping to aggregate syntactic knowledge from other encoder layers.

We bootstrap multilingual PLMs using the components individually and in combination, then perform supervised fine-tuning with weights initialized from our bootstrapped models. Our experimental results show improved average unlabeled and labeled attachment scores (UAS and LAS) for multilingual PLMs, especially on languages in the pre-training data. In addition, the experiment on probing test languages reveals higher UAS and undirected UAS (UUAS) for bootstrapped models compared to vanilla pre-trained models.

Our contributions are as follows: (I) We present a contrastive learning-based method to improve cross-lingual transferability, incorporating syntax-aware sentence augmentation, contextual knowledge preservation, and multi-layer representation aggregation. (II) We demonstrate zero-shot downstream performance on the adapter-based parser initialized with bootstrapped models. (III) We demonstrate robust syntax changes in bootstrapped models, improving unsupervised parsing with parameter-free tree probing.

2 Proposed Method

We design a bootstrapping method that enhances cross-lingual dependency parsing performance through unsupervised contrastive learning using only monolingual English data. Unlike typical contrastive setups, our approach generates syntax-

aware positive samples—sentences with altered word order that retain the original syntactic meaning. This avoids the need for multilingual data, which is often unavailable for low-resource languages. Our framework consists of three components: Syntax-aware Sentence Augmentation (Section 2.1, Contrastive Learning with MLM Auxiliary Loss (Section 2.2, and Multi-layer Representation Aggregation (Section 2.3).

2.1 Syntax-aware Sentence Augmentation

As shown in many contrastive learning works (Gao et al., 2021; Wang et al., 2022), strong and robust positive samples can yield significant improvement in downstream tasks. To create positive samples for dependency parsing, we need an augmentation scheme that significantly changes the word order while retaining the overall intended meaning of the sentence. Therefore, we create positive samples by implementing English subtree rotation based on three word ordering features¹. For example, applying Object-Verb (OV) augmentation to “The cat *is scratching* a fluffy mat.” returns “The cat a fluffy mat *is scratching*.” (Figure 2). Detailed implementation is provided in the Appendix A.2.




Figure 2: Original sentence (above) and OV reordered sentence (below). Dashed arcs indicate relations related to OV reordering, while solid arcs indicate relations unrelated to OV reordering.

We apply each augmentation function to original sentences, creating a one-to-one mapping. The resulting augmented sentences serve as positive sample candidates x^+ for the contrastive learning loss. Note that we also investigate various alternatives for augmentations in Appendix A.4.

2.2 Contrastive Learning with MLM Auxiliary Loss

For robust cross-lingual representations, we employ in-batch negative contrastive learning (Gao

¹83A: Order of Object and Verb, 85: Order of Adposition and Noun Phrase, 87A: Order of Adjective and Noun

et al., 2021). The contrastive loss for the i -th sentence pair in a mini-batch of N pairs is given as:

$$L_i^{CL} = -\log \frac{e^{\text{sim}(h_i^l, h_{i,l}^+)/\tau}}{\sum_{j=1}^N e^{\text{sim}(h_i^l, h_{i,l}^+)/\tau}} \quad (1)$$

where $h_{i,l}^+$ denotes the encoder’s sentence embedding of sentence x_i^+ from layer l , and $\text{sim}(\cdot, \cdot)$ is cosine similarity. We use the original sentences x_i as the anchor samples, augmented samples as the positive samples (Section 2.1), and the rest of the in-batch samples are the negative samples.

MLM Auxiliary Loss. We also apply MLM prediction (Devlin et al., 2019) as an auxiliary loss with a scalar weight λ to the contrastive loss to learn the grammatical understanding from the original sentence.

$$L_i = L_i^{CL} + \lambda L_{\text{mlm}} \quad (2)$$

2.3 Multi-layer Representation Aggregation

Based on Hosseini et al. (2023); Oh et al. (2022)’s improving sentence embedding quality through layer combination, we also aggregate multi-layer representations by averaging mean-pooled representations across selected layers, rather than using only the last layer. This results in a more robust overall representation without any additional cost for the training.

3 Experimental Setup

We conduct our experiment using multilingual encoder models like mBERT and XLM-R by using our four components: syntax-aware Object-Verb augmentation, contrastive learning, MLM auxiliary loss weight, and aggregation of representations from the last and sixth layers. Each model combination was hyperparameter-tuned for optimal similarity between original and syntax-aware sentences using English EWT treebank data (Silveira et al., 2014). We also conducted with other multilingual encoders: XLM-100 (Conneau and Lample, 2019), XLMR (Conneau et al., 2020), DistilBERT (Sanh et al., 2019), and MiniLM (Wang et al., 2020). For bootstrapping, a UDapter-based parser was fine-tuned using vanilla and bootstrapped models across 13 high-resource treebanks, utilizing trainable adapters contextualized by language typological features (Malaviya et al., 2017), and freezing model weights following Üstün et al. (2020). Performance was evaluated in 28 low-resource languages using average UAS and LAS, supplemented

by unsupervised tree parsing with a parameter-free tree probing method (Wu et al., 2020) to assess syntactic structure capture. We describe more details about the experimental setup in Appendix A.1.

4 Results and Discussion

Bucket Results. In this experiment, we split the performance of multilingual models by the amount of data (in MB) that appeared in the training data of a base model. With this evaluation split, we can group low-resource (0,50), middle-resource (50,100), and high-resource (200-) separately. Table 1 shows that *using bootstrapped models improves the performance of zero-shot parsing, especially for the (0,50) bucket*. The bootstrapped model with last-layer representation (only L12) and OV augmentation yields the highest average UAS and LAS on the group with less data, obtaining an average improvement of +1.27 UAS and +1.29 LAS scores. Notably, we found that combining multi-layer representation learning obtains almost similar improvement, but without any performance penalty. This is because aggregating soft-representation from multiple layers can improve the lower-bound performance as discussed in Section 2.3. We confirm this by obtaining a decrease in performance in UDapter-B-mBERT L12 (using only vanilla contrastive learning without any of our proposed techniques). This result emphasizes the importance of our proposed components to yield an improvement for low-resource languages.

Overall Performance Discussion. As expected, *using bootstrapping increases the performance in the low-resource multilingual scenarios*. From the overall performance, we found that we obtain significant improvements in the case of using L12 + SynAug OV + MLM, where we obtain +0.16 and +0.25 in UAS and LAS scores, respectively. Moreover, as expected, using multi-layer aggregation also yields improvements in all performance. We strongly believe that, with the grammatical changes from our augmentation schemes, this can also yield an improvement for large language models as well. In conclusion, our work can bootstrap the performance of existing techniques using the unsupervised technique (contrastive learning) with our strong data augmentation (Section 2.1). Note that we also experimented with other models (i.e., XLMR and DistilBERT), and the results are presented in Tables 6 and 7.

Varied performance based on verb-object order-

Model	All (n=28) Avg	Unseen / Avg	Seen from mBERT (grouped by pre-training data size in MB)			
			(0, 50]	(50, 100]	(200,)	Avg
UDapter (Reproduced)	51.29/36.65	42.01/27.52	67.49/51.09	65.73/49.75	75.99/62.63	70.88/55.92
UDapter-B-mBERT L12	-0.82 [†] /-0.48 [†]	-0.79 [†] /-0.33	-2.07 [†] /-1.52	-0.89 [†] /-1.83 [†]	+0.05/+0.21	-0.86 [†] /-0.82 [†]
with MLM	+0.16/+0.28 [†]	-0.31 [†] /-0.18	+2.75/+3.49	+0.69/+0.35	+0.22/-0.00 [†]	+1.16/+1.24
with SynAug OV	-0.30 [†] /+0.16	-1.05 [†] /-0.38	+3.70 [†] /+3.63 [†]	-1.41 [†] /-1.59	+0.78/+0.98	+1.27/+1.29[†]
with SynAug OV + MLM	+0.16[†]+/+0.25[†]	-0.03/+0.06 [†]	+2.63 [†] /+2.15 [†]	-1.44/-0.94 [†]	+0.01/+0.31	+0.56/+0.65 [†]
UDapter-B-mBERT L12+L6	+0.08/+0.04	+0.01 [†] /+0.16 [†]	-0.04 [†] /-1.32 [†]	+0.06/-0.15 [†]	+0.51/+0.60	+0.23 [†] /-0.21 [†]
with MLM	+0.20/+0.48	-0.06/+0.23	+1.64/+2.51 [†]	-0.72 [†] /-0.80	+0.84 [†] /+0.80	+0.76/+1.01
with SynAug OV	+0.04/+0.20	-0.20 [†] /0.00	+1.38 [†] /+1.96 [†]	-0.78/-0.66	+0.56/+0.27	+0.53/+0.63
with SynAug OV + MLM	+0.09/+0.15	-0.36 [†] /-0.27	+3.05 [†] /+3.45 [†]	-0.82 [†] /-1.22	+0.50/+0.38	+1.06/+1.05

Table 1: Zero-shot evaluation results on 28 target languages grouped by inclusion in mBERT pre-training data and the amount of pre-training data (low-resource, middle-resource, and high-resource languages). The scores reported are the average UAS/LAS change compared to UDapter. UDapter-B-mBERT denotes bootstrapped mBERT with two settings: L12 (last layer only) and L12+L6 (last and sixth layers). [†] indicates a statistically significant result from the McNemar’s test ($p < 0.05$).




Figure 3: Zero-shot LAS parsing performance grouped by the target languages’ canonical verb and object ordering. Results are from two UDapter models: Bootstrapped-mBERT L12 with MLM and VO augmentation, and Bootstrapped-mBERT L12+L6 with MLM loss. * denotes languages included in the mBERT pre-training data.

ing. To confirm the improvement seen in Table 1, we analyzed LAS differences from the baseline in three groups, based on the language’s canonical verb-object ordering (Figure 3). While we observe overall improvement of our model, it should be noted that improvement was not uniform – we found mixed results for OV languages while finding mostly positive results for VO languages as well as languages with no dominant order.

Unsupervised Tree Probing. To further understand the impact of our bootstrapping technique on improving robustness in downstream tasks, we conduct an experiment on tree probing using UAS and UUAS scores as the evaluation metric. As shown in Table 2, the bootstrapped mBERT achieves higher probed UAS and undirected UAS (UUAS) on test treebanks in single-layer and multi-layer settings. The Spearman’s rank correlation between the uplift in probed UUAS and downstream LAS for bootstrapped models with MLM loss ($\lambda = 0.1$), using a single-layer representation and multi-layer aggregation on seen languages, is 78.33 and 66.67, respectively ($p < 0.05$). Additionally, we observe that multilingual encoders pre-trained on Wikipedia show higher gains than those trained on CC-100 (Table 3). Notably, we found that the bootstrapped XLMR model’s parsing performance did *not* improve, which aligns with declines in its probed results.

Treebank (test set)	mBERT	Bootstrapped mBERT	
		L12	L12+L6
Unseen	50.85/55.76	-0.25/+0.95	+0.12/+1.05
Seen	53.74/59.57	+0.88/+1.85	+1.08/+1.88
(0, 50]	53.76/58.45	+0.21/+0.92	+1.03/+1.34
(50, 100]	53.55/60.01	+0.53/+0.83	+0.46/+0.77
(200,)	53.81/60.20	+1.56/+3.05	+1.43/+2.83
All (n=28)	51.75/56.95	+0.10/+1.23	+0.42/+1.30

Table 2: Comparison of average UAS/UUAS obtained from parameter-free tree probing between vanilla mBERT and bootstrapped models trained with MLM ($\lambda = 0.1$) and no sentence augmentation. The scores shown are from the layer with the highest UAS.

Encoder	All	Unseen	Seen
XLM-100 (Wiki)	+0.35/+0.34 (+0.26/+0.09)	+0.17/-0.07 (+0.36/+0.11)	+0.78/+1.26 (+0.06/+0.04)
Distil-mBERT (Wiki, Distill)	+0.53/+0.37 (+1.07/+1.82)	+1.40/+0.80 (+0.80/+1.60)	-0.30/-0.13 (+1.65/+2.31)
XLMR (CC-100)	-0.03/-0.39 (-0.90/-1.48)	-0.11/-0.36 (-0.27/-0.93)	-0.04/-0.52 (-2.05/-2.48)
mMiniLM (CC-100, Distill)	+0.31/+0.33 (+0.58/+0.44)	+0.38/+0.43 (+0.54/+0.20)	+0.26/+0.03 (+0.66/+0.91)

Table 3: Comparison of average UAS/LAS change and probed UAS/UUAS scores (in parentheses). The results come from a bootstrapped model that uses the last layer representation, MLM auxiliary loss, and VO augmentation. The results are selected based on the highest average UAS for the seen languages.

5 Conclusion

We improve cross-lingual transferability using syntax-aware sentence augmentation, MLM auxiliary loss, and layer-wise representation aggregation. Our method boosts zero-shot cross-lingual dependency parsing with mBERT by 1.27 UAS and 1.29 LAS on seen languages, and yields gains with other multilingual PLMs. Parameter-free tree probing reveals a positive link between parsing and

downstream performance, suggesting that intrinsic properties of multilingual PLMs (including both encoder-based and decoder-based models) merit further study.

Limitations

In this study, we focus on a model bootstrapping experiment conducted exclusively on a single source in one language, the UD English EWT treebank. Studies on data integration from more diverse text sources or non-English languages remain unexplored. Regarding syntax-aware sentence augmentation, we limit our exploration to specific modifications. Other categories of sentence augmentation, sample weights, or applying multiple modifications to the same sentence are left for future work.

We observe variability between mBERT and other pre-trained encoder-based multilingual models. This variability can be attributed to factors such as the quantity of pre-training data available for each language and inherent properties within the models. There is a clear need for a systematic and quantifiable methodology to identify combinations that enhance syntactic generalizability. The potential effects on other NLU tasks, such as relation extraction and question answering, as well as experimentation on different target task fine-tuning approaches, are areas for future investigation.

References

- Ofir Arviv, Dmitry Nikolaev, Taelin Karidi, and Omri Abend. 2023. [Improving cross-lingual transfer through subtree-aware word reordering](#). In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 718–736, Singapore. Association for Computational Linguistics.
- Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. 2020. [Unsupervised cross-lingual representation learning at scale](#). In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 8440–8451, Online. Association for Computational Linguistics.
- Alexis Conneau and Guillaume Lample. 2019. [Cross-lingual language model pretraining](#). In *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc.
- Miryam de Lhoneux, Sheng Zhang, and Anders Søgaard. 2022. [Zero-shot dependency parsing with worst-case aware automated curriculum learning](#). In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 578–587, Dublin, Ireland. Association for Computational Linguistics.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. [BERT: Pre-training of deep bidirectional transformers for language understanding](#). In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.
- Tianyu Gao, Xingcheng Yao, and Danqi Chen. 2021. [SimCSE: Simple contrastive learning of sentence embeddings](#). In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 6894–6910, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.
- MohammadSaleh Hosseini, Munawara Munia, and Latifur Khan. 2023. [BERT has more to offer: BERT layers combination yields better sentence embeddings](#). In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 15419–15431, Singapore. Association for Computational Linguistics.
- Tao Ji, Yuanbin Wu, and Xiaoling Wang. 2023. [Typology guided multilingual position representations: Case on dependency parsing](#). In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 13524–13541, Toronto, Canada. Association for Computational Linguistics.
- Dan Kondratyuk and Milan Straka. 2019. [75 languages, 1 model: Parsing Universal Dependencies universally](#). In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 2779–2795, Hong Kong, China. Association for Computational Linguistics.
- Simon Kornblith, Mohammad Norouzi, Honglak Lee, and Geoffrey Hinton. 2019. Similarity of neural network representations revisited. In *International conference on machine learning*, pages 3519–3529. PMLR.
- Anna Langedijk, Verna Dankers, Phillip Lippe, Sander Bos, Bryan Cardenas Guevara, Helen Yannakoudakis, and Ekaterina Shutova. 2022. [Meta-learning for fast cross-lingual adaptation in dependency parsing](#). In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 8503–8520, Dublin, Ireland. Association for Computational Linguistics.
- Lu Liu, Yi Zhou, Jianhan Xu, Xiaoqing Zheng, Kai-Wei Chang, and Xuanjing Huang. 2020. [Cross-lingual dependency parsing by POS-guided word reordering](#). In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pages 2938–2948, Online. Association for Computational Linguistics.

- Chaitanya Malaviya, Graham Neubig, and Patrick Littell. 2017. Learning language representations for typology prediction. In *Conference on Empirical Methods in Natural Language Processing (EMNLP)*, Copenhagen, Denmark.
- Dongsuk Oh, Yejin Kim, Hodong Lee, H. Howie Huang, and Heuiseok Lim. 2022. [Don't judge a language model by its last layer: Contrastive learning with layer-wise attention pooling](#). In *Proceedings of the 29th International Conference on Computational Linguistics*, pages 4585–4592, Gyeongju, Republic of Korea. International Committee on Computational Linguistics.
- Telmo Pires, Eva Schlinger, and Dan Garrette. 2019. [How multilingual is multilingual BERT?](#) In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 4996–5001, Florence, Italy. Association for Computational Linguistics.
- Nils Reimers and Iryna Gurevych. 2019. [Sentence-bert: Sentence embeddings using siamese bert-networks](#). In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics.
- Victor Sanh, Lysandre Debut, Julien Chaumond, and Thomas Wolf. 2019. [Distilbert, a distilled version of BERT: smaller, faster, cheaper and lighter](#). *CoRR*, abs/1910.01108.
- Natalia Silveira, Timothy Dozat, Marie-Catherine de Marneffe, Samuel Bowman, Miriam Connor, John Bauer, and Christopher D. Manning. 2014. A gold standard dependency corpus for English. In *Proceedings of the Ninth International Conference on Language Resources and Evaluation (LREC-2014)*.
- Ke Tran and Arianna Bisazza. 2019. [Zero-shot dependency parsing with pre-trained multilingual sentence representations](#). In *Proceedings of the 2nd Workshop on Deep Learning Approaches for Low-Resource NLP (DeepLo 2019)*, pages 281–288, Hong Kong, China. Association for Computational Linguistics.
- Ahmet Üstün, Arianna Bisazza, Gosse Bouma, and Gertjan van Noord. 2020. [UDapter: Language adaptation for truly Universal Dependency parsing](#). In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 2302–2315, Online. Association for Computational Linguistics.
- Wenhui Wang, Furu Wei, Li Dong, Hangbo Bao, Nan Yang, and Ming Zhou. 2020. [Minilm: Deep self-attention distillation for task-agnostic compression of pre-trained transformers](#).
- Yaoshian Wang, Ashley Wu, and Graham Neubig. 2022. [English contrastive learning can learn universal cross-lingual sentence embeddings](#). In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 9122–9133, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.
- Shijie Wu and Mark Dredze. 2019. [Beto, bentz, becas: The surprising cross-lingual effectiveness of BERT](#). In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 833–844, Hong Kong, China. Association for Computational Linguistics.
- Zhiyong Wu, Yun Chen, Ben Kao, and Qun Liu. 2020. [Perturbed masking: Parameter-free probing for analyzing and interpreting BERT](#). In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 4166–4176, Online. Association for Computational Linguistics.

A Appendix

A.1 Evaluation Setup

We bootstrap robust multilingual encoder models that were used in many previous cross-lingual dependency works, such as mBERT and XLM-R, using the three components detailed in Section 2. First, we selected Object-Verb (OV) augmentation for syntax-aware sentence augmentation due to its high CKA similarity sensitivity. Second, we conducted a grid search for the MLM auxiliary loss weight within $\{0.1, 0.01, 0.001\}$. Lastly, we aggregated representations from the last and sixth layers due to a noticeable decrease in CKA similarity starting at the sixth layer of mBERT (Figure 1). Thus, we used two settings: L12 (last layer) and L12+L6 (last and sixth layers).

For bootstrapping, we hyperparameter-tuned each combination to find the best model based on the average similarity between the original sentences and their three syntax-aware modifications in the final and middle-layer representations. Sentences for model bootstrapping and validation were sourced from the train and test sets of the English EWT treebank (UD v2.8) (Silveira et al., 2014). Hyperparameter details are provided in Appendix A.3. For generalizability evaluation, we conducted experiments using the same configuration on other multilingual encoders: XLM-100 (Conneau and Lample, 2019), XLMR (Conneau et al., 2020), and the multilingual versions of DistilBERT (Sanh et al., 2019) and MiniLM (Wang et al., 2020).

Then, we fine-tuned a UDapter-based parser using vanilla and bootstrapped models across 13 high-resource treebanks. UDapter employs trainable adapters contextualized by language typological features (Malaviya et al., 2017) and freezes the model weights. We followed the fine-tuning procedure from Üstün et al. (2020) and re-did sentence downsampling for UD Russian-SynTagRus since the downsampled 13k training sentences were unavailable. We evaluated model performance in 28 low-resource languages using average UAS and LAS. Additionally, we conducted an unsupervised tree parsing using the parameter-free tree probing method (Wu et al., 2020). This method decodes parsed trees from the token representation similarity matrix, evaluating how well the models capture syntactic structures.

A.2 Syntax-aware sentence augmentation on English

We rotate words based on three syntactic features of English using a parsed tree with UD syntactic relation annotation² while ensuring the swapped words remain within their respective subtree.

Order of Verb and Object (VO): The object of the verb predicate is determined by nominal and clausal core arguments from the relations: *iobj*, *obj*, *xcomp*, and *ccomp*. In our implementation, we also include non-core dependents from the relations: *cop*, *expl*, and *obl*, and verb dependents (e.g., auxiliary verb, phrasal verb) from the relations: *compound*, *aux*, *advmod*.

Order of Adposition and Noun (Postposition): The Adposition and Noun are determined by the following relations: *case* (case marking).

Order of Adjective and Noun (Noun-Adj): The Adjective and Noun is determined by the following relations: *amod* (adverbial modifier).




Figure 4: Sentences with Noun-Adj reordering (a) and Adposition (b) reordering. Dashed arcs indicate relations related to reordering.

A.3 Model training details

We modified the sentence-transformers codebase (Reimers and Gurevych, 2019) and varied the hyperparameters for model bootstrapping.

- Learning rate: $\{1e-5, 1.5e-5, 3e-5\}$
- Number of train epochs: $\{10, 25\}$
- Train batch size: $\{16, 32, 64\}$
- Warmup ratio: 0.1

We limit the train batch size search space to $\{16, 32\}$ for XLMR and XLM-100 due to the memory constraint. Each run takes approximately

²<https://universaldependencies.org/u/dep/index.html>

57 minutes for mBERT, 38 minutes for Distil-mBERT and Multilingual-MiniLM, 50 minutes for XLMR, and 97 minutes for XLM-100. Fine-tuning the UDapter-based parser takes approximately 38 hours on mBERT, 32 on Distil-mBERT, 31 on Multilingual-MiniLM, 37 on XLMR, and 38 on XLM-100. All experiments were conducted using NVIDIA V100 hardware except for XLM100, which ran on NVIDIA A100.

A.4 Additional experiments on the choices of augmentation function and MLM weight

We report the parsing performance of bootstrapped mBERT with last-layer representation under different types of sentence augmentation in Table 4 and the full results of bootstrapped mBERT for each value of the MLM loss weight in Table 5. Evaluation for Assyrian (aii) and Amharic (am) languages is excluded due to most tokens being unknown to mBERT’s WordPiece tokenizer.

	All	Unseen	Seen
Rand-5	-0.20/-0.17	-0.69/-0.55	+0.83/+0.65
Post	-0.20/+0.01	-0.35/-0.06	+0.13/+0.15
OV	-0.30/+0.16	-1.05/-0.38	+1.27/+1.29
Adj	-0.18/-0.17	-0.21/-0.08	-0.11/-0.35
OV, Adj	-0.21/-0.08	-0.36/-0.19	+0.10/+0.16

Table 4: Comparison in average UAS/LAS change with different augmentations between baseline and Bootstrapped-mBERT Single-Layer without MLM.

A.5 Zero-shot dependency parsing performance of other multilingual encoders.

We report the parsing performance of multilingual encoders pre-trained on Wikipedia data in Table 6 and CC-100 in Table 7.

Model	All (n=28) Avg	Unseen / Avg	Seen from mBERT (grouped by pre-training data size in MB)			
			(0, 50]	(50, 100]	(200,)	Avg
UDapter (Reproduced)	51.29/36.65	42.01/27.52	67.49/51.09	65.73/49.75	75.99/62.63	70.88/55.92
UDapter-B-mBERT L12	-0.82 [†] /-0.48 [†]	-0.79 [†] /-0.33	-2.07 [†] /-1.52	-0.89 [†] /-1.83 [†]	+0.05/+0.21	-0.86 [†] /-0.82 [†]
MLM ($\lambda = 0.1$)	+0.16/+0.28 [†]	-0.31 [†] /-0.18	+2.75/+3.49	+0.69/+0.35	+0.22/-0.00 [†]	+1.16/+1.24
MLM ($\lambda = 0.01$)	-0.38/+0.05	-0.81 [†] /-0.14	+1.71 [†] /+2.03 [†]	+0.21/-1.13	-0.14 [†] /+0.08 [†]	+0.55 [†] /+0.46 [†]
MLM ($\lambda = 0.001$)	-1.07 [†] /-0.93 [†]	-1.50 [†] /-0.81 [†]	-0.84 [†] /-2.22 [†]	+1.64/-1.03 [†]	-0.58 [†] /-0.51 [†]	-0.17 [†] /-1.20 [†]
SynAug	-0.30 [†] /+0.16	-1.05 [†] /-0.38	+3.70 [†] /+3.63 [†]	-1.41 [†] /-1.59	+0.78/+0.98	+1.27/+1.29 [†]
SynAug + MLM ($\lambda = 0.1$)	-0.36/+0.04	-0.74 [†] /-0.38	+1.26/+2.62 [†]	-0.71/-0.78	+0.37/+0.51	+0.43/+0.93
SynAug + MLM ($\lambda = 0.01$)	+0.16 [†] /+0.25 [†]	-0.03/+0.06 [†]	+2.63 [†] /+2.15 [†]	-1.44/-0.94 [†]	+0.01/+0.31	+0.56/+0.65 [†]
SynAug + MLM ($\lambda = 0.001$)	-0.23 [†] /-0.18 [†]	-0.45 [†] /-0.24 [†]	+0.67/+0.86 [†]	-0.23/-1.59	+0.10/+0.03	+0.21/-0.05
UDapter-B-mBERT L12+L6	+0.08/+0.04	+0.01 [†] /+0.16 [†]	-0.04 [†] /-1.32 [†]	+0.06/-0.15 [†]	+0.51/+0.60	+0.23 [†] /-0.21 [†]
MLM ($\lambda = 0.1$)	+0.20/+0.48	-0.06/+0.23	+1.64/+2.51 [†]	-0.72 [†] /-0.80	+0.84 [†] /+0.80	+0.76/+1.01
MLM ($\lambda = 0.01$)	+0.07 [†] /+0.06	-0.25/0.00	+1.77/+0.32 [†]	-0.54 [†] /-0.09	+0.66/+0.18 [†]	+0.76 [†] /+0.17
MLM ($\lambda = 0.001$)	-0.30/-0.00	-0.33 [†] /-0.09	+0.41/+1.70	-2.22 [†] /-1.78 [†]	+0.29/-0.00	-0.22 [†] /+0.17 [†]
SynAug	+0.04/+0.20	-0.20 [†] /0.00	+1.38 [†] /+1.96 [†]	-0.78/-0.66	+0.56/+0.27	+0.53/+0.63
SynAug + MLM ($\lambda = 0.1$)	+0.09/+0.15	-0.36 [†] /-0.27	+3.05 [†] /+3.45 [†]	-0.82 [†] /-1.22	+0.50/+0.38	+1.06/+1.05
SynAug + MLM ($\lambda = 0.01$)	-1.37 [†] /-1.07 [†]	-1.34 [†] /-0.63 [†]	-2.28 [†] /-3.94 [†]	-2.48 [†] /-2.77 [†]	-0.31 [†] /-0.17 [†]	-1.45 [†] /-2.00 [†]
SynAug + MLM ($\lambda = 0.001$)	-0.77 [†] /-0.42 [†]	-1.05 [†] /-0.54 [†]	+0.17/-0.18	-0.36 [†] /-0.21	-0.36 [†] /-0.17 [†]	-0.18 [†] /-0.18 [†]

Table 5: Zero-shot evaluation result on 28 target languages grouped by inclusion in mBERT pre-training data and the amount of pre-training data. The scores reported are the average UAS/LAS change compared to UDapter. UDapter-B-mBERT denotes bootstrapped mBERT with two settings: L12 (last layer only) and L12+L6 (last and sixth layers). The λ denotes the weight assigned to the MLM auxiliary loss during the model bootstrapping phase. [†] indicates a statistically significant result from McNemar’s test ($p < 0.05$). The pre-training data sizes (in MB) for seen languages are as follows: Breton (be), Tagalog (tl), Yoruba (yo) (0-50 MB); Marathi (mr), Welsh (cy) (50-100 MB); Belarusian (be), Kazakh (kk), Tamil (ta), Telugu (te) (>200 MB). Data sizes are calculated from the Wikipedia dump plaintext (snapshot: 2018-02-25).

Model	All (n=28) Avg	Unseen / Avg	Seen from the encoder (grouped by pre-training data size in MB)			
			(0, 50]	(50, 100]	(200,)	Avg
UDapter-Distil-MBert	45.73/30.74	39.31/25.29	50.13/31.34	56.24/37.45	67.65/52.84	59.27/42.25
UDapter XLM-100	49.87/36.18	43.67/29.92	55.25/41.61	62.33/46.76	69.08/56.51	62.97/49.38
UDapter-Distil-MBert L6	+0.30 [†] /+0.20 [†]	+1.41 [†] /+0.82 [†]	-0.94 [†] /+0.05	-1.92 [†] /-2.51 [†]	-0.41/-0.45	-0.92/-0.67 [†]
MLM ($\lambda = 0.01$)	+0.74 [†] /+0.49 [†]	+1.68 [†] /+0.62 [†]	-1.53 [†] /+0.81 [†]	+1.18/+0.33	-0.24/-0.02	-0.47 [†] /+0.38 [†]
SynAug	+0.58 [†] /+0.31	+1.40 [†] /+0.64 [†]	+0.55/+0.45 [†]	-0.18 [†] /-1.62 [†]	+0.56 [†] /+0.55 [†]	+0.40 [†] /+0.08 [†]
SynAug + MLM ($\lambda = 0.01$)	+0.73 [†] /+0.48 [†]	+1.76 [†] /+1.02 [†]	-1.84 [†] /-0.96 [†]	+0.97 [†] /+0.38	+0.28/+0.07	-0.43 [†] /-0.28 [†]
UDapter XLM-100 L16	+0.86 [†] /+0.60	+1.23 [†] /+0.65 [†]	+0.04 [†] /+0.74 [†]	+0.80/+0.11 [†]	+0.61 [†] /+1.05 [†]	+0.23 [†] /+0.57 [†]
MLM ($\lambda = 0.001$)	+2.08 [†] /+1.66 [†]	+1.87 [†] /+1.11 [†]	+3.89 [†] /+5.33 [†]	+2.65 [†] /+1.91 [†]	+1.76 [†] /+1.84 [†]	+2.32 [†] /+2.70 [†]
SynAug	-	-	-	-	-	-
SynAug + MLM ($\lambda = 0.1$)	+0.54/+0.41	+0.40/-0.00	-0.24 [†] /+0.18 [†]	-0.17/+0.07	+1.65 [†] /+2.23 [†]	+0.52/+0.92
UDapter XLM-100 L16+L8	-	-	-	-	-	-
MLM ($\lambda = 0.1$)	-0.30 [†] /-0.03 [†]	+0.09 [†] /+0.37	-0.20 [†] /-0.75 [†]	-0.28/-0.75 [†]	-1.29 [†] /-0.37 [†]	-0.79 [†] /-0.58 [†]
SynAug	+0.26 [†] /+0.09 [†]	+0.48/+0.02 [†]	+0.16 [†] /+0.62 [†]	-0.65 [†] /-0.90 [†]	-0.88 [†] /+0.01 [†]	-0.39 [†] /+0.02 [†]
SynAug + MLM ($\lambda = 0.001$)	+0.85 [†] /+0.47	+0.76 [†] /+0.16	+2.88 [†] /+2.55 [†]	+1.46 [†] /+0.24 [†]	-0.24/+0.80 [†]	+1.12 [†] /+1.13

Table 6: Zero-shot evaluation result on 28 target languages grouped by inclusion in mBERT pre-training data and the amount of pre-training data. The scores reported are the average UAS/LAS change compared to UDapter. UDapter-B-Distil-mBERT denotes bootstrapped mBERT. The λ denotes the weight assigned to the MLM auxiliary loss during the model bootstrapping phase. The row marked with "-" indicates that the model failed to converge. [†] indicates a statistically significant result from McNemar’s test ($p < 0.05$).

Model	All (n=28) Avg	Unseen / Avg	Seen from XLMR (grouped by pre-training data size in GB)			
			(0, 4]	(4, 10]	(10,)	Avg
UDapter-mMiniLM	51.50/36.85	40.52/26.53	56.86/35.80	75.94/61.09	80.01/72.22	68.01/51.62
UDapter-XLMR	53.96/40.20	41.03/27.80	66.71/47.05	78.57/64.03	81.58/73.84	73.73/58.10
UDapter-B-XLMR L12	-1.23/-0.86	-1.67/-0.98	-0.64/-0.57	-0.40/-0.61	-0.62/-0.45	-0.55/-0.56
MLM ($\lambda = 0.01$)	+0.14/-0.27	+0.10/-0.38	-0.36/-0.58	+0.29/+0.30	+0.29/+0.26	-0.01/-0.11
SynAug	-0.44/-0.48	-0.18/-0.21	-0.69/-0.94	-0.48/-1.31	+0.48/+0.40	-0.40/-0.83
SynAug + MLM ($\lambda = 0.05$)	-0.46/-0.35	-0.76/-0.30	-0.72/-0.77	+0.36/-0.38	+0.08/+0.10	-0.18/-0.47
UDapter-B-mMiniLM L12	+0.34/+0.36	+0.24/+0.42	-0.42/-0.36	+1.03/+0.33	+0.22/+0.06	+0.23/-0.03
MLM ($\lambda = 0.01$)	-0.24/+0.16	-0.51/+0.15	-0.59/-0.28	+1.04/+0.70	+0.09/-0.29	+0.13/+0.07
SynAug	+0.16/+0.35	+0.13/+0.44	-0.87/-0.53	+1.35/+0.74	-0.10/-0.10	+0.08/+0.01
SynAug + MLM ($\lambda = 0.001$)	+0.31/+0.33	+0.38/+0.43	-0.26/-0.15	+0.97/+0.35	+0.16/-0.17	+0.26/+0.03
UDapter-B-XLMR L12+L6	-1.21/-0.68	-1.70/-0.86	-0.75/-0.57	-0.13/-0.05	-0.26/+0.01	-0.44/-0.28
MLM ($\lambda = 0.05$)	-0.23/-0.41	-0.25/-0.02	-1.24/-1.80	+0.04/-0.94	-0.20/-0.07	-0.59/-1.17
SynAug	-0.38/-0.38	-0.33/-0.24	-1.28/-1.26	-0.52/-0.47	+0.21/+0.10	-0.74/-0.73
SynAug + MLM ($\lambda = 0.1$)	+0.01/-0.36	-0.00/-0.27	-0.51/-1.04	+0.80/+0.02	+0.04/-0.02	+0.06/-0.47
UDapter-B-mMiniLM L12+L6	-0.53/+0.02	-0.72/-0.05	-0.84/-0.01	+0.39/+0.18	-0.35/-0.31	-0.30/0.00
MLM ($\lambda = 0.05$)	+0.35/+0.41	+0.49/+0.48	-0.88/-0.50	+0.87/+0.66	+0.30/-0.25	-0.03/-0.03
SynAug	-0.12/+0.19	-0.20/+0.28	-1.04/-0.83	+0.92/+0.61	+0.18/+0.02	-0.10/-0.15
SynAug + MLM ($\lambda = 0.001$)	+0.15/+0.40	+0.02/+0.38	-0.50/-0.21	+1.60/+1.09	0.00/+0.05	+0.36/+0.31

Table 7: Zero-shot evaluation result on 28 target languages grouped by inclusion in mBERT pre-training data and the amount of pre-training data. The scores reported are the average UAS/LAS change compared to UDapter. UDapter-B-XLMR denotes bootstrapped XLMR. UDapter-B-mMiniLM denotes bootstrapped Multilingual MiniLM. The λ denotes the weight assigned to the MLM auxiliary loss during the model bootstrapping phase. † indicates a statistically significant result from McNemar’s test ($p < 0.05$).

	UDapter (Baseline)	UDapter-Bootstrapped mBERT					
		Single-Layer (L12)			Multi-Layer (L12+L6)		
		MLM	SynAug	MLM +SynAug	MLM	SynAug	MLM +SynAug
akk	42.38/49.11	-0.12/+0.40	-1.04/-0.12	+0.58/+1.15	-0.81/-0.86	-4.89/-6.10	+0.06/-0.29
be*	34.9/47.3	+2.58/+4.40	-0.11/-1.62	+1.67/+3.81	+2.61/+4.20	-1.44/-2.12	+1.44/+0.63
bho	40.09/48.86	-0.06/+1.27	-0.23/+1.82	-0.55/+0.80	-0.90/+0.55	-2.44/+1.15	-0.57/+0.57
bm	43.79/50.19	+0.25/+0.91	-0.18/+0.81	+0.41/+1.14	+0.94/+1.33	+0.47/+0.96	+0.49/+0.56
br*	57.29/61.33	-1.57/+0.17	-4.37/-1.23	-1.53/+0.24	-0.78/+0.75	-3.91/-3.27	-1.67/+0.24
bxr	50.92/56.64	+1.96/+3.00	+2.01/+2.80	+1.63/+3.26	+1.51/+2.73	-0.30/+1.37	+1.29/+2.78
cy*	44.48/53.51	+0.08/+0.44	-3.15/-1.88	-0.72/-0.18	+0.18/+0.32	-1.89/-1.85	-0.49/+0.55
fo	62.63/63.85	+0.15/+1.35	-0.53/+0.67	+0.23/+1.45	+0.32/+1.57	-1.63/-0.85	+0.11/+1.27
gsw	51.87/54.64	+0.07/+1.94	-2.08/-0.83	-0.42/+1.52	-0.07/+1.18	-3.12/-2.22	+0.21/+1.80
gun	46.05/50.99	+0.91/+1.14	+0.83/+0.76	+2.58/+3.03	+0.91/+1.14	+1.21/+0.46	+0.23/+1.67
hsb	38.05/45.25	+0.36/+0.59	-0.62/-0.88	+0.51/+0.45	+0.73/+0.49	-2.34/-2.16	+0.75/+0.34
kk*	56.24/59.92	+1.10/+2.70	-0.79/+0.27	+0.10/+1.97	+0.73/+2.18	-1.67/-0.27	+0.08/+1.64
kmr	44.9/50.23	+0.35/+2.04	-0.12/+1.03	+0.15/+1.16	+0.57/+2.05	+0.07/+0.13	+0.83/+0.89
koi	58.15/59.65	-1.00/+0.75	-1.75/+0.25	0.00/+2.01	-0.75/+0.75	-3.01/-1.75	+1.00/+2.01
kpv	53.3/58.12	-2.18/+1.40	-0.78/+1.55	-1.53/+1.09	-0.70/+1.71	-0.93/+0.70	-1.17/+1.55
krl	46.9/53.62	+0.71/+0.52	-0.87/-1.68	+0.32/+0.94	+0.58/+0.68	-0.87/-1.29	-0.06/-1.42
mdf	54.72/57.04	+1.96/+3.21	+2.14/+3.39	+2.14/+3.03	+4.10/+4.99	+0.89/+2.85	+3.21/+3.74
mr*	62.62/66.5	+0.97/+1.21	-0.24/-0.73	-0.73/+0.24	+0.73/+1.21	+0.73/+0.73	+1.21/+0.97
myv	52.92/58.24	-0.32/+0.35	-0.27/-0.58	-0.52/+0.72	+0.61/+1.53	-0.94/-0.48	-0.18/+0.04
olo	43.01/50.0	+1.75/+1.28	+0.20/-0.34	+1.14/+0.81	+1.61/+1.21	-0.47/-1.14	+0.94/+0.74
pcm	43.55/49.44	-0.79/+0.60	-1.45/+0.11	-0.16/+0.71	-0.68/+0.03	-1.78/-0.68	-0.71/+0.14
sa	57.89/60.39	-1.63/-0.11	-0.49/-1.79	-1.95/+0.16	-1.36/-0.27	-0.65/-2.01	-1.68/-0.43
ta*	42.28/51.73	+2.01/+3.02	+1.71/+2.11	+1.66/+2.77	+1.01/+2.46	-0.55/+1.81	+0.45/+2.16
te*	81.83/81.83	+0.55/+2.08	+0.69/+1.11	+0.83/+2.08	+1.39/+2.50	-0.28/+0.28	+0.69/+1.94
tl*	73.97/73.97	+1.71/+2.74	+1.71/+1.71	+1.71/+3.08	+2.74/+2.74	0.00/0.00	+1.03/+1.03
wbp	90.45/90.45	-1.91/-1.91	+0.64/+0.64	-0.96/-0.96	-0.64/-0.64	0.00/0.00	-1.27/-1.27
yo*	30.03/40.05	+0.49/-0.15	+0.68/+0.08	+0.49/+1.39	+1.13/+0.53	+0.68/-0.34	+0.64/+0.08
yue	45.03/51.22	-2.66/-0.19	-0.78/+0.06	-1.31/+0.70	-1.80/+0.26	+0.50/+1.54	-1.83/+0.32

Table 8: Comparison of per-language probing UAS/UUAS between vanilla mBERT and bootstrapped models on test languages. The test languages include Akkadian (akk), Bambara (bm), Belarusian (be), Bhojpuri (bho), Breton (be), Buryat (bxr), Cantonese (yue), Erzya (myv), Faroese (fo), Karelian (krl), Kazakh (kk), Komi Permyak (koi), Komi Zyrian (kpv), Kurmanji (kmr), Livvi (olo), Marathi (Mr), Mbya Guaraní (gun), Moksha (mdf), Nigerian Pidgin (pcm), Sanskrit (sa), Swiss German (gsw), Tagalog (tl), Tamil (ta), Telugu (te), Upper Sorbian (hsb), Warlpiri (wbp), Welsh (cy), and Yoruba (yo). Language codes with asterisks (*) indicate languages included in the mBERT pre-training data.

	UDapter (Baseline)	UDapter-Bootstrapped mBERT					
		Single-Layer (L12)			Multi-Layer (L12+L6)		
		MLM	SynAug	MLM +SynAug	MLM	SynAug	MLM +SynAug
akk	25.76/5.56	-0.22/+1.24 [†]	-9.29 [†] /-2.00 [†]	-1.94/+0.32	-1.35/+1.40 [†]	-7.13 [†] /-1.46 [†]	-0.54/+1.73 [†]
be*	84.31/79.54	+0.28/+0.52	+0.52/+0.66 [†]	+0.11/+0.46	+0.37/+0.70 [†]	+0.07/+0.48	+0.11/+0.42
bho	51.75/36.43	-0.10/+0.08	-0.49/-0.31	-0.84 [†] /+0.76 [†]	-0.14/+0.29	-0.14/-0.20	-0.47/-0.18
bn	27.99/7.97	+1.24 [†] /-0.54 [†]	+0.97 [†] /-0.43 [†]	+1.06 [†] /+0.49 [†]	+1.37 [†] /+0.12	+0.17/-0.72 [†]	+1.54 [†] /-0.34
br*	71.22/55.65	-0.21/+0.28	+1.00 [†] /+2.00 [†]	+0.92 [†] /+1.01 [†]	+0.39/+1.10 [†]	+1.08 [†] /+1.58 [†]	+0.94 [†] /+1.21 [†]
bxr	48.89/28.66	-0.58/-0.63 [†]	-1.02 [†] /-1.08 [†]	-0.18/+0.14	+1.02 [†] /+0.71 [†]	-0.54/-0.88 [†]	-0.15/-0.16
cy*	71.50/54.84	-0.08/-0.28	-0.39/-0.03	-0.21/+0.79 [†]	-0.47 [†] /-0.38	-0.35/-0.35	-0.42 [†] /-0.01
fo	76.04/68.63	+0.19/-0.40	+0.02/-0.57 [†]	-0.45/-0.62 [†]	+0.44/+0.05	+1.57 [†] /+0.91 [†]	-0.33/-0.46
gsw	52.49/39.27	+1.45/+0.97	-1.80/-0.90	+0.69/+0.42	+0.21/+0.62	+0.55/+0.07	-0.83/-1.25
gun	18.44/7.81	+0.61/0.00	+2.66 [†] /+1.21	+3.03 [†] /+0.68	+0.23/-0.08	+2.35 [†] /+1.14	+0.23/-0.46
hsb	60.62/51.99	+1.24 [†] /+0.83 [†]	+1.40 [†] /+1.41 [†]	+1.32 [†] /+1.46 [†]	+1.31 [†] /+1.15 [†]	-0.01/+0.02	+0.30/+0.18
kk*	73.31/61.48	-0.43/-1.22 [†]	-0.92 [†] /-1.12 [†]	-0.38/-0.83 [†]	+0.13/-0.23	+0.14/-0.77 [†]	-0.39/-1.45 [†]
kmr	27.09/12.27	-0.23/-0.77 [†]	-1.66 [†] /-0.97 [†]	+0.27/-0.12	-0.78 [†] /-1.21 [†]	-1.33 [†] /-1.80 [†]	-0.50/-1.20 [†]
koi	34.34/20.05	+0.50/+1.25	+1.50/+1.25	-0.75/-1.00	+3.26 [†] /+2.76	+0.25/+1.25	+1.75/+1.25
kpj	29.66/15.59	+0.90/+0.23	+0.81/+0.26	-1.24 [†] /-0.38	+0.12/+0.17	-0.61/-0.09	+0.35/-0.09
krl	62.18/48.58	-2.49 [†] /-2.13 [†]	-1.81 [†] /-1.65 [†]	-1.87 [†] /-1.81 [†]	-1.26 [†] /-1.29 [†]	-0.55/-0.48	-1.03 [†] /-1.23 [†]
mdf	35.47/22.99	0.00/0.00	+0.18/+0.18	+2.14/+1.43	0.00/+0.18	+1.60/+1.43	-0.71/-0.36
mr*	59.95/44.66	+1.46/+0.97	-2.43/-3.16 [†]	-2.67/-2.67	-0.97/-1.21	-1.21/-0.97	-1.21/-2.43
myv	33.07/18.38	-1.82 [†] /-0.61 [†]	-2.32 [†] /-0.90 [†]	-0.47/+0.29	-0.68 [†] /+0.12	-0.84 [†] /+0.02	-0.76 [†] /-0.20
olo	55.98/41.67	+0.60/+0.07	+1.01/+0.27	-1.08/-1.34	+0.87/+1.08	+1.14/+0.81	+1.14/+0.67
pcm	46.95/33.93	-0.54/+0.05	+1.50 [†] /+2.65 [†]	+1.28 [†] /+1.51 [†]	-0.44/+0.32	+0.94 [†] /+1.87 [†]	-0.26/+0.09
sa	39.88/19.05	-3.85 [†] /-2.60 [†]	-3.91 [†] /-0.98	-1.63/-0.33	-2.06 [†] /-1.14	-2.22 [†] /-1.03	-3.04 [†] /-1.47 [†]
ta*	65.36/41.68	+0.05/+0.55	+2.82 [†] /+3.27 [†]	+0.30/+1.21	+2.71 [†] /+2.46 [†]	+2.01 [†] /+1.51 [†]	+2.97 [†] /+2.82 [†]
te*	81.00/67.82	+0.97/+0.14	+0.69/+1.11	+0.00/+0.42	+0.14/+0.28	0.00/-0.14	-0.69/-0.28
tl*	73.97/57.88	+8.22 [†] /+9.93 [†]	+8.90 [†] /+8.56 [†]	+5.82 [†] /+4.45 [†]	+6.51 [†] /+7.88 [†]	+3.77/+4.11 [†]	+9.25 [†] /+9.93 [†]
wbp	21.02/9.87	-3.82 [†] /-1.59	-7.64 [†] /-4.46 [†]	-0.64/+0.32	-2.87/0.00	+0.32/-1.59	-4.14 [†] /-2.23
yo*	57.28/39.75	+0.23/+0.26	+1.20 [†] /+0.34	+1.16/+0.98	-1.99 [†] /-1.46 [†]	-0.71/+0.19	-1.05/-0.79
yue	50.61/34.21	+1.03 [†] /+1.11 [†]	-0.03/-0.21	+0.75 [†] /+0.37	-0.32/-0.63 [†]	+0.68 [†] /+0.86 [†]	+0.52 [†] /+0.50 [†]

Table 9: Comparison of zero-shot dependency parsing in UAS/LAS between vanilla and bootstrapped mBERT on 28 target languages. [†] indicates statistically significant results from McNemar’s test ($p < 0.05$). Language codes with asterisks (*) are languages included in the mBERT pre-training data.