

Zero-Compute Cross-Lingual Transferability Estimation Using Typological Feature Proxies

Dalton Raphael Harmsen^{*1}, Swier Garst², Thomas van Osch², Zarè Palanciyan², and Joaquin Vanschoren¹

¹AMOR/e Lab, Eindhoven University of Technology, Eindhoven, The Netherlands

²SURF, Amsterdam, The Netherlands

Abstract

Cross-lingual transfer describes how knowledge in a source language benefits a target language. Measuring it quantitatively requires broad multilingual pre-training, as prior work has done with cross-lingual transfer matrices. We ask whether transfer is predictable from freely available typological features, and whether the prominence of high-resource source languages reflects typology or data quality and quantity. We show that typological databases contain cheap and dense signals about cross-lingual transfer. Our typology-only random forest on a 24-language prior-work transfer matrix scores leave-one-language-out $\rho=0.705$ and $R^2=0.49$, beating a non-typological control at $\rho=0.62$, which verifies the ability of typology-only predictions to reconstruct costly measured cross-lingual transfer. The signal survives leave-one-script-out and leave-one-family-out protocols, so script and family confounding do not explain the effect. By decomposing the transfer into a typology term and a resource-and-script bias term, we find the best-source ranking sensitive to this bias. In contrast, typology is not affected by this bias, which makes it a zero-compute screening tool that replaces hundreds of training runs with a model fit. Our code is available here.

1 Introduction

Cross-lingual transfer describes how knowledge in a source language benefits a target language. Longpre et al. introduced ATLAS, which measures this through multilingual pre-training, finding that a few high-resource languages dominate in transfer due to their abundance of training data. However, methods such as ATLAS are prohibitively expensive, requiring hundreds of pre-training runs [1, 6]. On the other hand, Grambank [14, 15] and WALS [3] are readily-available typological databases holding hundreds of structural properties per language. Linguistic similarity has previously been shown to correlate with transfer [4, 9, 12]. We thus hypothesize that these databases contain valuable transfer signal, which can rank candidate source languages before any compute is spent. We therefore pose two questions; **RQ1**: can typological features reconstruct the transfer scores of the ATLAS matrix? **RQ2**: is the prominence of high-resource languages such as English driven by typological features, or by data quality and quantity?

Contributions First, we introduce a typology-only random forest that predicts transfer on a 24-language ATLAS subset, verifying the ability of typology-only predictions to reconstruct the cross-lingual transfer measured by ATLAS. Our inexpensive model replaces hundreds of LLM training runs, complementing forward-pass estimators such as LEEP [10] and LogME [16]. Second, we decompose the ATLAS scores into a typology term and a resource-and-script bias term, and show that best-source ranking is sensitive to this bias.

2 Method and Experiments

Data We use typological features from both the Grambank [14, 15] and WALS [3] databases. In total, 387 Glottocode-keyed [5] features were used, of which 195 originated from Grambank, and 192 from WALS. The exact list of features is given in Appendix A, Table 7. We use these features to predict the bilingual transfer scores (BTS) and fine-tuning adaptation score (FAS) introduced by ATLAS [8]. Keeping languages with at least 70% Grambank feature coverage leaves 24 languages and 552 language pairs; a set we refer to as ATLAS-24.

Model training Our main model is a 200-tree random forest swept per feature source. We compare four tiers: two random forest models, one using all features and one using the features determined by a feature selection and hyperparameter sweep, and two ridge regression models as baselines: a similarity proxy on typological similarity alone, and a generalized linear model on typological similarity, script, genealogical, and geographical distances. We also investigate a control of equal model capacity which uses five non-typological descriptors: writing script, WALS family, WALS genus, geographic region, and Wikipedia resource bin. We use leave-one-language-out (LOLO) and leave- k -languages-out cross-validation, reporting held-out Pearson ρ for ranking performance and R^2 for regression performance. In addition, we use leave-one-family-out (LOFO) and leave-one-script-out (LOSO) as more general holdouts. A fold-respecting permutation null, cluster bootstrap intervals by source language, and paired bootstrap tests of $\Delta\rho$ are employed for statistical tests. Refer to Appendix A for details.

Resource-bias decomposition To separate typology from resources, we model $\text{BTS} = T + b$, composed of typological signal T and resource-and-script bias b , which we model as Wikipedia article counts (source and target language separate), script difference, and genealogical and geographic distance. We fit a ridge regression to estimate $\hat{b}$ and then a random forest that fits the typology term $\hat{T}$ on the residual $\text{BTS} - \hat{b}$.

Experiments Experiments are grouped as follows: E1–E4 probe RQ1 and E5 probes RQ2. E1 examines whether typological features reconstruct measured transfer, by comparing held-out performance across the four model tiers and the matched-capacity metadata control against the permutation null. E2 examines whether the reconstruction is carried by shared writing script rather than by typology, comparing cross-script, same-script, and Latin-only held-out pairs against a script-only directed baseline. E3 examines the genealogical confound through grouped holdouts that leave an entire script or an entire family out of training at once. E4 examines where the signal lives, sweeping the number of features from a single one to the full set and measuring the stability of the importance ranking across folds. E5 examines which source language transfers best, and how a source’s data availability shapes this result, by ranking candidate sources under four operationalizations of transfer that vary in how much resource bias they admit. Full experimental configurations are in Appendix A.

3 Results

Reconstruction performance across model capacity (E1) The reconstruction performance for different model setups is given in Table 1. The predictive performance of the similarity proxy and ridge GLM baselines in both protocols does not meet the simple baseline threshold $\rho=0.225$ (Appendix B, Table 16). The untuned random forest passes this threshold and is able to empirically reconstruct the ATLAS transfer matrix. Performance is further increased with random forest tuned using a hyperparameter sweep, highlighting the value of the typological features for transfer prediction.

Ablations In harder protocols the results degrade but do not collapse, reaching $\rho=0.41$ in the worst case where both languages of each held-out pair are unseen (Appendix B, Table 15). In a matched-capacity setting, where metadata is compared against typology with 5 features each, the performance difference disappears, suggesting that the strength of typology lies in the breadth of the features (Appendix B, Table 12). Statistical inference supports the performance of the tuned model: the cluster bootstrap 95% CI of $[0.51, 0.82]$ excludes the permutation null (mean -0.007) at $p=0.005$. The ordering of feature sources survives metric and language-set changes (Tables 8 and 9). Prediction heatmaps of all tiers are in Appendix C. Interestingly, Grambank features alone outperform the Grambank + WALS union: $\rho=0.78$ vs. 0.705 (Appendix B, Table 8). The union’s degradation comes from the model fitting WALS patterns that hold only within the small training set and fail on held-out

languages, rather than from column dilution or WALS feature quality (Appendix B, Table 10). For the final results, the Grambank + WALS union is adopted anyway due to post-hoc selection bias.

Table 1: LOLO and leave-2-languages-out predictive performance on ATLAS-24 (E1).

Model	LOLO ρ	R^2	L2LO ρ
similarity proxy	0.037	-0.010	0.029
ridge GLM (sim/script/gene/geo)	0.162	0.014	0.154
random forest (all features)	0.615	0.350	0.648
tuned RF (typology)	0.705	0.492	0.702
metadata RF (matched-capacity, 5 fields)	0.581	0.264	0.611
metadata RF (own-sweep tuned)	0.620	0.375	0.621
single-feature ridges (script/family/wiki)	≤ 0.17	≈ 0	≤ 0.17

Generalization across scripts and families (E2, E3) Cross-script held-out pairs are predicted at least as well as same-script, at $\rho=0.728$ vs. 0.600 (Table 2), and the model stays well above the script-only baseline even on Latin-Latin pairs, where script carries no information. Grouped holdout does not decrease performance either: LOSO and LOFO macro- ρ exceed the matched LOLO baseline on the same held-out pairs, and the pair-weighted ρ is unchanged (Appendix B, Table 14). A symmetric cross-check agrees: language pairs that share a script transfer more on average, but a script-only model cannot predict the directed scores and stays near chance (Appendix B, Tables 15 and 13), highlighting that indeed script strongly correlates with transfer, but has no incremental directed power. To conclude, holding out an entire group does not collapse performance ($p<0.01$ for paired bootstrap test), indicating that the signal is typological and not confounded by script or language family.

Table 2: Cross-script robustness and grouped holdouts (E2, E3) on ATLAS-24.

Split	ρ
cross-script pairs	0.728
same-script pairs	0.600
Latin-Latin only	0.509
script-only model	0.138
LOLO (leave-one-language-out)	0.705
LOSO (leave-one-script-out)	0.776
matched LOLO (LOSO pairs)	0.667
LOFO (leave-one-family-out)	0.729
matched LOLO (LOFO pairs)	0.671

Where the signal lives (E4) Typological signal for cross-lingual transfer is highly redundant rather than concentrated in a few decisive features (Table 3). The top- k sweep is flat up to $k=100$ ($\rho=0.57-0.65$), peaks at $k=200$ (0.742), and settles at 0.705 for the full 387 feature set. The top-25 importance ranking is almost completely unstable across folds, yet the single best feature ($k=1$) already reaches $\rho=0.622$, because typological features are correlated (Appendix B, Table 15). This suggests that hundreds of typological features encode one coarse signal, and any one of them recovers most of it.

Table 3: Top- k feature sweep for Experiment E4 under Grambank+WALS; the leak-free row selects its top- k within each fold.

top- k	1	5	10	25	50	100	200	387
global-rank ρ	0.622	0.613	0.573	0.570	0.647	0.627	0.742	0.705
leak-free ρ	0.622	0.627	0.573	0.679	0.657	0.716	0.710	0.705

The best pre-training source (E5) Table 4 lists the top-scoring languages per operationalization, along with their transfer scores. On every BTS-scale operationalization, English ranks first in average transfer score across all languages. Debiasing the residual reverses this: Marathi and Filipino top the ranking instead. This reversal shows that raw rankings are highly sensitive to the resource-and-script bias term, which is exactly what makes typology an attractive alternative, since it never observes this metadata bias in the first place. The flip is statistically robust: Marathi’s mean residual exceeds English’s by 0.24 ($p < 0.001$), holds under a leak-free refit of the bias layer, and clears a permutation null (Appendix B, Table 15). Across 200 reruns, the specific top debiased language varies, so the robust finding is the flip away from English, rather than any particular ranking (Appendix B).

Table 4: “Best pre-training source” over a fixed candidate set (Experiment E5); rows are not comparable across scales.

Operationalization	#1 source	#2 source
empirical (ATLAS, raw BTS mean)	English (+0.022)	Hebrew (−0.074)
on-scale reweighted RF	English (−0.005)	Hebrew (−0.070)
OOD-generalizer (cross-family)	English (−0.011)	Hebrew (−0.065)
debiased residual (mean-zero, off-scale)	Marathi (+0.36)	Filipino (+0.36)

4 Conclusion, Discussion and Limitations

4.1 Conclusion and Discussion

We introduce a typology-only predictor that beats a non-typological control on ATLAS transfer under leave-one-language, leave-one-script, and leave-one-family holdouts. The signal it uses is redundant rather than localized: hundreds of correlated features encode one coarse dimension, and a single feature recovers most of it. Furthermore, we show that best-source rankings built from resource statistics inherit a resource-and-script bias; typological features never observe these resources, so they offer an independent lens on the same question.

Our model requires no new LLM training runs. Given an existing transfer matrix to fit on, adding a language costs only a prediction of a random forest, which makes typology a promising candidate for prioritizing source languages, or for proposing data mixtures to test on low compute budget. Further assessing the quality of such data mixtures requires more in-depth downstream analyses, which we leave for future work.

Beyond our results, the distributed signal also calls on linguistic theory: transfer emerges from many small structural alignments rather than any single feature family.

The bias decomposition warns that a source can look excellent merely because of resource abundance, raising the question whether current high-resource languages are the theoretical optimal training sources, especially in light of future dataset collection efforts.

4.2 Limitations

Ground truth and compute Our results rest entirely on the ATLAS matrix [8], which mixes measured BTS with FAS-estimated scores, so we model a noisy target whose confounds propagate to our findings. Compute constraints confine us to ATLAS’s published results, and strong claims about pre-training require verification at scale.

Scale and sampling All source rankings are 24-language extrapolations on the non-random ATLAS–Grambank overlap, which drops strong European sources such as Spanish and German, and the unseen-language $\rho \approx 0.41$ is our generalization estimate.

Residual debiasing is a diagnostic The bias layer’s weights describe ATLAS-24 rather than a stable law, so the off-scale residual T only exposes the ranking’s bias-sensitivity (Appendix D). Residuals are mean-zero by construction and unitless with respect to BTS, so they support only relative comparisons. A script-by-genus reweighted random forest on raw BTS scores keeps predictions on-scale and comparable.

Acknowledgments and Disclosure of Funding

This research was supported by the OpenEuroLLM project, co-funded by the Digital Europe Programme under GA no. 101195233.

References

- [1] X. Cao, Q. Liu, C. Xiao, Y. Oda, J. Wang, P. Stenetorp, D. Kawahara, M. Onizuka, S. Kurohashi, and S. Zheng. Shapleylaw: A game-theoretic approach to multilingual scaling laws. *arXiv preprint arXiv:2603.17945*, 2026.
- [2] W. B. Cavnar, J. M. Trenkle, et al. N-gram-based text categorization. In *Proceedings of SDAIR-94, 3rd annual symposium on document analysis and information retrieval*, volume 161175, page 14. Ann Arbor, Michigan, 1994.
- [3] M. S. Dryer and M. Haspelmath, editors. *WALS Online (v2020.4)*. Zenodo, 2013. doi: 10.5281/zenodo.13950591. URL <https://doi.org/10.5281/zenodo.13950591>.
- [4] J. Eronen, M. Ptaszynski, T. Wicherkiewicz, R. Borges, K. Janic, Z. Liu, T. Mahmud, and F. Masui. Language models are polyglots: Language similarity predicts cross-lingual transfer learning performance. *Machine Learning and Knowledge Extraction*, 8(3), 2026. ISSN 2504-4990. doi: 10.3390/make8030065. URL <https://www.mdpi.com/2504-4990/8/3/65>.
- [5] R. Forkel and H. Hammarström. Glottocodes: Identifiers linking families, languages and dialects to comprehensive reference information. *Semantic Web*, 13(6):917–924, 2022. doi: 10.3233/SW-212843. URL <https://journals.sagepub.com/doi/abs/10.3233/SW-212843>.
- [6] Y. He, A. Benhaim, B. Patra, P. Vaddamanu, S. Ahuja, P. Chopra, V. Chaudhary, H. Zhao, and X. Song. Scaling laws for multilingual language models. In W. Che, J. Nabende, E. Shutova, and M. T. Pilehvar, editors, *Findings of the Association for Computational Linguistics: ACL 2025*, pages 4257–4273, Vienna, Austria, July 2025. Association for Computational Linguistics. ISBN 979-8-89176-256-5. doi: 10.18653/v1/2025.findings-acl.221. URL <https://aclanthology.org/2025.findings-acl.221/>.
- [7] P. Littell, D. R. Mortensen, K. Lin, K. Kairis, C. Turner, and L. Levin. URIEL and lang2vec: Representing languages as typological, geographical, and phylogenetic vectors. In M. Lapata, P. Blunsom, and A. Koller, editors, *Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics: Volume 2, Short Papers*, pages 8–14, Valencia, Spain, Apr. 2017. Association for Computational Linguistics. URL <https://aclanthology.org/E17-2002/>.
- [8] S. Longpre, S. Kudugunta, N. Muennighoff, I.-H. Hsu, I. Caswell, A. Pentland, S. Arik, C.-Y. Lee, and S. Ebrahimi. Atlas: Adaptive transfer scaling laws for multilingual pretraining, finetuning, and decoding the curse of multilinguality. In C. Vondrick, B. Hariharan, C. Raffel, L. Pinto, D. Yang, and A. Faust, editors, *International Conference on Learning Representations*, volume 2026, pages 31839–31867, 2026. URL https://proceedings.iclr.cc/paper_files/paper/2026/file/35c26a810471039b3427e524565cbef9-Paper-Conference.pdf.
- [9] B. Muller, D. Gupta, J.-P. Fauconnier, S. Patwardhan, D. Vandyke, and S. Agarwal. Languages you know influence those you learn: Impact of language characteristics on multi-lingual text-to-text transfer. In A. Albalak, C. Zhou, C. Raffel, D. Ramachandran, S. Ruder, and X. Ma, editors, *Proceedings of The 1st Transfer Learning for Natural Language Processing Workshop*, volume 203 of *Proceedings of Machine Learning Research*, pages 88–102. PMLR, 03 Dec 2023. URL <https://proceedings.mlr.press/v203/muller23a.html>.
- [10] C. Nguyen, T. Hassner, M. Seeger, and C. Archambeau. LEEP: A new measure to evaluate transferability of learned representations. In H. D. III and A. Singh, editors, *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 7294–7305. PMLR, 13–18 Jul 2020. URL <https://proceedings.mlr.press/v119/nguyen20b.html>.

- [11] A. Petrov, E. La Malfa, P. Torr, and A. Bibi. Language model tokenizers introduce unfairness between languages. In A. Oh, T. Naumann, A. Globerson, K. Saenko, M. Hardt, and S. Levine, editors, *Advances in Neural Information Processing Systems*, volume 36, pages 36963–36990. Curran Associates, Inc., 2023. doi: 10.52202/075280-1608. URL https://proceedings.neurips.cc/paper_files/paper/2023/file/74bb24dca8334adce292883b4b651eda-Paper-Conference.pdf.
- [12] E. Rice, A. Marashian, H. Haynie, K. von der Wense, and A. Palmer. Untangling the influence of typology, data, and model architecture on ranking transfer languages for cross-lingual POS tagging. In S. Truong, R. A. Putri, D. Nguyen, A. Wang, D. Ho, A. Oh, and S. Koyejo, editors, *Proceedings of the 1st Workshop on Language Models for Underserved Communities (LM4UC 2025)*, pages 22–31, Albuquerque, New Mexico, May 2025. Association for Computational Linguistics. ISBN 979-8-89176-242-8. doi: 10.18653/v1/2025.lm4uc-1.4. URL <https://aclanthology.org/2025.lm4uc-1.4/>.
- [13] R. Sennrich, B. Haddow, and A. Birch. Neural machine translation of rare words with subword units. In K. Erk and N. A. Smith, editors, *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1715–1725, Berlin, Germany, Aug. 2016. Association for Computational Linguistics. doi: 10.18653/v1/P16-1162. URL <https://aclanthology.org/P16-1162/>.
- [14] H. Skirgård, H. J. Haynie, D. E. Blasi, H. Hammarström, J. Collins, J. J. Latache, J. Lesage, T. Weber, A. Witzlack-Makarevich, S. Passmore, A. Chira, L. Maurits, R. Dinnage, M. Dunn, G. Reesink, R. Singer, C. Bower, P. Epps, J. Hill, O. Vesakoski, M. Robbeets, N. K. Abbas, D. Auer, N. A. Bakker, G. Barbos, R. D. Borges, S. Danielsen, L. Dorenbusch, E. Dorn, J. Elliott, G. Falcone, J. Fischer, Y. Ghanggo Ate, H. Gibson, H.-P. Göbel, J. A. Goodall, V. Gruner, A. Harvey, R. Hayes, L. Heer, R. E. Herrera Miranda, N. Hübler, B. Huntington-Rainey, J. K. Ivani, M. Johns, E. Just, E. Kashima, C. Kipf, J. V. Klingenberg, N. König, A. Koti, R. G. A. Kowalik, O. Krasnoukhova, N. L. Lindvall, M. Lorenzen, H. Lutzenberger, T. R. Martins, C. Mata German, S. van der Meer, J. Montoya Samamé, M. Müller, S. Muradoglu, K. Neely, J. Nickel, M. Norvik, C. A. Oluoch, J. Peacock, I. O. Pearey, N. Peck, S. Petit, S. Pieper, M. Poblete, D. Prestipino, L. Raabe, A. Raja, J. Reimringer, S. C. Rey, J. Rizaew, E. Ruppert, K. K. Salmon, J. Sammet, R. Schembri, L. Schlabbach, F. W. Schmidt, A. Skilton, W. D. Smith, H. de Sousa, K. Sverredal, D. Valle, J. Vera, J. Voß, T. Witte, H. Wu, S. Yam, J. Ye, M. Yong, T. Yuditha, R. Zariquiey, R. Forkel, N. Evans, S. C. Levinson, M. Haspelmath, S. J. Greenhill, Q. D. Atkinson, and R. D. Gray. Grambank reveals the importance of genealogical constraints on linguistic diversity and highlights the impact of language loss. *Science Advances*, 9(16), 2023. doi: 10.1126/sciadv.adg6175.
- [15] H. Skirgård, H. J. Haynie, H. Hammarström, D. E. Blasi, J. Collins, J. Latache, J. Lesage, T. Weber, A. Witzlack-Makarevich, M. Dunn, G. Reesink, R. Singer, C. Bower, P. Epps, J. Hill, O. Vesakoski, N. K. Abbas, S. Ananth, D. Auer, N. A. Bakker, G. Barbos, A. Bolls, R. D. Borges, M. Browen, L. Chevallier, S. Danielsen, S. Dohlen, L. Dorenbusch, E. Dorn, M. Duhamel, F. E. H. Ali, J. Elliott, G. Falcone, A.-M. Fehn, J. Fischer, Y. G. Ate, H. Gibson, H.-P. Göbel, J. A. Goodall, V. Gruner, A. Harvey, R. Hayes, L. Heer, R. E. H. Miranda, N. Hübler, B. H. Huntington-Rainey, G. Inglese, J. K. Ivani, M. Johns, E. Just, I. Kapitonov, E. Kashima, C. Kipf, J. V. Klingenberg, N. König, A. Koti, R. G. A. Kowalik, O. Krasnoukhova, K. L. Lindsey, N. L. M. Lindvall, M. Lorenzen, H. Lutzenberger, A. Marley, T. R. A. Martins, C. M. German, S. van der Meer, J. Montoya, M. Müller, S. Muradoğlu, HunterGatherer, D. Nash, K. Neely, J. Nickel, M. Norvik, B. Olsson, C. A. Oluoch, D. Osgarby, J. Peacock, I. O. Pearey, N. Peck, J. Peter, S. Petit, S. Pieper, M. Poblete, D. Prestipino, L. Raabe, A. Raja, J. Reimringer, S. C. Rey, J. Rizaew, E. Ruppert, K. K. Salmon, J. Sammet, R. Schembri, L. Schlabbach, F. W. P. Schmidt, D. Schokkin, J. Siegel, A. Skilton, H. de Sousa, K. Sverredal, D. Valle, J. Vera, J. Voß, D. W. Smith, T. Witte, H. Wu, S. Yam, J. Ye, M. Yong, T. Yuditha, R. Zariquiey, R. Forkel, N. Evans, S. C. Levinson, M. Haspelmath, S. J. Greenhill, Q. D. Atkinson, and R. D. Gray. Grambank v1.0, Mar. 2023. URL <https://doi.org/10.5281/zenodo.7740140>. Dataset.
- [16] K. You, Y. Liu, J. Wang, and M. Long. Logme: Practical assessment of pre-trained models for transfer learning. In M. Meila and T. Zhang, editors, *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*,

A Experimental configuration

Notation Formally, the input is $[M_s, M_t, \Delta]$ with $M_s, M_t \in \{0, 1\}^{n_{\text{codes}}}$ the one-hot per-feature profiles ($n_{\text{codes}} = \sum_{f \in F} |C_f|$, with C_f the codes of feature f) and $\Delta \in \{0, 1\}^{n_{\text{feat}}}$ a per-feature disagreement block ($n_{\text{feat}} = |F|$).

Protocols, metrics, and controls in plain language Every experiment trains a model on some language pairs and then scores it on pairs it never trained on, and the protocols below differ only in how the pairs are split. In leave-one-language-out, every pair touching one language is hidden, the model trains on the remaining pairs and predicts the hidden ones, and each of the 24 languages takes a turn as the hidden language. Leave- k -languages-out hides k languages at once, so a test pair can involve languages that never appear in training, which is the harder setting. Pearson ρ checks whether the model orders pairs as ATLAS does: 1 means a perfect ordering, 0 means the predicted ordering carries no information about the true one, and negative values mean systematically reversed orderings. R^2 asks the stronger question of whether the predicted values are numerically close: it compares the model’s squared error against that of a baseline that always predicts the average BTS, so 1 is perfect, 0 matches the baseline, and negative is worse than it. This is the quantity also known as explained variance, the share of the variation in BTS that the predictions account for. The permutation null shuffles the training scores within each fold, reruns the procedure, and reports how often such chance data score as well as the real data. Because pairs that share a language are not independent, the cluster bootstrap resamples whole languages with replacement, and each drawn language brings all of its pairs. Repeating the evaluation on each resample expresses how much the reported score could plausibly vary. The matched-capacity control is a random forest of identical size and tuning budget that receives five non-typological descriptors instead of typological features. A gap in its favor therefore reflects the typological features, rather than model capacity or tuning.

Table 5: Shared setup underlying all experiments in Table 6. All typology experiments use the Grambank+WALS feature source and the one-decimal ATLAS target at $n=24$, which is 552 directed pairs, unless a row of Table 6 states a deviation.

Component	Exact configuration
Empirical target	the directed BTS transfer matrix digitized from Figure C.2 of the ATLAS paper, read at one decimal
Typological features	Grambank with 195 features and WALS with 192, keyed by Glottocode; the union carries 387 features
Modeling set	ATLAS-24: the 24 ATLAS languages with Grambank coverage of at least 0.70; the floor is Grambank-only, so WALS adds feature columns but no languages; all 24×23 directed pairs with $s \neq t$, which is 552
Input representation	$[M_s, M_t, \Delta]$, the one-hot code profiles of source and target plus a per-feature disagreement block, as defined above
Main model	random forest with 200 trees, <code>random_state= 42</code> , and <code>max_features= 0.5</code> ; under WALS alone <code>max_features</code> is <code>log2</code> ; all remaining parameters at scikit-learn defaults
Ridge models	$\alpha=1.0$ throughout: the similarity proxy, the GLM on similarity, script, genealogical, and geographic distances, the script-only model, and the feature-importance ranker; the bias ridge standardizes its inputs first
Cross-validation	leave-one-language-out with 24 folds; a pair is held out exactly when either endpoint is the held-out language; each fold refits the model; held-out predictions are pooled over folds, and a pair predicted in two folds resolves to the fold of its alphabetically later language
Metrics	held-out Pearson ρ and true $R^2 = 1 - \text{SS}_{\text{res}}/\text{SS}_{\text{tot}}$
Seeds and records	seed 42 throughout, with seeds 43 and 44 for seed stability; every result CSV carries a <code>_meta.json</code> holding the resolved configuration and the git commit; locked environment: Python 3.12, scikit-learn 1.9, NumPy 2.5, pandas 3.0, SciPy 1.18

Table 6: Exact configuration of the five experiments E1 to E5 and their sub-analyses. Each experiment addresses the research question named in its group header, with E1 to E4 probing RQ1 and E5 probing RQ2. Settings inherited from Table 5 are not repeated. Repository scripts preserve their own identifiers, so the experiment labels E1 to E5 are assigned here for readability.

Analysis	Exact configuration
<i>E1 (RQ1): held-out performance and capacity</i>	
Tier comparison	four tiers under identical folds: the similarity-proxy ridge, the GLM ridge, the 200-tree RF at scikit-learn defaults, and the tuned RF; metadata single-feature ridges for script, family, and Wikipedia and their combination, each with within-fold standardization on its own coverage-restricted universe: script and Wikipedia cover 24 languages, the WALS family map covers 22
Distance baselines	five non-typological distance baselines under the identical folds and metrics, each a single-column ridge except where noted, with within-fold standardization on the full 24-language universe: the lang2vec cosine over the concatenated imputed syntax, phonology, and inventory vectors; the URIEL design with six columns, genetic from the language-family vector, geographic as the great-circle distance on Glottolog coordinates normalized by half the circumference, syntactic, phonological, and inventory as one minus the cosine of the respective vectors, and featural as their mean; and three Jaccard overlaps over per-language Wikipedia lead-paragraph corpora of 2,000 random articles per edition with a committed sha256 manifest, namely byte-level BPE vocabularies of 8,000 entries, pooled character 1-to-3-gram sets over the 5,000 most frequent word types, and the 10,000 most frequent word types; lang2vec 1.1.2 imputed feature sets cover all 24 languages, and the learned embeddings are unusable because seven of the 24 languages are absent and the embedding file does not load under NumPy 2
Leave- k -languages-out	$k \in \{1, 2, 3\}$; $k=1$ is the deterministic LOLO partition; for $k \geq 2$ the tuned RF averages over 50 random disjoint partitions of the 24 languages and the remaining tiers over 25; a pair is held out when either endpoint is in the held-out group; the reported ρ is the partition mean and the interval is the partition spread; seed 42
Permutation null	fold-respecting: within each fold only the training labels are permuted and the held-out labels are untouched; $B=200$; $p = (1 + \#\{\text{null} \geq \text{observed}\})/(B+1)$; seed 42
Cluster bootstrap	95% intervals by resampling the 24 source languages with replacement, $B=2000$, seed 42; paired bootstrap of $\Delta\rho$ against the script-only ridge and against the GLM on shared pairs; a language-level variant resamples the 24 languages and reweights each pair by the product of how often its two endpoints were drawn
Feature sources	Grambank with 195 features and Grambank+WALS with 387 run at $n=24$; WALS runs at $n=22$ because WALS lacks Glottocode mappings for two of the 24 languages; each source carries its own swept <code>max_features</code> , which is 0.5, 0.5, and $\log_2$ in the order above
Shared-language sources	all three sources refit on the 22 ATLAS-24 languages covered by the WALS mapping, 462 directed pairs; per-source <code>max_features</code> mini-sweep over the seven grid values; identical LOLO folds; seed 42
WALS-block permutation	the WALS block of the wide matrix permuted across the 24 languages, preserving each feature’s marginal levels and missingness; ten permutations, each under the seven-value <code>max_features</code> mini-sweep on the production LOLO folds at $n=24$; forest seed 42, permutation seeds 1000 to 1009

Table 6: Exact configuration of Experiments E1 to E5, continued.

Analysis	Exact configuration
Coverage-floor sweep	the per-language Grambank coverage floor lowered from 0.70 to 0.60, 0.50, 0.40, and 0.00, admitting one language per step, namely Telugu, Thai, Indonesian, and Central Kurdish; every tier refit at each floor under the production configuration and the identical LOLO protocol; the tuned RF is additionally scored under the pure-unseen-language protocol at each floor; seed 42
Digitization-noise robustness	100 refits of the tuned RF on targets perturbed by independent $U(-0.05, 0.05)$ noise per cell, forest seed fixed at 42, scored on the clean target
Pure-unseen-language protocol	repeated grouped 5-fold over languages with five repeats; test pairs are those whose both languages are held out, so training pairs never touch a held-out language; seed 42, with three seeds in the refinement stage
Matched-capacity control	a non-typological RF over the one-hot per-language metadata profile: script with 9 levels, WALS family, WALS genus, a k -means geographic region with 6 clusters, and a Wikipedia article-count quartile bin; missing values get an explicit unknown level, which favors metadata and is the conservative direction; the same pair design, 200-tree RF, and LOLO folds as the typology model; the budget-matched row averages LOLO ρ over 20 random 5-feature typology subsets drawn from the top 15 of the global importance ranking, seed 42
Matched-tuning control	the metadata RF swept over the same curated grid as the typology model; all 168 configurations screened under LOLO at 200 trees, seed 42; top 8 refined over seeds 42 to 46; the winner by true R^2 is <code>max_features sqrt</code> with <code>max_depth 10</code> , <code>min_samples_leaf 1</code> , and <code>max_samples 1.0</code> ; leave-2-languages-out over 50 random partitions; paired cluster bootstrap of $\Delta\rho$ against the tuned typology model with source-language blocks, $B=2000$, seed 42
Hyperparameter sweep	curated grid over <code>max_features</code> $\in \{0.2, 0.3, 0.5, 0.7, 1.0, \text{sqrt}, \log 2\}$, <code>max_depth</code> $\in \{\text{None}, 6, 10, 16\}$, <code>min_samples_leaf</code> $\in \{1, 2, 5\}$, and <code>max_samples</code> $\in \{0.6, 1.0\}$; screening under LOLO at 200 trees and one seed; refinement of the top 8 configurations plus the scikit-learn-default and previously tuned references under both protocols at 200 and 500 trees, with five LOLO seeds and three unseen-language seeds; the metric of record is true R^2 with Pearson as tie-break; the per-source winner maximizes the combined rank of LOLO and unseen-language R^2
<i>E2 (RQ1): within-script typology isolation</i>	
Script stratification	pooled LOLO predictions split into same-script, cross-script, and Latin-Latin pairs; four models: the script-only ridge, the GLM with the script column, the GLM without the script column, and the tuned RF; run under Grambank+WALS and under Grambank alone; subgroup 95% intervals by cluster bootstrap, $B=2000$
<i>E3 (RQ1): out-of-distribution taxonomy</i>	
Grouped holdout	leave-one-script-out with groups by writing script and leave-one-family-out with groups by WALS major family; the fold for group g holds out every pair touching a language of g ; per-group ρ is scored when the group has at least three held-out pairs; the macro value is the unweighted mean over groups; 95% intervals by one-sample bootstrap over held-out groups, $B=2000$
Composition-matched baseline	pooled LOLO predictions restricted to the held-out pairs of each script or family group, macro-averaged and pair-weighted, compared against grouped holdout on the same groups

Table 6: Exact configuration of Experiments E1 to E5, continued.

Analysis	Exact configuration
Symmetric check	cross- per-factor Mantel r and MRM with $B=999$ permutations of the response-matrix labels on the 276 upper-triangle cells; the response is symmetrized BTS, the mean of the two directions, treated as a distance; predictors are min-max-normalized typological, genealogical, geographic, and script distances; partial Mantel is deliberately not used because of its Type-I error inflation
<i>E4 (RQ1): where the signal lives</i>	
Feature ranking	ridge permutation importance with $\alpha=1$ and seed 42; the importance of a feature is the drop in held-out ρ when its one-hot columns and disagreement bit are permuted within each fold’s training set; the global ranking pools this over folds, and the stability analysis keeps the 24 per-fold rankings
Top- k sweep	$k \in \{1, 5, 10, 25, 50, 100, 200\}$ plus the full 387; features ordered by the global ranking; the same tuned RF; the ranking is scored on the evaluation folds, so entries with $k < 387$ are optimistically biased
Leak-free selection	each fold takes its own top- k by mean importance over the other 23 folds, so the held-out language touches neither the fit nor the ranking; the same RF; seed stability over seeds 42, 43, and 44
Importance stability	mean pairwise Spearman correlation over the 24 per-fold importance vectors and mean pairwise top-25 Jaccard overlap; 95% interval by bootstrap over fold pairs, $B=2000$
<i>E5 (RQ2): the best pre-training source</i>	
Operationalizations	the candidate set and the target set are both the full ATLAS-24; empirical is the mean raw BTS per source over targets; the debiased residual is the mean residual T , with an on-scale variant $\hat{T} + \hat{B}$; centrality is the mean typological similarity to the other 23 languages on the Grambank+WALS features; the OOD-generalizer is the mean raw BTS to targets from a different WALS major family; the on-scale reweighted model is the 200-tree RF on raw BTS with sample weight $1/ \text{block} $ per unordered script-by-genus block; the top 10 sources are reported per operationalization, and the full 24 in Table 19
Bias layer	ridge with $\alpha=1$ on standardized script difference, genealogical distance, min-max-normalized geographic distance, and $\log 1p$ Wikipedia article counts of source and target, fitted in-sample on all 552 pairs; the residual $T = \text{BTS} - \hat{B}$ is mean-zero by construction; robustness is probed by refitting on all 31 non-empty descriptor subsets, Table 18
Leak-free bias layer	$\hat{B}$ refit out-of-fold under the LOLO folds, each pair’s bias predicted by a ridge that never saw its held-out language, and the residual ranking recomputed as the raw mean residual and through the production rf_T
Residual permutation null	the full operationalization, bias ridge, residual, rf_T , and per-source ranking, rerun on permuted BTS labels, $B=200$, seed 42, recording the top-source margin over the median source and the gap over English per replicate
Residual gap test	the difference of mean residuals between two sources is bootstrapped over targets, resampling targets and pairing both sources on the same resample, $B=2000$

Compute and provenance All experiments ran on a single CPU of a local workstation, and no GPU, cluster, or cloud resources were used. The models are scikit-learn random forests and ridge regressions on 552 directed pairs, so each configuration fits in seconds at this scale. Grambank v1.0 and WALS Online are distributed under CC-BY 4.0, lang2vec under CC-BY-SA 4.0, scikit-learn under the BSD 3-Clause license, and Wikipedia text under CC-BY-SA 4.0. The ATLAS paper is

published at ICLR 2026, and we digitize the values of its Figure C.2 for analysis only. Our released code is MIT-licensed.

Table 7: The 387 typological features used in this work, in natural ID order within each source: 195 Grambank parameters and 192 WALS features.

ID	Feature	ID	Feature
<i>Grambank</i> (195 features)			
GB020	Are there definite or specific articles?	GB021	Do indefinite nominals commonly have indefinite articles?
GB022	Are there prenominal articles?	GB023	Are there postnominal articles?
GB024	What is the order of numeral and noun in the NP?	GB025	What is the order of adnominal demonstrative and noun?
GB026	Can adnominal property words occur discontinuously?	GB027	Are nominal conjunction and comitative expressed by different elements?
GB028	Is there a distinction between inclusive and exclusive?	GB030	Is there a gender distinction in independent 3rd person pronouns?
GB031	Is there a dual or unit augmented form (in addition to plural or augmented) for all person categories in the pronoun system?	GB035	Are there three or more distance contrasts in demonstratives?
GB036	Do demonstratives show an elevation distinction?	GB037	Do demonstratives show a visible-nonvisible distinction?
GB038	Are there demonstrative classifiers?	GB039	Is there nonphonological allomorphy of noun number markers?
GB041	Are there several nouns (more than three) which are suppletive for number?	GB042	Is there productive overt morphological singular marking on nouns?
GB043	Is there productive morphological dual marking on nouns?	GB044	Is there productive morphological plural marking on nouns?
GB046	Is there an associative plural marker for nouns?	GB047	Is there a productive morphological pattern for deriving an action/state noun from a verb?
GB048	Is there a productive morphological pattern for deriving an agent noun from a verb?	GB049	Is there a productive morphological pattern for deriving an object noun from a verb?
GB051	Is there a gender/noun class system where sex is a factor in class assignment?	GB052	Is there a gender/noun class system where shape is a factor in class assignment?
GB053	Is there a gender/noun class system where animacy is a factor in class assignment?	GB054	Is there a gender/noun class system where plant status is a factor in class assignment?
GB057	Are there numeral classifiers?	GB058	Are there possessive classifiers?
GB059	Is the adnominal possessive construction different for alienable and inalienable nouns?	GB065	What is the pragmatically unmarked order of adnominal possessor noun and possessed noun?
GB068	Do core adjectives (defined semantically as property concepts such as value, shape, age, dimension) act like verbs in predicative position?	GB069	Do core adjectives (defined semantically as property concepts; value, shape, age, dimension) used attributively require the same morphological treatment as verbs?
GB070	Are there morphological cases for non-pronominal core arguments (i.e. S/A/P)?	GB071	Are there morphological cases for pronominal core arguments (i.e. S/A/P)?
GB072	Are there morphological cases for oblique non-pronominal NPs (i.e. not S/A/P)?	GB073	Are there morphological cases for independent oblique personal pronominal arguments (i.e. not S/A/P)?
GB074	Are there prepositions?	GB075	Are there postpositions?
GB079	Do verbs have prefixes/proclitics, other than those that only mark A, S or P (do include portmanteau: A & S + TAM)?	GB080	Do verbs have suffixes/enclitics, other than those that only mark A, S or P (do include portmanteau: A & S + TAM)?
GB081	Is there productive infixation in verbs?	GB082	Is there overt morphological marking of present tense on verbs?
GB083	Is there overt morphological marking on the verb dedicated to past tense?	GB084	Is there overt morphological marking on the verb dedicated to future tense?
GB086	Is a morphological distinction between perfective and imperfective aspect available on verbs?	GB089	Can the S argument be indexed by a suffix/enclitic on the verb in the simple main clause?
GB090	Can the S argument be indexed by a prefix/proclitic on the verb in the simple main clause?	GB091	Can the A argument be indexed by a suffix/enclitic on the verb in the simple main clause?
GB092	Can the A argument be indexed by a prefix/proclitic on the verb in the simple main clause?	GB093	Can the P argument be indexed by a suffix/enclitic on the verb in the simple main clause?
GB094	Can the P argument be indexed by a prefix/proclitic on the verb in the simple main clause?	GB095	Are variations in marking strategies of core participants based on TAM distinctions?
GB096	Are variations in marking strategies of core participants based on verb classes?	GB098	Are variations in marking strategies of core participants based on person distinctions?

(continued)

ID	Feature	ID	Feature
GB099	Can verb stems alter according to the person of a core participant?	GB103	Is there a benefactive applicative marker on the verb (including indexing)?
GB104	Is there an instrumental applicative marker on the verb (including indexing)?	GB105	Can the recipient in a ditransitive construction be marked like the monotransitive patient?
GB107	Can standard negation be marked by an affix, clitic or modification of the verb?	GB108	Is there directional or locative morphological marking on verbs?
GB109	Is there verb suppletion for participant number?	GB110	Is there verb suppletion for tense or aspect?
GB111	Are there conjugation classes?	GB113	Are there verbal affixes or clitics that turn intransitive verbs into transitive ones?
GB114	Is there a phonologically bound reflexive marker on the verb?	GB115	Is there a phonologically bound reciprocal marker on the verb?
GB116	Do verbs classify the shape, size or consistency of absolutive arguments by means of incorporated nouns, verbal affixes or suppletive verb stems?	GB117	Is there a copula for predicate nominals?
GB118	Are there serial verb constructions?	GB119	Can mood be marked by an inflecting word ("auxiliary verb")?
GB120	Can aspect be marked by an inflecting word ("auxiliary verb")?	GB121	Can tense be marked by an inflecting word ("auxiliary verb")?
GB122	Is verb compounding a regular process?	GB123	Are there verb-adjunct (aka light-verb) constructions?
GB124	Is incorporation of nouns into verbs a productive intransitivizing process?	GB126	Is there an existential verb?
GB127	Are different posture verbs used obligatorily depending on an inanimate locatum's shape or position (e.g. 'to lie' vs. 'to stand')?	GB129	Is there a notably small number, i.e. about 100 or less, of verb roots in the language?
GB130	What is the pragmatically unmarked order of S and V in intransitive clauses?	GB131	Is a pragmatically unmarked constituent order verb-initial for transitive clauses?
GB132	Is a pragmatically unmarked constituent order verb-medial for transitive clauses?	GB133	Is a pragmatically unmarked constituent order verb-final for transitive clauses?
GB134	Is the order of constituents the same in main and subordinate clauses?	GB135	Do clausal objects usually occur in the same position as nominal objects?
GB136	Is the order of core argument (i.e. S/A/P) constituents fixed?	GB137	Can standard negation be marked clause-finally?
GB138	Can standard negation be marked clause-initially?	GB139	Is there a difference between imperative (prohibitive) and declarative negation constructions?
GB140	Is verbal predication marked by the same negator as all of the following types of predication: locational, existential and nominal?	GB146	Is there a morpho-syntactic distinction between predicates expressing controlled versus uncontrolled events or states?
GB147	Is there a morphological passive marked on the lexical verb?	GB148	Is there a morphological antipassive marked on the lexical verb?
GB149	Is there a morphologically marked inverse on verbs?	GB150	Is there clause chaining?
GB151	Is there an overt verb marker dedicated to signalling coreference or noncoreference between the subject of one clause and an argument of an adjacent clause ("switch reference")?	GB152	Is there a morphologically marked distinction between simultaneous and sequential clauses?
GB155	Are causatives formed by affixes or clitics on verbs?	GB156	Is there a causative construction involving an element that is unmistakably grammaticalized from a verb for 'to say'?
GB158	Are verbs reduplicated?	GB159	Are nouns reduplicated?
GB160	Are elements apart from verbs or nouns reduplicated?	GB165	Is there productive morphological trial marking on nouns?
GB166	Is there productive morphological paucal marking on nouns?	GB167	Is there a logophoric pronoun?
GB170	Can an adnominal property word agree with the noun in gender/noun class?	GB171	Can an adnominal demonstrative agree with the noun in gender/noun class?
GB172	Can an article agree with the noun in gender/noun class?	GB177	Can the verb carry a marker of animacy of argument, unrelated to any gender/noun class of the argument visible in the NP domain?
GB184	Can an adnominal property word agree with the noun in number?	GB185	Can an adnominal demonstrative agree with the noun in number?
GB186	Can an article agree with the noun in number?	GB187	Is there any productive diminutive marking on the noun (exclude marking by system of nominal classification only)?

(continued)

ID	Feature	ID	Feature
GB188	Is there any productive augmentative marking on the noun (exclude marking by system of nominal classification only)?	GB192	Is there a gender system where a noun's phonological properties are a factor in class assignment?
GB193	What is the order of adnominal property word and noun?	GB196	Is there a male/female distinction in 2nd person independent pronouns?
GB197	Is there a male/female distinction in 1st person independent pronouns?	GB198	Can an adnominal numeral agree with the noun in gender/noun class?
GB203	What is the order of the adnominal collective universal quantifier ('all') and the noun?	GB204	Do collective ('all') and distributive ('every') universal quantifiers differ in their forms or their syntactic positions?
GB250	Can predicative possession be expressed with a transitive 'habeo' verb?	GB252	Can predicative possession be expressed with an S-like possessum and a locative-coded possessor?
GB253	Can predicative possession be expressed with an S-like possessum and a dative-coded possessor?	GB254	Can predicative possession be expressed with an S-like possessum and a possessor that is coded like an adnominal possessor?
GB256	Can predicative possession be expressed with an S-like possessor and a possessum that is coded like a comitative argument?	GB257	Can polar interrogation be marked by intonation only?
GB260	Can polar interrogation be indicated by a special word order?	GB262	Is there a clause-initial polar interrogative particle?
GB263	Is there a clause-final polar interrogative particle?	GB264	Is there a polar interrogative particle that most commonly occurs neither clause-initially nor clause-finally?
GB265	Is there a comparative construction that includes a form that elsewhere means 'surpass, exceed'?	GB266	Is there a comparative construction that employs a marker of the standard which elsewhere has a locational meaning?
GB270	Can comparatives be expressed using two conjoined clauses?	GB273	Is there a comparative construction with a standard marker that elsewhere has neither a locational meaning nor a 'surpass/exceed' meaning?
GB275	Is there a bound comparative degree marker on the property word in a comparative construction?	GB276	Is there a non-bound comparative degree marker modifying the property word in a comparative construction?
GB285	Can polar interrogation be marked by a question particle and verbal morphology?	GB286	Can polar interrogation be indicated by overt verbal morphology only?
GB291	Can polar interrogation be marked by tone?	GB296	Is there a phonologically or morphosyntactically definable class of ideophones that includes ideophones depicting imagery beyond sound?
GB297	Can polar interrogation be indicated by a V-not-V construction?	GB298	Can standard negation be marked by an inflecting word ("auxiliary verb")?
GB299	Can standard negation be marked by a non-inflecting word ("auxiliary particle")?	GB300	Does the verb for 'give' have suppletive verb forms?
GB301	Is there an inclusory construction?	GB302	Is there a phonologically free passive marker ("particle" or "auxiliary")?
GB303	Is there a phonologically free antipassive marker ("particle" or "auxiliary")?	GB304	Can the agent be expressed overtly in a passive clause?
GB305	Is there a phonologically independent reflexive pronoun?	GB306	Is there a phonologically independent non-bipartite reciprocal pronoun?
GB309	Are there multiple past or multiple future tenses, distinguishing distance from Time of Reference?	GB312	Is there overt morphological marking on the verb dedicated to mood?
GB313	Are there special adnominal possessive pronouns that are not formed by an otherwise regular process?	GB314	Can augmentative meaning be expressed productively by a shift of gender/noun class?
GB315	Can diminutive meaning be expressed productively by a shift of gender/noun class?	GB316	Is singular number regularly marked in the noun phrase by a dedicated phonologically free element?
GB317	Is dual number regularly marked in the noun phrase by a dedicated phonologically free element?	GB318	Is plural number regularly marked in the noun phrase by a dedicated phonologically free element?
GB319	Is trial number regularly marked in the noun phrase by a dedicated phonologically free element?	GB320	Is paucal number regularly marked in the noun phrase by a dedicated phonologically free element?
GB321	Is there a large class of nouns whose gender/noun class is not phonologically or semantically predictable?	GB322	Is there grammatical marking of direct evidence (perceived with the senses)?
GB323	Is there grammatical marking of indirect evidence (hearsay, inference, etc.)?	GB324	Is there an interrogative verb for content interrogatives (who?, what?, etc.)?
GB325	Is there a count/mass distinction in interrogative quantifiers?	GB326	Do (nominal) content interrogatives normally or frequently occur in situ?

(continued)

ID	Feature	ID	Feature
GB327	Can the relative clause follow the noun?	GB328	Can the relative clause precede the noun?
GB329	Are there internally-headed relative clauses?	GB330	Are there correlative relative clauses?
GB331	Are there non-adjacent relative clauses?	GB333	Is there a decimal numeral system?
GB334	Is there synchronic evidence for any element of a quinary numeral system?	GB335	Is there synchronic evidence for any element of a vigesimal numeral system?
GB336	Is there a body-part tallying system?	GB400	Are all person categories neutralized in some voice, tense, aspect, mood and/or negation?
GB401	Is there a class of patient-labile verbs?	GB402	Does the verb for 'see' have suppletive verb forms?
GB403	Does the verb for 'come' have suppletive verb forms?	GB408	Is there any accusative alignment of flagging?
GB409	Is there any ergative alignment of flagging?	GB410	Is there any neutral alignment of flagging?
GB415	Is there a politeness distinction in 2nd person forms?	GB421	Is there a preposed complementizer in complements of verbs of thinking and/or knowing?
GB422	Is there a postposed complementizer in complements of verbs of thinking and/or knowing?	GB430	Can adnominal possession be marked by a prefix on the possessor?
GB431	Can adnominal possession be marked by a prefix on the possessed noun?	GB432	Can adnominal possession be marked by a suffix on the possessor?
GB433	Can adnominal possession be marked by a suffix on the possessed noun?	GB519	Can mood be marked by a non-inflecting word ("auxiliary particle")?
GB520	Can aspect be marked by a non-inflecting word ("auxiliary particle")?	GB521	Can tense be marked by a non-inflecting word ("auxiliary particle")?
GB522	Can the S or A argument be omitted from a pragmatically unmarked clause when the referent is inferrable from context ("pro-drop" or "null anaphora")?		
WALS (192 features)			
1A	Consonant Inventories	2A	Vowel Quality Inventories
3A	Consonant-Vowel Ratio	4A	Voicing in Plosives and Fricatives
5A	Voicing and Gaps in Plosive Systems	6A	Uvular Consonants
7A	Glottalized Consonants	8A	Lateral Consonants
9A	The Velar Nasal	10A	Vowel Nasalization
10B	Nasal Vowels in West Africa	11A	Front Rounded Vowels
12A	Syllable Structure	13A	Tone
14A	Fixed Stress Locations	15A	Weight-Sensitive Stress
16A	Weight Factors in Weight-Sensitive Stress Systems	17A	Rhythm Types
18A	Absence of Common Consonants	19A	Presence of Uncommon Consonants
20A	Fusion of Selected Inflectional Formatives	21A	Exponence of Selected Inflectional Formatives
21B	Exponence of Tense-Aspect-Mood Inflection	22A	Inflectional Synthesis of the Verb
23A	Locus of Marking in the Clause	24A	Locus of Marking in Possessive Noun Phrases
25A	Locus of Marking: Whole-language Typology	25B	Zero Marking of A and P Arguments
26A	Prefixing vs. Suffixing in Inflectional Morphology	27A	Reduplication
28A	Case Syncretism	29A	Syncretism in Verbal Person/Number Marking
30A	Number of Genders	31A	Sex-based and Non-sex-based Gender Systems
32A	Systems of Gender Assignment	33A	Coding of Nominal Plurality
34A	Occurrence of Nominal Plurality	35A	Plurality in Independent Personal Pronouns
36A	The Associative Plural	37A	Definite Articles
38A	Indefinite Articles	39A	Inclusive/Exclusive Distinction in Independent Pronouns
39B	Inclusive/Exclusive Forms in Pama-Nyungan	40A	Inclusive/Exclusive Distinction in Verbal Inflection
41A	Distance Contrasts in Demonstratives	42A	Pronominal and Adnominal Demonstratives
43A	Third Person Pronouns and Demonstratives	44A	Gender Distinctions in Independent Personal Pronouns
45A	Politeness Distinctions in Pronouns	46A	Indefinite Pronouns
47A	Intensifiers and Reflexive Pronouns	48A	Person Marking on Adpositions
49A	Number of Cases	50A	Asymmetrical Case-Marking
51A	Position of Case Affixes	52A	Comitatives and Instrumentals
53A	Ordinal Numerals	54A	Distributive Numerals
55A	Numeral Classifiers	56A	Conjunctions and Universal Quantifiers
57A	Position of Pronominal Possessive Affixes	58A	Obligatory Possessive Inflection
58B	Number of Possessive Nouns	59A	Possessive Classification
60A	Genitives, Adjectives and Relative Clauses	61A	Adjectives without Nouns
62A	Action Nominal Constructions	63A	Noun Phrase Conjunction
64A	Nominal and Verbal Conjunction	65A	Perfective/Imperfective Aspect
66A	The Past Tense	67A	The Future Tense

(continued)

ID	Feature	ID	Feature
68A	The Perfect	69A	Position of Tense-Aspect Affixes
70A	The Morphological Imperative	71A	The Prohibitive
72A	Imperative-Hortative Systems	73A	The Optative
74A	Situational Possibility	75A	Epistemic Possibility
76A	Overlap between Situational and Epistemic Modal Marking	77A	Semantic Distinctions of Evidentiality
78A	Coding of Evidentiality	79A	Suppletion According to Tense and Aspect
79B	Suppletion in Imperatives and Hortatives	80A	Verbal Number and Suppletion
81A	Order of Subject, Object and Verb	81B	Languages with two Dominant Orders of Subject, Object, and Verb
82A	Order of Subject and Verb	83A	Order of Object and Verb
84A	Order of Object, Oblique, and Verb	85A	Order of Adposition and Noun Phrase
86A	Order of Genitive and Noun	87A	Order of Adjective and Noun
88A	Order of Demonstrative and Noun	89A	Order of Numeral and Noun
90A	Order of Relative Clause and Noun	90B	Prenominal relative clauses
90C	Postnominal relative clauses	90D	Internally-headed relative clauses
90E	Correlative relative clauses	90F	Adjoined relative clauses
90G	Double-headed relative clauses	91A	Order of Degree Word and Adjective
92A	Position of Polar Question Particles	93A	Position of Interrogative Phrases in Content Questions
94A	Order of Adverbial Subordinator and Clause	95A	Relationship between the Order of Object and Verb and the Order of Adposition and Noun Phrase
96A	Relationship between the Order of Object and Verb and the Order of Relative Clause and Noun	97A	Relationship between the Order of Object and Verb and the Order of Adjective and Noun
98A	Alignment of Case Marking of Full Noun Phrases	99A	Alignment of Case Marking of Pronouns
100A	Alignment of Verbal Person Marking	101A	Expression of Pronominal Subjects
102A	Verbal Person Marking	103A	Third Person Zero of Verbal Person Marking
104A	Order of Person Markers on the Verb	105A	Ditransitive Constructions: The Verb 'Give'
106A	Reciprocal Constructions	107A	Passive Constructions
108A	Antipassive Constructions	108B	Productivity of the Antipassive Construction
109A	Applicative Constructions	109B	Other Roles of Applied Objects
110A	Periphrastic Causative Constructions	111A	Nonperiphrastic Causative Constructions
112A	Negative Morphemes	113A	Symmetric and Asymmetric Standard Negation
114A	Subtypes of Asymmetric Standard Negation	115A	Negative Indefinite Pronouns and Predicate Negation
116A	Polar Questions	117A	Predicative Possession
118A	Predicative Adjectives	119A	Nominal and Locational Predication
120A	Zero Copula for Predicate Nominals	121A	Comparative Constructions
122A	Relativization on Subjects	123A	Relativization on Obliques
124A	'Want' Complement Subjects	125A	Purpose Clauses
126A	'When' Clauses	127A	Reason Clauses
128A	Utterance Complement Clauses	129A	Hand and Arm
130A	Finger and Hand	130B	Cultural Categories of Languages with Identity of 'Finger' and 'Hand'
131A	Numeral Bases	132A	Number of Non-Derived Basic Colour Categories
133A	Number of Basic Colour Categories	134A	Green and Blue
135A	Red and Yellow	136A	M-T Pronouns
136B	M in First Person Singular	137A	N-M Pronouns
137B	M in Second Person Singular	138A	Tea
139A	Irregular Negatives in Sign Languages	140A	Question Particles in Sign Languages
141A	Writing Systems	142A	Para-Linguistic Usages of Clicks
143A	Order of Negative Morpheme and Verb	143B	Obligatory Double Negation
143C	Optional Double Negation	143D	Optional Triple Negation
143E	Preverbal Negative Morphemes	143F	Postverbal Negative Morphemes
143G	Minor morphological means of signaling negation	144A	Position of Negative Word With Respect to Subject, Object, and Verb
144B	Position of negative words relative to beginning and end of clause and with respect to adjacency to verb	144C	Languages with different word order in negative clauses
144D	The Position of Negative Morphemes in SVO Languages	144E	Multiple Negative Constructions in SVO Languages
144F	Obligatory Double Negation in SVO languages	144G	Optional Double Negation in SVO languages
144H	NegSVO Order	144I	SNegVO Order
144J	SVNegO Order	144K	SVONeg Order

(continued)

ID	Feature	ID	Feature
144L	The Position of Negative Morphemes in SOV Languages	144M	Multiple Negative Constructions in SOV Languages
144N	Obligatory Double Negation in SOV languages	144O	Optional Double Negation in SOV languages
144P	NegSOV Order	144Q	SNegOV Order
144R	SONegV Order	144S	SOVNeg Order
144T	The Position of Negative Morphemes in Verb-Initial Languages	144U	Double negation in verb-initial languages
144V	Verb-Initial with Preverbal Negative	144W	Verb-Initial with Negative that is Immediately Postverbal or between Subject and Object
144X	Verb-Initial with Clause-Final Negative	144Y	The Position of Negative Morphemes in Object-Initial Languages

B Ablations

Table 8: Feature-source comparison under identical per-source tuning, from Experiment E1. The LOLO ordering is preserved on the pure-unseen-language metric, so the Grambank-only advantage is not overfitting. The LOLO columns use each source’s production configuration; the unseen-language column uses the per-source sweep winner. WALS runs at $n=22$; Grambank and Grambank+WALS run at $n=24$.

Feature source	#feat	LOLO ρ	LOLO R^2	unseen-lang ρ
Grambank (GB)	195	0.780	0.607	0.494
WALS	192	0.648	0.412	0.307
Grambank+WALS (operational)	387	0.705	0.492	0.405

Shared-language source comparison Table 8 compares Grambank at $n=24$ with WALS at $n=22$, so its rows rest on different language sets. Table 9 removes this caveat: all three sources are refit on the 22 languages that the WALS mapping covers, each after its own `max_features` mini-sweep, on identical LOLO folds. The ordering Grambank > Grambank+WALS > WALS is preserved, at $\rho=0.716$, 0.673 and 0.648. The Grambank advantage therefore does not depend on the language set. The production `max_features=0.5`, tuned at $n=24$, drops to 0.576 on the shared set. Removing two languages removes 90 directed pairs, from 552 down to 462, so a configuration tuned on the larger set no longer suits the smaller training problem. This is why each source carries its own sweep on its own language set.

Table 9: Feature-source comparison on the 22 languages shared with WALS (Experiment E1), each source after its own `max_features` mini-sweep on identical LOLO folds. The order of Table 8 is preserved on identical languages.

Feature source	best <code>max_features</code>	LOLO ρ	R^2
Grambank	0.3	0.716	0.511
Grambank+WALS	sqrt	0.673	0.447
WALS	log2	0.648	0.412

WALS-block permutation control Tables 8 and 9 show the union trailing Grambank under matched tuning. The permutation control asks whether that drop is generic column dilution at $n=24$, or a property of the real WALS data. The WALS block of the feature matrix is permuted across the 24 languages, so each language receives another language’s real WALS profile. This destroys the feature-to-language association, while every feature’s marginal levels and missingness are preserved. Each permuted design is rerun under the same seven-value `max_features` mini-sweep on the production LOLO folds. Scrambling the WALS block recovers most of the union’s drop: the per-design best configuration averages $\rho=0.751$ with standard deviation 0.011 over ten permutations, and all ten score above the real union’s 0.705, against Grambank’s 0.780 (Table 10). The union’s drop therefore decomposes into roughly 0.03 of generic dilution, which any matched block of 192

extra columns causes, and roughly 0.05 that is specific to the real WALs structure. The forest fits WALs-to-BTS associations within the training folds that do not transfer to the held-out language. The WALs features are not noise in isolation, since WALs alone reaches $\rho=0.648$, but combined with Grambank at $n=24$ they subtract held-out signal rather than adding it.

Table 10: WALs-block permutation control (Experiment E1) under identical LOLO folds and a per-design `max_features` mini-sweep. The scrambled rows permute the WALs block across the 24 languages, preserving marginal levels and missingness; the mean and standard deviation are over ten permutations, every one of which scores above the real union.

Feature design	#feat	LOLO ρ	R^2
Grambank	195	0.780	0.607
Grambank+WALs, real block	387	0.705	0.492
Grambank+WALs, block scrambled (10 perms)	387	0.751 ± 0.011	0.561 ± 0.016

Coverage-floor sweep The 0.7 Grambank coverage threshold defines ATLAS-24, so Table 11 refits every tier as the floor is lowered stepwise to zero. Each step admits exactly one further ATLAS language: Telugu at floor 0.60, Thai at 0.50, Indonesian at 0.40, and Central Kurdish at 0.00. Each admitted language is not one training example but $2(n-1)$ of them, since every ordered pair with an existing language becomes a directed training pair. The corpus therefore grows quadratically, from 552 pairs at $n=24$ to 756 at $n=28$. Moderately lowering the floor raises the tuned RF from $R^2=0.49$ at $n=24$ to 0.68 at $n=26$ and $n=27$. The untuned RF rises with it, collapsing the tuning gap from 0.14 to at most 0.04. The added languages relieve the overfitting that separates the untuned from the tuned forest. Removing the floor entirely reverses the gain. The near-empty Central Kurdish profile, with Grambank coverage 0.08, drops the untuned RF to $R^2=0.20$ and the tuned RF to 0.48. The GLM stays at chance across the entire sweep, so the RF movement tracks the separability of one-hot feature profiles rather than a stronger smooth typological signal. The pure-unseen-language protocol, whose test pairs share no language with training, shows that the moderate floors also improve generalization. Unseen-language ρ rises from 0.405 at floor 0.70 to 0.508 at 0.50 and 0.514 at 0.40, nearly doubling R^2 from 0.136 to 0.264. Adequately attested extra languages therefore improve prediction of languages the model has never seen, not just the LOLO score. At floor 0.00 the same protocol collapses to $\rho=-0.012$ with $R^2=-0.20$, below the mean predictor. The near-empty profile does not merely add noise, it breaks extrapolation entirely. A one-language change can also move the RF substantially. As throughout, at $n=24$ every language appears in training through other pairs, so the tuned column reads as threshold sensitivity, while the unseen-language column isolates the floor’s role: excluding profiles too sparse to extrapolate from.

Table 11: Coverage-floor sweep of the 0.7 Grambank threshold that defines ATLAS-24. Every tier is refit at each floor under the production configuration, and each lowering admits the listed language, reaching all 28 ATLAS languages with a Grambank profile at floor 0.00. The remaining ten of the 38 ATLAS languages, among them Spanish and German, are absent from Grambank and cannot enter at any floor. R^2 is LOLO true R^2 ; the final two columns are the tuned RF’s LOLO ρ and pure-unseen-language ρ , whose ATLAS-24 values are the headline 0.705 and 0.405.

Floor	n	language added	glm R^2	full R^2	tuned R^2	tuned ρ	unseen-lang ρ
0.70	24	—	0.014	0.350	0.492	0.705	0.405
0.60	25	Telugu	0.003	0.507	0.529	0.731	0.411
0.50	26	Thai	-0.009	0.658	0.680	0.824	0.508
0.40	27	Indonesian	0.001	0.642	0.676	0.823	0.514
0.00	28	Central Kurdish	0.033	0.205	0.476	0.700	-0.012

Matched-capacity control details The metadata RF in Table 12 one-hot encodes, per language, the writing script with 9 levels, the WALs family, the WALs genus, a k -means geographic region from lat/lon with 6 clusters, and a Wikipedia article-count bin with 4 quantiles. Missing values receive an explicit unknown level, so the metadata model is informed of the same missingness the typology model is spared. This choice is biased in favor of metadata, which is the conservative direction for the

Table 12: Matched-capacity and matched-tuning controls from Experiment E1. A matched-capacity non-typological RF recovers $\rho \approx 0.58$ at the shared configuration and 0.620 under its own hyperparameter sweep, well above the single-feature ridges. Typology’s full-capacity increment is $\Delta\rho=0.085$ under matched tuning and disappears at a matched five-feature budget, 0.597 against 0.620, which locates the advantage in feature breadth.

Model (same RF, same folds)	#feat	LOLO ρ	R^2
metadata RF (script/family/genus/geo/wiki)	5	0.581	0.264
metadata RF, own-sweep tuned	5	0.620	0.375
typology RF (Grambank+WALS)	387	0.705	0.492
typology RF, budget-matched to metadata	5	0.597	–

comparison. The budget-matched typology row averages LOLO ρ over 20 random 5-feature subsets drawn from the top informative features under a fixed seed. Code and per-experiment `_meta.json` records, holding the resolved config and git commit, accompany each result CSV.

Matched-tuning control details The production metadata control inherits `max_features=0.5` from the typology winner, which is conservative for metadata. We therefore swept the metadata RF over the same curated grid as the typology model. We screened all 168 configurations under LOLO at 200 trees and seed 42, and refined the top eight over seeds 42 to 46. The winner by true R^2 uses `max_features_sqrt` with `max_depth 10`, reaching LOLO $\rho=0.620$ and $R^2=0.375$ at seed 42, and $\rho=0.602\pm0.011$ over the five refinement seeds. Leave-2-languages-out gives 0.621 for the winner and 0.611 for the production configuration, against 0.702 for typology. The typology increment is therefore stable across seeds, configurations and holdout protocols, rather than an artifact of unequal tuning. A paired cluster bootstrap over source languages does not, however, separate the two models at $n=24$: $\Delta\rho=0.085$ at 95% CI $[-0.11, 0.41]$, whose width reflects coarse language-level resampling at this scale.

Digitization-noise robustness The target matrix is read from Figure C.2 at one decimal, so every BTS cell carries a rounding error of at most 0.05. We perturbed each of the 552 targets with independent $U(-0.05, 0.05)$ noise and reran the full tuned-RF LOLO on each noisy target, with the forest seed fixed so that only the labels vary. Across $B=100$ replicates, LOLO ρ averages 0.705 with standard deviation 0.007 and worst case 0.688. R^2 averages 0.492 with standard deviation 0.011. The main reported correlation is therefore insensitive to digitization error at the reading precision.




Figure 1: Label-permutation null versus observed LOLO scores for the tuned random forest on Grambank+WALS features (ATLAS-24, $B=200$ replicates, seed 42). Left: Pearson ρ ; right: R^2 . Bars show the fold-respecting permutation null, the dashed line its mean, and the solid line the observed score. The observed ρ exceeds all 200 null replicates ($p=0.005$).

Table 13: Symmetric distance regressions on the 24×24 upper triangle, the cross-check within Experiment E3. Script is a strong marginal correlate but provides no incremental directed power, since the script-only directed model is near chance.

Factor	Mantel r	Mantel p	MRM coef	MRM p
typological	0.266	0.015	0.249	0.281
script	0.334	0.017	0.149	0.035
genealogical	0.226	0.051	0.098	0.693
geographic	0.169	0.078	0.029	0.803

Composition-matched grouped holdout (E3) Macro- ρ under LOSO and LOFO averages held-out sets that are dominated by cross-script pairs, where every tier is stronger, so the pooled LOLO value of 0.705 is not the right baseline for them. Table 14 scores pooled LOLO predictions on exactly the pairs each group contributes. Grouped holdout exceeds this matched baseline on the macro average for both axes, and matches it under pair weighting. Individual groups move in both directions. The Arabic script dips to $\rho=0.459$ against 0.683 matched, and Latin to 0.597 against 0.692, while the single-language script groups improve markedly: Greek at 0.935 against 0.572, and Hebrew at 0.914 against 0.550. For a single-language group the grouped fold is that language’s own LOLO fold, so its gain over the matched column reflects the mixed fold provenance of pooled predictions rather than a training difference. No group approaches the script-only model at $\rho=0.138$, so the dips are attenuations, not a collapse.

Table 14: Composition-matched control for the grouped holdouts of Experiment E3. Grouped ρ retrains with every pair touching the group held out; matched LOLO scores the pooled LOLO predictions on exactly that group’s held-out pairs. Macro rows are unweighted means over groups; weighted rows average by held-out pair count.

Axis	Group	grouped ρ	matched LOLO ρ
LOSO	Arabic	0.459	0.683
LOSO	Cyrillic	0.935	0.749
LOSO	Devanagari	0.912	0.622
LOSO	Greek	0.935	0.572
LOSO	Han	0.730	0.819
LOSO	Hangul	0.793	0.643
LOSO	Hebrew	0.914	0.550
LOSO	Japanese	0.708	0.676
LOSO	Latin	0.597	0.692
LOSO	macro	0.776	0.667
LOSO	weighted	0.679	0.683
LOFO	Afro-Asiatic	0.900	0.718
LOFO	Altaic	0.838	0.676
LOFO	Austro-Asiatic	0.243	0.267
LOFO	Austronesian	0.892	0.801
LOFO	Indo-European	0.693	0.723
LOFO	Japanese	0.708	0.676
LOFO	Korean	0.793	0.643
LOFO	Niger-Congo	0.760	0.715
LOFO	Sino-Tibetan	0.730	0.819
LOFO	macro	0.729	0.671
LOFO	weighted	0.721	0.697

Leak-free top- k control (E4) The sweep’s global feature ranking is scored on the same LOLO folds that are used for evaluation, so its $k < 387$ entries are optimistically biased. In the control, fold i selects its own top- k by mean importance over the other folds only, so the held-out language touches neither the fit nor the ranking. The $k=200$ value falls from 0.742 to 0.710. Across three seeds, the full model scores $\rho = 0.708 \pm 0.004$, while leak-free $k=200$ scores 0.720 ± 0.016 , so the residual

gap is within seed noise. Per-fold selection also beats the global ranking at mid-range k , for example 0.716 versus 0.627 at $k=100$, yet it still never significantly beats the full 387-feature model.

Inferential statistics. Table 15 collects the permutation and bootstrap statistics behind the main results of E1, E3, E4, and E5.

Table 15: Inferential statistics, with each row labeled by the experiment and research question it addresses. The permutation null uses $B=200$, and the cluster and paired bootstraps use $B=2000$. The final row’s interval is the permuted-label null’s central 95% range, not a bootstrap interval.

Exp.	RQ	Quantity	Estimate	95% CI
E1	RQ1	LOLO ρ ; permutation $p=0.005$	0.705	[0.51, 0.82]
E1	RQ1	LOLO ρ ; language-level bootstrap 95% CI	0.705	[0.50, 0.85]
E1	RQ1	pure-unseen-language ρ (Grambank+WALS)	0.405	—
E3	RQ1	LOSO / LOFO macro- ρ	0.776 / 0.729	[0.67, 0.88] / [0.59, 0.83]
E4	RQ1	top-25 importance Jaccard (random ≈ 0.033)	0.073	[0.069, 0.078]
E5	RQ2	residual gap, Marathi–English (bootstrap over targets); $p<0.001$	+0.236	[0.19, 0.28]
E5	RQ2	residual margin; null $p=0.005$	0.246	[0.065, 0.173]

Residual-ranking validity controls Two controls ask whether the E5 residual flip is meaningful, or whether the operationalization produces decisive-looking rankings from nothing. The first removes the in-sample optimism of the bias layer, which explains $R^2=0.12$ in-sample but -0.006 out-of-fold under the LOLO folds. Refitting $\hat{B}$ out-of-fold and recomputing the ranking, both as the raw mean residual and through the production rf_T , leaves the flip intact: Marathi remains first at 0.36, English remains at rank 9 or 10, and both rankings correlate with the production ranking at Spearman 0.99. The flip is therefore carried by the nuisance association itself, which replicates across folds at out-of-fold Pearson 0.16, rather than by the layer’s in-sample optimism. The second control runs the entire operationalization on permuted BTS labels, refitting the bias ridge, the residual, the random forest, and the ranking per replicate. This quantifies the rankings the pipeline produces from meaningless labels. The null margin of the top source over the median source averages 0.116 with interval [0.065, 0.173] over $B=200$ replicates, and no replicate reached the observed 0.246, so the ranking’s sharpness exceeds the null at $p=0.005$. The top-source gap over English specifically is weaker evidence: 11 of 200 null replicates exceed the observed rf_T gap of 0.237 at $p=0.055$, because a random draw can seat English at the bottom of a null ranking. The residual ranking is thus sharper than what the operationalization produces on meaningless labels and stable under honest bias estimation. The identity of the top source is however weakly determined: the 200 permuted reruns place 24 different languages at rank one. E5 therefore reports the flip as a diagnostic rather than a recommendation.

Additional distance baselines We compare the typology random forest against five further distance baselines drawn from the transfer and tokenization literature [7, 11]. The lang2vec baseline scores each pair by the cosine of the concatenated imputed featural vectors of [7], covering syntax, phonology and inventory. The URIEL baseline feeds the six canonical distances of the same knowledge base, namely genetic, geographic, syntactic, phonological, inventory and their featural aggregate, as a six-column design to the same within-fold ridge as the metadata baselines. The geographic distance is the great-circle distance on Glottolog coordinates, because the lang2vec geographic feature is a vector of distances to fixed reference points rather than per-language coordinates. Three corpus-lexical baselines measure the Jaccard overlap between per-language artifacts of Wikipedia lead-paragraph corpora of 2,000 random articles per edition. These are byte-level BPE vocabularies of 8,000 entries trained per language following [13], pooled character one-to-three-gram sets over the 5,000 most frequent word types in the tradition of [2], and the 10,000 most frequent word types. The last two follow the tokenizer analysis of [11]. Table 16 scores all five under the protocol of the main text; every tier covers all 24 languages. All five sit at or below a true R^2 of 0.044. The character n -gram and subword-tokenizer overlaps lead at ρ of 0.225 and 0.222, followed by the lang2vec cosine at 0.148, the word-vocabulary overlap at 0.142, and the URIEL ridge at 0.095, which is at chance. The typology random forest explains 0.49 of held-out variance, eleven times the best distance baseline. The script-adjacent lexical overlaps outscore the typological-distance baselines, which matches the

symmetric analysis, where script is the strongest marginal correlate of transfer. None of the five approaches the full typological feature set.

Table 16: Additional distance baselines under the leave-one-language-out protocol of Table 1, on ATLAS-24. Every tier covers all 24 languages. The reference row repeats the tuned typology random forest from the main text.

Baseline	LOLO ρ	true R^2
character n -gram overlap	0.225	0.044
subword tokenizer overlap	0.222	0.044
lang2vec featural cosine	0.148	0.012
word vocabulary overlap	0.142	0.010
URIEL six-distance ridge	0.095	−0.019
tuned RF (typology, reference)	0.705	0.492

C Transfer matrices

This section visualizes the transfer matrices behind the ATLAS-24 evaluation. Every panel is a 38×38 heatmap on the axis order of the digitized ATLAS Figure C.2. The cell in row i , column j is the bilingual transfer score (BTS) for transferring from the column language, the source, to the row language, the target. The diagonal, self-transfer, is undefined, and the 14 ATLAS languages without Grambank coverage of at least 0.70 are masked in grey. Axis labels are colored by language family, at the granularity of the original figure’s legend. All BTS panels, ground truth and four model tiers, share one diverging color scale spanning the ground-truth range $[-1.60, 0.50]$ BTS. Its neutral point is the midpoint of that range, not zero. Model panels show leave-one-language-out predictions. Each cell is produced by a training fold that excludes all pairs involving one of the cell’s two languages, so no cell is an in-sample fit. The difference panels share one symmetric scale of ± 1.35 BTS. Red means the model underpredicts the ground truth, blue means it overpredicts.




Figure 2: Digitized ATLAS-38 ground-truth transfer matrix (Figure C.2 of the ATLAS paper). This axis order, family coloring, and BTS color scale are shared by all model and difference panels in this section.




Figure 3: LOLO predictions of the similarity tier (ridge on typological similarity alone). Held-out Pearson $\rho = 0.037$, MAE = 0.277 BTS.




Figure 4: LOLO predictions of the GLM tier (ridge on similarity, script, genealogical, and geographic distances). Held-out Pearson $\rho = 0.162$, MAE = 0.277 BTS.




Figure 5: LOLO predictions of the full random forest (all typological features, default hyperparameters). Held-out Pearson $\rho = 0.615$, MAE = 0.203 BTS.




Figure 6: LOLO predictions of the tuned random forest (the production model of the main experiments; max_features = 0.5). Held-out Pearson $\rho = 0.705$, MAE = 0.185 BTS – this is the $\rho = 0.705$ of the main ATLAS-24 result.




Figure 7: Ground truth minus the LOLO predictions of the similarity tier, on the shared symmetric difference scale. MAE 0.277 BTS.




Figure 8: Ground truth minus the LOLO predictions of the GLM tier. MAE 0.277 BTS.




Figure 9: Ground truth minus the LOLO predictions of the full random forest. MAE 0.203 BTS.




Figure 10: Ground truth minus the LOLO predictions of the tuned random forest. MAE 0.185 BTS. Note the shrinkage of the error relative to the weaker tiers: held-out error concentrates near the scale’s neutral midpoint.

D Additional results

Table 17: Terms of the bias layer $\hat{B}$, the ridge fit of BTS on five non-typological nuisance descriptors over the 552 ATLAS-24 directed pairs. Weights are on the standardized feature scale, and the mean absolute contribution is each feature’s contribution to $\hat{B}$ averaged over pairs. The layer explains $R^2=0.12$ of BTS in-sample at correlation 0.35, but approximately zero under leave-one-language-out cross-validation. Its weights are therefore descriptive of ATLAS-24, not a stable law. Its mean equals the BTS mean of -0.31 , so the residual $T = \text{BTS} - \hat{B}$ is mean-zero. The source-resource and script terms dominate, while the target-resource term is negligible, so the bias is driven by source-side resource and script sharing.

Nuisance descriptor	std. weight	mean contribution (BTS)
source resource (log)	+0.087	0.070
script difference	−0.077	0.071
genealogical distance	−0.034	0.027
geographic distance	−0.018	0.016
target resource (log)	+0.002	0.002

Table 18: Exhaustive feature-subset ablation of the ATLAS-24 bias layer B , grouped by subset size k . Each row refits B on that subset of the five nuisance descriptors and propagates to the debias residual $T = \text{BTS} - B$. Abbreviations: scr=script difference, gene=genealogical distance, geo=geographic distance, $\text{res}_s/\text{res}_t = \log 1p$ Wikipedia resource of source/target. $R^2(B, y)$ is the bias-explained variance of BTS, and $\|\Delta T\|$ is the relative shift of T from the full-five residual. LOLO ρ is the leave-one-language-out Pearson of the debiased BTS predictor, an RF on T with the bias B added back. The production biased baseline is $\rho = 0.705$, and the no-bias-layer row refits within this pipeline, landing at 0.701. Rank ρ is the Spearman correlation of the per-source pretraining ranking against the full-model ranking and against empirical BTS ground truth. The top source is English under every configuration; $\neq$ marks a flip, and none is observed.

Bias features	$R^2(B, y)$	$\ \Delta T\ $ (%)	LOLO ρ	rank ρ (full)	rank ρ (truth)	top
<i>k = 1 (1 feature)</i>						
geo	0.013	34.8	0.719	0.989	0.984	English
res_s	0.060	26.0	0.718	0.990	0.987	English
scr	0.051	28.0	0.717	0.979	0.984	English
gene	0.023	33.1	0.712	0.992	0.988	English
res_t	0.000	36.8	0.705	0.989	0.990	English
<i>k = 2 (2 features)</i>						
scr, res_s	0.106	12.7	0.748	0.989	0.987	English
scr, gene	0.066	24.8	0.742	0.978	0.982	English
scr, geo	0.063	25.3	0.734	0.978	0.974	English
gene, res_s	0.079	21.4	0.729	0.983	0.977	English
gene, res_t	0.023	33.1	0.723	0.993	0.992	English
scr, res_t	0.051	28.0	0.722	0.983	0.984	English
gene, geo	0.025	32.7	0.720	0.993	0.990	English
geo, res_t	0.013	34.8	0.717	0.994	0.988	English
geo, res_s	0.068	24.2	0.713	0.987	0.982	English
res_s , res_t	0.061	25.9	0.704	0.995	0.990	English
<i>k = 3 (3 features)</i>						
scr, gene, res_s	0.118	4.5	0.750	1.000	0.995	English
scr, res_s , res_t	0.106	12.6	0.746	0.995	0.993	English
scr, geo, res_t	0.063	25.3	0.740	0.987	0.979	English
scr, geo, res_s	0.114	8.1	0.738	0.995	0.993	English
scr, gene, res_t	0.066	24.8	0.734	0.989	0.989	English
scr, gene, geo	0.069	23.9	0.733	0.990	0.984	English
gene, geo, res_s	0.080	21.3	0.729	0.984	0.978	English
gene, res_s , res_t	0.080	21.4	0.727	0.985	0.982	English
geo, res_s , res_t	0.069	24.1	0.719	0.990	0.984	English
gene, geo, res_t	0.025	32.7	0.714	0.996	0.995	English
<i>k = 4 (4 features)</i>						
scr, gene, res_s , res_t	0.118	4.4	0.760	0.999	0.994	English
scr, geo, res_s , res_t	0.114	8.1	0.757	0.998	0.994	English
scr, gene, geo, res_s	0.120	0.5	0.756	0.997	0.995	English
scr, gene, geo, res_t	0.069	23.9	0.733	0.987	0.986	English
gene, geo, res_s , res_t	0.080	21.2	0.723	0.991	0.985	English
<i>k = 5 (5 features)</i>						
scr, gene, geo, res_s, res_t	0.120	0.0	0.747	1.000	0.995	English
<i>none (no bias layer)</i>	0.000	36.8	0.701	0.994	0.993	English

Table 19: Full 24-language ranking of the ATLAS-24 candidate set under each operationalization of Experiment E5. The candidate set is used as both sources and targets. The columns are the empirical raw-BTS mean, the debiased residual $T = \text{BTS} - \hat{B}$, the mean typological similarity to the targets, and the OOD-generalizer mean BTS to cross-family targets. Scores are on each column’s own scale and are not comparable across columns; only the within-column order is meaningful. The on-scale reweighted random forest of Table 4 is omitted here because its full 24-language ranking tracks the empirical one at Spearman 0.974, so its top sources are summarized in the main text only. The bold top row shows that the four methods disagree on the best source, which is the RQ2 result.

Rank	empirical		debiased		centrality		OOD-generalizer	
	source	score	source	score	source	score	source	score
1	English	0.022	Marathi	0.361	Ukrainian	0.717	English	-0.011
2	Modern Hebrew	-0.074	Filipino	0.355	Portuguese	0.700	Modern Hebrew	-0.065
3	French	-0.109	Modern Hebrew	0.328	Serbian-Croatian-Bosnian	0.679	Filipino	-0.114
4	Filipino	-0.113	Swahili	0.235	Catalan	0.678	Vietnamese	-0.114
5	Standard Arabic	-0.113	Standard Arabic	0.198	Italian	0.677	Standard Arabic	-0.120
6	Portuguese	-0.113	Western Farsi	0.187	Southern Pashto	0.673	Western Farsi	-0.122
7	Marathi	-0.113	Modern Greek	0.180	Swedish	0.662	Turkish	-0.124
8	Western Farsi	-0.113	Turkish	0.152	English	0.661	Marathi	-0.144
9	Vietnamese	-0.122	Standard Malay	0.152	Modern Greek	0.659	French	-0.144
10	Catalan	-0.122	Vietnamese	0.136	Welsh	0.659	Portuguese	-0.156
11	Turkish	-0.130	English	0.125	French	0.654	Catalan	-0.167
12	Italian	-0.170	Catalan	0.115	Filipino	0.654	Standard Malay	-0.171
13	Standard Malay	-0.174	Serbian-Croatian-Bosnian	0.115	Standard Malay	0.653	Swahili	-0.181
14	Swahili	-0.183	Portuguese	0.102	Russian	0.647	Modern Greek	-0.211
15	Serbian-Croatian-Bosnian	-0.200	French	0.057	Modern Hebrew	0.647	Italian	-0.233
16	Swedish	-0.204	Ukrainian	0.051	Standard Arabic	0.642	Swedish	-0.233
17	Modern Greek	-0.217	Russian	0.041	Western Farsi	0.623	Serbian-Croatian-Bosnian	-0.233
18	Russian	-0.217	Italian	0.022	Marathi	0.613	Russian	-0.267
19	Ukrainian	-0.230	Swedish	-0.036	Turkish	0.611	Ukrainian	-0.278
20	Korean	-0.752	Korean	-0.384	Mandarin Chinese	0.604	Welsh	-0.744
21	Japanese	-0.848	Japanese	-0.505	Korean	0.590	Korean	-0.776
22	Welsh	-0.883	Welsh	-0.589	Japanese	0.579	Japanese	-0.852
23	Mandarin Chinese	-1.087	Southern Pashto	-0.650	Swahili	0.575	Mandarin Chinese	-1.110
24	Southern Pashto	-1.217	Mandarin Chinese	-0.736	Vietnamese	0.573	Southern Pashto	-1.209

Table 20: Full 24-language ranking of the ATLAS-24 candidate set by positive-transfer coverage: the number of target languages with a positive transfer score. The columns are the empirical raw BTS out of 23 targets, the bias-removed residual $T = \text{BTS} - \hat{B}$ out of 23 targets, and the OOD-generalizer raw BTS to cross-family targets, out of that source’s cross-family target count. Count ties are broken by the corresponding mean score in Table 19. Counts are not comparable across columns; only the within-column order is meaningful.

Rank	empirical		bias-removed		OOD-generalizer	
	source	count	source	count	source	count
1	English	8/23	Marathi	23/23	Modern Hebrew	3/20
2	French	5/23	Filipino	23/23	English	2/9
3	Modern Hebrew	3/23	Modern Hebrew	23/23	French	1/9
4	Portuguese	3/23	Standard Arabic	23/23	Modern Greek	1/9
5	Catalan	3/23	Western Farsi	23/23	Filipino	0/22
6	Modern Greek	2/23	Modern Greek	23/23	Vietnamese	0/21
7	Standard Arabic	1/23	Standard Malay	22/23	Standard Arabic	0/20
8	Italian	1/23	Swahili	21/23	Western Farsi	0/9
9	Swedish	1/23	Turkish	21/23	Turkish	0/21
10	Russian	1/23	Vietnamese	21/23	Marathi	0/9
11	Ukrainian	1/23	English	20/23	Portuguese	0/9
12	Filipino	0/23	Catalan	20/23	Catalan	0/9
13	Marathi	0/23	Serbian-Croatian-Bosnian	20/23	Standard Malay	0/21
14	Western Farsi	0/23	Portuguese	19/23	Swahili	0/21
15	Vietnamese	0/23	Ukrainian	17/23	Italian	0/9
16	Turkish	0/23	Russian	16/23	Serbian-Croatian-Bosnian	0/9
17	Standard Malay	0/23	French	15/23	Swedish	0/9
18	Swahili	0/23	Italian	14/23	Russian	0/9
19	Serbian-Croatian-Bosnian	0/23	Swedish	8/23	Ukrainian	0/9
20	Korean	0/23	Korean	0/23	Welsh	0/9
21	Japanese	0/23	Japanese	0/23	Korean	0/21
22	Welsh	0/23	Welsh	0/23	Japanese	0/21
23	Mandarin Chinese	0/23	Southern Pashto	0/23	Mandarin Chinese	0/21
24	Southern Pashto	0/23	Mandarin Chinese	0/23	Southern Pashto	0/22

Table 21: Full 24-language ranking of the ATLAS-24 candidate set by best-source coverage: the number of target languages for which the source attains the highest transfer score. The columns are the empirical raw BTS, the bias-removed residual $T = \text{BTS} - \hat{B}$, and the raw BTS restricted to cross-family sources, the best outside-family option per target. A tie at a target’s maximum counts for every co-best source, so column counts sum to more than 24: empirically, 11 of 24 targets have tied maxima, up to 9-way. Count ties between sources are broken by the corresponding mean score in Table 19. Only the within-column order is meaningful.

Rank	empirical		bias-removed		OOD-generalizer	
	source	count	source	count	source	count
1	English	14/24	Marathi	10/24	Modern Hebrew	14/24
2	Modern Hebrew	6/24	Filipino	8/24	Swahili	10/24
3	Western Farsi	5/24	Modern Hebrew	6/24	English	9/24
4	French	4/24	Swahili	0/24	Vietnamese	9/24
5	Filipino	4/24	Standard Arabic	0/24	Standard Arabic	9/24
6	Marathi	4/24	Western Farsi	0/24	Turkish	8/24
7	Portuguese	4/24	Modern Greek	0/24	Western Farsi	4/24
8	Swahili	4/24	Turkish	0/24	Marathi	3/24
9	Vietnamese	3/24	Standard Malay	0/24	Standard Malay	2/24
10	Standard Arabic	2/24	Vietnamese	0/24	French	1/24
11	Catalan	2/24	English	0/24	Portuguese	1/24
12	Turkish	2/24	Catalan	0/24	Catalan	1/24
13	Italian	1/24	Serbian-Croatian-Bosnian	0/24	Modern Greek	1/24
14	Swedish	1/24	Portuguese	0/24	Swedish	1/24
15	Modern Greek	1/24	French	0/24	Filipino	0/24
16	Russian	1/24	Ukrainian	0/24	Italian	0/24
17	Ukrainian	1/24	Russian	0/24	Serbian-Croatian-Bosnian	0/24
18	Standard Malay	0/24	Italian	0/24	Russian	0/24
19	Serbian-Croatian-Bosnian	0/24	Swedish	0/24	Ukrainian	0/24
20	Korean	0/24	Korean	0/24	Welsh	0/24
21	Japanese	0/24	Japanese	0/24	Korean	0/24
22	Welsh	0/24	Welsh	0/24	Japanese	0/24
23	Mandarin Chinese	0/24	Southern Pashto	0/24	Mandarin Chinese	0/24
24	Southern Pashto	0/24	Mandarin Chinese	0/24	Southern Pashto	0/24

Residual debiasing detail The bias layer explains $R^2=0.12$ of BTS in-sample but roughly zero under LOLO, which is why its weights describe ATLAS-24 rather than a stable law.