

PointZero: 3D Point Track Completion for Learning Transferable 3D Dynamics

Bardienus P. Duisterhof
CMU

Kaifeng Zhang*
Columbia

Adam Hung*
CMU

Bowen Wen
NVIDIA

Stan Birchfield
NVIDIA

Yunzhu Li
Columbia

Deva Ramanan
CMU

Jeffrey Ichnowski
CMU

pointzero-wm.github.io




Figure 1: PointZero proposes *3D point track completion* as a pre-training objective for learning rich 3D dynamics priors. Given one RGB-D image and one or a few point trajectories (shown in orange), PointZero predicts the future 3D tracks of all observed scene points. PointZero is a robot-free pre-training objective for instilling 3D dynamics understanding in world models. Post-trained for dynamics modeling [1] and robot manipulation [2], it outperforms *application-specific* baselines.

Abstract

World models endow perceptual systems with the ability to predict how scenes evolve under interaction. They are most beneficial when trained on diverse volumes of data, to instill a rich prior into downstream applications. Existing methods typically require robot action labels to learn action-conditioned 3D dynamics, which excludes web video data from the training pool. We study *3D point track completion* as a pre-training objective for learning transferable 3D dynamics without robot data. Given a single RGB-D observation and sparse partial 3D trajectories (tracks), we predict future 3D tracks of all observed points. We show this objective produces a rich 3D dynamics prior, without requiring robot action labels. We contribute a diverse dataset of 2.9 million synthetic frames spanning deformable, articulated, and rigid objects, and use it to train PointZero. We show that a flexible and expressive transformer, PointZero, outperforms prior methods on the same data. We demonstrate the utility of our pre-training objective by post-training PointZero for two downstream applications: (1) action-conditioned 3D dynamics prediction and (2) imitation learning. When fine-tuned to condition on end-effector pose, PointZero outperforms the baselines on the recent PGND 3D dynamics benchmark. When fine-tuned to predict robot actions and 3D tracks, PointZero outperforms or matches the baselines on 6/7 simulated and real-world robot manipulation tasks. We furthermore evaluate training PointZero from scratch to isolate the benefits of our proposed architecture from those of our proposed pre-training objective and dataset. We release the dataset, checkpoints, and full training recipe.

*Equal contribution.

1 Introduction

Humans intuitively anticipate how the world responds to interaction: pulling a drawer, folding a sock, or sliding a cup. Endowing perception systems with comparable predictive abilities promises to unlock applications across robotics, simulation, and AR/VR/XR.

Challenges. Learning a generic 3D dynamics model is inherently challenging due to the vast *diversity* of physical phenomena, the *underobservability* of many aspects of physics, and the difficulty of characterizing the space of all possible *interactions*. Despite such challenges, humans readily interact with articulated, rigid, and deformable objects, and can predict plausible dynamics “zero-shot” before interacting with a particular object of interest. Prior methods learn robot-action-conditioned 3D dynamics models by fitting a separate model per scene from hundreds of interactions with the target object [1, 3]. Even hundreds of interactions may be insufficient to learn complex dynamics from scratch, motivating pre-training objectives that provide transferable priors over 3D scene dynamics.

Pre-training. Large-scale pre-training on video data has led to dramatic improvements in data efficiency and generalization capabilities of robot learning systems [4, 5]. However, most such approaches pre-train 2D visual representations or video prediction models, which cannot explicitly represent metric 3D scene motion.

Recent 3D world models have begun scaling dynamics prediction in 3D, but rely on robot interaction data with action labels [6]. Requiring robot action labels makes data collection considerably more expensive and excludes the vast amount of available web video. This raises the question, *can we learn 3D dynamics priors without action annotations?*

3D Point Track Completion. We propose 3D point track completion as a robot-free training objective for learning transferable 3D dynamics. Given a single RGB-D observation and 3D point trajectories for a few sparse points, we predict the 3D point tracks of all observed points. Three properties make the objective scalable. *Robot-free supervision:* The labels and conditioning features are both just 3D point tracks, available from simulation and in principle from any video via point tracking [7, 8]. No robot- or embodiment-specific annotations are needed. *Task-agnostic supervision:* As with other dynamics-modeling objectives, training examples need not correspond to successful task completions. Arbitrary play data or free-form interactions with objects can all provide useful supervision. *Flexible representation:* 3D point tracks can represent arbitrary objects, including those with high-dimensional state such as cloth.

Post-training. We study the utility of our pre-training objective by post-training pre-trained models for two practical applications. First, we adapt the model to condition on robot pose instead of partial point tracks, and train it on scene-specific action-conditioned dynamics modeling using the PGND benchmark [1]. Second, we adapt PointZero for robot manipulation by adding a small head to predict robot actions and supervise with robot manipulation demonstrations.

Zero-shot generalization. We further evaluate whether PointZero learns a *generalizable* dynamics prior by testing the model’s zero-shot capabilities. PointZero’s architecture consistently outperforms other 3D dynamics-modeling architectures when all methods are trained on our synthetic dataset and evaluated zero-shot on PGND scenes [1] and on a custom test set of unseen real-world objects.

Contributions.

- **Problem formulation:** We introduce 3D point track completion as a flexible and transferable pre-training objective for learning arbitrary 3D dynamics without requiring action labels.
- **Performant task transfer:** When post-trained for *action-conditioned dynamics modeling* and *robot manipulation*, PointZero outperforms strong *application-specific* baselines and training the PointZero architecture from scratch. This suggests that our pre-trained model learns broadly useful 3D dynamics priors that transfer effectively to robotic applications.
- **Dataset:** We release a diverse 4D synthetic dataset with dense per-point trajectory annotations spanning deformable, articulated, and rigid object interactions. We also release the training and inference code for pre- and post-training, as well as pre-trained checkpoints.

2 Related Work

Scene-specific Dynamics Models. A common problem setting in prior work is to fit a dynamics model to interaction data collected in a specific scene. Methods grounded in physics such as mass-spring systems [9, 10], the Finite Element Method (FEM) [11], Position-Based Dynamics (PBD) [12], and the Material Point Method (MPM) [13, 14] perform well only when state estimation and system identification are successful.

The difficulty in properly identifying system parameters under partial observability and noise has led researchers to explore learning-based approaches. Graph-Based Neural Dynamics (GBND) [15, 16, 17] has shown great promise in simulating complex, high-dimensional deformable objects. However, its reliance on manually designed graph topologies and local message passing limits its applicability across a broader range of objects, particularly to rigid and articulated objects where dynamics involve abrupt changes and constrained motion. Several works explored particle-based predictions without relational edges [1, 18, 3, 19] that can learn dynamics models successfully on challenging materials, but come with a limitation that the methods are only trained on single objects or scenes with predefined physical parameter types. In contrast, PointZero combines a simple transformer architecture with a 3D point track completion objective to learn representations that adapt to scene-specific dynamics in post-training, outperforming these baselines on their own benchmarks.

Large-scale 3D Representation Learning. Large-scale pre-training has transformed 3D computer vision, enabling models to generalize across diverse scenes, objects, and viewpoints. DUST3R [20] and follow-up works [21, 22, 23] have substantially advanced 3D reconstruction, while other efforts have improved object pose estimation [24], stereo matching [25], and scene completion [26].

Dynamics models trained at scale have primarily focused on image next-state prediction, either in latent [27] or pixel [28] space (e.g., video generation). Scalable 3D dynamics learning has remained largely unexplored, owing to the scarcity of large 3D temporal datasets.

Concurrent to our work, PointWorld [6] studies scalable 3D dynamics prediction and can model scene dynamics without scene-specific interaction data or explicit object geometry priors. However, it requires calibrated real-world robot interaction data to train, which limits scalability. PointZero instead trains on a point track completion objective, which provides action-like conditioning without requiring any robot annotations. We imagine future work will leverage diverse sets of data, and we show that 3D data without action annotations is useful.

Pre-training for Robotics. Prior works investigated pre-training visual representations for downstream manipulation policies. One approach is to learn generic visual features using self-supervised learning methods such as masked autoencoding [29, 30] or DINO [31], and then fine-tune on robotics tasks. Rising in popularity is predicting task-conditioned futures [32, 33, 34] across modalities such as video, DINO, point tracks and depth. Other methods learn representations through explicit supervision over manipulation-relevant signals, such as video-language alignment [35], human actions [36], or point trajectories [2, 37]. These works suggest that structuring representation learning around features relevant to manipulation can improve downstream policy learning. Our 3D point track completion objective follows a similar principle: by predicting dense 3D point trajectories, the model is encouraged to learn representations that capture task-relevant object geometry, motion, and dynamics. The closest setting to ours is 3PoinTr [2], which uses task-specific 3D point track prediction as pre-training for downstream manipulation; we compare against 3PoinTr and other baselines in our imitation-learning experiments.

3 Problem Statement

We introduce the pre-training objective of *3D point track completion*.

Point cloud observation. Starting from a single RGB-D observation, we use the RGB image $I \in \mathbb{R}^{H \times W \times 3}$, depth map $D \in \mathbb{R}^{H \times W}$, foreground mask $M \in \{0, 1\}^{H \times W}$, and camera intrinsics $K \in \mathbb{R}^{3 \times 3}$ to unproject the masked depth into an observed 3D point cloud $P^{\text{obs}} \in \mathbb{R}^{N_p \times 3}$, where N_p is the number of foreground pixels.




Figure 2: PointZero architecture overview. PointZero takes in a single RGB-D image and a small number of complete point tracks, and predicts dense 3D point trajectories. PointZero can also be fine-tuned to condition on robot pose instead of partial point tracks, or to output robot action chunks in addition to point track predictions. PointZero combines a Perceiver-IO [38] architecture with self-attention and cross-attention to encode diverse dynamics.

Partial point track conditioning. We condition the model on a small number of partial 3D trajectories: we select N_a conditioning points over T timesteps, represented as $A \in \mathbb{R}^{T \times N_a \times 3}$, where empirically $N_a \in \{1, 2, 3\}$.

Prediction. Given the initial observation P^{obs} , visual features extracted from I , and the conditioning A , PointZero completes point tracks $P \in \mathbb{R}^{T \times N_p \times 3}$, with $P_{1,i} = P_i^{\text{obs}}$ and predicted positions at frames $\tau \in \{2, \dots, T\}$.

The point-level formulation provides a unified dynamics representation for arbitrary object types. The pre-training objective can be used or adapted for several applications, including **partial point track completion**: the trained model directly predicts dense point tracks, given one or more conditioning point tracks. **Post-training for action-conditioned dynamics**: replace the partial point track conditioning with robot end-effector pose conditioning. **Post-training for robot manipulation**: attach a lightweight action prediction head to the pre-trained representation and supervise it with observation-action pairs from expert robot demonstrations.

4 Methods

We propose PointZero, a single-transformer architecture for modeling action-conditioned 3D dynamics. The model combines (i) point cloud geometry, (ii) action trajectories, and (iii) visual features into a single diffusion transformer (DiT) that predicts the target state from noise.

Point tokens. Given the observed point cloud P^{obs} , we repeat each initial position over the $T - 1$ future frames to form $r_i \in \mathbb{R}^{3(T-1)}$, and embed it using a shared MLP E_P , yielding $X_P \in \mathbb{R}^{N_p \times d}$.

Partial point track tokens. For each time step $\tau \in \{1, \dots, T\}$ and trajectory index $j \in \{1, \dots, N_a\}$, we embed the 3D coordinate $A_{\tau,j} \in \mathbb{R}^3$ using a shared MLP E_A . We inject positional information using a time embedding $e_t(\tau) \in \mathbb{R}^d$, produced by an MLP from the scalar τ , and a trajectory-index embedding $e_a(j) \in \mathbb{R}^d$, looked up from a learned table of N_a vectors. The resulting action token is $(X_A)_{\tau,j} = E_A(A_{\tau,j}) + e_t(\tau) + e_a(j)$, and we flatten these tokens into a single action sequence $X_A \in \mathbb{R}^{(TN_a) \times d}$.

Visual tokens. We extract dense image features using DINOv2 [39], yielding tokens $F_{\text{DINO}} \in \mathbb{R}^{\lfloor H/14 \rfloor \times \lfloor W/14 \rfloor \times d}$. To reduce memory, we compress them into N_V visual tokens using a Perceiver-IO module [38]: starting from learned latent queries $Z \in \mathbb{R}^{N_V \times d}$, we apply L layers of self-attention over Z and cross-attention from Z to F_{DINO} . This produces $X_V = \text{Perceiver}(Z, F_{\text{DINO}}) \in \mathbb{R}^{N_V \times d}$.



Figure 3: We contribute a novel dataset to learn diverse dynamics in simulation and the real world. The dataset contains 2.9 million synthetic image frames with deformable, articulated and rigid objects. We also collect a dataset with 14 objects and 124 interactions in the real world for evaluation of zero-shot sim-to-real transfer.

Diffusion transformer (DiT). We use a diffusion transformer with alternating layers of self-attention and cross-attention. For each point i , the query concatenates the current noisy future trajectory $p_{i,t} \in \mathbb{R}^{3(T-1)}$ with r_i , the initial XYZ position repeated $T - 1$ times, and projects the result with a shared MLP $E_Q : \mathbb{R}^{6(T-1)} \rightarrow \mathbb{R}^d$. This yields $X_{Q,i} = E_Q(\text{concat}(p_{i,t}, r_i))$, with $X_Q \in \mathbb{R}^{N_p \times d}$; a learned diffusion-time embedding is added to each query.

The cross-attention keys and values are formed by concatenating the point, action, and visual embeddings: $X_K = \text{concat}(X_P, X_A, X_V) \in \mathbb{R}^{(N_p + TN_a + N_V) \times d}$.

4.1 Training Objectives

We supervise the full trajectory per point to provide a rich supervision signal. We index the $T = 10$ physical frames by $\tau \in \{1, \dots, T\}$, with the initial observation at $\tau = 1$, and define the flattened future trajectory $p_i = \text{flatten}(P_{i,2:T}) \in \mathbb{R}^{3(T-1)}$, where $P_i \in \mathbb{R}^{T \times 3}$ denotes the ground-truth trajectory of point i in P . For all losses below, $\|\cdot\|_w^2$ denotes the coordinate-averaged, temporally weighted squared error defined in Appendix A.1; losses are averaged over points and training examples.

Regression. Given the dynamics model g_θ parameterized by θ , we directly regress the trajectory

$$\mathcal{L}_{\text{reg}} = \frac{1}{N_p} \sum_{i=1}^{N_p} \|g_{\theta,i}(P^{\text{obs}}, A, I) - p_i\|_w^2. \quad (1)$$

Flow matching (v-prediction). For flow matching [40], we sample an isotropic Gaussian source point $p_i^{\text{src}} = \varepsilon_i$, with $\varepsilon_i \sim \mathcal{N}(\mathbf{0}, 0.2^2 \mathbf{I}_{3(T-1)})$ in normalized coordinates, and interpolate between source and target as $p_{i,t} = (1-t)p_i^{\text{src}} + tp_i$ for diffusion time $t \in [0, 1]$. The target velocity is $v_i^* = (p_i - p_{i,t})/(1-t) = p_i - p_i^{\text{src}}$. Let $P_t \in \mathbb{R}^{N_p \times (T-1) \times 3}$ be the reshaped tensor corresponding to $\{p_{i,t}\}_{i=1}^{N_p}$. We train the model to predict v_i^* :

$$\mathcal{L}_{\text{FM}} = \frac{1}{N_p} \sum_{i=1}^{N_p} \|g_{\theta,i}(P_t, P^{\text{obs}}, A, I, t) - v_i^*\|_w^2. \quad (2)$$

JiT-style (x-prediction). Flow matching and diffusion models for image generation are often applied in learned autoencoder latent spaces, enabling generation in a more compact and smooth

representation [41, 42]. In contrast, Just image Transformers (JiT) [43] perform generation directly in pixel space. JiT argues that natural images lie on a low-dimensional manifold within pixel space, and therefore trains the model to directly predict the denoised image x_0 .

Similarly, PointZero does not use a low-dimensional VAE to encode 3D flow, and we hypothesize that the data also lies on a low-dimensional manifold. Accordingly, we follow JiT and train the model to perform x-prediction: g_θ outputs the trajectory $\hat{p}_i = g_\theta(P_t, P^{\text{obs}}, A, I, t)_i$. Following the JiT training objective, we supervise the implied velocity $\hat{v}_i = (\hat{p}_i - p_{i,t})/(1 - t)$ against the target velocity v_i^* :

$$\mathcal{L}_{\text{JiT}} = \frac{1}{N_p} \sum_{i=1}^{N_p} \left\| \frac{g_{\theta,i}(P_t, P^{\text{obs}}, A, I, t) - p_{i,t}}{1 - t} - v_i^* \right\|_w^2. \quad (3)$$

Following JiT, we clip the denominator $1 - t$ to a minimum of 0.05 when computing both target and predicted velocities during training.

4.2 Dataset

A major bottleneck for scaling 3D dynamics learning is the absence of standardized datasets that capture action-conditioned, physically grounded interactions across diverse object types. Unlike video prediction, 3D dynamics learning requires temporally consistent geometry, explicit object states, and controllable interventions, making data collection particularly costly and fragmented across prior work. To this end, we contribute a new synthetic dataset spanning deformable, articulated, and rigid objects with motions driven by randomized interactions. Details regarding our dataset generation are provided in Appendix A.3.

4.3 Post-training Recipes

We study the utility of 3D point track completion as a pre-training objective for downstream tasks.

Post-training on end-effector state. For accurate scene-specific dynamics, we replace the conditioning on sparse partial point tracks with conditioning on robot end-effector (EEF) pose. Concretely, we swap the action tokens X_A for EEF tokens that encode the 6-DoF pose and gripper state at each timestep, embedded by a new MLP E_{EEF} . We initialize compatible components from the pre-trained model and fine-tune on the target scene.

Imitation-learning post-training. For policy learning, we remove partial point track conditioning and add an action head π_ϕ that predicts an EEF trajectory. With point-track supervision, we jointly predict EEF and point trajectories. See Section 5.7 and Appendices A.4 and A.9 for task-specific recipes.

5 Results

5.1 Implementation Details

Normalization and augmentations. We normalize each point cloud using the initial-frame centroid and 99th-percentile radius, and invert this transformation before evaluating errors in physical units. We then apply random rotations and Gaussian noise to both the point clouds and partial point track conditioning points to enhance robustness to noisy real-world measurements. We also apply visual augmentations to image observations, including random changes in brightness and contrast, salt-and-pepper noise, and Gaussian noise.

Training. We train PointZero on a node of $8 \times$ H100 GPUs for approximately 2 days per variant. Following JiT [43], we use logit-normal time sampling and additionally set $t=0$ with probability $p_{t=0} = 0.2$. At test time, both flow matching and JiT use four forward-Euler updates on a deterministic logit-normal quantile time grid with parameters $\mu = -3$ and $\sigma = 1$. We adopt a ViT-Base backbone (768 token dimension, 12 heads, 12 layers) with a 3-layer Perceiver-IO encoder and 4 query tokens in the pre-training checkpoints. Post-training omits DINO visual conditioning for efficiency.

Table 1: Dynamics prediction errors on held-out samples of our generated synthetic dataset. All baselines were trained on the proposed dataset. MDE, CD, and EMD are in centimeters; MSE is in 10^{-2} m^2 . **Bold** marks the best result in each column, and underlining indicates the second-best result.

Method	Deformable				Articulated				Rigid			
	MDE ↓	MSE ↓	CD ↓	EMD ↓	MDE ↓	MSE ↓	CD ↓	EMD ↓	MDE ↓	MSE ↓	CD ↓	EMD ↓
GBND [44]	17.38	6.15	7.45	16.47	11.15	6.46	7.38	11.11	155.72	759.93	93.30	154.44
ParticleFormer [3]	17.35	6.15	7.42	16.44	10.86	6.46	7.11	10.83	155.04	760.43	92.76	153.77
PGND [1]	9.01	1.36	4.10	7.86	8.70	2.13	5.40	8.29	67.58	123.79	33.56	64.02
PTv3 [46]	9.20	1.59	3.91	8.28	8.25	2.31	5.25	8.00	61.97	114.77	29.87	58.57
PointZero-FM-mean-10	3.59	0.25	1.55	3.18	2.40	0.36	1.77	2.34	27.26	34.25	14.17	25.41
PointZero-FM-oracle-10	2.80	0.15	1.24	2.41	<u>1.96</u>	<u>0.25</u>	<u>1.48</u>	<u>1.91</u>	<u>19.91</u>	<u>18.80</u>	<u>10.39</u>	<u>18.43</u>
PointZero-Regression	4.08	0.32	1.74	3.63	3.85	0.66	2.57	3.68	32.14	44.58	16.43	29.78
PointZero-JiT-mean-10	3.62	0.26	1.56	3.22	2.36	0.37	1.70	2.30	28.06	39.25	14.65	26.35
PointZero-JiT-oracle-10	<u>2.85</u>	<u>0.16</u>	<u>1.26</u>	<u>2.47</u>	1.95	0.24	1.44	1.89	19.46	17.89	10.30	17.99

5.2 Baselines

We implement several strong existing learning-based dynamics methods, all *trained on our training dataset* with identical augmentations and a prediction horizon of $H = 10$. All methods use the same inputs, conditioning signals, output targets, and supervision; in particular, each baseline is adapted to condition on the same partial point tracks as PointZero.

Graph-Based Neural Dynamics (GBND) [44]: GBND downsamples the point cloud to 100 particles per scene, connects edges based on top- k nearest neighbors ($k = 5$) to form a spatial graph, and applies a GNN to predict next-step per-particle velocities. GBND is rolled out sequentially for longer predictions. **ParticleFormer [3]:** ParticleFormer uses the same input as GBND but uses a transformer for particle encoding and predicted velocity decoding. **Particle-Grid Neural Dynamics (PGND) [1]:** PGND uses PointNet [45] and a grid-based representation to predict next-step particle velocities. **Point Transformer v3 (PTv3) [46]:** PTv3 predicts next-step particle motions and performs sequential prediction in a similar way to PGND, but with a transformer architecture.

5.3 Evaluation Metrics

Following prior work [44, 3, 1], we evaluate prediction accuracy using the final-timestep point clouds. Given ground-truth points G and predicted points P , we report the mean squared error (MSE), mean distance error (MDE), the bi-directional Chamfer Distance (CD), and the Earth Mover’s Distance (EMD). Formal definitions of these metrics are provided in Appendix A.2.

5.4 Synthetic Evaluation

We evaluate on held-out samples of our training dataset: approximately 32k scenes across all object categories. We also provide ablations over model and data size in Appendix A.5.

Comparison against baselines. Table 1 shows that every PointZero variant outperforms every baseline on every metric and object category. This suggests that a flexible but expressive transformer, generating entire motion sequences, is highly performant for learning diverse dynamics.

Training objectives. Generative models are capable of modeling arbitrary distributions given incomplete observations. We generate ten seeded predictions and report the lowest error independently for each scene and metric. This is a ground-truth oracle. The generative objectives, FM and JiT, outperform the regression variant, suggesting that they capture a multimodal distribution over plausible point trajectories. More comprehensive statistics and analysis are available in Appendix A.6.

In our experiments, JiT does not consistently outperform flow matching (PointZero-FM) when both models are trained for sufficiently long.




Figure 4: Real-world qualitative 3D point track completion evaluation. All methods are trained with identical inputs and conditioning, and with identical data. We find GBND often predicts zero motion, while PTv3 and PGND struggle to recover rigid (articulated) motions.

5.5 Real-World Zero-shot Partial Point Track Completion

We evaluate zero-shot generalization to real-world objects: methods are trained only on our simulation dataset and tested on novel real-world scenes without fine-tuning.

Data collection. We collect 124 interactions across 14 objects: 6 articulated, 5 deformable, and 3 rigid objects, where a human operator manipulates each object. We obtain action and point-track trajectory labels using FoundationStereo [25] and CoTracker3 [8]. To obtain action labels, we manually annotate one human-object contact point per human hand in the first frame and forward-propagate the trajectories.

Analysis. We display qualitative results in Fig. 4. Compared to baselines, PointZero excels at adhering to the input trajectory actions (orange arrows) it is conditioned on. PointZero point track completions are also more faithful to object-specific physical structure, with better preservation of cloth surface area and less deformation of rigid bodies. Table 9 shows that both FM and JiT outperform all baselines on 11 of 12 real-world metrics; PTv3 wins on rigid-object MSE. This suggests that for learning diverse dynamics, simple transformer architectures beat networks with inductive biases such as spatial grids [1].

5.6 Post-training: Robot-Conditioned 3D Dynamics Prediction

3D point track completion is an incomplete approximation of contact-rich real-world dynamics, as is common in robot manipulation. We post-train PointZero (Section 4.3) to predict 3D dynamics conditioned on robot end-effector state, and study the performance of its pre-trained spatial prior. We evaluate PointZero on the six-scene benchmark from PGND [1] and compare against strong *application-specific* baselines. For each scene, we post-train a separate instance of PointZero using the same training set used to train the PGND baseline. We post-train with the JiT objective and LoRA. We also train PointZero-Scratch with the same objective, random initialization, and all parameters trainable. The results suggest two things: (1) PointZero convincingly outperforms state-of-the-art baselines on 4/6 scenes, and (2) pre-training is critical to its strong predictions.

Table 2: Dynamics prediction errors on the PGND benchmark [1] (centimeters). The PGND method is trained only on scene-specific interactions. We evaluate PointZero both trained from scratch on the scene-specific interactions (PointZero-Scratch), and also fine-tuned (PointZero-FT) on the scene-specific interactions from the pre-trained checkpoint. Both PointZero rows report a per-scene, per-metric best-of-10 oracle (Section 5.6). **Bold** marks the best result in each column.

Method	Bread			Paperbag			Cloth			Box			Rope			Sloth		
	MDE↓	CD↓	EMD↓	MDE↓	CD↓	EMD↓	MDE↓	CD↓	EMD↓	MDE↓	CD↓	EMD↓	MDE↓	CD↓	EMD↓	MDE↓	CD↓	EMD↓
GBND [17]	3.1	3.1	1.6	3.0	4.2	1.6	7.7	8.3	3.5	4.5	6.2	3.2	6.2	7.3	3.6	7.8	6.4	3.2
PGND [1]	2.0	1.8	1.0	1.6	2.1	0.9	4.5	4.3	2.2	2.2	1.5	1.6	3.9	3.8	2.1	4.3	3.3	1.7
PointZero-Scratch	4.2	3.9	1.9	4.2	4.4	1.9	5.6	4.7	2.1	3.7	3.9	2.1	9.3	10.8	5.0	7.3	5.9	2.8
PointZero-FT	1.5	1.1	0.6	1.6	2.0	0.8	4.0	3.4	1.5	2.4	2.7	1.4	3.3	3.3	1.6	3.9	3.0	1.5

Table 3: Imitation learning success (%). PointZero uses 20 labeled demos and 100 actionless videos per task.

Task	3PoinTr	DP3	DP	ATM	PointZero
<i>Simulation</i>					
Blockstack	90.9	44.4	45.4	40.0	99.8
Microwave	80.8	31.4	32.0	30.4	93.1
Glass	95.2	74.9	57.5	3.9	95.9
<i>Real-world</i>					
Drawer	90.0	70.0	–	30.0	100.0
Cup	100.0	80.0	–	30.0	100.0
Paper	90.0	10.0	–	0.0	70.0
Sock	90.0	20.0	–	0.0	90.0

Table 4: Pre-training **with** downstream track supervision. Success (%); 20 demos, no extra videos.

Recipe	Blockstack	Microwave	Glass	Avg.
Scratch	93.5	81.4	66.6	80.5
Pretrained	93.2	91.9	79.5	88.2

Table 5: Pre-training **without** downstream track supervision. Success (%); 20 demos, no extra videos.

Recipe	Blockstack	Microwave	Glass	Avg.
Scratch	83.8	89.5	49.1	74.1
Pretrained	85.2	90.1	64.6	80.0

We additionally evaluate PointZero in a zero-shot setting on the PGND benchmark. It achieves competitive performance with scene-specific baselines, *despite never having interacted with the objects*. We provide these results and additional details in Appendix A.8.

5.7 Post-training: Imitation Learning for Robot Manipulation

We test whether the trained representation effectively adapts to robot manipulation using the experimental evaluation protocol from 3PoinTr [2]. We independently post-train PointZero to predict robot actions in three simulation tasks and four real-world tasks. For each task, we use 20 expert demonstrations with robot action labels, and 100 additional videos of expert demonstrations without any action labels. We provide details about the tasks and policy-training setup in Appendix A.9.

Baselines. **DP3** [47] and **Diffusion Policy** [48] are performant behavior cloning methods that encode observations and then use conditional diffusion models to generate action chunks. **3PoinTr** [2] and **ATM** [37] pre-train point-track prediction models from videos, and then condition policies on the point-track predictions.

Analysis. PointZero achieves the highest or joint-highest success rate on six of seven manipulation tasks (Table 3). Using only 20 action-labeled demonstrations per simulation task and no additional actionless videos, pre-training increases average success from 80.5% to 88.2% with auxiliary point-track supervision (Table 4); without it, the pre-trained recipe achieves 80.0% versus 74.1% from scratch (Table 5). The latter recipe freezes the pre-trained point-processing stream, whereas Scratch trains the full model (Appendix A.4). Both comparisons use 1,000 rollouts per simulation task; bold entries mark the better variant. The results suggest that 3D point track completion as a pre-training objective helps downstream imitation learning applications. In particular, the isolated pre-training experiments in Table 4 and Table 5 suggest 3D point-track completion directly improves performance.

6 Conclusion

We present PointZero, a 3D dynamics model trained to do *3D point track completion*: given a single RGB-D observation and a small number of sparse point trajectories, the model predicts dense future 3D tracks for all observed points. This objective provides a scalable way to learn dynamics priors without requiring embodiment-specific annotations, using a metric point representation that can represent deformable, articulated, and rigid objects.

Across synthetic and real-world evaluations, PointZero substantially improves dense point-track completion over adapted 3D dynamics baselines. More importantly, the learned representation transfers effectively to downstream tasks: after post-training, PointZero improves scene-specific action-conditioned dynamics prediction and achieves strong performance on robot manipulation tasks. These results suggest that 3D point track completion can serve as a useful bridge between scalable robot-free dynamics pre-training and downstream embodied intelligence applications.

Limitations and Future Work. PointZero remains limited by the coverage and realism of its pre-training data. Although our synthetic dataset spans several object classes, it does not capture the full diversity of real-world materials, contact-rich hand-object interactions, cluttered scenes, or long-horizon dynamics. Future work should augment simulation with pseudo-annotations from real-world videos using 3D reconstruction and point tracking methods. PointZero also uses relatively simple conditioning signals: partial point tracks during pre-training and end-effector pose during action-conditioned post-training. Richer interaction representations, such as contact locations and forces, may further improve accuracy. Finally, our downstream evaluations remain task-specific and relatively small-scale; future work should study multi-scene and multi-task transfer across a broader range of applications.

References

- [1] Kaifeng Zhang, Baoyu Li, Kris Hauser, and Yunzhu Li. Particle-grid neural dynamics for learning deformable object models from rgb-d videos. In *Proceedings of Robotics: Science and Systems (RSS)*, 2025.
- [2] Adam Hung, Bardienus Pieter Duisterhof, and Jeffrey Ichnowski. 3point: 3d point tracks for robot manipulation pretraining from casual videos. *arXiv preprint arXiv:2603.08485*, 2026.
- [3] Suning Huang, Qianzhong Chen, Xiaohan Zhang, Jiankai Sun, and Mac Schwager. Particle-former: A 3d point cloud world model for multi-object, multi-material robotic manipulation. *arXiv preprint arXiv:2506.23126*, 2025.
- [4] Ruijie Zheng, Dantong Niu, Yuqi Xie, Jing Wang, Mengda Xu, Yunfan Jiang, Fernando Castañeda, Fengyuan Hu, You Liang Tan, Letian Fu, Trevor Darrell, Furong Huang, Yuke Zhu, Danfei Xu, and Linxi Fan. Egoscale: Scaling dexterous manipulation with diverse egocentric human data, 2026.
- [5] Hongtao Wu, Ya Jing, Chilam Cheang, Guangzeng Chen, Jiafeng Xu, Xinghang Li, Minghuan Liu, Hang Li, and Tao Kong. Unleashing large-scale video generative pre-training for visual robot manipulation, 2023.
- [6] Wenlong Huang, Yu-Wei Chao, Arsalan Mousavian, Ming-Yu Liu, Dieter Fox, Kaichun Mo, and Li Fei-Fei. Pointworld: Scaling 3d world models for in-the-wild robotic manipulation, 2026.
- [7] Jay Karhade, Nikhil Keetha, Yuchen Zhang, Tanisha Gupta, Akash Sharma, Sebastian Scherer, and Deva Ramanan. Any4d: Unified feed-forward metric 4d reconstruction. *arXiv preprint arXiv:2512.10935*, 2025.
- [8] Nikita Karaev, Iurii Makarov, Jianyuan Wang, Natalia Neverova, Andrea Vedaldi, and Christian Rupprecht. CoTracker3: Simpler and better point tracking by pseudo-labelling real videos. 2024.
- [9] Tiantian Liu, Adam W. Bargteil, James F. O’Brien, and Ladislav Kavan. Fast simulation of mass-spring systems. *ACM Trans. Graph.*, 32(6), November 2013.

- [10] Hanxiao Jiang, Hao-Yu Hsu, Kaifeng Zhang, Hsin-Ni Yu, Shenlong Wang, and Yunzhu Li. Phystwin: Physics-informed reconstruction and simulation of deformable objects from videos. *ICCV*, 2025.
- [11] Marcos García, César Mendoza, Luis Pastor, and Angel Rodríguez. Optimized linear fem for modeling deformable objects. *Computer Animation and Virtual Worlds*, 17(3-4):393–402, 2006.
- [12] Miles Macklin, Matthias Müller, Nuttapong Chentanez, and Tae-Yong Kim. Unified particle physics for real-time applications. *ACM Trans. Graph.*, 33(4), July 2014.
- [13] Deborah Sulsky, Shi-Jian Zhou, and Howard L. Schreyer. Application of a particle-in-cell method to solid mechanics. *Computer Physics Communications*, 87(1):236–252, 1995. Particle Simulation Methods.
- [14] Xuan Li, Yi-Ling Qiao, Peter Yichen Chen, Krishna Murthy Jatavallabhula, Ming Lin, Chenfanfu Jiang, and Chuang Gan. Pac-nerf: Physics augmented continuum neural radiance fields for geometry-agnostic system identification. *arXiv preprint arXiv:2303.05512*, 2023.
- [15] Yunzhu Li, Jiajun Wu, Russ Tedrake, Joshua B. Tenenbaum, and Antonio Torralba. Learning particle dynamics for manipulating rigid bodies, deformable objects, and fluids. In *International Conference on Learning Representations*, 2019.
- [16] Alvaro Sanchez-Gonzalez, Jonathan Godwin, Tobias Pfaff, Rex Ying, Jure Leskovec, and Peter Battaglia. Learning to simulate complex physics with graph networks. In *International conference on machine learning*, pages 8459–8468. PMLR, 2020.
- [17] Kaifeng Zhang, Baoyu Li, Kris Hauser, and Yunzhu Li. Adaptigraph: Material-adaptive graph-based neural dynamics for robotic manipulation. In *Proceedings of Robotics: Science and Systems (RSS)*, 2024.
- [18] William F Whitney, Jacob Varley, Deepali Jain, Krzysztof Choromanski, Sumeet Singh, and Vikas Sindhwani. Modeling the real world with high-density visual particle dynamics. *arXiv preprint arXiv:2406.19800*, 2024.
- [19] Tongxuan Tian, Haoyang Li, Bo Ai, Xiaodi Yuan, Zhiao Huang, and Hao Su. Diffusion dynamics models with generative state estimation for cloth manipulation. *Conference on Robot Learning (CoRL)*, 2025.
- [20] Shuzhe Wang, Vincent Leroy, Yohann Cabon, Boris Chidlovskii, and Jerome Revaud. Dust3r: Geometric 3d vision made easy. In *CVPR*, 2024.
- [21] Jianyuan Wang, Minghao Chen, Nikita Karaev, Andrea Vedaldi, Christian Rupprecht, and David Novotny. Vggt: Visual geometry grounded transformer. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2025.
- [22] Nikhil Keetha, Norman Müller, Johannes Schönberger, Lorenzo Porzi, Yuchen Zhang, Tobias Fischer, Arno Knapitsch, Duncan Zauss, Ethan Weber, Nelson Antunes, Jonathon Luiten, Manuel Lopez-Antequera, Samuel Rota Bulò, Christian Richardt, Deva Ramanan, Sebastian Scherer, and Peter Kotschieder. MapAnything: Universal feed-forward metric 3D reconstruction. In *International Conference on 3D Vision (3DV)*. IEEE, 2026.
- [23] Bardienus Duisterhof, Lojze Zust, Philippe Weinzaepfel, Vincent Leroy, Yohann Cabon, and Jerome Revaud. Mast3r-sfm: a fully-integrated solution for unconstrained structure-from-motion, 2024.
- [24] Bowen Wen, Wei Yang, Jan Kautz, and Stan Birchfield. Foundationpose: Unified 6d pose estimation and tracking of novel objects. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 17868–17879, 2024.
- [25] Bowen Wen, Matthew Trepte, Joseph Aribido, Jan Kautz, Orazio Gallo, and Stan Birchfield. Foundationstereo: Zero-shot stereo matching. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 5249–5260, 2025.

- [26] Bardienus P Duisterhof, Jan Oberst, Bowen Wen, Stan Birchfield, Deva Ramanan, and Jeffrey Ichnowski. Rayst3r: Predicting novel depth maps for zero-shot object completion. *NeurIPS*, 2025.
- [27] Gaoyue Zhou, Hengkai Pan, Yann LeCun, and Lerrel Pinto. DINO-WM: World models on pre-trained visual features enable zero-shot planning. In *International Conference on Machine Learning*, 2025.
- [28] Boyuan Chen, Diego Marti Monso, Yilun Du, Max Simchowitz, Russ Tedrake, and Vincent Sitzmann. Diffusion forcing: Next-token prediction meets full-sequence diffusion, 2024.
- [29] Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollar, and Ross Girshick. Masked autoencoders are scalable vision learners. In *CVPR*, 2022.
- [30] Shengyi Qian, Kaichun Mo, Valts Blukis, David F Fouhey, Dieter Fox, and Ankit Goyal. 3d-mvp: 3d multiview pretraining for manipulation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 22530–22539, 2025.
- [31] Mathilde Caron, Hugo Touvron, Ishan Misra, Hervé Jégou, Julien Mairal, Piotr Bojanowski, and Armand Joulin. Emerging properties in self-supervised vision transformers. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 9650–9660, 2021.
- [32] Adam Hung, Bardienus P. Duisterhof, Deva Ramanan, and Jeffrey Ichnowski. Modality-autoregressive world-action models, 2026.
- [33] Ge Yan, Jinghao Liu, Yuzhi Fan, Lei Cai, Minwen Liao, Jesse Zhang, and Dieter Fox. Flex- π : A multi-stream world-action model with compute flexibility. *arXiv preprint arXiv:2608.10860*, 2026.
- [34] Seonghyeon Ye, Yunhao Ge, Kaiyuan Zheng, Shenyuan Gao, Sihyun Yu, George Kurian, Suneel Indupuru, You Liang Tan, Chuning Zhu, Jiannan Xiang, Ayaan Malik, Kyungmin Lee, William Liang, Nadun Ranawaka, Jiasheng Gu, Yinzhen Xu, Guanzhi Wang, Fengyuan Hu, Avnish Narayan, Johan Bjorck, Jing Wang, Gwanghyun Kim, Dantong Niu, Ruijie Zheng, Yuqi Xie, Jimmy Wu, Qi Wang, Ryan Julian, Danfei Xu, Yilun Du, Yevgen Chebotar, Scott Reed, Jan Kautz, Yuke Zhu, Linxi "Jim" Fan, and Joel Jang. World action models are zero-shot policies, 2026.
- [35] Suraj Nair, Aravind Rajeswaran, Vikash Kumar, Chelsea Finn, and Abhinav Gupta. R3M: A universal visual representation for robot manipulation. In Karen Liu, Dana Kulic, and Jeff Ichnowski, editors, *Proceedings of The 6th Conference on Robot Learning*, volume 205 of *Proceedings of Machine Learning Research*, pages 892–909. PMLR, 14–18 Dec 2023.
- [36] Kenneth Shaw, Shikhar Bahl, and Deepak Pathak. Videodex: Learning dexterity from internet videos, 2022.
- [37] Chuan Wen, Xingyu Lin, John Ian Reyes So, Kai Chen, Qi Dou, Yang Gao, and Pieter Abbeel. Any-point trajectory modeling for policy learning. In *Robotics: Science and Systems*, 2024.
- [38] Andrew Jaegle, Sebastian Borgeaud, Jean-Baptiste Alayrac, Carl Doersch, Catalin Ionescu, David Ding, Skanda Koppula, Daniel Zoran, Andrew Brock, Evan Shelhamer, et al. Perceiver IO: A general architecture for structured inputs & outputs. In *ICLR*, 2022.
- [39] Maxime Oquab, Timothée Darcet, Theo Moutakanni, Huy V. Vo, Marc Szafraniec, Vasil Khalidov, Pierre Fernandez, Daniel Haziza, Francisco Massa, Alaaeldin El-Nouby, Russell Howes, Po-Yao Huang, Hu Xu, Vasu Sharma, Shang-Wen Li, Wojciech Galuba, Mike Rabbat, Mido Assran, Nicolas Ballas, Gabriel Synnaeve, Ishan Misra, Herve Jegou, Julien Mairal, Patrick Labatut, Armand Joulin, and Piotr Bojanowski. Dinov2: Learning robust visual features without supervision, 2023.
- [40] Yaron Lipman, Ricky T. Q. Chen, Heli Ben-Hamu, Maximilian Nickel, and Matt Le. Flow matching for generative modeling, 2023.

- [41] Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 10684–10695, 2022.
- [42] Quan Dao, Hao Phung, Binh Nguyen, and Anh Tran. Flow matching in latent space. *arXiv preprint arXiv:2307.08698*, 2023.
- [43] Tianhong Li and Kaiming He. Back to basics: Let denoising generative models denoise, 2026.
- [44] Mingtong Zhang, Kaifeng Zhang, and Yunzhu Li. Dynamic 3d gaussian tracking for graph-based neural dynamics modeling. In *8th Annual Conference on Robot Learning*, 2024.
- [45] Charles R Qi, Hao Su, Kaichun Mo, and Leonidas J Guibas. Pointnet: Deep learning on point sets for 3d classification and segmentation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 652–660, 2017.
- [46] Xiaoyang Wu, Li Jiang, Peng-Shuai Wang, Zhijian Liu, Xihui Liu, Yu Qiao, Wanli Ouyang, Tong He, and Hengshuang Zhao. Point transformer v3: Simpler, faster, stronger. In *CVPR*, 2024.
- [47] Yanjie Ze, Gu Zhang, Kangning Zhang, Chenyuan Hu, Muhan Wang, and Huazhe Xu. 3D diffusion policy: Generalizable visuomotor policy learning via simple 3D representations. In *Robotics: Science and Systems*, 2024.
- [48] Cheng Chi, Siyuan Feng, Yilun Du, Zhenjia Xu, Eric Cousineau, Benjamin Burchfiel, and Shuran Song. Diffusion policy: Visuomotor policy learning via action diffusion. In *Robotics: Science and Systems*, 2023.
- [49] Thomas Lips, Victor-Louis De Gussemme, and Francis wyffels. Learning keypoints for robotic cloth manipulation using synthetic data, 2024.
- [50] Blender Online Community. *Blender - a 3D modelling and rendering package*. Blender Foundation, Blender Institute, Amsterdam.
- [51] Poly Haven. Poly haven: Free high-quality assets, 2026.
- [52] Fanbo Xiang, Yuzhe Qin, Kaichun Mo, Yikuan Xia, Hao Zhu, Fangchen Liu, Minghua Liu, Hanxiao Jiang, Yifu Yuan, He Wang, Li Yi, Angel X. Chang, Leonidas J. Guibas, and Hao Su. Sapien: A simulated part-based interactive environment. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2020.
- [53] Genesis Authors. Genesis: A generative and universal physics engine for robotics and beyond, December 2024.
- [54] Klaus Greff, Francois Belletti, Lucas Beyer, Carl Doersch, Yilun Du, Daniel Duckworth, David J Fleet, Dan Gnanapragasam, Florian Golemo, Charles Herrmann, Thomas Kipf, Abhijit Kundu, Dmitry Lagun, Issam Laradji, Hsueh-Ti (Derek) Liu, Henning Meyer, Yishu Miao, Derek Nowrouzezahrai, Cengiz Oztireli, Etienne Pot, Noha Radwan, Daniel Rebain, Sara Sabour, Mehdi S. M. Sajjadi, Matan Sela, Vincent Sitzmann, Austin Stone, Deqing Sun, Suhani Vora, Ziyu Wang, Tianhao Wu, Kwang Moo Yi, Fangcheng Zhong, and Andrea Tagliasacchi. Kubric: a scalable dataset generator. 2022.

A Appendix

A.1 Training Loss Weighting

We give more weight to later timesteps to emphasize longer-horizon predictions, where uncertainty is greater. For future frames $\tau \in \{2, \dots, T\}$, we use $\|u_i\|_w^2 = \frac{1}{3(T-1)} \sum_{\tau=2}^T [0.1 + 0.9((\tau - 1)/T)^2] \|u_{i,\tau}\|_2^2$.

A.2 Dynamics Prediction Evaluation Metrics

The definitions below apply to PointZero’s corresponding, equal-cardinality final-frame point sets; $\Pi(P, G)$ denotes permutation matrices.

Mean Squared Error (MSE):

$$\mathcal{L}_{\text{MSE}}(P, G) = \frac{1}{N_p} \sum_{i=1}^{N_p} \|P_i - G_i\|_2^2. \quad (4)$$

Mean Distance Error (MDE):

$$\mathcal{L}_{\text{MDE}}(P, G) = \frac{1}{N_p} \sum_{i=1}^{N_p} \|P_i - G_i\|_2. \quad (5)$$

Bi-Directional Chamfer Distance (CD):

$$\mathcal{L}_{\text{CD}}(P, G) = \frac{1}{2N_p} \sum_{p \in P} \min_{g \in G} \|p - g\|_2 + \frac{1}{2N_p} \sum_{g \in G} \min_{p \in P} \|g - p\|_2. \quad (6)$$

Earth Mover’s Distance (EMD):

$$\mathcal{L}_{\text{EMD}}(P, G) = \min_{\pi \in \Pi(P, G)} \frac{1}{N_p} \sum_{i=1}^{N_p} \sum_{j=1}^{N_p} \pi_{ij} \|P_i - G_j\|_2. \quad (7)$$

For the PGND benchmark, EMD is computed using more points than the other metrics, which can yield lower reported distances.

A.3 Dataset Generation Details

Our dataset comprises deformable, articulated, and rigid object interactions. For all datasets, we randomize camera location and intrinsics and use a single-view RGB-D observation. This models the partial visibility and various viewpoints encountered in the real world.

Deformables. We follow prior work [49] to achieve procedural cloth generation.

- **Mesh Generation:** We generate *towels*, *t-shirts* and *shorts* meshes. We randomize both the scale and the proportions.
- **Physics:** We use NVIDIA FleX [12] to model deformable physics. We apply one or two action trajectories to the cloth, modeling interactions such as *fold*, *lift*, *drop*, or *push*. Concretely, given constraints on location of action points, we solve for the location of all other points that would produce static equilibrium. To enhance motion diversity, we randomize physics parameters such as stiffness and drag.
- **Appearance:** We render the scenes with Blender [50], with random cloth and background textures from PolyHaven [51].

Articulated Objects We use the PartNet-Mobility dataset [52] to retrieve articulated objects, and place them in Genesis [53] for simulating motion. We randomly pick a revolute or prismatic joint to articulate, and set a random configuration in its viable range to produce static equilibrium. This alone may result in an invisible articulation, or very small motions. To address this issue, we reject samples where the 2D optical flow of the sequence is small using privileged information in simulation.

Rigid Objects Finally, we aim to instill an understanding of rigid body dynamics and collision into PointZero. We modify the Kubric engine [54] to include ground-truth 3D trajectories and fewer objects (up to 3 instead of 23 objects).

Sampling Action Trajectories For partial point trajectory completion training, we automate the extraction of partial point trajectories. For deformable objects, we save the action trajectories that were used as kinematic constraints in NVIDIA Flex [12] to be used as training input. For articulated and rigid bodies, we pick 3D point tracks from the k largest displacements.

Dataset Mixing. The recorded training weights are 0.33 each for shorts, T-shirts, and towels, 1.0 for articulated objects, and 0.33 for rigid objects, giving category probabilities of approximately 42.67%, 43.10%, and 14.22%, respectively. This gives an approximate category ratio of 3 : 3 : 1, reflecting our emphasis on learning more complex non-rigid and articulated dynamics while still exposing the model to rigid-body motion and collisions.

A.4 Additional Manipulation Comparisons

Tables 4 and 5 report the pre-training ablations using only 20 demonstrations per simulation task, with no additional actionless videos. In Table 4, PointZero initializes from JiT pre-training and scratch initializes randomly; both train all parameters with point-trajectory regression and an $\ell_{2,1}$ action loss, using a separate action branch with learned queries. In Table 5, both use only the action loss; PointZero keeps its pre-trained point-processing stream fixed while training the remaining parameters, whereas scratch trains the full model. With downstream track supervision, pre-training improves two tasks and the average (80.5% to 88.2%), while Blockstack changes from 93.5% to 93.2%. Under this protocol, Diffusion Policy [48] and DP3 [47] achieve average success rates of 45.0% and 50.2%, respectively; their per-task results are listed in Table 3. Without downstream point-track supervision, pre-trained PointZero outperforms its scratch variant on all three tasks, with the largest gap on Glass (64.6% vs. 49.1%). DP3 outperforms PointZero without downstream track supervision on Glass (74.9% vs. 64.6%).

A.5 Ablations

Table 6: Data-scaling ablation on the articulated split of the real-world dataset: performance degrades gracefully as the pre-training dataset is reduced. Error values are in centimeters; MSE is in cm^2 . Training epochs are scaled inversely with the data fraction (250 epochs at 10%, 500 at 5%). **Bold** marks the best result for each metric.

Data Fraction	MDE↓	MSE↓	CD↓	EMD↓
100%	2.2	12.1	1.4	2.0
10%	3.1	49.6	2.0	2.9
5%	3.3	64.3	2.0	3.1

Table 7: Model-size ablation on the articulated split of the real-world dataset. Small uses 384 token dimensions, 6 heads, and 6 layers (45M parameters) versus the Base configuration (768 dimensions, 12 heads, 12 layers). Error values are in centimeters; MSE is in cm^2 . **Bold** marks the best result for each metric.

Size	MDE↓	MSE↓	CD↓	EMD↓
Base	2.2	12.1	1.4	2.0
Small	3.1	37.4	1.8	3.0

We study the impact of the training data fraction and of model size.

Training data fraction. Table 6 reports performance on the articulated split of the real-world set as the pre-training dataset is reduced, with training epochs scaled inversely to hold the optimization budget comparable. Performance degrades gracefully: reducing the data to 10% increases MDE from 2.2 to 3.1 cm, and further reduction to 5% yields only a small additional drop. This suggests the pre-training objective extracts useful dynamics priors even from a fraction of the dataset, while the full dataset remains clearly beneficial.

Model size. We additionally train a Small variant from scratch (384 token dimensions, 6 heads, 6 layers) with otherwise identical inputs and training data. Table 7 reports performance in the same setting: shrinking the model degrades all metrics substantially, suggesting that further scaling the Base model could yield additional gains.

A.6 Additional Synthetic Data Point Dynamics Completion Results

In Table 8, we expand Table 1 with additional evaluations of PointZero-JiT and PointZero-FM. For each sample, we generate ten predictions using different random noise initializations. The “-oracle-10” rows select the lowest error separately for each scene and metric; “-first” uses the first prediction, and “-mean-10” averages scalar errors over all ten predictions. For “-medoid-10”, each corresponding point’s final position is selected from its ten sampled positions to minimize the summed Euclidean distance to the other nine, without using ground truth. Different points may come from different samples. The “-pooled-scalar-median-10” rows take each metric’s median over scene–prediction pairs within each dataset, then average dataset medians. These distribution summaries are not directly comparable to mean-error rows.

PointZero-JiT-first outperforms PointZero-Regression on 11 of 12 metrics; the exception is rigid-object MSE (48.627 versus 44.576 in 10^{-2} m^2). Both per-metric best-of-10 oracles outperform regression on all 12 metrics, showing that sampling can produce candidates with lower reconstruction error.

Table 8: Dynamics prediction errors on held-out samples of our generated synthetic dataset. All baselines were trained on the proposed dataset. MDE, CD, and EMD are in centimeters; MSE is in 10^{-2} m^2 . First-sample, mean, pointwise medoid, per-metric oracle, and pooled scalar median statistics use ten seeded predictions and are defined in Appendix A.6. Pooled medians summarize a different statistic from mean errors; no cross-statistic ranking is applied.

Method	Deformable				Articulated				Rigid			
	MDE ↓	MSE ↓	CD ↓	EMD ↓	MDE ↓	MSE ↓	CD ↓	EMD ↓	MDE ↓	MSE ↓	CD ↓	EMD ↓
GBND [44]	17.38	6.15	7.45	16.47	11.15	6.46	7.38	11.11	155.72	759.93	93.30	154.44
ParticleFormer [3]	17.35	6.15	7.42	16.44	10.86	6.46	7.11	10.83	155.04	760.43	92.76	153.77
PGND [1]	9.01	1.36	4.10	7.86	8.70	2.13	5.40	8.29	67.58	123.79	33.56	64.02
PTv3 [46]	9.20	1.59	3.91	8.28	8.25	2.31	5.25	8.00	61.97	114.77	29.87	58.57
PointZero-Regression	4.08	0.32	1.74	3.63	3.85	0.66	2.57	3.68	32.14	44.58	16.43	29.78
PointZero-FM-first	3.60	0.25	1.56	3.17	2.39	0.35	1.77	2.33	28.97	38.79	15.16	27.20
PointZero-FM-mean-10	3.59	0.25	1.55	3.18	2.40	0.36	1.77	2.34	27.26	34.25	14.17	25.41
PointZero-FM-pooled-scalar-median-10	3.21	0.14	1.30	2.80	1.75	0.05	1.47	1.74	11.65	1.85	7.03	11.27
PointZero-FM-medoid-10	3.26	0.21	1.40	2.87	2.23	0.33	1.65	2.18	24.46	28.57	12.59	22.74
PointZero-FM-oracle-10	2.80	0.15	1.24	2.41	1.96	0.25	1.48	1.91	19.91	18.80	10.39	18.43
PointZero-JiT-first	3.65	0.26	1.59	3.24	2.36	0.36	1.70	2.29	30.26	48.63	16.03	28.67
PointZero-JiT-mean-10	3.62	0.26	1.56	3.22	2.36	0.37	1.70	2.30	28.06	39.25	14.65	26.35
PointZero-JiT-pooled-scalar-median-10	3.27	0.15	1.31	2.87	1.65	0.06	1.37	1.64	11.23	1.86	6.96	11.01
PointZero-JiT-medoid-10	3.32	0.22	1.42	2.92	2.23	0.33	1.61	2.17	24.93	33.08	12.81	23.32
PointZero-JiT-oracle-10	2.85	0.16	1.26	2.47	1.95	0.24	1.44	1.89	19.46	17.89	10.30	17.99

A.7 Real-World Dynamics Prediction Quantitative Results

In Table 9, we report point track completion error metrics for PointZero and baselines on our real-world dataset. All methods are trained on the same synthetic dataset and evaluated zero-shot on the unseen real-world objects. Both PointZero-FM and PointZero-JiT outperform all baselines on

Table 9: Dynamics prediction errors on the real-world dataset (centimeters; MSE in cm^2). All baselines were trained on the proposed simulation dataset. “-first” rows use a single sample; PointZero-FM and PointZero-JiT report all metrics of the sample with the lowest MDE out of 10 (best-of-10). **Bold** marks the best result in each column, and underlining indicates the second-best result.

Method	Deformable				Articulated				Rigid			
	MDE ↓	MSE ↓	CD ↓	EMD ↓	MDE ↓	MSE ↓	CD ↓	EMD ↓	MDE ↓	MSE ↓	CD ↓	EMD ↓
GBND	6.179	81.114	4.039	6.069	3.051	24.148	2.089	2.912	4.379	34.418	2.085	4.307
ParticleFormer	6.156	80.928	4.022	6.044	3.026	24.009	2.078	2.887	4.367	34.332	2.081	4.296
PGND	3.757	27.054	2.244	3.646	2.828	20.137	1.702	2.666	2.650	13.210	1.212	2.546
PTv3	4.705	35.109	2.975	4.606	4.430	43.665	2.645	4.284	2.487	11.604	1.108	2.371
PointZero-FM-first	3.739	28.765	2.293	3.642	2.046	10.152	1.168	1.883	2.711	15.697	1.216	2.542
PointZero-FM	<u>2.923</u>	17.385	<u>1.852</u>	2.827	1.720	8.096	1.031	1.580	2.322	12.484	1.078	2.182
PointZero-Regression	3.643	25.258	2.416	3.584	2.192	11.227	1.322	2.060	2.654	14.647	1.133	2.558
PointZero-JiT-first	3.706	32.545	2.294	3.636	2.317	12.608	1.338	2.166	2.815	15.969	1.276	2.656
PointZero-JiT	2.915	<u>19.162</u>	1.837	<u>2.846</u>	<u>1.914</u>	<u>9.670</u>	<u>1.156</u>	<u>1.767</u>	<u>2.398</u>	<u>12.376</u>	<u>1.103</u>	<u>2.238</u>

Table 10: Evaluation of different 3D dynamics architectures on zero-shot predictions on the PGND benchmark [1]. All methods were trained on synthetic data from the PointZero dataset, and evaluated on unseen PGND scenes. Errors are in centimeters. **Bold** marks the best result in each column.

Method	Box			Paperbag			Cloth			Rope			Sloth			Bread		
	MDE ↓	CD ↓	EMD ↓	MDE ↓	CD ↓	EMD ↓	MDE ↓	CD ↓	EMD ↓	MDE ↓	CD ↓	EMD ↓	MDE ↓	CD ↓	EMD ↓	MDE ↓	CD ↓	EMD ↓
PGND-ZS	3.1	2.0	3.0	2.9	1.7	2.7	5.9	3.0	5.6	8.6	5.1	8.5	8.3	3.1	7.5	2.9	1.3	2.8
GBND-ZS	2.5	1.6	2.4	3.7	2.2	3.6	8.9	4.5	8.7	13.0	8.8	12.9	11.1	4.8	10.3	3.3	1.6	3.3
ParticleFormer-ZS	2.5	1.6	2.4	3.7	2.1	3.6	8.9	4.5	8.7	13.0	8.8	12.9	11.1	4.8	10.3	3.3	1.6	3.3
PTv3-ZS	3.4	2.0	3.3	3.9	2.2	3.7	7.2	3.6	6.9	7.7	4.9	7.6	6.3	2.5	5.2	2.6	1.2	2.5
PointZero-FM-ZS	2.2	1.4	2.1	2.7	1.6	2.5	5.1	<u>2.5</u>	4.9	5.4	3.5	5.3	5.6	2.3	4.9	1.9	0.9	1.8
PointZero-Regression-ZS	2.5	1.6	<u>2.3</u>	<u>2.8</u>	<u>1.7</u>	<u>2.7</u>	4.9	<u>2.5</u>	<u>4.7</u>	5.9	<u>3.6</u>	<u>5.8</u>	6.3	<u>2.5</u>	<u>5.5</u>	2.4	1.1	2.4
PointZero-JiT-ZS	<u>2.3</u>	<u>1.5</u>	2.1	2.7	1.6	2.5	4.7	2.4	4.4	<u>5.8</u>	3.8	<u>5.8</u>	<u>6.1</u>	2.6	<u>5.5</u>	<u>2.1</u>	<u>1.0</u>	<u>2.0</u>

11 of 12 metrics; PTv3 achieves the lowest rigid-object MSE (11.604 cm^2 , versus 12.376 cm^2 for PointZero-JiT).

A.8 PGND Zero-shot Evaluation

We train PointZero and several 3D dynamics architecture baselines on point track completion on the PointZero synthetic dataset. Then, we evaluate the zero-shot performance on the PGND benchmark. To enable zero-shot predictions without fine-tuning the models to condition on robot pose, we extract a single object-point trajectory per PGND sample, and condition on this track.

Results are shown in Table 10. PointZero-FM-ZS achieves an average MDE of approximately 3.8 cm across the six scenes, compared with 5.2 cm for the strongest baseline, PTv3-ZS, a reduction of approximately 26%.

A.9 Imitation Learning Experimental Setup

Following 3PoinTr [2], we evaluate on three simulation tasks: (1) stacking blocks, (2) opening a microwave, and (3) righting a fallen glass. We also evaluate on four real-world tasks: (1) opening a drawer, (2) righting a fallen glass, (3) picking up a crumpled piece of paper and placing it in the trash, and (4) folding a sock in half. The position and orientation of the objects are varied across trials, and the same initial configurations are used across all methods. Figure 5 shows images of all the tasks.




Figure 5: Visualizations of the simulation and real-world tasks used for imitation learning evaluation.