

Unlocking the Potential of Image Editing via Concept Scaling and Dense Supervision

Long Cui^{1,2}, Xiaoqian Liu¹, Qi Qin², Yi Xin², Tao Lin²,
Jianguo Li^{2,†}, Linfeng Zhang^{1,†}

¹Shanghai Jiao Tong University

²Ant Group



GitHub Repo

<https://github.com/inclusionAI/ConceptEdit>



HuggingFace Dataset

<https://huggingface.co/collections/inclusionAI/conceptedit>

Abstract

Existing image editing frameworks predominantly follow the training paradigm of text-to-image diffusion models. However, extending this paradigm to image editing highlights two inherent discrepancies, specifically, the insufficient attention to edit concept granularity and the training inefficiency caused by sparse supervision signals. To address these issues, we establish a comprehensive hierarchical taxonomy featuring over 1,000 fine-grained edit concepts and build ConceptEdit-12M, a massive dataset of 12 million high-quality editing pairs via an improved synthesis framework. This library-driven approach effectively rectifies the distribution collapse of generated data while ensuring high data fidelity. Furthermore, we propose a dense supervision training strategy that synthesizes multiple non-interfering concepts into single image pairs. By providing richer learning signals, this strategy significantly enhances both training efficiency and overall model performance. Training results validate our strategy, significantly outperforming prior works. Finally, we present ConceptEdit-Bench, a granular evaluation suite designed to diagnose model capabilities across a vast array of real-world scenarios.

1 Introduction

Recent advancements in Text-to-Image (T2I) diffusion models [1, 2, 3, 4, 5, 6, 7] have achieved unprecedented success in generating diverse images of high quality. Building upon this, instruction-based image editing [8, 9, 10, 2, 11, 6] has emerged as a crucial application, allowing users to modify specific aspects of an image while preserving its original context. Most existing editing frameworks adopt a training paradigm similar to T2I, where the model is conditioned on both the source image and textual instructions to predict the edited target.

However, directly translating this training paradigm to image editing reveals two fundamental discrepancies. First, in the realm of T2I generation, it is a broad consensus that scaling up the diverse distribution of training data [12, 13, 14] is the key to enhancing generation capabilities. In contrast, an image editing sample fundamentally consists of two components: the source image and the **edit concept** (e.g., adding ob-

jects, replacing backgrounds, and altering attributes). While existing datasets [15, 16, 17, 18] have primarily scaled through the expansion of source image diversity, they pay insufficient attention to the diversity and granularity of the edit concepts (Fig. 1a). Second, unlike the global synthesis in T2I where generative signals apply to every pixel, image editing is fundamentally sparse. Specifically, only localized regions are actively modified, while the majority of the image serves as a static consistency constraint (Fig. 1b). Consequently, current research overlooks both the granularity of edit concepts and the training inefficiency caused by such sparse supervision.

In response to the first observation, we argue that the diversity of edit concepts is the true bottleneck for generalization in image editing. In this work, we move beyond simple data scaling and systematically investigate the impact of edit concept granularity on model performance. We hypothesize that the primary bottleneck in image editing training arises not from a lack of source image variety, but from insufficient exposure to a fine-grained distribution of potential modifications. To explore this, we establish a comprehensive taxonomy across multiple levels that defines over 1,000 fine-grained edit concepts, aiming to exhaustively cover the vast landscape of editing scenarios in the real world. As illustrated in Fig. 2, this system subdivides coarse categories into precise modifications. For instance, character actions are refined into specific movements like “finger heart” or “shrugging,” while expressions are expanded to include nuanced states such as “anxious” or “confused.” Our empirical findings demonstrate that scaling the diversity of edit concepts more effectively unlocks the model’s potential and enhances its overall editing capabilities. Furthermore, this taxonomy enables us to establish a comprehensive benchmark that evaluates editing models at a fine granularity.

To resolve the second discrepancy, we rethink the efficiency of editing supervision signals. While compositional editing has been introduced as a specific task in several studies [18, 19], it is mostly treated as an end goal rather than a fundamental mechanism for training. We argue that the inherent sparsity of single edit samples, where often only a fraction of pixels provide active learning signals, limits train-

[†]Corresponding authors.




Figure 1: **(a) Edit Concept Scaling.** Left: The previous paradigm is restricted by coarse categories and limited diversity. Right: Our approach scales up to 1,000+ fine-grained concepts to ensure a balanced and rich distribution. **(b) Dense Supervision.** Left: Conventional training relies on single edit pairs with sparse supervision signals. Right: Our composite edit strategy provides dense supervision, enhancing training efficiency.

ing efficiency. However, we observe that localized edits are often distributed across spatial regions that do not interfere with one another, making them ideal candidates for compositional compression. To leverage this, we propose a training strategy that synthesizes multiple fine-grained edit concepts into a single image pair, thereby providing dense supervision signals. Our experiments reveal that training on these densely supervised samples not only enhances the model’s capability for complex editing but also broadly improves its performance on ordinary single edits, providing a more efficient training paradigm for general image editing.

To operationalize these insights and ensure high training data fidelity, we propose an improved synthesis framework (Fig. 3) that enhances current editing pipelines [19, 20] by replacing stochastic sampling of coarse categories with a structured concept library. Rather than starting directly with instruction generation as in existing pipelines, we first distill extensive world knowledge from Large Language Models [21, 22] to proactively enumerate potential edit concepts across diverse domains. This allows us to controllably guide the distribution and diversity of the editing data to ensure exhaustive coverage of scenarios in the real world. To en-

sure the fidelity of our synthesis pipeline, we incorporate VQA filtering tailored to each instance. Rather than relying on generic templates, this mechanism generates customized pairs of questions and answers for every case. This guides the model to focus on localized regions prone to errors and directs a chain of thought (CoT) for systematic verification. This approach establishes a robust foundation for implementing concept scaling and dense supervision, supporting the construction of our dataset and a comprehensive, granular benchmark.

In summary, our main contributions are as follows:

- **Edit Concept Scaling.** We propose a paradigm shift in edit data scaling, moving from source image variety to edit concept richness. We establish a hierarchical taxonomy of 1,000 fine-grained categories to investigate concept diversity and enhance training performance.
- **Dense Supervision Training.** We propose a training methodology that leverages compositional edits to provide dense supervision signals, boosting training efficiency and performance for tasks involving both single and multiple concepts.

• 1000+ Fine-grained Edit Concepts Taxonomy •



Figure 2: **Hierarchical taxonomy of 1,000+ fine-grained edit concepts.** Top: Overall hierarchical framework. Mid: Specific leaf nodes for detailed edit concepts. Bottom: Visualizations of edit samples.

- **Improved Synthesis Framework.** We develop a framework that distills LLM world knowledge for exhaustive scenario coverage. It incorporates VQA filtering tailored to each instance, directing focus toward localized regions and assisting CoT for verification.
- **ConceptEdit Dataset and Benchmark.** We construct a 12M high-quality editing dataset and benchmark across over 1,000 fine-grained categories, facilitating robust training and granular evaluation in real-world scenarios. To our knowledge, this scale represents the largest image editing dataset to date, tying with ScaleEdit-12M [20].

2 Related Work

Image Editing Models. Diffusion priors [1, 23] catalyzed a paradigm shift in text-guided image editing. While early methods used manual latent engineering, Instruct-Pix2Pix [24] introduced instruction tuning, later refined by task-specific frameworks like OmniEdit [15]. Concurrently, unified multimodal models, such as Bagel [25], Emu3.5 [26], InternVL-U [27], and LLaDA2.0-Uni [28], demonstrate strong editing capabilities. However, open-source models still struggle to match the reasoning ceiling of proprietary systems like GPT-4o [29] and Nano Banana [6], highlighting the need for premium, knowledge-intensive datasets.

Image Editing Datasets. Image editing performance depends heavily on training data volume and diversity. Conse-

quently, the field has transitioned from manual curation like MagicBrush [30] to automated pipelines. These pipelines synthesize data using multi-tool workflows in UltraEdit [17], ImgEdit [18], and Step1X-Edit [10], or generative models in NHR [31] and HQ-Edit [32]. Recent efforts like UnicEdit [19] and ScaleEdit [20] optimize these synthesis processes for refined data. However, despite growing data volume, existing datasets neglect edit concept distributions, limiting model generalization across real-world scenarios.

3 Methodology

3.1 Rethinking Data: VLM Distribution Collapse

Overcoming the generalization bottleneck in image editing requires scaling the diversity of edit concepts. However, current pipelines heavily rely on Vision-Language Models (VLMs) to stochastically generate instructions based on limited coarse-grained categories. This unconstrained dependency leads to a severe distribution collapse due to inherent VLM biases. As shown in Fig. 4, in the “style transfer” category, stochastic sampling causes the top 5 styles to dominate 74.6% of the generated instructions, leaving dozens of others at less than 1%. This collapse hinders domain generalization, where the “domain” is the precise edit concept defined by the instruction. Existing datasets thus draw sparse, biased samples from the vast instruction space. We therefore propose a paradigm shift from stochastic VLM generation to a structured, library-driven approach. Explicitly populating




Figure 3: **Overview of the improved synthesis framework.** Stage 1: Library Construction leveraging LLM world knowledge. Stage 2: Semantic Matching and Instruction Generation including VQA checklists. Stage 3: Image Synthesis using various editing models. Stage 4: Instance Specific Verification using VQA.




Figure 4: Edit concept distributions. Stochastic sampling collapses while our library ensures diversity.

the instruction space with over 1,000 fine-grained categories ensures uniform exposure to diverse visual transformations and establishes a robust conceptual foundation.

3.2 An Improved Synthesis Framework

Based on the insights discussed in Sec. 3.1, we propose an improved synthesis framework designed to generate high-fidelity image editing pairs with a controllable concept distribution. Improving upon existing frameworks [19, 20], our pipeline consists of four key stages, as shown in Fig. 3: (1) **Library Construction**, where a structured Edit Concept Library is built to provide world knowledge; (2) **Semantic Matching and Instruction Generation**, where a VLM evaluates the compatibility between candidate concepts and specific source images to produce precise editing instructions and VQA verification metrics; (3) **Image Synthesis**, where an editing model is invoked to generate the target images based on the textual instructions; and (4) **Instance-Specific Verification**, where the results are filtered through local-

ized VQA. Leveraging this improved pipeline, we produce **ConceptEdit-12M**, a large dataset containing 12 million verified, high-quality image editing pairs.

Edit Concept Library Construction The core of our framework lies in the construction of the comprehensive Edit Concept Library. While existing pipelines often rely on a handful of human-predefined coarse categories (typically 10–20), we aim to exhaustively cover the broad spectrum of common and valuable edit operations. As illustrated in Fig. 2, we scale these operations into over 1,000 fine-grained categories to ensure high conceptual density for robust generalization. To materialize this hierarchical taxonomy, we propose an automated, iterative workflow to distill world knowledge from Large Language Models.

Specifically, starting with a lightweight, manually initialized seed taxonomy, the LLM is prompted to continuously evaluate and dynamically expand the classification tree. During each iteration, the LLM is tasked to: (1) merge or prune redundant concepts, (2) extrapolate new intermediate sub-categories, and (3) populate highly specific leaf nodes across diverse domains (e.g., physical attributes, complex human actions). This self-expanding loop repeats until the semantic expansion converges, effectively exhausting the LLM’s internal conceptual space for image manipulations. Finally, to ensure programmatic rigor, this LLM-generated taxonomy is meticulously refined by human experts to resolve remaining semantic overlaps and supplement missing high-value edge cases. As shown in Fig. 2, the resulting library comprises over 1,000 fine-grained edit concepts, providing a dense and structured conceptual space for downstream image editing.

Semantic Matching and Instruction Generation The extreme granularity of our library necessitates rigorous seman-




Figure 5: Training efficiency for different strategies.

tic grounding to ensure compatibility between concepts and image contexts (e.g., avoiding “finger heart” edits on landscapes). We employ a VLM generator Φ . For a source image $\mathbf{I}$, we sample a candidate concept subset $\mathcal{C}_{\text{cand}} \subset \mathcal{C}_{\text{lib}}$ of size N , and formalize the matching process as:

$$\Phi(\mathbf{I}, \mathcal{C}_{\text{cand}}) \mapsto \{(c_k, t_k, v_k)\}_{k=1}^M, \quad \text{s.t. } M \leq N \quad (1)$$

where $c_k \in \mathcal{C}_{\text{cand}}$ represents the matched concept, t_k is the generated editing instruction, and v_k denotes the accompanying VQA verification criteria generated concurrently. This fine-grained oversight enables dynamic distribution control. By tracking the frequencies of over 1,000 categories, we adaptively adjust sampling weights for $\mathcal{C}_{\text{cand}}$, which prevents distribution collapse and ensures conceptual diversity (Fig. 4b). Furthermore, to avoid restriction by the static taxonomy, we introduce a stochastic exploration mechanism. With a predefined probability, the VLM can bypass $\mathcal{C}_{\text{cand}}$ to autonomously propose novel concepts from its world knowledge, making the dataset both structured and diverse.

Instance-Specific VQA Filtering The quality of synthesized editing pairs depends on the precision of the filtering stage. VLM-based filtering typically utilizes generic prompts or predefined category-level templates for holistic assessment. However, these generalized approaches fail to account for the specific characteristics and potential failure modes of individual cases. To resolve this, we implement instance-specific VQA filtering as a supplementary verification layer.

Our framework utilizes the customized question-answer pairs v_k generated during the instruction phase. In addition to the holistic assessment, these targeted queries direct the VLM to inspect localized regions that are particularly prone to editing failures. This structured inquiry facilitates CoT reasoning, enabling the VLM to systematically evaluate the correspondence between the instruction and the visual modification. By guiding the model to focus on critical, instruction-relevant areas while maintaining a global perspective, this mechanism improves the detection of subtle misalignments and provides a basis for either discarding low-quality samples or refining the associated instructions through recaptioning.

3.3 Dense Supervision via Composition

Consistent with the observations in Sec. 1, the inherent sparsity of single-concept edits limits overall training efficiency. As modified regions typically occupy only a small fraction of the image, the training objective becomes dominated by the reconstruction loss of the static background. This results in highly sparse editing supervision, where the model primarily optimizes for an identity mapping rather than active generative transformations.

To resolve this, we propose integrating multiple non-interfering edit concepts into a single image pair, a strategy we formulate as dense supervision via composition. To this end, we employ a VLM-driven aggregator Ψ to perform compositional selection and instruction aggregation. For a source image $\mathbf{I}$, we sample a candidate concept subset $\{(c_n, m_n)\}_{n=1}^N$, where $c_n \in \mathcal{C}_{\text{lib}}$ is an edit concept and m_n is its corresponding edit region, and formalize the process as:

$$\Psi(\mathbf{I}, \{(c_n, m_n)\}_{n=1}^N) \mapsto (T_{\text{comp}}, V_{\text{comp}}, \{(c_k, m_k)\}_{k=1}^M), \quad \text{s.t. } m_i \cap m_j = \emptyset, \quad i \neq j, \quad M \leq N. \quad (2)$$

where M denotes the number of successfully selected concepts. In this formulation, the constraint $m_i \cap m_j = \emptyset$ is enforced on the output set to ensure that the selected edit regions are spatially disjoint, effectively preventing visual or conceptual interference. The mapping produces a single unified instruction T_{comp} , a global verification checklist V_{comp} , and the set of selected concept pairs $\{(c_k, m_k)\}_{k=1}^M$.

This approach strategically distributes edit points across disparate regions to achieve balanced spatial coverage, while strictly mitigating regional overlaps to prevent visual or conceptual interference. Such complex data synthesis is facilitated by the high-fidelity framework detailed in Sec. 3.2, where we perform single or multiple model invocations to sequentially or concurrently apply various modifications. Our instance-specific VQA filtering serves as a linchpin in this process. By leveraging customized queries V_{comp} , the system can rigorously verify the execution of each independent edit within the composite pair. This strategy functions as a form of spatial data compression, significantly increasing the information entropy per sample. By providing dense supervision signals within a single forward pass, the model is forced to allocate more representation capacity to learning structural transformations rather than background preservation, empirically accelerating convergence (Fig. 5) and enhancing performance for both single and multi concept editing tasks.

3.4 The ConceptEdit Benchmark

While existing benchmarks for instruction-based image editing, such as ImgEdit-Bench [18] and GEdit-Bench [10], have advanced the field, they focus on coarse-grained capabilities under 50 generic types. However, in practice, a high-level aggregate score often obfuscates critical model failures in complex or long-tail cases. For instance, a model may excel at general action changes but fail at precise gestures like a “finger heart.” To address this, ConceptEdit-Bench provides a “microscopic” view through over 1,000 fine-grained concepts, offering high controllability and modular diagnostic

Table 1: **Quantitative comparison and ablation study on the ImgEdit benchmark [18].** The models are trained on 2M and 5M data scales respectively. Abbreviations: Ext.: Extract, Rm.: Remove, Bg.: Background, Adj.: Adjust, Rep.: Replace, Act.: Action, Comp.: Compose. Δ Comp. Gain indicates the improvement brought by dense supervision (w/ Comp) over ConceptEdit₁₀₀₀. Δ Overall Gain highlights the total performance margin of our full framework over previous best-performing baseline (ScaleEdit). Best results per category at each scale are in bold.

Scale	Method	Fine-Grained Editing Categories									Overall
		Ext.	Add	Style	Rm.	Bg.	Adj.	Rep.	Act.	Comp.	
2M	UnicEdit	2.20	3.71	3.62	1.52	3.48	3.24	3.24	3.46	2.07	2.95
	ScaleEdit	2.10	3.71	4.35	3.22	2.86	2.70	3.57	3.58	2.42	3.17
	ConceptEdit ₁₀	2.18	3.82	3.61	2.00	3.51	3.27	2.69	3.83	2.53	3.05
	ConceptEdit ₅₀₀	2.19	4.02	4.49	2.46	3.58	3.66	2.43	3.78	2.75	3.26
	ConceptEdit ₁₀₀₀	2.17	3.96	4.55	2.71	3.49	3.59	3.33	3.63	2.52	3.33
	ConceptEdit ₁₀₀₀ w/ Comp	2.23	4.09	4.71	2.81	3.75	3.70	3.39	3.73	2.87	3.48
	Δ Comp. Gain	+0.06	+0.13	+0.16	+0.10	+0.26	+0.11	+0.06	+0.10	+0.35	+0.15
	Δ Overall Gain	+0.13	+0.38	+0.36	-0.41	+0.89	+1.00	-0.18	+0.15	+0.45	+0.31
5M	UnicEdit	2.26	3.80	3.70	2.22	3.57	3.40	2.89	4.01	2.62	3.16
	ScaleEdit	2.19	3.64	4.57	3.64	2.75	2.79	3.91	3.84	2.42	3.31
	ConceptEdit ₁₀	2.15	3.97	4.66	2.01	3.66	3.60	3.04	3.70	2.64	3.27
	ConceptEdit ₅₀₀	2.35	4.05	4.75	2.56	3.82	3.59	3.12	4.30	2.75	3.48
	ConceptEdit ₁₀₀₀	2.32	4.12	4.83	3.35	3.92	3.78	3.52	3.98	2.61	3.60
	ConceptEdit ₁₀₀₀ w/ Comp	2.50	4.24	4.78	3.46	3.75	3.98	3.78	4.23	3.04	3.75
	Δ Comp. Gain	+0.18	+0.12	-0.05	+0.11	-0.17	+0.20	+0.26	+0.25	+0.43	+0.15
	Δ Overall Gain	+0.31	+0.60	+0.21	-0.18	+1.00	+1.19	-0.13	+0.39	+0.62	+0.44

capability. Unlike benchmarks providing only a single aggregated score, our taxonomy allows selective monitoring of specific clusters of interest. This granular feedback is critical for iterative model development, enabling developers to precisely identify improvements in specific capabilities after training updates.

Leveraging our fine-grained concept library, we introduce ConceptEdit-Bench to test the limits of instruction-following precision. We selected 1,000 distinct editing categories from our library, ensuring that each represents a unique, fine-grained operation, such as distinguishing among a “smile,” “smirk,” and “laugh.” To guarantee broad visual distribution and high fidelity, source images are sampled from high-quality open-source datasets [33, 34], covering diverse categories. Benchmark results are provided in the Supplementary Appendix.

4 Experiments

4.1 Implementation Details

We conduct our experiments using the Z-Image [4] framework as our base model. We evaluate our method on ImgEdit-Bench and GEdit-Bench using training scales of 2M and 5M samples. To avoid confounding variables in ablations, all samples are synthesized using Qwen3.5-122B-A10B [35] (instructions/filtering) and FLUX.2-klein-9B [36] (image synthesis). We employ a constant learning rate of 1×10^{-5} and a total batch size of 512. Other hyperparameters remain fixed for fair comparison, unless otherwise specified.

4.2 Comparative Study

We evaluate ConceptEdit against UnicEdit and ScaleEdit, two advanced open-source datasets, the latter of which has established its superiority through standardized training evaluations. All models are assessed on ImgEdit-Bench [18] and GEdit-Bench [10] at 2M and 5M scales across diverse categories to measure overall editing capability. For the 5M scale, UnicEdit utilized repeated samples as only a portion of its data has been released.

As reported in Table 1, ConceptEdit_{1000 w/ Comp} consistently yields the highest overall scores on ImgEdit-Bench. At 2M and 5M scales, ConceptEdit achieves overall scores of 3.48 and 3.75, outperforming ScaleEdit by absolute margins of 0.31 and 0.44 points, respectively. ConceptEdit shows clear advantages in categories such as **Add**, **Style**, **Bg.**, and **Act.**. Similarly, results on GEdit-Bench (Table 2) demonstrate the consistent superiority of ConceptEdit across both English and Chinese evaluations. Notably, the performance boost is primarily attributed to the increased accuracy in instruction following (G_{SC}), which aligns with our theoretical expectations. These findings underscore the efficacy of scaling edit concepts to enhance model generalization.

4.3 Ablation Study

Effect of Concept Scaling To investigate the impact of edit concept diversity on model performance, we compare three variants of our dataset with increasing granularity: ConceptEdit₁₀, ConceptEdit₅₀₀, and ConceptEdit₁₀₀₀. On ImgEdit-Bench, scaling from 10 to 500 and 1,000+ categories improves 2M-scale scores from 3.05 to 3.26 and 3.33, respectively. At the 5M scale, ConceptEdit₁₀₀₀ (3.60) outperforms ConceptEdit₁₀ (3.27) by 0.33 points. GEdit-Bench

Table 2: **Quantitative comparison and ablation study on GEdit-Bench [10].** The models are evaluated at 2M and 5M training data scales. Δ Comp. Gain indicates the improvement brought by dense supervision (w/ Comp) over the baseline ConceptEdit₁₀₀₀. Δ Overall Gain highlights the performance margin of our full framework over the previous best baseline (ScaleEdit). Best results per metric at each scale are in bold.

Scale	Method	GEdit-Bench-EN			GEdit-Bench-CN		
		$G_{SC} \uparrow$	$G_{PQ} \uparrow$	$G_O \uparrow$	$G_{SC} \uparrow$	$G_{PQ} \uparrow$	$G_O \uparrow$
2M	UnicEdit	4.87	7.03	4.79	4.83	7.00	4.65
	ScaleEdit	5.30	6.79	5.38	5.33	6.66	5.25
	ConceptEdit ₁₀	5.34	6.76	5.41	5.54	7.03	5.15
	ConceptEdit ₅₀₀	5.90	7.13	5.54	5.51	6.70	5.45
	ConceptEdit ₁₀₀₀	5.91	6.76	5.48	5.87	7.00	5.48
	ConceptEdit ₁₀₀₀ w/ Comp	6.34	6.79	5.81	6.32	6.93	5.83
	Δ Comp. Gain	+0.43	+0.03	+0.33	+0.45	-0.07	+0.35
	Δ Overall Gain	+1.04	+0.00	+0.43	+0.99	+0.27	+0.58
5M	UnicEdit	5.39	7.17	5.25	5.32	7.13	5.07
	ScaleEdit	5.77	6.69	5.77	5.62	6.97	5.63
	ConceptEdit ₁₀	5.91	6.93	5.93	5.83	7.00	5.81
	ConceptEdit ₅₀₀	6.84	7.00	6.30	6.80	7.05	6.31
	ConceptEdit ₁₀₀₀	6.86	7.19	6.40	6.75	7.31	6.36
	ConceptEdit ₁₀₀₀ w/ Comp	7.07	7.30	6.62	7.07	7.42	6.60
	Δ Comp. Gain	+0.21	+0.11	+0.22	+0.32	+0.11	+0.24
	Δ Overall Gain	+1.30	+0.61	+0.85	+1.45	+0.45	+0.97

corroborates this trend. At the 5M scale, moving from 10 to 500 concepts boosts G_{SC} for English (5.91 to 6.84) and Chinese (5.83 to 6.80) evaluations, with ConceptEdit₁₀₀₀ maintaining these levels. These gains span tasks like **Style**, **Adj.**, and **Rep.**, proving that fine-grained concept distribution effectively outperforms naive scaling with coarse instructions.

Effect of Dense Supervision To evaluate dense supervision, we mix ConceptEdit₁₀₀₀ with composite edits in a 1:1 ratio. As shown in Table 1, this composition consistently improves ImgEdit-Bench scores by 0.15 points across scales. These gains extend beyond the **Comp.** task, boosting categories like **Adj.** (+0.20), **Rep.** (+0.26), and **Act.** (+0.25) at the 5M scale. On GEdit-Bench-EN, the G_{SC} score at the 2M scale corroborates this with a Δ Comp. Gain of up to 0.43 points, confirming that learning from spatially non-interfering composite edits improves core visual understanding. Furthermore, matching the w/ Comp performance without composite data requires $1.5\times$ more samples (Fig. 5). This validates that compositional edits provide dense supervision, significantly compressing training time.

Table 3: Ablation study of our VQA filtering pipeline.

Filtering Strategy	Precision (%)	Recall (%)	F1-Score (%)	Accuracy (%)
Pseudo GT (Gemini)	100.0	100.0	100.0	100.0
Generic Validation	75.0	57.0	65.0	90.0
Instance-Specific (Ours)	84.0	87.0	86.0	95.0
Δ Gain	$\uparrow 9.0$	$\uparrow 30.0$	$\uparrow 21.0$	$\uparrow 5.0$

Effect of VQA Filtering To ensure high fidelity alignment and suppress hallucinations, we compare our instance-specific VQA filtering against a generic VLM validation baseline. While the baseline uses uniform prompts for holistic assessment, the ConceptEdit pipeline dynamically formulates fine-grained questions tailored to specific edit concepts (e.g., checking for localized artifacts). Metrics are evaluated against pseudo-labels from Gemini-3-Pro [37]. As shown in Table 3, our VQA pipeline significantly outperforms the baseline, boosting Precision, Recall, F1-score, and Accuracy by 9.0%, 30.0%, 21.0%, and 5.0%, respectively. While generic validation often overlooks subtle failures due to salient object bias, our region-aware verification successfully detects localized artifacts. This customized approach proves highly effective at identifying hallucinations, ensuring high-quality training data.

5 Conclusion

This work addresses the lack of edit concept granularity and sparse training signals in instruction-based image editing. We introduce ConceptEdit, a structured paradigm emphasizing edit concept scaling and dense supervision. Specifically, we build a 1,000-category hierarchical taxonomy and leverage composite edits for training. Our experiments show that granular edit concepts significantly enhance editing capabilities across diverse scenarios. Additionally, dense supervision accelerates training convergence by $1.5\times$ and boosts performance on single-concept tasks. Our instance-specific VQA filtering also reduces errors compared to generic validation. Finally, we present the ConceptEdit-12M dataset and ConceptEdit-Bench. This suite achieves SOTA results, outperforming existing baselines like ScaleEdit and UnicEdit.

References

- [1] Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *CVPR*, 2022.
- [2] Chenfei Wu, Jiahao Li, Jingren Zhou, Junyang Lin, Kaiyuan Gao, Kun Yan, Sheng-ming Yin, Shuai Bai, Xiao Xu, Yilei Chen, et al. Qwen-image technical report. *arXiv preprint arXiv:2508.02324*, 2025.
- [3] Qi Qin, Le Zhuo, Yi Xin, Ruoyi Du, Zhen Li, Bin Fu, Yiting Lu, Xinyue Li, Dongyang Liu, Xiangyang Zhu, et al. Lumina-image 2.0: A unified and efficient image generative framework. In *Int. Conf. Comput. Vis.*, 2025.
- [4] Huanqia Cai, Sihan Cao, Ruoyi Du, Peng Gao, Steven Hoi, Zhaohui Hou, Shijie Huang, Dengyang Jiang, Xin Jin, Liangchen Li, et al. Z-image: An efficient image generation foundation model with single-stream diffusion transformer. *arXiv preprint arXiv:2511.22699*, 2025.
- [5] Meituan LongCat Team, Hanghang Ma, Haoxian Tan, Jiale Huang, Junqiang Wu, Jun-Yan He, Lishuai Gao, Songlin Xiao, Xiaoming Wei, Xiaoqi Ma, et al. Longcat-image technical report. *arXiv preprint arXiv:2512.07584*, 2025.
- [6] Google DeepMind. Nano banana: Gemini ai image generator and photo editor. <https://gemini.google/overview/image-generation/>, 2025.
- [7] OpenAI. Introducing 4o image generation. <https://openai.com/index/introducing-4o-image-generation/>, March 2025.
- [8] Yichun Shi, Peng Wang, and Weilin Huang. Seedit: Align image re-generation to image editing. *arXiv preprint arXiv:2411.06686*, 2024.
- [9] Black Forest Labs, Stephen Batifol, Andreas Blattmann, Frederic Boesel, Saksham Consul, Cyril Diagne, Tim Dockhorn, Jack English, Zion English, Patrick Esser, Sumith Kulal, Kyle Lacey, Yam Levi, Cheng Li, Dominik Lorenz, Jonas Müller, Dustin Podell, Robin Rombach, Harry Saini, Axel Sauer, and Luke Smith. Flux.1 kontext: Flow matching for in-context image generation and editing in latent space. *arXiv preprint arXiv:2506.15742*, 2025.
- [10] Shiyu Liu, Yucheng Han, Peng Xing, Fukun Yin, Rui Wang, Wei Cheng, Jiaqi Liao, Yingming Wang, Honghao Fu, Chunrui Han, Guopeng Li, Yuang Peng, Quan Sun, Jingwei Wu, Yan Cai, Zheng Ge, Ranchen Ming, Lei Xia, Xianfang Zeng, Yibo Zhu, Binxing Jiao, Xiangyu Zhang, Gang Yu, and Daxin Jiang. Step1x-edit: A practical framework for general image editing. *arXiv preprint arXiv:2504.17761*, 2025.
- [11] Yi Xin, Qi Qin, Siqi Luo, Kaiwen Zhu, Juncheng Yan, Yan Tai, Jiayi Lei, Yuwen Cao, Keqi Wang, Yibin Wang, et al. Lumina-dimoo: An omni diffusion large language model for multi-modal generation and understanding. *arXiv preprint arXiv:2510.06308*, 2025.
- [12] OpenAI. DALL·E 3. <https://openai.com/research/dall-e-3>, September 2023.
- [13] Patrick Esser, Sumith Kulal, Andreas Blattmann, Rahim Entezari, Jonas Müller, Harry Saini, Yam Levi, Dominik Lorenz, Axel Sauer, Frederic Boesel, Dustin Podell, Tim Dockhorn, Zion English, Kyle Lacey, Alex Goodwin, Yannik Marek, and Robin Rombach. Scaling rectified flow transformers for high-resolution image synthesis, 2024. URL <https://arxiv.org/abs/2403.03206>.
- [14] Dustin Podell, Zion English, Kyle Lacey, Andreas Blattmann, Tim Dockhorn, Jonas Müller, Joe Penna, and Robin Rombach. Sdxl: Improving latent diffusion models for high-resolution image synthesis, 2023. URL <https://arxiv.org/abs/2307.01952>.
- [15] Cong Wei, Zheyang Xiong, Weiming Ren, Xinrun Du, Ge Zhang, and Wenhui Chen. Omniedit: Building image editing generalist models through specialist supervision. *arXiv preprint arXiv:2411.07199*, 2024.
- [16] Qifan Yu, Wei Chow, Zhongqi Yue, Kaihang Pan, Yang Wu, Xiaoyang Wan, Juncheng Li, Siliang Tang, Hanwang Zhang, and Yueting Zhuang. Anyedit: Mastering unified high-quality image editing for any idea. *arXiv preprint arXiv:2411.15738*, 2024.
- [17] Haozhe Zhao, Xiaojian Shawn Ma, Liang Chen, Shuzheng Si, Rujie Wu, Kaikai An, Peiyu Yu, Minjia Zhang, Qing Li, and Baobao Chang. Ultraedit: Instruction-based fine-grained image editing at scale. *Advances in Neural Information Processing Systems*, 37:3058–3093, 2024.
- [18] Yang Ye, Xianyi He, Zongjian Li, Bin Lin, Shenghai Yuan, Zhiyuan Yan, Bohan Hou, and Li Yuan. Imgedit: A unified image editing dataset and benchmark. *arXiv preprint arXiv:2505.20275*, 2025.
- [19] Keming Ye, Zhipeng Huang, Canmiao Fu, Qingyang Liu, Jiani Cai, Zheqi Lv, Chen Li, Jing Lyu, Zhou Zhao, and Shengyu Zhang. Unicedit-10m: A dataset and benchmark breaking the scale-quality barrier via unified verification for reasoning-enriched edits, 2025. URL <https://arxiv.org/abs/2512.02790>.
- [20] Guanzhou Chen, Erfei Cui, Changyao Tian, Danni Yang, Ganlin Yang, Yu Qiao, Hongsheng Li, Gen Luo, and Hongjie Zhang. Scaleedit-12m: Scaling open-source image editing data generation via multi-agent framework, 2026. URL <https://arxiv.org/abs/2603.20644>.
- [21] Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altmenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023.
- [22] Google. Gemini. Large-scale multimodal model, 2024. URL <https://deepmind.google/technologies/gemini/>. Gemini 1.5 Flash version.
- [23] Dustin Podell, Zion English, Kyle Lacey, Andreas Blattmann, Tim Dockhorn, Jonas Müller, Joe Penna, and Robin Rombach. Sdxl: Improving latent diffusion models for high-resolution image synthesis. *arXiv preprint arXiv:2307.01952*, 2023.

- [24] Tim Brooks, Aleksander Holynski, and Alexei A Efros. Instructpix2pix: Learning to follow image editing instructions. In *CVPR*, 2023.
- [25] Chaorui Deng, Deyao Zhu, Kunchang Li, Chenhui Gou, Feng Li, Zeyu Wang, Shu Zhong, Weihao Yu, Xiaonan Nie, Ziang Song, Guang Shi, and Haoqi Fan. Emerging properties in unified multimodal pretraining. *arXiv preprint arXiv:2505.14683*, 2025.
- [26] Yufeng Cui, Honghao Chen, Haoge Deng, Xu Huang, Xinghang Li, Jirong Liu, Yang Liu, Zhuoyan Luo, Jinsheng Wang, Wenxuan Wang, et al. Emu3.5: Native multimodal models are world learners. *arXiv preprint arXiv:2510.26583*, 2025.
- [27] Changyao Tian, Danni Yang, Guanzhou Chen, Erfei Cui, Zhaokai Wang, Yuchen Duan, Penghao Yin, Sitao Chen, Ganlin Yang, Mingxin Liu, et al. Internvl-u: Democratizing unified multimodal models for understanding, reasoning, generation and editing. *arXiv preprint arXiv:2603.09877*, 2026.
- [28] Inclusion AI, Tiwei Bie, Haoxing Chen, Tiejuan Chen, Zhenglin Cheng, Long Cui, Kai Gan, Zhicheng Huang, Zhenzhong Lan, Haoquan Li, Jianguo Li, Tao Lin, Qi Qin, Hongjun Wang, Xiaomei Wang, Haoyuan Wu, Yi Xin, and Junbo Zhao. Llada2.0-uni: Unifying multimodal understanding and generation with diffusion large language model, 2026. URL <https://arxiv.org/abs/2604.20796>.
- [29] OpenAI. GPT-4o. Large-scale multimodal model, May 2024. URL <https://openai.com/index/hello-gpt-4o/>. May 13, 2024 version.
- [30] Kai Zhang, Lingbo Mo, Wenhui Chen, Huan Sun, and Yu Su. Magicbrush: A manually annotated dataset for instruction-guided image editing, 2024. URL <https://arxiv.org/abs/2306.10012>.
- [31] Maksim Kuprashevich, Grigorii Alekseenko, Irina Tolstykh, Georgii Fedorov, Bulat Suleimanov, Vladimir Dokholyan, and Aleksandr Gordeev. Nohumansrequired: Autonomous high-quality image editing triplet mining, 2025. URL <https://arxiv.org/abs/2507.14119>.
- [32] Mude Hui, Siwei Yang, Bingchen Zhao, Yichun Shi, Heng Wang, Peng Wang, Yuyin Zhou, and Cihang Xie. Hq-edit: A high-quality dataset for instruction-based image editing, 2024. URL <https://arxiv.org/abs/2404.09990>.
- [33] Alina Kuznetsova, Hassan Rom, Neil Alldrin, Jasper Uijlings, Ivan Krasin, Jordi Pont-Tuset, Shahab Kamali, Stefan Popov, Matteo Mallocci, Alexander Kolesnikov, et al. The open images dataset v4: Unified image classification, object detection, and visual relationship detection at scale. *IJCV*, 128(7):1956–1981, 2020.
- [34] Xu Ma, Yitian Zhang, Qihua Dong, and Yun Fu. Fine-t2i: An open, large-scale, and diverse dataset for high-quality t2i fine-tuning, 2026. URL <https://arxiv.org/abs/2602.09439>.
- [35] Qwen Team. Qwen3.5. <https://huggingface.co/collections/Qwen/qwen35>, 2026.
- [36] Black Forest Labs. Flux.2-klein. <https://huggingface.co/collections/black-forest-labs/flux2>, 2026.
- [37] Google. Gemini. Large-scale multimodal model, 2025. URL <https://aistudio.google.com/models/gemini-3>. Gemini 3.0 pro version.
- [38] John Canny. A computational approach to edge detection. *IEEE Trans. Pattern Anal. Mach. Intell.*, 1986.
- [39] Saining Xie and Zhuowen Tu. Holistically-nested edge detection. In *IEEE Conf. Comput. Vis. Pattern Recog.*, 2015.
- [40] Geonmo Gu, Byungsoo Ko, SeoungHyun Go, Sung-Hyun Lee, Jingeun Lee, and Minchul Shin. Towards light-weight and real-time line segment detection. In *AAAI*, 2022.
- [41] Kunchang Li, Yali Wang, Junhao Zhang, Peng Gao, Guanglu Song, Yu Liu, Hongsheng Li, and Yu Qiao. Uniformer: Unifying convolution and self-attention for visual recognition. *IEEE Trans. Pattern Anal. Mach. Intell.*, 2023.
- [42] Lihe Yang, Bingyi Kang, Zilong Huang, Zhen Zhao, Xiaogang Xu, Jiashi Feng, and Hengshuang Zhao. Depth anything v2. *arXiv:2406.09414*, 2024.
- [43] Haofei Xu, Jing Zhang, Jianfei Cai, Hamid Reza Tofighi, Fisher Yu, Dacheng Tao, and Andreas Geiger. Unifying flow, stereo and depth estimation. *IEEE Trans. Pattern Anal. Mach. Intell.*, 2023.
- [44] Z. Cao, G. Hidalgo Martinez, T. Simon, S. Wei, and Y. A. Sheikh. Openpose: Realtime multi-person 2d pose estimation using part affinity fields. *IEEE Trans. Pattern Anal. Mach. Intell.*, 2019.
- [45] Kai Zhang, Lingbo Mo, Wenhui Chen, Huan Sun, and Yu Su. Magicbrush: A manually annotated dataset for instruction-guided image editing. *Advances in Neural Information Processing Systems*, 36:31428–31449, 2023.
- [46] Yuying Ge, Sijie Zhao, Chen Li, Yixiao Ge, and Ying Shan. Seed-data-edit technical report: A hybrid dataset for instructional image editing. *arXiv preprint arXiv:2405.04007*, 2024.
- [47] Maksim Kuprashevich, Grigorii Alekseenko, Irina Tolstykh, Georgii Fedorov, Bulat Suleimanov, Vladimir Dokholyan, and Aleksandr Gordeev. Nohumansrequired: Autonomous high-quality image editing triplet mining. *arXiv preprint arXiv:2507.14119*, 2025.
- [48] Yuhan Wang, Siwei Yang, Bingchen Zhao, Letian Zhang, Qing Liu, Yuyin Zhou, and Cihang Xie. Gpt-image-edit-1.5 m: A million-scale, gpt-generated image dataset. *arXiv preprint arXiv:2507.21033*, 2025.
- [49] Meituan LongCat Team, Hanghang Ma, Haoxian Tan, Jiale Huang, Junqiang Wu, Jun-Yan He, Lishuai Gao, Songlin Xiao, Xiaoming Wei, Xiaoqi Ma, Xunliang Cai, Yayong Guan, and Jie Hu. Longcat-image technical report, 2025. URL <https://arxiv.org/abs/2512.07584>.
- [50] Super Intelligence Team, Changhao Qiao, Chao Hui, Chen Li, Cunzheng Wang, Dejia Song, Jiale Zhang,

Jing Li, Qiang Xiang, Runqi Wang, Shuang Sun, Wei Zhu, Xu Tang, Yao Hu, Yibo Chen, Yuhao Huang, Yuxuan Duan, Zhiyi Chen, and Ziyuan Guo. Firered-image-edit-1.0 technical report, 2026. URL <https://arxiv.org/abs/2602.13344>.

- [51] Team Seedream, :, Yunpeng Chen, Yu Gao, Lixue Gong, Meng Guo, Qiushan Guo, Zhiyao Guo, Xiaoxia Hou, Weilin Huang, Yixuan Huang, Xiaowen Jian, Huafeng Kuang, Zhichao Lai, Fanshi Li, Liang Li, Xiaochen Lian, Chao Liao, Liyang Liu, Wei Liu, Yanzuo Lu, Zhengxiong Luo, Tongtong Ou, Guang Shi, Yichun Shi, Shiqi Sun, Yu Tian, Zhi Tian, Peng Wang, Rui Wang, Xun Wang, Ye Wang, Guofeng Wu, Jie Wu, Wenxu Wu, Yonghui Wu, Xin Xia, Xuefeng Xiao, Shuang Xu, Xin Yan, Ceyuan Yang, Jianchao Yang, Zhonghua Zhai, Chenlin Zhang, Heng Zhang, Qi Zhang, Xinyu Zhang, Yuwei Zhang, Shijia Zhao, Wenliang Zhao, and Wenjia Zhu. Seedream 4.0: Toward next-generation multimodal image generation, 2025. URL <https://arxiv.org/abs/2509.20427>.

Supplementary Material

A Discussion on Generalized I2I Translation

Conceptually, any image-to-image (I2I) translation can be viewed as a generalized form of image editing, where the source image serves as a structural condition and the text instruction specifies the target domain mapping.

Our taxonomy of 1,000+ concepts primarily targets daily, user-centric interactive editing. We do not exhaustively categorize highly specialized or structural translation tasks, as they are typically treated as professional rendering or conditional generation rather than common interactive edits.

Nonetheless, to ensure broad scenario coverage and evaluate our model’s adaptability, we incorporate a representative subset of classic structural tasks into our dataset, including:

- Canny edges [38]
- HED edges [39]
- Hough lines [40]
- Semantic segmentation maps [41]
- Depth maps [42]
- Shape normal maps [43]
- Human keypoints [44]

This integration demonstrates that our framework remains robust and compatible with traditional, structurally constrained image translation paradigms.

As illustrated in Fig. 6, our dataset effectively supports these structurally conditioned transformations.



Figure 6: Visualizations of generalized image-to-image translation under various structural control signals.

B Detailed Ablation on VQA Filtering Strategy

Table 4 presents the complete ablation results of our VQA filtering pipeline, including the raw confusion matrix counts.

By dynamically formulating tailored questions, our instance-specific strategy significantly reduces False Negatives (FN) from 72 to 21 and increases True Positives (TP) from 95 to 146 compared to the generic validation baseline. This targeted, region-aware verification effectively suppresses subtle edit failures, resulting in substantial gains across all metrics: +9.0% in Precision, +30.0% in Recall, +21.0% in F1-Score, and +5.0% in Accuracy.

We also evaluate the per-sample computational overhead on Qwen3.5-122B-A10B. As shown in Table 5, our instance-specific strategy incurs only a marginal total overhead of +0.069s per sample. Crucially, the entire data synthesis pipeline is heavily dominated by the DiT image generation phase, whereas the instruction generation and filtering stages together account for merely 2%–10% of the total runtime (depending on the image generation model used).

Table 4: Detailed ablation of our VQA filtering pipeline, including raw confusion matrix counts.

Metric	Ground Truth	Generic	Ours	Δ Gain
TN	833	802	805	–
FN	0	72	21	–
TP	167	95	146	–
FP	0	31	28	–
Precision (%)	100.0	75.0	84.0	$\uparrow$ 9.0
Recall (%)	100.0	57.0	87.0	$\uparrow$ 30.0
F1-Score (%)	100.0	65.0	86.0	$\uparrow$ 21.0
Accuracy (%)	100.0	90.0	95.0	$\uparrow$ 5.0

Table 5: Per-sample processing latency (seconds) benchmarked on Qwen3.5-122B-A10B.

Stage	Generic	Ours	Overhead
Instruction Generation	0.523s	0.567s	+0.044s
Filtering Stage	0.312s	0.337s	+0.025s
Total	0.835s	0.904s	+0.069s

C Dataset Comparison

As compared in Table 6, we evaluate our proposed ConceptEdit dataset against existing mainstream image editing datasets across multiple dimensions. The comparison highlights several key advantages of ConceptEdit: First, it significantly scales up both data volume and task diversity, containing 12 million editing pairs across over 1,000 subtasks, which far exceeds the maximum of 23 found in previous datasets. Second, ConceptEdit establishes a more rigorous quality control pipeline. Notably, it is the only dataset that incorporates instance-specific filtering, which ensures high-fidelity alignment between editing instructions and visual changes. Third, it comprehensively supports both basic and complex editing scenarios, providing a more versatile resource for the community. Lastly, ConceptEdit is the only dataset that features distribution control, allowing for a more balanced and controllable training.

D Model Performance on ConceptEdit-Bench

Table 7 presents a comprehensive evaluation of mainstream models on ConceptEdit-Bench. Closed-source models demonstrate strong performance, with Nano Banana 2 achieving the highest overall score of 66.19, while Seedream 4.5 records a score of 63.34. Within the open-source category, FireRed-Image-Edit-1.0 leads with a score of 65.86. A primary observation is that although most models successfully follow basic instructions, nearly all experience a notable decline in the Portrait and Composition categories. This indicates a general difficulty in performing edits that rely on detailed world knowledge, such as micro-expressions, or sophisticated spatial reasoning. Such findings highlight the value of our high-quality dataset and structured synthesis framework in addressing these persistent challenges.

Table 6: Comparison of Image Editing datasets.

Dataset	Sub-tasks	Size	Post Verification			Basic Edit	Complex Edit	Dist. Control
			Failed Filtration	Inst.-Spec. Filtering	Recaption			
MagicBrush [45]	5	~10K	✓	✗	✗	✓	✗	✗
InstructPix2Pix [24]	4	~313K	✗	✗	✗	✓	✗	✗
HQ-Edit [32]	6	~197K	✗	✗	✓	✓	✗	✗
SEED-Data-Edit [46]	6	~3.7M	✓	✗	✗	✓	✗	✗
UltraEdit [17]	9	~4M	✗	✗	✗	✓	✗	✗
ImgEdit [18]	13	~1.2M	✓	✗	✗	✓	✓	✗
NHR-Edit [47]	-	~358K	✓	✗	✗	✓	✗	✗
GPT-Image-Edit-1.5M [48]	-	~1.5M	✗	✗	✓	✓	✗	✗
UnicEdit [19]	22	~10M	✓	✗	✓	✓	✓	✗
ScaleEdit [20]	23	~12M	✓	✗	✗	✓	✓	✗
ConceptEdit	1000	~12M	✓	✓	✓	✓	✓	✓

Table 7: Quantitative comparison on ConceptEdit-Bench. The “Overall” column represents the final aggregated performance across our 1,000 fine-grained categories.

Model	Advanced	Object	Compo.	Global	Portrait	Text	Overall
Open-source Models							
BAGEL-7B-MoT [25]	42.21	46.12	38.85	44.90	41.10	33.91	41.66
FLUX.1-Kontext-dev [9]	50.73	42.88	44.45	49.05	37.36	40.15	43.53
LongCat-Image-Edit [49]	64.06	61.46	57.51	65.39	51.68	62.08	59.05
Qwen-Image-Edit-2509 [2]	67.36	63.83	58.37	64.59	54.27	69.85	61.27
Qwen-Image-Edit-2511 [2]	66.78	68.45	60.38	70.39	53.75	73.50	63.29
FireRed-Image-Edit-1.0 [50]	70.12	72.40	63.52	71.21	56.42	74.72	65.86
Closed-source Models							
Seedream 4.5 [51]	69.10	68.00	63.62	68.60	52.90	71.32	63.34
Nano Banana 2 [6]	71.82	73.90	64.15	70.01	56.24	75.28	66.19

E Semantic Overlap Across Categories

In constructing our 1,000+ fine-grained edit taxonomy, we deliberately permit moderate semantic overlaps across different high-level categories rather than enforcing strict mutual exclusion. We consider that such concept overlap across categories is largely harmless to the overall dataset distribution and can inherently enhance instructional and visual diversity.

Specifically, we view a single visual attribute or physical primitive as carrying distinct operational semantics depending on its underlying intent and editing context. For instance, in our framework, the concept of “neon lighting” naturally manifests across multiple categories with subtle functional nuances: in Style Transfer, it serves as a holistic stylistic constraint governing global aesthetics; in Environmental Simulation, it acts as a plausible ambient atmospheric element; and in Global Relighting, it functions as an explicit light source manipulation that dictates surface reflections and shadow interactions.

In our view, strictly purging these intersections might impose artificial boundaries that decouple concepts from their real-world contexts. We hypothesize that retaining them allows the dataset to expose the model to identical visual primitives under varied instructional phrasing and generative

goals, thereby mitigating rote pattern matching and encouraging greater model flexibility.

F Rationale for Downstream Evaluation

While evaluating datasets via single-image aesthetic scores is an intuitive alternative, we deliberately prioritize downstream model training performance as our primary evaluation protocol.

We consider that the core value of our dataset lies in its *macro-level distribution richness*, *conceptual balance*, and *task coverage*, rather than merely maximizing the visual polish of isolated samples. A dataset containing aesthetically pleasing images can still suffer from severe distribution collapse if it lacks diverse edit operations. Because single-image aesthetic scores fail to measure conceptual diversity or instruction alignment, in our view, downstream training gains provide a far more rigorous indicator of dataset utility and real-world generalization.

G Hardware and Computing Infrastructure

All model training is conducted on NVIDIA H100 GPUs. Data synthesis, VQA filtering, and benchmark evaluations are performed on NVIDIA H20 GPUs. The entire frame-

work is implemented in PyTorch and executed within a Linux environment.

H Dataset and Code Availability

The ConceptEdit dataset, evaluation benchmark, and source code will be publicly released prior to or upon paper publication.

I Concept Library

Our concept library is organized as a three-level taxonomy consisting of 1028 fine-grained edit concepts. The hierarchy below lists all leaf concepts in the library.

1. Global Enhancement and Atmosphere

Image Restoration and Enhancement

Super Resolution

- Image Upscaling
- Anime Super-Resolution
- Screenshot Repair
- Hair Detail Restoration
- Night Scene Clarity
- Old Photo Restoration
- Text Sharpening
- Facial Detail Reconstruction
- Lossless Zoom

Denoise Deblur

- Motion Blur Removal
- Out-of-Focus Repair
- High ISO Denoising
- Moire Pattern Removal
- Smart Sharpening
- Night Sight Clarity
- Face Deblur
- Camera Shake Correction
- Lens Blur Removal
- Film Grain Removal
- Dehaze
- Edge Enhancement
- Screen Pattern Removal
- Background Denoising

Exposure Color

- Low Light Enhancement
- Overexposure Repair
- Dehaze
- HDR Effect
- Tone Unification
- Backlight Correction
- Color Cast Removal
- Shadow & Highlight Recovery
- Contrast Enhancement
- Color Match
- Skin Tone Correction
- Vibrance & Saturation
- Brightness Adjustment
- Faded Color Restoration
- Cinematic Color Grading

Atmosphere and Style

Background Manipulation

- Remove background
- Blur background
- E-commerce white background
- ID photo blue
- Gradient background
- Desaturate background
- Sky replacement
- Studio lighting
- Wooden tabletop
- Nature landscape
- Office interior
- Instagram style
- Minimalist geometry
- Abstract art
- Transparent background
- Bokeh effect
- Solid black background
- ID photo red
- Morandi colors
- Darken background
- Product podium
- Marble texture
- Silk background
- City street
- Home interior
- Cyberpunk background
- Holiday atmosphere

Environmental Simulation

- Sunny
- Overcast
- Heavy rain
- Rainbow
- Blizzard
- Frost
- Heavy fog
- Haze
- Windy
- Sunset
- Blue hour
- Starry sky
- Aurora
- Lens flare
- Fireflies
- Floating dust
- Puddle reflections
- Summer vibe
- Winter chill
- Post-apocalyptic
- Gloomy atmosphere
- Cloudy
- Light rain
- Thunderstorm
- Light snow
- Snow accumulation
- Icy surface
- Mist
- Sandstorm
- Sunrise
- Golden hour
- Midnight
- Moonlight
- God rays
- Bokeh effects
- Falling petals
- Wet pavement
- Spring bloom
- Autumn leaves
- Cyberpunk neon
- Dreamy atmosphere
- Underwater caustics

Style Transfer

- Oil Painting Style
- Pencil Sketch
- Ukiyo-e Style
- Classic Art/Renaissance
- Steampunk
- 3D Cartoon/Pixar Style
- American Comic Style
- Low Poly
- Glitch Art
- Pop Art
- Paper Cut/Origami
- Mosaic Art
- Vintage Film/Retro
- Watercolor Style
- Chinese Ink Wash
- Impressionism/Van Gogh
- Cyberpunk
- Pixel Art
- Ghibli/Anime Style
- Flat Illustration
- Claymation
- Vaporwave
- Graffiti/Street Art
- Stained Glass
- Neon Noir
- Film Noir/High Contrast B&W
- Game CG/Concept Art
- Woodblock Print
- Makoto Shinkai Style
- Relief/Emboss Style
- Fantasy Fairy Tale
- Rococo
- Chalk Drawing
- Polaroid Style
- Memphis Design
- Crayon/Doodle Style
- Line Art
- Charcoal Drawing
- Lego/Block Style
- Gothic Dark Style
- Wasteland Style
- Surrealism
- Voxel Art
- Acid Graphics
- Mechanical/Metallic Style

Global Relighting

- Change Light Direction
- Blue Hour
- Noon Sunlight
- Moonlight
- Butterfly Lighting
- Studio Soft Light
- Window Light
- Cinematic Lighting
- Candlelight Atmosphere
- Underwater Caustics
- Remove Shadows
- Match Background Lighting
- Side Backlight
- Golden Hour
- Sunset Glow
- Overcast Soft Light
- Rembrandt Lighting
- Rim Light
- Spotlight/Hard Light
- Neon Lighting
- Volumetric Rays (God Rays)
- Stage Lighting
- Face Fill Light
- Cast Shadows
- Silhouette Effect

2. General Object and Entity Editing

Object Management and Manipulation

Add Remove Object

- Remove passersby
- Remove power lines
- Remove vehicles
- Remove street signs
- Remove jewelry
- Remove reflections
- Add furniture
- Add decorations
- Add accessories
- Generative fill
- Generate in area
- Universal Removal
- Remove clutter
- Remove fences
- Remove trash
- Remove glasses
- Remove tattoos
- Remove shadows
- Add plants
- Add animals
- Add props
- Magic eraser
- Universal Addition

Replace Object

- Text-Guided Replacement
- Keep Shape Replacement
- Swap Object Positions
- Replace Furniture
- Replace Plants & Flowers
- Replace Handheld Objects
- Replace Food & Drinks
- Replace Signage
- Replace Background Props
- Replace Character Subject
- Replace Buildings
- Replace Sky
- Reference Image Replacement
- Free Form Replacement
- Generate Variations
- Replace Decor
- Replace Vehicles
- Replace Wall Art & Posters
- Replace Electronics
- Replace Packaging
- Replace Animals
- Replace Sculptures
- Replace Ground Surface
- Universal Replacement and Modification

Spatial Geometric

- Move Position
- 2D Rotate
- Flip Vertical
- 3D Object Rotation
- Bring Object Closer
- Straighten Object
- Mesh Transform
- Resize
- Flip Horizontal
- Change Object Facing
- Perspective Correction
- Push Object Back
- Free Warp
- Match Background Perspective
- Non-rigid Deformation
- Center Object
- Adjust Tilt Angle

Matting Layer

- One-click Background Removal
- Portrait Matting
- Refine Hair Details
- Split Foreground & Background
- Extract Sky
- Vehicle Cutout
- Head/Face Cutout
- Generate Alpha Mask
- Make Background Transparent
- Product Cutout
- Pet & Animal Cutout
- ID Photo Cutout
- Extract Text or Logo
- Clothing Segmentation
- Smart Object Selection
- Edge Refinement & Smoothing
- Food Cutout
- Batch Matting
- Green/Blue Screen Keying
- Complex Background Matting

Object Attribute Refinement

Color Material

- Precise local recoloring
- Change clothing fabric color
- Product color variant generation
- Reference color transfer
- Turn into silver chrome
- Turn into jade gemstone
- Turn into solid wood
- Turn into leather texture
- Turn into denim fabric
- Turn into knitted wool
- Turn into neon glowing
- Turn into LEGO bricks
- Turn into clay plasticine
- Apply glossy polish
- Add floral pattern
- Material aging weathering
- Smart object recoloring
- Change vehicle color
- Colorize black & white photo
- Turn into gold material
- Turn into transparent glass
- Turn into marble texture
- Turn into ceramic glaze
- Turn into silk satin
- Turn into plush fur
- Turn into rusty metal
- Turn into jelly gummy
- Turn into origami paper
- Apply matte finish
- Add camouflage pattern
- Add geometric plaid

Detail Refinement

- Remove wrinkles
- Remove stains
- Remove fingerprints
- Remove moire patterns
- Repair cracks
- Smooth edges
- Remove mold
- Enhance texture
- Remove sticker residue
- Metal polishing
- Glass repair
- Remove scratches
- Remove dust
- Remove glare
- Remove lint/pilling
- Repair damage
- Remove rust
- Remove local shadows
- Repair peeling paint
- Leather repair
- Ceramic repair
- Red-eye removal

3. Portrait and Human-Centered Editing

Face Editing

Beauty Makeup

- Auto Skin Smoothing
- Acne & Blemish Removal
- Remove Nasolabial Folds
- Remove Neck Lines
- Pore Minimizer
- Tanning
- Small Face
- Cheekbone Reduction
- Chin Reshaping
- Skin Whitening
- Remove Dark Circles
- Remove Tear Troughs
- Remove Shine/Oiliness
- Skin Tone Temperature
- Slim Face
- Jawline Definition
- Temple Filling
- Forehead Height Adjustment
- Enlarge Eyes
- Eye Distance Adjustment
- Double Eyelid Generation
- Red Eye Removal
- Nose Bridge Lift
- Nose Tip Reshaping
- Lip Plumping
- Teeth Whitening
- Lip Shape Adjustment
- Face Highlighting
- Eyebrow Density
- Lower Eyelid Down
- Hairline Filling
- Eye Brightening
- Eye Tilt/Angle
- Aegyo-sal (Under-eye fat)
- Slim Nose
- Nostril Reduction
- Philtrum Shortening
- Smile Lift
- Teeth Correction
- 3D Contouring
- Eyebrow Reshaping
- Eyelash Extension
- Facial Asymmetry Correction

Facial Attributes

- Make older
- Baby face
- Add bangs
- Short hair
- Straight hair
- Buzz cut
- Twin tails
- Black hair
- Silver/White hair
- Highlights/Ombre hair
- Add mustache
- Remove beard
- Tanned skin
- Change eye color
- Add sunglasses
- Add hat
- Add earrings
- Add face mask
- Remove makeup
- Double eyelids

Hairstyle Editing

- Add Bangs
- Curtain Bangs
- Side-swept Bangs
- Long Hair
- Curly Hair
- Fleece Curls
- Smooth Hair
- Buzz Cut
- Twin Tails
- Hair Bun
- Slicked Back
- Side Part
- Hime Cut
- Braids
- Undercut
- Recede Hairline
- Volumize Hair Roots
- Frizz Control
- Wet Hair Effect
- Hair Dye
- Black Hair
- Silver/White Hair
- Flaxen/Ash Brown
- Smoky Blue
- Inner Hair Color
- Ash Blonde
- Add Full Beard
- Add Goatee
- Stubble Effect
- Eyebrow Shaping
- Feathery Eyebrows
- Straight Eyebrows

Emotion Expression

- Make younger
- Gender swap
- Long hair
- Curly hair
- Make bald
- Dreadlocks
- Blonde hair
- Red hair
- Brown hair
- Add full beard
- Add goatee
- Add freckles
- Pale/Fair skin
- Add eyeglasses
- Remove glasses
- Add baseball cap
- Add necklace
- Heavy makeup
- Change lipstick color

- French Bangs
- Straight Bangs
- Baby Hair Bangs
- Short Hair
- Big Wavy Hair
- Straight Hair
- Bald
- Dreadlocks
- High Ponytail
- Bob Cut
- Middle Part
- Wolf Cut/Mullet
- Afro
- Updo
- Fill Hairline
- Increase Hair Volume
- Remove Flyaways
- Enhance Hair Shine
- Remove Greasy Hair
- Blonde Hair
- Red Hair
- Brown Hair
- Rose Gold
- Hair Highlights
- Ombre Hair
- Pink Hair
- Add Mustache
- Remove Beard
- Sideburns Trim
- Thicken Eyebrows
- Thin Eyebrows
- Arched Eyebrows

- Smile
- Closed-mouth Smile
- Bitter Smile
- Sadness
- Anger
- Surprise
- Disgust
- Confusion
- Poker Face/Cool
- Pout
- Bite Lip
- Wink
- Roll Eyes
- Scream
- Shy/Blush
- Confident
- Tipsy/Drunk
- Relieved
- Subtle Expression

Gaze Correction

- Look at Camera
- Open Closed Eyes
- Remove Red-eye
- Strabismus Correction
- Balance Asymmetric Eyes
- Fix Lifeless Eyes
- Simulate Squint
- Focus Gaze
- Sharpen Gaze
- Resize Pupil

Body and Fashion

Virtual Try On

- Change Top
- Full Outfit Change
- Try on Hoodie
- Try on Jeans
- Try on Suit
- Try on Hanfu/Costume
- Try on Sportswear
- Try on Puffer Jacket
- Mannequin to Model
- Preserve Logo Details
- Recolor Garment
- Adjust Hemline
- Slim Fit
- Untucked Shirt
- Zip Up
- Try on Glasses
- Try on Jewelry/Necklace
- Try on Handbag
- Batch E-commerce Try-on
- Studio Lighting Style
- Change Outfit Style

Body Reshape

- Laugh
- Smirk
- Giggle
- Crying
- Frown
- Fear
- Contempt
- Serious
- Bored/Apathetic
- Tongue Out
- Blow Kiss
- Close Eyes
- Open Mouth/Gasp
- Yawn
- Flirty/Seductive
- Tired
- Pain
- Exaggerate Expression

- Adjust Gaze Direction
- Add Eye Catchlights
- Fix Cross-eyed
- Whiten Sclera
- Enhance Iris Texture
- Generate Wink
- Lift Droopy Eyelids
- Soften Gaze
- Adjust Eye Distance
- Watery Eyes Effect

- Change Bottoms
- Try on Dress
- Try on Shirt
- Try on Skirt
- Try on Wedding Dress
- Try on Swimwear
- Try on Coat/Trench
- Flat Lay to Model
- Ghost Mannequin Effect
- Maintain Fabric Texture
- Replace Clothing Pattern
- Oversized Fit
- Tuck in Shirt
- Open Jacket
- Roll up Sleeves
- Try on Hat
- Try on Shoes
- Generate Virtual Model
- Street Snap Style
- Lingerie Model Gen
- Fix Garment Distortion

- Auto Body Slimming
- Waist Slimming
- Hip Enhancement
- Swan Neck
- Right-angled Shoulders
- Abs Definition
- Thigh Slimming
- Full Body Height
- Hunchback Correction
- Body Proportion Adjustment
- Leg Lengthening
- Arm Slimming
- Head Size Reduction
- Shoulder Width Adjustment
- Breast Enhancement
- Muscle Line Enhancement
- Calf Slimming
- Posture Correction
- Collarbone Definition
- Flatten Belly

Pose Action

- Reference pose transfer
- Turn head
- Look down
- Look at camera
- Fix deformed hands
- Peace sign
- Thumbs up
- Pointing
- Open palm
- Arms crossed
- Hands in pockets
- Raise hands
- Standing straight
- Sitting cross-legged
- Squatting
- Lying down
- Leaning
- Running
- Dancing
- Kicking
- Side profile
- Holding cup
- Custom skeleton
- Look up
- Tilt head
- Look away
- Refine fingers
- Finger heart
- Waving
- Clenched fist
- Praying hands
- Hands on hips
- Hands behind head
- Stretching
- Sitting
- Cross legs
- Kneeling
- Lying on side
- Walking
- Jumping
- Yoga pose
- Turn around
- Holding phone
- Hugging

4. Text and Graphic Design

Text Manipulation

Text Removal

- Smart Text Removal
- Remove TV Logo
- Remove Date Stamp
- Remove Stamp/Seal
- Remove Street Sign Text
- Remove Text on Clothing
- Remove Screenshot UI
- Remove Copyright Symbol
- Clear Exam Answers
- Remove Graffiti
- Remove Watermark
- Remove Subtitles
- Remove Handwriting
- Remove Manga Text
- Remove License Plate
- Remove Product Logo
- Remove Bullet Comments
- Remove Highlighter
- Remove Camera Watermark
- Remove Text from Complex Background

Text Editing

- Scene Text Modification
- Handwriting Generation
- 3D Text Effect
- Graffiti Text
- Translate Text in Image
- Calligraphy Style
- Neon Sign Text
- Elemental Text Effects (Fire/Water)
- Engraved & Embossed Text
- Chalk/Crayon Text
- Curved Surface Text
- Meme Captioning
- Text Texture Replacement
- Glowing Text Effect
- Metallic/Gold Foil Text
- Embroidery Style Text
- Perspective Text Matching
- Artistic Font Generation
- Retro Pixel Text
- Poster Headline Design

Design Elements

Typography Style

- 3D Text
- Metallic Text
- Calligraphy
- Pixel Text
- Fire Effect
- Bubble Text
- Retro Serif
- Liquid Text
- Stone Carving
- Chalk Style
- Cyberpunk Style
- Furry Text
- Outline Text
- Sticker Style
- Food Texture
- Neon Text
- Handwritten Style
- Graffiti Style
- Glitch Text
- Ice Effect
- Gothic Style
- Golden Text
- Glass Texture
- Wood Texture
- Ink Style
- Balloon Text
- Gradient Text
- Shadow Text
- Floral Text
- Glowing Text

Layout Logo

- Poster Layout
- Photo Collage
- E-commerce Page Layout
- Logo Generation
- Make Logo Transparent
- Logo Stylization
- Tiled Watermark
- Insert QR Code
- Add Borders
- Auto Alignment
- Smart Composition
- Magazine Cover Design
- Social Media Templates
- Insert Logo
- Logo Vectorization
- 3D Logo Effect
- Invisible Watermark
- Artistic QR Code
- Add Stickers
- Negative Space Management

5. Generation and Composition

Canvas and Viewpoint

Outpainting

- Horizontal Expansion
- Expand All Sides
- Subject Re-centering
- Background Extension
- Panorama Generation
- 1:1 Square Expansion
- Zoom Out (Uncrop)
- Vertical Expansion
- Smart Autofill
- Fit to Wallpaper
- Complete Cut-off Objects
- Fill Rotated Corners
- Feathered Expansion

Crop Composition

- ID Photo Crop
- Auto Straighten
- Rule of Thirds
- Cinematic Aspect Ratio
- Smart Subject Centering
- Perspective Crop
- Golden Ratio

Camera Shift

- Front View
- Back View
- Low Angle / Worm's Eye
- First-Person View
- Over-the-Shoulder
- Isometric View
- Fisheye Lens
- Panoramic View
- Zoom Out
- Perspective Correction
- Side View
- High Angle / Bird's Eye
- Three-quarter View
- Selfie Angle
- Drone Shot
- Wide Angle
- Macro / Close-up
- Zoom In
- Camera Pan
- 3D Rotation

Conditional Generation

Reference Driven

- Style Transfer
- Composition Reference
- Face Identity Lock
- Line Art Colorization
- Depth Reference
- Sketch to Realistic
- Photorealistic to Anime
- Outfit Style Reference
- Makeup Reference
- Lighting Layout Reference
- Background Reference
- Interior Design Reference
- Color Palette Matching
- Human Pose Copy
- Character IP Consistency
- Spatial Structure Reference
- Edge Outline Lock
- Anime to Photorealistic
- Generate Variations
- Hairstyle Reference
- Material Texture Copy
- Atmosphere Copy
- Product Design Reference
- Architectural Structure Reference

- Motion Capture
- Hand Gesture Reference
- Artistic Brushstroke Copy
- Semantic Segmentation Guide
- Film Aesthetic Copy

Sketch Control

- Sketch to Realistic Photo
- Line Art Colorization
- Architectural Sketch Rendering
- Product Design Rendering
- Refine Rough Sketch
- Generative Fill
- Add Element via Brush
- Fix Hands & Limbs
- Color Block Composition
- Structure-Preserved Redraw
- Scribble to Art
- Manga/Anime Coloring
- Interior Design Rendering
- Fashion Sketch Rendering
- Silhouette to Image
- Local Redraw
- Texture Inpainting
- Face Inpainting
- Palette Guided Generation

Multi Image Consistency

- Double Exposure
- Smart Collage
- Panorama Stitching
- Face Swap
- Character Consistency
- Image Blending
- Long Image Stitching
- 360 Panorama
- Head Swap
- Keep Character Change Pose
- Outfit Consistency
- Keep Character Change Background
- Multi-Angle Generation
- Character Sheet
- 4-Panel Comic
- Storyboard Generation
- Image Morphing
- Concept Blending
- HDR Merge
- Creative Compositing
- Collage Art
- 3-View Generation
- Comic Panel Generation
- Picture Book Consistency
- Cinematic Storyboard
- Style Mixing
- Seamless Texture Tiling
- Focus Stacking
- Montage Effect
- Photo Bash

Group Photo Synthesis

- Celebrity Group Photo
- Add Person to Group Photo
- Multi-person Face Swap
- Family Portrait Generation
- Couple Photo Synthesis
- Cross-time Group Photo
- Center Position Adjustment
- Multi-person Lighting Unification
- Multi-person Perspective Correction
- Fix Closed Eyes in Group Photo
- Eye Contact Alignment
- Hugging Pose Generation
- Back-to-Back Pose
- Dense Crowd Generation
- Business Meeting Group Photo
- Team Uniform Unification
- Fix Group Photo Edge Distortion
- Cinematic Ensemble Poster
- Virtual Idol Co-framing
- Remove Person from Group Photo
- Multi-person Outfit Swap
- BFF Photo Synthesis
- Wedding Photo Synthesis
- Swap Character Positions
- Height Proportion Adjustment
- Multi-person Color Tone Matching
- Unified Skin Texture
- Multi-person Expression Sync
- Hold Hands Generation
- Put Arm Around Shoulder
- Multi-character Consistency
- Party Scene Generation
- Graduation Photo Generation
- Remove Passersby from Background
- Anime Character Crossover Replica

6. Advanced and Domain-Specific Applications

Reasoning and Interaction

Complex Instruction

- Multiple Condition Stacking
- Precise Quantity Control
- Independent Multi-object Attributes
- Logical Causal Inference
- Abstract Concept Visualization
- Modification with Preservation
- Implicit Intent Inference
- Complex Composition Description
- Specific Style Fusion
- Exclusionary Editing
- Negative Constraints Handling
- Spatial Position Specification
- Referential Disambiguation
- Comparative Instructions
- Sequential Multi-step Operations
- Physics Common Sense Adherence
- Counterfactual Editing
- Relative Size Adjustment
- Reference-based Modification
- Multi-level Detail Description

Logic Process

- Storyboard Generation
- Assembly Instructions
- Science Experiment Procedure
- Spatial Position Constraints
- Component Breakdown (Knolling)
- Before and After Comparison
- Anatomical Structure
- Historical Timeline
- Maze Generation
- Hidden Object Game
- Visual Pun
- Logic Puzzle Illustration
- Comparison Diagram
- Inclusion Relationship
- Cyclic Process Diagram
- Evolutionary Process
- Cooking Steps Breakdown
- Exact Count Generation
- Floor Plan Generation
- Cross-Section View
- Cause and Effect Visualization
- Infographic Generation
- Spot the Difference Game
- Optical Illusion
- Calligram (Text as Objects)
- Physics Simulation
- Flowchart Visualization
- Multi-View Orthographic
- Exclusion Logic Diagram
- Hierarchy Diagram

Industry Solutions

Ecommerce

- AI Commercial Photography
- Mannequin to Model
- Model Face Swap/Localization
- AI Podium & Stand Generation
- White Background Shot
- Product Background Replacement
- Virtual Try-on
- Product Color Variation (SKU)
- Product Shadow & Reflection
- E-commerce Poster Generation
- Promotional Banner Design
- Product Infographic
- Apparel Pattern Preview
- Amazon Main Image Optimization
- Jewelry Sparkle Effect
- Seasonal Marketing Theme
- Listing Long Image Stitching
- Brand Logo Integration
- Model Age/Ethnicity Adjustment
- Cosmetic Texture Display
- Digital Screen Replacement
- Lifestyle Context Integration
- Packaging Design Mockup
- Social Media Marketing Image
- Food Photography Enhancement
- Furniture Scene Staging
- Batch Product Cutout
- Storefront Decoration Assets
- 3D Product Rendering
- Material Detail Zoom
- Flat Lay Generation
- Outfit Style Recommendation

Docs Education

- Remove Document Shadows
 - Document Background Whitening
 - Book Page Scanning Enhancement
 - Old Document Restoration
 - Receipt Clarification
 - Remove Grading Marks
 - Whiteboard Glare Removal
 - Math Formula Beautification
 - ID Photo Generation
 - ID Photo Smart Layout
 - Resume Photo Retouching
 - Digital Signature Extraction
 - Table Structure Restoration
 - PPT Slide Generation
 - Sketch to UI Design
 - Mind Map Beautification
 - Note Layout Optimization
 - Educational Illustration Generation
 - Infographic Design
 - Document Straightening & Dewarping
 - Remove Screen Moire Patterns
 - Remove Page Creases
 - Blueprint & Technical Drawing Enhancement
 - Remove Handwriting from Exam
 - Blackboard Writing Clarification
 - Error Problem Notebook Gen
 - Flashcard Generation
 - ID Photo Background Change
 - ID Photo Virtual Suit Try-on
 - ID Card Copy Generation
 - Stamp & Seal Extraction
 - Business Card Digitization
 - UI Interface Generation
 - Mind Map Generation
 - Journal Sticker Generation
 - Data Chart Generation
 - Certificate & Award Creation
 - Handwriting Simulation
 - Character Design Sheet
 - Chibi/Nendoroid Style
 - Game Icons & Props
 - Manga Page/Layout
 - Visual Novel Backgrounds
 - 90s Retro Anime
 - Monster & Creature Design
 - Character Turnaround
 - Pixel Art
 - Concept Art
 - Webtoon/Manhwa
 - TCG Card Illustration
 - Mecha & Robot Design
 - Weapon & Equipment Design
 - Game Sprite Sheets
 - Low Poly Style
 - Impasto/Thick Painting
 - Light Novel Cover
 - Furry/Anthro
 - Magic & Skill VFX
 - Storyboard
 - Makoto Shinkai Style
 - Vtuber Avatar
 - Game Map Tiles
 - American Comic Style
 - Isometric/2.5D View
 - Voxel Art
 - Cell Shading
 - Sticker/Emoji Generation
 - Game UI Assets
 - Seamless Textures
 - Character Variations
 - Cyberpunk Anime
 - Fan Art Illustration
 - Ghibli Style
 - Figurine/Model Rendering
-