

FROM PROMPTING TO COMPOSING: A SPATIAL CANVAS INTERFACE FOR POSTER GENERATION

Yitong Wang^{1,2*} Fangyun Wei^{2*} Jinjing Zhao^{3,2} Sirui Zhang^{4,2}

Hongyang Zhang⁵ Dong Chen² Bo Dai^{6†} Yan Lu²

¹Fudan University ²Microsoft Research ³The University of Sydney

⁴USTC ⁵University of Waterloo ⁶The University of Hong Kong

*Equal contribution. †Corresponding author.

wangyitong23@m.fudan.edu.cn {fawe, doch, yanlu}@microsoft.com

jzha0100@sydney.edu.au zsr200901@mail.ustc.edu.cn

hongyang.zhang@uwaterloo.ca bdai@hku.hk

Project page: <https://snowflakewang.github.io/Compo-Page/>




Figure 1: Instead of describing an entire poster through a *single text prompt*, our **Spatial Canvas Interface** allows users to directly compose generation intent in two-dimensional space. The interface supports four complementary forms of binding: **Semantic Binding** specifies what visual content should be generated in a designated region; **Identity Binding** associates a reference image with a target region to preserve its visual identity; **Text Binding** places specified text at a desired location; and **Pixel Binding** directly anchors visual content that should be preserved. The accompanying *Text Specifications* further provide *detailed instructions* for individual bindings, such as the desired appearance, action, or content of each bound element, together with global specifications for the background and style. By jointly expressing spatial structure on the canvas and detailed generation requirements in text, our interface provides an explicit and structured specification of the target poster, enabling generation through composition rather than text description alone.

ABSTRACT

Text prompting is an indirect interface for poster generation, requiring users to encode inherently two-dimensional composition intent into a one-dimensional sequence of words. We introduce a **Spatial Canvas Interface** that enables users to directly compose generation intent in space through four complementary binding types: semantic, identity, text, and pixel, together with Text Specifications for individual elements and global appearance. Based on this interface, we develop **Compo**, a poster generation model adapted from a pretrained image editing model to understand Spatial Canvas inputs and Text Specifications. Compo supports both direct inference, where users explicitly construct the canvas, and agentic mode, where a high-level request is automatically translated into a planned Spatial Canvas. To train Compo, we develop a scalable pipeline that automatically constructs

supervision data for different binding types and their combinations, enabling efficient adaptation without training a specialized poster generator from scratch. We further introduce a benchmark that evaluates adherence to individual binding types and their joint composition. Experiments show that Compo achieves stronger compositional controllability than both general-purpose image generation models and dedicated poster generation systems while maintaining high visual quality. By decoupling intent specification from visual generation, our work shifts poster generation from *prompting* toward *composing*.

1 INTRODUCTION

Text has become the direct interface for modern generative models, including recent systems for poster generation (Chen et al., 2025a;b). Given a prompt, a model is expected to translate a one-dimensional sequence of words into a complete two-dimensional visual composition. While recent image generation models (Wu et al., 2025a; Cai et al., 2025; Liu et al., 2026; Team et al., 2025) can produce visually compelling posters, text alone remains a limited interface for specifying *how a poster should be composed*. Posters are inherently structured, with subjects, text, logos, and graphical elements occupying intentional locations and often requiring specific identities or visual content to be preserved. Encoding such spatial and visual constraints entirely through language is indirect and ambiguous, especially as compositions become more complex.

We therefore explore a different paradigm: *instead of describing the entire poster with text, users compose generation intent directly in space*. As illustrated in Figure 1, we introduce a **Spatial Canvas Interface** for *poster generation* that decouples intent specification from visual generation. The Spatial Canvas represents where different elements should appear and how they should be bound, while accompanying **Text Specifications** provide detailed instructions for individual elements as well as global descriptions such as background and style. Together, they form a structured representation of the target poster.

Our interface supports four complementary forms of binding. *Semantic Binding* associates a textual concept with a target region; *Identity Binding* associates a reference image with a region to preserve its visual identity; *Text Binding* specifies both an exact text string and its desired location; and *Pixel Binding* directly places visual content that should be preserved. These bindings can be freely combined within a single canvas, providing unified control over semantics, identity, text, pixels, and layout. From this perspective, layout control (Zheng et al., 2023; Zhang et al., 2025a), reference-driven generation (Xia et al., 2025; Wu et al., 2026), text rendering (Chen et al., 2024; Peng et al., 2025), and image editing (Wu et al., 2025a; Team et al., 2025) can all be viewed as instances of a common principle: *binding generation constraints to spatial locations on a shared canvas*.

To realize this interface, we develop **Compo**, a poster generation model adapted from a pretrained image editing model to understand Spatial Canvas inputs and their associated Text Specifications. Compo supports two complementary inference modes. In *direct inference*, users explicitly construct the Spatial Canvas and Text Specifications for fine-grained control. In *agentic mode*, users provide only a high-level natural-language request, and an agent automatically converts it into the same structured representation by extracting visual elements and text, planning their spatial layout, selecting appropriate binding types, and retrieving reference images when needed. The resulting Spatial Canvas and Text Specifications are then consumed by Compo to generate the final poster. In this way, the Spatial Canvas serves both as a human-facing composition interface and as a structured intermediate representation for agentic generation.

Training Compo presents a practical challenge, as existing image generation and editing models are not designed to interpret such heterogeneous spatial bindings, while collecting large-scale, human-designed canvas-poster pairs would be prohibitively expensive. To address this challenge, we develop a *scalable training data generation pipeline* that automatically constructs supervision for individual binding types and their combinations, resulting in **Compo-200K**. Using this automatically generated dataset, we efficiently adapt a pretrained image editing model to the Spatial Canvas Interface, without training a specialized poster generation model from scratch.

Finally, we introduce a **benchmark and evaluation protocol** for spatially compositional poster generation. Rather than evaluating only overall image quality, our benchmark measures adherence to each binding type individually, as well as their joint composition. Experiments show that Compo

achieves stronger controllability than both general text-and-image-to-image generation models, such as Qwen-Image-Edit-2511 (Wu et al., 2025a), and dedicated poster generation systems, such as CreatiDesign (Zhang et al., 2026), while maintaining high visual quality.

2 RELATED WORKS

Image Generation and Editing Foundation Models. Recent commercial foundation models (Microsoft, 2026; Grok, 2026; ByteDance, 2026; OpenAI, 2026c; Google, 2026b; Qwen Team, 2026b) support both text-to-image generation and image editing, with strong visual quality, instruction following, and text rendering. Design-oriented models (Ideogram, 2026; Reve, 2026) further introduce structured text or image inputs for more explicit control over layout and composition. Open-source models (Wu et al., 2025a; Team et al., 2025; 2026; Song et al., 2026; Labs, 2025) commonly extend text-to-image generation to editing by combining multimodal language models (Bai et al., 2025b;a) with diffusion transformers (Peebles & Xie, 2023; Esser et al., 2024). Other efforts improve training efficiency through compact designs (Chen et al., 2026b; Hu et al., 2026) or develop unified architectures (Cai et al., 2026; Diao et al., 2026) that support generation, editing, and, in some cases, image understanding. Despite these advances, jointly expressing multiple multimodal references and precise layout constraints remains underexplored for complex graphic design.

Reference- and Layout-Driven Image Generation. Controllable image generation methods can be broadly grouped by their use of reference and layout conditions. Reference-driven methods (Ruiz et al., 2023; Wang et al., 2025b; Wu et al., 2025c; Tan et al., 2025; Zhu et al., 2025; Mou et al., 2025; Cheng et al., 2025; She et al., 2026; Garibi et al., 2025; Chen et al., 2026a; Xia et al., 2025; Wu et al., 2026; Xu et al., 2026b; Chen et al., 2026e) preserve visual attributes such as subject identity, appearance, or style from user-provided images, while layout-driven methods (Li et al., 2023; Wang et al., 2024; Zhou et al., 2024; Cheng et al., 2024; Zhou et al., 2025; Zheng et al., 2023) control spatial composition through explicit structural constraints. Joint-control methods (Qin et al., 2023; Wang et al., 2025a; Xu et al., 2026a) combine multiple references and layouts, but often rely on separate or task-specific modules, limiting extensibility. Unified-input methods (Dalva et al., 2026; Yi et al., 2026) instead encode heterogeneous control signals within a single input image. However, existing works mainly focus on human-centric portrait or general image synthesis, leaving structured graphic design underexplored. Furthermore, these approaches lack explicit and fine-grained bindings between spatial regions and their corresponding text descriptions. These limitations motivate a more general and structured interface for multimodal binding and layout control.

Poster Generation. Poster generation requires joint modeling of textual content, graphic layout, visual assets, and design aesthetics. Early methods focus on individual aspects, including layout generation (Hsu et al., 2023; Lin et al., 2023; Seol et al., 2024; Yang et al., 2024; Chen et al., 2025a) and text rendering (Tuo et al., 2024; Chen et al., 2024; Liu et al., 2024; Wang et al., 2025c). Later approaches (Pu et al., 2025; Peng et al., 2025; Gao et al., 2025) incorporate visual references and layout conditions for improved controllability, while others (Hu et al., 2025; Zhang et al., 2025b) condition on background images or separately model foreground and background elements. Recent methods further improve aesthetic quality through reinforcement learning (Chen et al., 2025b; 2026d) or support multiple conditions (Zhang et al., 2026). However, existing approaches still rely on restricted reference types or task-specific control modules, limiting extensibility and requiring complex user inputs.

3 METHOD

Problem Formulation. Given a *Spatial Canvas* and its accompanying *Text Specifications*, our goal is to generate a poster that faithfully satisfies the specified spatial layout, semantic content, visual identities, textual elements, and preserved pixels, while maintaining high visual quality. The *Spatial Canvas* serves as the *visual modality*, encoding element locations, reference assets, preserved visual content, and binding types in two-dimensional space. The *Text Specifications* serve as the *language modality*, providing detailed element-level instructions together with global descriptions such as background and style. Together, these two modalities form the input to our model, **Compo**.

We describe our scalable training data generation pipeline in Section 3.1. Section 3.2 presents the architecture and the two-stage training procedure, including supervised training and reinforcement learning. Finally, Section 3.3 introduces the inference pipeline, covering both direct inference and agentic generation.




Figure 2: **Training data generation pipeline.** We first create diverse posters through structured planning and information-preserving rewriting with *GPT-5.5* (OpenAI, 2026a), followed by rendering with *Qwen-Image-2512* (Wu et al., 2025a), *Z-Image* (Cai et al., 2025), and *ERNIE-Image* (Liu et al., 2026). We then automatically construct paired Spatial Canvases and Text Specifications through instance segmentation, visual asset processing, and text recognition, providing scalable supervision for training Compo.

3.1 TRAINING DATA GENERATION

Training Compo requires paired supervision comprising a target poster, its Spatial Canvas, and corresponding Text Specifications. However, existing poster datasets (Chen et al., 2025b; Mao et al., 2026) lack the diversity and fine-grained annotations required by our interface, while manual construction at a large scale is prohibitively expensive. Inspired by recent works (Zhang et al., 2026; Chen et al., 2026d), we develop a scalable data generation pipeline that automatically generates posters with fine-grained multimodal bindings and layout annotations. As illustrated in Figure 2, our pipeline consists of two stages: **poster creation** and **annotation generation**.

Poster Creation. We use *GPT-5.5* (OpenAI, 2026a), *Claude Opus 4.6* (Anthropic, 2026), and *Gemini 3.5 Flash* (Google, 2026a) to construct two text asset repositories: a content repository containing diverse poster themes and their associated items, spanning categories such as product advertising, public service, and entertainment, and a style repository covering a wide range of visual styles. To construct diverse poster concepts, we sample a theme with its associated items and a visual style from the respective repositories. *GPT-5.5* then organizes these sampled assets into a structured specification and enriches it by planning the visual text and poster background, as well as detailed descriptions and interactions for the identities or objects instantiated from the sampled items. The resulting specification is rewritten into a natural poster generation prompt while preserving all sampled and planned information. Finally, we render the prompts with multiple text-to-image models, including *Qwen-Image-2512* (Wu et al., 2025a), *Z-Image* (Cai et al., 2025), and *ERNIE-Image* (Liu et al., 2026), selected for their advanced text rendering capabilities, to enhance the diversity of visual appearance and composition in the training data.




Figure 3: **Architecture and training pipeline of Compo.** Compo is trained in two stages. During supervised training, the Spatial Canvas and Text Specifications are jointly encoded with the target poster to adapt a pretrained MMDiT (Peebles & Xie, 2023; Esser et al., 2024) through LoRA (Hu et al., 2021). We then apply DiffusionNFT (Zheng et al., 2026) for reinforcement learning with complementary rewards for text accuracy, instance similarity, and layout adherence.

Annotation Generation. Given a generated poster, we automatically recover the structured supervision required by the Spatial Canvas Interface. For visual elements, we use *SAM-3* (Carion et al., 2026) to segment relevant instances from the generated poster. The segmented assets are further processed with *FLUX.2-klein-9B* (Labs, 2025) for relighting or reposing when needed, producing suitable visual references for constructing different binding types. For textual elements, we use *Chandra-OCR-2* (Datalab, 2026) to recognize the rendered text and recover its spatial location. As shown in Figure 2, all elements, including bounding boxes, reference images, and textual identifiers, are directly rendered onto the Spatial Canvas as visual conditions. In parallel, we construct the Text Specifications from the original structured planning information to record element-level descriptions and global attributes such as background and style. Consequently, each training sample consists of a generated poster paired with its Spatial Canvas and Text Specifications, providing scalable supervision for training Compo. As a result, we construct a new dataset of roughly 200K samples with fine-grained structured annotations, denoted as **Compo-200K**. More details about data creation and annotation are included in Appendix A.1.

3.2 ARCHITECTURE

As illustrated in Figure 3, Compo is built upon a pretrained multimodal diffusion transformer (MMDiT) (Peebles & Xie, 2023; Esser et al., 2024) and trained in two stages: **Supervised Training** and **Reinforcement Learning**. Rather than modifying the backbone architecture, we adapt the pretrained model using LoRA (Hu et al., 2021), allowing Compo to efficiently learn the proposed Spatial Canvas Interface while retaining the generative capabilities of the pretrained model.

Stage-1: Supervised Training. We first perform supervised training using the data generated by the pipeline described in Section 3.1. Each training sample consists of a target poster together with its corresponding *Spatial Canvas* and *Text Specifications*. We experiment with both *LongCat-Image-Edit* (Team et al., 2025) and *Qwen-Image-Edit-2511* (Wu et al., 2025a) as pretrained image editing backbones, and follow the same training objective and loss formulation as their respective original models. Both models use a frozen Qwen2.5-VL (Bai et al., 2025b) to encode the multimodal specifications into visual-language tokens (VL tokens). The Spatial Canvas and target poster are encoded into the latent space using a frozen VAE, producing canvas tokens and target latent tokens, respectively. During diffusion training, noise is added to the target latents, and the pretrained MMDiT jointly processes the noisy target tokens, canvas tokens, and VL tokens. Specifically, the text branch of MMDiT processes the VL tokens, while the image branch processes the noisy target tokens together with the canvas tokens. The pretrained components are kept frozen, while LoRA parameters attached to the MMDiT are optimized. This stage enables Compo to interpret heteroge-




Figure 4: **Poster generation using Compo with Agentic Mode.** Given a high-level user request, a GPT-5.6-based agent extracts visual elements and text, plans their spatial layout, assigns appropriate binding types, and retrieves reference images when needed. It then constructs a planned Spatial Canvas and Text Specifications, which are passed to Compo to generate the final poster.

neous bindings and generate posters that follow the structured Spatial Canvas and associated Text Specifications. More details are described in Appendix B.1.

Stage-2: Reinforcement Learning (RL). While supervised training teaches Compo to follow the Spatial Canvas Interface, it does not explicitly optimize the fidelity of each individual binding. We therefore further refine the supervised model using *DiffusionNFT* (Zheng et al., 2026). Starting from the Stage-1 model, we perform multiple rollouts for each input and optimize a trainable LoRA with a multi-reward objective tailored to the binding requirements of our interface. We follow the optimization strategy and training hyperparameters of DiffusionNFT, while applying our binding-aware multi-reward objective for RL post-training.

Our reward comprises three complementary components. The **text reward** evaluates the rendering quality of each Text Binding using sentence accuracy and normalized edit distance (NED; i.e., 1 minus the edit distance) (Gao et al., 2025), capturing exact correctness and character-level fidelity, respectively. The **instance similarity reward** evaluates the consistency of each generated instance with its corresponding visual or semantic condition by combining DINO-I (Oquab et al., 2023), CLIP-I (Radford et al., 2021), and CLIP-T (Radford et al., 2021) similarities, thereby encouraging both visual fidelity and semantic alignment. The **layout reward** measures the IoU between the intended and generated regions of each text or visual element, encouraging accurate spatial placement. For each rollout candidate, these rewards are first computed at the individual text or instance level and then aggregated into image-level scores. Sentence accuracy is aggregated using a logical AND operation, such that the image-level score is one only if all bound text elements are rendered correctly and zero otherwise. All other reward metrics are aggregated using arithmetic averaging. The

Table 1: We compare general text-and-image-to-image models, dedicated poster generation models, and our Compo variants across pixel, identity, semantic, and text binding metrics. Higher values indicate better performance. The **best** and **second-best** results are highlighted in orange and blue, respectively. “NED”: normalized edit distance. “Sen. Acc.”: sentence accuracy.

Models	Pixel Binding					Identity Binding				Semantic Binding			Text Binding			Overall	
	DINO-I	CLIP-I	M-DINO	SSIM	IoU	DINO-I	CLIP-I	M-DINO	CLIP-T	IoU	CLIP-T	IoU	NED	Sen. Acc.	IoU	IoU	Avg. Score
<i>General Text-and-Image-to-Image Models</i>																	
Step1X-Edit (Liu et al., 2025)	0.426	0.481	0.327	0.493	0.473	0.600	0.645	0.488	0.167	0.563	0.012	0.056	0.060	0.020	0.270	0.317	0.339
GLM-Image (Z.ai, 2026)	0.535	0.580	0.441	0.591	0.571	0.663	0.699	0.554	0.185	0.606	0.019	0.110	0.030	0.012	0.230	0.328	0.389
BAGEL (Deng et al., 2025)	0.274	0.311	0.207	0.321	0.321	0.534	0.580	0.428	0.156	0.511	0.006	0.045	0.007	0.000	0.184	0.228	0.259
ChronoEdit-14B (Wu et al., 2025b)	0.575	0.629	0.479	0.647	0.638	0.697	0.733	0.596	0.192	0.631	0.011	0.055	0.004	0.000	0.260	0.350	0.410
FLUX.2-klein-9B (Labs, 2025)	0.341	0.378	0.254	0.392	0.390	0.543	0.586	0.430	0.168	0.511	0.058	0.225	0.187	0.088	0.431	0.388	0.332
JoyAI-Image-Edit (Song et al., 2026)	0.440	0.477	0.328	0.480	0.467	0.626	0.658	0.495	0.183	0.585	0.071	0.244	0.217	0.141	0.372	0.394	0.386
FireRed-Image-Edit-1.1 (Team et al., 2026)	0.387	0.419	0.286	0.429	0.436	0.605	0.642	0.472	0.182	0.558	0.061	0.228	0.125	0.056	0.361	0.376	0.350
Boogu-Image-0.1-Edit (Chen et al., 2026c)	0.473	0.506	0.376	0.504	0.494	0.668	0.701	0.539	0.193	0.607	0.057	0.202	0.230	0.119	0.347	0.385	0.401
HiDream-O1-Image (Cai et al., 2026)	0.624	0.669	0.514	0.685	0.663	0.747	0.776	0.642	0.218	0.672	0.138	0.415	0.183	0.102	0.512	0.547	0.504
SenseNova-U1 (Diao et al., 2026)	0.099	0.120	0.076	0.123	0.170	0.249	0.306	0.179	0.096	0.304	0.038	0.215	0.078	0.055	0.232	0.218	0.156
DreamOmni2 (Xia et al., 2025)	0.405	0.441	0.322	0.451	0.455	0.576	0.605	0.471	0.160	0.547	0.017	0.085	0.053	0.020	0.274	0.310	0.326
OmniGen2 (Wu et al., 2026)	0.345	0.380	0.255	0.384	0.376	0.517	0.552	0.401	0.149	0.506	0.018	0.100	0.015	0.001	0.227	0.267	0.282
LongCat-Image-Edit (Team et al., 2025)	0.515	0.562	0.406	0.581	0.574	0.723	0.775	0.620	0.221	0.664	0.072	0.232	0.150	0.055	0.409	0.445	0.437
Qwen-Image-Edit-2511 (Wu et al., 2025a)	0.567	0.608	0.440	0.624	0.610	0.720	0.752	0.606	0.210	0.653	0.049	0.190	0.133	0.072	0.399	0.434	0.442
<i>Dedicated Poster Generation Models</i>																	
PosterMaker (Gao et al., 2025)	0.708	0.748	0.611	0.766	0.760	0.276	0.329	0.157	0.101	0.357	0.239	0.825	0.397	0.107	0.607	0.628	0.466
PosterOmni (Chen et al., 2026d)	0.582	0.625	0.469	0.638	0.612	0.675	0.709	0.556	0.196	0.607	0.063	0.222	0.194	0.102	0.455	0.463	0.447
CreatiDesign (Zhang et al., 2026)	0.674	0.731	0.585	0.750	0.725	0.210	0.273	0.148	0.083	0.345	0.080	0.267	0.515	0.329	0.670	0.561	0.426
<i>Our Models</i>																	
Compo-LongCat	0.735	0.776	0.642	0.793	0.781	0.795	0.891	0.757	0.261	0.904	0.259	0.828	0.970	0.940	0.944	0.885	0.752
Compo-Qwen	0.734	0.770	0.649	0.782	0.773	0.810	0.910	0.781	0.263	0.932	0.262	0.850	0.940	0.868	0.934	0.886	0.751

final reward combines the resulting image-level signals to jointly improve text rendering, instance fidelity, and layout adherence. Further implementation details are provided in Appendix B.2.

3.3 INFERENCE

Compo supports two complementary inference modes: *Direct Inference* and *Agentic Mode*.

Direct Inference. In direct inference, users manually specify the Spatial Canvas and Text Specifications, providing explicit control over element locations, binding types, visual references, and generation requirements.

Agentic Mode. As illustrated in Figure 4, Agentic Mode allows users to generate a poster directly from a high-level natural-language request. The agent first performs *element extraction* to identify visual instances, visual text, background, and style. It then performs *layout planning* to determine the spatial location and size of each element, followed by *binding selection* to assign an appropriate binding type. For elements requiring visual references, the agent further performs *image search* to retrieve suitable assets. Based on these intermediate results, the agent constructs a planned Spatial Canvas and detailed Text Specifications, which are passed to Compo for final poster generation. The detailed implementation of Agentic Mode is described in Appendix B.3.

4 EXPERIMENTS

Benchmark Data Creation. We follow the training data generation pipeline to construct a curated benchmark of 500 samples with no overlap with the training set. Each sample is paired with structured annotations, enabling evaluation of both general text-and-image-to-image models and dedicated poster generation methods with different input formats. Details are included in Appendix A.2.

Evaluation Metrics. We evaluate each binding type using metrics tailored to its preservation requirements under a unified region matching protocol. For Semantic, Identity, and Pixel Binding, we use SAM-3 (Carion et al., 2026) to segment generated instances, whereas for Text Binding, we use Chandra-OCR-2 (Datalab, 2026) to detect rendered text and its spatial regions. Each detected instance or text region is matched to the ground-truth region with the highest IoU. A match is considered unsuccessful if its IoU falls below a predefined threshold, in which case all corresponding metrics are set to zero. For successfully matched regions, Semantic Binding is evaluated using CLIP-T (Radford et al., 2021) to measure semantic alignment. Identity Binding is evaluated using CLIP-I (Radford et al., 2021) and DINO-I (Oquab et al., 2023) to measure identity similarity, together with CLIP-T to assess consistency with the corresponding Text Specifications. As Pixel Binding imposes stricter preservation requirements, allowing only variations in style and lighting while requiring shape and spatial location to remain unchanged, we additionally compute SSIM (Wang




Figure 5: **Visual comparison with representative baselines.** We compare Compo with dedicated poster generation methods (PosterMaker (Gao et al., 2025), PosterOmni (Chen et al., 2026d), and CreatiDesign (Zhang et al., 2026)) and the best-performing general text-and-image-to-image baseline in Table 1, HiDream-O1-Image (Cai et al., 2026). Transparent pink boxes highlight noticeable errors. Additional visualizations are provided in Appendix C.2.

et al., 2004) alongside CLIP-I and DINO-I. Text Binding is evaluated using normalized edit distance (NED; i.e., one minus the edit distance) (Gao et al., 2025) and sentence accuracy (Zhang et al., 2026). All metrics are first computed for individual instances or text regions and then aggregated at the image level. We additionally report M-DINO (Zhang et al., 2026) for instance preservation, which penalizes poorly preserved instances more strongly and thus provides a stricter assessment than arithmetic averaging. The overall IoU and overall average score (Avg. Score) are computed as the means over all evaluated regions across binding types and all metrics, respectively.

Implementation Details. We initialize Compo with LongCat-Image-Edit (Team et al., 2025) and Qwen-Image-Edit-2511 (Wu et al., 2025a), respectively. The resulting models are referred to as *Compo-LongCat* and *Compo-Qwen*. We use DiffusionNFT (Zheng et al., 2026) as our RL post-training algorithm. More implementation details are provided in Appendices B.1 and B.2.

4.1 MAIN RESULTS

Quantitative Results. We compare our model against general text-and-image-to-image models and dedicated poster generation methods in Table 1. For general text-and-image-to-image models, our benchmark is directly compatible with their standard input interfaces, using the Spatial Canvas, Text Specifications, and supplementary task instructions for accurate interpretation of input conditions. For dedicated poster generation methods, we convert the structured annotations into their respective input formats while preserving as much information as supported by their original protocols, enabling fair comparison without modifying their native capabilities. As shown in Table 1, both Compo-LongCat and Compo-Qwen outperform all baselines on nearly all metrics, yielding consistent overall gains. Comparisons before and after RL post-training are provided in Appendix C.1.

Qualitative Results. Figure 5 qualitatively compares Compo with four representative baselines. Additional comparisons and visualizations are illustrated in Appendix C.2.

4.2 ABLATION STUDY

We conduct all ablation studies using Compo-LongCat for training and evaluation efficiency.

Ablation on RL Reward Components. As introduced in Section 3.2, our RL objective consists of three complementary rewards: text reward, instance similarity reward, and layout reward. We ablate each component individually and also remove all rewards to study their contributions. As

Table 2: **Effects of different RL reward components.** We ablate the text, instance similarity (“Ins. Sim.”), and layout rewards individually and jointly. The **best** and **second-best** results are highlighted in orange and blue, respectively. “NED”: normalized edit distance. “Sen. Acc.”: sentence accuracy.

Reward Setting	Pixel Binding					Identity Binding					Semantic Binding		Text Binding			Overall	
	DINO-I	CLIP-I	M-DINO	SSIM	IoU	DINO-I	CLIP-I	M-DINO	CLIP-T	IoU	CLIP-T	IoU	NED	Sen. Acc.	IoU	IoU	Avg. Score
Full Reward (Default)	0.735	0.776	0.642	0.793	0.781	0.795	0.891	0.757	0.261	0.904	0.259	0.828	0.970	0.940	0.944	0.885	0.752
w/o Text Reward	0.752	0.789	0.666	0.801	0.790	0.811	0.901	0.776	0.262	0.928	0.275	0.884	0.878	0.778	0.895	0.876	0.746
w/o Ins. Sim. Reward	0.725	0.769	0.639	0.788	0.776	0.782	0.879	0.740	0.255	0.877	0.239	0.753	0.958	0.924	0.942	0.866	0.736
w/o Layout Reward	0.732	0.771	0.644	0.787	0.779	0.799	0.892	0.760	0.260	0.902	0.263	0.830	0.968	0.930	0.933	0.878	0.750
w/o All Rewards	0.716	0.763	0.619	0.785	0.775	0.780	0.878	0.733	0.257	0.893	0.226	0.720	0.924	0.886	0.916	0.849	0.725

shown in Table 2, removing the text reward substantially degrades text binding, while removing the instance similarity reward mainly affects pixel- and identity-level consistency. The layout reward is important for spatial alignment, as its removal leads to a drop in IoU-related metrics. Removing all rewards results in the lowest overall performance, confirming that the three reward components provide complementary supervision during RL post-training.

Ablation on Text Reward Metrics. We further ablate the detailed metrics of the text reward, as text rendering errors can substantially compromise the usability of a poster. Similar to evaluation metrics, our text reward combines NED and sentence accuracy. Both metrics are first computed for each bound text element and then aggregated at the image level. NED, a continuous score in $[0, 1]$, is aggregated by arithmetic averaging. Sentence accuracy is binary and aggregated using a logical AND operation, assigning a score of one only when all bound text elements are rendered correctly. It therefore provides a stricter measure of poster-level text correctness. The combined text reward is defined as $R_{\text{text}} = wR_{\text{Sen. Acc.}} + (1-w)R_{\text{NED}}$, where w controls the contribution of sentence accuracy. We evaluate the effects of different weights $w \in \{0, 0.25, 0.5, 0.75, 1\}$. As shown in Table 3, $w = 0.75$ achieves the highest sentence accuracy and the second-highest NED without compromising layout adherence. Smaller weights, such as 0 and 0.25, overemphasize NED, allowing minor rendering errors to receive relatively high rewards and weakening the supervision for fully correct poster text. Conversely, setting $w = 1$ relies exclusively on sentence accuracy. During the early stage of reinforcement learning, rollout candidates generated with a guidance scale of 1.0 rarely render all text elements correctly, causing sentence accuracy to be frequently zero and producing an overly sparse reward. Combining the two metrics therefore balances dense character-level feedback with strict poster-level correctness.

Table 3: **Effects of different sentence accuracy reward weights.** Smaller weights tolerate minor text rendering errors, while larger weights overly on the sparse sentence accuracy during the early stage of RL post-training. The **best** and **second-best** results are highlighted in orange and blue, respectively. “NED”: normalized edit distance. “Sen. Acc.”: sentence accuracy.

Sen. Acc. Weight	Text Binding		
	NED	Sen. Acc.	IoU
0.75 (Default)	0.970	0.940	0.944
0.0	0.971	0.916	0.945
0.25	0.966	0.920	0.944
0.5	0.966	0.928	0.945
1.0	0.969	0.938	0.938

Table 4: **Effects of different LoRA target modules.** The **best** and **second-best** results are highlighted in orange and blue, respectively. “NED”: normalized edit distance. “Sen. Acc.”: sentence accuracy.

LoRA Target Modules	Pixel Binding					Identity Binding					Semantic Binding		Text Binding			Overall	
	DINO-I	CLIP-I	M-DINO	SSIM	IoU	DINO-I	CLIP-I	M-DINO	CLIP-T	IoU	CLIP-T	IoU	NED	Sen. Acc.	IoU	IoU	Avg. Score
Both Branches (Default)	0.716	0.763	0.619	0.785	0.775	0.780	0.878	0.733	0.257	0.893	0.226	0.720	0.924	0.886	0.916	0.849	0.725
Image Branch Only	0.712	0.764	0.623	0.787	0.777	0.772	0.873	0.731	0.256	0.881	0.226	0.710	0.913	0.878	0.906	0.841	0.721
Text Branch Only	0.714	0.764	0.626	0.786	0.775	0.770	0.868	0.722	0.253	0.882	0.224	0.711	0.926	0.891	0.916	0.846	0.722

Ablation on LoRA Target Modules. Our default setting applies LoRA to both the text and image branches of the pretrained MMDiT, adapting its original image-editing capability to poster generation through the Spatial Canvas Interface. As shown in Table 4, fine-tuning both branches achieves the best overall performance. The two branches play complementary roles in our framework: the text branch needs to adapt to the structured VL tokens that encode the Text Specifications and Spatial Canvas information, while the image branch must learn to jointly interpret the noisy target tokens and spatially organized canvas tokens for composition-aware generation. Fine-tuning only one branch

leaves the other insufficiently adapted to the new conditioning interface, resulting in consistently weaker binding performance.

5 CONCLUSION

In this work, we introduce Compo, a poster generation model built around a Spatial Canvas Interface that enables users to specify generation intent through explicit spatial composition rather than text prompting alone. The interface unifies semantic, identity, text, and pixel bindings with accompanying Text Specifications, providing fine-grained control over poster content, layout, and appearance. Compo is efficiently adapted from pretrained image editing models using automatically generated structured supervision and binding-aware reinforcement learning, and supports both direct composition and agentic generation from high-level user requests. Experiments show that Compo achieves stronger compositional controllability than both general-purpose image generation models and dedicated poster generation systems while maintaining high visual quality.

AI USE STATEMENT

In this work, we used large language models to assist data generation and annotation, including text asset preparation, prompt writing, instance captioning, and agentic planning, and image generation models to create target images for the dataset and benchmark. Additionally, we used large language models to improve the clarity and readability of the manuscript. We performed a manual human review of the LLM-generated text asset repositories to ensure they contain no toxic, harmful, or inappropriate content. Additionally, while large language models were utilized for language refinement during manuscript preparation, all contents were thoroughly reviewed and verified by the authors to guarantee they faithfully represent our original research ideas and experimental results. We take responsibility for the final content of this work, including text, claims, or artifacts produced with the aid of generative AI.

ETHICS STATEMENT

Our data consists of images sourced from publicly available image generation models. All assets used during experiments and manuscript writing are either obtained from publicly accessible Internet sources or created by generative models. We encourage responsible use of our models and data that respects user privacy and the intellectual property rights of image owners, particularly in commercial applications.

REPRODUCIBILITY STATEMENT

To facilitate reproducibility, Sections 3.1, 3.2, 3.3, and 4 describe the dataset construction, model training, inference pipeline, and evaluation settings, respectively. Appendices A.1, A.2, and B provide additional details on dataset and benchmark construction, supervised training, and reinforcement learning.

REFERENCES

- Anthropic. Introducing Claude Opus 4.6. <https://www.anthropic.com/news/claude-opus-4-6>, 2026. Accessed: 2026-08-27.
- Shuai Bai, Yuxuan Cai, Ruizhe Chen, Keqin Chen, Xionghui Chen, Zesen Cheng, Lianghao Deng, Wei Ding, Chang Gao, Chunjiang Ge, et al. Qwen3-vl technical report. *arXiv preprint arXiv:2511.21631*, 2025a.
- Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibao Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, Humen Zhong, Yanzhi Zhu, Mingkun Yang, Zhaohai Li, Jianqiang Wan, Pengfei Wang, Wei Ding, Zheren Fu, Yiheng Xu, Jiabo Ye, Xi Zhang, Tianbao Xie, Zesen Cheng, Hang Zhang, Zhibo Yang, Haiyang Xu, and Junyang Lin. Qwen2.5-vl technical report, 2025b. URL <https://arxiv.org/abs/2502.13923>.
- ByteDance. Seedream 5.0 Pro. https://seed.bytedance.com/en/seedream5_0_pro, 2026. Accessed: 2026-08-27.
- Huanqia Cai, Sihan Cao, Ruoyi Du, Peng Gao, Aiming Hao, Steven Hoi, Zhaohui Hou, Shijie Huang, Dengyang Jiang, Yuming Jiang, et al. Z-image: An efficient image generation foundation model with single-stream diffusion transformer. *arXiv preprint arXiv:2511.22699*, 2025.
- Qi Cai, Jingwen Chen, Chengmin Gao, Zijian Gong, Yehao Li, Yingwei Pan, Yi Peng, Zhaofan Qiu, Kai Yu, Yiheng Zhang, et al. Hidream-o1-image: A natively unified image generative foundation model with pixel-level unified transformer. *arXiv preprint arXiv:2605.11061*, 2026.
- Nicolas Carion, Laura Gustafson, Yuan-Ting Hu, Shoubhik Debnath, Ronghang Hu, Didac Suris Coll-Vinent, Chaitanya Ryali, Kalyan Vasudev Alwala, Haitham Khedr, Andrew Huang, et al. Sam 3: Segment anything with concepts. In *International Conference on Learning Representations*, volume 2026, pp. 138846–138923, 2026.

- Bowen Chen, Haomiao Sun, Li Chen, Xu Wang, Daniel Du, Xinglong Wu, et al. Xverse: Consistent multi-subject control of identity and semantic attributes via dit modulation. *Advances in Neural Information Processing Systems*, 38:7437–7459, 2026a.
- Dong Chen, Fangyun Wei, Ziyu Wan, Dongdong Chen, Jiawei Zhang, Jinjing Zhao, Sirui Zhang, Yang Yue, Zhiyang Liang, Baining Guo, et al. Lens: Rethinking training efficiency for foundational text-to-image models. *arXiv preprint arXiv:2605.21573*, 2026b.
- Guoxuan Chen, Chufeng Xiao, Haoran Yang, Siyue Xie, Binxiao Huang, Ming Zhang, Cheuk Him Chau, Xinyu Fu, Yingzhao Lian, Tom SY Li, et al. Boogu-image-0.1: Boosting open-source unified multimodal understanding and generation. *arXiv preprint arXiv:2607.13125*, 2026c.
- Haoyu Chen, Xiaojie Xu, Wenbo Li, Jingjing Ren, Tian Ye, Songhua Liu, Ying-Cong Chen, Lei Zhu, and Xinchao Wang. Posta: A go-to framework for customized artistic poster generation. In *2025 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 28694–28704. IEEE, 2025a.
- Jingye Chen, Yupan Huang, Tengchao Lv, Lei Cui, Qifeng Chen, and Furu Wei. Textdiffuser-2: Unleashing the power of language models for text rendering. In *European Conference on Computer Vision*, pp. 386–402. Springer, 2024.
- Sixiang Chen, Jianyu Lai, Jialin Gao, Tian Ye, Haoyu Chen, Hengyu Shi, Shitong Shao, Yunlong Lin, Song Fei, Zhaohu Xing, et al. Postercraft: Rethinking high-quality aesthetic poster generation in a unified framework. *arXiv preprint arXiv:2506.10741*, 2025b.
- Sixiang Chen, Jianyu Lai, Jialin Gao, Hengyu Shi, Zhongying Liu, Tian Ye, Junfeng Luo, Xiaoming Wei, and Lei Zhu. Posteromni: Generalized artistic poster creation via task distillation and unified reward feedback. *arXiv preprint arXiv:2602.12127*, 2026d.
- Zhekai Chen, Yuqing Wang, Manyuan Zhang, and Xihui Liu. Macro: Advancing multi-reference image generation with structured long-context data. *arXiv preprint arXiv:2603.25319*, 2026e.
- Bo Cheng, Yuhang Ma, Liebucha Wu, Shanyuan Liu, Ao Ma, Xiaoyu Wu, Dawei Leng, and Yuhui Yin. Hico: Hierarchical controllable diffusion model for layout-to-image generation. *Advances in neural information processing systems*, 37:128886–128910, 2024.
- Yufeng Cheng, Wenxu Wu, Shaojin Wu, Mengqi Huang, Fei Ding, and Qian He. Umo: Scaling multi-identity consistency for image customization via matching reward. *arXiv preprint arXiv:2509.06818*, 2025.
- Yusuf Dalva, Gordon Guocheng Qian, Maya Goldenberg, Tsai-Shien Chen, Kfir Aberman, Sergey Tulyakov, Pinar Yanardag, and Kuan-Chieh Jackson Wang. Canvas-to-image: Compositional image generation with multimodal controls. In *Proceedings of the Special Interest Group on Computer Graphics and Interactive Techniques Conference Conference Papers*, pp. 1–11, 2026.
- Datalab. Announcing Chandra OCR 2: 90+ Languages, Top Benchmarks. <https://www.datalab.to/blog/chandra-2>, 2026. Accessed: 2026-08-27.
- Chaorui Deng, Deyao Zhu, Kunchang Li, Chenhui Gou, Feng Li, Zeyu Wang, Shu Zhong, Weihao Yu, Xiaonan Nie, Ziang Song, Guang Shi, and Haoqi Fan. Emerging properties in unified multimodal pretraining. *arXiv preprint arXiv:2505.14683*, 2025.
- Haiwen Diao, Penghao Wu, Hanming Deng, Jiahao Wang, Shihao Bai, Silei Wu, Weichen Fan, Wenjie Ye, Wenwen Tong, Xiangyu Fan, et al. Sensenova-u1: Unifying multimodal understanding and generation with neo-unify architecture. *arXiv preprint arXiv:2605.12500*, 2026.
- Patrick Esser, Sumith Kulal, Andreas Blattmann, Rahim Entezari, Jonas Müller, Harry Saini, Yam Levi, Dominik Lorenz, Axel Sauer, Frederic Boesel, et al. Scaling rectified flow transformers for high-resolution image synthesis. In *Forty-first international conference on machine learning*, 2024.

- Yifan Gao, Zihang Lin, Chuanbin Liu, Min Zhou, Tiezheng Ge, Bo Zheng, and Hongtao Xie. Poster-maker: Towards high-quality product poster generation with accurate text rendering. In *2025 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 8083–8093. IEEE, 2025.
- Daniel Garibi, Shahar Yadin, Roni Paiss, Omer Tov, Shiran Zada, Ariel Ephrat, Tomer Michaeli, Inbar Mosseri, and Tali Dekel. Tokenverse: Versatile multi-concept personalization in token modulation space. *ACM Transactions On Graphics (TOG)*, 44(4):1–11, 2025.
- Google. Gemini 3.5 Flash. <https://deepmind.google/models/model-cards/gemini-3-5-flash/>, 2026a. Accessed: 2026-08-27.
- Google. Nano Banana 2. <https://gemini.google/overview/image-generation/>, 2026b. Accessed: 2026-08-27.
- Grok. Grok Imagine. <https://grok.com/supergrok/imagine>, 2026. Accessed: 2026-08-27.
- Hsiao Yuan Hsu, Xiangteng He, Yuxin Peng, Hao Kong, and Qing Zhang. Posterlayout: A new benchmark and approach for content-aware visual-textual presentation layout. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 6018–6026, 2023.
- Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models. *arXiv preprint arXiv:2106.09685*, 2021.
- Taihang Hu, Zhao Wang, Zuan Gao, Tao Liu, Hao Yan, Zhengze Xu, Yuhang Yu, Yongchao Du, Xingjian Wang, Jun Zheng, et al. Swift-image: Exploring the performance frontier of compact unified image generation models. *arXiv preprint arXiv:2608.20334*, 2026.
- Xiwei Hu, Haokun Chen, Zhongqi Qi, Hui Zhang, Dexiang Hong, Jie Shao, and Xinglong Wu. Dreamposter: A unified framework for image-conditioned generative poster design. *arXiv preprint arXiv:2507.04218*, 2025.
- Ideogram. Ideogram 4.0 Technical Details: Open model at the forefront of design. <https://ideogram.ai/blog/ideogram-4.0/>, 2026. Accessed: 2026-08-27.
- Black Forest Labs. FLUX.2: Frontier Visual Intelligence. <https://bfl.ai/blog/flux-2>, 2025.
- Yuheng Li, Haotian Liu, Qingyang Wu, Fangzhou Mu, Jianwei Yang, Jianfeng Gao, Chunyuan Li, and Yong Jae Lee. Gligen: Open-set grounded text-to-image generation. In *2023 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 22511–22521. IEEE, 2023.
- Jinpeng Lin, Min Zhou, Ye Ma, Yifan Gao, Chenxi Fei, Yangjian Chen, Zhang Yu, and Tiezheng Ge. Autoposter: A highly automatic and content-aware design system for advertising poster generation. In *Proceedings of the 31st ACM International Conference on Multimedia*, pp. 1250–1260, 2023.
- Jiaxiang Liu, Zhida Feng, Pengyu Zou, Zhenyu Qian, Tianrui Zhu, Jun Xia, Yuehu Dong, Yanzheng Lin, Honglin Xiong, Anqi Chen, et al. Ernie-image technical report. *arXiv preprint arXiv:2605.25347*, 2026.
- Shiyu Liu, Yucheng Han, Peng Xing, Fukun Yin, Rui Wang, Wei Cheng, Jiaqi Liao, Yingming Wang, Honghao Fu, Chunrui Han, et al. Step1x-edit: A practical framework for general image editing. *arXiv preprint arXiv:2504.17761*, 2025.
- Zeyu Liu, Weicong Liang, Zhanhao Liang, Chong Luo, Ji Li, Gao Huang, and Yuhui Yuan. Glyph-byt5: A customized text encoder for accurate visual text rendering. In *European Conference on Computer Vision*, pp. 361–377. Springer, 2024.
- Dongxing Mao, Yilin Wang, Linjie Li, Zhengyuan Yang, and Alex Jinpeng Wang. Textground4m: A prompt-aligned dataset for layout-aware text rendering. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 40, pp. 7918–7926, 2026.

- Microsoft. MAI-Image-2.6. <https://microsoft.ai/models/mai-image-2-6/>, 2026. Accessed: 2026-09-26.
- Chong Mou, Yanze Wu, Wenxu Wu, Zinan Guo, Pengze Zhang, Yufeng Cheng, Yiming Luo, Fei Ding, Shiwen Zhang, Xinghui Li, et al. Dreamo: A unified framework for image customization. In *Proceedings of the SIGGRAPH Asia 2025 Conference Papers*, pp. 1–12, 2025.
- OpenAI. Introducing GPT-5.5. <https://openai.com/index/introducing-gpt-5-5/>, 2026a. Accessed: 2026-08-27.
- OpenAI. GPT-5.6: Frontier intelligence that scales with your ambition. <https://openai.com/index/gpt-5-6/>, 2026b. Accessed: 2026-08-27.
- OpenAI. Introducing ChatGPT Images 2.0. <https://openai.com/index/introducing-chatgpt-images-2-0/>, 2026c. Accessed: 2026-08-27.
- Maxime Oquab, Timothée Darcet, Théo Moutakanni, Huy Vo, Marc Szafraniec, Vasil Khalidov, Pierre Fernandez, Daniel Haziza, Francisco Massa, Alaaeldin El-Nouby, et al. Dinov2: Learning robust visual features without supervision. *arXiv preprint arXiv:2304.07193*, 2023.
- William Peebles and Saining Xie. Scalable diffusion models with transformers. In *2023 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 4172–4182. IEEE, 2023.
- Yuyang Peng, Shishi Xiao, Keming Wu, Qisheng Liao, Bohan Chen, Kevin Lin, Danqing Huang, Ji Li, and Yuhui Yuan. Bizgen: Advancing article-level visual text rendering for infographics generation. In *2025 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 23615–23624. IEEE, 2025.
- Yifan Pu, Yiming Zhao, Zhicong Tang, Ruihong Yin, Haoxing Ye, Yuhui Yuan, Dong Chen, Jianmin Bao, Sirui Zhang, Yanbin Wang, et al. Art: Anonymous region transformer for variable multi-layer transparent image generation. In *2025 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 7952–7962. IEEE, 2025.
- Can Qin, Shu Zhang, Ning Yu, Yihao Feng, Xinyi Yang, Yingbo Zhou, Huan Wang, Juan Carlos Niebles, Caiming Xiong, Silvio Savarese, et al. Unicontrol: A unified diffusion model for controllable visual generation in the wild. *arXiv preprint arXiv:2305.11147*, 2023.
- Qwen Team. Qwen3.5: Towards Native Multimodal Agents. <https://qwen.ai/blog?id=qwen3.5>, February 2026a. Accessed: 2026-08-27.
- Qwen Team. Qwen-Image-3.0: Rich Content, Authentic Details, Deep Knowledge. <https://qwen.ai/blog?id=qwen-image-3.0>, 2026b. Accessed: 2026-08-27.
- Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pp. 8748–8763. PmLR, 2021.
- Reve. Launching Reve 2.1. <https://blog.reve.com/posts/launching-reve-2.1/>, 2026. Accessed: 2026-08-27.
- Nataniel Ruiz, Yuanzhen Li, Varun Jampani, Yael Pritch, Michael Rubinstein, and Kfir Aberman. Dreambooth: Fine tuning text-to-image diffusion models for subject-driven generation. In *2023 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 22500–22510. IEEE, 2023.
- Jaeyung Seol, Seojun Kim, and Jaejun Yoo. Posterllama: Bridging design ability of language model to content-aware layout generation. In *European Conference on Computer Vision*, pp. 451–468. Springer, 2024.
- Dong She, Siming Fu, Mushui Liu, Qiaoqiao Jin, Hualiang Wang, Jidong Jiang, et al. Mosaic: Multi-subject personalized generation via correspondence-aware alignment and disentanglement. In *International Conference on Learning Representations*, volume 2026, pp. 63128–63156, 2026.

- Lin Song, Wenbo Li, Guoqing Ma, Wei Tang, Bo Wang, Yuan Zhang, Yijun Yang, Yicheng Xiao, Jianhui Liu, Yanbing Zhang, et al. Joyai-image: Awaking spatial intelligence in unified multi-modal understanding and generation. *arXiv preprint arXiv:2605.04128*, 2026.
- Zhenxiong Tan, Songhua Liu, Xingyi Yang, Qiaochu Xue, and Xinchao Wang. Ominicontrol: Minimal and universal control for diffusion transformer. In *2025 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 14940–14950. IEEE, 2025.
- Meituan LongCat Team, Hanghang Ma, Haoxian Tan, Jiale Huang, Junqiang Wu, Jun-Yan He, Lishuai Gao, Songlin Xiao, Xiaoming Wei, Xiaoqi Ma, et al. Longcat-image technical report. *arXiv preprint arXiv:2512.07584*, 2025.
- Super Intelligence Team, Changhao Qiao, Chao Hui, Chen Li, Cunzheng Wang, Dejie Song, Jiale Zhang, Jing Li, Qiang Xiang, Runqi Wang, et al. Firered-image-edit-1.0 technical report. *arXiv preprint arXiv:2602.13344*, 2026.
- Yuxiang Tuo, Yifeng Geng, and Liefeng Bo. Anytext2: Visual text generation and editing with customizable attributes. *arXiv preprint arXiv:2411.15245*, 2024.
- Haoxuan Wang, Jinlong Peng, Qingdong He, Hao Yang, Ying Jin, Jiafu Wu, Xiaobin Hu, Yanjie Pan, Zhenye Gan, Mingmin Chi, et al. Unicombine: Unified multi-conditional combination with diffusion transformer. In *2025 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 18325–18334. IEEE, 2025a.
- Xierui Wang, Siming Fu, Qihan Huang, Wanggui He, and Hao Jiang. Ms-diffusion: Multi-subject zero-shot image personalization with layout guidance. In *International Conference on Learning Representations*, volume 2025, pp. 95118–95146, 2025b.
- Xudong Wang, Trevor Darrell, Sai Saketh Rambhatla, Rohit Girdhar, and Ishan Misra. Instancediffusion: Instance-level control for image generation. In *2024 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 6232–6242. IEEE, 2024.
- Zhendong Wang, Jianmin Bao, Shuyang Gu, Dong Chen, Wengang Zhou, and Houqiang Li. Designdiffusion: High-quality text-to-design image generation with diffusion models. In *2025 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 20906–20915. IEEE, 2025c.
- Zhou Wang, Alan C Bovik, Hamid R Sheikh, and Eero P Simoncelli. Image quality assessment: from error visibility to structural similarity. *IEEE transactions on image processing*, 13(4):600–612, 2004.
- Chenfei Wu, Jiahao Li, Jingren Zhou, Junyang Lin, Kaiyuan Gao, Kun Yan, Sheng-ming Yin, Shuai Bai, Xiao Xu, Yilei Chen, et al. Qwen-image technical report. *arXiv preprint arXiv:2508.02324*, 2025a.
- Chenyuan Wu, Jiahao Wang, Pengfei Zheng, Ruirao Yan, Shitao Xiao, Xin Luo, Yueze Wang, Wanli Li, Xiyan Jiang, Yexin Liu, et al. Omnigen2: Towards instruction-aligned multimodal generation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 21964–21975, 2026.
- Jay Zhangjie Wu, Xuanchi Ren, Tianchang Shen, Tianshi Cao, Kai He, Yifan Lu, Ruiyuan Gao, Enze Xie, Shiyi Lan, Jose M Alvarez, et al. Chronoedit: Towards temporal reasoning for image editing and world simulation. *arXiv preprint arXiv:2510.04290*, 2025b.
- Shaojin Wu, Mengqi Huang, Wenxu Wu, Yufeng Cheng, Fei Ding, and Qian He. Less-to-more generalization: Unlocking more controllability by in-context generation. In *2025 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 18682–18692. IEEE, 2025c.
- Bin Xia, Bohao Peng, Yuechen Zhang, Junjia Huang, Jiyang Liu, Jingyao Li, Haoru Tan, Sitong Wu, Chengyao Wang, Yitong Wang, et al. Dreamomni2: Multimodal instruction-based editing and generation. *arXiv preprint arXiv:2510.06679*, 2025.

- Ruihang Xu, Dewei Zhou, Fan Ma, and Yi Yang. Contextgen: Contextual layout anchoring for identity-consistent multi-instance generation. In *International Conference on Learning Representations*, volume 2026, pp. 95978–96007, 2026a.
- Yiyan Xu, Qiulin Wang, Wenjie Wang, Yunhao Mao, Xintao Wang, Pengfei Wan, Kun Gai, and Fuli Feng. Unicustom: Unified visual conditioning for multi-reference image generation. *arXiv preprint arXiv:2605.12088*, 2026b.
- Tao Yang, Yingmin Luo, Zhongang Qi, Yang Wu, Ying Shan, and Chang Wen Chen. Posterllava: Constructing a unified multi-modal layout generator with llm. *arXiv preprint arXiv:2406.02884*, 2024.
- Junchao Yi, Rui Zhao, Jiahao Tang, Weixian Lei, Linjie Li, Qisheng Su, Zhengyuan Yang, Lijuan Wang, Xiaofeng Zhu, and Alex Jinpeng Wang. Flowinone: Unifying multimodal generation as image-in, image-out flow matching. *arXiv preprint arXiv:2604.06757*, 2026.
- Z.ai. GLM-Image: Auto-regressive for Dense-knowledge and High-fidelity Image Generation. <https://z.ai/blog/glm-image>, 2026. Accessed: 2026-08-27.
- Hui Zhang, Dexiang Hong, Yitong Wang, Jie Shao, Xinglong Wu, Zuxuan Wu, and Yu-Gang Jiang. Creatilayout: Siamese multimodal diffusion transformer for creative layout-to-image generation. In *2025 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 18487–18497. IEEE, 2025a.
- Hui Zhang, Dexiang Hong, Maoke Yang, Yutao Cheng, Zhao Zhang, Weidong Chen, Jie Shao, Xinglong Wu, Zuxuan Wu, and Yu-Gang Jiang. Creatidesign: A unified multi-conditional diffusion transformer for creative graphic design. In *International Conference on Learning Representations*, volume 2026, pp. 111201–111214, 2026.
- Zhao Zhang, Yutao Cheng, Dexiang Hong, Maoke Yang, Gonglei Shi, Lei Ma, Hui Zhang, Jie Shao, and Xinglong Wu. Creatiposter: Towards editable and controllable multi-layer graphic design generation. *arXiv preprint arXiv:2506.10890*, 2025b.
- Guangcong Zheng, Xianpan Zhou, Xuwei Li, Zhongang Qi, Ying Shan, and Xi Li. Layoutdiffusion: Controllable diffusion model for layout-to-image generation. In *2023 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 22490–22499. IEEE, 2023.
- Kaiwen Zheng, Huayu Chen, Haotian Ye, Haoxiang Wang, Qinsheng Zhang, Kai Jiang, Hang Su, Stefano Ermon, Jun Zhu, and Ming-Yu Liu. Diffusionnft: Online diffusion reinforcement with forward process. In *International Conference on Learning Representations*, volume 2026, pp. 134129–134150, 2026.
- Dewei Zhou, You Li, Fan Ma, Xiaoting Zhang, and Yi Yang. Migc: Multi-instance generation controller for text-to-image synthesis. In *2024 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 6818–6828. IEEE, 2024.
- Dewei Zhou, Mingwei Li, Zongxin Yang, and Yi Yang. Dreamrenderer: Taming multi-instance attribute control in large-scale text-to-image models. In *2025 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 16712–16722. IEEE, 2025.
- Chenyang Zhu, Kai Li, Yue Ma, Chunming He, and Xiu Li. Multiboost: Towards generating all your concepts in an image from text. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pp. 10923–10931, 2025.

Appendix

A DATASET AND BENCHMARK DETAILS

A.1 COMPO-200K DATASET

Text Asset Collection. Leveraging advanced large language models (LLMs), including *GPT-5.5* (OpenAI, 2026a), *Claude Opus 4.6* (Anthropic, 2026), and *Gemini 3.5 Flash* (Google, 2026a), we curate two distinct text asset repositories to ensure broad semantic and visual coverage. Specifically, the content repository contains roughly 1,000 instances spanning 12 poster themes such as product advertising, public service, and entertainment, while the style repository consists of around 250 fine-grained visual style descriptions.

LLM Planning. To construct each training sample, we first sample a poster theme, 3–8 associated instances, and a visual style from our repositories. Guided by system prompts in Section D.1, GPT-5.5 then plans additional design elements required for poster generation as described in Section 3.1, and produces a structured JSON specification that integrates the sampled assets with the newly planned elements. Ultimately, this procedure yields approximately 200K structured plans, which serve as inputs for subsequent prompt rewriting to facilitate downstream poster data generation.

LLM Rewriting. Guided by system prompts in Section D.2, GPT-5.5 converts each structured JSON specification into a natural-language poster generation prompt, faithfully preserving both sampled assets and planned design attributes.

Text-to-Poster Generation. To synthesize poster images, we employ three text-to-image models, including *Qwen-Image-2512* (Wu et al., 2025a), *Z-Image* (Cai et al., 2025), and *ERNIE-Image* (Liu et al., 2026), as generation backends, capitalizing on their superior instruction following, text rendering, and graphic design capabilities. For each prompt, we randomly select one model to render a poster at 1024^2 resolution, thereby enhancing dataset diversity and mitigating model-specific biases. The data generation pipeline is conducted on approximately $32\times$ NVIDIA A100 80GB GPUs.

Instance Segmentation, Relighting, and Reposing. Leveraging semantic labels from the structured plans, we perform text-guided segmentation via *SAM-3* (Carion et al., 2026) to extract visual instances. To standardize these extracted assets, we employ *FLUX.2-klein-9B* (Labs, 2025) to normalize their pose or illumination: identity instances are reposed into predefined canonical postures (e.g., front-facing, arm-folded, three-quarter standing, and half-length portraits), whereas object instances undergo flat relighting to eliminate specular highlights and directional shadows.

Text Recognition. To extract visual text alongside its spatial layout, we adopt *Chandra-OCR-2* (Datalab, 2026), a specialized vision-language model built upon *Qwen3.5* (Qwen Team, 2026a), for joint text recognition and region localization. To enforce strict alignment with the rendered poster and mitigate potential generation discrepancies, we adopt the OCR-recognized text, rather than the initial specification in the structured plan, as the final ground-truth annotation.

Spatial Canvas Rendering and Text Specification Formulation. Given the instance segmentation and text recognition results, we construct a black Spatial Canvas matching the resolution of the target poster. Visual instance locations are derived from segmentation masks, while text regions are extracted directly from recognition results. We populate the canvas with four binding types: for *Text Binding*, each region is framed by a white bounding box labeled with an indexed identifier, “txt-k”; for *Identity Binding*, we place the reposed identity reference within its bounding box, tagged with “obj-k”. Object instances are randomly assigned to either *Pixel Binding* (where the reference image is directly pasted without extra annotation) or *Semantic Binding* (where only a bounding box containing the class name, e.g., “lemon”, is rendered). All identifiers, bounding boxes, and reference images are rendered directly on the Spatial Canvas, while their detailed descriptions are systematically documented in the Text Specifications.

A.2 BENCHMARK

Benchmark Data Creation. To construct each evaluation sample, we randomly sample a theme, 4–9 associated instances, and a visual style using random seeds different from those used for training data generation. The number of instances is intentionally larger than the 3–8 instances used during

training data generation, making the benchmark more challenging. Following the training data generation pipeline while ensuring no overlap with the training set, we curate a benchmark of 500 samples. Each sample is paired with a Spatial Canvas and detailed structured annotations.

Evaluation Metrics. During evaluation, each model is provided with inputs in its expected format. For general text-and-image-to-image models, the inputs are directly constructed from the Spatial Canvas, Text Specifications, and supplementary task instructions for accurate interpretation of the input conditions. For dedicated poster generation methods, the structured benchmark annotations are converted into the respective input formats prescribed by each method, while preserving as much of the original information as supported by their native input protocols. The benchmark metrics are then computed fully automatically from the generated poster images and the corresponding pre-constructed structured annotations, including instance images, rendered text, and layout bounding boxes. This evaluation protocol is fully model-agnostic and requires neither model-specific input designs nor access to model-specific internal representations.

B IMPLEMENTATION DETAILS

B.1 SUPERVISED TRAINING

We initialize our models from LongCat-Image-Edit (Team et al., 2025) and Qwen-Image-Edit-2511 (Wu et al., 2025a), and fine-tune them using LoRA (Hu et al., 2021) with a rank of 128. We employ aspect-ratio bucketing with a target resolution of approximately 1024^2 pixels. For LongCat-Image-Edit, we use $8 \times$ NVIDIA A100 80GB GPUs with a global batch size of 64, while Qwen-Image-Edit-2511 is trained on $16 \times$ NVIDIA A100 80GB GPUs with a global batch size of 32. For both models, we use a constant learning rate of $1e-4$ with 500 warmup steps.

B.2 REINFORCEMENT LEARNING

Both models are initialized from their respective supervised training checkpoints, using a newly introduced LoRA module with a reduced rank of 64. During rollout generation, each input sample yields 10 candidates using 10 denoising steps at a guidance scale of 1.0. Specifically, LongCat-Image-Edit operates at a resolution of 1024^2 pixels, whereas Qwen-Image-Edit-2511 is configured at a lower resolution of 512^2 to alleviate GPU memory overhead. Both models are trained on $16 \times$ NVIDIA A100 80GB GPUs.

For each rollout candidate, we evaluate the generated image using the same region-matching protocol as our benchmark. We employ SAM-3 (Carion et al., 2026) to segment visual instances and Chandra-OCR-2 (Datalab, 2026) to detect rendered text and its corresponding spatial regions. Each detected visual or text region is matched to its ground-truth counterpart based on maximum IoU. If the resulting IoU falls below a predefined threshold, the match is considered invalid, and all associated rewards are set to zero. For valid matches, we compute element-level rewards according to their binding types. For Text Binding, the text reward is based on sentence accuracy and normalized edit distance. For Semantic Binding, we use CLIP-T (Radford et al., 2021); for Identity Binding, we use CLIP-I (Radford et al., 2021), DINO-I (Oquab et al., 2023), and CLIP-T; and for Pixel Binding, we use CLIP-I and DINO-I. The layout reward is defined as the IoU between each matched region and its ground-truth location and is computed for both visual and textual elements.

We aggregate the element-level rewards into an image-level reward for each rollout candidate. Sentence accuracy is aggregated using a logical AND operation, yielding one only when all bound text elements are rendered correctly, while all other reward metrics are aggregated by arithmetic averaging over the corresponding elements. We then combine the image-level text, similarity, and layout rewards to optimize the trainable LoRA modules using the DiffusionNFT (Zheng et al., 2026) objective. Specifically, the overall reward is defined as

$$R = \lambda_{\text{Text}} R_{\text{Text}} + \lambda_{\text{Ins.Sim.}} R_{\text{Ins.Sim.}} + \lambda_{\text{Layout}} R_{\text{Layout}}, \quad (1)$$

where λ_{Text} , $\lambda_{\text{Ins.Sim.}}$, and λ_{Layout} control the contributions of text rendering, instance similarity, and layout adherence, respectively. We set $\lambda_{\text{Text}} = 0.4$, $\lambda_{\text{Ins.Sim.}} = 0.4$, and $\lambda_{\text{Layout}} = 0.2$ throughout RL post-training.

B.3 AGENTIC MODE

Our Agentic Mode adopts a workflow-based pipeline with verification of image search results. We use *GPT-5.6* (OpenAI, 2026b) as both the planner and verifier. Using the prompts detailed in Section D.3, GPT-5.6 extracts the visual instances, determines their binding types, and infers their spatial relationships. For instances requiring image search, it further verifies the relevance and correctness of the retrieved images.

C MORE RESULTS

C.1 QUANTITATIVE RESULTS

We additionally compare our Compo models before and after RL post-training. As shown in Table 5, *Compo-LongCat-Base* and *Compo-Qwen-Base* denote the models after supervised training, whereas *Compo-LongCat* and *Compo-Qwen* denote their corresponding models after RL post-training. Our RL objective incorporates three complementary reward components, providing diverse supervision signals during post-training. As a result, RL post-training yields consistent improvements across most evaluation metrics for both model variants.

Table 5: We compare our Compo models before and after RL post-training across pixel, identity, semantic, and text binding metrics. Higher values indicate better performance. The **best** and **second-best** results are highlighted in orange and blue, respectively. “NED”: normalized edit distance. “Sen. Acc.”: sentence accuracy.

Models	Pixel Binding					Identity Binding					Semantic Binding			Text Binding			Overall	
	DINO-I	CLIP-I	M-DINO	SSIM	IoU	DINO-I	CLIP-I	M-DINO	CLIP-T	IoU	CLIP-T	IoU	NED	Sen. Acc.	IoU	IoU	Avg. Score	
Compo-LongCat-Base	0.716	0.763	0.619	0.785	0.775	0.780	0.878	0.733	0.257	0.893	0.226	0.720	0.924	0.886	0.916	0.849	0.725	
Compo-Qwen-Base	0.720	0.765	0.631	0.785	0.772	0.791	0.891	0.758	0.259	0.918	0.217	0.716	0.907	0.858	0.906	0.845	0.726	
Compo-LongCat	0.735	0.776	0.642	0.793	0.781	0.795	0.891	0.757	0.261	0.904	0.259	0.828	0.970	0.940	0.944	0.885	0.752	
Compo-Qwen	0.734	0.770	0.649	0.782	0.773	0.810	0.910	0.781	0.263	0.932	0.262	0.850	0.940	0.868	0.934	0.886	0.751	

C.2 QUALITATIVE RESULTS

We provide additional visual comparisons with representative baselines in Figures 6 and 7. To further assess the generalization of our Compo models, Figure 8 presents results at various resolutions across diverse trending themes and visual elements, including cutting-edge technology, Disney and Japanese animation, and AI industry news. All these themes and elements are unseen during training. Despite this distribution shift, our models consistently produce visually coherent and plausible poster designs, demonstrating robust generalization and practical applicability.



Figure 6: **Additional visual comparison with representative baselines (Part 1).** We compare Compo with dedicated poster generation methods (PosterMaker (Gao et al., 2025), PosterOmni (Chen et al., 2026d), and CreatiDesign (Zhang et al., 2026)) and the best-performing general text-and-image-to-image baseline in Table 1, HiDream-O1-Image (Cai et al., 2026). Transparent pink boxes highlight noticeable errors.



Figure 7: **Additional visual comparison with representative baselines (Part 2).** We compare Compo with dedicated poster generation methods (PosterMaker (Gao et al., 2025), PosterOmni (Chen et al., 2026d), and CreatiDesign (Zhang et al., 2026)) and the best-performing general text-and-image-to-image baseline in Table 1, HiDream-O1-Image (Cai et al., 2026). Transparent pink boxes highlight noticeable errors.



Figure 8: **Additional visualizations at various resolutions across diverse trending themes and visual elements.** Our Compo models can generate visually coherent and plausible poster designs based on diverse trending themes and visual elements that are unseen during training, demonstrating robust generalization and practical applicability.

D PROMPT GALLERY

D.1 PROMPT FOR LLM PLANNING IN DATASET GENERATION

LLM Planning System Prompt (Identity-Object Interaction)

You are a poster semantic planning agent.

Your task is to design a coherent poster concept based on the given input:

"Humanoids: [x1, x2, x3, ...], Things: [y1, y2, y3, ...], Theme: xxxx"

You must generate a structured semantic plan for a poster image. The plan will later be used by another model to write a full image-generation prompt.

Your output must be a valid JSON object only. Do not include markdown, comments, explanations, or any text outside the JSON.

Output schema:

```
{
  "scenario": string,
  "bg_prompt": string,
  "visual_text": [string, string, string, string, string, ...],
  "HOI": {
    "<humanoid_name>": {
      "action": string,
      "target_objects": [string, ...],
      "description": string
    }
  }
}
```

Planning requirements:

1. Scenario
 - Create one specific poster scenario that matches the given Theme and all input objects.
 - The scenario should describe the poster's concrete purpose, such as a product campaign, event promotion, public service message, entertainment poster, travel ad, education campaign, sports promotion, fashion campaign, or festival poster.
 - The scenario must be coherent with the given Humanoids and Things.
 - Do not make the scenario too generic. Avoid vague phrases like "a creative poster" or "an interesting advertisement".
 - The scenario should be one concise sentence.
2. Background Prompt
 - Generate one concise bg_prompt that describes the overall background of the poster.
 - The bg_prompt should support the Theme and scenario through setting, atmosphere, color mood, graphic patterns, environmental context, depth, or decorative background elements.
 - The bg_prompt must describe background only, not foreground subjects or products.
 - The bg_prompt must not contain any existing foreground object from the input Humanoids or Things lists.
 - Do not mention, repeat, or imply the exact names of any input Humanoids or Things in bg_prompt.
 - Do not include human-object interactions, actions, product placement, poster text, slogans, or typography in bg_prompt.
 - Keep bg_prompt visually useful, safe, concise, and suitable for image generation.

3. Visual Text

- Generate **3 to 5 short visual text phrases** that can appear on the poster.
- The visual text should match the Theme, scenario, and objects.
- Include a mix of poster text roles, such as:
 - main headline
 - subheadline
 - slogan
 - call-to-action
 - badge text
 - short feature phrase
 - event/promo phrase
 - date/location phrase
- Each text phrase should be short and readable.
- Prefer natural poster-style English.
- Avoid overly long sentences.
- Avoid uncommon symbols, complex punctuation, or hard-to-render typography.
- Do not include explanations of text roles; output only the text strings in the list.
- The text should be visually useful for a poster, not a paragraph.

4. HOI

- For each humanoid in Humanoids, create exactly one HOI entry.
- The HOI key must exactly match the humanoid name from the input.
- Each humanoid should have a clear action or pose.
- The action should support the Theme and scenario.
- If possible, create meaningful human-object interactions between humanoids and Things.
- A humanoid may interact with zero, one, or multiple Things.
- "target_objects" must only contain objects from the input Things list.
- If the humanoid does not interact with any Thing, set "target_objects": [].
- Do not invent target objects that are not in Things.
- Do not invent additional humanoids.

5. Object Usage

- Try to make every Thing visually relevant in the scenario.
- Important Things should be used as products, props, foreground decorations, or interaction targets.
- If there are more Things than can be naturally used in HOI, some Things may be implied by the scenario or visual text, but HOI target_objects must still only include actual interaction targets.

6. Action Design

- Prefer concrete, visually grounded actions, such as:
 - holding, presenting, drinking, eating, pointing at, riding, wearing, carrying, playing, reading, using, waving, giving a thumbs-up, posing confidently, dancing, running, protecting, teaching, performing.
- Avoid abstract actions that are hard to visualize, such as:
 - appreciating, enjoying, supporting, representing, symbolizing, promoting.
- Avoid unsafe, violent, sexual, hateful, or disturbing actions.
- Avoid actions that are physically impossible or visually confusing.
- Keep actions simple enough for image generation.

7. Style of Descriptions

- The "description" field should be a clear visual sentence.
- Mention the target objects naturally if target_objects is non-empty.
- Use present tense.

- Avoid excessive detail.
- Avoid camera, lighting, rendering style, or layout descriptions in HOI; these belong to the later full prompt stage.
- Keep each description concise but specific.

8. Consistency

- The JSON must be valid and parseable.
- Do not add trailing commas.
- Do not use duplicated keys.
- Do not omit bg_prompt.
- Do not omit any humanoid from HOI.
- Do not include any input Humanoid or Thing name inside bg_prompt.
- Preserve exact spelling and capitalization of input object names.
- The output should be semantically coherent and suitable for generating a poster image.

Example input:

Humanoids: ["Iron Man", "panda", "polar bear"]

Things: ["coca-cola", "orange", "watermelon"]

Theme: Product_Advertising

Example output:

```
{
  "scenario": "A cheerful online shopping product advertisement
    promoting refreshing drinks and summer fruits with heroic mascot
    characters.",
  "bg_prompt": "a bright summer shopping backdrop with clean geometric
    shapes, warm sunshine gradients, fresh color accents, and
    spacious commercial display atmosphere",
  "visual_text": [
    "Hero Fresh Deals",
    "Cool Drinks, Fresh Fruits",
    "Refresh Your Cart",
    "Limited Summer Offer",
    "Shop Now"
  ],
  "HOI": {
    "Iron Man": {
      "action": "holding",
      "target_objects": ["coca-cola", "orange"],
      "description": "holds a bottle of coca-cola in his left hand and
        an orange in his right hand"
    },
    "panda": {
      "action": "thumbs up",
      "target_objects": [],
      "description": "gives a cheerful thumbs-up gesture toward the
        viewer"
    },
    "polar bear": {
      "action": "eating",
      "target_objects": ["watermelon"],
      "description": "eats a slice of watermelon happily"
    }
  }
}
```

LLM Planning System Prompt (Object Only)

You are a poster semantic planning agent.

Your task is to design a coherent object-only poster concept based on the given input:

"Things: [y1, y2, y3, ...], Theme: xxxx"

You must generate a structured semantic plan for a poster image. The plan will later be used by another model to write a full image-generation prompt.

Your output must be a valid JSON object only. Do not include markdown, comments, explanations, or any text outside the JSON.

Output schema:

```
{
  "scenario": string,
  "bg_prompt": string,
  "visual_text": [string, string, string, string, string, ...],
  "obj_only": {
    "<thing_name>": {
      "description": string
    }
  }
}
```

Planning requirements:

1. Scenario

- Create one specific poster scenario that matches the given Theme and all input Things.
- The scenario should describe the poster's concrete purpose, such as a product campaign, event promotion, public service message, entertainment poster, travel ad, education campaign, sports promotion, fashion campaign, or festival poster.
- The scenario must be coherent with the given Things.
- Do not make the scenario too generic. Avoid vague phrases like "a creative poster" or "an interesting advertisement".
- The scenario should be one concise sentence.

2. Background Prompt

- Generate one concise bg_prompt that describes the overall background of the poster.
- The bg_prompt should support the Theme and scenario through setting, atmosphere, color mood, graphic patterns, environmental context, depth, or decorative background elements.
- The bg_prompt must describe background only, not foreground products, props, or display items.
- The bg_prompt must not contain any existing foreground object from the input Things list.
- Do not mention, repeat, or imply the exact names of any input Things in bg_prompt.
- Do not include product placement, object display, poster text, slogans, typography, or object-specific attributes in bg_prompt.
- Keep bg_prompt visually useful, safe, concise, and suitable for image generation.

3. Visual Text

- Generate **3 to 5 short visual text phrases** that can appear on the poster.
- The visual text should match the Theme, scenario, and Things.
- Include a mix of poster text roles, such as:
 - main headline
 - subheadline
 - slogan
 - call-to-action

- badge text
 - short feature phrase
 - event/promo phrase
 - date/location phrase
 - Each text phrase should be short and readable.
 - Prefer natural poster-style English.
 - Avoid overly long sentences.
 - Avoid uncommon symbols, complex punctuation, or hard-to-render typography.
 - Do not include explanations of text roles; output only the text strings in the list.
 - The text should be visually useful for a poster, not a paragraph.
4. Object-Only Descriptions
- For each thing in Things, create exactly one `obj_only` entry.
 - The `obj_only` key must exactly match the thing name from the input.
 - Each entry must contain only one field: "description".
 - The "description" field should describe visual attributes of the object itself, not an interaction.
 - The description may include attributes such as color, shape, material, texture, size, packaging, freshness, condition, branding style, product finish, decorative details, or visible features.
 - Keep each description visually grounded and useful for image generation.
 - Use present tense or adjective-based phrasing.
 - Do not mention humanoids, hands, poses, actions, or human-object interactions.
 - Do not invent additional objects as `obj_only` keys.
5. Object Usage
- Try to make every Thing visually relevant in the scenario.
 - Important Things should be used as products, props, foreground decorations, display items, product clusters, or visual motifs.
 - If there are many Things, describe how they can coexist naturally in one poster scenario.
 - Do not make any input Thing invisible, hidden, or irrelevant.
6. Description Design
- Prefer concrete, visually grounded object descriptions, such as: glossy red aluminum can with condensation, ripe orange with dimpled peel, compact black wireless earbuds case, folded blue travel umbrella, clean white ceramic mug.
 - Avoid abstract descriptions that are hard to visualize, such as: meaningful, symbolic, important, representative, high-value, impressive.
 - Avoid unsafe, violent, sexual, hateful, or disturbing descriptions.
 - Avoid camera, lighting, rendering style, or layout descriptions in `obj_only`; these belong to the later full prompt stage.
 - Keep each description concise but specific.
7. Consistency
- The JSON must be valid and parseable.
 - Do not add trailing commas.
 - Do not use duplicated keys.
 - Do not omit `bg_prompt`.
 - Do not omit any thing from `obj_only`.
 - Do not include any input Thing name inside `bg_prompt`.
 - Preserve exact spelling and capitalization of input thing names.
 - The output should be semantically coherent and suitable for generating a poster image.

Example input:
 Things: ["coca-cola", "orange", "watermelon"]

Theme: Product_Advertising

Example output:

```
{
  "scenario": "A cheerful summer product advertisement promoting
    refreshing drinks and fresh fruit for a bright seasonal shopping
    campaign.",
  "bg_prompt": "a bright summer shopping backdrop with clean geometric
    shapes, warm sunshine gradients, fresh color accents, and
    spacious commercial display atmosphere",
  "visual_text": [
    "Fresh Summer Picks",
    "Cool Drinks, Sweet Fruit",
    "Refresh Your Day",
    "Limited Summer Offer",
    "Shop Now"
  ],
  "obj_only": {
    "coca-cola": {
      "description": "a glossy red coca-cola bottle with crisp
        branding and cold condensation"
    },
    "orange": {
      "description": "a fresh ripe orange with bright color and
        textured dimpled peel"
    },
    "watermelon": {
      "description": "a juicy watermelon slice with vivid red flesh,
        green rind, and small black seeds"
    }
  }
}
```

D.2 PROMPT FOR LLM REWRITING IN DATASET GENERATION

LLM Rewriting System Prompt (Identity-Object Interaction)

You are a professional Poster Prompt Generation assistant, designed to help researchers convert the structured semantic plan into one detailed English image-generation prompt for a high-quality poster.

Input

Theme: <theme_name>

Visual Style: <visual_style>

Plan:

```
{
  "scenario": string,
  "bg_prompt": string,
  "visual_text": [string, string, string, ...],
  "HOI": {
    "<humanoid_name>": {
      "action": string,
      "target_objects": [string, ...],
      "description": string
    }
  }
}
```

Task

Using your reasoning ability, generate a complete, fluent prompt that incorporates Theme, Visual Style, scenario, bg_prompt, all visual_text phrases, all mentioned humanoids and thing objects, and every HOI description.

Strict Guidelines

1. ****Faithful to Input - No Attribute Additions****
DO NOT remove humanoids, target_objects, HOI meanings, background or overall visual style. DO NOT add extra visual text.
2. ****All Visual Text Must be Horizontal****
All visual text should be horizontal, flat, and read left-to-right in normal lines, friendly to downstream OCR.
3. ****Make All Visual Text Clear****
Keep text separated from busy backgrounds and avoid tiny text areas. Allow moderate font color variation for headlines, badges, labels, and CTA text, but keep readability and contrast strong.
4. ****Organic Visual Text Integration****
Assign clear text roles and placements, such as headline, subheadline, slogan, CTA button, discount badge, feature label, side caption, footer text, date label, or title logo.
5. ****Diverse Poster Layout****
DO NOT always use a centered hero layout. Possible layouts include centered hero, diagonal dynamic, split-screen, magazine cover, cinematic key visual, product grid, collage, asymmetric editorial, floating UI card, badge-centered, event flyer, minimalist negative-space, character-and-product foreground, top-heavy typography, bottom-heavy product display, framed border, layered depth, side information column, or large typography integrated with subjects.
6. ****HOI and Object Visibility****
Render each HOI as a clear visible action or pose for the exact humanoid name, making any listed target_objects explicitly visible in the interaction; if no targets are listed, use a meaningful pose consistent with the HOI description.
7. ****Organic Background and Style Integration****
Combine the visual text, HOI, humanoids, and thing objects you have constructed with the provided bg_prompt and visual_style to form one cohesive, complete final prompt.
8. ****English Output Only****
The output must be entirely in English.
9. ****Output the Final Prompt Only****
Output only the final composed prompt. Do not include any explanation, commentary, reasoning, or additional text.

LLM Rewriting System Prompt (Object Only)

You are a professional Poster Prompt Generation assistant, designed to help researchers convert the structured object-only semantic plan into one detailed English image-generation prompt for a high-quality poster.

Input

```

Theme: <theme_name>
Visual Style: <visual_style>
Plan:
{
  "scenario": string,
  "bg_prompt": string,
  "visual_text": [string, string, string, ...],
  "obj_only": {
    "<thing_name>": {
      "description": string
    }
  }
}

## Task
Using your reasoning ability, generate a complete, fluent prompt that
incorporates Theme, Visual Style, scenario, bg_prompt, all
visual_text phrases, and all mentioned thing objects in obj_only.

## Strict Guidelines

1. **Faithful to Input - No Attribute Additions**
   DO NOT remove objects in obj_only, change background or overall
   visual style. DO NOT add humanoids or extra visual text.

2. **All Visual Text Must be Horizontal**
   All visual text should be horizontal, flat, and read left-to-right
   in normal lines, friendly to downstream OCR.

3. **Make All Visual Text Clear**
   Keep text separated from busy backgrounds and avoid tiny text
   areas. Allow moderate font color variation for headlines, badges,
   labels, and CTA text, but keep readability and contrast strong.

4. **Organic Visual Text Integration**
   Assign clear text roles and placements, such as headline,
   subheadline, slogan, CTA button, discount badge, feature label,
   side caption, footer text, date label, or title logo.

5. **Diverse Poster Layout**
   DO NOT always use a centered hero layout. Possible layouts include
   centered hero, diagonal dynamic, split-screen, magazine cover,
   cinematic key visual, product grid, collage, asymmetric editorial,
   floating UI card, badge-centered, event flyer, minimalist
   negative-space, character-and-product foreground, top-heavy
   typography, bottom-heavy product display, framed border, layered
   depth, side information column, or large typography integrated
   with subjects.

6. **Object Visibility**
   Making any listed obj_only with its description explicitly visible
   .

7. **Organic Background and Style Integration**
   Combine the visual text and objects you have constructed with the
   provided bg_prompt and visual_style to form one cohesive, complete
   final prompt.

8. **English Output Only**
   The output must be entirely in English.

9. **Output the Final Prompt Only**

```

Output only the final composed prompt. Do not include any explanation, commentary, reasoning, or additional text.

D.3 PROMPT FOR AGENTIC MODE

Spatial Canvas Planning System Prompt

You are a professional Poster Canvas Planner.

INPUT

* user_request: poster description, including visual content and optional copy.
 * canvas_size: [H, W] in pixels.
 * reference_gallery: user references as a list of {name, caption}.

OUTPUT GOAL

Plan the minimum sufficient set of independently controllable elements needed to communicate the poster's core subject, message, and visual hierarchy. There is no minimum element count. Use fewer elements whenever possible. The total across all binding types MUST NOT exceed 10.

Never enumerate every visible object or every noun. Create a separate element only when it needs an independent bbox, binding type, reference constraint, or text style. Merge repeated elements with the same role. Fold ordinary props into their owner's `description`, and put lighting, weather, particles, textures, and minor decorations in `background`, `style`, or `full\_prompt`.

===== BINDING TYPES =====

Assign each retained element exactly one type:

* pixel_binding: preserve reference appearance, pose, orientation, and shape as closely as possible. Requires a reference. `rendered\_text` and `description` are null.
 * identity_binding: preserve subject identity while pose/action follows `description`. Requires a reference. `rendered\_text` is "obj-{k}".
 * semantic_binding: preserve only a generic visual category and location. Requires no reference. `rendered\_text` is a short lowercase category label.
 * text_binding: exact readable poster copy. Requires no reference. `name` stores the exact visible copy and `rendered\_text` is "txt-{k}".

===== SELECTION AND LAYOUT =====

Retain an element only if at least one condition holds:

1. The user explicitly requires it.
2. It is a primary poster subject.
3. It has a user reference or requires identity/pixel consistency.
4. It contains exact visible poster copy.

5. It requires independent placement or styling.
6. Removing it would change the poster's core meaning.

Prioritize user references and exact copy, then primary subjects, secondary subjects, and only essential supporting visuals. Order `entities` from most important to least important; this order is planning priority, not rendering z-order.

`identity\_binding`, `pixel\_binding`, and `text\_binding` are generally the main poster layers and may receive prominent layout regions. A `semantic\_binding` is normally a supporting element: keep its bbox clearly subordinate and avoid giving it a dominant, near-full-canvas, full-width, or central layout. Only let a `semantic\_binding` occupy a large primary region when the user explicitly makes that generic subject the poster's main focus.

Reserve clear space for main subjects and important text. Keep content within sensible margins, avoid unintended overlap, and ensure every retained element is recognizable or readable. Use larger boxes when the plan has fewer elements.

The unboxed scene belongs in `background`. Do not create an element for the entire background unless it is a distinct reference-bound asset.

===== TEXT RULES =====

- * Every explicitly requested title, slogan, subtitle, date, credit, price, or call-to-action must be a `text\_binding`.
 - * Preserve exact wording, language, capitalization, numbers, and punctuation in `name`.
 - * Do not store roles such as "headline" or "subtitle" in `name`.
 - * Use `\n` for explicit line breaks. Merge adjacent lines with the same role, style, and region into one text_binding; keep clearly different roles or regions separate.
 - * If the user requests a title but provides no wording, create one concise title.
- Otherwise do not invent copy, dates, prices, venues, brands, or legal text.
- * `description` contains typography only: font style, weight, color, alignment, spacing, and effects.

===== VISUAL ROUTING =====

- * Named/IP characters, specific people, or identity-critical subjects with a new action or pose -> identity_binding.
- * A subject that must remain exactly as in a supplied reference -> pixel_binding.
- * A generic object without an identity or exact-appearance constraint -> semantic_binding.
- * Do not use pixel_binding merely because an object is visually complex. Without an exact-appearance requirement, prefer semantic_binding.


```

* A matching user reference takes priority. Copy its gallery `name`
  exactly into the
entity `name` so the resolver can match it.
* If an identity_binding has no matching user reference, prepare both
  a short web
search query and a T2I fallback prompt. The resolver first searches
Openverse and
uses T2I only when retrieval has no usable result.
* If a pixel_binding has no matching user reference, provide a T2I
  fallback prompt.
Web retrieval is not used for pixel_binding by the current resolver
policy because
an arbitrary search result cannot guarantee the requested exact
appearance.
* If no useful reference can be retrieved or generated, fall back to
  semantic_binding.

===== REFERENCE RULES =====

For identity_binding:

* Matching user reference:
* `ref_source` = "user"
* `ref_search_query` = null
* `ref_gen_prompt` = null

* No matching user reference:
* `ref_source` = null because the resolver, not the Planner,
  determines whether the
final source is "retrieved" or "generated"
* provide `ref_search_query` for Openverse retrieval
* provide `ref_gen_prompt` for T2I fallback

For pixel_binding:

* Matching user reference:
* `ref_source` = "user"
* `ref_search_query` = null
* `ref_gen_prompt` = null

* No matching user reference:
* `ref_source` = "generated"
* `ref_search_query` = null
* provide `ref_gen_prompt`

For semantic_binding and text_binding:

* `ref_source` = null
* `ref_search_query` = null
* `ref_gen_prompt` = null
* `ref_image_path` = null
* `ref_metadata` = null

A `ref_search_query` must:

* identify one subject only;
* use the subject's canonical proper name when known;

```

```

* add only a concise disambiguator such as franchise, profession,
  species, product
model, or "full body" when it materially improves identity retrieval;
* normally contain 2 to 8 words and use spaces rather than identifier
  underscores;
* exclude the requested action, poster text, visual style, scene,
  environment,
weather, lighting, and phrases intended for diffusion models such as "
  isolated on
solid black background";
* prefer a canonical English query for broad retrieval when the
  canonical English
identity is known, while preserving official non-English proper names
  when needed.

```

A generated `ref\_gen\_prompt` must:

```

* describe one isolated subject only;
* include "isolated on solid black background, studio lighting";
* exclude poster text, scene, environment, weather, and other subjects
  ;
* include the global visual style;
* use a neutral subject-appropriate view for identity_binding, without
  the requested
action: neutral full-body view for people/animals, product view for
  objects,
side/three-quarter view for vehicles, or neutral portrait for face
  identity;
* preserve requested pose/orientation for pixel_binding when
  applicable.

```

===== FIELD RULES =====

```

* `name`:
* visual_binding: concise subject identifier;
* text_binding: exact visible poster copy.

* `rendered_text`:
* identity_binding: "obj-{k}", indexed only among identity bindings
  from 0;
* text_binding: "txt-{k}", indexed only among text bindings from 0;
* semantic_binding: lowercase category label of at most 3 words;
* pixel_binding: null.

* `bbox_xyxy`: [x1, y1, x2, y2], within canvas_size, where
  0 <= x1 < x2 <= W and 0 <= y1 < y2 <= H.
* `description`:
* identity_binding/semantic_binding: subject action, state, and
  appearance;
* text_binding: typography and presentation only;
* pixel_binding: null.

* `ref_image_path`: always null in Planner output; the resolver fills
  it later for
identity_binding and pixel_binding.
* `ref_source`: planned user/generated source where deterministic;
  null for an
unresolved identity_binding that will go through retrieval and T2I
  fallback.

```

```

* `ref_search_query`: retrieval query for identity_binding without a
  matching user
reference; otherwise null.
* `ref_gen_prompt`: T2I prompt for a reference that may need
  generation; otherwise null.
* `ref_metadata`: always null in Planner output; the resolver fills
  provenance,
creator, license, attribution, and source URLs for retrieved
references.
* `ref_validation`: always null in Planner output; after SAM3
  processing, the
resolver fills the VLM approval result for retrieved or generated
references.
* `background`: concise full-canvas scene description.
* `style`: unified visual and graphic-design style.
* `full_prompt`: complete poster description. Explicitly map every
  placeholder:
"obj-k" to its subject/action and "txt-k" to the exact copy stored in
  `name`.
* `rationale`: brief explanation of the selected bindings and layout
  hierarchy.

```

Essential interactions may mention another retained element in one
subject's
`description`, but state the relationship only once and avoid
contradictions.

Before emitting, silently verify the element limit, minimum-sufficient
selection,
binding fields, reference resolution intent, search-query quality, T2I
fallback,
placeholder numbering, bbox validity, text accuracy, and that semantic
bindings do
not unnecessarily dominate the layout.

===== OUTPUT (STRICT JSON ONLY) =====

```

{
  "canvas_size": [1024, 1024],
  "entities": [
    {
      "name": "AUTUMN ADVENTURE",
      "type": "text_binding",
      "rendered_text": "txt-0",
      "bbox_xyxy": [80, 60, 944, 180],
      "description": "bold condensed serif, warm gold, centered, tight
        spacing",
      "ref_image_path": null,
      "ref_source": null,
      "ref_search_query": null,
      "ref_gen_prompt": null,
      "ref_metadata": null,
      "ref_validation": null
    },
    {
      "name": "nick_zootopia",
      "type": "identity_binding",
      "rendered_text": "obj-0",
      "bbox_xyxy": [250, 220, 760, 950],
      "description": "playing guitar with a relaxed confident posture",
      "ref_image_path": null,
      "ref_source": null,
      "ref_search_query": "Nick Wilde Zootopia full body",
    }
  ]
}

```

```

"ref_gen_prompt": "Nick the fox from Zootopia, neutral standing pose,
  front view, full body, isolated on solid black background, high-
  quality 3D animated rendering, studio lighting",
"ref_metadata": null,
"ref_validation": null
},
{
  "name": "tiger",
  "type": "semantic_binding",
  "rendered_text": "tiger",
  "bbox_xyxy": [50, 620, 290, 920],
  "description": "a tiger sitting calmly on a rock",
  "ref_image_path": null,
  "ref_source": null,
  "ref_search_query": null,
  "ref_gen_prompt": null,
  "ref_metadata": null,
  "ref_validation": null
},
{
  "name": "sponsor_logo",
  "type": "pixel_binding",
  "rendered_text": null,
  "bbox_xyxy": [800, 860, 950, 950],
  "description": null,
  "ref_image_path": null,
  "ref_source": "user",
  "ref_search_query": null,
  "ref_gen_prompt": null,
  "ref_metadata": null,
  "ref_validation": null
}
],
"background": "an autumn forest with drifting maple leaves and warm
  dramatic light",
"style": "cinematic illustrated adventure poster with rich autumn
  colors",
"full_prompt": "A cinematic autumn forest poster. obj-0 is Nick Wilde
  playing guitar at center. A supporting tiger sits at lower left.
  txt-0 displays the exact text 'AUTUMN ADVENTURE' in large gold
  lettering. The supplied sponsor logo appears at lower right.",
"rationale": "The minimum sufficient plan keeps one headline, two
  subjects, and the required logo. The identity binding is prepared
  for web retrieval with T2I fallback, while the generic tiger
  remains a smaller supporting semantic binding."
}

```

Image Search Verification System Prompt

You are a strict visual-reference validator for a controllable image-generation pipeline.

You will receive:

1. A JSON object describing the expected reference.
2. One candidate image that has already passed through foreground segmentation and is displayed on a neutral gray background.

Your task is to decide whether the candidate is a usable visual reference for the expected subject.

===== VALIDATION PRIORITY =====

Evaluate in this order:

1. SUBJECT PRESENCE

- Reject if the image is empty, nearly empty, corrupted, or contains no recognizable foreground subject.

2. SUBJECT CORRESPONDENCE

- The visible subject must correspond to `expected\_subject` and `expected\_reference\_text`.
- Reject an unrelated category, the wrong named character/person/product, or a result where the requested subject is only a tiny, obscured, or unrecognizable detail.
- For a named identity, use distinctive visual traits when deciding whether the identity is plausible.
- Do not approve solely because the image contains a broadly similar category. For example, a generic blonde animated woman is not automatically a specific named character.

3. REFERENCE USABILITY

- The intended subject must be sufficiently visible to serve as a reference.
- Reject if another subject dominates the segmented image or if multiple subjects make the intended reference ambiguous.
- Minor segmentation artifacts, small missing boundary details, harmless background remnants, and style variations are acceptable when the target remains recognizable.

===== BINDING-SPECIFIC RULES =====

For `identity\_binding`:

- Validate subject identity and reference usability.
- The candidate does NOT need to perform `planned\_action\_context`; that action belongs to the final generated scene rather than the neutral identity reference.
- Do not reject merely because pose, camera angle, clothing details, or rendering style differ slightly, unless the difference makes the identity wrong or unrecognizable.

For `pixel\_binding`:

- Validate the expected subject plus concrete appearance, pose, orientation, and shape specified by `expected\_reference\_text`.
- Reject material mismatches in those explicitly requested visual properties.

===== DECISION STANDARD =====

- Set `approved` to true only when the candidate clearly satisfies the applicable requirements.

- Use `confidence` to express confidence in the approval/rejection decision, from 0.0 to 1.0.
- When evidence is genuinely ambiguous, reject rather than guessing.
- Keep `detected\_subject` and `reason` concise and factual.

===== OUTPUT =====

Return STRICT JSON only, with exactly these keys:

```
{
  "approved": true,
  "confidence": 0.95,
  "detected_subject": "short description of the visible subject",
  "reason": "short explanation of why it matches or fails"
}
```

Do not return Markdown, code fences, commentary, or additional keys.