

Reasoning for Social Audio-Visual Question Answering: Where Do We Stand?

Koen P. de Vries^{1,2}, Xavier Alameda-Pineda¹, Estefanía Talavera², and Stéphane Lathuilière¹

¹ Inria at Univ. Grenoble Alpes, CNRS, LJK, France

² University of Twente, The Netherlands

Abstract. Training Multimodal Large Language Models for audio-visual social understanding is a crucial step toward embodied social intelligence. Chain-of-thought (CoT) reasoning has become the dominant approach, with HumanOmniV2 and its IntentBench benchmark as a prominent reference point. In this context, we report three findings. First, IntentBench is highly noisy: $\sim 7\%$ of questions are broken and $\sim 23\%$ are trivially answerable without the video input. We remove the affected questions and release INTENTBENCH-PRIME. Second, current reasoning approaches are expensive and surprisingly ineffective. A simple *Vanilla SFT* baseline matches or outperforms existing reasoning methods across three benchmarks at a fraction of the cost, establishing it as an essential baseline for evaluating novel fine-tuning techniques. Third, our analysis reveals that substantial priors can be learned solely from the text modality and that using a textual caption instead of the video yields performance on par with Vanilla SFT. These surprising findings reveal the limitations of current MLLMs when it comes to social understanding. IntentBench-Prime, *Vanilla SFT* model, and code are publicly available.

Keywords: Social Understanding · CoT Reasoning · Benchmark




Fig. 1: Social Audio-Visual Question Answering (AV-QA): Our three key findings.

1 Introduction

Understanding human intentions, emotions, and complex social scenarios is a crucial step toward embodied social intelligence. Multimodal Large Language Models (MLLMs), or Omni-models, have emerged as highly effective tools for this objective. They can natively process video, audio, and textual inputs to generate text or even audio, as demonstrated by the Qwen-omni series [29].

In this context, several works focus specifically on multimodal social understanding [9, 10, 25, 30] to improve how MLLMs respond to human-centric queries. Notably, HumanOmniV2 [30] has significantly impacted this field [8, 17, 23, 25] due to its strong performance and the introduction of INTENTBENCH, a benchmark specifically aimed at evaluating multimodal social understanding capabilities. However, our in-depth analysis of this benchmark reveals a critical limitation, leading to our first key finding (Fig. 1): **FINDING 1 INTENTBENCH evaluation is highly noisy.** We identify several issues within INTENTBENCH, specifically broken or poorly formulated questions ($\sim 7\%$) originating both from the Social-IQ 2.0 source data and the curation process. Furthermore, we show that for a substantial portion of the benchmark ($\sim 23\%$), pretrained LLMs unanimously agree on the correct answer without any video or audio inputs, relying entirely on language priors. Motivated by these observations, we introduce a rigorously curated version of this dataset, denoted as INTENTBENCH-PRIME.

Methodologically, recent approaches [9, 16, 21, 25, 30] have integrated reasoning techniques into MLLMs to enhance social Audio-Visual Question Answering (AV-QA). These models are typically trained to perform reasoning via a Chain-of-Thought [26] (CoT) strategy optimized with GRPO [4, 24]. In the case of HumanOmniV2 [30], the model is tasked to first summarize relevant context before performing reasoning. While intended to mitigate insufficient context comprehension and shortcut reasoning, CoT introduces substantial overhead. In this work, we explore an alternative direction: improving social AV-QA without the computational burden of CoT. Our experiments yield a second key finding: **FINDING 2 Current CoT-based reasoning for social understanding is expensive and ineffective.** To demonstrate this, we introduce a frustratingly straightforward yet successful baseline, termed *Vanilla SFT*. This baseline is trained using standard supervised fine-tuning (SFT) for direct AV-QA, leveraging the exact same AV-QA data as HumanOmniV2 but without reasoning traces. Through rigorous evaluation across three benchmarks, INTENTBENCH-PRIME, WORLDSENSE [6], and DAILY-OMNI [37], we show that *Vanilla SFT* matches or outperforms existing reasoning approaches. Crucially, it does so while being vastly more efficient. It circumvents the need to distill reasoning traces, accelerates training time, and dramatically reduces inference latency by bypassing the auto-regressive generation of lengthy rationales. Based on these results, we strongly advocate for the establishment of *Vanilla SFT* as an essential baseline when evaluating novel fine-tuning methods. Despite its simplicity, such grounding is key for measuring methodological progress in this domain.

Finally, motivated by Finding 2 and aiming to understand more thoroughly to what extent MLLMs are able to leverage the video for precise question answering, we compare our *Vanilla SFT* model with two finetuned reference points in the social domain using INTENTBENCH-PRIME. *Question SFT* is trained to answer questions based solely on the question and answer text while *Caption SFT* is its caption-based counterpart, which only has access to a question-independent, textual caption of the original video (generated by ASID-Captioner [12]) to answer corresponding questions. The results of *Question SFT* show that despite the curation of INTENTBENCH-PRIME, substantial learnable priors remain. Results using *Caption SFT* lead to our third finding: **FINDING 3 A generic textual caption yields QA performance on par with processing the full multimodal data.** Although the experiment is limited to the social domain, the comparable performance in both settings illustrates the need for further research in understanding the ability of MLLMs to extract question-specific information from the audio and video stream. Finally, we discuss a practical application of our findings: since captions can be pre-computed independently of the questions, a two-stage approach utilizing captions for question answering enables very low latency at query time and multiple questions to be answered based on a single textual trace.

2 Related Work

Multi-modal Large Language Models After the rise of Large Language Models (LLMs) following the release of ChatGPT [20] in 2022, researchers were quick to enable LLMs to process other modalities than text, starting with images. In [14] images are encoded and subsequently projected to the LLM token space, enabling strong LLM backbones to process images. This concept was quickly extended to the remaining modalities of audio and video [33], at which point models able to process video, audio and text started to be called omni-models. Qwen2.5-Omni [29] is an open-source omni-model that can output audio in addition to text. It is a common starting point for training specialized omni-models for various applications requiring access to all modalities [12, 16, 30].

Reasoning models At the start of 2025, DeepSeek-R1 [4] was released, demonstrating that the reasoning abilities of LLMs can be enhanced via a data-efficient reinforcement learning (RL) approach, making use of Group Relative Policy Optimization (GRPO) [24]. Previously, injecting LLMs with reasoning abilities was done via expensive supervised learning on human-produced examples. This new method caused an increase in the attention to reasoning and was quickly adapted to the MLLM domain [36] by, among others, [2, 28, 32]. The motivation for incorporating explicit thinking into these models is both explainability and to enhance downstream question-answering performance [26]. However, explicit reasoning requires multiple forward passes through the network to generate additional reasoning tokens, resulting in a significant computational overhead. There are works claiming that the long reasoning chains that these thinking

models produce are unnecessarily long, whereas better and quicker results can be obtained with shorter reasoning chains [5, 35]. AVATAR [8] addresses other limitations by incorporating an off-policy training architecture, improving sample efficiency, and a credit assignment strategy that emphasizes reasoning phases corresponding to planning and final answer synthesis.

Reasoning for social interaction understanding The concept of explicit thinking or reasoning has also been extended to the social domain [9, 16, 21, 25, 28, 30, 34]. A deep dive on reasoning in social settings is presented by the authors of [18], providing a benchmark to evaluate the reasoning capabilities of MLLMs or omni-models. To the best knowledge of the authors, R1-Omni [34] is the first application of RL to an Omni-model for emotion recognition and the first application of RL to such models for reasoning in the social setting in general. More recently, [16] introduced HitEmotion, a framework for emotion understanding based on Theory of Mind (ToM) modeling.

HumanOmniV2 [30] focuses on the broader social setting and takes reasoning a step further. The authors identify two main issues, namely insufficient context understanding and shortcut reasoning. To address these issues, they enforce a sequential reasoning process in which the model first summarizes the relevant video context, then performs explicit reasoning based on that context, and finally generates its answer. They finetune Qwen2.5-Omni [29] via a SFT training stage and implement two followup GRPO training phases. The resulting omni-model is able to answer questions about videos depicting social interaction but still generalizes to other settings. AffectOmni [25] extends the HumanOmniV2 framework with *People Focus* and *Temporal Order* rewards, boosting performance on emotion recognition and temporally sensitive tasks.

3 INTENTBENCH-PRIME

3.1 INTENTBENCH Diagnosis

Introduced by [30], this benchmark evaluates the ability of omni-models to understand complex human social interactions from both video and audio. It consists of three categories derived from existing audio-visual datasets: intention and social intelligence (Social-IQ 2.0 [27, 31]), emotion recognition (EMER [13]), and deception detection (MDPE [1]). Examples are shown in Fig. 3. For the Social-IQ 2.0 subset, 300 videos with 2,356 manually verified multimodal questions are selected. GPT-4o with access to only the text modality is used to identify challenging questions and replace easy distractor answer options. From EMER, 133 videos are converted into six-option multiple-choice emotion recognition tasks, potentially with multiple correct answers, and evaluated using the F1-score. From MDPE, 200 videos containing truthful responses and varying levels of deception are selected, with the task requiring models to determine whether the speaker is lying. We identify three types of issues with the Social-IQ 2.0 (S-IQ) part of the benchmark, which, as displayed in Fig. 2, represents




Fig. 2: Curation process of INTENTBENCH-PRIME and benchmark statistics. The two very small categories ‘when’ (14) and ‘who/which’ (25) are merged into ‘other’ in both IntentBench-Prime variants. 616 questions are flagged as answerable from text alone; 18 of them were already removed as broken.

87% of the questions. Examples of issues are displayed in Fig. 4 with more in the supplementary material, Appendix A. Below we provide details on each issue.

Issue 1: Text-only answerable questions We observe that a significant portion of questions can be answered with access to only the text modality (questions and answers), which means that they can be answered without the use of video and audio. To quantify this observation, we run four small-sized LLMs (Gemma-2-9B-Instruct [3], Llama-3.1-8B-Instruct [15], Mistral-7B-Instruct-v0.3 [19], and Qwen3.5-9B [22]) on only the S-IQ questions and answers of the benchmark. We propose to evaluate the text-answerability of the benchmark as the percentage of questions where all four LLMs agree on the correct answer, based on just the question and answers. This is a strict criterion, only capturing questions that we are sure are trivial. In practice, for a single model, text-only accuracy is higher as discussed in Section 3.2. We run our analysis for INTENTBENCH S-IQ questions, INTENTBENCH S-IQ questions with original answer options (recall easy options are replaced for additional difficulty), and a set of S-IQ questions randomly selected from the original dataset, not in INTENTBENCH, but the same size. We find that:

1. INTENTBENCH Social-IQ 2.0 questions and INTENTBENCH S-IQ questions with original answer options have similar text-answerability (26.1% vs 24.4%). This means that the replacement of distractor options to make questions harder in INTENTBENCH was unsuccessful. We investigate this further and find that the replacement of easy options in INTENTBENCH is not done by creating new options, but by replacing distractor options with ground-truth answers from other questions corresponding to the same video. At least one distractor is swapped in 54% of INTENTBENCH Social-IQ 2.0 questions. The answer options from other questions can be semantically inconsistent with




Fig. 3: Examples from Social-IQ 2.0, EMER and MDPE as they are adapted in INTENTBENCH. Images partly sourced from [30].

the question, seemingly making it easier for LLMs to identify them as not being the ground-truth answer.

2. INTENTBENCH Social-IQ 2.0 questions with original answer options and a random set of S-IQ questions have similar text-answerability (24.4% vs 24.2%). This indicates that the curation process did not successfully select a harder subset of questions. After investigation of the question sets and corresponding videos, we find this to stem from a granularity mismatch in the selection process: filtering was done on the video level rather than on individual questions.

Additionally, in HumanOmniV2, GPT-4o with only text modality is used to identify difficult questions and presumably also to replace easy options. To measure the increase in difficulty due to the modifications, HumanOmniV2 also uses GPT-4o. Using the same model for both of these tasks likely gave an inflated measure of increased difficulty.

Issue 2: Broken questions. We further investigate the swapping of distractor options with ground-truth answers from other questions. In addition to the fact that, contrary to the intentions of the constructors, the benchmark becomes slightly easier for LLMs, we find that the option-swapping can also break questions. For example, Fig. 4 shows an example of a question where the swapped-in option is equal to the ground-truth of the original question. Another relatively common problem is that the ground-truth can be a sub- or super-string of a distractor option, in the form of e.g. *A. Yes* and *B. Yes, [reason / rephrasing of question]*, which also makes the correct ground-truth ambiguous.




Fig. 4: Examples of issues in INTENTBENCH. More examples across all types of issues are provided in the supplementary material, Appendix A.

Table 1: Average accuracy on all IB Social-IQ questions, all IB Social-IQ questions where an option is swapped, and the same questions but with the swapping undone.

Benchmark subset → Number of samples →		IB S-IQ full 2,356	IB S-IQ swapped 1,264	IB S-IQ unswapped 1,264
Method ↓	Input ↓			
Qwen2.5-Omni-7B [29]	A+V+T	64.5	74.8	84.7
HumanOmniV2 [30]	A+V+T	68.9	75.9	88.1
LLMs agree on GT	T	26.1	42.4	39.2

An important note is that, for omni-models, the Social-IQ questions with swapped options are harder. This is shown in Tab. 1 where the 1,264 questions for which options were swapped are isolated in the two right-most columns. It is clear that despite the change having little effect for the LLMs w.r.t. overall difficulty, there is an effect for Qwen2.5-Omni and HumanOmniV2 models. The reason for this is likely that the swapped-in options are GT answers to another question, meaning they are factually grounded in the video and audio.

Issue 3: Original dataset issues. We also discover other issues in INTENTBENCH, that after investigation are determined to stem from the original dataset, such as a ground truth that makes no sense ("this is a test", "I do not speak Spanish", "N/A (Wrong video clip)"), questions or ground-truth answers with a major typo, and questions with two (almost) identical answer options of which one is GT. These broken questions amount to almost 6% of Social-IQ questions. Although not investigated in more detail in this paper, this number is a proxy for the amount of broken questions in the Social-IQ 2.0 dataset in general.

3.2 INTENTBENCH-PRIME

Motivated by the discovery of these issues, we propose a curated version of INTENTBENCH that we name INTENTBENCH-PRIME. It is curated using the following steps:

1. **Removing broken questions from the benchmark**, meaning questions with any of the breaking problems that were discussed prior. This is done by making a ranking of the questions, placing questions with highest suspicion of being broken at the top. The ranking consists of three elements, for which more details can be found in the supplementary material, Appendix B. We manually go through all Social-IQ 2.0 QA pairs in the benchmark in order of the ranking. We only inspect the video when we highly suspect a question is broken but cannot conclusively determine it from the QA pair alone. When we do not identify a broken question for 300 questions in a row, we stop the cleaning procedure. At this point, more than half of the S-IQ questions have been manually verified. With our pipeline, 192 out of 2,356 S-IQ questions in INTENTBENCH are removed. Of these 192, 57 (30%) were questions with swapped distractor options, the rest being issues with the original dataset.
2. **Removing questions that are answerable without looking at the video / audio**. Here, we drop the questions that are identified by the ensemble of 4 LLMs in Section 3.1 to be text-answerable. That means, when all 4 LLMs are able to identify the correct answer to a question based on just the questions and answers, we remove this question from the benchmark. We utilize this strict criterion because we aim to be conservative and retain non-trivial questions. Using this method, we are able to exclude 616 trivial questions from the benchmark. Out of these 616, 536 (87%) were questions with swapped distractor options. There is an overlap of 18 questions between the broken and text-answerable sets.

We do not undo the swapping of distractor options entirely despite it being an unusual and as shown, sometimes breaking, change. The reason for this is twofold: first of all, the omni-models seemingly struggling with this change makes it an interesting property of the benchmark. Secondly, many of the questions with options swapped are present in the two sets of removed questions listed above, meaning the questions that remain should be fair questions that are a challenge for omni-models, which is obviously a desired property for this benchmark. Note that we do not identify problems with the emotion and deception categories of the benchmark and leave those intact. Finally, two very small Social-IQ 2.0 sub-categories in the original INTENTBENCH, ‘when’ (14 samples) and ‘who/which’ (25 samples) are merged into the ‘other’ sub-category.

Since INTENTBENCH-PRIME is constructed strictly by removal of questions as opposed to modification or addition of questions, its release consists of an exclusion list. Any existing method with per-question results on INTENTBENCH can obtain INTENTBENCH-PRIME scores by simply filtering its existing results, meaning no re-evaluation runs are required, a highly practical property.

Table 2: Performance on the different versions of INTENTBENCH-PRIME. Detailed performance across categories can be found in the supplementary material, Appendix C. Granite-4.1-8B is an LLM answering the questions based on just the QA pairs.

Statistics ↓	Benchmark →	INTENTBENCH	INTENTBENCH-PRIME	
			Clean	Hard
# questions		2,689	2,497	1,899
# videos		633	633	633
Method ↓	Input			
Qwen2.5-Omni-7B [29]	A+V+T	64.6 (64.2*)	67.8	63.2
HumanOmniV2 [30]	A+V+T	68.9 (69.3*)	71.8	66.9
Qwen2.5-Omni-7B	T (QA only)	55.1	57.9	46.9
Granite-4.1-8B [7]	T (QA only)	52.1	53.7	41.5

* reported from [30]. Other numbers are computed using our pipeline.

Quantitative analysis of INTENTBENCH-PRIME. Question count, video count, and performance of Qwen2.5-Omni and HumanOmniV2 for three versions of INTENTBENCH are shown in Tab. 2: the original, INTENTBENCH with broken questions removed (INTENTBENCH-PRIME (Clean)), and finally INTENTBENCH with broken and trivial questions removed (INTENTBENCH-PRIME (hard)). Note that the emotion category is scored with F1-score, and that all categories are micro-averaged to obtain the overall accuracy. We also report the performance of Qwen2.5-Omni with only text as input to quantify the drop in text-answerability. Its accuracy of 46.9% on the hard split remains above the random-chance level ($\sim 28\%$), indicating that text-answerability is not fully eliminated. To complete the analysis, we include a text-only LLM (Granite-4.1-8B [7]) to assess if a more recent and text-specialized model could improve performance. We surprisingly observe the opposite trend with Granite underperforming Qwen2.5-Omni text-only baseline by 5.4% on the INTENTBENCH-PRIME (Hard) set. We hypothesize this result might be explained by either the benefit of multimodal training or simply differences in training dataset distribution. Nevertheless, we retain our strict removal criterion (unanimous agreement of all four LLMs), as loosening it, *e.g.* to a 3-out-of-4 majority, would also discard questions that remain challenging for omni-models and would further shrink the benchmark. Additional statistics for all three benchmark versions are displayed in Fig. 2.

4 Ineffectiveness of Reasoning for Social AV-QA

4.1 Experiment setup

The goal is to identify whether training a model to generate a reasoning trace improves performance on audio-visual question answering compared to training a model to directly answer the questions, with no intermediate steps. To isolate this result, we finetune the same base model (Qwen2.5-Omni) and train on the exact same original audio-video / image QA data used in HumanOmniV2. The model is trained to directly answer questions based on the audio and video with no intermediate steps, outputting only the letter(s) corresponding to the perceived correct answer(s).

For sufficient benchmark diversity, we evaluate on **WORLDSENSE** [6], **DAILY-OMNI** [37], **INTENTBENCH**, and **INTENTBENCH-PRIME**. The latter two are considered in-domain whereas **WORLDSENSE** and **DAILY-OMNI** are out-of-domain with respect to the training data. **WORLDSENSE** [6] is a benchmark with 3,172 questions corresponding to a diverse collection of 1,662 videos which include audio. The benchmark is designed to demand a strong coupling between video and audio, requiring strong cross-modal alignment to perform well. **DAILY-OMNI** [37] is a similar benchmark, also focusing on both video and audio and the corresponding cross-modal connections. It has 684 real-world videos with 1,197 corresponding questions. There are six categories of which two are particularly interesting in the context of this paper: context understanding and reasoning. Additionally, there are 30 and 60-second duration based subsets.

To validate our evaluation pipeline is working as intended we first reproduce the benchmarks’ Qwen2.5-Omni baseline numbers and the numbers from the HumanOmniV2 paper. Differences in our reproduction numbers are small, and are suspected to stem from slight prompting differences and FPS and maximum allowed frames settings.

Vanilla SFT training setup. For the training data, we aim to mirror the exact training data used in HumanOmniV2 [30] for a fair comparison. This includes data from OmniInstruct [11], Video-R1 [2], Social-IQ 2.0 training data, and the 200 entries from EMER not present in **INTENTBENCH**. We follow the HumanOmniV2 code-base to match the training data, which results in 20K videos and 10K images and their corresponding multiple-choice questions and answers being used. We finetune the thinker part of Qwen2.5-Omni-7B [29], freezing the video & audio encoders and aligner layers. We train LoRA with learning rate $1e^{-4}$ for 1 epoch. LoRA rank is 16 and the video settings are 2 FPS with 32 maximum frames, evenly spreading when the video is longer than 16 seconds. This mirrors the setup of evaluation in HumanOmniV2. Training takes less than 4.5 hours on 4× H100 80 GB. We also train a model using full parameter finetuning, which takes 2 epochs to reach similar or slightly worse performance than LoRA on the benchmarks.

4.2 Results and Discussions

Results for **INTENTBENCH**, **INTENTBENCH-PRIME**, **WORLDSENSE**, and **DAILY-OMNI** are shown in Tab. 3. For HumanOmniV2 [30] on **INTENTBENCH**, **WORLDSENSE**, and **DAILY-OMNI**, we report not our reproduction numbers but the original paper numbers, as the latter were generally marginally higher. This way, our comparison is conservative with respect to our claims. We include results on **INTENTBENCH** despite its known limitations, as it enables comparison with methods whose results we could not reproduce. In the deception category, 4 out of 200 videos led to a loading error, hence those are excluded from the evaluation.

Table 3: Performance comparison on all evaluated benchmarks.

(a) INTENTBENCH and INTENTBENCH-PRIME. The ‘Intent’ category corresponds to all Social-IQ 2.0 questions. Emotion and Deception are unchanged across variants (no such questions are removed) and are therefore reported only once, under INTENTBENCH. Detailed results can be found in the supplementary material, Appendix C.

Benchmark →		INTENTBENCH-PRIME							
		INTENTBENCH				Clean		Hard	
Method	CoT	Intent	Emo.*	Dec.**	Avg.	Intent	Avg.	Intent	Avg.
Qwen2.5-Omni-7B [29]	×	64.5	71.4	61.2	64.6	68.2	67.8	62.8	63.2
AVATAR (CVPR 2026) [8]	✓	-	-	-	63.9	-	-	-	-
AffectOmni (IEEE TAC 2026) [25]	✓	69.7	85.4	62.5	69.9	-	-	-	-
HumanOmniV2 [30]	✓	69.1	82.4	64.0	69.3	72.2	71.8	66.5	66.9
Vanilla SFT (Full FT)	×	70.8	82.6	58.2	70.5	74.4	73.6	69.2	69.0
Vanilla SFT (LoRA)	×	70.9	83.2	58.2	70.6	74.6	73.8	70.9	70.4

*Emo. = Emotion **Dec. = Deception

(b) WORLDSENSE and DAILY-OMNI. We include some of the interesting subcategories of DAILY-OMNI.

Benchmark →		WORLDSENSE		DAILY-OMNI				
Method	CoT			CU*	Reasoning	30s	60s	Avg.
Qwen2.5-Omni-7B [29]	×	45.4	58.6	73.1	64.6	59.1	62.1	
AVATAR (CVPR 2026) [8]	✓	46.0	-	-	-	-	55.7	
AffectOmni (IEEE TAC 2026) [25]	✓	48.8	56.0	78.2	-	58.6	61.9	
HumanOmniV2 [30]	✓	47.1	51.8	74.3	63.1	53.1	58.5	
Vanilla SFT (Full FT)	×	46.7	57.0	76.0	65.2	58.4	62.1	
Vanilla SFT (LoRA)	×	48.8	60.1	76.6	68.3	61.4	65.2	

*CU = Context Understanding

As can be seen in Tab. 3 (a) and (b), *Vanilla SFT*, despite its simple training setup, consistently outperforms both the baseline and HumanOmniV2 numbers. The one exception is the deception category, where HumanOmniV2 reports 64.0%. However, our reproduction of HumanOmniV2 numbers reaches only 60.2% on this category. We note all methods obtain close to chance on this small binary subset. The most striking result is on DAILY-OMNI, where HumanOmniV2 performance degrades compared to the baseline. Interestingly enough, our baseline also outperforms on the Context Understanding and Reasoning categories of DAILY-OMNI, despite these categories seemingly being particularly well-suited to the HumanOmniV2 model. Additional models leveraging reasoning, AVATAR [8] and AffectOmni³ [25], are not able to outperform our simple baseline, trained with HumanOmniV2 data, on any of the benchmarks. AffectOmni, which is trained with the same HumanOmniV2 data, does take the top spot in some of the sub-categories but remains worse on average. To our knowledge, there is no reasoning method with a comparable base-model and size that outperforms our *Vanilla SFT* baseline on the discussed benchmarks.

³ AffectOmni reports a macro-average over all categories of INTENTBENCH, which leads to a different number. Due to the imbalance between categories and to remain consistent with other methods, we deem micro-average the most suitable metric.

Table 4: Inference efficiency on the full INTENTBENCH-PRIME-Hard split. Same hardware (1×H100), where necessary, native protocol for the models is used, other than that the setup is identical. The latency gap is fully attributed to the decode stage, i.e. the auto-regressive generation of the output trace.

Method	Cost		Latency/question (s)			Accuracy (%)
	Train (GPU h)	Output (tok.)	Prefill	Decode	Total	
Direct answering (Vanilla SFT)	18	2	1.22	0.02	1.23	70.4
Reasoning (HumanOmniV2 [30])	~200	527	1.19	7.12	8.31	66.9
Reasoning <i>vs.</i> direct answering	~11×	263×	1.0×	356×	6.7×	−3.5

The impressive performance of *Vanilla SFT* suggests that, whenever possible, this simple baseline should be included as standard procedure in future papers on audio-visual (social) question answering. This way, benchmark gains stemming from fine-tuning on the task using training data can be properly disentangled from gains originating from a superior method. To our knowledge, direct supervised finetuning with LoRA as in our *Vanilla SFT* baseline is the simplest and cheapest way one can finetune a model, and hence obtain such a baseline.

Computational cost and latency analysis. In addition to its accuracy, *Vanilla SFT* benefits from several practical advantages in compute cost and inference latency compared to reasoning models. We now provide a quantitative analysis of these gains. To estimate the training cost of HumanOmniV2 training, we use training time and trace statistics measured from internal training runs with SFT and GRPO on long traces, making a conservative estimate of the total time. Results are reported in Tab. 4. Overall, it clearly demonstrates the superiority of the reasoning-free approach in terms of compute cost both at training and test time. The gains are especially clear in terms of decoding latency (356× factor gain) as direct answering avoids the auto-regressive cost of CoT.

5 Limited Gap Between Video and Caption-Based Answering

Motivated by the results of Section 4, we aim to understand more deeply to what extent MLLMs are able to leverage the video modality to provide accurate answers. To investigate this, we introduce two reference points. First, we introduce *Question SFT*, fine-tuning Qwen2.5-Omni to answer the questions exclusively from the QA text, without any context. This serves as a context-free reference, depicting the performance a finetuned MLLM can achieve by learning question-answer structure and other dataset priors. Secondly, we introduce *Caption SFT*, fine-tuning Qwen2.5-Omni to answer questions using only a textual caption of the corresponding video. Captions are generated using the recent ASID-Captioner model [12]. The captions are generated independently of the questions and are therefore not conditioned on the information required to an-

Table 5: Comparison of Qwen2.5-Omni-7B (top) in various modality settings to models finetuned (bottom) in those settings on INTENTBENCH-PRIME (Hard). The three settings are: answering questions based on 1. Audio and video (*Vanilla SFT*), 2. A fine-grained but question-independent caption generated by ASID-Captioner [12] (*Caption SFT*), 3. Only the question and answer pair (*Question SFT*).

Method ↓		Benchmark: INTENTBENCH-PRIME (hard)						
Model	Modalities	Why	How	What	Other	Emo.*	Dec.**	Avg.
Qwen2.5-Omni-7B	T (Q+A only)	44.1	43.3	43.5	55.3	37.7	60.0	46.9
Qwen2.5-Omni-7B	T (ASID caption [12])	62.6	56.9	61.6	65.2	70.0	63.5	62.1
Qwen2.5-Omni-7B	A+V+T	61.7	60.3	65.8	64.6	71.4	61.2	63.2
Question SFT	T (Q+A only)	61.9	58.2	57.1	68.0	75.8	60.0	62.0
Caption SFT	T (ASID caption [12])	68.2	64.1	68.5	74.2	84.5	60.5	68.6
Vanilla SFT	A+V+T	68.6	67.0	67.6	74.5	86.8	60.7	69.5

*Emo. = Emotion **Dec. = Deception

swer them. These baselines are compared with the *Vanilla SFT* method from Section 4. We limit the training data to Social-IQ 2.0 and EMER to reduce the cost of the experiment. Apart from the modality setup, training is identical between the three variants. Evaluation is done using INTENTBENCH-PRIME (Hard) in the same modality setting as training, for each model respectively.

Results in Tab. 5 show Qwen2.5-Omni baseline results for the three settings (top) and their finetuned counterparts (bottom). Results show that the finetuned *Question SFT* model achieves performance on the benchmark 15.1% higher than its Qwen2.5-Omni baseline. Part of this gain is to be expected, as training on same-source QA data increases format alignment and task knowledge, even without context. However, the magnitude of the gain is more than twice that of the context-based variants. Furthermore, the resulting model comes within 7.5% of *Vanilla SFT* and 6.6% of *Caption SFT*, indicating that there is substantial structure being learned in Social-IQ 2.0 and EMER questions. We note that this prior learning cannot explain the out-of-domain gains of *Vanilla SFT* on WorldSense and Daily-Omni reported in Section 4.

Turning to the contribution of context, in both the un-finetuned (top in Tab. 5) and finetuned setting (bottom), caption-based answering performance is on par with video-based answering, the difference being close to a single percentage point in both settings. This finding implies that the video-based *Vanilla SFT* model, despite its state-of-the-art performance, is unable to extract substantially more information from the video than its caption-based counterpart from a textual caption. Although the ASID-Captioner model [12], which shares Qwen2.5-Omni as base model, has been trained to generate a fine-grained textual caption based on the video and audio, it is a general-purpose caption model not geared towards the social domain. Importantly, the captions are generated unconditioned on the question. These results motivate further research to be done into the ability of MLLMs to extract question-relevant information from videos.

Potential applications of textual traces. The remarkably high performance of the introduced caption-only baseline motivates the usage of textual captions as a replacement for the corresponding video. A potential setting where the latter can be useful is a two-stage approach where an MLLM is first used to generate a dense caption of the video, independent of possible following questions, and then answering based on the generated textual trace. Although the generation of the caption is a computational burden, this enables the video to be ‘pre-processed’, decoupling the heavy video token processing from question answering. This drastically reduces inference time from the moment the query arrives. Additionally, as the caption is question-independent, it can be used to answer multiple questions.

6 Conclusion

In this paper, we present three key findings regarding the social understanding capabilities of Multimodal Large Language Models (MLLMs). First, we identify several issues within INTENTBENCH and address them through a combination of automated and manual filtering. This pipeline yields INTENTBENCH-PRIME, an improved benchmark for analyzing the social understanding of omni-models. Second, we investigate the effectiveness of reasoning for (social) audio-visual QA. By applying standard supervised fine-tuning, we introduce a baseline model, *Vanilla SFT*, that directly answers questions. Despite its simplicity, it achieves state-of-the-art performance among comparable models, outperforming or matching complex CoT reasoning methods. Consequently, we advocate for establishing standard SFT as a mandatory baseline to accurately measure methodological progress in the field. Finally, we examine the extent to which *Vanilla SFT* actually relies on audio-visual input. Our analysis reveals that models can learn substantial priors solely from the text modality in the training datasets. Additionally, a fine-grained but question-independent textual caption yields performance on par with *Vanilla SFT*. Together, these findings underscore the need for further research into how effectively MLLMs extract question-specific information directly from video modalities.

Limitations. For practical reasons, our curation of INTENTBENCH-PRIME from INTENTBENCH is limited to the removal of questions as opposed to addition or modification of questions. This reduces the amount of samples in the benchmark and only lightly balances the category distribution of the benchmark. Furthermore, while INTENTBENCH-PRIME (Hard) excludes a significant chunk of questions answerable by pretrained LLMs, our *Question SFT* reference shows that a model finetuned on data from the same source as the benchmark can still exploit considerable priors. Additionally, across all experiments, our results are limited to a single base model, Qwen2.5-Omni. Finally, the comparison of video-, caption- and question-based answering remains limited to the social domain and further investigation can be done to fully disentangle these results into format alignment, source-specific priors, or potential other sources. We deem the result an interesting starting point for multiple avenues of future research.

Acknowledgements

This work was granted access to the HPC resources of IDRIS under the allocation 2026-AD011017620 made by GENCI.

E. Talavera Martinez was supported by the NWO Talent Programme – VENI (project Understanding Social Interactions in First-Person Videos with Multi-modal Learning, file number 244507) which is financed by the Dutch Research Council (NWO).

References

1. Cai, C., Liang, S., Liu, X., Zhu, K., Wen, Z., Tao, J., Xie, H., Cui, J., Ma, Y., Cheng, Z., et al.: Mdpe: A multimodal deception dataset with personality and emotional characteristics. In: Proceedings of the 33rd ACM International Conference on Multimedia. pp. 12957–12964 (2025)
2. Feng, K., Gong, K., Li, B., Guo, Z., Wang, Y., Peng, T., Wu, J., Zhang, X., Wang, B., Yue, X.: Video-r1: Reinforcing video reasoning in mllms. In: Belgrave, D., Zhang, C., Lin, H., Pascanu, R., Koniusz, P., Ghassemi, M., Chen, N. (eds.) Advances in Neural Information Processing Systems. vol. 38, pp. 99114–99137. Curran Associates, Inc. (2025), https://proceedings.neurips.cc/paper_files/paper/2025/file/8eb3976840e08b80dda9667562574246-Paper-Conference.pdf
3. Gemma Team, Riviere, M., Pathak, S., Andreev, A., et al.: Gemma 2: Improving open language models at a practical size. arXiv preprint arXiv:2408.00118 (2024)
4. Guo, D., Yang, D., Zhang, H., Song, J., Wang, P., Zhu, Q., Xu, R., Zhang, R., Ma, S., Bi, X., Zhang, X., Yu, X., Wu, Y., Wu, Z.F., Gou, Z., et al.: Deepseek-r1 incentivizes reasoning in llms through reinforcement learning. Nature **645**(8081), 633–638 (2025). <https://doi.org/10.1038/s41586-025-09422-z>, <http://dx.doi.org/10.1038/s41586-025-09422-z>
5. Hassid, M., Synnaeve, G., Adi, Y., Schwartz, R.: Don’t overthink it. preferring shorter thinking chains for improved llm reasoning. arXiv preprint arXiv:2505.17813 (2025)
6. Hong, J., Yan, S., Cai, J., Jiang, X., Hu, Y., Xie, W.: Worldsense: Evaluating real-world omnimodal understanding for multimodal LLMs. In: The Fourteenth International Conference on Learning Representations (2026), <https://openreview.net/forum?id=YxsfxAvJv4>
7. IBM Research: Granite 4.1 language models. <https://www.ibm.com/granite/docs/models/granite4-1> (2026)
8. Kulkarni, Y., Fazli, P.: Avatar: Reinforcement learning to see, hear, and reason over video. In: IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) (2026)
9. Li, H., Fei, H., Hu, Z., Yang, Z., Wang, Z.: Vegas: Towards visually explainable and grounded artificial social intelligence. In: Proceedings of the AAAI Conference on Artificial Intelligence. vol. 39, pp. 4707–4715 (2025)
10. Li, X., Deng, S., Lai, B., Pian, W., Rehg, J.M., Tian, Y.: Towards online multi-modal social interaction understanding. Transactions on Machine Learning Research (TMLR) (2026)

11. LI, Y., Ma, Y., Zhang, G., Yuan, R., Zhu, K., Guo, H., Liang, Y., Liu, J., Wang, Z.M., Yang, J., Wu, S., Qu, X., Shi, J., Zhang, X., Yang, Z., WEN, Y., Wang, Y., Li, S., Zhang, Z., Liu, R., Benetos, E., Huang, W., Lin, C.: Omnibench: Towards the future of universal omni-language models. In: The Thirty-ninth Annual Conference on Neural Information Processing Systems Datasets and Benchmarks Track (2026), <https://openreview.net/forum?id=SSF4qgsNYE>
12. Li, Y., Zhang, H., Guo, M.H., Gao, W., Jia, S., Jiao, S., Hou, Q., Cheng, M.M.: Towards universal video mllms with attribute-structured and quality-verified instructions (2026), <https://arxiv.org/abs/2602.13013>
13. Lian, Z., Sun, H., Sun, L., Gu, H., Wen, Z., Zhang, S., Chen, S., Xu, M., Xu, K., Chen, K., et al.: Explainable multimodal emotion recognition. arXiv preprint arXiv:2306.15401 (2023)
14. Liu, H., Li, C., Wu, Q., Lee, Y.J.: Visual instruction tuning. *Advances in Neural Information Processing Systems* **36**, 34892–34916 (2023)
15. Llama Team, Meta: The llama 3 herd of models. arXiv preprint arXiv:2407.21783 (2024), <https://ai.meta.com/blog/meta-llama-3-1/>
16. Luo, M., Li, B., Xu, S., Zhang, S., Chen, Q., Han, M., Chen, W., Huang, Y., Fei, H., Lee, M.L., et al.: Unveiling the cognitive compass: Theory-of-mind-guided multimodal emotion reasoning. *International Conference on Learning Representations (ICLR)* (2026)
17. Ma, S., Dang, J., Zhang, W., Zhang, Y., Wang, B., Peng, H., Hu, B., Tian, Q., Chua, T.S.: Modf-sir: A multi-agent omni-modal distilled framework for social intelligence reasoning. arXiv preprint arXiv:2606.12018 (2026)
18. Mathur, L., Qian, M., Liang, P.P., Morency, L.P.: Social genome: Grounded social reasoning abilities of multimodal models. In: *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*. pp. 24879–24902 (2025)
19. Mistral AI Team: Mistral-7b-instruct-v0.3 open-weight model. <https://huggingface.co/mistralai/Mistral-7B-Instruct-v0.3> (2024), official Model Repository and Specification
20. OpenAI: Introducing ChatGPT. <https://openai.com/blog/chatgpt> (2022)
21. Qin, Z., Zheng, R., Wang, Y., Li, T., Yuan, Y., Chen, J., Wang, L.: Humansense: From multimodal perception to empathetic context-aware responses through reasoning mllms. In: *Proceedings of the AAAI Conference on Artificial Intelligence*. vol. 40, pp. 24973–24981 (2026)
22. Qwen Team: Qwen3.5 technical report: Towards native multimodal agents. arXiv preprint arXiv:2604.15804 (2026)
23. Rha, H., Yeo, J.H., Kim, Y., Ro, Y.M.: Emotion-coherent reasoning for multimodal llms via emotional rationale verifier. *Proceedings of the AAAI Conference on Artificial Intelligence* **40**(3), 2029–2037 (Mar 2026). <https://doi.org/10.1609/aaai.v40i3.37184>, <https://ojs.aaai.org/index.php/AAAI/article/view/37184>
24. Shao, Z., Wang, P., Zhu, Q., Xu, R., Song, J., Bi, X., Zhang, H., Zhang, M., Li, Y.K., Wu, Y., Guo, D.: Deepseekmath: Pushing the limits of mathematical reasoning in open language models (2024), <https://arxiv.org/abs/2402.03300>
25. Wang, Y., Yang, R., Dang, J., Wang, B., Wu, Y., Cao, P., Zhang, W., Peng, H., Hu, B., Chua, T.S.: Affectomni: RL-verifiable people-centric grounded affective reasoning for social and art-related scenes. *IEEE Transactions on Affective Computing* pp. 1–12 (01 2026). <https://doi.org/10.1109/TAFFC.2026.3707634>
26. Wei, J., Wang, X., Schuurmans, D., Bosma, M., Ichter, B., Xia, F., Chi, E.H., Le, Q.V., Zhou, D.: Chain-of-thought prompting elicits reasoning in large language models. In: *Proceedings of the 36th International Conference on Neural Information Processing Systems*. NIPS ’22, Curran Associates Inc., Red Hook, NY, USA (2022)

27. Wilf, A., Mathur, L., Mathew, S., Ko, C., Kebe, Y., Liang, P.P., Morency, L.P.: Social-iq 2.0 challenge: Benchmarking multimodal social understanding. <https://github.com/abwilf/Social-IQ-2.0-Challenge> (2023)
28. Xiao, T., Xu, X., Huang, Z., Gao, H., Liu, Q., Liu, Q., Chen, E.: Perception-rl: Advancing multimodal reasoning capabilities of MLLMs via visual perception reward. In: The Fourteenth International Conference on Learning Representations (2026), <https://openreview.net/forum?id=KttCXdj4w>
29. Xu, J., Guo, Z., He, J., Hu, H., He, T., Bai, S., Chen, K., Wang, J., Fan, Y., Dang, K., Zhang, B., Wang, X., Chu, Y., Lin, J.: Qwen2.5-omni technical report (2025), <https://arxiv.org/abs/2503.20215>
30. Yang, Q., Yao, S., Chen, W., Fu, S., Bai, D., Zhao, J., Sun, B., Yin, B., Wei, X., Zhou, J.: Humanomniv2: From understanding to omni-modal reasoning with context. arXiv preprint arXiv:2506.21277 (2025)
31. Zadeh, A., Chan, M., Liang, P.P., Tong, E., Morency, L.P.: Social-iq: A question answering benchmark for artificial social intelligence. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. pp. 8807–8817 (2019)
32. Zhang, C., Wang, Z., Ma, Y., Peng, J., Wang, Y., Zhou, Q., Song, J., Zheng, B.: Rewatch-rl: Boosting complex video reasoning in large vision-language models through agentic data synthesis. In: The Fourteenth International Conference on Learning Representations (2026), <https://openreview.net/forum?id=xindJJLSr1>
33. Zhang, H., Li, X., Bing, L.: Video-llama: An instruction-tuned audio-visual language model for video understanding. In: Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing: System Demonstrations. pp. 543–553 (2023)
34. Zhao, J., Wei, X., Bo, L.: R1-omni: Explainable omni-multimodal emotion recognition with reinforcement learning. arXiv preprint arXiv:2503.05379 (2025)
35. Zhong, Y., Hu, Z.Y., Li, Y., Wang, L.: Rethinking chain-of-thought reasoning for videos. arXiv preprint arXiv:2512.09616 (2025)
36. Zhou, G., Qiu, P., Chen, C., Wang, J., Yang, Z., Xu, J., Qiu, M.: Reinforced mllm: A survey on rl-based reasoning in multimodal large language models. arXiv preprint arXiv:2504.21277 (2025)
37. Zhou, Z., Wang, R., Wu, Z., Jiang, Y.G.: Daily-omni: Towards audio-visual reasoning with temporal alignment across modalities. arXiv preprint arXiv:2505.17862 (2025)

Reasoning for Social Audio-Visual Question Answering: Where Do We Stand?

Supplementary Material

A Additional examples of problematic questions

ORIGINALLY BROKEN 7 examples

■ ground truth
 ■ swapped-in option; *original option* it replaced

2uVTtK2UKJc_q2_3

Why does the man laugh a little when he mentions Mike Dubb?

- A He laughs because he remembers a funny moment.
- B No, he reacts with a smile when Mike Dubb is mentioned.
- C The man laughs because he made a joke.
- D This is a bad question.**

Vwn_QS9vB1g_q11_0

Does the woman seem open-minded in meeting and working with new people?

- A** He respects their opinion.
replaced: The woman is wearing a red dress.
- B Yes
- C** He does them to better emphasize the points he is conveying.
replaced: The woman in red is dominant and does not want to share the spotlight with anyone else.
- D Yes**

08iOYngEUBU_q4_3

Why does the man in the sweater move his hands forward and back?

- A He wants to karate chop the other man.
- B The man in the sweater is trying to emphasize his point.
- C The man in the sweater is trying to keep warm.
- D He waves to accentuate his point.**

FWBCTZiiJEM_q10_6

Why does the man seem frustrated?

- A No.**
- B The man is excited to show off his skills.
- C Sorry, I cannot fulfill this request. As an AI language model, I do not have the capability to determine the correct answer or context of the questions given, nor can I rewrite incorrect answers in a way that guarantees they remain incorrect. I suggest reaching out to a human tutor or educator for assistance with your dataset.
- D The man is annoyed with himself.

mr88Ud5V9uE_q10_10

Does the older woman seem to believe in the project?

- A Yes.**
- B Yes, she seems like she believes in the project.
- C The woman is discussing a new makeup line with the man.
- D The woman is skeptical about the app's usefulness.

Vwn_QS9vB1g_q24_0

Were the two people successful in explaining what they are looking for in an applicant?

- A Yes**
- B Yes
- C** Because that is the angle that is required to capture their heads and shoulders.
replaced: Are the two people successful in explaining what they are looking for in an applicant?
- D** They want to help YouTubers gain more sponsorships and use their service.
replaced: The man and woman start dancing in the middle of the interview.

FositxHjuUK_q1_1

Why does the man in the black think he knows the name of the food?

- A The man in black thinks he knows the name of the food because he is a food expert.
- B He thinks he knows the name of the food because he has had it before.
- C I do not speak spanish**
- D The man in black thinks he knows the name of the food because he has a good sense of smell.

Fig. 5: Additional examples of Social-IQ 2.0 questions used in INTENTBENCH that are ambiguous or otherwise broken. It is also clear that sometimes distractor options have issues, but this is never grounds for removal of the question.

BROKEN BY SWAPPING 7 examples

■ ground truth
 ■ swapped-in option; *original option it replaced*

ooUw7Hq8YLq_q4_0

Does the man in black remember his childhood fondly?

A Because he wants to share his past with the other man
replaced: The man in the blue shirt is a famous actor.

B Yes
replaced: The man is excited about the upcoming baseball game.

C No, he liked his childhood.

D Yes, he liked his childhood.

cQREa5Y-jqk_q7_11

How does the woman feel about the fact that the man does not drink coffee?

A Surprise and maybe some respect that he does not rely on caffeine like other journalists do.
replaced: She is happy.

B She does not expect it.

C They seem like they are building a personal connection with each other, being friendly
replaced: The woman feels sorry for the man's bad experience with coffee.

D The woman was surprised and impressed.
replaced: The woman thinks the man is lying about not drinking coffee.

7GRTyx4uMU_q4_3

Does the woman seem good at introducing things?

A The woman does seem good at introducing things.

B The woman's manner of speech makes her seem open-minded.
replaced: The woman is a terrible dancer.

C Yes
replaced: Does the woman seem good at introducing things that are not good?

D She is reaching for something
replaced: The man in the suit is a professional dancer.

OT3MVRv0TT4_q13_0

Why is the woman laughing while wearing the mask?

A She enjoys being complemented by and joking around with the man.
replaced: Candace is laughing because she is trying to scare her children with the mask.

B She is laughing at herself in the mask.
replaced: Candace is laughing because she is nervous about driving with the mask on.

C She finds the activity she is doing funny.

D Yes, she finds the mask funny.
replaced: She thinks people expect her to laugh.

ocg0MbBfCS0_q5_0

Does the woman agree with the man in black?

A Yes, she agrees with him.

B He is in a good mood.
replaced: The woman thinks the man in black is wrong.

C Yes
replaced: No, she disagrees with him.

D The woman raises her eyebrows to indicate that she thinks the man in black might be wrong.

U_JraRlieNQ_q2_9

Why is the topic so important to the woman?

A She wants people to recognize and fix the issue.

B She and people in her generation have been deeply affected by the issue.
replaced: The woman is discussing the topic because she wants to sell her book.

C She wants to appear serious.
replaced: The woman is only talking about this topic because she wants attention.

D She thinks the US is unfair.
replaced: She was paid to discuss the issue.

TA3Xy53hMqY_q5_6

How does the man standing behind the podium feel?

A He does not like that the man isn't answering his question.
replaced: He is satisfied with the answers he is getting.

B He wants his question to be answered.

C He is worried about his hair.

D He believes that he has made a strong argument.

Fig. 6: Additional examples of Social-IQ 2.0 questions used in INTENTBENCH where the swapping of options made the correct answer ambiguous. Note that, at first sight, some of these questions might not seem broken, but the fact that the swapped-in options are GT answers to other questions and hence factually grounded in the video causes their justified removal.

TOO EASY 7 examples

■ ground truth
 ■ swapped-in option; original option it replaced

~99aZZhUgRk_q3_0

Does the man face hardship well?

A The two people are respectful to each other because they are acquaintances, not enemies or good friends.
replaced: He struggles to face challenges.

B **Yes, he endures hardships well.**

C The man cares for his parents, as he dropped out of school to prevent straining the family finances.
replaced: The woman is impressed with the man's story.

D No, he is able to face hardship.

~sp3Q524oO4_q3_0

What is the woman feeling?

A **The woman is curious and amazed.**

B The woman is frustrated and bored.

C The woman feels interested in history.

D The woman is skeptical and uninterested.

0a21v4Iw2FY_q5_6

Why is no one feeling sad for the person trapped?

A The sitting woman seems boring, while the standing woman seems more fun
replaced: They cannot help him so they are focusing on other things.

B **Because they are watching him suffer in the context of a funny video, so it is harder to feel sympathy for him**

C The standing woman finds it entertaining
replaced: They are too busy enjoying the activities to notice the trapped person.

D Someone else wants to help him out of the trap.

~QQ0Lv4_--4_q17_6

The man's nods and vocal expression suggests that he

A It is a little awkward because of the different responses but largely they are still accepting
replaced: He is analyzing her.

B Yes, he doesn't get angry when she says she wouldn't date him.
replaced: He is trying to remember something.

C **is understanding her.**

D She seems flattered
replaced: The man's nods and vocal expression suggests that he is deeply interested in what

jBHRKeVa135M_q2_4

Why did the audience laugh during parts of the video?

A She was passionate about her position regarding alcohol prohibition in India.
replaced: Yes, because the audience laughed at the man's argument, which was well-received.

B Yes, given how many people kept on interrupting each other.
replaced: Laughing because there is a comedian on the stage telling jokes to the audience.

C **They're laughing because of the host's reaction to the people**

D Yes they're yelling amongst each other
replaced: Yes, because they laughed at the man's argument, which they agreed with.

2XFVnzr4Vho_q3_5

Why does the woman in the middle move her hands around like she is holding a ball?

A She is trying to keep her balance.

B She wants to seem more credible by moving her hands.

C **She is trying to articulate her words.**

D She is using hand signals to emphasize her humor.

k-ky&v_kKGU_q5_8

What is the overall mood of the video?

A The overall mood of the video is light and light.

B The video is about a cooking show.

C **Intriguing**

D The conversation is boring and uneventful.

Fig. 7: Additional examples of Social-IQ 2.0 questions used in INTENTBENCH. Sometimes due to the swapping of distractor options, the ground truth answer in these questions is easily identifiable from text alone.

B Details on broken question removal

To streamline the removal of broken questions from INTENTBENCH, all Social-IQ 2.0 questions are ranked, with questions with highest suspicion of being broken at the top. The ranking is based on, in descending order of weight:

- Programmatic checks such as a plain ‘yes’ or ‘no’ as answer, two identical answers of which one is the GT, the GT being a sub- or super-string of another answer option, and the appearance of GT answer options such as ‘This is a bad question’, ‘N/A (Wrong video clip)’. These programmatic checks were implemented based on initial manual inspection of the benchmark.
- An audit of Claude Haiku 4.5 for more fine-grained analysis. It is tasked to do a general audit and flag questions which are seemingly problematic. More specifically it flags: very similar answer options of which one is GT, GT answers which are a reformulation of another option, junk / artifact options, mismatch between question and GT answer, spelling or grammatical errors, and other, freely identified, quality issues.
- Various internally finetuned social reasoning models in various settings: answering based on video, answering based on a caption of the video, and answering based on a caption with an oracle hint included. An oracle hint is a reformulation of the question and ground-truth answer, which is appended to the caption. The proportion of correct answers across the various models is deemed as an indicator that a question might not make sense.

With the ranking in place, we manually go through all the Social-IQ 2.0 QA pairs in the benchmark in order of the ranking. We only inspect the video when we highly suspect a question is broken but cannot conclusively determine it from the QA pair alone. For example, this can occur in the case where a distractor option is a slightly more specific version of the GT. In case this slight specification is grounded in the video, the answer to the question is ambiguous and the question is removed. When we do not identify a broken question for 300 questions in a row, we stop the cleaning procedure. At this point, more than half of the questions have been manually verified. With our pipeline, 192 out of 2,356 Social-IQ 2.0 questions in INTENTBENCH are removed. We deem the fact that we eventually get 300 correct questions in a row a validation that our ranking effectively filtered broken questions.

C Detailed performance on INTENTBENCH-PRIME

Table 6: Detailed results on INTENTBENCH-PRIME (Clean).

Method ↓			Benchmark: INTENTBENCH-PRIME (Clean)						
Model	Categories → Modalities ↓ N →	Why 654	How 585	What 442	Other 483	Emo.* 133	Dec.** 196	Avg. 2,493	
Qwen2.5-Omni-7B [29]	A+V+T	66.4	65.6	69.7	72.5	71.4	61.2	67.8	
HumanOmniV2 [30]	A+V+T	69.0	70.8	71.7	78.7	81.9	60.2	71.8	
Vanilla SFT (Full FT)	A+V+T	71.1	72.3	74.7	81.2	82.6	58.2	73.6	
Vanilla SFT (LoRA)	A+V+T	72.0	72.5	75.3	79.9	83.2	58.2	73.8	

*Emo. = Emotion **Dec. = Deception

Table 7: Detailed results on INTENTBENCH-PRIME (Hard).

Method ↓		Benchmark: INTENTBENCH-PRIME (Hard)						
Model	Categories → Modalities ↓ N →	Why 465	How 443	What 336	Other 322	Emo.* 133	Dec.** 196	Avg. 1,895
Qwen2.5-Omni-7B [29]	A+V+T	61.7	60.3	65.8	64.6	71.4	61.2	63.2
HumanOmniV2 [30]	A+V+T	63.2	65.2	67.6	71.7	81.9	60.2	66.9
Vanilla SFT (Full FT)	A+V+T	66.5	66.4	70.8	75.5	82.6	58.2	69.0
Vanilla SFT (LoRA)	A+V+T	68.8	68.2	72.6	75.8	83.2	58.2	70.4

*Emo. = Emotion **Dec. = Deception