

# Reliability analysis for BraTS-GoAT segmentation: a controlled robustness study of deep-ensemble uncertainty

Riya Deepak Shet<sup>1</sup>  and Le Zhang<sup>2</sup> 

<sup>1</sup> Department of Cancer and Genomic Sciences, School of Medical Sciences, College of Medicine and Health, University of Birmingham, Birmingham, United Kingdom  
`rxs1355@student.bham.ac.uk`

<sup>2</sup> Department of Electronic, Electrical and Systems Engineering, School of Engineering, College of Engineering and Physical Sciences, University of Birmingham, Birmingham, United Kingdom  
`l.zhang.16@bham.ac.uk`

**Abstract.** Deep networks segment brain tumours accurately in-distribution, but can fail silently when the input differs from their training data. That risk is central to clinical deployment and is the premise of the BraTS-GoAT generalizability task. We ask not only how well a model segments, but whether its uncertainty knows when it is wrong. On BraTS-GoAT (Task 3) we train a 5-fold cross-validated nnU-Net baseline (one held-out prediction per case) and a 3-seed deep ensemble. Both are evaluated for calibration and error detection on a per-region relevant mask, aggregated per case. In-distribution the 3-seed ensemble improves modestly over the already strong single model on the same held-out split, with the clearest gain in calibration. The separation appears under shift. In a controlled robustness study using graded synthetic corruptions as a proxy for acquisition shift, the single model’s confidence stays flat while its accuracy and calibration degrade. Inter-member disagreement instead rises steeply, about a quarter to a third above the clean condition, several times the single model’s response. On the official validation leaderboard the 5-fold ensemble of those folds attains whole-tumour Dice 0.87. The generalization gap is concentrated on the harder regions, with a characteristic failure of missing small, satellite lesions on unseen cohorts. In the synthetic study, disagreement among the 3-seed members is a more sensitive case-level indicator of acquisition shift than single-model confidence. Its per-voxel error localisation weakens as severity grows. The contribution is a rigorous, honest reliability comparison rather than a claim that any one uncertainty method dominates.

**Keywords:** Brain tumour segmentation · Uncertainty quantification · Deep ensembles · Calibration · Robustness · nnU-Net.

## 1 Introduction

Automated segmentation of gliomas from multiparametric MRI underpins tumour measurement, treatment planning and response assessment. Modern convolutional pipelines, above all nnU-Net [7], reach expert-level overlap on the data distributions they are trained on. The obstacle to clinical use is not average accuracy but reliability under change. A model deployed on an unfamiliar scanner, protocol or patient population can degrade while remaining confident. Such a failure is silent, and dangerous precisely because nothing flags it. The BraTS-GoAT challenge [3,14,1] makes this concrete by evaluating generalization of tumour sub-region segmentation across heterogeneous tumour types.

We therefore treat the problem as one of *reliability*. Beyond the Dice score we ask whether a model’s own uncertainty lands on its mistakes, and whether it responds when acquisition conditions change. Two uncertainty signals are available from standard models: the maximum-softmax *confidence* of a single network, and the *disagreement* between ensemble members. A single nnU-Net trained with Dice and cross-entropy is known to be overconfident. The question is whether an ensemble’s disagreement is a more trustworthy signal, particularly as acquisition conditions depart from those seen in training.

We make four contributions. The first is a strong nnU-Net baseline for BraTS-GoAT, trained solely on the challenge data. The second is a paired, per-case comparison of single-model confidence and deep-ensemble disagreement on calibration and error-detection metrics. The third is a controlled robustness study under graded synthetic acquisition shift, isolating whether each signal rises as input quality drops. The fourth is external evaluation on the official leaderboard.<sup>3</sup> Prior work finds that no single uncertainty method dominates [13]. We therefore report an honest comparison, including where the 3-seed ensemble helps little and where it regresses.

### 1.1 Related work

**nnU-Net as the standing baseline.** Architectural novelty has repeatedly underperformed careful configuration in brain tumour segmentation. nnU-Net [7] automates that configuration, deriving patch size, spacing, normalization and augmentation from a dataset fingerprint. It has become the standard reference pipeline against which new methods are measured, with strong subsequent entries refining it rather than departing from it [8,11]. That maturity makes it a useful fixed substrate. We therefore treat it as a competitive baseline rather than an axis of contribution, and spend the budget on reliability.

**Uncertainty benchmarking and its inconclusive verdict.** Uncertainty quantification divides into epistemic uncertainty, what the model does not know and could learn from more data, and aleatoric uncertainty, noise inherent in the image. The QU-BraTS benchmark [13] evaluated a field of methods on brain

<sup>3</sup> Code and evaluation harness: <https://github.com/riyashet-hds/brats-goat-reliability>

tumour segmentation. It rewarded uncertainty that suppresses confident errors, and concluded that no single method dominated. Alongside it, modern networks are known to be systematically overconfident [6], and rankings measured in-distribution do not survive the shift that matters [15]. Those findings set our design: we compare few signals carefully, on paired cases, and report regressions as well as gains.

**Deep ensembles against the cheaper approximations.** Independently trained deep ensembles [10] are widely reported as among the strongest uncertainty estimators, and a common reference point for later methods [15]. Their cost is  $K$  full training runs. Two cheaper approximations are standard. Monte-Carlo dropout (MC-dropout) samples predictions with dropout left active at inference [4]. Test-time augmentation (TTA) treats the spread over acquisition-model transformations as uncertainty [17]. Both obtain a distribution from a single trained network, so both are weaker proxies for genuine model diversity. We therefore scope the study to the strongest estimator and the baseline it must beat, naming MC-dropout and TTA as the next comparators.

## 2 Materials and Methods

### 2.1 Data and task

We use BraTS-GoAT Task 3, the generalizability track. It comprises 1351 labelled training cases, each with four co-registered MRI sequences (native and contrast-enhanced T1, T2-weighted, T2-FLAIR) at  $240 \times 240 \times 155$  and  $1 \text{ mm}^3$  resolution [3,2,16]. The challenge data and its evaluation are distributed through the MedPerf federated benchmarking platform [9]. Evaluation uses the three nested BraTS regions: whole tumour (WT), tumour core (TC) and enhancing tumour (ET). About 2.4% of cases (33) contain no enhancing tumour, where over-segmentation is penalised heavily and which are salient for error detection. Per the GoAT rules, the model is trained only on the provided data, from scratch, with no external data or pretrained weights.

### 2.2 Segmentation baseline

The baseline is nnU-Net in its ResEnc-L 3d\_fullres configuration [7], trained from scratch under 5-fold cross-validation. Pooling the five held-out folds yields one prediction per case from a model that did not train on it. That gives the cross-validated single model over all 1351 cases. The same five networks are also used a second way: for the challenge submission all five are averaged at inference, giving the 5-fold ensemble. The two configurations are not interchangeable.

We use nnU-Net v2.8.0 with the stock trainer and residual-encoder-L plans. The network is a six-stage residual-encoder U-Net, 32 to 320 features, patch  $160 \times 192 \times 160$ , batch 3, trained 1000 epochs per fold (about 29 h on an A100 of our BlueBEAR cluster). Every other setting is the library default: stochastic gradient descent with Nesterov momentum 0.99, polynomial decay from  $10^{-2}$ ,

and a Dice and cross-entropy loss with deep supervision. Preprocessing is z-score normalisation inside the brain mask at the native 1 mm spacing, so no resampling occurs. Training uses the four tissue labels, with nested regions derived at evaluation. No post-processing is applied, so all numbers are raw. One inference setting differs between runs. nnU-Net’s end-of-training validation enables test-time mirroring by default, so the internal cross-validated numbers include it. Both the leaderboard predictions and the submitted container run with it disabled.

### 2.3 Deep ensemble

The uncertainty method is a 3-seed deep ensemble: three nnU-Nets trained on a single fixed split with different random seeds [10]. The seeds are nnU-Net’s default and two explicit alternatives. Because the members share one training split, their held-out cases are unseen by every member, so their disagreement is a clean, label-referenced uncertainty. The 5-fold ensemble lacks this property, since its members’ training sets overlap. The paired baseline is the fold-0 network of Section 2.2 on that split’s 271 held-out cases, the split-0 single model. We report two signals: maximum-softmax confidence (available to both) and inter-member disagreement (ensemble only). We use three members due to compute reasons: at about 29 h per training run, a  $K$ -member ensemble costs  $K$  full runs.

Three model configurations arise from two training regimes. The cross-validated single model of Section 2.2 provides the internal baseline: each case is predicted by the fold that held it out. The 5-fold challenge ensemble averages those same fold models at inference, is packaged in the container, and produces the leaderboard results of Section 3.5 only. Its members’ training sets overlap, so it is not used for label-referenced uncertainty. The 3-seed deep ensemble, paired with a single model on the same held-out split, carries the reliability and robustness comparisons. The leaderboard therefore anchors external segmentation performance, not the uncertainty analysis.

**Uncertainty signals.** Reliability quantities use a binary per-region probability from the four-class softmax:  $P(\text{WT}) = 1 - P(\text{bg})$ ,  $P(\text{TC}) = P(\text{NCR}) + P(\text{ET})$ , and  $P(\text{ET})$  directly. At a voxel  $v$ , *confidence* is that of the decided class,  $c(v) = \max(P(v), 1 - P(v))$ , with uncertainty  $1 - c(v)$ . *Disagreement* is the variance  $D(v) = \frac{1}{K} \sum_m (P_m(v) - \bar{P}(v))^2$  of the  $K = 3$  members about their mean  $\bar{P}(v) = \frac{1}{K} \sum_m P_m(v)$ , which is also the 3-seed ensemble’s predictive probability. Both are evaluated only on the relevant mask defined below. Being a variance of a probability,  $D$  is inherently small, so it is reported as a relative change.

### 2.4 Reliability metrics

Segmentation quality uses Dice, the 95th-percentile Hausdorff distance (HD95, mm) and normalized surface Dice (NSD) [12]. Calibration uses the expected calibration error (ECE) [6]. Error detection uses the AUROC of uncertainty against per-voxel error and the area under the risk-coverage curve (AURC) [5]. Following QU-BraTS [13], calibration and error-detection metrics are computed on the

per-region relevant mask (the union of predicted and reference region, lightly dilated) and aggregated per case then averaged. The relevant mask removes the class-imbalance dilution that makes all-brain ECE uninformative. Per-case aggregation avoids a Simpson’s-paradox inversion of AUROC across cases.

Concretely, the relevant mask dilates the union of the reference region and the thresholded prediction  $P(r) \geq 0.5$  by two iterations of a six-connected element. ECE uses 15 equal-width bins. At most 20 000 mask voxels per case and region are sampled, and AUROC is dropped for cases with no errors or only errors. Tables report per-case ECE, whereas Fig. 2 and the values quoted from it are pooled, so the two differ slightly by construction.

## 2.5 Controlled robustness study

GoAT anonymises the per-case cohort, so we cannot partition the labelled data by tumour type. We instead run a controlled robustness study. The validation images are degraded by four MRI-realistic corruptions (Gaussian noise, bias field, blur, gamma) at graded severity, with the reference segmentation held fixed, and inference is re-run. Because the corruption and its strength are controlled exactly, this isolates whether the model and its uncertainty respond as input quality drops. It is a controlled proxy for acquisition shift, not a substitute for validation on genuinely unseen cohorts, and we treat it as such.

Additive Gaussian noise uses  $\sigma$  of 0.05, 0.10 and 0.20 of each channel’s brain-intensity standard deviation. The multiplicative bias field has a peak fractional swing of 0.3, 0.5 and 0.8. Blur is an isotropic Gaussian of  $\sigma$  0.5, 0.75 and 1.0 voxels. Gamma remaps brain intensities rescaled to  $[0, 1]$  with exponents 0.8 and 1.25, a remap rather than an ordinal ladder, so its settings are categorical. With a shared clean condition this gives twelve in total. Corruptions are applied to all four modalities, inside the brain mask, before nnU-Net’s normalisation, so the model sees genuinely degraded input rather than a rescaling it would undo. For each corruption and severity we draw one fixed random realisation and apply it to every case, so cases differ in anatomy but not in the perturbation received. Severity was capped by inspecting previews, and the study runs on the 271 held-out cases of the fixed split.


# 3 Results

## 3.1 Segmentation baseline

The cross-validated single model is a strong baseline over all 1351 cases (Table 1). Per-case medians sit well above the means, and median HD95 is roughly 1 mm against means of 6–11 mm. The typical case is therefore excellent, and the means reflect a hard-case tail (Fig. 1). Mean ET HD95 is 10.73 mm over all cases but 5.62 mm on ET-present cases. The 33 no-ET cases, where the model hallucinates a small enhancing region, drive most of that boundary error.

**Table 1.** Cross-validated single-model segmentation quality (nnU-Net ResEnc-L, 5-fold,  $n = 1351$ ), distinct from the 5-fold challenge ensemble used for Section 3.5. Means with per-case medians in parentheses. Dice/NSD higher is better; HD95 (mm) lower is better. The final row restricts ET to the 1318 ET-present cases.

| Region            | Dice          | HD95 (mm)    | NSD           |
|-------------------|---------------|--------------|---------------|
| WT                | 0.925 (0.958) | 6.45 (1.73)  | 0.858 (0.913) |
| TC                | 0.909 (0.964) | 6.29 (1.17)  | 0.865 (0.950) |
| ET                | 0.869 (0.936) | 10.73 (1.00) | 0.891 (0.962) |
| ET (present only) | 0.880 (0.936) | 5.62 (1.00)  | 0.903 (0.962) |



**Fig. 1.** Per-case Dice distributions on the internal validation split ( $n = 271$ ), split-0 single model vs 3-seed deep ensemble, by region. The mass concentrates near 1.0 with thin tails reaching 0, so the typical case is excellent and the mean is set by a hard-case tail.

### 3.2 Calibration and error detection

On the relevant mask, over all 1351 cases, the cross-validated single model is overconfident. The reliability curves lie below the diagonal in every region (Fig. 2), with per-case ECE 0.070 / 0.076 / 0.080 (WT/TC/ET). Its confidence is a weak-but-genuine error detector, with AUROC 0.875 / 0.872 / 0.857 and AURC around 0.03–0.04, exceeding chance in 98–99% of cases. Overconfidence with usable-but-imperfect ranking is the gap an ensemble should close.

### 3.3 3-seed ensemble versus split-0 single model


On the 271 held-out cases of the fixed split the 3-seed ensemble is significantly better on almost every metric, but the effect sizes are small (Table 2). The clearest gain is calibration. Pooled ECE falls from 0.069 / 0.075 / 0.074 for the split-0 single model to 0.059 / 0.065 / 0.064. The 3-seed curve sits closer to the

diagonal in Fig. 2. The paired Wilcoxon test is run on the per-case deltas of Table 2 (all  $p < 0.001$ ). Dice improves by 0.003–0.007 and AUROC by 0.004–0.009. This paired test compares the two models on their *confidence* signal, the one both possess. Disagreement has no single-model counterpart, so it enters as the descriptive shift-response result in Section 3.4. The boundary effect is region-specific rather than a blanket cost. The 3-seed ensemble significantly improves ET HD95 (13.59 to 12.14 mm,  $p = 0.035$ ) but worsens TC HD95 (3.14 to 4.27 mm,  $p = 0.038$ ), with WT unchanged. In-distribution, then, the 3-seed ensemble is a modest, calibration-focused improvement over the split-0 single model.

The pattern differs by region in a way worth naming. Calibration improves almost identically everywhere ( $\Delta\text{ECE}$   $-0.010$  to  $-0.011$ ), so averaging helps globally. Boundary distance does not: the ensemble helps ET, whose errors are large, and slightly hurts TC, whose boundary is already tight at a median HD95 near 1 mm. Error detection improves most on TC ( $+0.009$ ) and least on WT ( $+0.004$ ). ET is the hardest region throughout, with the lowest Dice and worst calibration. Its aggregate boundary error is driven almost entirely by the no-ET cases. Mean ET HD95 falls from 10.73 mm to 5.62 mm once they are excluded.

### 3.4 Robustness under synthetic acquisition shift


The robustness study separates the split-0 single model from the 3-seed ensemble (Fig. 3, 4). Segmentation quality degrades gracefully. Bias field and blur bite most, with the split-0 single model’s region-averaged Dice falling from 0.900 to 0.882 under severe bias, while noise and gamma barely register. The informative result is the uncertainty. The single model’s confidence is nearly flat as quality drops. Its mean uncertainty rises only about 5% under severe bias, while its ECE on that split climbs about 25% (0.077 to 0.096). It becomes worse and



**Fig. 2.** Reliability diagrams on the per-region relevant mask ( $n = 271$ ). Both curves lie below the perfect-calibration diagonal, so both models are overconfident, as expected for nnU-Net. The 3-seed ensemble (blue) sits consistently closer to the diagonal, with lower pooled ECE in every region (legend); this calibration gain is its clearest in-distribution advantage.

**Table 2.** Paired comparison, 3-seed deep ensemble minus the split-0 single model, on the 271 held-out cases ( $\Delta$  = ensemble – single; Wilcoxon signed-rank; \* denotes  $p < 0.05$ ). Negative  $\Delta$  is an improvement for HD95/ECE/AURC.


| Metric ( $\Delta$ )       | WT           | TC      | ET      |
|---------------------------|--------------|---------|---------|
| Dice                      | +0.003*      | +0.004* | +0.007* |
| NSD                       | +0.004*      | +0.006* | +0.008* |
| HD95 (mm)                 | −0.01 (n.s.) | +1.14*  | −1.46*  |
| ECE                       | −0.010*      | −0.011* | −0.010* |
| AUROC (error, confidence) | +0.004*      | +0.009* | +0.007* |
| AURC                      | −0.002*      | −0.004* | −0.003* |



**Fig. 3.** Segmentation performance under the controlled robustness study ( $n = 271$ ), split-0 single model vs 3-seed deep ensemble, one panel per corruption. Dice is averaged over WT/TC/ET. Note the narrow  $y$ -axis: the drop is small in absolute terms even at severe bias and blur, and noise and gamma barely move. Gamma is an intensity remap, not an ordinal severity ladder, so its  $x$ -axis is categorical. These are synthetic, graded corruptions, a controlled proxy for acquisition shift rather than real cohort shift.

more miscalibrated while remaining equally confident, which is the silent-failure signature. Inter-member disagreement, by contrast, rises steeply, about +23% under bias and +31% under blur, several times the single model’s response. The sensitivity order on identical data is disagreement  $\gg$  3-seed confidence  $>$  single confidence. The error-detection AUROC dips slightly, from about 0.87 to 0.86.





**Fig. 4.** Percentage rise of each uncertainty signal from the clean condition, for the two corruptions that degrade Dice (bias, blur). Single-model confidence (black) barely moves; 3-seed confidence (blue) rises more; 3-seed disagreement (orange) rises steeply, to about +23% under severe bias and +31% under severe blur. The 3-seed ensemble’s disagreement responds to degradation that single-model confidence absorbs unchanged.

Disagreement is therefore the more sensitive case-level indicator of corruption-induced shift, even though its per-voxel error localisation weakens as severity grows.

### 3.5 External evaluation on the challenge leaderboard

We submitted predictions for all 451 cases of the official BraTS-GoAT validation set (the returned per-case score file covered 450 of them). The 5-fold ensemble attains mean per-case Dice 0.875 (WT), 0.814 (TC) and 0.782 (ET) over 450, 449 and 435 scored cases. The differing denominators reflect regions the official pipeline leaves unscored. Bootstrap 95% intervals are [0.856, 0.892], [0.789, 0.838], [0.753, 0.809]. Mean NSD is 0.48 / 0.50 / 0.55 and mean lesion-wise  $F_1$  0.69 / 0.74 / 0.67. Mean HD95 is 17.1 / 25.0 / 40.0 mm against medians of 2.2 / 2.0 / 1.4 mm. The HD95 mean is itself unstable under resampling where the median is not. Mean whole-tumour HD95 spans 11.5 to 23.6 mm under the same resampling, its median only 2.24 to 2.45 mm. That is the catastrophic tail seen from outside. The Dice gap against the internal numbers, 0.050 / 0.095 / 0.087, is two to four times the interval half-width and so is not a sampling artefact. The two sides use different inference configurations: the internal estimate is the cross-validated single model, the leaderboard the 5-fold challenge ensemble. Ensembling would raise the leaderboard score, disabling test-time mirroring would lower it. The gap is therefore an external anchor rather than a protocol-matched estimate, broadly consistent with the synthetic robustness trend but not directly comparable. Lesion-wise metrics are driven by under-detection of small satellite lesions rather than uniform decline. A case-level signal should ideally flag that, though the challenge outputs did not let us test it.

## 4 Discussion

Two findings stand out. First, in-distribution a single nnU-Net is already a strong reliability baseline. The 3-seed deep ensemble adds small, mostly calibration-focused gains rather than a decisive advantage, echoing QU-BraTS’s conclusion that no single method dominates [13]. The exception is boundary distance: ET HD95 improves, but TC HD95 slightly worsens. Because HD95 is set by the worst boundary tail rather than by average overlap, small changes in outlying points move it without implying a uniform improvement. A possible mechanism, which we did not test, is that averaging pulls in far outliers while smoothing a boundary that was already correct. Second, the 3-seed ensemble’s value is clearest under corruption-induced shift. Its disagreement rises when the single model’s confidence does not, which is why it is the more shift-sensitive signal.

A case-level error analysis explains the gap between the strong medians and the weaker means. Median Dice is 0.94 / 0.94 / 0.90. Removing the 6–12% of cases with HD95 above 50 mm drops mean HD95 to 3.5 / 4.5 / 2.8 mm. Two failure modes account for it. The first is under-detection of multifocal disease, in 16–19% of cases. The second is that errors are dominated by omission rather than hallucination. Mean false positives per case are 0.3–1.1 against false negatives of 1.6–2.5, so the model misses tumour quietly. This is the silent-failure profile the analysis targets.

Several limitations bound these claims. The controlled robustness study uses synthetic corruptions as a stand-in for real cohort shift. The leaderboard result corroborates those trends on a genuinely unseen cohort rather than validating them. The 3-seed ensemble comparison is on one held-out split, and its gains, while statistically significant, are small in absolute terms. Disagreement is small in magnitude, so its value is the relative rise under corruption-induced shift rather than an absolute threshold. Corruption severity was capped by our own judgement, and each condition uses one fixed realisation. Reliability was reported for one fold, so we also computed it per fold. The five held-out sets hold 271, 270, 270, 270 and 270 cases and sum to 1351. Across them ECE is  $0.0697 \pm 0.0028$  (WT),  $0.0761 \pm 0.0051$  (TC) and  $0.0798 \pm 0.0043$  (ET), as mean  $\pm$  SD. Detection AUROC is  $0.8748 \pm 0.0075$ ,  $0.8716 \pm 0.0056$  and  $0.8571 \pm 0.0050$ . Calibration and detection are therefore stable across all five folds. The ordering between regions is not: calibration WT < TC < ET holds in four folds and detection WT > TC > ET in three. Only ET having the lowest Dice and detection AUROC survives all five. These are single-model results, so the ensemble-versus-single difference is still a single-split measurement. Future work, scoped out to keep the comparison focused, includes MC-dropout and TTA as additional estimators, and validation on real external cohorts. Semi-supervised training is a natural extension, but GoAT permits no external data, and pseudo-labels inject error-correlated noise whose effect on calibration is itself an open question.

**Acknowledgments.** Computation used the University of Birmingham BlueBEAR HPC service. Data came from the BraTS-GoAT challenge (Synapse ID syn74274097).

**Disclosure of Interests.** The authors have no competing interests to declare.

## References

1. Baid, U., Ghodasara, S., Mohan, S., Bilello, M., et al.: The RSNA-ASNR-MICCAI BraTS 2021 benchmark on brain tumor segmentation and radiogenomic classification. arXiv preprint arXiv:2107.02314 (2021)
2. Bakas, S., Akbari, H., Sotiras, A., Bilello, M., et al.: Advancing the cancer genome atlas glioma MRI collections with expert segmentation labels and radiomic features. *Scientific Data* **4**, 170117 (2017). <https://doi.org/10.1038/sdata.2017.117>
3. BraTS-GoAT Challenge Organizers: BraTS generalizability across tumors (GoAT), task 3. Synapse:syn74274097 (2026)
4. Gal, Y., Ghahramani, Z.: Dropout as a Bayesian approximation: representing model uncertainty in deep learning. In: *International Conference on Machine Learning (ICML)*. pp. 1050–1059 (2016)
5. Geifman, Y., El-Yaniv, R.: Selective classification for deep neural networks. In: *Advances in Neural Information Processing Systems (NeurIPS)* (2017)
6. Guo, C., Pleiss, G., Sun, Y., Weinberger, K.Q.: On calibration of modern neural networks. In: *International Conference on Machine Learning (ICML)*. pp. 1321–1330 (2017)
7. Isensee, F., Jaeger, P.F., Kohl, S.A.A., Petersen, J., Maier-Hein, K.H.: nnU-Net: a self-configuring method for deep learning-based biomedical image segmentation. *Nature Methods* **18**(2), 203–211 (2021). <https://doi.org/10.1038/s41592-020-01008-z>
8. Isensee, F., Jäger, P.F., Full, P.M., Vollmuth, P., Maier-Hein, K.H.: nnU-Net for brain tumor segmentation. In: *Brainlesion: Glioma, Multiple Sclerosis, Stroke and Traumatic Brain Injuries (BrainLes 2020)*. *Lecture Notes in Computer Science*, vol. 12659, pp. 118–132. Springer, Cham (2021). [https://doi.org/10.1007/978-3-030-72087-2\\_11](https://doi.org/10.1007/978-3-030-72087-2_11)
9. Karargyris, A., Umeton, R., Sheller, M.J., Aristizabal, A., George, J., Wuest, A., Pati, S., et al.: Federated benchmarking of medical artificial intelligence with MedPerf. *Nature Machine Intelligence* **5**, 799–810 (2023). <https://doi.org/10.1038/s42256-023-00652-2>
10. Lakshminarayanan, B., Pritzel, A., Blundell, C.: Simple and scalable predictive uncertainty estimation using deep ensembles. In: *Advances in Neural Information Processing Systems (NeurIPS)* (2017)
11. Luu, H.M., Park, S.H.: Extending nn-UNet for brain tumor segmentation. In: *Brainlesion: Glioma, Multiple Sclerosis, Stroke and Traumatic Brain Injuries (BrainLes 2021)*. *Lecture Notes in Computer Science*, vol. 12963, pp. 173–186. Springer, Cham (2022), arXiv:2112.04653
12. Maier-Hein, L., Reinke, A., et al.: Metrics reloaded: recommendations for image analysis validation. *Nature Methods* **21**, 195–212 (2024). <https://doi.org/10.1038/s41592-023-02151-z>
13. Mehta, R., Filos, A., Baid, U., et al.: QU-BraTS: MICCAI BraTS 2020 challenge on quantifying uncertainty in brain tumor segmentation. *Journal of Machine Learning for Biomedical Imaging* (2022), arXiv:2112.10074
14. Menze, B.H., Jakab, A., Bauer, S., Kalpathy-Cramer, J., et al.: The multimodal brain tumor image segmentation benchmark (BRATS). *IEEE Transactions on Medical Imaging* **34**(10), 1993–2024 (2015). <https://doi.org/10.1109/TMI.2014.2377694>

15. Ovadia, Y., Fertig, E., Ren, J., Nado, Z., Sculley, D., Nowozin, S., Dillon, J.V., Lakshminarayanan, B., Snoek, J.: Can you trust your model's uncertainty? Evaluating predictive uncertainty under dataset shift. In: *Advances in Neural Information Processing Systems (NeurIPS)* (2019)
16. Correia de Verdier, M., Saluja, R., Gagnon, L., LaBella, D., Baid, U., et al.: The 2024 brain tumor segmentation (BraTS) challenge: Glioma segmentation on post-treatment MRI. *arXiv preprint arXiv:2405.18368* (2024). <https://doi.org/10.48550/arXiv.2405.18368>
17. Wang, G., Li, W., Aertsen, M., Deprest, J., Ourselin, S., Vercauteren, T.: Aleatoric uncertainty estimation with test-time augmentation for medical image segmentation with convolutional neural networks. *Neurocomputing* **338**, 34–45 (2019). <https://doi.org/10.1016/j.neucom.2019.01.103>